



OcNOS®
Open Compute
Network Operating System
for Data Centers
Version 6.5.3

Virtual Extensible Local Area Network Guide

November 2024

© 2024 IP Infusion Inc. All Rights Reserved.

This documentation is subject to change without notice. The software described in this document and this documentation are furnished under a license agreement or nondisclosure agreement. The software and documentation may be used or copied only in accordance with the terms of the applicable agreement. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or any means electronic or mechanical, including photocopying and recording for any purpose other than the purchaser's internal use without the written permission of IP Infusion Inc.

IP Infusion Inc.
3979 Freedom Circle
Suite 900
Santa Clara, California 95054
<http://www.ipinfusion.com/>

For support, questions, or comments via E-mail, contact:

support@ipinfusion.com

Trademarks:

IP Infusion and OcNOS are trademarks or registered trademarks of IP Infusion. All other trademarks, service marks, registered trademarks, or registered service marks are the property of their respective owners.

Use of certain software included in this equipment is subject to the IP Infusion, Inc. End User License Agreement at <http://www.ipinfusion.com/license>. By using the equipment, you accept the terms of the End User License Agreement.

Contents

Preface	8
IP Maestro Support	8
Audience	8
Conventions	8
Chapter Organization.....	8
Related Documentation.....	8
Migration Guide	9
Feature Availability.....	9
Support	9
Comments	9
Command Line Interface.....	10
Overview	10
Command Line Interface Help	10
Command Completion.....	11
Command Abbreviations.....	11
Command Line Errors	11
Command Negation.....	12
Syntax Conventions.....	12
Variable Placeholders	13
Command Description Format.....	14
Keyboard Operations.....	14
Show Command Modifiers	15
String Parameters	18
Command Modes	18
Transaction-based Command-line Interface	20
Virtual eXtensible Local Area Network Configuration	21
CHAPTER 1 VxLAN Overview	22
Terminology	24
VxLAN - Data Forwarding Configuration.....	25
CHAPTER 1 VxLAN Unicast Configuration	26
Port Mapping.....	26
Intermediate Non-VxLAN Router	31
CHAPTER 2 VLAN to VNID Mapping.....	37
Overview	37
Configuration.....	37
VLAN VNID Mapping Command	45
Glossary	47
VxLAN - Ethernet Virtual Private Network.....	48

CHAPTER 1	VXLAN-EVPN Configuration	49
Topology	49	
LAG as Access Port with ECMP on the Network Side	55	
CHAPTER 2	VXLAN Multi-homing Configuration	71
Overview	71	
Validation	89	
CHAPTER 3	VXLAN Hybrid Access Port Configuration	108
Overview	108	
Topology	108	
Validation	112	
CHAPTER 4	VXLAN Trunk Access Port	120
Topology	120	
CHAPTER 5	EVPN-VXLAN Hybrid Port Support	141
Overview	141	
Topology	141	
VXLAN-EVPN Hybrid Port Configuration	142	
Validation	153	
CHAPTER 6	VXLAN Quality of Service Configuration	161
Overview	161	
Topology	161	
COS-DSCP	161	
VxLAN - EVPN with Integrated Routing and Bridging Deployment Mode . . . 172		
CHAPTER 1	VXLAN-EVPN with IRB	173
Overview	173	
Topology	173	
Base Configuration - L2 VXLAN	174	
Centralized Gateway	190	
IRB Configuration for Centralized Gateway	190	
Anycast Gateway	195	
Distributed Gateway	216	
VXLAN IRB ECMP	223	
CHAPTER 2	EVPN IRB - Anycast Support for Multiple Subnets	231
Overview	231	
Topology	231	
CHAPTER 3	VxLAN-EVPN Symmetric IRB Support with Connected host	256
Overview	256	
Configuration	256	
Glossary	262	
CHAPTER 4	VXLAN-IRB-Inter-VRF Route Leaking	263
Topology	263	
CHAPTER 5	DHCP Relay Over IRB Interface	302
Overview	302	

Topology	302
CHAPTER 6 VXLAN-EVPN with IRB QoS	309
Overview	309
Topology	309
Base Configuration - L2 VXLAN	309
Centralized Gateway	322
IRB Configuration for Centralized Gateway	322
Anycast Gateway	331
IRB Configuration for Anycast	331
Distributed Gateway	352
IRB QoS Configuration for Distributed	352
CHAPTER 7 Single Home VxLAN IRB with OSPF or ISIS	365
Overview	365
Prerequisites	365
Topology for OSPF	366
Configuration	366
Topology for ISIS	372
Implementation Examples	379
New CLI Commands	379
Validation	379
Abbreviations	397
Glossary	397
CHAPTER 8 Multi Home VxLAN-EVPN IRB with OSPF or ISIS	399
Overview	399
Prerequisites	399
Topology for OSPF	399
Configuration	400
Abbreviations	432
Glossary	432
VxLAN - EVPN for Service Provider Network	433
CHAPTER 1 VXLAN EVPN EVC Configuration	434
Overview	434
Topology	434
Validation	437
CHAPTER 2 EVPN VXLAN E-Tree	446
Overview	446
Prerequisites	447
Configuration	451
Implementation Examples	466
E-Tree CLI Commands	467
Revised CLI Commands	467
Troubleshooting	468
Glossary	468

CHAPTER 3 VXLAN Tunnel Over SVI	470
Overview	470
Topology	470
Validation	487
VxLAN Command Reference	494
CHAPTER 1 VXLAN Commands	495
arp-cache disable	497
arp-nd flood-suppress	498
arp-nd refresh timer	499
clear mac address table dynamic vxlan	500
clear nvo vxlan counters	501
clear nvo vxlan tunnels	502
clear nvo vxlan mac-stale-entries	503
description	504
dynamic-learning disable	505
encapsulation	506
evpn esi holdtime	507
evpn vxlan multi-homing enable	508
evpn multi-homed	509
evpn-vlan-service	510
garp-gna enable	511
load-balance rtag7 vxlan inner-l2	512
load-balance rtag7 vxlan inner-l3	513
mac	514
mac vrf	515
mac-holdtime	516
map vnid	517
nd-cache disable	518
no nvo vxlan	519
nvo vxlan	520
nvo vxlan id	521
nvo vxlan access-if	523
nvo vxlan mac-ageing-time	525
nvo vxlan max-cache-disable	526
nvo vxlan vtep-ip-global	527
show nvo vxlan	528
show nvo vxlan access-if-config	530
show nvo vxlan arp-cache	531
show nvo vxlan counters access-port	533
show nvo vxlan counters network-port	536
show nvo vxlan mac-table	538
show nvo vxlan nd-cache	541
show nvo vxlan static host state	543
show nvo vxlan tunnel	545
show running-config nvo vxlan	546

show evpn multi-homing all.....	.548
show evpn multihoming-status.....	.549
show nvo vxlan route-count550
show nvo vxlan vni-name552
shutdown553
vxlan host-reachability-protocol evpn-bgp554
vlan-xlate-1 large555
CHAPTER 2 VXLAN - IRB Commands	556
evpn irb557
evpn irb-forwarding anycast-gateway-mac.....	.558
evpn irb-if-forwarding anycast-gateway-mac.....	.559
interface irb560
l3vni561
nvo vxlan irb562
show interface irb.....	.563
show evpn l3vni-map.....	.564
show evpn irb-status565
show running-config interface irb.....	.566
CHAPTER 3 VXLAN Quality of Service Commands	567
clear nvo vxlan tunnels568
cos queue569
dscp queue.....	.570
map qos-profile571
map qos-profile cos-to-queue.....	.572
map qos-profile queue-color-to-cos.....	.573
nvo vxlan disable-arp-storm-control-for-cpu.....	.574
nvo vxlan tunnel qos-map-mode cos-dscp575
qos profile cos-to-queue576
qos profile dscp-to-queue577
qos profile queue-color-to-cos578
qos profile queue-color-to-dscp579
queue cos580
queue dscp581
Index	582

Preface

This guide describes how to configure OcNOS.

IP Maestro Support

Monitor devices running OcNOS Release 6.3.4-70 and above using IP Maestro software.

Audience

This guide is intended for network administrators and other engineering professionals who configure OcNOS.

Conventions

[Table P-1](#) shows the conventions used in this guide.

Table P-1: Conventions

Convention	Description
<i>Italics</i>	Emphasized terms; titles of books
Note:	Special instructions, suggestions, or warnings
monospaced type	Code elements such as commands, parameters, files, and directories

Chapter Organization

The chapters in command references are organized as described in [Command Description Format](#).

The chapters in configuration guides are organized into these major sections:

- An overview that explains a configuration in words
- Topology with a diagram that shows the devices and connections used in the configuration
- Configuration steps in a table for each device where the left-hand side shows the commands you enter and the right-hand side explains the actions that the commands perform
- Validation which shows commands and their output that verify the configuration

Related Documentation

For information about installing of OcNOS, see the *Installation Guide* for your platform.

Migration Guide

Check the *Migration Guide* for configuration changes to make when migrating from one version of OcNOS to another.

Feature Availability

The features described in this document that are available depend upon the OcNOS SKU that you purchased. See the *Application Notes* for a description of the OcNOS SKUs.

Support

For support-related questions, contact support@ipinfusion.com.

Comments

If you have comments, or need to report a problem with the content, contact techpubs@ipinfusion.com.

Command Line Interface

This chapter introduces the OcNOS Command Line Interface (CLI) and how to use its features.

Overview

You use the CLI to configure, monitor, and maintain OcNOS devices. The CLI is text-based and each command is usually associated with a specific task.

You can give the commands described in this manual locally from the console of a device running OcNOS or remotely from a terminal emulator such as `putty` or `xterm`. You can also use the commands in scripts to automate configuration tasks.

Command Line Interface Help

You access the CLI help by entering a full or partial command string and a question mark "?". The CLI displays the command keywords or parameters along with a short description. For example, at the CLI command prompt, type:

```
> show ?
```

The CLI displays this keyword list with short descriptions for each keyword:

show ?	
application-priority	Application Priority
arp	Internet Protocol (IP)
bfd	Bidirectional Forwarding Detection (BFD)
bgp	Border Gateway Protocol (BGP)
bi-lsp	Bi-directional lsp status and configuration
bridge	Bridge group commands
ce-vlan	COS Preservation for Customer Edge VLAN
class-map	Class map entry
cli	Show CLI tree of current mode
clns	Connectionless-Mode Network Service (CLNS)
control-adjacency	Control Adjacency status and configuration
control-channel	Control Channel status and configuration
cspf	CSPF Information
customer	Display Customer spanning-tree
cvlan	Display CVLAN information
debugging	Debugging functions (see also 'undebbug')
etherchannel	LACP etherchannel
ethernet	Layer-2
...	

If you type the ? in the middle of a keyword, the CLI displays help for that keyword only.

```
> show de?
debugging Debugging functions (see also 'undebbug')
```

If you type the ? in the middle of a keyword, but the incomplete keyword matches several other keywords, OcNOS displays help for all matching keywords.

```
> show i? (CLI does not display the question mark).
interface Interface status and configuration
ip IP information
isis ISIS information
```

Command Completion

The CLI can complete the spelling of a command or a parameter. Begin typing the command or parameter and then press the tab key. For example, at the CLI command prompt type sh:

```
> sh
```

Press the tab key. The CLI displays:

```
> show
```

If the spelling of a command or parameter is ambiguous, the CLI displays the choices that match the abbreviation. Type show i and press the tab key. The CLI displays:

```
> show i
  interface  ip          ipv6        isis
> show i
```

The CLI displays the interface and ip keywords. Type n to select interface and press the tab key. The CLI displays:

```
> show in
> show interface
```

Type ? and the CLI displays the list of parameters for the show interface command.

```
> show interface
  IFNAME  Interface name
  |       Output modifiers
  >       Output redirection
<cr>
```

The CLI displays the only parameter associated with this command, the IFNAME parameter.

Command Abbreviations

The CLI accepts abbreviations that uniquely identify a keyword in commands. For example:

```
> sh int xe0
```

is an abbreviation for:

```
> show interface xe0
```

Command Line Errors

Any unknown spelling causes the CLI to display the error Unrecognized command in response to the ?. The CLI displays the command again as last entered.

```
> show dd?
% Unrecognized command
> show dd
```

When you press the Enter key after typing an invalid command, the CLI displays:

```
(config)#router ospf here
^
% Invalid input detected at '^' marker.
```

where the ^ points to the first character in error in the command.

If a command is incomplete, the CLI displays the following message:

```
> show
% Incomplete command.
```

Some commands are too long for the display line and can wrap mid-parameter or mid-keyword, as shown below. This does *not* cause an error and the command performs as expected:

```
area 10.10.0.18 virtual-link 10.10.0.19 authentication-key 57393
```

Command Negation

Many commands have a `no` form that resets a feature to its default value or disables the feature. For example:

- The `ip address` command assigns an IPv4 address to an interface
- The `no ip address` command removes an IPv4 address from an interface

Syntax Conventions

[Table P-2](#) describes the conventions used to represent command syntax in this reference.

Table P-2: Syntax conventions

Convention	Description	Example
monospaced font	Command strings entered on a command line	<code>show ip ospf</code>
lowercase	Keywords that you enter exactly as shown in the command syntax.	<code>show ip ospf</code>
UPPERCASE	See Variable Placeholders	<code>IFNAME</code>
()	Optional parameters, from which you must select one. Vertical bars delimit the selections. Do not enter the parentheses or vertical bars as part of the command.	<code>(A.B.C.D <0-4294967295>)</code>
()	Optional parameters, from which you select one or none. Vertical bars delimit the selections. Do not enter the parentheses or vertical bars as part of the command.	<code>(A.B.C.D <0-4294967295>)</code>
()	Optional parameter which you can specify or omit. Do not enter the parentheses or vertical bar as part of the command.	<code>(IFNAME)</code>
{ }	Optional parameters, from which you must select one or more. Vertical bars delimit the selections. Do not enter the braces or vertical bars as part of the command.	<code>{intra-area <1-255> inter-area <1-255> external <1-255>}</code>

Table P-2: Syntax conventions (Continued)

Convention	Description	Example
[]	Optional parameters, from which you select zero or more. Vertical bars delimit the selections. Do not enter the brackets or vertical bars as part of the command.	[<1-65535> AA:NN internet local-AS no-advertise no-export]
?	Nonrepeatable parameter. The parameter that follows a question mark can only appear once in a command string. Do not enter the question mark as part of the command.	?route-map WORD
.	Repeatable parameter. The parameter that follows a period can be repeated more than once. Do not enter the period as part of the command.	set as-path prepend .<1-65535>

Variable Placeholders

Table P-3 shows the tokens used in command syntax use to represent variables for which you supply a value.

Table P-3: Variable placeholders

Token	Description
WORD	A contiguous text string (excluding spaces)
LINE	A text string, including spaces; no other parameters can follow this parameter
IFNAME	Interface name whose format varies depending on the platform; examples are: eth0, Ethernet0, ethernet0, xe0
A.B.C.D	IPv4 address
A.B.C.D/M	IPv4 address and mask/prefix
X:X::X:X	IPv6 address
X:X::X:X/M	IPv6 address and mask/prefix
HH:MM:SS	Time format
AA:NN	BGP community value
XX:XX:XX:XX:XX:XX	MAC address
<1-5> <1-65535> <0-2147483647> <0-4294967295>	Numeric range

Command Description Format

[Table P-4](#) explains the sections used to describe each command in this reference.

Table P-4: Command descriptions

Section	Description
Command Name	The name of the command, followed by what the command does and when should it be used
Command Syntax	The syntax of the command
Parameters	Parameters and options for the command
Default	The state before the command is executed
Command Mode	The mode in which the command runs; see Command Modes
Example	An example of the command being executed

Keyboard Operations

[Table P-5](#) lists the operations you can perform from the keyboard.

Table P-5: Keyboard operations

Key combination	Operation
Left arrow or Ctrl+b	Moves one character to the left. When a command extends beyond a single line, you can press left arrow or Ctrl+b repeatedly to scroll toward the beginning of the line, or you can press Ctrl+a to go directly to the beginning of the line.
Right arrow or Ctrl+f	Moves one character to the right. When a command extends beyond a single line, you can press right arrow or Ctrl+f repeatedly to scroll toward the end of the line, or you can press Ctrl+e to go directly to the end of the line.
Esc, b	Moves back one word
Esc, f	Moves forward one word
Ctrl+e	Moves to end of the line
Ctrl+a	Moves to the beginning of the line
Ctrl+u	Deletes the line
Ctrl+w	Deletes from the cursor to the previous whitespace
Alt+d	Deletes the current word
Ctrl+k	Deletes from the cursor to the end of line
Ctrl+y	Pastes text previously deleted with Ctrl+k, Alt+d, Ctrl+w, or Ctrl+u at the cursor

Table P-5: Keyboard operations (Continued)

Key combination	Operation
Ctrl+t	Transposes the current character with the previous character
Ctrl+c	Ignores the current line and redisplays the command prompt
Ctrl+z	Ends configuration mode and returns to exec mode
Ctrl+l	Clears the screen
Up Arrow or Ctrl+p	Scroll backward through command history
Down Arrow or Ctrl+n	Scroll forward through command history

Show Command Modifiers

You can use two tokens to modify the output of a `show` command. Enter a question mark to display these tokens:

```
# show users ?
| Output modifiers
> Output redirection
```

You can type the | (vertical bar character) to use output modifiers. For example:

```
> show bgp | ?
begin      Begin with the line that matches
exclude    Exclude lines that match
include    Include lines that match
last       Last few lines
redirect   Redirect output
```

Begin Modifier

The `begin` modifier displays the output beginning with the first line that contains the input string (everything typed after the `begin` keyword). For example:

```
# show running-config | begin xe1
...skipping
interface xe1
  ipv6 address fe80::204:75ff:fee6:5393/64
!
interface xe2
  ipv6 address fe80::20d:56ff:fe96:725a/64
!
line con 0
  login
!
end
```

You can specify a regular expression after the `begin` keyword. This example begins the output at a line with either "xe2" or "xe4":

```
# show running-config | begin xe[3-4]
```

```

...skipping
interface xe3
  shutdown
!
interface xe4
  shutdown
!
interface svlan0.1
  no shutdown
!
route-map myroute permit 3
!
route-map mymap1 permit 10
!
route-map rmap1 permit 3
!
line con 0
  login
line vty 0 4
  login
!
end

```

Include Modifier

The `include` modifier includes only those lines of output that contain the input string. In the output below, all lines containing the word “input” are included:

```
# show interface xe1 | include input
  input packets 80434552, bytes 2147483647, dropped 0, multicast packets 0
    input errors 0, length 0, overrun 0, CRC 0, frame 0, fifo 1, missed 0
```

You can specify a regular expression after the `include` keyword. This examples includes all lines with “input” or “output”:

```
#show interface xe0 | include (in|out)put
  input packets 597058, bytes 338081476, dropped 0, multicast packets 0
    input errors 0, length 0, overrun 0, CRC 0, frame 0, fifo 0, missed 0
    output packets 613147, bytes 126055987, dropped 0
      output errors 0, aborted 0, carrier 0, fifo 0, heartbeat 0, window 0
```

Exclude Modifier

The `exclude` modifier excludes all lines of output that contain the input string. In the following output example, all lines containing the word “input” are excluded:

```
# show interface xe1 | exclude input
Interface xe1
Scope: both
Hardware is Ethernet, address is 0004.75e6.5393
index 3 metric 1 mtu 1500 <UP,BROADCAST,RUNNING,MULTICAST>
VRF Binding: Not bound
Administrative Group(s): None
DSTE Bandwidth Constraint Mode is MAM
inet6 fe80::204:75ff:fee6:5393/64
  output packets 4438, bytes 394940, dropped 0
  output errors 0, aborted 0, carrier 0, fifo 0, heartbeat 0, window 0
```

```
    collisions 0
```

You can specify a regular expression after the `exclude` keyword. This example excludes lines with “output” or “input”:

```
# show interface xe0 | exclude (in|out)put
Interface xe0
Scope: both
Hardware is Ethernet Current HW addr: 001b.2139.6c4a
Physical:001b.2139.6c4a Logical:(not set)
index 2 metric 1 mtu 1500 duplex-full arp ageing timeout 3000
<UP,BROADCAST,RUNNING,MULTICAST>
VRF Binding: Not bound
Bandwidth 100m
DHCP client is disabled.
inet 10.1.2.173/24 broadcast 10.1.2.255
  VRRP Master of : VRRP is not configured on this interface.
inet6 fe80::21b:21ff:fe39:6c4a/64
  collisions 0
```

Redirect Modifier

The `redirect` modifier writes the output into a file. The output is not displayed.

```
# show cli history | redirect /var/frame.txt
```

The output redirection token (`>`) does the same thing:

```
# show cli history >/var/frame.txt
```

Last Modifier

The `last` modifier displays the output of last few number of lines (As per the user input). The last number ranges from 1 to 9999.

For example:

```
#show running-config | last 10
```

String Parameters

The restrictions in [Table P-6](#) apply for all string parameters used in OcNOS commands, unless some other restrictions are noted for a particular command.

Table P-6: String parameter restrictions

Restriction	Description
Input length	1965 characters or less
Restricted special characters	“?”, “;”, “>”, “ ”, and “=” The “ ” is allowed only for <code>description</code> CLI in interface mode.

Command Modes

Commands are grouped into modes arranged in a hierarchy. Each mode has its own set of commands. [Table P-7](#) lists the command modes common to all protocols.

Table P-7: Common command modes

Name	Description
Executive mode	Also called <code>view</code> mode, this is the first mode to appear after you start the CLI. It is a base mode from where you can perform basic commands such as <code>show</code> , <code>exit</code> , <code>quit</code> , <code>help</code> , and <code>enable</code> .
Privileged executive mode	Also called <code>enable</code> mode, in this mode you can run additional basic commands such as <code>debug</code> , <code>write</code> , and <code>show</code> .
Configure mode	Also called <code>configure terminal</code> mode, in this mode you can run configuration commands and go into other modes such as <code>interface</code> , <code>router</code> , <code>route map</code> , <code>key chain</code> , and <code>address family</code> . Configure mode is single user. Only one user at a time can be in configure mode.
Interface mode	In this mode you can configure protocol-specific settings for a particular interface. Any setting you configure in this mode overrides a setting configured in router mode.
Router mode	This mode is used to configure router-specific settings for a protocol such as BGP or OSPF.

Command Mode Tree

The diagram below shows the common command mode hierarchy.




Figure P-1: Common command modes

To change modes:

1. Enter privileged executive mode by entering `enable` in Executive mode.
2. Enter configure mode by entering `configure terminal` in Privileged Executive mode.

The example below shows moving from executive mode to privileged executive mode to configure mode and finally to router mode:

```

> enable mypassword
# configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
(config)# router ospf
(config-router)#
  
```

Note: Each protocol can have modes in addition to the common command modes. See the command reference for the respective protocol for details.

Transaction-based Command-line Interface

The OcNOS command line interface is transaction based:

- Any changes done in configure mode are stored in a separate *candidate* configuration that you can view with the [show transaction current](#) command.
- When a configuration is complete, apply the candidate configuration to the running configuration with the [commit](#) command.
- If a [commit](#) fails, no configuration is applied as the entire transaction is considered failed. You can continue to change the candidate configuration and then retry the [commit](#).
- Discard the candidate configuration with the [abort transaction](#) command.
- Check the last aborted transaction with the [show transaction last-aborted](#) command.
- Multiple configurations cannot be removed with a single commit. You must remove each configuration followed by a commit.

Note: All commands MUST be executed only in the default CML shell (`cmlsh`). If you log in as `root` and start `imish` then the system configurations will go out of sync. The `imish` shell is not supported and should not be started manually.

Virtual eXtensible Local Area Network Configuration

CHAPTER 1 VxLAN Overview

This chapter provides an overview of Virtual Extensible Local Area Network (VxLAN) and its implementation within OcNOS.

VxLAN

Virtual eXtensible Local Area Network (VxLAN) is widely used in Data Centers (DC) networks. VxLAN is an overlay transport virtualization technology commonly used in cloud networks to support the ever-increasing Virtual LAN (VLAN) and multi-tenant networks in data centers. It enables the "stretching" of a Layer 2 network over a physical Layer 3 network.

Overlay Network

VxLAN creates an overlay of virtual L2 LAN segments using a MAC address, and L4 UDP packets in IP encapsulation on top of the physical underlay L3 infrastructure. Technically, it encapsulates L2 Ethernet frames received from a host with L3 IP/UDP packets in a VxLAN header and sends it to the destination in the data center network using IP tunnels. This allows for the extension of L2 networks across data center without changing the underlying physical infrastructure.

EVPN - VxLAN

VxLAN creates LAN segments using MAC-in-IP encapsulation. The encapsulation carries the original L2 frame received from a host to the destination in another host using IP tunnels. The endpoints of the virtualized tunnel formed using VxLAN are called VXLAN Tunnel End Points (VTEPs). The VxLAN segments carry tenant data in L3 tunnels over the network which permits the network to support multiple tenants. The tenant data is not used in routing or switching. This aids in tenant machine movement and allows the tenants to have the same IP or MAC addresses.

Ethernet Virtual Private Network (EVPN) is a protocol based on industry standards used for network virtualization in multi-tenant data center and service provider networks. When used with VxLAN networks, it provides a control plane to create L2 overlays across a L3 network. This enables seamless communication between virtual machines (VMs) or containers across different physical locations as though they are on the same Ethernet segment. EVPN leverages BGP for scalable routing information exchange and distribution of L2 and L3 reachability information across a large network. It also tracks and updates the location of devices based on MAC and IP addresses as they move across the network. It is a critical feature in virtualized environments where VMs or containers may frequently migrate.

Additionally, EVPN supports redundant and active-active multi-homing for robust failover and high availability, by allowing a host to connect to multiple VTEPs. Thus, EVPN ensures, that the traffic is rerouted through an alternate VTEP if a connection to VTEP fails. EVPN is essential for scalable, resilient, and efficient multi-tenant network virtualization when deployed in conjunction with VxLAN in modern data center environments.

Underlay Network

The underlay network consists of a physical L3 infrastructure, which provides the foundation for communication in the network. The underlay network is abstracted in the overlay network, allowing seamless communication of the large virtualized L2 network.

VxLAN Architecture

Typically, VxLAN network operates as an overlay network over an IP underlay network based on a Spine-Leaf CLOS architecture. The underlay network is often referred to as IP fabric or CLOS fabric.

VxLAN allows the network to support several tenants with minimum changes in the network. They carry tenant data in virtual tunnels over the network. The tenant data is not used in routing or switching. This aids in tenant machine movement and allows the tenants to have the same IP or MAC addresses on end devices, hosts, or VMs.

Each overlay tunnel is referred to as a VxLAN segment. VMs can only communicate with each other within the same VxLAN segment, similar to how communication occurs within a traditional VLAN. Each VxLAN segment is identified through a 24-bit segment ID termed the VxLAN Network Identifier (VNI). This allows up to 16 million VxLAN segments to coexist within the same administrative domain. For VMs on different VxLAN segments to communicate, inter-VxLAN routing can be performed on a VxLAN-enabled router or distributed gateway. This is similar to routing between VLANs in a traditional L2 network.

The VNI determines the scope of the inner MAC frame originated from the individual VM. This ensures there can be overlapping MAC addresses across segments, but traffic remains isolated due to the VNI preventing cross-segment interference.




Figure 1-1: VxLAN Deployment - VTEPs across a L3 Network

Features

- Leaf nodes act as VTEP for hosts to connect to the data center and provide VPN services
- With multihoming facility load distribution, link and node level redundancies of the CLOS fabric are extended to hosts
- Hosts are identified using either the port number, port number with VLAN ID or VLAN range, or the port number with a stacked VLAN ID.
- Any packets (including ARP-ND) that are uplifted to the VxLAN CPU queue from any port are rate limited to 500 packets per second. This is done to protect the system and CPU during an ARP storm.
- OcNOS supports VxLAN IPv4 tunnels, but both IPv4 and IPv6 hosts.

-
- VxLAN works over UDP, with destination port 4789. Source port can be randomized based on L2 frame information carried, hence provides good hashing input for load-sharing on ECMP/LAG paths in the L3 fabric.
 - EVPN uses multiprotocol BGP with AFI=25 (L2VPN) and SAFI=70 (EVPN).
 - EVPN is used with VxLAN data-plane encapsulations in OcNOS Data Center.
 - EVPN helps with discovering VTEPs and learning MAC and IP addresses of the connected hosts in a VxLAN network.
 - EVPN is used to implement Integrated routing and bridging (IRB), and E-Tree in OcNOS Data Center. It's becoming umbrella for multiple service types.
 - EVPN provides multihoming service, with redundancy and more bandwidth with multihoming facility load distribution, extends link and node level redundancies of the CLOS fabric to hosts.
-

Terminology

Terms related to VxLAN configuration are defined in the table below.

VLAN	Virtual Local Area Network
VM	Virtual Machine
VNI	VxLAN Network Identifier (or VxLAN Segment ID)
VTEP	VxLAN Tunnel End Point. An entity that originates and/or terminates VxLAN tunnels
VxLAN	Virtual eXtensible Local Area Network
VxLAN Segment	VxLAN L2 overlay network over which VMs communicate

VxLAN - Data Forwarding Configuration

CHAPTER 1 VxLAN Unicast Configuration

This chapter contains basic Static-VxLAN unicast configuration examples.

Port Mapping

In this example each VTEP (VTEP1 and VTEP2) is a multilayer switch where xe2 is an access port while xe1 is network port.

After we start sending a packet (say untagged ipv4 packet) from VM1, it hits the VTEP1, VTEP1 does encapsulation based on the VNID configured and send it on xe1. Now the packet reaches VTEP2 and it does decapsulation of the packet. Now based on VNID packet is sent out on access port and it reaches destination VM, VM2.

Topology

The procedures in this section use the topology in [Figure 1-2](#)




Figure 1-2: VxLAN unicast

VTEP1

#configure terminal	Enter the configure mode
(config)#interface xe2	Enter interface mode
(config-if)#switchport	Configure the interface as switchport
(config-if)#no shutdown	Bring the interface into operation with the no shutdown

(config-if)#exit	Exit interface mode
(config)#interface lo	Enter the configure mode
(config-if)#ip address 1.1.1.1/32 secondary	Configure IP address on the interface xe1
(config-if)#no shutdown	Bring the interface into operation with the no shutdown
(config-if)#exit	Exit interface mode
(config)#interface xe1	Enter the configure mode
(config-if)#ip address 5.5.5.2/24	Configure IP address on the interface xe1
(config-if)#no shutdown	Bring the interface into operation with the no shutdown
(config-if)#exit	Exit interface mode
(config)#ip route 2.2.2.2/32 5.5.5.4	Configure static route
(config)#nvo vxlan enable	Enable VxLAN globally on this vtep
(config)#interface tunnel 4	Specify the interface (Tunnel4)to be configured and Enter interface mode
(config-if)#tunnel mode vxlan	Assign this tunnel mode as VxLAN
(config-if)#tunnel source 1.1.1.1	Configure the source IP of this tunnel as an IP address which is configured on the interface xe1 of VTEP1
(config-if)#tunnel destination 2.2.2.2	Configure the destination IP of this tunnel as an IP address which is configured on the interface xe1 of VTEP2.
(config-if)#exit	Exit interface mode
(config)#nvo vxlan id 2	Configure a VNID on this VTEP and enter the nvo mode.
(config-nvo)#vxlan map-network tunnel Tunnel4	Map the tunnel 4 with VNID 2
(config-nvo)#vxlan static-entry host-mac 0000.0000.aaaa remote-vtep-ip 2.2.2.2	Configure a static entry for remote VM with MAC address and IP address.
(config-nvo)#exit	Exit the nvo mode
(config)#nvo vxlan access-if port xe2	Map the access port xe2 of this VTEP
(config-nvo-acc-if)#map vnid 2	Map the VNID 2 to access-port xe2
(config-nvo-acc-if)#exit	Exit the nvo access-if mode
(config)#commit	Perform commit operation for the changes to take effect.

VTEP2

#configure terminal	Enter the configure mode
(config)#interface xe2	Enter interface mode
(config-if)#switchport	Configure the interface as switchport
(config-if)#no shutdown	Bring the interface into operation with the no shutdown
(config-if)#exit	Exit interface mode
(config)#interface lo	Enter the configure mode
(config-if)#ip address 2.2.2.2/32 secondary	Configure IP address on the interface xe1
(config-if)#no shutdown	Bring the interface into operation with the no shutdown
(config-if)#exit	Exit interface mode
(config)#interface xe1	Enter the configure mode

(config-if)#ip address 5.5.5.4/24	Configure IP address on the interface xe1
(config-if)#no shutdown	Bring the interface into operation with the no shutdown
(config-if)#exit	Exit interface mode
(config)#ip route 1.1.1.1/32 5.5.5.2	Configure static route
(config)#nvo vxlan enable	Enable VxLAN globally on this vtep
(config)#interface tunnel 4	Specify the interface (Tunnel4)to be configured and Enter interface mode.
(config-if)#tunnel mode vxlan	Assign this tunnel mode as VxLAN
(config-if)#tunnel source 2.2.2.2	Configure the source IP of this tunnel as an IP address which is configured on the interface xe1 of VTEP1.
(config-if)#tunnel destination 1.1.1.1	Configure the destination IP of this tunnel as an IP address which is configured on the interface xe1 of VTEP2.
(config-if)#exit	Exit interface mode.
(config)#nvo vxlan id 2	Configure a VNID on this VTEP and enter the nvo mode.
(config-nvo)#vxlan map-network tunnel Tunnel4	Map the tunnel 4 with VNID 2
(config-nvo)#vxlan static-entry host-mac 0000.0000.bbbb remote-vtep-ip 1.1.1.1	Configure a static entry for remote VM with MAC address and IP address.
(config-nvo)#exit	Exit the nvo mode.
(config)#nvo vxlan access-if port xe2	Map the access port xe2 of this VTEP
(config-nvo-acc-if)#map vnid 2	Map the VNID 2 to access-port xe2
(config-nvo-acc-if)#exit	Exit the nvo access-if mode
(config)#commit	Perform commit operation for the changes to take effect.

Validation

VTEP1

```
VTEP1#show nvo vxlan tunnel
VVXLAN Network tunnel Entries
  Source          Destination        Status      Up/Down      Update
=====
2.2.2.4          3.3.3.4           Installed   00:37:56    00:37:56
```

Total number of entries are 1
VTEP1#

```
VTEP1#show nvo vxlan
VXLAN Information
=====
Codes: NW - Network Port
       AC - Access Port
       (u) - Untagged
```

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-
Status	Src-Addr	Dst-Addr					

2.2.2.1	xe1	00:11:25	00:03:44	Active	2.2.2.4
3.3.3.1	xe2	00:01:36	00:04:17	Active	3.3.3.4

VTEP2

VTEP2#show nvo vxlan tunnel

VXLAN Information

=====

Codes: NW - Network Port

AC - Access Port

(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-
Status	Src-Addr			Dst-Addr			
3	---	L2	NW	----	-----	-----	-----
--	3.3.3.4			2.2.2.4			
3	---	L2	NW	----	-----	-----	-----
--	3.3.3.4			239.10.10.9			
3	---	--	AC	xe1	--- Single Homed Port ---	-----	-----
--	----			----			

Total number of entries are 3

VTEP2#

VTEP#2show nvo vxlan vnid 3

VXLAN Information

=====

Codes: NW - Network Port

AC - Access Port

(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-
Status	Src-Addr			Dst-Addr			
3	---	L2	NW	----	-----	-----	-----
--	3.3.3.4			2.2.2.4			
3	---	--	AC	xe2	--- Single Homed Port ---	-----	-----
--	----			----			

Total number of entries are 2

VTEP#show vno vxlan mac-table

=====

=====

VXLAN MAC Entries

=====

=====

=====

VNID	Interface	VlanId	Inner-VlanId	Mac-Addr	VTEP-Ip/ESI
Type				AccessPortDesc	

```
3      xe2      ----  ----      0000.0000.aaaa Local
Dynamic Local      -----      -----
3      ----      ----  ----      0000.0000.bbbb 2.2.2.4
Static Remote      -----      -----
```

Total number of entries are : 2

```
VTEP2#show nvo vxlan mac-table vnid 3
```

```
=====
===== VXLAN MAC Entries =====
=====
```

VNID Type	Interface	VlanId Status	Inner-VlanId	Mac-Addr AccessPortDesc	VTEP-Ip/ESI
3 Dynamic Local	xe2	---- -----	----	0000.0000.aaaa Local	-----
3 Static Remote	----	---- -----	----	0000.0000.bbbb 2.2.2.4	-----

```
=====
```

Total number of entries are : 2

Intermediate Non-VxLAN Router

This example is same as port mapping but we have an intermediate non VxLAN router. It does forwarding based on IP header.

Topology

The procedures in this section use the topology in [Figure 1-3](#)




Figure 1-3: VxLAN unicast

VTEP1

#configure terminal	Enter the configure mode.
(config)#interface xe2	Enter interface mode.
(config-if)#switchport	Configure the interface as switchport.
(config-if)#no shutdown	Bring the interface into operation with the no shutdown
(config-if)#exit	Exit interface mode.
(config)#interface xe1	Enter the configure mode.
(config-if)#ip address 2.2.2.4/24	Configure IP address on the interface xe1.
(config-if)#no shutdown	Bring the interface into operation with the no shutdown
(config-if)#exit	Exit interface mode.
(config)#ip route 3.3.3.0/24 2.2.2.1	Configuring static route
(config)#nvo vxlan enable	Enable VxLAN globally on this vtep.
(config)#interface tunnel 4	Specify the interface (Tunnel4)to be configured and Enter interface mode.
(config-if)#tunnel mode vxlan	Assign this tunnel mode as VxLAN .
(config-if)#tunnel source 2.2.2.4	Configure the source IP of this tunnel as an IP address which is configured on the interface xe1 of VTEP1.
(config-if)#tunnel destination 3.3.3.4	Configure the destination IP of this tunnel as an IP address which is configured on the interface xe1 of VTEP2.
(config-if)#exit	Exit interface mode.
(config)#nvo vxlan id 3	Configure a VNID on this VTEP and enter the nvo mode.

(config-nvo) #vxlan map-network tunnel Tunnel4	Map the tunnel 4 with this VNID
(config-nvo) #vxlan static-entry host-mac 0000.0000.aaaa remote-vtep-ip 3.3.3.4	Configure a static entry for remote VM with MAC address and IP address.
(config) #nvo vxlan access-if port xe2	Map the access port xe2 of this VTEP
(config-nvo-acc-if) #map vnid 3	Map the VNID 2 to access-port xe2
(config-nvo-acc-if) #exit	Exit NVO access-interface mode
(config) #commit	Perform commit operation for the changes to take effect.

RTR1

(config) #interface xe1	Enter the configure mode.
(config-if) #ip address 2.2.2.1/24	Configure IP address on the interface xe1.
(config-if) #no shutdown	Bring the interface into operation with the no shutdown
(config-if) #exit	Exit interface mode.
(config) #interface xe2	Enter the configure mode.
(config-if) #ip address 3.3.3.1/24	Configure IP address on the interface xe2.
(config-if) #no shutdown	Bring the interface into operation with the no shutdown
(config-if) #exit	Exit interface mode.
(config) #commit	Perform commit operation for the changes to take effect.

VTEP2

#configure terminal	Enter the configure mode.
(config) #interface xe2	Enter interface mode.
(config-if) #switchport	Configure the interface as switchport.
(config-if) #no shutdown	Bring the interface into operation with the no shutdown
(config-if) #exit	Exit interface mode.
(config) #interface xe1	Enter the configure mode.
(config-if) #ip address 3.3.3.4/24	Configure IP address on the interface xe1.
(config-if) #no shutdown	Bring the interface into operation with the no shutdown
(config-if) #exit	Exit interface mode.
(config) #ip route 2.2.2.0/24 3.3.3.1	Configuring static route
(config) #nvo vxlan enable	Enable VxLAN globally on this vtep.
(config) #interface tunnel 4	Specify the interface (Tunnel4)to be configured and Enter interface mode.
(config-if) #tunnel mode vxlan	Assign this tunnel mode as VxLAN .
(config-if) #tunnel source 3.3.3.4	Configure the source IP of this tunnel as an IP address which is configured on the interface xe1 of VTEP1.
(config-if) #tunnel destination 2.2.2.4	Configure the destination IP of this tunnel as an IP address which is configured on the interface xe1 of VTEP2.
(config-if) #exit	Exit interface mode.
(config) #nvo vxlan id 3	Configure a VNID on this VTEP and enter the nvo mode.

(config-nvo) #vxlan map-network tunnel Tunnel4	Map the tunnel 4 with this VNID
(config-nvo) #vxlan static-entry host-mac 0000.0000.bbbb remote-vtep-ip 2.2.2.4	Configure a static entry for remote VM with MAC address and IP address.
(config) #nvo vxlan access-if port xe2	Map the access port xe2 of this VTEP
(config-nvo-acc-if) #map vnid 3	Map the VNID 3 to access-port xe2
(config-nvo-acc-if) #exit	Exit the NVO access interface mode
(config) #commit	Perform commit operation for the changes to take effect.

Validation

VTEP1

```
VTEP1#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination      Status        Up/Down      Update
=====
2.2.2.4          3.3.3.4       Installed     00:37:56     00:37:56
Total number of entries are 1
VTEP1#
VTEP1#
VTEP1#show nvo vxlan
VXLAN Information
=====
Codes: NW - Network Port
       AC - Access Port
       (u) - Untagged

VNID      VNI-Name      VNI-Type Type Interface      ESI      VLAN DF-
Status    Src-Addr      Dst-Addr
=====
3          ----          L2      NW      ----      -----
--          2.2.2.4        3.3.3.4
3          ----          --      AC      xe2       --- Single Homed Port ---      -----
-----      -----
Total number of entries are 2
VTEP1#
VTEP1#show nvo vxlan mac-table
=====
=====      VXLAN MAC Entries
=====      -----
=====      -----
VNID      Interface  VlanId Inner-VlanId Mac-Addr      VTEP-Ip/ESI
Type       Status      AccessPortDesc
=====      -----
-----      -----
```

```

3      ----      ----      ----      0000.0000.aaaa 3.3.3.4
Static Remote      -----
3      xe2      ----      ----      0000.0000.bbbb Local      Dynamic
Local      -----

```

Total number of entries are : 2

```

VTEP1#
VTEP1#
VTEP1#sh nvo vxlan mac-table vnid 3
=====
```

VXLAN MAC Entries					
VNID Type	Interface	VlanId Status	Inner-VlanId	Mac-Addr	VTEP-Ip/ESI AccessPortDesc
3 Static	Remote	-----	-----	0000.0000.aaaa	3.3.3.4
3 Local	xe2	-----	-----	0000.0000.bbbb	Local Dynamic

Total number of entries are : 2

```
VTEP1#
```

VTEP2

```
VTEP2#show nvo vxlan tunnel
VXLAN Network tunnel Entries
```

Source	Destination	Status	Up/Down	Update
3.3.3.4	2.2.2.4	Installed	00:34:02	00:34:02

Total number of entries are 1

```
VTEP2#show nvo vxlan
```

VXLAN Information

```
=====
```

Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNID Status	VNI-Name Src-Addr	VNI-Type Dst-Addr	Type	Interface	ESI	VLAN DF-
----------------	----------------------	----------------------	------	-----------	-----	----------

CHAPTER 2 VLAN to VNID Mapping

Overview

OcNOS supports mapping Virtual Local Area Network Identifier (VLAN ID) to Virtual Extensible Local Area Network Identifier (VNID) to extend the Layer 2 VLAN over to the Layer 3 VxLAN. The VLAN ID is a unique number assigned to a specific VLAN, and the VNID is the same for a specific VxLAN. The Virtual Tunnel Endpoint (VTEP) is a network device or a software component that encapsulates the ethernet frames from a specific VLAN ID into a ~~VxLAN-VxLAN~~ header that contains the VNID. This encapsulated frame is the ~~VxLAN-VxLAN~~ packet, which is again encapsulated in the UDP packet and wrapped in an outer IP header to transport it to the IP network.

Feature Characteristics

- The VLAN ID to VNID communication is regardless the physical and logical port.
- Each VNID is allowed to map with a single VLAN ID.
- VLAN is removed over the tunnel and re-added when egressing out of the host-connected port.

Benefits

The feature enhances the scalability and flexibility by extending the VLAN to ~~VxLAN-VxLAN~~ boundaries.

Configuration

This section shows the procedure for configuring ~~VxLAN-VxLAN~~ using VLAN to VNI mapping.

Topology

This topology demonstrates the configuration necessary to enable ~~VxLAN-VxLAN~~ VLAN-to-VNID mapping. Leaf1 and Leaf2 are ~~VxLAN-VxLAN~~ VTEPs in the Autonomous System (ASN) 100, and the Spine1 resides in a different Autonomous System (ASN) 200. The setup involves establishing eBGP IPv4 (underlay) neighborship between interface addresses and L2VPN EVPN (overlay) neighborship between loopback interfaces.

Once the underlay and overlay neighborships are established, configure the ~~VxLAN-VxLAN~~ tunnel between Leaf1 and Leaf2. The global VTEP IP is the loopback address.




Figure 2-4: VLAN to VNID mapping

Configuring VLAN to VNID mapping

Follow the steps to configure the ~~VxLAN~~VxLAN EVPN using VLAN to VNI mapping. The detailed configuration procedure demonstrates how access-if ~~vxl~~vxlan is configured on a switchport in trunk mode.

Note: The configuration of access-if ~~vxl~~vxlan is allowed in the access mode also. The example is as follows:

```
(config)#interface xe12
(config-if)# switchport
(config-if)# bridge-group 1 spanning-tree disable
(config-if)# switchport mode access
(config-if)# switchport access vlan 20
(config-if)# access-if-vxlan
(config-if)#exit
```

Configure the Leaf1 and Leaf2:

The parameters used in the configuration procedure are as present for Leaf1. Use the same commands with the Leaf2 parameters to configure the Leaf2.

1. Configure the hostname of the VTEP.

```
(config)#hostname Leaf1
(config)#commit
```

2. Configure the bridge type using the `bridge 1 protocol rstp vlan-bridge` command. This command enables the RSTP VLAN bridge type.

```
(config)#bridge 1 protocol rstp vlan-bridge
```

3. Enter the VLAN database using the `vlan` command and associate the VLAN with a bridge.

```
(config)#vlan database
(config-vlan)#vlan 10 bridge 1 state enable
```

4. Enable the **VXLAN-VxLAN** globally on the VTEP.

```
(config)#nvo vxlan enable
```

Note: Save and reboot the system to enable the **VXLAN-VxLAN** in the hardware.

5. Create the MAC VRF and name it using `mac vrf vrf10`. Configure the VLAN-based service type using `evpn-vlan-service` command, assign a unique route distinguisher and route target value using `rd 1.1.1.1:10` and `route-target both 100:10` commands respectively.

```
(config)#mac vrf vrf10
(config-vrf)#evpn-vlan-service vlan-based
(config-vrf)#rd 1.1.1.1:10
(config-vrf)#route-target both 100:10
```

6. Configure a global IP to the VTEP. This IP address uniquely identifies the VTEP.

```
(config)#nvo vxlan vtep-ip-global 1.1.1.1
```

7. Create a VNID and map it with the bridge VLAN using `nvo vxlan id 10` ingress-replication bridge-vlan 10. Configure the host-reachability-protocol as BGP-EVPN and associate the MAC VRF.

```
(config)#nvo vxlan id 10 ingress-replication bridge-vlan 10
(config-nvo)#vxlan host-reachability-protocol evpn-bgp vrf10
```

8. Assign the IP addresses to the physical and loopback interfaces of the Leaf1 to connect to the Spine.

```
(config)#interface ce49
(config-if)#ip address 11.10.1.1/24
(config-if)#exit
(config)#interface lo
(config-if)#ip address 1.1.1.1/32 secondary
```

9. Configure the interface `xe11` as a switchport. Use the command `bridge-group 1 spanning-tree disable` to associate the bridge group to this interface and disable the Spanning Tree Protocol (STP) to avoid the port block. Configure the switching characteristic of this interface to trunk mode using the `switchport mode trunk` command and this allows multiple VLANs to run in the interface. Use the command `switchport trunk allowed vlan add 10` to enable VLAN 10 through this interface. Map this interface with the **VXLAN-VxLAN** using `access-if-vxlan` command.

```
(config)#interface xe11
(config-if)#switchport
(config-if)# bridge-group 1 spanning-tree disable
(config-if)#switchport mode trunk
(config-if)#switchport trunk allowed vlan add 10
(config-if)#access-if-vxlan
```

10. Configure the BGP and specify the autonomous number (ASN).

```
(config)#router bgp 100
```

11. Configure the router ID.

```
(config-router)#bgp router-id 1.1.1.1
```

12. Configure the neighboring eBGP peers in a different ASN.

```
(config-router)#neighbor 11.10.1.2 remote-as 200
(config-router)#neighbor 11.11.11.11 remote-as 200
```

13. Configure eBGP multihop as the neighboring peer is not directly connected.

```
(config-router)#neighbor 11.11.11.11 ebgp-multihop
```

14. Configure the source loopback address.

```
(config-router)#neighbor 11.11.11.11 update-source lo
```

15. Configure the IPv4 address family and activate the neighbor.

```
(config-router)#address-family ipv4 unicast
(config-router-af)#network 1.1.1.1/32
(config-router)#neighbor 11.10.1.2 activate
(config-router-af)#neighbor 11.10.1.2 allowas-in 1
(config-router-af)#exit-address-family
```

16. Configure the Layer 2 VPN address family and activate the neighbor.

```
(config-router)#address-family l2vpn evpn
(config-router-af)#neighbor 11.11.11.11 activate
(config-router-af)#neighbor 11.11.11.11 allowas-in 1
(config-router-af)#exit-address-family
(config-router)#exit
(config)#commit
```

Configure the Spine1:**1. Configure the hostname of the Spine.**

```
(config)#hostname Spine1
(config)#commit
```

2. Assign the IP addresses to the physical and loopback interfaces of the Spine.

```
(config)#interface ce1
(config-if)#ip address 11.10.1.2/24
(config-if)#exit
(config)#interface ce24
(config-if)#ip address 21.10.1.2/24
(config-if)#exit
(config)#interface lo
(config-if)#ip address 11.11.11.11/32 secondary
(config-if)#exit
```

3. Configure the BGP and specify the ASN.

```
(config)#router bgp 200
```

4. Configure the router ID.

```
(config-router)#bgp router-id 11.11.11.11
```

5. Disable the inbound route filter.

```
(config-router)#no bgp inbound-route-filter
```

6. Configure the neighboring eBGP neighbor in a different ASN.

```
(config-router)#neighbor 11.10.1.1 remote-as 100
(config-router)#neighbor 21.10.1.1 remote-as 100
(config-router)#neighbor 1.1.1.1 remote-as 100
(config-router)#neighbor 2.2.2.2 remote-as 100
```

7. Configure eBGP multihop as the neighboring peer might not be directly connected.

```
(config-router)#neighbor 1.1.1.1 ebgp-multihop
(config-router)#neighbor 2.2.2.2 ebgp-multihop
```

8. Configure the source loopback address.

```
(config-router)#neighbor 1.1.1.1 update-source
(config-router)#neighbor 2.2.2.2 update-source
```

9. Configure the IPv4 address family and activate the neighbor.

```
(config-router)#address-family ipv4 unicast
(config-router-af)#network 11.11.11.11/32
(config-router-af)#neighbor 11.10.1.1 activate
(config-router-af)#neighbor 21.10.1.1 activate
(config-router-af)#exit-address-family
```

10. Configure the Layer 2 VPN address family and activate the neighbor.

```
(config-router)#address-family l2vpn evpn
(config-router-af)#neighbor 1.1.1.1 activate
(config-router-af)#neighbor 2.2.2.2 activate
(config-router-af)#exit-address-family
(config-router)#exit
(config)#commit
```

Running configurations

The running configuration for the Leaf1 is as follows:

```
hostname Leaf1
bridge 1 protocol rstp vlan-bridge
tfo Disable
!
vlan database
  vlan 10 bridge 1 state enable
!
nvo vxlan-VxLAN enable
!
mac vrf vrf10
  evpn-vlan-service vlan-based
  rd 1.1.1.1:10
  route-target both 100:10
!
nvo vxlan-VxLAN vtep-ip-global 1.1.1.1
!
nvo vxlan-VxLAN id 10 ingress-replication bridge-vlan 10
  vxlan-VxLAN host-reachability-protocol evpn-bgp vrf10
!
interface ce49
  ip address 11.10.1.1/24
!
interface lo
  ip address 1.1.1.1/32 secondary
!
interface xe11
  switchport
  bridge-group 1 spanning-tree disable
  switchport mode trunk
  switchport trunk allowed vlan add 10
  access-if-vxlan
!
exit
!
router bgp 100
  bgp router-id 1.1.1.1
  neighbor 11.10.1.2 remote-as 200
  neighbor 11.11.11.11 remote-as 200
  neighbor 11.11.11.11 ebgp-multipath
```

```

neighbor 11.11.11.11 update-source lo
!
address-family ipv4 unicast
network 1.1.1.1/32
neighbor 11.10.1.2 activate
neighbor 11.10.1.2 allowas-in 1
exit-address-family
!
address-family l2vpn evpn
neighbor 11.11.11.11 activate
neighbor 11.11.11.11 allowas-in 1
exit-address-family
!
exit
!
end

```

The running configuration for the Spine1 is as follows:

```

hostname Spine1
!
interface ce1
 ip address 11.10.1.2/24
!
interface ce24
 ip address 21.10.1.2/24
 lldp-agent
!
interface lo
 ip address 11.11.11.11/32 secondary
!
router bgp 200
 bgp router-id 11.11.11.11
 no bgp inbound-route-filter
 neighbor 1.1.1.1 remote-as 100
 neighbor 2.2.2.2 remote-as 100
 neighbor 11.10.1.1 remote-as 100
 neighbor 21.10.1.1 remote-as 100
 neighbor 1.1.1.1 ebgp-multihop
 neighbor 1.1.1.1 update-source lo
 neighbor 2.2.2.2 ebgp-multihop
 neighbor 2.2.2.2 update-source lo
!
address-family ipv4 unicast
network 11.11.11.11/32
neighbor 11.10.1.1 activate
neighbor 21.10.1.1 activate
exit-address-family
!
address-family l2vpn evpn
neighbor 1.1.1.1 activate
neighbor 2.2.2.2 activate
exit-address-family

```

```
!
exit
end
```

Validation

Validate the show output after configuration as shown below.

Leaf1:

```
Leaf1#show ip bgp summary
BGP router identifier 1.1.1.1, local AS number 100
BGP table version is 7
3 BGP AS-PATH entries
0 BGP community entries
```

Neighbor State/PfxRcd	Desc	V	AS	MsgRcv	MsgSen	TblVer	InQ	OutQ	Up/Down
11.10.1.2	2	4	200	266	264	7	0	0	01:37:50

Total number of neighbors 1

Total number of Established sessions 1

```
Leaf1#show bgp l2vpn evpn summary
BGP router identifier 1.1.1.1, local AS number 100
BGP table version is 8
3 BGP AS-PATH entries
0 BGP community entries
```

Neighbor State/PfxRcd	AD	V	AS	MsgRcv	MsgSen	TblVer	InQ	OutQ	Up/Down
		MACIP	MCAST	ESI	PREFIX-ROUTE				
11.11.11.11	3	0	1	2	0	237	235	8	0
					0				01:36:10

Total number of neighbors 1

Total number of Established sessions 1

```
Leaf1#show nvo vxlan-VxLAN tunnel
VXLAN-VxLAN Network tunnel Entries
Source          Destination        Status        Up/Down        Update        Redund
Description
=====
=====
```

Source Description	Destination	Status	Up/Down	Update	Redund
1.1.1.1	2.2.2.2	Installed	01:35:22	01:35:22	----

Total number of entries are 1

```
Leaf1#show nvo vxlan-VxLAN vlan-vnid bridge-vlan 10
VLAN      VNID      Interface
```

10	10	xell
----	----	------

Total number of entries are 1

```
Leaf1#show nvo vxlan-VxLAN vlan-vnid vnid 10
VLAN      VNID      Interface
```

10	10	xel1
----	----	------

Total number of entries are 1

```
Leaf1#show nvo vxlan-VxLAN vlan-vnid
VLAN      VNID      Interface
```

10	10	xel1
----	----	------

Total number of entries are 2

Leaf1#

Leaf1#show nvo vxlan

VXLAN-VxLAN Information

=====

Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI		VLAN	DF-
Status	Src-Addr	Dst-Addr			Redund	Description		
10	---	L2	NW	---	---	---	---	-
---	1.1.1.1		2.2.2.2		---	---		
10	---	--	AC	xel1	---	Single Homed Port ---	10	-
---	----		----					

Total number of entries are 2

Spine1:

```
Spine1#show ip bgp summary
BGP router identifier 11.11.11.11, local AS number 200
BGP table version is 3
2 BGP AS-PATH entries
0 BGP community entries
```

Neighbor State/PfxRcd	Desc	V	AS	MsgRcv	MsgSen	TblVer	InQ	OutQ	Up/Down
11.10.1.1		4	100	247	246	3	0	0	01:44:11
21.10.1.1		4	100	249	247	3	0	0	01:44:11

Total number of neighbors 2

```
Total number of Established sessions 2
Spine1#
Spine1#show bgp l2vpn evpn summary
BGP router identifier 11.11.11.11, local AS number 200
BGP table version is 9
2 BGP AS-PATH entries
0 BGP community entries
```

Neighbor State/PfxRcd	AD	V MACIP	AS MCAST	MsgRcv ESI	MsgSen PREFIX-ROUTE	TblVer	InQ	OutQ	Up/Down
1.1.1.1 3 0	1	4 2	100 0	249 0	252	9 0	0	01:42:31	
2.2.2.2 3 0	1	4 2	100 0	251 0	250	9 0	0	01:42:01	

Total number of neighbors 2

Total number of Established sessions 2

VLAN VNID Mapping Command

The VLAN VNID mapping feature introduces the following configuration command.

access-if-vxlan

Use this command to create a logical port per parent interface for egress VLAN translation.

Use no form of this command to unconfigure the access-if-vxlan.

Command Syntax

```
access-if-vxlan
no access-if-vxlan
```

Parameters

None

Default

None

Command Mode

Interface mode

Applicability

Introduced in OcNOS version 6.5.2.

Example

The below example shows how to configure a logical port per parent interface:

```
OcNOS#configure terminal
```

```
OcNOS(config)#interface xe1
OcNOS(config-if)#access-if-vxlan
```

show nvo vxlan-VxLAN vlan-vnid

Use this command to display the VLAN ID to VNID mapping.

Command Syntax

```
show nvo vxlan-VxLAN vlan-vnid [bridge-vlan <VLAN ID>] [vnid <VNID>] [summary]
```

Parameters

vnid <VNID>	(Optional) Displays all the VLAN ID to VNID mapping.
bridge-vlan <VLAN ID>	(Optional) Displays all the VLAN ID to VNID mapping.
summary	(Optional) Displays the total count of VLAN to VNID mapping.

Default

None

Command Mode

Exec mode

Applicability

Introduced in OcNOS version 6.5.2.

Example

The below examples show the output of VLAN to VNID mapping:

```
OcNOS#show nvo vxlan-VxLAN vlan-vnid
VLAN      VNID      Interface
-----  -----
10        10        xe11
-----
Total number of entries are 1
OcNOS#
OcNOS#show nvo vxlan-VxLAN vlan-vnid bridge-vlan 10
VLAN      VNID      Interface
-----  -----
10        10        xe11
-----
Total number of entries are 1
OcNOS#
```

Table P-2-1 explains the output fields.

Table 2-1: VLAN VNID fields

Field	Description
VLAN	VLAN Identifier.
VNID	VxLAN <ins>VxLAN</ins> Identifier.
Interface	Name of the interface.

Glossary

The following provides definitions for key terms or abbreviations and their meanings used throughout this document:

Key Terms/Acronym	Description
Virtual Local Area Network Identifier (VLAN ID)	Virtual Local Area Network Identifier is a 12-bit unique identifier assigned to a VLAN to identify it in a network.
Virtual Extensible Local Area Network Identifier (VNID)	Virtual Extensible Local Area Network Identifier is a unique 24-bit identifier assigned to a VxLAN <ins>VxLAN</ins> to identify it in a network.
Virtual Local Area Network (VLAN)	Virtual Local Area Network in a network configuration creates a separate and isolated virtual network with other virtual networks over a single physical interface.
Virtual Extensible Local Area Network (VxLAN)	Virtual Extensible Local Area Network (VxLAN) enables the creation of a virtualized Layer 2 network over the Layer 3 infrastructure. This is an overlay network on Layer 3 designed to overcome the limitations of VLANs.
Virtual Tunnel Endpoint (VTEP)	Virtual Tunnel Endpoint is a significant component in VxLAN <ins>VxLAN</ins> that encapsulates or decapsulates the VxLAN <ins>VxLAN</ins> traffic as it enters or leaves the VxLAN <ins>VxLAN</ins> overlay network respectively.

VxLAN - Ethernet Virtual Private Network

CHAPTER 1 VXLAN-EVPN Configuration

This section contains basic VXLAN-EVPN configuration examples.

VXLAN (Virtual eXtended LAN) creates LAN segments using a MAC-in-IP encapsulation. The encapsulation carries the original L2 frame received from a host to the destination in another host using IP tunnels. The endpoints of the virtualized tunnel formed using VXLAN are called VTEPs (VXLAN Tunnel End Points). The VTEPs carry tenant data in L3 tunnels over the network which permits the network to support multiple tenants. The tenant data is not used in routing or switching. This aids in tenant machine movement and allows the tenants to have same IP/MAC addresses.

Information about the given VM to get to the VTEP is crucial in VXLAN protocol; therefore BGP-MP is used to carry this information across VTEPs.

Note: For port-channel/Static-channel interface, storm control will be applied on each member port. For Example: if Interface eth1 and interface eth2 is part of port-channel i.e. po1 and storm control 2mbps is applied for broadcast traffic, then the storm control settings will be applied on each member port and broadcast traffic on each member port will be rate limited to 2mbps each.

Topology

The procedures in this section use the topology in [Figure 1-5](#).




Figure 1-5: VXLAN EVPN

VTEP1

#configure terminal	Enter configure mode
(config)#interface xe1	Enter interface mode
(config-if)#switchport	Configure the interface as a switch port.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode
(config)#interface xe2	Enter interface mode
(config-if)#switchport	Configure the interface as switch port.
(config-if)#no shutdown	Bring the interface into operation.
(config-if)#exit	Exit interface mode.
(config)#interface xe22	Enter interface mode.
(config-if)#ip address 10.1.1.1/24	Set an IP address on the interface.

(config-if)#no shutdown	Bring the interface into operation.
(config-if)#exit	Exit interface mode.
(config)#interface lo	Enter interface mode.
(config-if)#ip address 1.1.1.1/32 secondary	Set an IP address on the interface.
(config-if)#no shutdown	Bring the interface into operation.
(config-if)#exit	Exit interface mode.
(config)#router isis ABC	Create an IS-IS routing instance (ABC).
(config-router)#is-type level-1	Configure instance as level-1-only routing.
(config-router)#net 49.0001.1111.1111.1111.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
(config-router)#exit	Exit router mode.
(config)#interface xe22	Enter interface mode
(config-if)#ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if)#isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if)#exit	Exit interface mode.
(config)#interface lo	Enter interface mode.
(config-if)#ip router isis ABC	Enable IS-IS routing on an interface for area 49 (ABC).
(config-if)#isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if)#exit	Exit interface mode.
(config)#mac vrf vrf_evpn_100	Configure a new VRF named vrf_evpn_100.
(config-vrf)#rd 1.1.1.1:1	Assign the Route Distinguisher value.
(config-vrf)#route-target both 100:1	Configure route target to import and export the routes.
(config-vrf)#exit	Exit VRF mode.
(config)#router bgp 1	Define the routing process. The number 1 specifies the AS number of VTEP1.
(config-router)#bgp router-id 1.1.1.1	Configure router-id for this BGP process.
(config-router)#neighbor 2.2.2.2 remote-as 1	Define BGP neighbor: 2.2.2.2 is the IP address of the neighbor (VTEP2), and 1 is the neighbor's AS number.
(config-router)# neighbor 2.2.2.2 update-source 1.1.1.1	Define BGP neighbor: 1.1.1.1 is the peer interface.
(config-router)#address-family l2vpn evpn	Configure address-family L2VPN EVPN.
(config-router-af)#neighbor 2.2.2.2 activate	Activate the neighbor in the EVPN address family.
(config-router-af)#exit-address-family	Exit the address-family mode.
(config-router)#exit	Exit router mode.
(config)#nvo vxlan enable	Enable VXLAN globally on this VTEP.
(config)#nvo vxlan vtep-ip-global 1.1.1.1	Assign a global IP to the VTEP.
(config)#nvo vxlan id 100 ingress-replication	Configure a VNID on this VTEP and enter NVO mode.
(config-nvo)#vxlan host-reachability-protocol evpn-bgp vrf_evpn_100	Configure host-reachability-protocol as BGP-EVPN and associate the VNID with vrf_evpn_100.
(config-nvo)#exit	Exit NVO mode.

(config) #nvo vxlan access-if port-vlan xe1 2	Configure access-port xe1 and map vlan 2
(config-nvo-acc-if) #map vnid 100	Map VNID 100 to access-port xe1.
(config-nvo-acc-if) #exit	Exit NVO access-if mode.
(config) #nvo vxlan id 200 ingress-replication	Configure second VNID on this VTEP and enter NVO mode.
(config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf_evpn_100	Configure host-reachability-protocol as BGP-EVPN and associate the VNID with vrf_evpn_100
(config-nvo) #exit	Exit NVO mode.
(config) #nvo vxlan access-if port-vlan xe2 3	Configure access-port xe2 and map vlan 3
(config-nvo-acc-if) #map vnid 200	Map VNID 200 to access-port xe2.
(config-nvo-acc-if) #exit	Exit NVO access-if mode.
(config) #commit	Commit the configurations

RR

#configure terminal	Enter configure mode.
(config) #interface xe22	Enter interface mode.
(config-if) #ip address 10.1.1.2/24	Set an IP address on the interface.
(config-if) #no shutdown	Bring the interface into operation
(config-if) #exit	Exit interface mode.
(config) #interface xe11	Enter interface mode.
(config-if) #ip address 20.1.1.2/24	Set an IP address on the interface.
(config-if) #no shutdown	Bring the interface into operation
(config-if) #exit	Exit interface mode.
(config) #router isis ABC	Create an IS-IS routing instance (ABC).
(config-router) #is-type level-1	Configure instance as level-1-only routing.
(config-router) #net 49.0001.3333.3333.3333.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
(config-router) #exit	Exit router mode.
(config) #interface xe22	Enter interface mode.
(config-if) #ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if) #isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if) #exit	Exit interface mode.
(config) #interface xe11	Enter interface mode.
(config-if) #ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if) #isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if) #exit	Exit interface mode.
(config) #commit	Commit the configurations

VTEP2

#configure terminal	Enter configure mode.
(config)#interface xe1	Enter interface mode.
(config-if)#switchport	Configure the interface as switchport.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#interface xe2	Enter interface mode.
(config-if)#switchport	Configure the interface as switchport.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#interface xe11	Enter interface mode.
(config-if)#ip address 20.1.1.1/24	Set an IP address on the interface.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#interface lo	Enter interface mode.
(config-if)#ip address 2.2.2.2/32 secondary	Set an IP address on the interface.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#router isis ABC	Create an IS-IS routing instance (ABC).
(config-router)#is-type level-1	Configure instance as level-1-only routing.
(config-router)#net 49.0001.2222.2222.2222.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
(config-router)#exit	Exit router mode.
(config)#interface xe11	Enter interface mode.
(config-if)#ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if)#isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if)#exit	Exit interface mode.
(config)#interface lo	Enter interface mode.
(config-if)#ip router isis ABC	Enable IS-IS routing on an interface for area 49 (ABC).
(config-if)#isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if)#exit	Exit interface mode.
(config)#mac vrf vrf_evpn_100	Configure a new VRF named vrf_evpn_100.
(config-vrf)#rd 2.2.2.1:1	Assign the Route Distinguisher value.
(config-vrf)#route-target both 100:1	Configure route target to import and export the routes.
(config-vrf)#exit	Exit VRF mode.
(config)#router bgp 1	Define the routing process. The number 1 specifies the AS number of VTEP1.
(config-router)#neighbor 1.1.1.1 remote-as 1	Define BGP neighbor: 1.1.1.1 is the IP address of the neighbor (VTEP1), and 1 is the neighbor's AS number.
(config-router)# neighbor 1.1.1.1 update-source 2.2.2.2	Define BGP neighbor: 2.2.2.2 is the peer interface.

(config-router) #address-family l2vpn evpn	Configure address-family L2VPN EVPN.
(config-router-af) #neighbor 1.1.1.1 activate	Activate the neighbor in the EVPN address family.
(config-router-af) #exit-address-family	Exit address-family mode.
(config-router) #exit	Exit router mode.
(config) #nvo vxlan enable	Enable VXLAN globally on this VTEP.
(config) #nvo vxlan vtep-ip-global 2.2.2.2	Assign a global IP to the VTEP.
(config) #nvo vxlan id 100 ingress-replication	Configure a VNID on this VTEP and enter NVO mode.
(config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf_evpn_100	Configure host-reachability-protocol as BGP-EVPN and associate the VNID with <code>vrf_evpn_100</code> .
(config-nvo) #exit	Exit NVO mode.
(config) #nvo vxlan access-if port-vlan xe1 2	Configure access-port xe1 and map vlan 2
(config-nvo-acc-if) #map vnid 100	Map VNID 100 to access-port xe1.
(config-nvo-acc-if) #exit	Exit NVO access-if mode.
(config) #nvo vxlan id 200 ingress-replication	Configure second VNID on this VTEP and enter NVO mode.
(config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf_evpn_100	Configure host-reachability-protocol as BGP-EVPN and associate the VNID with <code>vrf_evpn_100</code>
(config-nvo) #exit	Exit NVO mode.
(config) #nvo vxlan access-if port-vlan xe2 3	Configure access-port xe2 and map vlan 3
(config-nvo-acc-if) #map vnid 200	Map VNID 200 to access-port xe2.
(config-nvo-acc-if) #exit	Exit NVO access-if mode.
(config) #commit	Commit the configurations

Validation

CE1 and CE2 have hosts configured with MAC addresses, IP addresses, and VLAN identifiers as shown below.

		VLAN	IP Address	Mac Address
VTEP1	CE-1	2	12.12.12.10	0000.0000.abab
VTEP2	CE-2	2	12.12.12.20	0000.0000.cdc当地
VTEP1	CE-1	3	13.13.13.10	0000:0b60:25f2
VTEP2	CE-2	3	13.13.13.20	0000:0b60:25f3

Perform a tagged ping of VLAN 2 from CE1 to CE2 and vice-versa. Also perform a tagged ping of VLAN 3 from CE1 to CE2 and vice-versa.

VTEP Tunnel Status

```
VTEP-1#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination        Status      Up/Down      Update
=====
```

```
1.1.1.1          2.2.2.2          Installed      00:05:53      00:05:53
Total number of entries are 1
```

```
VTEP-2#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source           Destination       Status        Up/Down      Update
=====
2.2.2.2          1.1.1.1          Installed     00:05:46      00:05:46
Total number of entries are 1
```

VTEP ARP Cache

```
VTEP-1#sh nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====
ARP Timeout : 300 sec Random-Jitter-Max : 640
VNID   Ip-Addr           Mac-Addr         Type          Age-Out
Retries-Left
-----
200    13.13.13.10       0000.0b60.25f2   Dynamic Local   246
200    13.13.13.20       0000.0b60.25f3   Dynamic Remote  -----
100    12.12.12.20       0000.0000.ccdc   Dynamic Remote  -----
100    12.12.12.10       0000.0000.abab   Dynamic Local   246
Total number of entries are 4
```

```
VTEP-2#sh nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====
ARP Timeout : 300 sec Random-Jitter-Max : 640
VNID   Ip-Addr           Mac-Addr         Type          Age-
Out   Retries-Left
-----
200    13.13.13.10       0000.0b60.25f2   Dynamic Remote  -----
200    13.13.13.20       0000.0b60.25f3   Dynamic Local   257
2      12.12.12.10       0000.0000.abab   Dynamic Remote  -----
100    12.12.12.20       0000.0000.ccdc   Dynamic Local   257
2
Total number of entries are 4
```

VTEP MAC Tables

```
VTEP-1#show nvo vxlan mac-table
=====
VXLAN MAC Entries
=====
VNID   Interface  VlanId   Inner-VlanId   Mac-Addr      VTEP-Ip/ESI   Type
Status  AccessPortDesc
-----
```

```

100      ----      -----      -----      0000.0000.ccdc      2.2.2.2
Dynamic Remote      -----      -----      0000.0000.abab      1.1.1.1
100      xe1      2      -----      0000.0000.abab      1.1.1.1
Dynamic Local      -----      -----      0000.0b60.25f2      1.1.1.1
200      xe2      3      -----      0000.0b60.25f2      1.1.1.1
Dynamic Local      -----      -----      0000.0b60.25f3      2.2.2.2
200      ----      -----      -----      0000.0b60.25f3      2.2.2.2
Dynamic Remote      -----      -----      Total number of entries are : 4

```

VTEP-2#show nvo vxlan mac-table

```

=====
          VXLAN MAC Entries
=====
VNID  Interface  VlanId  Inner-VlanId  Mac-Addr      VTEP-Ip/ESI  Type    Status     AccessPortDesc
=====
100   xe1        2        ----          0000.0000.ccdc  2.2.2.2    Dynamic Local  -----      -----
100   ----       2        ----          0000.0000.abab  1.1.1.1    Dynamic Remote -----      -----
200   ----       2        ----          0000.0b60.25f2  1.1.1.1    Dynamic Remote -----      -----
200   xe2        3        ----          0000.0b60.25f3  2.2.2.2    Dynamic Local  -----      -----
Total number of entries are : 4

```

VTEP MAC-IP BGP EVPN Entries

VTEP-1#show bgp 12vpn evpn mac-ip

```

RD[1.1.1.1:1] VRF[vrf_evpn_100]:
ESI      Eth-Tag      Mac-Address      IP-Address      VNID      L3VNID      Nexthop      GW-Type
0        100         0000:0000:abab  12.12.12.10  100       0           1.1.1.1      --
0        200         0000:0b60:25f2  13.13.13.10  200       0           1.1.1.1      --
RD[2.2.2.2:1]
ESI      Eth-Tag      Mac-Address      IP-Address      VNID      L3VNID      Nexthop      GW-Type
0        100         0000:0000:cddc  12.12.12.20  100       0           2.2.2.2      --
0        200         0000:0b60:25f3  13.13.13.20  200       0           2.2.2.2      --

```

VTEP-2#show bgp 12vpn evpn mac-ip

```

RD[1.1.1.1:1]
ESI      Eth-Tag      Mac-Address      IP-Address      VNID      L3VNID      Nexthop      GW-Type
0        100         0000:0000:abab  12.12.12.10  100       0           1.1.1.1      --
0        200         0000:0b60:25f2  13.13.13.10  200       0           1.1.1.1      --
RD[2.2.2.2:1] VRF[vrf_evpn_100]:
ESI      Eth-Tag      Mac-Address      IP-Address      VNID      L3VNID      Nexthop      GW-Type
0        100         0000:0000:cddc  12.12.12.20  100       0           2.2.2.2      --
0        100         0000:0b60:25f2  13.13.13.10  100       0           2.2.2.2      --

```

LAG as Access Port with ECMP on the Network Side

This section contains basic VXLAN EVPN configuration with LAG as an access port and ECMP on the network side.

Topology

The procedures in this section use the topology in [Figure 1-6](#).




Figure 1-6: VXLAN EVPN with LAG and ECMP

SW-1

#configure terminal	Enter configure mode
(config)#bridge 1 protocol ieee vlan-bridge	Configure IEEE vlan bridge
(config)#vlan database	Enter into the vlan database
(config-vlan)#vlan 2 bridge 1 state enable	Configure vlan 2 and associate with bridge 1
(config-vlan)#vlan 3 bridge 1 state enable	Configure vlan 3 and associate with bridge 1
(config-vlan)#exit	Exit from the vlan database
(config)#in xe41	Enter interface mode
(config-if)#no shutdown	Make interface admin up
(config-if)#switchport	Set the interface as Layer2 port
(config-if)#bridge-group 1	Associate the Interface with bridge-group.
(config-if)#switchport mode trunk	Set the switching characteristics of this interface to trunk mode
(config-if)#switchport trunk allowed vlan add 2	Configure the VLANs that should be allowed through this interface
(config-if)#switchport trunk allowed vlan add 3	Configure the VLANs that should be allowed through this interface
(config-if)#exit	Exit interface mode.
(config)#interface po1	Enter interface mode
(config-if)#switchport	Set the interface as Layer2 port
(config-if)#exit	Exit interface mode.
(config)#in xe29	Enter interface mode
(config-if)#switchport	Set the interface as Layer2 port
(config-if)#channel-group 1 mode active	Configure the interface to be part of port channel 1
(config-if)#exit	Exit interface mode.
(config)#in xe30	Enter interface mode
(config-if)#switchport	Set the interface as Layer2 port
(config-if)#channel-group 1 mode active	Configure the interface to be part of port channel 1

(config-if)#exit	Exit interface mode.
(config)#in xe31	Enter interface mode
(config-if)#switchport	Set the interface as Layer2 port
(config-if)#channel-group 1 mode active	Configure the interface to be part of port channel 1
(config-if)#exit	Exit interface mode.
(config)#in xe32	Enter interface mode
(config-if)#switchport	Set the interface as Layer2 port
(config-if)#channel-group 1 mode active	Configure the interface to be part of port channel 1
(config-if)#exit	Exit interface mode.
(config-if)#inter po1	Enter interface mode
(config-if)#bridge-group 1	Associate the Interface with bridge-group.
(config-if)#switchport mode trunk	Set the switching characteristics of this interface to trunk mode
(config-if)#switchport trunk allowed vlan add 2	Configure the VLANs that should be allowed through this interface
(config-if)#switchport trunk allowed vlan add 3	Configure the VLANs that should be allowed through this interface
(config-if)#exit	Exit interface mode.
(config)#commit	Commit the configurations

VTEP-1

#configure terminal	Enter configure mode
(config)#interface po1	Create interface po1
(config-if)#switchport	Configure the interface as switchport.
(config-if)#exit	Exit interface mode
(config)#interface xe3	Enter interface mode.
(config-if)#switchport	Configure the interface as switchport.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode
(config)#interface xe5	Enter interface mode
(config-if)#switchport	Configure the interface as switchport.
(config-if)#channel-group 1 mode active	Configure the interface to be part of port channel 1
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode
(config)#interface xe6	Enter interface mode
(config-if)#switchport	Configure the interface as switchport.
(config-if)#channel-group 1 mode active	Configure the interface to be part of port channel 1
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode
(config)#interface xe7	Enter interface mode
(config-if)#switchport	Configure the interface as switchport.

(config-if)#channel-group 1 mode active	Configure the interface to be part of port channel 1
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode
(config)#interface xe8	Enter interface mode
(config-if)#switchport	Configure the interface as switchport.
(config-if)#channel-group 1 mode active	Configure the interface to be part of port channel 1
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#interface xe1	Enter interface mode.
(config-if)#ip address 10.1.1.0/31	Configure IP address on the interface xe1.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#interface xe2	Enter interface mode.
(config-if)#ip address 10.1.1.2/31	Configure IP address on the interface xe2.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#interface lo	Enter interface mode.
(config-if)#ip address 1.1.1.1/32 secondary	Configure IP address on the interface xe3.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#router isis ABC	Create an IS-IS routing instance (ABC).
(config-router)#is-type level-1	Configure instance as level-1-only routing.
(config-router)#net 49.0001.1111.1111.1111.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
(config-router)#exit	Exit router mode.
(config)#interface xe1	Enter interface mode.
(config-if)#ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if)#isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if)#exit	Exit interface mode.
(config)#interface xe2	Enter interface mode.
(config-if)#ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if)#isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if)#exit	Exit interface mode.
(config)#interface lo	Enter interface mode.
(config-if)#ip router isis ABC	Enable IS-IS routing on an interface for area 49 (ABC).
(config-if)#isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if)#exit	Exit interface mode.
(config)#mac vrf vrf_evpn_100	Configure a new VRF named vrf_evpn_100.
(config-vrf)#rd 1.1.1.1:1	Assign the Route Distinguisher value.
(config-vrf)#route-target both 100:1	Configure route target to import and export the routes.

(config-vrf) #exit	Exit VRF mode.
(config) #load-balance rtag7	Enable load balancing for RTAG7 globally.
(config) #load-balance rtag7 ipv4 src-ipv4	Enable load balancing for RTAG7 for IPv4 for source IP.
(config) #router bgp 65535	Define the routing process. The number 65535 specifies the AS number of VTEP1.
(config-router) #bgp router-id 1.1.1.1	Configure router-id for this BGP process.
(config-router) #neighbor 2.2.2.2 remote-as 65535	Define BGP neighbor: 2.2.2.2 is the IP address of the neighbor (VTEP2), and 65535 is the neighbor's AS number.
(config-router) # neighbor 2.2.2.2 update-source 1.1.1.1	Define BGP neighbor: 1.1.1.1 is the peer interface.
(config-router) #neighbor 3.3.3.3 remote-as 65535	Define BGP neighbor: 3.3.3.3 is the IP address of the neighbor (VTEP3), and 65535 is the neighbor's AS number.
(config-router) # neighbor 3.3.3.3 update-source 1.1.1.1	Define BGP neighbor: 1.1.1.1 is the peer interface.
(config-router) #address-family l2vpn evpn	Configure address-family L2VPN EVPN.
(config-router-af) #neighbor 2.2.2.2 activate	Activate the neighbor at VTEP2 in the EVPN address family.
(config-router-af) #neighbor 3.3.3.3 activate	Activate the neighbor at VTEP3 in the EVPN address family.
(config-router-af) #exit-address-family	Exit address-family mode.
(config-router) #exit	Exit router mode.
(config) #nvo vxlan enable	Enable VXLAN globally on this VTEP.
(config) #nvo vxlan vtep-ip-global 1.1.1.1	Assign a global IP to the VTEP.
(config) #nvo vxlan id 100001 ingress-replication	Configure a VNID on this VTEP and enter NVO mode.
(config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf_evpn_100	Configure host-reachability-protocol as BGP-EVPN and associate the VNID with VRF vrf_evpn_100.
(config-nvo) #exit	Exit NVO mode.
(config) #nvo vxlan access-if port-vlan xe3 2	Configure access-port xe3 and map vlan 2
(config-nvo-acc-if) #map vnid 100001	Map VNID 100001 to access-port xe3.
(config-nvo-acc-if) #exit	Exit NVO access-if mode.
(config) #nvo vxlan access-if port-vlan po1 2	Configure access-port po1 and map vlan 2
(config-nvo-acc-if) #map vnid 100001	Map VNID 100001 to access-port po1.
(config-nvo-acc-if) #exit	Exit NVO access-if mode.
(config) #nvo vxlan id 200001 ingress-replication	Configure second VNID on this VTEP and enter NVO mode.
(config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf_evpn_100	Configure host-reachability-protocol as BGP-EVPN and associate the VNID with VRF vrf_evpn_100.
(config-nvo) #exit	Exit NVO mode.
(config) #nvo vxlan access-if port-vlan xe3 3	Configure access-port xe3 and map vlan 3
(config-nvo-acc-if) #map vnid 200001	Map VNID 200001 to access-port xe3.
(config-nvo-acc-if) #exit	Exit NVO access-if mode.

(config) #nvo vxlan access-if port-vlan po1 3	Configure access-port po1 and map vlan 3
(config-nvo-acc-if) #map vnid 200001	Map VNID 200001 to access-port xe3.
(config-nvo-acc-if) #exit	Exit NVO access-if mode.
(config) #commit	Commit the configurations

RR-1

#configure terminal	Enter configure mode.
(config) #interface lo	Enter interface mode
(config-if) #ip address 12.12.12.12/32 secondary	Set an IP address on the interface.
(config-if) #no shutdown	Bring the interface into operation
(config-if) #exit	Exit interface mode.
(config) #interface xe1	Enter interface mode.
(config-if) #ip address 10.1.1.1/31	Configure IP address on the interface xe1.
(config-if) #no shutdown	Bring the interface into operation
(config-if) #exit	Exit interface mode.
(config) #interface xe2	Enter interface mode.
(config-if) #ip address 20.1.1.1/31	Configure IP address on the interface xe2.
(config-if) #no shutdown	Bring the interface into operation
(config-if) #exit	Exit interface mode.
(config) #interface xe3	Enter interface mode.
(config-if) #ip address 30.1.1.1/31	Configure IP address on the interface xe3.
(config-if) #no shutdown	Bring the interface into operation
(config-if) #exit	Exit interface mode.
(config) #router isis ABC	Create an IS-IS routing instance (ABC).
(config-router) #is-type level-1	Configure instance as level-1-only routing.
(config-router) #net 49.0001.4444.4444.4444.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
(config-router) #exit	Exit router mode.
(config) #interface lo	Enter interface mode.
(config-if) #ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if) #isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if) #exit	Exit interface mode.
(config) #interface xe1	Enter interface mode.
(config-if) #ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if) #isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if) #exit	Exit interface mode.
(config) #interface xe2	Enter interface mode.
(config-if) #ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if) #isis circuit-type level-1	Configure instance as level-1-only routing.

(config-if)#exit	Exit interface mode.
(config)#interface xe3	Enter interface mode.
(config-if)#ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if)#isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if)#exit	Exit interface mode.
(config)#commit	Commit the configurations

RR-2

#configure terminal	Enter configure mode.
(config)#interface lo	Enter interface mode.
(config-if)#ip address 13.13.13.13/32 secondary	Set an IP address on the interface.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#interface xe1	Enter interface mode.
(config-if)#ip address 10.1.1.3/31	Configure IP address on the interface xe1.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#interface xe2	Enter interface mode.
(config-if)#ip address 20.1.1.3/31	Configure IP address on the interface xe2.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#interface xe3	Enter interface mode.
(config-if)#ip address 30.1.1.3/31	Configure IP address on the interface xe3.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#router isis ABC	Create an IS-IS routing instance (ABC).
(config-router)#is-type level-1	Configure instance as level-1-only routing.
(config-router)#net 49.0001.5555.5555.5555.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
(config-router)#exit	Exit router mode.
(config)#interface lo	Enter interface mode.
(config-if)#ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if)#isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if)#exit	Exit interface mode.
(config)#interface xe1	Enter interface mode.
(config-if)#ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if)#isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if)#exit	Exit interface mode.
(config)#interface xe2	Enter interface mode.
(config-if)#ip router isis ABC	Enable IS-IS routing on an interface (ABC).

(config-if)#isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if)#exit	Exit interface mode.
(config)#interface xe3	Enter interface mode.
(config-if)#ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if)#isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if)#exit	Exit interface mode.
(config)#commit	Commit the configurations

VTEP-2

#configure terminal	Enter configure mode
(config)#interface po1	Enter interface mode
(config-if)#switchport	Configure the interface as switchport
(config-if)#exit	Exit interface mode
(config)#interface xe3	Enter interface mode
(config-if)#switchport	Configure the interface as switchport.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#interface xe1	Enter interface mode.
(config-if)#ip address 20.1.1.0/31	Configure IP address on the interface xe1.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#interface xe2	Enter interface mode.
(config-if)#ip address 20.1.1.2/31	Configure IP address on the interface xe2.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#interface lo	Enter interface mode.
(config-if)#ip address 2.2.2.2/32 secondary	Configure IP address on the interface xe3.
(config-if)#no shutdown	Bring the interface into operation
(config-if)#exit	Exit interface mode.
(config)#router isis ABC	Create an IS-IS routing instance (ABC).
(config-router)#is-type level-1	Configure instance as level-1-only routing.
(config-router)#net 49.0001.2222.2222.2222.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
(config-router)#exit	Exit router mode.
(config)#interface xe1	Enter interface mode.
(config-if)#ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if)#isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if)#exit	Exit interface mode.
(config)#interface xe2	Enter interface mode.
(config-if)#ip router isis ABC	Enable IS-IS routing on an interface (ABC).

(config-if)#isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if)#exit	Exit interface mode.
(config)#interface lo	Enter interface mode.
(config-if)#ip router isis ABC	Enable IS-IS routing on an interface for area 49 (ABC).
(config-if)#isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if)#exit	Exit interface mode.
(config)#mac vrf vrf_evpn_100	Configure a new VRF named vrf_evpn_100.
(config-vrf)#rd 1.1.1.1:1	Assign the Route Distinguisher value.
(config-vrf)#route-target both 100:1	Configure route target to import and export the routes.
(config-vrf)#exit	Exit VRF mode.
(config)#load-balance rtag7	Enable load balancing for RTAG7 globally.
(config)#load-balance rtag7 ipv4 src-ipv4	Enable load balancing for RTAG7 for IPv4 for source IP.
(config)#router bgp 65535	Define the routing process. The number 65535 specifies the AS number of VTEP1.
(config-router)#neighbor 1.1.1.1 remote-as 65535	Define BGP neighbor: 1.1.1.1 is the IP address of the neighbor (VTEP1), and 65535 is the neighbor's AS number.
(config-router)#neighbor 1.1.1.1 update-source 2.2.2.2	Define BGP neighbor: 2.2.2.2 is the peer interface.
(config-router)#neighbor 3.3.3.3 remote-as 65535	Define BGP neighbor: 3.3.3.3 is the IP address of the neighbor (VTEP3), and 65535 is the neighbor's AS number.
(config-router)#neighbor 3.3.3.3 update-source 2.2.2.2	Define BGP neighbor: 2.2.2.2 is the peer interface.
(config-router)#address-family l2vpn evpn	Configure address-family L2VPN EVPN.
(config-router-af)#neighbor 1.1.1.1 activate	Activate the neighbor at VTEP1 in the EVPN address family.
(config-router-af)#neighbor 3.3.3.3 activate	Activate the neighbor at VTEP3 in the EVPN address family.
(config-router-af)#exit-address-family	Exit address-family mode.
(config-router)#exit	Exit router mode.
(config)#nvo vxlan enable	Enable VXLAN globally on this VTEP.
(config)#nvo vxlan vtep-ip-global 2.2.2.2	Assign a global IP to the VTEP.
(config)#nvo vxlan id 100001 ingress-replication	Configure a VNID on this VTEP and enter NVO mode.
(config-nvo)#vxlan host-reachability-protocol evpn-bgp vrf_evpn_100	Configure host-reachability-protocol as BGP-EVPN and associate the VNID with VRF vrf_evpn_100.
(config-nvo)#exit	Exit NVO mode.
(config)#nvo vxlan access-if port-vlan xe3 2	Configure access-port xe3 and map vlan 2
(config-nvo-acc-if)#map vnid 100001	Map VNID 100001 to access-port xe3.
(config-nvo-acc-if)#exit	Exit NVO access-if mode.
(config)#nvo vxlan id 200001 ingress-replication	Configure second VNID on this VTEP and enter NVO mode.
(config-nvo)#vxlan host-reachability-protocol evpn-bgp vrf_evpn_100	Configure host-reachability-protocol as BGP-EVPN and associate the VNID with VRF vrf_evpn_100.
(config-nvo)#exit	Exit NVO mode.

(config) #nvo vxlan access-if port-vlan xe3 3	Configure access-port xe3 and map vlan 3
(config-nvo-acc-if) #map vnid 200001	Map VNID 200001 to access-port xe3.
(config-nvo-acc-if) #exit-address-family	Exit NVO access-if mode.
(config) #commit	Commit the configurations

VTEP-3

#configure terminal	Enter configure mode.
(config) #interface xe3	Enter interface mode.
(config-if) #switchport	Configure the interface as switchport.
(config-if) #no shutdown	Bring the interface into operation
(config-if) #exit	Exit interface mode.
(config) #interface xe1	Enter interface mode.
(config-if) #ip address 30.1.1.0/31	Configure IP address on the interface xe1.
(config-if) #no shutdown	Bring the interface into operation
(config-if) #exit	Exit interface mode.
(config) #interface xe2	Enter interface mode.
(config-if) #ip address 30.1.1.2/31	Configure IP address on the interface xe2.
(config-if) #no shutdown	Bring the interface into operation
(config-if) #exit	Exit interface mode.
(config) #interface lo	Enter interface mode.
(config-if) #ip address 3.3.3.3/32 secondary	Configure IP address on the loopback interface.
(config-if) #no shutdown	Bring the interface into operation
(config-if) #exit	Exit interface mode.
(config) #router isis ABC	Create an IS-IS routing instance (ABC).
(config-router) #is-type level-1	Configure instance as level-1-only routing.
(config-router) #net 49.0001.3333.3333.3333.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
(config-router) #exit	Exit router mode.
(config) #interface xe1	Enter interface mode.
(config-if) #ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if) #isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if) #exit	Exit interface mode.
(config) #interface xe2	Enter interface mode.
(config-if) #ip router isis ABC	Enable IS-IS routing on an interface (ABC).
(config-if) #isis circuit-type level-1	Configure instance as level-1-only routing.
(config-if) #exit	Exit interface mode.
(config) #interface lo	Enter interface mode.
(config-if) #ip router isis ABC	Enable IS-IS routing on an interface for area 49 (ABC).
(config-if) #isis circuit-type level-1	Configure instance as level-1-only routing.

(config-if)#exit	Exit interface mode.
(config)#mac vrf vrf_evpn_100	Configure a new VRF named vrf_evpn_100.
(config-vrf)#rd 1.1.1.1:1	Assign the Route Distinguisher value.
(config-vrf)#route-target both 100:1	Configure route target to import and export the routes.
(config-vrf)#exit	Exit VRF mode.
(config)#load-balance rtag7	Enable load balancing for RTAG7 globally.
(config)#load-balance rtag7 ipv4 src-ipv4	Enable load balancing for RTAG7 for IPv4 for source IP.
(config)#router bgp 65535	Define the routing process. The number 65535 specifies the AS number of VTEP1.
(config-router)#neighbor 1.1.1.1 remote-as 65535	Define BGP neighbor: 1.1.1.1 is the IP address of the neighbor (RR1), and 65535 is the neighbor's AS number.
(config-router)#neighbor 1.1.1.1 update-source 3.3.3.3	Define BGP neighbor: 3.3.3.3 is the peer interface.
(config-router)#neighbor 2.2.2.2 remote-as 65535	Define BGP neighbor: 2.2.2.2 is the IP address of the neighbor (VTEP3), and 65535 is the neighbor's AS number.
(config-router)#neighbor 2.2.2.2 update-source 3.3.3.3	Define BGP neighbor: 3.3.3.3 is the peer interface.
(config-router)#address-family l2vpn evpn	Configure address-family L2VPN EVPN.
(config-router-af)#neighbor 1.1.1.1 activate	Activate the neighbor at VTEP1 in the EVPN address family.
(config-router-af)#neighbor 2.2.2.2 activate	Activate the neighbor at VTEP2 in the EVPN address family.
(config-router-af)#exit-address-family	Exit address-family mode.
(config-router)#exit	Exit router mode.
(config)#nvo vxlan enable	Enable VXLAN globally on this VTEP.
(config)#nvo vxlan vtep-ip-global 3.3.3.3	Assign a global IP to the VTEP.
(config)#nvo vxlan id 100001 ingress-replication	Configure a VNID on this VTEP and enter NVO mode.
(config-nvo)#vxlan host-reachability-protocol evpn-bgp vrf_evpn_100	Configure host-reachability-protocol as BGP-EVPN and associate the VNID with VRF vrf_evpn_100.
(config-nvo)#exit	Exit NVO mode.
(config)#nvo vxlan access-if port-vlan xe3 2	Configure access-port xe3 and map vlan 2
(config-nvo-acc-if)#map vnid 100001	Map VNID 100001 to access-port xe3.
(config-nvo-acc-if)#exit-address-family	Exit NVO access-if mode.
(config)#nvo vxlan id 200001 ingress-replication	Configure second VNID on this VTEP and enter NVO mode.
(config-nvo)#vxlan host-reachability-protocol evpn-bgp vrf_evpn_100	Configure host-reachability-protocol as BGP-EVPN and associate the VNID with VRF vrf_evpn_100
(config-nvo)#exit	Exit NVO mode.
(config)#nvo vxlan access-if port-vlan xe3 3	Configure access-port xe3 and map vlan 3
(config-nvo-acc-if)#map vnid 200001	Map VNID 200001 to access-port xe3.
(config-nvo-acc-if)#exit	Exit NVO access-if mode.
(config)#commit	Commit the configurations

Validation

CE1, CE2, CE3, and CE4 have hosts configured with MAC addresses, IP addresses, and VLAN identifiers as shown below.

		VLAN	IP Address	MAC Address
VTEP1	CE-1	2	12.12.12.10	0000.0000.aaaa
VTEP1	CE-2	2	12.12.12.20	0000.0000.bbbb
VTEP2	CE-3	2	12.12.12.30	0000.0000.cccc
VTEP3	CE-4	2	12.12.12.40	0000.0000.dddd
VTEP1	CE-1	3	14.14.14.10	0000.058e.2181
VTEP1	CE-2	3	14.14.14.20	0000.058e.2182
VTEP2	CE-3	3	14.14.14.30	0000.058e.2183
VTEP3	CE-4	3	14.14.14.40	0000.058e.2184

Perform a tagged ping of VLAN 2 from CE1 to CE2,CE3 and CE4 and vice-versa. Also perform a tagged ping of VLAN 3 from CE1 to CE2, CE3 and CE4 and vice-versa.

VTEP Tunnel Status

```
VTEP1#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination      Status        Up/Down      Update
=====
1.1.1.1         3.3.3.3         Installed     01:25:20    01:25:20
1.1.1.1         2.2.2.2         Installed     01:35:19    01:35:19
Total number of entries are 2
```

```
VTEP2#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination      Status        Up/Down      Update
=====
2.2.2.2         1.1.1.1         Installed     01:35:42    01:35:42
2.2.2.2         3.3.3.3         Installed     01:25:43    01:25:43
Total number of entries are 2
```

```
VTEP3#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination      Status        Up/Down      Update
=====
3.3.3.3         2.2.2.2         Installed     01:25:35    01:25:35
3.3.3.3         1.1.1.1         Installed     01:25:35    01:25:35
Total number of entries are 2
```

VTEP ARP Tables

```
VTEP-1#show nvo vxlan arp-cache
```

VXLAN ARP-CACHE Information

=====

ARP Timeout : 300 sec Random-Jitter-Max : 640

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
200	13.13.13.10	0000.0b60.25f2	Dynamic Local	246	2
200	13.13.13.20	0000.0b60.25f3	Dynamic Remote	-----	
100	12.12.12.20	0000.0000.ccdc	Dynamic Remote	-----	
100	12.12.12.10	0000.0000.abab	Dynamic Local	246	2

Total number of entries are 4

VTEP-2#sh nvo vxlan arp-cache

VXLAN ARP-CACHE Information

=====

ARP Timeout : 300 sec Random-Jitter-Max : 640

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
200	13.13.13.10	0000.0b60.25f2	Dynamic Remote	-----	
200	13.13.13.20	0000.0b60.25f3	Dynamic Local	257	2
100	12.12.12.10	0000.0000.abab	Dynamic Remote	-----	
100	12.12.12.20	0000.0000.ccdc	Dynamic Local	257	2

Total number of entries are 4

VTEP3#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
100001	12.12.12.30	0000.0000.cccc	Dynamic Remote	----	
100001	12.12.12.10	0000.0000.aaaa	Dynamic Remote	----	
100001	12.12.12.20	0000.0000.bbbb	Dynamic Remote	----	
100001	12.12.12.40	0000.0000.dddd	Dynamic Local	----	
200001	14.14.14.20	0000.058e.2182	Dynamic Remote	----	
200001	14.14.14.10	0000.058e.2181	Dynamic Remote	----	
200001	14.14.14.40	0000.058e.2184	Dynamic Local	----	
200001	14.14.14.30	0000.058e.2183	Dynamic Remote	----	

Total number of entries are 8

VTEP3#

VTEP MAC Tables

VTEP1#show nvo vxlan mac-table

=====

=====

VXLAN MAC Entries

=====

=====

VNID	Interface	VlanId	Inner-VlanId	Mac-Addr	VTEP-Ip/ESI
	Type		Status		AccessPortDesc
1	xe1/1	1000	2000	0000.339a.9abb	33.33.33.0
	Dynamic Local		-----		-----
1	---	---	---	0000.339a.9397	34.34.34.0
	Dynamic Remote		-----		-----

Total number of entries are : 2

VTEP2#show nvo vxlan mac-table

VXLAN MAC Entries						
VNID	Interface	VlanId	Inner-VlanId	Mac-Addr	VTEP-Ip/ESI	
	Type		Status		AccessPortDesc	
1	---	---	---	0000.339a.9abb	33.33.33.0	
	Dynamic Remote		-----		-----	
1	xe1/1	1000	2000	0000.339a.9397	34.34.34.0	
	Dynamic Local		-----		-----	

Total number of entries are : 2

VTEP MAC-IP BGP EVPN Entries

VTEP-1#show bgp 12vpn evpn mac-ip

RD[1.1.1.1:1] VRF[vrf_evpn_100]:

ESI	Eth-Tag	Mac-Address	IP-Address	VNID	L3VNID
Nexthop	GW-Type				
0	100	0000:0000:abab	12.12.12.10	100	0
1.1.1.1	--				
0	200	0000:0b60:25f2	13.13.13.10	200	0
1.1.1.1	--				

RD[2.2.2.2:1]

ESI	Eth-Tag	Mac-Address	IP-Address	VNID	L3VNID	Nexthop
GW-Type						
0	100	0000:0000:cdcd	12.12.12.20	100		0
2.2.2.2	--					
0	200	0000:0b60:25f3	13.13.13.20	200		0
2.2.2.2	--					

VTEP-2#show bgp 12vpn evpn mac-ip

RD[1.1.1.1:1]		Eth-Tag	Mac-Address	IP-Address	VNID	L3VNID
ESI	Nexthop	GW-Type				
0	1.1.1.1	100	0000:0000:abab	12.12.12.10	100	0
0	1.1.1.1	200	0000:0b60:25f2	13.13.13.10	200	0
		--				

RD[2.2.2.2:1] VRF[vrf_evpn_100]:		Eth-Tag	Mac-Address	IP-Address	VNID	L3VNID
ESI	Nexthop	GW-Type				
0	2.2.2.2	100	0000:0000:cddc	12.12.12.20	100	0
0	2.2.2.2	100	0000:0b60:25f2	13.13.13.10	100	0
		--				

VTEP-3#show bgp 12vpn evpn mac-ip

RD[1.1.1.1:1] VRF[vrf_evpn_100]:		Eth-Tag	Mac-Address	IP-Address
ESI	VNID	L3VNID	Nexthop	GW-Type
0			100001	0000:0000:dddd --
100001	0	0	3.3.3.3	--
0			100001	0000:0000:dddd 12.12.12.40
100001	0	0	3.3.3.3	--
0			200001	0000:058e:2184 --
200001	0	0	3.3.3.3	--
0			200001	0000:058e:2184 14.14.14.40
200001	0	0	3.3.3.3	--

RD[1.1.1.1:1]		Eth-Tag	Mac-Address	IP-Address
ESI	VNID	L3VNID	Nexthop	GW-Type
0			100001	0000:0000:aaaa --
100001	0	0	1.1.1.1	--
0			100001	0000:0000:aaaa 12.12.12.10
100001	0	0	1.1.1.1	--
0			100001	0000:0000:bbbb --
100001	0	0	1.1.1.1	--
0			100001	0000:0000:bbbb 12.12.12.20
100001	0	0	1.1.1.1	--
0			100001	0000:0000:cccc --
100001	0	0	2.2.2.2	--
0			100001	0000:0000:cccc 12.12.12.30
100001	0	0	2.2.2.2	--
0			200001	0000:058e:2181 --
200001	0	0	1.1.1.1	--
0			200001	0000:058e:2181 14.14.14.10
200001	0	0	1.1.1.1	--
0			200001	0000:058e:2182 --
200001	0	0	1.1.1.1	--
0			200001	0000:058e:2182 14.14.14.20
200001	0	0	1.1.1.1	--
0			200001	0000:058e:2183 --
200001	0	0	2.2.2.2	--

0		200001	200001	0000:058e:2183	14.14.14.30
200001	0		2.2.2.2	--	

CHAPTER 2 VXLAN Multi-homing Configuration

This chapter contains the configurations for VXLAN Multi-homing feature.

Overview

VXLAN EVPN Multi-homing features enables to connect a CE/Host node to two VTEPs with all-active redundancy mode. EVPN Multi-homing helps in VTEP to host failure and VTEP failure. If one VTEP goes down, other will forward the entire traffic.

Below are Multi-homing concepts:

- Ethernet Segment: Set of links which connect host/CE to two active-active multi-homed VTEP (only two VTEPs are supported) which appears as LACP link for host.
- Ethernet Segment Identifier: Ethernet Segment Identifier (ESI) which is an 10 octet-value, which can be configured in two ways, system mac is configured as esi in case of Dynamic Lag and 10-octet ESI format config is used on physical interface ES.
- Ethernet Segment Route (ES route): When a multi-homed CE is configured as an VXLAN access-port, Ethernet segment route is sent. The main purpose of this route is to discover other VTEPs which share the ES and to perform DF election.
- Ethernet A-D route per ESI: This route is used for Fast Convergence and Split Horizon.
- Ethernet A-D route per EVI: This route is used for load sharing between DF and NON-DF by the remote VTEPs

Topology




Figure 2-7: VxLAN-Multihoming

Note: Enable VXLAN MUTIHOMING before executing any configurations.

VXLAN-EVPN MH Configuration

ESI can be configured in below two ways

Ethernet Segment through Dynamic Lag interface

#configure terminal	Enter configure mode.
(config)#interface po1	Enter interface mode for po1
(config-if)#switchport	Make it L2 interface
(config-if)#evpn multi-homed system-mac 8899.4400.6745	Configure system mac as ESI value for Lag (po1) interface

(config-if) #exit	Exit interface mode.
(config) #commit	Commit the candidate configuration to the running configuration

OR

Ethernet Segment through Physical interface

#configure terminal	Enter configure mode.
(config) #interface xe41	Enter interface mode for xe41
(config-if) #switchport	Make it L2 interface
(config-if) # evpn multi-homed esi 00:01:02:03:04:05:06:07:08	Configure 9-octet ESI value for xe41 interface (in static config, out of 10-octet ESI value, first octet is reserved)
(config-if) #exit	Exit interface mode.
(config) #commit	Commit the candidate configuration to the running configuration

VTEP1

(Multi-homed group1) – Part of both Multi-homed with po1 (MH1)

Generic Configuration

#configure terminal	Enter Configure mode.
(config) #evpn vxlan multihoming enable	Enable Multihoming, save configs and reboot the board for multihoming to be effective
(config) #qos enable	Enabling QoS
(config) #commit	Commit the candidate configuration to the running configuration

Interface and Loopback Configuration

(config) #interface po1	Enter Interface mode for po1 (MH1)
(config-if) #switchport	Make it L2 interface
(config-if) # evpn multi-homed system-mac 0000.0000.1111	Configure system MAC as ESI value for LAG (po1) interface
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe9	Enter Interface mode for xe9
(config-if) #channel-group 1 mode active	Make it member port of po1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe10	Enter Interface mode for xe10
(config-if) #channel-group 1 mode active	Make it member port of po1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 1.1.1.1/32 secondary	Configure loopback ip address as 1.1.1.1 for VTEP1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe8	Enter Interface mode for xe8
(config-if) #ip address 10.10.10.1/24	Configure IP address as 10.10.10.1 on network side of Spine1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe31	Enter Interface mode for xe31
(config-if) #ip address 20.20.20.1/24	Configure IP address as 20.20.20.1 on network side of Spine2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

OSPF Configuration

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo ip address)
(config-router) #network 1.1.1.1/32 area 0.0.0.0	Add 1.1.1.1 (lo IP address) network into area 0
(config-router) #network 10.10.10.0/24 area 0.0.0.0	Add 10.10.10.0 (Spine1) network into area 0
(config-router) #network 20.20.20.0/24 area 0.0.0.0	Add 20.20.20.0 (Spine2) network into area 0

(config-router) #bfd all-interfaces	Enabling BFD on all OSPF interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

BGP Configuration

(config) #router bgp 500	Enter into Router BGP mode
(config-router) #bgp router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo IP address)
(config-router) #neighbor 2.2.2.2 remote-as 500	Specify a VTEP2 loopback IP address and remote-as defined
(config-router) #neighbor 2.2.2.2 update-source lo	Configure update as loopback for VTEP2
(config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2
(config-router) #neighbor 3.3.3.3 remote-as 500	Specify a VTEP3 loopback IP address and remote-as defined
(config-router) #neighbor 3.3.3.3 update-source lo	Configure update as loopback for VTEP3
(config-router) #neighbor 3.3.3.3 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP3
(config-router) #address-family ipv4 unicast	Enter into ipv4 unicast address family mode
(config-router-af) #network 1.1.1.1/32	Advertise loopback network into BGP for VTEP ID reachability
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2 (VTEP2) into ipv4 unicast address family mode
(config-router-af) #neighbor 3.3.3.3 activate	Activate 3.3.3.3 (VTEP2) into ipv4 unicast address family mode
(config-router-af) #exit-address-family	Exit from ipv4 unicast address family mode
(config-router) #address-family l2vpn evpn	Enter into L2VPN EVPN address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2 (VTEP2) into L2VPN evpn address family mode
(config-router-af) #neighbor 3.3.3.3 activate	Activate 3.3.3.3 (VTEP3) into L2VPN evpn address family mode
(config-router-af) #exit-address-family	Exit from L2VPN address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Commit the candidate configuration to the running configuration

VRF Configuration

(config) #mac vrf VRF1	Create mac routing/forwarding instance with VRF1 name and enter into VRF mode
(config-vrf) #rd 1.1.1.1:11	Assign RD value
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for VRF1
(config-vrf) #exit	Exit from VRF mode
(config) #mac vrf VRF2	Create MAC routing/forwarding instance with VRF1 name and enter into VRF mode
(config-vrf) #rd 1.1.1.1:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export
(config-vrf) #exit	Exit from VRF mode
(config) #commit	Commit the candidate configuration to the running configuration

VxLAN Configuration

(config) #nvo vxlan enable	Enable VxLAN
(config) #evpn esi hold-time 90	Configure ESI hold time to allow tunnel to come up at the time of VxLAN initialization before making the ESI up
(config) #nvo vxlan vtep-ip-global 1.1.1.1	Configure Source VTEP-IP-global configuration
(config) #nvo vxlan id 10 ingress-replication inner-vid-disabled	Configure VxLAN Network identifier with/without inner-VID-disabled configure and enter into VxLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) #vni-name VNI-RED	Configure VNI-name as VNI-RED
(config-nvo) #exit	Exit from VxLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 20 ingress-replication inner-vid-disabled	Configure VxLAN Network identifier with/without inner-VID-disabled configure and enter into VxLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) #vni-name VNI-BLUE	Configure VNI-name as VNI-BLUE
(config-nvo) #exit	Exit from VxLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan access-if port-vlan p01 1001	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vni-name VNI-RED	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan p01 1002	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vni-name VNI-RED	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan p01 3001	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vni-name VNI-BLUE	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode
(config) #commit	Commit the candidate configuration to the running configuration
(config) #exit	Exit from configuration mode

VTEP2

(Multi-homed group1) – Part of both Multi-homed with p01. And it has xe32 as single home access-if port (SH2)

Generic Configuration

#configure terminal	Enter Configure mode.
(config) #evpn vxlan multihoming enable	Enable Multihoming, save configs and reboot the board for multihoming to be effective
(config) #qos enable	Enabling QoS
(config) #commit	Commit the candidate configuration to the running configuration

Interface and Loopback Configuration

(config) #interface po1	Enter Interface mode for po1 (MH1)
(config-if) #switchport	Make it L2 interface
(config-if) # evpn multi-homed system-mac 0000.0000.1111	Configure system MAC as ESI value for LAG (po1) interface
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe3	Enter Interface mode for xe3
(config-if) #channel-group 1 mode active	Make it member port of po1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe4	Enter Interface mode for xe4
(config-if) #channel-group 1 mode active	Make it member port of po1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe32	Enter Interface mode for xe32 (SH2)
(config-if) #switchport	Make it L2 interface
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 2.2.2.2/32 secondary	Configure loopback IP address as 2.2.2.2 for VTEP2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe21	Enter Interface mode for xe21
(config-if) #ip address 30.30.30.1/24	Configure IP address as 30.30.30.1 on network side of Spine1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce53	Enter Interface mode for ce53
(config-if) #ip address 40.40.40.1/24	Configure IP address as 40.40.40.1 on network side of Spine2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

OSPF Configuration

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 2.2.2.2	Configure router-id as 2.2.2.2 (lo IP address)
(config-router) #network 2.2.2.2/32 area 0.0.0.0	Add 2.2.2.2 (lo IP address) network into area 0
(config-router) #network 30.30.30.0/24 area 0.0.0.0	Add 30.30.30.0 (Spine1) network into area 0
(config-router) #network 40.40.40.0/24 area 0.0.0.0	Add 40.40.40.0 (Spine2) network into area 0

(config-router) #bfd all-interfaces	Enabling BFD on all OSPF interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

BGP Configuration

(config) #router bgp 500	Enter into Router BGP mode
(config-router) #bgp router-id 2.2.2.2	Configure router-id as 2.2.2.2 (lo IP address)
(config-router) #neighbor 1.1.1.1 remote-as 500	Specify a VTEP1 loopback IP address and remote-as defined
(config-router) #neighbor 1.1.1.1 update-source lo	Configure update as loopback for VTEP1
(config-router) #neighbor 1.1.1.1 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP1
(config-router) #neighbor 3.3.3.3 remote-as 500	Specify a VTEP3 loopback IP address and remote-as defined
(config-router) #neighbor 3.3.3.3 update-source lo	Configure update as loopback for VTEP3
(config-router) #neighbor 3.3.3.3 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP3
(config-router) #address-family ipv4 unicast	Enter into ipv4 unicast address family mode
(config-router-af) #network 2.2.2.2/32	Advertise loopback network into BGP for VTEP ID reachability
(config-router-af) #neighbor 1.1.1.1 activate	Activate 1.1.1.1 (VTEP2) into ipv4 unicast address family mode
(config-router-af) #neighbor 3.3.3.3 activate	Activate 3.3.3.3 (VTEP2) into ipv4 unicast address family mode
(config-router-af) #exit-address-family	Exit from ipv4 unicast address family mode
(config-router) #address-family l2vpn evpn	Enter into L2VPN EVPN address family mode
(config-router-af) #neighbor 1.1.1.1 activate	Activate 1.1.1.1(VTEP1) into L2VPN evpn address family mode
(config-router-af) #neighbor 3.3.3.3 activate	Activate 3.3.3.3(VTEP3) into L2VPN evpn address family mode
(config-router-af) #exit-address-family	Exit from L2VPN address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Commit the candidate configuration to the running configuration

VRF Configuration

(config) # mac vrf VRF1	Create mac routing/forwarding instance with VRF1 name and enter into VRF mode
(config-vrf) #rd 2.2.2.2:11	Assign RD value
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for VRF1
(config-vrf) #exit	Exit from VRF mode
(config) #mac vrf VRF2	Create MAC routing/forwarding instance with VRF1 name and enter into VRF mode
(config-vrf) #rd 2.2.2.2:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export
(config-vrf) #exit	Exit from VRF mode
(config) #commit	Commit the candidate configuration to the running configuration

VxLAN Configuration

(config) #nvo vxlan enable	Enable VxLAN
(config) #evpn esi hold-time 90	Configure ESI hold time to allow tunnel to come up at the time of VxLAN initialization before making the ESI up
(config) #nvo vxlan vtep-ip-global 2.2.2.2	Configure Source VTEP-IP-global configuration
(config) #nvo vxlan id 10 ingress-replication inner-vid-disabled	Configure VxLAN Network identifier with/without inner-VID-disabled configure and enter into VxLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) #vni-name VNI-RED	Configure VNI-name as VNI-RED
(config-nvo) #exit	Exit from VxLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 20 ingress-replication inner-vid-disabled	Configure VxLAN Network identifier with/without inner-VID-disabled configure and enter into VxLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) #vni-name VNI-BLUE	Configure VNI-name as VNI-BLUE
(config-nvo) #exit	Exit from VxLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan access-if port-vlan pol 1001	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vni-name VNI-RED	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan pol 1002	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vni-name VNI-RED	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan pol 3001	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) - Multihomed access port

(config-nvo-acc-if) #map vni-name VNI-BLUE	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port xe32	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vni-name VNI-RED	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode
(config) #commit	Commit the candidate configuration to the running configuration
(config) #exit	Exit from configuration mode

VTEP3

It has xe48 as Single home access-if port (SH2)

Generic Configuration

#configure terminal	Enter Configure mode.
(config) #evpn vxlan multihoming enable	Enable Multihoming, save configs and reboot the board for multihoming to be effective
(config) #qos enable	Enabling QoS
(config) #commit	Commit the candidate configuration to the running configuration

Interface and loopback configuration

(config) #interface xe48	Enter Interface mode for xe48 (SH3)
(config-if) #switchport	Make it L2 interface
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 3.3.3.3/32 secondary	Configure loopback IP address as 3.3.3.3 for VTEP3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe18	Enter Interface mode for xe18
(config-if) #ip address 50.50.50.1/24	Configure IP address as 50.50.50.1 on network side of Spine1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe19	Enter Interface mode for xe19
(config-if) #ip address 60.60.60.1/24	Configure IP address as 60.60.60.1 on network side of Spine2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

OSPF Configuration

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 3.3.3.3	Configure router-ID as 3.3.3.3 (lo IP address)
(config-router) #network 3.3.3.3/32 area 0.0.0.0	Add 3.3.3.3 (lo IP address) network into area 0
(config-router) #network 50.50.50.0/24 area 0.0.0.0	Add 50.50.50.0 (Spine1) network into area 0
(config-router) #network 60.60.60.0/24 area 0.0.0.0	Add 60.60.60.0 (Spine2) network into area 0
(config-router) #bfd all-interfaces	Enabling BFD on all OSPF interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

BGP Configuration

(config) #router bgp 500	Enter into Router BGP mode
(config-router) #bgp router-id 3.3.3.3	Configure router-ID as 3.3.3.3 (lo ip address)
(config-router) #neighbor 1.1.1.1 remote-as 500	Specify a VTEP1 loopback IP address and remote-as defined
(config-router) #neighbor 1.1.1.1 update-source lo	Configure update as loopback for VTEP1
(config-router) #neighbor 1.1.1.1 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP1
(config-router) #neighbor 2.2.2.2 remote-as 500	Specify a VTEP2 loopback IP address and remote-as defined
(config-router) #neighbor 2.2.2.2 update-source lo	Configure update as loopback for VTEP2
(config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP3
(config-router) #address-family ipv4 unicast	Enter into ipv4 unicast address family mode
(config-router-af) #network 3.3.3.3/32	Advertise loopback network into BGP for VTEP ID reachability
(config-router-af) #neighbor 1.1.1.1 activate	Activate 1.1.1.1 (VTEP2) into ipv4 unicast address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2 (VTEP2) into ipv4 unicast address family mode
(config-router-af) #exit-address-family	Exit from ipv4 unicast address family mode
(config-router) #address-family l2vpn evpn	Enter into L2VPN EVPN address family mode
(config-router-af) #neighbor 1.1.1.1 activate	Activate 1.1.1.1 (VTEP1) into L2VPN evpn address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2 (VTEP2) into L2VPN evpn address family mode
(config-router-af) #exit-address-family	Exit from L2VPN address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Commit the candidate configuration to the running configuration

VRF Configuration

(config) # mac vrf VRF1	Create MAC routing/forwarding instance with VRF1 name and enter into VRF mode
(config-vrf) #rd 3.3.3.3:11	Assign RD value
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for VRF1
(config-vrf) #exit	Exit from VRF mode
(config) #mac vrf VRF2	Create MAC routing/forwarding instance with VRF2 name and enter into VRF mode
(config-vrf) #rd 3.3.3.3:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export
(config-vrf) #exit	Exit from VRF
(config) #commit	Commit the candidate configuration to the running configuration

VxLAN Configuration

(config) #nvo vxlan enable	Enable VxLAN
(config) #nvo vxlan vtep-ip-global 3.3.3.3	Configure Source VTEP-IP-global configuration
(config) #nvo vxlan id 10 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-VID-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) #vni-name VNI-RED	Configure VNI-name as VNI-RED
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 20 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-VID-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) #vni-name VNI-BLUE	Configure VNI-name as VNI-BLUE
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan access-if port-vlan xe48 1001	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vni-name VNI-RED	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan xe48 1002	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vni-name VNI-RED	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan xe48 3001	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vni-name VNI-BLUE	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #commit	Commit the candidate configuration to the running configuration
(config) #exit	Exit from configuration mode

Switch (CE2)

Multihomed to 2-VTEPs (VTEP1 and VTEP2)

#configure terminal	Enter Configure mode.
(config) #bridge 1 protocol ieee vlan-bridge	Configure IEEE VLAN bridge
(config) #vlan 1001-1002 bridge 1 state enable	Configure VLANs from 1001-1002 and associate with bridge 1
(config) #vlan 3001 bridge 1 state enable	Configure VLANs from 3001 and associate with bridge 1
(config) #interface xe22	Enter Interface mode for xe22
(config-if) #switchport	Make xe22 as L2 port by configuring switchport

(config-if)#bridge-group 1	Associate xe22 to bridge 1
(config-if)#switchport mode hybrid	Configure xe22 as hybrid port
(config-if)#switchport hybrid allowed vlan add 1001-1002,3001 egress-tagged enable	Allow 1001-1002 and 3001 configured VLANs on xe22
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface po1	Enter Interface mode for po1
(config-if)#switchport	Make po1 as L2 port by configuring switchport
(config-if)#bridge-group 1	Associate po1 to bridge 1
(config-if)#switchport mode hybrid	Configure po1 as hybrid port
(config-if)#switchport hybrid allowed vlan add 1001-1002,3001 egress-tagged enable	Allow 1001-1002 and 3001 configured VLANs on po1
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface xe3	Enter Interface mode for xe3
(config-if)#channel-group 1 mode active	Make it member port of po1
(config)#interface xe4	Enter Interface mode for xe4
(config-if)#channel-group 1 mode active	Make it member port of po1
(config)#exit	Exit from configuration mode
(config)#interface xe9	Enter Interface mode for xe9
(config-if)#channel-group 1 mode active	Make it member port of po1
(config)#interface xe10	Enter Interface mode for xe10
(config-if)#channel-group 1 mode active	Make it member port of po1
(config)#exit	Exit from configuration mode
(config)#commit	Commit the candidate configuration to the running configuration
(config)#exit	Exit from configuration mode

Spine 1

Spine node where all VTEPs are connected

Generic Configuration

#configure terminal	Enter Configure mode.
(config) #qos enable	Enabling QoS
(config) #commit	Commit the candidate configuration to the running configuration

Interface and Loopback Configuration

#configure terminal	Enter Configure mode.
(config) #qos enable	Enabling QoS
(config) #interface lo	Enter Interface mode for lo
(config-if)#ip address 11.11.11.11/32 secondary	Configure loopback IP address as 11.11.11.11 for Spine1
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) #interface xe8	Enter Interface mode for xe8
(config-if)#ip address 10.10.10.2/24	Configure IP address as 10.10.10.2 on network side of VTEP1
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) #interface xe1	Enter Interface mode for xe1
(config-if)#ip address 30.30.30.2/24	Configure IP address as 30.30.30.2 on network side of VTEP2
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) #interface xe18	Enter Interface mode for xe18
(config-if)#ip address 50.50.50.2/24	Configure IP address as 50.50.50.2 on network side of VTEP3
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

OSPF configuration

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 11.11.11.11	Configure router-ID as 11.11.11.11 (lo IP address)
(config-router) #network 11.11.11.11/32 area 0.0.0.0	Add 11.11.11.11 (lo IP address) network into area 0
(config-router) #network 10.10.10.0/24 area 0.0.0.0	Add 10.10.10.0 (VTEP1) network into area 0
(config-router) #network 30.30.30.0/24 area 0.0.0.0	Add 30.30.30.0 (VTEP2) network into area 0
(config-router) #network 50.50.50.0/24 area 0.0.0.0	Add 50.50.50.0 (VTEP3) network into area 0
(config-router) #bfd all-interfaces	Enabling BFD on all OSPF interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

Spine 2

Spine node where all VTEPs are connected

Generic configuration

#configure terminal	Enter Configure mode.
(config) #qos enable	Enabling QoS
(config) #commit	Commit the candidate configuration to the running configuration

Interface and loopback configuration

(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 22.22.22.22/32 secondary	Configure loopback IP address as 22.22.22.22 for Spine2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe5	Enter Interface mode for xe5
(config-if) #ip address 20.20.20.2/24	Configure IP address as 20.20.20.2 on network side of VTEP1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce0	Enter Interface mode for ce0
(config-if) #ip address 40.40.40.2/24	Configure IP address as 40.40.40.2 on network side of VTEP2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe19	Enter Interface mode for xe19
(config-if) #ip address 60.60.60.2/24	Configure IP address as 60.60.60.2 on network side of VTEP3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

OSPF configuration

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 22.22.22.22	Configure router-id as 11.11.11.11 (lo IP address)
(config-router) #network 22.22.22.22/32 area 0.0.0.0	Add 22.22.22.22 (lo IP address) network into area 0
(config-router) #network 20.20.20.0/24 area 0.0.0.0	Add 20.20.20.0 (VTEP1) network into area 0
(config-router) #network 40.40.40.0/24 area 0.0.0.0	Add 40.40.40.0 (VTEP2) network into area 0
(config-router) #network 60.60.60.0/24 area 0.0.0.0	Add 60.60.60.0 (VTEP3) network into area 0
(config-router) #bfd all-interfaces	Enabling BFD on all OSPF interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

Validation

VTEP1

```
VTEP1#show nvo vxlan
VXLAN Information
=====
Codes: NW - Network Port
       AC - Access Port
       (u) - Untagged

VNID      VNI-Name      VNI-Type Type Interface ESI           VLAN DF-Status
Src-Addr    Dst-Addr

-----
10        VNI-RED       L2          NW   ----  -----
1.1.1.1    3.3.3.3
10        VNI-RED       L2          NW   ----  -----
1.1.1.1    2.2.2.2
10        VNI-RED       --          AC   po1   00:00:00:00:00:11:11:00:00:00 1001 NON-DF
----      -----
10        VNI-RED       --          AC   po1   00:00:00:00:00:11:11:00:00:00 1002 DF
----      -----
20        VNI-BLUE      L2          NW   ----  -----
1.1.1.1    3.3.3.3
20        VNI-BLUE      L2          NW   ----  -----
1.1.1.1    2.2.2.2
20        VNI-BLUE      --          AC   po1   00:00:00:00:00:11:11:00:00:00 3001 NON-DF
----      -----
```

Total number of entries are 7

```
VTEP1#show nvo vxlan access-if brief
```

Interface	Inner				Admin status	Link status
	Vlan	vlan	Ifindex	Vnid		
po1	1002	---	500001	10	up	up
po1	1001	---	500000	10	up	up
po1	3001	---	500002	20	up	up

Total number of entries are 3

```
VTEP1#show bgp l2vpn evpn summary
BGP router identifier 1.1.1.1, local AS number 500
BGP table version is 6
1 BGP AS-PATH entries
0 BGP community entries
```

Neighbor PfxRcd	AD	MACIP	V MCAST	AS	MsgRcv ESI	MsgSen PREFIX-ROUTE	TblVer	InQ	OutQ	Up/Down	State/
2.2.2.2 6	3	0	2	4	500 1	161 0	163	5	0	0	01:05:15
3.3.3.3 2	0	0	2	4	500 0	157 0	161	5	0	0	01:05:07

Total number of neighbors 2

Total number of Established sessions 2

VTEP1#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
1.1.1.1	3.3.3.3	Installed	00:31:11	00:31:11
1.1.1.1	2.2.2.2	Installed	01:05:25	00:31:11

Total number of entries are 2

VTEP1#show bgp 12vpn evpn multihoming es-route

RD[1.1.1.1:1] VRF[evpn-gvrf-1]:

ESI	PE IP-Address	Nexthop IP	Encap
00:00:00:00:00:11:11:00:00:00	1.1.1.1	1.1.1.1	VXLAN
00:00:00:00:00:11:11:00:00:00	2.2.2.2	2.2.2.2	VXLAN

RD[2.2.2.2:1]

ESI	PE IP-Address	Nexthop IP	Encap
00:00:00:00:00:11:11:00:00:00	2.2.2.2	2.2.2.2	VXLAN

VTEP1#show bgp 12vpn evpn multihoming ethernet-ad-per-es

RD[1.1.1.1:1] VRF[evpn-gvrf-1]:

ESI	Eth-Tag	VNID/LABEL	Nexthop IP	Encap
00:00:00:00:00:11:11:00:00:00	4294967295	0	1.1.1.1	VXLAN

RD[1.1.1.1:11] VRF[VRF1]:

ESI	Eth-Tag	VNID/LABEL	Nexthop IP	Encap
00:00:00:00:00:11:11:00:00:00	4294967295	0	2.2.2.2	VXLAN

RD[1.1.1.1:21] VRF[VRF2]:

ESI	Eth-Tag	VNID/LABEL	Nexthop IP	Encap
00:00:00:00:00:11:11:00:00:00	4294967295	0	2.2.2.2	VXLAN

RD[2.2.2.2:1]

ESI	Eth-Tag	VNID/LABEL	Nexthop IP	Encap
00:00:00:00:00:11:11:00:00:00	4294967295	0	2.2.2.2	VXLAN

VTEP1#show bgp 12vpn evpn multihoming ethernet-ad-per-evi

RD[1.1.1.1:11] VRF[VRF1]:

ESI	Eth-Tag	VNIID/LABEL	Nexthop IP	Encap
00:00:00:00:00:11:11:00:00:00	10	10	2.2.2.2	VXLAN
00:00:00:00:00:11:11:00:00:00	10	10	1.1.1.1	VXLAN

RD[1.1.1.1:21] VRF[VRF2]:

ESI	Eth-Tag	VNIID/LABEL	Nexthop IP	Encap
00:00:00:00:00:11:11:00:00:00	20	20	2.2.2.2	VXLAN
00:00:00:00:00:11:11:00:00:00	20	20	1.1.1.1	VXLAN

RD[2.2.2.2:11]

ESI	Eth-Tag	VNIID/LABEL	Nexthop IP	Encap
00:00:00:00:00:11:11:00:00:00	10	10	2.2.2.2	VXLAN

RD[2.2.2.2:21]

ESI	Eth-Tag	VNIID/LABEL	Nexthop IP	Encap
00:00:00:00:00:11:11:00:00:00	20	20	2.2.2.2	VXLAN

VTEP1#show bgp l2vpn evpn

BGP table version is 6, local router ID is 1.1.1.1
 Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
 l - labeled, S Stale
 Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNIID]:[relevent route informantion]

1 - Ethernet Auto-discovery Route
 2 - MAC/IP Route
 3 - Inclusive Multicast Route
 4 - Ethernet Segment Route
 5 - Prefix Route

Network	Next Hop	Metric	LocPrf	Weight	Path	Peer
---------	----------	--------	--------	--------	------	------

RD[1.1.1.1:1] VRF[evpn-gvrf-1]:

*> [1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]	1.1.1.1	0	100	32768	i	-----
---	VXLAN					
*> [4]:[00:00:00:00:00:11:11:00:00:00]:[32,1.1.1.1]	1.1.1.1	0	100	32768	i	-----
---	VXLAN					
* i [4]:[00:00:00:00:00:11:11:00:00:00]:[32,2.2.2.2]	2.2.2.2	0	100	0	i	2.2.2.2
VXLAN						

RD[1.1.1.1:11] VRF[VRF1]:

* i [1]:[00:00:00:00:00:11:11:00:00:00]:[10]:[10]	2.2.2.2	0	100	0	i	2.2.2.2
---	---------	---	-----	---	---	---------

VXLAN

*>	1.1.1.1	0	100	32768	i	-----
---	VXLAN					
* i [1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]						

```

          2.2.2.2          0      100          0      i  2.2.2.2
VXLAN
*> [3]:[10]:[32,1.1.1.1]
          1.1.1.1          0      100      32768      i  -----
---      VXLAN
* i  [3]:[10]:[32,2.2.2.2]
          2.2.2.2          0      100          0      i  2.2.2.2
VXLAN
* i  [3]:[10]:[32,3.3.3.3]
          3.3.3.3          0      100          0      i  3.3.3.3
VXLAN

RD[1.1.1.1:21] VRF[VRF2]:
* i  [1]:[00:00:00:00:00:11:11:00:00:00]:[20]:[20]
          2.2.2.2          0      100          0      i  2.2.2.2
VXLAN
*>          1.1.1.1          0      100      32768      i  -----
---      VXLAN
* i  [1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]
          2.2.2.2          0      100          0      i  2.2.2.2
VXLAN
*> [3]:[20]:[32,1.1.1.1]
          1.1.1.1          0      100      32768      i  -----
---      VXLAN
* i  [3]:[20]:[32,2.2.2.2]
          2.2.2.2          0      100          0      i  2.2.2.2
VXLAN
* i  [3]:[20]:[32,3.3.3.3]
          3.3.3.3          0      100          0      i  3.3.3.3
VXLAN

RD[2.2.2.2:1]
*>i  [1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]
          2.2.2.2          0      100          0      i  2.2.2.2
VXLAN
*>i  [4]:[00:00:00:00:00:11:11:00:00:00]:[32,2.2.2.2]
          2.2.2.2          0      100          0      i  2.2.2.2
VXLAN

RD[2.2.2.2:11]
*>i  [1]:[00:00:00:00:00:11:11:00:00:00]:[10]:[10]
          2.2.2.2          0      100          0      i  2.2.2.2
VXLAN
*>i  [3]:[10]:[32,2.2.2.2]
          2.2.2.2          0      100          0      i  2.2.2.2
VXLAN

RD[2.2.2.2:21]
*>i  [1]:[00:00:00:00:00:11:11:00:00:00]:[20]:[20]
          2.2.2.2          0      100          0      i  2.2.2.2
VXLAN
*>i  [3]:[20]:[32,2.2.2.2]
          2.2.2.2          0      100          0      i  2.2.2.2
VXLAN

```

```
RD[3.3.3.3:11]
*>i [3]:[10]:[32,3.3.3.3]
          3.3.3.3           0       100           0     i 3.3.3.3
VXLAN
```

```
RD[3.3.3.3:21]
*>i [3]:[20]:[32,3.3.3.3]
          3.3.3.3           0       100           0     i 3.3.3.3
VXLAN
```

Total number of prefixes 21

VTEP2

```
VTEP2#show nvo vxlan
```

VXLAN Information

=====

Codes: NW - Network Port
 AC - Access Port
 (u) - Untagged

VNID Src-Addr	VNI-Name Dst-Addr	VNI-Type	Type	Interface	ESI	VLAN	DF-Status
10 2.2.2.2	VNI-RED 1.1.1.1	L2	NW	-----	-----	-----	-----
10 2.2.2.2	VNI-RED 3.3.3.3	L2	NW	-----	-----	-----	-----
10 ----	VNI-RED ----	--	AC	xe32	--- Single Homed Port ---	-----	-----
10 ----	VNI-RED ----	--	AC	po1	00:00:00:00:00:11:11:00:00:00	1001	DF
10 ----	VNI-RED ----	--	AC	po1	00:00:00:00:00:11:11:00:00:00	1002	NON-DF
20 2.2.2.2	VNI-BLUE 1.1.1.1	L2	NW	-----	-----	-----	-----
20 2.2.2.2	VNI-BLUE 3.3.3.3	L2	NW	-----	-----	-----	-----
20 ----	VNI-BLUE ----	--	AC	po1	00:00:00:00:00:11:11:00:00:00	3001	DF

Total number of entries are 8

```
VTEP2#show nvo vxlan access-if
% Incomplete command.
```

```
VTEP2#show nvo vxlan access-if brief
```

Interface	Inner Vlan	vlan	Ifindex	Vnid	Admin status	Link status
-----	-----	-----	-----	-----	-----	-----

xe32	---	---	500004	10	up	up
pol	1002	---	500001	10	up	up
pol	1001	---	500000	10	up	up
pol	3001	---	500002	20	up	up

Total number of entries are 4

```
VTEP2#show bgp l2vpn evpn summary
BGP router identifier 2.2.2.2, local AS number 500
BGP table version is 4
1 BGP AS-PATH entries
0 BGP community entries
```

Neighbor PfxRcd	AD	MACIP	V MCAST	AS MCAST	MsgRcv ESI	MsgSen PREFIX-ROUTE	TblVer	InQ	OutQ	Up/Down	State/
1.1.1.1 6 3	0	2	4	500 1	172 0	171	4	0	0	01:09:28	
3.3.3.3 2 0	0	2	4	500 0	165 0	173	4	0	0	01:09:29	

Total number of neighbors 2

Total number of Established sessions 2

```
VTEP2#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination        Status          Up/Down          Update
=====
2.2.2.2          1.1.1.1        Installed       01:09:38        00:35:24
2.2.2.2          3.3.3.3        Installed       01:09:39        01:09:39
```

Total number of entries are 2

```
VTEP2#show bgp l2vpn evpn multihoming es-route
```

```
RD[1.1.1.1:1]
ESI                               PE IP-Address      Nexthop IP      Encap
00:00:00:00:00:11:11:00:00:00  1.1.1.1           1.1.1.1        VXLAN
```

```
RD[2.2.2.2:1] VRF[evpn-gvrf-1]:
ESI                               PE IP-Address      Nexthop IP      Encap
00:00:00:00:00:11:11:00:00:00  1.1.1.1           1.1.1.1        VXLAN
00:00:00:00:00:11:11:00:00:00  2.2.2.2           2.2.2.2        VXLAN
```

```
VTEP2#show bgp l2vpn evpn multihoming ethernet-ad-per-es
```

```
RD[1.1.1.1:1]
ESI                               Eth-Tag        VNID/LABEL      Nexthop IP      Encap
00:00:00:00:00:11:11:00:00:00  4294967295  0              1.1.1.1        VXLAN
```

```
RD[2.2.2.2:1] VRF[evpn-gvrf-1]:
ESI                               Eth-Tag        VNID/LABEL      Nexthop IP      Encap
```

```

00:00:00:00:00:11:11:00:00:00 4294967295 0           2.2.2.2       VXLAN
RD[2.2.2.2:11] VRF[VRF1]:
ESI                           Eth-Tag      VNID/LABEL   Nexthop IP    Encap
00:00:00:00:00:11:11:00:00:00 4294967295 0           1.1.1.1       VXLAN

RD[2.2.2.2:21] VRF[VRF2]:
ESI                           Eth-Tag      VNID/LABEL   Nexthop IP    Encap
00:00:00:00:00:11:11:00:00:00 4294967295 0           1.1.1.1       VXLAN

VTEP2#show bgp 12vpn evpn multihoming ethernet-ad-per-evi

RD[1.1.1.1:11]
ESI                           Eth-Tag      VNID/LABEL   Nexthop IP    Encap
00:00:00:00:00:11:11:00:00:00 10          10          1.1.1.1       VXLAN

RD[1.1.1.1:21]
ESI                           Eth-Tag      VNID/LABEL   Nexthop IP    Encap
00:00:00:00:00:11:11:00:00:00 20          20          1.1.1.1       VXLAN

RD[2.2.2.2:11] VRF[VRF1]:
ESI                           Eth-Tag      VNID/LABEL   Nexthop IP    Encap
00:00:00:00:00:11:11:00:00:00 10          10          2.2.2.2       VXLAN
00:00:00:00:00:11:11:00:00:00 10          10          1.1.1.1       VXLAN

RD[2.2.2.2:21] VRF[VRF2]:
ESI                           Eth-Tag      VNID/LABEL   Nexthop IP    Encap
00:00:00:00:00:11:11:00:00:00 20          20          2.2.2.2       VXLAN
00:00:00:00:00:11:11:00:00:00 20          20          1.1.1.1       VXLAN

VTEP2# show bgp 12vpn evpn
BGP table version is 4, local router ID is 2.2.2.2
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
              l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route
4 - Ethernet Segment Route
5 - Prefix Route

      Network          Next Hop          Metric     LocPrf      Weight     Path  Peer
Encap

RD[1.1.1.1:1]
*>i  [1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]
                  1.1.1.1          0          100          0          i  1.1.1.1
VXLAN
*>i  [4]:[00:00:00:00:00:11:11:00:00:00]:[32,1.1.1.1]

```

VXLAN	1.1.1.1	0	100	0	i 1.1.1.1
RD[1.1.1.1:11]					
*>i [1]:[00:00:00:00:00:11:11:00:00:00]:[10]:[10]	1.1.1.1	0	100	0	i 1.1.1.1
VXLAN					
*>i [3]:[10]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1
VXLAN					
RD[1.1.1.1:21]					
*>i [1]:[00:00:00:00:00:11:11:00:00:00]:[20]:[20]	1.1.1.1	0	100	0	i 1.1.1.1
VXLAN					
*>i [3]:[20]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1
VXLAN					
RD[2.2.2.2:1] VRF[evpn-gvrf-1]:					
*> [1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]	2.2.2.2	0	100	32768	i -----
---	VXLAN				
* i [4]:[00:00:00:00:00:11:11:00:00:00]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1
VXLAN					
*> [4]:[00:00:00:00:00:11:11:00:00:00]:[32,2.2.2.2]	2.2.2.2	0	100	32768	i -----
---	VXLAN				
RD[2.2.2.2:11] VRF[VRF1]:					
*> [1]:[00:00:00:00:00:11:11:00:00:00]:[10]:[10]	2.2.2.2	0	100	32768	i -----
---	VXLAN				
* i 1.1.1.1	1.1.1.1	0	100	0	i 1.1.1.1
VXLAN					
* i [1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]	1.1.1.1	0	100	0	i 1.1.1.1
VXLAN					
* i [3]:[10]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1
VXLAN					
*> [3]:[10]:[32,2.2.2.2]	2.2.2.2	0	100	32768	i -----
---	VXLAN				
* i [3]:[10]:[32,3.3.3.3]	3.3.3.3	0	100	0	i 3.3.3.3
VXLAN					
RD[2.2.2.2:21] VRF[VRF2]:					
*> [1]:[00:00:00:00:00:11:11:00:00:00]:[20]:[20]	2.2.2.2	0	100	32768	i -----
---	VXLAN				

```

* i 1.1.1.1 0 100 0 i 1.1.1.1
VXLAN
* i [1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]
          1.1.1.1 0 100 0 i 1.1.1.1
VXLAN
* i [3]:[20]:[32,1.1.1.1]
          1.1.1.1 0 100 0 i 1.1.1.1
VXLAN
*> [3]:[20]:[32,2.2.2.2]
          2.2.2.2 0 100 32768 i -----
--- VXLAN
* i [3]:[20]:[32,3.3.3.3]
          3.3.3.3 0 100 0 i 3.3.3.3
VXLAN

RD[3.3.3.3:11]
*>i [3]:[10]:[32,3.3.3.3]
          3.3.3.3 0 100 0 i 3.3.3.3
VXLAN

RD[3.3.3.3:21]
*>i [3]:[20]:[32,3.3.3.3]
          3.3.3.3 0 100 0 i 3.3.3.3
VXLAN

```

Total number of prefixes 21

VTEP3

VNID Src-Addr	VNI-Name Dst-Addr	VNI-Type Type	Interface	ESI	VLAN	DF-Status
10 3.3.3.3	VNI-RED 2.2.2.2	L2 NW	---	---	---	----
10 3.3.3.3	VNI-RED 1.1.1.1	L2 NW	---	---	---	----
10 ---	VNI-RED ---	-- AC	xe48	--- Single Homed Port ---	1001	----
10 ---	VNI-RED ---	-- AC	xe48	--- Single Homed Port ---	1002	----
20 3.3.3.3	VNI-BLUE 2.2.2.2	L2 NW	---	---	---	----
20 3.3.3.3	VNI-BLUE 1.1.1.1	L2 NW	---	---	---	----
20 ---	VNI-BLUE ---	-- AC	xe48	--- Single Homed Port ---	3001	----

Total number of entries are 7

```
VTEP3#show nvo vxlan access-if brief
```

Interface	Vlan	Inner			Admin status	Link status
		vlan	Ifindex	Vnid		
xe48	1002	---	500001	10	up	up
xe48	1001	---	500000	10	up	up
xe48	3001	---	500002	20	up	up

Total number of entries are 3

```
VTEP3#show bgp l2vpn evpn summary
```

BGP router identifier 3.3.3.3, local AS number 500

BGP table version is 4

1 BGP AS-PATH entries

0 BGP community entries

Neighbor PfxRcd	AD	MACIP	V MCAST	AS 500	MsgRcv 177	MsgSen 173	TblVer 3	InQ 0	OutQ 0	Up/Down 01:11:49	State/
1.1.1.1 6	3	0	2	4 1	500 0	177 0	173	3	0	0	01:11:49
2.2.2.2 6	3	0	2	4 1	500 0	177 0	171	2	0	0	01:11:59

Total number of neighbors 2

Total number of Established sessions 2

```
VTEP3#show nvo vxlan tunnel
```

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
3.3.3.3	2.2.2.2	Installed	01:12:10	01:12:10
3.3.3.3	1.1.1.1	Installed	01:12:00	01:12:00

Total number of entries are 2

```
VTEP3#show bgp l2vpn evpn multihoming es-route
```

RD[1.1.1.1:1]

ESI	PE IP-Address	Nexthop IP	Encap
00:00:00:00:00:11:11:00:00:00	1.1.1.1	1.1.1.1	VXLAN

RD[2.2.2.2:1]

ESI	PE IP-Address	Nexthop IP	Encap
00:00:00:00:00:11:11:00:00:00	2.2.2.2	2.2.2.2	VXLAN

```
VTEP3#show bgp l2vpn evpn multihoming ethernet-ad-per-es
```

RD[1.1.1.1:1]					
ESI	Eth-Tag	VNID/LABEL	Nexthop	IP	Encap
00:00:00:00:00:11:11:00:00:00	4294967295	0		1.1.1.1	VXLAN
RD[2.2.2.2:1]					
ESI	Eth-Tag	VNID/LABEL	Nexthop	IP	Encap
00:00:00:00:00:11:11:00:00:00	4294967295	0		2.2.2.2	VXLAN
RD[3.3.3.3:11] VRF[VRF1]:					
ESI	Eth-Tag	VNID/LABEL	Nexthop	IP	Encap
00:00:00:00:00:11:11:00:00:00	4294967295	0		2.2.2.2	VXLAN
00:00:00:00:00:11:11:00:00:00	4294967295	0		1.1.1.1	VXLAN
RD[3.3.3.3:21] VRF[VRF2]:					
ESI	Eth-Tag	VNID/LABEL	Nexthop	IP	Encap
00:00:00:00:00:11:11:00:00:00	4294967295	0		2.2.2.2	VXLAN
00:00:00:00:00:11:11:00:00:00	4294967295	0		1.1.1.1	VXLAN
VTEP3#show bgp l2vpn evpn multihoming ethernet-ad-per-evi					
RD[1.1.1.1:11]					
ESI	Eth-Tag	VNID/LABEL	Nexthop	IP	Encap
00:00:00:00:00:11:11:00:00:00	10	10		1.1.1.1	VXLAN
RD[1.1.1.1:21]					
ESI	Eth-Tag	VNID/LABEL	Nexthop	IP	Encap
00:00:00:00:00:11:11:00:00:00	20	20		1.1.1.1	VXLAN
RD[2.2.2.2:11]					
ESI	Eth-Tag	VNID/LABEL	Nexthop	IP	Encap
00:00:00:00:00:11:11:00:00:00	10	10		2.2.2.2	VXLAN
RD[2.2.2.2:21]					
ESI	Eth-Tag	VNID/LABEL	Nexthop	IP	Encap
00:00:00:00:00:11:11:00:00:00	20	20		2.2.2.2	VXLAN
RD[3.3.3.3:11] VRF[VRF1]:					
ESI	Eth-Tag	VNID/LABEL	Nexthop	IP	Encap
00:00:00:00:00:11:11:00:00:00	10	10		2.2.2.2	VXLAN
00:00:00:00:00:11:11:00:00:00	10	10		1.1.1.1	VXLAN
RD[3.3.3.3:21] VRF[VRF2]:					
ESI	Eth-Tag	VNID/LABEL	Nexthop	IP	Encap
00:00:00:00:00:11:11:00:00:00	20	20		2.2.2.2	VXLAN
00:00:00:00:00:11:11:00:00:00	20	20		1.1.1.1	VXLAN

VTEP3#show bgp l2vpn evpn

BGP table version is 4, local router ID is 3.3.3.3

Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,

l - labeled, S Stale

Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]

- 1 - Ethernet Auto-discovery Route
- 2 - MAC/IP Route
- 3 - Inclusive Multicast Route
- 4 - Ethernet Segment Route
- 5 - Prefix Route

Network Encap	Next Hop	Metric	LocPrf	Weight	Path	Peer
RD[1.1.1.1:1]						
*>i [1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]	1.1.1.1	0	100	0	i	1.1.1.1
VXLAN						
*>i [4]:[00:00:00:00:00:11:11:00:00:00]:[32,1.1.1.1]	1.1.1.1	0	100	0	i	1.1.1.1
VXLAN						
RD[1.1.1.1:11]						
*>i [1]:[00:00:00:00:00:11:11:00:00:00]:[10]:[10]	1.1.1.1	0	100	0	i	1.1.1.1
VXLAN						
*>i [3]:[10]:[32,1.1.1.1]	1.1.1.1	0	100	0	i	1.1.1.1
VXLAN						
RD[1.1.1.1:21]						
*>i [1]:[00:00:00:00:00:11:11:00:00:00]:[20]:[20]	1.1.1.1	0	100	0	i	1.1.1.1
VXLAN						
*>i [3]:[20]:[32,1.1.1.1]	1.1.1.1	0	100	0	i	1.1.1.1
VXLAN						
RD[2.2.2.2:1]						
*>i [1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]	2.2.2.2	0	100	0	i	2.2.2.2
VXLAN						
*>i [4]:[00:00:00:00:00:11:11:00:00:00]:[32,2.2.2.2]	2.2.2.2	0	100	0	i	2.2.2.2
VXLAN						
RD[2.2.2.2:11]						
*>i [1]:[00:00:00:00:00:11:11:00:00:00]:[10]:[10]	2.2.2.2	0	100	0	i	2.2.2.2
VXLAN						
*>i [3]:[10]:[32,2.2.2.2]	2.2.2.2	0	100	0	i	2.2.2.2
VXLAN						

```

RD[2.2.2.2:21]
*>i [1]:[00:00:00:00:00:11:11:00:00:00]:[20]:[20]
          2.2.2.2      0      100      0      i  2.2.2.2
VXLAN
*>i [3]:[20]:[32,2.2.2.2]
          2.2.2.2      0      100      0      i  2.2.2.2
VXLAN

RD[3.3.3.3:11] VRF[VRF1]:
* i [1]:[00:00:00:00:00:11:11:00:00:00]:[10]:[10]
          2.2.2.2      0      100      0      i  2.2.2.2
VXLAN
* i 1.1.1.1      0      100      0      i  1.1.1.1
VXLAN
* i [1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]
          2.2.2.2      0      100      0      i  2.2.2.2
VXLAN
* i 1.1.1.1      0      100      0      i  1.1.1.1
VXLAN
* i [3]:[10]:[32,1.1.1.1]
          1.1.1.1      0      100      0      i  1.1.1.1
VXLAN
* i [3]:[10]:[32,2.2.2.2]
          2.2.2.2      0      100      0      i  2.2.2.2
VXLAN
*> [3]:[10]:[32,3.3.3.3]
          3.3.3.3      0      100      32768    i  -----
---      VXLAN

RD[3.3.3.3:21] VRF[VRF2]:
* i [1]:[00:00:00:00:00:11:11:00:00:00]:[20]:[20]
          2.2.2.2      0      100      0      i  2.2.2.2
VXLAN
* i 1.1.1.1      0      100      0      i  1.1.1.1
VXLAN
* i [1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]
          2.2.2.2      0      100      0      i  2.2.2.2
VXLAN
* i 1.1.1.1      0      100      0      i  1.1.1.1
VXLAN
* i [3]:[20]:[32,1.1.1.1]
          1.1.1.1      0      100      0      i  1.1.1.1
VXLAN
* i [3]:[20]:[32,2.2.2.2]
          2.2.2.2      0      100      0      i  2.2.2.2
VXLAN
*> [3]:[20]:[32,3.3.3.3]
          3.3.3.3      0      100      32768    i  -----
---      VXLAN

```

Total number of prefixes 22

Static MAC-IP advertise through Single Home and Multihomed VTEPs

Advertise static MAC IPv4 from MH1 and SH3.

MH1-VTEPs: VTEP1 & VTEP2- same MAC should be configured on both VTEPs under po access-port, configs should be symmetric between MH VTEPs

SH3-VTEP: VTEP3

VTEP1(MH1)

#configure terminal	Enter Configure mode.
(config)# nvo vxlan access-if port-vlan po1 1001	Enter into VxLAN MH po1 access-port with VLAN 1001
(config-nvo-acc-if) #mac 0000.1111.1001 ip 11.11.10.1	Configure static MAC IP
(config-nvo-acc-if) #exit	Exit from VxLAN access-port config mode
(config)#commit	Commit the candidate configuration to the running configuration
(config)#exit	Exit from configuration mode

VTEP2(MH1)

#configure terminal	Enter Configure mode.
(config)#nvo vxlan access-if port-vlan po1 1001	Enter into VxLAN MH po1 access-port with vlan 1001
(config-nvo-acc-if) # mac 0000.1111.1001 ip 11.11.10.1	Configure static MAC IP
(config-nvo-acc-if) #exit	Exit from VxLAN access-port config mode
(config)#commit	Commit the candidate configuration to the running configuration
(config)#exit	Exit from configuration mode

VTEP3(SH)

#configure terminal	Enter Configure mode.
(config)# nvo vxlan access-if port-vlan xe48 1001	Enter into single-homed access-port - xe48 with VLAN 1001
(config-nvo-acc-if) #mac 0000.3333.1001 ip 11.11.10.2	Configure static MAC IP
(config-nvo-acc-if) #exit	Exit from VxLAN access-port config mode
(config)#commit	Commit the candidate configuration to the running configuration
(config)#exit	Exit from configuration mode

Validation

Verify MAC-table in MH VTEPs and Single Home VTEP, MAC will be advertised through ESI value which is advertised from VTEP1 and VTEP2 and VTEP IP from SH VTEP VTEP3.

Verify ARP-cache table in all VTEPs, VTEP1 and VTEP2 will learn VTEP3 IP.

Any ARP request comes for 11.11.10.2, VTEP1/VTEP2 will do proxy-ARP.

VTEP1

```
VTEP1#show nvo vxlan mac-table
=====
=====

                                         VXLAN MAC Entries
=====

VNID      Interface VlanId Inner-VlanId Mac-Addr          VTEP-Ip/ESI
Type       Status     AccessPortDesc

=====

10        po1       1001    ----   0000.1111.1001 00:00:00:00:00:11:11:00:00:00
Static Local  -----  -----
10        ----      ----    ----   0000.3333.1001 3.3.3.3
Static Remote -----  -----
```

Total number of entries are : 2

```
VTEP1#show nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====

VNID      Ip-Addr      Mac-Addr      Type      Age-Out      Retries-Left
-----  -----  -----  -----  -----  -----
10        11.11.10.1  0000.1111.1001 Static Local  ----
10        11.11.10.2  0000.3333.1001 Static Remote ----
Total number of entries are 2
```

VTEP2

```
VTEP2#show nvo vxlan mac-table
=====
=====

                                         VXLAN MAC Entries
=====

VNID      Interface VlanId Inner-VlanId Mac-Addr          VTEP-Ip/ESI
Type       Status     AccessPortDesc

=====

10        po1       1001    ----   0000.1111.1001 00:00:00:00:00:11:11:00:00:00
Static Local  -----  -----
```

```
10      ----      ----      ----      0000.3333.1001 3.3.3.3
Static Remote      -----      -----
```

Total number of entries are : 2

VTEP2#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
10	11.11.10.1	0000.1111.1001	Static Local	----	
10	11.11.10.2	0000.3333.1001	Static Remote	----	

Total number of entries are 2

VTEP3

VTEP3#show nvo vxlan mac-table

VXLAN MAC Entries					
VNID	Interface	VlanId	Inner-VlanId	Mac-Addr	VTEP-Ip/ESI
Type		Status		AccessPortDesc	
10	-----	1001	----	0000.1111.1001	00:00:00:00:00:11:11:00:00:00
Static Remote	-----	-----			
10	xe48	1001	----	0000.3333.1001	3.3.3.3
Static Local	-----	-----			

Total number of entries are : 2

VTEP3#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
10	11.11.10.1	0000.1111.1001	Static Remote	----	
10	11.11.10.2	0000.3333.1001	Static Local	----	

Total number of entries are 2

Dynamic MAC advertise through Single Home and Multihomed VTEPs

Advertise 2 MAC's through CE1 connected IXIA, dynamic MAC entries and verify MAC-table in all VTEPs.

One MAC will be dynamic local in VTEP1 and same will be remote in VTEP2 and other be dynamic local in VTEP2 and same will be remote in VTEP1.

Both MAC's will be in remote in VTEP3.

VTEP1

```
VTEP1#show nvo vxlan mac-table
=====
===== VXLAN MAC Entries =====
=====

VNID      Interface VlanId Inner-VlanId Mac-Addr      VTEP-Ip/ESI
Type      Status     AccessPortDesc

=====
10        po1       1001   ----      0000.1111.1002 00:00:00:00:00:11:11:00:00:00
Dynamic Local  -----  -----
10        ----      1002   ----      0000.1111.1003 00:00:00:00:00:11:11:00:00:00
Dynamic Remote -----  -----
```

Total number of entries are : 2

```
VTEP1#show nvo vxlan arp-cache
VXLAN ARP-CACHE Information
```

```
=====
VNID      Ip-Addr      Mac-Addr      Type      Age-Out      Retries-Left
10        21.21.21.1  0000.1111.1002 Dynamic Local  -----
10        31.1.31.1    0000.1111.1003 Dynamic Remote -----
Total number of entries are 2
```

VTEP2

```
VTEP2#show nvo vxlan mac-table
=====
```

```
===== VXLAN MAC Entries =====
=====

VNID      Interface VlanId Inner-VlanId Mac-Addr      VTEP-Ip/ESI
Type      Status     AccessPortDesc

=====
10        ----      1001   ----      0000.1111.1002 00:00:00:00:00:11:11:00:00:00
Dynamic Remote -----  -----
10        po1       1002   ----      0000.1111.1003 00:00:00:00:00:11:11:00:00:00
Dynamic Local  -----  -----
```

Total number of entries are : 2

```
VTEP2#show nvo vxlan arp-cache
VXLAN ARP-CACHE Information
```

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
10	21.21.21.1	0000.1111.1002	Dynamic	Remote	----
10	31.1.31.1	0000.1111.1003	Dynamic	Local	----
Total number of entries are 2					

VTEP3

VTEP3#show nvo vxlan mac-table

VXLAN MAC Entries					
VNID	Interface	VlanId	Inner-VlanId	Mac-Addr	VTEP-Ip/ESI
Type		Status		AccessPortDesc	
10	-----	1001	----	0000.1111.1002	00:00:00:00:00:11:11:00:00:00
Dynamic	Remote	-----	-----		
10	-----	1002	----	0000.1111.1003	00:00:00:00:00:11:11:00:00:00
Dynamic	Remote	-----	-----		

Total number of entries are : 2

VTEP3#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
10	21.21.21.1	0000.1111.1002	Dynamic	Remote	----
10	31.1.31.1	0000.1111.1003	Dynamic	Remote	----
Total number of entries are 2					

Note: When VTEP1 tunnel goes down, then traffic from VTEP3 will use VTEP2 for forwarding. But Traffic from Switch to VTEP1 will be lost in VTEP1 itself.

When DUT is rebooted, access-if will be in hold down state until ESI hold timer value expiry. After ESI hold timer expiry, access-if port will be up and started learning.

MAC Hold timer will not be applicable on ESI interface, because of mass-withdraw requirement.

A CE can connect to maximum two nodes for multihoming, more than two nodes in a multihoming group is not supported.

All configuration (shutdown, disable learning, disable arp/nd cache, disable arp/nd flood, map vnid, qos profiles, encapsulation) on a multihomed access port should be same on both VTEPs sharing the ESI for multihoming functionalities to work properly.

Multiple ESI values are supported on same VTEP.

CHAPTER 3 VXLAN Hybrid Access Port Configuration

This chapter shows how to configure a hybrid access port which is a Layer 2 Port (configured switchport) that is part of both a VXLAN domain and a Layer 2 bridge with different VLANs.


Overview

A hybrid VXLAN access port is a Layer 2 port that is part of regular Layer 2 bridge (RSTP/MSTP/STP) and a VXLAN bridge. The mapping between Layer 2 bridging and VxLAN untagged and tagged access interface is supported on the same Layer 2 switch port interface. The same VLAN cannot be a part of both a VXLAN domain and a Layer 2 bridge.

If a port is created with “all” VLANs, then the port should not allow VXLAN access-port configurations. If a VXLAN with a specific VLAN is mapped, then configuring VLAN “all” on the same port does not allow that specified VLAN in a Layer 2 bridge. If the VXLAN access-port configurations are removed, then the specified VLAN is added immediately in a Layer 2 bridge.

Ingress traffic with a VXLAN VLAN does not receive Layer 2 traffic or vice-versa. STP states on the Port P1 do not affect VXLAN traffic.

Topology



RTR1/VTEP1

#configure terminal	Enter config mode.
(config)#interface lo	Enter interface mode for loopback.
(config-if)#ip address 10.10.10.10/32 secondary	Assign secondary IP address.
(config-if)#exit	Exit interface mode.
(config)#mac vrf vrf12345	Create mac routing/forwarding instance with vrf12345 name and enter VRF mode.
(config-vrf)#rd 1.1.1.1:1	Assign Rd value.
(config-vrf)#route-target both 10.10.10.10:10	Assign route-target both value.
(config-vrf)#exit	Exit VRF configuration mode.
(config)#bridge 32 protocol ieee vlan-bridge	Configure the ieee vlan-bridge with Id 32.

(config) #vlan 2-5 bridge 32	Configure the vlans 2-5 for the configured bridge Id 32.
(config) #interface ce25/1	Enter interface mode for ce25/1.
(config-if)#ip address 20.20.20.0/31	Assign IP address 20.20.20.0 in /31 mask.
(config-if)#exit	Exit interface mode.
(config) #interface ce25/2	Enter interface mode for ce25/2.
(config-if) #switchport	Make it L2 interface.
(config-if) #bridge-group 32	Associate the bridge-group 32 to the interface.
(config-if) #switchport mode hybrid	Configure the Hybrid mode.
(config-if) # switchport hybrid allowed vlan add 4 egress-tagged enable	Configure hybrid allowed vlan add 4 to support the created vlan in the L2 Bridge.
(config-if) #exit	Exit interface mode.
(config) #interface ce31/1	Enter interface mode for ce31/1.
(config-if) #switchport	Make it L2 interface.
(config-if) #bridge-group 32	Associate the bridge-group 32 to the interface.
(config-if) #switchport mode hybrid	Configure the Hybrid mode.
(config-if) # switchport hybrid allowed vlan add 4 egress-tagged enable	Configure hybrid allowed vlan add 4 to support the created vlan in the L2 Bridge.
(config-if) #exit	Exit interface mode.
(config) #router bgp 64512	Enter BGP router mode.
(config-router) # bgp router-id 1.1.1.1	Assign BGP router ID
(config-router) #neighbor 20.20.20.1 remote-as 64513	Specify a neighbor router with peer ip address and remote-as defined.
(config-router) #address-family l2vpn evpn	Enter l2vpn address family mode.
(config-router-af) #neighbor 20.20.20.1 activate	Activate the peer into address family mode.
(config-router) #address-family ipv4 unicast	Enter into ipv4 unicast address family
(config-router-af) #network 10.10.10.10/32	Advertise loopback network into BGP for VTEP ID reachability
(config-router-af) #exit-address-family	Exit ipv4 unicast address family mode
(config-router-af) #exit-address-family	Exit l2vpn address family mode.
(config-router) #exit	Exit BGP router mode.
(config) #nvo vxlan enable	Enable Vxlan.
(config) #nvo vxlan vtep-ip-global 10.10.10.10	Configure the source Vtep-ip.
(config) #nvo vxlan id 16777215 ingress-replication inner-vid-disabled	Configure Vxlan Network identifier with/without inner-vid-disabled configure and enter Vxlan tenant mode.
(config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf12345	Assign VRF for evpn-bgp to carry evpn route.
(config-nvo) #exit	Exit Vxlan tenant mode.
(config) #nvo vxlan access-if port-vlan ce31/1 3	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) mapping.
(config-nvo-acc-if) #map vniid 16777215	Map Vxlan Identifier to access-port.
(config-nvo-acc-if) #exit	Exit Vxlan access-interface mode.
(config) #commit	Commit the candidate configuration to the running configuration

RTR2

#configure terminal	Enter configure mode.
(config)#bridge 32 protocol ieee vlan-bridge	Configure the ieee vlan-bridge with Id 32.
(config)#vlan 2-5 bridge 32	Configure the vlans 2-5 for the configured bridge Id 32.
(config)#interface xe17	Enter interface mode for xe17.
(config-if)#ip address 20.20.20.1/31	Assign IP address 20.20.20.1 in /31 mask.
(config-if)#exit	Exit interface mode.
(config)#interface xe18	Enter interface mode for xe18.
(config-if)#switchport	Make it L2 interface .
(config-if)#bridge-group 32	Associate the bridge-group 32 to the interface.
(config-if)#switchport mode hybrid	Configure the Hybrid mode.
(config-if)#switchport hybrid allowed vlan add 4 egress-tagged enable	Configure hybrid allowed vlan add 4 to support the created vlan in the L2 Bridge.
(config-if)#exit	Exit interface mode.
(config)#interface xe33	Enter interface mode for xe33.
(config-if)#ip address 30.30.30.0/31	Assign IP address 30.30.30.0 in /31 mask.
(config-if)#exit	Exit interface mode.
(config)#interface xe34	Enter interface mode for xe34.
(config-if)#switchport	Make it L2 interface.
(config-if)#bridge-group 32	Associate the bridge-group 32 to the interface.
(config-if)#switchport mode hybrid	Configure the Hybrid mode.
(config-if)#switchport hybrid allowed vlan add 4 egress-tagged enable	Configure hybrid allowed vlan add 4 to support the created vlan in the L2 Bridge.
(config-if)#exit	Exit interface mode.
(config)#router bgp 64513	Enter BGP router mode.
(config-router)#bgp router-id 2.2.2.2	Assign BGP router ID
(config-router)#neighbor 20.20.20.0 remote-as 64512	Specify a neighbor router with peer ip address and remote-as defined.
(config-router)#neighbor 30.30.30.1 remote-as 64514	Specify a neighbor router with peer ip address and remote-as defined.
(config-router)#address-family l2vpn evpn	Enter l2vpn address family mode.
(config-router-af)#neighbor 20.20.20.0 activate	Activate the peer into address family mode.
(config-router-af)#neighbor 30.30.30.1 activate	Activate the peer into address family mode.
(config-router-af)#exit-address-family	Exit l2vpn address family mode.
(config-router)#exit	Exit BGP router mode.
(config)#commit	Commit the candidate configuration to the running configuration

RTR3/VTEP2

#configure terminal	Enter configure mode.
(config)#interface lo	Enter interface mode for loopback.
(config-if)#ip address 40.40.40.40/32 secondary	Assign secondary IP address.
(config-if)#exit	Exit interface mode.
(config)#mac vrf vrf12345	Create mac routing/forwarding instance with vrf12345 name and enter VRF mode.
(config-vrf)#rd 2.2.2.2:2	Assign Rd value.
(config-vrf)#route-target both 10.10.10.10:10	Assign route-target both value.
(config-vrf)#exit	Exit VRF configuration mode.
(config)#bridge 32 protocol ieee vlan-bridge	Configure the ieee vlan-bridge with Id 32.
(config)#vlan 2-5 bridge 32	Configure the vlans 2-5 for the configured bridge Id 32.
(config)#interface xe 49/1	Enter interface mode for xe49/1.
(config-if)#ip address 30.30.30.1/31	Assign Ip address 30.30.30.1 in /31 mask.
(config-if)#exit	Exit interface mode.
(config)#interface xe49/2	Enter interface mode for xe49/2.
(config-if)#switchport	Make it L2 interface .
(config-if)#bridge-group 32	Associate the bridge-group 32 to the interface.
(config-if)#switchport mode hybrid	Configure the Hybrid mode.
(config-if)#switchport hybrid allowed vlan add 4 egress-tagged enable	Configure hybrid allowed vlan add 4 to support the created vlan in the L2 Bridge.
(config-if)#exit	Exit interface mode.
(config)#interface xe1	Enter interface mode for xe1.
(config-if)#switchport	Make it L2 interface .
(config-if)#bridge-group 32	Associate the bridge-group 32 to the interface.
(config-if)#switchport mode hybrid	Configure the Hybrid mode.
(config-if)#switchport hybrid allowed vlan add 4 egress-tagged enable	Configure hybrid allowed vlan add 4 to support the created vlan in the L2 Bridge.
(config-if)#exit	Exit interface mode.
(config)#router bgp 64514	Enter BGP router mode.
(config-router)# bgp router-id 3.3.3.3	Assign BGP router ID
(config-router)#neighbor 30.30.30.0 remote-as 64513	Specify a neighbor router with peer IP address and remote-as defined.
(config-router)#address-family ipv4 unicast	Enter into ipv4 unicast address family
(config-router-af)#network 40.40.40.40/32	Advertise loopback network into BGP for VTEP ID reachability
(config-router-af)#exit-address-family	Exit ipv4 unicast address family mode
(config-router)#address-family l2vpn evpn	Enter l2vpn address family mode.
(config-router-af)#neighbor 30.30.30.0 activate	Activate the peer into address family mode.
(config-router-af)#exit-address-family	Exit l2vpn address family mode.
(config-router)#exit	Exit BGP router mode.

(config) #nvo vxlan enable	Enable Vxlan.
(config) #nvo vxlan vtep-ip-global 40.40.40.40	Configure the source Vtep-ip.
(config) #nvo vxlan id 16777215 ingress-replication inner-vid-disabled	Configure Vxlan Network identifier with/without inner-vid-disabled configure and enter Vxlan tenant mode.
(config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf12345	Assign VRF for evpn-bgp to carry evpn route.
(config-nvo) #exit	Exit Vxlan tenant mode.
(config) #nvo vxlan access-if port-vlan xe1 3	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) mapping.
(config-nvo-acc-if) #map vniid 16777215	Map Vxlan Identifier to access-port.
(config-nvo-acc-if) #exit	Exit Vxlan access-interface mode.
(config) #commit	Commit the candidate configuration to the running configuration

Validation

VTEP1

```
#show running-config nvo vxlan
!
nvo vxlan enable
!
nvo vxlan vtep-ip-global 10.10.10.10
!
nvo vxlan id 16777215 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp vrf12345
!
nvo vxlan access-if port-vlan ce31/1 3
  map vniid 16777215
!
```

VTEP1#show nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port
 AC - Access Port
 (u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-
Status	Src-Addr		Dst-Addr				
16777215	---	L2	NW	----	-----	-----	-----
--	10.10.10.10			40.40.40.40			
16777215	---	--	AC	ce31/1	--- Single Homed Port ---	3	-
---	---			---			

Total number of entries are 2

```
VTEP1#show nvo vxlan vnid 16777215
```

VXLAN Information

```
=====
```

Codes: NW - Network Port

AC - Access Port

(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-
Status	Src-Addr		Dst-Addr				
16777215	---	L2	NW	----	-----	-----	-----
--	10.10.10.10			40.40.40.40			
16777215	---	--	AC	ce31/1	--- Single Homed Port ---	3	-
---	---			----			

Total number of entries are 2!

```
VTEP1#show ip route
```

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
ia - IS-IS inter area, E - EVPN,
v - vrf leaked
* - candidate default

IP Route Table for VRF "default"

C	10.10.10.10/32	is directly connected,	lo	01:15:55
C	20.20.20.0/31	is directly connected,	xe10/1	01:07:53
B	40.40.40.40/32 [20/0]	via 20.20.20.1,	xe10/1	00:42:54
C	127.0.0.0/8	is directly connected,	lo	1d05h02m

Gateway of last resort is not set

```
VTEP1#show nvo vxlan tunnel
```

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
33.33.33.0	34.34.34.0	Installed	00:26:27	00:26:27

Total number of entries are 1

```
VTEP1#show bgp l2vpn evpn summary
```

BGP router identifier 10.10.10.2, local AS number 64512

BGP table version is 10

2 BGP AS-PATH entries

0 BGP community entries

Total number of neighbors 1

Total number of Established sessions 1

```
VTEP1#show bgp 12vpn evpn
```

BGP table version is 4, local router ID is 10.10.10.10

Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
l - labeled, S Stale

Origin codes: i = IGP, e = EGP, ? = incomplete

[EVPN route type]:[ESI]:[VNID]:[relevant route information]

1 = Ethernet Auto-discovery Route

3 - MAC/TB Route

2 MAC/II Route

Ethernet Segment Routing

4 - Ethernet seg
5 - Busfire Router

Network	Next Hop	Metric	LocPrf	Weight	Path	Peer
Encoder						

BD[1 1 1 1:1] VBE["utf12345"];

* [31:[01:[16777215]:[48 0000 0744 4433]:[01:[16777215]

.. [2].[0].[16777215].[48,0000.0744.4433].[0].[16777215] 40.40.40.40 0 100 0 64513 64514

```
*> [2]:[0]:[16777215]:[48,0000.2222.2222]:[0]:[16777215]
```

-- VXLAN 10.10.10.10 0 100 32768 i -----

```
*> [3]:[16777215]:[32,10.10.10.10]
          10.10.10.10      0      100      32768    i  -----
```

```
--          VXLAN  
* [3]:[16777215]:[32,40,40,40,40]
```

```
i 20 20 20 1      vxlan    40.40.40.40          0       100          0       64513 64514
```

BD [2 2 2 2 • 2]

```
*> [2]:[0]:[16777215]:[48 0000 0744 4433]:[0]:[16777215]
```

```
> [2].[0].[10777215].[40,0000.0]44.4453].[0].[10777215] 40.40.40.40 0 100 0 64513 64514
```

```
*>      [3]:[16777215]:[32,40.40.40.40]
```

```
i 20.20.20.1      40.40.40.40      0      100      0      64513 64514  
          VXLAN
```

Total number of prefixes 6

```
VTEP1#show nvo vxlan mac-table
```

=====

VXLAN MAC Entries

=====

VNID Type	Interface Status	VlanId	Inner-VlanId	Mac-Addr	VTEP-IP/ESI AccessPortDesc
16777215 Dynamic Local	ce31/1	3	----	0000.2222.2222	10.10.10.10
16777215 Dynamic Remote	----	----	----	0000.0744.4433	40.40.40.40

Total number of entries are : 2

```
VTEP1#show nvo vxlan arp-cache
VXLAN ARP-CACHE Information
```

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
------	---------	----------	------	---------	--------------

Total number of entries are 0

```
VTEP1#show vlan brief
```

Bridge	VLAN ID	Name	State	H/W Status	Member ports (u)-Untagged, (t)-Tagged
32	1	default	ACTIVE	Success	ce25/2 (u) ce31/1 (u)
32	2	VLAN0002	ACTIVE	Success	
32	3	VLAN0003	ACTIVE	Success	
32	4	VLAN0004	ACTIVE	Success	ce25/2 (t) ce31/1 (t)
32	5	VLAN0005	ACTIVE	Success	

RTR2

```
RTR2#show ip route
```

```
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
      O - OSPF, IA - OSPF inter area
      N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
      E1 - OSPF external type 1, E2 - OSPF external type 2
      i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
      ia - IS-IS inter area, E - EVPN,
      v - vrf leaked
      * - candidate default
```

```
IP Route Table for VRF "default"
```

```
B    10.10.10.10/32 [20/0] via 20.20.20.0, xe17, 00:29:48
C    20.20.20.0/31 is directly connected, xe17, 02:33:29
C    30.30.30.0/31 is directly connected, xe33, 02:31:56
B    40.40.40.40/32 [20/0] via 30.30.30.1, xe33, 02:23:26
C    127.0.0.0/8 is directly connected, lo, 21:17:41
```

Gateway of last resort is not set

```
RTR2#show bgp l2vpn evpn summary
BGP router identifier 11.11.11.1, local AS number 64513
BGP table version is 10
2 BGP AS-PATH entries
0 BGP community entries
```

Neighbor PfxRcd	AD	MACIP	V MCAST	AS 64512	MsgRcv 111	MsgSen PREFIX-ROUTE	TblVer 112	InQ 10	OutQ 0	Up/Down 00:49:36	State/
20.20.20.0 3	0	2	1	0	0						
30.30.30.1 3	0	2	1	0	101		103	10	0	00:45:10	

Total number of neighbors 2

Total number of Established sessions 2

```
#show nvo vxlan vnid 16777215
```

VXLAN Information

=====

Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNID Status	VNI-Name Src-Addr	VNI-Type Dst-Addr	Type	Interface	ESI	VLAN	DF-
16777215 --	40.40.40.40	L2 10.10.10.10	NW ---		-----	-----	---
16777215 ----	----	--	AC	xel	--- Single Homed Port ---	3	----
----- Total number of entries are 2	-----	-----					

```
RTR2#show vlan brief
```

Bridge	VLAN ID	Name	State	H/W Status	Member ports (u)-Untagged, (t)-Tagged
32	1	default	ACTIVE	Success	ce10/2(u) ce11/2(u)
32	2	VLAN0002	ACTIVE	Success	
32	3	VLAN0003	ACTIVE	Success	
32	4	VLAN0004	ACTIVE	Success	ce10/2(t) ce11/2(t)
32	5	VLAN0005	ACTIVE	Success	

VTEP2

```
#show running-config nvo vxlan
!
```

```

nvo vxlan enable
!
nvo vxlan vtep-ip-global 40.40.40.40
!
nvo vxlan id 16777215 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp vrf12345
!
nvo vxlan access-if port-vlan xel 3
  no shutdown
  map vnid 16777215
!

```

VTEP2#show nvo vxlan

VXLAN Information

=====

```

Codes: NW - Network Port
      AC - Access Port
      (u) - Untagged

```

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status	Src-Addr	Dst-Addr
16777215	----	L2	NW	----			-----		---- --
--	40.40.40.40			10.10.10.10					
16777215	----	--	AC	xel		---	Single Homed Port ---	3	----
----		----							

Total number of entries are 2

VTEP2#show ip route

```

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
      O - OSPF, IA - OSPF inter area
      N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
      E1 - OSPF external type 1, E2 - OSPF external type 2
      i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
      ia - IS-IS inter area, E - EVPN,
      v - vrf leaked
      * - candidate default

```

IP Route Table for VRF "default"

```

B    10.10.10.10/32 [20/0] via 30.30.30.0, xel1/1, 00:27:32
C    30.30.30.0/31 is directly connected, xel1/1, 00:30:00
C    40.40.40.40/32 is directly connected, lo, 00:31:00
C    127.0.0.0/8 is directly connected, lo, 06:25:00

```

Gateway of last resort is not set

VTEP2#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update

```
40.40.40.40      10.10.10.10      Installed      00:14:40      00:14:40
Total number of entries are 1
```

```
VTEP2#show bgp l2vpn evpn summary
BGP router identifier 33.33.33.33, local AS number 64514
BGP table version is 8
2 BGP AS-PATH entries
0 BGP community entries
```

Neighbor PfxRcd	AD	V MACIP	AS MCAST	MsgRcv ESI	MsgSen PREFIX-ROUTE	TblVer	InQ	OutQ	Up/Down	State/
30.30.30.0 2	0	1	1	4 0	64513 0	267 270	8	0	0 02:09:07	

Total number of neighbors 1

Total number of Established sessions 1

```
VTEP2#show nvo vxlan access-if-config
nvo vxlan access-if port-vlan xe1/1 3
no shutdown
map vnid 16777215
!
```

```
VTEP2#show bgp l2vpn evpn
BGP table version is 8, local router ID is 40.40.40.40
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
              l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete
```

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]

- 1 - Ethernet Auto-discovery Route
- 2 - MAC/IP Route
- 3 - Inclusive Multicast Route
- 4 - Ethernet Segment Route
- 5 - Prefix Route

Network Encap	Next Hop	Metric	LocPrf	Weight	Path	Peer
RD[1.1.1.1:1] *> [2]:[0]:[16777215]:[48,0000.2222.2222]:[0]:[16777215]	10.10.10.10	0	100	0	64513	64512
i 30.30.30.0	VXLAN					
*> [3]:[16777215]:[32,10.10.10.10]	10.10.10.10	0	100	0	64513	64512
i 30.30.30.0	VXLAN					

RD[2.2.2.2:2] VRF[vrf12345]:
*> [2]:[0]:[16777215]:[48,0000.0744.4433]:[0]:[16777215]

```

--          VXLAN           40.40.40.40      0       100      32768     i  -----
*  [2]:[0]:[16777215]:[48,0000.2222.2222]:[0]:[16777215]
          10.10.10.10      0       100      0       64513 64512
i  30.30.30.0    VXLAN
*  [3]:[16777215]:[32,10.10.10.10]
          10.10.10.10      0       100      0       64513 64512
i  30.30.30.0    VXLAN
*> [3]:[16777215]:[32,40.40.40.40]
          40.40.40.40      0       100      32768     i  -----
--          VXLAN

```

Total number of prefixes 6

VTEP2#show nvo vxlan mac-table

```

=====
===== VXLAN MAC Entries =====
=====

VNID      Interface  VlanId Inner-VlanId Mac-Addr      VTEP-Ip/ESI
Type      Status      AccessPortDesc

=====
16777215  ----      ----  ----      0000.2222.2222 10.10.10.10
Dynamic  Remote      -----  -----
16777215  xe1        3      ----      0000.0744.4433 40.40.40.40
Dynamic  Local      -----  -----

```

Total number of entries are : 2

VTEP2#show vlan brief

Bridge	VLAN ID	Name	State	H/W Status	Member ports (u) -Untagged, (t) -Tagged
32	1	default	ACTIVE	Success	xe1(u) xe49/2(u)
32	2	VLAN0002	ACTIVE	Success	
32	3	VLAN0003	ACTIVE	Success	
32	4	VLAN0004	ACTIVE	Success	xe1(t) xe49/2(t)
32	5	VLAN0005	ACTIVE	Success	

VTEP2#

CHAPTER 4 VXLAN Trunk Access Port

In VxLAN, most of the use cases demand to carry the complete traffic received on the access interface to another VTEP access-port. Hence, this support of accepting all tagged and untagged traffic received on the mapped physical port.

Topology

The configurations used in this section use the topology in [Figure 4-8](#).




Figure 4-8: VXLAN Trunk Access Port

Base Configuration - L2 VXLAN

VTEP1

Hardware profile and generic configuration:

#configure terminal	Enter Configure mode.
(config) #qos enable	Enable qos
(config) #commit	Committing the configurations

Interface and loopback configuration:

(config) #interface xe7	Enter Interface mode for xe7
(config-if)#switchport	Make it L2 interface
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe8	Enter Interface mode for xe8
(config-if) #ip add 10.10.10.1/24	Configuring the ip address in the network side
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 1.1.1.1/32 secondary	Configure loopback ip address as 1.1.1.1 for VTEP1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Committing the interface configurations

OSPF configuration:

(config) #router ospf 1	Enter into router OSPF mode
(config-router) #ospf router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo ip address)
(config-router) #network 1.1.1.1/32 area 0.0.0.0	Add 1.1.1.1 (lo ip address) network into area 0
(config-router) #network 10.10.10.0/24 area 0.0.0.0	Add 10.10.10.0(Spine) network into area 0
(config-router) #bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-router) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Committing the ospf configurations

BGP configuration:

(config) #router bgp 1	Enter into Router BGP mode
(config-router) #bgp router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo ip address)
(config-router) #neighbor 2.2.2.2 remote-as 1	Specify a VTEP2 loopback ip address and remote-as defined
(config-router) #neighbor 2.2.2.2 update-source lo	Configure update as loopback for VTEP2
(config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2
(config-router) #address-family l2vpn evpn	Enter into l2vpn EVPN address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2(VTEP2) into l2vpn evpn address family mode
(config-router-af) #exit-address-family	Exit from l2vpn address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Committing the bgp configurations

L2 MAC VRF Configuration:

(config) #mac vrf L2VRF1	Create mac routing/forwarding instance with L2VRF1 name and enter into vrf mode
(config-vrf) #rd 1.1.1.1:1	Assign RD value
(config-vrf) #route-target both 1:1	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) #exit	Exit from vrf mode
(config) #commit	Committing the vrf configurations

L2 VXLAN configuration:

(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan vtep-ip-global 1.1.1.1	Configure Source vtep-ip-global configuration - Use loopback ip address
(config) #nvo vxlan id 100 ingress-replication	Configure VXLAN Network identifier without inner-vid-disabled configured for vxlan trunk access port and enter into VXLAN tenant mode

(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #commit	Committing the vxlan configurations

VTEP2

Hardware profile and generic configuration:

#configure terminal	Enter Configure mode.
(config) #qos enable	Enable qos
(config) #commit	Committing the configurations

Interface and loopback configuration:

(config) #interface xe23	Enter Interface mode for xe23
(config-if) #switchport	Make it L2 interface
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe14	Enter Interface mode for xe14
(config-if) #ip add 20.20.20.1/24	Configuring the ip address in the network side
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 2.2.2.2/32 secondary	Configure loopback ip address as 2.2.2.2 for VTEP2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Committing the interface configurations

OSPF configuration:

(config) #router ospf 1	Enter into router OSPF mode
(config-router) #ospf router-id 2.2.2.2	Configure router-id as 2.2.2.2 (lo ip address)
(config-router) #network 2.2.2.2/32 area 0.0.0.0	Add 2.2.2.2 (lo ip address) network into area 0
(config-router) #network 20.20.20.0/24 area 0.0.0.0	Add 20.20.20.0(Spine) network into area 0
(config-router) #bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-router) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Committing the ospf configurations

BGP configuration:

(config) #router bgp 1	Enter into Router BGP mode
(config-router) #bgp router-id 2.2.2.2	Configure router-id as 2.2.2.2 (lo ip address)
(config-router) #neighbor 1.1.1.1 remote-as 1	Specify a VTEP1 loopback ip address and remote-as defined

(config-router) #neighbor 1.1.1.1 update-source lo	Configure update as loopback for VTEP2
(config-router) #neighbor 1.1.1.1 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP1
(config-router) #address-family l2vpn evpn	Enter into l2vpn EVPN address family mode
(config-router-af) #neighbor 1.1.1.1 activate	Activate 1.1.1.1(VTEP1) into l2vpn evpn address family mode
(config-router-af) #exit-address-family	Exit from l2vpn address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Committing the bgp configurations

L2 MAC VRF Configuration:

(config) #mac vrf L2VRF1	Create mac routing/forwarding instance with L2VRF1 name and enter into vrf mode
(config-vrf) #rd 2.2.2.2:1	Assign RD value
(config-vrf) #route-target both 1:1	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) #exit	Exit from vrf mode
(config) #commit	Committing the vrf configurations

L2 VXLAN configuration:

(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan vtep-ip-global 2.2.2.2	Configure Source vtep-ip-global configuration - Use loopback ip address
(config) #nvo vxlan id 100 ingress-replication	Configure VXLAN Network identifier without inner-vid-disabled configured for vxlan trunk access port and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #commit	Committing the vxlan configurations

SPINE

Spine node where all VTEPs are connected.

Generic configuration:

#configure terminal	Enter Configure mode.
(config) #qos enable	Enabling qos
(config) #commit	Committing the configuration

Interface configuration:

(config) #interface xe8	Enter Interface mode for xe8
(config-if) #ip address 10.10.10.2/24	Configure ip address as 10.10.10.2 on network side of VTEP1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) interface xe14	Enter into ce5/1 interface mode
(config-if) #ip address 20.20.20.2/24	Configure ip address as 20.20.20.2 on network side of VTEP2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) commit	Committing the configuration

OSPF configuration:

(config) #router ospf 1	Enter into router OSPF mode
(config-router) #ospf router-id 3.3.3.3	Configure router-id as 3.3.3.3
(config-router) #network 10.10.10.0/24 area 0.0.0.0	Add 10.10.10.0 (VTEP1) network into area 0
(config-router) #network 20.20.20.0/24 area 0.0.0.0	Add 20.20.20.0 (VTEP2) network into area 0
(config-router) #bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) commit	Committing the ospf configuration

VxLAN Trunk Access port as default

In VxLAN, most of the use cases demand to carry the complete traffic received on the access interface to another VTEP access-port. Hence this support of accepting all tagged and untagged traffic received on the mapped physical port.

VTEP1

(config) #nvo vxlan access-if port xe7 default	Configuring the vxlan access port as default to receive untagged, single and double tagged traffic
(config-nvo-acc-if) #map vniid 100	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) #arp-cache disable	Disable arp-cache - mandatory
(config-nvo-acc-if) #nd-cache disable	Disable nd-cache - mandatory
(config-nvo-acc-if) # mac 0000.1111.0001	Configure static mac-only
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #commit	Committing the vxlan configuration

VTEP2

(config)#nvo vxlan access-if port xe23 default	Configuring the vxlan access port as default to receive untagged, single and double tagged traffic
(config-nvo-acc-if) #map vniid 100	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) #arp-cache disable	Disable arp-cache - mandatory
(config-nvo-acc-if) #nd-cache disable	Disable nd-cache - mandatory
(config-nvo-acc-if) # mac 0000.2222.0001	Configure static mac-only
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #commit	Committing the vxlan configuration

Validation**VTEP1**

```
VTEP1#sh run nvo vxlan
!
nvo vxlan enable
!
nvo vxlan vtep-ip-global 1.1.1.1
!
nvo vxlan id 100 ingress-replication
  vxlan host-reachability-protocol evpn-bgp L2VRF1
!
nvo vxlan access-if port xe7 default
  map vniid 100
  arp-cache disable
  nd-cache disable
  mac 0000.1111.0001
!
```

```
!
!
VTEP1#sh nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination        Status      Up/Down      Update
=====
1.1.1.1         2.2.2.2           Installed   00:02:49    00:02:49
```

Total number of entries are 1

```
VTEP1#sh nvo vxlan mac-table
```

```
=====
=====
===== VXLAN MAC Entries =====
=====
=====
=====
```

VNIID	Interface	VlanId	Vlan-RangeId	Inner-VlanId	Mac-Addr	VTEP-Ip/ESI
Type	Status	AccessPortDesc				

```

100      xe7      ----  ----  ----      0000.1111.0001 1.1.1.1
Static Local  -----  -----  -----
100      ----  ----  ----      0000.2222.0001 2.2.2.2
Static Remote  -----  -----  -----
100      xe7      ----  ----  ----      b0da.1d10.6496 1.1.1.1
Dynamic Local  -----  -----  -----

```

Total number of entries are : 3

VTEP1#sh nvo vxlan mac-table hardware

```
=====
=====

                                         VXLAN MAC Entries
=====

VNID      Interface VlanId Vlan-RangeId Inner-VlanId Mac-Addr      VTEP-Ip/ESI
Type          Status           Time-out AccessPortDesc

=====

100      xe7      ----  ----      0000.1111.0001 1.1.1.1
Static Local  -----  ---  -----
100      ---  ----  ----      0000.2222.0001 2.2.2.2
Remote     -----  ---  -----
100      xe7      ----  ----      b0da.1d10.6496 1.1.1.1
Dynamic Local  -----  300  -----

```

Total number of entries are 3

VTEP1#show nvo vxlan

VXLAN Information

```
=====
Codes: NW - Network Port
       AC - Access Port
       (u) - Untagged
```

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status
Src-Addr							
		Dst-Addr					
100	---	L2	NW	---	---	---	---
1.1.1.1		2.2.2.2					
100	---	--	AC	xe7	--- Single Homed Port ---	---	---
---		---					

Total number of entries are 2

VTEP1#sh nvo vxlan route-count

VXLAN Active route count information

```
=====
Max route count   : 32768
```

Active route count: 3

VNID	Total	MACONLY	MACIPv4	MACIPv6
100	3	3	0	0

Total number of entries are 1
VTEP1#sh nvo vxlan access-if-config
nvo vxlan access-if port xe7 default
map vnid 100
arp-cache disable
nd-cache disable
mac 0000.1111.0001
!
VTEP1#sh nvo vxlan access-if brief

Interface	Inner				Admin status	Link status
	Vlan	vlan	Ifindex	Vnid		
xe7	---	---	500000	100	up	up

Total number of entries are 1
VTEP1#sh bgp l2vpn evpn summary
BGP router identifier 1.1.1.1, local AS number 1
BGP table version is 2
1 BGP AS-PATH entries
0 BGP community entries

Neighbor	PfxRcd	V	AS	MsgRcv	MsgSen	TblVer	InQ	OutQ	Up/Down	State/
	AD	MACIP	MCAST	ESI	PREFIX-ROUTE					
2.2.2.2	2	0	1	1	0	15	17	2	0	0 00:04:52

Total number of neighbors 1

Total number of Established sessions 1
VTEP1#sh bgp l2vpn evpn
BGP table version is 2, local router ID is 1.1.1.1
Status codes: s suppressed, d damped, h history, a add-path, * valid, > best, i - internal,
l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route
4 - Ethernet Segment Route
5 - Prefix Route

Network Encap	Next Hop	Metric	LocPrf	Weight	Path	Peer

```

RD[1.1.1.1:1] VRF[L2VRF1]:
*> [2]:[0]:[100]:[48,0000:1111:0001]:[0]:[100]
      1.1.1.1          0        100      32768 i -----
VXLAN
* i [2]:[0]:[100]:[48,0000:2222:0001]:[0]:[100]
      2.2.2.2          0        100      0 i 2.2.2.2 VXLAN
*> [2]:[0]:[100]:[48,b0da:1d10:6496]:[0]:[100]
      1.1.1.1          0        100      32768 i -----
VXLAN
*> [3]:[100]:[32,1.1.1.1]
      1.1.1.1          0        100      32768 i -----
VXLAN
* i [3]:[100]:[32,2.2.2.2]
      2.2.2.2          0        100      0 i 2.2.2.2 VXLAN

RD[2.2.2.2:1]
*>i [2]:[0]:[100]:[48,0000:2222:0001]:[0]:[100]
      2.2.2.2          0        100      0 i 2.2.2.2 VXLAN
*>i [3]:[100]:[32,2.2.2.2]
      2.2.2.2          0        100      0 i 2.2.2.2 VXLAN

Total number of prefixes 7
VTEP1#sh nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====
VNID      Ip-Addr          Mac-Addr       Type      Age-Out      Retries-Left
=====

Total number of entries are 0
VTEP1#sh nvo vxlan nd-cache
VXLAN ND-CACHE Information
=====
VNID      Ip-Addr          Mac-Addr       Type      Age-Out
Retries-Left
=====

Total number of entries are 0
VTEP1#

```

VTEP2

```

VTEP2#sh run nvo vxlan
!
nvo vxlan enable
!
nvo vxlan vtep-ip-global 2.2.2.2
!
nvo vxlan id 100 ingress-replication
  vxlan host-reachability-protocol evpn-bgp L2VRF1
!

```

```
nvo vxlan access-if port xe23 default
map vnid 100
arp-cache disable
nd-cache disable
mac 0000.2222.0001
```

!

!

VTEP2#sh nvo vxlan tunnel
VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
2.2.2.2	1.1.1.1	Installed	00:05:47	00:05:47

Total number of entries are 1

VTEP2#sh nvo vxlan
VXLAN Information

Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNID	Src-Addr	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status
100	---		L2	NW	---	---	---	---
2.2.2.2			1.1.1.1					
100	---		--	AC	xe23	--- Single Homed Port ---	---	---
	---		---					

Total number of entries are 2

VTEP2#sh nvo vxlan mac-table

VXLAN MAC Entries								
<hr/>								

VNID	Type	Interface	VlanId	Vlan-RangeId	Inner-VlanId	Mac-Addr	VTEP-Ip/ESI
100	Static Remote	xe23	---	-----	-----	0000.1111.0001	1.1.1.1

100	Static Remote	xe23	---	-----	-----	0000.1111.0001	1.1.1.1
100	Static Local	xe23	---	-----	-----	0000.2222.0001	2.2.2.2

100 ----- ----- ----- b0da.1d10.6496 1.1.1.1

Dynamic Remote ----- -----

Total number of entries are : 3

VTEP2#sh nvo vxlan mac-table hardware

```
=====
===== VXLAN MAC Entries =====
=====

VNID      Interface VlanId Vlan-RangeId Inner-VlanId Mac-Addr      VTEP-IP/ESI
Type       Status          Status           AccessPortDesc

=====

100      ---      ----      ----      0000.1111.0001 1.1.1.1
Remote    -----      ---      -----      -----
100      xe23      ----      ----      0000.2222.0001 2.2.2.2
Static Local  -----      ---      -----      -----
100      ---      ----      ----      b0da.1d10.6496 1.1.1.1
Remote    -----      ---      -----      -----
```

Total number of entries are 3

```
VTEP2#sh nvo vxlan route-count
VXLAN Active route count information
=====

Max route count : 32768
Active route count: 3
```

VNID	Total	MACONLY	MACIPv4	MACIPv6
100	3	3	0	0

Total number of entries are 1

```
VTEP2#sh nvo vxlan access-if br
```

Interface	Inner	Admin	Link			
Vlan	vlan	Ifindex	Vnid	status	status	
xe23	---	---	500000	100	up	up

Total number of entries are 1

```
VTEP2#sh nvo vxlan access-if-config
nvo vxlan access-if port xe23 default
map vnid 100
arp-cache disable
nd-cache disable
mac 0000.2222.0001
!
```

```
VTEP2#sh nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====
```

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
------	---------	----------	------	---------	--------------

Total number of entries are 0

```
VTEP2#sh nvo vxlan nd-cache
```

VXLAN ND-CACHE Information

VNID	Ip-Addr	Mac-Addr	Type	Age-Out
Retries-Left				

Total number of entries are 0

VTEP2#

```
VTEP2#sh bgp l2vpn evpn summary
BGP router identifier 2.2.2.2, local AS number 1
BGP table version is 2
1 BGP AS-PATH entries
0 BGP community entries
```

Neighbor	V	AS	MsgRcv	MsgSen	TblVer	InQ	OutQ	Up/Down	State/
PfxRcd	AD	MACIP	MCAST	ESI	PREFIX-ROUTE				
1.1.1.1		4	1	27	27	1	0	0	00:09:54
3	0	2	1	0	0				

Total number of neighbors 1

Total number of Established sessions 1

```
VTEP2#sh bgp l2vpn evpn
BGP table version is 2, local router ID is 2.2.2.2
Status codes: s suppressed, d damped, h history, a add-path, * valid, > best, i -
internal,
          l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete
```

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]

- 1 - Ethernet Auto-discovery Route
- 2 - MAC/IP Route
- 3 - Inclusive Multicast Route
- 4 - Ethernet Segment Route
- 5 - Prefix Route

Network	Next Hop	Metric	LocPrf	Weight	Path	Peer
Encap						

```
RD[1.1.1.1:1]
*>i [2]:[0]:[100]:[48,0000:1111:0001]:[0]:[100]
           1.1.1.1          0          100        0   i 1.1.1.1      VXLAN
*>i [2]:[0]:[100]:[48,b0da:1d10:6496]:[0]:[100]
           1.1.1.1          0          100        0   i 1.1.1.1      VXLAN
*>i [3]:[100]:[32,1.1.1.1]
           1.1.1.1          0          100        0   i 1.1.1.1      VXLAN
```

RD[2.2.2.2:1] VRF[L2VRF1]:

```
* i [2]:[0]:[100]:[48,0000:1111:0001]:[0]:[100]
           1.1.1.1          0          100        0   i 1.1.1.1      VXLAN
*> [2]:[0]:[100]:[48,0000:2222:0001]:[0]:[100]
```

```

          2.2.2.2           0      100      32768 i -----
VXLAN
* i [2]:[0]:[100]:[48,b0da:1d10:6496]:[0]:[100]
          1.1.1.1           0      100      0 i 1.1.1.1      VXLAN
* i [3]:[100]:[32,1.1.1.1]
          1.1.1.1           0      100      0 i 1.1.1.1      VXLAN
*> [3]:[100]:[32,2.2.2.2]
          2.2.2.2           0      100      32768 i -----
VXLAN

```

Total number of prefixes 8

VTEP2#

VxLAN Trunk access port with vlan range

When access port with a specific vlan range configured, all the traffic in that specific range are accepted and forwarded.

VTEP1

(config)#nvo vxlan access-if port-vlan xe7 2-100	Configuring the vxlan access port with vlan range 2-100 where traffic in the vlan range 2-100 are accepted
(config-nvo-acc-if)#map vniid 100	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if)#arp-cache disable	Disable arp-cache - mandatory
(config-nvo-acc-if)#nd-cache disable	Disable nd-cache - mandatory
(config-nvo-acc-if)# mac 0000.1111.0001	Configure static mac-only
(config-nvo-acc-if)#exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config)#commit	Committing the vxlan configuration

VTEP2

(config)#nvo vxlan access-if port-vlan xe23 2-100	Configuring the vxlan access port with vlan range 2-100 where traffic in the vlan range 2-100 are accepted
(config-nvo-acc-if)#map vniid 100	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if)#arp-cache disable	Disable arp-cache - mandatory
(config-nvo-acc-if)#nd-cache disable	Disable nd-cache - mandatory
(config-nvo-acc-if)# mac 0000.2222.0001	Configure static mac-only
(config-nvo-acc-if)#exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config)#commit	Committing the vxlan configuration

Validations

VTEP1

VTEP1#sh run nvo vx

```
!
nvo vxlan enable
!
nvo vxlan vtep-ip-global 1.1.1.1
!
nvo vxlan id 100 ingress-replication
  vxlan host-reachability-protocol evpn-bgp L2VRF1
!
nvo vxlan access-if port-vlan xe7 2-100
  map vnid 100
  arp-cache disable
  nd-cache disable
  mac 0000.1111.0001
!
!
```

VTEP1#
VTEP1#sh nvo vxlan tunnel summary

Total number of entries: 1 [Installed: 1, Resolved: 0, Unresolved: 0]

Total number of entries are 1

VTEP1#sh nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
1.1.1.1	2.2.2.2	Installed	00:20:10	00:20:10

Total number of entries are 1

VTEP1#sh nvo vx

VXLAN Information

=====

Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status
Src-Addr				Dst-Addr			
100	---	L2	NW	---	---	---	---
1.1.1.1				2.2.2.2			
100	---	--	AC	xe7	--- Single Homed Port ---	2	---
---				---			

Total number of entries are 2

VTEP1#sh nvo vxlan mac-table

VXLAN MAC Entries							
=====	=====	=====	=====	=====	=====	=====	=====

VNID Type	Interface Status	VlanId AccessPort	Vlan-RangeId PortDesc	Inner-VlanId Mac-Addr	VTEP-Ip/ESI
100 Static	xe7 Local	-----	2-100 -----	0000.1111.0001	1.1.1.1
100 Static	---	-----	-----	0000.2222.0001	2.2.2.2
100 Dynamic	xe7 Local	-----	2-100 -----	b0da.1d10.6496	1.1.1.1

Total number of entries are : 3

VTEP1#sh nvo vxlan mac-table hardware

VXLAN MAC Entries					
VNID Type	Interface Status	VlanId Time-out	Vlan-RangeId AccessPort	Inner-VlanId Mac-Addr	VTEP-Ip/ESI
100 Static	xe7 Local	-----	2-100 ---	0000.1111.0001	1.1.1.1
100 Remote	---	-----	-----	0000.2222.0001	2.2.2.2
100 Dynamic	xe7 Local	-----	2-100 300	b0da.1d10.6496	1.1.1.1

Total number of entries are 3

VTEP1#sh nvo vxlan arp-cache

VXLAN ARP-CACHE Information

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left

Total number of entries are 0

VTEP1#sh nvo vxlan nd-cache

VXLAN ND-CACHE Information

VNID Retries-Left	Ip-Addr	Mac-Addr	Type	Age-Out

Total number of entries are 0

VTEP1#sh nvo vxlan access-if-config

nvo vxlan access-if port-vlan xe7 2-100

map vnid 100

arp-cache disable

nd-cache disable

mac 0000.1111.0001

!

```
VTEP1#sh nvo vxlan access-if brief
```

Interface	Vlan	Inner vlan	Ifindex	Vnid	Admin status	Link status
xe7	2	---	500000	100	up	up

Total number of entries are 1

```
VTEP1#
```

```
VTEP1#sh nvo vxlan route-count
VXLAN Active route count information
=====
```

Max route count : 32768

Active route count: 3

VNID	Total	MACONLY	MACIPv4	MACIPv6
100	3	3	0	0

Total number of entries are 1

```
VTEP1#sh bgp l2vpn evpn summary
```

BGP router identifier 1.1.1.1, local AS number 1

BGP table version is 5

1 BGP AS-PATH entries

0 BGP community entries

Neighbor PfxRcd	V AD	AS MACIP	MCAST	MsgRcv ESI	MsgSen PREFIX-ROUTE	TblVer	InQ	OutQ	Up/Down	State/
2.2.2.2 2	0	1	1	0	58	61	5	0	0	00:22:05

Total number of neighbors 1

Total number of Established sessions 1

```
VTEP1#sh bgp l2vpn evpn
```

BGP table version is 5, local router ID is 1.1.1.1

Status codes: s suppressed, d damped, h history, a add-path, * valid, > best, i - internal,

l - labeled, S Stale

Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]

1 - Ethernet Auto-discovery Route

2 - MAC/IP Route

3 - Inclusive Multicast Route

4 - Ethernet Segment Route

5 - Prefix Route

Network Encap	Next Hop	Metric	LocPrf	Weight	Path	Peer
------------------	----------	--------	--------	--------	------	------

```

RD[1.1.1.1:1] VRF[L2VRF1]:
*> [2]:[0]:[100]:[48,0000:1111:0001]:[0]:[100]
          1.1.1.1      0      100      32768 i -----
VXLAN
* i [2]:[0]:[100]:[48,0000:2222:0001]:[0]:[100]
          2.2.2.2      0      100      0 i 2.2.2.2 VXLAN
*> [2]:[0]:[100]:[48,b0da:1d10:6496]:[0]:[100]
          1.1.1.1      0      100      32768 i -----
VXLAN
*> [3]:[100]:[32,1.1.1.1]
          1.1.1.1      0      100      32768 i -----
VXLAN
* i [3]:[100]:[32,2.2.2.2]
          2.2.2.2      0      100      0 i 2.2.2.2 VXLAN

RD[2.2.2.2:1]
*>i [2]:[0]:[100]:[48,0000:2222:0001]:[0]:[100]
          2.2.2.2      0      100      0 i 2.2.2.2 VXLAN
*>i [3]:[100]:[32,2.2.2.2]
          2.2.2.2      0      100      0 i 2.2.2.2 VXLAN

```

Total number of prefixes 7

VTEP2

```

VTEP2#sh run nvo vxlan
!
nvo vxlan enable
!
nvo vxlan vtep-ip-global 2.2.2.2
!
nvo vxlan id 100 ingress-replication
  vxlan host-reachability-protocol evpn-bgp L2VRF1
!
nvo vxlan access-if port-vlan xe23 2-100
  map vnid 100
  arp-cache disable
  nd-cache disable
  mac 0000.2222.0001
!
!
```

```

VTEP2#sh nvo vxlan tunnel
VXLAN Network tunnel Entries
Source        Destination      Status      Up/Down      Update
=====
2.2.2.2       1.1.1.1        Installed   00:19:28    00:19:28

```

Total number of entries are 1

VTEP2#sh nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
2.2.2.2	1.1.1.1	Installed	00:21:06	00:21:06

Total number of entries are 1

VTEP2#sh nvo vxlan

VXLAN Information

Codes: NW - Network Port

AC - Access Port

(u) - Untagged

VNID Src-Addr	VNI-Name Dst-Addr	VNI-Type	Type	Interface	ESI	VLAN	DF-Status
------------------	----------------------	----------	------	-----------	-----	------	-----------

100	---	L2	NW	---	---	---	---
2.2.2.2		1.1.1.1					
100	---	--	AC	xe23	--- Single Homed Port ---	2	---
---		---					

Total number of entries are 2

VTEP2#sh nvo vxlan mac-table

VXLAN MAC Entries

VNID Type	Interface Status	VlanId AccessPortDesc	Vlan-RangeId PortDesc	Inner-VlanId PortDesc	Mac-Addr	VTEP-Ip/ESI
--------------	---------------------	--------------------------	--------------------------	--------------------------	----------	-------------

100	----	----	----	-----	0000.1111.0001	1.1.1.1
Static	Remote	-----	-----	-----		
100	xe23	-----	2-100	----	0000.2222.0001	2.2.2.2
Static	Local	-----	-----	-----		
100	----	----	----	-----	b0da.1d10.6496	1.1.1.1
Dynamic	Remote	-----	-----	-----		

Total number of entries are : 3

VTEP2#sh nvo vxlan mac-table hardware

VXLAN MAC Entries

VNID Type	Interface Status	VlanId Time-out	Vlan-RangeId AccessPortDesc	Inner-VlanId PortDesc	Mac-Addr	VTEP-Ip/ESI
--------------	---------------------	--------------------	--------------------------------	--------------------------	----------	-------------

```

100      ---      ----      -----      0000.1111.0001 1.1.1.1
Remote   -----      ---      -----      -----
100      xe23      -----      2-100 -----      0000.2222.0001 2.2.2.2
Static Local -----      ---      -----      -----
100      ---      ----      -----      b0da.1d10.6496 1.1.1.1
Remote   -----      ---      -----      -----

```

Total number of entries are 3
VTEP2#sh nvo vxlan route-count
VXLAN Active route count information
=====
Max route count : 32768
Active route count: 3

VNID	Total	MACONLY	MACIPv4	MACIPv6
100	3	3	0	0

Total number of entries are 1

VTEP2#sh nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====
VNID Ip-Addr Mac-Addr Type Age-Out Retries-Left

Total number of entries are 0

VTEP2#sh nvo vxlan nd-cache
VXLAN ND-CACHE Information
=====
VNID Ip-Addr Mac-Addr Type Age-Out
Retries-Left

Total number of entries are 0

VTEP2#
VTEP2#
VTEP2#sh nvo vxlan access-if brief

Interface	Inner Vlan	vlan	Ifindex	Vnid	Admin status	Link status
xe23	2	---	500000	100	up	up

Total number of entries are 1
VTEP2#sh nvo vxlan access-if-config
nvo vxlan access-if port-vlan xe23 2-100
map vnid 100
arp-cache disable
nd-cache disable
mac 0000.2222.0001
!

```
VTEP2#sh bgp l2vpn evpn summary
BGP router identifier 2.2.2.2, local AS number 1
BGP table version is 4
1 BGP AS-PATH entries
0 BGP community entries
```

Neighbor PfxRcd	AD	MACIP	V MCAST	AS 4	MsgRcv 1	MsgSen 59	TblVer 57	InQ 3	OutQ 0	Up/Down 00:21:48	State/
1.1.1.1 3	0	2	1	0	0						

Total number of neighbors 1

Total number of Established sessions 1

VTEP2#sh bgp l2vpn evpn

BGP table version is 4, local router ID is 2.2.2.2

Status codes: s suppressed, d damped, h history, a add-path, * valid, > best, i - internal,

l - labeled, S Stale

Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]

1 - Ethernet Auto-discovery Route

2 - MAC/IP Route

3 - Inclusive Multicast Route

4 - Ethernet Segment Route

5 - Prefix Route

Network Encap	Next Hop	Metric	LocPrf	Weight	Path	Peer
RD[1.1.1.1:1]						
*>i [2]:[0]:[100]:[48,0000:1111:0001]:[0]:[100]	1.1.1.1	0	100	0	i 1.1.1.1	VXLAN
*>i [2]:[0]:[100]:[48,b0da:1d10:6496]:[0]:[100]	1.1.1.1	0	100	0	i 1.1.1.1	VXLAN
*>i [3]:[100]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1	VXLAN
RD[2.2.2.2:1] VRF[L2VRF1]:						
* i [2]:[0]:[100]:[48,0000:1111:0001]:[0]:[100]	1.1.1.1	0	100	0	i 1.1.1.1	VXLAN
*> [2]:[0]:[100]:[48,0000:2222:0001]:[0]:[100]	2.2.2.2	0	100	32768	i -----	
VXLAN						
* i [2]:[0]:[100]:[48,b0da:1d10:6496]:[0]:[100]	1.1.1.1	0	100	0	i 1.1.1.1	VXLAN
* i [3]:[100]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1	VXLAN
*> [3]:[100]:[32,2.2.2.2]	2.2.2.2	0	100	32768	i -----	
VXLAN						

Total number of prefixes 8
VTEP2#

CHAPTER 5 EVPN-VXLAN Hybrid Port Support

This chapter contains the configurations for EVPN-VXLAN Hybrid Port Support.

Overview

This feature is to map VxLAN untagged and tagged (port+vlan) access interfaces on the same parent interface (Physical, Dynamic and Static LAG). It also supports the Bridge vlan and vxlan untagged access on the same parent interface.

Topology

The procedures in this section use the topology in [Figure 5-9](#)




Figure 5-9: EVPN-VxLAN hybrid port

VXLAN-EVPN Hybrid Port Configuration

VTEP1

Interface and Loopback Configuration

(config) #interface xe9	Enter Interface mode for xe9
(config-if) #switchport	Make it L2 interface
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 1.1.1.1/32 secondary	Configure loopback ip address as 1.1.1.1 for VTEP1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe8	Enter Interface mode for xe8
(config-if) #ip address 10.10.10.1/24	Configure IP address as 10.10.10.1 on network side of Spine1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe31	Enter Interface mode for xe31
(config-if) #ip address 20.20.20.1/24	Configure IP address as 20.20.20.1 on network side of Spine2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

OSPF Configuration

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo ip address)
(config-router) #network 1.1.1.1/32 area 0.0.0.0	Add 1.1.1.1 (lo IP address) network into area 0
(config-router) #network 10.10.10.0/24 area 0.0.0.0	Add 10.10.10.0 (Spine1) network into area 0
(config-router) #network 20.20.20.0/24 area 0.0.0.0	Add 20.20.20.0 (Spine2) network into area 0
(config-router) #bfd all-interfaces	Enabling BFD on all OSPF interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

BGP Configuration

(config) #router bgp 500	Enter into Router BGP mode
(config-router) #bgp router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo IP address)
(config-router) #neighbor 2.2.2.2 remote-as 500	Specify a VTEP2 loopback IP address and remote-as defined 500
(config-router) #neighbor 2.2.2.2 update-source lo	Configure update as loopback for VTEP2
(config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2
(config-router) #neighbor 3.3.3.3 remote-as 500	Specify a VTEP3 loopback IP address and remote-as defined 500
(config-router) #neighbor 3.3.3.3 update-source lo	Configure update as loopback for VTEP3
(config-router) #neighbor 3.3.3.3 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP3
(config-router) #address-family ipv4 unicast	Enter into ipv4 unicast address family mode
(config-router-af) #network 1.1.1.1/32	Advertise loopback network into BGP for VTEP ID reachability
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2 (VTEP2) into ipv4 unicast address family mode
(config-router-af) #neighbor 3.3.3.3 activate	Activate 3.3.3.3 (VTEP2) into ipv4 unicast address family mode
(config-router-af) #exit-address-family	Exit from ipv4 unicast address family mode
(config-router) #address-family l2vpn evpn	Enter into L2VPN EVPN address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2 (VTEP2) into L2VPN evpn address family mode
(config-router-af) #neighbor 3.3.3.3 activate	Activate 3.3.3.3 (VTEP3) into L2VPN evpn address family mode
(config-router-af) #exit-address-family	Exit from L2VPN address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Commit the candidate configuration to the running configuration

VRF Configuration

(config) #mac vrf VRF1	Create mac routing/forwarding instance with VRF1 name and enter into VRF mode
(config-vrf) #rd 1.1.1.1:11	Assign RD value
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for VRF1
(config-vrf) #exit	Exit from VRF mode
(config) #commit	Commit the candidate configuration to the running configuration

VxLAN Configuration

(config) #nvo vxlan enable	Enable VxLAN
(config) #nvo vxlan vtep-ip-global 1.1.1.1	Configure Source VTEP-IP-global configuration
(config) #nvo vxlan id 10 ingress-replication inner-vid-disabled	Configure VxLAN Network identifier with/without inner-VID-disabled configure and enter into VxLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) #vni-name VNI-RED	Configure VNI-name as VNI-RED
(config-nvo) #exit	Exit from VxLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 20 ingress-replication inner-vid-disabled	Configure VxLAN Network identifier with/without inner-VID-disabled configure and enter into VxLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) #vni-name VNI-BLUE	Configure VNI-name as VNI-BLUE
(config-nvo) #exit	Exit from VxLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan access-if port xe9	Enable port mapping i.e. access port to the physical interface
(config-nvo-acc-if) #map vni-name VNI-RED	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan xe9 1001	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) – physical interface
(config-nvo-acc-if) #map vni-name VNI-RED	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan xe9 2001	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) – physical interface
(config-nvo-acc-if) #map vni-name VNI-BLUE	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode

(config) #commit	Commit the candidate configuration to the running configuration
(config) #exit	Exit from configuration mode

VTEP2

Interface and Loopback Configuration

(config) #interface xe3	Enter Interface mode for xe3
(config-if) #switchport	Make it L2 interface
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 2.2.2.2/32 secondary	Configure loopback IP address as 2.2.2.2 for VTEP2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe21	Enter Interface mode for xe21
(config-if) #ip address 30.30.30.1/24	Configure IP address as 30.30.30.1 on network side of Spine1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce53	Enter Interface mode for ce53
(config-if) #ip address 40.40.40.1/24	Configure IP address as 40.40.40.1 on network side of Spine2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

OSPF Configuration

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 2.2.2.2	Configure router-id as 2.2.2.2 (lo IP address)
(config-router) #network 2.2.2.2/32 area 0.0.0.0	Add 2.2.2.2 (lo IP address) network into area 0
(config-router) #network 30.30.30.0/24 area 0.0.0.0	Add 30.30.30.0 (Spine1) network into area 0
(config-router) #network 40.40.40.0/24 area 0.0.0.0	Add 40.40.40.0 (Spine2) network into area 0
(config-router) #bfd all-interfaces	Enabling BFD on all OSPF interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

BGP Configuration

(config) #router bgp 500	Enter into Router BGP mode
(config-router) #bgp router-id 2.2.2.2	Configure router-id as 2.2.2.2 (lo IP address)
(config-router) #neighbor 1.1.1.1 remote-as 500	Specify a VTEP1 loopback IP address and remote-as defined 500
(config-router) #neighbor 1.1.1.1 update-source lo	Configure update as loopback for VTEP1
(config-router) #neighbor 1.1.1.1 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP1
(config-router) #neighbor 3.3.3.3 remote-as 500	Specify a VTEP3 loopback IP address and remote-as defined 500
(config-router) #neighbor 3.3.3.3 update-source lo	Configure update as loopback for VTEP3
(config-router) #neighbor 3.3.3.3 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP3
(config-router) #address-family ipv4 unicast	Enter into ipv4 unicast address family mode
(config-router-af) #network 2.2.2.2/32	Advertise loopback network into BGP for VTEP ID reachability
(config-router-af) #neighbor 1.1.1.1 activate	Activate 1.1.1.1 (VTEP2) into ipv4 unicast address family mode
(config-router-af) #neighbor 3.3.3.3 activate	Activate 3.3.3.3 (VTEP2) into ipv4 unicast address family mode
(config-router-af) #exit-address-family	Exit from ipv4 unicast address family mode
(config-router) #address-family l2vpn evpn	Enter into L2VPN EVPN address family mode
(config-router-af) #neighbor 1.1.1.1 activate	Activate 1.1.1.1(VTEP1) into L2VPN evpn address family mode
(config-router-af) #neighbor 3.3.3.3 activate	Activate 3.3.3.3(VTEP3) into L2VPN evpn address family mode
(config-router-af) #exit-address-family	Exit from L2VPN address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Commit the candidate configuration to the running configuration

VRF Configuration

(config) # mac vrf VRF1	Create mac routing/forwarding instance with VRF1 name and enter into VRF mode
(config-vrf) #rd 2.2.2.2:11	Assign RD value
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for VRF1
(config-vrf) #exit	Exit from VRF mode
(config) #commit	Commit the candidate configuration to the running configuration

VxLAN Configuration

(config) #nvo vxlan enable	Enable VxLAN
(config) #nvo vxlan vtep-ip-global 2.2.2.2	Configure Source VTEP-IP-global configuration
(config) #nvo vxlan id 10 ingress-replication inner-vid-disabled	Configure VxLAN Network identifier with/without inner-VID-disabled configure and enter into VxLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) #vni-name VNI-RED	Configure VNI-name as VNI-RED
(config-nvo) #exit	Exit from VxLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 20 ingress-replication inner-vid-disabled	Configure VxLAN Network identifier with/without inner-VID-disabled configure and enter into VxLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) #vni-name VNI-BLUE	Configure VNI-name as VNI-BLUE
(config-nvo) #exit	Exit from VxLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan access-if port xe3	Enable port mapping i.e. access port to physical interface
(config-nvo-acc-if) #map vni-name VNI-RED	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan xe3 1002	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) – physical interface
(config-nvo-acc-if) #map vni-name VNI-RED	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan xe3 2001	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) – physical interface
(config-nvo-acc-if) #map vni-name VNI-BLUE	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode
(config) #commit	Commit the candidate configuration to the running configuration
(config) #exit	Exit from configuration mode

VTEP3

Interface and loopback configuration

#configure terminal	Enter Configure mode.
(config) #interface xe48	Enter Interface mode for xe48 (SH3)
(config-if) #switchport	Make it L2 interface
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 3.3.3.3/32 secondary	Configure loopback IP address as 3.3.3.3 for VTEP3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe18	Enter Interface mode for xe18
(config-if) #ip address 50.50.50.1/24	Configure IP address as 50.50.50.1 on network side of Spine1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe19	Enter Interface mode for xe19
(config-if) #ip address 60.60.60.1/24	Configure IP address as 60.60.60.1 on network side of Spine2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

OSPF Configuration

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 3.3.3.3	Configure router-ID as 3.3.3.3 (lo IP address)
(config-router) #network 3.3.3.3/32 area 0.0.0.0	Add 3.3.3.3 (lo IP address) network into area 0
(config-router) #network 50.50.50.0/24 area 0.0.0.0	Add 50.50.50.0 (Spine1) network into area 0
(config-router) #network 60.60.60.0/24 area 0.0.0.0	Add 60.60.60.0 (Spine2) network into area 0
(config-router) #bfd all-interfaces	Enabling BFD on all OSPF interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

BGP Configuration

(config) #router bgp 500	Enter into Router BGP mode
(config-router) #bgp router-id 3.3.3.3	Configure router-ID as 3.3.3.3 (lo ip address)
(config-router) #neighbor 1.1.1.1 remote-as 500	Specify a VTEP1 loopback IP address and remote-as defined 500
(config-router) #neighbor 1.1.1.1 update-source lo	Configure update as loopback for VTEP1
(config-router) #neighbor 1.1.1.1 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP1
(config-router) #neighbor 2.2.2.2 remote-as 500	Specify a VTEP2 loopback IP address and remote-as defined 500
(config-router) #neighbor 2.2.2.2 update-source lo	Configure update as loopback for VTEP2
(config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP3
(config-router) #address-family ipv4 unicast	Enter into ipv4 unicast address family mode
(config-router-af) #network 3.3.3.3/32	Advertise loopback network into BGP for VTEP ID reachability
(config-router-af) #neighbor 1.1.1.1 activate	Activate 1.1.1.1 (VTEP2) into ipv4 unicast address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2 (VTEP2) into ipv4 unicast address family mode
(config-router-af) #exit-address-family	Exit from ipv4 unicast address family mode
(config-router) #address-family l2vpn evpn	Enter into L2VPN EVPN address family mode
(config-router-af) #neighbor 1.1.1.1 activate	Activate 1.1.1.1 (VTEP1) into L2VPN evpn address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2 (VTEP2) into L2VPN evpn address family mode
(config-router-af) #exit-address-family	Exit from L2VPN address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Commit the candidate configuration to the running configuration

VRF Configuration

(config) # mac vrf VRF1	Create MAC routing/forwarding instance with VRF1 name and enter into VRF mode
(config-vrf) #rd 3.3.3.3:11	Assign RD value
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for VRF1
(config-vrf) #exit	Exit from VRF mode
(config) #commit	Commit the candidate configuration to the running configuration

VxLAN Configuration

(config) #nvo vxlan enable	Enable VxLAN
(config) #nvo vxlan vtep-ip-global 3.3.3.3	Configure Source VTEP-IP-global configuration
(config) #nvo vxlan id 10 ingress-replication inner-vid-disabled	Configure VxLAN Network identifier with/without inner-VID-disabled configure and enter into VxLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) #vni-name VNI-RED	Configure VNI-name as VNI-RED
(config-nvo) #exit	Exit from VxLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 20 ingress-replication inner-vid-disabled	Configure VxLAN Network identifier with/without inner-VID-disabled configure and enter into VxLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) #vni-name VNI-BLUE	Configure VNI-name as VNI-BLUE
(config-nvo) #exit	Exit from VxLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan access-if port xe48	Enable port mapping i.e. access port to physical interface
(config-nvo-acc-if) #map vni-name VNI-RED	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan xe48 1001	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) – physical interface
(config-nvo-acc-if) #map vni-name VNI-RED	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan xe48 2001	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) – physical interface
(config-nvo-acc-if) #map vni-name VNI-BLUE	Map VxLAN Identified to access-port for VxLAN
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode

(config) #commit	Commit the candidate configuration to the running configuration
(config) #exit	Exit from configuration mode

Spine 1

Spine node where all VTEPs are connected

Interface and Loopback Configuration

#configure terminal	Enter Configure mode.
(config) #qos enable	Enabling QoS
(config) #interface lo	Enter Interface mode for lo
(config-if)#ip address 11.11.11.11/32 secondary	Configure loopback IP address as 11.11.11.11 for Spine1
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) #interface xe8	Enter Interface mode for xe8
(config-if)#ip address 10.10.10.2/24	Configure IP address as 10.10.10.2 on network side of VTEP1
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) #interface xe1	Enter Interface mode for xe1
(config-if)#ip address 30.30.30.2/24	Configure IP address as 30.30.30.2 on network side of VTEP2
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) #interface xe18	Enter Interface mode for xe18
(config-if)#ip address 50.50.50.2/24	Configure IP address as 50.50.50.2 on network side of VTEP3
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

OSPF configuration

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 11.11.11.11	Configure router-ID as 11.11.11.11 (lo IP address)
(config-router) #network 11.11.11.11/32 area 0.0.0.0	Add 11.11.11.11 (lo IP address) network into area 0
(config-router) #network 10.10.10.0/24 area 0.0.0.0	Add 10.10.10.0 (VTEP1) network into area 0
(config-router) #network 30.30.30.0/24 area 0.0.0.0	Add 30.30.30.0 (VTEP2) network into area 0
(config-router) #network 50.50.50.0/24 area 0.0.0.0	Add 50.50.50.0 (VTEP3) network into area 0

(config-router) #bfd all-interfaces	Enabling BFD on all OSPF interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

Spine 2

Spine node where all VTEPs are connected

Interface and loopback configuration

(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 22.22.22.22/32 secondary	Configure loopback IP address as 22.22.22.22 for Spine2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe5	Enter Interface mode for xe5
(config-if) #ip address 20.20.20.2/24	Configure IP address as 20.20.20.2 on network side of VTEP1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce0	Enter Interface mode for ce0
(config-if) #ip address 40.40.40.2/24	Configure IP address as 40.40.40.2 on network side of VTEP2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe19	Enter Interface mode for xe19
(config-if) #ip address 60.60.60.2/24	Configure IP address as 60.60.60.2 on network side of VTEP3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

OSPF configuration

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 22.22.22.22	Configure router-id as 11.11.11.11 (lo IP address)
(config-router) #network 22.22.22.22/32 area 0.0.0.0	Add 22.22.22.22 (lo IP address) network into area 0
(config-router) #network 20.20.20.0/24 area 0.0.0.0	Add 20.20.20.0 (VTEP1) network into area 0
(config-router) #network 40.40.40.0/24 area 0.0.0.0	Add 40.40.40.0 (VTEP2) network into area 0
(config-router) #network 60.60.60.0/24 area 0.0.0.0	Add 60.60.60.0 (VTEP3) network into area 0
(config-router) #bfd all-interfaces	Enabling BFD on all OSPF interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to the running configuration

Validation

VTEP1

```
VTEP1#sh nvo vxlan
VXLAN Information
=====
```

Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNIID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-
Status	Src-Addr	Dst-Addr					
10	VNI-RED	L2	NW	---	----	----	-
---	1.1.1.1		3.3.3.3				
10	VNI-RED	L2	NW	---	----	----	-
---	1.1.1.1		2.2.2.2				
10	VNI-RED	--	AC	xe9	--- Single Homed Port ---	0	--
---	-----	----					
10	VNI-RED	--	AC	xe9	--- Single Homed Port ---	1001	--
---	-----	----					
20	VNI-BLUE	L2	NW	---	----	----	-
---	1.1.1.1		3.3.3.3				
20	VNI-BLUE	L2	NW	---	----	----	-
---	1.1.1.1		2.2.2.2				
20	VNI-BLUE	--	AC	xe9	--- Single Homed Port ---	2001	--
---	-----	----					

Total number of entries are 7

```
VTEP1#sh nvo vxlan access-if brief
```

Interface	Vlan	Inner vlan	Ifindex	Vnid	Admin status	Link status
xe57	---	---	500000	10	up	up
xe57	1001	---	500001	10	up	up
xe57	2001	---	500002	20	up	up

Total number of entries are 3

```
VTEP1#show bgp 12vpn evpn summary
BGP router identifier 1.1.1.1, local AS number 500
BGP table version is 4
1 BGP AS-PATH entries
0 BGP community entries
```

Neighbor PfxRcd	AD	MACIP	V MCAST	AS ESI	MsgRcv PREFIX-ROUTE	MsgSen	TblVer	InQ	OutQ	Up/Down	State/
2.2.2.2 2 0	0	0	4 2	500 0	53 0	54	3	0	0	00:20:58	
3.3.3.3 2 0	0	0	4 2	500 0	53 0	53	3	0	0	00:20:58	

Total number of neighbors 2

Total number of Established sessions 2

```
VTEP1#show nvo vxlan tunnel
VXLAN Network tunnel Entries
```

Source	Destination	Status	Up/Down	Update
1.1.1.1	3.3.3.3	Installed	00:10:44	00:10:44
1.1.1.1	2.2.2.2	Installed	00:10:58	00:10:58

Total number of entries are 2

```
VTEP1#show bgp 12vpn evpn
```

BGP table version is 4, local router ID is 1.1.1.1

Status codes: s suppressed, d damped, h history, a add-path, * valid, > best, i - internal,

l - labeled, S Stale

Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route information]

1 - Ethernet Auto-discovery Route

2 - MAC/IP Route

3 - Inclusive Multicast Route
 4 - Ethernet Segment Route
 5 - Prefix Route

Network Encap	Next Hop	Metric	LocPrf	Weight	Path	Peer
RD[1.1.1.1:1] VRF[VRF1]:						
*> [3]:[10]:[32,1.1.1.1]	1.1.1.1	0	100	32768	i	-----
VXLAN						
* i[3]:[10]:[32,2.2.2.2]	2.2.2.2	0	100	0	i	2.2.2.2
* i[3]:[10]:[32,3.3.3.3]	3.3.3.3	0	100	0	i	3.3.3.3
*> [3]:[20]:[32,1.1.1.1]	1.1.1.1	0	100	32768	i	-----
VXLAN						
* i[3]:[20]:[32,2.2.2.2]	2.2.2.2	0	100	0	i	2.2.2.2
* i[3]:[20]:[32,3.3.3.3]	3.3.3.3	0	100	0	i	3.3.3.3
RD[2.2.2.2:1]						
*>i[3]:[10]:[32,2.2.2.2]	2.2.2.2	0	100	0	i	2.2.2.2
*>i[3]:[20]:[32,2.2.2.2]	2.2.2.2	0	100	0	i	2.2.2.2
RD[3.3.3.3:1]						
*>i[3]:[10]:[32,3.3.3.3]	3.3.3.3	0	100	0	i	3.3.3.3
*>i[3]:[20]:[32,3.3.3.3]	3.3.3.3	0	100	0	i	3.3.3.3

Total number of prefixes 10

VTEP2

VTEP2#sh nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port
 AC - Access Port
 (u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-
Status	Src-Addr		Dst-Addr				

10	VNI-RED	L2	NW	----	----	----	----
---	2.2.2.2		1.1.1.1				-
10	VNI-RED	L2	NW	----	----	----	----
---	2.2.2.2		3.3.3.3				-
10	VNI-RED	--	AC	xe8	--- Single Homed Port ---	0	-
---	-----						
10	VNI-RED	--	AC	xe8	--- Single Homed Port ---	1001	-
---	-----						
20	VNI-BLUE	L2	NW	----	----	----	----
---	2.2.2.2		1.1.1.1				-
20	VNI-BLUE	L2	NW	----	----	----	----
---	2.2.2.2		3.3.3.3				-
20	VNI-BLUE	--	AC	xe8	--- Single Homed Port ---	2001	-
---	-----						

Total number of entries are 7

VTEP2#sh nvo vxlan access-if brief

Interface	Inner				Admin status	Link status
	Vlan	vlan	Ifindex	Vnid		
<hr/>						
xe8	---	---	500000	10	up	up
xe8	1001	---	500001	10	up	up
xe8	2001	---	500002	20	up	up

Total number of entries are 3

VTEP2#show bgp l2vpn evpn summary

BGP router identifier 2.2.2.2, local AS number 500

BGP table version is 4

1 BGP AS-PATH entries

0 BGP community entries

Neighbor	V	AS	MsgRcv	MsgSen	TblVer	InQ	OutQ	Up/Down	State/
PfxRcd	AD	MACIP	MCAST	ESI	PREFIX-ROUTE				
1.1.1.1		4	500	53	53	3	0	0	00:20:56
2 0	0	2	0	0					
3.3.3.3		4	500	51	54	3	0	0	00:20:56
2 0	0	2	0	0					

Total number of neighbors 2

Total number of Established sessions 2

VTEP2#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
<hr/>				
2.2.2.2	1.1.1.1	Installed	00:11:01	00:11:01

2.2.2.2	3.3.3.3	Installed	00:10:47	00:10:47
---------	---------	-----------	----------	----------

Total number of entries are 2

VTEP2#show bgp l2vpn evpn

BGP table version is 4, local router ID is 2.2.2.2

Status codes: s suppressed, d damped, h history, a add-path, * valid, > best, i - internal,

l - labeled, S Stale

Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]

1 - Ethernet Auto-discovery Route

2 - MAC/IP Route

3 - Inclusive Multicast Route

4 - Ethernet Segment Route

5 - Prefix Route

Network Encap	Next Hop	Metric	LocPrf	Weight	Path	Peer
RD[1.1.1.1:1]						
*>i [3]:[10]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1	VXLAN
*>i [3]:[20]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1	VXLAN
RD[2.2.2.2:1] VRF[VRF1]:						
* i [3]:[10]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1	VXLAN
*> [3]:[10]:[32,2.2.2.2]	2.2.2.2	0	100	32768	i -----	
VXLAN						
* i [3]:[10]:[32,3.3.3.3]	3.3.3.3	0	100	0	i 3.3.3.3	VXLAN
* i [3]:[20]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1	VXLAN
*> [3]:[20]:[32,2.2.2.2]	2.2.2.2	0	100	32768	i -----	
VXLAN						
* i [3]:[20]:[32,3.3.3.3]	3.3.3.3	0	100	0	i 3.3.3.3	VXLAN
RD[3.3.3.3:1]						
*>i [3]:[10]:[32,3.3.3.3]	3.3.3.3	0	100	0	i 3.3.3.3	VXLAN
*>i [3]:[20]:[32,3.3.3.3]	3.3.3.3	0	100	0	i 3.3.3.3	VXLAN

Total number of prefixes 10

VTEP3

VTEP3#sh nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port
 AC - Access Port
 (u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-
	Status	Src-Addr		Dst-Addr			
10	VNI-RED	L2	NW	---	---	---	-
---	3.3.3.3		2.2.2.2				
10	VNI-RED	L2	NW	---	---	---	-
---	3.3.3.3		1.1.1.1				
10	VNI-RED	--	AC	ce13/1	--- Single Homed Port ---	0	-
---	---		---				
10	VNI-RED	--	AC	ce13/1	--- Single Homed Port ---	1001	-
---	---		---				
20	VNI-BLUE	L2	NW	---	---	---	-
---	3.3.3.3		2.2.2.2				
20	VNI-BLUE	L2	NW	---	---	---	-
---	3.3.3.3		1.1.1.1				
20	VNI-BLUE	--	AC	ce13/1	--- Single Homed Port ---	2001	-
---	---		---				

Total number of entries are 7

VTEP3#sh nvo vxlan access-if brief

Interface	Inner				Admin status	Link status
	Vlan	vlan	Iffindex	Vnid		
<hr/>						
ce13/1	---	---	500000	10	up	up
ce13/1	1001	---	500001	10	up	up
ce13/1	2001	---	500002	20	up	up

Total number of entries are 3

VTEP3#show bgp 12vpn evpn summary

BGP router identifier 3.3.3.3, local AS number 500

BGP table version is 3

1 BGP AS-PATH entries

0 BGP community entries

Neighbor	V	AS	MsgRcv	MsgSen	TblVer	InQ	OutQ	Up/Down	State/
PfxRcd	AD	MACIP	MCAST	ESI	PREFIX-ROUTE				
1.1.1.1		4	500	52	52	3	0	00:20:37	
2 0	0	2	0	0					
2.2.2.2		4	500	52	51	3	0	00:20:37	
2 0	0	2	0	0					

Total number of neighbors 2

Total number of Established sessions 2

```
VTEP3#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination      Status       Up/Down      Update
=====
3.3.3.3         2.2.2.2        Installed    00:10:50    00:10:50
3.3.3.3         1.1.1.1        Installed    00:10:50    00:10:50
```

Total number of entries are 2

```
VTEP3#show bgp 12vpn evpn
BGP table version is 3, local router ID is 3.3.3.3
Status codes: s suppressed, d damped, h history, a add-path, * valid, > best, i -
internal,
l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete
```

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]

1 - Ethernet Auto-discovery Route
 2 - MAC/IP Route
 3 - Inclusive Multicast Route
 4 - Ethernet Segment Route
 5 - Prefix Route

Network Encap	Next Hop	Metric	LocPrf	Weight	Path	Peer
RD[1.1.1.1:1]						
*>i [3]:[10]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1	VXLAN
*>i [3]:[20]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1	VXLAN
RD[2.2.2.2:1]						
*>i [3]:[10]:[32,2.2.2.2]	2.2.2.2	0	100	0	i 2.2.2.2	VXLAN
*>i [3]:[20]:[32,2.2.2.2]	2.2.2.2	0	100	0	i 2.2.2.2	VXLAN
RD[3.3.3.3:1] VRF[VRF1]:						
* i [3]:[10]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1	VXLAN
* i [3]:[10]:[32,2.2.2.2]	2.2.2.2	0	100	0	i 2.2.2.2	VXLAN
*> [3]:[10]:[32,3.3.3.3]	3.3.3.3	0	100	32768	i -----	
VXLAN						
* i [3]:[20]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1	VXLAN

```
* i [3]:[20]:[32,2.2.2.2]
      2.2.2.2          0       100      0   i 2.2.2.2      VXLAN
*> [3]:[20]:[32,3.3.3.3]
      3.3.3.3          0       100      32768 i -----
VXLAN
```

Total number of prefixes 10

CHAPTER 6 VXLAN Quality of Service Configuration

This chapter contains the configurations for VXLAN Quality of Service (QoS) .

Overview

VXLAN enables multiple tenants to operate in a data center. Each tenant is assigned a priority group to prioritize their traffic. Cloud carriers want to use quality of service to differentiate different applications.

Data center networks are being increasingly used by telecommunications operators as well as by enterprises. Currently these networks are organized as one large Layer 2 network in a single building. In some cases such a network is extended geographically using Virtual Local Area Network (VLAN) technologies as an even larger Layer 2 network connecting the virtual machines (VM), each with its own MAC address.

Multiple tenants might want their own isolated network domain. In a data center hosting multiple tenants, each tenant may independently assign MAC addresses and VLAN IDs and this might lead to duplication.

Cloud carriers wish to categorize the traffic based on the application such as voice, video, etc. Based on the type of the application different traffic classes may be identified and different priority levels can be assigned to each. To do so, quality of service marking is needed in VXLAN.

This chapter shows how to mark packet headers with the VXLAN tunnel end point (VTEP) when the frames are introduced by the virtual machines. The (re)marking /setting of QoS field DSCP/TOS in the VXLAN IP header is done with the two modes which are set globally.

Topology




Figure 6-10: VXLAN QoS

COS-DSCP

RTR1/VTEP1

#configure terminal	Enter Configure mode.
(config) #mac vrf vrf1	Create mac routing/forwarding instance with vrf1 name and enter into vrf mode

(config-vrf) #rd 1.1.1.1:11	Assign RD value
(config-vrf) #route-target both 10.10.10.10:100	Assign route-target value for import/export
(config-vrf) #exit	Exit from vrf mode
(config) #qos enable	Enable qos
(config) #qos profile cos-to-queue COS-QUE	Create qos profile for mapping traffic towards tunnel from access-if.
(config-ingress-cos-map) #cos 2 queue 3	Configure particular COS value to the queue value for configured profile.
(config-ingress-cos-map) #exit	Exit from qos profile config mode
(config) #qos profile queue-color-to-dscp QUE-DSCP	Create qos profile for attaching in vxlan tunnel egress.
(config-egress-dscp-map) #queue 3 dscp 16	Configure particular queue value to the dscp value for configured profile.
(config-egress-dscp-encap-map) #exit	Exit from qos profile config mode
(config) #interface po2	Create a port channel po2
(config-if) #switchport	Configure port as switchport
(config-if) #load-interval 30	Set load-interval
(config-if) #interface po24	Create a port channel po24
(config-if) #load-interval 30	Configure port as switchport
(config-if) #ip address 24.1.1.1/30	Set load-interval
(config-if) #interface lo	Enter in to loopback interface
(config-if) #ip address 1.1.1.1/32 secondary	Configure ip address
(config-if) #interface xe1	Enter in to interface mode
(config-if) #channel-group 2 mode active	Map to channel-group
(config-if) #interface xe2	Enter in to interface mode
(config-if) #channel-group 2 mode active	Map to channel-group
(config-if) #interface xe14	Enter in to interface mode
(config-if) #channel-group 24 mode ac-tive	Map to channel-group
(config-if) #interface xe15	Enter in to interface mode
(config-if) #channel-group 24 mode ac-tive	Map to channel-group
(config-if) #router ospf 1	Create ospf instance
(config-router) #ospf router-id 1.1.1.1	Configure ospf router-id
(config-router) #network 1.1.1.1/32 area 0.0.0.0	Configure loopback network address in to ospf
(config-router) #network 24.1.1.0/30 area 0.0.0.0	Configure network address in to ospf
(config-router) #router bgp 100	Enter into Router BGP mode
(config-router) #neighbor 6.6.6.6 re-mote-as 100	Specify a neighbor router with peer ip address and remote-as defined
(config-router) #neighbor 6.6.6.6 up-date-source lo	Specify the neighbor to use loopback address as source
(config-router) #address-family l2vpn evpn	Enter into l2vpn evpn address-family
(config-router-af) #neighbor 6.6.6.6 activate	Activate the neighbor to address-family

(config-router) #nvo vxlan vtep-ip-global 1.1.1.1	Configure Source vtep-ip-global configuration
(config) #nvo vxlan tunnel qos-map-mode cos-dscp egress QUE-DSCP	Configure the mapping qos profile in to vxlan tunnel egress
(config) #nvo vxlan id 1 in-gress-replication inner-vid-disabled	Create vnid 1 and disable inner-vid
(config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) #nvo vxlan access-if port-vlan po2 1001	Create vxlan access-if with vlan 1001
(config-nvo-acc-if) #no shutdown	No shut the vxlan access-if
(config-nvo-acc-if) #map vnid 1	Map vnid to the vxlan access-if
(config-nvo-acc-if) #map qos-profile cos-to-queue COS-QUE	Map qos profile for vxlan access-if ingress traffic from CE
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode.
(config) #commit	Commit the candidate configuration to the running configuration

R2

#configure terminal	Enter Configure mode.
(config) #interface po24	Create port channel
(config-if) #load-interval 30	Set load-interval
(config-if) #ip address 24.1.1.2/30	Assign ip address
(config-if) #interface po46	Create port channel
(config-if) #load-interval 30	Set load-interval
(config-if) #ip address 46.1.1.1/30	Assign ip address
(config-if) #interface lo	Enter in to loopback interface
(config-if) #ip address 4.4.4.4/32 sec-ondary	Assign secondary ip address
(config-if) #interface xe4	Enter into interface mode
(config-if) #channel-group 46 mode active	Map port channel to the interface
(config-if) #interface xe5	Enter into interface mode
(config-if) #channel-group 46 mode active	Map port channel to the interface
(config-if) #interface xe14	Enter into interface mode
(config-if) #channel-group 24 mode active	Map port channel to the interface
(config-if) #interface xe15	Enter into interface mode
(config-if) #channel-group 24 mode active	Map port channel to the interface
(config-if) #router ospf 1	Create ospf instance
(config-router) #ospf router-id 4.4.4.4	Configure ospf router-id
(config-router) #network 4.4.4.4/32 area 0.0.0.0	Configure ospf network address with respective area
(config-router) #network 24.1.1.0/30 area 0.0.0.0	Configure ospf network address with respective area

(config-router) #network 46.1.1.0/30 area 0.0.0.0	Configure ospf network address with respective area
(config-router) #exit	Exit from router mode.
(config) #commit	Commit the candidate configuration to the running configuration

RTR3/VTEP2

#configure terminal	Enter Configuration mode
(config) #mac vrf vrf1	Create mac routing/forwarding instance with vrf1 name and enter into vrf mode
(config-vrf) #rd 6.6.6.6:11	Assign RD value
(config-vrf) #route-target both 10.10.10.10:100	Assign route-target value for import/export
(config-vrf) #exit	Exit from vrf mode
(config) #qos enable	Enable QOS
(config) #qos statistics	Enable QOS statistics
(config) #qos profile queue-color-to-cos QUE-COS	Create qos profile for mapping incoming traffic from tunnel to access-if.
(config-egress-cos-map) #queue 4 cos 5	Configure particular queue value to the cos value for configured profile.
(config-egress-cos-map) #qos profile dscp-to-queue DSCP-QUE	Create qos profile for attaching in vxlan tunnel ingress.
(config-ingress-dscp-map) #dscp 16 queue 4	Configure particular dscp value to the queue value for configured profile.
(config-egress-dscp-map) #interface po46	Create port channel
(config-if) #load-interval 30	Set load interval
(config-if) #ip address 46.1.1.2/30	Assign ip address
(config-if) #interface lo	Enter into loopback interface
(config-if) #ip address 6.6.6.6/32 secondary	Assign secondary ip address
(config-if) #interface xe4	Enter into interface mode
(config-if) #channel-group 46 mode active	Map channel group into the interface
(config-if) #interface xe5	Enter into interface mode
(config-if) #channel-group 46 mode active	Map channel group into the interface
(config-if) #interface xe15	Enter into interface mode
(config-if) #switchport	Make interface as L2 port
(config-if) #load-interval 30	Set load interval
(config-if) #router ospf 1	Create ospf instance
(config-router) #ospf router-id 6.6.6.6	Configure ospf router-id
(config-router) #network 6.6.6.6/32 area 0.0.0.0	Configure ospf network address with respective area
(config-router) #network 46.1.1.0/30 area 0.0.0.0	Configure ospf network address with respective area
(config-router) #router bgp 100	Enter into Router BGP mode

(config-router) #neighbor 1.1.1.1 re-mote-as 100	Specify a neighbor router with peer ip address and remote-as defined
(config-router) #neighbor 1.1.1.1 up-date-source lo	Specify the neighbor to use loopback address as source
(config-router) #address-family l2vpn evpn	Enter into l2vpn evpn address-family
(config-router-af) #neighbor 1.1.1.1 activate	Activate the neighbor to address-family
(config) #nvo vxlan vtep-ip-global 6.6.6.6	Configure Source vtep-ip-global configuration
(config) #nvo vxlan tunnel qos-map-mode cos-dscp ingress DSCP-QUE	Configure the mapping qos profile in to vxlan tunnel ingress
(config) #nvo vxlan id 1 in-gress-replication inner-vid-disabled	Create vnid 1 and disable inner-vid
(config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) #nvo vxlan access-if port-vlan xe15 1000	Create vxlan access-if with vlan 1000
(config-nvo-acc-if) #no shutdown	No shut the vxlan access-if
(config-nvo-acc-if) #map vnid 1	Map vnid to the vxlan access-if
(config-nvo-acc-if) #map qos-profile queue-color-to-cos QUE-COS	Map qos profile for vxlan access-if egress traffic to CE
(config-nvo-acc-if) #exit	Exit from VxLAN access-interface mode and enter into configuration mode
(config) #commit	Commit the candidate configuration to the running configuration

Validation

As per the QoS configuration, when L2 traffic with cos value 2 sent to VTEP1 access-if, the packets forwarded to queue 3 and packets in queue 3 are mapped with overlay dscp value 16 while egress out of tunnel. At VTEP2, when packets with overlay dscp value 16 ingresses at tunnel, it is forwarded to queue 4 and packets of queue 4 are remarked with cos value 5.

RTR1/VTEP1

```
VTEP1#sh run nvo vxlan
!
nvo vxlan enable
!
nvo vxlan vtep-ip-global 1.1.1.1
!
nvo vxlan tunnel qos-map-mode cos-dscp egress QUE-DSCP
!
nvo vxlan id 1 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp vrf1
!
nvo vxlan access-if port-vlan po2 1001
  map vnid 1
  map qos-profile cos-to-queue COS-QUE
!
VTEP1#show run qos
qos enable
```

```
!
qos profile cos-to-queue COS-QUE
cos 2 dei all queue 3
!
qos profile queue-color-to-dscp QUE-DSCP
queue 3 color all dscp 16
!

VTEP1#show interface xe14 count queue-stats
E - Egress, I - Ingress, Q-Size is in bytes
+-----+-----+-----+-----+
+-----+
| Queue/Class-map | Q-Size | Tx pkts | Tx bytes | Dropped pkts |
Dropped bytes   |
+-----+-----+-----+-----+
+-----+
q0          (E) 12517376 0           0           0           0
q1          (E) 12517376 0           0           0           0
q2          (E) 12517376 0           0           0           0
q3          (E) 12517376 205284588    188040683524 0           0
q4          (E) 12517376 0           0           0           0
q5          (E) 12517376 0           0           0           0
q6          (E) 12517376 0           0           0           0
q7          (E) 12517376 7518        1007412      0           0

VTEP1#show interface xe15 count queue-stats
E - Egress, I - Ingress, Q-Size is in bytes
+-----+-----+-----+-----+
+-----+
| Queue/Class-map | Q-Size | Tx pkts | Tx bytes | Dropped pkts |
Dropped bytes   |
+-----+-----+-----+-----+
+-----+
q0          (E) 12517376 0           0           0           0
q1          (E) 12517376 0           0           0           0
q2          (E) 12517376 0           0           0           0
q3          (E) 12517376 205624494    188352040168 0           0
q4          (E) 12517376 0           0           0           0
q5          (E) 12517376 0           0           0           0
q6          (E) 12517376 0           0           0           0
q7          (E) 12517376 9006        1136741      0           0

VTEP1#show nvo vxlan
VXLAN Information
=====
Codes: NW - Network Port
       AC - Access Port
       (u) - Untagged

VNID      VNI-Name      VNI-Type Type Interface ESI      VLAN DF-Status
Src-Addr   Dst-Addr
```

```

1      ----      L2      NW      ----      -----
1.1.1.1      6.6.6.6
1      ----      AC      po2      --- Single Homed port ---      1001      -----
-----
```

Total number of entries are 3

VTEP1#show nvo vxlan mac-table

```

=====
===== VXLAN MAC Entries =====
=====
```

VNID Type	Interface Status	VlanId Inner-VlanId	Mac-Addr AccessPortDesc	VTEP-Ip/ESI
1 Dynamic	po2 Local	1001 -----	0000.2000.9991 -----	1.1.1.1

Total number of entries are : 1

VTEP1#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
1.1.1.1	6.6.6.6	Installed	00:11:29	00:11:29

Total number of entries are 2

VTEP1#show qos-profile COS-QUE

profile name: COS-QUE

profile type: cos-to-queue

profile attached to 1 instances

configured mapping:

cos 2 dei all queue 3

Detailed mapping:

INPUT				OUTPUT				INPUT				OUTPUT			
COS	DEI	Queue	Color	COS	DEI	Queue	Color	COS	DEI	Queue	Color	COS	DEI	Queue	Color
0	0	0	green	0	1	0	yellow								
1	0	1	green	1	1	1	yellow								
2	0	3	green	2	1	3	yellow								
3	0	3	green	3	1	3	yellow								
4	0	4	green	4	1	4	yellow								
5	0	5	green	5	1	5	yellow								
6	0	6	green	6	1	6	yellow								

7	0	7	green		7	1	7	yellow
---	---	---	-------	--	---	---	---	--------

```
VTEP1#show qos-profile QUE-DSCP
profile name: QUE-DSCP
profile type: queue-color-to-dscp
profile attached to 1 instances
configured mapping:
queue 3 color all dscp 16
```

Detailed mapping:

INPUT			OUTPUT			INPUT			OUTPUT			INPUT			OUTPUT		
Queue	Color	DSCP	Queue	Color	DSCP	Queue	Color	DSCP	Queue	Color	DSCP	Queue	Color	DSCP	Queue	Color	DSCP
0	green	0	0	yellow	0	0	red	0	1	red	14	2	red	22	3	red	16
1	green	10	1	yellow	12	1	red	14	4	red	38	5	red	40	6	red	48
2	green	18	2	yellow	20	2	red	22	3	red	16	7	red	56	4	red	36
3	green	16	3	yellow	16	5	yellow	40	5	red	40	6	red	48	6	yellow	48
4	green	34	4	yellow	36	4	red	38	7	red	56	7	red	56	0	yellow	0
5	green	40	5	yellow	40	5	red	40	1	red	14	2	red	22	3	red	16
6	green	48	6	yellow	48	6	red	48	2	red	22	3	red	16	4	red	38
7	green	56	7	yellow	56	7	red	56	1	red	14	0	yellow	0	5	yellow	56

RTR2/VTEP2

```
VTEP2#show run nvo vxlan
!
nvo vxlan enable
!
nvo vxlan vtep-ip-global 6.6.6.6
!
nvo vxlan tunnel qos-map-mode cos-dscp ingress DSCP-QUE
!
nvo vxlan id 1 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp vrf1
!
nvo vxlan access-if port-vlan xe15 1000
  map vnid 1
  map qos-profile queue-color-to-cos QUE-COS
!
!
VTEP2#show run qos
qos enable
qos statistics
!
qos profile queue-color-to-cos QUE-COS
  queue 4 color all cos 5
!
qos profile dscp-to-queue DSCP-QUE
```

```
dscp 16 queue 4
```

```
!
```

```
VTEP2#show nvo vxlan mac-table
```

VXLAN MAC Entries					
VNID Type	Interface Status	VlanId Inner-VlanId	Mac-Addr AccessPortDesc	VTEP-Ip/ESI	
1 Dynamic	----- Remote	----- -----	0000.2000.9991 -----	1.1.1.1	

Total number of entries are : 1

```
VTEP2#show nvo vxlan tunnel
```

```
VXLAN Network tunnel Entries
```

Source	Destination	Status	Up/Down	Update
6.6.6.6	1.1.1.1	Installed	00:09:39	00:09:39

Total number of entries are 2

```
VTEP2#show nvo vxlan
```

```
VXLAN Information
```

```
=====
```

Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNID Src-Addr	VNI-Name Dst-Addr	VNI-Type	Type	Interface	ESI	VLAN	DF-Status
1 6.6.6.6	----- 1.1.1.1	L2	NW	-----	-----	-----	-----
1 -----	----- AC	xe15	---	Single Homed port	---	1000	-----
-----	-----	-----	-----	-----	-----	-----	-----

Total number of entries are 3

```
VTEP2#show interface xe15 count queue-stats
```

E - Egress, I - Ingress, Q-Size is in bytes

Queue/Class-map	Q-Size	Tx pkts	Tx bytes	Dropped pkts
Dropped bytes				
q0	(E)	12517376	0	0
				0

q1	(E)	12517376	0	0	0	0
q2	(E)	12517376	0	0	0	0
q3	(E)	12517376	0	0	0	0
q4	(E)	12517376	37895872	36455829826	0	0
q5	(E)	12517376	0	0	0	0
q6	(E)	12517376	0	0	0	0
q7	(E)	12517376	0	0	0	0

```
VTEP2#show qos-profile QUE-COS
profile name: QUE-COS
profile type: queue-color-to-cos
profile attached to 1 instances
configured mapping:
queue 4 color all cos 5
```

Detailed mapping:

INPUT			INPUT			INPUT		
Queue	Color	COS	Queue	Color	COS	Queue	Color	COS
0	green	0	0	yellow	0	0	red	0
1	green	1	1	yellow	1	1	red	1
2	green	2	2	yellow	2	2	red	2
3	green	3	3	yellow	3	3	red	3
4	green	5	4	yellow	5	4	red	5
5	green	5	5	yellow	5	5	red	5
6	green	6	6	yellow	6	6	red	6
7	green	7	7	yellow	7	7	red	7

```
VTEP2#show qos-profile DSCP-QUE
profile name: DSCP-QUE
profile type: dscp-to-queue
profile attached to 1 instances
configured mapping:
```

dscp 16 queue 4

Detailed mapping:

Ingress map for dscp to queue-color

INPUT			INPUT			INPUT		
INPUT	OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT	INPUT
DSCP	Queue	Color	DSCP	Queue	Color	DSCP	Queue	Color
	Queue	Color		Queue	Color		Queue	Color
0	0	green	16	4	green	32	4	green
6	green							48
1	0	green	17	2	green	33	4	green
6	green							49

2	0	green		18	2	green		34	4	green		50
6	0	green		19	2	green		35	4	green		51
6	0	green		20	2	yellow		36	4	yellow		52
6	0	green		21	2	green		37	4	green		53
6	0	green		22	2	red		38	4	red		54
6	0	green		23	2	green		39	4	green		55
7	1	green		24	3	green		40	5	green		56
7	1	green		25	3	green		41	5	green		57
7	1	green		26	3	green		42	5	green		58
7	1	green		27	3	green		43	5	green		59
7	1	green		28	3	yellow		44	5	green		60
7	1	green		29	3	green		45	5	green		61
7	1	green		30	3	red		46	5	green		62
7	1	green		31	3	green		47	5	green		63

VxLAN - EVPN with Integrated Routing and Bridging Deployment Mode

CHAPTER 1 VXLAN-EVPN with IRB

Overview

An EVPN-based Integrated Routing and Bridging solution used for forwarding of intra-subnets and inter-subnets traffic.
There are 2 modes of IRB.

Symmetric IRB

In this mode, both the ingress and egress VTEPs perform layer-2 and layer-3 lookups (switching and routing). In this case, a given VTEP needs to learn the ARP and MAC-address entries only for tenant systems (TSs) across the tenant VxLAN network belonging to VNIDs attached to that VTEP.

Asymmetric IRB


In this mode, the ingress VTEP perform layer-2 and layer-3 lookups and egress VTEPs perform layer-2 lookups only.
The disadvantage of this mode is the need for each VTEP in the tenant network to be configured with all the VNIDs for that tenant irrespective of whether a given VTEP has TS attached for that VNID or not.

Three approaches are available to achieve IRB solution.

- Centralized Gateway
 - Anycast Gateway
 - Distributed Gateway
-

Topology

The procedures in this section use the topology in [Figure 1-11](#).

**Figure 1-11: VxLAN EVPN IRB**

Note: In the above topology TS1, TS2 are the tenant systems.

Base Configuration - L2 VXLAN

VTEP1

(Multi-homed group1) - Part of both Multi-homed with po1(MH2).

Generic configuration:

#configure terminal	Enter Configure mode.
(config) #evpn vxlan multihoming enable	Enable Multihoming, save configs and reboot the board for multihoming to be effective
(Config) #qos enable	Enabling QoS
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

Interface and loopback configuration:

(config) #interface po1	Enter Interface mode for po1 (MH2)
(config-if) #switchport	Make it L2 interface
(config-if) # evpn multi-homed system-mac 0000.0000.2222	Configure system MAC as ESI value for Lag (po1) interface. VTEP1 and VTEP2 should have same ESI value
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe2	Enter Interface mode for xe2
(config-if) #channel-group 1 mode active	Make it member port of po1

(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface xe3	Enter Interface mode for xe3
(config-if)#channel-group 1 mode active	Make it member port of po1
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface lo	Enter Interface mode for lo
(config-if)#ip address 1.1.1.1/32 secondary	Configure loopback IP address as 1.1.1.1 for VTEP1
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface po2	Enter Interface mode for po2
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface xe25	Enter Interface mode for xe25
(config-if)#channel-group 2 mode active	Make it member port of po2
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface xe26	Enter Interface mode for xe26
(config-if)#channel-group 2 mode active	Make it member port of po2
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface po2	Enter Interface mode for po2
(config-if)#ip address 100.11.11.1/24	Configure IP address as 100.11.11.1 on network side of Spine-P3
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

OSPF configuration:

(config)#router ospf 100	Enter into router OSPF mode
(config-router)#ospf router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo IP address)
(config-router)#network 1.1.1.1/32 area 0.0.0.0	Add 1.1.1.1 (lo IP address) network into area 0
(config-router)#network 100.11.11.0/24 area 0.0.0.0	Add 100.11.11.0 (Spine-P3) network into area 0
(config-router)#bfd all-interfaces	Enabling BFD on all OSPF interface for fast convergence
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

BGP configuration:

(Config)#router bgp 5000	Enter into Router BGP mode
(config-router)#bgp router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo IP address)
(config-router)#neighbor 2.2.2.2 remote-as 5000	Specify a VTEP2 loopback IP address and remote-as defined
(config-router)#neighbor 2.2.2.2 update-source lo	Configure update as loopback for VTEP2
(config-router)#neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2

(config-router) #neighbor 4.4.4.4 remote-as 5000	Specify a VTEP4 loopback IP address and remote-as defined
(config-router) #neighbor 4.4.4.4 update-source lo	Configure update as loopback for VTEP4
(config-router) #neighbor 4.4.4.4 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP4
(config-router) #neighbor 5.5.5.5 remote-as 5000	Specify a VTEP5 loopback IP address and remote-as defined
(config-router) #neighbor 5.5.5.5 update-source lo	Configure update as loopback for VTEP5
(config-router) #neighbor 5.5.5.5 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP5
(config-router) #address-family l2vpn evpn	Enter into L2VPN EVPN address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2(VTEP2) into L2VPN EVPN address family mode
(config-router-af) #neighbor 4.4.4.4 activate	Activate 3.3.3.3(VTEP4) into L2VPN EVPN address family mode
(config-router-af) #neighbor 5.5.5.5 activate	Activate 5.5.5.5(VTEP5) into L2VPN EVPN address family mode
(config-router-af) #exit-address-family	Exit from L2VPN address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

L2 MAC VRF Configuration:

(config) #mac vrf L2VRF1	Create MAC routing/forwarding instance with L2VRF1 name and enter into VRF mode
(config-vrf) #rd 1.1.1.1:11	Assign RD value
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as RED
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) #exit	Exit from VRF mode
(config) #mac vrf L2VRF2	Create MAC routing/forwarding instance with L2VRF2 name and enter into VRF mode
(config-vrf) #rd 1.1.1.1:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as BLUE
(config-vrf) #exit	Exit from VRF mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

L2 VXLAN configuration:

(config) #nvo vxlan enable	Enable VXLAN
(config) #evpn esi hold-time 90	Configure ESI hold time to allow tunnel to come up at the time of VXLAN initialization before making the ESI up. It should be same on both VTEP1 and VTEP2
(config) #nvo vxlan vtep-ip-global 1.1.1.1	Configure Source vtep-ip-global configuration - Use loopback IP address
(config) #nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # vni-name VNI-101	Configure VNI name as VNI-101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # vni-name VNI-201	Configure VNI name as VNI-201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan access-if port-vlan po1 10	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vnid 101	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1010 ip 11.11.11.51	Configure static MAC-IP
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan po1 20	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vnid 201	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1020 ip 21.21.21.51	Configure static MAC-IP
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #exit	Exit from configuration mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VTEP2

(Multi-homed group1) - Part of both Multi-homed with po1(MH1).

Generic configuration:

#configure terminal	Enter Configure mode.
(config) #evpn vxlan multihoming enable	Enable Multihoming, save configs and reboot the board for multihoming to be effective

(Config) #qos enable	Enabling QoS
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

Interface and loopback configuration:

(config) #interface po1	Enter Interface mode for po1 (MH2)
(config-if) #switchport	Make it L2 interface
(config-if) # evpn multi-homed system-mac 0000.0000.2222	Configure system MAC as ESI value for Lag (po1) interface. VTEP1 and VTEP2 should have same ESI value
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe8	Enter Interface mode for xe2
(config-if) #channel-group 1 mode active	Make it member port of po1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe9	Enter Interface mode for xe3
(config-if) #channel-group 1 mode active	Make it member port of po1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 2.2.2.2/32 secondary	Configure loopback IP address as 2.2.2.2 for VTEP2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface po3	Enter Interface mode for po3
(config-if) #switchport	Configure po3 as L2 interface
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe27	Enter Interface mode for xe27
(config-if) #channel-group 3 mode active	Make it member port of po3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe28	Enter Interface mode for xe28
(config-if) #channel-group 3 mode active	Make it member port of po3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) # bridge 1 protocol rstp vlan-bridge	Configure bridge 1
(config) # vlan database	Enter into VLAN database mode
(config) #vlan 2 bridge 1 state enable	Configure VLAN 2 as part of bridge 1
(config) #interface po3	Enter Interface mode for po3
(config-if) # bridge-group 1	Configure bridge 1 for po3
(config-if) # switchport mode trunk	Switchport mode as trunk
(config-if) # switchport trunk allowed vlan add 2	Trunk allowed VLAN 2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface vlan1.2	Enter into SVI port VLAN1.2
(config-if) #ip address 100.12.12.1/24	Configure IP address as 100.12.12.1 on network side of Spine-P3

(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

OSPF configuration:

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 2.2.2.2	Configure router-id as 2.2.2.2 (lo IP address)
(config-router) #network 2.2.2.2/32 area 0.0.0.0	Add 2.2.2.2 (lo IP address) network into area 0
(config-router) #network 100.12.12.0/24 area 0.0.0.0	Add 100.12.12.0(Spine-P3) network into area 0
(config-router) #bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.

BGP configuration:

(Config) #router bgp 5000	Enter into Router BGP mode
(config-router) #bgp router-id 2.2.2.2	Configure router-id as 2.2.2.2 (lo IP address)
(config-router) #neighbor 1.1.1.1 remote-as 5000	Specify a VTEP1 loopback IP address and remote-as defined
(config-router) #neighbor 1.1.1.1 update-source lo	Configure update as loopback for VTEP1
(config-router) #neighbor 1.1.1.1 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP1
(config-router) #neighbor 4.4.4.4 remote-as 5000	Specify a VTEP4 loopback IP address and remote-as defined
(config-router) #neighbor 4.4.4.4 update-source lo	Configure update as loopback for VTEP4
(config-router) #neighbor 4.4.4.4 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP4
(config-router) #neighbor 5.5.5.5 remote-as 5000	Specify a VTEP5 loopback IP address and remote-as defined
(config-router) #neighbor 5.5.5.5 update-source lo	Configure update as loopback for VTEP5
(config-router) #neighbor 5.5.5.5 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP5
(config-router) #address-family l2vpn evpn	Enter into L2VPN EVPN address family mode
(config-router-af) #neighbor 1.1.1.1 activate	Activate 1.1.1.1(VTEP1) into L2VPN EVPN address family mode
(config-router-af) #neighbor 4.4.4.4 activate	Activate 4.4.4.4(VTEP4) into L2VPN EVPN address family mode
(config-router-af) #neighbor 5.5.5.5 activate	Activate 5.5.5.5(VTEP5) into L2VPN EVPN address family mode
(config-router-af) #exit-address-family	Exit from L2VPN address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VRF Configuration:

(config) #mac vrf L2VRF1	Create MAC routing/forwarding instance with L2VRF1 name and enter into VRF mode
(config-vrf) #rd 2.2.2.2:11	Assign RD value
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as RED
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) #exit	Exit from VRF mode
(config) #mac vrf L2VRF2	Create MAC routing/forwarding instance with L2VRF2 name and enter into VRF mode
(config-vrf) #rd 2.2.2.2:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as BLUE
(config-vrf) #exit	Exit from VRF mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VXLAN configuration:

(config) #nvo vxlan enable	Enable VXLAN
(config) #evpn esi hold-time 90	Configure ESI hold time to allow tunnel to come up at the time of vxlan initialization before making the ESI up. It should be same on both VTEP1 and VTEP2
(config) #nvo vxlan vtep-ip-global 2.2.2.2	Configure Source vtep-IP-global configuration - Use loopback IP address
(config) #nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # vni-name VNI-101	Configure VNI name as VNI-101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # vni-name VNI-201	Configure VNI name as VNI-201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan access-if port-vlan po1 10	Enable port-VLAN mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vnid 101	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1010 ip 11.11.11.51	Configure static MAC-IP
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode

(config) #nvo vxlan access-if port-vlan po1 20	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vniid 201	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1020 ip 21.21.21.51	Configure static MAC-IP
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #exit	Exit from configuration mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VTEP4

Single Home -SH5.

Generic configuration:

#configure terminal	Enter Configure mode.
(Config) #qos enable	Enabling qos

Interface and loopback configuration:

(config) #interface sa1	Enter Interface mode for sa1 (SH5)
(config-if) #switchport	Make it L2 interface
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 4.4.4.4/32 secondary	Configure loopback IP address as 4.4.4.4 for VTEP4
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface po4	Enter Interface mode for po4
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe7	Enter Interface mode for xe7
(config-if) #channel-group 4 mode active	Make it member port of po4
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe9	Enter Interface mode for xe9
(config-if) #channel-group 4 mode active	Make it member port of po4
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface po4	Enter L3SI po4.4
(config-if) #ip address 100.14.14.1/24	Configure IP address as 100.14.14.1 on network side of Spine-P3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

OSPF configuration:

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 4.4.4.4	Configure router-id as 4.4.4.4 (lo IP address)
(config-router) #network 4.4.4.4/32 area 0.0.0.0	Add 4.4.4.4 (lo IP address) network into area 0
(config-router) #network 100.14.14.0/24 area 0.0.0.0	Add 100.14.14.0(Spine-P3) network into area 0
(config-router) #bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

BGP configuration:

(Config) #router bgp 5000	Enter into Router BGP mode
(config-router) #bgp router-id 4.4.4.4	Configure router-id as 4.4.4.4 (lo IP address)
(config-router) #neighbor 1.1.1.1 remote-as 5000	Specify a VTEP1 loopback IP address and remote-as defined
(config-router) #neighbor 1.1.1.1 update-source lo	Configure update as loopback for VTEP1
(config-router) #neighbor 1.1.1.1 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP1
(config-router) #neighbor 2.2.2.2 remote-as 5000	Specify a VTEP2 loopback IP address and remote-as defined
(config-router) #neighbor 2.2.2.2 update-source lo	Configure update as loopback for VTEP2
(config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2
(config-router) #neighbor 5.5.5.5 remote-as 5000	Specify a VTEP5 loopback IP address and remote-as defined
(config-router) #neighbor 5.5.5.5 update-source lo	Configure update as loopback for VTEP5
(config-router) #neighbor 5.5.5.5 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP5
(config-router) #address-family l2vpn evpn	Enter into L2VPN EVPN address family mode
(config-router-af) #neighbor 1.1.1.1 activate	Activate 1.1.1.1(VTEP1) into L2VPN EVPN address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2(VTEP2) into L2VPN EVPN address family mode
(config-router-af) #neighbor 5.5.5.5 activate	Activate 5.5.5.5(VTEP5) into L2VPN EVPN address family mode
(config-router-af) #exit-address-family	Exit from L2VPN address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VRF Configuration:

(config) #mac vrf L2VRF1	Create MAC routing/forwarding instance with L2VRF1 name and enter into VRF mode
(config-vrf) #rd 4.4.4.4:11	Assign RD value
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as RED
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) #exit	Exit from VRF mode
(config) #mac vrf L2VRF2	Create MAC routing/forwarding instance with L2VRF2 name and enter into VRF mode
(config-vrf) #rd 4.4.4.4:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as BLUE
(config-vrf) #exit	Exit from VRF mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VXLAN configuration:

(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan vtep-ip-global 4.4.4.4	Configure Source vtep-IP-global configuration. Use loopback IP address
(config) #nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # vni-name VNI-101	Configure VNI name as VNI-101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # vni-name VNI-201	Configure VNI name as VNI-201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) # nvo vxlan access-if port-vlan sal 20	Enable port-VLAN mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vnid 201	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.5555.1020 ip 21.21.21.101	Configure static MAC-IP
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode

(config) #exit	Exit from configuration mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VTEP5

Single Home -SH3

Generic configuration:

#configure terminal	Enter Configure mode.
(Config) #qos enable	Enabling qos
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

Interface and loopback configuration:

(config) #interface xe48	Enter Interface mode for xe48 (SH3)
(config-if)#switchport	Make it L2 interface
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) #interface lo	Enter Interface mode for lo
(config-if)#ip address 5.5.5.5/32 secondary	Configure loopback IP address as 5.5.5.5 for VTEP5
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) #interface xe40	Enter interface mode
(config-if)#ip address 100.15.15.1/24	Configure IP address as 100.15.15.1 on network side of Spine-P3
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

OSPF configuration:

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 5.5.5.5	Configure router-id as 5.5.5.5 (lo IP address)
(config-router) #network 5.5.5.5/32 area 0.0.0.0	Add 5.5.5.5 (lo IP address) network into area 0
(config-router) #network 100.15.15.0/24 area 0.0.0.0	Add 100.15.15.0(Spine-P3) network into area 0
(config-router) #bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

BGP configuration:

(Config) #router bgp 5000	Enter into Router BGP mode
(config-router) #bgp router-id 5.5.5.5	Configure router-id as 5.5.5.5(lo IP address)

(config-router) #neighbor 1.1.1.1 remote-as 5000	Specify a VTEP1 loopback IP address and remote-as defined
(config-router) #neighbor 1.1.1.1 update-source lo	Configure update as loopback for VTEP1
(config-router) #neighbor 1.1.1.1 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP1
(config-router) #neighbor 2.2.2.2 remote-as 5000	Specify a VTEP2 loopback IP address and remote-as defined
(config-router) #neighbor 2.2.2.2 update-source lo	Configure update as loopback for VTEP2
(config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2
(config-router) #neighbor 4.4.4.4 remote-as 5000	Specify a VTEP4 loopback IP address and remote-as defined
(config-router) #neighbor 4.4.4.4 update-source lo	Configure update as loopback for VTEP4
(config-router) #neighbor 4.4.4.4 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP4
(config-router) #address-family l2vpn evpn	Enter into L2VPN EVPN address family mode
(config-router-af) #neighbor 1.1.1.1 activate	Activate 1.1.1.1(VTEP1) into L2VPN EVPN address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2(VTEP2) into L2VPN EVPN address family mode
(config-router-af) #neighbor 4.4.4.4 activate	Activate 4.4.4.4(VTEP4) into L2VPN EVPN address family mode
(config-router-af) #exit-address-family	Exit from L2VPN address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VRF Configuration:

(config) #mac vrf L2VRF1	Create MAC routing/forwarding instance with L2VRF1 name and enter into VRF mode
(config-vrf) #rd 5.5.5.5:11	Assign RD value
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as RED
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) #exit	Exit from VRF mode
(config) #mac vrf L2VRF2	Create MAC routing/forwarding instance with L2VRF2 name and enter into VRF mode
(config-vrf) #rd 5.5.5.5:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as BLUE
(config-vrf) #exit	Exit from VRF mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VXLAN configuration:

(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan vtep-ip-global 5.5.5.5	Configure Source vtep-IP-global configuration. Use loopback IP address
(config) #nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # vni-name VNI-101	Configure VNI name as VNI-101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign vrf for EVPN-BGP to carry EVPN route
(config-nvo) # vni-name VNI-201	Configure VNI name as VNI-201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) # nvo vxlan access-if port-vlan xe48 10	Enable port-VLAN mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vnid 101	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.4444.1010 ip 11.11.11.201	Configure static MAC-IP
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #exit	Exit from configuration mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

Switch1 (MH2)

Multihomed to 2-VTEPs (VTEP1 and VTEP2). It acts as Tenant system for VLAN1.20.

#configure terminal	Enter Configure mode.
(config) # bridge 1 protocol rstp vlan-bridge	Configure RSTP VLAN bridge
(config) # vlan database	Enter into VLAN database mode
(config) #vlan 2-20 bridge 1 state enable	Configure VLANs from 2-20 and associate with bridge 1
(config) #interface xe7	Enter Interface mode for xe7
(config-if) #switchport	Make as L2 port by configuring switchport
(config-if) #bridge-group 1	Associate bridge 1 into interface
(config-if) # bridge-group 1 spanning-tree disable	Configure interface as STP disable
(config-if) # switchport mode trunk	Mode as trunk
(config-if) # switchport trunk allowed vlan add 2,10,20	Trunk allowed VLAN as 2.10.20
(config-if) #switchport trunk native vlan 2	Native VLAN as 2

(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface po1	Enter Interface mode for po1
(config-if)#switchport	Make po1 as L2 port by configuring switchport
(config-if)#bridge-group 1	Associate po1 to bridge 1
(config-if)# bridge-group 1 spanning-tree disable	Configure po1 as STP disable
(config-if)# switchport mode trunk	Mode as trunk
(config-if)# switchport trunk allowed vlan add 2,10,20	Trunk allowed VLAN as 2.10.20
(config-if)#switchport trunk native vlan 2	Native VLAN as 2
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface xe3	Enter Interface mode for xe3
(config-if)#channel-group 1 mode active	Make it member port of po1
(config)#interface xe4	Enter Interface mode for xe4
(config-if)#channel-group 1 mode active	Make it member port of po1
(config)#exit	Exit from configuration mode
(config)#interface xe9	Enter Interface mode for xe9
(config-if)#channel-group 1 mode active	Make it member port of po1
(config)#interface xe10	Enter Interface mode for xe10
(config-if)#channel-group 1 mode active	Make it member port of po1
(config)#exit	Exit from configuration mode
(config)#interface vlan1.20	Enter Interface mode for VLAN1.20
(config-if)# ip address 21.21.21.2/24	Configure IP address
(config-if)#ipv6 address 21:21::21:2/48	Configure IPv6 address
(config)#exit	Exit from configuration mode
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

Switch2 (SH5)

#configure terminal	Enter Configure mode.
(config)# bridge 1 protocol rstp vlan-bridge	Configure RSTP VLAN bridge
(config)# vlan database	
(config)#vlan 2-20 bridge 1 state enable	Configure VLANs from 2-20 and associate with bridge 1
(config)#interface xe22	Enter Interface mode for xe22
(config-if)#switchport	Make xe22 as L2 port by configuring switchport
(config-if)#bridge-group 1	Associate xe22 to bridge 1
(config-if)# bridge-group 1 spanning-tree disable	Configure xe22 as STP disable
(config-if)# switchport mode trunk	Mode as trunk
(config-if)# switchport trunk allowed vlan add 6,10,20	Trunk allowed VLAN as 6,.10 &.20
(config-if)#switchport trunk native vlan 6	Native VLAN as 6

(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface sa1	Enter Interface mode for sa1
(config-if)#switchport	Make sa1 as L2 port by configuring switchport
(config-if)#bridge-group 1	Associate sa1 to bridge 1
(config-if)# bridge-group 1 spanning-tree disable	Configure sa1 as STP disable
(config-if)# switchport mode trunk	Mode as trunk
(config-if)# switchport trunk allowed vlan add 6,10,20	Trunk allowed VLAN as 2,10.& 20
(config-if)#switchport trunk native vlan 6	Native VLAN as 6
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface xe3	Enter Interface mode for xe3
(config-if)# static-channel-group 1	Make it member port of sa1
(config)#interface xe4	Enter Interface mode for xe4
(config-if)# static-channel-group 1	Make it member port of sa1
(config)#exit	Exit from configuration mode
(config)#interface vlan1.20	Enter Interface mode for VLAN1.20
(config-if)# ip address 21.21.21.3/24	Configure IP address
(config-if)#ipv6 address 21:21::21:3/48	Configure IPv6 address
(config)#exit	Exit from configuration mode
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

Spine-P3

Spine node where all VTEPs are connected.

Generic configuration:

#configure terminal	Enter Configure mode.
(Config)#qos enable	Enabling qos
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

Interface and loopback configuration:

(config)#interface lo	Enter Interface mode for lo
(config-if)#ip address 100.100.100.100/32	Configure loopback IP address as 100.100.100.100 for Spine-P3
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface po2	Enter Interface mode for po2
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface xe25	Enter Interface mode for xe25
(config-if)#channel-group 2 mode active	Make it member port of po2
(config-if)#exit	Exit Interface mode and return to Configure mode.

(config) #interface xe26	Enter Interface mode for xe26
(config-if) #channel-group 2 mode active	Make it member port of po3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface po2	Enter Interface mode for po2
(config-if) #ip address 100.11.11.2/24	Configure IP address as 100.11.11.2 on network side of VTEP1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface po3	Enter Interface mode for po3
(config) #i switchport	Configure po3 as L2 interface
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe27	Enter Interface mode for xe27
(config-if) #channel-group 3 mode active	Make it member port of po3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe28	Enter Interface mode for xe28
(config-if) #channel-group 3 mode active	Make it member port of po3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) # bridge 1 protocol rstp vlan-bridge	Configure bridge 1
(config) # vlan database	Enter into VLAN database mode
(config) #vlan 2 bridge 1 state enable	Configure VLAN 2 as part of bridge 1
(config) #interface po3	Enter Interface mode for po3
(config-if) # bridge-group 1	Configure bridge 1 for po3
(config-if) # switchport mode trunk	Switchport mode as trunk
(config-if) # switchport trunk allowed vlan add 2	Trunk allowed VLAN 2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface vlan1.2	Enter into SVI port VLAN1.2
(config-if) #ip address 100.12.12.2/24	Configure IP address as 100.12.12.2 on network side of VTEP2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface po4	Enter Interface mode for po4
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe7	Enter Interface mode for xe7
(config-if) #channel-group 4 mode active	Make it member port of po4
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe9	Enter Interface mode for xe9
(config-if) #channel-group 4 mode active	Make it member port of po4
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface po4	Enter L3SI po4.4
(config-if) #ip address 100.14.14.2/24	Configure IP address as 100.14.14.12 on network side of VTEP4
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe40	Enter interface mode

(config-if)#ip address 100.15.15.1/24	Configure IP address as 100.15.15.1 on network side of VTEP5
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

OSPF configuration:

(config)#router ospf 100	Enter into router OSPF mode
(config-router)#ospf router-id 100.100.100.100	Configure router-id as 100.100.100.100 (lo IP address)
(config-router)#network 100.100.100.100/32 area 0.0.0.0	Add 100.100.100.100 (lo IP address) network into area 0
(config-router)#network 100.11.11.0/24 area 0.0.0.0	Add 100.11.11.0 (VTEP1) network into area 0
(config-router)#network 100.12.12.0/24 area 0.0.0.0	Add 100.12.12.0 (VTEP2) network into area 0
(config-router)#network 100.14.14.0/24 area 0.0.0.0	Add 100.14.14.0 (VTEP4) network into area 0
(config-router)#network 100.15.15.0/24 area 0.0.0.0	Add 100.15.15.0 (VTEP5) network into area 0
(config-router)#bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

Centralized Gateway

In Centralized gateway approach, when two TS belonging to two different subnets connected to the same/different VTEP node, wanted to communicate with each other, their traffic needed to be back hauled from the VTEP node to the centralized gateway node where inter- subnet switching is performed and then back to the VTEP node.

IRB Configuration for Centralized Gateway

Configure from Base Configuration-L2 VXLAN section, then configure below commands for centralized gateway approach.

VTEP5

(config)#nvo vxlan irb	Enable VXLAN IRB
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board
(config)#ip vrf L3VRF1	Create MAC routing/forwarding instance with L3VRF1 name and enter into VRF mode
(config-vrf)#rd 51000:11	Assign RD value
(config-vrf)# route-target both 100:100	Assign route-target value for same for import and export.

(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from VRF mode
(config) # interface irb1001	Configure IRB interface 1001
(config-if)#ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if)#ip address 11.11.11.1/24	Configure IP address
(config-if)#ipv6 address 11:11::11:1/48	Configure IPv6 address
(config-if) #exit	Exit from interface config mode
(config) # interface irb2001	Configure IRB interface 2001
(config-if)#ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if)#ip address 21.21.21.1/24	Configure IP address
(config-if)#ipv6 address 21:21::21:1/48	Configure IPv6 address
(config-if) #exit	Exit from interface config mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board
(config) #router bgp 5000	Enter into BGP router mode
(config-router) #address-family ipv4 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) #exit-address-family	Exit from address-family
(config) # nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # evpn irb1001	Configure IRB1001 under VXLAN ID 101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # evpn irb2001	Configure IRB2001 under VXLAN ID 201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

Validation

VTEP5

```
TB2-VTEP5#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination      Status        Up/Down      Update
=====
5.5.5.5        2.2.2.2        Installed     00:26:30    00:26:30
5.5.5.5        4.4.4.4        Installed     00:26:30    00:26:30
5.5.5.5        1.1.1.1        Installed     00:26:30    00:26:30
```

Total number of entries are 3

```

TB2-VTEP5#show nvo vxlan
VXLAN Information
=====
Codes: NW - Network Port
      AC - Access Port
      (u) - Untagged



| VNID | VNI-Name | VNI-Type | Type | Interface | ESI                       | VLAN | DF-Status | Src-Addr | Dst-Addr |
|------|----------|----------|------|-----------|---------------------------|------|-----------|----------|----------|
| 101  | VNI-101  | L2       | NW   | ----      | ----                      | ---- | ----      | 5.5.5.5  | 2.2.2.2  |
| 101  | VNI-101  | L2       | NW   | ----      | ----                      | ---- | ----      | 5.5.5.5  | 4.4.4.4  |
| 101  | VNI-101  | L2       | NW   | ----      | ----                      | ---- | ----      | 5.5.5.5  | 1.1.1.1  |
| 101  | VNI-101  | --       | AC   | xe48      | --- Single Homed Port --- | 10   | ----      | ----     | ----     |
| 201  | VNI-201  | L2       | NW   | ----      | ----                      | ---- | ----      | 5.5.5.5  | 2.2.2.2  |
| 201  | VNI-201  | L2       | NW   | ----      | ----                      | ---- | ----      | 5.5.5.5  | 4.4.4.4  |
| 201  | VNI-201  | L2       | NW   | ----      | ----                      | ---- | ----      | 5.5.5.5  | 1.1.1.1  |



Total number of entries are 7
TB2-VTEP5#show nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====


| VNID | Ip-Addr      | Mac-Addr       | Type          | Age-Out | Retries-Left |
|------|--------------|----------------|---------------|---------|--------------|
| 201  | 21.21.21.51  | 0000.2222.1020 | Static Remote | ----    | ----         |
| 201  | 21.21.21.1   | 3c2c.99d6.167a | Static Local  | ----    | ----         |
| 201  | 21.21.21.101 | 0000.4444.1020 | Static Remote | ----    | ----         |
| 101  | 11.11.11.51  | 0000.2222.1010 | Static Remote | ----    | ----         |
| 101  | 11.11.11.1   | 3c2c.99d6.167a | Static Local  | ----    | ----         |
| 101  | 11.11.11.201 | 0000.5555.1010 | Static Local  | ----    | ----         |



Total number of entries are 6
TB2-VTEP5#show nvo vxlan nd-cache
VXLAN ND-CACHE Information
=====


| VNID | Ip-Addr     | Mac-Addr       | Type         | Age-Out | Retries-Left |
|------|-------------|----------------|--------------|---------|--------------|
| 201  | 21:21::21:1 | 3c2c.99d6.167a | Static Local | ----    | ----         |
| 101  | 11:11::11:1 | 3c2c.99d6.167a | Static Local | ----    | ----         |



Total number of entries are 2
TB2-VTEP5#show nvo vxlan l3vni-map
L3VNI          L2VNI          IRB-interface
=====


| 1000 | 101 | irb1001 |
|------|-----|---------|
| 1000 | 201 | irb2001 |



TB2-VTEP5#show ip route vrf L3VRF1
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
       O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
       ia - IS-IS inter area, E - EVPN,
       v - vrf leaked
       * - candidate default

IP Route Table for VRF "L3VRF1"
C           11.11.11.0/24 is directly connected, irb1001, 00:27:00
C           21.21.21.0/24 is directly connected, irb2001, 00:26:58
C           127.0.0.0/8 is directly connected, lo.L3VRF1, 00:32:53

Gateway of last resort is not set
TB2-VTEP5#show ipv6 route vrf L3VRF1
IPv6 Routing Table
Codes: K - kernel route, C - connected, S - static, R - RIP, O - OSPF,
       IA - OSPF inter area, E1 - OSPF external type 1,
       E2 - OSPF external type 2, E - EVPN  N1 - OSPF NSSA external type 1,
       N2 - OSPF NSSA external type 2, i - IS-IS, B - BGP
Timers: Uptime

IP Route Table for VRF "L3VRF1"
C           ::1/128 via ::, lo.L3VRF1, 00:32:53
C           11:11::/48 via ::, irb1001, 00:27:00
C           21:21::/48 via ::, irb2001, 00:26:58

```

```

C      fe80::/64 via ::, irb2001, 00:04:38
TB2-VTEP5#show ip route summary

-----
IP routing table name is Default-IP-Routing-Table(0)
-----
IP routing table maximum-paths : 8
Total number of IPv4 routes : 12
Total number of IPv4 paths : 12
Pending routes (due to route max reached): 0
Route Source Networks
connected 3
ospf 9
Total 12
FIB 12

ECMP statistics (active in ASIC):
 Total number of IPv4 ECMP routes : 0
 Total number of IPv4 ECMP paths : 0
TB2-VTEP5#show ipv6 route summary

-----
IPv6 routing table name is Default-IPv6-Routing-Table(0)
-----
IPv6 routing table maximum-paths : 8
Total number of IPv6 routes : 2
Total number of IPv6 paths : 2
Pending routes (due to route max reached): 0
Route Source Networks
connected 2
Total 2
FIB 2

ECMP statistics (active in ASIC):
 Total number of IPv6 ECMP routes : 0
 Total number of IPv6 ECMP paths : 0
TB2-VTEP5#show bgp 12vpn evpn
BGP table version is 11, local router ID is 5.5.5.5
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
              l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route
4 - Ethernet Segment Route
5 - Prefix Route

      Network          Next Hop           Metric     LocPrf      Weight     Path   Peer        Encap
RD[1.1.1.1:1]
*>i  [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
          1.1.1.1          0         100          0     i  1.1.1.1        VXLAN
*>i  [4]:[00:00:00:00:00:22:22:00:00:00]:[32,1.1.1.1]
          1.1.1.1          0         100          0     i  1.1.1.1        VXLAN

RD[1.1.1.1:11]
*>i  [1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101]
          1.1.1.1          0         100          0     i  1.1.1.1        VXLAN
*>i  [2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]
          1.1.1.1          0         100          0     i  1.1.1.1        VXLAN
*>i  [3]:[101]:[32,1.1.1.1]
          1.1.1.1          0         100          0     i  1.1.1.1        VXLAN

RD[1.1.1.1:21]
*>i  [1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201]
          1.1.1.1          0         100          0     i  1.1.1.1        VXLAN
*>i  [2]:[00:00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
          1.1.1.1          0         100          0     i  1.1.1.1        VXLAN
*>i  [3]:[201]:[32,1.1.1.1]
          1.1.1.1          0         100          0     i  1.1.1.1        VXLAN

```

```

RD[2.2.2.2:1]
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
    2.2.2.2      0     100      0   i 2.2.2.2      VXLAN
*>i [4]:[00:00:00:00:00:22:22:00:00:00]:[32,2.2.2.2]
    2.2.2.2      0     100      0   i 2.2.2.2      VXLAN

RD[2.2.2.2:11]
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101]
    2.2.2.2      0     100      0   i 2.2.2.2      VXLAN
*>i [2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]
    2.2.2.2      0     100      0   i 2.2.2.2      VXLAN
*>i [3]:[101]:[32,2.2.2.2]
    2.2.2.2      0     100      0   i 2.2.2.2      VXLAN

RD[2.2.2.2:21]
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201]
    2.2.2.2      0     100      0   i 2.2.2.2      VXLAN
*>i [2]:[00:00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
    2.2.2.2      0     100      0   i 2.2.2.2      VXLAN
*>i [3]:[201]:[32,2.2.2.2]
    2.2.2.2      0     100      0   i 2.2.2.2      VXLAN

RD[4.4.4.4:11]
*>i [3]:[101]:[32,4.4.4.4]
    4.4.4.4      0     100      0   i 4.4.4.4      VXLAN

RD[4.4.4.4:21]
*>i [2]:[0]:[201]:[48,0000:4444:1020]:[32,21.21.21.101]:[201]
    4.4.4.4      0     100      0   i 4.4.4.4      VXLAN
*>i [3]:[201]:[32,4.4.4.4]
    4.4.4.4      0     100      0   i 4.4.4.4      VXLAN

RD[5.5.5.5:11] VRF[L2VRF1]:
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101]
    1.1.1.1      0     100      0   i 1.1.1.1      VXLAN
* i 2.2.2.2      0     100      0   i 2.2.2.2      VXLAN
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
    1.1.1.1      0     100      0   i 1.1.1.1      VXLAN
* i 2.2.2.2      0     100      0   i 2.2.2.2      VXLAN
* i [2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]
    1.1.1.1      0     100      0   i 1.1.1.1      VXLAN
* i 2.2.2.2      0     100      0   i 2.2.2.2      VXLAN
*> [2]:[0]:[101]:[48,0000:5555:1010]:[32,11.11.11.201]:[101]
    5.5.5.5      0     100     32768 i -----      VXLAN
*> [2]:[0]:[101]:[48,3c2c:99d6:167a]:[32,11.11.11.1]:[101]
    5.5.5.5      0     100     32768 i -----      VXLAN
*> [2]:[0]:[101]:[48,3c2c:99d6:167a]:[128,11:11::11:1]:[101]
    5.5.5.5      0     100     32768 i -----      VXLAN
* i [3]:[101]:[32,1.1.1.1]
    1.1.1.1      0     100      0   i 1.1.1.1      VXLAN
* i [3]:[101]:[32,2.2.2.2]
    2.2.2.2      0     100      0   i 2.2.2.2      VXLAN
* i [3]:[101]:[32,4.4.4.4]
    4.4.4.4      0     100      0   i 4.4.4.4      VXLAN
*> [3]:[101]:[32,5.5.5.5]
    5.5.5.5      0     100     32768 i -----      VXLAN

RD[5.5.5.5:21] VRF[L2VRF2]:
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201]
    1.1.1.1      0     100      0   i 1.1.1.1      VXLAN
* i 2.2.2.2      0     100      0   i 2.2.2.2      VXLAN
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
    1.1.1.1      0     100      0   i 1.1.1.1      VXLAN
* i 2.2.2.2      0     100      0   i 2.2.2.2      VXLAN
* i [2]:[00:00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
    1.1.1.1      0     100      0   i 1.1.1.1      VXLAN
* i 2.2.2.2      0     100      0   i 2.2.2.2      VXLAN
* i [2]:[0]:[201]:[48,0000:4444:1020]:[32,21.21.21.101]:[201]
    4.4.4.4      0     100      0   i 4.4.4.4      VXLAN
*> [2]:[0]:[201]:[48,3c2c:99d6:167a]:[32,21.21.21.1]:[201]
    5.5.5.5      0     100     32768 i -----      VXLAN
*> [2]:[0]:[201]:[48,3c2c:99d6:167a]:[128,21:21::21:1]:[201]
    5.5.5.5      0     100     32768 i -----      VXLAN

```

```
* i [3]:[201]:[32,1.1.1.1]
      1.1.1.1          0     100    0   i 1.1.1.1       VXLAN
* i [3]:[201]:[32,2.2.2.2]
      2.2.2.2          0     100    0   i 2.2.2.2       VXLAN
* i [3]:[201]:[32,4.4.4.4]
      4.4.4.4          0     100    0   i 4.4.4.4       VXLAN
*> [3]:[201]:[32,5.5.5.5]
      5.5.5.5          0     100    32768 i -----       VXLAN

Total number of prefixes 39
TB2-VTEP5#
```

Anycast Gateway

For today's large multi-tenant data center, centralized L3 gateway scheme is very inefficient and sometimes impractical. In order to overcome the drawback of centralized L3GW approach, anycast mode is used.

In Anycast gateway approach, all the VTEPs acts as default gateway for all the VNIDs. We will configure same anycast MAC in all VTEPs.

IRB Configuration for Anycast

Configure from Base Configuration-L2 VXLAN section, then configure below commands for Anycast gateway approach.

VTEP1

(config) #nvo vxlan irb	Enable VXLAN IRB
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board
(config) #ip vrf L3VRF1	Create MAC routing/forwarding instance with L3VRF1 name and enter into VRF mode
(config-vrf) #rd 11000:11	Assign RD value
(config-vrf) # route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from VRF mode
(config) # evpn irb-forwarding anycast-gateway-mac 0000.0000.1111	Configure anycast MAC address
(config) # interface irb1001	Configure IRB interface 1001
(config-if)#ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if)#ip address 11.11.11.1/24 anycast	Configure IP address
(config-if)#ipv6 address 11:11::11:1/48	Configure IPv6 address
(config-if)#evpn irb-if-forwarding anycast-gateway-mac	Configure anycast MAC address
(config-if) #exit	Exit from interface config mode
(config) #interface irb2001	Configure IRB interface 2001
(config-if)#ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if)#ip address 21.21.21.1/24 anycast	Configure IP address
(config-if)#ipv6 address 21:21::21:1/48	Configure IPv6 address

(config-if)#evpn irb-if-forwarding anycast-gateway-mac	Configure anycast MAC address
(config-if)#exit	Exit from interface config mode
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board
(config)#router bgp 5000	Enter into BGP router mode
(config-router)#address-family ipv4 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router-af)#redistribute connected	Redistribute connected
(config-router-af)#exit-address-family	Exit from address-family
(config)# nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo)#vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo)# evpn irb1001	Configure IRB1001 under VXLAN ID 101
(config-nvo)#exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config)#nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo)#vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo)# evpn irb2001	Configure IRB2001 under VXLAN ID 201
(config-nvo)#exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

VTEP2

(config)#nvo vxlan irb	Enable VXLAN IRB
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board
(config)#ip vrf L3VRF1	Create MAC routing/forwarding instance with L3VRF1 name and enter into VRF mode
(config-vrf)#rd 21000:11	Assign RD value
(config-vrf)# route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf)# l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf)#exit	Exit from VRF mode
(config)# evpn irb-forwarding anycast-gateway-mac 0000.0000.1111	Configure anycast MAC address
(config)# interface irb1001	Configure IRB interface 1001
(config-if)#ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if)#ip address 11.11.11.1/24 anycast	Configure IP address
(config-if)#ipv6 address 11:11::11:1/48	Configure IPv6 address
(config-if)#evpn irb-if-forwarding anycast-gateway-mac	Configure anycast MAC address

(config-if)#exit	Exit from interface config mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board
(config) #interface irb2001	Configure IRB interface 2001
(config-if) #ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) #ip address 21.21.21.1/24 anycast	Configure IP address
(config-if) #ipv6 address 21:21::21:1/48	Configure IPv6 address
(config-if) #evpn irb-if-forwarding anycast-gateway-mac	Configure anycast MAC address
(config-if) #exit	Exit from interface config mode
(config) #router bgp 5000	Enter into BGP router mode
(config-router) #address-family ipv4 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) #exit-address-family	Exit from address-family
(config) # nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # evpn irb1001	Configure IRB1001 under VXLAN ID 101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # evpn irb2001	Configure IRB2001 under VXLAN ID 201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VTEP4

(config) #nvo vxlan irb	Enable VXLAN IRB
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board
(config) #ip vrf L3VRF1	Create MAC routing/forwarding instance with L3VRF1 name and enter into VRF mode
(config-vrf) #rd 41000:11	Assign RD value
(config-vrf) # route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from VRF mode
(config) # evpn irb-forwarding anycast-gateway-mac 0000.0000.1111	Configure anycast MAC address
(config) # interface irb1001	Configure IRB interface 1001

(config-if)#ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if)#ip address 11.11.11.1/24 anycast	Configure IP address
(config-if)#ipv6 address 11:11::11:1/48	Configure IPv6 address
(config-if)#evpn irb-if-forwarding anycast-gateway-mac	Configure anycast MAC address
(config-if)#exit	Exit from interface config mode
(config)#interface irb2001	Configure IRB interface 2001
(config-if)#ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if)#ip address 21.21.21.1/24 anycast	Configure IP address
(config-if)#ipv6 address 21:21::21:1/48	Configure IPv6 address
(config-if)#evpn irb-if-forwarding anycast-gateway-mac	Configure anycast MAC address
(config-if)#exit	Exit from interface config mode
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board
(config)#router bgp 5000	Enter into BGP router mode
(config-router)#address-family ipv4 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router-af)#redistribute connected	Redistribute connected
(config-router-af)#exit-address-family	Exit from address-family
(config)# nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo)#vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo)# evpn irb1001	Configure IRB1001 under VXLAN ID 101
(config-nvo)#exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config)#nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo)#vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo)# evpn irb2001	Configure IRB2001 under VXLAN ID 201
(config-nvo)#exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

VTEP5

(config)#nvo vxlan irb	Enable VXLAN IRB
(config)#ip vrf L3VRF1	Create MAC routing/forwarding instance with L3VRF1 name and enter into VRF mode
(config-vrf)#rd 51000:11	Assign RD value
(config-vrf)# route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf)# l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf)#exit	Exit from VRF mode

(config) # evpn irb-forwarding anycast-gateway-mac 0000.0000.1111	Configure anycast MAC address
(config) # interface irb1001	Configure IRB interface 1001
(config-if)#ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if)#ip address 11.11.11.1/24 anycast	Configure IP address
(config-if)#ipv6 address 11:11::11:1/48	Configure IPv6 address
(config-if)#evpn irb-if-forwarding anycast-gateway-mac	Configure anycast MAC address
(config-if)#exit	Exit from interface config mode
(config) #interface irb2001	Configure IRB interface 2001
(config-if)#ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if)#ip address 21.21.21.1/24 anycast	Configure IP address
(config-if)#ipv6 address 21:21::21:1/48	Configure IPv6 address
(config-if) evpn irb-if-forwarding anycast-gateway-mac	Configure anycast MAC address
(config-if)#exit	Exit from interface config mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board
(config) #router bgp 5000	Enter into BGP router mode
(config-router) #address-family ipv4 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) #exit-address-family	Exit from address-family
(config) # nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # evpn irb1001	Configure IRB1001 under VXLAN ID 101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # evpn irb2001	Configure IRB2001 under VXLAN ID 201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

Validations

VTEP1

```
TB2-VTEP1#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination      Status      Up/Down      Update
=====
```

```

1.1.1.1      5.5.5.5      Installed      00:13:05      00:13:05
1.1.1.1      4.4.4.4      Installed      00:18:33      00:18:33
1.1.1.1      2.2.2.2      Installed      00:18:34      00:18:34

```

Total number of entries are 3

TB2-VTEP1#show nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port

AC - Access Port

(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status	Src-Addr	Dst-Addr
101	VNI-101	L2	NW	----	----	----	----	1.1.1.1	5.5.5.5
101	VNI-101	L2	NW	----	----	----	----	1.1.1.1	4.4.4.4
101	VNI-101	L2	NW	----	----	----	----	1.1.1.1	2.2.2.2
101	VNI-101	--	AC	pol	00:00:00:00:00:00:22:22:00:00:00	10	DF	----	----
201	VNI-201	L2	NW	----	----	----	----	1.1.1.1	5.5.5.5
201	VNI-201	L2	NW	----	----	----	----	1.1.1.1	4.4.4.4
201	VNI-201	L2	NW	----	----	----	----	1.1.1.1	2.2.2.2
201	VNI-201	--	AC	pol	00:00:00:00:00:00:22:22:00:00:00	20	DF	----	----

Total number of entries are 8

TB2-VTEP1#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
201	21.21.21.51	0000.2222.1020	Static Local	----	
201	21.21.21.1	0000.0000.1111	Static Local	----	
201	21.21.21.101	0000.4444.1020	Static Remote	----	
101	11.11.11.51	0000.2222.1010	Static Local	----	
101	11.11.11.1	0000.0000.1111	Static Local	----	
101	11.11.11.201	0000.5555.1010	Static Remote	----	

Total number of entries are 6

TB2-VTEP1#show nvo vxlan nd-cache

VXLAN ND-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
201	21.21.21.1	0000.0000.1111	Static Local	----	
101	11.11.11.1	0000.0000.1111	Static Local	----	
Total number of entries are 2					
TB2-VTEP1#show nvo vxlan l3vni-map					
L3VNI L2VNI IRB-interface					
=====					
1000	101	irb1001			
1000	201	irb2001			

TB2-VTEP1#show ip route vrf L3VRF1

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
ia - IS-IS inter area, E - EVPN,
v - vrf leaked
* - candidate default

IP Route Table for VRF "L3VRF1"

```

C      11.11.11.0/24 is directly connected, irb1001, 00:19:26
C      21.21.21.0/24 is directly connected, irb2001, 00:19:26
C      127.0.0.0/8 is directly connected, lo.L3VRF1, 00:19:28

```

Gateway of last resort is not set

TB2-VTEP1#show ipv6 route vrf L3VRF1

IPv6 Routing Table

Codes: K - kernel route, C - connected, S - static, R - RIP, O - OSPF,
IA - OSPF inter area, E1 - OSPF external type 1,
E2 - OSPF external type 2, E - EVPN N1 - OSPF NSSA external type 1,
N2 - OSPF NSSA external type 2, i - IS-IS, B - BGP

Timers: Uptime

```
IP Route Table for VRF "L3VRF1"
C      ::1/128 via ::, lo.L3VRF1, 00:19:28
C      11:11::/48 via ::, irb1001, 00:19:26
C      21:21::/48 via ::, irb2001, 00:19:26
C      fe80::/64 via ::, irb2001, 00:19:25
TB2-VTEP1#show ip route summary
```

```
-----  
IP routing table name is Default-IP-Routing-Table(0)  
-----
```

```
IP routing table maximum-paths : 8
Total number of IPv4 routes : 12
Total number of IPv4 paths : 12
Pending routes (due to route max reached): 0
Route Source Networks
connected 3
ospf 9
Total 12
FIB 12
```

```
ECMP statistics (active in ASIC):
 Total number of IPv4 ECMP routes : 0
 Total number of IPv4 ECMP paths : 0
TB2-VTEP1#show ipv6 route summary
```

```
-----  
IPv6 routing table name is Default-IPv6-Routing-Table(0)  
-----
```

```
IPv6 routing table maximum-paths : 8
Total number of IPv6 routes : 2
Total number of IPv6 paths : 2
Pending routes (due to route max reached): 0
Route Source Networks
connected 2
Total 2
FIB 2
```

```
ECMP statistics (active in ASIC):
 Total number of IPv6 ECMP routes : 0
 Total number of IPv6 ECMP paths : 0
TB2-VTEP1#show bgp l2vpn evpn
```

```
BGP table version is 6, local router ID is 1.1.1.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
              l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete
```

```
[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]
```

```
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route
4 - Ethernet Segment Route
5 - Prefix Route
```

Network	Next Hop	Metric	LocPrf	Weight	Path	Peer	Encap
RD[21000:11]							
*>i [5]:[0]:[1000]:[24]:[11.11.11.0]:[0.0.0.0]:[1000]	2.2.2.2	0	100	0	?	2.2.2.2	VXLAN
*>i [5]:[0]:[1000]:[24]:[21.21.21.0]:[0.0.0.0]:[1000]	2.2.2.2	0	100	0	?	2.2.2.2	VXLAN
RD[41000:11]							
*>i [5]:[0]:[1000]:[24]:[11.11.11.0]:[0.0.0.0]:[1000]	4.4.4.4	0	100	0	?	4.4.4.4	VXLAN
*>i [5]:[0]:[1000]:[24]:[21.21.21.0]:[0.0.0.0]:[1000]	4.4.4.4	0	100	0	?	4.4.4.4	VXLAN
RD[51000:11]							
*>i [5]:[0]:[1000]:[24]:[11.11.11.0]:[0.0.0.0]:[1000]	5.5.5.5	0	100	0	?	5.5.5.5	VXLAN
*>i [5]:[0]:[1000]:[24]:[21.21.21.0]:[0.0.0.0]:[1000]							

<pre> RD[1.1.1.1:1] VRF[evpn-gvrf-1]: *> [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0] 1.1.1.1 0 100 32768 i ----- VXLAN *> [4]:[00:00:00:00:00:22:22:00:00:00]:[32,1.1.1.1] 1.1.1.1 0 100 32768 i ----- VXLAN * i [4]:[00:00:00:00:00:22:22:00:00:00]:[32,2.2.2.2] 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN RD[1.1.1.1:11] VRF[L2VRF1]: *> [1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101] 1.1.1.1 0 100 32768 i ----- VXLAN * i 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN * i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0] 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN * i [2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101] 5.5.5.5 0 100 0 i 5.5.5.5 VXLAN * i 4.4.4.4 0 100 0 i 4.4.4.4 VXLAN * i 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN *> 1.1.1.1 0 100 32768 i ----- VXLAN * i [2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101] 5.5.5.5 0 100 0 i 5.5.5.5 VXLAN * i 4.4.4.4 0 100 0 i 4.4.4.4 VXLAN * i 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN *> 1.1.1.1 0 100 32768 i ----- VXLAN *> [2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101] 1.1.1.1 0 100 32768 i ----- VXLAN * i 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN * i [2]:[0]:[101]:[48,0000:5555:1010]:[32,11.11.11.201]:[101] 5.5.5.5 0 100 0 i 5.5.5.5 VXLAN *> [3]:[101]:[32,1.1.1.1] 1.1.1.1 0 100 32768 i ----- VXLAN * i [3]:[101]:[32,2.2.2.2] 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN * i [3]:[101]:[32,4.4.4.4] 4.4.4.4 0 100 0 i 4.4.4.4 VXLAN * i [3]:[101]:[32,5.5.5.5] 5.5.5.5 0 100 0 i 5.5.5.5 VXLAN RD[1.1.1.1:21] VRF[L2VRF2]: *> [1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201] 1.1.1.1 0 100 32768 i ----- VXLAN * i 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN * i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0] 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN * i [2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201] 5.5.5.5 0 100 0 i 5.5.5.5 VXLAN * i 4.4.4.4 0 100 0 i 4.4.4.4 VXLAN * i 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN *> 1.1.1.1 0 100 32768 i ----- VXLAN * i [2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201] 5.5.5.5 0 100 0 i 5.5.5.5 VXLAN * i 4.4.4.4 0 100 0 i 4.4.4.4 VXLAN * i 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN *> 1.1.1.1 0 100 32768 i ----- VXLAN *> [2]:[00:00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201] 1.1.1.1 0 100 32768 i ----- VXLAN * i 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN * i [2]:[0]:[201]:[48,0000:4444:1020]:[32,21.21.21.101]:[201] 4.4.4.4 0 100 0 i 4.4.4.4 VXLAN *> [3]:[201]:[32,1.1.1.1] 1.1.1.1 0 100 32768 i ----- VXLAN * i [3]:[201]:[32,2.2.2.2] 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN * i [3]:[201]:[32,4.4.4.4] 4.4.4.4 0 100 0 i 4.4.4.4 VXLAN * i [3]:[201]:[32,5.5.5.5] 5.5.5.5 0 100 0 i 5.5.5.5 VXLAN RD[2.2.2.2:1] *>i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0] 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN </pre>	
--	--

```

*>i [4]:[00:00:00:00:00:22:22:00:00:00]:[32,2.2.2.2]
      2.2.2.2          0         100      0   i  2.2.2.2       VXLAN

RD[2.2.2.2:11]
*>i [1]:[00:00:00:00:22:22:00:00:00]:[101]:[101]
      2.2.2.2          0         100      0   i  2.2.2.2       VXLAN
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101]
      2.2.2.2          0         100      0   i  2.2.2.2       VXLAN
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101]
      2.2.2.2          0         100      0   i  2.2.2.2       VXLAN
*>i [2]:[00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]
      2.2.2.2          0         100      0   i  2.2.2.2       VXLAN
*>i [3]:[101]:[32,2.2.2.2]
      2.2.2.2          0         100      0   i  2.2.2.2       VXLAN

RD[2.2.2.2:21]
*>i [1]:[00:00:00:00:22:22:00:00:00]:[201]:[201]
      2.2.2.2          0         100      0   i  2.2.2.2       VXLAN
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201]
      2.2.2.2          0         100      0   i  2.2.2.2       VXLAN
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201]
      2.2.2.2          0         100      0   i  2.2.2.2       VXLAN
*>i [2]:[00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
      2.2.2.2          0         100      0   i  2.2.2.2       VXLAN
*>i [3]:[201]:[32,2.2.2.2]
      2.2.2.2          0         100      0   i  2.2.2.2       VXLAN

RD[4.4.4.4:11]
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101]
      4.4.4.4          0         100      0   i  4.4.4.4       VXLAN
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101]
      4.4.4.4          0         100      0   i  4.4.4.4       VXLAN
*>i [3]:[101]:[32,4.4.4.4]
      4.4.4.4          0         100      0   i  4.4.4.4       VXLAN

RD[4.4.4.4:21]
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201]
      4.4.4.4          0         100      0   i  4.4.4.4       VXLAN
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201]
      4.4.4.4          0         100      0   i  4.4.4.4       VXLAN
*>i [2]:[0]:[201]:[48,0000:4444:1020]:[32,21.21.21.101]:[201]
      4.4.4.4          0         100      0   i  4.4.4.4       VXLAN
*>i [3]:[201]:[32,4.4.4.4]
      4.4.4.4          0         100      0   i  4.4.4.4       VXLAN

RD[5.5.5.5:11]
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101]
      5.5.5.5          0         100      0   i  5.5.5.5       VXLAN
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101]
      5.5.5.5          0         100      0   i  5.5.5.5       VXLAN
*>i [2]:[0]:[101]:[48,0000:5555:1010]:[32,11.11.11.201]:[101]
      5.5.5.5          0         100      0   i  5.5.5.5       VXLAN
*>i [3]:[101]:[32,5.5.5.5]
      5.5.5.5          0         100      0   i  5.5.5.5       VXLAN

RD[5.5.5.5:21]
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201]
      5.5.5.5          0         100      0   i  5.5.5.5       VXLAN
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201]
      5.5.5.5          0         100      0   i  5.5.5.5       VXLAN
*>i [3]:[201]:[32,5.5.5.5]
      5.5.5.5          0         100      0   i  5.5.5.5       VXLAN

Total number of prefixes 55
TB2-VTEP1#

```

```

TB2-VTEP2#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination        Status        Up/Down        Update
=====
2.2.2.2          4.4.4.4        Installed     00:18:42      00:18:42
2.2.2.2          1.1.1.1        Installed     00:18:43      00:18:43

```

2.2.2.2 5.5.5.5 Installed 00:13:14 00:13:14

Total number of entries are 3
TB2-VTEP2#show nvo vxlan
VXLAN Information
=====
Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status	Src-Addr	Dst-Addr
101	VNI-101	L2	NW	----	----	----	----	2.2.2.2	4.4.4.4
101	VNI-101	L2	NW	----	----	----	----	2.2.2.2	1.1.1.1
101	VNI-101	L2	NW	----	----	----	----	2.2.2.2	5.5.5.5
101	VNI-101	--	AC	pol	00:00:00:00:00:22:22:00:00:00	10	NON-DF	----	----
201	VNI-201	L2	NW	----	----	----	----	2.2.2.2	4.4.4.4
201	VNI-201	L2	NW	----	----	----	----	2.2.2.2	1.1.1.1
201	VNI-201	L2	NW	----	----	----	----	2.2.2.2	5.5.5.5
201	VNI-201	--	AC	pol	00:00:00:00:00:22:22:00:00:00	20	NON-DF	----	----

Total number of entries are 8
TB2-VTEP2#show nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====
VNID Ip-Addr Mac-Addr Type Age-Out Retries-Left

201	21.21.21.51	0000.2222.1020	Static Local	----	
201	21.21.21.1	0000.0000.1111	Static Local	----	
201	21.21.21.101	0000.4444.1020	Static Remote	----	
101	11.11.11.51	0000.2222.1010	Static Local	----	
101	11.11.11.1	0000.0000.1111	Static Local	----	
101	11.11.11.201	0000.5555.1010	Static Remote	----	

Total number of entries are 6
TB2-VTEP2#show nvo vxlan nd-cache
VXLAN ND-CACHE Information
=====
VNID Ip-Addr Mac-Addr Type Age-Out Retries-Left

201	21.21.21.1	0000.0000.1111	Static Local	----	
101	11.11.11.1	0000.0000.1111	Static Local	----	

Total number of entries are 2
TB2-VTEP2#show nvo vxlan l3vni-map
L3VNI L2VNI IRB-interface
=====
1000 101 irb1001
1000 201 irb2001

TB2-VTEP2#show ip route vrf L3VRF1
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
ia - IS-IS inter area, E - EVPN,
v - vrf leaked
* - candidate default

IP Route Table for VRF "L3VRF1"
C 11.11.11.0/24 is directly connected, irb1001, 00:19:37
C 21.21.21.0/24 is directly connected, irb2001, 00:19:37
C 127.0.0.0/8 is directly connected, lo.L3VRF1, 00:19:40

Gateway of last resort is not set
TB2-VTEP2#show ipv6 route vrf L3VRF1
IPv6 Routing Table
Codes: K - kernel route, C - connected, S - static, R - RIP, O - OSPF,
IA - OSPF inter area, E1 - OSPF external type 1,
E2 - OSPF external type 2, E - EVPN N1 - OSPF NSSA external type 1,
N2 - OSPF NSSA external type 2, i - IS-IS, B - BGP
Timers: Uptime

```

IP Route Table for VRF "L3VRF1"
C      ::1/128 via ::, lo.L3VRF1, 00:19:40
C      11:11::/48 via ::, irb1001, 00:19:37
C      21:21::/48 via ::, irb2001, 00:19:37
C      fe80::/64 via ::, irb2001, 00:19:36
TB2-VTEP2#show ip route summary

-----
IP routing table name is Default-IP-Routing-Table(0)
-----
IP routing table maximum-paths : 8
Total number of IPv4 routes : 12
Total number of IPv4 paths : 12
Pending routes (due to route max reached): 0
Route Source Networks
connected 3
ospf 9
Total 12
FIB 12

ECMP statistics (active in ASIC):
 Total number of IPv4 ECMP routes : 0
 Total number of IPv4 ECMP paths : 0
TB2-VTEP2#show ipv6 route summary

-----
IPv6 routing table name is Default-IPv6-Routing-Table(0)
-----
IPv6 routing table maximum-paths : 8
Total number of IPv6 routes : 2
Total number of IPv6 paths : 2
Pending routes (due to route max reached): 0
Route Source Networks
connected 2
Total 2
FIB 2

ECMP statistics (active in ASIC):
 Total number of IPv6 ECMP routes : 0
 Total number of IPv6 ECMP paths : 0
TB2-VTEP2#show bgp 12vpn evpn
BGP table version is 6, local router ID is 2.2.2.2
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
              l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route
4 - Ethernet Segment Route
5 - Prefix Route

      Network          Next Hop           Metric     LocPrf      Weight     Path   Peer        Encap
RD[11000:11]
*>i[5]:[0]:[1000]:[24]:[11.11.11.0]:[0.0.0.0]:[1000]
               1.1.1.1          0         100      0    ? 1.1.1.1      VXLAN
*>i[5]:[0]:[1000]:[24]:[21.21.21.0]:[0.0.0.0]:[1000]
               1.1.1.1          0         100      0    ? 1.1.1.1      VXLAN

RD[41000:11]
*>i[5]:[0]:[1000]:[24]:[11.11.11.0]:[0.0.0.0]:[1000]
               4.4.4.4          0         100      0    ? 4.4.4.4      VXLAN
*>i[5]:[0]:[1000]:[24]:[21.21.21.0]:[0.0.0.0]:[1000]
               4.4.4.4          0         100      0    ? 4.4.4.4      VXLAN

RD[51000:11]
*>i[5]:[0]:[1000]:[24]:[11.11.11.0]:[0.0.0.0]:[1000]
               5.5.5.5          0         100      0    ? 5.5.5.5      VXLAN
*>i[5]:[0]:[1000]:[24]:[21.21.21.0]:[0.0.0.0]:[1000]
               5.5.5.5          0         100      0    ? 5.5.5.5      VXLAN

```

```

RD[1.1.1.1:1]
*>i[1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>i[4]:[00:00:00:00:00:22:22:00:00:00]:[32,1.1.1.1]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN

RD[1.1.1.1:11]
*>i[1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>i[2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>i[2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>i[2]:[00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>i[3]:[101]:[32,1.1.1.1]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN

RD[1.1.1.1:21]
*>i[1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>i[2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>i[2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>i[2]:[00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>i[3]:[201]:[32,1.1.1.1]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN

RD[2.2.2.2:1] VRF[evpn-gvrf-1]:
*> [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
    2.2.2.2          0      100      32768   i  -----      VXLAN
* i[4]:[00:00:00:00:00:22:22:00:00:00]:[32,1.1.1.1]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*> [4]:[00:00:00:00:00:22:22:00:00:00]:[32,2.2.2.2]
    2.2.2.2          0      100      32768   i  -----      VXLAN

RD[2.2.2.2:11] VRF[L2VRF1]:
* i[1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>     2.2.2.2          0      100      32768   i  -----      VXLAN
* i[1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
* i[2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101]
    5.5.5.5          0      100      0   i  5.5.5.5      VXLAN
* i     4.4.4.4          0      100      0   i  4.4.4.4      VXLAN
* i     1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>     2.2.2.2          0      100      32768   i  -----      VXLAN
* i[2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101]
    5.5.5.5          0      100      0   i  5.5.5.5      VXLAN
* i     4.4.4.4          0      100      0   i  4.4.4.4      VXLAN
* i     1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>     2.2.2.2          0      100      32768   i  -----      VXLAN
* i[2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>     2.2.2.2          0      100      32768   i  -----      VXLAN
* i[2]:[0]:[101]:[48,0000:5555:1010]:[32,11.11.11.201]:[101]
    5.5.5.5          0      100      0   i  5.5.5.5      VXLAN
* i[3]:[101]:[32,1.1.1.1]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*> [3]:[101]:[32,2.2.2.2]
    2.2.2.2          0      100      32768   i  -----      VXLAN
* i[3]:[101]:[32,4.4.4.4]
    4.4.4.4          0      100      0   i  4.4.4.4      VXLAN
* i[3]:[101]:[32,5.5.5.5]
    5.5.5.5          0      100      0   i  5.5.5.5      VXLAN

RD[2.2.2.2:21] VRF[L2VRF2]:
* i[1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201]
    1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>     2.2.2.2          0      100      32768   i  -----      VXLAN
* i[1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]

```

```

        1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
* i[2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201]
        5.5.5.5          0      100      0   i  5.5.5.5      VXLAN
* i          4.4.4.4          0      100      0   i  4.4.4.4      VXLAN
* i          1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>          2.2.2.2          0      100    32768 i  -----
* i[2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201]
        5.5.5.5          0      100      0   i  5.5.5.5      VXLAN
* i          4.4.4.4          0      100      0   i  4.4.4.4      VXLAN
* i          1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>          2.2.2.2          0      100    32768 i  -----
* i[2]:[0]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
        1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*>          2.2.2.2          0      100    32768 i  -----
* i[2]:[0]:[201]:[48,0000:4444:1020]:[32,21.21.21.101]:[201]
        4.4.4.4          0      100      0   i  4.4.4.4      VXLAN
* i[3]:[201]:[32,1.1.1.1]
        1.1.1.1          0      100      0   i  1.1.1.1      VXLAN
*> [3]:[201]:[32,2.2.2.2]
        2.2.2.2          0      100    32768 i  -----
* i[3]:[201]:[32,4.4.4.4]
        4.4.4.4          0      100      0   i  4.4.4.4      VXLAN
* i[3]:[201]:[32,5.5.5.5]
        5.5.5.5          0      100      0   i  5.5.5.5      VXLAN

RD[4.4.4.4:11]
*>i[2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101]
        4.4.4.4          0      100      0   i  4.4.4.4      VXLAN
*>i[2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101]
        4.4.4.4          0      100      0   i  4.4.4.4      VXLAN
*>i[3]:[101]:[32,4.4.4.4]
        4.4.4.4          0      100      0   i  4.4.4.4      VXLAN

RD[4.4.4.4:21]
*>i[2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201]
        4.4.4.4          0      100      0   i  4.4.4.4      VXLAN
*>i[2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201]
        4.4.4.4          0      100      0   i  4.4.4.4      VXLAN
*>i[2]:[0]:[201]:[48,0000:4444:1020]:[32,21.21.21.101]:[201]
        4.4.4.4          0      100      0   i  4.4.4.4      VXLAN
*>i[3]:[201]:[32,4.4.4.4]
        4.4.4.4          0      100      0   i  4.4.4.4      VXLAN

RD[5.5.5.5:11]
*>i[2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101]
        5.5.5.5          0      100      0   i  5.5.5.5      VXLAN
*>i[2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101]
        5.5.5.5          0      100      0   i  5.5.5.5      VXLAN
*>i[2]:[0]:[101]:[48,0000:5555:1010]:[32,11.11.11.201]:[101]
        5.5.5.5          0      100      0   i  5.5.5.5      VXLAN
*>i[3]:[101]:[32,5.5.5.5]
        5.5.5.5          0      100      0   i  5.5.5.5      VXLAN

RD[5.5.5.5:21]
*>i[2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201]
        5.5.5.5          0      100      0   i  5.5.5.5      VXLAN
*>i[2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201]
        5.5.5.5          0      100      0   i  5.5.5.5      VXLAN
*>i[3]:[201]:[32,5.5.5.5]
        5.5.5.5          0      100      0   i  5.5.5.5      VXLAN

Total number of prefixes 55
TB2-VTEP2#

```

VTEP4

```

TB2-VTEP4#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination       Status      Up/Down      Update
=====
4.4.4.4          2.2.2.2       Installed   00:18:55    00:18:55

```

```
4.4.4.4      1.1.1.1      Installed      00:18:55      00:18:55
4.4.4.4      5.5.5.5      Installed      00:13:27      00:13:27
```

Total number of entries are 3

TB2-VTEP4#show nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port

AC - Access Port

(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status	Src-Addr	Dst-Addr
101	VNI-101	L2	NW	----	----	----	----	4.4.4.4	2.2.2.2
101	VNI-101	L2	NW	----	----	----	----	4.4.4.4	1.1.1.1
101	VNI-101	L2	NW	----	----	----	----	4.4.4.4	5.5.5.5
201	VNI-201	L2	NW	----	----	----	----	4.4.4.4	2.2.2.2
201	VNI-201	L2	NW	----	----	----	----	4.4.4.4	1.1.1.1
201	VNI-201	L2	NW	----	----	----	----	4.4.4.4	5.5.5.5
201	VNI-201	--	AC	sal	--- Single Homed Port ---	20	----	----	----

Total number of entries are 7

TB2-VTEP4#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
201	21.21.21.51	0000.2222.1020	Static Remote	----	
201	21.21.21.1	0000.0000.1111	Static Local	----	
201	21.21.21.101	0000.4444.1020	Static Local	----	
101	11.11.11.51	0000.2222.1010	Static Remote	----	
101	11.11.11.1	0000.0000.1111	Static Local	----	
101	11.11.11.201	0000.5555.1010	Static Remote	----	

Total number of entries are 6

TB2-VTEP4#show nvo vxlan nd-cache

VXLAN ND-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
201	21.21.21.1	0000.0000.1111	Static Local	----	
101	11.11.11.1	0000.0000.1111	Static Local	----	

Total number of entries are 2

TB2-VTEP4#show nvo vxlan l3vni-map

L3VNI L2VNI IRB-interface

=====

1000	101	irb1001
1000	201	irb2001

TB2-VTEP4#show ip route vrf L3VRF1

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP

O - OSPF, IA - OSPF inter area

N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2

E1 - OSPF external type 1, E2 - OSPF external type 2

i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,

ia - IS-IS inter area, E - EVPN,

v - vrf leaked

* - candidate default

IP Route Table for VRF "L3VRF1"

C 11.11.11.0/24 is directly connected, irb1001, 00:19:46

C 21.21.21.0/24 is directly connected, irb2001, 00:19:46

C 127.0.0.0/8 is directly connected, lo.L3VRF1, 00:19:49

Gateway of last resort is not set

TB2-VTEP4#show ipv6 route vrf L3VRF1

IPv6 Routing Table

Codes: K - kernel route, C - connected, S - static, R - RIP, O - OSPF,

IA - OSPF inter area, E1 - OSPF external type 1,

E2 - OSPF external type 2, E - EVPN N1 - OSPF NSSA external type 1,

N2 - OSPF NSSA external type 2, i - IS-IS, B - BGP

Timers: Uptime

```

IP Route Table for VRF "L3VRF1"
C      ::1/128 via ::, lo.L3VRF1, 00:19:49
C      11:11::/48 via ::, irb1001, 00:19:46
C      21:21::/48 via ::, irb2001, 00:19:46
C      fe80::/64 via ::, irb2001, 00:19:46
TB2-VTEP4#show ip route summary

-----
IP routing table name is Default-IP-Routing-Table(0)
-----
IP routing table maximum-paths : 8
Total number of IPv4 routes : 12
Total number of IPv4 paths : 12
Pending routes (due to route max reached): 0
Route Source Networks
connected 3
ospf 9
Total 12
FIB 12

ECMP statistics (active in ASIC):
 Total number of IPv4 ECMP routes : 0
 Total number of IPv4 ECMP paths : 0
TB2-VTEP4#show ipv6 route summary

-----
IPv6 routing table name is Default-IPv6-Routing-Table(0)
-----
IPv6 routing table maximum-paths : 8
Total number of IPv6 routes : 2
Total number of IPv6 paths : 2
Pending routes (due to route max reached): 0
Route Source Networks
connected 2
Total 2
FIB 2

ECMP statistics (active in ASIC):
 Total number of IPv6 ECMP routes : 0
 Total number of IPv6 ECMP paths : 0
TB2-VTEP4#show bgp 12vpn evpn
BGP table version is 4, local router ID is 4.4.4.4
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
              l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route
4 - Ethernet Segment Route
5 - Prefix Route

      Network          Next Hop           Metric     LocPrf      Weight     Path   Peer        Encap
RD[11000:11]
*>i  [5]:[0]:[1000]:[24]:[11.11.11.0]:[0.0.0.0]:[1000]
          1.1.1.1          0         100      0    ?  1.1.1.1      VXLAN
*>i  [5]:[0]:[1000]:[24]:[21.21.21.0]:[0.0.0.0]:[1000]
          1.1.1.1          0         100      0    ?  1.1.1.1      VXLAN

RD[21000:11]
*>i  [5]:[0]:[1000]:[24]:[11.11.11.0]:[0.0.0.0]:[1000]
          2.2.2.2          0         100      0    ?  2.2.2.2      VXLAN
*>i  [5]:[0]:[1000]:[24]:[21.21.21.0]:[0.0.0.0]:[1000]
          2.2.2.2          0         100      0    ?  2.2.2.2      VXLAN

RD[51000:11]
*>i  [5]:[0]:[1000]:[24]:[11.11.11.0]:[0.0.0.0]:[1000]
          5.5.5.5          0         100      0    ?  5.5.5.5      VXLAN
*>i  [5]:[0]:[1000]:[24]:[21.21.21.0]:[0.0.0.0]:[1000]
          5.5.5.5          0         100      0    ?  5.5.5.5      VXLAN

```

```

RD[1.1.1.1:1]
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
*>i [4]:[00:00:00:00:00:22:22:00:00:00]:[32,1.1.1.1]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN

RD[1.1.1.1:11]
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
*>i [2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
*>i [3]:[101]:[32,1.1.1.1]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN

RD[1.1.1.1:21]
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
*>i [2]:[00:00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
*>i [3]:[201]:[32,1.1.1.1]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN

RD[2.2.2.2:1]
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
      2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>i [4]:[00:00:00:00:00:22:22:00:00:00]:[32,2.2.2.2]
      2.2.2.2          0     100      0   i  2.2.2.2       VXLAN

RD[2.2.2.2:11]
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101]
      2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101]
      2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101]
      2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>i [2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]
      2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>i [3]:[101]:[32,2.2.2.2]
      2.2.2.2          0     100      0   i  2.2.2.2       VXLAN

RD[2.2.2.2:21]
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201]
      2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201]
      2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201]
      2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>i [2]:[00:00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
      2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>i [3]:[201]:[32,2.2.2.2]
      2.2.2.2          0     100      0   i  2.2.2.2       VXLAN

RD[4.4.4.4:11] VRF[L2VRF1]:
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i 2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i 2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
* i [2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101]
      5.5.5.5          0     100      0   i  5.5.5.5       VXLAN
* i 1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i 2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
* > 4.4.4.4          0     100    32768 i  -----       VXLAN
* i [2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101]

```

```

      5.5.5.5          0     100      0   i  5.5.5.5       VXLAN
* i    1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i    2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>    4.4.4.4          0     100      32768 i  -----  VXLAN
* i  [2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i  [2]:[0]:[101]:[48,0000:5555:1010]:[32,11.11.11.201]:[101]
      5.5.5.5          0     100      0   i  5.5.5.5       VXLAN
* i  [3]:[101]:[32,1.1.1.1]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i  [3]:[101]:[32,2.2.2.2]
      2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>  [3]:[101]:[32,4.4.4.4]
      4.4.4.4          0     100      32768 i  -----  VXLAN
* i  [3]:[101]:[32,5.5.5.5]
      5.5.5.5          0     100      0   i  5.5.5.5       VXLAN

RD[4.4.4.4:21] VRF[L2VRF2]:
* i  [1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i  2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
* i  [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i  2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
* i  [2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201]
      5.5.5.5          0     100      0   i  5.5.5.5       VXLAN
* i  1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i  2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>  4.4.4.4          0     100      32768 i  -----  VXLAN
* i  [2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201]
      5.5.5.5          0     100      0   i  5.5.5.5       VXLAN
* i  1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i  2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>  4.4.4.4          0     100      32768 i  -----  VXLAN
* i  [2]:[00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i  2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>  [2]:[0]:[201]:[48,0000:4444:1020]:[32,21.21.21.101]:[201]
      4.4.4.4          0     100      32768 i  -----  VXLAN
* i  [3]:[201]:[32,1.1.1.1]
      1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i  [3]:[201]:[32,2.2.2.2]
      2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>  [3]:[201]:[32,4.4.4.4]
      4.4.4.4          0     100      32768 i  -----  VXLAN
* i  [3]:[201]:[32,5.5.5.5]
      5.5.5.5          0     100      0   i  5.5.5.5       VXLAN

RD[5.5.5.5:11]
*>i  [2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101]
      5.5.5.5          0     100      0   i  5.5.5.5       VXLAN
*>i  [2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101]
      5.5.5.5          0     100      0   i  5.5.5.5       VXLAN
*>i  [2]:[0]:[101]:[48,0000:5555:1010]:[32,11.11.11.201]:[101]
      5.5.5.5          0     100      0   i  5.5.5.5       VXLAN
*>i  [3]:[101]:[32,5.5.5.5]
      5.5.5.5          0     100      0   i  5.5.5.5       VXLAN

RD[5.5.5.5:21]
*>i  [2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201]
      5.5.5.5          0     100      0   i  5.5.5.5       VXLAN
*>i  [2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201]
      5.5.5.5          0     100      0   i  5.5.5.5       VXLAN
*>i  [3]:[201]:[32,5.5.5.5]
      5.5.5.5          0     100      0   i  5.5.5.5       VXLAN

```

Total number of prefixes 57
TB2-VTEP4#

VTEP5

```

TB2-VTEP5#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination      Status        Up/Down      Update
=====
5.5.5.5         2.2.2.2        Installed     00:13:36    00:13:36
5.5.5.5         4.4.4.4        Installed     00:13:36    00:13:36
5.5.5.5         1.1.1.1        Installed     00:13:36    00:13:36

Total number of entries are 3
TB2-VTEP5#show nvo vxlan
VXLAN Information
=====
Codes: NW - Network Port
       AC - Access Port
       (u) - Untagged

VNID   VNI-Name   VNI-Type Type Interface ESI           VLAN DF-Status Src-Addr      Dst-Addr
-----
101    VNI-101    L2      NW   ----  ----           ---- ----  5.5.5.5   2.2.2.2
101    VNI-101    L2      NW   ----  ----           ---- ----  5.5.5.5   4.4.4.4
101    VNI-101    L2      NW   ----  ----           ---- ----  5.5.5.5   1.1.1.1
101    VNI-101    --      AC   xe48  --- Single Homed Port ---  10   ----  ----  -----
201    VNI-201    L2      NW   ----  ----           ---- ----  5.5.5.5   2.2.2.2
201    VNI-201    L2      NW   ----  ----           ---- ----  5.5.5.5   4.4.4.4
201    VNI-201    L2      NW   ----  ----           ---- ----  5.5.5.5   1.1.1.1

Total number of entries are 7
TB2-VTEP5#show nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====
VNID   Ip-Addr     Mac-Addr      Type      Age-Out      Retries-Left
-----
201    21.21.21.51 0000.2222.1020 Static Remote  ----
201    21.21.21.1  0000.0000.1111 Static Local   ----
201    21.21.21.101 0000.4444.1020 Static Remote  ----
101    11.11.11.51 0000.2222.1010 Static Remote  ----
101    11.11.11.1  0000.0000.1111 Static Local   ----
101    11.11.11.201 0000.5555.1010 Static Local   ----

Total number of entries are 6
TB2-VTEP5#show nvo vxlan nd-cache
VXLAN ND-CACHE Information
=====
VNID   Ip-Addr     Mac-Addr      Type      Age-Out      Retries-Left
-----
201    21.21::21:1 0000.0000.1111 Static Local   ----
101    11.11::11:1 0000.0000.1111 Static Local   ----

Total number of entries are 2
TB2-VTEP5#show nvo vxlan l3vni-map
L3VNI   L2VNI      IRB-interface
=====
1000    101        irb1001
1000    201        irb2001

TB2-VTEP5#show ip route vrf L3VRF1
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
       O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
       ia - IS-IS inter area, E - EVPN,
       v - vrf leaked
       * - candidate default

IP Route Table for VRF "L3VRF1"
C      11.11.11.0/24 is directly connected, irb1001, 00:14:07
C      21.21.21.0/24 is directly connected, irb2001, 00:14:05
C      127.0.0.0/8 is directly connected, lo.L3VRF1, 00:20:00

Gateway of last resort is not set
TB2-VTEP5#show ipv6 route vrf L3VRF1

```

```

IPv6 Routing Table
Codes: K - kernel route, C - connected, S - static, R - RIP, O - OSPF,
       IA - OSPF inter area, E1 - OSPF external type 1,
       E2 - OSPF external type 2, E - EVPN N1 - OSPF NSSA external type 1,
       N2 - OSPF NSSA external type 2, i - IS-IS, B - BGP
Timers: Uptime

IP Route Table for VRF "L3VRF1"
C      ::/128 via ::, lo.L3VRF1, 00:20:00
C      11:11::/48 via ::, irb1001, 00:14:07
C      21:21::/48 via ::, irb2001, 00:14:05
C      fe80::/64 via ::, irb2001, 00:14:05
TB2-VTEP5#show ip route summary

-----
IP routing table name is Default-IP-Routing-Table(0)
-----
IP routing table maximum-paths : 8
Total number of IPv4 routes : 12
Total number of IPv4 paths : 12
Pending routes (due to route max reached): 0
Route Source Networks
connected 3
ospf 9
Total 12
FIB 12

ECMP statistics (active in ASIC):
Total number of IPv4 ECMP routes : 0
Total number of IPv4 ECMP paths : 0
TB2-VTEP5#show ipv6 route summary

-----
IPv6 routing table name is Default-IPv6-Routing-Table(0)
-----
IPv6 routing table maximum-paths : 8
Total number of IPv6 routes : 2
Total number of IPv6 paths : 2
Pending routes (due to route max reached): 0
Route Source Networks
connected 2
Total 2
FIB 2

ECMP statistics (active in ASIC):
Total number of IPv6 ECMP routes : 0
Total number of IPv6 ECMP paths : 0
TB2-VTEP5#show bgp 12vpn evpn
BGP table version is 7, local router ID is 5.5.5.5
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
              1 - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route
4 - Ethernet Segment Route
5 - Prefix Route

Network          Next Hop           Metric     LocPrf    Weight     Path   Peer          Encap
RD[11000:11]
*>i  [5]:[0]:[1000]:[24]:[11.11.11.0]:[0.0.0.0]:[1000]
          1.1.1.1          0        100      0      ?  1.1.1.1      VXLAN
*>i  [5]:[0]:[1000]:[24]:[21.21.21.0]:[0.0.0.0]:[1000]
          1.1.1.1          0        100      0      ?  1.1.1.1      VXLAN

RD[21000:11]
*>i  [5]:[0]:[1000]:[24]:[11.11.11.0]:[0.0.0.0]:[1000]
          2.2.2.2          0        100      0      ?  2.2.2.2      VXLAN
*>i  [5]:[0]:[1000]:[24]:[21.21.21.0]:[0.0.0.0]:[1000]
          2.2.2.2          0        100      0      ?  2.2.2.2      VXLAN

```

```

RD[41000:11]
*>i [5]:[0]:[1000]:[24]:[11.11.11.0]:[0.0.0.0]:[1000]
        4.4.4.4          0      100      0      ? 4.4.4.4      VXLAN
*>i [5]:[0]:[1000]:[24]:[21.21.21.0]:[0.0.0.0]:[1000]
        4.4.4.4          0      100      0      ? 4.4.4.4      VXLAN

RD[1.1.1.1:1]
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
        1.1.1.1          0      100      0      i 1.1.1.1      VXLAN
*>i [4]:[00:00:00:00:00:22:22:00:00:00]:[32,1.1.1.1]
        1.1.1.1          0      100      0      i 1.1.1.1      VXLAN

RD[1.1.1.1:11]
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101]
        1.1.1.1          0      100      0      i 1.1.1.1      VXLAN
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101]
        1.1.1.1          0      100      0      i 1.1.1.1      VXLAN
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101]
        1.1.1.1          0      100      0      i 1.1.1.1      VXLAN
*>i [2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]
        1.1.1.1          0      100      0      i 1.1.1.1      VXLAN
*>i [3]:[101]:[32,1.1.1.1]
        1.1.1.1          0      100      0      i 1.1.1.1      VXLAN

RD[1.1.1.1:21]
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201]
        1.1.1.1          0      100      0      i 1.1.1.1      VXLAN
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201]
        1.1.1.1          0      100      0      i 1.1.1.1      VXLAN
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201]
        1.1.1.1          0      100      0      i 1.1.1.1      VXLAN
*>i [2]:[00:00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
        1.1.1.1          0      100      0      i 1.1.1.1      VXLAN
*>i [3]:[201]:[32,1.1.1.1]
        1.1.1.1          0      100      0      i 1.1.1.1      VXLAN

RD[2.2.2.2:1]
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
        2.2.2.2          0      100      0      i 2.2.2.2      VXLAN
*>i [4]:[00:00:00:00:00:22:22:00:00:00]:[32,2.2.2.2]
        2.2.2.2          0      100      0      i 2.2.2.2      VXLAN

RD[2.2.2.2:11]
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101]
        2.2.2.2          0      100      0      i 2.2.2.2      VXLAN
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101]
        2.2.2.2          0      100      0      i 2.2.2.2      VXLAN
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101]
        2.2.2.2          0      100      0      i 2.2.2.2      VXLAN
*>i [2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]
        2.2.2.2          0      100      0      i 2.2.2.2      VXLAN
*>i [3]:[101]:[32,2.2.2.2]
        2.2.2.2          0      100      0      i 2.2.2.2      VXLAN

RD[2.2.2.2:21]
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201]
        2.2.2.2          0      100      0      i 2.2.2.2      VXLAN
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201]
        2.2.2.2          0      100      0      i 2.2.2.2      VXLAN
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201]
        2.2.2.2          0      100      0      i 2.2.2.2      VXLAN
*>i [2]:[00:00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
        2.2.2.2          0      100      0      i 2.2.2.2      VXLAN
*>i [3]:[201]:[32,2.2.2.2]
        2.2.2.2          0      100      0      i 2.2.2.2      VXLAN

RD[4.4.4.4:11]
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101]
        4.4.4.4          0      100      0      i 4.4.4.4      VXLAN
*>i [2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101]
        4.4.4.4          0      100      0      i 4.4.4.4      VXLAN
*>i [3]:[101]:[32,4.4.4.4]

```

```

RD[4.4.4.4:21]
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201]
        4.4.4.4          0         100          0     i 4.4.4.4          VXLAN
*>i [2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201]
        4.4.4.4          0         100          0     i 4.4.4.4          VXLAN
*>i [2]:[0]:[201]:[48,0000:4444:1020]:[32,21.21.21.101]:[201]
        4.4.4.4          0         100          0     i 4.4.4.4          VXLAN
*>i [3]:[201]:[32,4.4.4.4]
        4.4.4.4          0         100          0     i 4.4.4.4          VXLAN

RD[5.5.5.5:11] VRF[L2VRF1]:
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101]
        1.1.1.1          0         100          0     i 1.1.1.1          VXLAN
* i 2.2.2.2          0         100          0     i 2.2.2.2          VXLAN
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
        1.1.1.1          0         100          0     i 1.1.1.1          VXLAN
* i 2.2.2.2          0         100          0     i 2.2.2.2          VXLAN
*> [2]:[0]:[101]:[48,0000:0000:1111]:[32,11.11.11.1]:[101]
        5.5.5.5          0         100          32768 i -----          VXLAN
* i 4.4.4.4          0         100          0     i 4.4.4.4          VXLAN
* i 2.2.2.2          0         100          0     i 2.2.2.2          VXLAN
* i 1.1.1.1          0         100          0     i 1.1.1.1          VXLAN
*> [2]:[0]:[101]:[48,0000:0000:1111]:[128,11:11::11:1]:[101]
        5.5.5.5          0         100          32768 i -----          VXLAN
* i 4.4.4.4          0         100          0     i 4.4.4.4          VXLAN
* i 2.2.2.2          0         100          0     i 2.2.2.2          VXLAN
* i 1.1.1.1          0         100          0     i 1.1.1.1          VXLAN
* i [2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]
        1.1.1.1          0         100          0     i 1.1.1.1          VXLAN
* i 2.2.2.2          0         100          0     i 2.2.2.2          VXLAN
*> [2]:[0]:[101]:[48,0000:5555:1010]:[32,11.11.11.201]:[101]
        5.5.5.5          0         100          32768 i -----          VXLAN
* i [3]:[101]:[32,1.1.1.1]
        1.1.1.1          0         100          0     i 1.1.1.1          VXLAN
* i [3]:[101]:[32,2.2.2.2]
        2.2.2.2          0         100          0     i 2.2.2.2          VXLAN
* i [3]:[101]:[32,4.4.4.4]
        4.4.4.4          0         100          0     i 4.4.4.4          VXLAN
*> [3]:[101]:[32,5.5.5.5]
        5.5.5.5          0         100          32768 i -----          VXLAN

RD[5.5.5.5:21] VRF[L2VRF2]:
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201]
        1.1.1.1          0         100          0     i 1.1.1.1          VXLAN
* i 2.2.2.2          0         100          0     i 2.2.2.2          VXLAN
* i [1]:[00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
        1.1.1.1          0         100          0     i 1.1.1.1          VXLAN
* i 2.2.2.2          0         100          0     i 2.2.2.2          VXLAN
*> [2]:[0]:[201]:[48,0000:0000:1111]:[32,21.21.21.1]:[201]
        5.5.5.5          0         100          32768 i -----          VXLAN
* i 4.4.4.4          0         100          0     i 4.4.4.4          VXLAN
* i 2.2.2.2          0         100          0     i 2.2.2.2          VXLAN
* i 1.1.1.1          0         100          0     i 1.1.1.1          VXLAN
*> [2]:[0]:[201]:[48,0000:0000:1111]:[128,21:21::21:1]:[201]
        5.5.5.5          0         100          32768 i -----          VXLAN
* i 4.4.4.4          0         100          0     i 4.4.4.4          VXLAN
* i 2.2.2.2          0         100          0     i 2.2.2.2          VXLAN
* i 1.1.1.1          0         100          0     i 1.1.1.1          VXLAN
* i [2]:[00:00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
        1.1.1.1          0         100          0     i 1.1.1.1          VXLAN
* i 2.2.2.2          0         100          0     i 2.2.2.2          VXLAN
*> [2]:[0]:[201]:[48,0000:4444:1020]:[32,21.21.21.101]:[201]
        4.4.4.4          0         100          0     i 4.4.4.4          VXLAN
* i [3]:[201]:[32,1.1.1.1]
        1.1.1.1          0         100          0     i 1.1.1.1          VXLAN
* i [3]:[201]:[32,2.2.2.2]
        2.2.2.2          0         100          0     i 2.2.2.2          VXLAN
* i [3]:[201]:[32,4.4.4.4]
        4.4.4.4          0         100          0     i 4.4.4.4          VXLAN
*> [3]:[201]:[32,5.5.5.5]
        5.5.5.5          0         100          32768 i -----          VXLAN

```

```
Total number of prefixes 57
TB2-VTEP5#
```

Distributed Gateway

In distributed gateway approach, VTEP will act as default gateways for one or more VNIDs, Each VTEP having its own default gateway IP and MAC configuration for a given VNID.

IRB Configuration for Distributed

Configure from Base Configuration-L2 VXLAN section, then configure below commands for centralized distributed approach.

VTEP4

(config)#nvo vxlan irb	Enable VXLAN irb
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board
(config)#ip vrf L3VRF1	Create MAC routing/forwarding instance with L3VRF1 name and enter into VRF mode
(config-vrf)#rd 41000:11	Assign RD value
(config-vrf)# route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf)# l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf)#exit	Exit from VRF mode
(config)# interface irb2001	Configure IRB interface 2001
(config-if)#ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if)#ip address 21.21.21.1/24	Configure IP address
(config-if)#ipv6 address 21:21::21:1/48	Configure IPv6 address
(config-if)#exit	Exit from interface config mode
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board
(config)#router bgp 5000	Enter into BGP router mode
(config-router)#address-family ipv4 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router-af)#redistribute connected	Redistribute connected
(config-router-af)#exit-address-family	Exit from address-family
(config)#nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo)#vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo)# evpn irb2001	Configure IRB2001 under VXLAN id 201
(config-nvo)#exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

VTEP5

Unconfigure vnid 201 from nvo vxlan.

(config) #nvo vxlan irb	Enable VXLAN IRB
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board
(config) #ip vrf L3VRF1	Create mac routing/forwarding instance with L3VRF1 name and enter into VRF mode
(config-vrf) #rd 51000:11	Assign RD value
(config-vrf) # route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from VRF mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board
(config) # interface irb1001	Configure IRB interface 1001
(config-if) #ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) #ip address 11.11.11.1/24	Configure IP address
(config-if) #ipv6 address 11:11::11:1/48	Configure IPv6 address
(config-if) #exit	Exit from interface config mode
(config) #router bgp 5000	Enter into BGP router mode
(config-router) #address-family ipv4 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) #exit-address-family	Exit from address-family
(config) # nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # evpn irb1001	Configure IRB under VXLAN id 101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

Validations

VTEP4

```
TB2-VTEP4#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination      Status        Up/Down      Update
=====
4.4.4.4         2.2.2.2        Installed     00:01:17    00:01:17
4.4.4.4         1.1.1.1        Installed     00:01:17    00:01:17
4.4.4.4         5.5.5.5        Installed     00:02:22    00:02:22
```

Total number of entries are 3

```
TB2-VTEP4#show nvo vxlan
```

```
VXLAN Information
=====
```

Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status	Src-Addr	Dst-Addr
201	VNI-201	L2	NW	----	----	----	----	4.4.4.4	2.2.2.2
201	VNI-201	L2	NW	----	----	----	----	4.4.4.4	1.1.1.1
201	VNI-201	--	AC	sa1	--- Single Homed Port ---	20	----	----	----
1000	---	L3	NW	----	----	----	----	4.4.4.4	5.5.5.5

Total number of entries are 4

TB2-VTEP4#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
201	21.21.21.51	0000.2222.1020	Static Remote	----	
201	21.21.21.1	3c2c.99c7.077a	Static Local	----	
201	21.21.21.101	0000.4444.1020	Static Local	----	
Total number of entries are 3					
TB2-VTEP4#show nvo vxlan l3vni-map					
L3VNI	L2VNI	IRB-interface			
=====					
1000	201	irb2001			

TB2-VTEP4#show ip route vrf L3VRF1

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
ia - IS-IS inter area, E - EVPN,
v - vrf leaked
* - candidate default

IP Route Table for VRF "L3VRF1"

B	5.5.5.5/32 [0/0] is directly connected, tunvxlan2, 00:02:23
B	11.11.11.0/24 [200/0] via 5.5.5.5 (recursive is directly connected, tunvxlan2), 00:01:26
C	21.21.21.0/24 is directly connected, irb2001, 00:01:18
C	127.0.0.0/8 is directly connected, lo.L3VRF1, 00:02:23

Gateway of last resort is not set

TB2-VTEP4#show ip route summary

IP routing table name is Default-IP-Routing-Table(0)

IP routing table maximum-paths : 8
Total number of IPv4 routes : 12
Total number of IPv4 paths : 12
Pending routes (due to route max reached): 0
Route Source Networks
connected 3
ospf 9
Total 12
FIB 12

ECMP statistics (active in ASIC):

Total number of IPv4 ECMP routes : 0
Total number of IPv4 ECMP paths : 0

TB2-VTEP4#show bgp l2vpn evpn

BGP table version is 13, local router ID is 4.4.4.4
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]

1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route

4 - Ethernet Segment Route
 5 - Prefix Route

Network	Next Hop	Metric	LocPrf	Weight	Path	Peer	Encap
RD[51000:11]							
*>i [5]:[0]:[1000]:[24]:[11.11.11.0]:[0.0.0.0]:[1000]	5.5.5.5	0	100	0	? 5.5.5.5		VXLAN
RD[1.1.1.1:1]							
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]	1.1.1.1	0	100	0	i 1.1.1.1		VXLAN
*>i [4]:[00:00:00:00:00:22:22:00:00:00]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1		VXLAN
RD[1.1.1.1:11]							
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101]	1.1.1.1	0	100	0	i 1.1.1.1		VXLAN
*>i [2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]	1.1.1.1	0	100	0	i 1.1.1.1		VXLAN
*>i [3]:[101]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1		VXLAN
RD[1.1.1.1:21]							
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201]	1.1.1.1	0	100	0	i 1.1.1.1		VXLAN
*>i [2]:[00:00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]	1.1.1.1	0	100	0	i 1.1.1.1		VXLAN
*>i [3]:[201]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1		VXLAN
RD[2.2.2.2:1]							
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
*>i [4]:[00:00:00:00:00:22:22:00:00:00]:[32,2.2.2.2]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
RD[2.2.2.2:11]							
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
*>i [2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
*>i [3]:[101]:[32,2.2.2.2]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
RD[2.2.2.2:21]							
*>i [1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
*>i [2]:[00:00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
*>i [3]:[201]:[32,2.2.2.2]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
RD[4.4.4.4:11] VRF[L2VRF1]:							
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101]	1.1.1.1	0	100	0	i 1.1.1.1		VXLAN
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[2.2.2.2]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]	1.1.1.1	0	100	0	i 1.1.1.1		VXLAN
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[2.2.2.2]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
* i [2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]	1.1.1.1	0	100	0	i 1.1.1.1		VXLAN
* i [2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[2.2.2.2]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
* i [2]:[0]:[101]:[48,0000:5555:1010]:[32,11.11.11.201]:[101]	5.5.5.5	0	100	0	i 5.5.5.5		VXLAN
* i [2]:[0]:[101]:[48,3c2c:99d6:167a]:[32,11.11.11.1]:[101]	5.5.5.5	0	100	0	i 5.5.5.5		VXLAN
* i [2]:[0]:[101]:[48,3c2c:99d6:167a]:[128,11:11::11:1]:[101]	5.5.5.5	0	100	0	i 5.5.5.5		VXLAN
* i [3]:[101]:[32,1.1.1.1]	1.1.1.1	0	100	0	i 1.1.1.1		VXLAN
* i [3]:[101]:[32,2.2.2.2]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN

```

* i [3]:[101]:[32,5.5.5.5]
      5.5.5.5          0     100      0   i 5.5.5.5       VXLAN

RD[4.4.4.4:21] VRF[L2VRF2]:
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201]
      1.1.1.1          0     100      0   i 1.1.1.1       VXLAN
* i 2.2.2.2          0     100      0   i 2.2.2.2       VXLAN
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
      1.1.1.1          0     100      0   i 1.1.1.1       VXLAN
* i 2.2.2.2          0     100      0   i 2.2.2.2       VXLAN
* i [2]:[00:00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
      1.1.1.1          0     100      0   i 1.1.1.1       VXLAN
* i 2.2.2.2          0     100      0   i 2.2.2.2       VXLAN
*> [2]:[0]:[201]:[48,0000:4444:1020]:[32,21.21.21.101]:[201]
      4.4.4.4          0     100    32768 i -----       VXLAN
*> [2]:[0]:[201]:[48,3c2c:99c7:077a]:[32,21.21.21.1]:[201]
      4.4.4.4          0     100    32768 i -----       VXLAN
*> [2]:[0]:[201]:[48,3c2c:99c7:077a]:[128,21:21::21:1]:[201]
      4.4.4.4          0     100    32768 i -----       VXLAN
* i [3]:[201]:[32,1.1.1.1]
      1.1.1.1          0     100      0   i 1.1.1.1       VXLAN
* i [3]:[201]:[32,2.2.2.2]
      2.2.2.2          0     100      0   i 2.2.2.2       VXLAN
*> [3]:[201]:[32,4.4.4.4]
      4.4.4.4          0     100    32768 i -----       VXLAN

RD[5.5.5.5:11]
*>i [2]:[0]:[101]:[48,0000:5555:1010]:[32,11.11.11.201]:[101]
      5.5.5.5          0     100      0   i 5.5.5.5       VXLAN
*>i [2]:[0]:[101]:[48,3c2c:99d6:167a]:[32,11.11.11.1]:[101]
      5.5.5.5          0     100      0   i 5.5.5.5       VXLAN
*>i [2]:[0]:[101]:[48,3c2c:99d6:167a]:[128,11:11::11:1]:[101]
      5.5.5.5          0     100      0   i 5.5.5.5       VXLAN
*>i [3]:[101]:[32,5.5.5.5]
      5.5.5.5          0     100      0   i 5.5.5.5       VXLAN

```

Total number of prefixes 39
TB2-VTEP4#

VTEP5

TB2-VTEP5#show nvo vxlan tunnel
VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
5.5.5.5	2.2.2.2	Installed	00:34:13	00:34:13
5.5.5.5	4.4.4.4	Installed	00:01:26	00:01:26
5.5.5.5	1.1.1.1	Installed	00:34:13	00:34:13

Total number of entries are 3

TB2-VTEP5#show nvo vxlan

VXLAN Information

=====
Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status	Src-Addr	Dst-Addr
101	VNI-101	L2	NW	---	----	---	---	5.5.5.5	2.2.2.2
101	VNI-101	L2	NW	---	----	---	---	5.5.5.5	1.1.1.1
101	VNI-101	--	AC	xe48	--- Single Homed Port ---	10	---	---	---
1000	---	L3	NW	---	----	---	---	5.5.5.5	4.4.4.4

Total number of entries are 4

TB2-VTEP5#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
101	11.11.11.51	0000.2222.1010	Static Remote	----	

```

101      11.11.11.1      3c2c.99d6.167a Static Local    ----
101      11.11.11.201     0000.5555.1010 Static Local    ----
Total number of entries are 3
Total number of entries are 1
TB2-VTEP5#show nvo vxlan 13vni-map
L3VNI          L2VNI          IRB-interface
=====
1000          101           irb1001

TB2-VTEP5#show ip route vrf L3VRF1
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
      O - OSPF, IA - OSPF inter area
      N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
      E1 - OSPF external type 1, E2 - OSPF external type 2
      i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
      ia - IS-IS inter area, E - EVPN,
      v - vrf leaked
      * - candidate default

IP Route Table for VRF "L3VRF1"
B        4.4.4.4/32 [0/0] is directly connected, tunvxlan2, 00:01:26
C        11.11.11.0/24 is directly connected, irb1001, 00:34:43
B        21.21.21.0/24 [200/0] via 4.4.4.4 (recursive is directly connected, tunvxlan2), 00:01:26
C        127.0.0/0/8 is directly connected, lo.L3VRF1, 00:40:36

Gateway of last resort is not set
TB2-VTEP5#show ip route summary

-----
IP routing table name is Default-IP-Routing-Table(0)
-----
IP routing table maximum-paths : 8
Total number of IPv4 routes : 12
Total number of IPv4 paths : 12
Pending routes (due to route max reached): 0
Route Source Networks
connected      3
ospf          9
Total         12
FIB          12

ECMP statistics (active in ASIC):
  Total number of IPv4 ECMP routes : 0
  Total number of IPv4 ECMP paths : 0
TB2-VTEP5#show bgp 12vpn evpn
BGP table version is 13, local router ID is 5.5.5.5
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
              l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route
4 - Ethernet Segment Route
5 - Prefix Route

      Network          Next Hop          Metric      LocPrf      Weight      Path    Peer          Encap
RD[41000:11]
*>i  [5]:[0]:[1000]:[21.21.21.0]:[0.0.0.0]:[1000]
          4.4.4.4          0          100          0      ?  4.4.4.4          VXLAN

RD[1.1.1.1:1]
*>i  [1]:[00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
          1.1.1.1          0          100          0      i  1.1.1.1          VXLAN
*>i  [4]:[00:00:00:00:22:22:00:00:00]:[32,1.1.1.1]
          1.1.1.1          0          100          0      i  1.1.1.1          VXLAN

RD[1.1.1.1:1]
*>i  [1]:[00:00:00:00:22:22:00:00:00]:[101]:[101]
          1.1.1.1          0          100          0      i  1.1.1.1          VXLAN
*>i  [2]:[00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]

```

```

        1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
*>i [3]:[101]:[32,1.1.1.1]
        1.1.1.1          0     100      0   i  1.1.1.1       VXLAN

RD[1.1.1.1:21]
*>i [1]:[00:00:00:00:00:00:22:22:00:00:00]:[201]:[201]
        1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
*>i [2]:[00:00:00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
        1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
*>i [3]:[201]:[32,1.1.1.1]
        1.1.1.1          0     100      0   i  1.1.1.1       VXLAN

RD[2.2.2.2:1]
*>i [1]:[00:00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
        2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>i [4]:[00:00:00:00:00:00:22:22:00:00:00]:[32,2.2.2.2]
        2.2.2.2          0     100      0   i  2.2.2.2       VXLAN

RD[2.2.2.2:11]
*>i [1]:[00:00:00:00:00:00:22:22:00:00:00]:[101]:[101]
        2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>i [2]:[00:00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]
        2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>i [3]:[101]:[32,2.2.2.2]
        2.2.2.2          0     100      0   i  2.2.2.2       VXLAN

RD[2.2.2.2:21]
*>i [1]:[00:00:00:00:00:00:22:22:00:00:00]:[201]:[201]
        2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>i [2]:[00:00:00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
        2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*>i [3]:[201]:[32,2.2.2.2]
        2.2.2.2          0     100      0   i  2.2.2.2       VXLAN

RD[4.4.4.4:21]
*>i [2]:[0]:[201]:[48,0000:4444:1020]:[32,21.21.21.101]:[201]
        4.4.4.4          0     100      0   i  4.4.4.4       VXLAN
*>i [2]:[0]:[201]:[48,3c2c:99c7:077a]:[32,21.21.21.1]:[201]
        4.4.4.4          0     100      0   i  4.4.4.4       VXLAN
*>i [2]:[0]:[201]:[48,3c2c:99c7:077a]:[128,21:21::21:1]:[201]
        4.4.4.4          0     100      0   i  4.4.4.4       VXLAN
*>i [3]:[201]:[32,4.4.4.4]
        4.4.4.4          0     100      0   i  4.4.4.4       VXLAN

RD[5.5.5.5:11] VRF[L2VRF1]:
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[101]:[101]
        1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i 2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
        1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i 2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
* i [2]:[00:00:00:00:00:22:22:00:00:00]:[101]:[48,0000:2222:1010]:[32,11.11.11.51]:[101]
        1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i 2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*> [2]:[0]:[101]:[48,0000:5555:1010]:[32,11.11.11.201]:[101]
        5.5.5.5          0     100    32768 i  -----       VXLAN
*> [2]:[0]:[101]:[48,3c2c:99d6:167a]:[32,11.11.11.1]:[101]
        5.5.5.5          0     100    32768 i  -----       VXLAN
*> [2]:[0]:[101]:[48,3c2c:99d6:167a]:[128,11:11::11:1]:[101]
        5.5.5.5          0     100    32768 i  -----       VXLAN
* i [3]:[101]:[32,1.1.1.1]
        1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i [3]:[101]:[32,2.2.2.2]
        2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
*> [3]:[101]:[32,5.5.5.5]
        5.5.5.5          0     100    32768 i  -----       VXLAN

RD[5.5.5.5:21] VRF[L2VRF2]:
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[201]:[201]
        1.1.1.1          0     100      0   i  1.1.1.1       VXLAN
* i 2.2.2.2          0     100      0   i  2.2.2.2       VXLAN
* i [1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
        1.1.1.1          0     100      0   i  1.1.1.1       VXLAN

```

```

* i 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN
* i [2]:[00:00:00:00:00:22:22:00:00:00]:[201]:[48,0000:2222:1020]:[32,21.21.21.51]:[201]
    1.1.1.1 0 100 0 i 1.1.1.1 VXLAN
* i 2.2.2.2 0 100 0 i 2.2.2.2 VXLAN
* i [2]:[0]:[201]:[48,0000:4444:1020]:[32,21.21.21.101]:[201]
    4.4.4.4 0 100 0 i 4.4.4.4 VXLAN
* i [2]:[0]:[201]:[48,3c2c:99c7:077a]:[32,21.21.21.1]:[201]
    4.4.4.4 0 100 0 i 4.4.4.4 VXLAN
* i [2]:[0]:[201]:[48,3c2c:99c7:077a]:[128,21:21::21:1]:[201]
    4.4.4.4 0 100 0 i 4.4.4.4 VXLAN
* i [3]:[201]:[32,1.1.1.1]
    1.1.1.1 0 100 0 i 1.1.1.1 VXLAN
* i [3]:[201]:[32,2.2.2.2]
    2.2.2.2 0 100 0 i 2.2.2.2 VXLAN
* i [3]:[201]:[32,4.4.4.4]
    4.4.4.4 0 100 0 i 4.4.4.4 VXLAN

```

Total number of prefixes 39
TB2-VTEP5#

VXLAN IRB ECMP

In multihoming, anycast-IP and the same subnet is configured on the multihomed devices within the same VPN on IRB interfaces connected to the multihomed CE. Both VTEP's will advertise same connected prefix route, remote VTEP need to understand this and treat the traffic destined to multihomed CE as ECMP traffic i.e Routed traffic should loadshare to both the VTEP's.

IRB ECMP Configuration

Configure from Base Configuration-L2 VXLAN section and perform commit after configuration, then configure below commands for ECMP approach.

VTEP1

Configure max-path ibgp 2 on VTEP1 under BGP IPv4 VRF address family.

#configure terminal	Enter Configure mode.
(config)#router bgp 5000	Enter into BGP router mode
(config-router)#address-family ipv4 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router)#max-paths ibgp 2	Configure BGP max-path
(config-router-af)#redistribute connected	Redistribute connected
(config-router-af)#exit-address-family	Exit from address-family
(config-router-af)#commit	Commit the transaction

VTEP1 IRB configuration

(config) #nvo vxlan irb	Enable VXLAN IRB
(config) #commit	Commit the transaction and save config and reload board
(config) #ip vrf L3VRF1	Create MAC routing/forwarding instance with L3VRF1 name and enter into VRF mode
(config-vrf) #rd 11000:11	Assign RD value
(config-vrf) # route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from VRF mode
(config) # evpn irb-forwarding anycast-gateway-mac 0000.0000.1111	Configure anycast MAC address
(config) #commit	Commit the transaction
(config) # interface irb1001	Configure IRV interface 1001
(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 11.11.11.1/24 anycast	Configure IP address
(config-if) ipv6 address 11:11::11:1/48	Configure IPv6 address
(config-if) evpn irb-if-forwarding anycast-gateway-mac	Configure anycast MAC address
(config-if) exit	Exit from interface config mode
(config) # interface irb 2001	Configure IRB interface 2001
(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 21.21.21.1/24 anycast	Configure IP address
(config-if) ipv6 address 21:21::21:1/48	Configure IPv6 address
(config-if) evpn irb-if-forwarding anycast-gateway-mac	Configure anycast MAC address
(config-if) exit	Exit from interface config mode
(config) #commit	Commit the transaction
(config) router bgp 5000	Enter into BGP router mode
(config-router) #address-family ipv4 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) #exit-address-family	Exit form address-family
(config) # nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign VRF for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb1001	Configure IRB1001 under VXLAN ID 101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign VRF for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb2001	Configure irb2001 under VXLAN ID 201

(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #commit	Commit the transaction

VTEP2

Configure `max-path ibgp 2` on VTEP1 under BGP IPv4 VRF address family.

#configure terminal	Enter Configure mode.
(config) #router bgp 5000	Enter into BGP router mode
(config-router) #address-family ipv4 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router-af) #max-paths ibgp 2	Configure BGP max-path
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) #exit-address-family	Exit from address-family
(config-router-af) #commit	Commit the transaction

VTEP2 IRB configuration

(config) #nvo vxlan irb	Enable VXLAN irb
(config) #commit	Commit the transaction and save config and reload board
(config) #ip vrf L3VRF1	Create MAC routing/forwarding instance with L3VRF1 name and enter into VRF mode
(config-vrf) #rd 21000:11	Assign RD value
(config-vrf) # route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from VRF mode
(config) # evpn irb-forwarding anycast-gateway-mac 0000.0000.1111	Configure anycast MAC address
(config) #commit	Commit the transaction
(config) # interface irb 1001	Configure IRB interface 1001
(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 11.11.11.1/24 anycast	Configure IP address
(config-if) ipv6 address 11:11::11:1/48	Configure IPv6 address
(config-if) evpn irb-if-forwarding anycast-gateway-mac	Configure anycast MAC address
(config-if) exit	Exit from interface config mode
(config) # interface irb 2001	Configure IRB interface 2001
(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 21.21.21.1/24 anycast	Configure IP address
(config-if) ipv6 address 21:21::21:1/48	Configure IPv6 address
(config-if) evpn irb-if-forwarding anycast-gateway-mac	Configure anycast MAC address
(config-if) exit	Exit from interface config mode
(config) #commit	Commit the transaction
(config) router bgp 5000	Enter into BGP router mode
(config-router) #address-family ipv4 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) #exit-address-family	Exit form address-family
(config) # nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign VRF for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb1001	Configure irb1001 under VXLAN ID 101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign VRF for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb2001	Configure irb2001 under VXLAN id 201

(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #commit	Commit the transaction

VTEP5

Unconfigure - evpn irb-forwarding anycast-gateway-mac and assign different IP address and IPv6 address to IRB interfaces on VTEP1. Resolve the ARP on Traffic generator and verify the learnt MAC is same as IRB interface MAC not the anycast MAC (0000.0000.1111). Configure BGP max-path under BGP process.

Enable VXLAN Multihoming on VTEP5 and reboot the node to apply the Multihoming configuration to hardware.

#configure terminal	Enter Configure mode.
(config) #evpn vxlan multihoming enable	Enable Multihoming, save configs and reboot the board for multihoming to be effective
(config) #commit	Commit the transaction and save config and reload board
(config) #nvo vxlan irb	Enable VXLAN IRB
(config) #commit	Commit the transaction
(config) #ip vrf L3VRF1	Create MAC routing/forwarding instance with L3VRF1 name and enter into VRF mode
(config-vrf) #rd 51000:11	Assign RD value
(config-vrf) # route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #commit	Commit the transaction
(config) # no evpn irb-forwarding anycast-gateway-mac	Delete evpn irb-forwarding anycast-gateway-mac address
(config) #commit	Commit the transaction
(config) # interface irb1001	Configure IRB interface 1001
(config-irb-if) #ip vrf forwarding L3VRF1	Configure L3VRF1
(config-irb-if) #ip address 101.11.11.1/24	Configure IP address
(config-irb-if) #ipv6 address 101:11::11:1/48	Configure IPv6 address
(config-irb-if) #commit	Commit the transaction
(config) #router bgp 5000	Enter into BGP router mode
(config-router) #address-family ipv4 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router-af) # max-paths ibgp 2	Configure BGP max-path .
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) #exit-address-family	Exit from address-family
(config-router-af) #commit	Commit the transaction
(config) # nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # evpn irb1001	Configure IRB under VXLAN ID 101

(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config-nvo) #commit	Commit the transaction

Validations

On VTEP5, verify that in the VRF routing table , ECMP path for the IRB address (11.11.11.1) is via VTEP1 - 1.1.1.1 and VTEP2 -2.2.2.2 . Send the Traffic from VTEP5 Single homed to Multihomed. Traffic should be forwarded via VTEP1 and VTEP2 and is loadshared between the Multihome VTEPs.

VTEP5

TB2-VTEP5#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
5.5.5.5	2.2.2.2	Installed	00:34:13	00:34:13
5.5.5.5	4.4.4.4	Installed	00:01:26	00:01:26
5.5.5.5	1.1.1.1	Installed	00:34:13	00:34:13

Total number of entries are 3

TB2-VTEP5#show nvo vxlan

VXLAN Information

=====
Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status	Src-Addr	Dst-Addr
101	VNI-101	L2	NW	----	----	----	----	5.5.5.5	2.2.2.2
101	VNI-101	L2	NW	----	----	----	----	5.5.5.5	1.1.1.1
101	VNI-101	--	AC	xe48	--- Single Homed Port ---	10	----	----	----
1000	----	L3	NW	----	----	----	----	5.5.5.5	4.4.4.4

Total number of entries are 4

TB2-VTEP5#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
101	11.11.11.1	0000.0000.1111	Static	Remote	----
101	101.11.11.1	3c2c.99d6.168a	Static	Local	----
101	11.11.11.201	0000.5555.1010	Static	Local	----

Total number of entries are 3

Total number of entries are 1

TB2-VTEP5#show nvo vxlan l3vni-map

L3VNI L2VNI IRB-interface

1000	101	irb1001
------	-----	---------

TB2-VTEP5#show ip route vrf L3VRF1

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
 O - OSPF, IA - OSPF inter area
 N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
 E1 - OSPF external type 1, E2 - OSPF external type 2
 i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
 ia - IS-IS inter area, E - EVPN,
 v - vrf leaked
 * - candidate default

```
IP Route Table for VRF "L3VRF1"
C          101.11.11.0/24 is directly connected, irb1001, 00:34:43
B          11.11.11.0/24 [200/0] via 1.1.1.1 (recursive is directly connected, tunvxlan2), 00:01:26
                  [200/0] via 2.2.2.2 (recursive is directly connected, tunvxlan2), 00:01:26
C          127.0.0.0/8 is directly connected, lo.L3VRF1, 00:40:36
```

Gateway of last resort is not set

Send 10000 pps from VTEP5 (Traffic generator- SH5) and verify the counters on VTEP5, VTEP1, VTEP2 and Switch

TB2-VTEP5#show interface counter rate mbps

Interface	Rx mbps	Rx pps	Tx mbps	Tx pps
xe48	100	10000	0.01	8
xe40	0.00	0	106.76	10000

On VTEP1 and VTEP2, verify that traffic is load-balanced on ECMP path from VTEP5.

VTEP1

TB2-VTEP1#show interface counter rate mbps

Interface	Rx mbps	Rx pps	Tx mbps	Tx pps
po2	62.75	5000	0.01	8
po1	0.00	0	62.98	5000
xe25	31.98	2500	0	0
xe26	30.95	2501	0	0
xe2	0.00	0	31.53	2500
xe3	0.00	0	30.53	2500

VTEP2

TB2-VTEP2#show interface counter rate mbps

Interface	Rx mbps	Rx pps	Tx mbps	Tx pps
po3	62.75	5000	0.01	8
po1	0.00	0	62.98	5000
xe27	31.98	2500	0	0
xe28	30.95	2501	0	0
xe8	0.00	0	31.53	2500
xe9	0.00	0	30.53	2500

Verify the Traffic on Multihomed Switch:

SW1 (Multihomed)

TB2-SW1#show interface counter rate mbps

Interface	Rx mbps	Rx pps	Tx mbps	Tx pps
xe1	62.75	5000	0.01	8
xe2	0.00	0	62.98	5000
xe3	31.98	2500	0	0
xe4	30.95	2501	0	0
xe5	0.00	0	31.53	2500
xe6	0.00	0	30.53	2500

Interface	Rx mbps	Rx pps	Tx mbps	Tx pps
po1	100	10000	0.01	8
xe7	0.00	0	100	10000
xe8	25.01	2501	0	0
xe9	24.99	2499	0	0
xe2	24.98	2499	0	0
xe3	25.02	2501	0	0

CHAPTER 2 EVPN IRB - Anycast Support for Multiple Subnets

Overview

An EVPN-based Integrated Routing and Bridging solution enables communication between two Layer-2 Virtual Network Identifiers (VNIDs) using IP-based Virtual Routing and Forwarding (IP-VRF). This enhancement provides Anycast Gateway Routing support for multiple subnets under the IRB interface (per VNID).

Feature Characteristics

- Connects primary or secondary subnets with either router MAC or anycast MAC address.
- Supports Anycast Gateway for multiple subnets under the layer-2 VNID's.
- Subnets A, B, and C can have Anycast Gateway support, while subnet D is reserved for BGP.
- Supports the Interfacefull model for ARP/ND requests and the interfaceless model using the kernel interface with a unique MAC per interface (Router MAC or Anycast MAC) for all subnets.

ARP/ND replies come from the ARP/ND cache table for host requests. Hosts can send Layer-3 packets with either Anycast MAC or Router MAC, and Layer-3 termination in the VTEP happens for both. By default, each subnet uses the Router MAC in ARP/ND cache. When the anycast argument is configured, it updates the ARP cache with the Anycast MAC. BGP withdraws the Route-Type 2 and update with Anycast/Router MAC to inform the configured gateway for the layer-2 VNID to non-default gateway nodes.

Topology

The procedures in this section use the topology in [Figure 2-12](#).




Figure 2-12: EVPN IRB for Multiple Subnets

Note: In the above topology TS1, and TS2 are the tenant systems.

VTEP1: L2 VXLAN configuration

(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan irb	Enable VXLAN IRB
(config) #evpn esi hold-time 90	Configure ESI hold time to allow tunnel to come up at the time of vxlan initialization before making the ESI up. It should be same on both VTEP1 and VTEP2
(config) #evpn vxlan multihoming enable	Enable Multihoming, save configs and reboot the board for multihoming to be effective
(config) #mac vrf L2VRF2	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as Blue
(config-vrf) #rd 1.1.1.1:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF2
(config-vrf) #exit	Exit from vrf mode
(config) #ip vrf L3VRF1	Create MAC routing/forwarding instance with L3VRF1 name and enter into VRF mode
(config-vrf) #rd 11000:11	Assign RD value
(config-vrf) #route-target both 100:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from vrf mode
(config) #mac vrf L2VRF1	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as Red
(config-vrf) #rd 1.1.1.1:11	Assign RD value
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config) # evpn irb-forwarding anycast-gateway-mac	Add evpn irb-forwarding anycast-gateway-mac address
(config) #nvo vxlan vtep-ip-global 1.1.1.1	Assign a global IP to the VTEP
(config) #nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-viddisabled configure and enter into VXLAN tenant mode
(config) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN rout
(config-nvo) # evpn irb1001	Configure irb1001 under vxlan id 101
(config-nvo) # vni-name VNI-101	Configure VNI name as VNI-101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-viddisabled configure and enter into VXLAN tenant mode

(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # evpn irb2001	Configure irb2001 under vxlan id 201
(config-nvo) # vni-name VNI-201	Configure VNI name as VNI-201
(config) #qos enable	Enabling QoS
(config) #hostname VTEP1	Configure hostname

VTEP1: Interface and Loopback configuration

(config) #interface po1	Enter Interface mode for po1 (MH2)
(config-if) #switchport	Make it L2 interface
(config-if) # evpn multi-homed system-mac 0000.0000.2222	Configure system mac as ESI value for Lag (po1) interface. VTEP1 and VTEP2 should have same ESI value
(config) #interface po100	Enter Interface mode for po100
(config-if) #load-interval 30	Make it member port of po1
(config-if) #ip address 100.11.11.1/24	Configure ip address as 100.11.11.1 on network side of Spine-P3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce49	Enter Interface mode for ce49
(config-if) #channel-group 100 mode active	Map the interface ce49 to po1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce52	Enter Interface mode for network side port
(config-if) #ip address 100.11.11.1/24	Configure ip address as 100.11.11.1 on network side of Spine-P3
(config-if) #channel-group 1 mode active	Map the ce52 interface to po100
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) # interface irb1001	Configure IRB interface 1001
(config-if) #ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) #evpn irb-if-forwarding anycast-gateway-mac	Enable an IRB interface to use the global anycast IRB mac-address.
(config-irb-if) # ip address 11.11.11.1/24 anycast	Configure the IPv4 primary address as anycast
(config-irb-if) # ip address 12.11.11.1/24 secondary anycast	Configure secondary IPv4 secondary address as anycast
(config-irb-if) # ip address 13.11.11.1/16 secondary	Configure secondary IPv4 secondary address as anycast
(config-irb-if) # ip address 14.11.11.1/24 secondary	Configure secondary IPv4 secondary address as anycast
(config-irb-if) # ip address 15.11.11.1/16 secondary anycast	Configure secondary IPv4 secondary address as anycast
(config-irb-if) # ip address 16.11.11.1/8 secondary anycast	Configure secondary IPv4 secondary address as anycast
(config-irb-if) # ip address 17.11.11.1/24 secondary anycast	Configure secondary IPv4 secondary address as anycast

(config-irb-if) # ip address 18.11.11.1/16	Configure secondary IPv4 secondary address as anycast
(config-irb-if) # ip address 19.11.11.1/8	Configure secondary IPv4 secondary address as anycast
(config-irb-if) # ip address 20.11.11.1/24	Configure secondary IPv4 secondary address as anycast
(config-irb-if) # ip address 21.11.11.1/8	Configure secondary IPv4 secondary address as anycast
(config-irb-if) # ip address 22.11.11.1/24	Configure secondary IPv4 secondary address as anycast
(config-irb-if) # ip address 25.11.11.1/16	Configure secondary IPv4 secondary address as anycast
(config-irb-if) # ipv6 address 11:11::11:1/48	Configure secondary IPv6 primary address as anycast
(config-irb-if) # ipv6 address 12:11::11:1/64	Configure secondary IPv6 address
(config-irb-if) # ipv6 address 13:11::11:1/48	Configure secondary IPv6 secondary address as anycast
(config-irb-if) # ipv6 address 14:11::11:1/50	Configure secondary IPv6 secondary address as anycast

VTEP1:OSPF configuration

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo ip address)
(config-router) #network 1.1.1.1/32 area 0.0.0.0	Add 1.1.1.1 (lo ip address) network into area 0
(config-router) #network 100.11.11.0/24 area 0.0.0.0	Add 100.11.11.0(Spine-P3) network into area 0
(config-router) #bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.

VTEP1:BGP configuration

(config) #router bgp 5000	Enter into Router BGP mode
(config-router) #bgp router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo ip address)
(config-router) #neighbor 2.2.2.2 remote-as 5000	Specify a VTEP2 loopback ip address and remote-as defined
(config-router) #neighbor 2.2.2.2 update-source lo	Configure update as loopback for VTEP2
(config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2
(config-router) #neighbor 4.4.4.4 remote-as 5000	Specify a VTEP4 loopback ip address and remote-as defined
(config-router) #neighbor 4.4.4.4 update-source lo	Configure update as loopback for VTEP4
(config-router) #neighbor 4.4.4.4 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP4

(config-router) #neighbor 5.5.5.5 remote-as 5000	Specify a VTEP5 loopback ip address and remote-as defined
(config-router) #neighbor 5.5.5.5 update-source lo	Configure update as loopback for VTEP5
(config-router) #neighbor 5.5.5.5 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP5
(config-router) #address-family l2vpn evpn	Enter into l2vpn EVPN address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2(VTEP2) into l2vpn evpn address family mode
(config-router-af) #neighbor 4.4.4.4 activate	Activate 3.3.3.3(VTEP4) into l2vpn evpn address family mode
(config-router-af) #neighbor 5.5.5.5 activate	Activate 5.5.5.5(VTEP5) into l2vpn evpn address family mode
(config-router-af) #exit-address-family	Exit from l2vpn address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode

VTEP1:L2 MAC VRF Configuration

(config) #mac vrf L2VRF1	Create mac routing/forwarding instance with L2VRF1 name and enter into vrf mode
(config-vrf) #rd 1.1.1.1:11	Assign RD value
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as RED
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) #exit	Exit from vrf mode
(config) #mac vrf L2VRF2	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #rd 1.1.1.1:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as BLUE
(config-vrf) #exit	Exit from vrf mode

VTEP1:L2 VXLAN configuration

(config) #nvo vxlan access-if port-vlan po1 10	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vniid 101	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1010 ip 11.11.11.51	Configure static mac-ip
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan po1 20	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vniid 201	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1020 ip 21.21.21.51	Configure static mac-ip
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration

(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #exit	Exit from configuration mode

VTEP2 L2 VXLAN configuration:

(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan irb	Enable VXLAN IRB
(config) #evpn esi hold-time 90	Configure ESI hold time to allow tunnel to come up at the time of vxlan initialization before making the ESI up. It should be same on both VTEP1 and VTEP2
(config) #evpn vxlan multihoming enable	Enable Multihoming
(config) #mac vrf L2VRF2	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as Blue
(config-vrf) #rd 1.1.1.1:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF2
(config-vrf) #exit	Exit from vrf mode
(config) #ip vrf L3VRF1	Create MAC routing/forwarding instance with L3VRF1 name and enter into VRF mode
(config-vrf) #rd 11000:11	Assign RD value
(config-vrf) #route-target both 100:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from vrf mode
(config) #mac vrf L2VRF1	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as Red
(config-vrf) #rd 1.1.1.1:11	Assign RD value
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config) # evpn irb-forwarding anycast-gateway-mac	Add evpn irb-forwarding anycast-gateway-mac address
(config) #nvo vxlan vtep-ip-global 1.1.1.1	Assign a global IP to the VTEP
(config) #nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-viddisabled configure and enter into VXLAN tenant mode
(config) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN rout
(config-nvo) # evpn irb1001	Configure irb1001 under vxlan id 101
(config-nvo) # vni-name VNI-101	Configure VNI name as VNI-101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode

(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-viddisabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # evpn irb2001	Configure irb2001 under vxlan id 201
(config-nvo) # vni-name VNI-201	Configure VNI name as VNI-201
(config) #qos enable	Enabling QoS
VTEP1 (config)#hostname VTEP2	Configure hostname
VTEP2 (config)#exit	Exit from VTEP1

VTEP2:Interface and loopback configuration

(config) #interface po1	Enter Interface mode for po1 (MH2)
(config-if) #switchport	Make it L2 interface
(config-if) # evpn multi-homed system-mac 0000.0000.2222	Configure system mac as ESI value for Lag (po1) interface. VTEP1 and VTEP2 should have same ESI value
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface po100	Enter Interface mode for xe3
(config-if) #load-interval 30	Make it member port of po1
(config-if) #ip address 100.11.11.1/24	Configure ip address as 100.11.11.1 on network side of Spine-P3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce49	Enter Interface mode for ce49
(config-if) #channel-group 100 mode active	Map the ce49 interface to po100
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce52	Enter Interface mode for network side port
(config-if) #ip address 100.11.11.1/24	Configure ip address as 100.11.11.1 on network side of Spine-P3
(config-if) #channel-group 1 mode active	Map the ce52 interface to po1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) # interface irb1001	Configure IRB interface 1001
(config-if) #ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) #evpn irb-if-forwarding anycast-gateway-mac	Enable an IRB interface to use the global anycast IRB mac-address.
(config-irb-if) # ip address 11.11.11.1/24 anycast	Configure primary IPv4 address as anycast
(config-irb-if) # ip address 12.11.11.1/24 secondary anycast	Configure primary IPv4 address as anycast
(config-irb-if) # ip address 13.11.11.1/16 secondary	Configure primary IPv4 address as anycast
(config-irb-if) # ip address 14.11.11.1/24 secondary	Configure primary IPv4 address as anycast
(config-irb-if) # ip address 15.11.11.1/16 secondary anycast	Configure primary IPv4 address as anycast

(config-irb-if) # ip address 16.11.11.1/8 secondary anycast	Configure primary IPv4 address as anycast
(config-irb-if) # ip address 17.11.11.1/24 secondary anycast	Configure primary IPv4 address as anycast
(config-irb-if) # ip address 18.11.11.1/16 secondary anycast	Configure primary IPv4 address as anycast
(config-irb-if) # ip address 19.11.11.1/8 secondary	Configure primary IPv4 address as anycast
(config-irb-if) # ip address 20.11.11.1/24 secondary anycast	Configure primary IPv4 address as anycast
(config-irb-if) # ip address 21.11.11.1/8 secondary anycast	Configure primary IPv4 address as anycast
(config-irb-if) # ip address 22.11.11.1/24 secondary anycast	Configure primary IPv4 address as anycast
(config-irb-if) # ip address 25.11.11.1/16 secondary anycast	Configure primary IPv4 address as anycast
(config-irb-if) # ipv6 address 11:11::11:1/48 anycast	Configure primary IPv4 address as anycast
(config-irb-if) # ipv6 address 12:11::11:1/64	Configure the IPv6 address
(config-irb-if) # ipv6 address 13:11::11:1/48 anycast	Configure the IPv6 address as primary anycast
(config-irb-if) # ipv6 address 14:11::11:1/50 anycast	Configure the IPv6 address as anycast

VTEP2:OSPF configuration

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo ip address)
(config-router) #network 1.1.1.1/32 area 0.0.0.0	Add 1.1.1.1 (lo ip address) network into area 0
(config-router) #network 100.11.11.0/24 area 0.0.0.0	Add 100.11.11.0(Spine-P3) network into area 0
(config-router) #bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.

VTEP2:BGP configuration

(config) #router bgp 5000	Enter into Router BGP mode
(config-router) #bgp router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo ip address)
(config-router) #neighbor 2.2.2.2 remote-as 5000	Specify a VTEP2 loopback ip address and remote-as defined
(config-router) #neighbor 2.2.2.2 update-source lo	Configure update as loopback for VTEP2
(config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2
(config-router) #neighbor 4.4.4.4 remote-as 5000	Specify a VTEP4 loopback ip address and remote-as defined

(config-router) #neighbor 4.4.4.4 update-source lo	Configure update as loopback for VTEP4
(config-router) #neighbor 4.4.4.4 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP4
(config-router) #neighbor 5.5.5.5 remote-as 5000	Specify a VTEP5 loopback ip address and remote-as defined
(config-router) #neighbor 5.5.5.5 update-source lo	Configure update as loopback for VTEP5
(config-router) #neighbor 5.5.5.5 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP5
(config-router) #address-family l2vpn evpn	Enter into l2vpn EVPN address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2(VTEP2) into l2vpn evpn address family mode
(config-router-af) #neighbor 4.4.4.4 activate	Activate 3.3.3.3(VTEP4) into l2vpn evpn address family mode
(config-router-af) #neighbor 5.5.5.5 activate	Activate 5.5.5.5(VTEP5) into l2vpn evpn address family mode
(config-router-af) #exit-address-family	Exit from l2vpn address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode

VTEP2:L2 MAC VRF Configuration

(config) #mac vrf L2VRF1	Create mac routing/forwarding instance with L2VRF1 name and enter into vrf mode
(config-vrf) #rd 1.1.1.1:11	Assign RD value
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as RED
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) #exit	Exit from vrf mode
(config) #mac vrf L2VRF2	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #rd 1.1.1.1:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as BLUE
(config-vrf) #exit	Exit from vrf mode

VTEP2:L2 VXLAN configuration

(config) #nvo vxlan access-if port-vlan po1 10	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vniid 101	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1010 ip 11.11.11.51	Configure static mac-ip
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan po1 20	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vniid 201	Map VXLAN Identified to access-port for VXLAN

(config-nvo-acc-if) # mac 0000.2222.1020 ip 21.21.21.51	Configure static mac-ip
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #exit	Exit from configuration mode

VTEP3:L2 VXLAN configuration

(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan irb	Enable VXLAN IRB
(config) #evpn esi hold-time 90	Configure ESI hold time to allow tunnel to come up at the time of vxlan initialization before making the ESI up. It should be same on both VTEP1 and VTEP2
(config) #evpn vxlan multihoming enable	Enable Multihoming
(config) #mac vrf L2VRF2	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as Blue
(config-vrf) #rd 1.1.1.1:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF2
(config-vrf) #exit	Exit from vrf mode
(config) #ip vrf L3VRF1	Create MAC routing/forwarding instance with L3VRF1 name and enter into VRF mode
(config-vrf) #rd 11000:11	Assign RD value
(config-vrf) #route-target both 100:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from vrf mode
(config) #mac vrf L2VRF1	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as Red
(config-vrf) #rd 1.1.1.1:11	Assign RD value
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config) # evpn irb-forwarding anycast-gateway-mac	Add evpn irb-forwarding anycast-gateway-mac address
(config) #nvo vxlan vtep-ip-global 1.1.1.1	Assign a global IP to the VTEP
(config) #nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-viddisabled configure and enter into VXLAN tenant mode

(config) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb1001	Configure irb1001 under vxlan id 101
(config-nvo) # vni-name VNI-101	Configure VNI name as VNI-101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-viddisabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # evpn irb2001	Configure irb2001 under vxlan id 201
(config-nvo) # vni-name VNI-201	Configure VNI name as VNI-201
(config) #qos enable	Enabling QoS
VTEP3(config)#hostname VTEP3	Configure hostname

VTEP3:Interface and loopback configuration

(config) #interface po1	Enter Interface mode for po1 (MH2)
(config-if) #switchport	Make it L2 interface
(config-if) # evpn multi-homed system-mac 0000.0000.2222	Configure system mac as ESI value for Lag (po1) interface. VTEP1 and VTEP2 should have same ESI value
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface po100	Enter Interface mode for xe3
(config-if) #load-interval 30	Make it member port of po1
(config-if) #ip address 100.11.11.1/24	Configure ip address as 100.11.11.1 on network side of Spine-P3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce49	Enter Interface mode for ce49
(config-if) #channel-group 100 mode active	Map the interface ce49 to po100
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce52	Enter Interface mode for network side port
(config-if) #ip address 100.11.11.1/24	Configure ip address as 100.11.11.1 on network side of Spine-P3
(config-if) #channel-group 1 mode active	Map the interface ce52 to po1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) # interface irb1001	Configure IRB interface 1001
(config-if) #ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) #evpn irb-if-forwarding anycast-gateway-mac	Enable an IRB interface to use the global anycast IRB mac-address.
(config-irb-if) # ip address 11.11.11.1/24 anycast	Configure the IPv4 address
(config-irb-if) # ip address 12.11.11.1/24 secondary anycast	Configure secondary IPv4 address as anycast
(config-irb-if) # ip address 13.11.11.1/16 secondary	Configure secondary IPv4 address as anycast

(config-irb-if) # ip address 14.11.11.1/24 secondary	Configure secondary IPv4 address as anycast
(config-irb-if) # ip address 15.11.11.1/16 secondary anycast	Configure secondary IPv4 address as anycast
(config-irb-if) # ip address 16.11.11.1/8 secondary anycast	Configure secondary IPv4 address as anycast
(config-irb-if) # ip address 17.11.11.1/24 secondary anycast	Configure secondary IPv4 address as anycast
(config-irb-if) # ip address 18.11.11.1/16 secondary anycast	Configure secondary IPv4 address as anycast
(config-irb-if) # ip address 19.11.11.1/8 secondary	Configure secondary IPv4 address as anycast
(config-irb-if) # ip address 20.11.11.1/24 secondary anycast	Configure secondary IPv4 address as anycast
(config-irb-if) # ip address 21.11.11.1/8 secondary anycast	Configure secondary IPv4 address as anycast
(config-irb-if) # ip address 22.11.11.1/24 secondary anycast	Configure secondary IPv4 address as anycast
(config-irb-if) # ip address 25.11.11.1/16 secondary anycast	Configure secondary IPv4 address as anycast
(config-irb-if) # ipv6 address 11:11::11:1/48 anycast	Configure the IPv6 as primary anycast
(config-irb-if) # ipv6 address 12:11::11:1/64	Configure the IPv6 address
(config-irb-if) # ipv6 address 13:11::11:1/48 anycast	Configure the IPv6 address as anycast
(config-irb-if) # ipv6 address 14:11::11:1/50 anycast	Configure the IPv6 address as anycast

VTEP3:OSPF configuration

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo ip address)
(config-router) #network 1.1.1.1/32 area 0.0.0.0	Add 1.1.1.1 (lo ip address) network into area 0
(config-router) #network 100.11.11.0/24 area 0.0.0.0	Add 100.11.11.0(Spine-P3) network into area 0
(config-router) #bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.

VTEP3:BGP configuration

(config) #router bgp 5000	Enter into Router BGP mode
(config-router) #bgp router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo ip address)
(config-router) #neighbor 2.2.2.2 remote-as 5000	Specify a VTEP2 loopback ip address and remote-as defined
(config-router) #neighbor 2.2.2.2 update-source lo	Configure update as loopback for VTEP2

(config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2
(config-router) #neighbor 4.4.4.4 remote-as 5000	Specify a VTEP4 loopback ip address and remote-as defined
(config-router) #neighbor 4.4.4.4 update-source lo	Configure update as loopback for VTEP4
(config-router) #neighbor 4.4.4.4 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP4
(config-router) #neighbor 5.5.5.5 remote-as 5000	Specify a VTEP5 loopback ip address and remote-as defined
(config-router) #neighbor 5.5.5.5 update-source lo	Configure update as loopback for VTEP5
(config-router) #neighbor 5.5.5.5 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP5
(config-router) #address-family l2vpn evpn	Enter into l2vpn EVPN address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2(VTEP2) into l2vpn evpn address family mode
(config-router-af) #neighbor 4.4.4.4 activate	Activate 3.3.3.3(VTEP4) into l2vpn evpn address family mode
(config-router-af) #neighbor 5.5.5.5 activate	Activate 5.5.5.5(VTEP5) into l2vpn evpn address family mode
(config-router-af) #exit-address-family	Exit from l2vpn address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode

VTEP3:L2 MAC VRF Configuration

(config) #mac vrf L2VRF1	Create mac routing/forwarding instance with L2VRF1 name and enter into vrf mode
(config-vrf) #rd 1.1.1.1:11	Assign RD value
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as RED
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) #exit	Exit from vrf mode
(config) #mac vrf L2VRF2	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #rd 1.1.1.1:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as BLUE
(config-vrf) #exit	Exit from vrf mode

VTEP3:L2 VXLAN configuration

(config) #nvo vxlan access-if port-vlan pol 10	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vniid 101	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1010 ip 11.11.11.51	Configure static mac-ip
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode

(config) #nvo vxlan access-if port-vlan po1 20	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vnid 201	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1020 ip 21.21.21.51	Configure static mac-ip
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #exit	Exit from configuration mode

VTEP4:L2 VXLAN configuration

(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan irb	Enable VXLAN IRB
(config) #evpn esi hold-time 90	Configure ESI hold time to allow tunnel to come up at the time of vxlan initialization before making the ESI up. It should be same on both VTEP1 and VTEP2
(config) #evpn vxlan multihoming enable	Enable Multihoming
(config) #mac vrf L2VRF2	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as Blue
(config-vrf) #rd 1.1.1.1:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF2
(config-vrf) #exit	Exit from vrf mode
(config) #ip vrf L3VRF1	Create MAC routing/forwarding instance with L3VRF1 name and enter into VRF mode
(config-vrf) #rd 11000:11	Assign RD value
(config-vrf) #route-target both 100:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from vrf mode
(config) #mac vrf L2VRF1	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as Red
(config-vrf) #rd 1.1.1.1:11	Assign RD value
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config) # evpn irb-forwarding anycast-gateway-mac	Add evpn irb-forwarding anycast-gateway-mac address
(config) #nvo vxlan vtep-ip-global 1.1.1.1	Assign a global IP to the VTEP

(config) #nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-viddisabled configure and enter into VXLAN tenant mode
(config) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb1001	Configure irb1001 under vxlan id 101
(config-nvo) # vni-name VNI-101	Configure VNI name as VNI-101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-viddisabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign VRF for EVPN-BGP to carry EVPN route
(config-nvo) # evpn irb2001	Configure irb2001 under vxlan id 201
(config-nvo) # vni-name VNI-201	Configure VNI name as VNI-201
(config) #qos enable	Enabling QoS
VTEP4 (config)#hostname VTEP4	Configure hostname

VTEP4:Interface and loopback configuration

(config) #interface po1	Enter Interface mode for po1 (MH2)
(config-if) #switchport	Make it L2 interface
(config-if) # evpn multi-homed system-mac 0000.0000.2222	Configure system mac as ESI value for Lag (po1) interface. VTEP1 and VTEP2 should have same ESI value
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface po100	Enter Interface mode for xe3
(config-if) #load-interval 30	Make it member port of po1
(config-if) #ip address 100.11.11.1/24	Configure ip address as 100.11.11.1 on network side of Spine-P3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce49	Enter Interface mode for ce49
(config-if) #channel-group 100 mode active	Map the ce49 interface to po100
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce52	Enter Interface mode for network side port
(config-if) #ip address 100.11.11.1/24	Configure ip address as 100.11.11.1 on network side of Spine-P3
(config-if) #channel-group 1 mode active	Map the ce52 interface to po01
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) # interface irb1001	Configure IRB interface 1001
(config-if) #ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) #evpn irb-if-forwarding anycast-gateway-mac	Enable an IRB interface to use the global anycast IRB mac-address.
(config-irb-if) # ip address 11.11.11.1/24 anycast	Configure the IPv4 address anycast gateway
(config-irb-if) # ip address 12.11.11.1/24 secondary anycast	Configure the IPv4 address anycast gateway

(config-irb-if) # ip address 13.11.11.1/16	Configure the IPv4 address as anycast secondary
(config-irb-if) # ip address 14.11.11.1/24	Configure the IPv4 address as anycast secondary
(config-irb-if) # ip address 15.11.11.1/16	Configure the IPv4 address as anycast secondary anycast
(config-irb-if) # ip address 16.11.11.1/8	Configure the IPv4 address as anycast secondary anycast
(config-irb-if) # ip address 17.11.11.1/24	Configure the IPv4 address as anycast secondary anycast
(config-irb-if) # ip address 18.11.11.1/16	Configure the IPv4 address as anycast secondary anycast
(config-irb-if) # ip address 19.11.11.1/8	Configure the IPv4 address as anycast secondary
(config-irb-if) # ip address 20.11.11.1/24	Configure the IPv4 address as anycast secondary anycast
(config-irb-if) # ip address 21.11.11.1/8	Configure the IPv4 address as anycast secondary anycast
(config-irb-if) # ip address 22.11.11.1/24	Configure the IPv4 address as anycast secondary anycast
(config-irb-if) # ip address 25.11.11.1/16	Configure the IPv4 address as anycast secondary anycast
(config-irb-if) # ipv6 address 11:11::11:1/48	Configure the IPv4 address as anycast anycast
(config-irb-if) # ipv6 address 12:11::11:1/64	Configure the IPv6 address as anycast
(config-irb-if) # ipv6 address 13:11::11:1/48	Configure the IPv6 address as anycast anycast
(config-irb-if) # ipv6 address 14:11::11:1/50	Configure the IPv6 address as anycast anycast

VTEP4:OSPF configuration

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo ip address)
(config-router) #network 1.1.1.1/32 area 0.0.0.0	Add 1.1.1.1 (lo ip address) network into area 0
(config-router) #network 100.11.11.0/24 area 0.0.0.0	Add 100.11.11.0(Spine-P3) network into area 0
(config-router) #bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.

VTEP4:BGP configuration

(config) #router bgp 5000	Enter into Router BGP mode
(config-router) #bgp router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo ip address)
(config-router) #neighbor 2.2.2.2 remote-as 5000	Specify a VTEP2 loopback ip address and remote-as defined

(config-router) #neighbor 2.2.2.2 update-source lo	Configure update as loopback for VTEP2
(config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2
(config-router) #neighbor 4.4.4.4 remote-as 5000	Specify a VTEP4 loopback ip address and remote-as defined
(config-router) #neighbor 4.4.4.4 update-source lo	Configure update as loopback for VTEP4
(config-router) #neighbor 4.4.4.4 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP4
(config-router) #neighbor 5.5.5.5 remote-as 5000	Specify a VTEP5 loopback ip address and remote-as defined
(config-router) #neighbor 5.5.5.5 update-source lo	Configure update as loopback for VTEP5
(config-router) #neighbor 5.5.5.5 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP5
(config-router) #address-family l2vpn evpn	Enter into l2vpn EVPN address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2(VTEP2) into l2vpn evpn address family mode
(config-router-af) #neighbor 4.4.4.4 activate	Activate 3.3.3.3(VTEP4) into l2vpn evpn address family mode
(config-router-af) #neighbor 5.5.5.5 activate	Activate 5.5.5.5(VTEP5) into l2vpn evpn address family mode
(config-router-af) #exit-address-family	Exit from l2vpn address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode

VTEP4:L2 MAC VRF Configuration

(config) #mac vrf L2VRF1	Create mac routing/forwarding instance with L2VRF1 name and enter into vrf mode
(config-vrf) #rd 1.1.1.1:11	Assign RD value
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as RED
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) #exit	Exit from vrf mode
(config) #mac vrf L2VRF2	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #rd 1.1.1.1:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as BLUE
(config-vrf) #exit	Exit from vrf mode

VTEP4:L2 VXLAN configuration

(config) #nvo vxlan access-if port-vlan po1 10	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vnid 101	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1010 ip 11.11.11.51	Configure static mac-ip

(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan po1 20	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vniid 201	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1020 ip 21.21.21.51	Configure static mac-ip
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #exit	Exit from configuration mode

Spine1

Spine node where all VTEPs are connected.

Generic configuration:

#configure terminal	Enter Configure mode.
(config) #evpn vxlan multihoming enable	Enable Multihoming, save configs and reboot the board for multihoming to be effective
(config) #qos enable	Enabling qos

Interface and loopback configuration:

(config) #interface po1	Enter Interface mode for po1 (MH2)
(config-if) #switchport	Make it L2 interface
(config-if) # bridge-group 1	Configure system mac as ESI value for Lag (po1) interface. VTEP1 and VTEP2 should have same ESI value
(config-if) #switchport mode trunk	Exit Interface mode and return to Configure mode.
(config-if) #switchport trunk allowed vlan add 2	Configure the VLANs that should be allowed through this interface
(config) #interface xe3	Enter Interface mode for xe3
(config-if) #load-interval 30	Make it member port of po1
(config-if) #ip address 100.11.11.1/24	Configure ip address as 100.11.11.1 on network side of Spine-P3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface lo	Enter Interface mode for lo
(config-if) #load-interval 30	Make it member port of po1
(config-if) #ip address 100.11.11.1/24	Configure ip address as 100.11.11.1 on network side of Spine-P1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface po100	Enter Interface mode for network side port
(config-if) #ip address 100.11.11.1/24	Configure ip address as 100.11.11.1 on network side of Spine-P3
(config-if) #exit	Exit Interface mode and return to Configure mode.

(config) #interface ce1	Enter Interface mode for network side port
(config-if) #channel-group 1 mode activev	Map the ce1 interface to po1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce2	Enter Interface mode for network side port
(config-if) #channel-group 2 mode active	Map the ce2 interface to po2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce3	Enter Interface mode for network side port
(config-if) #channel-group 1 mode active	Map the ce3 interface to po1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce4	Enter Interface mode for network side port
(config-if) #channel-group 1 mode active	Map the ce4 interface to po1
(config) # interface lo	Configure IRB interface 1001
(config) #ip address 127.0.0.1/8	Configure the IPv4 address
(config) #ip address 100.100.100.100/32 secondary	Configure the IPv4 address
(config) #ipv6 address ::1/128	Configure the IPv6 address
(config) # vlan1.2	Configure IRB interface 1001
(config) #ip address 100.12.12.2/24	Configure the Ip address
(config) #exit	Exit Interface mode and return to Configure mode.

OSPF configuration:

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo ip address)
(config-router) #network 1.1.1.1/32 area 0.0.0.0	Add 1.1.1.1 (lo ip address) network into area 0
(config-router) #network 100.11.11.0/24 area 0.0.0.0	Add 100.11.11.0(Spine-P3) network into area 0
(config-router) #bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.

Switch1

Interface and loopback configuration:

(config) #interface po1	Enter Interface mode for po1 (MH2)
(config-if) #switchport	Enable switch port under po1
(config-if) # bridge-group 1	Map the bridge group
(config-if) #switchport mode trunk	Configure switch port as trunk

(config-if)#switchport trunk allowed vlan add 2,10,20	Add the vlan for the trunk
(config-if)#switchport trunk allowed vlan add 2	Add the vlan for the trunk
(config)#interface ce56	Enter Interface mode for network side port
(config-if)#channel-group 1 mode active	Map interface ce56 for channel group
(config)#interface vlan1.20	Configure the vlan
(config)#ip address 21.21.21.2/24	Configure the IPv4 address for vlan1.20
(config)#ipv6 address 21:21::21:2/48	Configure the IPv6 address for vlan1.20
(config)# interface vlan1.2	Configure the interface Vlan1.2
(config)# ip address 100.12.12.2/24	Configure the IP address for vlan1.2 interface.
(config)#exit	Exit Interface mode and return to Configure mode.
(config)#interface xe1	Enter Interface mode for xe1
(config-if)#switchport	Enable switch port under xe1
(config-if)# bridge-group 1	Map the bridge group
(config-if)#switchport mode trunk	Configure switch port as trunk
(config-if)#switchport trunk allowed vlan add 2,10,20	Add the vlan for the trunk
(config)#exit	Exit Interface mode and return to Configure mode.

Switch2

OSPF configuration:

(config)#router ospf 100	Enter into router OSPF mode
(config-router)#ospf router-id 5.5.5.5	Configure router-id as 5.5.5.5 (lo ip address)
(config-router)#network 5.5.5.5/32 area 0.0.0.0	Add 5.5.5.5/32 (lo ip address) network into area 0
(config-router)#network 100.14.14.0/24 .0/24 area 0.0.0.0	Add 100.14.14.0/24 (Spine-P3) network into area 0
(config-router)#bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if)#exit	Exit Interface mode and return to Configure mode.

Validation

VTEP1:

```
Leaf1#show nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====
VNID    Ip-Addr        Mac-Addr      Type     Age-Out   Retries-Left
101     11.11.11.1     0000.0000.1111 Static Local   ----
101     11.11.11.51    0000.2222.1010 Static Local   ----
```

```

101 11.11.11.201 0000.4444.1010 Static Remote ----
101 12.11.11.1 0000.0000.1111 Static Local ----
101 13.11.11.1 1444.8f10.d8c9 Static Local ----
101 14.11.11.1 1444.8f10.d8c9 Static Local ----
101 15.11.11.1 0000.0000.1111 Static Local ----
101 16.11.11.1 0000.0000.1111 Static Local ----
101 17.11.11.1 0000.0000.1111 Static Local ----
101 18.11.11.1 0000.0000.1111 Static Local ----
101 19.11.11.1 1444.8f10.d8c9 Static Local ----
101 20.11.11.1 0000.0000.1111 Static Local ----
201 21.21.21.1 0000.0000.1111 Static Local ----
201 21.21.21.51 0000.2222.1020 Static Local ----
201 22.22.22.1 1444.8f10.d8c9 Static Local ----
201 23.23.23.1 0000.0000.1111 Static Local ----
201 24.24.24.1 0000.0000.1111 Static Local ----
201 25.25.25.1 1444.8f10.d8c9 Static Local ----
201 26.26.26.1 0000.0000.1111 Static Local ----
201 27.27.27.1 1444.8f10.d8c9 Static Local ----
201 28.28.28.1 0000.0000.1111 Static Local ----
201 29.29.29.1 1444.8f10.d8c9 Static Local ----
201 30.30.30.1 0000.0000.1111 Static Local ----
201 192.85.1.2 0039.4400.0020 Dynamic Local ----
Total number of entries are 24
-----
```

```

Leaf1#sh nvo vxlan nd-cache
VXLAN ND-CACHE Information
=====
VNID      Ip-Addr                         Mac-Addr        Type       Age
-Out      Retries-Left

-----
```

VNID	Ip-Addr	Mac-Addr	Type	Age
-Out	Retries-Left			
101	11:11::11:1	0000.0000.1111	Static Local	----
101	12:11::11:1	1444.8f10.d8c9	Static Local	----
101	13:11::11:1	0000.0000.1111	Static Local	----
101	14:11::11:1	0000.0000.1111	Static Local	----
101	15:11::11:1	0000.0000.1111	Static Local	----
101	16:11::11:1	1444.8f10.d8c9	Static Local	----
101	17:11::11:1	0000.0000.1111	Static Local	----
101	18:11::11:1	1444.8f10.d8c9	Static Local	----
101	19:11::11:1	1444.8f10.d8c9	Static Local	----
101	20:20::20:1	1444.8f10.d8c9	Static Local	----
201	21:21::21:1	1444.8f10.d8c9	Static Local	----
201	22:22::22:1	0000.0000.1111	Static Local	----
201	23:23::23:1	1444.8f10.d8c9	Static Local	----
201	24:24::24:1	1444.8f10.d8c9	Static Local	----
201	25:25::25:1	0000.0000.1111	Static Local	----
201	26:26::26:1	0000.0000.1111	Static Local	----
201	27:27::27:1	1444.8f10.d8c9	Static Local	----
201	28:28::28:1	0000.0000.1111	Static Local	----
201	29:29::29:1	1444.8f10.d8c9	Static Local	----
201	30:30::30:1	0000.0000.1111	Static Local	----

Total number of entries are 20

Leaf1#

VTEP2:

```

Leaf2#show int counters rate mbps
+-----+-----+-----+-----+-----+
| Interface | Rx mbps | Rx pps | Tx mbps | Tx pps |
+-----+-----+-----+-----+-----+
ce49      1099.23   771933    0.00     1
ce50      0.00      0        0.00     0
ce51      0.00      0        0.00     0
ce52      0.00      0        0.00     0
ce53      0.00      0        0.00     0
ce54      0.00      0        0.00     0
ce55      0.00      0        0.00     0
ce56      0.00      0        0.00     0
po3       1099.23   771934    0.00     1
xe3       0.00      0        0.00     0
xe5       0.00      0        0.00     0

```

```
-----
Leaf2#show nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====
VNID      Ip-Addr          Mac-Addr        Type       Age-Out     Retries-Left
-----  

101      11.11.11.1        0000.0000.1111  Static Local   ----  

101      11.11.11.51       0000.2222.1010  Static Remote  ----  

101      11.11.11.201      0000.4444.1010  Static Remote  ----  

101      12.11.11.1        0000.0000.1111  Static Local   ----  

101      13.11.11.1        b86a.979c.1669  Static Local   ----  

101      14.11.11.1        b86a.979c.1669  Static Local   ----  

101      15.11.11.1        0000.0000.1111  Static Local   ----  

101      16.11.11.1        0000.0000.1111  Static Local   ----  

101      17.11.11.1        0000.0000.1111  Static Local   ----  

101      18.11.11.1        0000.0000.1111  Static Local   ----  

101      19.11.11.1        b86a.979c.1669  Static Local   ----  

101      20.11.11.1        0000.0000.1111  Static Local   ----  

201      21.21.21.1        0000.0000.1111  Static Local   ----  

201      21.21.21.51       0000.2222.1020  Static Remote  ----  

201      22.22.22.1        b86a.979c.1669  Static Local   ----  

201      23.23.23.1        0000.0000.1111  Static Local   ----  

201      24.24.24.1        0000.0000.1111  Static Local   ----  

201      25.25.25.1        b86a.979c.1669  Static Local   ----  

201      26.26.26.1        0000.0000.1111  Static Local   ----  

201      27.27.27.1        b86a.979c.1669  Static Local   ----  

201      28.28.28.1        0000.0000.1111  Static Local   ----  

201      29.29.29.1        b86a.979c.1669  Static Local   ----  

201      30.30.30.1        0000.0000.1111  Static Local   ----  

201      192.85.1.2        0039.4400.0020  Dynamic Remote  ----  

Total number of entries are 24
-----
```

```
Leaf2# show nvo vxlan nd-cache
VXLAN ND-CACHE Information
=====
VNID      Ip-Addr          Mac-Addr        Type       Age
-Out      Retries-Left
-----  

101      11:11::11:1        0000.0000.1111  Static Local   ----  

101      12:11::11:1        b86a.979c.1669  Static Local   ----  

101      13:11::11:1        0000.0000.1111  Static Local   ----  

101      14:11::11:1        0000.0000.1111  Static Local   ----  

101      15:11::11:1        0000.0000.1111  Static Local   ----  

101      16:11::11:1        b86a.979c.1669  Static Local   ----  

101      17:11::11:1        0000.0000.1111  Static Local   ----  

101      18:11::11:1        b86a.979c.1669  Static Local   ----  

101      19:11::11:1        b86a.979c.1669  Static Local   ----  

101      20:20::20:1        b86a.979c.1669  Static Local   ----  

201      21:21::21:1        b86a.979c.1669  Static Local   ----  

201      22:22::22:1        0000.0000.1111  Static Local   ----  

201      23:23::23:1        b86a.979c.1669  Static Local   ----  

201      24:24::24:1        b86a.979c.1669  Static Local   ----  

201      25:25::25:1        0000.0000.1111  Static Local   ----  

201      26:26::26:1        0000.0000.1111  Static Local   ----  

201      27:27::27:1        b86a.979c.1669  Static Local   ----  

201      28:28::28:1        0000.0000.1111  Static Local   ----  

201      29:29::29:1        b86a.979c.1669  Static Local   ----  

201      30:30::30:1        0000.0000.1111  Static Local   ----  

Total number of entries are 20
Leaf2#
```

VTEP4:

```
Leaf3#show interface counters rate mbps
+-----+-----+-----+-----+-----+-----+
| Interface | Rx mbps | Rx pps | Tx mbps | Tx pps |  

+-----+-----+-----+-----+-----+-----+
ce49      0.00    1      0.00    0  

ce51      0.00    0      0.00    0  

ce52      0.00    0      0.00    0
```

```

ce54      0.00      0      0.00      0
ce55      0.00      0      0.00      0
ce56    1175.78  844671      0.00      1
po4     1175.78  844671      0.00      1
xe4      0.00      0      0.00      0
xe5      0.00      0      0.00      0
xe7      0.00      0      0.00      0
xe8      0.00      0      0.00      0
xe9      0.00      0      0.00      0
xe10     0.00      0      0.00      0
xe11     0.00      0      0.00      0
xe30     0.00      0      0.00      0
xe31     0.00      0      0.00      0
xe32     0.00      0      0.00      0
Leaf3#
Leaf3#
-----
```

```
Leaf3#show nvo vxlan arp-cache
```

```
VXLAN ARP-CACHE Information
```

VNIID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
101	11.11.11.1	0000.0000.1111	Static Local	----	
101	11.11.11.51	0000.2222.1010	Static Remote	----	
101	11.11.11.201	0000.4444.1010	Static Remote	----	
101	12.11.11.1	0000.0000.1111	Static Local	----	
101	13.11.11.1	b86a.9735.d79d	Static Local	----	
101	14.11.11.1	b86a.9735.d79d	Static Local	----	
101	15.11.11.1	0000.0000.1111	Static Local	----	
101	16.11.11.1	0000.0000.1111	Static Local	----	
101	17.11.11.1	0000.0000.1111	Static Local	----	
101	18.11.11.1	0000.0000.1111	Static Local	----	
101	19.11.11.1	b86a.9735.d79d	Static Local	----	
101	20.11.11.1	0000.0000.1111	Static Local	----	
201	21.21.21.1	0000.0000.1111	Static Local	----	
201	21.21.21.51	0000.2222.1020	Static Remote	----	
201	22.22.22.1	b86a.9735.d79d	Static Local	----	
201	23.23.23.1	0000.0000.1111	Static Local	----	
201	24.24.24.1	0000.0000.1111	Static Local	----	
201	25.25.25.1	b86a.9735.d79d	Static Local	----	
201	26.26.26.1	0000.0000.1111	Static Local	----	
201	27.27.27.1	b86a.9735.d79d	Static Local	----	
201	28.28.28.1	0000.0000.1111	Static Local	----	
201	29.29.29.1	b86a.9735.d79d	Static Local	----	
201	30.30.30.1	0000.0000.1111	Static Local	----	
201	192.85.1.2	0039.4400.0020	Dynamic Remote	----	

```
Total number of entries are 24
```

```
Leaf3#show nvo vxlan nd-cache
```

```
VXLAN ND-CACHE Information
```

VNIID	Ip-Addr	Mac-Addr	Type	Age
-Out	Retries-Left			
101	11:11::11:1	0000.0000.1111	Static Local	----
101	12:11::11:1	b86a.9735.d79d	Static Local	----
101	13:11::11:1	0000.0000.1111	Static Local	----
101	14:11::11:1	0000.0000.1111	Static Local	----
101	15:11::11:1	0000.0000.1111	Static Local	----
101	16:11::11:1	b86a.9735.d79d	Static Local	----
101	17:11::11:1	0000.0000.1111	Static Local	----
101	18:11::11:1	b86a.9735.d79d	Static Local	----
101	19:11::11:1	b86a.9735.d79d	Static Local	----
101	20:20::20:1	b86a.9735.d79d	Static Local	----
201	21:21::21:1	b86a.9735.d79d	Static Local	----
201	22:22::22:1	0000.0000.1111	Static Local	----
201	23:23::23:1	b86a.9735.d79d	Static Local	----
201	24:24::24:1	b86a.9735.d79d	Static Local	----
201	25:25::25:1	0000.0000.1111	Static Local	----
201	26:26::26:1	0000.0000.1111	Static Local	----
201	27:27::27:1	b86a.9735.d79d	Static Local	----

```

201    28:28::28:1          0000.0000.1111 Static Local   ----
201    29:29::29:1          b86a.9735.d79d Static Local   ----
201    30:30::30:1          0000.0000.1111 Static Local   ----
Total number of entries are 20
Leaf3#

```

VTEP5:

```

Leaf4#show interface counters rate mbps
+-----+-----+-----+-----+-----+
| Interface | Rx mbps | Rx pps | Tx mbps | Tx pps |
+-----+-----+-----+-----+-----+
ce49      0.00     0       0.00     0
ce50      0.00     0       0.00     0
ce52      0.00     0       0.00     0
ce53      0.00     0       0.00     0
ce54      1175.70  844612  0.00     1
ce55      0.00     0       0.00     0
po25      1175.70  844612  0.00     1
xe7       0.00     0       0.00     0
xe12      0.00     0       0.00     0
xe13      0.00     0       0.00     0
xe14      0.00     0       0.00     0
xe15      0.00     0       0.00     0
xe16      0.00     0       0.00     0
xe17      0.00     0       0.00     0
xe18      0.00     0       0.00     0
xe30      0.00     0       0.00     0
xe31      0.00     0       0.00     0
xe32      0.00     0       0.00     0
-----
```

```

Leaf4#show nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====
VNID  Ip-Addr        Mac-Addr      Type      Age-Out    Retries-Left
-----+-----+-----+-----+-----+
101   11.11.11.1    0000.0000.1111 Static Local   ----
101   11.11.11.51   0000.2222.1010 Static Remote  ----
101   11.11.11.201  0000.4444.1010 Static Local   ----
101   12.11.11.1    0000.0000.1111 Static Local   ----
101   13.11.11.1    1444.8f45.8dc9 Static Local   ----
101   14.11.11.1    1444.8f45.8dc9 Static Local   ----
101   15.11.11.1    0000.0000.1111 Static Local   ----
101   16.11.11.1    0000.0000.1111 Static Local   ----
101   17.11.11.1    0000.0000.1111 Static Local   ----
101   18.11.11.1    0000.0000.1111 Static Local   ----
101   19.11.11.1    1444.8f45.8dc9 Static Local   ----
101   20.11.11.1    0000.0000.1111 Static Local   ----
201   21.21.21.1    0000.0000.1111 Static Local   ----
201   21.21.21.51   0000.2222.1020 Static Remote  ----
201   22.22.22.1    1444.8f45.8dc9 Static Local   ----
201   23.23.23.1    0000.0000.1111 Static Local   ----
201   24.24.24.1    0000.0000.1111 Static Local   ----
201   25.25.25.1    1444.8f45.8dc9 Static Local   ----
201   26.26.26.1    0000.0000.1111 Static Local   ----
201   27.27.27.1    1444.8f45.8dc9 Static Local   ----
201   28.28.28.1    0000.0000.1111 Static Local   ----
201   29.29.29.1    1444.8f45.8dc9 Static Local   ----
201   30.30.30.1    0000.0000.1111 Static Local   ----
201   192.85.1.2    0039.4400.0020 Dynamic Remote ----
Total number of entries are 24
-----
```

```

Leaf4#show nvo vxlan nd-cache
VXLAN ND-CACHE Information
=====
VNID  Ip-Addr        Mac-Addr      Type      Age
-Out  Retries-Left
-----+-----+-----+-----+
101   11:11::11:1    0000.0000.1111 Static Local   ----
101   12:11::11:1    1444.8f45.8dc9 Static Local   ----
-----
```

```
101    13:11::11:1      0000.0000.1111 Static Local      ----
101    14:11::11:1      0000.0000.1111 Static Local      ----
101    15:11::11:1      0000.0000.1111 Static Local      ----
101    16:11::11:1      1444.8f45.8dc9 Static Local      ----
101    17:11::11:1      0000.0000.1111 Static Local      ----
101    18:11::11:1      1444.8f45.8dc9 Static Local      ----
101    19:11::11:1      1444.8f45.8dc9 Static Local      ----
101    20:20::20:1      1444.8f45.8dc9 Static Local      ----
201    21:21::21:1      1444.8f45.8dc9 Static Local      ----
201    22:22::22:1      0000.0000.1111 Static Local      ----
201    23:23::23:1      1444.8f45.8dc9 Static Local      ----
201    24:24::24:1      1444.8f45.8dc9 Static Local      ----
201    25:25::25:1      0000.0000.1111 Static Local      ----
201    26:26::26:1      0000.0000.1111 Static Local      ----
201    27:27::27:1      1444.8f45.8dc9 Static Local      ----
201    28:28::28:1      0000.0000.1111 Static Local      ----
201    29:29::29:1      1444.8f45.8dc9 Static Local      ----
201    30:30::30:1      0000.0000.1111 Static Local      ----
Total number of entries are 20
Leaf4#
```

CHAPTER 3 VxLAN-EVPN Symmetric IRB Support with Connected host

Overview

EVPN-IRB enables communication between two L2VNI's by employing Routing through IP-VRF. This functionality offers Host (/32) based Symmetric IRB support, directing inter-subnet traffic directly to the Host attached VTEP. To implement this, configure "evpn irb-advertise-host-route" within VNID (BGP type 2) settings, or "redistribute connected-host-routes" under BGP (BGP type 5) configurations.

Note:

- In VxLAN-EVPN Interface-less mode, only the 'redistribute connected-host-routes' command is supported. However, in Interface-full mode, both commands are supported.
- It is advisable to configure a route map in ESI configured Multi-Homed (MH) nodes to block Hosts from peer MH. This configuration is not required in non-ESI MH VTEPs.

Feature Characteristics

The preferred and recommended approach for AOS-CX VXLAN/EVPN Distributed L3 Gateways is Symmetric IRB. This implementation offers superior scalability by eliminating the need to manage MAC/ARP entries for both source and destination hosts, and it doesn't require configuring the same VLAN/VNI as in the case of Asymmetric IRB. These advantages facilitate simpler and more scalable deployments in both Data Center and Campus networks.

Benefits

The advantages of utilizing a VxLAN-EVPN Symmetric IRB Support:

- Routing is employed on both ingress and egress VTEPs.
- Bi-directional traffic follows a symmetric path, such as utilizing an L3 VNI per VRF.
- VTEPs are relieved from holding unnecessary ARP/MAC resources.
- Configuration of the destination VLAN/VNI on the source VTEP is unnecessary.

Configuration

Ensure that the VTEPs have a base configuration with Symmetric IRB settings. Then, initiate dynamic traffic from VTEP4 originating from the same subnet (53.1.X.XX/XXXX::XX) as the IRB interface. Typically, in EVPN, a single IP-VRF can accommodate multiple IRB interfaces. Each IRB interface corresponds to a VNI, and multiple VNIs can be associated with a MAC-VRF.

Topology

The procedures in this section use the topology in [Figure 3-1](#)




Figure 3-1: VxLAN EVPN IRB Connected host

Note: In the above topology TG1 is Multi homed Host and TG2 and TG3 are Single homed host with same subnet configured so there will be ECMP for 53 network in VTEP1 and VTEP2.

Base Configurations

Begin with a basic configuration that includes Symmetric IRB configurations on VTEPs, then initiate dynamic traffic transmission from VTEP4 within the same subnet (53.1.1.40/5301::40) as the IRB interface.

Validation

Verification before configuring evpn irb-advertise-host-route under VNID configurations or redistribute connected-host-routes under bgp.

In VTEP1:

```
VTEP1#show ip route vrf vxlan_13_elan_mhsh
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
      O - OSPF, IA - OSPF inter area
      N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
      E1 - OSPF external type 1, E2 - OSPF external type 2
      i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
      ia - IS-IS inter area, E - EVPN,
      v - vrf leaked
      * - candidate default

IP Route Table for VRF "vxlan_13_elan_mhsh"
B          2.2.2.2/32 [0/0] is directly connected, tunvxlan3, 00:21:33
B          5.5.5.5/32 [0/0] is directly connected, tunvxlan3, 00:21:33
B          6.6.6.6/32 [0/0] is directly connected, tunvxlan3, 00:21:33
B          53.1.1.0/24 [200/0] via 6.6.6.6 (recursive is directly connected,
tunvxlan3), 00:21:34
                                         [200/0] via 5.5.5.5 (recursive is directly connected,
tunvxlan3)
C          127.0.0.0/8 is directly connected, lo.vxlan_13_elan_mhsh, 07:17:43
C          200.1.1.0/24 is directly connected, irb1604, 07:17:41

Gateway of last resort is not set
VTEP1#
VTEP1#show ipv6 route vrf vxlan_13_elan_mhsh
IPv6 Routing Table
IP Route Table for VRF "vxlan_13_elan_mhsh"
C          ::1/128 via ::, lo.vxlan_13_elan_mhsh, 07:18:01
B          ::ffff:202:202/128 [0/0] via ::, tunvxlan3, 00:21:51
B          ::ffff:505:505/128 [0/0] via ::, tunvxlan3, 00:21:51
B          ::ffff:606:606/128 [0/0] via ::, tunvxlan3, 00:21:51
C          2000::/48 via ::, irb1604, 07:17:59
B          5301::/48 [200/0] via ::ffff:606:606 (recursive via ::, tunvxlan3), 00:21:52
                                         [200/0] via ::ffff:505:505 (recursive via ::, tunvxlan3)
C          fe80::/64 via ::, irb1604, 07:17:59
VTEP1#
```

In VTEP2:

```
VTEP2#show ip route vrf vxlan_13_elan_mhsh
IP Route Table for VRF "vxlan_13_elan_mhsh"
B          1.1.1.1/32 [0/0] is directly connected, tunvxlan3, 00:22:50
B          5.5.5.5/32 [0/0] is directly connected, tunvxlan3, 00:22:50
B          6.6.6.6/32 [0/0] is directly connected, tunvxlan3, 00:22:50
```

```

B      53.1.1.0/24 [200/0] via 6.6.6.6 (recursive is directly connected,
tunvxlan3), 00:22:51
                                              [200/0] via 5.5.5.5 (recursive is directly connected,
tunvxlan3)
C      127.0.0.0/8 is directly connected, lo.vxlan_13_elan_mhsh, 07:19:21
C      200.1.1.0/24 is directly connected, irb1604, 07:19:19

Gateway of last resort is not set
VTEP2#
VTEP2#
VTEP2#show ipv6 route vrf vxlan_13_elan_mhsh
IPv6 Routing Table
IP Route Table for VRF "vxlan_13_elan_mhsh"
C      ::1/128 via ::, lo.vxlan_13_elan_mhsh, 07:19:22
B      ::ffff:101:101/128 [0/0] via ::, tunvxlan3, 00:22:51
B      ::ffff:505:505/128 [0/0] via ::, tunvxlan3, 00:22:51
B      ::ffff:606:606/128 [0/0] via ::, tunvxlan3, 00:22:51
C      2000::/48 via ::, irb1604, 07:19:20
B      5301::/48 [200/0] via ::ffff:606:606 (recursive via ::, tunvxlan3), 00:22:51
                  [200/0] via ::ffff:505:505 (recursive via ::, tunvxlan3)
C      fe80::/64 via ::, irb1604, 07:19:20
VTEP2#
VTEP2#show bgp 12vpn evpn mac-ip | grep 0000:0053:0040
0          605      0000:0053:0040 --
605        0        6.6.6.6      --          VxLAN
0          605      0000:0053:0040 53.1.1.40
605        0        6.6.6.6      --          VxLAN
0          605      0000:0053:0040 5301::40
605        0        6.6.6.6      --          VxLAN
VTEP2#

```

In VTEP4:

```

VTEP4#show bgp 12vpn evpn mac-ip | grep 0000:0053:0040
0          605      0000:0053:0040 --
605        0        6.6.6.6      --          VxLAN
0          605      0000:0053:0040 53.1.1.40
605        0        6.6.6.6      --          VxLAN
0          605      0000:0053:0040 5301::40
605        0        6.6.6.6      --          VxLAN
VTEP4#

```

Evpn irb-advertise-host-route configuration

1. To enable the EVPN irb-advertise-host-route, execute the following command in the config mode.

```
(config)#nvo vxlan id 605 ingress-replication inner-vid-disabled
(config-nvo)#vxlan host-reachability-protocol evpn-bgp vxlan_12_elan_sh2
(config-nvo)#evpn irb605
(config-nvo)#evpn irb-advertise-host-route
```
2. To redistributed connected-host-routes, execute the following command.

```
(config)#nvo vxlan id 605 ingress-replication inner-vid-disabled
```

```
(config)#router bgp 1
(config-router)#address-family ipv4 vrf vxlan_13_elan_sh
VTEP4(config-router-af)#redistribute connected-host-routes
```

Note: With static mac ip configured on vxlan access interface and when redistribute connected-host-routes is configured under bgp. Then routes will not be advertised as /32 or /128 because for static mac-ip Arp entry will not be present so only for dynamic routes.

Note: With redistribute connected-host-routes, show bgp l2vpn evpn mac-ip will not show the l3vnid.

Validation

Use this command to validate the VxLAN-EVPN Symmetric IRB.

In VTEP1:

```
VTEP1#show ip route vrf vxlan_13_elan_mhsh
IP Route Table for VRF "vxlan_13_elan_mhsh"
B          2.2.2.2/32 [0/0] is directly connected, tunvxlan3, 00:37:03
B          5.5.5.5/32 [0/0] is directly connected, tunvxlan3, 00:37:03
B          6.6.6.6/32 [0/0] is directly connected, tunvxlan3, 00:37:03
B          53.1.1.0/24 [200/0] via 6.6.6.6 (recursive is directly connected,
tunvxlan3), 00:37:04
                                         [200/0] via 5.5.5.5 (recursive is directly connected,
tunvxlan3)
B          53.1.1.40/32 [200/0] via 6.6.6.6 (recursive is directly connected,
tunvxlan3), 00:05:49
C          127.0.0.0/8 is directly connected, lo.vxlan_13_elan_mhsh, 07:33:13
C          200.1.1.0/24 is directly connected, irb1604, 07:33:11
Gateway of last resort is not set
VTEP1#
VTEP1#show ipv6 route vrf vxlan_13_elan_mhsh
IPv6 Routing Table
IP Route Table for VRF "vxlan_13_elan_mhsh"
C          ::1/128 via ::, lo.vxlan_13_elan_mhsh, 07:33:21
B          ::ffff:202:202/128 [0/0] via ::, tunvxlan3, 00:37:11
B          ::ffff:505:505/128 [0/0] via ::, tunvxlan3, 00:37:11
B          ::ffff:606:606/128 [0/0] via ::, tunvxlan3, 00:37:11
C          2000::/48 via ::, irb1604, 07:33:19
B          5301::/48 [200/0] via ::ffff:606:606 (recursive via ::, tunvxlan3), 00:37:12
                                         [200/0] via ::ffff:505:505 (recursive via ::, tunvxlan3)
B          5301::40/128 [200/0] via ::ffff:606:606 (recursive via ::, tunvxlan3), 00:05:57
C          fe80::/64 via ::, irb1604, 07:33:19
VTEP1#
VTEP1#show bgp l2vpn evpn mac-ip | grep 0000:0053:0040
0          605      0000:0053:0040 --
605        0         6.6.6.6      --          VxLAN
0          605      0000:0053:0040 53.1.1.40
605        1604     6.6.6.6      --          VxLAN
0          605      0000:0053:0040 5301::40
605        1604     6.6.6.6      --          VxLAN
VTEP1#
```

In VTEP2:

```
VTEP2#show ip route vrf vxlan_13_elan_mhsh
IP Route Table for VRF "vxlan_13_elan_mhsh"
B          1.1.1.1/32 [0/0] is directly connected, tunvxlan3, 00:31:16
B          5.5.5.5/32 [0/0] is directly connected, tunvxlan3, 00:31:16
B          6.6.6.6/32 [0/0] is directly connected, tunvxlan3, 00:31:16
B          53.1.1.0/24 [200/0] via 6.6.6.6 (recursive is directly connected,
tunvxlan3), 00:31:17
                                         [200/0] via 5.5.5.5 (recursive is directly connected,
tunvxlan3)
B          53.1.1.40/32 [200/0] via 6.6.6.6 (recursive is directly connected,
tunvxlan3), 00:00:03
C          127.0.0.0/8 is directly connected, lo.vxlan_13_elan_mhsh, 07:27:47
C          200.1.1.0/24 is directly connected, irb1604, 07:27:45
Gateway of last resort is not set
VTEP2#
VTEP2#show ipv6 route vrf vxlan_13_elan_mhsh
IPv6 Routing Table
IP Route Table for VRF "vxlan_13_elan_mhsh"
C          ::1/128 via ::, lo.vxlan_13_elan_mhsh, 07:27:54
B          ::ffff:101:101/128 [0/0] via ::, tunvxlan3, 00:31:23
B          ::ffff:505:505/128 [0/0] via ::, tunvxlan3, 00:31:23
B          ::ffff:606:606/128 [0/0] via ::, tunvxlan3, 00:31:23
C          2000::/48 via ::, irb1604, 07:27:52
B          5301::/48 [200/0] via ::ffff:606:606 (recursive via ::, tunvxlan3), 00:31:23
                                         [200/0] via ::ffff:505:505 (recursive via ::, tunvxlan3)
B          5301::40/128 [200/0] via ::ffff:606:606 (recursive via ::, tunvxlan3), 00:00:10
C          fe80::/64 via ::, irb1604, 07:27:52
VTEP2#
VTEP2#show bgp 12vpn evpn mac-ip | grep 0000:0053:0040
0          605      0000:0053:0040 --
605        0        6.6.6.6      --          VxLAN
0          605      0000:0053:0040 53.1.1.40
605        1604    6.6.6.6      --          VxLAN
0          605      0000:0053:0040 5301::40
605        1604    6.6.6.6      --          VxLAN
VTEP2#
```

In VTEP4:

```
VTEP4#show arp vrf vxlan_13_elan_mhsh
Flags: D - Static Adjacencies attached to down interface
IP ARP Table for context vxlan_13_elan_mhsh
Total number of entries: 1
Address      Age      MAC Address      Interface  State
1.1.1.1       -       e8c5.7aa3.2cb0  tunvxlan3  PERMANENT
2.2.2.2       -       e001.a657.ef01  tunvxlan3  PERMANENT
5.5.5.5       -       6cb9.c5b1.ab9c  tunvxlan3  PERMANENT
53.1.1.40     00:02:57 0000.0053.0040  irb604    STALE
VTEP4#
```

```
VTEP4#show bgp 12vpn evpn mac-ip | grep 0000:0053:0040
0          605      0000:0053:0040 --
605        0       6.6.6.6      --           VxLAN
0          605      0000:0053:0040 53.1.1.40
605        1604    6.6.6.6      --           VxLAN
0          605      0000:0053:0040 5301::40
605        1604    6.6.6.6      --           VxLAN
VTEP4#
```

Glossary

The following provides definitions for key terms or abbreviations and their meanings used throughout this document:

Key Terms/Acronym	Description
ECMP	ECMP stands for Equal-Cost Multi-Path. It's a routing technique used in computer networks, particularly in IP-based routing protocols like OSPF (Open Shortest Path First) and BGP (Border Gateway Protocol).
VTEPs	VTEP stands for VXLAN Tunnel Endpoint. It's a crucial component in network virtualization architectures, particularly in overlay networks using VXLAN (Virtual Extensible LAN) technology.
ARP/MAC	ARP (Address Resolution Protocol) and MAC (Media Access Control) address are both essential components of networking, particularly in Ethernet-based networks.
VLAN/VNI	VLAN (Virtual Local Area Network) and VNI (Virtual Network Identifier) are both technologies used in networking to segment and manage traffic within a larger network infrastructure.

CHAPTER 4 VXLAN-IRB-Inter-VRF Route Leaking

A VRF is a mechanism used to provide logical separation between routing tables on the same router. It is locally significant to the router. Each interface on a router can only be assigned to one VRF, but a VRF can have multiple interfaces. VRF route leaking can be done using route-target import/export.

The routes of VRF catering shared services shall be leaked to tenant VRFs. The leaking of routes shall be possible over one overlay VRF to another overlay VRF. By doing so shared services like Internet access through gateway routes can be made possible. Introduction of this feature shall cater various use cases of shared services like storage / Internet access etc.

Topology

The procedures in this section use the topology in [Figure 4-2](#).




Figure 4-2: VxLAN_EVPN_IVRF

Note: SH means Single homing host and MH means Multihoming host.

VTEP1

Single Home -SH

Hardware profile and generic configuration:

#configure terminal	Enter Configure mode.
(config)#nvo vxlan enable	Enable VXLAN
(config)#nvo vxlan irb	Enable VXLAN irb
(Config)#qos enable	Enabling qos
(Config)# bfd interval 3 minrx 3 multiplier 3	Configure bfd
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

Interface and loopback configuration:

(config)#interface ce50	Enter Interface mode for ce50 (SH1)
(config-if)# description ***Connected to TOR1***	Interface description
(config-if)#switchport	Make it L2 interface
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface lo	Enter Interface mode for lo
(config-if)#ip address 51.51.51.51/32 secondary	Configure loopback ip address
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) interface xe40	Enter interface mode
(config-if)# description ***Connected to Spine2***	Interface description
(config-if)# ip address 10.10.10.1/31	Configure ip address on network side of Spine1
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board
(config-if)#exit	Exit Interface mode and return to Configure mode.

OSPF configuration:

(config)#router ospf 100	Enter into router OSPF mode
(config-router)#ospf router-id 51.51.51.51	Configure router-id as lo ip address
(config-router)#network 51.51.51.51/32 area 0.0.0.0	Add lo ip address network into area 0
(config-router)#network 10.10.10.0/24 area 0.0.0.0	Add Spine-connected network into area 0
(config-router)#bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

BGP configuration:

(config) #router bgp 500	Enter into Router BGP mode
(config-router) #bgp router-id 51.51.51.51	Configure router-id as lo ip address
(config-router) #neighbor 66.66.66.66 remote-as 500	Specify a BorderVTEP1 loopback ip address and remote-as defined
(config-router) #neighbor 66.66.66.66 update-source lo	Configure update as loopback for BorderVTEP1
(config-router) #neighbor 66.66.66.66 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for BorderVTEP1
(config-router) # address-family ipv4 unicast	Enter into IPV4 unicast address family mode
(config-router-af) # neighbor 66.66.66.66 activate	Activate BorderVTEP1 into ipv4 unicast family
(config-router-af) # exit-address-family	Exit from IPV4 unicast address family
(config-router) #address-family l2vpn evpn	Enter into L2VPN EVPN address family mode
(config-router-af) #neighbor 66.66.66.66 activate	Activate BorderVTEP1 into L2VPN EVPN address family mode
(config-router-af) #exit-address-family	Exit from L2VPN address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

L2 VRF Configuration:

(config) # mac vrf RED	Create mac routing/forwarding instance with RED name and enter into vrf mode
(config-vrf) # rd 2.3.4.5:1	Assign RD value
(config-vrf) # route-target both 6000:6000	Assign route-target value for same for import and export. Should be same on all nodes for RED
(config-vrf) #exit	Exit from vrf mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

L3 VRF and BGP Configuration:

(config) # ip vrf FAX	Create mac routing/forwarding instance with FAX name and enter into vrf mode
(config-vrf) # rd 51.51.51.51:1050	Assign RD value
(config-vrf) # route-target both 1050:1050	Assign route-target value for same for import and export.
(config-vrf) # l3vni 10502	Configure L3VNI as 10502 for FAX vrf
(config-vrf) #exit	Exit from vrf mode
(config) # interface irb 1050	Configure IRB interface 1050
(config-if) ip vrf forwarding FAX	Configure FAX
(config-if) ip address 10.12.32.1/24	Configure IP address
(config-if) exit	Exit from interface config mode

(config) #commit	Commit the candidate configuration to running configuration and save config and reload board
(config) router bgp 500	Enter into bgp router mode
(config-router) #address-family ipv4 vrf FAX	Enter into address-family mode for FAX
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) #exit-address-family	Exit from address-family
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VXLAN configuration:

(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan vtep-ip-global 51.51.51.51	Configure Source vtep-ip-global configuration. Use loopback ip address
(config) #nvo vxlan id 1050 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp RED	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb1050	Configure irb1050 under vxlan id 1050
(config) # nvo vxlan access-if port-vlan ce50 1050	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN)
(config-nvo-acc-if) # map vnid 1050	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.3333.1050 ip 10.12.32.10	Configure static mac-ip
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VTEP2

(Multi-homed group) - Part of both Multi-homed with po1000(MH).

Hardware profile and generic configuration:

#configure terminal	Enter Configure mode.
(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan irb	Enable VXLAN irb
(config) # evpn irb-forwarding anycast-gateway-mac 0000.2222.3333	Configure Anycast gateway mac
(Config) #qos enable	Enabling qos
(Config) # bfd interval 3 minrx 3 multiplier 3	Configure bfd
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

Interface and loopback configuration:

(config)#interface xe4	Enter Interface mode for xe4(MH)
(config-if)# description ***Connected to TOR2***	Interface description
(config-if)# channel-group 1000 mode active	Make it member of po1000
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)# interface po1000	Enter into po1000 mode
(config-if)# switchport	Configure L2 mode
(config-if)# evpn multi-homed system-mac 0000.4444.5555	Configure System mac
(config)#interface lo	Enter Interface mode for lo
(config-if)#ip address 60.60.60.60/32	Configure loopback ip address
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) interface xe25	Enter interface mode
(config-if)# description ***Connected to Spine1***	Interface description
(config-if)# ip address ip address 10.10.12.1/31	Configure ip address on network side of Spine1
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

OSPF configuration:

(config)#router ospf 100	Enter into router OSPF mode
(config-router)#ospf router-id 60.60.60.60	Configure router-id as lo ip address
(config-router)#network 60.60.60.60/32 area 0.0.0.0	Add lo ip address network into area 0
(config-router)#network 10.10.12.0/24 area 0.0.0.0	Add Spine-connected network into area 0
(config-router)#bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

BGP configuration:

(config)#router bgp 500	Enter into Router BGP mode
(config-router)#bgp router-id 60.60.60.60	Configure router-id as lo ip address
(config-router)#neighbor 66.66.66.66 remote-as 500	Specify a BorderVTEP1 loopback ip address and remote-as defined
(config-router)#neighbor 66.66.66.66 update-source lo	Configure update as loopback for BorderVTEP1
(config-router)#neighbor 66.66.66.66 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for BorderVTEP1

(config-router) #neighbor 76.76.76.76 remote-	Specify a VTEP3 loopback ip address and remote-as defined as 500
(config-router) #neighbor 76.76.76.76 update-	Configure update as loopback for VTEP3 source lo
(config-router) #neighbor 76.76.76.76 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP3
(config-router) # address-family ipv4 unicast	Enter into IPV4 unicast address family mode
(config-router-af) # neighbor 66.66.66.66 activate	Activate BorderVTEP1 into ipv4 unicast family
(config-router-af) # neighbor 76.76.76.76 activate	Activate VTEP3 into ipv4 unicast family
(config-router-af) # exit-address-family	Exit from IPV4 unicast address family
(config-router) #address-family l2vpn evpn	Enter into l2vpn EVPN address family mode
(config-router-af) #neighbor 66.66.66.66 activate	Activate BorderVTEP1 into l2vpn evpn address family mode
(config-router-af) #neighbor 76.76.76.76 activate	Activate VTEP3 into l2vpn evpn address family mode
(config-router-af) #exit-address-family	Exit from l2vpn address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

L2 VRF Configuration:

(config) # mac vrf RED	Create mac routing/forwarding instance with RED name and enter into vrf mode
(config-vrf) # rd 2.3.4.5:2	Assign RD value
(config-vrf) # route-target both 6000:6000	Assign route-target value for same for import and export. Should be same on all node for RED
(config-vrf) #exit	Exit from vrf mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

L3 VRF and BGP Configuration:

(config) # ip vrf SMS	Create mac routing/forwarding instance with SMS name and enter into vrf mode
(config-vrf) # rd 60.60.60.60:1040	Assign RD value
(config-vrf) # route-target both 1040:1040	Assign route-target value for same for import and export.
(config-vrf) # l3vni 10402	Configure L3VNI as 10402 for SMS vrf
(config-vrf) #exit	Exit from vrf mode
(config) # interface irb 1060	Configure irb interface 1060
(config-if) ip vrf forwarding SMS	Configure ip vrf forwarding
(config-if) ip address 10.240.38.1/24	Configure ip address
(config-if) evpn irb-if-forwarding anycast-gateway-mac	Anycast mac configured
(config-if) exit	Exit from interface config mode

(config) #commit	Commit the candidate configuration to running configuration and save config and reload board
(config) router bgp 500	Enter into bgp router mode
(config-router) #address-family ipv4 vrf SMS	Enter into address-family mode for SMS
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) #exit-address-family	Exit from address-family
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VXLAN configuration:

(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan vtep-ip-global 60.60.60.60	Configure Source vtep-ip-global configuration. Use loopback ip address
(config) #nvo vxlan id 1060 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp RED	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb1060	Configure irb1060 under vxlan id 1060
(config) # nvo vxlan access-if port-vlan po1000 1060	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) # map vnid 1060	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1060 ip 10.240.38.10	Configure static mac-ip
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VTEP3

(Multi-homed group) - Part of both Multi-homed with po1000(MH).

Hardware profile and generic configuration:

#configure terminal	Enter Configure mode.
(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan irb	Enable VXLAN irb
(config) # evpn irb-forwarding anycast-gateway-mac 0000.2222.3333	Configure Anycast gateway mac
(Config) #qos enable	Enabling qos
(Config) # bfd interval 3 minrx 3 multiplier 3	Configure bfd
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

Interface and loopback configuration:

(config)#interface xe10	Enter Interface mode for xe10(MH)
(config-if)# description ***Connected to TOR2***	Interface description
(config-if)# channel-group 1000 mode active	Make it member of po1000
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)# interface po1000	Enter into po1000 mode
(config-if)# switchport	Configure L2 mode
(config-if)# evpn multi-homed system-mac 0000.4444.5555	Configure System mac
(config)#interface lo	Enter Interface mode for lo
(config-if)#ip address 76.76.76.76/32 secondary	Configure loopback ip address
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) interface xe27	Enter interface mode
(config-if)# description ***Connected to Spine1***	Interface description
(config-if)# ip address ip address 10.10.24.1/31	Configure ip address on network side of Spine1
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

OSPF configuration:

(config)#router ospf 100	Enter into router OSPF mode
(config-router)#ospf router-id 76.76.76.76	Configure router-id as lo ip address
(config-router)#network 76.76.76.76/32 area 0.0.0.0	Add lo ip address network into area 0
(config-router)#network 10.10.24.0/24 area 0.0.0.0	Add Spine-connected network into area 0
(config-router)#bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

BGP configuration:

(config)#router bgp 500	Enter into Router BGP mode
(config-router)#bgp router-id 76.76.76.76	Configure router-id as lo ip address
(config-router)#neighbor 66.66.66.66 remote-as 500	Specify a BorderVTEP1 loopback ip address and remote-as defined
(config-router)#neighbor 66.66.66.66 update-source lo	Configure update as loopback for BorderVTEP1

(config-router) #neighbor 66.66.66.66 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for BorderVTEP1
(config-router) #neighbor 60.60.60.60 remote-as 500	Specify a VTEP2 loopback ip address and remote-as defined as 500
(config-router) #neighbor 60.60.60.60 update-source lo	Configure update as loopback for VTEP2
(config-router) #neighbor 60.60.60.60 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2
(config-router) # address-family ipv4 unicast	Enter into IPV4 unicast address family mode
(config-router-af) # neighbor 66.66.66.66 activate	Activate BorderVTEP1 into ipv4 unicast family
(config-router-af) # neighbor 60.60.60.60 activate	Activate VTEP2 into ipv4 unicast family
(config-router-af) # exit-address-family	Exit from IPV4 unicast address family
(config-router) #address-family l2vpn evpn	Enter into l2vpn EVPN address family mode
(config-router-af) #neighbor 66.66.66.66 activate	Activate BorderVTEP1 into l2vpn evpn address family mode
(config-router-af) #neighbor 60.60.60.60 activate	Activate VTEP2 into l2vpn evpn address family mode
(config-router-af) #exit-address-family	Exit from l2vpn address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

L2 VRF Configuration:

(config) # mac vrf RED	Create mac routing/forwarding instance with RED name and enter into vrf mode
(config-vrf) # rd 2.3.4.6:2	Assign RD value
(config-vrf) # route-target both 6000:6000	Assign route-target value for same for import and export. Should be same on all node for RED
(config-vrf) #exit	Exit from vrf mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

L3 VRF and BGP Configuration:

(config) # ip vrf SMS	Create mac routing/forwarding instance with SMS name and enter into vrf mode
(config-vrf) # rd 76.76.76.76:1040	Assign RD value
(config-vrf) # route-target both 1040:1040	Assign route-target value for same for import and export.
(config-vrf) # l3vni 10402	Configure L3VNI as 10402 for SMS vrf
(config-vrf) #exit	Exit from vrf mode
(config) # interface irb 1060	Configure irb interface 1060
(config-if) ip vrf forwarding SMS	Configure ip vrf forwarding
(config-if) ip address 10.240.38.1/24	Configure ip address

(config-if) evpn irb-if-forwarding anycast-gateway-mac	Anycast mac configured
(config-if) exit	Exit from interface config mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board
(config) router bgp 500	Enter into bgp router mode
(config-router) #address-family ipv4 vrf SMS	Enter into address-family mode for SMS
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) #exit-address-family	Exit form address-family
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VXLAN configuration:

(config) #nvo vxlan vtep-ip-global 76.76.76.76	Configure Source vtep-ip-global configuration. Use loopback ip address
(config) #nvo vxlan id 1060 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp RED	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb1060	Configure irb1060 under vxlan id 1060
(config) # nvo vxlan access-if port-vlan po1000 1060	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) # map vnid 1060	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1060 ip 10.240.38.10	Configure static mac-ip
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

BorderVTEP1

Hardware profile and generic configuration:

#configure terminal	Enter Configure mode.
(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan irb	Enable VXLAN irb
(Config) #qos enable	Enabling qos
(Config) # bfd interval 3 minrx 3 multiplier 3	Configure bfd
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

Interface and loopback configuration:

(config)#interface ce50	Enter Interface mode
(config-if)# description ***Connected to FW***	Interface description
(config-if)# switchport	Configure L2 mode
(config)#interface lo	Enter Interface mode for lo
(config-if)#ip address 66.66.66.66/32	Configure loopback ip address
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) interface xe39	Enter interface mode
(config-if)# description ***Connected to Spine1***	Interface description
(config-if)# ip address ip address 10.10.14.1/31	Configure ip address on network side of Spine1
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

OSPF configuration:

(config)#router ospf 100	Enter into router OSPF mode
(config-router)#ospf router-id 66.66.66.66	Configure router-id as lo ip address
(config-router)#network 66.66.66.66/32 area 0.0.0.0	Add lo ip address network into area 0
(config-router)#network 10.10.14.0/24 area 0.0.0.0	Add Spine-connected network into area 0
(config-router)#bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

BGP configuration:

(config)#router bgp 500	Enter into Router BGP mode
(config-router)#bgp router-id 66.66.66.66	Configure router-id as lo ip address
(config-router)#neighbor 51.51.51.51 remote-as 500	Specify a VTEP1 loopback ip address and remote-as defined
(config-router)#neighbor 51.51.51.51 update-source lo	Configure update as loopback for VTEP1
(config-router)#neighbor 51.51.51.51 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP1
(config-router)#neighbor 60.60.60.60 remote-as 500	Specify a VTEP2 loopback ip address and remote-as defined
(config-router)#neighbor 60.60.60.60 update-source lo	Configure update as loopback for VTEP2
(config-router)#neighbor 60.60.60.60 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2

(config-router) #neighbor 76.76.76.76 remote-	Specify a VTEP3 loopback ip address and remote-as defined as 500
(config-router) #neighbor 76.76.76.76 update-source lo	Configure update as loopback for VTEP3
(config-router) #neighbor 76.76.76.76 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP3
(config-router) # no bgp default ipv4-unicast	It will avoid default ipv4 unicast routing
(config-router) # address-family ipv4 unicast	Enter into IPV4 unicast address family mode
(config-router-af) # neighbor 51.51.51.51 activate	Activate VTEP1 into ipv4 unicast family
(config-router-af) # neighbor 60.60.60.60 activate	Activate VTEP2 into ipv4 unicast family
(config-router-af) # neighbor 76.76.76.76 activate	Activate VTEP3 into ipv4 unicast family
(config-router-af) # exit-address-family	Exit from IPV4 unicast address family
(config-router) #address-family l2vpn evpn	Enter into l2vpn EVPN address family mode
(config-router-af) #neighbor 51.51.51.51 activate	Activate VTEP1 into l2vpn evpn address family mode
(config-router-af) #neighbor 60.60.60.60 activate	Activate VTEP2 into l2vpn evpn address family mode
(config-router-af) #neighbor 76.76.76.76 activate	Activate VTEP3 into l2vpn evpn address family mode
(config-router-af) #exit-address-family	Exit from l2vpn address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

L2 VRF Configuration:

(config) # mac vrf RED	Create mac routing/forwarding instance with RED name and enter into vrf mode
(config-vrf) # rd 2.2.4.4:4	Assign RD value
(config-vrf) # route-target both 6000:6000	Assign route-target value for same for import and export. Should be same on all node for RED
(config-vrf) #exit	Exit from vrf mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

L3 VRF and BGP Configuration:

(config) # ip vrf gvrf	Create mac routing/forwarding instance with gvrf name and enter into vrf mode
(config-vrf) # rd 4.5.6.8:6	Assign RD value
(config-vrf) # route-target import 100:100	Assign route-target value for import from FAX vrf
(config-vrf) # route-target import 300:300	Assign route-target value for import from SMS vrf
(config-vrf) # route-target export 1000:1000	Assign route-target value for export from gvrf
(config-vrf) # l3vni 500	Configure L3VNI as 500 for gvrf vrf

(config-vrf) #exit	Exit from vrf mode
(config) # interface irb 1067	Configure irb interface 1060
(config-if) ip vrf forwarding gvrif	Configure ip vrf forwarding
(config-if) ip address 10.10.18.1/24	Configure ip address
(config-if) exit	Exit from interface config mode
(config) # ip vrf FAX	Create mac routing/forwarding instance with FAX name and enter into vrf mode
(config-vrf) # rd 66.66.66.66:1050	Assign RD value
(config-vrf) # route-target both 1050:1050	Assign route-target value for same for import and export.
(config-vrf) # route-target export 100:100	Assign route-target value export from FAX
(config-vrf) # route-target import 1000:1000	Assign route-target value for import from gvrif
(config-vrf) # l3vni 10502	Configure L3VNI as 10502 for FAX vrf
(config-vrf) #exit	Exit from vrf mode
(config) # ip vrf SMS	Create mac routing/forwarding instance with SMS name and enter into vrf mode
(config-vrf) # rd 66.66.66.66:1060	Assign RD value
(config-vrf) # route-target both 1040:1040	Assign route-target value for same for import and export.
(config-vrf) # route-target export 300:300	Assign route-target value export from SMS
(config-vrf) # route-target import 1000:1000	Assign route-target value for import from gvrif
(config-vrf) # l3vni 10402	Configure L3VNI as 10402 for SMS vrf
(config-vrf) #exit	Exit from vrf mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board
(config) router bgp 500	Enter into bgp router mode
(config-router) #address-family ipv4 vrf gvrif	Enter into address-family mode for gvrif
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) # neighbor 10.10.18.2 remote-as 64603	Add Firewall as neighbor
(config-router-af) # neighbor 10.10.18.2 fall-over bfd	Configure bfd for better convergence
(config-router-af) # neighbor 10.10.18.2 activate	Activate the neighbor
(config-router-af) # neighbor 10.10.18.2 advertisement-interval 0	Configure interval 0 for better convergence
(config-router-af) #exit-address-family	Exit form address-family
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

VXLAN configuration:

(config) #nvo vxlan vtep-ip-global 66.66.66.66	Configure Source vtep-ip-global configuration. Use loopback ip address
(config) # nvo vxlan id 1067 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode

(config-nvo) #vxlan host-reachability-protocol evpn-bgp RED	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb1067	Configure irb1067 under vxlan id 1067
(config) # nvo vxlan access-if port-vlan ce50 1067	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) # map vnid 1067	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

Firewall

Hardware profile and generic configuration:

#configure terminal	Enter Configure mode.
(Config) #qos enable	Enabling qos
(Config) #bfd interval 3 minrx 3 multiplier 3	Configure bfd
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

Interface and loopback configuration:

#configure terminal	Enter Configure mode.
(config) # bridge 1 protocol rstp vlan-bridge	Configure rstp vlan bridge
(config) # vlan database	
(config) #vlan 1067 bridge 1 state enable	Configure vlans from 1067 and associate with bridge 1
(config) #interface ce30/1	Enter Interface mode for ce30/1
(config-if) # description ***Connected to BorderVTEP1***	Interface description
(config-if) #bridge-group 1	Associate to bridge 1
(config-if) # bridge-group 1 spanning-tree disable	Configure stp disable
(config-if) # switchport mode trunk	Mode as trunk
(config-if) # switchport trunk allowed vlan add 1067	Trunk allowed vlan as 1067
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface vlan1.1067	Enter Interface mode
(config-if) # ip address 10.10.18.2/24	Configure ip address
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce1/1	Enter Interface mode
(config-if) #ip address 10.10.20.1/24	Configure ip address to advertise
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

BGP configuration:

(Config) #router bgp 64603	Enter into Router BGP mode
(config-router) # neighbor 10.10.18.1 remote-as 500	Specify a BorderVTEP1 gvrif ip address and remote-as defined
(config-router) # neighbor 10.10.18.1 fall-over bfd	Configure fall-over bfd for fast convergence
(config-router) #neighbor 10.10.18.1 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence
(config-router) # address-family ipv4 unicast	Enter into IPV4 unicast address family mode
(config-router-af) # network 10.10.20.0/24	Add lo addrs as network for advertise
(config-router-af) # max-paths ebgp 8	Add max path
(config-router-af) # neighbor 10.10.18.1 activate	Activate the neighbor
(config-router-af) # neighbor 10.10.18.1 default-originate	Do default originate
(config-router-af) # exit-address-family	Exit from IPV4 unicast address family
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

TOR1 (SH)

#configure terminal	Enter Configure mode.
(config) # bridge 1 protocol rstp vlan-bridge	Configure rstp vlan bridge
(config) # vlan database	
(config) #vlan 1050 bridge 1 state enable	Configure vlans from 1050 and associate with bridge 1
(config) #interface ce1/1	Enter Interface mode for ce1/1
(config-if) #switchport	Make as L2 port by configuring switchport
(config-if) #bridge-group 1	Associate to bridge 1
(config-if) # bridge-group 1 spanning-tree disable	Configure stp disable
(config-if) # switchport mode trunk	Mode as trunk
(config-if) # switchport trunk allowed vlan add 1050	Trunk allowed vlan as 1050
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce25/1	Enter Interface mode for ce25/1
(config-if) #switchport	Make as L2 port by configuring switchport
(config-if) #bridge-group 1	Associate to bridge 1
(config-if) # bridge-group 1 spanning-tree disable	Configure stp disable
(config-if) # switchport mode trunk	Mode as trunk
(config-if) # switchport trunk allowed vlan add 1050	Trunk allowed vlan as 1050
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

TOR2 (MH)

Multihomed to 2-VTEPs (VTEP2 and VTEP3).

#configure terminal	Enter Configure mode.
(config)# bridge 1 protocol rstp vlan-bridge	Configure rstp vlan bridge
(config)# vlan database	
(config)#vlan 1060 bridge 1 state enable	Configure vlans from 1060 and associate with bridge 1
(config)#interface po1000	Enter Interface mode for po1000
(config-if)#switchport	Make as L2 port by configuring switchport
(config-if)#bridge-group 1	Associate to bridge 1
(config-if)# bridge-group 1 spanning-tree disable	Configure stp disable
(config-if)# switchport mode trunk	Mode as trunk
(config-if)# switchport trunk allowed vlan add 1060	Trunk allowed vlan as 1060
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface xe4	Enter Interface mode for xe4
(config-if)# channel-group 1000 mode active	Make it member of po1000
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface xe7	Enter Interface mode for xe7
(config-if)# channel-group 1000 mode active	Make it member of po1000
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface xe7	Enter Interface mode for ce25/1
(config-if)#switchport	Make as L2 port by configuring switchport
(config-if)#bridge-group 1	Associate to bridge 1
(config-if)# bridge-group 1 spanning-tree disable	Configure stp disable
(config-if)# switchport mode trunk	Mode as trunk
(config-if)# switchport trunk allowed vlan add 1060	Trunk allowed vlan as 1060
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#commit	Commit the candidate configuration to running configuration and save config and reload board

Spine1

Spine node where all VTEPs are connected.

Generic configuration:

#configure terminal	Enter Configure mode.
(Config)#qos enable	Enabling qos

(Config) # bfd interval 3 minrx 3 multiplier 3	Configure bfd
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

Interface and loopback configuration:

(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 62.62.62.62/32 secondary	Configure loopback ip address
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe40	Enter Interface mode
(config-if) # description ***Connected to VTEP1***	Description of interface
(config-if) #ip address ip address 10.10.10.2/31	Configure ip address on network side of VTEP1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe25	Enter Interface mode
(config-if) # description ***Connected to VTEP2***	Description of interface
(config-if) #ip address ip address 10.10.12.2/31	Configure ip address on network side of VTEP2
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe27	Enter Interface mode
(config-if) # description ***Connected to VTEP3***	Description of interface
(config-if) #ip address ip address 10.10.24.2/31	Configure ip address on network side of VTEP3
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe39	Enter Interface mode
(config-if) # description ***Connected to BorderVTEP1***	Description of interface
(config-if) #ip address ip address 10.10.14.2/31	Configure ip address on network side of BorderVTEP1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

OSPF configuration:

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 62.62.62.62	Configure router-id as lo ip address
(config-router) #network 62.62.62.62/32 area 0.0.0.0	Add lo ip address network into area 0
(config-router) #network 10.10.10.0/24 area 0.0.0.0	Add VTEP1 network into area 0

(config-router) #network 10.10.12.0/24 area 0.0.0.0	Add VTEP2 network into area 0
(config-router) #network 10.10.14.0/24 area 0.0.0.0	Add VTEP4 network into area 0
(config-router) #network 10.10.24.0/24 area 0.0.0.0	Add VTEP3 network into area 0
(config-router) #bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #commit	Commit the candidate configuration to running configuration and save config and reload board

Validations

Firewall

=====

```
Firewall#show ip bgp summary
BGP router identifier 10.10.19.2, local AS number 64603
BGP table version is 3
2 BGP AS-PATH entries
0 BGP community entries
8 Configured ebgp ECMP multipath: Currently set at 8
```

Neighbor n State/PfxRcd	V	AS	MsgRcv	MsgSen	TblVer	InQ	OutQ	Up/Dow
10.10.18.1	4	500	46	58	3	0	0	00:17:36
	3							

Total number of neighbors 1

Total number of Established sessions 1

Firewall#show ip rov

Firewall#show ip route vrf all

```
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
      O - OSPF, IA - OSPF inter area
      N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
      E1 - OSPF external type 1, E2 - OSPF external type 2
      i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
      ia - IS-IS inter area, E - EVPN,
      v - vrf leaked
      * - candidate default
```

IP Route Table for VRF "default"

```
C          10.10.18.0/24 is directly connected, vlan1.1067, 00:19:40
C          10.10.20.0/24 is directly connected, ce1/1, 00:00:13
B          10.12.32.0/24 [20/0] via 10.10.18.1, vlan1.1067, 00:17:43
B          10.240.38.0/24 [20/0] via 10.10.18.1, vlan1.1067, 00:17:43
C          127.0.0.0/8 is directly connected, lo, 00:52:18
```

IP Route Table for VRF "management"

```
C          10.12.85.0/24 is directly connected, eth0, 00:52:07
```

C 127.0.0.0/8 is directly connected, lo.management, 00:52:18

Gateway of last resort is not set

FW#

BorderVTEP1

=====

BorderVTEP1#show nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status
Src-Addr							
1067	---	--	AC	ce50	--- Single Homed Port ---	1067	---
---	---	---				---	---
10402	----	L3	NW	----	----	----	----
66.66.66.66	60.60.60.60						
10402	----	L3	NW	----	----	----	----
66.66.66.66	76.76.76.76						
10502	----	L3	NW	----	----	----	----
66.66.66.66	51.51.51.51						

Total number of entries are 4

BorderVTEP1#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
66.66.66.66	51.51.51.51	Installed	00:22:36	00:22:36
66.66.66.66	60.60.60.60	Installed	00:22:36	00:22:36
66.66.66.66	76.76.76.76	Installed	00:22:36	00:22:36

Total number of entries are 3

BorderVTEP1#show ip route vrf all

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP

O - OSPF, IA - OSPF inter area

N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2

E1 - OSPF external type 1, E2 - OSPF external type 2

i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,

ia - IS-IS inter area, E - EVPN,

v - vrf leaked

* - candidate default

IP Route Table for VRF "default"

O	10.10.10.0/31 [110/2] via 10.10.14.0, xe39, 00:22:44
O	10.10.12.0/31 [110/2] via 10.10.14.0, xe39, 00:22:44
C	10.10.14.0/31 is directly connected, xe39, 00:23:29

```

O      10.10.24.0/31 [110/2] via 10.10.14.0, xe39, 00:22:44
O      51.51.51.51/32 [110/3] via 10.10.14.0, xe39, 00:22:44
O      60.60.60.60/32 [110/3] via 10.10.14.0, xe39, 00:22:44
C      66.66.66.66/32 is directly connected, lo, 00:23:32
O      76.76.76.76/32 [110/3] via 10.10.14.0, xe39, 00:22:44
C      127.0.0.0/8 is directly connected, lo, 00:24:12
IP Route Table for VRF "management"
C          10.12.86.0/24 is directly connected, eth0, 00:23:38
C          127.0.0.0/8 is directly connected, lo.management, 00:24:12
IP Route Table for VRF "gvrf"
Gateway of last resort is 10.10.18.2 to network 0.0.0.0

B*      0.0.0.0/0 [20/0] via 10.10.18.2, irb1067, 00:21:31
C          10.10.18.0/24 is directly connected, irb1067, 00:23:30
B          10.10.20.0/24 [20/0] via 10.10.18.2, irb1067, 00:04:01
B      v      10.12.32.0/24 [200/0] via 51.51.51.51 (recursive is directly connected,
tunvxlan3), 00:22:39
B      v      10.240.38.0/24 [200/0] via 60.60.60.60 (recursive is directly connected,
tunvxlan4), 00:22:40
C          127.0.0.0/8 is directly connected, lo.gvrf, 00:23:36
IP Route Table for VRF "SMS"
Gateway of last resort is 10.10.18.2 to network 0.0.0.0

B*      v      0.0.0.0/0 [20/0] via 10.10.18.2, irb1067, 00:21:31
B      v      10.10.18.0/24 [20/0] is directly connected, irb1067, 00:23:30
B      v      10.10.20.0/24 [20/0] via 10.10.18.2, irb1067, 00:04:01
B          10.240.38.0/24 [200/0] via 60.60.60.60 (recursive is directly connected,
tunvxlan4), 00:22:40
B          60.60.60.60/32 [0/0] is directly connected, tunvxlan4, 00:22:39
B          76.76.76.76/32 [0/0] is directly connected, tunvxlan4, 00:22:39
C          127.0.0.0/8 is directly connected, lo.SMS, 00:23:35
IP Route Table for VRF "FAX"
Gateway of last resort is 10.10.18.2 to network 0.0.0.0

B*      v      0.0.0.0/0 [20/0] via 10.10.18.2, irb1067, 00:21:31
B      v      10.10.18.0/24 [20/0] is directly connected, irb1067, 00:23:30
B      v      10.10.20.0/24 [20/0] via 10.10.18.2, irb1067, 00:04:01
B          10.12.32.0/24 [200/0] via 51.51.51.51 (recursive is directly connected,
tunvxlan3), 00:22:39
B          51.51.51.51/32 [0/0] is directly connected, tunvxlan3, 00:22:39
C          127.0.0.0/8 is directly connected, lo.FAX, 00:23:35
IP Route Table for VRF "SMM"
C          127.0.0.0/8 is directly connected, lo.SMM, 00:23:35

Gateway of last resort is not set
BorderVTEP1#          show bgp l2vpn evpn summary
BGP router identifier 66.66.66.66, local AS number 500
BGP table version is 6
2 BGP AS-PATH entries
0 BGP community entries

```

Neighbor PfxRcd	AD	MACIP	V MCAST	AS ESI	MsgRcv PREFIX-ROUTE	MsgSen	TblVer	InQ	OutQ	Up/Down	State/
51.51.51.51 7	0	5	1	4 0	500 1	62	71	6	0	0	00:22:50
60.60.60.60 8	2	3	1	4 1	500 1	65	71	6	0	0	00:22:50
76.76.76.76 9	2	4	1	4 1	500 1	65	70	6	0	0	00:22:50

Total number of neighbors 3

Total number of Established sessions 3

BorderVTEP1# show bgp 12vpn evpn

BGP table version is 6, local router ID is 66.66.66.66

Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
l - labeled, S Stale

Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route information]

- 1 - Ethernet Auto-discovery Route
- 2 - MAC/IP Route
- 3 - Inclusive Multicast Route
- 4 - Ethernet Segment Route
- 5 - Prefix Route

Network Encap	Next Hop	Metric	LocPrf	Weight	Path	Peer
------------------	----------	--------	--------	--------	------	------

RD[2.2.4.4:4] VRF[RED]:

* i [1]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[1060]	76.76.76.76	0	100	0	i	76.76.76.76	VXLAN
* i 60.60.60.60	0	100	0	i	60.60.60.60	VXLAN	
* i [1]:[00:00:00:44:44:55:55:00:00:00]:[4294967295]:[0]	76.76.76.76	0	100	0	i	76.76.76.76	VXLAN
* i 60.60.60.60	0	100	0	i	60.60.60.60	VXLAN	
* i [2]:[0]:[1050]:[48,0000:0e8d:561a]:[0]:[1050]	51.51.51.51	0	100	0	i	51.51.51.51	VXLAN
* i [2]:[0]:[1050]:[48,0000:0e8d:561a]:[32,10.12.32.11]:[1050]	51.51.51.51	0	100	0	i	51.51.51.51	VXLAN
* i [2]:[0]:[1050]:[48,0000:3333:1050]:[32,10.12.32.10]:[1050]	51.51.51.51	0	100	0	i	51.51.51.51	VXLAN
* i [2]:[0]:[1050]:[48,3c2c:99d6:167a]:[32,10.12.32.1]:[1050]	51.51.51.51	0	100	0	i	51.51.51.51	VXLAN
* i [2]:[0]:[1050]:[48,3c2c:99d6:167a]:[128,2401::1]:[1050]	51.51.51.51	0	100	0	i	51.51.51.51	VXLAN
* i [2]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[48,0000:0e8d:5619]:[0]:[1060]	76.76.76.76	0	100	0	i	76.76.76.76	VXLAN
* i [2]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[48,0000:2222:1060]:[32,10.240.38.10]:[1060]	76.76.76.76	0	100	0	i	76.76.76.76	VXLAN
* i 60.60.60.60	0	100	0	i	60.60.60.60	VXLAN	
* i [2]:[0]:[1060]:[48,0000:2222:3333]:[32,10.240.38.1]:[1060]							

	76.76.76.76	0	100	0	i	76.76.76.76	VXLAN
* i	60.60.60.60	0	100	0	i	60.60.60.60	VXLAN
* i [2]:[0]:[1060]:[48,0000:2222:3333]:[128,1601::1]:[1060]	76.76.76.76	0	100	0	i	76.76.76.76	VXLAN
* i	60.60.60.60	0	100	0	i	60.60.60.60	VXLAN
*> [2]:[0]:[1067]:[48,3c2c:991c:dc7a]:[32,10.10.18.1]:[1067]	66.66.66.66	0	100	32768	i	-----	VXLAN
*> [2]:[0]:[1067]:[48,a82b:b5cf:f806]:[32,10.10.18.2]:[1067]	66.66.66.66	0	100	32768	i	-----	VXLAN
* i [3]:[1050]:[32,51.51.51.51]	51.51.51.51	0	100	0	i	51.51.51.51	VXLAN
* i [3]:[1060]:[32,60.60.60.60]	60.60.60.60	0	100	0	i	60.60.60.60	VXLAN
* i [3]:[1060]:[32,76.76.76.76]	76.76.76.76	0	100	0	i	76.76.76.76	VXLAN
*> [3]:[1067]:[32,66.66.66.66]	66.66.66.66	0	100	32768	i	-----	VXLAN
RD[2.3.4.5:1]							
*>i [2]:[0]:[1050]:[48,0000:0e8d:561a]:[0]:[1050]	51.51.51.51	0	100	0	i	51.51.51.51	VXLAN
*>i [2]:[0]:[1050]:[48,0000:0e8d:561a]:[32,10.12.32.11]:[1050]	51.51.51.51	0	100	0	i	51.51.51.51	VXLAN
*>i [2]:[0]:[1050]:[48,0000:3333:1050]:[32,10.12.32.10]:[1050]	51.51.51.51	0	100	0	i	51.51.51.51	VXLAN
*>i [2]:[0]:[1050]:[48,3c2c:99d6:167a]:[32,10.12.32.1]:[1050]	51.51.51.51	0	100	0	i	51.51.51.51	VXLAN
*>i [2]:[0]:[1050]:[48,3c2c:99d6:167a]:[128,2401::1]:[1050]	51.51.51.51	0	100	0	i	51.51.51.51	VXLAN
*>i [3]:[1050]:[32,51.51.51.51]	51.51.51.51	0	100	0	i	51.51.51.51	VXLAN
RD[2.3.4.5:2]							
*>i [1]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[1060]	60.60.60.60	0	100	0	i	60.60.60.60	VXLAN
*>i [2]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[48,0000:2222:1060]:[32,10.240.38.10]:[1060]	60.60.60.60	0	100	0	i	60.60.60.60	VXLAN
*>i [2]:[0]:[1060]:[48,0000:2222:3333]:[32,10.240.38.1]:[1060]	60.60.60.60	0	100	0	i	60.60.60.60	VXLAN
*>i [2]:[0]:[1060]:[48,0000:2222:3333]:[128,1601::1]:[1060]	60.60.60.60	0	100	0	i	60.60.60.60	VXLAN
*>i [3]:[1060]:[32,60.60.60.60]	60.60.60.60	0	100	0	i	60.60.60.60	VXLAN
RD[2.3.4.6:2]							
*>i [1]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[1060]	76.76.76.76	0	100	0	i	76.76.76.76	VXLAN

```

*>i [2]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[48,0000:0e8d:5619]:[0]:[1060]
      76.76.76.76          0         100          0   i 76.76.76.76    VXLAN
*>i
[2]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[48,0000:2222:1060]:[32,10.240.38.10]:[1060]
      76.76.76.76          0         100          0   i 76.76.76.76    VXLAN
*>i [2]:[0]:[1060]:[48,0000:2222:3333]:[32,10.240.38.1]:[1060]
      76.76.76.76          0         100          0   i 76.76.76.76    VXLAN
*>i [2]:[0]:[1060]:[48,0000:2222:3333]:[128,1601::1]:[1060]
      76.76.76.76          0         100          0   i 76.76.76.76    VXLAN
*>i [3]:[1060]:[32,76.76.76.76]
      76.76.76.76          0         100          0   i 76.76.76.76    VXLAN

RD[51.51.51.51:1050]
*>i [5]:[0]:[10502]:[24]:[10.12.32.0]:[0.0.0.0]:[10502]
      51.51.51.51          0         100          0   ? 51.51.51.51    VXLAN

RD[60.60.60.60:1]
*>i [1]:[00:00:00:44:44:55:55:00:00:00]:[4294967295]:[0]
      60.60.60.60          0         100          0   i 60.60.60.60    VXLAN
*>i [4]:[00:00:00:44:44:55:55:00:00:00]:[32,60.60.60.60]
      60.60.60.60          0         100          0   i 60.60.60.60    VXLAN

RD[60.60.60.60:1040]
*>i [5]:[0]:[10402]:[24]:[10.240.38.0]:[0.0.0.0]:[10402]
      60.60.60.60          0         100          0   ? 60.60.60.60    VXLAN

RD[76.76.76.76:1]
*>i [1]:[00:00:00:44:44:55:55:00:00:00]:[4294967295]:[0]
      76.76.76.76          0         100          0   i 76.76.76.76    VXLAN
*>i [4]:[00:00:00:44:44:55:55:00:00:00]:[32,76.76.76.76]
      76.76.76.76          0         100          0   i 76.76.76.76    VXLAN

RD[76.76.76.76:1040]
*>i [5]:[0]:[10402]:[24]:[10.240.38.0]:[0.0.0.0]:[10402]
      76.76.76.76          0         100          0   ? 76.76.76.76    VXLAN

```

Total number of prefixes 41

BorderVTEP1#

BorderVTEP1#show bgp 12vpn evpn prefix-route

RD[51.51.51.51:1050]		ESI	Eth-Tag	Prefix-Length	L3VNID	IP-Address	Nexthop	Encap	Router-Mac	GW-
IP Address										
0	10502	24		10.12.32.0				0.0.0.0		
10502	51.51.51.51		VXLAN		3c2c:99d6:167a					

RD[60.60.60.60:1040]		ESI	Eth-Tag	Prefix-Length	L3VNID	IP-Address	Nexthop	Encap	Router-Mac	GW-
IP Address										

0 10402	10402 60.60.60	24 VXLAN	10.240.38.0 3c2c:99d1:117a	0.0.0.0	
RD[76.76.76.76:1040]					
ESI IPAddress		Eth-Tag L3VNID	Prefix-Length Nexthop	IP-Address Encap	GW- Router-Mac
0 10402	10402 76.76.76	24 VXLAN	10.240.38.0 3c2c:99de:1e7a	0.0.0.0	

VTEP3

=====

VTEP3#show nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port

AC - Access Port

(u) - Untagged

VNID Src-Addr	VNI-Name Dst-Addr	VNI-Type	Type	Interface	ESI	VLAN	DF-Status
1060 76.76.76.76	---	L2	NW	----	----	-----	-----
1060 ----	60.60.60.60 ----	--	AC	po1000	00:00:00:44:44:55:55:00:00:00	1060	NON-DF
10402 76.76.76	---	L3	NW	----	----	-----	-----
	66.66.66.66						

Total number of entries are 3

VTEP3#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
76.76.76.76	66.66.66.66	Installed	00:24:35	00:24:35
76.76.76.76	60.60.60.60	Installed	00:54:40	00:54:40

Total number of entries are 2

VTEP3#show ip route vrf all

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP

O - OSPF, IA - OSPF inter area

N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2

E1 - OSPF external type 1, E2 - OSPF external type 2

i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,

ia - IS-IS inter area, E - EVPN,

v - vrf leaked

* - candidate default

IP Route Table for VRF "default"

```

O      10.10.10.0/31 [110/2] via 10.10.24.1, xe27, 00:54:56
O      10.10.12.0/31 [110/2] via 10.10.24.1, xe27, 00:54:56
O      10.10.14.0/31 [110/2] via 10.10.24.1, xe27, 00:25:31
C      10.10.24.0/31 is directly connected, xe27, 00:55:37
O      51.51.51.51/32 [110/3] via 10.10.24.1, xe27, 00:54:47
O      60.60.60.60/32 [110/3] via 10.10.24.1, xe27, 00:54:45
O      66.66.66.66/32 [110/3] via 10.10.24.1, xe27, 00:24:46
C      76.76.76.76/32 is directly connected, lo, 00:55:38
C      127.0.0.0/8 is directly connected, lo, 00:55:39
IP Route Table for VRF "management"
C      10.12.20.0/24 is directly connected, eth0, 00:55:10
C      127.0.0.0/8 is directly connected, lo.management, 00:55:39
IP Route Table for VRF "SMS"
Gateway of last resort is 66.66.66.66 to network 0.0.0.0

B*      0.0.0.0/0 [200/0] via 66.66.66.66 (recursive is directly connected,
tunvxlan2), 00:23:33
B      10.10.18.0/24 [200/0] via 66.66.66.66 (recursive is directly connected,
tunvxlan2), 00:24:41
B      10.10.20.0/24 [200/0] via 66.66.66.66 (recursive is directly connected,
tunvxlan2), 00:06:03
C      10.240.38.0/24 is directly connected, irb1060, 00:55:38
B      66.66.66.66/32 [0/0] is directly connected, tunvxlan2, 00:24:41
C      127.0.0.0/8 is directly connected, lo.SMS, 00:55:39
VTEP3#    show bgp l2vpn evpn summary
BGP router identifier 76.76.76.76, local AS number 500
BGP table version is 8
2 BGP AS-PATH entries
0 BGP community entries

```

Neighbor	V	AS	MsgRcv	MsgSen	TblVer	InQ	OutQ	Up/Down	State/
PfxRcd	AD	MACIP	MCAST	ESI	PREFIX-ROUTE				
60.60.60.60			4	500	144	140	7	0	0 00:54:55
8	2	3	1	1	1				
66.66.66.66			4	500	127	125	7	0	0 00:24:51
12	0	2	1	0	9				

Total number of neighbors 2

Total number of Established sessions 2

VTEP3# show bgp l2vpn evpn

BGP table version is 8, local router ID is 76.76.76.76

Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
l - labeled, S Stale

Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route information]

1 - Ethernet Auto-discovery Route

2 - MAC/IP Route

3 - Inclusive Multicast Route

4 - Ethernet Segment Route

5 - Prefix Route

Network Encap	Next Hop	Metric	LocPrf	Weight	Path	Peer
RD[2.2.4.4:4]						
*>i [2]:[0]:[1067]:[48,3c2c:991c:dc7a]:[32,10.10.18.1]:[1067]	66.66.66.66	0	100	0	i 66.66.66.66	VXLAN
*>i [2]:[0]:[1067]:[48,a82b:b5cf:f806]:[32,10.10.18.2]:[1067]	66.66.66.66	0	100	0	i 66.66.66.66	VXLAN
*>i [3]:[1067]:[32,66.66.66.66]	66.66.66.66	0	100	0	i 66.66.66.66	VXLAN
RD[2.3.4.5:2]						
*>i [1]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[1060]	60.60.60.60	0	100	0	i 60.60.60.60	VXLAN
*>i [2]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[48,0000:2222:1060]:[32,10.240.38.10]:[1060]	60.60.60.60	0	100	0	i 60.60.60.60	VXLAN
*>i [2]:[0]:[1060]:[48,0000:2222:3333]:[32,10.240.38.1]:[1060]	60.60.60.60	0	100	0	i 60.60.60.60	VXLAN
*>i [2]:[0]:[1060]:[48,0000:2222:3333]:[128,1601::1]:[1060]	60.60.60.60	0	100	0	i 60.60.60.60	VXLAN
*>i [3]:[1060]:[32,60.60.60.60]	60.60.60.60	0	100	0	i 60.60.60.60	VXLAN
RD[2.3.4.6:2] VRF[RED]:						
*> [1]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[1060]	76.76.76.76	0	100	32768	i -----	
VXLAN						
* i 60.60.60.60	0	100	0	i 60.60.60.60	VXLAN	
* i [1]:[00:00:00:44:44:55:55:00:00:00]:[4294967295]:[0]	60.60.60.60	0	100	0	i 60.60.60.60	VXLAN
*> [2]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[48,0000:0e8d:5619]:[0]:[1060]	76.76.76.76	0	100	32768	i -----	
VXLAN						
*> [2]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[48,0000:2222:1060]:[32,10.240.38.10]:[1060]	76.76.76.76	0	100	32768	i -----	
VXLAN						
* i 60.60.60.60	0	100	0	i 60.60.60.60	VXLAN	
* i [2]:[0]:[1060]:[48,0000:2222:3333]:[32,10.240.38.1]:[1060]	60.60.60.60	0	100	0	i 60.60.60.60	VXLAN
*> 76.76.76.76	0	100	32768	i -----		
VXLAN						
* i [2]:[0]:[1060]:[48,0000:2222:3333]:[128,1601::1]:[1060]	60.60.60.60	0	100	0	i 60.60.60.60	VXLAN
*> 76.76.76.76	0	100	32768	i -----		
VXLAN						
* i [2]:[0]:[1067]:[48,3c2c:991c:dc7a]:[32,10.10.18.1]:[1067]	66.66.66.66	0	100	0	i 66.66.66.66	VXLAN
* i [2]:[0]:[1067]:[48,a82b:b5cf:f806]:[32,10.10.18.2]:[1067]	66.66.66.66	0	100	0	i 66.66.66.66	VXLAN

```

* i [3]:[1060]:[32,60.60.60.60]
          60.60.60.60      0      100      0   i 60.60.60.60    VXLAN
*> [3]:[1060]:[32,76.76.76.76]
          76.76.76.76      0      100      32768 i -----
VXLAN
* i [3]:[1067]:[32,66.66.66.66]
          66.66.66.66      0      100      0   i 66.66.66.66    VXLAN

RD[4.5.6.8:6]
*>i [5]:[0]:[500]:[0]:[0.0.0.0]:[0.0.0.0]:[500]
          66.66.66.66      0      100      0   64603 i 66.66.66.66
VXLAN
*>i [5]:[0]:[500]:[24]:[10.10.18.0]:[0.0.0.0]:[500]
          66.66.66.66      0      100      0   ? 66.66.66.66    VXLAN
*>i [5]:[0]:[500]:[24]:[10.10.20.0]:[0.0.0.0]:[500]
          66.66.66.66      0      100      0   64603 i 66.66.66.66
VXLAN

RD[60.60.60.60:1]
*>i [1]:[00:00:00:44:44:55:55:00:00:00]:[4294967295]:[0]
          60.60.60.60      0      100      0   i 60.60.60.60    VXLAN
*>i [4]:[00:00:00:44:44:55:55:00:00:00]:[32,60.60.60.60]
          60.60.60.60      0      100      0   i 60.60.60.60    VXLAN

RD[60.60.60.60:1040]
*>i [5]:[0]:[10402]:[24]:[10.240.38.0]:[0.0.0.0]:[10402]
          60.60.60.60      0      100      0   ? 60.60.60.60    VXLAN

RD[66.66.66.66:1050]
*>i [5]:[0]:[500]:[0]:[0.0.0.0]:[0.0.0.0]:[500]
          66.66.66.66      0      100      0   64603 i 66.66.66.66
VXLAN
*>i [5]:[0]:[500]:[24]:[10.10.18.0]:[0.0.0.0]:[500]
          66.66.66.66      0      100      0   ? 66.66.66.66    VXLAN
*>i [5]:[0]:[500]:[24]:[10.10.20.0]:[0.0.0.0]:[500]
          66.66.66.66      0      100      0   64603 i 66.66.66.66
VXLAN

RD[66.66.66.66:1060]
*>i [5]:[0]:[500]:[0]:[0.0.0.0]:[0.0.0.0]:[500]
          66.66.66.66      0      100      0   64603 i 66.66.66.66
VXLAN
*>i [5]:[0]:[500]:[24]:[10.10.18.0]:[0.0.0.0]:[500]
          66.66.66.66      0      100      0   ? 66.66.66.66    VXLAN
*>i [5]:[0]:[500]:[24]:[10.10.20.0]:[0.0.0.0]:[500]
          66.66.66.66      0      100      0   64603 i 66.66.66.66
VXLAN

RD[76.76.76.76:1] VRF[evpn-gvrf-1]:
*> [1]:[00:00:00:44:44:55:55:00:00:00]:[4294967295]:[0]
          76.76.76.76      0      100      32768 i -----
VXLAN

```

```
* i [4]:[00:00:00:44:44:55:55:00:00:00]:[32,60.60.60.60]
      60.60.60.60          0         100          0   i 60.60.60.60      VXLAN
*> [4]:[00:00:00:44:44:55:55:00:00:00]:[32,76.76.76.76]
      76.76.76.76          0         100        32768 i -----
VXLAN
```

Total number of prefixes 34

VTEP3#

VTEP3#show bgp 12vpn evpn prefix-route

RD[4.5.6.8:6]

ESI IPAddress	Eth-Tag	Prefix-Length	L3VNID	IP-Address Nexthop	Encap	GW- Router-Mac
0 500	500 66.66.66.66	0 24	VXLAN	0.0.0.0 3c2c:991c:dc7a	0.0.0.0	
0 500	500 66.66.66.66	24	VXLAN	10.10.18.0 3c2c:991c:dc7a	0.0.0.0	
0 500	500 66.66.66.66	24	VXLAN	10.10.20.0 3c2c:991c:dc7a	0.0.0.0	
0 500	500 66.66.66.66	24	VXLAN	10.240.38.0 3c2c:99d1:117a	0.0.0.0	

RD[60.60.60.60:1040]

ESI IPAddress	Eth-Tag	Prefix-Length	L3VNID	IP-Address Nexthop	Encap	GW- Router-Mac
0 10402	10402 60.60.60.60	24	VXLAN	0.0.0.0 3c2c:991c:dc7a	0.0.0.0	
10402						

RD[66.66.66.66:1050]

ESI IPAddress	Eth-Tag	Prefix-Length	L3VNID	IP-Address Nexthop	Encap	GW- Router-Mac
0 500	500 66.66.66.66	0 24	VXLAN	0.0.0.0 3c2c:991c:dc7a	0.0.0.0	
0 500	500 66.66.66.66	24	VXLAN	10.10.18.0 3c2c:991c:dc7a	0.0.0.0	
0 500	500 66.66.66.66	24	VXLAN	10.10.20.0 3c2c:991c:dc7a	0.0.0.0	
0 500	500 66.66.66.66	24	VXLAN	10.240.38.0 3c2c:991c:dc7a	0.0.0.0	

RD[66.66.66.66:1060]

ESI IPAddress	Eth-Tag	Prefix-Length	L3VNID	IP-Address Nexthop	Encap	GW- Router-Mac
0 500	500 66.66.66.66	0 24	VXLAN	0.0.0.0 3c2c:991c:dc7a	0.0.0.0	
0 500	500 66.66.66.66	24	VXLAN	10.10.18.0 3c2c:991c:dc7a	0.0.0.0	
0 500	500 66.66.66.66	24	VXLAN	10.10.20.0 3c2c:991c:dc7a	0.0.0.0	
0 500	500 66.66.66.66	24	VXLAN	10.240.38.0 3c2c:991c:dc7a	0.0.0.0	

VTEP2

=====

VTEP2#show nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port

AC - Access Port
(u) - Untagged

VNID Src-Addr	VNI-Name Dst-Addr	VNI-Type Type	Interface	ESI	VLAN	DF-Status
1060 60.60.60.60	---	L2 76.76.76.76	NW	----	----	----
1060 ----	----	-- AC	po1000	00:00:00:44:44:55:55:00:00:00	1060	DF
10402 60.60.60.60	----	L3 66.66.66.66	NW	----	----	----

Total number of entries are 3

VTEP2#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
60.60.60.60	66.66.66.66	Installed	00:26:50	00:26:50
60.60.60.60	76.76.76.76	Installed	00:56:51	00:56:51

Total number of entries are 2

VTEP2#show ip route vrf all

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
ia - IS-IS inter area, E - EVPN,
v - vrf leaked
* - candidate default

IP Route Table for VRF "default"

O 10.10.10.0/31 [110/2] via 10.10.12.0, xe25, 00:57:13
C 10.10.12.0/31 is directly connected, xe25, 00:57:57
O 10.10.14.0/31 [110/2] via 10.10.12.0, xe25, 00:27:47
O 10.10.16.0/31 [110/2] via 10.10.12.0, xe25, 00:57:13
O 10.10.24.0/31 [110/2] via 10.10.12.0, xe25, 00:57:13
O 51.51.51.51/32 [110/3] via 10.10.12.0, xe25, 00:57:03
C 60.60.60.60/32 is directly connected, lo, 00:57:59
O 66.66.66.66/32 [110/3] via 10.10.12.0, xe25, 00:27:02
O 76.76.76.76/32 [110/3] via 10.10.12.0, xe25, 00:57:13
C 127.0.0.0/8 is directly connected, lo, 00:58:00

IP Route Table for VRF "management"

C 10.12.20.0/24 is directly connected, eth0, 00:57:29
C 127.0.0.0/8 is directly connected, lo.management, 00:58:00

IP Route Table for VRF "SMS"

Gateway of last resort is 66.66.66.66 to network 0.0.0.0

B* 0.0.0.0/0 [200/0] via 66.66.66.66 (recursive is directly connected,
tunvxlan2), 00:25:49

```
B          10.10.18.0/24 [200/0] via 66.66.66.66 (recursive is directly connected,
tunvxlan2), 00:26:58
B          10.10.20.0/24 [200/0] via 66.66.66.66 (recursive is directly connected,
tunvxlan2), 00:08:19
C          10.240.38.0/24 is directly connected, irb1060, 00:57:58
B          66.66.66.66/32 [0/0] is directly connected, tunvxlan2, 00:26:58
C          127.0.0.0/8 is directly connected, lo.SMS, 00:58:00
```

VTEP2#show bgp l2vpn evpn sum
BGP router identifier 60.60.60.60, local AS number 500
BGP table version is 12
2 BGP AS-PATH entries
0 BGP community entries

Neighbor	V	AS	MsgRcv	MsgSen	TblVer	InQ	OutQ	Up/Down	State/
PfxRcd	AD	MACIP	MCAST	ESI	PREFIX-ROUTE				
66.66.66.66			4	500	135	133	11	0	00:27:29
12	0	2	1	0	9				
76.76.76.76			4	500	146	150	11	0	00:57:30
9	2	4	1	1	1				

Total number of neighbors 2

Total number of Established sessions 2
VTEP2#show bgp l2vpn evpn
BGP table version is 12, local router ID is 60.60.60.60
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route
4 - Ethernet Segment Route
5 - Prefix Route

Network	Next Hop	Metric	LocPrf	Weight	Path	Peer
Encap						
RD[2.2.4.4:4]						
*>i [2]:[0]:[1067]:[48,3c2c:991c:dc7a]:[32,10.10.18.1]:[1067]	66.66.66.66	0	100	0	i 66.66.66.66	VXLAN
*>i [2]:[0]:[1067]:[48,a82b:b5cf:f806]:[32,10.10.18.2]:[1067]	66.66.66.66	0	100	0	i 66.66.66.66	VXLAN
*>i [3]:[1067]:[32,66.66.66.66]	66.66.66.66	0	100	0	i 66.66.66.66	VXLAN
RD[2.3.4.5:2] VRF[RED]:						
* i [1]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[1060]	76.76.76.76	0	100	0	i 76.76.76.76	VXLAN

```

*>          60.60.60.60      0      100      32768 i -----
VXLAN
* i [1]:[00:00:00:44:44:55:55:00:00:00]:[4294967295]:[0]
    76.76.76.76      0      100      0 i 76.76.76.76 VXLAN
* i [2]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[48,0000:0e8d:5619]:[0]:[1060]
    76.76.76.76      0      100      0 i 76.76.76.76 VXLAN
* i
[2]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[48,0000:2222:1060]:[32,10.240.38.10]:[1060]
    76.76.76.76      0      100      0 i 76.76.76.76 VXLAN
*>          60.60.60.60      0      100      32768 i -----
VXLAN
* i [2]:[0]:[1060]:[48,0000:2222:3333]:[32,10.240.38.1]:[1060]
    76.76.76.76      0      100      0 i 76.76.76.76 VXLAN
*>          60.60.60.60      0      100      32768 i -----
VXLAN
* i [2]:[0]:[1060]:[48,0000:2222:3333]:[128,1601::1]:[1060]
    76.76.76.76      0      100      0 i 76.76.76.76 VXLAN
*>          60.60.60.60      0      100      32768 i -----
VXLAN
* i [2]:[0]:[1067]:[48,3c2c:991c:dc7a]:[32,10.10.18.1]:[1067]
    66.66.66.66      0      100      0 i 66.66.66.66 VXLAN
* i [2]:[0]:[1067]:[48,a82b:b5cf:f806]:[32,10.10.18.2]:[1067]
    66.66.66.66      0      100      0 i 66.66.66.66 VXLAN
*> [3]:[1060]:[32,60.60.60.60]
    60.60.60.60      0      100      32768 i -----
VXLAN
* i [3]:[1060]:[32,76.76.76.76]
    76.76.76.76      0      100      0 i 76.76.76.76 VXLAN
* i [3]:[1067]:[32,66.66.66.66]
    66.66.66.66      0      100      0 i 66.66.66.66 VXLAN

RD[2.3.4.6:2]
*>i [1]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[1060]
    76.76.76.76      0      100      0 i 76.76.76.76 VXLAN
*>i [2]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[48,0000:0e8d:5619]:[0]:[1060]
    76.76.76.76      0      100      0 i 76.76.76.76 VXLAN
*>i
[2]:[00:00:00:44:44:55:55:00:00:00]:[1060]:[48,0000:2222:1060]:[32,10.240.38.10]:[1060]
    76.76.76.76      0      100      0 i 76.76.76.76 VXLAN
*>i [2]:[0]:[1060]:[48,0000:2222:3333]:[32,10.240.38.1]:[1060]
    76.76.76.76      0      100      0 i 76.76.76.76 VXLAN
*>i [2]:[0]:[1060]:[48,0000:2222:3333]:[128,1601::1]:[1060]
    76.76.76.76      0      100      0 i 76.76.76.76 VXLAN
*>i [3]:[1060]:[32,76.76.76.76]
    76.76.76.76      0      100      0 i 76.76.76.76 VXLAN

RD[4.5.6.8:6]
*>i [5]:[0]:[500]:[0]:[0.0.0.0]:[0.0.0.0]:[500]
    66.66.66.66      0      100      0 64603 i 66.66.66.66
VXLAN
*>i [5]:[0]:[500]:[24]:[10.10.18.0]:[0.0.0.0]:[500]
    66.66.66.66      0      100      0 ? 66.66.66.66 VXLAN

```

```

*>i [5]:[0]:[500]:[24]:[10.10.20.0]:[0.0.0.0]:[500]
       66.66.66.66          0         100      0   64603 i  66.66.66.66
VXLAN

RD[60.60.60.60:1] VRF[evpn-gvrf-1]:
*> [1]:[00:00:00:44:44:55:55:00:00:00]:[4294967295]:[0]
       60.60.60.60          0         100      32768 i  -----
VXLAN
*> [4]:[00:00:00:44:44:55:55:00:00:00]:[32,60.60.60.60]
       60.60.60.60          0         100      32768 i  -----
VXLAN
* i [4]:[00:00:00:44:44:55:55:00:00:00]:[32,76.76.76.76]
       76.76.76.76          0         100      0   i  76.76.76.76    VXLAN

RD[66.66.66.66:1050]
*>i [5]:[0]:[500]:[0]:[0.0.0.0]:[0.0.0.0]:[500]
       66.66.66.66          0         100      0   64603 i  66.66.66.66
VXLAN
*>i [5]:[0]:[500]:[24]:[10.10.18.0]:[0.0.0.0]:[500]
       66.66.66.66          0         100      0   ?  66.66.66.66    VXLAN
*>i [5]:[0]:[500]:[24]:[10.10.20.0]:[0.0.0.0]:[500]
       66.66.66.66          0         100      0   64603 i  66.66.66.66
VXLAN

RD[66.66.66.66:1060]
*>i [5]:[0]:[500]:[0]:[0.0.0.0]:[0.0.0.0]:[500]
       66.66.66.66          0         100      0   64603 i  66.66.66.66
VXLAN
*>i [5]:[0]:[500]:[24]:[10.10.18.0]:[0.0.0.0]:[500]
       66.66.66.66          0         100      0   ?  66.66.66.66    VXLAN
*>i [5]:[0]:[500]:[24]:[10.10.20.0]:[0.0.0.0]:[500]
       66.66.66.66          0         100      0   64603 i  66.66.66.66
VXLAN

RD[76.76.76.76:1]
*>i [1]:[00:00:00:44:44:55:55:00:00:00]:[4294967295]:[0]
       76.76.76.76          0         100      0   i  76.76.76.76    VXLAN
*>i [4]:[00:00:00:44:44:55:55:00:00:00]:[32,76.76.76.76]
       76.76.76.76          0         100      0   i  76.76.76.76    VXLAN

RD[76.76.76.76:1040]
*>i [5]:[0]:[10402]:[24]:[10.240.38.0]:[0.0.0.0]:[10402]
       76.76.76.76          0         100      0   ?  76.76.76.76    VXLAN

Total number of prefixes 35
VTEP2#
VTEP2#show bgp 12vpn evpn prefix-route

RD[4.5.6.8:6]
ESI          Eth-Tag Prefix-Length     IP-Address      GW-
IPAddress    L3VNID    Nexthop        Encap        Router-Mac

```

0	500	0	0.0.0.0		0.0.0.0
500	66.66.66.66	VXLAN	3c2c:991c:dc7a		
0	500	24	10.10.18.0		0.0.0.0
500	66.66.66.66	VXLAN	3c2c:991c:dc7a		
0	500	24	10.10.20.0		0.0.0.0
500	66.66.66.66	VXLAN	3c2c:991c:dc7a		

RD[66.66.66.66:1050]

ESI		Eth-Tag	Prefix-Length	IP-Address		GW-
IPAddress			L3VNID	Nexthop	Encap	Router-Mac
0	500	0	0.0.0.0		0.0.0.0	
500	66.66.66.66	VXLAN	3c2c:991c:dc7a			
0	500	24	10.10.18.0		0.0.0.0	
500	66.66.66.66	VXLAN	3c2c:991c:dc7a			
0	500	24	10.10.20.0		0.0.0.0	
500	66.66.66.66	VXLAN	3c2c:991c:dc7a			

RD[66.66.66.66:1060]

ESI		Eth-Tag	Prefix-Length	IP-Address		GW-
IPAddress			L3VNID	Nexthop	Encap	Router-Mac
0	500	0	0.0.0.0		0.0.0.0	
500	66.66.66.66	VXLAN	3c2c:991c:dc7a			
0	500	24	10.10.18.0		0.0.0.0	
500	66.66.66.66	VXLAN	3c2c:991c:dc7a			
0	500	24	10.10.20.0		0.0.0.0	
500	66.66.66.66	VXLAN	3c2c:991c:dc7a			

RD[76.76.76.76:1040]

ESI		Eth-Tag	Prefix-Length	IP-Address		GW-
IPAddress			L3VNID	Nexthop	Encap	Router-Mac
0	10402	24	10.240.38.0		0.0.0.0	
10402	76.76.76.76	VXLAN	3c2c:99de:1e7a			

VTEP2#

VTEP1

=====

VTEP1#show nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status
Src-Addr							
Dst-Addr							
1050	---	--	AC	ce50	--- Single Homed Port ---	1050	----
---	---	---					
10502	----	L3	NW	-----	-----	-----	-----
51.51.51.51		66.66.66.66					

Total number of entries are 2

```
VTEP1#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination      Status        Up/Down      Update
=====
51.51.51.51    66.66.66.66    Installed     00:28:13    00:28:13
```

Total number of entries are 1

VTEP1#show ip route vrf all

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
ia - IS-IS inter area, E - EVPN,
v - vrf leaked
* - candidate default

IP Route Table for VRF "default"

```
C      10.10.10.0/31 is directly connected, xe40, 00:59:46
O      10.10.12.0/31 [110/2] via 10.10.10.0, xe40, 00:59:01
O      10.10.14.0/31 [110/2] via 10.10.10.0, xe40, 00:29:45
O      10.10.24.0/31 [110/2] via 10.10.10.0, xe40, 00:59:01
C      51.51.51.51/32 is directly connected, lo, 00:59:47
O      60.60.60.60/32 [110/3] via 10.10.10.0, xe40, 00:59:01
O      66.66.66.66/32 [110/3] via 10.10.10.0, xe40, 00:29:00
O      76.76.76.76/32 [110/3] via 10.10.10.0, xe40, 00:59:01
C      127.0.0.0/8 is directly connected, lo, 00:59:49
```

IP Route Table for VRF "management"

```
C      10.12.20.0/24 is directly connected, eth0, 00:59:22
C      127.0.0.0/8 is directly connected, lo.management, 00:59:49
```

IP Route Table for VRF "FAX"

Gateway of last resort is 66.66.66.66 to network 0.0.0.0

```
B*      0.0.0.0/0 [200/0] via 66.66.66.66 (recursive is directly connected,
tunvxlan2), 00:27:47
B      10.10.18.0/24 [200/0] via 66.66.66.66 (recursive is directly connected,
tunvxlan2), 00:28:55
B      10.10.20.0/24 [200/0] via 66.66.66.66 (recursive is directly connected,
tunvxlan2), 00:10:17
C      10.12.32.0/24 is directly connected, irb1050, 00:59:47
B      66.66.66.66/32 [0/0] is directly connected, tunvxlan2, 00:28:55
C      127.0.0.0/8 is directly connected, lo.FAX, 00:59:48
```

VTEP1# show bgp l2vpn evpn summary

BGP router identifier 51.51.51.51, local AS number 500

BGP table version is 9

2 BGP AS-PATH entries

0 BGP community entries

Neighbor PfxRcd	V AD	AS MACIP	MsgRcv MCAST	MsgSen ESI	TblVer PREFIX-ROUTE	InQ	OutQ	Up/Down	State/
-----------------	------	----------	--------------	------------	---------------------	-----	------	---------	--------

66.66.66.66	4	500	138	9	132	8	0	0	00:29:07
12	0	2	1						

Total number of neighbors 1

Total number of Established sessions 1

VTEP1# show bgp 12vpn evpn

BGP table version is 9, local router ID is 51.51.51.51

Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
l - labeled, S Stale

Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]

- 1 - Ethernet Auto-discovery Route
- 2 - MAC/IP Route
- 3 - Inclusive Multicast Route
- 4 - Ethernet Segment Route
- 5 - Prefix Route

Network Encap	Next Hop	Metric	LocPrf	Weight	Path	Peer
------------------	----------	--------	--------	--------	------	------

RD[2.2.4.4:4]

*>i [2]:[0]:[1067]:[48,3c2c:991c:dc7a]:[32,10.10.18.1]:[1067]	66.66.66.66	0	100	0	i	66.66.66.66	VXLAN
*>i [2]:[0]:[1067]:[48,a82b:b5cf:f806]:[32,10.10.18.2]:[1067]	66.66.66.66	0	100	0	i	66.66.66.66	VXLAN
*>i [3]:[1067]:[32,66.66.66.66]	66.66.66.66	0	100	0	i	66.66.66.66	VXLAN

RD[2.3.4.5:1] VRF[RED]:

*> [2]:[0]:[1050]:[48,0000:0e8d:561a]:[0]:[1050]	51.51.51.51	0	100	32768	i	-----	VXLAN
*> [2]:[0]:[1050]:[48,0000:0e8d:561a]:[32,10.12.32.11]:[1050]	51.51.51.51	0	100	32768	i	-----	VXLAN
*> [2]:[0]:[1050]:[48,0000:3333:1050]:[32,10.12.32.10]:[1050]	51.51.51.51	0	100	32768	i	-----	VXLAN
*> [2]:[0]:[1050]:[48,3c2c:99d6:167a]:[32,10.12.32.1]:[1050]	51.51.51.51	0	100	32768	i	-----	VXLAN
*> [2]:[0]:[1050]:[48,3c2c:99d6:167a]:[128,2401::1]:[1050]	51.51.51.51	0	100	32768	i	-----	VXLAN
* i [2]:[0]:[1067]:[48,3c2c:991c:dc7a]:[32,10.10.18.1]:[1067]	66.66.66.66	0	100	0	i	66.66.66.66	VXLAN
* i [2]:[0]:[1067]:[48,a82b:b5cf:f806]:[32,10.10.18.2]:[1067]	66.66.66.66	0	100	0	i	66.66.66.66	VXLAN
*> [3]:[1050]:[32,51.51.51.51]							

VXLAN	51.51.51.51	0	100	32768	i	-----
* i [3]:[1067]:[32,66.66.66.66]	66.66.66.66	0	100	0	i	66.66.66.66
RD[4.5.6.8:6]						
*>i [5]:[0]:[500]:[0]:[0.0.0.0]:[0.0.0.0]:[500]	66.66.66.66	0	100	0	64603	i 66.66.66.66
VXLAN						
*>i [5]:[0]:[500]:[24]:[10.10.18.0]:[0.0.0.0]:[500]	66.66.66.66	0	100	0	?	66.66.66.66
*>i [5]:[0]:[500]:[24]:[10.10.20.0]:[0.0.0.0]:[500]	66.66.66.66	0	100	0	64603	i 66.66.66.66
VXLAN						
RD[66.66.66.66:1050]						
*>i [5]:[0]:[500]:[0]:[0.0.0.0]:[0.0.0.0]:[500]	66.66.66.66	0	100	0	64603	i 66.66.66.66
VXLAN						
*>i [5]:[0]:[500]:[24]:[10.10.18.0]:[0.0.0.0]:[500]	66.66.66.66	0	100	0	?	66.66.66.66
*>i [5]:[0]:[500]:[24]:[10.10.20.0]:[0.0.0.0]:[500]	66.66.66.66	0	100	0	64603	i 66.66.66.66
VXLAN						
RD[66.66.66.66:1060]						
*>i [5]:[0]:[500]:[0]:[0.0.0.0]:[0.0.0.0]:[500]	66.66.66.66	0	100	0	64603	i 66.66.66.66
VXLAN						
*>i [5]:[0]:[500]:[24]:[10.10.18.0]:[0.0.0.0]:[500]	66.66.66.66	0	100	0	?	66.66.66.66
*>i [5]:[0]:[500]:[24]:[10.10.20.0]:[0.0.0.0]:[500]	66.66.66.66	0	100	0	64603	i 66.66.66.66
VXLAN						

Total number of prefixes 21

VTEP1#

VTEP1#show ip route vrf FAX
 Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
 O - OSPF, IA - OSPF inter area
 N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
 E1 - OSPF external type 1, E2 - OSPF external type 2
 i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
 ia - IS-IS inter area, E - EVPN,
 v - vrf leaked
 * - candidate default

IP Route Table for VRF "FAX"

Gateway of last resort is 66.66.66.66 to network 0.0.0.0

```
B*          0.0.0.0/0 [200/0] via 66.66.66.66 (recursive is directly connected,
tunvxlan2), 00:29:26
B          10.10.18.0/24 [200/0] via 66.66.66.66 (recursive is directly connected,
tunvxlan2), 00:30:34
B          10.10.20.0/24 [200/0] via 66.66.66.66 (recursive is directly connected,
tunvxlan2), 00:11:56
C          10.12.32.0/24 is directly connected, irb1050, 01:01:26
B          66.66.66.66/32 [0/0] is directly connected, tunvxlan2, 00:30:34
C          127.0.0.0/8 is directly connected, lo.FAX, 01:01:27
```

VTEP1#show bgp 12vpn evpn prefix-route

RD[4.5.6.8:6]

ESI IPAddress	Eth-Tag	Prefix-Length	IP-Address L3VNID	Nexthop	Encap	GW- Router-Mac
0 500 0		0.0.0.0			0.0.0.0	
500 66.66.66.66	VXLAN		3c2c:991c:dc7a			
0 500 24		10.10.18.0			0.0.0.0	
500 66.66.66.66	VXLAN		3c2c:991c:dc7a			
0 500 24		10.10.20.0			0.0.0.0	
500 66.66.66.66	VXLAN		3c2c:991c:dc7a			

RD[66.66.66.66:1050]

ESI IPAddress	Eth-Tag	Prefix-Length	IP-Address L3VNID	Nexthop	Encap	GW- Router-Mac
0 500 0		0.0.0.0			0.0.0.0	
500 66.66.66.66	VXLAN		3c2c:991c:dc7a			
0 500 24		10.10.18.0			0.0.0.0	
500 66.66.66.66	VXLAN		3c2c:991c:dc7a			
0 500 24		10.10.20.0			0.0.0.0	
500 66.66.66.66	VXLAN		3c2c:991c:dc7a			

RD[66.66.66.66:1060]

ESI IPAddress	Eth-Tag	Prefix-Length	IP-Address L3VNID	Nexthop	Encap	GW- Router-Mac
0 500 0		0.0.0.0			0.0.0.0	
500 66.66.66.66	VXLAN		3c2c:991c:dc7a			
0 500 24		10.10.18.0			0.0.0.0	
500 66.66.66.66	VXLAN		3c2c:991c:dc7a			
0 500 24		10.10.20.0			0.0.0.0	
500 66.66.66.66	VXLAN		3c2c:991c:dc7a			

Ping to 10.10.20.1 network which is advertised by Firewall from VTEP1 FAX vrf

```
VTEP1#      ping 10.10.20.1 vrf FAX
Press CTRL+C to exit
PING 10.10.20.1 (10.10.20.1) 56(84) bytes of data.
64 bytes from 10.10.20.1: icmp_seq=1 ttl=63 time=0.446 ms
64 bytes from 10.10.20.1: icmp_seq=2 ttl=63 time=0.413 ms
64 bytes from 10.10.20.1: icmp_seq=3 ttl=63 time=0.373 ms
```

```
--- 10.10.20.1 ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 73ms
```

```
rtt min/avg/max/mdev = 0.373/0.410/0.446/0.037 ms
VTEP1#
```

CHAPTER 5 DHCP Relay Over IRB Interface

This chapter contains configurations for DHCP relay over IRB interface.

Overview

Dynamic Host Configuration Protocol (DHCP) is a protocol that allows a DHCP server to dynamically allocate IP addresses to DHCP clients. The DHCP relay agent forwards DHCP messages between DHCP clients and DHCP servers when they are on different networks.

For DHCP relay to function, uplink interface (server facing) and downlink interface (client facing) are to be configured along with DHCP server address. These configurations are done in the interface mode.

In the IRB deployment, IRB interface acts as gateway and hence it might need to provide the service of DHCP for the hosts connected to IRB network per L2 VPN. Since the DHCP server will not be present in the VTEP, it can forward the DHCP requests to the DHCP server acting as relay agent.

Topology

The procedures in this section use the topology in [Figure 5-3](#).



Figure 5-3: DHCP Relay over IRB

ROUTER-1

#configure terminal	Enter Configure mode.
OcNOS(config)#interface lo	Enter Interface mode for loopback.
OcNOS(config-if)#ip address 1.1.1.1/32 secondary	Assign secondary IP address.
OcNOS(config-if)#exit	Exit Interface mode and return to Configure mode.
OcNOS(config)#nvo vxlan enable	Enable VXLAN
OcNOS(config)#nvo vxlan irb	Enable VXLAN IRB
OcNOS(config)#ip vrf vrf1	Create routing/forwarding instance with VRF1 name and enter into VRF mode
OcNOS(config-vrf)#rd 200:1	Assign RD value
OcNOS(config-vrf)#route-target both 200:1	Assign route target value
OcNOS(config-vrf)#ip dhcp relay address 40.40.40.1	The relay address configured should be server interface address connected to DUT machine
OcNOS(config-vrf)#ip dhcp relay uplink evpn	Configure the uplink interface as L3 VNI interface for specific VRF
OcNOS(config-vrf)#l3vni 45001	Configure L3VNI as 45001 for VRF1
OcNOS(config-vrf)#exit	Exit IP VRF mode

OcNOS (config)#mac vrf vrfred	Create MAC VRF instance with vrfred name and enter into VRF mode
OcNOS (config-vrf)#rd 1.1.1.1:1	Assign RD value
OcNOS (config-vrf)#route-target both 1.1.1.1:1	Assign route target value
OcNOS (config-vrf)#exit	Exit MAC VRF mode
OcNOS (config)#interface irb 1	Configure IRB interface
OcNOS (config-irb-if)#ip vrf forwarding vrf1	Configure IP VRF forwarding
OcNOS (config-irb-if)#ip address 11.1.1.1/24	Assign IP address on IRB interface.
OcNOS (config-irb-if)#ip dhcp relay	Relay should be configured on the interface connecting to the relay
OcNOS (config-irb-if)#exit	Exit IRB interface mode
OcNOS (config)#interface irb 2	Configure irb interface
OcNOS (config-irb-if)#ip vrf forwarding vrf1	Configure IP VRF forwarding
OcNOS (config-irb-if)#ip address 70.70.70.1/24	Assign IP address on IRB interface.
OcNOS (config-irb-if)#exit	Exit IRB interface mode
OcNOS (config)#interface ce49	Enter Interface mode for ce49.
OcNOS (config-if)#ip address 10.1.1.2/24	Assign IP address on ce49 interface.
OcNOS (config-if)#exit	Exit Interface mode and return to Configure mode.
OcNOS (config)#interface xe5	Enter Interface mode for xe5.
OcNOS (config-if)#switchport	Configure interface as L2 interface
OcNOS (config-if)#exit	Exit Interface mode and return to Configure mode.
OcNOS (config)#router ospf	Enter the Router OSPF mode
OcNOS (config-router)#network 1.1.1.1/32 area 0.0.0.0	Advertise loopback address in OSPF
OcNOS (config-router)#network 10.1.1.0/24 area 0.0.0.0	Advertise network address in OSPF
OcNOS (config-router)#exit	Exit from Router OSPF mode and enter into config mode
OcNOS (config)#router bgp 1	Enter into BGP router mode
OcNOS (config-router)#neighbor 2.2.2.2 remote-as 1	Specify a VTEP2 loopback IP address and remote-as defined
OcNOS (config-router)#neighbor 2.2.2.2 update-source 1.1.1.1	Configure update as loopback for VTEP2
OcNOS (config-router)#address-family l2vpn evpn	Enter into L2VPN EVPN address family mode
OcNOS (config-router-af)#neighbor 2.2.2.2 activate	Activate neighbor in L2VPN mode
OcNOS (config-router-af)#exit-address-family	Exit from Address family mode
OcNOS (config-router)#address-family ipv4 vrf vrf1	Enter into address-family mode for VRF1
OcNOS (config-router-af)#redistribute connected	Configure Redistribute connected
OcNOS (config-router-af)#exit-address-family	Exit from Address family mode
OcNOS (config-router)#exit	Exit from router BGP mode and enter into config mode

OcNOS (config)#nvo vxlan vtep-ip-global 1.1.1.1	Configure Source VTEP-IP-global configuration. Use loopback IP address
OcNOS (config)#nvo vxlan id 10 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
OcNOS (config-nvo)#vxlan host-reachability-protocol evpn-bgp vrfred	Assign VRF for EVPN-BGP to carry EVPN route
OcNOS (config-nvo)#evpn irb1	Configure IRB1 under VXLAN ID 10
OcNOS (config-nvo)#exit	Exit from VXLAN tenant mode and enter into configuration mode.
OcNOS (config)#nvo vxlan id 30 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
OcNOS (config-nvo)#vxlan host-reachability-protocol evpn-bgp vrfred	Assign VRF for EVPN-BGP to carry EVPN route
OcNOS (config-nvo)#evpn irb2	Configure IRB2 under VXLAN ID 30
OcNOS (config-nvo)#exit	Exit from VXLAN tenant mode and enter into configuration mode.
OcNOS (config)#nvo vxlan access-if port-vlan xe5 2	Enable port-VLAN mapping i.e. access port to outer-VLAN (SVLAN) - Multihomed access port
OcNOS (config-nvo-acc-if)#map vnid 10	Map VXLAN Identified to access-port for VXLAN
OcNOS (config-nvo-acc-if)#exit	Exit from VXLAN access-interface mode and enter into configuration mode
OcNOS (config)#commit	Commit the candidate configuration to the running configuration
OcNOS (config)#exit	Exit from configuration mode

ROUTER-2

OcNOS#configure terminal	Enter Configure mode.
OcNOS (config)#interface ce0	Enter Interface mode for ce0.
OcNOS (config-if)#ip address 10.1.1.1/24	Assign IP address on ce0 interface.
OcNOS (config-if)#exit	Exit Interface mode and return to Configure mode.
OcNOS (config)#interface xe13	Enter Interface mode for xe13.
OcNOS (config-if)#ip address 30.1.1.1/24	Assign IP address on xe13 interface.
OcNOS (config-if)#exit	Exit Interface mode and return to Configure mode.
OcNOS (config)#router ospf	Enter the Router OSPF mode
OcNOS (config-router)#network 10.1.1.0/24 area 0.0.0.0	Advertise network address in OSPF
OcNOS (config-router)#network 30.1.1.10/24 area 0.0.0.0	Advertise network address in OSPF
OcNOS (config-router)#exit	Exit from Router OSPF mode and enter into config mode
OcNOS (config)#commit	commit the candidate configuration to the running configuration
OcNOS (config)#exit	Exit from configuration mode

ROUTER-3

OcNOS#configure terminal	Enter Configure mode.
OcNOS(config)#interface lo	Enter Interface mode for loopback.
OcNOS(config-if)#ip address 2.2.2.2/32 secondary	Assign secondary IP address.
OcNOS(config-if)#exit	Exit Interface mode and return to Configure mode.
OcNOS(config)#nvo vxlan enable	Enable VXLAN
OcNOS(config)#nvo vxlan irb	Enable VXLAN IRB
OcNOS(config)#ip vrf vrf1	Create routing/forwarding instance with VRF1 name and enter into VRF mode
OcNOS(config-vrf)#rd 300:1	Assign RD value
OcNOS(config-vrf)#route-target both 200:1	Assign route target value
OcNOS(config-vrf)#ip dhcp relay uplink evpn	Configure the uplink interface as L3 VNI interface for specific VRF
OcNOS(config-vrf)#l3vni 45001	Configure L3VNI as 45001 for VRF1
OcNOS(config-vrf)#exit	Exit IP VRF mode
OcNOS(config)#mac vrf vrfred	Create MAC VRF instance with vrfred name and enter into VRF mode
OcNOS(config-vrf)#rd 2.2.2.1:1	Assign RD value
OcNOS(config-vrf)#route-target both 1.1.1.1:1	Assign route target value
OcNOS(config-vrf)#exit	Exit MAC VRF mode
OcNOS(config)#interface irb 2	Configure IRB interface
OcNOS(config-irb-if)#ip vrf forwarding vrf1	Configure IP VRF forwarding
OcNOS(config-irb-if)#ip address 40.40.40.2/24	Assign IP address on IRB interface.
OcNOS(config-irb-if)#exit	Exit IRB interface mode
OcNOS(config)#interface xe13	Enter Interface mode for xe13.
OcNOS(config-if)#ip address 30.1.1.2/24	Assign IP address on xe13 interface.
OcNOS(config-if)#exit	Exit Interface mode and return to Configure mode.
OcNOS(config)#interface xe19	Enter Interface mode for xe19.
OcNOS(config-if)#switchport	Configure interface as L2 interface
OcNOS(config-if)#exit	Exit Interface mode and return to Configure mode.
OcNOS(config)#router ospf	Enter the Router OSPF mode
OcNOS(config-router)#network 2.2.2.2/32 area 0.0.0.0	Advertise loopback address in OSPF
OcNOS(config-router)#network 30.1.1.0/24 area 0.0.0.0	Advertise network address in OSPF
OcNOS(config-router)#network 40.1.1.0/24 area 0.0.0.0	Advertise network address in OSPF
OcNOS(config-router)#exit	Exit from Router OSPF mode and enter into config mode
OcNOS(config)#router bgp 1	Enter into BGP router mode
OcNOS(config-router)#neighbor 1.1.1.1 remote-as 1	Specify a VTEP1 loopback IP address and remote-as defined

OcNOS (config-router) #neighbor 1.1.1.1 update-source 2.2.2.2	Configure update as loopback for VTEP1
OcNOS (config-router) #address-family l2vpn evpn	Enter into L2VPN EVPN address family mode
OcNOS (config-router-af) #neighbor 1.1.1.1 activate	Activate neighbor in L2VPN mode
OcNOS (config-router-af) #exit-address-family	Exit from Address family mode
OcNOS (config-router) #address-family ipv4 vrf vrf1	Enter into address-family mode for VRF1
OcNOS (config-router-af) #redistribute connected	Configure Redistribute connected
OcNOS (config-router-af) #exit-address-family	Exit from Address family mode
OcNOS (config-router) #exit	Exit from router BGP mode and enter into config mode
OcNOS (config) #nvo vxlan vtep-ip-global 2.2.2.2	Configure Source VTEP-IP-global configuration. Use loopback IP address
OcNOS (config) #nvo vxlan id 10 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
OcNOS (config-nvo) #vxlan host-reachability-protocol evpn-bgp vrfred	Assign VRF for EVPN-BGP to carry EVPN route
OcNOS (config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
OcNOS (config) #nvo vxlan id 20 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
OcNOS (config-nvo) #vxlan host-reachability-protocol evpn-bgp vrfred	Assign VRF for EVPN-BGP to carry EVPN route
OcNOS (config-nvo) #evpn irb2	Configure IRB2 under VXLAN ID 20
OcNOS (config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
OcNOS (config) #nvo vxlan access-if port xe19	Enable port mapping i.e. access port
OcNOS (config-nvo-acc-if) #map vnid 20	Map VXLAN Identified to access-port for VXLAN
OcNOS (config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
OcNOS (config) #commit	Commit the candidate configuration to the running configuration
OcNOS (config) #exit	Exit from configuration mode

Validation

ROUTER-1

```
VTEP1#
!
nvo vxlan enable
!
nvo vxlan irb
!
nvo vxlan vtep-ip-global 1.1.1.1
!
nvo vxlan id 10 ingress-replication inner-vid-disabled
    vxlan host-reachability-protocol evpn-bgp vrfred
```

```

evpn irb1
!
nvo vxlan id 30 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp vrfred
  evpn irb2
!
nvo vxlan access-if port xe2
  map vnid 10
!
nvo vxlan access-if port-vlan xe5 2
  map vnid 10
!
VTEP1#show ip dhcp relay
DHCP relay service is Enabled.
VRF Name: vrf1
  Option 82: Disabled
  DHCP Servers configured: 40.40.40.1

  Interface          Uplink/Downlink
  -----
  irb1              Downlink
  evpn              uplink

Incoming DHCPv4 packets which already contain relay agent option are FORWARDED
unchanged.

VTEP1#show nvo vxlan mac-table
=====
===== VXLAN MAC Entries =====
=====

VNID      Interface VlanId Vlan-RangeId Inner-VlanId Mac-Addr      VTEP-Ip/ESI      Type      Status
AccessPortDesc

-----
10        xe5       2        ----      ----      0000.2837.ddf5 1.1.1.1      Dynamic Local   -----
10        irb1      1        ----      b86a.97f9.85be 1.1.1.1      Static Local   -----   -----
30        irb2      2        ----      b86a.97f9.85be 1.1.1.1      Static Local   -----   -----


Total number of entries are : 3

VTEP1#show nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====
VNID      Ip-Addr      Mac-Addr      Type      Age-Out      Retries-Left
-----      -----      -----      -----      -----      -----
30        70.70.70.1    b86a.97f9.85be  Static Local   ----
10        11.1.1.1      b86a.97f9.85be  Static Local   ----
10        11.1.1.30     0000.2837.ddf5  Dynamic Local   ----

Total number of entries are 3

VTEP1#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source      Destination      Status      Up/Down      Update
-----      -----      -----      -----      -----

```

```
=====
1.1.1.1          2.2.2.2          Installed        01:51:11        01:51:11
```

Total number of entries are 1

ROUTER-2

```
VTEP2#show running-config nvo vxlan
!
nvo vxlan enable
!
nvo vxlan irb
!
nvo vxlan vtep-ip-global 2.2.2.2
!
nvo vxlan id 10 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp vrfred
!
nvo vxlan id 20 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp vrfred
  evpn irb2
!
nvo vxlan access-if port xe19
  map vnid 20
!
!
```

```
VTEP2#show nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====
```

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
20	40.40.40.2	b86a.9761.ea3d	Static	Local	----
20	40.40.40.1	0002.a54f.1577	Dynamic	Local	----
20	40.40.40.101	0000.2837.ddf3	Dynamic	Local	----
10	11.1.1.1	b86a.97f9.85be	Static	Remote	----
10	11.1.1.30	0000.2837.ddf6	Dynamic	Remote	----

Total number of entries are 5

```
VTEP2#show running-config dhcp
interface eth0
  ip address dhcp
!
!
ip vrf vrf1
  ip dhcp relay uplink evpn
```

CHAPTER 6 VXLAN-EVPN with IRB QoS

Overview

An EVPN-based Integrated Routing and Bridging solution used for forwarding of intra-subnets and inter-subnets traffic. Here QoS is applied on IRB solution for L3 packets.

VXLAN quality of service (QoS) provides differentiated service in VXLAN applications. A device implements mapping between QoS priorities in original packets, internal priorities (local precedence assigned by the device to differentiate service classes of packets), and priorities of encapsulated packets. In this way, the switch provides the differentiated QoS service based on original packets.

Topology

The procedures in this section use the topology in [Figure 6-4](#)




Figure 6-4: VxLAN_EVPN_IRB

Note: In the above topology TS1, TS2 are the tenant systems. The blue and red color denotes different subnets in the Tenant systems.

Base Configuration - L2 VXLAN

VTEP1

(Multi-homed group1) - Part of both Multi-homed with po1(MH2).

Generic configuration:

#configure terminal	Enter Configure mode.
(config) #evpn vxlan multihoming enable	Enable Multihoming, save configs and reboot the board for multihoming to be effective
(config) #qos enable	Enabling qos

Interface and loopback configuration:

(config) #interface po1	Enter Interface mode for po1 (MH2)
(config-if) #switchport	Make it L2 interface
(config-if) # evpn multi-homed system-mac 0000.0000.2222	Configure system mac as ESI value for Lag (po1) interface. VTEP1 and VTEP2 should have same ESI value
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe3	Enter Interface mode for xe3
(config-if) #channel-group 1 mode active	Make it member port of po1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 1.1.1.1/32 secondary	Configure loopback ip address as 1.1.1.1 for VTEP1
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface ce52	Enter Interface mode for network side port
(config-if) #ip address 100.11.11.1/24	Configure ip address as 100.11.11.1 on network side of Spine-P3
(config-if) #exit	Exit Interface mode and return to Configure mode.

OSPF configuration:

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo ip address)
(config-router) #network 1.1.1.1/32 area 0.0.0.0	Add 1.1.1.1 (lo ip address) network into area 0
(config-router) #network 100.11.11.0/24 area 0.0.0.0	Add 100.11.11.0(Spine-P3) network into area 0
(config-router) #bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.

BGP configuration:

(config) #router bgp 5000	Enter into Router BGP mode
(config-router) #bgp router-id 1.1.1.1	Configure router-id as 1.1.1.1 (lo ip address)
(config-router) #neighbor 2.2.2.2 remote-as 5000	Specify a VTEP2 loopback ip address and remote-as defined
(config-router) #neighbor 2.2.2.2 update-source lo	Configure update as loopback for VTEP2

(config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2
(config-router) #neighbor 4.4.4.4 remote-as 5000	Specify a VTEP4 loopback ip address and remote-as defined
(config-router) #neighbor 4.4.4.4 update-source lo	Configure update as loopback for VTEP4
(config-router) #neighbor 4.4.4.4 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP4
(config-router) #neighbor 5.5.5.5 remote-as 5000	Specify a VTEP5 loopback ip address and remote-as defined
(config-router) #neighbor 5.5.5.5 update-source lo	Configure update as loopback for VTEP5
(config-router) #neighbor 5.5.5.5 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP5
(config-router) #address-family l2vpn evpn	Enter into l2vpn EVPN address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2(VTEP2) into l2vpn evpn address family mode
(config-router-af) #neighbor 4.4.4.4 activate	Activate 3.3.3.3(VTEP4) into l2vpn evpn address family mode
(config-router-af) #neighbor 5.5.5.5 activate	Activate 5.5.5.5(VTEP5) into l2vpn evpn address family mode
(config-router-af) #exit-address-family	Exit from l2vpn address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode

L2 MAC VRF Configuration:

(config) #mac vrf L2VRF1	Create mac routing/forwarding instance with L2VRF1 name and enter into vrf mode
(config-vrf) #rd 1.1.1.1:11	Assign RD value
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as RED
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) #exit	Exit from vrf mode
(config) #mac vrf L2VRF2	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #rd 1.1.1.1:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as BLUE
(config-vrf) #exit	Exit from vrf mode

L2 VXLAN configuration:

(config) #nvo vxlan enable	Enable VXLAN
(config) #evpn esi hold-time 90	Configure ESI hold time to allow tunnel to come up at the time of vxlan initialization before making the ESI up. It should be same on both VTEP1 and VTEP2
(config) #nvo vxlan vtep-ip-global 1.1.1.1	Configure Source vtep-ip-global configuration - Use loopback ip address

(config) #nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # vni-name VNI-101	Configure VNI name as VNI-101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # vni-name VNI-201	Configure VNI name as VNI-201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan access-if port-vlan po1 10	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vnid 101	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1010 ip 11.11.11.51	Configure static mac-ip
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan po1 20	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vnid 201	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1020 ip 21.21.21.51	Configure static mac-ip
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #exit	Exit from configuration mode

VTEP2

(Multi-homed group1) - Part of both Multi-homed with po1(MH1).

Hardware profile and generic configuration:

#configure terminal	Enter Configure mode.
(config) #evpn vxlan multihoming enable	Enable Multihoming, save configs and reboot the board for multihoming to be effective
(config) #qos enable	Enabling qos

Interface and loopback configuration:

(config) #interface po1	Enter Interface mode for po1 (MH2)
(config-if) #switchport	Make it L2 interface
(config-if) # evpn multi-homed system-mac 0000.0000.2222	Configure system mac as ESI value for Lag (po1) interface. VTEP1 and VTEP2 should have same ESI value

(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface xe2	Enter Interface mode for xe2
(config-if)#channel-group 1 mode active	Make it member port of po1
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface lo	Enter Interface mode for lo
(config-if)#ip address 2.2.2.2/32 secondary	Configure loopback ip address as 2.2.2.2 for VTEP2
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) interface xe29	Enter into network side interface
(config-if)#ip address 100.12.12.1/24	Configure ip address as 100.12.12.1 on network side of Spine-P3
(config-if)#exit	Exit Interface mode and return to Configure mode.

OSPF configuration:

(config)#router ospf 100	Enter into router OSPF mode
(config-router)#ospf router-id 2.2.2.2	Configure router-id as 2.2.2.2 (lo ip address)
(config-router)#network 2.2.2.2/32 area 0.0.0.0	Add 2.2.2.2 (lo ip address) network into area 0
(config-router)#network 100.12.12.0/24 area 0.0.0.0	Add 100.12.12.0(Spine-P3) network into area 0
(config-router)#bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if)#exit	Exit Interface mode and return to Configure mode.

BGP configuration:

(config)#router bgp 5000	Enter into Router BGP mode
(config-router)#bgp router-id 2.2.2.2	Configure router-id as 2.2.2.2 (lo ip address)
(config-router)#neighbor 1.1.1.1 remote-as 5000	Specify a VTEP1 loopback ip address and remote-as defined
(config-router)#neighbor 1.1.1.1 update-source lo	Configure update as loopback for VTEP1
(config-router)#neighbor 1.1.1.1 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP1
(config-router)#neighbor 4.4.4.4 remote-as 5000	Specify a VTEP4 loopback ip address and remote-as defined
(config-router)#neighbor 4.4.4.4 update-source lo	Configure update as loopback for VTEP4
(config-router)#neighbor 4.4.4.4 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP4
(config-router)#neighbor 5.5.5.5 remote-as 5000	Specify a VTEP5 loopback ip address and remote-as defined
(config-router)#neighbor 5.5.5.5 update-source lo	Configure update as loopback for VTEP5
(config-router)#neighbor 5.5.5.5 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP5
(config-router)#address-family l2vpn evpn	Enter into l2vpn EVPN address family mode

(config-router-af) #neighbor 1.1.1.1 activate	Activate 1.1.1.1(VTEP1) into l2vpn evpn address family mode
(config-router-af) #neighbor 4.4.4.4 activate	Activate 4.4.4.4(VTEP4) into l2vpn evpn address family mode
(config-router-af) #neighbor 5.5.5.5 activate	Activate 5.5.5.5(VTEP5) into l2vpn evpn address family mode
(config-router-af) #exit-address-family	Exit from l2vpn address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode

VRF Configuration:

(config) #mac vrf L2VRF1	Create mac routing/forwarding instance with L2VRF1 name and enter into vrf mode
(config-vrf) #rd 2.2.2.2:11	Assign RD value
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as RED
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) #exit	Exit from vrf mode
(config) #mac vrf L2VRF2	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #rd 2.2.2.2:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as BLUE
(config-vrf) #exit	Exit from vrf mode

VXLAN configuration:

(config) #nvo vxlan enable	Enable VXLAN
(config) #evpn esi hold-time 90	Configure ESI hold time to allow tunnel to come up at the time of vxlan initialization before making the ESI up. It should be same on both VTEP1 and VTEP2
(config) #nvo vxlan vtep-ip-global 2.2.2.2	Configure Source vtep-ip-global configuration - Use loopback ip address
(config) #nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # vni-name VNI-101	Configure VNI name as VNI-101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # vni-name VNI-201	Configure VNI name as VNI-201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan access-if port-vlan pol 10	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port

(config-nvo-acc-if) #map vniid 101	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1010 ip 11.11.11.51	Configure static mac-ip
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #nvo vxlan access-if port-vlan po1 20	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) - Multihomed access port
(config-nvo-acc-if) #map vniid 201	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.2222.1020 ip 21.21.21.51	Configure static mac-ip
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #exit	Exit from configuration mode

VTEP4

Single Home -SH5.

Hardware profile and generic configuration:

#configure terminal	Enter Configure mode.
(config) #evpn vxlan multihoming enable	Enable Multihoming, save configs and reboot the board for multihoming to be effective
(config) #qos enable	Enabling qos

Interface and loopback configuration:

(config) #interface xe3	Enter Interface mode for xe3
(config-if) #switchport	Make it L2 interface
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 4.4.4.4/32 secondary	Configure loopback ip address as 4.4.4.4 for VTEP4
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) interface ce49	Enter interface towards network side
(config-if) #ip address 100.14.14.1/24	Configure ip address as 100.14.14.1 on network side of Spine-P3
(config-if) #exit	Exit Interface mode and return to Configure mode.

OSPF configuration:

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 4.4.4.4	Configure router-id as 4.4.4.4 (lo ip address)
(config-router) #network 4.4.4.4/32 area 0.0.0.0	Add 4.4.4.4 (lo ip address) network into area 0

(config-router) #network 100.14.14.0/24 area 0.0.0.0	Add 100.14.14.0(Spine-P3) network into area 0
(config-router) #bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.

BGP configuration:

(config) #router bgp 5000	Enter into Router BGP mode
(config-router) #bgp router-id 4.4.4.4	Configure router-id as 4.4.4.4 (lo ip address)
(config-router) #neighbor 1.1.1.1 remote-as 5000	Specify a VTEP1 loopback ip address and remote-as defined
(config-router) #neighbor 1.1.1.1 update-source lo	Configure update as loopback for VTEP1
(config-router) #neighbor 1.1.1.1 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP1
(config-router) #neighbor 2.2.2.2 remote-as 5000	Specify a VTEP2 loopback ip address and remote-as defined
(config-router) #neighbor 2.2.2.2 update-source lo	Configure update as loopback for VTEP2
(config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2
(config-router) #neighbor 5.5.5.5 remote-as 5000	Specify a VTEP5 loopback ip address and remote-as defined
(config-router) #neighbor 5.5.5.5 update-source lo	Configure update as loopback for VTEP5
(config-router) #neighbor 5.5.5.5 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP5
(config-router) #address-family l2vpn evpn	Enter into l2vpn EVPN address family mode
(config-router-af) #neighbor 1.1.1.1 activate	Activate 1.1.1.1(VTEP1) into l2vpn evpn address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2(VTEP2) into l2vpn evpn address family mode
(config-router-af) #neighbor 5.5.5.5 activate	Activate 5.5.5.5(VTEP5) into l2vpn evpn address family mode
(config-router-af) #exit-address-family	Exit from l2vpn address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode

VRF Configuration:

(config) #mac vrf L2VRF1	Create mac routing/forwarding instance with L2VRF1 name and enter into vrf mode
(config-vrf) #rd 4.4.4.4:11	Assign RD value
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as RED
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) #exit	Exit from vrf mode
(config) #mac vrf L2VRF2	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #rd 4.4.4.4:21	Assign RD value

(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as BLUE
(config-vrf) #exit	Exit from vrf mode

VXLAN configuration:

(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan vtep-ip-global 4.4.4.4	Configure Source vtep-ip-global configuration. Use loopback ip address
(config) #nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # vni-name VNI-101	Configure VNI name as VNI-101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # vni-name VNI-201	Configure VNI name as VNI-201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) # nvo vxlan access-if port-vlan xe3 20	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN)
(config-nvo-acc-if) #map vnid 201	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) # mac 0000.5555.1020 ip 21.21.21.101	Configure static mac-ip
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #exit	Exit from configuration mode

VTEP5

Single Home -SH3

Hardware profile and generic configuration:

#configure terminal	Enter Configure mode.
(config) #evpn vxlan multihoming enable	Enable Multihoming, save configs and reboot the board for multihoming to be effective
(config) #qos enable	Enabling qos

Interface and loopback configuration:

(config) #interface xe1	Enter Interface mode for xe1 (SH5)
(config-if)#switchport	Make it L2 interface
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface lo	Enter Interface mode for lo
(config-if) #ip address 5.5.5.5/32 secondary	Configure loopback ip address as 5.5.5.5 for VTEP5
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) interface ce53	Enter interface mode
(config-if) #ip address 100.15.15.1/24	Configure ip address as 100.15.15.1 on network side of Spine-P3
(config-if) #exit	Exit Interface mode and return to Configure mode.

OSPF configuration:

(config) #router ospf 100	Enter into router OSPF mode
(config-router) #ospf router-id 5.5.5.5	Configure router-id as 5.5.5.5 (lo ip address)
(config-router) #network 5.5.5.5/32 area 0.0.0.0	Add 5.5.5.5 (lo ip address) network into area 0
(config-router) #network 100.15.15.0/24 area 0.0.0.0	Add 100.15.15.0(Spine-P3) network into area 0
(config-router) #bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence
(config-if) #exit	Exit Interface mode and return to Configure mode.

BGP configuration:

(config) #router bgp 5000	Enter into Router BGP mode
(config-router) #bgp router-id 5.5.5.5	Configure router-id as 5.5.5.5(lo ip address)
(config-router) #neighbor 1.1.1.1 remote-as 5000	Specify a VTEP1 loopback ip address and remote-as defined
(config-router) #neighbor 1.1.1.1 update-source lo	Configure update as loopback for VTEP1
(config-router) #neighbor 1.1.1.1 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP1
(config-router) #neighbor 2.2.2.2 remote-as 5000	Specify a VTEP2 loopback ip address and remote-as defined
(config-router) #neighbor 2.2.2.2 update-source lo	Configure update as loopback for VTEP2
(config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2
(config-router) #neighbor 4.4.4.4 remote-as 5000	Specify a VTEP4 loopback ip address and remote-as defined
(config-router) #neighbor 4.4.4.4 update-source lo	Configure update as loopback for VTEP4
(config-router) #neighbor 4.4.4.4 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP4

(config-router) #address-family l2vpn evpn	Enter into l2vpn EVPN address family mode
(config-router-af) #neighbor 1.1.1.1 activate	Activate 1.1.1.1(VTEP1) into l2vpn evpn address family mode
(config-router-af) #neighbor 2.2.2.2 activate	Activate 2.2.2.2(VTEP2) into l2vpn evpn address family mode
(config-router-af) #neighbor 4.4.4.4 activate	Activate 4.4.4.4(VTEP4) into l2vpn evpn address family mode
(config-router-af) #exit-address-family	Exit from l2vpn address family mode
(config-router) #exit	Exit from Router BGP mode and enter into config mode

VRF Configuration:

(config) #mac vrf L2VRF1	Create mac routing/forwarding instance with L2VRF1 name and enter into vrf mode
(config-vrf) #rd 5.5.5.5:11	Assign RD value
(config-vrf) #description MAC VRF RED	Give description to L2VRF1 as RED
(config-vrf) #route-target both 9.9.9.9:100	Assign route-target value for same for import and export. Should be same on all node for L2VRF1
(config-vrf) #exit	Exit from vrf mode
(config) #mac vrf L2VRF2	Create mac routing/forwarding instance with L2VRF2 name and enter into vrf mode
(config-vrf) #rd 5.5.5.5:21	Assign RD value
(config-vrf) #route-target both 90.90.90.90:100	Assign route-target value for same for import and export
(config-vrf) #description MAC VRF BLUE	Give description to L2VRF2 as BLUE
(config-vrf) #exit	Exit from vrf mode

VXLAN configuration:

(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan vtep-ip-global 5.5.5.5	Configure Source vtep-ip-global configuration. Use loopback ip address
(config) #nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # vni-name VNI-101	Configure VNI name as VNI-101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # vni-name VNI-201	Configure VNI name as VNI-201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) # nvo vxlan access-if port-vlan xe1 10	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN)
(config-nvo-acc-if) #map vnid 101	Map VXLAN Identified to access-port for VXLAN

(config-nvo-acc-if) # mac 0000.4444.1010 ip 11.11.11.201	Configure static mac-ip
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config-nvo-acc-if) #exit	Exit from VXLAN access-interface mode and enter into configuration mode
(config) #exit	Exit from configuration mode

Switch1 (MH2)

Multihomed to 2-VTEPs (VTEP1 and VTEP2). It acts as Tenant system for vlan1.20.

#configure terminal	Enter Configure mode.
(config) # bridge 1 protocol rstp vlan-bridge	Configure rstp vlan bridge
(config) # vlan database	Enter vlan database config mode
(config) #vlan 2-20 bridge 1 state enable	Configure vlans from 2-20 and associate with bridge 1
(config) #interface xe5	Enter Interface mode for xe5 which is connected to TG
(config-if) #switchport	Make as L2 port by configuring switchport
(config-if) #bridge-group 1	Associate bridge 1 into interface
(config-if) # bridge-group 1 spanning-tree disable	Configure interface as stp disable
(config-if) # switchport mode trunk	Mode as trunk
(config-if) # switchport trunk allowed vlan add 10,20	Trunk allowed vlan as 10.20
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface po1	Enter Interface mode for po1
(config-if) #switchport	Make po1 as L2 port by configuring switchport
(config-if) #bridge-group 1	Associate po1 to bridge 1
(config-if) # bridge-group 1 spanning-tree disable	Configure po1 as stp disable
(config-if) # switchport mode trunk	Mode as trunk
(config-if) # switchport trunk allowed vlan add 10,20	Trunk allowed vlan as 2.10.20
(config-if) #exit	Exit Interface mode and return to Configure mode.
(config) #interface xe3	Enter Interface mode for xe3
(config-if) #channel-group 1 mode active	Make it member port of po1
(config) #interface xe2	Enter Interface mode for xe2
(config-if) #channel-group 1 mode active	Make it member port of po1
(config-if) #commit	Commit the candidate configuration to the running configuration
(config-if) #exit	Exit from configuration mode

Spine-P3

Spine node where all VTEPs are connected.

Generic configuration:

#configure terminal	Enter Configure mode.
(Config) #qos enable	Enabling qos

Interface and loopback configuration:

(config)#interface lo	Enter Interface mode for lo
(config-if)#ip address 100.100.100.100/32 secondary	Configure loopback ip address as 100.100.100.100 for Spine-P3
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config)#interface ce16/1	Enter Interface mode for ce16/1
(config-if)#ip address 100.11.11.2/24	Configure ip address as 100.11.11.2 on network side of VTEP1
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) interface ce5/1	Enter into ce5/1 interface mode
(config-if)#ip address 100.12.12.2/24	Configure ip address as 100.12.12.2 on network side of VTEP2
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) interface ce9/1	Enter ce9/1 interface mode
(config-if)#ip address 100.14.14.2/24	Configure ip address as 100.14.14.12 on network side of VTEP4
(config-if)#exit	Exit Interface mode and return to Configure mode.
(config) interface ce23/1	Enter interface mode
(config-if)#ip address 100.15.15.1/24	Configure ip address as 100.15.15.1 on network side of VTEP5
(config-if)#exit	Exit Interface mode and return to Configure mode.

OSPF configuration:

(config)#router ospf 100	Enter into router OSPF mode
(config-router)#ospf router-id 100.100.100.100	Configure router-id as 100.100.100.100 (lo ip address)
(config-router)#network 100.100.100.100/32 area 0.0.0.0	Add 100.100.100.100 (lo ip address) network into area 0
(config-router)#network 100.11.11.0/24 area 0.0.0.0	Add 100.11.11.0 (VTEP1) network into area 0
(config-router)#network 100.12.12.0/24 area 0.0.0.0	Add 100.12.12.0 (VTEP2) network into area 0
(config-router)#network 100.14.14.0/24 area 0.0.0.0	Add 100.14.14.0 (VTEP4) network into area 0
(config-router)#network 100.15.15.0/24 area 0.0.0.0	Add 100.15.15.0 (VTEP5) network into area 0
(config-router)#bfd all-interfaces	Enabling bfd on all ospf interface for fast convergence

(config-router) #commit	Commit the candidate configuration to the running configuration
(config-router) #exit	Exit Interface mode and return to Configure mode.

Centralized Gateway

In Centralized gateway approach, when two TS belonging to two different subnets connected to the same/different VTEP node, wanted to communicate with each other, their traffic needed to be back hauled from the VTEP node to the centralized gateway node where inter- subnet switching is performed and then back to the VTEP node.

IRB Configuration for Centralized Gateway

Configure from Base Configuration-L2 VXLAN section, then configure below commands for centralized gateway approach. Here VTEP4 is the centralized GW. In VTEP4, dscp-to-queue qos profile should be applied on the particular incoming L2VNID IRB interface.

Note: For L3 traffic, when L2VNID is sent in the traffic, then dscp-to-queue qos profile mapped at IRB interface of that particular L2VNID takes effect.

VTEP1

(config) #qos profile cos-to-queue COS_QUEUE	Create QoS profile for mapping traffic towards tunnel from access-if
(config-ingress-cos-map) #cos 1 queue 5	Configure particular COS value to queue value for the profile
(config-ingress-cos-map) #exit	Exit from qos profile mode
(config) #qos profile queue-color-to-dscp QUEUE_DSCP	Create QoS profile for attaching in vxlan tunnel egress
(config-egress-dscp-map) #queue 5 dscp 34	Configure queue value to DSCP value for the profile
(config) #nvo vxlan tunnel qos-map-mode cos-dscp egress QUEUE_DSCP	Map the configured QoS profile to vxlan tunnel egress
(config) #nvo vxlan access-if port-vlan p01 20	Enter into vxlan access port mode
(config-nvo-acc-if) #map qos-profile cos-to-queue COS_QUEUE	Map the qos profile in vxlan access-if
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config-nvo-acc-if) #end	Exit from vxlan access port

VTEP2

(config) #qos profile cos-to-queue COS_QUEUE	Create QoS profile for mapping traffic towards tunnel from access-if
(config-ingress-cos-map) #cos 1 queue 5	Configure particular COS value to queue value for the profile
(config-ingress-cos-map) #exit	Exit from qos profile mode
(config) #qos profile queue-color-to-dscp QUEUE_DSCP	Create QoS profile for attaching in vxlan tunnel egress
(config-egress-dscp-map) #queue 5 dscp 34	Configure queue value to DSCP value for the profile

(config) #nvo vxlan tunnel qos-map-mode cos-dscp egress QUEUE_DSCP	Map the configured QoS profile to vxlan tunnel egress
(config) #nvo vxlan access-if port-vlan pol 20	Enter into vxlan access port mode
(config-nvo-acc-if) #map qos-profile cos-to-queue COS_QUEUE	Map the qos profile in vxlan access-if
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config-nvo-acc-if) #end	Exit from vxlan access port

VTEP4

(config) #nvo vxlan irb	Enable VXLAN irb
(config) #ip vrf L3VRF1	Create mac routing/forwarding instance with L3VRF1 name and enter into vrf mode
(config-vrf) #rd 51000:11	Assign RD value
(config-vrf) # route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from vrf mode
(config) # interface irb1001	Configure IRB interface 1001
(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 11.11.11.1/24	Configure ip address
(config-if) ipv6 address 1111::1/64	Configure ipv6 address
(config-if) exit	Exit from interface config mode
(config) # interface irb2001	Configure IRB interface 2001
(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 21.21.21.1/24	Configure ip address
(config-if) ipv6 address 2121::1/64	Configure ipv6 address
(config-if) exit	Exit from interface config mode
(config) # nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb1001	Configure irb1001 under vxlan id 101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb2001	Configure irb2001 under vxlan id 201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #qos profile dscp-to-queue DSCP_QUEUE	Configure the QoS profile to match the inner dscp value of the traffic at the IRB interface

(config-ingress-dscp-map) #dscp 20 queue 1	Configure particular dscp to a queue value. Configure particular dscp to a queue value. Here classification at the IRB L3 interface is based on customer dscp value.
(config-ingress-dscp-map) #exit	Exit from qos profile config mode
config) #int irb2001	Enter IRB L3 interface mode
(config-irb-if) #qos map-profile dscp-to-queue DSCP_QUEUE	Map the qos profile in the IRB interface
(config-irb-if) #exit	Exit from interface mode
(config) #commit	Commit the candidate configuration to the running configuration
(config) #end	Exit from global config mode

VTEP5

(config) #qos profile queue-color-to-cos QUEUE_COS	Create QoS profile for remark the queue value to COS value
(config-egress-cos-map) #queue 2 cos 5	Configure particular queue value to COS value for the profile
(config-ingress-cos-map) #exit	Exit from qos profile mode
(config) # qos profile dscp-to-queue DSCP_QUEUE	Create QoS profile for attaching in vxlan tunnel ingress
(config-ingress-dscp-map) #dscp 56 queue 2	Configure DSCP value to queue value for the profile
(config) #nvo vxlan tunnel qos-map-mode cos-dscp ingress DSCP_QUEUE	Map the configured QoS profile to vxlan tunnel ingress
(config) #nvo vxlan access-if port-vlan xe1 10	Enter into vxlan access port mode
(config-nvo-acc-if) #map qos-profile queue-color-to-cos QUEUE_COS	Map the qos profile in vxlan access-if
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config-nvo-acc-if) #end	Exit from vxlan access port

Validation

Send traffic from TS2-21 to MH2 access-if with dscp value 20 and COS value 1(vlan20) and verify traffic received at TS1-11 with dscp value 32 and COS value 5(vlan10) at the VTEP5 access-if.

VTEP1

```
VTEP1#show running-config qos
qos enable
!
qos profile cos-to-queue COS_QUEUE
cos 1 queue 5
!
qos profile queue-color-to-dscp QUEUE_DSCP
queue 5 color all dscp 34
!
!
!
VTEP1#show running-config nvo vxlan
!
nvo vxlan enable
!
```

```

evpn vxlan multihoming enable
!
nvo vxlan vtep-ip-global 1.1.1.1
!
nvo vxlan tunnel qos-map-mode cos-dscp egress QUEUE_DSCP
!
nvo vxlan id 101 ingress-replication inner-vid-disabled
vxlan host-reachability-protocol evpn-bgp L2VRF1
vni-name VNI-101
!
nvo vxlan id 201 ingress-replication inner-vid-disabled
vxlan host-reachability-protocol evpn-bgp L2VRF2
vni-name VNI-201
!
nvo vxlan access-if port-vlan pol 10
map vnid 101
mac 0000.2222.1010 ip 11.11.11.51
!
nvo vxlan access-if port-vlan pol 20
map vnid 201
mac 0000.2222.1020 ip 21.21.21.51
map qos-profile cos-to-queue COS_QUEUE
!
!
VTEP1#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination      Status        Up/Down      Update
=====          =====          =====        =====        =====
1.1.1.1         5.5.5.5       Installed     01:15:13    01:15:13
1.1.1.1         4.4.4.4       Installed     01:15:28    01:15:28
1.1.1.1         2.2.2.2       Installed     01:11:40    01:11:40

Total number of entries are 3
VTEP1#show interface ce52 counters queue-stats
E - Egress, I - Ingress, Q-Size is in bytes
+-----+-----+-----+-----+-----+-----+
| Queue/Class-map | Q-Size | Tx pkts | Tx bytes | Dropped pkts | Dropped bytes |
+-----+-----+-----+-----+-----+-----+
q0          (E) 125304832 0          0          0          0
q1          (E) 125304832 0          0          0          0
q2          (E) 125304832 0          0          0          0
q3          (E) 125304832 0          0          0          0
q4          (E) 125304832 0          0          0          0
q5          (E) 125304832 1316880 1316879000 0          0
q6          (E) 125304832 0          0          0          0
q7          (E) 125304832 0          0          0          0
VTEP1#show qos-profile COS_QUEUE
profile name: COS_QUEUE
profile type: cos-to-queue
profile attached to 1 instances
configured mapping:
cos 1 queue 5
Detailed mapping:
+-----+-----+-----+-----+-----+-----+
| INPUT | OUTPUT |           | INPUT | OUTPUT |
+-----+-----+-----+-----+-----+-----+
| COS  | DEI  | Queue | Color | COS  | DEI  | Queue | Color |
+-----+-----+-----+-----+-----+-----+
0     0     0     green | 0     1     0     yellow
1     0     5     green | 1     1     5     yellow
2     0     2     green | 2     1     2     yellow
3     0     3     green | 3     1     3     yellow
4     0     4     green | 4     1     4     yellow
5     0     5     green | 5     1     5     yellow
6     0     6     green | 6     1     6     yellow
7     0     7     green | 7     1     7     yellow
VTEP1#show qos-profile QUEUE_DSCP
profile name: QUEUE_DSCP
profile type: queue-color-to-dscp
profile attached to 1 instances
configured mapping:
queue 5 color all dscp 34

```

Detailed mapping:

INPUT	OUTPUT		INPUT	OUTPUT		INPUT	OUTPUT	
Queue	Color	DSCP	Queue	Color	DSCP	Queue	Color	DSCP
0	green	0	0	yellow	0	0	red	0
1	green	10	1	yellow	12	1	red	14
2	green	18	2	yellow	20	2	red	22
3	green	26	3	yellow	28	3	red	30
4	green	34	4	yellow	36	4	red	38
5	green	34	5	yellow	34	5	red	34
6	green	48	6	yellow	48	6	red	48
7	green	56	7	yellow	56	7	red	56

VTEP4

```
VTEP4#show running-config qos
qos enable
!
qos profile dscp-to-queue DSCP_QUEUE
  dscp 20 queue 1
!
!
!
interface irb2001
  qos map-profile dscp-to-queue DSCP_QUEUE
!
VTEP4#show running-config nvo vxlan
!
nvo vxlan enable
!
nvo vxlan irb
!
evpn vxlan multihoming enable
!
nvo vxlan vtep-ip-global 4.4.4.4
!
nvo vxlan id 101 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp L2VRF1
  evpn irb1001
  vni-name VNI-101
!
nvo vxlan id 201 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp L2VRF2
  evpn irb2001
  vni-name VNI-201
!
nvo vxlan access-if port-vlan xe3 20
  map vnid 201
  mac 0000.5555.1020 ip 21.21.21.101
!
!
```

```
VTEP4#show nvo vxlan tunnel
VXLAN Network Tunnel Entries
Source      Destination      Status      Up/Down      Update
=====
4.4.4.4      2.2.2.2      Installed      00:08:40      00:08:40
4.4.4.4      1.1.1.1      Installed      00:12:28      00:12:28
4.4.4.4      5.5.5.5      Installed      00:12:13      00:12:13
```

Total number of entries are 3

VTEP4#show nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port
 AC - Access Port
 (u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status	Src-Addr	Dst-Addr

```

101    VNI-101    L2      NW  ----  ----  -----  -----  4.4.4.4  2.2.2.2
101    VNI-101    L2      NW  -----  ----  -----  -----  4.4.4.4  1.1.1.1
101    VNI-101    L2      NW  ----  ----  -----  -----  4.4.4.4  5.5.5.5
201    VNI-201    L2      NW  ----  ----  -----  -----  4.4.4.4  2.2.2.2
201    VNI-201    L2      NW  ----  ----  -----  -----  4.4.4.4  1.1.1.1
201    VNI-201    L2      NW  ----  ----  -----  -----  4.4.4.4  5.5.5.5
201    VNI-201    --      AC  xe3   --- Single Homed Port ---  20  -----  -----

```

Total number of entries are 7

VTEP4#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
201	21.21.21.51	0000.2222.1020	Static Remote	----	
201	21.21.21.1	3c2c.991a.da7a	Static Local	----	
201	21.21.21.101	0000.5555.1020	Static Local	----	
101	11.11.11.51	0000.2222.1010	Static Remote	----	
101	11.11.11.1	3c2c.991a.da7a	Static Local	----	
101	11.11.11.201	0000.4444.1010	Static Remote	----	

Total number of entries are 6

VTEP4#show nvo vxlan nd-cache

VXLAN ND-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
201	2121::1	3c2c.991a.da7a	Static Local	----	
101	1111::1	3c2c.991a.da7a	Static Local	----	

Total number of entries are 2

VTEP4#show nvo vxlan l3vni-map

L3VNI L2VNI IRB-interface

=====

1000	101	irb1001
1000	201	irb2001

VTEP4#show ipv4 route vrf L3VRF1

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP

O - OSPF, IA - OSPF inter area

N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2

E1 - OSPF external type 1, E2 - OSPF external type 2

i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,

ia - IS-IS inter area, E - EVPN,

v - vrf leaked

* - candidate default

IP Route Table for VRF "L3VRF1"

C 11.11.11.0/24 is directly connected, irb1001, 00:01:35

C 21.21.21.0/24 is directly connected, irb2001, 00:01:16

C 127.0.0.0/8 is directly connected, lo.L3VRF1, 00:06:12

Gateway of last resort is not set

VTEP4#show ipv6 route vrf L3VRF1

IPv6 Routing Table

Codes: K - kernel route, C - connected, S - static, D- DHCP, R - RIP,

O - OSPF, IA - OSPF inter area, E1 - OSPF external type 1,

E2 - OSPF external type 2, E - EVPN N1 - OSPF NSSA external type 1,

N2 - OSPF NSSA external type 2, i - IS-IS, B - BGP,

v - vrf leaked

Timers: Uptime

IP Route Table for VRF "L3VRF1"

C ::1/128 via ::, lo.L3VRF1, 00:06:29

C 1111::/64 via ::, irb1001, 00:01:52

C 2121::/64 via ::, irb2001, 00:01:33

C fe80::/64 via ::, irb2001, 00:01:33

VTEP4#show interface ce49 counters queue-stats

E - Egress, I - Ingress, Q-Size is in bytes

Queue/Class-map	Q-Size	Tx pkts	Tx bytes	Dropped pkts	Dropped bytes
q0	(E) 125304832 0	0	0	0	0
q1	(E) 125304832 1422755	1488201730	0	0	0
q2	(E) 125304832 0	0	0	0	0

```

q3          (E) 125304832 0      0      0      0
q4          (E) 125304832 0      0      0      0
q5          (E) 125304832 0      0      0      0
q6          (E) 125304832 0      0      0      0
q7          (E) 125304832 0      0      0      0
VTEP4#show qos-profile DSCP_QUEUE
profile name: DSCP_QUEUE
profile type: dscp-to-queue
profile attached to 1 instances
configured mapping:
  dscp 20 queue 1
Detailed mapping:
-----+-----+-----+-----+-----+-----+-----+
| INPUT | OUTPUT |           | INPUT | OUTPUT |           | INPUT | OUTPUT |           | INPUT |
-----+-----+-----+-----+-----+-----+-----+-----+
| Queue | Color | Out DSCP | DSCP | Queue | Color | Out DSCP | DSCP | Queue | Color | Out DSCP | DSCP |
| Queue | Color | Out DSCP |       |       |       |       |       |       |       |       |       |       |
-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
0 green   48     0      0      16    2      green   16     16    32    4      green   32     48    6
1 green   49     0      1      17    2      green   17     17    33    4      green   33     49    6
2 green   50     0      2      18    2      green   18     18    34    4      green   34     50    6
3 green   51     0      3      19    2      green   19     19    35    4      green   35     51    6
4 green   52     0      4      20    1      yellow  20     20    36    4      yellow  36     52    6
5 green   53     0      5      21    2      green   21     21    37    4      green   37     53    6
6 green   54     0      6      22    2      yellow  22     22    38    4      yellow  38     54    6
7 green   55     0      7      23    2      green   23     23    39    4      green   39     55    6
8 green   56     1      8      24    3      green   24     24    40    5      green   40     56    7
9 green   57     1      9      25    3      green   25     25    41    5      green   41     57    7
10 green  58     1      10     26   3      green   26     26    42    5      green   42     58    7
11 green  59     1      11     27   3      green   27     27    43    5      green   43     59    7
12 green  60     1      12     28   3      yellow  28     28    44    5      green   44     60    7
13 green  61     1      13     29   3      green   29     29    45    5      green   45     61    7
14 green  62     1      14     30   3      yellow  30     30    46    5      green   46     62    7
15 green  63     1      15     31   3      green   31     31    47    5      green   47     63    7
VTEP4#show qos-profile interface irb2001
profile name: DSCP_QUEUE
profile type: dscp-to-queue (Ingress)
mapping:
-----+-----+-----+-----+-----+-----+-----+
| INPUT | OUTPUT |           | INPUT | OUTPUT |           | INPUT |
-----+-----+-----+-----+-----+-----+-----+-----+
| Queue | Color | Out DSCP | DSCP | Queue | Color | Out DSCP | DSCP |
| Queue | Color | Out DSCP |       |       |       |       |       |
-----+-----+-----+-----+-----+-----+-----+-----+
0 green   48     0      0      16    2      green   16     16    32    4      green   32     48    6
1 green   49     0      1      17    2      green   17     17    33    4      green   33     49    6
2 green   50     0      2      18    2      green   18     18    34    4      green   34     50    6
3 green   51     0      3      19    2      green   19     19    35    4      green   35     51    6
4 green   52     0      4      20    1      yellow  20     20    36    4      yellow  36     52    6

```

5	0	green	5		21	2	green	21		37	4	green	37		53	6
green	53						yellow	22		38	4	yellow	38		54	6
6	0	green	6		22	2	green	23		39	4	green	39		55	6
green	54															
7	0	green	7		23	2	green	24		40	5	green	40		56	7
green	55						green	25		41	5	green	41		57	7
8	1	green	8		24	3	green	26		42	5	green	42		58	7
green	56															
9	1	green	9		25	3	green	27		43	5	green	43		59	7
green	57						yellow	28		44	5	green	44		60	7
10	1	green	10		26	3	green	29		45	5	green	45		61	7
green	58						yellow	30		46	5	green	46		62	7
11	1	green	11		27	3	green	31		47	5	green	47		63	7
green	59															
12	1	green	12		28	3	yellow	28								
green	60															
13	1	green	13		29	3	green	29								
green	61															
14	1	green	14		30	3	yellow	30								
green	62															
15	1	green	15		31	3	green	31								
green	63															

VTEP5

```
VTEP5#show running-config qos
qos enable
!
qos profile queue-color-to-cos QUEUE_COS
queue 2 color all cos 5
!
qos profile dscp-to-queue DSCP_QUEUE
dscp 56 queue 2
!
!
!
VTEP5#show running-config nvo vxlan
!
nvo vxlan enable
!
evpn vxlan multihoming enable
!
nvo vxlan vtep-ip-global 5.5.5.5
!
nvo vxlan tunnel qos-map-mode cos-dscp ingress DSCP_QUEUE
!
nvo vxlan id 101 ingress-replication inner-vid-disabled
vxlan host-reachability-protocol evpn-bgp L2VRF1
vni-name VNI-101
!
nvo vxlan id 201 ingress-replication inner-vid-disabled
vxlan host-reachability-protocol evpn-bgp L2VRF2
vni-name VNI-201
!
nvo vxlan access-if port-vlan xe1 10
map vnid 101
mac 0000.4444.1010 ip 11.11.11.201
map qos-profile queue-color-to-cos QUEUE_COS
!
```

```
VTEP5#show nvo vxlan tunnel
VXLAN Network Tunnel Entries
Source          Destination        Status      Up/Down      Update
=====
5.5.5.5         2.2.2.2           Installed   01:11:17    01:11:17
5.5.5.5         4.4.4.4           Installed   01:14:50    01:14:50
5.5.5.5         1.1.1.1           Installed   01:14:50    01:14:50
```

Total number of entries are 3

```
VTEP5#show interface xe1 counters queue-stats
E - Egress, I - Ingress, Q-Size is in bytes
```

Queue/Class-map	Q-Size	Tx pkts	Tx bytes	Dropped pkts	Dropped bytes
q0 (E)	12517376	0	0	0	0

```

q1          (E) 12517376 0           0           0           0
q2          (E) 12517376 1005800     1052066800  0           0
q3          (E) 12517376 0           0           0           0
q4          (E) 12517376 0           0           0           0
q5          (E) 12517376 0           0           0           0
q6          (E) 12517376 0           0           0           0
q7          (E) 12517376 0           0           0           0

```

```

VTEP5#sh qos-profile QUEUE_COS
profile name: QUEUE_COS
profile type: queue-color-to-cos
profile attached to 1 instances
configured mapping:
queue 2 color all cos 5
Detailed mapping:

```

INPUT			OUTPUT			INPUT			OUTPUT			INPUT			OUTPUT		
Queue	Color	COS	Queue	Color	COS	Queue	Color	COS	Queue	Color	COS	Queue	Color	COS	Queue	Color	COS
0	green	0	0	yellow	0	0	red	0									
1	green	1	1	yellow	1	1	red	1									
2	green	5	2	yellow	5	2	red	5									
3	green	3	3	yellow	3	3	red	3									
4	green	4	4	yellow	4	4	red	4									
5	green	5	5	yellow	5	5	red	5									
6	green	6	6	yellow	6	6	red	6									
7	green	7	7	yellow	7	7	red	7									

```

VTEP5#show qos-profile DSCP_QUEUE
profile name: DSCP_QUEUE
profile type: dscp-to-queue
profile attached to 1 instances
configured mapping:
dscp 56 queue 2
Detailed mapping:

```

INPUT			OUTPUT			INPUT			OUTPUT			INPUT			OUTPUT			
OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT	OUTPUT	INPUT	OUTPUT	OUTPUT	INPUT	OUTPUT	OUTPUT	INPUT	OUTPUT	
DSCP	Queue	Color	Out DSCP	DSCP	Queue	Color	Out DSCP	DSCP	Queue	Color	Out DSCP	DSCP	Queue	Color	Out DSCP	DSCP	Queue	Color
Queue	Color	Out DSCP																
0	0	green	0	16	2	green	16	1	32	4	green	32	1	48	6			
green	48																	
1	0	green	1	17	2	green	17	1	33	4	green	33	1	49	6			
green	49																	
2	0	green	2	18	2	green	18	1	34	4	green	34	1	50	6			
green	50																	
3	0	green	3	19	2	green	19	1	35	4	green	35	1	51	6			
green	51																	
4	0	green	4	20	2	yellow	20	1	36	4	yellow	36	1	52	6			
green	52																	
5	0	green	5	21	2	green	21	1	37	4	green	37	1	53	6			
green	53																	
6	0	green	6	22	2	yellow	22	1	38	4	yellow	38	1	54	6			
green	54																	
7	0	green	7	23	2	green	23	1	39	4	green	39	1	55	6			
green	55																	
8	1	green	8	24	3	green	24	1	40	5	green	40	1	56	2			
green	56																	
9	1	green	9	25	3	green	25	1	41	5	green	41	1	57	7			
green	57																	
10	1	green	10	26	3	green	26	1	42	5	green	42	1	58	7			
green	58																	
11	1	green	11	27	3	green	27	1	43	5	green	43	1	59	7			
green	59																	
12	1	yellow	12	28	3	yellow	28	1	44	5	green	44	1	60	7			
green	60																	
13	1	green	13	29	3	green	29	1	45	5	green	45	1	61	7			
green	61																	
14	1	yellow	14	30	3	yellow	30	1	46	5	green	46	1	62	7			
green	62																	
15	1	green	15	31	3	green	31	1	47	5	green	47	1	63	7			
green	63																	

Anycast Gateway

For today's large multi-tenant data center, centralized L3 gateway scheme is very inefficient and sometimes impractical. In order to overcome the drawback of centralized L3GW approach, anycast mode is used.

In Anycast gateway approach, all the VTEPs acts as default gateway for all the VNIDs. We will configure same anycast mac in all VTEPs.

IRB Configuration for Anycast

Configure from Base Configuration-L2 VXLAN section, then configure below commands for Anycast gateway approach.

Note: For L2 traffic, always dscp-to-queue qos profile at tunnel ingress takes effect.

Note: For L3 traffic in the local VTEP, routing is done at IRB level and also QoS applied at the IRB interface and it sends with l2vnid.

VTEP1

(config) #nvo vxlan irb	Enable VXLAN irb
(config) #ip vrf L3VRF1	Create mac routing/forwarding instance with L3VRF1 name and enter into vrf mode
(config-vrf) #rd 11000:11	Assign RD value
(config-vrf) # route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from vrf mode
(config) # evpn irb-forwarding anycast-gateway-mac 0000.0000.1111	Configure anycast mac address
(config) # interface irb1001	Configure IRB interface 1001
(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 11.11.11.1/24	Configure ip address
(config-if) ipv6 address 1111::1/64	Configure ipv6 address
(config-if) evpn irb-if-forwarding anycast-gateway-mac	Configure anycast mac address
(config-if) exit	Exit from interface config mode
(config) # interface irb2001	Configure IRB interface 2001
(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 21.21.21.1/24	Configure ip address
(config-if) ipv6 address 2121::1/64	Configure ipv6 address
(config-if) evpn irb-if-forwarding anycast-gateway-mac	Configure anycast mac address
(config-if) exit	Exit from interface config mode
(config) # nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode

(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb1001	Configure irb1001 under vxlan id 101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb2001	Configure irb2001 under vxlan id 201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #qos profile dscp-to-queue DSCP_QUEUE	Configure QoS profile to remark the traffic received from access-if
(config-ingress-dscp-map) #dscp 20 queue 4	Configure particular dscp value to queue value in the profile
(config-ingress-dscp-map) #exit	Exit from qos profile mode
(config) #int irb2001	Enter IRB L3 interface
(config-irb-if) #qos map-profile dscp-to-queue DSCP_QUEUE	Map the qos profile
(config-irb-if) #exit	Exit from interface mode
(config) #commit	Commit the candidate configuration to the running configuration
(config) #end	Exit from global config mode

VTEP2

(config) #nvo vxlan irb	Enable VXLAN IRB
(config) #ip vrf L3VRF1	Create mac routing/forwarding instance with L3VRF1 name and enter into vrf mode
(config-vrf) #rd 21000:11	Assign RD value
(config-vrf) # route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from vrf mode
(config) # evpn irb-forwarding anycast-gateway-mac 0000.0000.1111	Configure anycast mac address
(config) # interface irb1001	Configure IRB interface 1001
(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 11.11.11.1/24	Configure ip address
(config-if) ipv6 address 1111::1/64	Configure ipv6 address
(config-if) evpn irb-if-forwarding anycast-gateway-mac	Configure anycast mac address
(config-if) exit	Exit from interface config mode
(config) # interface irb2001	Configure IRB interface 2001
(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 21.21.21.1/24	Configure ip address

(config-if) ipv6 address 2121::1/64	Configure ipv6 address
(config-if) evpn irb-if-forwarding anycast-gateway-mac	Configure anycast mac address
(config-if) exit	Exit from interface config mode
(config) # nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb1001	Configure irb1001 under vxlan id 101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb2001	Configure irb2001 under vxlan id 201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #qos profile dscp-to-queue DSCP_QUEUE	Configure QoS profile to remark the traffic at remote vtep at the ingress tunnel.
(config-ingress-dscp-map) #dscp 20 queue 4	Configure particular dscp value to queue value in the profile
(config-ingress-dscp-map) #exit	Exit from qos profile mode
(config) #int irb2001	Enter IRB L3 interface
(config-irb-if) #qos map-profile dscp-to-queue DSCP_QUEUE	Map the qos profile
(config-irb-if) #exit	Exit from interface mode
(config) #commit	Commit the candidate configuration to the running configuration
(config) #end	Exit from global config mode

VTEP4

(config) #nvo vxlan irb	Enable VXLAN IRB
(config) #ip vrf L3VRF1	Create mac routing/forwarding instance with L3VRF1 name and enter into vrf mode
(config-vrf) #rd 41000:11	Assign RD value
(config-vrf) # route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from vrf mode
(config) # evpn irb-forwarding anycast-gateway-mac 0000.0000.1111	Configure anycast mac address
(config) # interface irb1001	Configure IRB interface 1001
(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 11.11.11.1/24	Configure ip address
(config-if) ipv6 address 1111::1/64	Configure ipv6 address

(config-if) evpn irb-if-forwarding anycast-gateway-mac	Configure anycast mac address
(config-if) exit	Exit from interface config mode
(config) # interface irb2001	Configure IRB interface 2001
(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 21.21.21.1/24	Configure ip address
(config-if) ipv6 address 2121::1/64	Configure ipv6 address
(config-if) evpn irb-if-forwarding anycast-gateway-mac	Configure anycast mac address
(config-if) exit	Exit from interface config mode
(config) # nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb1001	Configure irb1001 under vxlan id 101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb2001	Configure irb2001 under vxlan id 201
(config-nvo) #commit	Commit the candidate configuration to the running configuration
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.

VTEP5

(config) #nvo vxlan irb	Enable VXLAN IRB
(config) #ip vrf L3VRF1	Create mac routing/forwarding instance with L3VRF1 name and enter into vrf mode
(config-vrf) #rd 51000:11	Assign RD value
(config-vrf) # route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from vrf mode
(config) # evpn irb-forwarding anycast-gateway-mac 0000.0000.1111	Configure anycast mac address
(config) # interface irb1001	Configure IRB interface 1001
(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 11.11.11.1/24	Configure ip address
(config-if) ipv6 address 1111::1/64	Configure ipv6 address
(config-if) evpn irb-if-forwarding anycast-gateway-mac	Configure anycast mac address
(config-if) exit	Exit from interface config mode
(config) # interface irb2001	Configure IRB interface 2001

(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 21.21.21.1/24	Configure ip address
(config-if) ipv6 address 2121::1/64	Configure ipv6 address
(config-if) evpn irb-if-forwarding anycast-gateway-mac	Configure anycast mac address
(config-if) exit	Exit from interface config mode
(config)# nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb1001	Configure irb1001 under vxlan id 101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config)#nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb2001	Configure irb2001 under vxlan id 201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #qos profile dscp-to-queue DSCP_QUEUE	Configure the qos profile to remark outer dscp to queue of the ingress tunnel traffic. Here classification at the ingress vtep is based on overlay dscp value.
(config-ingress-dscp-map) #dscp 34 queue 2	Configure particular dscp value to queue value in the profile. Here dscp to <queue, dscp> is not applicable. I.e ingress remarking of dscp at the ingress tunnel is not applicable.
(config-ingress-dscp-map) #exit	Exit from qos profile mode
(config) #qos profile queue-color-to-cos QUEUE_COS	Configure qos profile to remark the queue value to COS value
(config-egress-cos-map) #queue 2 cos 6	Configure particular queue value to COS value
(config-egress-cos-map) #exit	Exit from qos profile config mode
(config) #nvo vxlan tunnel qos-map-mode cos-dscp ingress DSCP_QUEUE	Map the qos profile in tunnel ingress
(config) #nvo vxlan access-if port-vlan xe1 10	Enter to vxlan access port config mode
(config-nvo-acc-if) #map qos-profile queue-color-to-cos QUEUE_COS	Map the qos profile in vxlan access port
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config-nvo-acc-if) #end	Exit from config mode

Validations

Send traffic from TS2-21 to MH2 access-if with dscp value 20 and COS value 1(vlan20) and verify traffic received at TS1-11 with dscp value 20 and COS value 6(vlan10) at the VTEP5 access-if.

VTEP1

VTEP1#show running-config qos

```

qos enable
!
qos profile dscp-to-queue DSCP_QUEUE
  dscp 20 queue 4
!
!
!
!
interface irb2001
  qos map-profile dscp-to-queue DSCP_QUEUE
!
VTEP1#show running-config nvo vxlan
!
nvo vxlan enable
!
nvo vxlan irb
!
evpn vxlan multihoming enable
!
evpn irb-forwarding anycast-gateway-mac 0000.0000.1111
!
nvo vxlan vtep-ip-global 1.1.1.1
!
nvo vxlan id 101 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp L2VRF1
  evpn irb1001
  vni-name VNI-101
!
nvo vxlan id 201 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp L2VRF2
  evpn irb2001
  vni-name VNI-201
!
nvo vxlan access-if port-vlan pol 10
  map vnid 101
  mac 0000.2222.1010 ip 11.11.11.51
!
nvo vxlan access-if port-vlan pol 20
  map vnid 201
  mac 0000.2222.1020 ip 21.21.21.51
!
!
VTEP1#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination        Status      Up/Down      Update
=====
1.1.1.1          5.5.5.5        Installed    01:15:13    01:15:13
1.1.1.1          4.4.4.4        Installed    01:15:28    01:15:28
1.1.1.1          2.2.2.2        Installed    01:11:40    01:11:40

```

Total number of entries are 3

VTEP1#show nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port

AC - Access Port

(u) - Untagged

VNID Src-Addr	VNI-Name Dst-Addr	VNI-Type	Type	Interface	ESI	VLAN	DF	Status
101 1.1.1.1	VNI-101 5.5.5.5	L2	NW	----	----	-----	-----	-----
101 1.1.1.1	VNI-101 4.4.4.4	L2	NW	----	----	-----	-----	-----
101 1.1.1.1	VNI-101 2.2.2.2	L2	NW	----	----	-----	-----	-----
101 ----	VNI-101 ----	--	AC	pol	00:00:00:00:00:22:22:00:00:00 10	DF		
201 1.1.1.1	VNI-201 5.5.5.5	L2	NW	----	----	-----	-----	-----
201 1.1.1.1	VNI-201 4.4.4.4	L2	NW	----	----	-----	-----	-----
201 1.1.1.1	VNI-201 2.2.2.2	L2	NW	----	----	-----	-----	-----
201 ----	VNI-201 ----	--	AC	pol	00:00:00:00:00:22:22:00:00:00 20	DF		

Total number of entries are 8

VTEP1#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
201	21.21.21.51	0000.2222.1020	Static Local	----	
201	21.21.21.1	0000.0000.1111	Static Local	----	
201	21.21.21.101	0000.5555.1020	Static Remote	----	
101	11.11.11.51	0000.2222.1010	Static Local	----	
101	11.11.11.10	0010.9400.0002	Dynamic Remote	----	
101	11.11.11.1	0000.0000.1111	Static Local	----	
101	11.11.11.201	0000.4444.1010	Static Remote	----	

Total number of entries are 7

VTEP1#show nvo vxlan nd-cache

VXLAN ND-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out
Retries-Left				
201	2121::1	0000.0000.1111	Static Local	----
101	1111::10	0010.9400.0002	Dynamic Remote	----
101	1111::1	0000.0000.1111	Static Local	----

```
Total number of entries are 3
VTEP1#show ipv4 route vrf L3VRF1
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
      O - OSPF, IA - OSPF inter area
      N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
      E1 - OSPF external type 1, E2 - OSPF external type 2
      i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
      ia - IS-IS inter area, E - EVPN,
      v - vrf leaked
      * - candidate default
```

```
IP Route Table for VRF "L3VRF1"
C           11.11.11.0/24 is directly connected, irb1001, 00:13:19
C           21.21.21.0/24 is directly connected, irb2001, 00:12:56
C           127.0.0.0/8 is directly connected, lo.L3VRF1, 00:17:13
```

Gateway of last resort is not set

```
VTEP1#show ipv6 route vrf L3VRF1
```

IPv6 Routing Table

```
Codes: K - kernel route, C - connected, S - static, D- DHCP, R - RIP,
      O - OSPF, IA - OSPF inter area, E1 - OSPF external type 1,
      E2 - OSPF external type 2, E - EVPN  N1 - OSPF NSSA external type 1,
      N2 - OSPF NSSA external type 2, i - IS-IS, B - BGP,
      v - vrf leaked
```

Timers: Uptime

```
IP Route Table for VRF "L3VRF1"
C     ::1/128 via ::, lo.L3VRF1, 00:17:23
C     1111::/64 via ::, irb1001, 00:13:29
C     2121::/64 via ::, irb2001, 00:13:06
C     fe80::/64 via ::, irb2001, 00:13:06
```

```
VTEP1#show interface ce52 counters queue-stats
```

E - Egress, I - Ingress, Q-Size is in bytes

Queue/Class-map	Q-Size	Tx pkts	Tx bytes	Dropped pkts
Dropped bytes				
q0	(E) 125304832	0	0	0
q1	(E) 125304832	0	0	0
q2	(E) 125304832	0	0	0
q3	(E) 125304832	0	0	0
q4	(E) 125304832	0	0	0
q5	(E) 125304832	0	0	0
q6	(E) 125304832	0	0	0
q7	(E) 125304832	0	0	0

```
VTEP1#show nvo vxlan l3vni-map
L3VNI          L2VNI          IRB-interface
=====
```

```
1000      101      irb1001
1000      201      irb2001
```

```
VTEP1#show qos-profile DSCP_QUEUE
```

```
profile name: DSCP_QUEUE
profile type: dscp-to-queue
profile attached to 1 instances
configured mapping:
dscp 20 queue 4
Detailed mapping:
```

INPUT OUTPUT	OUTPUT INPUT	INPUT OUTPUT	OUTPUT	INPUT				
DSCP Queue	Queue Color	Color Out DSCP	DSCP	DSCP Queue	Queue Color	Color Out DSCP	DSCP	DSCP
0 green	0 32	green 48	0 6	16 green	2 48	green 16	32	4
1 green	0 33	green 49	1 6	17 green	2 49	green 17	33	4
2 green	0 34	green 50	2 6	18 green	2 50	green 18	34	4
3 green	0 35	green 51	3 6	19 green	2 51	green 19	35	4
4 yellow	0 36	green 52	4 6	20 green	4 52	yellow 20	36	4
5 green	0 37	green 53	5 6	21 green	2 53	green 21	37	4
6 yellow	0 38	green 54	6 6	22 green	2 54	yellow 22	38	4
7 green	0 39	green 55	7 6	23 green	2 55	green 23	39	4
8 green	1 40	green 56	8 7	24 green	3 56	green 24	40	5
9 green	1 41	green 57	9 7	25 green	3 57	green 25	41	5
10 green	1 42	green 58	10 7	26 green	3 58	green 26	42	5
11 green	1 43	green 59	11 7	27 green	3 59	green 27	43	5
12 green	1 44	yellow 60	12 7	28 green	3 60	yellow 28	44	5
13 green	1 45	green 61	13 7	29 green	3 61	green 29	45	5
14 green	1 46	yellow 62	14 7	30 green	3 62	yellow 30	46	5
15 green	1 47	green 63	15 7	31 green	3 63	green 31	47	5

```
VTEP1#show qos-profile interface irb2001
```

```
profile name: DSCP_QUEUE
```

profile type: dscp-to-queue (Ingress)

mapping:

INPUT OUTPUT	OUTPUT INPUT	INPUT OUTPUT	OUTPUT	INPUT
DSCP Queue	Queue Color	DSCP Out DSCP	DSCP Queue	DSCP Queue
Color	Out DSCP	DSCP	Color	Out DSCP
0 green	0 32	green 48	0 6	16 green 48
1 green	0 33	green 49	1 6	17 green 49
2 green	0 34	green 50	2 6	18 green 50
3 green	0 35	green 51	3 6	19 green 51
4 yellow	0 36	green 52	4 6	20 yellow 52
5 green	0 37	green 53	5 6	21 green 53
6 yellow	0 38	green 54	6 6	22 yellow 54
7 green	0 39	green 55	7 6	23 green 55
8 green	1 40	green 56	8 7	24 green 56
9 green	1 41	green 57	9 7	25 green 57
10 green	1 42	green 58	10 7	26 green 58
11 green	1 43	green 59	11 7	27 green 59
12 green	1 44	yellow 60	12 7	28 yellow 60
13 green	1 45	green 61	13 7	29 green 61
14 green	1 46	yellow 62	14 7	30 yellow 62
15 green	1 47	green 63	15 7	31 green 63

VTEP2

```
VTEP2#show running-config qos
qos enable
!
qos profile dscp-to-queue DSCP_QUEUE
  dscp 20 queue 4
!
!
```

```
!
interface irb2001
  qos map-profile dscp-to-queue DSCP_QUEUE
!
VTEP2#show running-config nvo vxlan
!
nvo vxlan enable
!
nvo vxlan irb
!
evpn esi hold-time 90
!
evpn vxlan multihoming enable
!
evpn irb-forwarding anycast-gateway-mac 0000.0000.1111
!
nvo vxlan vtep-ip-global 2.2.2.2
!
nvo vxlan id 101 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp L2VRF1
  evpn irb1001
  vni-name VNI-101
!
nvo vxlan id 201 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp L2VRF2
  evpn irb2001
  vni-name VNI-201
!
nvo vxlan access-if port-vlan pol 10
  map vnid 101
  mac 0000.2222.1010 ip 11.11.11.51
!
nvo vxlan access-if port-vlan pol 20
  map vnid 201
  mac 0000.2222.1020 ip 21.21.21.51
!
!
VTEP2#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination        Status      Up/Down      Update
=====
2.2.2.2          4.4.4.4        Installed    01:13:43    01:13:43
2.2.2.2          1.1.1.1        Installed    01:13:43    01:13:43
2.2.2.2          5.5.5.5        Installed    01:13:43    01:13:43

Total number of entries are 3
VTEP2#show nvo vxlan
VXLAN Information
=====
Codes: NW - Network Port
```

AC - Access Port
(u) - Untagged

VNID Src-Addr	VNI-Name Dst-Addr	VNI-Type Type	Interface ESI		VLAN	DF-Status
101 2.2.2.2	VNI-101 4.4.4.4	L2 NW	----	----	-----	-----
101 2.2.2.2	VNI-101 1.1.1.1	L2 NW	----	----	-----	-----
101 2.2.2.2	VNI-101 5.5.5.5	L2 NW	----	----	-----	-----
101 ----	VNI-101 ----	-- AC	po1 00:00:00:00:00:22:22:00:00:00	00:00:00:00:00:22:22:00:00:00 10	NON-DF	
201 2.2.2.2	VNI-201 4.4.4.4	L2 NW	----	----	-----	-----
201 2.2.2.2	VNI-201 1.1.1.1	L2 NW	----	----	-----	-----
201 2.2.2.2	VNI-201 5.5.5.5	L2 NW	----	----	-----	-----
201 ----	VNI-201 ----	-- AC	po1 00:00:00:00:00:22:22:00:00:00	00:00:00:00:00:22:22:00:00:00 20	NON-DF	

Total number of entries are 8

VTEP2#show nvo vxlan arp-cache
VXLAN ARP-CACHE Information

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
201	21.21.21.51	0000.2222.1020	Static Local	----	
201	21.21.21.1	0000.0000.1111	Static Local	----	
201	21.21.21.101	0000.5555.1020	Static Remote	----	
101	11.11.11.51	0000.2222.1010	Static Local	----	
101	11.11.11.10	0010.9400.0002	Dynamic Remote	----	
101	11.11.11.1	0000.0000.1111	Static Local	----	
101	11.11.11.201	0000.4444.1010	Static Remote	----	

Total number of entries are 7

VTEP2#show nvo vxlan nd-cache
VXLAN ND-CACHE Information

VNID	Ip-Addr	Mac-Addr	Type	Age-Out
Retries-Left				
201	2121::1	0000.0000.1111	Static Local	----
101	1111::10	0010.9400.0002	Dynamic Remote	----
101	1111::1	0000.0000.1111	Static Local	----

Total number of entries are 3

VTEP2#show ipv4 route vrf L3VRF1

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP

O - OSPF, IA - OSPF inter area

N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2

E1 - OSPF external type 1, E2 - OSPF external type 2
 i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
 ia - IS-IS inter area, E - EVPN,
 v - vrf leaked
 * - candidate default

IP Route Table for VRF "L3VRF1"

```
C      11.11.11.0/24 is directly connected, irb1001, 00:10:20
C      21.21.21.0/24 is directly connected, irb2001, 00:09:55
C      127.0.0.0/8 is directly connected, lo.L3VRF1, 00:13:30
```

Gateway of last resort is not set

VTEP2#show ipv6 route vrf L3VRF1

IPv6 Routing Table

Codes: K - kernel route, C - connected, S - static, D- DHCP, R - RIP,
 O - OSPF, IA - OSPF inter area, E1 - OSPF external type 1,
 E2 - OSPF external type 2, E - EVPN N1 - OSPF NSSA external type 1,
 N2 - OSPF NSSA external type 2, i - IS-IS, B - BGP,
 v - vrf leaked

Timers: Uptime

IP Route Table for VRF "L3VRF1"

```
C      ::1/128 via ::, lo.L3VRF1, 00:13:36
C      1111::/64 via ::, irb1001, 00:10:26
C      2121::/64 via ::, irb2001, 00:10:01
C      fe80::/64 via ::, irb2001, 00:10:01
```

VTEP2#show nvo vxlan 13vni-map

L3VNI	L2VNI	IRB-interface
1000	101	irb1001
1000	201	irb2001

VTEP2#show interface xe29 counters queue-stats

E - Egress, I - Ingress, Q-Size is in bytes

Queue/Class-map	Q-Size	Tx pkts	Tx bytes	Dropped pkts
Dropped bytes				
q0	(E) 12517376 0	0	0	0
q1	(E) 12517376 0	0	0	0
q2	(E) 12517376 0	0	0	0
q3	(E) 12517376 0	0	0	0
q4	(E) 12517376 2998022	2998045000	0	0
q5	(E) 12517376 0	0	0	0
q6	(E) 12517376 0	0	0	0
q7	(E) 12517376 0	0	0	0

VTEP2#show qos-profile DSCP_QUEUE

profile name: DSCP_QUEUE

```
profile type: dscp-to-queue
profile attached to 1 instances
configured mapping:
  dscp 20 queue 4
Detailed mapping:
```

INPUT OUTPUT				INPUT OUTPUT				INPUT			
OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT	INPUT
DSCP Queue	Color	Out DSCP	DSCP	DSCP Queue	Color	Out DSCP	DSCP	DSCP Queue	Color	Out DSCP	DSCP
0 green	0	green	0	16	green	16	green	16	32	4	
	32	48	6		green	48					
1 green	0	green	1	17	green	17	green	17	33	4	
	33	49	6		green	49					
2 green	0	green	2	18	green	18	green	18	34	4	
	34	50	6		green	50					
3 green	0	green	3	19	green	19	green	19	35	4	
	35	51	6		green	51					
4 yellow	0	green	4	20	green	20	yellow	20	36	4	
	36	52	6		green	52					
5 green	0	green	5	21	green	21	green	21	37	4	
	37	53	6		green	53					
6 yellow	0	green	6	22	green	22	yellow	22	38	4	
	38	54	6		green	54					
7 green	0	green	7	23	green	23	green	23	39	4	
	39	55	6		green	55					
8 green	1	green	8	24	green	24	green	24	40	5	
	40	56	7		green	56					
9 green	1	green	9	25	green	25	green	25	41	5	
	41	57	7		green	57					
10 green	1	green	10	26	green	26	green	26	42	5	
	42	58	7		green	58					
11 green	1	green	11	27	green	27	green	27	43	5	
	43	59	7		green	59					
12 green	1	yellow	12	28	green	28	yellow	28	44	5	
	44	60	7		green	60					
13 green	1	green	13	29	green	29	green	29	45	5	
	45	61	7		green	61					
14 green	1	yellow	14	30	green	30	yellow	30	46	5	
	46	62	7		green	62					
15 green	1	green	15	31	green	31	green	31	47	5	
	47	63	7		green	63					

```
VTEP2#show qos-profile interface irb2001
```

```
profile name: DSCP_QUEUE
profile type: dscp-to-queue (Ingress)
mapping:
```

INPUT OUTPUT				INPUT OUTPUT				INPUT			
OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT	INPUT

DSCP Queue	Color	Out DSCP	DSCP Queue	Color	Out DSCP	DSCP	
Queue	Color	Out DSCP	DSCP	Queue	Color	Out DSCP	DSCP
0 green	0 32	green 48	0 6	16 green	2 48	green 16	32 4
1 green	0 33	green 49	1 6	17 green	2 49	green 17	33 4
2 green	0 34	green 50	2 6	18 green	2 50	green 18	34 4
3 green	0 35	green 51	3 6	19 green	2 51	green 19	35 4
4 yellow	0 36	green 52	4 6	20 green	4 52	yellow 20	36 4
5 green	0 37	green 53	5 6	21 green	2 53	green 21	37 4
6 yellow	0 38	green 54	6 6	22 green	2 54	yellow 22	38 4
7 green	0 39	green 55	7 6	23 green	2 55	green 23	39 4
8 green	1 40	green 56	8 7	24 green	3 56	green 24	40 5
9 green	1 41	green 57	9 7	25 green	3 57	green 25	41 5
10 green	1 42	green 58	10 7	26 green	3 58	green 26	42 5
11 green	1 43	green 59	11 7	27 green	3 59	green 27	43 5
12 green	1 44	yellow 60	12 7	28 green	3 60	yellow 28	44 5
13 green	1 45	green 61	13 7	29 green	3 61	green 29	45 5
14 green	1 46	yellow 62	14 7	30 green	3 62	yellow 30	46 5
15 green	1 47	green 63	15 7	31 green	3 63	green 31	47 5

VTEP4

VTEP4#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
4.4.4.4	2.2.2.2	Installed	01:14:47	01:14:47
4.4.4.4	1.1.1.1	Installed	01:18:35	01:18:35
4.4.4.4	5.5.5.5	Installed	01:18:20	01:18:20

Total number of entries are 3

VTEP4#show nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port

AC - Access Port

(u) - Untagged

VNID Src-Addr	VNI-Name Dst-Addr	VNI-Type Type	Interface	ESI	VLAN	DF-Status
101 4.4.4.4	VNI-101 2.2.2.2	L2 NW	-----	-----	-----	-----
101 4.4.4.4	VNI-101 1.1.1.1	L2 NW	-----	-----	-----	-----
101 4.4.4.4	VNI-101 5.5.5.5	L2 NW	-----	-----	-----	-----
201 4.4.4.4	VNI-201 2.2.2.2	L2 NW	-----	-----	-----	-----
201 4.4.4.4	VNI-201 1.1.1.1	L2 NW	-----	-----	-----	-----
201 4.4.4.4	VNI-201 5.5.5.5	L2 NW	-----	-----	-----	-----
201 -----	VNI-201 -----	-- AC	xe3	--- Single Homed Port ---	20	-----

Total number of entries are 7

VTEP4#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
201	21.21.21.51	0000.2222.1020	Static Remote	-----	
201	21.21.21.1	0000.0000.1111	Static Local	-----	
201	21.21.21.101	0000.5555.1020	Static Local	-----	
101	11.11.11.51	0000.2222.1010	Static Remote	-----	
101	11.11.11.10	0010.9400.0002	Dynamic Remote	-----	
101	11.11.11.1	0000.0000.1111	Static Local	-----	
101	11.11.11.201	0000.4444.1010	Static Remote	-----	

Total number of entries are 7

VTEP4#show nvo vxlan nd-cache

VXLAN ND-CACHE Information

VNID	Ip-Addr	Mac-Addr	Type	Age-Out
201	2121::1	0000.0000.1111	Static Local	-----
101	1111::10	0010.9400.0002	Dynamic Remote	-----
101	1111::1	0000.0000.1111	Static Local	-----

Total number of entries are 3

VTEP4#show ipv4 route vrf L3VRF1

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP

O - OSPF, IA - OSPF inter area

N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2

E1 - OSPF external type 1, E2 - OSPF external type 2

i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,

ia - IS-IS inter area, E - EVPN,

v - vrf leaked

```
* - candidate default

IP Route Table for VRF "L3VRF1"
C           11.11.11.0/24 is directly connected, irb1001, 00:07:24
C           21.21.21.0/24 is directly connected, irb2001, 00:07:14
C           127.0.0.0/8 is directly connected, lo.L3VRF1, 00:10:16
```

Gateway of last resort is not set

```
VTEP4#show ipv6 route vrf L3VRF1
```

IPv6 Routing Table

```
Codes: K - kernel route, C - connected, S - static, D- DHCP, R - RIP,
       O - OSPF, IA - OSPF inter area, E1 - OSPF external type 1,
       E2 - OSPF external type 2, E - EVPN N1 - OSPF NSSA external type 1,
       N2 - OSPF NSSA external type 2, i - IS-IS, B - BGP,
       v - vrf leaked
```

Timers: Uptime

```
IP Route Table for VRF "L3VRF1"
C           ::1/128 via ::, lo.L3VRF1, 00:10:21
C           1111::/64 via ::, irb1001, 00:07:29
C           2121::/64 via ::, irb2001, 00:07:19
C           fe80::/64 via ::, irb2001, 00:07:19
```

```
VTEP4#show nvo vxlan l3vni-map
```

L3VNI	L2VNI	IRB-interface
1000	101	irb1001
1000	201	irb2001

VTEP5

```
VTEP5#show running-config qos
qos enable
!
qos profile queue-color-to-cos QUEUE_COS
  queue 2 color all cos 6
!
qos profile dscp-to-queue DSCP_QUEUE
  dscp 34 queue 2
!
!
!
VTEP5#show running-config nvo vxlan
!
nvo vxlan enable
!
nvo vxlan irb
!
evpn vxlan multihoming enable
!
evpn irb-forwarding anycast-gateway-mac 0000.0000.1111
```

```
!
nvo vxlan vtep-ip-global 5.5.5.5
!
nvo vxlan tunnel qos-map-mode cos-dscp ingress DSCP_QUEUE
!
nvo vxlan id 101 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp L2VRF1
    evpn irb1001
    vni-name VNI-101
!
nvo vxlan id 201 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp L2VRF2
    evpn irb2001
    vni-name VNI-201
!
nvo vxlan access-if port-vlan xe1 10
  map vnid 101
  mac 0000.4444.1010 ip 11.11.11.201
  map qos-profile queue-color-to-cos QUEUE_COS
!
```

```
VTEP5#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination        Status      Up/Down      Update
=====
5.5.5.5          2.2.2.2           Installed   01:11:17    01:11:17
5.5.5.5          4.4.4.4           Installed   01:14:50    01:14:50
5.5.5.5          1.1.1.1           Installed   01:14:50    01:14:50
```

Total number of entries are 3

```
VTEP5#sh nvo vxlan
```

VXLAN Information

=====

```
Codes: NW - Network Port
       AC - Access Port
       (u) - Untagged
```

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status
Src-Addr		Dst-Addr					
101	VNI-101	L2	NW	----	----	----	----
5.5.5.5		2.2.2.2					
101	VNI-101	L2	NW	----	----	----	----
5.5.5.5		4.4.4.4					
101	VNI-101	L2	NW	----	----	----	----
5.5.5.5		1.1.1.1					
101	VNI-101	--	AC	xe1	--- Single Homed Port ---	10	----
----		----					
201	VNI-201	L2	NW	----	----	----	----
5.5.5.5		2.2.2.2					

201 5.5.5.5	VNI-201 4.4.4.4	L2	NW	----	----	----- -----
201 5.5.5.5	VNI-201 1.1.1.1	L2	NW	----	----	----- -----

Total number of entries are 7

VTEP5#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
201	21.21.21.51	0000.2222.1020	Static Remote	----	
201	21.21.21.1	0000.0000.1111	Static Local	----	
201	21.21.21.101	0000.5555.1020	Static Remote	----	
101	11.11.11.51	0000.2222.1010	Static Remote	----	
101	11.11.11.10	0010.9400.0002	Dynamic Local	----	
101	11.11.11.1	0000.0000.1111	Static Local	----	
101	11.11.11.201	0000.4444.1010	Static Local	----	

Total number of entries are 7

VTEP5#show nvo vxlan nd-cache

VXLAN ND-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out
		Retries-Left		
201	2121::1	0000.0000.1111	Static Local	----
101	1111::10	0010.9400.0002	Dynamic Local	----
101	1111::1	0000.0000.1111	Static Local	----

Total number of entries are 3

VTEP5#show ipv4 route vrf L3VRF1

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP

O - OSPF, IA - OSPF inter area

N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2

E1 - OSPF external type 1, E2 - OSPF external type 2

i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,

ia - IS-IS inter area, E - EVPN,

v - vrf leaked

* - candidate default

IP Route Table for VRF "L3VRF1"

C 11.11.11.0/24 is directly connected, irb1001, 00:05:08

C 21.21.21.0/24 is directly connected, irb2001, 00:04:57

C 127.0.0.0/8 is directly connected, lo.L3VRF1, 00:07:30

Gateway of last resort is not set

VTEP5#show ipv6 route vrf L3VRF1

IPv6 Routing Table

Codes: K - kernel route, C - connected, S - static, D- DHCP, R - RIP,

O - OSPF, IA - OSPF inter area, E1 - OSPF external type 1,

E2 - OSPF external type 2, E - EVPN N1 - OSPF NSSA external type 1,

N2 - OSPF NSSA external type 2, i - IS-IS, B - BGP,
 v - vrf leaked
 Timers: Uptime

IP Route Table for VRF "L3VRF1"
 C ::1/128 via ::, lo.L3VRF1, 00:07:35
 C 1111::/24 via ::, irb1001, 00:05:13
 C 2121::/64 via ::, irb2001, 00:05:02
 C fe80::/64 via ::, irb2001, 00:05:02

```
VTEP5#show nvo vxlan l3vni-map
  L3VNI      L2VNI      IRB-interface
=====
  1000       101        irb1001
  1000       201        irb2001
```

VTEP5#show interface xe1 counters queue-stats
 E - Egress, I - Ingress, Q-Size is in bytes

Queue/Class-map	Q-Size	Tx pkts	Tx bytes	Dropped pkts
Dropped bytes				
q0	(E) 12517376 0	0	0	0
q1	(E) 12517376 0	0	0	0
q2	(E) 12517376 1170696	1224549062	0	0
q3	(E) 12517376 0	0	0	0
q4	(E) 12517376 0	0	0	0
q5	(E) 12517376 0	0	0	0
q6	(E) 12517376 0	0	0	0
q7	(E) 12517376 0	0	0	0

VTEP5#show qos-profile QUEUE_COS
 profile name: QUEUE_COS
 profile type: queue-color-to-cos
 profile attached to 1 instances
 configured mapping:

queue 2 color all cos 6

Detailed mapping:

INPUT	OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT
Queue	Color	COS	Queue	Color	COS
0	green	0	0	yellow	0
1	green	1	1	yellow	1
2	green	6	2	yellow	6
3	green	3	3	yellow	3
4	green	4	4	yellow	4
5	green	5	5	yellow	5
6	green	6	6	yellow	6

7	green	7		7	yellow	7		7	red	7																
VTEP5#show qos-profile DSCP_QUEUE																										
profile name: DSCP_QUEUE																										
profile type: dscp-to-queue																										
profile attached to 1 instances																										
configured mapping:																										
dscp 34 queue 2																										
Detailed mapping:																										
<table border="1"> <thead> <tr> <th>INPUT OUTPUT</th><th>OUTPUT INPUT </th><th>INPUT OUTPUT</th><th>OUTPUT</th><th>INPUT</th></tr> </thead> <tbody> <tr> <td>DSCP Queue</td><td>Color Out DSCP</td><td>DSCP Queue</td><td>Color Out DSCP</td><td>DSCP</td></tr> <tr> <td>Queue Color</td><td>Out DSCP</td><td>DSCP</td><td>Queue Color</td><td>Out DSCP</td><td>DSCP</td></tr> </tbody> </table>											INPUT OUTPUT	OUTPUT INPUT	INPUT OUTPUT	OUTPUT	INPUT	DSCP Queue	Color Out DSCP	DSCP Queue	Color Out DSCP	DSCP	Queue Color	Out DSCP	DSCP	Queue Color	Out DSCP	DSCP
INPUT OUTPUT	OUTPUT INPUT	INPUT OUTPUT	OUTPUT	INPUT																						
DSCP Queue	Color Out DSCP	DSCP Queue	Color Out DSCP	DSCP																						
Queue Color	Out DSCP	DSCP	Queue Color	Out DSCP	DSCP																					
0 green 32	green 0 48	6 16 green 2	48 green 16	32 4																						
1 green 33	green 1 49	6 17 green 2	49 green 17	33 4																						
2 green 34	green 2 50	6 18 green 2	50 green 18	34 2																						
3 green 35	green 3 51	6 19 green 2	51 green 19	35 4																						
4 yellow 36	green 4 52	6 20 green 2	52 yellow 20	36 4																						
5 green 37	green 5 53	6 21 green 2	53 green 21	37 4																						
6 yellow 38	green 6 54	6 22 green 2	54 yellow 22	38 4																						
7 green 39	green 7 55	6 23 green 2	55 green 23	39 4																						
8 green 40	green 8 56	7 24 green 3	56 green 24	40 5																						
9 green 41	green 9 57	7 25 green 3	57 green 25	41 5																						
10 green 42	green 10 58	7 26 green 3	58 green 26	42 5																						
11 green 43	green 11 59	7 27 green 3	59 green 27	43 5																						
12 green 44	yellow 12 60	7 28 green 3	60 yellow 28	44 5																						
13 green 45	green 13 61	7 29 green 3	61 green 29	45 5																						
14 green 46	yellow 14 62	7 30 green 3	62 yellow 30	46 5																						
15 green 47	green 15 63	7 31 green 3	63 green 31	47 5																						

 | | | | | | | | | |

Distributed Gateway

In distributed gateway approach, VTEP will act as default gateways for one or more VNIDs, Each VTEP having its own default gateway IP and MAC configuration for a given VNID.

IRB QoS Configuration for Distributed

Configure from Base Configuration-L2 VXLAN section, then configure below commands for centralized distributed approach.

Note: For L3 traffic, when l3vni is sent in the traffic, then dscp-to-queue qos profile mapped at tunnel ingress takes effect.

VTEP4

Unconfigure vnid 101 from nvo vxlan.

(config) #nvo vxlan irb	Enable VXLAN irb
(config) #ip vrf L3VRF1	Create mac routing/forwarding instance with L3VRF1 name and enter into vrf mode
(config-vrf) #rd 41000:11	Assign RD value
(config-vrf) # route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from vrf mode
(config) # interface irb2001	Configure IRB interface 2001
(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 21.21.21.1/24	Configure ip address
(config-if) ipv6 address 2121::1/64	Configure ipv6 address
(config-if) exit	Exit from interface config mode
(config) router bgp 5000	Enter into bgp router mode
(config-router) #address-family ipv4 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) #exit-address-family	Exit form address-family
(config-router) #address-family ipv6 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) #exit-address-family	Exit form address-family
(config) #nvo vxlan id 201 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF2	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb2001	Configure irb2001 under vxlan id 201
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.

(config) #qos remark dscp	Enable qos dscp remark for dscp-to-dscp mapping if required
(config) #qos profile dscp-to-queue DSCP_QUEUE	Configure qos profile to remark at vxlan ingress tunnel. Here dscp to <queue, dscp> is not applicable. I.e ingress remarking of dscp at the ingress tunnel is not applicable.
(config-ingress-dscp-map) #dscp 56 queue 6	Configure particular outer dscp value to queue value. Here classification at the ingress vtep is based on overlay dscp value
(config-ingress-dscp-map) #exit	Exit from qos profile config mode
(config-egress-dscp-map) #dscp 20 dscp 32	Configure particular dscp value to dscp value
(config-egress-dscp-map) #exit	Exit from qos profile config mode
(config) #qos profile queue-color-to-cos QUEUE_COS	Configure qos profile for remark at vxlan access-if
(config-egress-cos-map) #queue 6 cos 2	Configure particular queue value to COS value
(config-egress-cos-map) #exit	Exit from qos profile config mode
(config) #nvo vxlan tunnel qos-map-mode cos-dscp ingress DSCP_QUEUE	Map the qos profile to vxlan tunnel ingress
(config) #nvo vxlan access-if port-vlan xe3 20	Enter vxlan access-if mode
(config-nvo-acc-if) #map qos-profile queue-color-to-cos QUEUE_COS	Map qos profile
(config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration
(config-nvo-acc-if) #end	Exit from global configuration mode

VTEP5

Unconfigure vnid 201 from nvo vxlan.

(config) #nvo vxlan irb	Enable VXLAN IRB
(config) #ip vrf L3VRF1	Create mac routing/forwarding instance with L3VRF1 name and enter into vrf mode
(config-vrf) #rd 51000:11	Assign RD value
(config-vrf) # route-target both 100:100	Assign route-target value for same for import and export.
(config-vrf) # l3vni 1000	Configure L3VNI as 1000 for L3VRF1
(config-vrf) #exit	Exit from vrf mode
(config) # interface irb1001	Configure IRB interface 1001
(config-if) ip vrf forwarding L3VRF1	Configure L3VRF1
(config-if) ip address 11.11.11.1/24	Configure ip address
(config-if) ipv6 address 1111::1/64	Configure ipv6 address
(config-if) exit	Exit from interface config mode
(config) router bgp 5000	Enter into bgp router mode
(config-router) #address-family ipv4 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) #exit-address-family	Exit form address-family

(config-router) #address-family ipv6 vrf L3VRF1	Enter into address-family mode for L3VRF1
(config-router-af) #redistribute connected	Redistribute connected
(config-router-af) #exit-address-family	Exit from address-family
(config) # nvo vxlan id 101 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp L2VRF1	Assign vrf for evpn-bgp to carry EVPN route
(config-nvo) # evpn irb1001	Configure irb1001 under vxlan id 101
(config-nvo) #exit	Exit from VXLAN tenant mode and enter into configuration mode.
(config) #qos profile dscp-to-queue DSCP_QUEUE	Configure qos profile for dscp to queue for ingress traffic
(config-ingress-dscp-map) # dscp 20 queue 4	Configure particular dscp value to queue value
(config) #interface irb1001	Enter IRB L3 interface
(config-irb-if) #qos map-profile dscp-to-queue DSCP_QUEUE	Map qos profile
(config-irb-if) #commit	Commit the candidate configuration to the running configuration
(config-irb-if) #end	Exit from global conf mode

Validations

Send traffic from TS1-11 to VTEP5 access-if with dscp value 20 COS value 1(vlan10) and verify traffic received at TS2-21 with dscp value 32 and COS value 2(vlan20) at the VTEP4 access-if.

VTEP5

```
VTEP5#show running-config qos
qos enable
!
qos profile dscp-to-queue DSCP_QUEUE
  dscp 20 queue 4
!
!
!
!
interface irb1001
  qos map-profile dscp-to-queue DSCP_QUEUE
!
VTEP5#show run nvo vxlan
!
nvo vxlan enable
!
nvo vxlan irb
!
evpn vxlan multihoming enable
!
```

```

nvo vxlan vtep-ip-global 5.5.5.5
!
nvo vxlan id 101 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp L2VRF1
  evpn irb1001
  vni-name VNI-101
!
nvo vxlan id 201 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp L2VRF2
  vni-name VNI-201
!
nvo vxlan access-if port-vlan xe1 10
  map vnid 101
  mac 0000.4444.1010 ip 11.11.11.201
!
!
```

VTEP5#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
5.5.5.5	2.2.2.2	Installed	00:29:54	00:29:54
5.5.5.5	4.4.4.4	Installed	00:29:54	00:29:54
5.5.5.5	1.1.1.1	Installed	00:29:54	00:29:54

Total number of entries are 3

VTEP5#show nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port
 AC - Access Port
 (u) - Untagged

VNID Src-Addr	VNI-Name Dst-Addr	VNI-Type	Type	Interface	ESI	VLAN	DF-Status
101 5.5.5.5	VNI-101 2.2.2.2	L2	NW	----	-----	-----	-----
101 5.5.5.5	VNI-101 4.4.4.4	L2	NW	----	-----	-----	-----
101 5.5.5.5	VNI-101 1.1.1.1	L2	NW	----	-----	-----	-----
101 ----	VNI-101 ----	--	AC	xe1	--- Single Homed Port ---	10	-----
201 5.5.5.5	VNI-201 2.2.2.2	L2	NW	----	-----	-----	-----
201 5.5.5.5	VNI-201 4.4.4.4	L2	NW	----	-----	-----	-----
201 5.5.5.5	VNI-201 1.1.1.1	L2	NW	----	-----	-----	-----
1000 5.5.5.5	----	L3	NW	----	-----	-----	-----

Total number of entries are 8

VTEP5#show nvo vxlan arp-cache
VXLAN ARP-CACHE Information

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
201	21.21.21.51	0000.2222.1020	Static Remote	----	
201	21.21.21.1	3c2c.991a.da7a	Static Remote	----	
201	21.21.21.101	0000.5555.1020	Static Remote	----	
101	11.11.11.51	0000.2222.1010	Static Remote	----	
101	11.11.11.1	04f8.f82f.8eee	Static Local	----	
101	11.11.11.201	0000.4444.1010	Static Local	----	

Total number of entries are 6

VTEP5#show nvo vxlan nd-cache
VXLAN ND-CACHE Information

VNID	Ip-Addr	Mac-Addr	Type	Age-Out
Retries-Left				
201	2121::1	3c2c.991a.da7a	Static Remote	----
101	1111::1	04f8.f82f.8eee	Static Local	----

Total number of entries are 2

VTEP5#show nvo vxlan l3vni-map

L3VNI	L2VNI	IRB-interface
1000	101	irb1001

VTEP5#show ipv4 route vrf L3VRF1

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
ia - IS-IS inter area, E - EVPN,
v - vrf leaked
* - candidate default

IP Route Table for VRF "L3VRF1"

B	4.4.4.4/32 [0/0] is directly connected, tunvxlan1000, 00:04:09
C	11.11.11.0/24 is directly connected, irb1001, 00:02:38
B	21.21.21.0/24 [200/0] via 4.4.4.4 (recursive is directly connected, tunvxlan1000), 00:04:09
C	127.0.0.0/8 is directly connected, lo.L3VRF1, 00:04:46

Gateway of last resort is not set

VTEP5#show ipv6 route vrf L3VRF1

IPv6 Routing Table

Codes: K - kernel route, C - connected, S - static, D- DHCP, R - RIP,
O - OSPF, IA - OSPF inter area, E1 - OSPF external type 1,
E2 - OSPF external type 2, E - EVPN N1 - OSPF NSSA external type 1,

N2 - OSPF NSSA external type 2, i - IS-IS, B - BGP,
v - vrf leaked
Timers: Uptime

IP Route Table for VRF "L3VRF1"

C	::1/128 via ::, lo.L3VRF1, 00:04:50
B	::ffff:404:404/128 [0/0] via ::, tunvxlan1000, 00:04:13
C	1111::/64 via ::, irb1001, 00:02:42
B	2121::/64 [200/0] via ::ffff:404:404 (recursive via ::, unknown), 00:04:13
C	fe80::/64 via ::, irb1001, 00:02:42

VTEP5#show interface ce53 counter queue-stats

E - Egress, I - Ingress, Q-Size is in bytes

Queue/Class-map	Q-Size	Tx pkts	Tx bytes	Dropped pkts
Dropped bytes				
q0	(E) 50069504 0	0	0	0
q1	(E) 50069504 0	0	0	0
q2	(E) 50069504 0	0	0	0
q3	(E) 50069504 0	0	0	0
q4	(E) 50069504 498796	698314400	0	0
q5	(E) 50069504 0	0	0	0
q6	(E) 50069504 0	0	0	0
q7	(E) 50069504 0	0	0	0

VTEP5#show qos-profile DSCP_QUEUE

profile name: DSCP_QUEUE

profile type: dscp-to-queue

profile attached to 1 instances

configured mapping:

dscp 20 queue 4

Detailed mapping:

INPUT	OUTPUT	INPUT	OUTPUT	INPUT
OUTPUT	INPUT	OUTPUT	OUTPUT	INPUT
DSCP	Queue	Color	Out DSCP	DSCP
Queue	Color	Out DSCP	DSCP	Queue
0 green	32	green 0 48	6	16 green 2 48
1 green	33	green 1 49	6	17 green 2 49
2 green	34	green 2 50	6	18 green 2 50
3 green	35	green 3 51	6	19 green 2 51
				green 16 32
				green 17 33
				green 18 34
				green 19 35
				4

4 yellow	0 36	green 52	4 6	20 green 52	4 52	yellow 20	36	4
5 green	0 37	green 53	5 6	21 green 53	2 53	green 21	37	4
6 yellow	0 38	green 54	6 6	22 green 54	2 54	yellow 22	38	4
7 green	0 39	green 55	7 6	23 green 55	2 55	green 23	39	4
8 green	1 40	green 56	8 7	24 green 56	3 56	green 24	40	5
9 green	1 41	green 57	9 7	25 green 57	3 57	green 25	41	5
10 green	1 42	green 58	10 7	26 green 58	3 58	green 26	42	5
11 green	1 43	green 59	11 7	27 green 59	3 59	green 27	43	5
12 green	1 44	yellow 60	12 7	28 green 60	3 60	yellow 28	44	5
13 green	1 45	green 61	13 7	29 green 61	3 61	green 29	45	5
14 green	1 46	yellow 62	14 7	30 green 62	3 62	yellow 30	46	5
15 green	1 47	green 63	15 7	31 green 63	3 63	green 31	47	5

VTEP5#show qos-profile interface irb1001

profile name: DSCP_QUEUE

profile type: dscp-to-queue (Ingress)

mapping:

INPUT	OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT	INPUT		
OUTPUT		INPUT		OUTPUT		INPUT		
DSCP	Queue	Color	Out DSCP	DSCP	Queue	DSCP		
Queue	Color	Out DSCP		DSCP	Color	Out DSCP		
0 green	0 32	green 48	0 6	16 green 48	2 48	green 16	32	4
1 green	0 33	green 49	1 6	17 green 49	2 49	green 17	33	4
2 green	0 34	green 50	2 6	18 green 50	2 50	green 18	34	4
3 green	0 35	green 51	3 6	19 green 51	2 51	green 19	35	4
4 yellow	0 36	green 52	4 6	20 green 52	4 52	yellow 20	36	4
5 green	0 37	green 53	5 6	21 green 53	2 53	green 21	37	4
6 yellow	0 38	green 54	6 6	22 green 54	2 54	yellow 22	38	4
7 green	0 39	green 55	7 6	23 green 55	2 55	green 23	39	4

8 green	1 40	green 56	8 9 green	7 57	24 green 25 green	3 3 56 57	green green green	24 25 26 27	40 41 42 43	5
10 green	1 42	green 58	10 11 green	7 59	26 green 27 green	3 3 58 59	green green green	26 27 28	42 43 44	5
12 green	1 44	yellow 60	12 13 green	7 61	28 green 29 green	3 3 60 61	yellow green	28 29	44 45	5
14 green	1 46	yellow 62	14 15 green	7 63	30 green 31 green	3 3 62 63	yellow green	30 31	46 47	5

VTEP4

```

VTEP4#show run qos
qos enable
qos remark dscp
!
!
qos profile queue-color-to-cos QUEUE_COS
queue 6 color all cos 2
!
qos profile dscp-to-queue DSCP_QUEUE
dscp 56 queue 6
!
!
!
!
VTEP4#show run nvo vxlan
!
nvo vxlan enable
!
nvo vxlan irb
!
evpn vxlan multihoming enable
!
nvo vxlan vtep-ip-global 4.4.4.4
!
nvo vxlan tunnel qos-map-mode cos-dscp ingress DSCP_QUEUE
!
nvo vxlan id 101 ingress-replication inner-vid-disabled
vxlan host-reachability-protocol evpn-bgp L2VRF1
vni-name VNI-101
!
nvo vxlan id 201 ingress-replication inner-vid-disabled
vxlan host-reachability-protocol evpn-bgp L2VRF2
evpn irb2001

```

```
vni-name VNI-201
!
nvo vxlan access-if port-vlan xe3 20
map vnid 201
mac 0000.5555.1020 ip 21.21.21.101
map qos-profile queue-color-to-cos QUEUE_COS
!
```

VTEP4#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
4.4.4.4	2.2.2.2	Installed	00:28:32	00:28:32
4.4.4.4	1.1.1.1	Installed	00:28:38	00:28:38
4.4.4.4	5.5.5.5	Installed	00:28:31	00:28:31

Total number of entries are 3

VTEP4#show nvo vxlan

VXLAN Information

=====

```
Codes: NW - Network Port
      AC - Access Port
      (u) - Untagged
```

VNID Src-Addr	VNI-Name Dst-Addr	VNI-Type	Type	Interface	ESI	VLAN	DF-Status
101 4.4.4.4	VNI-101 2.2.2.2	L2	NW	----	----	-----	-----
101 4.4.4.4	VNI-101 1.1.1.1	L2	NW	----	----	-----	-----
101 4.4.4.4	VNI-101 5.5.5.5	L2	NW	----	----	-----	-----
201 4.4.4.4	VNI-201 2.2.2.2	L2	NW	----	----	-----	-----
201 4.4.4.4	VNI-201 1.1.1.1	L2	NW	----	----	-----	-----
201 4.4.4.4	VNI-201 5.5.5.5	L2	NW	----	----	-----	-----
201 ----	VNI-201 ----	--	AC	xe3	--- Single Homed Port ---	20	-----
1000 4.4.4.4	----	L3	NW	----	----	-----	-----
4.4.4.4	5.5.5.5						

Total number of entries are 8

VTEP4#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
201	21.21.21.51	0000.2222.1020	Static Remote	----	
201	21.21.21.1	3c2c.991a.da7a	Static Local	----	

```

201      21.21.21.101      0000.5555.1020 Static Local   ----
101      11.11.11.51       0000.2222.1010 Static Remote  ----
101      11.11.11.1        04f8.f82f.8eee Static Remote  ----
101      11.11.11.201      0000.4444.1010 Static Remote  ----
Total number of entries are 6

```

VTEP4#show nvo vxlan nd-cache

VXLAN ND-CACHE Information

VNID	Ip-Addr	Mac-Addr	Type	Age-Out
Retries-Left				
201	2121::1	3c2c.991a.da7a	Static Local	----
101	1111::1	04f8.f82f.8eee	Static Remote	----
Total number of entries are 2				
VTEP4#show ipv4 route vrf L3VRF1				
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP O - OSPF, IA - OSPF inter area N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2 E1 - OSPF external type 1, E2 - OSPF external type 2 i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area, E - EVPN, v - vrf leaked * - candidate default				

IP Route Table for VRF "L3VRF1"

```

B          5.5.5.5/32 [0/0] is directly connected, tunvxlan1000, 00:01:03
B          11.11.11.0/24 [200/0] via 5.5.5.5 (recursive is directly connected,
tunvxlan1000), 00:01:03
C          21.21.21.0/24 is directly connected, irb2001, 00:03:31
C          127.0.0.0/8 is directly connected, lo.L3VRF1, 00:15:13

```

Gateway of last resort is not set

VTEP4#show ipv6 route vrf L3VRF1

IPv6 Routing Table

```

Codes: K - kernel route, C - connected, S - static, D- DHCP, R - RIP,
O - OSPF, IA - OSPF inter area, E1 - OSPF external type 1,
E2 - OSPF external type 2, E - EVPN  N1 - OSPF NSSA external type 1,
N2 - OSPF NSSA external type 2, i - IS-IS, B - BGP,
v - vrf leaked

```

Timers: Uptime

IP Route Table for VRF "L3VRF1"

```

C      ::1/128 via ::, lo.L3VRF1, 00:15:18
B      ::ffff:505:505/128 [0/0] via ::, tunvxlan1000, 00:01:08
B      1111::/64 [200/0] via ::ffff:505:505 (recursive via ::, unknown), 00:01:08
C      2121::/64 via ::, irb2001, 00:03:36
C      fe80::/64 via ::, irb2001, 00:03:36

```

VTEP4#show nvo vxlan l3vni-map

L3VNI	L2VNI	IRB-interface
=====		

1000 201 irb2001

```
VTEP4#show interface xe3 counter queue-stats
E - Egress, I - Ingress, Q-Size is in bytes
```

Dropped bytes	Queue/Class-map	Q-Size	Tx pkts	Tx bytes	Dropped pkts	
q0	(E)	12517376 0	0	0	0	0
q1	(E)	12517376 0	0	0	0	0
q2	(E)	12517376 0	0	0	0	0
q3	(E)	12517376 0	0	0	0	0
q4	(E)	12517376 0	0	0	0	0
q5	(E)	12517376 0	0	0	0	0
q6	(E)	12517376 2219303		3209162748	0	0
q7	(E)	12517376 0	0	0	0	0

```
VTEP4#show qos-profile QUEUE_COS
```

```
profile name: QUEUE_COS
profile type: queue-color-to-cos
profile attached to 1 instances
configured mapping:
```

```
queue 6 color all cos 2
```

```
Detailed mapping:
```

INPUT	OUTPUT	INPUT	OUTPUT	INPUT	OUTPUT
Queue	Color	COS	Queue	Color	COS
0	green	0	0	yellow	0
1	green	1	1	yellow	1
2	green	2	2	yellow	2
3	green	3	3	yellow	3
4	green	4	4	yellow	4
5	green	5	5	yellow	5
6	green	2	6	yellow	2
7	green	7	7	yellow	7

```
VTEP4#show qos-profile DSCP_QUEUE
```

```
profile name: DSCP_QUEUE
profile type: dscp-to-queue
profile attached to 1 instances
configured mapping:
```

```
dscp 56 queue 6
```

```
Detailed mapping:
```

INPUT	OUTPUT	INPUT	OUTPUT	INPUT
OUTPUT	INPUT	OUTPUT	OUTPUT	INPUT

DSCP	Queue	Color	Out DSCP	DSCP	Queue	Color	Out DSCP	DSCP
Queue	Color	Out DSCP	DSCP	Queue	Color	Out DSCP	DSCP	
0 green	0 32	green 48	0 6	16 green	2 48	green 16	32	4
1 green	0 33	green 49	1 6	17 green	2 49	green 17	33	4
2 green	0 34	green 50	2 6	18 green	2 50	green 18	34	4
3 green	0 35	green 51	3 6	19 green	2 51	green 19	35	4
4 yellow	0 36	green 52	4 6	20 green	2 52	yellow 20	36	4
5 green	0 37	green 53	5 6	21 green	2 53	green 21	37	4
6 yellow	0 38	green 54	6 6	22 green	2 54	yellow 22	38	4
7 green	0 39	green 55	7 6	23 green	2 55	green 23	39	4
8 green	1 40	green 56	8 6	24 green	3 56	green 24	40	5
9 green	1 41	green 57	9 7	25 green	3 57	green 25	41	5
10 green	1 42	green 58	10 7	26 green	3 58	green 26	42	5
11 green	1 43	green 59	11 7	27 green	3 59	green 27	43	5
12 green	1 44	yellow 60	12 7	28 green	3 60	yellow 28	44	5
13 green	1 45	green 61	13 7	29 green	3 61	green 29	45	5
14 green	1 46	yellow 62	14 7	30 green	3 62	yellow 30	46	5
15 green	1 47	green 63	15 7	31 green	3 63	green 31	47	5

VTEP4#show qos-profile interface irb2001

profile name: default

profile type: dscp-to-queue (Ingress)

mapping:

INPUT	OUTPUT	INPUT	OUTPUT	INPUT
OUTPUT	INPUT	OUTPUT	OUTPUT	INPUT
DSCP	Queue	Color	Out DSCP	DSCP
Queue	Color	Out DSCP	DSCP	Queue
0 green	0 32	green 48	0 6	16 green
				2 48
				green 16
				32
				4

1 green	0 33	green 49	1 6	17 green 49	2 49	green 17	33	4
2 green	0 34	green 50	2 6	18 green 50	2 50	green 18	34	4
3 green	0 35	green 51	3 6	19 green 51	2 51	green 19	35	4
4 yellow	0 36	green 52	4 6	20 green 52	2 52	yellow 20	36	4
5 green	0 37	green 53	5 6	21 green 53	2 53	green 21	37	4
6 yellow	0 38	green 54	6 6	22 green 54	2 54	yellow 22	38	4
7 green	0 39	green 55	7 6	23 green 55	2 55	green 23	39	4
8 green	1 40	green 56	8 7	24 green 56	3 56	green 24	40	5
9 green	1 41	green 57	9 7	25 green 57	3 57	green 25	41	5
10 green	1 42	green 58	10 7	26 green 58	3 58	green 26	42	5
11 green	1 43	green 59	11 7	27 green 59	3 59	green 27	43	5
12 green	1 44	yellow 60	12 7	28 green 60	3 60	yellow 28	44	5
13 green	1 45	green 61	13 7	29 green 61	3 61	green 29	45	5
14 green	1 46	yellow 62	14 7	30 green 62	3 62	yellow 30	46	5
15 green	1 47	green 63	15 7	31 green 63	3 63	green 31	47	5

CHAPTER 7 Single Home VxLAN IRB with OSPF or ISIS

Overview

Single Home Virtual Extensible LAN (VxLAN) with Integrated Routing (IRB) using Open Shortest Path First (OSPF) and Intermediate System to Intermediate System (ISIS) protocols provides the solution for connecting and managing virtual networks within a data center or network infrastructure.

This feature offers a solution for networks where the interconnection of VLANs is required. These protocols can be configured on IRB interfaces within layer 3 switches or routers. This configuration enables dynamic routing, facilitating the exchange of routing information with other devices in the network. By assigning IP addresses to the IRB interfaces, they serve as the default gateways for devices within the respective VLANs.

Both OSPF and ISIS routing updates are dynamically exchanged over IRB interfaces, ensuring up-to-date routing tables and optimized traffic routing across different VLANs and networks.

This feature offers flexibility in configuring network topologies, and ensures compatibility and interoperability within diverse network environments.

Feature Characteristics

The OSPF and ISIS support over the IRB Interface feature has the following characteristics:

- Enables the control of Receive (RX)/ Transmit (TX) of OSPF and ISIS packets on IRB interfaces, providing effective management of IRB interfaces interactions with OSPF and ISIS for optimized network communication and routing.
- IRB interfaces process configured MTU size packets.
- Maintains consistency in CLI commands with SVI interfaces for OSPF and ISIS configurations, simplifying network management tasks.

Benefits

The OSPF and ISIS support over the IRB Interface has the following benefits:


- Enables seamless inter-subnet communication across different VNIDs and subnets within the same customer network.
- Promotes seamless connectivity between devices, irrespective of whether they are connected through IRB or SVI interfaces, and simplifies network management.
- The network gains greater adaptability to various scenarios and evolving requirements, offering greater versatility in its operations.

Prerequisites

- Router must be up and running.
- Maintain synchronization with VRF changes by performing IRB shut/no shut actions when specific events occur within the IPVRF. These events may involve adding or removing Route Targets (RTs), updating Route Distinguishers (RDs), or modifying Layer 3 Virtual Network Identifiers (L3VNIs).

Topology for OSPF

The network topology includes various network elements such as routers, customer edge (CE) devices, Service Aggregator (SA) devices, and Provider Edge (PE) routers. The feature enables OSPF on the IRB interfaces, allowing for efficient routing and communication between network devices within the topology.



Configuration

Perform the following configurations to set up different interfaces, routing protocols, and BGP parameters to enable VXLAN, IRB, and EVPN functionality in the network.

Configure OSPF

PE1

PE1 (Config) # terminal	Enters the configuration mode.
PE1 (config) #interface sa1	Configure the sa1 interface as a network interface.
PE1 (config-if) # ip address 10.1.1.1/24	Assigns an IP address to the sa1 interface with a subnet mask of /24.
PE1 (config-if) # ip ospf cost 10	Configures the OSPF cost for the sa1 interface, setting it to 10.
PE1 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the sa1 interface.
PE1 (config) #interface xe1	Enters the interface xe1 mode.
PE1 (config-if) # static-channel-group 1	Assigns the static channel group 1 to the xe1 interface.
PE1 (config-irb-if) #interface lo	Configures the loopback (lo) interface.
PE1 (config-if) # ip address 1.1.1.1/32 secondary	Assigns the primary IP address 1.1.1.1/32 to the loopback interface and specifies it as secondary.

PE1(config)#router ospf 1	Enters the OSPF configuration mode for OSPF process 1.
PE1(config-router)# ospf router-id 1.1.1.1	Sets the OSPF router ID to 1.1.1.1 for OSPF process 1.
PE1(config-router)# network 1.1.1.1/32 area 0.0.0.0	Advertises the network 1.1.1.1/32 into OSPF area 0.0.0.0.
PE1(config-router)# network 10.1.1.0/24 area 0.0.0.0	Advertises the network 10.1.1.0/24 into OSPF area 0.0.0.0.
PE1(config)#nvo vxlan enable	Enables the VXLAN feature on the device.
PE1(config)#nvo vxlan irb	Enables VXLAN IRB functionality.
PE1(config-vrf)#mac vrf L2VRF1	Configures a MAC VRF named L2VRF1.
PE1(config-vrf)# rd 1.1.1.1:11	Sets the Route Distinguisher (RD) to 1.1.1.1:11 for the VRF.
PE1(config-vrf)# route-target both 9.9.9.9:100	Configures both import and export route targets for the VRF.
PE1(config-vrf)#ip vrf L3VRF1	Configures an IP VRF named L3VRF1.
PE1(config-vrf)# rd 51000:11	Sets the RD value to 51000:11 for the L3VRF1.
PE1(config-vrf)# route-target both 100:100	Configures both import and export route targets for L3VRF1.
PE1(config-vrf)# l3vni 1000	Configures the L3 Virtual Network Identifier (L3VNI) with the value 1000.
PE1(config)#interface irb1001	Configures the IRB interface for L3VRF1.
PE1(config-irb-if)# ip vrf forwarding L3VRF1	Assigns the L3VRF1 to the IRB interface.
PE1(config-irb-if)# ip address 11.11.11.1/24	Assigns an IP address 11.11.11.1/24 to the IRB interface.
PE1(config-irb)#interface irb2001	Configures the IRB interface for IPv6 in L3VRF1.
PE1(config-irb-if)# ip vrf forwarding L3VRF1	Assigns the L3VRF1 to the IPv6 IRB interface.
PE1(config-irb-if)# ipv6 address 2001::1/64	Assigns an IP address 11.11.11.1/24 to the IRB interface.
PE1(config-irb-if)#mtu 9000	Sets the Maximum Transmission Unit (MTU) for this IRB interface to 9000 bytes.
PE1(config-router)#router ospf 2 L3VRF1	Configures OSPF on the L3VRF1.
PE1(config-router)# network 11.11.11.0/24 area 0.0.0.0	Advertises the network 11.11.11.0/24 into OSPF area 0.0.0.0.
PE1(config-router)#router ipv6 vrf ospf L3VRF1	Configures OSPFv3 on the L3VRF1.
PE1(config-router)# router-id 1.1.1.1	Configures the router ID as 1.1.1.1.
PE1(config-irb)#interface irb2001	Configures the IPv6 IRB interface.
PE1(config-irb-if)# ipv6 router ospf area 0.0.0.0 tag L3VRF1 instance-id 0	Attaches the OSPFv3 instance ID to the IPv6 IRB interface.
PE1(config)#nvo vxlan vtep-ip-global 1.1.1.1	Configures the global VTEP IP address as 1.1.1.1.
PE1(config)#nvo vxlan id 101 ingress-replication	Configures the VXLAN ID as 101 for ingress replication.
PE1(config-nvo)# vxlan host-reachability-protocol evpn-bgp L2VRF1	Maps the EVPN-BGP host reachability protocol to L2VRF1.
PE1(config-nvo)# evpn irb1001	Maps the IRB interface 1001 to EVPN.
PE1(config-nvo)# vni-name VNI-101	Configures the VNI name as VNI-101.
PE1(config)#nvo vxlan id 2001 ingress-replication	Configures the VXLAN ID as 2001 for ingress replication.
PE1(config-nvo)# vxlan host-reachability-protocol evpn-bgp L2VRF1	Maps the EVPN-BGP host reachability protocol to L2VRF1.

PE1(config-nvo) # evpn irb2001	Maps the IPv6 IRB interface to EVPN.
PE1(config)#interface xe2	Configures the xe2 interface.
PE1(config-if) # switchport	Configures the port as a Layer 2 (L2) switchport.
PE1(config-if) # load-interval 30	Configures the load-interval of 30 minutes for monitoring traffic on the xe2 interface.
PE1(config)#nvo vxlan access-if port-vlan xe2 100	Configures a VxLAN network virtualization overlay (NVO) on the interface xe2 with VLAN ID 100
PE1(config-nvo-acc-if) # map vnid 101	Maps VLAN 100 to the VxLAN Network Identifier (VNID) 101.
PE1(config-nvo-acc-if) #nvo vxlan access-if port-vlan xe2 2001	Configures another VxLAN NVO on the same interface xe2, but this time with VLAN ID 2001
PE1(config-nvo-acc-if) # map vnid 2001	Maps VLAN 2001 to a different VxLAN VNID.
PE1(config-router) #router bgp 100	Configures the BGP process with AS number 100.
PE1(config-router) # bgp router-id 1.1.1.1	Assigns the router ID as 1.1.1.1 for the BGP instance.
PE1(config-router) # neighbor 4.4.4.4 remote-as 100	Configures neighbor 4.4.4.4 with a remote AS number of 100.
PE1(config-router) # neighbor 4.4.4.4 update-source lo	Configures the update source for neighbor 4.4.4.4 to be the loopback interface.
PE1(config-router) # neighbor 4.4.4.4 advertisement-interval 0	Configures the advertisement interval for neighbor 4.4.4.4 as 0.
PE1(config-router) # address-family l2vpn evpn	Configures the address-family for L2VPN EVPN.
PE1(config-router-af) # neighbor 4.4.4.4 activate	Activates the neighbor for the L2VPN EVPN address-family.
PE1(config-router-af) # exit-address-family	Exits from the address family configuration.
PE1(config-router) # address-family ipv4 vrf L3VRF1	Configures the IPv4 address-family for VRF L3VRF1.
PE1(config-router-af) # redistribute connected	Configures the redistribution of connected routes within the IPv4 address-family.
PE1(config-router-af) # exit-address-family	Exits the IPv4 address-family configuration.
PE1(config-router) # address-family ipv6 vrf L3VRF1	Configures the IPv6 address-family for VRF L3VRF1.
PE1(config-router-af) # redistribute connected	Configures the redistribution of connected routes within the IPv6 address-family.
PE1(config-router-af) # exit-address-family	Exits the IPv6 address-family configuration.

PE5

PE5#configure terminal	Enters the configuration mode
PE5(config)#interface sa1	Configure the sa1 interface as a network interface.
PE5(config-if) # ip address 10.1.1.1/24	Assigns an IP address to the sa1 interface with a subnet mask of /24.
PE5(config-if) # ip ospf cost 10	Configures the OSPF cost for the sa1 interface, setting it to 10.
PE5(config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the sa1 interface.
PE5(config)#interface xe1	Configure network interface towards PE6.
PE5(config-if) # static-channel-group 1	Assigns the static channel group 1 to the xe1 interface.

PE5(config)#interface xe5	configures the xe5 interface.
PE5(config-if)#ip address 30.1.1.1/24	Assigns the primary IP address 1.1.1.1/32 to the loopback interface and specifies it as secondary.
PE5(config)#ip ospf cost 10	Configures the OSPF cost for the xe5 interface, setting it to 10.
PE5(config-router)# ospf router-id 1.1.1.1	Assigns an IP address (30.1.1.1) to the xe5 interface with a subnet mask of /24.
PE5(config)#load-interval 30	Configures the load-interval for monitoring traffic on the xe5 interface.
PE5(config)#router ospf 1	Enters the OSPF configuration mode for OSPF process 1.
PE5(config-router)# network 30.1.1.0/24 area 0.0.0.0	Advertises the network 30.1.1.0/24 into OSPF area 0.0.0.0.
PE5(config-router)# network 10.1.1.0/24 area 0.0.0.0	Advertises the network 10.1.1.0/24 into OSPF area 0.0.0.0.

PE3

PE3#configure terminal	Enters the configuration mode
PE3(config)#interface ce30	Configure the ce30 interface as a network interface.
PE3(config-if)# ip address 40.1.1.2/24	Assigns an IP address to the ce30 interface with a subnet mask of /24.
PE3(config-if)# ip ospf cost 10	Configures the OSPF cost for the sa1 interface, setting it to 10.
PE3(config-if)# load-interval 30	Configures the load-interval for monitoring traffic on the sa1 interface.
PE3(config)#interface lo	Configure the loopback interface.
PE3(config-if)#ip address 4.4.4.4/32 secondary	Assign an secondary IP to an loopback interface.
PE3(config)#ip ospf cost 10	Configures the OSPF cost for the xe7interface, setting it to 10.
PE3(config)#load-interval 30	Configures the load-interval for monitoring traffic on the xe5 interface.
PE3(config)#router ospf 1	Enters the OSPF configuration mode for OSPF process 1.
PE3(config-router)# ospf router-id 4.4.4.4	Configures the router id to an ospf instance.
PE3(config-router)# network 4.4.4.4/32 area 0.0.0.0	Advertises the loopback address.
PE3(config-router)# network 40.1.1.0/24 area 0.0.0.0	Advertises the network interface IP address.
PE3(config)#nvo vxlan enable	Enables VXLAN on the device, allowing it to participate in VXLAN networks.
PE3(config)#nvo vxlan irb	Enables VXLAN IRB functionality, that allows routing between VXLAN and non-VXLAN networks.
PE3(config-vrf)#mac vrf L2VRF1	Configures a L2 MAC VRF instance named L2VRF1, which is a logical network segment for L2 traffic isolation.
PE3(config-vrf)# rd 4.4.4.4:11	Configures a RD for the L2VRF1, with the value 4.4.4.4:11.
PE3(config-vrf)# route-target both 9.9.9.9:100	Configures a route target for the VRF.

PE3 (config-vrf) # ip vrf L3VRF1	Configures a L3 VRF named L3VRF1.
PE3 (config-vrf) # rd 56000:11	Configures a RD for the L3VRF1, with the value 56000:11.
PE3 (config-vrf) # route-target both 100:100	Configures a route target for the VRF.
PE3 (config-vrf) # l3vni 1000	Configures a L3VNI with the ID 1000 for the VRF.
PE3 (config) # interface irb1001	Configures the IRB interface with the ID 1001.
PE3 (config-irb-if) # ip vrf forwarding L3VRF1	Associates the IRB interface with the L3VRF1, ensuring that traffic from this interface is isolated within that VRF.
PE3 (config-irb-if) # ip address 12.12.12.1/24	Assigns an IP address 12.12.12.1 with a subnet mask of /24 to the IRB interface, enabling it for L3 routing.
PE3 (config-irb-if) # mtu 1500	Configures the MTU for the interface irb1001 to 1500 bytes.
PE3 (config) # interface irb2001	Configures another IRB interface with the ID 2001.
PE3 (config-irb-if) # ip vrf forwarding L3VRF1	Associates the IRB interface with the L3VRF1.
PE3 (config-irb-if) # ipv6 address 2002::1/64	Assigns an IPv6 address 2002::1 with a subnet mask of /64 to the IRB interface, enabling it for IPv6 routing.
PE3 (config-irb-if) # mtu 1500	Configures the MTU for the interface irb2001 to 1500 bytes.
PE3 (config-router) # router ospf 2 L3VRF1	Configures the OSPF routing process on OSPF instance 2 for the L3VRF1.
PE3 (config-router) # network 12.12.12.0/24 area 0.0.0.0	Advertises the network 12.12.12.0/24 to OSPF area 0.0.0.0.
PE3 (config-router) # router ipv6 vrf ospf L3VRF1	Configures the OSPFv3 routing process on OSPFv3 instance for the L3VRF1.
PE3 (config-router) # router-id 4.4.4.4	Sets the router ID for the OSPF/OSPFv3 instances to 4.4.4.4.
PE3 (config) # nvo vxlan vtep-ip-global 4.4.4.4	Configures the global VTEP IP address as 4.4.4.4 for VXLAN.
PE3 (config) # nvo vxlan id 102 ingress-replication	Configures the VXLAN with VNI ID 102 for ingress replication.
PE3 (config-nvo) # vxlan host-reachability-protocol evpn-bgp L2VRF1	Maps the VXLAN configuration with the EVPN-BGP protocol and associates it with the L2VRF1.
PE3 (config-nvo) # evpn irb1001	Maps the IRB interface irb1001 to the VXLAN.
PE3 (config-nvo) # vni-name VNI-101	Configures the VNI name as VNI-101.
PE3 (config) # nvo vxlan id 2002 ingress-replication	Configures another VXLAN with VNI ID 2002 for ingress replication.
PE3 (config-nvo) # vxlan host-reachability-protocol evpn-bgp L2VRF1	Maps the VXLAN configuration with the EVPN-BGP protocol and associates it with the L2VRF1.
PE3 (config-nvo) # evpn irb2001	Maps the IPv6 IRB interface irb2001 to the VXLAN.
PE3 (config) # interface sa4	Configures interface sa4.
PE3 (config-if) # switchport	Configures the interface as a switchport.
PE3 (config-if) # load-interval 30	Sets the load interval for the interface to 30 seconds.
PE3 (config-if) # mtu 1500	Configures the MTU for the interface to 1500 bytes.
PE3 (config) # interface xe1	Configures interface xe1.
PE3 (config-if) # static-channel-group 4	Assigns a static channel group to interface xe1.
PE3 (config) # nvo vxlan access-if port-vlan sa4 100	Configures a VxLAN nVVO on the interface xe2 with VLAN ID 100

PE3(config-nvo-acc-if) # map vnid 101	Maps VLAN 100 to the VxLAN VNID 101.
PE3(config-nvo-acc-if) #nvo vxlan access-if port-vlan sa4 2001	Configures another VxLAN NVO on the same interface xe2.
PE3(config-nvo-acc-if) # map vnid 2001	Maps VLAN 2001 to a different VxLAN VNID, in this case, VNID 2001.
PE3(config-router) #router bgp 100	Configures the BGP with AS number 100.
PE3(config-router) # bgp router-id 4.4.4.4	Sets the BGP router ID to 4.4.4.4.
PE3(config-router) # neighbor 1.1.1.1 remote-as 100	Configures a BGP neighbor with the remote AS number 100 and the IP address 1.1.1.1.
PE3(config-router) # neighbor 1.1.1.1 update-source lo	Specifies the BGP neighbor to use the loopback interface as the source for updates.
PE3(config-router) # neighbor 1.1.1.1 advertisement-interval 0	Configures the advertisement interval for BGP neighbor updates.
PE3(config-router) # address-family l2vpn evpn	Configures the BGP address family for Layer 2 VPN EVPN.
PE3(config-router-af) # neighbor 1.1.1.1 activate	Activates the BGP neighbor for the specified address family.
PE3(config-router-af) # exit-address-family	Exits the BGP address family configuration.
PE3(config-router) # address-family ipv4 vrf L3VRF1	Configures the BGP address family for IPv4 within VRF L3VRF1.
PE3(config-router-af) # redistribute connected	Configures BGP to redistribute connected routes into the BGP process.
PE3(config-router-af) # exit-address-family	Exits the BGP address family configuration for IPv4.
PE3(config-router) # address-family ipv6 vrf L3VRF1	Configures the BGP address family for IPv6 within VRF L3VRF1.
PE3(config-router-af) # redistribute connected	Configures BGP to redistribute connected routes into the BGP process.
PE3(config-router-af) # exit-address-family	Exits the BGP address family configuration for IPv6.


PE6

PE6#configure terminal	Enters the configuration mode.
PE6(config)#interface ce2	Configure the ce2 interface as a network interface.
PE6(config-if) # ip address 10.1.1.1/24	Assigns an IP address to the sa1 interface with a subnet mask of /24.
PE6(config-if) # ip ospf cost 10	Configures the OSPF cost for the sa1 interface, setting it to 10.
PE6(config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the sa1 interface.
PE6(config)#interface xe7	Configure network interface towards PE5.
PE6(config-if) # static-channel-group 1	Assigns the static channel group 1 to the xe1 interface.
PE6(config-if) #ip address 30.1.1.1/24	Assign IP address to network interface.
PE6(config)#ip ospf cost 10	Configures the OSPF cost for the xe7 interface, setting it to 10.

PE6(config)#load-interval 30	Configures the load-interval for monitoring traffic on the xe5 interface.
PE6(config)#router ospf 1	Enters the OSPF configuration mode for OSPF process 1.
PE6(config-router)# network 30.1.1.0/24 area 0.0.0.0	Advertises the network 30.1.1.0/24 into OSPF area 0.0.0.0.
PE6(config-router)# network 40.1.1.0/24 area 0.0.0.0	Advertises the network 40.1.1.0/24 into OSPF area 0.0.0.0.

Topology for ISIS

The network topology includes various network elements such as routers, customer edge (CE) devices, Service Aggregator (SA) devices, and Provider Edge (PE) routers. The feature enables OSPF and ISIS support on the IRB interfaces, allowing for efficient routing and communication between network devices within the topology.



Configure ISIS

PE2

PE2(config-if)# interface po1	Enters configuration mode for po 1.
PE2(config-if)# ip address 20.1.1.1/24	Assigns the IP address 20.1.1.1 with a subnet mask of 255.255.255.0 to the interface.
PE2(config-if)#ip router isis 1	Enables ISIS routing protocol on the interface with process ID 1.
PE2(config-if)#load-interval 30	Sets the interval for which interface statistics are collected to 30 seconds.
PE2(config)#nvo vxlan enable	Enables the VXLAN feature on the device.
PE2(config)#nvo vxlan irb	Enables VXLAN IRB functionality.
PE2(config-vrf)#mac vrf L2VRF2	Enters the configuration mode for a MAC VRF named L2VRF2.

PE2(config-vrf) # rd 2.2.2.2:11	Sets the route distinguisher (RD) for the VRF to 2.2.2.2:11.
PE2(config-vrf) #route-target both 10.10.10.10:100	Specifies import and export route targets for the VRF.
PE2(config-vrf) #ip vrf L3VRF2	Enters the configuration mode for an IP VRF named L3VRF2.
PE2(config-vrf) #rd 61000:11	Sets the RD for the IP VRF to 61000:11
PE2(config-vrf) # route-target both 101:101	Specifies import and export route targets for the IP VRF.
PE2(config-vrf) # 13vni 2000	Configures the Layer 3 VNI (Virtual Network Identifier) for the IP VRF.
PE2(config) #interface irb2001	Enters the configuration mode for interface IRB2001.
PE2(config-irb-if) # ip vrf forwarding L3VRF2	Associates the interface with the IP VRF L3VRF2.
PE2(config-irb-if) # ip address 13.13.13.1/24	Configures an IP address with a subnet mask of /24 on IRB2001.
PE2(config-irb-if) #mtu 9000	Sets the Maximum Transmission Unit (MTU) for the interface to 9000 bytes.
PE2(config-irb-if) #ip router isis 2	Associates the interface with ISIS routing process 2.
PE2(config-irb) #interface irb3001	Enters the configuration mode for interface IRB3001.
PE2(config-irb-if) # ip vrf forwarding L3VRF2	Associates the interface with the IP VRF L3VRF2.
PE2(config-irb-if) # ipv6 address 3001::1/64	Configures an IPv6 address on IRB3001 with the specified prefix length.
PE2(config-irb-if) #mtu 9000	Sets the MTU for the interface to 9000 bytes.
PE2(config-irb) #ipv6 router isis 3	Associates the interface with IPv6 ISIS routing process 3.
PE2(config) #router isis 2 L3VRF2	Enters the configuration mode for ISIS routing process 2 within VRF L3VRF2.
PE2(config-router) #is-type level-1-2	Specifies the ISIS level type as level-1-2.
PE2(config-router) #metric-style wide	Configures a wide metric style for ISIS.
PE2(config-router) # dynamic-hostname	Enables dynamic hostname assignment for the ISIS router.
PE2(config-router) # bfd all-interfaces	Enables Bidirectional Forwarding Detection (BFD) on all interfaces within ISIS.
PE2(config-router) #net 49.0000.0000.0221.00	Configures the network entity title (NET) for the ISIS process.
PE2(config) #router isis 3 L3VRF2	Enters the configuration mode for ISIS routing process 3 within VRF L3VRF2.
PE2(config-router) #is-type level-1-2	Specifies the ISIS level type as level-1-2.
PE2(config-router) # metric-style wide	Configures a wide metric style for ISIS.
PE2(config-router) # dynamic-hostname	Enables dynamic hostname assignment for the ISIS router.
PE2(config-router) #bfd all-interfaces	Enables BFD on all interfaces within ISIS.
PE2(config-router) # net 49.0000.0000.0222.00	Configures the network entity title (NET) for ISIS routing with the specified value.
PE2(config) #nvo vxlan vtep-ip-global 2.2.2.2	Configures the global VxLAN VTEP IP address to 2.2.2.2.
PE2(config) #nvo vxlan id 201 ingress-replication	Configures a VxLAN with VNI 201 and specifies ingress-replication for multicast traffic handling.
PE2(config-nvo) # vxlan host-reachability-protocol evpn-bgp L2VRF2	Specifies the EVPN-BGP host-reachability-protocol for the VxLAN with the VRF L2VRF2
PE2(config-nvo) # evpn irb2001	Enables EVPN IRB (Integrated Routing and Bridging) for VxLAN interface IRB2001.
PE2(config-nvo) # vni-name VNI-201	Assigns a name VNI-201 to the VxLAN VNI 201.

PE2(config)#nvo vxlan id 3001 ingress-replication	Configures another VxLAN with VNI 3001 and specifies ingress-replication for multicast traffic handling.
PE2(config-nvo)# vxlan host-reachability-protocol evpn-bgp L2VRF2	Specifies the EVPN-BGP host-reachability-protocol for the VxLAN with the VRF L2VRF2.
PE2(config-nvo)# evpn irb3001	Enables EVPN IRB for VxLAN interface IRB3001.
PE2(config-if)#interface xe11	Enters the configuration mode for the interface 11.
PE2(config-if)#switchport	Configures the interface as a Layer 2 switchport.
PE2(config-if)#load-interval 30	Sets the interval for which interface statistics are collected to 30 seconds.
PE2(config)#nvo vxlan access-if port-vlan xe11 100	Configures a VxLAN network virtualization overlay (NVO) on the interface xe2 with VLAN ID 100
PE2(config-nvo-acc-if)# map vnid 101	Maps VLAN 100 to the VxLAN Network Identifier (VNID) 101.
PE2(config-nvo-acc-if)#nvo vxlan access-if port-vlan xe11 2001	Configures another VxLAN NVO on the same interface xe2, but this time with VLAN ID 2001
PE2(config-nvo-acc-if)# map vnid 101	Maps VLAN 100 to the VxLAN Network Identifier (VNID) 101.
PE2(config-nvo-acc-if)#nvo vxlan access-if port-vlan xe11 2001	Configures another VxLAN NVO on the same interface xe2, but this time with VLAN ID 2001
PE2(config-nvo-acc-if)# map vnid 2001	Maps VLAN 2001 to a different VxLAN VNID.
PE2(config-if)#router isis 1	Starts the ISIS routing process with process ID 1.
PE2(config-if)#is-type level-1-2	Specifies that the router participates in both Level 1 and Level 2 routing.
PE2(config-if)#metric-style wide	Configures the metric style to be wide, enabling more flexibility in metric calculations.
PE2(config-if)#dynamic-hostname	Enables the dynamic hostname feature for ISIS.
PE2(config-if)#bfd all-interfaces	Configures Bidirectional Forwarding Detection on all interfaces.
PE2(config-if)#net 49.0000.0000.0001.00	Specifies the network entity title (NET) for ISIS.

BGP Configuration

PE2(config)#router bgp 100	Starts the BGP routing process with an autonomous system number (AS) of 100.
PE2(config-router)#bgp router-id 2.2.2.2	Sets the BGP router ID to 2.2.2.2.
PE2(config-router)#neighbor 3.3.3.3 remote-as 100	Configures a BGP neighbor with the IP address 3.3.3.3 and specifies the remote AS number as 100.
PE2(config-router)#neighbor 3.3.3.3 update-source lo	Specifies that loopback interface (lo) is the source for BGP updates to the neighbor.
PE2(config-router)#neighbor 3.3.3.3 advertisement-interval 0	Sets the advertisement interval to 0, which means updates will be sent immediately.
PE2(config-router)#address-family ipv4 unicast	Enters the configuration mode for the IPv4 unicast address family within the router configuration.
PE2(config-router-af)#network 2.2.2.2/32	Specifies that network 2.2.2.2 with a /32 subnet mask is part of the IPv4 unicast address family.
PE2(config-router-af)#neighbor 3.3.3.3 activate	Activates the neighbor with the IP address 3.3.3.3 for the IPv4 unicast address family.
PE2(config-router-af)#exit-address-family	Exits the configuration mode for the IPv4 unicast address family.

PE2(config-router)#address-family l2vpn evpn	Enters the configuration mode for the L2VPN EVPN address family within the router configuration.
PE2(config-router-af)#neighbor 3.3.3.3 activate	Activates the neighbor with the IP address 3.3.3.3 for the L2VPN EVPN address family.
PE2(config-router-af)#exit-address-family	Exits the configuration mode for the L2VPN EVPN address family.
PE2(config-router)#address-family ipv4 vrf L3VRF2	Enters the configuration mode for the IPv4 address family within the VRF named L3VRF2.
PE2(config-router-af)#redistribute connected	Configures the redistribution of directly connected routes into the IPv4 address family for the specified VRF.
PE2(config-router-af)#exit-address-family	Exits the configuration mode for the IPv4 address family within the VRF L3VRF2.
PE2(config-router-af)#address-family ipv6 vrf L3VRF2	Enters the configuration mode for the IPv6 address family within the VRF named L3VRF2.
PE2(config-router-af)#redistribute connected	Configures the redistribution of directly connected routes into the IPv6 address family for the specified VRF.
PE2(config-router-af)#exit-address-family	Exits the configuration mode for the IPv6 address family within the VRF L3VRF2.

PE5

PE5(config-if)#interface po1	Enters the configuration mode for po1.
PE5(config-if)#ip address 20.1.1.2/24	Assigns the IP address 20.1.1.2 with a subnet mask of /24 to this interface.
PE5(config-if)#ip router isis 1	Specifies that ISIS routing process 1 is enabled on this interface.
PE5(config-if)#load-interval 30	Sets the load interval to 30 seconds for monitoring the interface.
PE5(config-if)#interface po2	Enters the configuration mode for po2.
PE5(config-if)#ip address 70.1.1.2/24	Assigns the IP address 70.1.1.2 with a subnet mask of /24 to this interface.
PE5(config-if)#load-interval 30	Sets the load interval to 30 seconds for monitoring the interface.
PE5(config-if)#interface sa1	Assigns the IP address 10.1.1.2 with a subnet mask of /24 to this interface.
PE5(config-if)#ip ospf cost 10	Sets the OSPF cost for this interface to 10.
PE5(config-if)#load-interval 30	Sets the load interval to 30 seconds for monitoring the interface.
PE5(config-if)#interface ce50	Enters the configuration mode for ce50.
PE5(config-if)#ip address 50.1.1.1/24	Assigns the IP address 50.1.1.1 with a subnet mask of /24 to this interface.
PE5(config-if)#ip router isis 1	Specifies that ISIS routing process 1 is enabled on this interface.
PE5(config-if)#load-interval 30	Sets the load interval to 30 seconds for monitoring the interface.
PE5(config-if)#router ospf 1	Enters ISIS configuration mode with process ID 1.
PE5(config-if)#network 10.1.1.0/24 area 0.0.0.0	Specifies that the network 10.1.1.0 with subnet mask 255.255.255.0 belongs to OSPF area 0.0.0.0.

PE5(config-if) #network 30.1.1.0/24 area 0.0.0.0	Specifies another network, 30.1.1.0 with subnet mask 255.255.255.0, also belonging to OSPF area 0.0.0.0.
PE5(config-if) #network 70.1.1.0/24 area 0.0.0.0	Specifies a third network, 70.1.1.0 with subnet mask 255.255.255.0, in OSPF area 0.0.0.0.
PE5(config-if) #router isis 1	Enters ISIS configuration mode with process ID 1.
PE5(config-if) #is-type level-1-2	Configures this ISIS router to support both Level 1 and Level 2 routing.
PE5(config-if) #metric-style wide	Configures ISIS to use the wide metric style, which allows for greater flexibility in metric values.
PE5(config-if) #dynamic-hostname	Allows the hostname to be dynamically generated.
PE5(config-if) #bfd all-interfaces	Enables Bidirectional Forwarding Detection on all interfaces.
PE5(config-if) #net 49.0000.0005.0001.00	Sets the NET for this router.
PE5(config-if) #exit	Exits from the router mode.

PE 6

PE6#configure terminal	Enters the configuration mode.
PE6(config-if) #interface sa2	Enters configuration mode for interface sa2.
PE6(config-if) #ip address 80.1.1.2/24	Assigns the IP address 80.1.1.2 with a subnet mask of 255.255.255.0 to interface sa2.
PE6(config-if) #ip router isis 1	Associates ISIS routing protocol with this interface using process ID 1.
PE6(config-if) #load-interval 30	Sets the load-interval to 30 seconds.
PE6(config-if) #interface ce1	Enters configuration mode for interface ce1.
PE6(config-if) #ip address 50.1.1.2/24	Assigns the IP address 50.1.1.2 with a subnet mask of 255.255.255.0 to interface ce1.
PE6(config-if) #ip router isis 1	Associates ISIS routing protocol with this interface using process ID 1.
PE6(config-if) #load-interval 30	Sets the load-interval to 30 seconds.
PE6(config-if) #interface ce2	Enters configuration mode for interface ce2.
PE6(config-if) #speed 40g	Sets the interface speed to 40 gigabits per second.
PE6(config-if) #ip address 40.1.1.1/24	Assigns the IP address 40.1.1.1 with a subnet mask of 255.255.255.0 to interface ce2.
PE6(config-if) #ip ospf cost 10	Sets the OSPF cost for this interface to 10.
PE6(config-if) #load-interval 30	Sets the load-interval to 30 seconds.
PE6(config-if) #router ospf 1	Enters ISIS configuration mode with process ID 1.
PE6(config-if) #network 30.1.1.0/24 area 0.0.0.0	Specifies another network, 30.1.1.0 with subnet mask 255.255.255.0, also belonging to OSPF area 0.0.0.0.
PE6(config-if) #network 40.1.1.0/24 area 0.0.0.0	Specifies a third network, 40.1.1.0/24 with subnet mask 255.255.255.0, in OSPF area 0.0.0.0.
PE6(config-if) #router isis 1	Enters ISIS configuration mode with process ID 1.
PE6(config-if) #is-type level-1-2	Configures this ISIS router to support both Level 1 and Level 2 routing.
PE6(config-if) #metric-style wide	Configures ISIS to use the wide metric style, which allows for greater flexibility in metric values.

PE6(config-if) #dynamic-hostname	Allows the hostname to be dynamically generated.
PE6(config-if) #bfd all-interfaces	Enable BFD on all network interfaces.

PE4

PE4#configure terminal	Enters the configuration mode.
PE4(config-if) # interface xe5	Enters configuration mode for xe5.
PE4(config-if) # ip address 60.1.1.2/24	Assigns the IP address 60.1.1.2 with a subnet mask of 255.255.255.0 to the interface.
PE4(config-if) #ip router isis 1	Enables ISIS routing protocol on the interface with process ID 1.
PE4(config-if) #load-interval 30	Sets the interval for which interface statistics are collected to 30 seconds.
PE4(config) #nvo vxlan enable	Enables the VXLAN feature on the device.
PE4(config) #nvo vxlan irb	Enables VXLAN IRB functionality.
PE4(config-vrf) #mac vrf L2VRF2	Configures a VRF instance named L2VRF2 and associates it with a specific RD
PE4(config-vrf) # rd 3.3.3.3:11	Sets the RD for the L2VRF2 VRF to 3.3.3.3:11.
PE4(config-vrf) #route-target both 10.10.10.10:100	Associates a route target with the L2VRF2 VRF for VPN route distribution.
PE4(config-vrf) #ip vrf L3VRF2	Configures another VRF named L3VRF2.
PE4(config-vrf) #rd 63000:11	Sets the RD for the L3VRF2 VRF to 63000:11.
PE4(config-vrf) # route-target both 101:101	Associates a route target with the L3VRF2 VRF for VPN route distribution.
PE4(config-vrf) # l3vni 2000	Configures the L3VNI for the L3VRF2 VRF.
PE4(config) #interface irb2001	Configuring an IRB interface with the number 2001.
PE4(config-irb-if) # ip vrf forwarding L3VRF2	Associates the IRB interface with the L3VRF2 VRF.
PE4(config-irb-if) # ip address 14.14.14.1/24	Assigns an IP address to the IRB interface.
PE4(config-irb-if) #mtu 9000	Sets the MTU for the IRB interface.
PE4(config-irb-if) #ip router isis 2	Associates the IRB interface with ISIS routing.
PE4(config-irb) #interface irb3002	Configures another IRB interface with the number 3002.
PE4(config-irb-if) # ip vrf forwarding L3VRF2	Associates the second IRB interface with the "L3VRF2" VRF.
PE4(config-irb-if) # ipv6 address 3002::1/64	Assigns an IPv6 address to the second IRB interface.
PE4(config-irb-if) #mtu 9000	Sets the MTU for the second IRB interface.
PE4(config-irb) #ipv6 router isis 3	Associates the IRB interfaces with IPv6 and ISIS routing.
PE4(config) #router isis 2 L3VRF2	Configures ISIS routing with the VRF L3VRF2.
PE4(config-router) #is-type level-1-2	Sets the ISIS level type to level-1-2.
PE4(config-router) # metric-style wide	Configures a wide metric style for ISIS.
PE4(config-router) # dynamic-hostname	Enables dynamic hostname assignment for the ISIS router.
PE4(config-router) #bfd all-interfaces	Enables BFD on all interfaces within ISIS.
PE4(config-router) # net 49.0000.0000.0441.00	Configures the network entity title (NET) for ISIS routing with the specified value.
PE4(config) #router isis 3 L3VRF2	Configures ISIS routing with the VRF L3VRF2.
PE4(config-router) #is-type level-1-2	Sets the ISIS level type to level-1-2.

PE4 (config-router) # metric-style wide	Configures a wide metric style for ISIS.
PE4 (config-router) # dynamic-hostname	Enables dynamic hostname assignment for the ISIS router.
PE4 (config-router) #bfd all-interfaces	Enables BFD on all interfaces within ISIS.
PE4 (config-router) # net 49.0000.0000.0442.00	Configures the network entity title (NET) for ISIS routing with the specified value.
PE4 (config) #nvo vxlan vtep-ip-global 3.3.3.3	Configures the global VxLAN VTEP IP address to 3.3.3.3.
PE4 (config) #nvo vxlan id 201 ingress-replication	Configures a VxLAN with VNI 201 and specifies ingress-replication for multicast traffic handling.
PE4 (config-nvo) # vxlan host-reachability-protocol evpn-bgp L2VRF2	Specifies the EVPN-BGP host-reachability-protocol for the VxLAN with the VRF L2VRF2
PE4 (config-nvo) # evpn irb2001	Enables EVPN IRB (Integrated Routing and Bridging) for VxLAN interface IRB2001.
PE4 (config-nvo) # vni-name VNI-201	Assigns a name VNI-201 to the VxLAN VNI 201.
PE4 (config) #nvo vxlan id 3002 ingress-replication	Configures another VxLAN with VNI 3002 and specifies ingress-replication for multicast traffic handling.
PE4 (config-nvo) # vxlan host-reachability-protocol evpn-bgp L2VRF2	Specifies the EVPN-BGP host-reachability-protocol for the VxLAN with the VRF L2VRF2.
PE4 (config-nvo) # evpn irb3002	Enables EVPN IRB for VxLAN interface IRB3002
PE4 (config-if) #interface xe5	Enters the configuration mode for the interface 5.
PE4 (config-if) #switchport	Configures the interface as a L2 switchport.
PE4 (config-if) #load-interval 30	Sets the interval for which interface statistics are collected to 30 seconds.
PE4 (config) #nvo vxlan access-if port-vlan xe5 100	Configures a VxLAN network virtualization overlay (NVO) on the interface xe2 with VLAN ID 100
PE4 (config-nvo-acc-if) # map vnid 101	Maps VLAN 100 to the VxLAN Network Identifier (VNID) 101.
PE4 (config-nvo-acc-if) #nvo vxlan access-if port-vlan xe5 2001	Configures another VxLAN NVO on the same interface xe2, but this time with VLAN ID 2001
PE4 (config-nvo-acc-if) # map vnid 2001	Maps VLAN 2001 to a different VxLAN VNID.
PE4 (config-if) #router isis 1	Starts the ISIS routing process with process ID 1.
PE4 (config-if) #is-type level-1-2	Specifies that the router participates in both Level 1 and Level 2 routing.
PE4 (config-if) #metric-style wide	Configures the metric style to be wide, enabling more flexibility in metric calculations.
PE4 (config-if) #dynamic-hostname	Enables the dynamic hostname feature for ISIS.
PE4 (config-if) #bfd all-interfaces	Configures Bidirectional Forwarding Detection on all interfaces.
PE4 (config-if) #net 49.0000.0003.0001.00	Specifies the network entity title (NET) for ISIS.

BGP Configuration

PE4 (config) #router bgp 100	Starts the BGP routing process with an autonomous system number (AS) of 100.
PE4 (config-router) #bgp router-id 3.3.3.3	Sets the BGP router ID to 3.3.3.3
PE4 (config-router) #neighbor 2.2.2.2 remote-as 100	Configures a BGP neighbor with the IP address 2.2.2.2 and specifies the remote AS number as 100.
PE4 (config-router) #neighbor 2.2.2.2 update-source lo	Specifies that loopback interface (lo) is the source for BGP updates to the neighbor.

PE4 (config-router) #neighbor 2.2.2.2 advertisement-interval 0	Sets the advertisement interval to 0, which means updates will be sent immediately.
PE4 (config-router) #address-family ipv4 unicast	Enters the configuration mode for the IPv4 unicast address family within the router configuration.
PE4 (config-router-af) #network 3.3.3.3/32	Specifies that network 3.3.3.3 with a /32 subnet mask is part of the IPv4 unicast address family.
PE4 (config-router-af) #neighbor 2.2.2.2 activate	Activates the neighbor with the IP address 2.2.2.2 for the IPv4 unicast address family.
PE4 (config-router-af) #exit-address-family	Exits the configuration mode for the IPv4 unicast address family.
PE4 (config-router) #address-family l2vpn evpn	Enters the configuration mode for the L2VPN EVPN address family within the router configuration.
PE4 (config-router-af) #neighbor 2.2.2.2 activate	Activates the neighbor with the IP address 2.2.2.2 for the L2VPN EVPN address family.
PE4 (config-router-af) #exit-address-family	Exits the configuration mode for the L2VPN EVPN address family.
PE4 (config-router) #address-family ipv4 vrf L3VRF2	Enters the configuration mode for the IPv4 address family within the VRF named L3VRF2.
PE4 (config-router-af) #redistribute connected	Configures the redistribution of directly connected routes into the IPv4 address family for the specified VRF.
PE4 (config-router-af) #exit-address-family	Exits the configuration mode for the IPv4 address family within the VRF L3VRF2.
PE4 (config-router-af) #address-family ipv6 vrf L3VRF2	Enters the configuration mode for the IPv6 address family within the VRF named L3VRF2.
PE4 (config-router-af) #redistribute connected	Configures the redistribution of directly connected routes into the IPv6 address family for the specified VRF.
PE4 (config-router-af) #exit-address-family	Exits the configuration mode for the IPv6 address family within the VRF L3VRF2.

Implementation Examples

Scenario: Configure OSPF and ISIS protocols on an IRB interface with an assigned IP address.

New CLI Commands

No CLI commands are introduced.

Validation

OSPF Validation

```
PE1#show ip ospf neighbor
Total number of full neighbors: 1
OSPF process 1 VRF(default):
Neighbor ID      Pri     State            Dead Time      Address          Interface
                Instance ID
50.1.1.1          1      Full/DR        00:00:38      10.1.1.2        s1
```

0

Total number of full neighbors: 1

OSPF process 2 VRF(L3VRF1):

Neighbor ID	Pri	State	Dead Time	Address	Interface
Instance ID					
192.0.0.1	0	Full/DROther	00:00:34	11.11.11.2	irb1001
	0				

PE1#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
--------	-------------	--------	---------	--------

1.1.1.1	4.4.4.4	Installed	00:15:59	00:15:59
---------	---------	-----------	----------	----------

Total number of entries are 2

PE1# show evpn irb-status

IRB is ACTIVE in Hardware

PE1#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
------	---------	----------	------	---------	--------------

101	11.11.11.1	9819.2ccd.9301	Static Local	----	
101	11.11.11.2	0010.9400.0001	Dynamic Local	----	

Total number of entries are 2

PE1#show ip route vrf all

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
ia - IS-IS inter area, E - EVPN,
v - vrf leaked
* - candidate default

IP Route Table for VRF "default"

C	1.1.1.1/32	is directly connected, lo,	00:53:03
O	4.4.4.4/32	[110/31] via 10.1.1.2, sa1,	00:16:29
O	7.7.7.7/32	[110/12] via 10.1.1.2, sa1,	00:44:26
C	10.1.1.0/24	is directly connected, sa1,	00:50:10
O	30.1.1.0/24	[110/20] via 10.1.1.2, sa1,	00:44:22
O	40.1.1.0/24	[110/30] via 10.1.1.2, sa1,	00:17:14
O	70.1.1.0/24	[110/11] via 10.1.1.2, sa1,	00:45:18
C	127.0.0.0/8	is directly connected, lo,	00:53:03

IP Route Table for VRF "management"

C	10.12.98.0/24	is directly connected, eth0,	00:53:03
C	127.0.0.0/8	is directly connected, lo.management,	00:53:03

IP Route Table for VRF "L2VRF1"

IP Route Table for VRF "L3VRF1"

B	4.4.4.4/32	[0/0]	is directly connected, tunvxlan2,	00:16:25
---	------------	-------	-----------------------------------	----------

```
B      7.7.7.7/32 [0/0] is directly connected, tunvxlan2, 00:44:21
C      11.11.11.0/24 is directly connected, irb1001, 00:53:03
B      12.12.12.0/24 [200/0] via 4.4.4.4 (recursive is directly connected,
tunvxlan2), 00:16:26
B      16.16.16.0/24 [200/0] via 7.7.7.7 (recursive is directly connected,
tunvxlan2), 00:44:21
C      127.0.0.0/8 is directly connected, lo.L3VRF1, 00:53:03
```

Gateway of last resort is not set

```
PE1#show bgp l2vpn evpn
BGP table version is 5, local router ID is 1.1.1.1
Status codes: s suppressed, d damped, h history, a add-path, * valid, > best, i
- internal,
      l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete
```

```
[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route
4 - Ethernet Segment Route
5 - Prefix Route
```

Network	Next Hop	Metric	LocPrf	Weight	Path	Peer	Encap
RD[7100:11]							
*>i [5]:[0]:[0]:[24]:[16.16.16.0]:[0.0.0.0]:[1000]	7.7.7.7	0	100	0	i	7.7.7.7	VXLAN
*>i [5]:[0]:[0]:[64]:[7002::]:[::]:[1000]	7.7.7.7	0	100	0	i	7.7.7.7	VXLAN
RD[56000:11]							
*>i [5]:[0]:[0]:[24]:[12.12.12.0]:[0.0.0.0]:[1000]	4.4.4.4	0	100	0	?	4.4.4.4	VXLAN
*>i [5]:[0]:[0]:[64]:[2002::]:[::]:[1000]	4.4.4.4	0	100	0	?	4.4.4.4	VXLAN
RD[1.1.1.1:11] VRF[L2VRF1]:							
*> [2]:[0]:[101]:[48,0010:9400:0001]:[0]:[101]	1.1.1.1	0	100	32768	i	-----	VXLAN
*> [2]:[0]:[101]:[48,0010:9400:0001]:[32,11.11.11.2]:[101]	1.1.1.1	0	100	32768	i	-----	VXLAN
*> [2]:[0]:[101]:[48,9819:2ccd:9301]:[32,11.11.11.1]:[101]	1.1.1.1	0	100	32768	i	-----	VXLAN
* i [2]:[0]:[102]:[48,0010:9400:0002]:[0]:[102]	4.4.4.4	0	100	0	i	4.4.4.4	VXLAN
* i [2]:[0]:[102]:[48,0010:9400:0002]:[32,12.12.12.2]:[102]	4.4.4.4	0	100	0	i	4.4.4.4	VXLAN

```

* i [2]:[0]:[102]:[48,5c07:5813:425e]:[32,12.12.12.1]:[102]
        4.4.4.4          0       100      0   i 4.4.4.4    VXLAN
*> [2]:[0]:[2001]:[48,0010:9400:0009]:[0]:[2001]
        1.1.1.1          0       100     32768 i ----- VXLAN
*> [2]:[0]:[2001]:[48,0010:9400:0009]:[128,2001::2][2001]
        1.1.1.1          0       100     32768 i ----- VXLAN
*> [2]:[0]:[2001]:[48,9819:2cccd:9301]:[128,2001::1][2001]
        1.1.1.1          0       100     32768 i ----- VXLAN
* i [2]:[0]:[2002]:[48,0010:9400:000a]:[0]:[2002]
        4.4.4.4          0       100      0   i 4.4.4.4    VXLAN
* i [2]:[0]:[2002]:[48,0010:9400:000a]:[128,2002::2][2002]
        4.4.4.4          0       100      0   i 4.4.4.4    VXLAN
* i [2]:[0]:[2002]:[48,5c07:5813:425e]:[128,2002::1][2002]
        4.4.4.4          0       100      0   i 4.4.4.4    VXLAN
*> [3]:[101]:[32,1.1.1.1]
        1.1.1.1          0       100     32768 i ----- VXLAN
* i [3]:[102]:[32,4.4.4.4]
        4.4.4.4          0       100      0   i 4.4.4.4    VXLAN
*> [3]:[2001]:[32,1.1.1.1]
        1.1.1.1          0       100     32768 i ----- VXLAN
* i [3]:[2002]:[32,4.4.4.4]
        4.4.4.4          0       100      0   i 4.4.4.4    VXLAN

RD[4.4.4.4:11]
*>i [2]:[0]:[102]:[48,0010:9400:0002]:[0]:[102]
        4.4.4.4          0       100      0   i 4.4.4.4    VXLAN
*>i [2]:[0]:[102]:[48,0010:9400:0002]:[32,12.12.12.2]:[102]
        4.4.4.4          0       100      0   i 4.4.4.4    VXLAN
*>i [2]:[0]:[102]:[48,5c07:5813:425e]:[32,12.12.12.1]:[102]
        4.4.4.4          0       100      0   i 4.4.4.4    VXLAN
*>i [2]:[0]:[2002]:[48,0010:9400:000a]:[0]:[2002]
        4.4.4.4          0       100      0   i 4.4.4.4    VXLAN
*>i [2]:[0]:[2002]:[48,0010:9400:000a]:[128,2002::2][2002]
        4.4.4.4          0       100      0   i 4.4.4.4    VXLAN
*>i [2]:[0]:[2002]:[48,5c07:5813:425e]:[128,2002::1][2002]
        4.4.4.4          0       100      0   i 4.4.4.4    VXLAN
*>i [3]:[102]:[32,4.4.4.4]
        4.4.4.4          0       100      0   i 4.4.4.4    VXLAN
*>i [3]:[2002]:[32,4.4.4.4]
        4.4.4.4          0       100      0   i 4.4.4.4    VXLAN

```

Total number of prefixes 28

```

PE3#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source           Destination      Status      Up/Down      Update
=====
4.4.4.4          1.1.1.1        Installed    00:18:19    00:18:19

```

Total number of entries are 1

```
PE3#show ip ospf neighbor
```

Total number of full neighbors: 1

OSPF process 1 VRF(default):

Neighbor ID	Pri	State	Dead Time	Address	Interface
Instance ID					
40.1.1.2	1	Full/DR	00:00:36	40.1.1.1	ce30
0					

Total number of full neighbors: 1

OSPF process 2 VRF(L3VRF1):

Neighbor ID	Pri	State	Dead Time	Address	Interface
Instance ID					
192.0.0.2	0	Full/DROther	00:00:36	12.12.12.2	irb1001
0					

```
PE3#show ip route vrf all
```

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
ia - IS-IS inter area, E - EVPN,
v - vrf leaked
* - candidate default

IP Route Table for VRF "default"

O	1.1.1.1/32 [110/31] via 40.1.1.1, ce30, 00:18:35
C	4.4.4.4/32 is directly connected, lo, 00:19:22
O	7.7.7.7/32 [110/22] via 40.1.1.1, ce30, 00:18:35
O	10.1.1.0/24 [110/30] via 40.1.1.1, ce30, 00:18:35
O	30.1.1.0/24 [110/20] via 40.1.1.1, ce30, 00:18:35
C	40.1.1.0/24 is directly connected, ce30, 00:19:21
O	70.1.1.0/24 [110/21] via 40.1.1.1, ce30, 00:18:35
C	127.0.0.0/8 is directly connected, lo, 00:20:05

IP Route Table for VRF "management"

C	10.12.98.0/24 is directly connected, eth0, 00:19:19
C	127.0.0.0/8 is directly connected, lo.management, 00:20:05

IP Route Table for VRF "L3VRF1"

B	1.1.1.1/32 [0/0] is directly connected, tunvxlan2, 00:18:31
B	11.11.11.0/24 [200/0] via 1.1.1.1 (recursive is directly connected, tunvxlan2), 00:18:32
C	12.12.12.0/24 is directly connected, irb1001, 00:19:28
C	127.0.0.0/8 is directly connected, lo.L3VRF1, 00:19:29

IP Route Table for VRF "L2VRF1"

Gateway of last resort is not set

```
PE3# show bgp l2vpn evpn
```

BGP table version is 4, local router ID is 4.4.4.4

Status codes: s suppressed, d damped, h history, a add-path, * valid, > best, i - internal,

l - labeled, S Stale
 Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]

- 1 - Ethernet Auto-discovery Route
- 2 - MAC/IP Route
- 3 - Inclusive Multicast Route
- 4 - Ethernet Segment Route
- 5 - Prefix Route

Network	Next Hop	Metric	LocPrf	Weight	Path	Peer	Encap
RD[51000:11]							
*>i [5]:[0]:[0]:[24]:[11.11.11.0]:[0.0.0.0]:[1000]	1.1.1.1	0	100	0	?	1.1.1.1	VXLAN
*>i [5]:[0]:[0]:[64]:[2001::]:[::]:[1000]	1.1.1.1	0	100	0	?	1.1.1.1	VXLAN
RD[1.1.1.1:11]							
*>i [2]:[0]:[101]:[48,0010:9400:0001]:[0]:[101]	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
*>i [2]:[0]:[101]:[48,0010:9400:0001]:[32,11.11.11.2]:[101]	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
*>i [2]:[0]:[101]:[48,9819:2ccd:9301]:[32,11.11.11.1]:[101]	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
*>i [2]:[0]:[2001]:[48,0010:9400:0009]:[0]:[2001]	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
*>i [2]:[0]:[2001]:[48,0010:9400:0009]:[128,2001::2][2001]	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
*>i [2]:[0]:[2001]:[48,9819:2ccd:9301]:[128,2001::1][2001]	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
*>i [3]:[101]:[32,1.1.1.1]	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
*>i [3]:[2001]:[32,1.1.1.1]	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
RD[4.4.4.4:11] VRF[L2VRF1]:							
* i [2]:[0]:[101]:[48,0010:9400:0001]:[0]:[101]	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
* i [2]:[0]:[101]:[48,0010:9400:0001]:[32,11.11.11.2]:[101]	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
* i [2]:[0]:[101]:[48,9819:2ccd:9301]:[32,11.11.11.1]:[101]	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
*> [2]:[0]:[102]:[48,0010:9400:0002]:[0]:[102]	4.4.4.4	0	100	32768	i	-----	VXLAN
*> [2]:[0]:[102]:[48,0010:9400:0002]:[32,12.12.12.2]:[102]	4.4.4.4	0	100	32768	i	-----	VXLAN
*> [2]:[0]:[102]:[48,5c07:5813:425e]:[32,12.12.12.1]:[102]	4.4.4.4	0	100	32768	i	-----	
VXLAN							
* i [2]:[0]:[2001]:[48,0010:9400:0009]:[0]:[2001]							

	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
* i [2]:[0]:[2001]:[48,0010:9400:0009]:[128,2001::2][2001]	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
* i [2]:[0]:[2001]:[48,9819:2ccd:9301]:[128,2001::1][2001]	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
*> [2]:[0]:[2002]:[48,0010:9400:000a]:[0]:[2002]	4.4.4.4	0	100	32768	i	-----	VXLAN
*> [2]:[0]:[2002]:[48,0010:9400:000a]:[128,2002::2][2002]	4.4.4.4	0	100	32768	i	-----	VXLAN
*> [2]:[0]:[2002]:[48,5c07:5813:425e]:[128,2002::1][2002]	4.4.4.4	0	100	32768	i	-----	VXLAN
* i [3]:[101]:[32,1.1.1.1]	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
*> [3]:[102]:[32,4.4.4.4]	4.4.4.4	0	100	32768	i	-----	VXLAN
* i [3]:[2001]:[32,1.1.1.1]	1.1.1.1	0	100	0	i	1.1.1.1	VXLAN
*> [3]:[2002]:[32,4.4.4.4]	4.4.4.4	0	100	32768	i	-----	VXLAN

Total number of prefixes 26

ISIS Validation

```
PE2#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination      Status        Up/Down      Update
=====
```

2.2.2.2	3.3.3.3	Installed	00:00:10	00:00:10
---------	---------	-----------	----------	----------

Total number of entries are 1

```
PE2#show clns neighbors
```

Total number of L1 adjacencies: 1

Total number of L2 adjacencies: 1

Total number of adjacencies: 2

Tag 1: VRF : default

System Id	Interface	SNPA	State	Holdtime	Type	Protocol
PE5	pol	b86a.9725.a7f2	Up	28	L1	IS-IS
			Up	28	L2	IS-IS

Total number of L1 adjacencies: 0

Total number of L2 adjacencies: 1

Total number of adjacencies: 1

Tag 2: VRF : L3VRF2

System Id	Interface	SNPA	State	Holdtime	Type	Protocol
Spirent-1	irb2001	0010.9400.0003	Up	28	L2	IS-IS

Total number of L1 adjacencies: 0

Total number of L2 adjacencies: 1

Total number of adjacencies: 1

```

Tag 3: VRF : L3VRF2
System Id      Interface   SNPA           State  Holdtime  Type  Protocol
Spirent-1       irb3001    0010.9400.000c   Up     28        L2    IS-IS
PE2#show ip route vrf all
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
      O - OSPF, IA - OSPF inter area
      N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
      E1 - OSPF external type 1, E2 - OSPF external type 2
      i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
      ia - IS-IS inter area, E - EVPN,
      v - vrf leaked
      * - candidate default

IP Route Table for VRF "default"
C          2.2.2.2/32 is directly connected, lo, 02:13:57
i L2        3.3.3.3/32 [115/30] via 20.1.1.2, po1, 00:00:32
i L1        7.7.7.7/32 [115/40] via 20.1.1.2, po1, 01:05:49
C          20.1.1.0/24 is directly connected, po1, 02:13:21
i L1        50.1.1.0/24 [115/20] via 20.1.1.2, po1, 01:06:05
i L1        60.1.1.0/24 [115/30] via 20.1.1.2, po1, 00:00:47
i L1        80.1.1.0/24 [115/30] via 20.1.1.2, po1, 01:05:49
C          127.0.0.0/8 is directly connected, lo, 02:13:57
IP Route Table for VRF "management"
C          10.12.98.0/24 is directly connected, eth0, 02:13:57
C          127.0.0.0/8 is directly connected, lo.management, 02:13:57
IP Route Table for VRF "L3VRF2"
B          3.3.3.3/32 [0/0] is directly connected, tunvxlan2, 00:00:28
C          13.13.13.0/24 is directly connected, irb2001, 02:13:57
B          14.14.14.0/24 [200/0] via 3.3.3.3 (recursive is directly connected,
tunvxlan2), 00:00:28
C          127.0.0.0/8 is directly connected, lo.L3VRF2, 02:13:57
IP Route Table for VRF "L2VRF2"

Gateway of last resort is not set
PE2# show bgp l2vpn evpn
BGP table version is 2, local router ID is 2.2.2.2
Status codes: s suppressed, d damped, h history, a add-path, * valid, > best, i
- internal,
      l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route information]
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route
4 - Ethernet Segment Route
5 - Prefix Route

```

Network	Next Hop	Metric	LocPrf	Weight	Path	Peer	Encap
---------	----------	--------	--------	--------	------	------	-------

RD[63000:11]

*>i [5]:[0]:[0]:[24]:[14.14.14.0]:[0.0.0.0]:[2000]
 3.3.3.3 0 100 0 ? 3.3.3.3 VXLAN

*>i [5]:[0]:[0]:[64]:[3002::]:[::]:[2000]
 3.3.3.3 0 100 0 ? 3.3.3.3 VXLAN

RD[2.2.2.2:11] VRF[L2VRF2]:

*> [2]:[0]:[201]:[48,0010:9400:0003]:[0]:[201]
 2.2.2.2 0 100 32768 i ----- VXLAN

*> [2]:[0]:[201]:[48,0010:9400:0003]:[32,13.13.13.2]:[201]
 2.2.2.2 0 100 32768 i ----- VXLAN

* i [2]:[0]:[201]:[48,0010:9400:0005]:[0]:[201]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

* i [2]:[0]:[201]:[48,0010:9400:0005]:[32,14.14.14.2]:[201]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*> [2]:[0]:[201]:[48,e8c5:7a76:581d]:[32,13.13.13.1]:[201]
 2.2.2.2 0 100 32768 i ----- VXLAN

* i [2]:[0]:[201]:[48,e8c5:7aa8:7cb3]:[32,14.14.14.1]:[201]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*> [2]:[0]:[3001]:[48,0010:9400:000c]:[0]:[3001]
 2.2.2.2 0 100 32768 i ----- VXLAN

*> [2]:[0]:[3001]:[48,0010:9400:000c]:[128,3001::2][3001]
 2.2.2.2 0 100 32768 i ----- VXLAN

*> [2]:[0]:[3001]:[48,e8c5:7a76:581d]:[128,3001::1][3001]
 2.2.2.2 0 100 32768 i ----- VXLAN

* i [2]:[0]:[3002]:[48,0010:9400:000b]:[0]:[3002]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

* i [2]:[0]:[3002]:[48,0010:9400:000b]:[128,3002::2][3002]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

* i [2]:[0]:[3002]:[48,e8c5:7aa8:7cb3]:[128,3002::1][3002]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*> [3]:[201]:[32,2.2.2.2]
 2.2.2.2 0 100 32768 i ----- VXLAN

* i [3]:[201]:[32,3.3.3.3]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*> [3]:[3001]:[32,2.2.2.2]
 2.2.2.2 0 100 32768 i ----- VXLAN

* i [3]:[3002]:[32,3.3.3.3]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

RD[3.3.3.3:11]

*>i [2]:[0]:[201]:[48,0010:9400:0005]:[0]:[201]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*>i [2]:[0]:[201]:[48,0010:9400:0005]:[32,14.14.14.2]:[201]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*>i [2]:[0]:[201]:[48,e8c5:7aa8:7cb3]:[32,14.14.14.1]:[201]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*>i [2]:[0]:[3002]:[48,0010:9400:000b]:[0]:[3002]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*>i [2]:[0]:[3002]:[48,0010:9400:000b]:[128,3002::2][3002]

	3.3.3.3	0	100	0	i	3.3.3.3	VXLAN
*>i [2]:[0]:[3002]:[48,e8c5:7aa8:7cb3]:[128,3002::1][3002]	3.3.3.3	0	100	0	i	3.3.3.3	VXLAN
*>i [3]:[201]:[32,3.3.3.3]	3.3.3.3	0	100	0	i	3.3.3.3	VXLAN
*>i [3]:[3002]:[32,3.3.3.3]	3.3.3.3	0	100	0	i	3.3.3.3	VXLAN
	3.3.3.3	0	100	0	i	3.3.3.3	VXLAN

Total number of prefixes 26

```
PE2# show nvo vxlan arp-
arp-cache arp-nd
PE2# show nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====
```

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
201	13.13.13.1	e8c5.7a76.581d	Static Local	----	
201	13.13.13.2	0010.9400.0003	Dynamic Local	----	
201	14.14.14.1	e8c5.7aa8.7cb3	Static Remote	----	
201	14.14.14.2	0010.9400.0005	Dynamic Remote	----	

Total number of entries are 4

```
PE2# show evpn irb-status
IRB is ACTIVE in Hardware
PE2#
```

```
PE4#show nvo vxlan tunnel
VXLAN Network tunnel Entries
```

Source	Destination	Status	Up/Down	Update
3.3.3.3	7.7.7.7	Installed	00:01:28	00:01:28
3.3.3.3	2.2.2.2	Installed	00:01:28	00:01:28

Total number of entries are 2

```
PE4#show clns neighbors
```

Total number of L1 adjacencies: 1

Total number of L2 adjacencies: 1

Total number of adjacencies: 2

Tag 1: VRF : default

System Id	Interface	SNPA	State	Holddtime	Type	Protocol
PE6	xe5	00e0.4b71.f12c	Up	25	L1	IS-IS
			Up	25	L2	IS-IS

Total number of L1 adjacencies: 0

Total number of L2 adjacencies: 1

Total number of adjacencies: 1

Tag 2: VRF : L3VRF2

System Id	Interface	SNPA	State	Holddtime	Type	Protocol
Spirent-1	irb2001	0010.9400.0005	Up	28	L2	IS-IS

```

Total number of L1 adjacencies: 0
Total number of L2 adjacencies: 1
Total number of adjacencies: 1
Tag 3: VRF : L3VRF2
System Id      Interface   SNPA           State  Holdtime  Type  Protocol
Spirent-1       irb3002     0010.9400.000b    Up      28        L2    IS-IS
PE4#show ip route vrf all
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
      O - OSPF, IA - OSPF inter area
      N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
      E1 - OSPF external type 1, E2 - OSPF external type 2
      i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
      ia - IS-IS inter area, E - EVPN,
      v - vrf leaked
      * - candidate default

IP Route Table for VRF "default"
i L2          2.2.2.2/32 [115/30] via 60.1.1.1, xe5, 00:01:46
C             3.3.3.3/32 is directly connected, lo, 02:09:52
i L1          7.7.7.7/32 [115/30] via 60.1.1.1, xe5, 00:01:46
i L1          20.1.1.0/24 [115/30] via 60.1.1.1, xe5, 00:01:46
i L1          50.1.1.0/24 [115/20] via 60.1.1.1, xe5, 00:01:46
C             60.1.1.0/24 is directly connected, xe5, 00:02:02
i L1          80.1.1.0/24 [115/20] via 60.1.1.1, xe5, 00:01:46
C             127.0.0.0/8 is directly connected, lo, 02:09:52
IP Route Table for VRF "management"
C             10.12.98.0/24 is directly connected, eth0, 02:09:52
C             127.0.0.0/8 is directly connected, lo.management, 02:09:52
IP Route Table for VRF "L3VRF2"
B             2.2.2.2/32 [0/0] is directly connected, tunvxlan2, 00:01:42
B             7.7.7.7/32 [0/0] is directly connected, tunvxlan2, 00:01:42
B             13.13.13.0/24 [200/0] via 2.2.2.2 (recursive is directly connected,
tunvxlan2), 00:01:42
C             14.14.14.0/24 is directly connected, irb2001, 02:09:52
B             17.17.17.0/24 [200/0] via 7.7.7.7 (recursive is directly connected,
tunvxlan2), 00:01:42
C             127.0.0.0/8 is directly connected, lo.L3VRF2, 02:09:52
IP Route Table for VRF "L2VRF2"

Gateway of last resort is not set
PE4# show bgp l2vpn evpn
BGP table version is 3, local router ID is 3.3.3.3
Status codes: s suppressed, d damped, h history, a add-path, * valid, > best, i -
internal,
      l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route

```

4 - Ethernet Segment Route

5 - Prefix Route

Network	Next Hop	Metric	LocPrf	Weight	Path	Peer	Encap
RD[7400:11]							
*>i [5]:[0]:[0]:[24]:[17.17.17.0]:[0.0.0.0]:[2000]	7.7.7.7	0	100	0	i 7.7.7.7		VXLAN
*>i [5]:[0]:[0]:[64]:[8002::]:[::]:[2000]	7.7.7.7	0	100	0	i 7.7.7.7		VXLAN
RD[61000:11]							
*>i [5]:[0]:[0]:[24]:[13.13.13.0]:[0.0.0.0]:[2000]	2.2.2.2	0	100	0	? 2.2.2.2		VXLAN
*>i [5]:[0]:[0]:[64]:[3001::]:[::]:[2000]	2.2.2.2	0	100	0	? 2.2.2.2		VXLAN
RD[2.2.2.2:11]							
*>i [2]:[0]:[201]:[48,0010:9400:0003]:[0]:[201]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
*>i [2]:[0]:[201]:[48,0010:9400:0003]:[32,13.13.13.2]:[201]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
*>i [2]:[0]:[201]:[48,e8c5:7a76:581d]:[32,13.13.13.1]:[201]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
*>i [2]:[0]:[3001]:[48,0010:9400:000c]:[0]:[3001]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
*>i [2]:[0]:[3001]:[48,0010:9400:000c]:[128,3001::2][3001]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
*>i [2]:[0]:[3001]:[48,e8c5:7a76:581d]:[128,3001::1][3001]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
*>i [3]:[201]:[32,2.2.2.2]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
*>i [3]:[3001]:[32,2.2.2.2]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
RD[3.3.3.3:11] VRF[L2VRF2]:							
* i [2]:[0]:[201]:[48,0010:9400:0003]:[0]:[201]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
* i [2]:[0]:[201]:[48,0010:9400:0003]:[32,13.13.13.2]:[201]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
*> [2]:[0]:[201]:[48,0010:9400:0005]:[0]:[201]	3.3.3.3	0	100	32768	i -----		VXLAN
*> [2]:[0]:[201]:[48,0010:9400:0005]:[32,14.14.14.2]:[201]	3.3.3.3	0	100	32768	i -----		VXLAN
VXLAN							
* i [2]:[0]:[201]:[48,e8c5:7a76:581d]:[32,13.13.13.1]:[201]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
*> [2]:[0]:[201]:[48,e8c5:7aa8:7cb3]:[32,14.14.14.1]:[201]	3.3.3.3	0	100	32768	i -----		VXLAN
VXLAN							
* i [2]:[0]:[3001]:[48,0010:9400:000c]:[0]:[3001]							

	2.2.2.2	0	100	0	i	2.2.2.2	VXLAN
* i [2]:[0]:[3001]:[48,0010:9400:000c]:[128,3001::2][3001]	2.2.2.2	0	100	0	i	2.2.2.2	VXLAN
* i [2]:[0]:[3001]:[48,e8c5:7a76:581d]:[128,3001::1][3001]	2.2.2.2	0	100	0	i	2.2.2.2	VXLAN
*> [2]:[0]:[3002]:[48,0010:9400:000b]:[0]:[3002]	3.3.3.3	0	100	32768	i	-----	VXLAN
*> [2]:[0]:[3002]:[48,0010:9400:000b]:[128,3002::2][3002]	3.3.3.3	0	100	32768	i	-----	VXLAN
*> [2]:[0]:[3002]:[48,e8c5:7aa8:7cb3]:[128,3002::1][3002]	3.3.3.3	0	100	32768	i	-----	VXLAN
* i [3]:[201]:[32,2.2.2.2]	2.2.2.2	0	100	0	i	2.2.2.2	VXLAN
*> [3]:[201]:[32,3.3.3.3]	3.3.3.3	0	100	32768	i	-----	VXLAN
* i [3]:[3001]:[32,2.2.2.2]	2.2.2.2	0	100	0	i	2.2.2.2	VXLAN
*> [3]:[3002]:[32,3.3.3.3]	3.3.3.3	0	100	32768	i	-----	VXLAN

Total number of prefixes 28

ISIS Validation

PE2#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
2.2.2.2	3.3.3.3	Installed	00:00:10	00:00:10

Total number of entries are 1

PE2#show clns neighbors

Total number of L1 adjacencies: 1

Total number of L2 adjacencies: 1

Total number of adjacencies: 2

Tag 1: VRF : default

System Id	Interface	SNPA	State	Holddtime	Type	Protocol
PE5	po1	b86a.9725.a7f2	Up	28	L1	IS-IS
			Up	28	L2	IS-IS

Total number of L1 adjacencies: 0

Total number of L2 adjacencies: 1

Total number of adjacencies: 1

Tag 2: VRF : L3VRF2

System Id	Interface	SNPA	State	Holddtime	Type	Protocol
Spirent-1	irb2001	0010.9400.0003	Up	28	L2	IS-IS

Total number of L1 adjacencies: 0

Total number of L2 adjacencies: 1

Total number of adjacencies: 1

Tag 3: VRF : L3VRF2

System Id	Interface	SNPA	State	Holddtime	Type	Protocol

```

Spirent-1      irb3001      0010.9400.000c      Up       28      L2      IS-IS
PE2#
PE2#
PE2#show ip route vrf all
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
      O - OSPF, IA - OSPF inter area
      N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
      E1 - OSPF external type 1, E2 - OSPF external type 2
      i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
      ia - IS-IS inter area, E - EVPN,
      v - vrf leaked
      * - candidate default

IP Route Table for VRF "default"
C          2.2.2.2/32 is directly connected, lo, 02:13:57
i L2        3.3.3.3/32 [115/30] via 20.1.1.2, po1, 00:00:32
i L1        7.7.7.7/32 [115/40] via 20.1.1.2, po1, 01:05:49
C          20.1.1.0/24 is directly connected, po1, 02:13:21
i L1        50.1.1.0/24 [115/20] via 20.1.1.2, po1, 01:06:05
i L1        60.1.1.0/24 [115/30] via 20.1.1.2, po1, 00:00:47
i L1        80.1.1.0/24 [115/30] via 20.1.1.2, po1, 01:05:49
C          127.0.0.0/8 is directly connected, lo, 02:13:57
IP Route Table for VRF "management"
C          10.12.98.0/24 is directly connected, eth0, 02:13:57
C          127.0.0.0/8 is directly connected, lo.management, 02:13:57
IP Route Table for VRF "L3VRF2"
B          3.3.3.3/32 [0/0] is directly connected, tunvxlan2, 00:00:28
C          13.13.13.0/24 is directly connected, irb2001, 02:13:57
B          14.14.14.0/24 [200/0] via 3.3.3.3 (recursive is directly connected,
tunvxlan2), 00:00:28
C          127.0.0.0/8 is directly connected, lo.L3VRF2, 02:13:57
IP Route Table for VRF "L2VRF2"

Gateway of last resort is not set
PE2# show bgp l2vpn evpn
BGP table version is 2, local router ID is 2.2.2.2
Status codes: s suppressed, d damped, h history, a add-path, * valid, > best, i
- internal,
      l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route information]
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route
4 - Ethernet Segment Route
5 - Prefix Route
Network           Next Hop           Metric     LocPrf      Weight      Path
Peer              Encap

```

RD[63000:11]

*>i [5]:[0]:[0]:[24]:[14.14.14.0]:[0.0.0.0]:[2000]
 3.3.3.3 0 100 0 ? 3.3.3.3 VXLAN

*>i [5]:[0]:[0]:[64]:[3002::]:[::]:[2000]
 3.3.3.3 0 100 0 ? 3.3.3.3 VXLAN

RD[2.2.2.2:11] VRF[L2VRF2]:

*> [2]:[0]:[201]:[48,0010:9400:0003]:[0]:[201]
 2.2.2.2 0 100 32768 i ----- VXLAN

*> [2]:[0]:[201]:[48,0010:9400:0003]:[32,13.13.13.2]:[201]
 2.2.2.2 0 100 32768 i ----- VXLAN

* i [2]:[0]:[201]:[48,0010:9400:0005]:[0]:[201]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

* i [2]:[0]:[201]:[48,0010:9400:0005]:[32,14.14.14.2]:[201]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*> [2]:[0]:[201]:[48,e8c5:7a76:581d]:[32,13.13.13.1]:[201]
 2.2.2.2 0 100 32768 i ----- VXLAN

* i [2]:[0]:[201]:[48,e8c5:7aa8:7cb3]:[32,14.14.14.1]:[201]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*> [2]:[0]:[3001]:[48,0010:9400:000c]:[0]:[3001]
 2.2.2.2 0 100 32768 i ----- VXLAN

*> [2]:[0]:[3001]:[48,0010:9400:000c]:[128,3001::2][3001]
 2.2.2.2 0 100 32768 i ----- VXLAN

*> [2]:[0]:[3001]:[48,e8c5:7a76:581d]:[128,3001::1][3001]
 2.2.2.2 0 100 32768 i ----- VXLAN

* i [2]:[0]:[3002]:[48,0010:9400:000b]:[0]:[3002]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

* i [2]:[0]:[3002]:[48,0010:9400:000b]:[128,3002::2][3002]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

* i [2]:[0]:[3002]:[48,e8c5:7aa8:7cb3]:[128,3002::1][3002]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*> [3]:[201]:[32,2.2.2.2]
 2.2.2.2 0 100 32768 i ----- VXLAN

* i [3]:[201]:[32,3.3.3.3]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*> [3]:[3001]:[32,2.2.2.2]
 2.2.2.2 0 100 32768 i ----- VXLAN

* i [3]:[3002]:[32,3.3.3.3]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

RD[3.3.3.3:11]

*>i [2]:[0]:[201]:[48,0010:9400:0005]:[0]:[201]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*>i [2]:[0]:[201]:[48,0010:9400:0005]:[32,14.14.14.2]:[201]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*>i [2]:[0]:[201]:[48,e8c5:7aa8:7cb3]:[32,14.14.14.1]:[201]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*>i [2]:[0]:[3002]:[48,0010:9400:000b]:[0]:[3002]
 3.3.3.3 0 100 0 i 3.3.3.3 VXLAN

*>i [2]:[0]:[3002]:[48,0010:9400:000b]:[128,3002::2][3002]

	3.3.3.3	0	100	0	i	3.3.3.3	VXLAN
*>i [2]:[0]:[3002]:[48,e8c5:7aa8:7cb3]:[128,3002::1][3002]	3.3.3.3	0	100	0	i	3.3.3.3	VXLAN
*>i [3]:[201]:[32,3.3.3.3]	3.3.3.3	0	100	0	i	3.3.3.3	VXLAN
*>i [3]:[3002]:[32,3.3.3.3]	3.3.3.3	0	100	0	i	3.3.3.3	VXLAN
	3.3.3.3	0	100	0	i	3.3.3.3	VXLAN

Total number of prefixes 26

```
PE2#      show nvo vxlan arp-
arp-cache arp-nd
PE2#      show nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====
```

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
201	13.13.13.1	e8c5.7a76.581d	Static Local	----	
201	13.13.13.2	0010.9400.0003	Dynamic Local	----	
201	14.14.14.1	e8c5.7aa8.7cb3	Static Remote	----	
201	14.14.14.2	0010.9400.0005	Dynamic Remote	----	

Total number of entries are 4

```
PE2# show evpn irb-status
IRB is ACTIVE in Hardware
PE2#
```

```
PE4#show nvo vxlan tunnel
VXLAN Network tunnel Entries
```

Source	Destination	Status	Up/Down	Update
3.3.3.3	7.7.7.7	Installed	00:01:28	00:01:28
3.3.3.3	2.2.2.2	Installed	00:01:28	00:01:28

Total number of entries are 2

```
PE4#show clns neighbors
```

Total number of L1 adjacencies: 1

Total number of L2 adjacencies: 1

Total number of adjacencies: 2

Tag 1: VRF : default

System Id	Interface	SNPA	State	Holddtime	Type	Protocol
PE6	xe5	00e0.4b71.f12c	Up	25	L1	IS-IS
			Up	25	L2	IS-IS

Total number of L1 adjacencies: 0

Total number of L2 adjacencies: 1

Total number of adjacencies: 1

Tag 2: VRF : L3VRF2

System Id	Interface	SNPA	State	Holddtime	Type	Protocol
Spirent-1	irb2001	0010.9400.0005	Up	28	L2	IS-IS

```

Total number of L1 adjacencies: 0
Total number of L2 adjacencies: 1
Total number of adjacencies: 1
Tag 3: VRF : L3VRF2
System Id      Interface   SNPA           State  Holdtime  Type  Protocol
Spirent-1       irb3002     0010.9400.000b    Up      28        L2    IS-IS
PE4#show ip route vrf all
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
      O - OSPF, IA - OSPF inter area
      N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
      E1 - OSPF external type 1, E2 - OSPF external type 2
      i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
      ia - IS-IS inter area, E - EVPN,
      v - vrf leaked
      * - candidate default

IP Route Table for VRF "default"
i L2          2.2.2.2/32 [115/30] via 60.1.1.1, xe5, 00:01:46
C             3.3.3.3/32 is directly connected, lo, 02:09:52
i L1          7.7.7.7/32 [115/30] via 60.1.1.1, xe5, 00:01:46
i L1          20.1.1.0/24 [115/30] via 60.1.1.1, xe5, 00:01:46
i L1          50.1.1.0/24 [115/20] via 60.1.1.1, xe5, 00:01:46
C             60.1.1.0/24 is directly connected, xe5, 00:02:02
i L1          80.1.1.0/24 [115/20] via 60.1.1.1, xe5, 00:01:46
C             127.0.0.0/8 is directly connected, lo, 02:09:52
IP Route Table for VRF "management"
C             10.12.98.0/24 is directly connected, eth0, 02:09:52
C             127.0.0.0/8 is directly connected, lo.management, 02:09:52
IP Route Table for VRF "L3VRF2"
B             2.2.2.2/32 [0/0] is directly connected, tunvxlan2, 00:01:42
B             7.7.7.7/32 [0/0] is directly connected, tunvxlan2, 00:01:42
B             13.13.13.0/24 [200/0] via 2.2.2.2 (recursive is directly connected,
tunvxlan2), 00:01:42
C             14.14.14.0/24 is directly connected, irb2001, 02:09:52
B             17.17.17.0/24 [200/0] via 7.7.7.7 (recursive is directly connected,
tunvxlan2), 00:01:42
C             127.0.0.0/8 is directly connected, lo.L3VRF2, 02:09:52
IP Route Table for VRF "L2VRF2"

Gateway of last resort is not set
PE4# show bgp l2vpn evpn
BGP table version is 3, local router ID is 3.3.3.3
Status codes: s suppressed, d damped, h history, a add-path, * valid, > best, i -
internal,
      l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route

```

4 - Ethernet Segment Route

5 - Prefix Route

Network Encap	Next Hop	Metric	LocPrf	Weight	Path	Peer
RD[7400:11]						
*>i [5]:[0]:[0]:[24]:[17.17.17.0]:[0.0.0.0]:[2000]	7.7.7.7	0	100	0	i 7.7.7.7	VXLAN
*>i [5]:[0]:[0]:[64]:[8002::]:[::]:[2000]	7.7.7.7	0	100	0	i 7.7.7.7	VXLAN
RD[61000:11]						
*>i [5]:[0]:[0]:[24]:[13.13.13.0]:[0.0.0.0]:[2000]	2.2.2.2	0	100	0	? 2.2.2.2	VXLAN
*>i [5]:[0]:[0]:[64]:[3001::]:[::]:[2000]	2.2.2.2	0	100	0	? 2.2.2.2	VXLAN
RD[2.2.2.2:11]						
*>i [2]:[0]:[201]:[48,0010:9400:0003]:[0]:[201]	2.2.2.2	0	100	0	i 2.2.2.2	VXLAN
*>i [2]:[0]:[201]:[48,0010:9400:0003]:[32,13.13.13.2]:[201]	2.2.2.2	0	100	0	i 2.2.2.2	VXLAN
*>i [2]:[0]:[201]:[48,e8c5:7a76:581d]:[32,13.13.13.1]:[201]	2.2.2.2	0	100	0	i 2.2.2.2	VXLAN
*>i [2]:[0]:[3001]:[48,0010:9400:000c]:[0]:[3001]	2.2.2.2	0	100	0	i 2.2.2.2	VXLAN
*>i [2]:[0]:[3001]:[48,0010:9400:000c]:[128,3001::2][3001]	2.2.2.2	0	100	0	i 2.2.2.2	VXLAN
*>i [2]:[0]:[3001]:[48,e8c5:7a76:581d]:[128,3001::1][3001]	2.2.2.2	0	100	0	i 2.2.2.2	VXLAN
*>i [3]:[201]:[32,2.2.2.2]	2.2.2.2	0	100	0	i 2.2.2.2	VXLAN
*>i [3]:[3001]:[32,2.2.2.2]	2.2.2.2	0	100	0	i 2.2.2.2	VXLAN
RD[3.3.3.3:11] VRF[L2VRF2]:						
* i [2]:[0]:[201]:[48,0010:9400:0003]:[0]:[201]	2.2.2.2	0	100	0	i 2.2.2.2	VXLAN
* i [2]:[0]:[201]:[48,0010:9400:0003]:[32,13.13.13.2]:[201]	2.2.2.2	0	100	0	i 2.2.2.2	VXLAN
*> [2]:[0]:[201]:[48,0010:9400:0005]:[0]:[201]	3.3.3.3	0	100	32768	i -----	VXLAN
*> [2]:[0]:[201]:[48,0010:9400:0005]:[32,14.14.14.2]:[201]	3.3.3.3	0	100	32768	i -----	VXLAN
* i [2]:[0]:[201]:[48,e8c5:7a76:581d]:[32,13.13.13.1]:[201]	2.2.2.2	0	100	0	i 2.2.2.2	VXLAN
*> [2]:[0]:[201]:[48,e8c5:7aa8:7cb3]:[32,14.14.14.1]:[201]	3.3.3.3	0	100	32768	i -----	VXLAN
* i [2]:[0]:[3001]:[48,0010:9400:000c]:[0]:[3001]	2.2.2.2	0	100	0	i 2.2.2.2	VXLAN

```
* i [2]:[0]:[3001]:[48,0010:9400:000c]:[128,3001::2][3001]
      2.2.2.2          0       100       0   i 2.2.2.2           VXLAN
* i [2]:[0]:[3001]:[48,e8c5:7a76:581d]:[128,3001::1][3001]
      2.2.2.2          0       100       0   i 2.2.2.2           VXLAN
*> [2]:[0]:[3002]:[48,0010:9400:000b]:[0]:[3002]
      3.3.3.3          0       100     32768 i -----           VXLAN
*> [2]:[0]:[3002]:[48,0010:9400:000b]:[128,3002::2][3002]
      3.3.3.3          0       100     32768 i -----           VXLAN
*> [2]:[0]:[3002]:[48,e8c5:7aa8:7cb3]:[128,3002::1][3002]
      3.3.3.3          0       100     32768 i -----           VXLAN
* i [3]:[201]:[32,2.2.2.2]
      2.2.2.2          0       100       0   i 2.2.2.2           VXLAN
*> [3]:[201]:[32,3.3.3.3]
      3.3.3.3          0       100     32768 i -----           VXLAN
* i [3]:[3001]:[32,2.2.2.2]
      2.2.2.2          0       100       0   i 2.2.2.2           VXLAN
*> [3]:[3002]:[32,3.3.3.3]
      3.3.3.3          0       100     32768 i -----           VXLAN
```

Total number of prefixes 28

Abbreviations

The following are some key abbreviations and their meanings relevant to this document:

Acronym	Description
ECMP	Equal-Cost Multipath
EVPN	Ethernet Virtual Private Network
VxLAN	Virtual Extensible LAN
SR	Segment Routing
IRB	Integrated Routing
OSPF	Open Shortest Path First
ISIS	Intermediate System to Intermediate System

Glossary

The following provides definitions for key terms used throughout this document.

Single Home VxLAN	This refers to a Virtual Extensible LAN (VxLAN) deployment where a single data center or network site is connected to a single external network (usually the internet) for connectivity.
IRB	A networking feature that enables the integration of Layer 3 IP routing and Layer 2 MAC address bridging within the same interface, simplifying network management and resource utilization.

OSPF	A dynamic and efficient link-state routing protocol used to determine the best path for data packets in an IP network. It is characterized by rapid convergence and adaptability, making it suitable for large and dynamic networks.
ISIS	A routing protocol designed for scalability and stability in computer networks, commonly used in large Service Provider networks. It provides a robust framework for routing information exchange.
Layer 3 Routing	Network routing operations at the Network Layer (Layer 3) of the OSI model, focusing on routing IP packets between different subnets or networks.
Layer 2 Bridging	Network bridging operations at the Data Link Layer (Layer 2) of the OSI model, handling the forwarding of data frames based on MAC addresses within the same network segment.
EVPN	Ethernet VPN, a technology that provides advanced and efficient methods for Layer 2 and Layer 3 services in Ethernet networks, often used in data centers and service provider environments.

CHAPTER 8 Multi Home VxLAN-EVPN IRB with OSPF or ISIS

Overview

The support for Open Shortest Path First (OSPF) and Intermediate System to Intermediate System (ISIS) protocols on Virtual Extensible LAN (VxLAN) Integrated Routing (IRB) interface is enhanced with multihoming switches that provides the solution for connecting and managing virtual networks within a data center or network infrastructure.

This feature offers flexibility in configuring network topologies, and ensures compatibility and interoperability within diverse network environments.

Note: Configure mutually exclusive secondary IP subnets between each anycast-IRB and CE within the same L2VNI in multi-homing scenarios or when the same IRB anycast interface is configured on multiple nodes. This ensures unique identification of the routing protocol peer.

Feature Characteristics

The OSPF and ISIS support over the IRB Interface with multihoming feature has the following characteristics:

- Connect the host node to two VTEPs with all-active redundancy mode. It helps forward all traffic from VTEP to the host when one VTEP goes down.

Benefits

The OSPF and ISIS support over the IRB Interface has the following benefits:

- Uninterrupted service between host and VTEP.

Prerequisites

- Router must be up and running.
- Maintain synchronization with VRF changes by performing IRB `shut/no shut` actions when specific events occur within the IPVRF. These events may involve adding or removing Route Targets (RTs), updating Route Distinguishers (RDs), or modifying Layer 3 Virtual Network Identifiers (L3VNIs).

Topology for OSPF

The network topology includes various network elements such as routers, customer edge (CE) devices, Service Aggregator (SA) devices, and Provider Edge (PE) routers. The feature enables OSPF on the IRB interfaces, allowing for efficient routing and communication between network devices within the topology.




Figure 8-5: Multi Home VxLAN-EVPN IRB with OSPF or ISIS

Configuration

Perform the following configurations to set up different interfaces, routing protocols, and BGP parameters to enable VXLAN, IRB, and EVPN functionality with multihoming in the network.

Configure OSPF Router

Perform the following configurations to create multiple VxLAN interfaces and set up OSPF routing process on PE1 node.

PE1

PE1(config)#vlan database	Enter the VLAN configuration mode.
PE1(config-vlan)# vlan 200-201 bridge 1 state enable	Enable VLAN (200-201) on bridge 1. Specifying the enable state allows forwarding of frames on this VLAN-aware bridge.
PE1(config-vlan)#interface sa1	Enter sa1 interface mode.
PE1(config-if)# switchport	Configure port as L2.
PE1(config-if)# bridge-group 1	Associate the interface with bridge group 1.
PE1(config-if)# switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
PE1(config-if)# switchport trunk allowed vlan add 200-201	Enable VLAN ID 200-201 on this port.
PE1(config-if)# load-interval 30	Configures the load-interval for monitoring traffic on the sa1 interface.
PE1(config-if)# exit	Exit from sa1 interface configuration mode.
PE1(config)#interface ce0	Enter ce0 interface mode.
PE1(config-if)# static-channel-group 1	Make it member port of sa1
PE1(config-if)#interface lo	Configures the loopback (lo) interface.
PE1(config-if)# ip address 1.1.1.1/32 secondary	Assigns a secondary the IP address 1.1.1.1/32 to the loopback interface.
PE1(config-if)# ipv6 address ::1/128	Assigns the IPv6 address ::1/128 to the loopback interface.
PE1(config-if)#interface vlan1.200	Enter interface VLAN1.200 configuration mode.
PE1(config-if)# ip address 101.11.11.1/24	Assigns the primary IP address.
PE1(config-if)# ip address 16.16.16.1/24 secondary	Assigns the secondary IP address.
PE1(config-if)# ip address 17.17.17.1/24 secondary	Assigns the secondary IP address.
PE1(config-if)# exit	Exit from VLAN interface configuration mode.
PE1(config)#interface xe2	Enter xe2 interface configuration mode.
PE1(config-if)# load-interval 30	Configures the load-interval for monitoring traffic on the xe2 interface.
PE1(config-if)#interface xe2.103	Enter VLAN ID 103 interface config mode.
PE1(config-if)# encapsulation dot1q 103	Setting Encapsulation to dot1q with VLAN ID 103.
PE1(config-if)# ip address 20.1.1.1/24	Assigns the primary IP address.
PE1(config-if)# exit	Exit from xe2 VLAN interface configuration mode.
PE1(config)#interface xe23	Enter xe23 interface configuration mode.
PE1(config-if)# static-channel-group 1	Configure static channel 1 member port
PE1(config)#router ospf 1	Enters the OSPF configuration mode for OSPF process 1.
PE1(config-router)# network 16.16.16.0/24 area 0.0.0.0	Advertises the network 16.16.16.0/24 into OSPF area 0.0.0.0.
PE1(config-router)# network 17.17.17.0/24 area 0.0.0.0	Advertises the network 17.17.17.0/24 into OSPF area 0.0.0.0.
PE1(config-router)# network 20.1.1.0/24 area 0.0.0.0	Advertises the network 20.1.1.0/24 into OSPF area 0.0.0.0.

Configure ISIS Router

Perform the following configurations to create multiple VxLAN interfaces and set up ISIS routing process on PE2 node.

PE2

PE2 (config) #vlan database	Enter the VLAN configuration mode.
PE2 (config-vlan) # vlan 100-101 bridge 1 state enable	Enable VLAN (100-101) on bridge 1. Specifying the enable state allows forwarding of frames on this VLAN-aware bridge
PE2 (config-vlan) #interface po1	Enter po1 interface mode.
PE2 (config-if) # switchport	Configure port as L2.
PE2 (config-if) # bridge-group 1	Associate the interface with bridge group 1.
PE2 (config-if) # switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
PE2 (config-if) # switchport trunk allowed vlan add 100-101	Enable VLAN ID 100-101 on this port.
PE2 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the po1 interface.
PE2 (config-if) #interface lo	Configure loopback interface
PE2 (config-if) # ip address 2.2.2.2/32 secondary	Assign the secondary IP address to lo
PE2 (config-if) #interface vlan1.100	Enter interface VLAN1.100 configuration mode.
PE2 (config-if) # ip address 11.11.11.1/24	Assign primary IP address
PE2 (config-if) # ip address 12.1.1.1/24 secondary	Assign secondary IP address towards MH node.
PE2 (config-if) # ip address 13.1.1.1/24 secondary	Assign secondary address towards MH node
PE2 (config-if) # ip router isis 1	Configure the isis
PE2 (config-if) # exit	Exit from VLAN interface configuration mode.
PE2 (config) #interface xe11	Enter xe11 interface configuration mode.
PE2 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the xe11 interface.
PE2 (config-if) #interface xe11.105	Configure subinterface xe11.105.
PE2 (config-if) # encapsulation dot1q 105	Setting Encapsulation to dot1q with VLAN ID 105.
PE2 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the xe11 interface.
PE2 (config-if) # ip address 10.1.1.1/24	Assign an IP address
PE2 (config-if) # ip router isis 1	Configure interface as ISIS router
PE2 (config-if) # exit	Exit from xe11 interface configuration mode.
PE2 (config) #interface xe24	Enter xe24 interface configuration mode.
PE2 (config-if) # channel-group 1 mode active	Configure the member port for po1 interface
PE2 (config-if) # exit	Exit from xe24 interface configuration mode.
PE2 (config-if) #interface xe26	Enter xe26 interface configuration mode.

PE2(config-if) # channel-group 1 mode active	Configure the member port for po1 interface
PE2(config)#router isis 1	Configure the ISIS router.
PE2(config-router) # is-type level-1-2	Configure level1-2 ISIS mode.
PE2(config-router) # metric-style wide	Configure metric style as wide.
PE2(config-router) # dynamic-hostname	Configure the hostname to be advertised for an ISIS 1 instance.
PE2(config-router) # bfd all-interfaces	Enable the Bidirectional Forwarding Detection (BFD) feature on all the interfaces enabled with this ISIS instance.
PE2(config-router) # net 49.0000.0000.0001.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
PE2(config-router) # redistribute connected	Redistribute the connected routes.

Configure VxLAN IRB with Multihoming for OSPF and ISIS Router

Perform the following configurations to create VxLAN IRB interfaces with multihoming for OSPF and ISIS routing process on PE7 and PE8 node.

PE7

PE7(config)#nvo vxlan enable	Enable VxLAN.
PE7(config)#nvo vxlan irb	Enable VxLAN IRB
PE7(config)#evpn esi hold-time 60	Configure hold time for the tunnels to come up during VxLAN initialization before making the esi up.
PE7(config)#evpn vxlan multihoming enable	Enable VxLAN multihome
PE7(config)#ip vrf management	Enter into VRF configuration mode.
PE7(config-vrf)#ip vrf L3VRF3	Create a VRF routing information base called L3VRF3 for OSPF router.
PE7(config-vrf)# rd 7100:11	Specify a route distinguisher for the VRF.
PE7(config-vrf)# route-target both 100:100	Add import and export route-target extended communities to the VRF.
PE7(config-vrf)# 13vni 1000	Configure the L3 Virtual Network Identifier for an IP VRF.
PE7(config-vrf)#ip vrf L3VRF4	Create a VRF routing information base called L3VRF4 for ISIS router.
PE7(config-vrf)# rd 7400:11	Specify a route distinguisher for the VRF.
PE7(config-vrf)# route-target both 101:101	Add import and export route-target extended communities to the VRF.
PE7(config-vrf)# 13vni 2000	Configure the L3 Virtual Network Identifier for an IP VRF.
PE7(config-vrf)#mac vrf L2VRF1	Create a L2 MAC VRF to use in EVPN routes.
PE7(config-vrf)# rd 7.7.7.7:11	Specify a route distinguisher for the MAC VRF.
PE7(config-vrf)# route-target both 7.7.7.7:100	Add import and export route-target extended communities to the VRF.
PE7(config-vrf)#mac vrf L2VRF2	Create a L2 MAC VRF to use in EVPN routes.
PE7(config-vrf)# rd 7.7.7.7:12	Specify a route distinguisher for the VRF.

PE7 (config-vrf) # route-target both 7.7.7.7:101	Add import and export route-target extended communities to the VRF
PE7 (config-vrf) #exit	Exit the VRF configuration mode.
PE7 (config) #evpn irb-forwarding anycast-gateway-mac 0000.0000.1111	Configure common Anycast MAC address for all the IRB interfaces.
PE7 (config) #interface irb701	Enter into IRB interface configuration mode to configure IRB interfaces for OSPF router.
PE7 (config-irb-if) # ip vrf forwarding L3VRF3	Associate IRB interface with L3VRF3.
PE7 (config-irb-if) # evpn irb-if-forwarding anycast-gateway-mac	Map the global anycast IRB MAC address with L3VRF3.
PE7 (config-irb-if) # ip address 17.12.13.1/24 anycast	Configure an Anycast IP address.
PE7 (config-irb-if) # ip address 16.16.16.2/24 secondary	Configure a secondary IP address.
PE7 (config-irb-if) #exit	Exit from the IRB interface.
PE7 (config-irb-if) #interface irb801	Enter into IRB interface configuration mode to configure IRB interfaces for ISIS router.
PE7 (config-irb-if) # ip vrf forwarding L3VRF4	Associate IRB interface with L3VRF4.
PE7 (config-irb-if) # evpn irb-if-forwarding anycast-gateway-mac	Map the global anycast IRB MAC address with L3VRF4.
PE7 (config-irb-if) # ip address 12.13.14.2/24 anycast	Configure an Anycast IP address.
PE7 (config-irb-if) # ip address 13.1.1.2/24 secondary	Configure a secondary IP address.
PE7 (config-irb-if) # ip router isis 2	Configure ISIS router on IRB interface.
PE7 (config-irb-if) #exit	Exit from the IRB interface.
PE7 (config) #nvo vxlan vtep-ip-global 7.7.7.7	Configure the source VTEP IP address of the VxLAN tunnel.
PE7 (config) #nvo vxlan id 701 ingress-replication inner-vid-disabled	Add a tenant L2 VNID to the VxLAN. Specify <ul style="list-style-type: none"> ingress-replication to use head end replication for forwarding BUM traffic inner-vid-disabled to not carry VID out of network port.
PE7 (config-nvo) # vxlan host-reachability-protocol evpn-bgp L2VRF1	Associate the L2VRF1reachable protocol to Ethernet-VPN over BGP
PE7 (config-nvo) # evpn irb701	Configure default gateway behavior for IRB interface irb701.
PE7 (config-nvo) # vni-name VNI-701	Configure VNI name.
PE7 (config-nvo) #exit	Exit from NVO mode.
PE7 (config-nvo) #nvo vxlan id 801 ingress-replication inner-vid-disabled	Add a tenant L2 VNID to the VxLAN. Specify <ul style="list-style-type: none"> ingress-replication to use head end replication for forwarding BUM traffic inner-vid-disabled to not carry VID out of network port
PE7 (config-nvo) # vxlan host-reachability-protocol evpn-bgp L2VRF2	Associate the L2VRF2reachable protocol to Ethernet-VPN over BGP

PE7 (config-nvo) # evpn irb801	Configure default gateway behavior for IRB interface irb801.
PE7 (config-nvo) # vni-name VNI-101	Configure VNI name.
PE7 (config-nvo) #qos enable	Enable QoS.
PE7 (config-nvo) #exit	Exit from NVO mode.
PE7 (config) #interface po1	Configure po1 interface.
PE7 (config-if) # switchport	Configure port as L2.
PE7 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the po1 interface.
PE7 (config-if) # evpn multi-homed system-mac 0000.0000.7782	Configure system MAC as ESI value for po1 interface. VTEP1 and VTEP2 should have same ESI value.
PE7 (config-if) #interface sa1	Configure sa1 interface.
PE7 (config-if) # switchport	Configure port as L2.
PE7 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the po1 interface.
PE7 (config-if) # evpn multi-homed esi 00:01:02:03:04:05:06:07:08	Configure 9-octet ESI value for sa1 interface.
PE7 (config-if-es) #interface sa2	Configure sa2 interface.
PE7 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the sa2 interface.
PE7 (config-if) # ip address 80.1.1.1/24	Configure IP address.
PE7 (config-if) # mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE7 (config-if) # ip router isis 1	Configure ISIS router on sa2 interface.
PE7 (config-if) #exit	Exit from the sa2 interface.
PE7 (config) #interface sa3	Configure sa3 interface.
PE7 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the sa3 interface.
PE7 (config-if) # ip address 22.1.1.1/24	Configure IP address.
PE7 (config-if) # mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE7 (config-if) #interface ce50	Configure ce50 interface.
PE7 (config-if) # static-channel-group 1	Configure member port for sa3
PE7 (config-if) #exit	Exit from ce50 interface configuration mode.
PE7 (config) #interface lo	Configure loopback interface.
PE7 (config-if) # ip address 7.7.7.7/32 secondary	Configure secondary IP address
PE7 (config-if) #exit	Exit from the lo interface.
PE7 (config) #interface xe1	Configure xe1 interface.
PE7 (config-if) # channel-group 1 mode active	Configure member port of po1 interface.
PE7 (config-if) #interface xe39	Configure xe39 interface.
PE7 (config-if) # static-channel-group 3	Configure member port of sa3 interface.
PE7 (config-if) #interface xe40	Configure xe40 interface.
PE7 (config-if) # static-channel-group 2	Configure member port of sa2 interface.
PE7 (config-if) #exit	Exit from the xe40 interface.
PE7 (config) #router ospf 1	Configure OSPF router.

PE7(config-router)# ospf router-id 7.7.7.7	Configure router id for OSPF.
PE7(config-router)# network 7.7.7.7/32 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 7.7.7.7/32
PE7(config-router)# network 22.1.1.0/24 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on interface with IP address that match the network address 22.1.1.0/24 .
PE7(config-router)#router ospf 2 L3VRF3	Configure OSPF on IRB L3VRF3.
PE7(config-router)# redistribute bgp	Redistribute BGP routes.
PE7(config-router)# network 16.16.16.0/24 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 16.16.16.0/24.
PE7(config-router)#router isis 1	Configure ISIS router.
PE7(config-router)# is-type level-1-2	Configure IS type as level 1 and level 2.
PE7(config-router)# metric-style wide	Configure metric-style as wide.
PE7(config-router)# dynamic-hostname	Configure the hostname to advertise for the ISIS router.
PE7(config-router)# bfd all-interfaces	Enable the Bidirectional Forwarding Detection (BFD) feature on all the interfaces enabled with this ISIS instance.
PE7(config-router)# net 49.0000.0007.0001.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
PE7(config-router)# redistribute connected	Redistribute connected routes.
PE7(config-router)#router isis 2 L3VRF4	Configure ISIS on IRB L3VRF4.
PE7(config-router)# is-type level-1-2	Configure IS type as level 1 and level 2.
PE7(config-router)# metric-style wide	Configure metric-style as wide.
PE7(config-router)# dynamic-hostname	Configure the hostname to advertise for the ISIS router.
PE7(config-router)# bfd all-interfaces	Enable the Bidirectional Forwarding Detection (BFD) feature on all the interfaces enabled with this ISIS instance.
PE7(config-router)# net 49.0000.0000.0475.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
PE7(config-router)# redistribute bgp	Redistribute connected routes.
PE7(config-router)#router bgp 700	Start the eBGP router.
PE7(config-router)# bgp router-id 7.7.7.7	Configure BGP router id.
PE7(config-router)# no bgp inbound-route-filter	Disable the VPN/BGP inbound route-target filter.
PE7(config-router)# neighbor 5.5.5.5 remote-as 500	Configure BGP peering relationship with a customer edge router.
PE7(config-router)# neighbor 6.6.6.6 remote-as 600	Configure BGP peering relationship with a customer edge router.
PE7(config-router)# neighbor 6.6.6.6 advertisement-interval 0	Configure a minimum advertisement interval between the sending of BGP routing updates.
PE7(config-router)# address-family l2vpn evpn	Enter to the L2 VPN address family mode to configure the address-family specific parameters.
PE7(config-router-af)# neighbor 5.5.5.5 activate	Enable the exchange of specific address family routes with a neighboring router 5.5.5.5.

PE7(config-router-af) # neighbor 6.6.6.6 activate	Enable the exchange of specific address family routes with a neighboring router 6.6.6.6.
PE7(config-router-af) # exit-address-family	Exit from address family mode.
PE7(config-router) # address-family ipv4 vrf L3VRF3	Enter to the IRB IPv4 VRF address family mode to configure the address-family specific parameters.
PE7(config-router-af) # network 16.16.16.0/24	Enable OSPF routing on IRB interface with IP address that match the network address 16.16.16.0/24.
PE7(config-router-af) # redistribute ospf	Redistribute OSPF routes.
PE7(config-router-af) # exit-address-family	Exit from address family mode.
PE7(config-router) # address-family ipv4 vrf L3VRF4	Enter to the IRB IPv4 VRF address family mode to configure the address-family specific parameters.
PE7(config-router-af) # network 12.1.1.0/24	Enable OSPF routing on IRB interface with IP address that match the network address 12.1.1.0/24.
PE7(config-router-af) # redistribute isis	Redistribute ISIS routes.
PE7(config-router-af) # exit-address-family	Exit address family mode.
PE7(config)#nvo vxlan access-if port-vlan po1 100	Map the VLAN port for ISIS switch on po1 interface to identify the VxLAN traffic and to enter NVO access interface mode.
PE7(config-nvo-acc-if) # map vnid 801	Map the l2vnid to an access-port.
PE7(config-nvo-acc-if) #nvo vxlan access-if port-vlan sa1 200	Configure access-if port for OSPF switch.
PE7(config-nvo-acc-if) # map vnid 701	Map the l2vnid to an access-port.

PE8

PE8(config)#nvo vxlan enable	Enable VxLAN
PE8(config)#nvo vxlan irb	Enable VxLAN IRB
PE8(config)#evpn esi hold-time 60	Configure hold time for the tunnels to come up during VxLAN initialization before making the esi up.
PE8(config)#evpn vxlan multihoming enable	Enable VxLAN multihome
PE8(config)#ip vrf managemen	Enter into VRF configuration mode.
PE8(config-vrf)#ip vrf L3VRF3	Create a VRF routing information base called L3VRF3 for OSPF router.
PE8(config-vrf)# rd 8100:11	Specify a route distinguisher for the VRF.
PE8(config-vrf)# route-target both 100:100	Add import and export route-target extended communities to the VRF.
PE8(config-vrf)# 13vni 1000	Configure the L3 Virtual Network Identifier for an IP VRF.
PE8(config-vrf)#ip vrf L3VRF4	Create a VRF routing information base called L3VRF4 for ISIS router.
PE8(config-vrf)# rd 8400:11	Specify a route distinguisher for the VRF.
PE8(config-vrf)# route-target both 101:101	Add import and export route-target extended communities to the VRF.
PE8(config-vrf)# 13vni 2000	Configure the L3 Virtual Network Identifier for an IP VRF.
PE8(config-vrf)#mac vrf L2VRF1	Create a L2 MAC VRF to use in EVPN routes.
PE8(config-vrf)# rd 8.8.8.8:11	Specify a route distinguisher for the MAC VRF.

PE8 (config-vrf) # route-target both 7.7.7.7:100	Add import and export route-target extended communities to the VRF.
PE8 (config-vrf) #mac vrf L2VRF2	Create a L2 MAC VRF to use in EVPN routes.
PE8 (config-vrf) # rd 8.8.8.8:12	Specify a route distinguisher for the VRF.
PE8 (config-vrf) # route-target both 7.7.7.7:101	Add import and export route-target extended communities to the VRF.
PE7 (config-vrf) #exit	Exit the VRF configuration mode.
PE8 (config) #evpn irb-forwarding anycast-gateway-mac 0000.0000.1111	Configure common Anycast MAC address for all the IRB interfaces.
PE8 (config-if) #interface irb701	Enter into IRB interface configuration mode to configure IRB interfaces for OSPF router.
PE8 (config-irb-if) # ip vrf forwarding L3VRF3	Associate IRB interface with L3VRF3.
PE8 (config-irb-if) # evpn irb-if-forwarding anycast-gateway-mac	Map the global anycast IRB MAC address with L3VRF3.
PE8 (config-irb-if) # ip address 17.12.13.1/24 anycast	Configure an Anycast IP address.
PE8 (config-irb-if) # ip address 17.17.17.2/24 secondary	Configure a secondary IP address. PE7(config-irb-if)#exit Exit from the IRB interface.
PE8 (config-irb-if) #interface irb801	Enter into IRB interface configuration mode to configure IRB interfaces for ISIS router.
PE8 (config-irb-if) # ip vrf forwarding L3VRF4	Associate IRB interface with L3VRF4.
PE8 (config-irb-if) # evpn irb-if-forwarding anycast-gateway-mac	Map the global anycast IRB MAC address with L3VRF4.
PE8 (config-irb-if) # ip address 12.13.14.2/24 anycast	Configure an Anycast IP address.
PE8 (config-irb-if) # ip address 12.1.1.2/24 secondary	Configure an Anycast IP address.
PE8 (config-irb-if) # ip router isis 2	Configure ISIS router on IRB interface.
PE7 (config-irb-if) #exit	Exit from the IRB interface.
PE8 (config) #nvo vxlan vtep-ip-global 8.8.8.8	Configure the source VTEP IP address of the VxLAN tunnel.
PE8 (config) #nvo vxlan id 701 ingress-replication inner-vid-disabled	Add a tenant L2 VNID to the VxLAN. Specify ingress-replication to use head end replication for forwarding BUM traffic inner-vid-disabled to not carry VID out of network port
PE8 (config-nvo) # vxlan host-reachability-protocol evpn-bgp L2VRF1	Associate the L2VRF1reachable protocol to Ethernet-VPN over BGP
PE8 (config-nvo) # evpn irb701	Configure default gateway behavior for IRB interface irb701.
PE8 (config-nvo) # vni-name VNI-701	Configure VNI name.
PE7 (config-nvo) #exit	Exit from NVO mode.
PE8 (config-nvo) #nvo vxlan id 801 ingress-replication inner-vid-disabled	Add a tenant L2 VNID to the VxLAN. Specify ingress-replication to use head end replication for forwarding BUM traffic inner-vid-disabled to not carry VID out of network port
PE8 (config-nvo) # vxlan host-reachability-protocol evpn-bgp L2VRF2	Associate the L2VRF2reachable protocol to Ethernet-VPN over BGP

PE8 (config-nvo) # evpn irb801	Configure default gateway behavior for IRB interface irb801.
PE8 (config-nvo) # vni-name VNI-101	Configure VNI name.
PE8 (config-nvo) #qos enable	Enable QoS.
PE8 (config-nvo) #exit	Exit from NVO mode.
PE8 (config-vlan) #interface po1	Configure po1 interface.
PE8 (config-if) # switchport	Configure port as L2.
PE8 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the po1 interface.
PE8 (config-if) # evpn multi-homed system-mac 0000.0000.7782	Configure system MAC as ESI value for po1 interface. VTEP1 and VTEP2 should have same ESI value.
PE8 (config-if-es) #interface sa1	Configure sa1 interface.
PE8 (config-if) # switchport	Configure port as L2.
PE8 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the po1 interface.
PE8 (config-if) # evpn multi-homed esi 00:01:02:03:04:05:06:07:08	Configure 9-octet ESI value for sa1 interface.
PE8 (config-irb-if) #interface lo	Configure loopback interface
PE8 (config-if) # ip address 8.8.8.8/32 secondary	Configure secondary IP address
PE8 (config-if) #exit	Exit from the lo interface.
PE8 (config) #interface xe1	Configure xe1 interface.
PE8 (config-if) # static-channel-group 1	Configure member port of sa3 interface.
PE8 (config-if) #interface xe2	Configure xe2 interface.
PE8 (config-if) # ip address 90.1.1.1/24	Configure IP address
PE8 (config-if) # mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE8 (config-if) # ip router isis 1	Configure ISIS router on IRB interface.
PE8 (config-if) #exit	Exit from the lo interface.
PE8 (config) #interface xe12	Configure xe1 interface.
PE8 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the po1 interface.
PE8 (config-if) # ip address 21.1.1.1/24	Configure IP address
PE8 (config-if) # mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE8 (config-if) #exit	Exit from the lo interface.
PE8 (config-if) #interface xe26	Configure xe26 interface.
PE8 (config-if) # channel-group 1 mode active	Configure member port of xe26 interface.
PE8 (config) #router ospf 1	Configure OSPF router.
PE8 (config-router) # ospf router-id 8.8.8.8	Configure router id for OSPF.
PE8 (config-router) # network 8.8.8.8/32 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 8.8.8.8/32.
PE8 (config-router) # network 21.1.1.0/24 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 21.1.1.0/24.
PE8 (config-router) #router ospf 2 L3VRF3	Configure OSPF on IRB L3VRF3.

PE8 (config-router) # redistribute bgp	Redistribute BGP routes.
PE8 (config-router) # network 17.17.17.0/24 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 17.17.17.0/24
PE8 (config-router) #router isis 1	Configure ISIS router.
PE8 (config-router) # is-type level-1-2	Configure IS type as level 1 and level 2.
PE8 (config-router) # metric-style wide	Configure metric-style as wide.
PE8 (config-router) # dynamic-hostname	Configure the hostname to advertise for the ISIS router.
PE8 (config-router) # bfd all-interfaces	Enable the Bidirectional Forwarding Detection (BFD) feature on all the interfaces enabled with this ISIS instance.
PE8 (config-router) # net 49.0000.0008.0001.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
PE8 (config-router) # redistribute connected	Redistribute connected routes.
PE8 (config-router) #router isis 2 L3VRF4	Configure ISIS on IRB L3VRF4.
PE8 (config-router) # is-type level-1-2	Configure IS type as level 1 and level 2.
PE8 (config-router) # metric-style wide	Configure metric-style as wide.
PE8 (config-router) # dynamic-hostname	Configure the hostname to advertise for the ISIS router.
PE8 (config-router) # bfd all-interfaces	Enable the Bidirectional Forwarding Detection (BFD) feature on all the interfaces enabled with this ISIS instance.
PE8 (config-router) # net 49.0000.0000.0485.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
PE8 (config-router) # redistribute bgp	Redistribute connected routes.
PE8 (config-router) #router bgp 800	Start the eBGP router.
PE8 (config-router) # bgp router-id 8.8.8.8	Configure BGP router id.
PE8 (config-router) # no bgp inbound-route-filter	Disable the VPN/BGP inbound route-target filter.
PE8 (config-router) # neighbor 5.5.5.5 remote-as 500	Configure BGP peering relationship with a customer edge router.
PE8 (config-router) # neighbor 6.6.6.6 remote-as 600	Configure BGP peering relationship with a customer edge router.
PE8 (config-router) # neighbor 6.6.6.6 update-source lo	Configure a minimum advertisement interval between the sending of BGP routing updates.
PE8 (config-router) # address-family l2vpn evpn	Enter to the L2 VPN address family mode to configure the address-family specific parameters.
PE8 (config-router-af) # neighbor 5.5.5.5 activate	Enable the exchange of specific address family routes with a neighboring router 5.5.5.5.
PE8 (config-router-af) # neighbor 6.6.6.6 activate	Enable the exchange of specific address family routes with a neighboring router 6.6.6.6.
PE8 (config-router-af) # exit-address-family	Exit from address family mode.
PE8 (config-router) # address-family ipv4 vrf L3VRF3	Enter to the IRB IPv4 VRF address family mode to configure the address-family specific parameters.
PE8 (config-router-af) # network 16.16.16.0/24	Enable OSPF routing on IRB interface with IP address that match the network address 16.16.16.0/24.
PE8 (config-router-af) # redistribute ospf	Redistribute OSPF routes.
PE8 (config-router-af) # exit-address-family	Exit from address family mode.
PE8 (config-router) # address-family ipv4 vrf L3VRF4	Enter to the IRB IPv4 VRF address family mode to configure the address-family specific parameters.

PE8 (config-router-af) # network 12.1.1.0/24	Enable OSPF routing on IRB interface with IP address that match the network address 12.1.1.0/24.
PE8 (config-router-af) # redistribute isis	Redistribute ISIS routes.
PE8 (config-router-af) # exit-address-family	Exit address family mode.
PE8 (config-router) # exit	Exit from router mode configuration.
PE8 (config) #nvo vxlan access-if port-vlan po1 100	Map the VLAN port for ISIS switch on po1 interface to identify the VxLAN traffic and to enter NVO access interface mode.
PE8 (config-nvo-acc-if) # map vnid 801	Map the l2vnid to an access-port.
PE8 (config-nvo-acc-if) #nvo vxlan access-if port-vlan sa1 200	Configure access-if port for OSPF switch.
PE8 (config-nvo-acc-if) # map vnid 701	Map the l2vnid to an access-port.
PE8 (config-nvo-acc-if) #end	End global configuration.

Configure Spine Node with OSPF Router

Perform the following configurations to make the node as spine with routing protocol as OSPF.

PE5

PE5 (config-if) #interface sa3	Configure sa3 interface.
PE5 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the sa3 interface.
PE5 (config-if) # ip address 22.1.1.2/24	Configure IP address
PE5 (config-if) # mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE5 (config-if) #interface lo	Configure loopback interface
PE5 (config-if) # ip address 5.5.5.5/32 secondary	Configure secondary IP address.
PE7 (config-if) #exit	Exit from the lo interface.
PE5 (config-if) #interface xe8	Configure xe8 interface.
PE5 (config-if) # static-channel-group 3	Configure member port of sa3 interface.
PE5 (config-if) #interface xe12	Configure xe12 interface.
PE5 (config-if) # ip address 21.1.1.2/24	Configure IP address
PE5 (config-if) # mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE5 (config-if) #interface xe14	Configure xe14 interface.
PE5 (config-if) # ip address 23.1.1.2/24	Configure IP address
PE5 (config-if) # mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE5 (config-if) #interface xe25	Configure xe25 interface.
PE5 (config-if) # ip address 24.1.1.2/24	Configure IP address
PE5 (config-if) # mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE5 (config) #router ospf 1	Configure OSPF router.

PE5(config-router)# network 5.5.5.5/32 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 5.5.5.5/32.
PE5(config-router)# network 21.1.1.0/24 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 21.1.1.0/24.
PE5(config-router)# network 22.1.1.0/24 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 22.1.1.0/24.
PE5(config-router)# network 23.1.1.0/24 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 23.1.1.0/24.
PE5(config-router)# network 24.1.1.0/24 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 24.1.1.0/24.
PE5(config-router)#router bgp 500	Start the eBGP router 500.
PE5(config-router)# bgp router-id 5.5.5.5	Configure BGP router id 5.5.5.5.
PE5(config-router)# no bgp inbound-route-filter	Disable the VPN/BGP inbound route-target filter.
PE5(config-router)# neighbor 3.3.3.3 remote-as 300	Configure BGP 3.3.3.3 peering relationship with a customer edge router.
PE5(config-router)# neighbor 4.4.4.4 remote-as 400	Configure BGP 4.4.4.4 peering relationship with a customer edge router.
PE5(config-router)# neighbor 7.7.7.7 remote-as 700	Configure BGP 7.7.7.7 peering relationship with a customer edge router.
PE5(config-router)# neighbor 8.8.8.8 remote-as 800	Configure BGP 8.8.8.8 peering relationship with a customer edge router.
PE5(config-router)# neighbor 3.3.3.3 update-source lo	Specifies that loopback interface (lo) is the source for the BGP 3.3.3.3 to establish the TCP connections.
PE5(config-router)# neighbor 4.4.4.4 update-source lo	Specifies that loopback interface (lo) is the source for the BGP 4.4.4.4 to establish the TCP connections.
PE5(config-router)# neighbor 7.7.7.7 update-source lo	Specifies that loopback interface (lo) is the source for the BGP 7.7.7.7 to establish the TCP connections.
PE5(config-router)# neighbor 8.8.8.8 update-source lo	Specifies that loopback interface (lo) is the source for the BGP 8.8.8.8 to establish the TCP connections.
PE5(config-router)# address-family l2vpn evpn	Enter to the L2 VPN address family mode to configure the address-family specific parameters.
PE5(config-router-af)# neighbor 3.3.3.3 activate	Enable the exchange of specific address family routes with a neighboring router 3.3.3.3.
PE5(config-router-af)# neighbor 4.4.4.4 activate	Enable the exchange of specific address family routes with a neighboring router 4.4.4.4.
PE5(config-router-af)# neighbor 7.7.7.7 activate	Enable the exchange of specific address family routes with a neighboring router 7.7.7.7.
PE5(config-router-af)# neighbor 8.8.8.8 activate	Enable the exchange of specific address family routes with a neighboring router 8.8.8.8.
PE5(config-router-af)# exit-address-family	Exit address family configuration mode.
PE5(config-router)# exit	Exit router configuration mode.
PE5(config)#end	Exit global configuration mode.

Configure Spine Node with ISIS Router

Perform the following configurations to make the node as spine with routing protocol as ISIS.

PE6

PE6(config-if)#interface sa2	Configure sa2 interface.
PE6(config-if)# load-interval 30	Configures the load-interval for monitoring traffic on the sa2 interface.
PE6(config-if)# ip address 80.1.1.2/24	Configure IP address.
PE6(config-if)# mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE6(config-if)# ip router isis 1	Configure ISIS router on sa2 interface.
PE6(config-if)#interface ce2	Configure ce2 interface.
PE6(config-if)# ip address 101.1.1.1/24	Configure IP address
PE6(config-if)# mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE6(config-if)# ip router isis 1	Configure ISIS router on sa2 interface.
PE6(config-if)#interface lo	Configure loopback interface
PE6(config-if)# ip address 6.6.6.6/32 secondary	Configure secondary IP address.
PE6(config-if)# ip router isis 1	Configure ISIS router on sa2 interface.
PE6(config-if)#interface xe5	Configure xe5 interface.
PE6(config-if)# ip address 102.1.1.1/24	Configure IP address
PE6(config-if)# mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE6(config-if)# ip router isis 1	Configure ISIS router on xe5 interface.
PE6(config-if)#interface xe9	Configure xe9 interface.
PE6(config-if)# static-channel-group 2	Configure member port of sa2 interface.
PE6(config-if)#interface xe24	Configure xe24 interface.
PE6(config-if)# ip address 90.1.1.2/24	Configure IP address
PE6(config-if)# mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE6(config-if)# ip router isis 1	Configure ISIS router on xe24 interface.
PE6(config)#router isis 1	Configure ISIS router on xe24 interface.
PE6(config-router)# is-type level-1-2	Configure IS type as level 1 and level 2.
PE6(config-router)# metric-style wide	Configure metric-style as wide.
PE6(config-router)# dynamic-hostname	Configure the hostname to advertise for the ISIS router.
PE6(config-router)# bfd all-interfaces	Enable the Bidirectional Forwarding Detection (BFD) feature on all the interfaces enabled with this ISIS instance.
PE6(config-router)# net 49.0000.0006.0001.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
PE6(config-router)#router bgp 600	Start the eBGP router.
PE6(config-router)# bgp router-id 6.6.6.6	Configure BGP router id.
PE6(config-router)# no bgp inbound-route-filter	Disable the VPN/BGP inbound route-target filter.
PE6(config-router)# neighbor 3.3.3.3 remote-as 300	Configure BGP peering relationship with a customer edge router.
PE6(config-router)# neighbor 4.4.4.4 remote-as 400	Configure BGP peering relationship with a customer edge router.

PE6(config-router)# neighbor 7.7.7.7 remote-as 700	Configure BGP peering relationship with a customer edge router.
PE6(config-router)# neighbor 8.8.8.8 remote-as 800	Configure BGP peering relationship with a customer edge router.
PE6(config-router)# neighbor 3.3.3.3 update-source lo	Specifies that loopback interface (lo) is the source for the BGP 3.3.3.3 to establish the TCP connections
PE6(config-router)# neighbor 4.4.4.4 update-source lo	Specifies that loopback interface (lo) is the source for the BGP 4.4.4.4 to establish the TCP connections
PE6(config-router)# neighbor 7.7.7.7 update-source lo	Specifies that loopback interface (lo) is the source for the BGP 7.7.7.7 to establish the TCP connections
PE6(config-router)# neighbor 8.8.8.8 update-source lo	Specifies that loopback interface (lo) is the source for the BGP 8.8.8.8 to establish the TCP connections
PE6(config-router)# address-family l2vpn evpn	Enter to the L2 VPN address family mode to configure the address-family specific parameters.
PE6(config-router-af)# neighbor 3.3.3.3 activate	Enable the exchange of specific address family routes with a neighboring router 3.3.3.3.
PE6(config-router-af)# neighbor 4.4.4.4 activate	Enable the exchange of specific address family routes with a neighboring router 4.4.4.4.
PE6(config-router-af)# neighbor 7.7.7.7 activate	Enable the exchange of specific address family routes with a neighboring router 7.7.7.7.
PE6(config-router-af)# neighbor 8.8.8.8 activate	Enable the exchange of specific address family routes with a neighboring router 8.8.8.8.
PE6(config-router-af)# exit-address-family	Exit address family configuration mode.
PE6(config-router)# exit	Exit router configuration mode.
PE6(config)#end	Exit global configuration mode.

Configure VxLAN IRB with Single Homing OSPF and ISIS Router

Perform the following configurations to create VxLAN IRB interfaces with singlehomming for OSPF and ISIS routing process on PE3 and PE4 nodes.

PE3

PE3(config)#nvo vxlan enable	Enable VxLAN.
PE3(config)#nvo vxlan irb	Enable VxLAN IRB
PE3(config)#ip vrf management	Enter into VRF configuration mode.
PE3(config-vrf)#ip vrf L3VRF1	Create a VRF routing information base called L3VRF3 for OSPF router.
PE3(config-vrf)# rd 56000:11	Specify a route distinguisher for the VRF.
PE3(config-vrf)# route-target both 100:100	Add import and export route-target extended communities to the VRF.
PE3(config-vrf)# 13vni 1000	Configure the L3 Virtual Network Identifier for an IP VRF.
PE3(config-vrf)#mac vrf L2VRF1	Create a L2 MAC VRF to use in EVPN routes.
PE3(config-vrf)# rd 4.4.4.4:11	Specify a route distinguisher for the MAC VRF.

PE3 (config-vrf) # route-target both 9.9.9.9:100	Add import and export route-target extended communities to the VRF.
PE3 (config-if) # interface irb1001	Enter into IRB interface configuration mode to configure IRB interfaces for OSPF router.
PE3 (config-irb-if) # ip vrf forwarding L3VRF1	Associate IRB interface with L3VRF3.
PE3 (config-irb-if) # ip address 40.1.1.1/24	Configure an Anycast IP address.
PE3 (config-irb-if) # ip ospf cost 1	Specify the cost of the link-state metric in a router-LSA.
PE3 (config-vrf) # nvo vxlan vtep-ip-global 3.3.3.3	Configure the source VTEP IP address of the VxLAN tunnel.
PE3 (config) # nvo vxlan id 102 ingress-replication	Add a tenant L2 VNID to the VxLAN. Specify ingress-replication to use head end replication for forwarding BUM traffic inner-vid-disabled to not carry VID out of network port
PE3 (config-nvo) # vxlan host-reachability-protocol evpn-bgp L2VRF1	Associate the L2VRF1 reachable protocol to Ethernet-VPN over BGP
PE3 (config-nvo) # evpn irb1001	Configure default gateway behavior for IRB interface irb1001.
PE3 (config-nvo) # vni-name VNI-102	Configure VNI name.
PE3 (config-nvo) # nvo vxlan id 2002 ingress-replication	Add a tenant L2 VNID to the VxLAN. Specify ingress-replication to use head end replication for forwarding BUM traffic inner-vid-disabled to not carry VID out of network port
PE3 (config-nvo) # vxlan host-reachability-protocol evpn-bgp L2VRF1	Associate the L2VRF1 reachable protocol to Ethernet-VPN over BGP
PE3 (config-nvo) # evpn irb2002	Configure default gateway behavior for IRB interface irb72002.
PE3 (config-nvo) # qos enable	Enable QoS.
PE3 (config) # interface sa4	Configure sa4 interface.
PE3 (config-if) # switchport	Configure port as L2.
PE3 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the po1 interface.
PE3 (config) # nvo vxlan access-if port-vlan sa4 100	Map the VLAN port for ISIS switch on sa4 interface to identify the VxLAN traffic and to enter NVO access interface mode.
PE3 (config-acc-if-evpn) # map vpn-id 102	Map the l2vnid to an access-port.
PE3 (config-if) # interface ce3	Configure ce3 interface.
PE3 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the ce3 interface.
PE3 (config-if) # ip address 101.1.1.2/24	Configure IP address.
PE3 (config-if) # mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE3 (config-if) # ip router isis 1	Configure ISIS router on ce3 interface.
PE3 (config-irb-if) # interface lo	Configure loopback interface
PE3 (config-if) # ip address 3.3.3.3/32 secondary	Configure secondary IP address
PE3 (config-if) # ip router isis 1	Configure ISIS router on ce3 interface.
PE3 (config-if) # interface xe10	Configure xe10 interface.
PE3 (config-if) # static-channel-group 4	Configure member port of ce3 interface.

PE3(config-if)#interface xe14	Configure xe14 interface.
PE3(config-if)# speed 10g	Set the link speed of the xe14 interface.
PE3(config-if)# ip address 23.1.1.1/24	Configure IP address.
PE3(config-if)# mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE3(config)#router ospf 1	Configure OSPF router.
PE3(config-router)# ospf router-id 3.3.3.3	Configure router id for OSPF.
PE3(config-router)# network 3.3.3.3/32 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 3.3.3.3/32.
PE3(config-router)# network 23.1.1.0/24 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 23.1.1.0/24.
PE3(config-router)# network 101.1.1.0/24 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 101.1.1.0/24.
PE3(config-router)#router ospf 2 L3VRF1	Configure OSPF on IRB L3VRF1.
PE3(config-router)# redistribute bgp	Redistribute BGP into OSPF.
PE3(config-router)# network 40.1.1.0/24 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 40.1.1.0/24.
PE3(config-router)#router isis 1	Configure ISIS router on xe24 interface.
PE3(config-router)# is-type level-1-2	Configure IS type as level 1 and level 2.
PE3(config-router)# metric-style wide	Configure metric-style as wide.
PE3(config-router)# dynamic-hostname	Configure the hostname to advertise for the ISIS router.
PE3(config-router)# bfd all-interfaces	Enable the Bidirectional Forwarding Detection (BFD) feature on all the interfaces enabled with this ISIS instance.
PE3(config-router)# net 49.0000.0003.0001.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
PE3(config-router)# redistribute connected	Redistribute connected routes.
PE3(config-router)#router bgp 300	Start the eBGP router.
PE3(config-router)# bgp router-id 3.3.3.3	Configure BGP router id.
PE3(config-router)# no bgp inbound-route-filter	Disable the VPN/BGP inbound route-target filter.
PE3(config-router)# neighbor 5.5.5.5 remote-as 500	Configure BGP peering relationship with a customer edge router.
PE3(config-router)# neighbor 6.6.6.6 remote-as 600	Configure BGP peering relationship with a customer edge router.
PE3(config-router)# neighbor 5.5.5.5 update-source lo	Specifies that loopback interface (lo) is the source for the BGP 5.5.5.5 to establish the TCP connections
PE3(config-router)# neighbor 6.6.6.6 advertisement-interval 0	Configure a minimum advertisement interval between the sending of BGP routing updates.
PE3(config-router)# address-family l2vpn evpn	Enter to the L2 VPN address family mode to configure the address-family specific parameters.
PE3(config-router-af)# neighbor 5.5.5.5 activate	Enable the exchange of specific address family routes with a neighboring router 5.5.5.5.

PE3(config-router-af) # neighbor 6.6.6.6 activate	Enable the exchange of specific address family routes with a neighboring router 6.6.6.6.
PE3(config-router-af) # exit-address-family	Exit address family configuration mode.
PE3(config-router) # address-family ipv4 vrf L3VRF1	Enter to the IRB IPv4 VRF address family mode to configure the address-family specific parameters.
PE3(config-router-af) # redistribute connected	Redistribute connected routes.
PE3(config-router-af) # redistribute ospf	Redistribute OSPF routes.
PE3(config-router-af) # exit-address-family	Exit address family configuration mode.
PE3(config-router) # exit	Exit router configuration mode.
PE3(config)#end	Exit global configuration mode.

PE4

PE4(config)#nvo vxlan enable	Enable VxLAN.
PE4(config)#nvo vxlan irb	Enable VxLAN IRB
PE4(config)#ip vrf management	Enter into VRF configuration mode.
PE4(config-vrf)#ip vrf L3VRF2	Create a VRF routing information base called L3VRF2 for OSPF router.
PE4(config-vrf)# rd 63000:11	Specify a route distinguisher for the VRF.
PE4(config-vrf)# route-target both 101:101	Add import and export route-target extended communities to the VRF.
PE4(config-vrf)# l3vni 2000	Configure the L3 Virtual Network Identifier for an IP VRF.
PE4(config-vrf)#mac vrf L2VRF2	Create a L2 MAC VRF to use in EVPN routes.
PE4(config-vrf)# rd 3.3.3.3:11	Specify a route distinguisher for the MAC VRF.
PE4(config-vrf)# route-target both 10.10.10.10:100	Add import and export route-target extended communities to the VRF.
PE4(config-if)#interface irb2001	Enter into IRB interface configuration mode to configure IRB interfaces for OSPF router.
PE4(config-irb-if)# ip vrf forwarding L3VRF2	Associate IRB interface with L3VRF3.
PE4(config-irb-if)# ip address 50.50.50.1/24	Configure an Anycast IP address.
PE4(config-irb-if)# ip router isis 2	Configure ISIS router on IRB interface.
PE4(config-vrf)#nvo vxlan vtep-ip-global 4.4.4.4	Configure the source VTEP IP address of the VxLAN tunnel.
PE4(config)#nvo vxlan id 201 ingress-replication	Add a tenant L2 VNID to the VxLAN. Specify ingress-replication to use head end replication for forwarding BUM traffic
PE4(config-nvo)# vxlan host-reachability-protocol evpn-bgp L2VRF2	Associate the L2VRF1 reachable protocol to Ethernet-VPN over BGP
PE4(config-nvo)# evpn irb2001	Configure default gateway behavior for IRB interface irb2001.
PE4(config-nvo)# vni-name VNI-201	Configure VNI name.
PE4(config-nvo)#nvo vxlan id 3002 ingress-replication	Add a tenant L2 VNID to the VxLAN. Specify ingress-replication to use head end replication for forwarding BUM traffic.

PE4 (config-nvo) # vxlan host-reachability-protocol evpn-bgp L2VRF2	Associate the L2VRF2 reachable protocol to Ethernet-VPN over BGP.
PE4 (config-nvo) # evpn irb3002	Configure default gateway behavior for IRB interface irb3002.
PE4 (config-nvo) #nvo vxlan id 3003 ingress-replication	Add a tenant L2 VNID to the VxLAN. Specify ingress-replication to use head end replication for forwarding BUM traffic.
PE4 (config-nvo) #qos enable	Enable QoS.
PE4 (config-irb-if) #interface lo	Configure loopback interface
PE4 (config-if) # ip address 4.4.4.4/32 secondary	Configure secondary IP address
PE4 (config-if) # ip router isis 1	Configure ISIS router on lo interface.
PE4 (config-if) #interface xe5	Configure xe5 interface.
PE4 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the xe5 interface.
PE4 (config-if) # ip address 102.1.1.2/24	Configure IP address.
PE4 (config-if) # mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE4 (config-if) # ip router isis 1	Configure ISIS router on ce3 interface.
PE4 (config-if) #interface xe25	Configure xe25 interface.
PE4 (config-if) # ip address 24.1.1.1/24	Configure IP address.
PE4 (config-if) # mtu 9000	Configure the Maximum Transmission Unit (MTU).
PE4 (config-if) #interface xe26	Configure xe26 interface.
PE4 (config-if) # switchport	Configure port as L2.
PE4 (config-if) # load-interval 30	Configures the load-interval for monitoring traffic on the xe26 interface.
PE4 (config) #nvo vxlan access-if port-vlan xe26 200	Map the VLAN port for ISIS switch on xe26 interface to identify the VxLAN traffic and to enter NVO access interface mode.
PE4 (config-acc-if-evpn) # map vpn-id 201	Map the l2vnid to an access-port.
PE4 (config-if) # exit	Exit the interface configuration mode.
PE4 (config) #router ospf 1	Configure OSPF router.
PE4 (config-router) # network 4.4.4.4/32 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 4.4.4.4/32.
PE4 (config-router) # network 24.1.1.0/24 area 0.0.0.0	Enable OSPF routing with area ID 0.0.0.0 on IRB interface with IP address that match the network address 24.1.1.0/24.
PE4 (config-router) #router isis 1	Configure ISIS router on xe24 interface.
PE4 (config-router) # is-type level-1-2	Configure IS type as level 1 and level 2.
PE4 (config-router) # metric-style wide	Configure metric-style as wide.
PE4 (config-router) # dynamic-hostname	Configure the hostname to advertise for the ISIS router.
PE4 (config-router) # bfd all-interfaces	Enable the Bidirectional Forwarding Detection (BFD) feature on all the interfaces enabled with this ISIS instance.
PE4 (config-router) # net 49.0000.0004.0001.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
PE4 (config-router) # redistribute connected	Redistribute connected routes.

PE4 (config-router) # !	
PE4 (config-router) # router isis 2 L3VRF2	Configure ISIS on IRB L3VRF2.
PE4 (config-router) # is-type level-1-2	Configure IS type as level 1 and level 2.
PE4 (config-router) # metric-style wide	Configure metric-style as wide.
PE4 (config-router) # dynamic-hostname	Configure the hostname to advertise for the ISIS router.
PE4 (config-router) # bfd all-interfaces	Enable the Bidirectional Forwarding Detection (BFD) feature on all the interfaces enabled with this ISIS instance.
PE4 (config-router) # net 49.0000.0000.0441.00	Set a Network Entity Title for this instance, specifying the area address and the system ID.
PE4 (config-router) # router bgp 400	Start the eBGP router.
PE4 (config-router) # bgp router-id 4.4.4.4	Configure BGP router id.
PE4 (config-router) # no bgp inbound-route-filter	Disable the VPN/BGP inbound route-target filter.
PE4 (config-router) # neighbor 5.5.5.5 remote-as 500	Configure BGP peering relationship with a customer edge router.
PE4 (config-router) # neighbor 6.6.6.6 remote-as 600	Configure BGP peering relationship with a customer edge router.
PE4 (config-router) # neighbor 5.5.5.5 update-source lo	Specifies that loopback interface (lo) is the source for the BGP 5.5.5.5 to establish the TCP connections
PE4 (config-router) # neighbor 6.6.6.6 advertisement-interval 0	Configure a minimum advertisement interval between the sending of BGP routing updates.
PE4 (config-router) # address-family l2vpn evpn	Enter to the L2 VPN address family mode to configure the address-family specific parameters.
PE4 (config-router-af) # neighbor 5.5.5.5 activate	Enable the exchange of specific address family routes with a neighboring router 5.5.5.5.
PE4 (config-router-af) # neighbor 6.6.6.6 activate	Enable the exchange of specific address family routes with a neighboring router 6.6.6.6.
PE4 (config-router-af) # exit-address-family	Exit address family configuration mode.
PE4 (config-router) # address-family ipv4 vrf L3VRF2	Enter to the IRB IPv4 VRF address family mode to configure the address-family specific parameters.
PE4 (config-router-af) # redistribute connected	Redistribute connected routes.
PE4 (config-router-af) # exit-address-family	Exit address family configuration mode.
PE4 (config-router) # exit	Exit router configuration mode.
PE4 (config) #end	Exit global configuration mode.

Validation

PE1#show ip ospf neighbor

Total number of full neighbors: 2

OSPF process 1 VRF(default) :

Neighbor ID	Pri	State	Dead Time	Address	Interface	Instance ID
17.12.13.1	1	Full/DR	00:00:35	16.16.16.2	vlan1.200	0
17.17.17.2	1	Full/DR	00:00:31	17.17.17.2	vlan1.200	0

PE1#show ip route vrf all

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
ia - IS-IS inter area, E - EVPN,
v - vrf leaked
* - candidate default

IP Route Table for VRF "default"

C	1.1.1.1/32	is directly connected, lo, 00:23:27
O E2	3.3.3.3/32	[110/1] via 16.16.16.2, vlan1.200, 00:18:02
		[110/1] via 17.17.17.2, vlan1.200
O E2	7.7.7.7/32	[110/1] via 17.17.17.2, vlan1.200, 00:18:45
O E2	8.8.8.8/32	[110/1] via 16.16.16.2, vlan1.200, 00:19:14
C	16.16.16.0/24	is directly connected, vlan1.200, 00:21:24
C	17.17.1.0/24	is directly connected, vlan1.200, 00:21:24
C	17.17.17.0/24	is directly connected, vlan1.200, 00:21:24
C	20.1.1.0/24	is directly connected, xe2.103, 00:22:31
O E2	40.1.1.0/24	[110/1] via 16.16.16.2, vlan1.200, 00:18:02
		[110/1] via 17.17.17.2, vlan1.200
C	101.11.11.0/24	is directly connected, vlan1.200, 00:21:24
C	127.0.0.0/8	is directly connected, lo, 00:23:27

IP Route Table for VRF "management"

C	10.12.98.0/24	is directly connected, eth0, 00:23:27
C	127.0.0.0/8	is directly connected, lo.management, 00:23:27

Gateway of last resort is not set

PE1#

PE1#ping 40.1.1.1

Press CTRL+C to exit

```
PING 40.1.1.1 (40.1.1.1) 56(84) bytes of data.
64 bytes from 40.1.1.1: icmp_seq=1 ttl=63 time=0.678 ms
64 bytes from 40.1.1.1: icmp_seq=2 ttl=63 time=0.568 ms
64 bytes from 40.1.1.1: icmp_seq=3 ttl=63 time=0.567 ms
64 bytes from 40.1.1.1: icmp_seq=4 ttl=63 time=0.657 ms
```

--- 40.1.1.1 ping statistics ---

```
4 packets transmitted, 4 received, 0% packet loss, time 59ms
rtt min/avg/max/mdev = 0.567/0.617/0.678/0.056 ms
```

PE1#

```
PE2#show clns neighbors
```

```
Total number of L1 adjacencies: 4
Total number of L2 adjacencies: 4
Total number of adjacencies: 8
Tag 1: VRF : default
System Id      Interface   SNPA          State   Holdtime  Type  Protocol
PE7            vlan1.100  0000.0000.1111  Up     21        L1    IS-IS
                                         Up     21        L2    IS-IS
PE8            vlan1.100  0000.0000.1111  Up     20        L1    IS-IS
                                         Up     20        L2    IS-IS
PE7            vlan1.101  0000.0000.1111  Up     21        L1    IS-IS
                                         Up     21        L2    IS-IS
PE8            vlan1.101  0000.0000.1111  Up     20        L1    IS-IS
                                         Up     20        L2    IS-IS
```

```
PE2#show ip route vrf all
```

```
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
       O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
       ia - IS-IS inter area, E - EVPN,
       v - vrf leaked
       * - candidate default
```

```
IP Route Table for VRF "default"
```

```
C          2.2.2.2/32 is directly connected, lo, 00:25:56
i L2       4.4.4.4/32 [115/10] via 13.1.1.2, vlan1.100, 00:22:51
             [115/10] via 12.1.1.2, vlan1.100
i L2       7.7.7.7/32 [115/10] via 12.1.1.2, vlan1.100, 00:24:20
i L2       8.8.8.8/32 [115/10] via 13.1.1.2, vlan1.100, 00:24:03
C          10.1.1.0/24 is directly connected, xe11.105, 00:25:23
C          11.11.11.0/24 is directly connected, vlan1.100, 00:25:22
C          12.1.1.0/24 is directly connected, vlan1.100, 00:25:22
i L1       12.13.14.0/24 [115/20] via 13.1.1.2, vlan1.100, 00:24:20
             [115/20] via 12.1.1.2, vlan1.100
C          13.1.1.0/24 is directly connected, vlan1.100, 00:25:22
i L2       50.50.50.0/24 [115/10] via 13.1.1.2, vlan1.100, 00:22:51
             [115/10] via 12.1.1.2, vlan1.100
C          127.0.0.0/8 is directly connected, lo, 00:25:56
```

```
IP Route Table for VRF "management"
```

```
C          10.12.98.0/24 is directly connected, eth0, 00:25:56
C          127.0.0.0/8 is directly connected, lo.management, 00:25:56
```

Gateway of last resort is not set

```
PE2#ping 50.50.50.1
```

```
Press CTRL+C to exit
```

```
PING 50.50.50.1 (50.50.50.1) 56(84) bytes of data.
```

```

64 bytes from 50.50.50.1: icmp_seq=1 ttl=63 time=0.491 ms
64 bytes from 50.50.50.1: icmp_seq=2 ttl=63 time=0.411 ms
64 bytes from 50.50.50.1: icmp_seq=3 ttl=63 time=0.628 ms
64 bytes from 50.50.50.1: icmp_seq=4 ttl=63 time=0.661 ms

--- 50.50.50.1 ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 65ms
rtt min/avg/max/mdev = 0.411/0.547/0.661/0.105 ms
PE2#

```

```
PE7#show clns neighbors
```

```

Total number of L1 adjacencies: 1
Total number of L2 adjacencies: 1
Total number of adjacencies: 2
Tag 1: VRF : default
System Id      Interface    SNPA          State   Holdtime  Type  Protocol
PE6            sa2          e8c5.7a19.c3c8  Up      5          L1    IS-IS
                                         Up      5          L2    IS-IS

```

```

Total number of L1 adjacencies: 2
Total number of L2 adjacencies: 2
Total number of adjacencies: 4
Tag 2: VRF : L3VRF4
System Id      Interface    SNPA          State   Holdtime  Type  Protocol
PE2            irb801       e8c5.7a76.581d  Up      5          L1    IS-IS
                                         Up      5          L2    IS-IS
PE2            irb802       e8c5.7a76.581d  Up      5          L1    IS-IS
                                         Up      5          L2    IS-IS

```

```
PE7#show ip ospf neighbor
```

```

Total number of full neighbors: 1
OSPF process 1 VRF(default):
Neighbor ID      Pri  State          Dead Time     Address      Interface  Instance ID
5.5.5.5          1    Full/Backup   00:00:34     22.1.1.2    sa3        0

Total number of full neighbors: 1
OSPF process 2 VRF(L3VRF3):
Neighbor ID      Pri  State          Dead Time     Address      Interface  Instance ID
1.1.1.1          1    Full/Backup   00:00:34     16.16.16.1   irb701     0

```

```
PE7#show ip route 2023 Nov 27 13:04:32.790 : PE7 : HSL : NOTIF : [IF_PKT_ERRORS_4] :
Fragment packets received on xe43 (1 packets)
```

```
vrf all
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
```

O - OSPF, IA - OSPF inter area
 N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
 E1 - OSPF external type 1, E2 - OSPF external type 2
 i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
 ia - IS-IS inter area, E - EVPN,
 v - vrf leaked
 * - candidate default

IP Route Table for VRF "default"

```
O      3.3.3.3/32 [110/3] via 22.1.1.2, sa3, 00:23:42
O      4.4.4.4/32 [110/3] via 22.1.1.2, sa3, 00:23:27
O      5.5.5.5/32 [110/2] via 22.1.1.2, sa3, 00:26:13
i L1   6.6.6.6/32 [115/20] via 80.1.1.2, sa2, 00:25:44
C      7.7.7.7/32 is directly connected, lo, 00:29:00
O      8.8.8.8/32 [110/3] via 22.1.1.2, sa3, 00:26:09
O      21.1.1.0/24 [110/2] via 22.1.1.2, sa3, 00:26:13
C      22.1.1.0/24 is directly connected, sa3, 00:27:04
O      23.1.1.0/24 [110/2] via 22.1.1.2, sa3, 00:24:37
O      24.1.1.0/24 [110/2] via 22.1.1.2, sa3, 00:24:20
C      80.1.1.0/24 is directly connected, sa2, 00:25:59
i L1   90.1.1.0/24 [115/20] via 80.1.1.2, sa2, 00:25:44
O      101.1.1.0/24 [110/3] via 22.1.1.2, sa3, 00:23:42
i L1   102.1.1.0/24 [115/20] via 80.1.1.2, sa2, 00:23:31
C      127.0.0.0/8 is directly connected, lo, 00:29:00
```

IP Route Table for VRF "management"

```
C      10.12.93.0/24 is directly connected, eth0, 00:29:00
C      127.0.0.0/8 is directly connected, lo.management, 00:29:00
```

IP Route Table for VRF "L3VRF3"

```
B      3.3.3.3/32 [0/0] is directly connected, tunvxlan2, 00:23:42
B      8.8.8.8/32 [0/0] is directly connected, tunvxlan2, 00:25:09
C      16.16.16.0/24 is directly connected, irb701, 00:29:00
C      17.12.13.0/24 is directly connected, irb701, 00:29:00
O      17.17.17.0/24 [110/2] via 16.16.16.1, irb701, 00:26:33
O      20.1.1.0/24 [110/2] via 16.16.16.1, irb701, 00:26:33
B      40.1.1.0/24 [20/0] via 3.3.3.3 (recursive is directly connected, tunvxlan2),
00:23:56
C      127.0.0.0/8 is directly connected, lo.L3VRF3, 00:29:00
```

IP Route Table for VRF "L3VRF4"

```
i L2   2.2.2.2/32 [115/10] via 13.1.1.1, irb801, 00:25:22
B      4.4.4.4/32 [0/0] is directly connected, tunvxlan3, 00:23:27
B      8.8.8.8/32 [0/0] is directly connected, tunvxlan3, 00:25:09
i L1   10.1.1.0/24 [115/20] via 13.1.1.1, irb801, 00:25:24
i L1   11.11.11.0/24 [115/20] via 13.1.1.1, irb801, 00:25:24
i L1   12.1.1.0/24 [115/20] via 13.1.1.1, irb801, 00:25:24
C      12.13.14.0/24 is directly connected, irb801, 00:29:00
C      13.1.1.0/24 is directly connected, irb801, 00:29:00
B      50.50.50.0/24 [20/0] via 4.4.4.4 (recursive is directly connected,
tunvxlan3), 00:23:56
```

```
C           127.0.0.0/8 is directly connected, lo.L3VRF4, 00:29:00
IP Route Table for VRF "L2VRF1"
IP Route Table for VRF "L2VRF2"
IP Route Table for VRF "evpn-gvrf-1"
```

Gateway of last resort is not set

PE7# show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
7.7.7.7	8.8.8.8	Installed	00:25:36	00:25:36
7.7.7.7	4.4.4.4	Installed	00:23:53	00:23:53
7.7.7.7	3.3.3.3	Installed	00:24:08	00:24:08

Total number of entries are 3

PE7#show nvo vxlan l3vni-map

L3VNI	L2VNI	IRB-interface
2000	801	irb801
2000	8001	irb802
1000	701	irb701
1000	7001	irb702

PE7#show 2023 Nov 27 13:05:12.791 : PE7 : HSL : NOTIF : [IF_PKT_ERRORS_4]: Fragment packets received on xe43 (1 packets)

nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port

AC - Access Port

(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status	Src-Addr	Dst-Addr
701	VNI-701	L2	NW	----	----	----	----	7.7.7.7	8.8.8.8
701	VNI-701	--	AC	sal	00:00:01:02:03:04:05:06:07:08	200	DF	----	----
801	VNI-101	L2	NW	----	----	----	----	7.7.7.7	8.8.8.8
801	VNI-101	--	AC	pol	00:00:00:00:00:00:77:82:00:00:00	100	DF	----	----
1000	---	L3	NW	----	----	----	----	7.7.7.7	8.8.8.8
1000	---	L3	NW	----	----	----	----	7.7.7.7	3.3.3.3
2000	---	L3	NW	----	----	----	----	7.7.7.7	8.8.8.8
2000	---	L3	NW	----	----	----	----	7.7.7.7	4.4.4.4
7001	---	L2	NW	----	----	----	----	7.7.7.7	8.8.8.8
7001	---	--	AC	sal	00:00:01:02:03:04:05:06:07:08	201	NON-DF	----	----
8001	---	L2	NW	----	----	----	----	7.7.7.7	8.8.8.8
8001	---	--	AC	pol	00:00:00:00:00:00:77:82:00:00:00	101	NON-DF	----	----

Total number of entries are 12

PE7#

PE7#show bgp 12vpn evpn prefix-route

RD[8100:11]								
ESI	Eth-Tag	Prefix-Length	IP-Address	GW-IPAddress	L3VNID/LABEL	Nexthop	Encap	Router-Mac
0	0	24	17.17.17.0	0.0.0.0	1000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	24	17.17.17.0	0.0.0.0	1000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	64	30::	::	1000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	64	30::	::	1000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	64	7102::	::	1000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	64	7102::	::	1000	8.8.8.8	VXLAN	1444:8f53:3e9e

RD[8400:11]								
ESI	Eth-Tag	Prefix-Length	IP-Address	GW-IPAddress	L3VNID/LABEL	Nexthop	Encap	Router-Mac
0	0	24	10.1.1.0	0.0.0.0	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	24	10.1.1.0	0.0.0.0	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	24	11.11.11.0	0.0.0.0	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	24	11.11.11.0	0.0.0.0	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	24	12.1.1.0	0.0.0.0	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	24	12.1.1.0	0.0.0.0	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	24	12.13.14.0	0.0.0.0	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	24	12.13.14.0	0.0.0.0	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	24	13.1.1.0	0.0.0.0	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	24	13.1.1.0	0.0.0.0	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	32	2.2.2.2	0.0.0.0	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	32	2.2.2.2	0.0.0.0	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	64	2::	::	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	64	2::	::	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	64	40::	::	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	64	40::	::	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	64	50::	::	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	64	50::	::	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	64	8002::	::	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	64	8002::	::	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	64	8102::	::	2000	8.8.8.8	VXLAN	1444:8f53:3e9e
0	0	64	8102::	::	2000	8.8.8.8	VXLAN	1444:8f53:3e9e

RD[56000:11]								
ESI	Eth-Tag	Prefix-Length	IP-Address	GW-IPAddress	L3VNID/LABEL	Nexthop	Encap	Router-Mac
0	0	24	40.1.1.0	0.0.0.0	1000	3.3.3.3	VXLAN	e49d:73b1:c301
0	0	24	40.1.1.0	0.0.0.0	1000	3.3.3.3	VXLAN	e49d:73b1:c301
0	0	64	2002::	::	1000	3.3.3.3	VXLAN	e49d:73b1:c301
0	0	64	2002::	::	1000	3.3.3.3	VXLAN	e49d:73b1:c301

RD[63000:11]								
ESI	Eth-Tag	Prefix-Length	IP-Address	GW-IPAddress	L3VNID/LABEL	Nexthop	Encap	Router-Mac
0	0	24	50.50.50.0	0.0.0.0	2000	4.4.4.4	VXLAN	e8c5:7aa8:7cb3
0	0	24	50.50.50.0	0.0.0.0	2000	4.4.4.4	VXLAN	e8c5:7aa8:7cb3
0	0	64	3002::	::	2000	4.4.4.4	VXLAN	e8c5:7aa8:7cb3
0	0	64	3002::	::	2000	4.4.4.4	VXLAN	e8c5:7aa8:7cb3

PE7#PE8#show clns neighbors

Total number of L1 adjacencies: 1

Total number of L2 adjacencies: 1

Total number of adjacencies: 2

Tag 1: VRF : default

System Id	Interface	SNPA	State	Holddtime	Type	Protocol
PE6	xe2	e8c5.7a19.c3c1	Up	7	L1	IS-IS
			Up	7	L2	IS-IS

Total number of L1 adjacencies: 2

Total number of L2 adjacencies: 2

Total number of adjacencies: 4

Tag 2: VRF : L3VRF4

System Id	Interface	SNPA	State	Holddtime	Type	Protocol
PE2	irb801	e8c5.7a76.581d	Up	7	L1	IS-IS
			Up	7	L2	IS-IS

```

PE2          irb802      e8c5.7a76.581d      Up       7        L1     IS-IS
                                         Up       7        L2     IS-IS

PE8#show ip ospf neighbor

Total number of full neighbors: 1
OSPF process 1 VRF(default):
Neighbor ID      Pri      State           Dead Time    Address      Interface Instance ID
5.5.5.5          1        Full/Backup     00:00:31    21.1.1.2    xe12          0

Total number of full neighbors: 1
OSPF process 2 VRF(L3VRF3):
Neighbor ID      Pri      State           Dead Time    Address      Interface     Instance ID
1.1.1.1          1        Full/Backup     00:00:35    17.17.17.1  irb701        0
PE8#terminal width 511

PE8#show ip route vrf all
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
      O - OSPF, IA - OSPF inter area
      N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
      E1 - OSPF external type 1, E2 - OSPF external type 2
      i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
      ia - IS-IS inter area, E - EVPN,
      v - vrf leaked
      * - candidate default

IP Route Table for VRF "default"
O          3.3.3.3/32 [110/3] via 21.1.1.2, xe12, 00:26:22
O          4.4.4.4/32 [110/3] via 21.1.1.2, xe12, 00:26:07
O          5.5.5.5/32 [110/2] via 21.1.1.2, xe12, 00:28:59
i L1       6.6.6.6/32 [115/20] via 90.1.1.2, xe2, 00:28:23
O          7.7.7.7/32 [110/3] via 21.1.1.2, xe12, 00:28:52
C          8.8.8.8/32 is directly connected, lo, 00:31:21
C          21.1.1.0/24 is directly connected, xe12, 00:29:44
O          22.1.1.0/24 [110/2] via 21.1.1.2, xe12, 00:28:59
O          23.1.1.0/24 [110/2] via 21.1.1.2, xe12, 00:27:17
O          24.1.1.0/24 [110/2] via 21.1.1.2, xe12, 00:27:00
i L1       80.1.1.0/24 [115/20] via 90.1.1.2, xe2, 00:28:23
C          90.1.1.0/24 is directly connected, xe2, 00:28:39
O          101.1.1.0/24 [110/3] via 21.1.1.2, xe12, 00:26:22
i L1       102.1.1.0/24 [115/20] via 90.1.1.2, xe2, 00:26:11
C          127.0.0.0/8 is directly connected, lo, 00:31:21

IP Route Table for VRF "management"
C          10.12.93.0/24 is directly connected, eth0, 00:31:21
C          127.0.0.0/8 is directly connected, lo.management, 00:31:21

IP Route Table for VRF "L3VRF3"
B          3.3.3.3/32 [0/0] is directly connected, tunvxlan2, 00:26:22
B          7.7.7.7/32 [0/0] is directly connected, tunvxlan2, 00:28:17
B          16.16.16.0/24 [20/0] via 7.7.7.7 (recursive is directly connected,
tunvxlan2), 00:28:17

```

```
C          17.12.13.0/24 is directly connected, irb701, 00:31:21
C          17.17.17.0/24 is directly connected, irb701, 00:31:21
B          20.1.1.0/24 [20/0] via 7.7.7.7 (recursive is directly connected, tunvxlan2),
00:28:17
B          40.1.1.0/24 [20/0] via 3.3.3.3 (recursive is directly connected, tunvxlan2),
00:26:37
C          127.0.0.0/8 is directly connected, lo.L3VRF3, 00:31:21
```

IP Route Table for VRF "L3VRF4"

```
i L2        2.2.2.2/32 [115/10] via 12.1.1.1, irb801, 00:28:44
B          4.4.4.4/32 [0/0] is directly connected, tunvxlan3, 00:26:07
B          7.7.7.7/32 [0/0] is directly connected, tunvxlan3, 00:28:17
i L1        10.1.1.0/24 [115/20] via 12.1.1.1, irb801, 00:28:44
i L1        11.11.11.0/24 [115/20] via 12.1.1.1, irb801, 00:28:44
C          12.1.1.0/24 is directly connected, irb801, 00:31:21
C          12.13.14.0/24 is directly connected, irb801, 00:31:21
i L1        13.1.1.0/24 [115/20] via 12.1.1.1, irb801, 00:28:44
B          50.50.50.0/24 [20/0] via 4.4.4.4 (recursive is directly connected,
tunvxlan3), 00:26:37
C          127.0.0.0/8 is directly connected, lo.L3VRF4, 00:31:21
```

IP Route Table for VRF "L2VRF1"

IP Route Table for VRF "L2VRF2"

IP Route Table for VRF "evpn-gvrf-1"

Gateway of last resort is not set

PE8#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
8.8.8.8	7.7.7.7	Installed	00:28:24	00:28:24
8.8.8.8	3.3.3.3	Installed	00:26:28	00:26:28
8.8.8.8	4.4.4.4	Installed	00:26:13	00:26:13

Total number of entries are 3

PE8#show nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port

AC - Access Port

(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status	Src-Addr	Dst-Addr
701	VNI-701	L2	NW	----	----	----	----	8.8.8.8	7.7.7.7
701	VNI-701	--	AC	sal	00:00:01:02:03:04:05:06:07:08 200	NON-DF	----	----	----
801	VNI-101	L2	NW	----	----	----	----	8.8.8.8	7.7.7.7
801	VNI-101	--	AC	pol	00:00:00:00:00:77:82:00:00:00 100	NON-DF	----	----	----
1000	---	L3	NW	----	----	----	----	8.8.8.8	7.7.7.7
1000	---	L3	NW	----	----	----	----	8.8.8.8	3.3.3.3
2000	---	L3	NW	----	----	----	----	8.8.8.8	7.7.7.7
2000	---	L3	NW	----	----	----	----	8.8.8.8	4.4.4.4
7001	---	L2	NW	----	----	----	----	8.8.8.8	7.7.7.7
7001	---	--	AC	sal	00:00:01:02:03:04:05:06:07:08 201	DF	----	----	----
8001	---	L2	NW	----	----	----	----	8.8.8.8	7.7.7.7
8001	---	--	AC	pol	00:00:00:00:00:77:82:00:00:00 101	DF	----	----	----

Total number of entries are 12

PE8#show bgp 12vpn evpn prefix-route

RD[7100:11]								
ESI	Eth-Tag	Prefix-Length	IP-Address	GW-IPAddress	L3VNID/LABEL	Nexthop	Encap	Router-Mac
0	0	24	16.16.16.0	0.0.0.0	1000	7.7.7.7	VXLAN	e001:a666:056d
0	0	24	16.16.16.0	0.0.0.0	1000	7.7.7.7	VXLAN	e001:a666:056d
0	0	24	17.17.17.0	0.0.0.0	1000	7.7.7.7	VXLAN	e001:a666:056d
0	0	24	17.17.17.0	0.0.0.0	1000	7.7.7.7	VXLAN	e001:a666:056d
0	0	24	20.1.1.0	0.0.0.0	1000	7.7.7.7	VXLAN	e001:a666:056d
0	0	24	20.1.1.0	0.0.0.0	1000	7.7.7.7	VXLAN	e001:a666:056d
0	0	64	30::	::	1000	7.7.7.7	VXLAN	e001:a666:056d
0	0	64	30::	::	1000	7.7.7.7	VXLAN	e001:a666:056d
0	0	64	7002::	::	1000	7.7.7.7	VXLAN	e001:a666:056d
0	0	64	7002::	::	1000	7.7.7.7	VXLAN	e001:a666:056d

RD[7400:11]								
ESI	Eth-Tag	Prefix-Length	IP-Address	GW-IPAddress	L3VNID/LABEL	Nexthop	Encap	Router-Mac
0	0	24	10.1.1.0	0.0.0.0	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	24	10.1.1.0	0.0.0.0	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	24	11.11.11.0	0.0.0.0	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	24	11.11.11.0	0.0.0.0	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	24	12.1.1.0	0.0.0.0	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	24	12.1.1.0	0.0.0.0	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	24	12.13.14.0	0.0.0.0	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	24	12.13.14.0	0.0.0.0	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	24	13.1.1.0	0.0.0.0	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	24	13.1.1.0	0.0.0.0	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	32	2.2.2.2	0.0.0.0	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	32	2.2.2.2	0.0.0.0	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	64	2::	::	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	64	2::	::	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	64	40::	::	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	64	40::	::	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	64	50::	::	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	64	50::	::	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	64	8002::	::	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	64	8002::	::	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	64	8102::	::	2000	7.7.7.7	VXLAN	e001:a666:056d
0	0	64	8102::	::	2000	7.7.7.7	VXLAN	e001:a666:056d

RD[56000:11]								
ESI	Eth-Tag	Prefix-Length	IP-Address	GW-IPAddress	L3VNID/LABEL	Nexthop	Encap	Router-Mac
0	0	24	40.1.1.0	0.0.0.0	1000	3.3.3.3	VXLAN	e49d:73b1:c301
0	0	24	40.1.1.0	0.0.0.0	1000	3.3.3.3	VXLAN	e49d:73b1:c301
0	0	64	2002::	::	1000	3.3.3.3	VXLAN	e49d:73b1:c301
0	0	64	2002::	::	1000	3.3.3.3	VXLAN	e49d:73b1:c301

RD[63000:11]								
ESI	Eth-Tag	Prefix-Length	IP-Address	GW-IPAddress	L3VNID/LABEL	Nexthop	Encap	Router-Mac
0	0	24	50.50.50.0	0.0.0.0	2000	4.4.4.4	VXLAN	e8c5:7aa8:7cb3
0	0	24	50.50.50.0	0.0.0.0	2000	4.4.4.4	VXLAN	e8c5:7aa8:7cb3
0	0	64	3002::	::	2000	4.4.4.4	VXLAN	e8c5:7aa8:7cb3
0	0	64	3002::	::	2000	4.4.4.4	VXLAN	e8c5:7aa8:7cb3

PE8#

PE3#show ip ospf neighbor

Total number of full neighbors: 1

OSPF process 1 VRF(default):

Neighbor ID	Pri	State	Dead Time	Address	Interface	Instance ID
5.5.5.5	1	Full/DR	00:00:29	23.1.1.2	xe14	0

Total number of full neighbors: 1

OSPF process 2 VRF(L3VRF1):

Neighbor ID	Pri	State	Dead Time	Address	Interface	Instance ID
192.0.0.2	0	Full/DROther	00:00:35	40.1.1.2	irb1001	0

PE3#show ip route vrf all

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
ia - IS-IS inter area, E - EVPN,
v - vrf leaked
* - candidate default

IP Route Table for VRF "default"

C	3.3.3.3/32	is directly connected, lo,	00:37:01
O	4.4.4.4/32	[110/3] via 23.1.1.2, xe14,	00:35:25
O	5.5.5.5/32	[110/2] via 23.1.1.2, xe14,	00:35:44
i L1	6.6.6.6/32	[115/20] via 101.1.1.1, ce3,	00:36:20
O	7.7.7.7/32	[110/3] via 23.1.1.2, xe14,	00:35:44
O	8.8.8.8/32	[110/3] via 23.1.1.2, xe14,	00:35:44
O	21.1.1.0/24	[110/2] via 23.1.1.2, xe14,	00:35:44
O	22.1.1.0/24	[110/2] via 23.1.1.2, xe14,	00:35:44
C	23.1.1.0/24	is directly connected, xe14,	00:36:36
O	24.1.1.0/24	[110/2] via 23.1.1.2, xe14,	00:35:44
i L1	80.1.1.0/24	[115/20] via 101.1.1.1, ce3,	00:36:20
i L1	90.1.1.0/24	[115/20] via 101.1.1.1, ce3,	00:36:20
C	101.1.1.0/24	is directly connected, ce3,	00:36:35
i L1	102.1.1.0/24	[115/20] via 101.1.1.1, ce3,	00:35:30
C	127.0.0.0/8	is directly connected, lo,	00:37:01

IP Route Table for VRF "management"

C	10.12.98.0/24	is directly connected, eth0,	00:37:01
C	127.0.0.0/8	is directly connected, lo.management,	00:37:01

IP Route Table for VRF "L3VRF1"

B	7.7.7.7/32	[0/0] is directly connected, tunvxlan2,	00:35:44
B	8.8.8.8/32	[0/0] is directly connected, tunvxlan2,	00:35:44
B	16.16.16.0/24	[20/0] via 7.7.7.7 (recursive is directly connected, tunvxlan2),	00:36:15
B	17.17.17.0/24	[20/0] via 7.7.7.7 (recursive is directly connected, tunvxlan2),	00:36:15
B	20.1.1.0/24	[20/0] via 7.7.7.7 (recursive is directly connected, tu nvxlan2),	00:36:15
C	40.1.1.0/24	is directly connected, irb1001,	00:37:01
O	55.0.0.0/24	[110/2] via 40.1.1.2, irb1001,	00:01:38
O	55.0.1.0/24	[110/2] via 40.1.1.2, irb1001,	00:01:38
O	55.0.2.0/24	[110/2] via 40.1.1.2, irb1001,	00:01:38
O	55.0.3.0/24	[110/2] via 40.1.1.2, irb1001,	00:01:38

```
O      55.0.4.0/24 [110/2] via 40.1.1.2, irb1001, 00:01:38
O      55.0.5.0/24 [110/2] via 40.1.1.2, irb1001, 00:01:38
O      55.0.6.0/24 [110/2] via 40.1.1.2, irb1001, 00:01:38
O      55.0.7.0/24 [110/2] via 40.1.1.2, irb1001, 00:01:38
O      55.0.8.0/24 [110/2] via 40.1.1.2, irb1001, 00:01:38
O      55.0.9.0/24 [110/2] via 40.1.1.2, irb1001, 00:01:38
C      127.0.0.0/8 is directly connected, lo.L3VRF1, 00:37:01
```

IP Route Table for VRF "L2VRF1"

Gateway of last resort is not set

PE3#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
<hr/>				
3.3.3.3	7.7.7.7	Installed	00:35:56	00:35:56
3.3.3.3	8.8.8.8	Installed	00:35:56	00:35:56

Total number of entries are 2

PE3#

PE4#show clns neighbors

Total number of L1 adjacencies: 1

Total number of L2 adjacencies: 1

Total number of adjacencies: 2

Tag 1: VRF : default

System Id	Interface	SNPA	State	Holddtime	Type	Protocol
PE6	xe5	e8c5.7a19.c3ae	Up	21	L1	IS-IS
			Up	21	L2	IS-IS

Total number of L1 adjacencies: 0

Total number of L2 adjacencies: 1

Total number of adjacencies: 1

Tag 2: VRF : L3VRF2

System Id	Interface	SNPA	State	Holddtime	Type	Protocol
Spirent-1	irb2001	0010.9400.0007	Up	26	L2	IS-IS

Total number of L1 adjacencies: 0

Total number of L2 adjacencies: 1

Total number of adjacencies: 1

Tag 3: VRF : L3VRF2

System Id	Interface	SNPA	State	Holddtime	Type	Protocol
0010.9400.0009	irb3002	0010.9400.0009	Up	25	L2	IS-IS

PE4#show ip route vrf all

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP

O - OSPF, IA - OSPF inter area

N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2

E1 - OSPF external type 1, E2 - OSPF external type 2

i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,

ia - IS-IS inter area, E - EVPN,

```

v - vrf leaked
* - candidate default

IP Route Table for VRF "default"
O      3.3.3.3/32 [110/3] via 24.1.1.2, xe25, 00:36:12
C      4.4.4.4/32 is directly connected, lo, 00:37:52
O      5.5.5.5/32 [110/2] via 24.1.1.2, xe25, 00:36:12
i L1   6.6.6.6/32 [115/20] via 102.1.1.1, xe5, 00:36:48
O      7.7.7.7/32 [110/3] via 24.1.1.2, xe25, 00:36:12
O      8.8.8.8/32 [110/3] via 24.1.1.2, xe25, 00:36:12
O      21.1.1.0/24 [110/2] via 24.1.1.2, xe25, 00:36:12
O      22.1.1.0/24 [110/2] via 24.1.1.2, xe25, 00:36:12
O      23.1.1.0/24 [110/2] via 24.1.1.2, xe25, 00:36:12
C      24.1.1.0/24 is directly connected, xe25, 00:37:04
i L1   80.1.1.0/24 [115/20] via 102.1.1.1, xe5, 00:36:48
i L1   90.1.1.0/24 [115/20] via 102.1.1.1, xe5, 00:36:48
O      101.1.1.0/24 [110/3] via 24.1.1.2, xe25, 00:36:12
C      102.1.1.0/24 is directly connected, xe5, 00:37:04
C      127.0.0.0/8 is directly connected, lo, 00:37:52
IP Route Table for VRF "management"
C      10.12.98.0/24 is directly connected, eth0, 00:37:52
C      127.0.0.0/8 is directly connected, lo.management, 00:37:52
IP Route Table for VRF "L3VRF2"
Gateway of last resort is 7.7.7.7 to network 0.0.0.0

B*      0.0.0.0/0 [20/0] via 7.7.7.7 (recursive is directly connected, tunv
xlan2), 00:01:50
B      2.2.2.2/32 [20/0] via 7.7.7.7 (recursive is directly connected, tun
vxlan2), 00:36:41
B      7.7.7.7/32 [0/0] is directly connected, tunvxlan2, 00:36:12
B      8.8.8.8/32 [0/0] is directly connected, tunvxlan2, 00:36:12
B      10.1.1.0/24 [20/0] via 7.7.7.7 (recursive is directly connected, tu
nvxlan2), 00:36:41
B      11.11.11.0/24 [20/0] via 7.7.7.7 (recursive is directly connected,
tunvxlan2), 00:36:41
B      12.1.1.0/24 [20/0] via 7.7.7.7 (recursive is directly connected, tu
nvxlan2), 00:36:41
B      12.13.14.0/24 [20/0] via 7.7.7.7 (recursive is directly connected,
tunvxlan2), 00:36:41
B      13.1.1.0/24 [20/0] via 7.7.7.7 (recursive is directly connected, tu
nvxlan2), 00:36:41
C      50.50.50.0/24 is directly connected, irb2001, 00:37:52
C      127.0.0.0/8 is directly connected, lo.L3VRF2, 00:37:52
IP Route Table for VRF "L2VRF2"

Gateway of last resort is not set
PE4# show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination        Status       Up/Down      Update
=====
```

4.4.4.4	7.7.7.7	Installed	00:36:18	00:36:18
4.4.4.4	8.8.8.8	Installed	00:36:18	00:36:18

Total number of entries are 2
PE4#

Abbreviations

The following are some key abbreviations and their meanings relevant to this document:

Acronym	Description
ECMP	Equal-Cost Multipath
EVPN	Ethernet Virtual Private Network
VxLAN	Virtual Extensible LAN
SR	Segment Routing
IRB	Integrated Routing
OSPF	Open Shortest Path First
ISIS	Intermediate System to Intermediate System

Glossary

The following provides definitions for key terms used throughout this document.

Multi Home VxLAN	This refers to a Virtual Extensible LAN (VxLAN) deployment where a Multi data center or network site is connected to a Multi external network (usually the internet) for connectivity.
IRB	A networking feature that enables the integration of Layer 3 IP routing and Layer 2 MAC address bridging within the same interface, simplifying network management and resource utilization.
OSPF	A dynamic and efficient link-state routing protocol used to determine the best path for data packets in an IP network. It is characterized by rapid convergence and adaptability, making it suitable for large and dynamic networks.
ISIS	A routing protocol designed for scalability and stability in computer networks, commonly used in large Service Provider networks. It provides a robust framework for routing information exchange.
Layer 3 Routing	Network routing operations at the Network Layer (Layer 3) of the OSI model, focusing on routing IP packets between different subnets or networks.
Layer 2 Bridging	Network bridging operations at the Data Link Layer (Layer 2) of the OSI model, handling the forwarding of data frames based on MAC addresses within the same network segment.
EVPN	Ethernet VPN, a technology that provides advanced and efficient methods for Layer 2 and Layer 3 services in Ethernet networks, often used in data centers and service provider environments.

VxLAN - EVPN for Service Provider Network

CHAPTER 1 VXLAN EVPN EVC Configuration

This chapter shows how to configure VXLAN EVPN Ethernet Virtual Circuit (EVC) which embeds the functionality of EVPN-VXLAN access ports to allow EVC frames across VTEPs. With this configuration, customers in the same VLAN can communicate even they are placed across distributed data centers.

Overview

An EVC represents a logical relationship between Ethernet User Network Interface (UNI) in a provider-based Ethernet service. An EVC represents the service offered and is carried through the provider network. Each EVC is configured by a unique name across the provider network.

An EVC is an end-to-end representation of a single instance of a Layer 2 service that a service provider offers. An EVC embodies the different parameters based on which the service is offered. EVC prevents data transfer between sites that are not part of the same EVC.

EVC is an A-Z circuit that enables you to pass customer VLANs from one port on a node to another port on another node in the network. EVC represents a Carrier Ethernet service and is an entity that provides end-to-end connection between two or more customer end points.

Topology




Figure 1-6: VXLAN EVPN EVC

RTR1/VTEP1

#configure terminal	Enter configure mode.
(config)#interface lo	Enter interface mode for loopback.
(config-if)#ip address 33.33.33.0/31 secondary	Assign secondary IP address.
(config-if)#exit	Exit interface mode.
(config)#mac vrf vrf1	Create mac routing/forwarding instance with vrf1 name and enter into VRF mode
(config-vrf) # rd 100:11	Assign RD value

(config-vrf) # route-target export 200:11	Assign route-target value for export
(config-vrf) # route-target import 400:11	Assign route-target value for import
(config-vrf) #exit	Exit VRF configuration mode
(config) #interface xe37	Enter interface mode for xe37
(config-if) #ip address 11.11.11.0/31	Assign IP address in /31 mask.
(config-if) #exit	Exit interface mode.
(config) #interface xe15	Enter interface mode for xe15
(config-if) #switchport	Make it L2 interface
(config-if) #exit	Exit interface mode.
(config) #router bgp 100	Enter BGP router mode
(config-router) # bgp router-id 1.1.1.1	Assign BGP router ID
(config-router) #neighbor 11.11.11.1 remote-as 200	Specify a neighbor router with peer IP address and remote-as defined
(config-router) #neighbor 11.11.11.1 fall-over bfd	Configure single-hop BFD session for its BGP peer
(config-router) #address-family ipv4 unicast	Enter into ipv4 unicast address family
(config-router-af) #network 33.33.33.0/31	Advertise loopback network into BGP for VTEP ID reachability
(config-router-af) #exit-address-family	Exit ipv4 unicast address family mode
(config-router) #address-family l2vpn evpn	Enter into l2vpn address family mode
(config-router-af) #neighbor 11.11.11.1 activate	Activate the peer into address family mode
(config-router-af) #exit-address-family	Exit l2vpn address family mode
(config-router) #exit	Exit BGP router mode
(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan vtep-ip-global 33.33.33.0	Configure Source vtep-ip-global configuration
(config) #nvo vxlan id 1 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf1	Assign VRF for evpn-bgp to carry EVPN route
(config-nvo) #exit	Exit VXLAN tenant mode.
(config) #nvo vxlan access-if port-vlan xe15 1000 inner-vlan 2000	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) and inner-vlan (CVLAN) mapping
(config-nvo-acc-if) #map vniid 1	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) #exit	Exit VXLAN access-interface mode
(config) #commit	Commit the candidate configuration to the running configuration
(config) #exit	Exit configuration mode

RTR2

#configure terminal	Enter config mode.
(config) #interface xe13/3	Enter interface mode for xe13/3
(config-if) #ip address 11.11.11.1/31	Assign IP address in /31 mask.

(config-if) #exit	Exit interface mode.
(config) #interface xe13/1	Enter interface mode for xe13/1
(config-if) #ip address 12.12.12.1/31	Assign IP address in /31 mask.
(config-if) #exit	Exit interface mode
(config) #router bgp 200	Enter BGP router mode
(config-router) # bgp router-id 2.2.2.2	Assign BGP router ID
(config-router) #neighbor 11.11.11.0 remote-as 100	Specify a neighbor router with peer ip address and remote-as defined
(config-router) #neighbor 11.11.11.0 fall-over bfd	Configure single-hop BFD session for its BGP peer
(config-router) #neighbor 12.12.12.0 remote-as 300	Specify a neighbor router with peer ip address and remote-as defined
(config-router) #neighbor 12.12.12.0 fall-over bfd	Configure single-hop BFD session for its BGP peer
(config-router) #address-family l2vpn evpn	Enter into l2vpn address family mode
(config-router-af) #neighbor 11.11.11.0 activate	Activate the peer into address family mode
(config-router-af) #neighbor 12.12.12.0 activate	Activate the peer into address family mode
(config-router-af) #exit-address-family	Exit l2vpn address family mode
(config-router) #commit	Commit the candidate configuration to the running configuration
(config-router) #exit	Exit BGP router mode

RTR3/VTEP2

#configure terminal	Enter configure mode.
(config) #interface lo	Enter interface mode for loopback.
(config-if) #ip address 34.34.34.0/31 secondary	Assign secondary IP address.
(config-if) #exit	Exit interface mode.
(config) #mac vrf vrf1	Create mac routing/forwarding instance with vrf1 name and enter into vrf mode
(config-vrf) #rd 300:11	Assign RD value
(config-vrf) #route-target export 400:11	Assign route-target value for export
(config-vrf) #route-target import 200:11	Assign route-target value for import
(config-vrf) #exit	Exit vrf configuration mode
(config) #interface xe13	Enter interface mode for xe13
(config-if) #ip address 12.12.12.0/31	Assign IP address in /31 mask.
(config-if) #exit	Exit interface mode.
(config) #interface xe6	Enter interface mode for xe6
(config-if) #switchport	Make it L2 interface
(config-if) #exit	Exit interface mode.
(config) #router bgp 300	Enter BGP router mode
(config-router) # bgp router-id 3.3.3.3	Assign BGP router ID

(config-router) #neighbor 12.12.12.1 remote-as 200	Specify a neighbor router with peer ip address and remote-as defined
(config-router) #neighbor 12.12.12.1 fall-over bfd	Configure single-hop BFD session for its BGP peer
(config-router) #address-family ipv4 unicast	Enter into ipv4 unicast address family
(config-router-af) #network 34.34.34.0/31	Advertise loopback network into BGP for VTEP ID reachability
(config-router-af) #exit-address-family	Exit ipv4 unicast address family mode
(config-router) #address-family l2vpn evpn	Enter into l2vpn address family mode
(config-router-af) #neighbor 12.12.12.1 activate	Activate the peer into address family mode
(config-router-af) #exit-address-family	Exit l2vpn address family mode
(config-router) #exit	Exit BGP router mode
(config) #nvo vxlan enable	Enable VXLAN
(config) #nvo vxlan vtep-ip-global 34.34.34.0	Configure Source vtep-ip-global configuration
(config) #nvo vxlan id 1 ingress-replication inner-vid-disabled	Configure VXLAN Network identifier with/without inner-vid-disabled configure and enter into VXLAN tenant mode
(config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf1	Assign VRF for evpn-bgp to carry EVPN route
(config-nvo) #exit	Exit VXLAN tenant mode.
(config) #nvo vxlan access-if port-vlan xe6 1000 inner-vlan 2000	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) and inner-vlan (CVLAN) mapping
(config-nvo-acc-if) #map vnid 1	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) #exit	Exit VXLAN access-interface mode
(config) #commit	Commit the candidate configuration to the running configuration
(config) #exit	Exit configuration mode

Validation

Retaining SVLAN and CVLAN tags across Data Centers

RTR1/VTEP1

```
VTEP1#show running-config nvo vxlan
!
nvo vxlan enable
!
nvo vxlan vtep-ip-global 33.33.33.0
!
nvo vxlan id 1 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp vrf1
!
nvo vxlan access-if port-vlan xe1/1 1000 inner-vlan 2000
  map vnid 1
!
```

```
VTEP1#show bgp 12vpn evpn summary
BGP router identifier 1.1.1.1, local AS number 100
BGP table version is 8
2 BGP AS-PATH entries
0 BGP community entries

Neighbor          V   AS  MsgRcv    MsgSen TblVer  InQ   OutQ  Up/Dow
n  State/PfxRcd  AD  MACIP  MCAST    ESI  PREFIX-ROUTE
11.11.11.1        4    200    73       73      8        0      0  00:30:41
                2     0     1     1       0      0

Total number of neighbors 1

Total number of Established sessions 1

VTEP1#show bgp 12vpn evpn
BGP table version is 8, local router ID is 1.1.1.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
              l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVNP route type]:[ESI]:[VNID]:[relevent route informantion]
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route
4 - Ethernet Segment Route
5 - Prefix Route

      Network          Next Hop          Metric      LocPrf      Weight      Path
Peer      Encap

RD[100:11] VRF[vrf1]:
*      [2]:[0]:[1]:[48,0000.339a.9397]:[0]:[1]
                  34.34.34.0          0          100          0          200
300 i  11.11.11.1      VXLAN
*>      [2]:[0]:[1]:[48,0000.339a.9abb]:[0]:[1]
                  33.33.33.0          0          100         32768      i  -
-----      VXLAN
*>      [3]:[1]:[32,33.33.33.1]
33.33.33.0          0          100         32768
i  -----      VXLAN

*      [3]:[1]:[32,34.34.34.0]
                  34.34.34.0          0          100          0          200
300 i  11.11.11.1      VXLAN

RD[300:11]
*>      [2]:[0]:[1]:[48,0000.339a.9397]:[0]:[1]
                  34.34.34.0          0          100          0          200
```

```

300 i 11.11.11.1      VXLAN
*> [3]:[1]:[32,34.34.34.0]
            34.34.34.0          0        100          0       200
300 i 11.11.11.1      VXLAN

```

Total number of prefixes 6

VTEP1#show ip route

Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
ia - IS-IS inter area, E - EVPN,
v - vrf leaked
* - candidate default

IP Route Table for VRF "default"

```

C   11.11.11.0/31 is directly connected, xe10/1, 00:36:00
C   33.33.33.0/31 is directly connected, lo, 00:37:33
B   34.34.34.0/31 [20/0] via 11.11.11.1, xe10/1, 00:27:03
C   127.0.0.0/8 is directly connected, lo, 23:14:51

```

Gateway of last resort is not set

VTEP1

VTEP1#show nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNIID	VNI-Name	VNI-Type	Type	Interface	ESI
VLAN	DF-Status	Src-Addr		Dst-Addr	
1	---	L2	NW	----	-----
---	---	33.33.33.0		34.34.34.0	
1	---	--	AC	xe1/1	--- Single Homed Port ---
1000	----	----		----	

Total number of entries are 2

VTEP1#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
33.33.33.0	34.34.34.0	Installed	00:26:27	00:26:27

Total number of entries are 1
VTEP1#show nvo vxlan mac-table

VXLAN MAC Entries							
VNID	Interface	VlanId	Inner-VlanId	Mac-Addr	VTEP-Ip/ESI	AccessPortDesc	
	Type		Status				
1	xe1/1	1000	2000	0000.339a.9abb	33.33.33.0		
	Dynamic Local		-----		-----		
1	---	---	----	0000.339a.9397	34.34.34.0		
	Dynamic Remote		-----		-----		

Total number of entries are : 2
VTEP1#

RTR3/VTEP2

```
#show running-config nvo vxlan
!
nvo vxlan enable
!
nvo vxlan vtep-ip-global 34.34.34.0
!
nvo vxlan id 1 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp vrf1
!
nvo vxlan access-if port-vlan xe6 1000 inner-vlan 2000
  map vnid 1
!
VTEP2#show bgp 12vpn evpn summary
BGP router identifier 3.3.3.3, local AS number 300
BGP table version is 7
2 BGP AS-PATH entries
0 BGP community entries
```

Neighbor	V	AS	MsgRcv	MsgSen	TblVer	InQ	OutQ	Up/Dow
n State/PfxRcd	AD	MACIP	MCAST	ESI	PREFIX-ROUTE			
12.12.12.1		4	200	63	64	7	0	00:26:54
	2	0	1	1	0	0		

Total number of neighbors 1

Total number of Established sessions 1

```
VTEP2#show bgp 12vpn evpn
BGP table version is 7, local router ID is 3.3.3.3
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
               l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]
1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route
4 - Ethernet Segment Route
5 - Prefix Route

      Network          Next Hop          Metric     LocPrf     Weight     Path
Peer      Encap

RD[100:11]
*>   [2]:[0]:[1]:[48,0000.339a.9abb]:[0]:[1]
                  33.33.33.0          0          100          0         200
100 i 12.12.12.1      VXLAN
*>   [3]:[1]:[32,33.33.33.0]
                  33.33.33.0          0          100          0         200
100 i 12.12.12.1      VXLAN

*>   [2]:[0]:[1]:[48,0000.339a.9397]:[0]:[1]
                  34.34.34.0          0          100     32768     i -
-----      VXLAN
*   [2]:[0]:[1]:[48,0000.339a.9abb]:[0]:[1]
                  33.33.33.0          0          100          0         200
100 i 12.12.12.1      VXLAN
*   [3]:[1]:[32,33.33.33.0]
                  33.33.33.0          0          100          0         200
100 i 12.12.12.1      VXLAN
*>   [3]:[1]:[32,34.34.34.0]
                  34.34.34.0          0          100     32768     i -
-----      VXLAN

Total number of prefixes 6

#show ip route
Codes: K - kernel, C - connected, S - static, R - RIP, B - BGP
       O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2,
       ia - IS-IS inter area, E - EVPN,
       v - vrf leaked
       * - candidate default
```

```
IP Route Table for VRF "default"
C    12.12.12.0/31 is directly connected, xe13, 00:28:41
B    33.33.33.0/31 [20/0] via 12.12.12.1, xe13, 00:26:56
C    34.34.34.0/31 is directly connected, lo, 00:29:36
C    127.0.0.0/8 is directly connected, lo, 00:52:46
```

Gateway of last resort is not set

```
VTEP2#show nvo vxlan
VXLAN Information
=====
Codes: NW - Network Port
       AC - Access Port
       (u) - Untagged

VNID      VNI-Name      VNI-Type Type Interface      ESI
VLAN DF-Status Src-Addr          Dst-Addr

-----
1        ----      L2      NW      ----      -----
-----      34.34.34.0      33.33.33.0
1        ----      --      AC      xe1/1      --- Single Homed Port ---
1000     ----      ----      ----
Total number of entries are 2
```

```
VTEP1#show nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination      Status      Up/Down      Update
=====
33.33.33.0      34.34.34.0      Installed      00:26:27      00:26:27
Total number of entries are 1
```

```
VTEP2#show nvo vxlan mac-table
=====
=====

VXLAN MAC Entries
=====

VNID      Interface  VlanId Inner-VlanId Mac-Addr      VTEP-Ip/ESI
Type          Status          AccessPortDesc

-----
1        ----      ----      ----      0000.339a.9abb 33.33.33.0
      Dynamic Remote      -----
1        xe6      1000      2000      0000.339a.9397 34.34.34.0
      Dynamic Local      -----
```

```
Total number of entries are : 2
#
```

Popping SVLAN and CVLAN Tag

Use the previous configuration on VTEP1 and perform the configuration below on VTEP2.

VTEP2

(config) #nvo vxlan access-if port xe6	Enable port-only mapping for access port
(config-nvo-acc-if) #map vniid 1	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) #exit	Exit VXLAN access-interface mode
(config) #commit	Commit the candidate configuration to the running configuration
(config) #exit	Exit configuration mode

RTR3/VTEP2

```
#show nvo vxlan
VXLAN Information
=====
Codes: NW - Network Port
AC - Access Port
(u) - Untagged
VNID VNI-Name VNI-Type Type Interface ESI
VLAN DF-Status Src-Addr Dst-Addr
```

```
1 ---- L2 NW ---- -----
---- ---- 34.34.34.0 33.33.33.0
1 ---- -- AC xe6 --- Single Homed Port ---
---- -----
```

Total number of entries are 2

```
VTEP2#show nvo vxlan mac-table
```

```
=====
=====
```

VXLAN MAC Entries					
VNID	Interface	VlanId	Inner-VlanId	Mac-Addr	VTEP-Ip/ESI
Type		Status			AccessPortDesc
1	---	---	---	0000.339a.9abb	33.33.33.0
	Dynamic	Remote	-----		-----

```
Total number of entries are : 1
#
```

```
VTEP2#show running-config nvo vxlan
!
nvo vxlan enable
!
nvo vxlan vtep-ip-global 34.34.34.0
!
nvo vxlan id 1 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp vrf1
!
nvo vxlan access-if port-vlan xe1/1 3000 inner-vlan 2000
  map vnid 1
```

```
VTEP1#show nvo vxlan tunnel
VXLAN Network tunnel Entries
  Source          Destination      Status        Up/Down      Update
=====
  33.33.33.0      34.34.34.0    Installed     00:26:27    00:26:27
Total number of entries are 1
```

Popping and Later Pushing SVLAN Tag

Use the previous configuration on VTEP1 and perform the configuration below on VTEP2.

(config) #nvo vxlan access-if port-vlan xe6 3000 inner-vlan 2000	Enable port-vlan mapping i.e. access port to outer-vlan (SVLAN) and inner-vlan (CVLAN) mapping
(config-nvo-acc-if) #map vnid 1	Map VXLAN Identified to access-port for VXLAN
(config-nvo-acc-if) #exit	Exit VXLAN access-interface mode
(config) #commit	Commit the candidate configuration to the running configuration
(config) #exit	Exit configuration mode

RTR3/VTEP2

```
#show running-config nvo vxlan
!
nvo vxlan enable
!
nvo vxlan vtep-ip-global 34.34.34.0
!
nvo vxlan id 1 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp vrf1
!
nvo vxlan access-if port-vlan xe1/1 3000 inner-vlan 2000
  map vnid 1
!
#show nvo vxlan
VXLAN Information
=====
Codes: NW - Network Port
```

AC - Access Port

(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI
VLAN	DF-Status	Src-Addr		Dst-Addr	
1	---	L2	NW	---	-----
---	---	34.34.34.0		33.33.33.0	
1	---	--	AC	xe6	--- Single Homed Port ---
3000	----	----		----	

Total number of entries are 2

#show nvo vxlan tunnel				
VXLAN Network tunnel Entries				
Source	Destination	Status	Up/Down	Update
34.34.34.0	33.33.33.0	Installed	00:06:48	00:06:48

Total number of entries are 1

VTEP2#show nvo vxlan mac-table

=====					
=====					
=====					
=====					
=====					
VXLAN MAC Entries					
=====					
=====					
=====					
=====					
VNID	Interface	VlanId	Inner-VlanId	Mac-Addr	VTEP-Ip/ESI
	Type				AccessPortDesc
1	---	---	---	0000.339a.9abb	33.33.33.0
	Dynamic	Remote	-----		-----

Total number of entries are : 1

#

CHAPTER 2 EVPN VXLAN E-Tree

Overview


Ethernet VPN Ethernet-Tree (EVPN E-Tree), is a networking solution designed to manage communication within broadcast domains, incorporating redundancy through multi-homing in a network. It optimizes traffic routing and control, especially in scenarios where specific services or devices need controlled communication. It categorizes network nodes based on predefined definitions of EVPN Instances as Leaf or Root, allowing or restricting communication between them.

Feature Characteristics

Implemented Scenario 1 of the EVPN E-Tree solution, as defined by RFC-8317, designates each Provider Edge (PE) node as either a Leaf or a Root site per Virtual Private Network (VPN) for VXLAN and MPLS EVPN in OcNOS.

Scenario 1: Leaf or Root Site(s) per PE

Scenario 1 involves a topology with three PE nodes: PE-1, PE-2, and PE-3. PE-1 and PE-2 are Multi-Homed nodes (MH-1 and MH-2), with PE-3 acting as the Root node. PE-1 and PE-2 function as Leaf nodes and are part of a single home access interface (SH1 and SH2).



The classification ensures that communication follows specific rules:

- Communication between Leaf hosts is restricted, as indicated by red dotted lines with a cross mark (X) in the topology diagram. However, communication between Leaf and Root nodes, as well as between Root nodes, is permitted, marked by green dotted lines.

- Leaf nodes within PE-1 and PE-2 are isolated from each other, preventing intra-PE communication.

The scenario 1 is achieved through two main concepts:

1. Inter-PE Communication

- The inter-PE Route Target (RT) Constraint Method is applicable only to Single-Homing (SH) devices. Two RTs per broadcast domain are utilized, with Leaf PEs exporting Leaf RTs and Root nodes exporting Root RTs. Leaf nodes import only Root RTs, allowing communication with Root PEs while preventing communication with other Leaf nodes. RT constraints limit the import of specific EVPN routes (MAC-IP and IMET routes) to designated paths for inter-PE communication.
- IPI employs a proprietary method to support inter-PE connectivity for both SH and MH devices, using BGP extended community to advertise Leaf Indication in BGP routes and influence traffic flow for both Unicast and BUM traffic. This method enables implementation of ARP or ND cache suppression and MAC mobility sub-features specified in RFC-7432.

2. **Intra-PE communication:** Local Split Horizon controls intra-PE communication between Attachment Circuits (ACs) within Leaf PE nodes, ensuring that traffic between ACs does not egress to other Leaf ACs.

Note: This functionality depends on hardware capabilities.

Benefits

EVPN E-Tree offers benefits in networking environments by providing efficient traffic control, enhanced security, scalability, and improved performance.

Efficient Traffic Control: EVPN E-Tree allows for efficient control over traffic within network broadcast domains. By segregating nodes into Leaf and Root categories, it enables precise management of communication flows, ensuring the traffic is directed only where needed.

Enhanced Security: The isolation of Leaf hosts from each other adds a layer of security to the network. This prevents unauthorized communication between devices within the same broadcast domain, reducing the risk of data breaches and unauthorized access.

Scalability: EVPN E-Tree is scalable, making it suitable for networks of various sizes and complexities. Whether deploying in small-scale environments or large enterprise networks, EVPN E-Tree offers flexibility and scalability to meet evolving business needs.

Improved Performance: By controlling communication paths and optimizing traffic flows, EVPN E-Tree can improve network performance. This ensures that critical data packets are delivered efficiently, reducing latency and enhancing overall network performance.

Prerequisites

In setting up a VXLAN EVPN network, certain prerequisites are essential to ensure proper functionality and connectivity.

Ensure VXLAN EVPN Configuration: Confirm that VXLAN, EVPN VXLAN, and VXLAN filtering are already enabled in the network as they are required for VXLAN EVPN Multihoming.

Define Interfaces and Loopback Addresses: Configure Layer 2 interfaces, like port channel interfaces (e.g., po1), and assign specific system MAC addresses (Ethernet Segment Identifier (ESI) values) for proper identification and routing. Additionally, assign loopback IP addresses to establish essential points of connectivity. These configurations establish the efficient network routing and communication.

Configure OSPF and BGP for Dynamic Routing: Enable OSPF to facilitate dynamic routing within the network. Define OSPF router IDs to match loopback IP addresses and add network segments to OSPF areas for proper route

distribution. Additionally, establish BGP sessions to advertise routes between different nodes. Set up neighbor relationships using loopback IP addresses, ensuring efficient route advertisement and convergence for optimal network performance.

Leaf Node

1. Enable VXLAN and EVPN MH

Enable features like VXLAN and EVPN Multihoming, VXLAN filtering, and quality of service (QoS) capabilities on all Leaf nodes.

```
!
nvo vxlan enable
!
evpn vxlan multihoming enable
!
qos enable
!
```

2. Configure Interfaces and Loopback

Define a port channel interface (`po1`) as an L2 interface and assign the system MAC (`0000.0000.1111`) as the ESI value. Designate an interface (`xe7`) as a member port of `po1`. Assign the loopback IP address (`1.1.1.1`) to Leaf node, and set IP addresses (`10.10.10.1` and `10.10.11.1`) to interfaces (`xe45` and `xe49/2`), respectively, for connectivity with Spine nodes.

```
!
interface po1
  switchport
  evpn multi-homed system-mac 0000.0000.1111
!
interface lo
  ip address 1.1.1.1/32 secondary
!
interface xe7
  channel-group 1 mode active
!
interface xe45
  ip address 10.10.10.1/24
!
interface xe49/2
  ip address 10.10.11.1/24
  exit
!
```

3. Configure OSPF

In OSPF router mode, set the router ID (`1.1.1.1`), to match the loopback IP address. Add the loopback network (`1.1.1.1/32`) and networks (`10.10.10.0/24` and `10.10.11.0/24`) connected to Spine nodes in OSPF area 0. Enable Bidirectional Forwarding Detection (BFD) on all OSPF interfaces for faster convergence.

```
!
router ospf 100
  ospf router-id 1.1.1.1
  bfd all-interfaces
  network 1.1.1.1/32 area 0.0.0.0
  network 10.10.10.0/24 area 0.0.0.0
  network 10.10.11.0/24 area 0.0.0.0
!
```

4. Configure BGP

In BGP router mode, set the router ID (1.1.1.1) to match the loopback IP address. Specify the loopback IP address of each Leaf node as neighbors with their respective remote AS numbers. Configure the loopback as the update source for each neighbor and set the advertisement interval (0) for rapid convergence. In L2VPN EVPN address family mode, activate each Leaf node (2.2.2.2, 3.3.3.3, 4.4.4.4) to establish connections within the EVPN address family.

```
!
router bgp 100
  bgp router-id 1.1.1.1
  neighbor 2.2.2.2 remote-as 100
  neighbor 3.3.3.3 remote-as 100
  neighbor 4.4.4.4 remote-as 100
  neighbor 2.2.2.2 update-source lo
  neighbor 2.2.2.2 advertisement-interval 0
  neighbor 3.3.3.3 update-source lo
  neighbor 3.3.3.3 advertisement-interval 0
  neighbor 4.4.4.4 update-source lo
  neighbor 4.4.4.4 advertisement-interval 0
!
address-family l2vpn evpn
  neighbor 2.2.2.2 activate
  neighbor 3.3.3.3 activate
  neighbor 4.4.4.4 activate
exit-address-family
!
exit
!
```

5. Configure VRF

In VRF mode, create a MAC routing or forwarding instance (VRF1). Assign the Route Distinguisher (RD) value (1.1.1.1:100) and set both import and export route-target value (100:100). Ensure that the same route-target value is configured on all Leaf nodes for MAC VRF to maintain consistency.

```
!
mac vrf VRF1
  rd 1.1.1.1:100
  route-target both 100:100
!
```

Spine Node

1. Configure Interfaces and Loopback

Enable QoS and assign specific IP addresses to loopback interfaces. Configure IP addresses for interfaces connected to each Leaf node.

```
!
qos enable
!
interface ce1/2
  ip address 40.40.40.2/24
!
interface ce1/4
  ip address 10.10.10.2/24
!
interface ce24/1
  ip address 30.30.30.2/24
```

```
!
interface ce27/1
  ip address 20.20.20.2/24
!
interface lo
  ip address 5.5.5.5/32 secondary
!
```

2. Configure OSPF

In OSPF router mode, set the router ID (5.5.5.5), to match the loopback IP address. Add the loopback network (5.5.5.5/32) and networks (10.10.10.0/24, 20.20.20.0/24, 30.30.30.0/24, and 40.40.40.0/24) connected to Leaf nodes in OSPF area 0. Enable BFD on all OSPF interfaces for faster convergence.

```
!
router ospf 100
  ospf router-id 5.5.5.5
  bfd all-interfaces
  network 5.5.5.5/32 area 0.0.0.0
  network 10.10.10.0/24 area 0.0.0.0
  network 20.20.20.0/24 area 0.0.0.0
  network 30.30.30.0/24 area 0.0.0.0
  network 40.40.40.0/24 area 0.0.0.0
!
```

Configure Switch

Set up an IEEE VLAN bridge, enabling VLANs and associating them with bridge 1. Configure interfaces (xe57, po1, xe46, xe47) to be part of bridge 1, setting them as hybrid ports with VLAN (1000) allowed and egress-tagged enabled. Designate interfaces connected to Leaf nodes (xe46 and xe47) as member ports of po1.

```
!
bridge 1 protocol ieee vlan-bridge
!
vlan database
  vlan-reservation 4000-4094
  vlan 1000 bridge 1 state enable
!
interface po1
  switchport
  bridge-group 1
  switchport mode hybrid
  switchport mode hybrid acceptable-frame-type all
  switchport hybrid allowed vlan add 1000 egress-tagged enable
!
interface xe46
  channel-group 1 mode active
!
interface xe47
  channel-group 1 mode active
!
interface xe57
  switchport
  bridge-group 1
  switchport mode hybrid
  switchport mode hybrid acceptable-frame-type all
  switchport hybrid allowed vlan add 1000 egress-tagged enable
!
```


Configuration

Configure various nodes within the topology to set up a VXLAN EVPN E-Tree network.

Topology

The sample topology includes Leaf Nodes (VTEP1, VTEP2, VTEP3, and VTEP4), Spine Nodes (SPINE1 and SPINE2), and Switches (SWITCH1 and SWITCH2).

VTEP1 and VTEP2 belong to Multi-homed group 1 (MH1) with po1, while VTEP3 and VTEP4 are in Multi-homed group 2 (MH2) with po2. VTEP2 and VTEP4 connect to single home access ports SH1 and SH2, respectively. All VTEPs link to Spine nodes SPINE1 and SPINE2. SWITCH1 is multi-homed to VTEP1 and VTEP2, and SWITCH2 connects to VTEP3 and VTEP4.



VXLAN EVPN E-Tree Topology

Note: Before configuring E-Tree, meet all [Prerequisites](#) for the following nodes:

- Leaf nodes: VTEP1, VTEP2, VTEP3, and VTEP4

- Spine nodes: SPINE1 and SPINE2
- Switches: SWITCH1 and SWITCH2

Enable EVPN E-Tree

The following E-Tree configurations applies to the VTEP nodes within the VXLAN network.

1. Enable EVPN E-Tree on VTEP3 and VTEP4 nodes, allowing them to participate in E-Tree functionality within the VXLAN network, controlling traffic and establishing hierarchical connections between Leaf nodes in the network architecture.

```
(config)#evpn etree enable
```

2. Set the ESI hold time (90 seconds) on all VTEP nodes to allow the tunnel to establish during VXLAN initialization before bringing up the ESI. Configure the source VTEP IP address (3.3.3.3) which serves as the global identifier for VXLAN encapsulation and decapsulation within the network, facilitating proper communication and tunnel establishment.

```
(config)#evpn esi hold-time 90
(config)#nvo vxlan vtep-ip-global 3.3.3.3
```

3. Define VXLAN identifier (10) with ingress replication and disabled inner VLAN ID (VID) for **E-Tree leaf nodes** (VTEP3 and VTEP4) to support hierarchical connectivity and traffic control within the VXLAN network. This configuration allows for efficient replication of traffic at the ingress point and ensures that inner VLAN IDs are disabled, optimizing the functionality of E-Tree leaf nodes within the network architecture. On the VXLAN tenant node, assign VRF (VRF1) to EVPN-BGP for carrying EVPN routes within the VXLAN network.

```
(config)#nvo vxlan id 10 ingress-replication inner-vid-disabled etree-leaf
(config-nvo)#vxlan host-reachability- protocol evpn-bgp VRF1
(config-nvo)#exit
```

4. Enable port-VLAN mapping (po2) with VLAN ID (1000) to facilitate multi-homed access on all VTEP nodes. Map VXLAN identifier (10) to the access port for VXLAN connectivity.

```
(config)#nvo vxlan access-if port-vlan po2 1000
(config-nvo-acc-if)#map vnid 10
(config-nvo-acc-if)#exit
(config)#commit
```

Validation

Use the show commands described in this section to verify the network for proper VXLAN EVPN E-Tree configuration.

Verify OSPF sessions between the VTEP nodes and the SPINEs within the VXLAN network using the `show ip ospf neighbor` command. This command displays OSPF neighbor details, including the state of the OSPF neighbor relationship. A State of Full/DR indicates a fully adjacent and operational state between the routers, confirming proper OSPF connectivity within the network.

```
VTEP1#show ip ospf neighbor
```

```
Total number of full neighbors: 2
```

```
OSPF process 100 VRF(default):
```

Neighbor ID	Pri	State	Dead Time	Address	Interface	Instance ID
5.5.5.5	1	Full/DR	00:00:32	10.10.10.2	xe45	0
6.6.6.6	1	Full/DR	00:00:30	10.10.11.2	xe49/2	0

Verify the BGP session status between VTEPs, using the `show bgp 12vpn evpn summary` command output. The Up/Down field indicates the duration for which the BGP session has been up or down.

```
VTEP1#show bgp 12vpn evpn summary
BGP router identifier 1.1.1.1, local AS number 100
BGP table version is 9
```

1 BGP AS-PATH entries
0 BGP community entries

Neighbor	V	AS	MsgRcv	MsgSen	TblVer	InQ	OutQ	Up/Down	State/PfxRcd	AD	MACIP	MCAST	ESI	PREFIX-ROUTE
2.2.2.2	4	100	34	28	7	0	0	00:07:37	9	3	4	1	1	0
3.3.3.3	4	100	30	33	8	0	0	00:07:34	6	3	2	1	0	0
4.4.4.4	4	100	31	28	7	0	0	00:07:37	8	3	4	1	0	0

Total number of neighbors 3

Total number of Established sessions 3

To validate the BGP L2VPN output on VTEPs and check MAC-IP routes and ESI information, use the show bgp l2vpn evpn command output. This command verifies routes with status code i (internal) and EVPN route types 2 and 4, displaying detailed information for each VTEP nodes.

```
VTEP1#show bgp l2vpn evpn
BGP table version is 9, local router ID is 1.1.1.1
Status codes: s suppressed, d damped, h history, a add-path, b back-up, * valid, > best, i - internal,
               l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete
```

[EVPN route type]:[ESI]:[VNID]:[relevent route informantion]

1 - Ethernet Auto-discovery Route
2 - MAC/IP Route
3 - Inclusive Multicast Route
4 - Ethernet Segment Route
5 - Prefix Route

Network	Next Hop	Metric	LocPrf	Weight	Path	Peer	Encap
RD[1.1.1.1:100] VRF[VRF1]:							
*> [1]:[00:00:00:00:00:11:11:00:00:00]:[10]:[10]	1.1.1.1	0	100	32768	i -----		VXLAN
* i 2.2.2.2	0	100	0	i 2.2.2.2			VXLAN
*> [1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]							
* i 2.2.2.2	0	100	0	i 2.2.2.2			VXLAN
* i[1]:[00:00:00:00:00:22:22:00:00:00]:[10]:[10]	1.1.1.1	0	100	32768	i -----		VXLAN
* i 2.2.2.2	0	100	0	i 2.2.2.2			VXLAN
* i 2.2.2.2	0	100	0	i 2.2.2.2			VXLAN
* i[1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]	1.1.1.1	0	100	32768	i -----		VXLAN
* i 3.3.3.3	0	100	0	i 3.3.3.3			VXLAN
* i 4.4.4.4	0	100	0	i 4.4.4.4			VXLAN
* i[1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]	1.1.1.1	0	100	32768	i -----		VXLAN
* i 3.3.3.3	0	100	0	i 3.3.3.3			VXLAN
* i 4.4.4.4	0	100	0	i 4.4.4.4			VXLAN
*> [2]:[00:00:00:00:00:11:11:00:00:00]:[10]:[48,0000:1000:1000]:[32,100.100.100.1]:[10]	1.1.1.1	0	100	32768	i -----		VXLAN
* i 2.2.2.2	0	100	0	i 2.2.2.2			VXLAN
*> [2]:[00:00:00:00:00:11:11:00:00:00]:[10]:[48,0000:1000:1001]:[128,1000::1]:[10]	1.1.1.1	0	100	32768	i -----		VXLAN
* i 2.2.2.2	0	100	0	i 2.2.2.2			VXLAN
* i[2]:[0]:[10]:[48,0000:2000:2000]:[32,200.200.200.1]:[10]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
* i[2]:[0]:[10]:[48,0000:2000:2001]:[128,2000::1]:[10]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
* i[2]:[00:00:00:00:00:22:22:00:00:00]:[10]:[48,0000:3000:3000]:[32,103.103.103.1]:[10]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
* i 3.3.3.3	0	100	0	i 3.3.3.3			VXLAN
* i 4.4.4.4	0	100	0	i 4.4.4.4			VXLAN
* i[2]:[00:00:00:00:00:22:22:00:00:00]:[10]:[48,0000:3000:3001]:[128,1003::1]:[10]	3.3.3.3	0	100	0	i 3.3.3.3		VXLAN
* i 4.4.4.4	0	100	0	i 4.4.4.4			VXLAN
* i[2]:[0]:[10]:[48,0000:4000:4000]:[32,104.104.104.1]:[10]	4.4.4.4	0	100	0	i 4.4.4.4		VXLAN
* i[2]:[0]:[10]:[48,0000:4000:4001]:[128,1004::1]:[10]	4.4.4.4	0	100	0	i 4.4.4.4		VXLAN
*> [3]:[10]:[32,1.1.1.1]	1.1.1.1	0	100	32768	i -----		VXLAN
* i[3]:[10]:[32,2.2.2.2]	2.2.2.2	0	100	0	i 2.2.2.2		VXLAN
* i[3]:[10]:[32,3.3.3.3]	3.3.3.3	0	100	0	i 3.3.3.3		VXLAN

```

* i[3]:[10]:[32,4.4.4.4]
    4.4.4.4          0     100      0   i  4.4.4.4        VXLAN

RD[1.1.1.1:64512] VRF[evpn-gvrf-1]:
*> [1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]
    1.1.1.1          0     100      32768 i  -----        VXLAN
*> [4]:[00:00:00:00:00:11:11:00:00:00]:[32,1.1.1.1]
    1.1.1.1          0     100      32768 i  -----        VXLAN
* i[4]:[00:00:00:00:00:11:11:00:00:00]:[32,2.2.2.2]
    2.2.2.2          0     100      0   i  2.2.2.2        VXLAN

RD[2.2.2.2:100]
*>i[1]:[00:00:00:00:00:11:11:00:00:00]:[10]:[10]
    2.2.2.2          0     100      0   i  2.2.2.2        VXLAN
*>i[1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]
    2.2.2.2          0     100      0   i  2.2.2.2        VXLAN
*>i[2]:[00:00:00:00:00:11:11:00:00:00]:[10]:[48,0000:1000:1000]:[32,100.100.100.1]:[10]
    2.2.2.2          0     100      0   i  2.2.2.2        VXLAN
*>i[2]:[00:00:00:00:00:11:11:00:00:00]:[10]:[48,0000:1000:1001]:[128,1000::1][10]
    2.2.2.2          0     100      0   i  2.2.2.2        VXLAN
*>i[2]:[0]:[10]:[48,0000:2000:2000]:[32,200.200.200.1]:[10]
    2.2.2.2          0     100      0   i  2.2.2.2        VXLAN
*>i[2]:[0]:[10]:[48,0000:2000:2001]:[128,2000::1][10]
    2.2.2.2          0     100      0   i  2.2.2.2        VXLAN
*>i[3]:[10]:[32,2.2.2.2]
    2.2.2.2          0     100      0   i  2.2.2.2        VXLAN

RD[2.2.2.2:64512]
*>i[1]:[00:00:00:00:00:11:11:00:00:00]:[4294967295]:[0]
    2.2.2.2          0     100      0   i  2.2.2.2        VXLAN
*>i[4]:[00:00:00:00:00:11:11:00:00:00]:[32,2.2.2.2]
    2.2.2.2          0     100      0   i  2.2.2.2        VXLAN

RD[3.3.3.3:100]
*>i[1]:[00:00:00:00:00:22:22:00:00:00]:[10]:[10]
    3.3.3.3          0     100      0   i  3.3.3.3        VXLAN
*>i[1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
    3.3.3.3          0     100      0   i  3.3.3.3        VXLAN
*>i[2]:[00:00:00:00:00:22:22:00:00:00]:[10]:[48,0000:3000:3000]:[32,103.103.103.1]:[10]
    3.3.3.3          0     100      0   i  3.3.3.3        VXLAN
*>i[2]:[00:00:00:00:00:22:22:00:00:00]:[10]:[48,0000:3000:3001]:[128,1003::1][10]
    3.3.3.3          0     100      0   i  3.3.3.3        VXLAN
*>i[3]:[10]:[32,3.3.3.3]
    3.3.3.3          0     100      0   i  3.3.3.3        VXLAN

RD[3.3.3.3:64512]
*>i[1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
    3.3.3.3          0     100      0   i  3.3.3.3        VXLAN

RD[4.4.4.4:100]
*>i[1]:[00:00:00:00:00:22:22:00:00:00]:[10]:[10]
    4.4.4.4          0     100      0   i  4.4.4.4        VXLAN
*>i[1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
    4.4.4.4          0     100      0   i  4.4.4.4        VXLAN
*>i[2]:[00:00:00:00:00:22:22:00:00:00]:[10]:[48,0000:3000:3000]:[32,103.103.103.1]:[10]
    4.4.4.4          0     100      0   i  4.4.4.4        VXLAN
*>i[2]:[00:00:00:00:00:22:22:00:00:00]:[10]:[48,0000:3000:3001]:[128,1003::1][10]
    4.4.4.4          0     100      0   i  4.4.4.4        VXLAN
*>i[2]:[0]:[10]:[48,0000:4000:4000]:[32,104.104.104.1]:[10]
    4.4.4.4          0     100      0   i  4.4.4.4        VXLAN
*>i[2]:[0]:[10]:[48,0000:4000:4001]:[128,1004::1][10]
    4.4.4.4          0     100      0   i  4.4.4.4        VXLAN
*>i[3]:[10]:[32,4.4.4.4]
    4.4.4.4          0     100      0   i  4.4.4.4        VXLAN

RD[4.4.4.4:64512]
*>i[1]:[00:00:00:00:00:22:22:00:00:00]:[4294967295]:[0]
    4.4.4.4          0     100      0   i  4.4.4.4        VXLAN

```

Total number of prefixes 42

Validate the LAG interfaces (po1 and po2) are up for MH1 and MH2 by reviewing the show etherchannel summary output. Check the Link and sync fields, where link displays the port channel interface and ID number, and sync indicates whether MAC address synchronization is enabled to forward Layer 3 packets arriving on these interfaces.

```
VTEP1#show etherchannel summary
```

```
Aggregator po1 100001
Aggregator Type: Layer2
Admin Key: 0001 - Oper Key 0001
Link: xe7 (5005) sync: 1
```

Validate the status of NVO VXLAN on VTEPs by examining the output of the show nvo vxlan command. The DF-Status field displays the forwarding status of VXLAN tunnels as a Designated Forwarder (DF) or Non-Designated Forwarder (Non-DF).

```
VTEP1#show nvo vxlan
VXLAN Information
```

```
=====
Codes: NW - Network Port
       AC - Access Port
       (u) - Untagged
```

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status	Src-Addr	Dst-Addr
10	---	L2	NW	----	----	----	----	1.1.1.1	4.4.4.4
10	---	L2	NW	----	----	----	----	1.1.1.1	3.3.3.3
10	---	L2	NW	----	----	----	----	1.1.1.1	2.2.2.2
10	---	--	AC	po1	00:00:00:00:00:11:11:00:00:00	1000	DF	----	----

Total number of entries are 4

```
VTEP2#show nvo vxlan
VXLAN Information
```

```
=====
Codes: NW - Network Port
       AC - Access Port
       (u) - Untagged
```

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status	Src-Addr	Dst-Addr
10	---	L2	NW	----	----	----	----	2.2.2.2	4.4.4.4
10	---	L2	NW	----	----	----	----	2.2.2.2	1.1.1.1
10	---	L2	NW	----	----	----	----	2.2.2.2	3.3.3.3
10	---	--	AC	xe37	--- Single Homed Port ---	1000	---	---	----
10	---	--	AC	po1	00:00:00:00:00:11:11:00:00:00	1000	NON-DF	----	----

Total number of entries are 5

```
VTEP3#show nvo vxlan
VXLAN Information
```

```
=====
Codes: NW - Network Port
       AC - Access Port
       (u) - Untagged
```

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status	Src-Addr	Dst-Addr
10	---	L2	NW	----	----	----	----	3.3.3.3	2.2.2.2
10	---	L2	NW	----	----	----	----	3.3.3.3	1.1.1.1
10	---	L2	NW	----	----	----	----	3.3.3.3	4.4.4.4
10	---	--	AC	po2	00:00:00:00:00:22:22:00:00:00	1000	DF	----	----

Total number of entries are 4

```
VTEP4#show nvo vxlan
VXLAN Information
```

```
=====
Codes: NW - Network Port
       AC - Access Port
       (u) - Untagged
```

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status	Src-Addr	Dst-Addr
10	---	L2	NW	----	----	----	----	4.4.4.4	2.2.2.2
10	---	L2	NW	----	----	----	----	4.4.4.4	3.3.3.3
10	---	L2	NW	----	----	----	----	4.4.4.4	1.1.1.1
10	---	--	AC	xe34	--- Single Homed Port ---	1000	----	----	----
10	---	--	AC	po2	00:00:00:00:22:22:00:00:00	1000	NON-DF	----	----

Total number of entries are 5

Validate the NVO VXLAN tunnel status on VTEPs by reviewing the output of the `show nvo vxlan tunnel` command. The `Status` field indicates the current status of each tunnel. In this case, all three tunnels between VTEPs and their respective destinations are marked as `Installed`, confirming that these tunnels are successfully established and operating.

VTEP1#show nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
1.1.1.1	4.4.4.4	Installed	00:02:26	00:01:58
1.1.1.1	3.3.3.3	Installed	00:02:26	00:01:55
1.1.1.1	2.2.2.2	Installed	00:02:25	00:01:55

Total number of entries are 3

Validate the VXLAN access interface status on VTEPs by examining the output of the `show nvo vxlan access-if brief` command. The `up` admin and link status confirms that the access port associated with VXLAN is active and functioning properly on the VTEP nodes.

VTEP1#show nvo vxlan access-if brief

Interface	Inner Vlan	Inner vlan	Ifindex	Vnid	Admin status	Link status
po1	1000	---	0x7a120	10	up	up

Total number of entries are 1

Static MAC-IP Advertisement

Configure static MAC-IP advertisement through SH and MH VTEPs from Root and Leaf nodes. Advertise static MAC addresses for IPv4 and IPv6 from MH1, MH2, SH1, and SH2 VTEPs. Ensure that VTEP1 and VTEP2 in MH1 have the same MAC addresses configured under the port-channel access port. Symmetrical configurations between MH VTEPs should be maintained.

Configure MH1 and MH2 VTEPs

Configure static MAC addresses for IPv4 (100.100.100.1) and IPv6 (1000::1) under the VXLAN MH access-port (`po1`) with VLAN ID (1000). Ensure that identical MAC addresses are set up within the MH1-VTEPs for advertisement. Apply similar configurations to MH2-VTEPs for static MAC-IP advertisement.

```
!
nvo vxlan access-if port-vlan po1 1000
  map vnid 10
  mac 0000.1000.1000 ip 100.100.100.1
  mac 0000.1000.1001 ipv6 1000::1
!
```

Configure SH1 and SH2 VTEPs

Configure static MAC addresses for IPv4 (200.200.200.1) and IPv6 (2000::1) under the VXLAN SH access-port (xe37) with VLAN ID (1000) on SH1 (VTEP2). This setup ensures that SH1 advertises these static MAC addresses over the specified VXLAN access-port. Repeat similar configurations for SH2 (VTEP4) using different static MAC addresses for both IPv4 and IPv6.

```
!
nvo vxlan access-if port-vlan xe37 1000
map vnid 10
mac 0000.2000.2000 ip 200.200.200.1
mac 0000.2000.2001 ipv6 2000::1
!
```

Validation

Verify the MAC table entries on MH VTEPs (MH1 and MH2) and the SH VTEPs (VTEP2 and VTEP4). The MAC addresses are advertised using the ESI values from VTEP1 and VTEP2 for MH1, and from VTEP3 and VTEP4 for MH2. Additionally, verify the VTEP IP addresses associated with SH VTEP2 and VTEP4 for MAC advertisement.

In the output of the `show nvo vxlan mac-table` command on all VTEP nodes, the MAC entries advertised from Leaf VTEPs will have the `LeafFlag` field set.

Note:

- MAC IPv4 or IPv6 configured under SH Leaf VTEP access port will be advertised to the Root VTEP and other Leaf VTEPs.
- MAC IPv4 or IPv6 configured under an MH Leaf VTEP access port must be symmetric and will be advertised to both the Root VTEP and other leaf VTEPs.
- MAC IPv4 or IPv6 configured under either SH or MH Root VTEP will be advertised to both the Root VTEP and the Leaf VTEPs.
- The Leaf-to-Leaf communication will display MAC status and tunnel status per VNI as Leaf type. The MAC will be in the discard state in the BCM shell.

```
VTEP1#show nvo vxlan mac-table
=====
          VXLAN MAC Entries
=====
VNID Interface VlanId In-VlanId Mac-Addr      VTEP-Ip/ESI      Type  Status  MAC move AccessPortDesc LeafFlag
10   po1     1000   ----  0000.1000.1000  00:00:00:00:00:11:11:00:00:00:00  Static Local  -----  0  -----  -----
10   po1     1000   ----  0000.1000.1001  00:00:00:00:00:11:11:00:00:00:00  Static Local  -----  0  -----  -----
10   ----     ----   ----  0000.2000.2000  2.2.2.2           Static Remote -----  0  -----  -----
10   ----     ----   ----  0000.2000.2001  2.2.2.2           Static Remote -----  0  -----  -----
10   ----     ----   ----  0000.3000.3000  00:00:00:00:00:22:22:00:00:00:00  Static Remote -----  0  -----  set
10   ----     ----   ----  0000.3000.3001  00:00:00:00:00:22:22:00:00:00:00  Static Remote -----  0  -----  set
10   ----     ----   ----  0000.4000.4000  4.4.4.4           Static Remote -----  0  -----  set
10   ----     ----   ----  0000.4000.4001  4.4.4.4           Static Remote -----  0  -----  set

Total number of entries are : 8
```

```
VTEP3#show nvo vxlan mac-table
=====
          VXLAN MAC Entries
=====
VNID Interface VlanId In-VlanId Mac-Addr      VTEP-Ip/ESI      Type  Status  MAC move AccessPortDesc LeafFlag
10   ----     ----   ----  0000.1000.1000  00:00:00:00:00:11:11:00:00:00:00  Static Remote -----  0  -----  -----
10   ----     ----   ----  0000.1000.1001  00:00:00:00:00:11:11:00:00:00:00  Static Remote -----  0  -----  -----
10   ----     ----   ----  0000.2000.2000  2.2.2.2           Static Remote -----  0  -----  -----
10   ----     ----   ----  0000.2000.2001  2.2.2.2           Static Remote -----  0  -----  -----
10   po2     1000   ----  0000.3000.3000  00:00:00:00:00:22:22:00:00:00:00  Static Local  -----  0  -----  set
10   po2     1000   ----  0000.3000.3001  00:00:00:00:00:22:22:00:00:00:00  Static Local  -----  0  -----  set
10   ----     ----   ----  0000.4000.4000  4.4.4.4           Static Remote -----  0  -----  set
```

```
10 ----      ---      0000.4000.4001 4.4.4.4           Static Remote  -----  0  ----- set
```

Total number of entries are : 8

Use the `show nvo vxlan arp-cache` command to verify the Address Resolution Protocol (ARP) cache information on all VTEP nodes. This command displays entries that map IPv4 addresses to MAC addresses within the specified VXLAN VNID network.

VTEP1#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
10	100.100.100.1	0000.1000.1000	Static	Local	----
10	103.103.103.1	0000.3000.3000	Static	Remote	----
10	104.104.104.1	0000.4000.4000	Static	Remote	----
10	200.200.200.1	0000.2000.2000	Static	Remote	----

Total number of entries are 4

VTEP3#show nvo vxlan arp-cache

VXLAN ARP-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
10	100.100.100.1	0000.1000.1000	Static	Remote	----
10	103.103.103.1	0000.3000.3000	Static	Local	----
10	104.104.104.1	0000.4000.4000	Static	Remote	----
10	200.200.200.1	0000.2000.2000	Static	Remote	----

Total number of entries are 4

Use the `show nvo vxlan nd-cache` command to verify the Neighbor Discovery (ND) cache information on all VTEP nodes. This command displays entries that map IPv6 addresses to MAC addresses within the specified VXLAN VNID network.

VTEP1#show nvo vxlan nd-cache

VXLAN ND-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
10	1000::1	0000.1000.1001	Static	Local	----
10	1003::1	0000.3000.3001	Static	Remote	----
10	1004::1	0000.4000.4001	Static	Remote	----
10	2000::1	0000.2000.2001	Static	Remote	----

Total number of entries are 4

VTEP3#show nvo vxlan nd-cache

VXLAN ND-CACHE Information

=====

VNID	Ip-Addr	Mac-Addr	Type	Age-Out
Retries-Left				
10	1000::1	0000.1000.1001	Static	Remote
10	1003::1	0000.3000.3001	Static	Local
10	1004::1	0000.4000.4001	Static	Remote

10	2000::1	0000.2000.2001 Static Remote	----
Total number of entries are 4			

Network Topology Snippet Configurations

Here are the snippet configurations for all nodes in the given network topology.

VTEP1

```
!
nvo vxlan enable
!
evpn esi hold-time 90
!
evpn vxlan multihoming enable
!
mac vrf VRF1
  rd 1.1.1.1:100
  route-target both 100:100
!
nvo vxlan vtep-ip-global 1.1.1.1
!
nvo vxlan id 10 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp VRF1
!
qos enable
!
interface po1
  switchport
  evpn multi-homed system-mac 0000.0000.1111
!
interface lo
  ip address 1.1.1.1/32 secondary
!
interface xe7
  channel-group 1 mode active
!
interface xe45
  ip address 10.10.10.1/24
!
interface xe49/2
  ip address 10.10.11.1/24
!
exit
!

router ospf 100
  ospf router-id 1.1.1.1
  bfd all-interfaces
  network 1.1.1.1/32 area 0.0.0.0
  network 10.10.10.0/24 area 0.0.0.0
  network 10.10.11.0/24 area 0.0.0.0
!
router bgp 100
  bgp router-id 1.1.1.1
  neighbor 2.2.2.2 remote-as 100
  neighbor 3.3.3.3 remote-as 100
  neighbor 4.4.4.4 remote-as 100
```

```

neighbor 2.2.2.2 update-source lo
neighbor 2.2.2.2 advertisement-interval 0
neighbor 3.3.3.3 update-source lo
neighbor 3.3.3.3 advertisement-interval 0
neighbor 4.4.4.4 update-source lo
neighbor 4.4.4.4 advertisement-interval 0
!
address-family l2vpn evpn
neighbor 2.2.2.2 activate
neighbor 3.3.3.3 activate
neighbor 4.4.4.4 activate
exit-address-family
!
exit
!
nvo vxlan access-if port-vlan pol 1000
map vnid 10
mac 0000.1000.1000 ip 100.100.100.1
mac 0000.1000.1001 ipv6 1000::1
!

```

VTEP2

```

!
nvo vxlan enable
!
evpn esi hold-time 90
!
evpn vxlan multihoming enable
!
mac vrf VRF1
  rd 2.2.2.2:100
  route-target both 100:100
!
nvo vxlan vtep-ip-global 2.2.2.2
!
nvo vxlan id 10 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp VRF1
!
qos enable
!
interface pol
  switchport
  evpn multi-homed system-mac 0000.0000.1111
!
interface lo
  ip address 2.2.2.2/32 secondary
!
interface xe38
  channel-group 1 mode active
!
interface xe49/1
  ip address 20.20.20.1/24
!
interface xe50/1
  ip address 20.20.21.1/24

```

```

!
exit
!

router ospf 100
  ospf router-id 2.2.2.2
  bfd all-interfaces
  network 2.2.2.2/32 area 0.0.0.0
  network 20.20.20.0/24 area 0.0.0.0
  network 20.20.21.0/24 area 0.0.0.0
!
router bgp 100
  bgp router-id 2.2.2.2
  neighbor 1.1.1.1 remote-as 100
  neighbor 3.3.3.3 remote-as 100
  neighbor 4.4.4.4 remote-as 100
  neighbor 1.1.1.1 update-source lo
  neighbor 1.1.1.1 advertisement-interval 0
  neighbor 3.3.3.3 update-source lo
  neighbor 3.3.3.3 advertisement-interval 0
  neighbor 4.4.4.4 update-source lo
  neighbor 4.4.4.4 advertisement-interval 0
!
address-family l2vpn evpn
  neighbor 1.1.1.1 activate
  neighbor 3.3.3.3 activate
  neighbor 4.4.4.4 activate
exit-address-family
!
exit
!
nvo vxlan access-if port-vlan xe37 1000
  map vnid 10
  mac 0000.2000.2000 ip 200.200.200.1
  mac 0000.2000.2001 ipv6 2000::1
!
nvo vxlan access-if port-vlan po1 1000
  map vnid 10
  mac 0000.1000.1000 ip 100.100.100.1
  mac 0000.1000.1001 ipv6 1000::1
!
```

VTEP3

```

!
nvo vxlan enable
!
evpn esi hold-time 90
!
evpn vxlan multihoming enable
!
evpn etree enable
!
mac vrf VRF1
  rd 3.3.3.3:100
  route-target both 100:100
```

```

!
nvo vxlan vtep-ip-global 3.3.3.3
!
nvo vxlan id 10 ingress-replication inner-vid-disabled etree-leaf
  vxlan host-reachability-protocol evpn-bgp VRF1
!
qos enable
!
interface po2
  switchport
    evpn multi-homed system-mac 0000.0000.2222
!
interface lo
  ip address 3.3.3.3/32 secondary
!
interface xe53/1
  ip address 30.30.30.1/24
!
interface xe54/1
  ip address 30.30.31.1/24
!
interface xe55/1
  channel-group 2 mode active
!
exit
!
router ospf 100
  ospf router-id 3.3.3.3
  bfd all-interfaces
  network 3.3.3.3/32 area 0.0.0.0
  network 30.30.30.0/24 area 0.0.0.0
  network 30.30.31.0/24 area 0.0.0.0
!
router bgp 100
  bgp router-id 3.3.3.3
  neighbor 1.1.1.1 remote-as 100
  neighbor 2.2.2.2 remote-as 100
  neighbor 4.4.4.4 remote-as 100
  neighbor 1.1.1.1 update-source lo
  neighbor 1.1.1.1 advertisement-interval 0
  neighbor 2.2.2.2 update-source lo
  neighbor 2.2.2.2 advertisement-interval 0
  neighbor 4.4.4.4 update-source lo
  neighbor 4.4.4.4 advertisement-interval 0
!
  address-family l2vpn evpn
    neighbor 1.1.1.1 activate
    neighbor 2.2.2.2 activate
    neighbor 4.4.4.4 activate
  exit-address-family
!
exit
!
!
nvo vxlan access-if port-vlan po2 1000
  map vnid 10
  mac 0000.3000.3000 ip 103.103.103.1

```

```
mac 0000.3000.3001 ipv6 1003::1
!
```

VTEP4

```
!
nvo vxlan enable
!
evpn esi hold-time 90
!
evpn vxlan multihoming enable
!
evpn etree enable
!
mac vrf VRF1
  rd 4.4.4.4:100
  route-target both 100:100
!
nvo vxlan vtep-ip-global 4.4.4.4
!
nvo vxlan id 10 ingress-replication inner-vid-disabled etree-leaf
  vxlan host-reachability-protocol evpn-bgp VRF1
!
qos enable
!
interface po2
  switchport
  evpn multi-homed system-mac 0000.0000.2222
!
interface lo
  ip address 4.4.4.4/32 secondary
!
interface xe11/1
  ip address 40.40.41.1/24
!
interface xe31/1
  channel-group 2 mode active
!
interface xe33
  ip address 40.40.40.1/24
!
interface xe34
  switchport
!
exit
!
router ospf 100
  ospf router-id 4.4.4.4
  bfd all-interfaces
  network 4.4.4.4/32 area 0.0.0.0
  network 40.40.40.0/24 area 0.0.0.0
  network 40.40.41.0/24 area 0.0.0.0
!
router bgp 100
  bgp router-id 4.4.4.4
  neighbor 1.1.1.1 remote-as 100
```

```

neighbor 2.2.2.2 remote-as 100
neighbor 3.3.3.3 remote-as 100
neighbor 1.1.1.1 update-source lo
neighbor 1.1.1.1 advertisement-interval 0
neighbor 2.2.2.2 update-source lo
neighbor 2.2.2.2 advertisement-interval 0
neighbor 3.3.3.3 update-source lo
neighbor 3.3.3.3 advertisement-interval 0
!
address-family l2vpn evpn
neighbor 1.1.1.1 activate
neighbor 2.2.2.2 activate
neighbor 3.3.3.3 activate
exit-address-family
!
exit
!
nvo vxlan access-if port-vlan xe34 1000
map vnid 10
mac 0000.4000.4000 ip 104.104.104.1
mac 0000.4000.4001 ipv6 1004::1
!
nvo vxlan access-if port-vlan po2 1000
map vnid 10
mac 0000.3000.3000 ip 103.103.103.1
mac 0000.3000.3001 ipv6 1003::1
!
```

SPINE1

```

!
qos enable
!
interface ce1/2
ip address 40.40.40.2/24
!
interface ce1/4
ip address 10.10.10.2/24
!
interface ce24/1
ip address 30.30.30.2/24
!
interface ce27/1
ip address 20.20.20.2/24
!
interface lo
ip address 5.5.5.5/32 secondary
!
exit
!
router ospf 100
ospf router-id 5.5.5.5
bfd all-interfaces
network 5.5.5.5/32 area 0.0.0.0
network 10.10.10.0/24 area 0.0.0.0
network 20.20.20.0/24 area 0.0.0.0
```

```

network 30.30.30.0/24 area 0.0.0.0
network 40.40.40.0/24 area 0.0.0.0
!
```

SPINE2

```

!
qos enable
!
interface ce5/1
  ip address 20.20.21.2/24
!
interface ce10/1
  ip address 30.30.31.2/24
!
interface ce11/1
  ip address 40.40.41.2/24
!
interface ce14/2
  ip address 10.10.11.2/24
!
interface lo
  ip address 6.6.6.6/32 secondary
!
exit
!
router ospf 100
  ospf router-id 6.6.6.6
  bfd all-interfaces
  network 6.6.6.6/32 area 0.0.0.0
  network 10.10.11.0/24 area 0.0.0.0
  network 20.20.21.0/24 area 0.0.0.0
  network 30.30.31.0/24 area 0.0.0.0
  network 40.40.41.0/24 area 0.0.0.0
!
```

SWITCH1

```

!
bridge 1 protocol ieee vlan-bridge
!
vlan database
  vlan-reservation 4000-4094
  vlan 1000 bridge 1 state enable
!
interface po1
  switchport
  bridge-group 1
  switchport mode hybrid
  switchport mode hybrid acceptable-frame-type all
  switchport hybrid allowed vlan add 1000 egress-tagged enable
!
interface xe46
  channel-group 1 mode active
!
interface xe47
```

```

channel-group 1 mode active
!
interface xe57
  switchport
  bridge-group 1
  switchport mode hybrid
  switchport mode hybrid acceptable-frame-type all
  switchport hybrid allowed vlan add 1000 egress-tagged enable
!
exit
!
```

SWITCH2

```

!
bridge 1 protocol ieee vlan-bridge
!
vlan database
  vlan-reservation 4000-4094
  vlan 1000 bridge 1 state enable
!
interface po2
  switchport
  bridge-group 1
  switchport mode hybrid
  switchport mode hybrid acceptable-frame-type all
  switchport hybrid allowed vlan add 1000 egress-tagged enable
!
interface xe33
  switchport
  bridge-group 1
  switchport mode hybrid
  switchport mode hybrid acceptable-frame-type all
  switchport hybrid allowed vlan add 1000 egress-tagged enable
!
interface xe49/1
  channel-group 2 mode active
!
interface xe51/1
  channel-group 2 mode active
!
exit
!
```

Implementation Examples

Here is an example scenario and a solution for implementing EVPN E-Tree.

Scenario 1: Specific traffic isolation and control measures are essential in a network of EVPN L2VPN services or instances. Within a broadcast domain, services communicating with each other may result in flooding BUM traffic to all services within the domain. Moreover, hosts are learned and advertised between different sites/services.

Use Case 1: Implementing an EVPN E-Tree solution defines the network topology with distinct Root and Leaf classifications, BUM traffic flooding can be minimized, and traffic isolation can be achieved. This ensures efficient communication between services while preventing unnecessary traffic propagation and maintaining network integrity.

Scenario 2: An Internet Service Provider (ISP) provides services to multiple subscribers and aims to facilitate communication with them. However, the ISP needs to ensure that subscribers exclusively communicate with the ISP and not among themselves.

Use Case 2: Implementing EVPN E-Tree is essential to fulfill this requirement. By categorizing ISP services as Root and subscribers as Leaf, traffic isolation can be enforced. This configuration enables the ISP to communicate with subscribers while preventing inter-subscriber communication. As a result, network security is enhanced, and the ISP maintains control over communication within its network.

E-Tree CLI Commands

The EVPN E-Tree introduces the following configuration commands in OcNOS.

evpn etree

Use this command to enable E-Tree functionality within the EVPN configuration.

Command Syntax

```
evpn etree enable
```

Parameters

None

Default

Disabled

Command Mode

Configure mode

Applicability

Introduced in OcNOS version 6.5.1.

Example

The following example illustrates how to activate E-Tree functionality for EVPN:

```
OcNOS#configure terminal
OcNOS(config)#evpn etree enable
```

Revised CLI Commands

The following is the revised command for configuring VXLAN EVPN E-Tree

nvo vxlan id

- The existing syntax now includes the newly added parameter for E-Tree, namely `etree-leaf`.
- The command `nvo vxlan id <VNID> ingress-replication inner-vid-disabled etree-leaf` allows users to tailor VXLAN behavior on a network device, specifying VXLAN parameters and indicating its

participation as a leaf node in an E-Tree deployment. For more details, refer to the [nvo vxlan id](#) command in the [VXLAN Commands](#) chapter in the [OcNOS VXLAN Guide](#).

Troubleshooting

1. When traffic, whether unicast (UC) or broadcast, is passed to the Intra Leaf site:
 - Check the sub-interface or physical interface counters to monitor traffic throughput and potential issues.
 - Verify the Leaf status of the corresponding VNI to ensure proper functionality.
 - Use packet sniffing tools to analyze packets in the egress direction for any anomalies or errors.
 - MAC entries learned via leaf access port should include the `set` keyword in the MAC table output.
2. If UC traffic is routed within inter-PE leaf sites:
 - Check the Leaf status of the VNI at both participating PE devices to confirm operational status.
 - Check if the advertised MAC is in discard or non-discard status using the `show mac table` command and `show` in the BCM shell.
3. Verify if BUM traffic is transmitted between Leaf sites inter-PE:
 - Ensure that a BUM tunnels are not established between inter-PE devices.
 - Validate this by examining the Multicast ingress group, using the `show evpn mpls tunnel` command. For EVPN MPLS, confirm that BUM tunnels are not created.
4. Investigate UC traffic drops from the Root to MH Leaf PE:
 - Check if MAC addresses are not installed in discard status within the MH peer's access port. This status could indicate issues with MAC learning or forwarding.
5. Evaluate traffic between Root and Leaf:
 - Confirm the establishment of both UC and BUM tunnels.
 - Ensure that unicast MAC addresses are not marked with a discard status in the MAC table.
6. Validate the exchange of routes between two BGP L2VPN peers:
 - Monitor BGP (Border Gateway Protocol) sessions to verify successful route exchange and propagation between the peers.
7. Convergence: Assess convergence by checking BFD configuration between BGP sessions.

Glossary

The following provides definitions for key terms or abbreviations and their meanings used throughout this document:

Key Terms/Acronym	Description
Ethernet VPN Ethernet-Tree (EVPN E-Tree)	A networking solution designed to manage communication within broadcast domains, incorporating redundancy through multi-homing in a network. It optimizes traffic routing and control, categorizing network nodes based on predefined definitions of EVPN Instances as Leaf or Root, allowing or restricting communication between them.

Virtual Extensible LAN (VXLAN)	A technology that provides encapsulation techniques to create virtualized Layer 2 networks over Layer 3 infrastructure, facilitating scalable and flexible network designs.
Ethernet Virtual Private Network (EVPN)	A Layer 2 VPN technology that extends Ethernet services across data centers and wide-area networks using BGP.
Multi-homing (MH)	The ability of a device to connect to multiple network segments simultaneously to increase network availability and redundancy.
Provider Edge (PE) Node	A device at the edge of a service provider network that connects to customer premises equipment (CE) and participates in providing services to customers.
Leaf Node	In the context of EVPN E-Tree, a network node categorized to handle communication within specific broadcast domains and may connect to Root nodes.
Root Node	A network node within EVPN E-Tree that serves as the central point of communication and handles BUM traffic distribution.
Ethernet Segment Identifier (ESI)	A unique identifier used to identify Ethernet segments within a VXLAN network.

CHAPTER 3 VXLAN Tunnel Over SVI

This chapter contains the configurations for VXLAN Tunnel Over SVI.

Overview

VxLAN EVPN solution is envisioned to simplify the topology and configurations in Data Centers (DC). In Data Centers, CLOS topology was used, which makes network side pure L3 and uses EBGP as IGP.

VxLAN solution is required for Service Providers (SP) as well to run few of the services or all services in their network over VxLAN. When they choose to run few services over VxLAN, then on the network side there will be a need to run VxLAN over SVI.

Topology

The Topology shown below contains the 3 VTEPS i.e VTEP1 ,VTEP2 and VTEP3 and 3 core nodes P1 ,P2 and P3. Vxlan tunnel will be established between VTEPS over SVI interfaces. OSPF as IGP will be running between VTEPS and the core node to provide the end to end connectivity. Switch is connected between host and VTEP-1, VTEP-2 via dynamic LAG.




Figure 3-7: VXLAN over SVI

RTR1/VTEP1

VTEP1#configure terminal	Enter configuration terminal
VTEP1(config)#hostname VTEP1	Configure hostname
VTEP1(config)#mac vrf vrf1	Configure MAC vrf vrf1
VTEP1(config-vrf)#rd 1.1.1.1:11	Configure RD for vrf1

VTEP1 (config-vrf) #route-target both 10.10.10.10:100	Configure RT for vrf1
VTEP1 (config-vrf) #mac vrf vrf2	Configure MAC vrf vrf2
VTEP1 (config-vrf) #rd 1.1.1.1:12	Configure RD for vrf2
VTEP1 (config-vrf) #route-target both 10.10.10.10:102	Configure RT for vrf2
VTEP1 (config-vrf) #bfd interval 3 minrx 3 multiplier 3	Configure BFD interval globally
VTEP1 (config) #evpn vxlan multihoming enable	Enable EVPN VXLAN multihoming
VTEP1 (config) #nvo vxlan enable	Enable VXLAN
VTEP1 (config) #qos enable	Enable qos
VTEP1 (config) #qos statistics	Enable qos statistics
VTEP1 (config) #bridge 1 protocol ieee vlan- bridge	Configure IEEE VLAN bridge
VTEP1 (config) #no bridge 1 spanning-tree enable	Disable spanning tree in bridge 1 globally
VTEP1 (config) #no igmp snooping	Disable igmp snooping messages globally
VTEP1 (config) #vlan database	Enter into the VLAN database
VTEP1 (config-vlan) #vlan 10-200 bridge 1 state enable	Configure VLAN 10-200 and associate with bridge 1
VTEP1 (config-vlan) #vlan 4000 bridge 1 state enable	Configure VLAN 4000 and associate with bridge 1
VTEP1 (config-vlan) #interface po1	Enter interface mode
VTEP1 (config-if) #switchport	Set the interface as Layer2 port
VTEP1 (config-if) #load-interval 30	Configure load period in multiple of 30 seconds
VTEP1 (config-if) #evpn multi-homed system-mac aa22.3344.5566	Configure EVPN system-MAC
VTEP1 (config-if) #interface lo	Enter lo interface mode
VTEP1 (config-if) #ip address 1.1.1.1/32 secondary	Assign loopback IP
VTEP1 (config-if) #interface vlan1.10	Specify interface VLAN1.10 to be configured.
VTEP1 (config-if) #ip address 12.1.1.1/24	Assign IP address
VTEP1 (config-if) #ip ospf cost 1	Change OSPF cost of the link
VTEP1 (config-if) #interface vlan1.20	Specify interface VLAN1.20 to be configured.
VTEP1 (config-if) #ip address 13.1.1.1/24	Assign IP address
VTEP1 (config-if) #ip ospf cost 1	Change OSPF cost of the link
VTEP1 (config-if) #interface vlan1.30	Specify interface VLAN1.30 to be configured.
VTEP1 (config-if) #ip address 14.1.1.1/24	Assign IP address
VTEP1 (config-if) #ip ospf cost 1	Change OSPF cost of the link
VTEP1 (config-if) #interface xe1	Enter interface mode
VTEP1 (config-if) #switchport	Set the interface as Layer2 port
VTEP1 (config-if) #bridge-group 1 spanning- tree disable	Associate the interface with bridge group 1 and disable spanning tree
VTEP1 (config-if) #switchport mode trunk	Set the switching characteristics of this interface to trunk mode.

VTEP1 (config-if) #switchport trunk allowed vlan add 20,29	Enable VLAN's allowed on this interface.
VTEP1 (config-if) #switchport trunk native vlan 29	Configure native VLAN
VTEP1 (config-if) #load-interval 30	Configure load period in multiple of 30 seconds
VTEP1 (config-if) #spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
VTEP1 (config-if) #interface xe5	Enter interface mode
VTEP1 (config-if) #switchport	Set the interface as Layer2 port
VTEP1 (config-if) #bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
VTEP1 (config-if) #switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
VTEP1 (config-if) #switchport trunk allowed vlan add 10,19	Enable VLAN's allowed on this interface.
VTEP1 (config-if) #switchport trunk native vlan 19	Configure native VLAN
VTEP1 (config-if) #load-interval 30	Configure load period in multiple of 30 seconds
VTEP1 (config-if) #spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
VTEP1 (config-if) #interface xe7	Enter interface mode
VTEP1 (config-if) #switchport	Set the interface as Layer2 port
VTEP1 (config-if) #bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
VTEP1 (config-if) #switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
VTEP1 (config-if) #switchport trunk allowed vlan add 30,39	Enable VLAN's allowed on this interface.
VTEP1 (config-if) #switchport trunk native vlan 39	Configure native VLAN
VTEP1 (config-if) #load-interval 30	Configure load period in multiple of 30 seconds
VTEP1 (config-if) #spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
VTEP1 (config-if) #interface xe41	Enter interface mode
VTEP1 (config-if) #channel-group 1 mode active	Map this interface to po1
VTEP1 (config-if) #interface xe42	Enter interface mode
VTEP1 (config-if) #channel-group 1 mode active	Map this interface to po1
VTEP1 (config-if) #interface xe46	Enter interface mode
VTEP1 (config-if) #switchport	Map this interface to po1
VTEP1 (config-if) #router ospf 1	Enter OSPF configuration mode
VTEP1 (config-router) #ospf router-id 1.1.1.1	Configure OSPF router id
VTEP1 (config-router) #bfd all-interfaces	Enable BFD in all OSPF interfaces
VTEP1 (config-router) #network 1.1.1.1/32 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
VTEP1 (config-router) #network 12.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
VTEP1 (config-router) #network 13.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.

VTEP1 (config-router) #network 14.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
VTEP1 (config-router) #router bgp 100	Enter Router BGP mode and define the AS number 100.
VTEP1 (config-router) #address-family ipv4 unicast	Enter address-family IPv4 unicast mode
VTEP1 (config-router) #network 1.1.1.1/32	Add the lo network to BGP route
VTEP1 (config-router-af) #neighbor 2.2.2.2 activate	Activate neighbors
VTEP1 (config-router-af) #neighbor 6.6.6.6 activate	Activate neighbors
VTEP1 (config-router-af) #exit-address-family	Exit address-family mode.
VTEP1 (config-router) #neighbor 2.2.2.2 remote-as 100	Configure BGP remote-as 100 with neighbor IP
VTEP1 (config-router) #neighbor 2.2.2.2 update-source lo	Define BGP neighbors, to update the source routes with lo
VTEP1 (config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP2
VTEP1 (config-router) #neighbor 6.6.6.6 remote-as 100	Configure BGP remote-as 100 with neighbor IP
VTEP1 (config-router) #neighbor 6.6.6.6 update-source lo	Define BGP neighbors, to update the source routes with lo
VTEP1 (config-router) #neighbor 6.6.6.6 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP3
VTEP1 (config-router) #address-family l2vpn evpn	Enter in to BGP L2VPN EVPN address-family
VTEP1 (config-router-af) #neighbor 2.2.2.2 activate	Activate neighbors
VTEP1 (config-router-af) #neighbor 6.6.6.6 activate	Activate neighbors
VTEP1 (config-router-af) #exit-address-family	Exit from BGP L2VPN EVPN address-family
VTEP1 (config-router) #nvo vxlan vtep-ip-global 1.1.1.1	Configure VXLAN global IP
VTEP1 (config) #nvo vxlan id 1 ingress-replication inner-vid-disabled	Create VNID 1
VTEP1 (config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf1	Associate VNID with EVPN and vrf1
VTEP1 (config-nvo) #nvo vxlan id 1000 ingress-replication inner-vid-disabled	Create VNID 1000
VTEP1 (config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf2	Associate VNID with EVPN and vrf2
VTEP1 (config-nvo-acc-if) #nvo vxlan access-if port-vlan po1 2000	Create VXLAN access port port-vlan
VTEP1 (config-nvo-acc-if) #no shutdown	Unshut the access interface
VTEP1 (config-nvo-acc-if) #map vnid 1000	Map the VNID to access-if
VTEP1 (config-nvo) #nvo vxlan access-if port xe46	Create VXLAN access port
VTEP1 (config-nvo-acc-if) #no shutdown	Unshut the access interface
VTEP1 (config-nvo-acc-if) #map vnid 1	Map the VNID to access-if

VTEP1 (config-nvo-acc-if) #nvo vxlan access-if port-vlan pol 1000	Create VXLAN access port port-vlan
VTEP1 (config-nvo-acc-if) #no shutdown	Unshut the access interface
VTEP1 (config-nvo-acc-if) #map vnid 1	Map the VNID to access-if
VTEP1 (config-nvo-acc-if) #mac 0000.1111.1111 ip 100.1.1.100	Configure static MAC IP
VTEP1 (config-nvo-acc-if) #mac 0000.1111.1112	Configure static MAC
VTEP1 (config-nvo-acc-if) #mac 0000.1111.1113	Configure static MAC
VTEP1 (config-nvo-acc-if) #mac 0000.1111.1114	Configure static MAC
VTEP1 (config-nvo-acc-if) #mac 0000.1111.1115	Configure static MAC
VTEP1 (config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration

VTEP2

VTEP2#configure terminal	Enter configuration terminal
VTEP2 (config) #hostname VTEP2	Configure hostname
VTEP2 (config) #mac vrf vrf1	Configure MAC VRF vrf1
VTEP2 (config-vrf) #rd 2.2.2.2:11	Configure RD for vrf1
VTEP2 (config-vrf) #route-target both 10.10.10.10:100	Configure RT for vrf1
VTEP2 (config-vrf) #mac vrf vrf2	Configure MAC VRF vrf2
VTEP2 (config-vrf) #rd 2.2.2.2:12	Configure RD for vrf2
VTEP2 (config-vrf) #route-target both 10.10.10.10:102	Configure RT for vrf2
VTEP2 (config) #nvo vxlan enable	Enable VXLAN
VTEP2 (config) #evpn vxlan multihoming enable	Enable EVPN VXLAN multihoming
VTEP2 (config) #qos enable	Enable QOS
VTEP2 (config) #qos statistics	Enable QOS statistics
VTEP2 (config) #bridge 1 protocol ieee vlan-bridge	Configure IEEE VLAN bridge
VTEP2 (config) #no bridge 1 spanning-tree enable	Disable spanning tree in bridge 1 globally
VTEP2 (config) #vlan database	Enter into the VLAN database
VTEP2 (config-vlan) #vlan 10-200 bridge 1 state enable	Configure VLAN 10-200 and associate with bridge 1
VTEP2 (config-vlan) #interface pol	Enter interface mode
VTEP2 (config-if) #switchport	Set the interface as Layer2 port
VTEP2 (config-if) #load-interval 30	Configure load period in multiple of 30 seconds
VTEP2 (config-if) #evpn multi-homed system-mac aa22.3344.5566	Configure EVPN system-MAC
VTEP2 (config-if) #interface lo	Enter interface mode
VTEP2 (config-if) #ip address 2.2.2.2/32 secondary	Configure loopback IP
VTEP2 (config-if) #interface vlan1.10	Specify interface VLAN1.10 to be configured.

VTEP2 (config-if) #ip address 12.1.1.2/24	Assign IP address
VTEP2 (config-if) #interface vlan1.40	Specify interface VLAN1.40 to be configured.
VTEP2 (config-if) #ip address 23.1.1.1/24	Assign IP address
VTEP2 (config-if) #ip ospf cost 1	Change OSPF cost of the link
VTEP2 (config-if) #interface vlan1.50	Specify interface VLAN1.50 to be configured.
VTEP2 (config-if) #ip address 24.1.1.1/24	Assign IP address
VTEP2 (config-if) #interface ce53	Enter interface mode
VTEP2 (config-if) #switchport	Set the interface as Layer2 port
VTEP2 (config-if) #bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
VTEP2 (config-if) #switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
VTEP2 (config-if) #switchport trunk allowed vlan add 40,49	Enable VLAN's allowed on this interface.
VTEP2 (config-if) #switchport trunk native vlan 49	Configure native VLAN
VTEP2 (config-if) #load-interval 30	Configure load period in multiple of 30 seconds
VTEP2 (config-if) #spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
VTEP2 (config-if) #interface xe5	Enter interface mode
VTEP2 (config-if) #switchport	Set the interface as Layer2 port
VTEP2 (config-if) #bridge-group 1 spanningtree disable	Associate the interface with bridge group 1 and disable spanning tree
VTEP2 (config-if) #switchport mode trunk	Set the switching characteristics of this interface to trunk mode
VTEP2 (config-if) #switchport trunk allowed vlan add 10,19	Enable VLAN's allowed on this interface
VTEP2 (config-if) #switchport trunk native vlan 19	Configure native VLAN
VTEP2 (config-if) #load-interval 30	Configure load period in multiple of 30 seconds
VTEP2 (config-if) #spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
VTEP2 (config-if) #interface xe9	Enter interface mode
VTEP2 (config-if) #switchport	Set the interface as Layer2 port
VTEP2 (config-if) #bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
VTEP2 (config-if) #switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
VTEP2 (config-if) #switchport trunk allowed vlan add 50,59	Enable VLAN's allowed on this interface.
VTEP2 (config-if) #switchport trunk native vlan 59	Configure native VLAN
VTEP2 (config-if) #load-interval 30	Configure load period in multiple of 30 seconds
VTEP2 (config-if) #spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
VTEP2 (config-if) #interface xe41	Enter interface mode
VTEP2 (config-if) #channel-group 1 mode active	Map the interface to po1
VTEP2 (config-if) #interface xe42	Enter interface mode

VTEP2 (config-if) #channel-group 1 mode active	Map the interface to po1
VTEP2 (config-if) #interface xe47	Enter interface mode
VTEP2 (config-if) #switchport	Set the interface as Layer2 port
VTEP2 (config-if) #router ospf 1	Enter OSPF configuration mode
VTEP2 (config-router) #ospf router-id 2.2.2.2	Configure OSPF router id
VTEP2 (config-router) #network 2.2.2.2/32 area 0.0.0.0	Enable BFD in all ospf interfaces
VTEP2 (config-router) #network 12.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
VTEP2 (config-router) #network 23.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
VTEP2 (config-router) #network 24.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
VTEP2 (config-router) #network 25.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
VTEP2 (config-router) #router bgp 100	Enter Router BGP mode and define the AS number 100.
VTEP2 (config-router) #address-family ipv4 unicast	Enter address-family IPv4 unicast mode
VTEP2 (config-router) #network 2.2.2.2/32	Add the lo network to BGP route
VTEP2 (config-router-af) #neighbor 1.1.1.1 activate	Activate neighbors
VTEP2 (config-router-af) #neighbor 6.6.6.6 activate	Activate neighbors
VTEP2 (config-router-af) #exit-address-family	Exit address-family mode.
VTEP2 (config-router) #neighbor 1.1.1.1 remote-as 100	Configure BGP remote-as 100 with neighbor IP
(config-router) #neighbor 1.1.1.1 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP1
VTEP2 (config-router) #neighbor 1.1.1.1 update-source lo	Define BGP neighbors, to update the source routes with lo
VTEP2 (config-router) #neighbor 6.6.6.6 remote-as 100	Configure BGP remote-as 100 with neighbor IP
(config-router) #neighbor 6.6.6.6 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP3
VTEP2 (config-router) #neighbor 6.6.6.6 update-source lo	Define BGP neighbors, to update the source routes with lo
VTEP2 (config-router) #address-family l2vpn evpn	Enter in to BGP L2VPN EVPN address-family
VTEP2 (config-router-af) #neighbor 1.1.1.1 activate	Activate neighbors
VTEP2 (config-router-af) #neighbor 6.6.6.6 activate	Activate neighbors
VTEP2 (config-router-af) #exit-address-family	Exit from BGP L2VPN EVPN address-family
VTEP2 (config-router) #nvo vxlan vtep-ip-global 2.2.2.2	Configure VXLAN global IP
VTEP2 (config) #nvo vxlan id 1 ingress-replication inner-vid-disabled	Create VNID 1

VTEP2 (config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf1	Associate VNID with EVPN and vrf1
VTEP2 (config-nvo) #nvo vxlan id 1000 ingress-replication inner-vid-disabled	Create VNID 1000
VTEP2 (config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf2	Associate VNID with EVPN and vrf2
VTEP2 (config-nvo) #nvo vxlan access-if port xe47	Create VXLAN access port
VTEP2 (config-nvo-acc-if) #map vnid 1	Map the VNID to access-if
VTEP2 (config-nvo-acc-if) #nvo vxlan access-if port-vlan po1 2001	Create VXLAN access port
VTEP2 (config-nvo-acc-if) #map vnid 1000	Map the VNID to access-if
VTEP2 (config-nvo-acc-if) #nvo vxlan access-if port-vlan po1 2000	Create VXLAN access port
VTEP2 (config-nvo-acc-if) #map vnid 1000	Map the VNID to access-if
VTEP2 (config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration

P1

P1#configure terminal	Enter configuration terminal
P1(config)#hostname P1	Configure hostname
P1(config)#bfd interval 3 minrx 3 multiplier 3	Configure BFD interval globally
P1(config)#qos enable	Enable qos
P1(config)#bridge 1 protocol ieee vlan-bridge	Configure IEEE VLAN bridge
P1(config)#no bridge 1 spanning-tree enable	Disable spanning tree in bridge 1 globally
P1(config)#no igmp snooping	Disable igmp snooping messages globally
P1(config)#vlan database	Enter into the VLAN database
P1(config-vlan)#vlan 10-200 bridge 1 state enable	Configure VLAN 10-200 and associate with bridge 1
P1(config-if)#interface lo	Enter loopback interface mode
P1(config-if)#ip address 3.3.3.3/32 secondary	Assign loopback IP
P1(config-if)#interface vlan1.20	Specify interface VLAN1.20 to be configured.
P1(config-if)#ip address 13.1.1.2/24	Assign IP address
P1(config-if)#ip ospf cost 1	Change OSPF cost of the link
P1(config-if)#interface vlan1.40	Specify interface VLAN1.40 to be configured.
P1(config-if)#ip address 23.1.1.2/24	Assign IP address
P1(config-if)#interface vlan1.60	Specify interface VLAN1.60 to be configured.
P1(config-if)#ip address 35.1.1.1/24	Assign IP address
P1(config-if)#ip ospf cost 1	Change OSPF cost of the link
P1(config-if)#interface vlan1.100	Specify interface VLAN1.100 to be configured.
P1(config-if)#ip address 34.1.1.1/24	Assign IP address

P1(config-if)#ip ospf cost 1	Change OSPF cost of the link
P1(config-vlan)#interface ce49	Enter interface mode
P1(config-if)#switchport	Set the interface as Layer2 port
P1(config-if)#bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
P1(config-if)#switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
P1(config-if)#switchport trunk allowed vlan add 40,49	Enable VLAN's allowed on this interface.
P1(config-if)#switchport trunk native vlan 49	Configure native VLAN
P1(config-if)#load-interval 30	Configure load period in multiple of 30 seconds
P1(config-if)#spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
P1(config-if)#interface xe1	Enter interface mode
P1(config-if)#switchport	Set the interface as Layer2 port
P1(config-if)#bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
P1(config-if)#switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
P1(config-if)#switchport trunk allowed vlan add 20,29	Enable VLAN's allowed on this interface.
P1(config-if)#switchport trunk native vlan 29	Configure native VLAN
P1(config-if)#load-interval 30	Configure load period in multiple of 30 seconds
P1(config-if)#mtu 1600	Change the interface mtu value
P1(config-if)#spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
P1(config-if)#interface xe10	Enter interface mode
P1(config-if)#switchport	Set the interface as Layer2 port
P1(config-if)#bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
P1(config-if)#switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
P1(config-if)#switchport trunk allowed vlan add 60,69	Enable VLAN's allowed on this interface.
P1(config-if)#switchport trunk native vlan 69	Configure native VLAN
P1(config-if)#load-interval 30	Configure load period in multiple of 30 seconds
P1(config-if)#mtu 1600	Change the interface mtu value
P1(config-if)#spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
P1(config-if)#interface xe25	Enter interface mode
P1(config-if)#switchport	Set the interface as Layer2 port
P1(config-if)#bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
P1(config-if)#switchport mode trunk	Set the switching characteristics of this interface to trunk mode.

P1(config-if)#switchport trunk allowed vlan add 100,109	Enable VLAN's allowed on this interface.
P1(config-if)#switchport trunk native vlan 109	Configure native VLAN
P1(config-if)#load-interval 30	Configure load period in multiple of 30 seconds
P1(config-if)#spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
P1(config-if)#router ospf 1	Enter OSPF configuration mode
P1(config-router)#ospf router-id 3.3.3.3	Configure OSPF router id
P1(config-router)#bfd all-interfaces	Enable BFD in all OSPF interfaces
P1(config-router)#network 3.3.3.3/32 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P1(config-router)#network 10.10.10.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P1(config-router)#network 13.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P1(config-router)#network 23.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P1(config-router)#network 34.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P1(config-router)#network 35.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P1(config-router)#commit	Commit the candidate configuration to the running configuration

P2

P2#configure terminal	Enter configuration terminal
P2(config)#bfd interval 3 minrx 3 multiplier 3	Configure BFD interval globally
P2(config)#qos enable	Enable qos
P2(config)#hostname P2	Configure hostname
P2(config)#bridge 1 protocol ieee vlan-bridge	Configure IEEE VLAN bridge
P2(config)#no bridge 1 spanning-tree enable	Disable spanning tree in bridge 1 globally
P2(config)#no igmp snooping	Disable igmp snooping messages globally
P2(config)#vlan database	Enter into the VLAN database
P2(config-vlan)#vlan 10-200 bridge 1 state enable	Configure VLAN 10-200 and associate with bridge 1
P2(config-vlan)#interface lo	Enter lo interface mode
P2(config-if)#ip address 4.4.4.4/32 secondary	Assign loopback IP
P2(config-if)#interface vlan1.30	Specify interface VLAN1.30 to be configured.
P2(config-if)#ip address 14.1.1.2/24	Assign IP address
P2(config-if)#ip ospf cost 1	Change OSPF cost of the link
P2(config-if)#interface vlan1.50	Specify interface VLAN1.50 to be configured.
P2(config-if)#ip address 24.1.1.2/24	Assign IP address

P2(config-if)#interface vlan1.70	Specify interface VLAN1.70 to be configured.
P2(config-if)#ip address 45.1.1.1/24	Assign IP address
P2(config-if)#ip ospf cost 1	Change OSPF cost of the link
P2(config-if)#interface vlan1.90	Specify interface VLAN1.90 to be configured.
P2(config-if)#ip address 46.1.1.1/24	Assign IP address
P2(config-if)#ip ospf cost 1	Change OSPF cost of the link
P2(config-if)#interface vlan1.100	Specify interface VLAN1.100 to be configured.
P2(config-if)#ip address 34.1.1.2/24	Assign IP address
P2(config-if)#ip ospf cost 1	Change OSPF cost of the link
P2(config-if)#interface xe2	Enter interface mode
P2(config-if)#switchport	Set the interface as Layer2 port
P2(config-if)#bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
P2(config-if)#switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
P2(config-if)#switchport trunk allowed vlan add 70,79	Enable VLAN's allowed on this interface.
P2(config-if)#switchport trunk native vlan 79	Configure native VLAN
P2(config-if)#load-interval 30	Configure load period in multiple of 30 seconds
P2(config-if)#spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
P2(config-if)#interface xe3	Enter interface mode
P2(config-if)#switchport	Set the interface as Layer2 port
P2(config-if)#bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
P2(config-if)#switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
P2(config-if)#switchport trunk allowed vlan add 90,99	Enable VLAN's allowed on this interface.
P2(config-if)#switchport trunk native vlan 99	Configure native VLAN
P2(config-if)#load-interval 30	Configure load period in multiple of 30 seconds
P2(config-if)#spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
P2(config-if)#interface xe7	Enter interface mode
P2(config-if)#switchport	Set the interface as Layer2 port
P2(config-if)#bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
P2(config-if)#switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
P2(config-if)#switchport trunk allowed vlan add 30,39	Enable VLAN's allowed on this interface.
P2(config-if)#switchport trunk native vlan 39	Configure native VLAN
P2(config-if)#load-interval 30	Configure load period in multiple of 30 seconds
P2(config-if)#spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions

P2(config-if)#interface xe9	Enter interface mode
P2(config-if)#switchport	Set the interface as Layer2 port
P2(config-if)#bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
P2(config-if)#switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
P2(config-if)#switchport trunk allowed vlan add 50,59	Enable VLAN's allowed on this interface.
P2(config-if)#switchport trunk native vlan 59	Configure native VLAN
P2(config-if)#load-interval 30	Configure load period in multiple of 30 seconds
P2(config-if)#spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
P2(config-if)#interface xe25	Enter interface mode
P2(config-if)#switchport	Set the interface as Layer2 port
P2(config-if)#bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
P2(config-if)#switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
P2(config-if)#switchport trunk allowed vlan add 100,109	Enable VLAN's allowed on this interface.
P2(config-if)#switchport trunk native vlan 109	Configure native VLAN
P2(config-if)#load-interval 30	Configure load period in multiple of 30 seconds
P2(config-if)#spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
P2(config-if)#router ospf 1	Enter OSPF configuration mode
P2(config-router)#ospf router-id 4.4.4.4	Configure OSPF router id
P2(config-router)#bfd all-interfaces	Enable BFD in all OSPF interfaces
P2(config-router)#network 4.4.4.4/32 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P2(config-router)#network 14.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P2(config-router)#network 24.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P2(config-router)#network 34.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P2(config-router)#network 45.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P2(config-router)#network 46.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P2(config-router)#commit	Commit the candidate configuration to the running configuration

P3

P3(config)#hostname P3	Configure hostname
P3(config)#bfd interval 3 minrx 3 multiplier 3	Configure BFD interval globally

P3(config)#qos enable	Enable qos
P3(config)#bridge 1 protocol ieee vlan-bridge	Configure IEEE VLAN bridge
P3(config)#no bridge 1 spanning-tree enable	Disable spanning tree in bridge 1 globally
P3(config)#no igmp snooping	Disable igmp snooping messages globally
P3(config)#vlan database	Enter into the VLAN database
P3(config-vlan)#vlan 10-200 bridge 1 state enable	Configure VLAN 10-200 and associate with bridge 1
P3(config-vlan)#interface lo	Enter lo interface mode
P3(config-if)#ip address 5.5.5.5/32 secondary	Assign loopback IP
P3(config-if)#interface vlan1.60	Specify interface VLAN1.60 to be configured.
P3(config-if)#ip address 35.1.1.2/24	Assign IP address
P3(config-if)#ip ospf cost 1	Change OSPF cost of the link
P3(config-if)#interface vlan1.70	Specify interface VLAN1.70 to be configured.
P3(config-if)#ip address 45.1.1.2/24	Assign IP address
P3(config-if)#ip ospf cost 1	Change OSPF cost of the link
P3(config-if)#interface vlan1.80	Specify interface VLAN1.80 to be configured.
P3(config-if)#ip address 56.1.1.1/24	Assign IP address
P3(config-if)#ip ospf cost 1	Change OSPF cost of the link
P3(config-if)#interface vlan1.110	Specify interface VLAN1.110 to be configured.
P3(config-if)#ip address 15.1.1.2/24	Assign IP address
P3(config-if)#ip ospf cost 1	Change OSPF cost of the link
P3(config-if)#interface vlan1.160	Specify interface VLAN1.160 to be configured.
P3(config-if)#ip address 25.1.1.2/24	Assign IP address
P3(config-if)#ip ospf cost 1	Change OSPF cost of the link
P3(config-if)#interface xe2	Enter interface mode
P3(config-if)#switchport	Set the interface as Layer2 port
P3(config-if)#bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
P3(config-if)#switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
P3(config-if)#switchport trunk allowed vlan add 70,79	Enable VLAN's allowed on this interface.
P3(config-if)#switchport trunk native vlan 79	Configure native VLAN
P3(config-if)#load-interval 30	Configure load period in multiple of 30 seconds
P3(config-if)#spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
P3(config-if)#interface xe10	Enter interface mode
P3(config-if)#switchport	Set the interface as Layer2 port
P3(config-if)#bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
P3(config-if)#switchport mode trunk	Set the switching characteristics of this interface to trunk mode.

P3(config-if)#switchport trunk allowed vlan add 60,69	Enable VLAN's allowed on this interface.
P3(config-if)#switchport trunk native vlan 69	Configure native VLAN
P3(config-if)#load-interval 30	Configure load period in multiple of 30 seconds
P3(config-if)#mtu 1600	Change interface mtu value
P3(config-if)#spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
P3(config-if)#interface xe15	Enter interface mode
P3(config-if)#switchport	Set the interface as Layer2 port
P3(config-if)#bridge-group 1 spanning-tree disable	Associate the interface with bridge group 1 and disable spanning tree
P3(config-if)#switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
P3(config-if)#switchport trunk allowed vlan add 80,89	Enable VLAN's allowed on this interface.
P3(config-if)#switchport trunk native vlan 89	Configure native VLAN
P3(config-if)#load-interval 30	Configure load period in multiple of 30 seconds
P3(config-if)#mtu 1600	Change interface mtu value
P3(config-if)#spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
P3(config-if)#router ospf 1	Enter OSPF configuration mode
P3(config-router)#ospf router-id 5.5.5.5	Configure OSPF router id
P3(config-router)#bfd all-interfaces	Enable BFD in all ospf interfaces
P3(config-router)#network 5.5.5.5/32 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P3(config-router)#network 15.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P3(config-router)#network 25.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P3(config-router)#network 35.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P3(config-router)#network 45.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P3(config-router)#network 56.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
P3(config-router)#commit	Commit the candidate configuration to the running configuration

VTEP3

VTEP3#configure terminal	Enter configuration terminal
VTEP3(config)#hostname VTEP3	Configure hostname
VTEP3(config)#mac vrf vrf1	Configure MAC vrf vrf1
VTEP3(config-vrf)#rd 6.6.6.6:11	Configure RD for vrf1
VTEP3(config-vrf)#route-target both 10.10.10.10:100	Configure RT for vrf1

VTEP3 (config-vrf) #mac vrf vrf2	Configure MAC vrf vrf2
VTEP3 (config-vrf) #rd 6.6.6.6:12	Configure RD for vrf2
VTEP3 (config-vrf) #route-target both 10.10.10.10:101	Configure RT for vrf2
VTEP3 (config-vrf) #route-target both 10.10.10.10:102	Configure RT for vrf2
VTEP3 (config-vrf) #bfd interval 3 minrx 3 multiplier 3	Enable EVPN VXLAN multihoming
VTEP3 (config) #evpn vxlan multihoming enable	Enable statistics on VXLAN tunnel interface
VTEP3 (config) #nvo vxlan enable	Enable VXLAN
VTEP3 (config) #qos enable	Enable qos
VTEP3 (config) #qos statistics	Enable qos statistics
VTEP3 (config) #bridge 1 protocol ieee vlan- bridge	Configure IEEE VLAN bridge
VTEP3 (config) #no bridge 1 spanning-tree enable	Disable spanning tree in bridge 1 globally
VTEP3 (config) #no igmp snooping	Disable igmp snooping messages globally
VTEP3 (config) #vlan database	Enter into the VLAN database
VTEP3 (config-vlan) #vlan 10-200 bridge 1 state enable	Configure VLAN 10-200 and associate with bridge 1
VTEP3 (config-vlan) #interface lo	Enter lo interface mode
VTEP3 (config-if) #ip address 6.6.6.6/32 secondary	Assign loopback IP
VTEP3 (config-if) #interface vlan1.80	Specify interface VLAN1.80 to be configured.
VTEP3 (config-if) #ip address 56.1.1.2/24	Assign IP address
VTEP3 (config-if) #ip ospf cost 1	Change OSPF cost of the link
VTEP3 (config-if) #interface vlan1.90	Specify interface VLAN1.90 to be configured.
VTEP3 (config-if) #ip address 46.1.1.2/24	Assign IP address
VTEP3 (config-if) #ip ospf cost 1	Change OSPF cost of the link
VTEP3 (config-if) #interface xe3	Enter interface mode
VTEP3 (config-if) #switchport	Set the interface as Layer2 port
VTEP3 (config-if) #bridge-group 1 spanning- tree disable	Associate the interface with bridge group 1 and disable spanning tree
VTEP3 (config-if) #switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
VTEP3 (config-if) #switchport trunk allowed vlan add 90,99	Enable VLAN's allowed on this interface.
VTEP3 (config-if) #switchport trunk native vlan 99	Configure native VLAN
VTEP3 (config-if) #load-interval 30	Configure load period in multiple of 30 seconds
VTEP3 (config-if) #spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
VTEP3 (config-if) #interface xe15	Enter interface mode
VTEP3 (config-if) #switchport	Set the interface as Layer2 port
VTEP3 (config-if) #bridge-group 1 spanning- tree disable	Associate the interface with bridge group 1 and disable spanning tree

VTEP3 (config-if) #switchport mode trunk	Set the switching characteristics of this interface to trunk mode.
VTEP3 (config-if) #switchport trunk allowed vlan add 80,89	Enable VLAN's allowed on this interface.
VTEP3 (config-if) #switchport trunk native vlan 89	Configure native VLAN
VTEP3 (config-if) #load-interval 30	Configure load period in multiple of 30 seconds
VTEP3 (config-if) #mtu 1600	Change interface mtu value
VTEP3 (config-if) #spanning-tree edgeport	Set the port as an edge-port to enable rapid transitions
VTEP3 (config-if) #interface xe45	Enter interface mode
VTEP3 (config-if) #switchport	Set the interface as Layer2 port
VTEP3 (config-if) #load-interval 30	Configure load period in multiple of 30 seconds
VTEP3 (config-if) #interface xe46	Enter interface mode
VTEP3 (config-if) #switchport	Set the interface as Layer2 port
VTEP3 (config-if) #load-interval 30	Configure load period in multiple of 30 seconds
VTEP3 (config-if) #router ospf 1	Enter OSPF configuration mode
VTEP3 (config-router) #ospf router-id 6.6.6.6	Configure OSPF router id
VTEP3 (config-router) #bfd all-interfaces	Enable BFD in all OSPF interfaces
VTEP3 (config-router) #network 6.6.6.6/32 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
VTEP3 (config-router) #network 46.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
VTEP3 (config-router) #network 56.1.1.0/24 area 0.0.0.0	Define the Network on which OSPF runs and associate the area ID (area 0) with the interface.
VTEP3 (config-router) #router bgp 100	Enter address-family IPv4 unicast mode
VTEP3 (config-router) #address-family ipv4 unicast	Add the lo network to BGP route
VTEP3 (config-router) #network 6.6.6.6/32	Activate neighbors
VTEP3 (config-router-af) #neighbor 1.1.1.1 activate	Activate neighbors
VTEP3 (config-router-af) #neighbor 2.2.2.2 activate	Exit address-family mode.
VTEP3 (config-router-af) #exit-address-family	Enter Router BGP mode and define the AS number 100.
VTEP3 (config-router) #neighbor 1.1.1.1 remote-as 100	Configure BGP remote-as 100 with neighbor IP
VTEP3 (config-router) #neighbor 1.1.1.1 update-source lo	Define BGP neighbors, to update the source routes with lo
VTEP3 (config-router) #neighbor 2.2.2.2 remote-as 100	Configure BGP remote-as 100 with neighbor IP
VTEP3 (config-router) #neighbor 2.2.2.2 update-source lo	Configure advertisement-interval as 0 for fast convergence for VTEP2
(config-router) #neighbor 2.2.2.2 advertisement-interval 0	Configure advertisement-interval as 0 for fast convergence for VTEP1
(config-router) #neighbor 1.1.1.1 advertisement-interval 0	Define BGP neighbors, to update the source routes with lo
VTEP3 (config-router) #address-family 12vpn evpn	Enter in to BGP L2VPN EVPN address-family

VTEP3 (config-router-af) #neighbor 1.1.1.1 activate	Activate neighbors
VTEP3 (config-router-af) #neighbor 2.2.2.2 activate	Activate neighbors
VTEP3 (config-router-af) #exit-address-family	Exit from BGP L2VPN EVPN address-family
VTEP3 (config-router) #nvo vxlan vtep-ip-global 6.6.6.6	Configure VXLAN global IP
VTEP3 (config) #nvo vxlan id 1 ingress-replication inner-vid-disabled	Create VNID 1
VTEP3 (config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf1	Associate VNID with EVPN and vrf1
VTEP3 (config-nvo) #nvo vxlan id 1000 ingress-replication inner-vid-disabled	Create VNID 1000
VTEP3 (config-nvo) #vxlan host-reachability-protocol evpn-bgp vrf2	Associate VNID with EVPN and vrf2
VTEP3 (config-nvo) #nvo vxlan access-if port-vlan xe45 3001	Create VXLAN access port port-VLAN
VTEP3 (config-nvo-acc-if) #map vnid 1	Map the VNID to access-if
VTEP3 (config-nvo-acc-if) #nvo vxlan access-if port xe46	Create VXLAN access port
VTEP3 (config-nvo-acc-if) #map vnid 1000	Map the VNID to access-if
VTEP3 (config-nvo-acc-if) #commit	Commit the candidate configuration to the running configuration

SWITCH

SWITCH#configure terminal	Enter configuration terminal
SWITCH#(config) # bridge 1 protocol rstp vlan-bridge	Configure rstp vlan bridge
SWITCH#(config-vlan) #interface po1	Enter interface mode
SWITCH#(config-if) #switchport	Set the interface as Layer2 port
SWITCH#(config-if) #load-interval 30	Configure load period in multiple of 30 seconds
SWITCH#(config-if) #interface ce9/1	Enter interface mode
SWITCH#(config-if) #channel-group 1 mode active	Map this interface to po1
SWITCH#(config-if) #interface ce9/2	Enter interface mode
SWITCH#(config-if) #channel-group 1 mode active	Map this interface to po1
SWITCH#(config-if) #interface ce10/1	Enter interface mode
SWITCH#(config-if) #channel-group 1 mode active	Map this interface to po1
SWITCH#(config-if) #interface ce10/2	Enter interface mode
SWITCH#(config-if) #channel-group 1 mode active	Map this interface to po1
SWITCH#(config-if) #interface ce31/1	Set the port as an edge-port to enable rapid transitions
SWITCH#(config-if) #switchport	Enter interface mode

SWITCH#(config-if)#bridge-group 1 spanning-tree disable	Set the interface as Layer2 port
SWITCH#(config-if)#switchport mode trunk	Associate the interface with bridge group 1 and disable spanning tree
SWITCH#(config-if)#switchport trunk allowed vlan all	Set the switching characteristics of this interface to trunk mode.
SWITCH#(config-if)#load-interval 30	Configure native VLAN
SWITCH#(config-if)#commit	Commit the candidate configuration to the running configuration

Validation

VTEP1#sh ip ospf neighbor

Total number of full neighbors: 3

OSPF process 1 VRF(default):

Neighbor ID Instance ID	Pri	State	Dead Time	Address	Interface	
2.2.2.2 0	1	Full/DR	00:00:30	12.1.1.2	vlan1.10	0
3.3.3.3 0	1	Full/DR	00:00:31	13.1.1.2	vlan1.20	0
4.4.4.4 0	1	Full/DR	00:00:33	14.1.1.2	vlan1.30	0

VTEP2#sh ip ospf neighbor

Total number of full neighbors: 3

OSPF process 1 VRF(default):

Neighbor ID Instance ID	Pri	State	Dead Time	Address	Interface	
1.1.1.1 0	1	Full/Backup	00:00:38	12.1.1.1	vlan1.10	
3.3.3.3 0	1	Full/DR	00:00:39	23.1.1.2	vlan1.40	0
4.4.4.4 0	1	Full/DR	00:00:39	24.1.1.2	vlan1.50	0

P1#sh ip ospf neighbor

Total number of full neighbors: 4

OSPF process 1 VRF(default):

Neighbor ID Instance ID	Pri	State	Dead Time	Address	Interface	
1.1.1.1 0	1	Full/Backup	00:00:39	13.1.1.1	vlan1.20	
2.2.2.2 0	1	Full/Backup	00:00:38	23.1.1.1	vlan1.40	
4.4.4.4 0	1	Full/DR	00:00:40	34.1.1.2	vlan1.100	0
5.5.5.5 0	1	Full/DR	00:00:36	35.1.1.2	vlan1.60	0

P2#sh ip ospf neighbor

Total number of full neighbors: 5

OSPF process 1 VRF(default):

Neighbor ID Instance ID	Pri	State		Dead Time	Address	Interface
1.1.1.1 0	1	Full/Backup		00:00:30	14.1.1.1	vlan1.30
2.2.2.2 0	1	Full/Backup		00:00:38	24.1.1.1	vlan1.50
3.3.3.3 0	1	Full/Backup		00:00:33	34.1.1.1	vlan1.100
5.5.5.5	1	Full/DR		00:00:30	45.1.1.2	vlan1.70
6.6.6.6	1	Full/DR		00:00:34	46.1.1.2	vlan1.90

P2#

P3#sh ip ospf neighbor

Total number of full neighbors: 3

OSPF process 1 VRF(default):

Neighbor ID Instance ID	Pri	State		Dead Time	Address	Interface
3.3.3.3 0	1	Full/Backup		00:00:34	35.1.1.1	vlan1.60
4.4.4.4 0	1	Full/Backup		00:00:34	45.1.1.1	vlan1.70
6.6.6.6	1	Full/DR		00:00:33	56.1.1.2	vlan1.80

P3#

VTEP1#sh bgp 12vpn evpn summary

BGP router identifier 1.1.1.1, local AS number 100

BGP table version is 4

1 BGP AS-PATH entries

0 BGP community entries

Neighbor PfxRcd	AD	MACIP	V MCAST	AS ESI	MsgRcv PREFIX-ROUTE	MsgSen	TblVer	InQ	OutQ	Up/Down	State/
2.2.2.2 2 0	0	2	4 2	100 0	23 0	22	4	0	0	00:07:34	
6.6.6.6 2 0	0	2	4 2	100 0	21 0	22	4	0	0	00:07:34	

Total number of neighbors 2

Total number of Established sessions 2

VTEP1#

VTEP2#sh bgp 12vpn evpn summary

BGP router identifier 2.2.2.2, local AS number 100

BGP table version is 5

1 BGP AS-PATH entries

0 BGP community entries

Neighbor PfxRcd	AD	MACIP	V MCAST	AS ESI	MsgRcv PREFIX-ROUTE	MsgSen	TblVer	InQ	OutQ	Up/Down	State/
1.1.1.1 2 0	0	2	4 2	100 0	22 0	24	5	0	0	00:07:41	
6.6.6.6 2 0	0	2	4 2	100 0	24 0	27	5	0	0	00:08:51	

Total number of neighbors 2

Total number of Established sessions 2

VTEP2#

```
VTEP3#sh bgp l2vpn evpn summary
BGP router identifier 6.6.6.6, local AS number 100
BGP table version is 5
 1 BGP AS-PATH entries
 0 BGP community entries
```

Neighbor PfxRcd	AD	MACIP	V MCAST	AS ESI	MsgRcv PREFIX-ROUTE	MsgSen	TblVer	InQ	OutQ	Up/Down	State/
1.1.1.1 2	0	0	4 2	100 0	23 0	21	5	0	0	00:07:44	
2.2.2.2 2	0	0	4 2	100 0	26 0	24	5	0	0	00:08:54	

Total number of neighbors 2

Total number of Established sessions 2

VTEP3#

VTEP1#show nvo vxlan mac-table

VXLAN MAC Entries						
VNID Type	Interface Status	VlanId Inner-VlanId	Mac-Addr AccessPortDesc	VTEP-Ip/ESI		
1 Static Local	pol	1000 -----	0000.1111.1111 00:aa:22:33:44:55:66:00:00:00			
1 Static Local	pol	1000 -----	0000.1111.1112 00:aa:22:33:44:55:66:00:00:00			
1 Static Local	pol	1000 -----	0000.1111.1113 00:aa:22:33:44:55:66:00:00:00			
1 Static Local	pol	1000 -----	0000.1111.1114 00:aa:22:33:44:55:66:00:00:00			
1 Static Local	pol	1000 -----	0000.1111.1115 00:aa:22:33:44:55:66:00:00:00			
1 Dynamic Local	pol	1000 -----	a82b.b57c.4470 00:aa:22:33:44:55:66:00:00:00			
1000 Dynamic Remote	----	---- ----	a82b.b57c.4476 00:aa:22:33:44:55:66:00:00:00			

Total number of entries are : 7

VTEP1#

VTEP2#sh nvo vxlan mac-table

VXLAN MAC Entries						
VNID	Type	Interface	VlanId	Inner-VlanId	Mac-Addr	VTEP-Ip/ESI
				Status	AccessPortDesc	
1	---	---	---	---	0000.1111.1111	00:aa:22:33:44:55:66:00:00:00
Static	Remote	---	---	---	-----	-----
1	---	---	---	---	0000.1111.1112	00:aa:22:33:44:55:66:00:00:00
Static	Remote	---	---	---	-----	-----
1	---	---	---	---	0000.1111.1113	00:aa:22:33:44:55:66:00:00:00
Static	Remote	---	---	---	-----	-----
1	---	---	---	---	0000.1111.1114	00:aa:22:33:44:55:66:00:00:00
Static	Remote	---	---	---	-----	-----
1	---	---	---	---	0000.1111.1115	00:aa:22:33:44:55:66:00:00:00
Static	Remote	---	---	---	-----	-----
1	---	---	---	---	a82b.b57c.4470	00:aa:22:33:44:55:66:00:00:00
Dynamic	Remote	---	---	---	-----	-----
1000	pol	2000	---	---	a82b.b57c.4476	00:aa:22:33:44:55:66:00:00:00
Dynamic	Local	---	---	---	-----	-----

Total number of entries are : 7

VTEP2#

VTEP3#sh nvo vxlan mac-table

VXLAN MAC Entries						
VNID	Type	Interface	VlanId	Inner-VlanId	Mac-Addr	VTEP-Ip/ESI
				Status	AccessPortDesc	
1	---	---	---	---	0000.1111.1111	00:aa:22:33:44:55:66:00:00:00
Static	Remote	---	---	---	-----	-----
1	---	---	---	---	0000.1111.1112	00:aa:22:33:44:55:66:00:00:00
Static	Remote	---	---	---	-----	-----
1	---	---	---	---	0000.1111.1113	00:aa:22:33:44:55:66:00:00:00
Static	Remote	---	---	---	-----	-----
1	---	---	---	---	0000.1111.1114	00:aa:22:33:44:55:66:00:00:00
Static	Remote	---	---	---	-----	-----
1	---	---	---	---	0000.1111.1115	00:aa:22:33:44:55:66:00:00:00
Static	Remote	---	---	---	-----	-----
1	---	---	---	---	a82b.b57c.4470	00:aa:22:33:44:55:66:00:00:00
Dynamic	Remote	---	---	---	-----	-----
1000	---	---	---	---	a82b.b57c.4476	00:aa:22:33:44:55:66:00:00:00
Dynamic	Remote	---	---	---	-----	-----

Total number of entries are : 7

VTEP3#
VTEP1#show nvo vxlan access-if brief

Interface	Vlan	Inner			Admin status	Link status
		vlan	Ifindex	Vnid		
xe46	---	---	500000	1	up	up
pol	2000	---	500001	1000	up	up
pol	2001	---	500002	1000	up	up

Total number of entries are 2

VTEP1#
VTEP2#show nvo vxlan access-if brief

Interface	Vlan	Inner			Admin status	Link status
		vlan	Ifindex	Vnid		
xe47	---	---	500000	1	up	up
pol	2001	---	500001	1000	up	up
pol	2000	---	500002	1000	up	up

Total number of entries are 3

VTEP2#
VTEP3#show nvo vxlan access-if brief

Interface	Vlan	Inner			Admin status	Link status
		vlan	Ifindex	Vnid		
xe45	3001	---	500000	1	up	up
xe46	---	---	500001	1000	up	up

Total number of entries are 2

VTEP3#
VTEP1#sh nvo vxlan tunnel
VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
1.1.1.1	6.6.6.6	Installed	00:03:59	00:03:59
1.1.1.1	2.2.2.2	Installed	00:03:59	00:03:59

Total number of entries are 2

VTEP1#sh nvo vxlan
VXLAN Information

Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-
Status	Src-Addr			Dst-Addr			
1	---	L2	NW	---	---	---	---
--	1.1.1.1		6.6.6.6				
1	---	L2	NW	---	---	---	---
--	1.1.1.1		2.2.2.2				
1000	----	--	AC	pol	--- 00:aa:22:33:44:55:66:00:00:00 2000 DF		
----		---					
1000	----	--	AC	pol	--- 00:aa:22:33:44:55:66:00:00:00 2001 DF		
----		---					
1000	----	L2	NW	---	---	---	---
---	1.1.1.1		6.6.6.6				
1000	----	L2	NW	---	---	---	---
---	1.1.1.1		2.2.2.2				
1000	----	--	AC	xe46	--- Single Homed Port ---	---	---
---	----	---					

Total number of entries are 10

VTEP1#

VTEP2#sh nvo vxlan tunnel

VXLAN Network tunnel Entries

Source	Destination	Status	Up/Down	Update
2.2.2.2	1.1.1.1	Installed	00:03:59	00:03:59
2.2.2.2	6.6.6.6	Installed	00:05:09	00:05:09

Total number of entries are 2

VTEP2#sh nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port
AC - Access Port
(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-
Status	Src-Addr			Dst-Addr			
1	---	L2	NW	---	---	---	---
--	2.2.2.2		1.1.1.1				
1	---	L2	NW	---	---	---	---
--	2.2.2.2		6.6.6.6				
1	----	--	AC	xe47	--- Single Homed Port ---	---	---
--	----	---					
1000	----	L2	NW	---	---	---	---
--	2.2.2.2		1.1.1.1				
1000	----	L2	NW	---	---	---	---
--	2.2.2.2		6.6.6.6				
1000	----	--	AC	pol	--- 00:aa:22:33:44:55:66:00:00:00 2001 NON-DF		
DF	----	---					

```
1000      ----      --      AC      po1      --- 00:aa:22:33:44:55:66:00:00:00 2000 NON-
DF      ----
```

Total number of entries are 11
VTEP2#

```
VTEP3#sh nvo vxlan tunnel
VXLAN Network tunnel Entries
Source          Destination        Status        Up/Down        Update
=====
6.6.6.6          1.1.1.1        Installed      00:03:58      00:03:58
6.6.6.6          2.2.2.2        Installed      00:05:08      00:04:03
```

Total number of entries are 2

VTEP3#sh nvo vxlan

VXLAN Information

=====

Codes: NW - Network Port

AC - Access Port

(u) - Untagged

VNID	VNI-Name	VNI-Type	Type	Interface	ESI	VLAN	DF-Status
Src-Addr			Dst-Addr				
1	----	L2	NW	----	----	----	----
6.6.6.6		1.1.1.1					
1	----	L2	NW	----	----	----	----
6.6.6.6		2.2.2.2					
1	----	--	AC	xe45	--- Single Homed port ---	3001	----
---		----					
1000	----	L2	NW	----	----	----	----
6.6.6.6		1.1.1.1					
1000	----	L2	NW	----	----	----	----
6.6.6.6		2.2.2.2					
1000	----	--	AC	xe46	--- Single Homed Port ---	----	----
---		----					

Total number of entries are 10

VTEP3#

VxLAN Command Reference

CHAPTER 1 VXLAN Commands

This chapter describes the VXLAN commands:

- access-if-vxlan
- arp-cache disable
- arp-nd flood-suppress
- arp-nd refresh timer
- clear mac address table dynamic vxlan
- clear nvo vxlan counters
- clear nvo vxlan tunnels
- clear nvo vxlan mac-stale-entries
- description
- dynamic-learning disable
- encapsulation
- evpn esi holdtime
- evpn etree
- evpn vxlan multi-homing enable
- evpn multi-homed
- evpn-vlan-service
- garp-gna enable
- load-balance rtag7 vxlan inner-l2
- load-balance rtag7 vxlan inner-l3
- mac
- mac vrf
- mac-holdtime
- map vnid
- nd-cache disable
- no nvo vxlan
- nvo vxlan
- nvo vxlan id
- nvo vxlan access-if
- nvo vxlan mac-ageing-time
- nvo vxlan max-cache-disable
- nvo vxlan vtep-ip-global
- show nvo vxlan
- show nvo vxlan access-if-config

- [show nvo vxlan arp-cache](#)
- [show nvo vxlan counters access-port](#)
- [show nvo vxlan counters network-port](#)
- [show nvo vxlan mac-table](#)
- [show nvo vxlan nd-cache](#)
- [show nvo vxlan static host state](#)
- [show nvo vxlan tunnel](#)
- [show nvo vxlan VxLAN vlan-vnid](#)
- [show running-config nvo vxlan](#)
- [show evpn multi-homing all](#)
- [show evpn multihoming-status](#)
- [show nvo vxlan route-count](#)
- [show nvo vxlan vni-name](#)
- [shutdown](#)
- [vxlan host-reachability-protocol evpn-bgp](#)
- [vlan-xlate-1 large](#)

arp-cache disable

Use this command to disable the ARP cache for MAC/IP.

When the ARP cache is disabled on a VxLAN access port, OcNOS does not reply to any ARP arriving on this port from the cache. OcNOS withdraws all MAC/IPs configured/learned on this access port and removes the MAC/IP entry for this access port from the local ARP cache.

OcNOS also makes sure that on withdrawing the MAC/IP route, the MAC does not become unknown. If all routes for this MAC are being withdrawn because of this command, then OcNOS advertises a MAC-only route. This is done so that the MAC does not become unknown and only the cache functionality becomes disabled.

Use the `no` form of this command to enable ARP cache for MAC/IP.

Note: On enabling the cache, an IP will be in conflict, then the cache enable will fail. The conflict has to be manually removed and then the cache enabled.

Command Syntax

```
arp-cache disable  
no arp-cache disable
```

Parameters

None

Default

By default, the arp-cache option is enabled.

Command Mode

NVO access interface mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal  
(config)#nvo vxlan access-if port-vlan xe1 2  
(config-nvo-acc-if)#arp-cache disable  
(config-nvo-acc-if)#exit
```

arp-nd flood-suppress

Use this command to *completely* restrict the flood of ARP/ND packets towards remote VTEPs or other access ports.

This command applies only when the ARP cache and ND cache are enabled. When the ARP cache is disabled, ARP flooding is not suppressed even if this command is given. When the ND cache is disabled, ND flooding is not disabled, even if this command is given.

Use the `no` form of this command to not restrict the flood of ARP/ND packets.

Command Syntax

```
arp-nd flood-suppress  
no arp-nd flood-suppress
```

Parameters

None

Default

By default, the arp-nd flood-suppress option is disabled.

Command Mode

NVO access interface mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal  
(config)#nvo vxlan access-if port-vlan xe1 2  
(config-nvo-acc-if)#arp-nd flood-suppress  
(config-nvo-acc-if)#exit
```

arp-nd refresh timer

Use this command to configure aging out the arp-cache and nd-cache entries for given time multiplied by 3 in secs

Use the no form of this command to remove the configuration.

Command Syntax

```
nvo vxlan arp-nd refresh-timer <3-190> mac (XX-XX-XX-XX-XX-  
XX|XX:XX:XX:XX:XX|XXXX.XXXX.XXXX)  
no nvo vxlan arp-nd refresh-timer
```

Parameters

<3-190> refresh time in seconds
XX-XX-XX-XX-XX-XX
v-mac is mandatory for MH

Command Mode

Config mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#config mode  
(config)#nvo vxlan arp-nd refresh-timer 100  
(config)#no nvo vxlan arp-nd refresh-timer
```

Example to configure in MH node

```
(config)#nvo vxlan arp-nd refresh-timer 100 mac 0000.1111.2222
```

clear mac address table dynamic vxlan

Use this command to clear dynamically learned MACs.

Command Syntax

```
clear mac address table dynamic vxlan
```

Parameters

None

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#clear mac address table dynamic vxlan
```

clear nvo vxlan counters

Use this command to clear the counters of access ports or network ports.

Command Syntax

```
clear nvo vxlan counters((access-port (port IFNAME | port-vlan IFNAME (VLAN_ID |
outer-vlan) | all)) | (network-port (dst A.B.C.D | all)))
```

Parameters

port	Port
IFNAME	Interface name
port-vlan	VLAN port
IFNAME	Interface name
VLAN_ID	VLAN identifier
Outer-vlan	Outer Vlan
A.B.C.D	Tunnel destination IPv4 address
all	All access or network ports

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

Example for clearing a VLAN port counter:

```
#clear nvo vxlan counters access-port port-vlan xe1 2
```

Example for clearing all access port counters:

```
#clear nvo vxlan counters access-port all
```

Example for clearing network port counters:

```
#clear nvo vxlan counters network-port dst 1.1.1.1
```

Example for clearing all network port counters:

```
#clear nvo vxlan counters network-port all
```

clear nvo vxlan tunnels

Use this command to clear the nvo vxlan tunnels to re-establish the tunnel after mapping/un-mapping the QoS profile to vxlan tunnel.

Command Syntax

```
clear nvo vxlan tunnels (|dst-ip A.B.C.D)
```

Parameters

dst-ip	VXLAN tunnel destination
A.B.C.D	destination IPv4 address

Command Mode

Exec mode

Applicability

This command was introduced in OcNOS version 3.0.

Example

```
#clear nvo vxlan tunnels dst-ip 2.2.2.2
```

Note: `clear nvo vxlan tunnels` This command will clear all the VXLAN tunnels destination.

`clear nvo vxlan tunnels dst-ip A.B.C.D` – This command to clear individual tunnel destination(i.e A.B.C.D).

clear nvo vxlan mac-stale-entries

Use this command to clear MAC entries that are in discard state in the forwarding database.

Command Syntax

```
clear nvo vxlan mac-stale-entries (vnid <1-16777215> |)
```

Parameters

<1-16777215> VXLAN network identifier

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#clear nvo vxlan mac-stale-entries vnid 100
```

description

Use this command to set a description for a port.

Use the `no` form of this command to remove the description for a port.

Command Syntax

```
description LINE  
no description
```

Parameters

LINE	Maximum 32 characters describing this port.
------	---

Default

No default value is specified for description LINE commands.

Command Mode

NVO access interface mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal  
(config)#nvo vxlan access-if port-vlan xe1 2  
(config-nvo-acc-if)#description member-port xe1 with vlan 2  
(config-nvo-acc-if)#exit
```

dynamic-learning disable

Use this command to disable dynamic learning of MACs at the access port. This command also disables dynamic learning of MAC/IP from ARP/ND messages received on this access port.

Use the `no` form of this command to enable dynamic learning of MACs at the access port.

Command Syntax

```
dynamic-learning disable  
no dynamic-learning disable
```

Parameters

None

Default

By default, the dynamic-learning option is enabled.

Command Mode

NVO access interface mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal  
(config)#nvo vxlan access-if port-vlan xe1 2  
(config-nvo-acc-if)#dynamic-learning disable  
(config-nvo-acc-if)#exit
```

encapsulation

Use this command to assign a Tag Protocol Identifier (TPID) to an access port.

Use the `no` form of this command to set the default TPID (0x8100: IEEE 802.1Q VLAN-tagged frame) to an access port.

Command Syntax

```
encapsulation TPID  
no encapsulation
```

Parameters

TPID	Tag Protocol Identifier: 0x88A8: IEEE 802.1ad Provider Bridging 0x9100: IEEE 802.1Q VLAN-tagged frame with double tagging
------	---

Default

The encapsulation TPID default is 0X8100.

Command Mode

NVO access interface mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal  
(config)#nvo vxlan access-if port-vlan xe1 2  
(config-nvo-acc-if)#encapsulation 0x9100  
(config-nvo-acc-if)#exit
```

evpn esi holdtime

Use this command to allow some time for the tunnels to come up at the time of vxlan initialization before making the esi up. This avoids traffic to be black-holed when a new PE is added and connected to an already running CE for multi-homing.

Use the no form of this command to make the esi up immediately when configuring the access-if cli.

Command Syntax

```
evpn esi holdtime <10-300>
no evpn esi holdtime <10-300>
```

Parameters

<10-300>	Hold time in seconds
----------	----------------------

Default

Default value is 0.

Command Mode

Configuration Mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal
(config)# evpn esi holdtime 100
(config)# exit
```

evpn vxlan multi-homing enable

Use this command to enable evpn vxlan multi-homing

Use the no form of this command to disable evpn vxlan multi-homing.

Note: Node will have to be restarted for this to be applicable. If there are some nodes in topology which have multi-homed CEs, then nodes which do not have multi-homed CEs should also enable multihoming so, that they can load share traffic to the multi-homed CEs.

Command Syntax

```
evpn vxlan multihoming enable  
no evpn vxlan multihoming enable
```

Parameters

None

Default

By Default Multi-homing will be disabled

Command Mode

Configuration Mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal  
#(config)# evpn vxlan multihoming enable  
#(config)# exit
```

evpn multi-homed

Use this command to configure interfaces as multi-homed and configure esi-value in case of physical and static lag and system-mac in case of Dynamic lag.

Use the no parameter of this command to unconfigure multi-homed on the interface.

Command Syntax

```
evpn multi-homed (esi XX:XX:XX:XX:XX:XX:XX:XX:XX:XX | system-mac (XX-XX-XX-XX-XX-  
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX)  
no evpn multi-homed (esi | system-mac)
```

Parameters

XX:XX:XX:XX:XX:XX:XX:XX:XX	ESI value in HH:HH:HH:HH:HH:HH:HH:HH - 9 octet format
XX-XX-XX-XX-XX-XX	Host MAC address (Option 1)
XX:XX:XX:XX:XX:XX	Host MAC address (Option 2)
XXXX.XXXX.XXXX	Host MAC address (Option 3)

Default

Default value is 0.

Command Mode

Interface Mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal  
(config)# interface xe1  
(config)# evpn multi-homed esi 00:11:22:33:44:55:66:77:88  
(config)# exit  
  
configure terminal  
(config)# interface po1  
(config)# evpn multi-homed system-mac 0000.0000.1111  
(config)# exit
```

evpn-vlan-service

Use this command to configure EVPN-Service type.

Use the `no` form of this command to delete the `evpn vlan service`.

Note: If access port mappings to vnid exists already and VLAN service is configured later and mapped to tenant then we should not allow the mapping, user should either remove and reconfigure the access port mappings.

Command Syntax

```
evpn-vlan-service (vlan-aware-bundle | vlan-based)
no evpn-vlan-service
```

Parameters

vlan-based	VLAN-based mapping of a mac-vrf to single VNI (1 to 1)
vlan-aware-bundle	VLAN-aware-bundle mapping of a mac-vrf to multiple VNI (1 to many)

Default

By default, `vlan-aware-bundle` service is applied when we no `evpn-vlan-service` configuration is specified explicitly.

Command Mode

MAC vrf mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal
(config)#mac vrf vrf1
(config-vrf) # evpn-vlan-service vlan-based
(config-vrf) # no evpn-vlan-service vlan-based
```

garp-gna enable

Use this command to enable GARP/GNA packets per vxlan on the outgoing access interfaces where it is configured.

Use the no form this command to disable GARP/GNA packets on the outgoing access interfaces.

By default it will be disable

Command Syntax

```
garp-gna enable  
no garp-gna enable
```

Parameters

None

Command Mode

config-nvo-acc-if mode

Applicability

This command is introduced in OcNOS version 1.3.6.

Example

```
#configure terminal  
(config)#nvo vxlan access-if port-vlan xe1 10  
config-nvo-acc-if)#garp-gna enable
```

load-balance rtag7 vxlan inner-l2

Use this command to enable RTAG7 load balancing for VxLAN for inner-L2 packets on the access side for load sharing of traffic on tunnel paths. This command also enables random UDP source port generation for the VxLAN UDP tunnels based on the L2 frame being received on the VxLAN access port.

Use the `no` parameter of this command to disable load balance for RTAG7 for VxLAN for inner-L2 frames.

Command Syntax

```
load-balance rtag7 vxlan inner-l2 (dest-mac | src-mac)
no load-balance rtag7 vxlan inner-l2 (dest-mac | src-mac)
```

Parameter

dest-mac	Destination MAC Address.
src-mac	Source MAC Address.

Default

By default, the `load-balance rtag7 vxlan inner-l2` default is `src-mac`.

Command Mode

Configure mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal
(config)#load-balance rtag7 vxlan inner-l2 dest-mac
(config)#no load-balance rtag7 vxlan inner-l2 dest-mac
```

load-balance rtag7 vxlan inner-l3

Use this command to enable RTAG7 load balancing for VxLAN for inner-L3 IPv4 and IPv6 packets on the access side for load sharing of traffic on tunnel paths. This command also enables random UDP source port generation for the VxLAN UDP tunnels based on the L3 frame being received on the VxLAN access port.

Use the `no` parameter of this command to disable load balance for RTAG7 for VxLAN for inner-L3 IPv4 and IPv6 frames.

Command Syntax

```
load-balance rtag7 vxlan inner-l3 (dest-ip | destl4-port | protocol-id | src-ip |
    src14-port)
no load-balance rtag7 vxlan inner-l3 (dest-ip | destl4-port | protocol-id | src-ip |
    | src14-port)
```

Parameter

<code>dest-ip</code>	Destination IP.
<code>destl4-port</code>	Destination l4 port.
<code>protocol-id</code>	Protocol (IPv4).
<code>src-ip</code>	Source IP.
<code>src14-port</code>	Source l4 port.

Default

By default, the `load-balance rtag7 vxlan inner-l3` default is `src-ip`.

Command Mode

Configure mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal
(config)#load-balance rtag7 vxlan inner-l3 dest-ip
(config)#no load-balance rtag7 vxlan inner-l3 dest-ip
```

mac

Use this command to associate a static MAC address and a static IPv4 or IPv6 address on an access interface.

Use the `no` form of this command to disassociate a static MAC address and an IPv4 or IPv6 address for an access interface.

Note: When a static host is configured on an access port which is in the down state, its state is Inactive.

Note: The same static mac configuration is not allowed on a different access port as then there will be a chance of conflict. However, if a dynamic packet is sent at another access port which is up and running with the same MAC, it learns as usual. As soon as the port on which the static MAC is configured comes up, static learning is given precedence and the dynamically learned MAC is moved to the port where it is configured statically.

Command Syntax

```
mac XXXX.XXXX.XXXX
mac XXXX.XXXX.XXXX (ip A.B.C.D | ipv6 X:X::X:X)
no mac XXXX.XXXX.XXXX (ip A.B.C.D | ipv6 X:X::X:X)
```

Parameters

`XXXX.XXXX.XXXX` Static MAC address. The following formats are supported:

`XX-XX-XX-XX-XX-XX` Source MAC address (Option 1)

`XX:XX:XX:XX:XX:XX` Source MAC address (Option 2)

`XXXX.XXXX.XXXX` Source MAC address (Option 3)

`A.B.C.D` Static IPv4 address.

`X:X::X:X` Static IPv6 address.

Default

No default value is specified for mac command.

Command Mode

NVO access interface mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal
(config)#nvo vxlan access-if port-vlan xe1 2
(config-nvo-acc-if)#mac 0000.0000.aaaa ip 10.10.10.1
(config-nvo-acc-if)#mac 0000.0000.aaaa ipv6 1201::1
(config-nvo-acc-if)#exit
```

mac vrf

Use this command to create a MAC VRF to use in EVPN routes.

See also [vxlan host-reachability-protocol evpn-bgp](#).

Use the `no` parameter of this command to delete the MAC VRF.

Command Syntax

```
mac vrf WORD  
no mac vrf WORD
```

Parameter

WORD	MAC routing or forwarding instance name.
------	--

Default

No default value is specified for `mac vrf WORD` command.

Command Mode

Configure mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal  
(config)#mac vrf vrf1  
  
(config)#no mac vrf vrf1
```

mac-holdtime

Use this command to set the MAC hold time for a MAC/IP or MAC.

The feature holds the MAC in hardware until BGP has withdrawn from the neighbors. This helps to reduce flooding to other access ports.

This setting applies when the access port is shut down, the physical port on which the access port is down, or the access port is removed from the VNID using the `no` form of the `map vnid` command.

When the MAC hold time is configured as -1, then the MAC is not removed from the hardware and is also not withdrawn from EVPN BGP.

Use the `no` form of this command to remove the MAC hold time for the MAC/IP or MAC.

Note: When a MAC is moved to discard state, traffic to and from this MAC is discarded. This is applicable only on statically configured MAC/MAC-IPs.

Command Syntax

```
mac-holdtime <-1-300>
no mac-holdtime
```

Parameters

<-1-300>	MAC hold time in seconds. Specify -1 to “never expire”.
----------	---

Default

The default holdtime for mac is 3 seconds.

Command Mode

NVO mode and NVO_ACC_IF_MODE mode

Note: When configured in both modes, then the NVO_ACC_IF_MODE value takes preference for that access port.

Applicability

This command was introduced before OcNOS version 1.3.

This command in NVO_ACC_IF_MODE mode is introduced in OcNOS version 1.3.4.

Example

```
#configure terminal
(config)#nvo vxlan id 3 ingress-replication inner-vid-disabled
(config-nvo)#mac-holdtime -1
(config-nvo)#exit
```

map vnid

Use this command to map a tenant to an access-port.

Use the `no` form of this command to remove the tenant from an access-port

Command Syntax

```
map vnid <1-16777215>
no map vnid <1-16777215>
```

Parameters

`<1-16777215>` VxLAN network identifier.

Default

No default value is specified for `map vnid` command.

Command Mode

NVO access interface mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal
(config)#nvo vxlan access-if port-vlan xe1 2
(config-nvo-acc-if)#map vnid 100
(config-nvo-acc-if)#exit
```

nd-cache disable

Use this command to disable ND cache for MAC/IPv6.

When the ND cache is disabled on a VxLAN access port, OcNOS does not reply to any ND arriving on this port from the cache. OcNOS withdraws all MAC/IPs configured/learned on this access port and removes the MAC/IP entry for this access port from the local ND cache.

OcNOS also makes sure that on withdrawing the MAC/IP route, the MAC does not become unknown. If all routes for this MAC are being withdrawn because of this command, then OcNOS advertises a MAC-only route. This is done so that the MAC does not become unknown and only the cache functionality becomes disabled.

See also [arp-cache disable](#).

Use the `no` form of this command to enable ND cache for MAC/IPv6.

Note: On enabling the cache, an IP will be in conflict, then the cache enable will fail. The conflict has to be manually removed and then the cache enabled.

Command Syntax

```
nd-cache disable  
no nd-cache disable
```

Parameters

None

Default

By default, the nd-cache option is enabled.

Command Mode

NVO access interface mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal  
(config)#nvo vxlan access-if port-vlan xe1 2  
(config-nvo-acc-if)#nd-cache disable  
(config-nvo-acc-if)#exit
```

no nvo vxlan

Use this command to delete a given tenant or all tenants/VPNs.

Command Syntax

```
no nvo vxlan (id <1-16777215>|all-vnids)
```

Parameters

<1-16777215>	VXLAN Network Identifier.
all-vnids	Delete all VxLAN network identifiers.

Command Mode

Configure mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal  
(config)#no nvo vxlan id 100
```

nvo vxlan

Use this command to enable or disable VxLAN.

Command Syntax

```
nvo vxlan (enable | disable)
```

Parameters

None

Default

By default, the nvo vxlan option is disabled.

Command Mode

Configure mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal  
(config)#nvo vxlan enable  
  
(config)#nvo vxlan disable
```

nvo vxlan id

Use this command to add a tenant and the type of VPN. This command changes the mode to NVO mode.

Use `no` form of this command to unconfigure the VXLAN ID.

Before using this command, enable VXLAN by using the [nvo vxlan](#) command.

Command Syntax

```
nvo vxlan id <1-16777215> (etree-leaf|) ((ingress-replication (inner-vid-disabled |
    bridge-vlan VLAN-ID | etree-leaf)
no nvo vxlan id <1-16777215>
```

Parameters

<code>vxlan id <1-16777215></code>	Specifies the VXLAN Network Identifier (VNID) to identify the virtual VXLAN overlay network segment.
<code>multicast</code>	(Optional) Specifies a multicast mode (point to multipoint) used for transmitting VXLAN encapsulated multicast packets.
<code>ingress-replication</code>	(Optional) Enables head-end replication for forwarding BUM traffic.
<code>bridge-vlan VLAN-ID</code>	(Optional) Specifies the VLAN ID.
<code>inner-vid-disabled</code>	(Optional) Disables the transmission of the VLAN ID (VID) with traffic leaving the network port.
<code>etree-leaf</code>	(Optional) Configures the device as a leaf node within the E-Tree topology, implying its role in forwarding BUM traffic within the E-Tree service model.

Command Mode

Configure mode

Applicability

This command was introduced before OcNOS version 1.3. Introduced the `etree-leaf` parameter in the OcNOS version 6.5.1

Example

```
#configure terminal
(config)#nvo vxlan id 300 ingress-replication
(config-nvo)#exit

(config)#nvo vxlan id 200 ingress-replication inner-vid-disabled
(config-nvo)#exit
```

To configure a VXLAN instance with VXLAN ID for ingress replication, with inner VLAN ID disabled, and as an E-Tree leaf node:

```
(config)#nvo vxlan id 10 ingress-replication inner-vid-disabled etree-leaf
(config-nvo)#exit
```

To configure a VXLAN instance with VLAN-VNID mapping for ingress replication on the leaf node:

```
(config)#nvo vxlan id 101 ingress-replication bridge-vlan 101
```

```
(config-nvo) #exit
```

nvo vxlan access-if

Use this command to map a complete interface or a VLAN or VLAN range on an interface to identify the tenant traffic and to enter NVO access interface mode.

The command "nvo vxlan access-if port <if_name> default" accepts all tagged, double tagged and untagged traffic received on the mapped physical port.

Use the `no` form of this command to unmap an interface or a VLAN.

Note: When a VxLAN access interface configured as a port VLAN as `vlan-range` or port as `default`, then arp-cache and nd-cache should be disabled and only VNID with inner-vid-enable is mapped.

Note: Inner-vid-enable is one-to-one mapping. VNID is mapped to only on one access-port.

Note: Vlan Range not allowed to be configured for Vxlan stacked access-port.

Command Syntax

```
nvo vxlan access-if (port IFNAME (| default) | port-vlan IFNAME VLAN_RANGE (|  
inner-vlan <2-4094>))  
  
no nvo vxlan access-if (port IFNAME | port-vlan IFNAME VLAN_RANGE(| inner-vlan <2-  
4094>))
```

Parameters

<code>port</code>	A physical port.
<code>IFNAME</code>	Interface name (Physical/Static lag/Dynamic lag)
<code>default</code>	Default access interface
<code>port-vlan</code>	The physical port on which VLANs are configured
<code>IFNAME</code>	Interface name (Physical/Static lag/Dynamic lag)
<code>VLAN_RANGE</code>	Configure VlanId or Vlan-Range for outer vlan
<code>Inner-vlan</code>	Inner-vlan id
<code><2-4094></code>	VLAN id

Default

By default, the `nvo vxlan access-if` option is `port VLAN ID` and `VLAN_RANGE` option is introduced in OcNOS version 5.0..

Command Mode

Configure mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal  
(config)#nvo vxlan access-if port-vlan xe1 2-10  
(config-nvo-acc-if)#exit  
  
#configure terminal
```

```
(config)#nvo vxlan access-if port xe1
(config-nvo-acc-if)#exit

#configure terminal
(config)#nvo vxlan access-if port xe1 default
(config-nvo-acc-if)#exit

#configure terminal
(config)#nvo vxlan access-if port-vlan xe1 2 inner-vlan 10
(config-nvo-acc-if)#exit
```

nvo vxlan mac-ageing-time

Use this command to set the dynamically learned MAC ageing time.

Use the `no` form of this command to set the age out the MACs in hardware to its default (300 seconds).

Command Syntax

```
nvo vxlan mac-ageing-time <10-572>
no nvo vxlan mac-ageing-time
```

Parameters

<10-572> Ageing time in seconds.

Default

The default age out time is 300 seconds.

Command Mode

Configure mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal
(config)#nvo vxlan mac-ageing-time 10
```

nvo vxlan max-cache-disable

Use this command to configure the maximum number of ARP and ND cache disables on access ports configured with the port+VLAN options. This command does not limit the ARP and ND cache disables on access ports created with only the port option.

Use the `no` form of this command to set the maximum number of ARP and ND cache disables to its default (0).

Note: If any MAC is in conflict when the max cache disable is being unconfigured, then the corresponding caches will not be enabled. This can be enabled after manually, removing the conflict. Caches where there is no conflict, will be enabled.

Command Syntax

```
nvo vxlan max-cache-disable <1-200>
no nvo vxlan max-cache-disable
```

Parameters

<-1-200>	Number of ARP/ND cache disable allowed
----------	--

Default

The default maximum number of ARP and ND cache disables is 0.

Command Mode

Configuration mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal
(config)#nvo vxlan max-cache-disable 10
(config-nvo)#exit
```

nvo vxlan vtep-ip-global

Use this command to set the source IP address of the VxLAN tunnels.

Use the `no` form of this command to remove the source IP address of the VxLAN tunnels.

Command Syntax

```
nvo vxlan vtep-ip-global A.B.C.D  
no nvo vxlan vtep-ip-global A.B.C.D
```

Parameters

A.B.C.D	Source VTEP IP address of the global configuration
---------	--

Default

No default value is specified for `nvo vxlan vtep-ip-global` command.

Command Mode

NVO mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
(config-nvo) #nvo vxlan vtep-ip-global 10.10.11.1
```

show bgp l2vpn evpn

Use this command to display details about Layer 2 Virtual Private Network (L2VPN) Ethernet Virtual Private Network (EVPN) routes.

- Note: A BGP EVPN route update received for an unreachable IP address is also listed by this command and as a best route. This is because the next hop tracking feature is not supported for the EVPN address family. However, the tunnel to this IP address is shown in unresolved state by the [show nvo vxlan tunnel](#) output.
- Note: An E-tag (Ethernet tag) can have the value of zero/VID/VNID based on the use case. An E-tag can go up to 32 bits and no restrictions are noted in the RFC. Since an E-tag can have different values, it should not be compared with the label/VNID.

Command Syntax

```
show bgp l2vpn evpn ((vrf WORD) | (rd WORD) | time)
show bgp l2vpn evpn mac-ip ((vrf WORD) | (rd WORD) | )
show bgp l2vpn evpn mcast
show bgp l2vpn evpn multihoming es-route <(rd WORD) | (vrf WORD)>
show bgp l2vpn evpn multihoming ethernet-ad-per-evi <(rd WORD) | (vrf WORD)>
show bgp l2vpn evpn multihoming ethernet-ad-per-es <(rd WORD) | (vrf WORD)>
```

Parameters

vrf	Virtual Routing and Forwarding instance
WORD	VRF name
rd	Route distinguisher
WORD	Route distinguisher: ASN:nn or IP:nn
time	Display learned time for EVPN routes
mac-ip	MAC/IP routes (EVPN type 2)
mcast	Multicast routes (EVPN type 3)

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#show bgp l2vpn evpn

BGP table version is 25, local router ID is 1.1.1.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
               l - labeled, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

[EVPN route type]:[ESI]:[VNID]:[relevent route information]
1 - Ethernet Auto-discovery Route
```

- 2 - MAC/IP Route
 3 - Inclusive Multicast Route
 4 - Ethernet Segment Route

Network	Next Hop	Metric	LocPrf	Weight	Path	Peer
RD[1.1.1.1:1] VRF[vrfblue]:						
*> [2]:[0]:[100]:[48,0000.00aa.aaaa]:[32,10.1.1.2]:[100]	1.1.1.1	0	100	32768	i	
*>i [2]:[0]:[100]:[48,0000.00bb.bbbb]:[32,10.1.1.3]:[100]	4.4.4.4	0	100	0	i	10.1.1.1
*> [3]:[100]:[32,1.1.1.1]	1.1.1.1	0	100	32768	i	
*>i [3]:[100]:[32,4.4.4.4]	4.4.4.4	0	100	0	i	10.1.1.1
*> [3]:[101]:[32,1.1.1.1]	1.1.1.1	0	100	32768	i	
*>i [3]:[101]:[32,4.4.4.4]	4.4.4.4	0	100	0	i	10.1.1.1
RD[2.2.2.2:1]						
*>i [2]:[0]:[100]:[48,0000.00bb.bbbb]:[32,10.1.1.3]:[100]	4.4.4.4	0	100	0	i	10.1.1.1
*>i [3]:[100]:[32,4.4.4.4]	4.4.4.4	0	100	0	i	10.1.1.1
*>i [3]:[101]:[32,4.4.4.4]	4.4.4.4	0	100	0	i	10.1.1.1

Total number of prefixes 9

[Table 1-1](#) shows the status codes displayed at the start of a route entry.

Table 1-1: status codes

Status code	Description	Comments
s	suppressed	Whether the route is suppressed and is not advertised to neighbors.
d	damped	When the penalty of a flapping route exceeds the suppress limit, the route is damped and remains in a withdrawn state until its penalty decreases below the reuse limit.
h	history	When the penalty of a flapping route does not exceed the suppress limit, the route is not damped and BGP maintains a history of the flapping route.
*	valid	Whether the route is valid. When a route is not suppressed, damped, or present in the history, it is valid.
>	best	The selected route to be installed in the kernel routing table.
i	internal	The prefix was learned from an iBGP peer.
l	labeled	BGP Labeled Unicast advertises route information between inter region routers.

[Table 1-2](#) shows the codes at the end of each route entry that indicate where the route originated.

Table 1-2: origin codes

Origin Code	Description	Comments
i	IGP	The route is from an Interior Gateway Protocol.
e	EGP	The route is from an Exterior Gateway Protocol.
?	incomplete	Origin not known. Typically, these are routes redistributed from an IGP.

[Table 1-3](#) explains the fields for each route.

Table 1-3: route entry fields

Field	Description
RD	Route distinguisher: AS number or IP address.
VRF	Name of the VRF.
Network	<p>EVPN route information.</p> <p>The route type indicates the type of routing information advertised by the EVPN control plane:</p> <ul style="list-style-type: none"> 2 MAC/IP Route: Endpoint reachability information, including MAC and IP addresses of the endpoints. 3 Inclusive Multicast Route: Information about how to forward Broadcast, Unknown Unicast and Multicast (BUM) traffic. <p>The other fields included depend on the route type:</p> <ul style="list-style-type: none"> Type 2: [ESI]:[E-Tag]:[Length, Host MAC address]:[Length, Host IP address]:[Label/VNID] Type 3: [E-Tag]:[Length, PE IP address] <p>ESI (Ethernet Segment Identifier): a unique non-zero identifier that identifies an Ethernet segment, which is a set of links that connects a network or device to one or more PEs. ESI 0 denotes a single-homed site.</p> <p>E-Tag (Ethernet tag): identifies a particular broadcast domain such as a VLAN or VNID in the VxLAN case. An EVPN instance consists of one or more broadcast domains.</p> <p>VNID (VXLAN network identifier): identifies Layer 2 segments and maintains Layer 2 isolation between the segments, allowing the addressing of up to 16 million logical networks in the same administrative domain.</p> <p>The status codes are explained in Table 1-1.</p>
Next Hop	IP address of the nexthop for this route.
Metric	Multiple-Exit Discriminator (MED). If there are multiple paths to the same destination from a single routing protocol, then the multiple paths have the same administrative distance and the best path is selected based on this metric. The path with the lowest metric is selected as the optimal path and installed in the routing table.
LocPrf	Local preference set with the <code>set local-preference</code> command. This value is used only with iBGP sessions within the local autonomous system to determine if a route towards a destination is the “best” one. The path with the highest local preference is preferred.
Weight	This field applies only to routes within an individual router. If a route was learned from a peer, it has a default weight of 0. All routes generated by the local router have a weight of 32,768.

Table 1-3: route entry fields (Continued)

Field	Description
Path	The autonomous systems through which the prefix advertisement passed. The origin codes are explained in Table 1-2 .
Peer	Neighbor address.
Total number of prefixes	The total number of prefixes listed.

show bgp l2vpn evpn summary

Use this command to display a summary of BGP EVPN neighbor status.

Command Syntax

```
show bgp l2vpn evpn summary
```

Parameters

None

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#show bgp l2vpn evpn summary
BGP router identifier 1.1.1.1, local AS number 100
BGP table version is 17
1 BGP AS-PATH entries
0 BGP community entries

Neighbor          V   AS   MsgRcv   MsgSen TblVer   InQ    OutQ     Up/Down   State/PfxRcd   AD   MACIP   MCAST   ESI
8.8.8.8           4   100  111      112     17      0       0  00:53:03        3   0       0       3       0
9.9.9.9           4   100  110      110     17      0       0  00:52:10        15  0       13      2       0
13.13.13.13      4   100  132      109     17      0       0  00:51:57        4   0       2       2       0

Total number of neighbors 3

Total number of Established sessions 3
```

The start of the output shows:

- The BGP router identifier and the local router AS number.
- The BGP table version tracks the local BGP table version. Any time the BGP best path algorithm executes, the table version increments.
- BGP AS-PATH entry and community entries.

[Table 1-4](#) explains the fields for each neighbor entry.

Table 1-4: neighbor fields

Field	Description
Neighbor	IP address of peer.
V	BGP version of peer.
AS	Autonomous system number of peer.
MsgRcvd	Messages received since the BGP connection was established.
MsgSent	Messages sent since the BGP connection was established.

Table 1-4: neighbor fields (Continued)

Field	Description
TblVer	Last version of the local router's BGP database advertised to the peer.
InQ	Received messages waiting in the input queue for further processing.
OutQ	Messages waiting in the output queue to be sent.
Up/Down	Connection up time in the interface.
State/PfxRcd	<p>If the TCP session is up and the BGP peers have formed an adjacency, this field shows how many prefixes have been received from the remote neighbor.</p> <p>Other states:</p> <ul style="list-style-type: none"> Idle: The local router has not allocated resources for the peer connection, so incoming connection requests are refused Idle (Admin): The peer has shut down Idle (PfxCt): Prefix overflow Idle (G-shut): Graceful shutdown Connect: BGP is waiting for the TCP connection to complete Active: the local router is trying to establish a TCP connection to the remote peer. You might see this if the local peer has been configured, but the remote peer is unreachable or has not been configured. OpenSent: BGP is waiting for an open message from its peer OpenConfirm: BGP received an open message from the peer and is now waiting for a keepalive or notification message. If BGP receives a keep alive message from the peer, the state changes to established. If the message is a notification, the state changes to idle. Established: BGP is ready to exchange update, notification, and keep alive messages with its peer Invalid: The session state is invalid.
AD	Number of EVPN type 1 Ethernet Auto-discovery routes: Only originated for multi-homed sites. Type 1 routes allow fast convergence where PE devices can change the next-hop adjacencies for all MAC addresses associated with a particular Ethernet Segment and aliasing where traffic can be balanced across multiple egress points
MACIP	Number of EVPN type 2 MAC/IP routes: Endpoint reachability information, including MAC and IP addresses of the endpoints.
MCAST	Number of EVPN type 3 Inclusive Multicast routes: Broadcast, Unknown Unicast and Multicast (BUM) traffic.
ESI	Number of EVPN type 4 Ethernet Segment Routes: Used in multi-homing for Designated Forwarder Election. The Designated Forwarder sends BUM traffic to the CE on a particular Ethernet Segment.

show nvo vxlan

Use this command to display VXLAN information.

Command Syntax

```
show nvo vxlan (vnid <1-16777215>|)
```

Parameters

<1-16777215> VXLAN network identifier.

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#sh nvo vxlan
VXLAN Information
=====
Codes: NW - Network Port
       AC - Access Port
       (u) - Untagged

VNID      Vni-name      Type Interface ESI
Status    Src-addr      Dst-addr

-----
10        ----          NW   ----      ----
           1.1.1.1        3.3.3.3
10        ----          NW   ----      ----
           1.1.1.1        2.2.2.2
10        ----          AC   ce21/1   00:00:11:22:33:44:55:66:77:88 2
DF        ----          ----
20        ----          NW   ----      ----
           1.1.1.1        3.3.3.3
20        ----          NW   ----      ----
           1.1.1.1        2.2.2.2
20        ----          AC   ce21/1   00:00:11:22:33:44:55:66:77:88 3
DF        ----          ----
                                         Vlan DF-
```

Total number of entries are 6

[Table 1-1](#) explains the fields in the output.

Table 1-5: VxLAN fields

Field	Description
VNID	VXLAN network identifier.
Type	NW - Network Port: VxLAN tunnel AC - Access Port: Host connection

Table 1-5: VxLAN fields

Field	Description
Interface	Name of the Interface.
Vlan	VLAN identifier
Src-addr	Source address in the interface.
Dst-addr	Destination address in the interface.
Total number of entries	The total number of entries listed.

show nvo vxlan access-if-config

Use this command to display the current running configuration of the access interface.

Command Syntax

```
show nvo vxlan access-if-config (LINE|)
```

Parameters

LINE	Access port description.
------	--------------------------

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3,

Added new cli "garp-gna enable" under access-if cli in OcNOS version 1.3.6.

Example

```
#show nvo vxlan access-if-config
nvo vxlan access-if port-vlan xe1 2
map vnid 100
garp-gna enable
access-if-description member-port with xe1 as vlan 2
dynamic-learning disable
arp-nd flood-suppress
arp-cache disable
nd-cache disable
shutdown
mac 0000.0000.1111
mac 0000.0000.aaaa ip 12.12.12.1
mac 0000.0000.bbbb ipv6 1201::1
map qos-profile ingress 100
cos 2 egress
!
nvo vxlan access-if port-vlan po1 6 inner-vlan 5
encapsulation 0x9100
no shutdown
map vnid 100
!
```

show nvo vxlan arp-cache

Use this command to display the ARP cache information.

Command Syntax

```
show nvo vxlan arp-cache (vnid <1-16777215>|summary|)
```

Parameters

<1-16777215> VXLAN network identifier.

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3, modified to include new fields – Age-Out and Retries-Left in OcNOS version 1.3.5.

Remote Static and Dynamic keyword got changed to Static and Dynamic Remote in MAC table in OcNOS version 1.3.6.

Example

```
#sh nvo vxlan arp-cache
VXLAN ARP-CACHE Information
=====
ND Timeout : 300 sec Random-Jitter-Max : 640

VNID      Ip-Addr          Mac-Addr        Type      Age-Out     Retries-Left
-----  -----
10        11.11.11.2       0000.0000.bbbb  Dynamic   Local    224        2
10        11.11.11.1       0000.0000.aaaa  Dynamic   Remote---
Total number of entries are 2
```

[Table 1-6](#) explains the output fields.

Table 1-6: ARP cache fields

Field	Description
VNID	VXLAN network identifier
Ip-Addr	IP address of the vxlan
Mac-Addr	Device MAC address
Type	<p>How a host learns a MAC/IP pair:</p> <p>Dynamic: Learned by data plane source learning Evpn: Learned by EVPN Type 2 (MAC/IP) routes Static Remote: Statically configured for remote; used only for static VxLAN, not with EVPN Static Local: Configured on local VTEP</p>

Table 1-6: ARP cache fields

Field	Description
Age=Out	ARP entry expire time
Total number of entries	The total number of entries listed.

show nvo vxlan counters access-port

Use this command to display the receive and transmit counters of an access port including ARP, ND and GARP counters in the same command.

Note: Due to a limitation in the hardware, the transmit packet counters includes the BUM traffic received on that port.

Command Syntax

```
show nvo vxlan counters access-port (port IFNAME | port-vlan IFNAME VLAN_ID)
```

Parameters

port	Port Mapping
IFNAME	Access port name
port-vlan	Port-vlan Mapping
IFNAME	Access port name
VLAN_ID RANGE	Vlan Id or Vlan Range <2-4094>
INNER_VLAN_ID	Inner-Vlan Id
all	All ports and VLANs

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3 and added Control packet (ARP, ND and GARP) counters in OcNOS version 1.3.5. The VLAN_RANGE option is introduced in OcNOS version 5.0.

Example

```
#show nvo vxlan counters access-port port-vlan xe1 2
  Data packets:
    *If ARP/ND cache is enabled, TX doesn't count ARP/ND replies
      from ARP/ND cache and ARP/ND forwarded after uplifting to
      the control plane.
      RX:  packets : 2774939
            bytes  : 210553516
      TX:  packets : 4322274
            bytes  : 326026474

  Control Packets:
    *ARP/ND uplifted and sent/replied from control plane:
      Rx Vxlan Arp discard count      : 0
      Rx Vxlan Nd discard count      : 2
      Tx Vxlan Arp discard count      : 0
      Tx Vxlan Nd discard count      : 0
      Rx Vxlan Arp Request count     : 2
      Tx Vxlan Arp Request count     : 0
      Rx Vxlan Arp Reply count       : 5
      Tx Vxlan Arp Reply count       : 1
      Rx Vxlan Neighbor Solicitation count : 6
      Tx Vxlan Neighbor Solicitation count : 0
```

```

Rx Vxlan Neighbor Advertisement count: 0
Tx Vxlan Neighbor Advertisement count: 4
Rx Vxlan Gratuitous ARP count      : 0
Tx Vxlan Gratuitous ARP count      : 0
Rx Vxlan Gratuitous Neighbor Advertisement count: 3
Tx Vxlan Gratuitous Neighbor Advertisement count: 0
#

```

[Table 1-3](#) explains the fields in the output.

Table 1-7: access port counters

Field	Description
RX: packets	Number of packets received.
RX: bytes	Number of bytes received.
TX: packets	Number of packets transmitted.
TX: bytes	Number of bytes transmitted.
Rx Vxlan Nd discard count	Number of discarded ND that is received from neighbor.
Tx Vxlan Arp discard count	Number of discarded Arp that is transmitted to peer.
Rx Vxlan Nd discard count	Number of discarded ND that is transmitted to peer.
Rx Vxlan Arp Request count	Number of request ARP that is received from neighbor.
Tx Vxlan Arp Request count	Number of request ARP that is transmitted to peer.
Rx Vxlan Arp Reply count	Number of replied ARP that is received from neighbor.
Tx Vxlan Arp Reply count	Number of replied ARP which is transmitted to peer.
Rx Vxlan Neighbor Solicitation count	Number of request ND that is received from neighbor.
Tx Vxlan Neighbor Solicitation count	Number of replied ND that is transmitted to peer.
Rx Vxlan Neighbor Advertisement count	Number of Neighbor Advertisement that is received from neighbor.

Table 1-7: access port counters (Continued)

Field	Description
Tx Vxlan Neighbor Advertisement count	Number of Neighbor Advertisement that is transmitted to peer
Rx Vxlan Gratuitous ARP count	Number of Gratuitous ARP that is received from neighbor.
Tx Vxlan Gratuitous ARP count	Number of Gratuitous ARP which is transmitted to peer.
Rx Vxlan Gratuitous Neighbor Advertisement count	Number of Gratuitous Neighbor Advertisement that is received from neighbor.
Tx Vxlan Neighbor Gratuitous Advertisement count	Number of Gratuitous Neighbor Advertisement which is transmitted to peer.

show nvo vxlan counters network-port

Use this command to display the receive and transmit counters of a network port including ARP, ND and GARP counters in the same command.

Command Syntax

```
show nvo vxlan counters network-port dst A.B.C.D
```

Parameters

A.B.C.D	Tunnel IPv4 address
---------	---------------------

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3 and added control packets (ARP, ND, and GARP) counters in OcNOS version 1.3.5.

Example

```
VTEP1#sh nvo vxlan counters network-port dst 100.2.2.2
```

Data packets:

- *If ARP/ND cache is enabled, TX doesn't count ARP/ND replies from ARP/ND cache and ARP/ND forwarded after uplifting to the control plane.

RX:	packets	:	814327
	bytes	:	92833544
TX:	packets	:	1508023
	bytes	:	171914622

Control Packets:

- *ARP/ND uplifted and sent/replied from control plane:

TX VXLAN Arp discard count	:	0
TX VXLAN ND discard count	:	0
Tx Vxlan Arp Request count	:	0
Tx Vxlan Arp Reply count	:	0
Tx Vxlan Neighbor Solicitation count	:	0
Tx Vxlan Neighbor Advertisement count	:	0
Rx Vxlan Gratuitous ARP count	:	0
Tx Vxlan Gratuitous ARP count	:	0
Rx Vxlan Gratuitous Neighbor Advertisement count	:	0
Tx Vxlan Gratuitous Neighbor Advertisement count	:	0

Table 1-4 explains each network entry fields.

Table 1-8: show nvo vxlan counters network-port output fields

Field	Description
RX: packets	Number of hello packets received from neighbor.
RX: bytes	Number of hello packets received from neighbor in bytes received.
TX: packets	Number of hello packets transmitted to neighbor.
TX: bytes	Number of hello packets transmitted to neighbor in bytes transmitted.
Rx Vxlan Nd discard count	Number of discarded ND that is received from neighbor.
Tx Vxlan Arp discard count	Number of discarded Arp that is transmitted to peer.
Rx Vxlan Nd discard count	Number of discarded ND that is transmitted to peer.
Rx Vxlan Arp Request count	Number of request ARP that is received from neighbor.
Tx Vxlan Arp Request count	Number of request ARP that is transmitted to peer.
Rx Vxlan Arp Reply count	Number of replied ARP that is received from neighbor.
Tx Vxlan Arp Reply count	Number of replied ARP which is transmitted to peer.
Rx Vxlan Neighbor Solicitation count	Number of request ND that is received from neighbor.
Tx Vxlan Neighbor Solicitation count	Number of replied ND that is transmitted to peer.
Rx Vxlan Neighbor Advertisement count	Number of Neighbor Advertisement that is received from neighbor.
Tx Vxlan Neighbor Advertisement count	Number of Neighbor Advertisement that is transmitted to peer.
Rx Vxlan Gratuitous ARP count	Number of Gratuitous ARP that is received from neighbor.
Tx Vxlan Gratuitous ARP count	Number of Gratuitous ARP which is transmitted to peer.
Rx Vxlan Gratuitous Neighbor Advertisement count	Number of Gratuitous Neighbor Advertisement that is received from neighbor.
Tx Vxlan Neighbor Gratuitous Advertisement count	Number of Gratuitous Neighbor Advertisement which is transmitted to peer.

show nvo vxlan mac-table

Use this command to display the host MAC address table. Use the `hardware` option to see the age out time for dynamically learned macs.

Command Syntax

```
show nvo vxlan mac-table (vnid <1-16777215>|) (summary | hardware |)
```

Parameters

<1-16777215>	VXLAN network identifier.
<code>summary</code>	Count the MAC addresses.

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3.

Remote Static and Dynamic keyword got changed to Static and Dynamic Remote in MAC table in OcNOS version 1.3.6.

Example

```
#show nvo vxlan mac-table
=====
===== VXLAN MAC Entries =====
=====

VNID      Interface   VlanId Inner-VlanId Mac-Addr          VTEP-Ip/
ESI       Type        Status           AccessPortDesc

=====
10        ce21/1     2      ---- 0000.0000.1111
1.1.1.1   partner-port      Static Local  -----
3.3.3.3   ---        ---      ---- 0000.0000.2222
3.3.3.3   ---        ---      ----  Static Remote -----
1.1.1.1   ce21/1     3      ---- 0000.0000.cccc
1.1.1.1   ce21/1     3      ----  Static Local   Discard
3.3.3.3   ---        ---      ---- 0000.0000.dddd
3.3.3.3   ---        ---      ----  Static Remote -----
-         ce21/1     3      ---- 0000.0000.eeee
-         ce21/1     3      ----  Static Local   Discard
-         ce21/1     3      ---- 0000.0000.ffff
-         ce21/1     3      ----  Static Remote -----
```

Total number of entries are : 4

```
#show nvo vxlan mac-table hardware
=====
===== VXLAN MAC Entries =====
=====
```

VNIID ESI AccessPortDesc	Interface	VlanId	Inner-VlanId	Mac-Addr	Status	VTEP-Ip/ Time-out
Type						
10 1.1.1.1 partner-port	ce21/1	2	---	0000.0000.1111	Static Local	-----
10 3.3.3.3	---	---	---	0000.0000.2222	Static Remote	-----
--						-
10 3.3.3.3	---	---	---	0000.0000.aa11	Static Remote	-----
--						-
10 1.1.1.1 partner-port	ce21/1	2	---	0000.0000.bb11	Dynamic Local	-----
10 1.1.1.1 partner-port	ce21/1	2	---	0000.0000.bb12	Dynamic Local	-----
20 1.1.1.1	---	---	---	0000.0000.cccc	Static Local	Discard
20 3.3.3.3	---	---	---	0000.0000.dddd	Static Remote	-----
--						-

Total number of entries are 7

Table 1-5 explains the fields in the output.

Table 1-9: MAC table fields

Field	Description
VNIID	VXLAN network identifier
Interface	Interface name
VlanId	VLAN identifier
Mac-Addr	MAC address
VTEP-Ip	VTEP identifier/Ethernet Segment Identifier
Type	<p>How a host learns a MAC/IP pair:</p> <p>Remote: Statically configured for remote; used only for static VxLAN, not with EVPN</p> <p>Static Local: Configured on local VTEP</p> <p>Dynamic Local: Learned by data plane source learning</p>
Status	<p>Max Move conflict: When a MAC has moved too many times (5 or more times in 180 seconds). This is according to the procedures defined in RFC 7432, Section 15.1.</p> <p>Discard: If a MAC hold time is configured, then if the VxLAN access port goes down (admin or operational), the MAC is moved to the discard state for the period of the hold time. The MAC is also moved to the discard state if the VNIID is unmapped from the port. In dynamically learned cases, the MAC is also moved to discard when learning is disabled.</p>
Time-out	Age timeout for dynamically learned MACs.

Table 1-9: MAC table fields (Continued)

Field	Description
AccessPortDesc	Access port description.
Total number of entries	The total number of entries listed.

show nvo vxlan nd-cache

Use this command to display the Neighbor Discovery cache.

Command Syntax

```
show nvo vxlan nd-cache (vnid <1-16777215>|summary|)
```

Parameters

<1-16777215> VXLAN network identifier.

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3, modified to include new fields – Age-Out and Retries-Left in OcNOS version 1.3.5.

Remote Static and Dynamic keyword got changed to Static and Dynamic Remote in ND table in OcNOS version 1.3.6.

Example

```
#show nvo vxlan nd-cache
VXLAN ND-CACHE Information
=====
ND Timeout : 300 sec Random-Jitter-Max : 640
```

VNID	Ip-Addr	Mac-Addr	Type	Age-Out	Retries-Left
10	2001::1	0000.0000.1111	Dynamic Local	274	2
10	2001::2	0000.0000.2222	Dynamic Remote	----	
Total number of entries are 2					

Table 1-6 explains the output fields.

Table 1-10: ND cache fields

Field	Description
VNID	VXLAN network identifier
Ip-Addr	IP address
Mac-Addr	MAC address
Type	How a host learns a MAC/IP pair: Static Remote: Statically configured for remote; used only for static VxLAN, not with EVPN Static Local: Configured on local VTEP Dynamic: Learned by data plane source learning Evpn: Learned by EVPN Type 2 (MAC/IP) routes

Table 1-10: ND cache fields

Field	Description
Age-Out	ND entry expire Time
Total number of entries	The total number of entries listed.

show nvo vxlan static host state

Use this command to display the state of the host which is configured statically.

Command Syntax

```
show nvo vxlan static host state
```

Parameters

None

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#sh nvo vxlan static host state
VNID Ifname      Vlan      Ip-Addr          Mac-Addr          Status
----- -----
100   xe1         2        12.12.12.1       0000.0000.aaaa    Inactive
100   xe2         2        1201::1           0000.0000.bbbb    Conflict
100   xe3         2        120.120.120.1     0000.0000.bb11    Active
```

[Table 1-7](#) explains the output fields.

Table 1-11: Static host fields

Field	Description
VNID	VXLAN network identifier
Ifname	Interface name
Vlan	VLAN name
Ip-Addr	IP address

Table 1-11: Static host fields

Field	Description
Mac-Addr	MAC address
Status	<p>Status of the MAC/IP on the host:</p> <p>Conflict: When a MAC/IP was configured, the conflict was not known as the VNID was not mapped to the access port. After the VNID is mapped, if the same MAC/IP is present statically on some other port on the same VNID, then it is in conflict state.</p> <p>Learnt Conflict: When a MAC/IP was configured, the conflict was not known. However, it is now in conflict because the same MAC/IP is configured on an access port on VTEP1 and on an access port on VTEP2. Because the BGP session/tunnel was not up, the MAC/IP was not known to the other VTEP and the configuration was allowed. When the BGP session/tunnel comes up and it finds such a conflicted route, it marks the state as Learnt Conflict.</p> <p>Inactive: Configured but not operating, such as when the port is not mapped to any VNID. The port is down and the ARP/ND cache is disabled.</p> <p>Active: Operating host MAC/IP.</p>

show nvo vxlan tunnel

Use this command to view the source, destination, and status of the VxLAN tunnel entries.

Command Syntax

```
show nvo vxlan tunnel
```

Parameters

None

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

The following is a sample output of the `show nvo vxlan tunnel` command.

```
#show nvo vxlan tunnel
VXLAN Network tunnel Entries
  Source Destination      Status Up/Down Update
=====
  1.1.1.1 2.2.2.2        Installed 00:00:20 00:00:20
Total number of entries are 1
#
```

[Table 1-8](#) explains the output fields.

Table 1-12: VxLAN tunnel fields

Field	Description
Source	Tunnel source IP address.
Destination	Tunnel destination IP address.
Status	Installed: Tunnel Installed in the hardware and operating. Resolved: Tunnel destination IP is reachable, but VxLAN tunnel not installed in hardware. Therefore, not operating. Unresolved: Tunnel destination IP not reachable because L3 route is down.
Up/Down	When the tunnel came up or went down
Update	When the tunnel was last updated
Total number of entries	The total number of entries listed.

show running-config nvo vxlan

Use this command to display the current running configuration of VxLANs.

Command Syntax

```
show running-config nvo vxlan
```

Parameters

None

Command Mode

Exec mode

Applicability

This command was introduced in a version before OcNOS version 1.3 and added few CLIs for IRB and ARP-ND refresh timer for OcNOS version 1.3.5.

Example

```
#show running-config nvo vxlan
!
nvo vxlan multihoming enable
!
nvo vxlan enable
!
nvo vxlan vtep-ip-global 1.1.1.1
!
nvo vxlan max-cache-disable 10
!
nvo vxlan tunnel qos-map-mode cos-dscp ingress QUE_DSCP
!
nvo vxlan tunnel qos-map-mode cos-dscp egress DSCP_QUE
!
nvo vxlan id 100 ingress-replication inner-vid-disabled
  vxlan host-reachability-protocol evpn-bgp vrf1
  mac-holdtime 20
!
nvo vxlan access-if port-vlan xe1 2
  map vnid 100
access-if-description member-port with xe1 as vlan 2
dynamic-learning disable
arp-nd flood-suppress
arp-cache disable
nd-cache disable
shutdown
mac 0000.0000.1111
mac 0000.0000.aaaa ip 12.12.12.1
mac 0000.0000.bbbb ipv6 1201::1
map qos-profile cos-to-queue COS_QUE
map qos-profile queue-color-to-cos QUE_COS
!
nvo vxlan access-if port-vlan po1 6 inner-vlan 5
  encapsulation 0x9100
```

```
no shutdown
map vnid 100
!
```

show evpn multi-homing all

Use this command to display the multi-homed VTEP details.

Command Syntax

```
show evpn multi-homing (all |)
```

Parameters

None

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#show evpn multi-homing all
ESI                               Access-IF      PE-IP-ADDRESS
=====
00:00:11:22:33:44:55:66:77:88   ce21/1       1.1.1.1
00:00:11:22:33:44:55:66:77:88   ----         2.2.2.2
Total number of entries are 2
```

[Table 1-9](#) explains the output fields.

Table 1-13: show evpn multi-homing all output details

Field	Description
ESI	An Ethernet segment has an unique nonzero identifier, called the Ethernet segment identifier (ESI). The ESI is encoded as a 10-octet integer that identifies this segment. When manually configuring an ESI value, the most significant octet, known as the type byte, must be 00. When a single-homed CE device is attached to an Ethernet segment, the entire ESI value is zero.
Access-IF	Map the access port ce21/1 for evpn.
PE-IP-ADDRESS	Address of the provider edge router in the interface.

show evpn multihoming-status

Use this command to display the status of multihoming on a VTEP.

Command Syntax

```
show evpn multihoming-status
```

Parameters

None

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#show evpn multihoming-status
Multihoming is ACTIVE in Hardware
```

show nvo vxlan route-count

Use this command to display the vxlan active route (MAC-IP.MAC-IPv6 and MAC-only) count information.

Command Syntax

```
show nvo vxlan route-count (|vnid <1-16777215>)
```

Parameters

<1-16777215> Range supported for VNID.

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3 and modified to include new fields – GW-IPv4, GW_IPv6, Prefix IPv4 and Prefix IPv6 in OcNOS version 1.3.5.

Example

```
#show nvo vxlan route-count
VXLAN Active route count information
=====
Max route count : 32768
Active route count: 7

Note: Prefix count refers only local routes
      It does not include evpn prefix routes
```

VNID Prefix	Total	MAONLY	MACIPv4	MACIPv6	GW MACIPv4	GW MACIPv6	Prefix IPv4
IPv6							
2000 0	3	1	1	1	0	0	0
1000 0	0	0	0	0	0	0	0
10002 1	4	0	0	0	1	1	1

Total number of entries are 3

[Table 1-10](#) explains the output fields.

Table 1-14: show nvo vxlan route-count output details

Field	Description
Max route count	Maximum number of route count in vxlan.
Active route count	Number of active route count in the interface.

Table 1-14: show nvo vxlan route-count output details

Field	Description
VNID	VNID is used to identify Layer 2 segments and to maintain Layer 2 isolation between the segments.
Total	Total number of entries for the interface.
MACONLY	The MAC-only route for the local interface appears in the VXLAN instance route table.
MACIPv4	IPv4 media access control (MAC) address for a default virtual gateway.
MACIPv6	IPv6 media access control (MAC) address for a default virtual gateway.

show nvo vxlan vni-name

Use this command to display the vxlan results based on vni-name.

Command Syntax

```
show nvo vxlan vni-name (WORD)
```

Parameters

WORD	VNI name of max size 10 character and should not be only numeric.
------	---

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#show nvo vxlan vni-name SITEA-PRO
VXLAN Information
=====
Codes: NW - Network Port
AC - Access Port
(u) - Untagged
VNID Vni-name Type Interface ESI Vlan DF-Status Src-addr Dst-addr

1 ----- NW ----- ----- ----- 10.0.1.1 10.0.6.8
1 ----- NW ----- ----- ----- 10.0.1.1 10.0.6.9
1 ----- NW ----- ----- ----- 10.0.1.1 10.0.3.1
1 ----- NW ----- ----- ----- 10.0.1.1 10.0.1.2
1 ----- NW ----- ----- ----- 10.0.1.1 10.0.5.1
1 ----- NW ----- ----- ----- 10.0.1.1 10.0.2.2
1 ----- NW ----- ----- ----- 10.0.1.1 10.0.2.1
1 SITEA-PRO AC xe7 - Single Homed port - 2 ----- -----
1 SITEA-PRO AC xe1 - Single Homed port - 1010 ----- -----
1 SITEA-PRO AC xe1 - Single Homed port - 100 ----- -----
1 SITEA-PRO AC xe1 - Single Homed port - 2020 ----- -----
1 SITEA-PRO AC po1 - Single Homed port - 100 ----- -----
1 SITEA-PRO AC po1 - Single Homed port - 2 ----- -----
1 SITEA-PRO AC po1 - Single Homed port - 200 ----- -----
1 SITEA-PRO AC xe8 - Single Homed port - ----- -----
1 SITEA-PRO AC po2 - Single Homed port - ----- -----
Total number of entries are 16
```

shutdown

Use this command to administratively shut down an NVO access interface.

Use the `no` form of this command to start an NVO access interface.

Command Syntax

```
shutdown  
no shutdown
```

Parameters

None

Default

The NVO access interface is running by default.

Command Mode

NVO access interface mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
#configure terminal  
(config)#nvo vxlan access-if port-vlan xe1 2  
(config-nvo-acc-if)#shutdown  
(config-nvo-acc-if)#exit
```

vxlan host-reachability-protocol evpn-bgp

Use this command to set the host reachable protocol to Ethernet-VPN over BGP. This defines BGP as the mechanism for host reachability advertisement.

Use the no form of this command to remove Ethernet-VPN as the host reachable protocol.

Command Syntax

```
vxlan host-reachability-protocol evpn-bgp NAME  
no vxlan host-reachability-protocol evpn-bgp
```

Parameters

NAME	Name of the VRF to carry VNID routes.
------	---------------------------------------

Default

No default value is specified for vxlan host-reachability-protocol command.

Command Mode

NVO mode

Applicability

This command was introduced before OcNOS version 1.3.

Example

```
(config)#nvo vxlan id 3  
(config-nvo)#vxlan host-reachability-protocol evpn-bgp Blue
```

vlan-xlate-1 large

Use this command to increase the size of the VLAN_XLATE_1_DOUBLE table to 20k. Internally, the BCM maintains VLAN_XLATE_1_DOUBLE table for access interfaces, L2vnid, and L3vnid. The default size of the table is 16k. After configuring the CLI, the table size is increased to 20k.

Use the `no` form of this command to change the VLAN_XLATE_1_DOUBLE table size to default.

Note: Reboot the system after configuring the CLI.

Command Syntax

```
vlan-xlate-1 large  
no vlan-xlate-1 large
```

Parameters

None

Default

None

Command Mode

Configuration Mode

Applicability

This command was introduced before OcNOS version 6.5.3.

Examples

```
(config)#vlan-xlate-1 large  
OcNOS(config)#commit  
%% System Reboot required, please save the config and reboot the board.  
OcNOS(config)#end  
OcNOS#
```

CHAPTER 2 VXLAN - IRB Commands

This chapter describes the VXLAN - IRB commands: These commands are applicable for TR3 and Maverick platform only.

- [evpn irb](#)
- [evpn irb-forwarding anycast-gateway-mac](#)
- [evpn irb-if-forwarding anycast-gateway-mac](#)
- [interface irb](#)
- [l3vni](#)
- [nvo vxlan irb](#)
- [show interface irb](#)
- [show evpn l3vni-map](#)
- [show evpn irb-status](#)
- [show running-config interface irb](#)

evpn irb

Use this command to configure default gateway behavior on a VTEP for particular VNID.

Use the no form this command to disable default gateway behavior on a VTEP for the particular VNID.

Note: Map an IRB interface to an L2 VNID. This IRB interface can have multiple IP address as configured in IRB IP address CLI and can serve all subnets attached to the L2 VNID.

Command Syntax

```
evpn <NAME>
no evpn <NAME>
```

Parameters

NAME	IRB interface name
------	--------------------

Command Mode

NVO Mode

Applicability

This command was introduced in OcNOS version 5.1.

Example

```
#config mode
(config)# nvo vxlan id 2000 ingress-replication inner-vid-disabled
(config-nvo)# evpn irb1
(config-nvo)# no evpn irb1
```

evpn irb-forwarding anycast-gateway-mac

Use this command to configure common anycast mac-address for all the IRB interfaces

Use the `no` form of this command to remove the global MAC address on all the the IRB interfaces.

Command Syntax

```
evpn irb-forwarding anycast-gateway-mac XXXX.XXXX.XXXX  
no evpn irb-forwarding anycast-gateway-mac
```

Parameters

XX-XX-XX-XX-XX-XX	Source MAC address (Option 1)
XX:XX:XX:XX:XX:XX	Source MAC address (Option 2)
XXXX.XXXX.XXXX	Source MAC address (Option 3)

Command Mode

Configuration Mode

Applicability

This command was introduced in OcNOS version 5.1.

Example

```
#configure terminal  
(config)#evpn irb-forwarding anycast-gateway-mac 0000.0000.1313  
Or  
(config)#evpn irb-forwarding anycast-gateway-mac 00:00:00:00:13:13  
Or  
(config)#evpn irb-forwarding anycast-gateway-mac 00-00-00-00-13-13  
(config)# no evpn irb-forwarding anycast-gateway-mac
```

evpn irb-if-forwarding anycast-gateway-mac

Use this command to enable an IRB interface to use the global anycast IRB mac-address.

Use the `no` form of this command to un-configure anycast MAC at IRB interface.

Command Syntax

```
evpn irb-if-forwarding anycast-gateway-mac
no evpn irb-if-forwarding anycast-gateway-mac
```

Parameters

None

Command Mode

IRB_IF_Mode

Applicability

This command was introduced in OcNOS version 5.1.

Example

```
#configure terminal
(config)# interface irb 1
(config-irb-if)# ip vrf forwarding vrfip
(config-irb-if)#evpn irb-if-forwarding anycast-gateway-mac
(config-irb-if)#no evpn irb-if-forwarding anycast-gateway-mac
```

interface irb

Use this command to configure logical IRB interface.

Use the `no` form of this command to un-configure logical IRB interface.

Command Syntax

```
interface irb<1-4094>
no interface irb<1-4094>
```

Parameters

<1-4094>	IRB interface number
----------	----------------------

Command Mode

Configure mode

Applicability

This command was introduced in OcNOS version 5.1.

Example

```
#configure terminal
(config)#interface irb1
(config)#no interface irb1
```

I3vni

Use this command to configure L3 Virtual Network Identifier for an ip vrf

Use the no form of this command to remove L3 Virtual Network Identifier

This identifies a tenant, with this one tenant can have L3VNI as its identifier and he can have multiple L2 networks identified with L2VNI's.

Note: L3 VNID cannot be same as L2 VNID.

Command Syntax

```
l3vni <L3 VNID>
no l3vni <L3 VNID>
```

Parameters

<1-16777215> L3 VNID. Cannot be same as L2 VNID

Command Mode

Configure VRF mode

Applicability

This command was introduced in OcNOS version 5.1.

Example

```
#configure terminal
(config)#ip vrf vrfip
(config-vrf)#l3vni 10002
(config-vrf)#no l3vni 10002
```

nvo vxlan irb

Use this command to enable IRB functionality.

Use the `no` form of this command to disable IRB functionality.

Note: Remove the existing L2 VNID configuration to enable IRB.

Command Syntax

```
nvo vxlan irb  
no nvo vxlan irb
```

Parameters

None

Command Mode

Configure mode

Applicability

This command was introduced in OcNOS version 5.1.

Example

```
#configure terminal  
(config)#nvo vxlan irb  
(config)#no nvo vxlan irb
```

show bgp l2vpn evpn

Use this command to display details about Layer 2 Virtual Private Network (L2VPN) Ethernet Virtual Private Network (EVPN) routes.

Note: A BGP EVPN route update received for an unreachable IP address is also listed by this command and as a best route. This is because the next hop tracking feature is not supported for the EVPN address family. However, the tunnel to this IP address is shown in unresolved state by the [show nvo vxlan tunnel](#) output.

Command Syntax

```
show bgp l2vpn evpn (((vrf WORD) | (rd WORD) |) ((prefix WORD) |) (detail| time|))
show bgp l2vpn evpn mac-ip ((vrf WORD) | (rd WORD) |)
show bgp l2vpn evpn mcast
show bgp l2vpn evpn multihoming es-route <(rd WORD) | (vrf WORD)>
show bgp l2vpn evpn multihoming ethernet-ad-per-evi <(rd WORD) | (vrf WORD)>
show bgp l2vpn evpn multihoming ethernet-ad-per-es <(rd WORD) | (vrf WORD)>
```

Parameters

vrf	Virtual Routing and Forwarding instance
WORD	VRF name
rd	Route distinguisher
WORD	Route distinguisher: ASN:nn or IP:nn
prefix-route	Shows detail of the Prefix-Route (Type:5))
detail	Detailed output of the route-path
time	Display learnt time for details for evpn routes.
mac-ip	Show detail of the MAC-IP route (Type:2)
mcast	Show detail of the Inclusive MULTICAST route (Type:3)
multihoming	Show multihoming information
peer-group	Dynamic peer-group

Command Mode

Exec mode

Applicability

This command was introduced in OcNOS version 5.1.

Example

```
show bgp l2vpn evpn detail
BGP route entry for prefix : [1]:[00:00:00:00:11:12:12:22:11:11]:[100]:[100]
Route-Distinguisher: 1.1.1.1:1
Flags : Valid, Selected, IBGP, Labelled
Nexthop : 1.1.1.1 MED value : 0
```

Community:

Extended Community: RT:100:1 Encapsulation:VxLAN ESI-Label:0

Weight :0, Local Preference :100

AS Path : Local

Origin : IGP

Last Update : Thu Apr 13 12:05:23 2023

Peer : 1.1.1.1

BGP route entry for prefix : [2]:[0]:[100]:[48,0000:1111:0000]:[32,10.12.11.12]:[100]

Route-Distinguisher: 1.1.1.1:1

Flags : Valid, Selected, IBGP, Labelled

Nexthop : 1.1.1.1 MED value : 0

Community:

Extended Community: RT:100:1 Encapsulation:VxLAN MAC_mob_seq:Static

Weight :0, Local Preference :100

AS Path : Local

Origin : IGP

Last Update : Thu Apr 13 12:05:23 2023

Peer : 1.1.1.1

Total number of prefixes 2

show bgp l2vpn evpn prefix-route

Use this command to display the Type-5 prefix remote routes.

Command Syntax

```
show bgp l2vpn evpn prefix-route <vrf WORD | rd Word>
```

Parameters

None

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 4.1.

Example

```
rtr1#show bgp l2vpn evpn prefix-route

RD[300:1]
ESI
GW-IP Address      Eth-Tag Prefix-Length   IP-Address
                    L3VNID    Nexthop      Encap
0                  45001     24            80.80.80.0
0.0.0.0             45001     24            45001      2.2.2.2      VXLAN
0                  45001     24            90.90.90.0
0.0.0.0             45001     24            45001      2.2.2.2      VXLAN
0                  45001     64            8001:::
::                 45001     64            45001      2.2.2.2      VXLAN
0                  45001     64            9001:::
::                 45001     64            45001      2.2.2.2      VXLAN
rtr1#
```

show interface irb

Use this command to display the current running configuration of IRB interface.

Command Syntax

```
show interface irb<1-4094>
```

Parameters

None

Command Mode

Exec mode

Applicability

This command was introduced in OcNOS version 5.1.

Example

```
rtr1#show interface irb1
Interface irb1
  Hardware is IRB  Current HW addr: 0000.0000.fff0
  Physical:(Not Applicable)  Logical:0000.0000.fff0
  Port Mode is Router
  Interface index: 700001
  Metric 0 mtu 1500
  Debounce timer: disable
  ARP ageing timeout 1500
  <UP,BROADCAST,RUNNING,MULTICAST>
  VRF Binding: Associated with vrf1
  Label switching is disabled
  Administrative Group(s): None
  DHCP client is disabled.
  Last Flapped: Never
  Statistics last cleared: 2019 Mar 14 17:57:06 (00:21:31 ago)
    inet 80.80.80.1/24 broadcast 80.80.80.255
    inet6 8001::1/64
    inet6 fe80::200:ff:fe00:fff10/64
    RX
      unicast packets 0 multicast packets 0 broadcast packets 0
      input packets 0 bytes 0
      jumbo packets 0
      undersize 0 oversize 0 CRC 0 fragments 0 jabbers 0
      input error 0
      input with dribble 0 input discard 0
      Rx pause 0
    TX
      unicast packets 0 multicast packets 0 broadcast packets 0
      output packets 0 bytes 0
      jumbo packets 0
      output errors 0 collision 0 deferred 0 late collision 0
      output discard 0
      Tx pause 0
rtr1#
```

show evpn l3vni-map

Use this command to display the L3 VNI, L2 VNI and IRB interface mapping.

Command Syntax

```
show evpn l3vni-map
```

Parameters

None

Command Mode

Exec mode

Applicability

This command was introduced in OcNOS version 5.1.

Example

```
rtr3#show evpn l3vni-map
L3VNI          L2VNI          IRB-interface
=====
45001          10            irb1
45001          20            irb2

rtr3#
```

show evpn irb-status

Use this command to display the status of the IRB on a VTEP.

Command Syntax

```
show evpn irb-status
```

Parameters

None

Command Mode

Exec mode

Applicability

This command was introduced before OcNOS version 5.1.

Example

```
#show evpn irb-status
IRB is ACTIVE in Hardware
```

show running-config interface irb

Use this command to display the current running configuration of IRB interface.

Command Syntax

```
show running-config interface irb<1-4094>
```

Parameters

None

Command Mode

Exec mode

Applicability

This command was introduced in OcNOS version 5.1.

Example

```
#show running-config interface irb1
!
interface irb1
ip vrf forwarding vrfip
ip address 144.144.144.1/24
ipv6 address 1201::1/48
evpn irb-if-forwarding anycast-gateway-mac
mac-address 0000.0000.1234
qos map-profile dscp-to-queue DSCP_QUE
qos map-profile queue-color-to-dscp QUE_DSCP
shutdown
!
```

CHAPTER 3 VXLAN Quality of Service Commands

This chapter describes the VXLAN commands for QoS (Quality of Service):

- [clear nvo vxlan tunnels](#)
- [cos queue](#)
- [dscp queue](#)
- [map qos-profile](#)
- [map qos-profile cos-to-queue](#)
- [map qos-profile queue-color-to-cos](#)
- [nvo vxlan disable-arp-storm-control-for-cpu](#)
- [nvo vxlan tunnel qos-map-mode cos-dscp](#)
- [qos profile cos-to-queue](#)
- [qos profile dscp-to-queue](#)
- [qos profile queue-color-to-cos](#)
- [qos profile queue-color-to-dscp](#)
- [queue cos](#)
- [queue dscp](#)

clear nvo vxlan tunnels

Use this command to clear the nvo vxlan tunnels to re-establish the tunnel after mapping/un-mapping the QoS profile to vxlan tunnel.

Command Syntax

```
clear nvo vxlan tunnels (|dst-ip A.B.C.D)
```

Parameters

dst-ip	VXLAN tunnel destination
A.B.C.D	destination IPv4 address

Command Mode

Exec mode

Applicability

This command was introduced in OcNOS version 1.3.

Example

```
#clear nvo vxlan tunnels dst-ip 2.2.2.2
```

Note: `clear nvo vxlan tunnels` This command will clear all the VXLAN tunnels destination.

`clear nvo vxlan tunnels dst-ip A.B.C.D` - This command to clear individual tunnel destination(i.e A.B.C.D).

cos queue

Use this command to configure user defined mapping for cos and queue.

Use the `no` form of this command to remove the mapping.

Command Syntax

```
cos <0-7> queue <0-7>
no cos <0-7>
```

Parameters

<0-7>	COS and Queue ranger
-------	----------------------

Default

Default cos and queue value is one-one default mapping if it is not configured.

Command Mode

QoS config mode

Applicability

This command was introduced in OcNOS version 1.3.

Example

```
(config)#qos profile cos-to-queue ac_port_ingress
(config-ingress-cos-map)#cos 1 queue 7
(config-ingress-cos-map)#no cos 1
```

dscp queue

Use this command to configure user defined mapping for DSCP to queue. This will be mapped with nvo VXLAN tunnel of remote VTEP.

Use the `no` form of this command to delete the mapping.

Command Syntax

```
dscp <0-63> queue <0-7> (color (green|yellow|red) |) (dscp <0-63> |)  
no dscp <0-63>
```

Parameters

<0-63>	DSCP
<0-7>	Queue number
color	Color to map
green	Set mapping for green packets
red	Set mapping for red packets
yellow	Set mapping for yellow packets
<0-63>	out DSCP value

Default

Default queue and cos value is one-one default mapping if it is not configured.

Command Mode

Ingress-dscp-map mode

Applicability

This command was introduced in OcNOS version 1.3.

Example

```
(config)#qos profile dscp-to-queue nw_profile  
(config-ingress-dscp-map)#dscp 50 queue 1  
(config-ingress-dscp-map)#no dscp 50
```

map qos-profile

Use this command to map (attach) the qos profile to an IRB interface.

Use the `no` form of this command to remove a profile.

Use the following qos profile type for mapping from/to on the IRB interface.

- dscp-to-queue for ingress traffic and
- queue-color-to-dscp profile for egress traffic

Removing the `map qos-profile`, applies the default profile to the IRB interface.

Note: Default profile is applied to all the IRB interface only when qos is enabled.

Command Syntax

```
map qos-profile (dscp-to-queue | queue-color-to-dscp) <NAME>
no map qos-profile (dscp-to-queue | queue-color-to-dscp) <NAME>
```

Parameters

NAME	Profile name
------	--------------

Default

By default, the default dscp-to-queue and queue-color-to-dscp profile is attached to all IRB interface.

Changing the value in the default profile, will impact both the IRB interfaces and L3 interfaces.

Command Mode

IRB_IF_Mode

Default

Default mapping between queue and DSCP value is one-one.

Applicability

This command is introduced in OcNOS version 5.1.

Example

```
#configure terminal
(config)#interface irb 1
(config-irb-if)# map qos-profile queue-color-to-dscp QUE_DSCP
(config-irb-if)# no map qos-profile queue-color-to-dscp QUE_DSCP

(config)#interface irb 1
(config-irb-if)# map qos-profile dscp-to-queue DSCP_QUE
(config-irb-if)# no map qos-profile dscp-to-queue DSCP_QUE
```

map qos-profile cos-to-queue

Use this command to map the cos-to-queue profile to vxlan access port on the local VTEP.

Use the `no` form of the command to remove the mapping.

Command Syntax

```
map qos-profile cos-to-queue NAME  
no map qos-profile cos-to-queue NAME
```

Parameters

NAME	Profile name
------	--------------

Default

None

Command Mode

NVO access interface mode

Applicability

This command was introduced in OcNOS version 4.2.

Example

```
(config)#nvo vxlan access-if port-vlan xe1 10  
(config-nvo-acc-if)#map qos-profile cos-to-queue ac_port_ingress  
(config-nvo-acc-if)#no map qos-profile cos-to-queue ac_port_ingress
```

map qos-profile queue-color-to-cos

Use this command to map the queue-color-to-cos profile to vxlan access port on the remote VTEP.

Use the `no` form of the command to remove the mapping.

Command Syntax

```
map qos-profile queue-color-to-cos NAME  
no map qos-profile queue-color-to-cos NAME
```

Parameters

NAME	Profile name
------	--------------

Default

None

Command Mode

NVO access interface mode

Applicability

This command was introduced in OcNOS version 4.2.

Example

```
(config)#nvo vxlan access-if port-vlan xe2 10  
(config-nvo-acc-if)#map qos-profile queue-color-to-cos ac_profile  
(config-nvo-acc-if)#no map qos-profile queue-color-to-cos ac_profile
```

nvo vxlan disable-arp-storm-control-for-cpu

Use this command to uplift the ARP/ND packet to CPU if packet is marked for DROP by storm control.

Use the `no` form of this command not to uplift the ARP/ND packet to CPU if marked for drop by storm-control. This is the default behavior.

Command Syntax

```
nvo vxlan disable-arp-storm-control-for-cpu  
no nvo vxlan disable-arp-storm-control-for-cpu
```

Parameters

None

Command Mode

Configure mode

Applicability

This command was introduced in OcNOS version 6.5.3.

Example

```
(config) #nvo vxlan disable-arp-storm-control-for-cpu
```

nvo vxlan tunnel qos-map-mode cos-dscp

Use this command to map QoS profile for network side to nvo vxlan tunnel. For outgoing/incoming traffic, you need to provide the direction with the keyword egress/ingress.

Use the `no` form of this command to delete the mapping.

You must give the [clear nvo vxlan tunnels](#) command to do the network port setting for QoS profile mapped.

Command Syntax

```
nvo vxlan tunnel qos-map-mode cos-dscp (ingress|egress) NAME  
no nvo vxlan tunnel qos-map-mode cos-dscp (ingress|egress)
```

Parameters

NAME	Profile name
ingress	Ingress direction
egress	Egress direction

Command Mode

Configure mode

Applicability

This command was introduced in OcNOS version 1.3.

Example

```
(config)#nvo vxlan tunnel qos-map-mode cos-dscp egress nw_profile  
(config)#no nvo vxlan tunnel qos-map-mode cos-dscp egress  
(config)#nvo vxlan tunnel qos-map-mode cos-dscp ingress nw_profile  
(config)#no nvo vxlan tunnel qos-map-mode cos-dscp ingress
```

qos profile cos-to-queue

Use this command to configure cos-to-queue profile. This profile has to be mapped to VXLAN access port on the local VTEP.

Use the `no` form of this command to delete the qos profile.

Command Syntax

```
qos profile cos-to-queue (NAME|default)  
no qos profile cos-to-queue NAME
```

Parameters

NAME	QoS profile name for cos-to-queue
default	Default name

Command Mode

Configure mode

Applicability

This command was introduced in OcNOS version 1.3.

Example

```
(config)#qos profile cos-to-queue ac_port_ingress  
(config)#no qos profile cos-to-queue ac_port_ingress
```

qos profile dscp-to-queue

Use this command to configure QoS profile for DSCP to Queue mapping. This profile will be mapped to nvo vxlan tunnel of remote VTEP. The created profile will support remarking of the data packets.

Use the `no` form of this command to delete the QoS profile

Command Syntax

```
qos profile dscp-to-queue {NAME|default}  
no qos profile dscp-to-queue NAME
```

Parameters

NAME	Profile name
default	Default name

Command Mode

Configure mode

Applicability

This command was introduced in OcNOS version 1.3.

Example

```
(config)#qos profile dscp-to-queue nw_profile  
(config-ingress-dscp-map)#exit  
(config)#no qos profile dscp-to-queue nw_profile  
(config)#+
```

qos profile queue-color-to-cos

Use this command to configure queue-color-to-cos profile. This profile has to be mapped to VXLAN access port on remote VTEP.

Use the `no` form of this command to delete the qos profile.

Command Syntax

```
qos profile queue-color-to-cos (NAME|default)  
no qos profile queue-color-to-cos NAME
```

Parameters

NAME	Profile name
default	Default name

Command Mode

Configure mode

Applicability

This command was introduced in OcNOS version 1.3.

Example

```
(config)#qos profile queue-color-to-cos ac_profile  
(config)#no qos profile queue-color-to-cos ac_profile
```

qos profile queue-color-to-dscp

Use this command to create a QoS profile queue-color-to-dscp. This profile will be mapped to nvo vxlan tunnel of local VTEP. The created profile supports remarking of the data packets.

Use the `no` form of this command to delete the profile.

Command Syntax

```
qos profile queue-color-to-dscp (NAME|default)  
no qos profile queue-color-to-dscp NAME
```

Parameters

NAME	Profile name
default	Default name

Default

None

Command Mode

Configure mode

Applicability

This command was introduced in OcNOS version 1.3.

Example

```
(config)#qos profile queue-color-to-dscp nw_profile  
(config-egress-dscp-map)#exit  
(config)#no qos profile queue-color-to-dscp nw_profile
```

queue cos

Use this command to configure user defined mapping for queue and cos.

Use the no form of this command to remove the mapping.

Command Syntax

```
queue <0-7> (color(green|yellow|red|all) |) cos <0-7>
no queue <0-7> (color(green|yellow|red|all) |)
```

Parameters

<0-7>	Queue and cos range
color	Color to map
all	Set mapping for all packets
green	Set mapping for green packets
red	Set mapping for red packets
yellow	Set mapping for yellow packets

Default

Default queue and cos value is one-one default mapping if it is not configured.

Command Mode

QoS config mode

Applicability

This command was introduced in OcNOS version 1.3.

Example

```
(config)#qos profile queue-color-to-cos ac_profile
(config-egress-cos-map)#queue 5 cos 2
(config-egress-cos-map)#no queue 5
```

queue dscp

Use this command to configure user-defined mapping for queue to DSCP. This will be mapped with nvo VXLAN tunnel of local VTEP.

Use the `no` form of this command to remove the queue-to-DSCP mapping.

Command Syntax

```
queue <0-7> (color(green|yellow|red|all)!) dscp <0-63>
no queue <0-7> (color(green|yellow|red|all)!)
```

Parameters

<0-7>	Queue number
<0-63>	DSCP
color	Color to map
all	Set mapping for all packets
green	Set mapping for green packets
red	Set mapping for red packets
yellow	Set mapping for yellow packets

Default

Default queue and cos value is one-one default mapping if it is not configured.

Command Mode

QoS config mode

Applicability

This command was introduced in OcNOS version 1.3.

Example

```
(config)#qos profile queue-color-to-dscp nw_profile
(config-egress-dscp-map)# queue 1 dscp 63
(config-egress-dscp-map)#no queue 1
```

Index

A

arp-cache disable 497
arp-nd flood-suppress 498, 579

B

begin modifier 15
BGP community value
 command syntax 13
braces
 command syntax 12

C

clear mac address table dynamic vxlan 499
clear nvo vxlan counters 501, 577
command abbreviations 11
command completion 11
command line
 errors 11
 help 10
 keyboard operations 14
command modes 18
configure 18
exec 18
interface 18
privileged exec 18
router 18
command negation 12
command syntax
 ? 13
 . 13
 () 12
 {} 12
 | 12
A.B.C.D/M 13
AA:NN 13
BGP community value 13
braces 12
conventions 12
curly brackets 12
HH:MM:SS 13
IFNAME 13
interface name 13
IPv4 address 13
IPv6 address 13
LINE 13
lowercase 12
MAC address 13
monospaced font 12
numeric range 13
parentheses 12
parentheses 12
period 13

question mark 13
square brackets 13
time 13
uppercase 12
variable placeholders 13
vertical bars 12
WORD 13
X:X::X:X 13
X:X::X:X/M 13
XX:XX:XX:XX:XX:XX 13
configure mode 18
curly brackets
 command syntax 12

D

dynamic-learning disable 505, 557, 568

E

evpn esi holdtime 507
evpn multi-homing enable 508, 560, 573
exec command mode 18

I

IFNAME 13
Interface irb 511
interface mode 18
IPv4 address
 command syntax 13
IPv6 address
 command syntax 13

L

LINE 13
load-balance rtag7 vxlan inner-l2 512
load-balance rtag7 vxlan inner-l3 513

M

mac 514, 562
MAC address
 command syntax 13
mac vrf 515, 562
mac-holdtime 516, 562
map vnid 517

N

nd-cache disable 533, 564
no nvo vxlan 519
nvo 523
nvo vxlan 520
nvo vxlan id 521, 525
nvo vxlan irb 527
nvo vxlan mac-ageing-time 543, 566

nvo vxlan tunnel qos-map-mode 527
nvo vxlan vtep-ip-global 527

P

parentheses
 command syntax 12
parentheses
 command syntax 12
period
 command syntax 13
port breakout configuration 256
Port Mapping 26
privileged exec mode 18

Q

question mark
 command syntax 13

R

router mode 18

S

show commands 15
 exclude modifier 16
 include modifier 16
 redirect modifier 17
show interface irb 552
show nvo vxlan 528, 563
show nvo vxlan arp-cache 531
show nvo vxlan counters access-port 533, 564

show nvo vxlan counters network-port 536, 564
show nvo vxlan interface counters 538
show nvo vxlan mac-table 538, 564
show nvo vxlan nd-cache 541, 566
show nvo vxlan static host state 543, 566
show nvo vxlan tunnel 545
show running-config nvo vxlan 546
shutdown 516, 552, 553, 562
square brackets
 command syntax 13

T

time
 command syntax 13
Tunnel End Point 24

U

unicast configuration 26

V

vertical bars
 command syntax 12
VXLAN Architecture 22
VXLAN Commands 495, 556, 567
vxlan host-reachability-protocol evpn-bgp 554
VXLAN Unicast Configuration 26

W

WORD 13