



**OcNOS®**

**Open Compute  
Network Operating System  
for Data Centers  
Version 6.5.3**

**NetConf Command Reference**

**October 2024**

---

© 2024 IP Infusion Inc. All Rights Reserved.

This documentation is subject to change without notice. The software described in this document and this documentation are furnished under a license agreement or nondisclosure agreement. The software and documentation may be used or copied only in accordance with the terms of the applicable agreement. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or any means electronic or mechanical, including photocopying and recording for any purpose other than the purchaser's internal use without the written permission of IP Infusion Inc.

IP Infusion Inc.  
3979 Freedom Circle  
Suite 900  
Santa Clara, California 95054  
<http://www.ipinfusion.com/>

For support, questions, or comments via E-mail, contact:

[support@ipinfusion.com](mailto:support@ipinfusion.com)

Trademarks:

IP Infusion and OcNOS are trademarks or registered trademarks of IP Infusion. All other trademarks, service marks, registered trademarks, or registered service marks are the property of their respective owners.

Use of certain software included in this equipment is subject to the IP Infusion, Inc. End User License Agreement at <http://www.ipinfusion.com/license>. By using the equipment, you accept the terms of the End User License Agreement.

# Contents

Preface .....	79
IP Maestro Support .....	79
Audience .....	79
Conventions .....	79
Related Documentation .....	79
Feature Availability .....	79
Support .....	79
Comments .....	80
CHAPTER 1 NetConf Reference .....	45
IPI-MANAGEMENT-SERVER .....	45
Configure feature enabled .....	45
Configure management port .....	45
Configure port .....	46
Configure enable .....	46
Configure retry max attempts .....	47
Configure retry interval .....	47
Configure translation mode .....	48
Configure debug enable .....	48
Configure feature netconf ssh .....	49
Configure vrf name .....	49
Configure feature netconf tls .....	50
Configure netconf-tls-config feature-netconf-tls .....	50
Configure ssh port .....	51
Configure tls port .....	51
Configure notification-cache feature-enabled .....	52
Configure max cache notifications .....	52
Configure cache period .....	53
IPI-STREAMING-TELEMETRY .....	53
Configure feature enabled .....	53
Configure retry interval .....	54
Configure gnmi severity .....	55
Configure gnmi debug .....	55
Configure name .....	56
Configure encoding .....	57
Configure sensor group .....	57
Configure group id .....	58
Configure sensor group id .....	59
Configure path .....	60
Configure vrf name .....	61
Configure destination port .....	61
IPI-MANAGEMENT-SERVER-NOTIFICATION .....	62
Configure severity .....	62
IPI-VRF .....	63
Configure instance name .....	63

---

Configure instance type . . . . .	64
Configure description . . . . .	64
Configure router id . . . . .	65
Configure evpn layer3 network id . . . . .	66
Configure snmp context name . . . . .	66
clear router-id . . . . .	67
clear router-id vrf (VRFNAME ) . . . . .	67
<b>IPI-INTERFACE . . . . .</b>	<b>67</b>
Configure name . . . . .	67
Configure enable switchport . . . . .	68
Configure vrf name . . . . .	68
Configure vr name . . . . .	69
Configure mtu . . . . .	69
Configure allow first frame . . . . .	70
Configure dot1ad ether type . . . . .	70
Configure description . . . . .	71
Configure shutdown . . . . .	71
Configure if loopback . . . . .	72
clear interface (IFNAME ) counters . . . . .	72
<b>IPI-IF-ETHERNET . . . . .</b>	<b>73</b>
Configure duplex mode . . . . .	73
Configure mac address . . . . .	73
Configure secondary mac address . . . . .	74
Configure port speed . . . . .	74
Configure enable rcv . . . . .	75
Configure enable rcv . . . . .	76
Configure enable snd . . . . .	76
<b>IPI-IF-IP . . . . .</b>	<b>77</b>
Configure primary ip addr . . . . .	77
Configure enable dhcp ip address . . . . .	77
Configure ip addr label . . . . .	78
Configure ipv4 unnumbered if name . . . . .	79
Configure remote address . . . . .	79
Configure primary anycast . . . . .	80
Configure ip address . . . . .	80
Configure ip label . . . . .	81
Configure secondary anycast . . . . .	81
Configure enable auto config . . . . .	82
Configure ipv6 unnumbered if name . . . . .	83
Configure enable dhcp ipv6 address . . . . .	83
Configure enable dhcp temporary ipv6 address . . . . .	84
Configure dhcp address prefix length . . . . .	84
Configure ipv6 address . . . . .	85
Configure anycast . . . . .	85
Configure disable ip forwarding . . . . .	86
Configure disable ipv6 forwarding . . . . .	86
Configure router id . . . . .	87

Configure enable auto router id selection . . . . . 87

Configure default vrf enable icmp broadcast . . . . . 87

Configure disable ip vrf forwarding . . . . . 88

Configure disable ipv6 vrf forwarding . . . . . 88

Configure enable icmp broadcast . . . . . 89

**IPI-IF-EXTENDED . . . . . 89**

Configure protected port . . . . . 89

Configure name . . . . . 90

Configure extended protected-port . . . . . 90

Configure link flap error disable . . . . . 91

Configure storm control error disable . . . . . 91

Configure mac move limit error disable . . . . . 92

Configure disable snmp trap link status . . . . . 92

Configure mac move priority . . . . . 93

Configure mau default type . . . . . 93

Configure debounce time . . . . . 94

Configure ucmp port . . . . . 94

Configure enable re routing . . . . . 95

Configure enable speed . . . . . 95

Configure enable queue drops . . . . . 96

Configure warning threshold . . . . . 97

Configure aclif type . . . . . 97

Configure linkup debounce time . . . . . 98

Configure l2cp type . . . . . 98

Configure forward err correction . . . . . 99

Configure load interval . . . . . 100

Configure bcast value . . . . . 100

Configure bcast rate limit format . . . . . 101

Configure mcast value . . . . . 102

Configure mcast rate limit format . . . . . 103

Configure dlf bcast value . . . . . 103

Configure dlf bcast rate limit format . . . . . 104

Configure error disable stp bpdu guard . . . . . 105

Configure reason . . . . . 105

Configure link flap timer interval . . . . . 106

Configure storm control timer interval . . . . . 107

Configure error-disable reason . . . . . 107

Configure error-disable error-disable-stp-bpdu-guard . . . . . 108

Configure timeout interval . . . . . 108

Configure mac move limit . . . . . 109

Configure mode . . . . . 109

Configure src . . . . . 110

Configure multicast interface . . . . . 110

Configure dst . . . . . 111

Configure checksum enable . . . . . 111

Configure tos byte . . . . . 112

Configure ttl . . . . . 112

---

Configure path mtu enable. . . . .	113
Configure dst mac address . . . . .	113
Configure gre key. . . . .	114
Configure hit based ageing . . . . .	114
clear interface (IFNAME) cpu counters. . . . .	115
clear interface (IFNAME) fec. . . . .	115
clear interface IFNAME error-disable. . . . .	115
clear I2protocol interface (IFNAME) counters (peer tunnel discard tunnel-discard). . . . .	116
<b>IPI-SYSTEM . . . . .</b>	<b>116</b>
Configure hostname. . . . .	116
Configure timezone name . . . . .	117
<b>IPI-NETWORK-SERVICES-MANAGER . . . . .</b>	<b>117</b>
Configure options. . . . .	117
Configure pkt-mgr options . . . . .	118
Configure module name. . . . .	118
debug nsm ((addressmonitor bfd events hal events hal ipc linkmonitor packet packet detail packet recv packet recv detail packet send packet send detail vxlan ipsec all)) . . . . .	119
no debug nsm ((addressmonitor bfd events hal events hal ipc linkmonitor packet packet detail packet recv packet recv detail packet send packet send detail vxlan ipsec all)) . . . . .	119
debug hsl	
(general ifmgr bridge msg fib fdb devdrv pktdrv platform pbr bfd lacp qos helper rbridge nvo ofl mlog srv6 ptp extphy) {all default info debug warn error fatal admin counter pkt} . . . . .	120
no debug hsl	
(general ifmgr bridge msg fib fdb devdrv pktdrv platform pbr bfd lacp qos helper rbridge nvo ofl mlog srv6 ptp extphy) {all default info debug warn error fatal admin counter pkt} . . . . .	120
debug pktmgr (I2 protocol cfm I2 protocol eap I2 protocol efm I2 protocol igmp-snoop I2 protocol lacp I2 protocol lldp I2 protocol mldp-snoop I2 protocol mstp I2 protocol ptp I2 protocol all) . . . . .	121
no debug pktmgr . . . . .	121
debug pktmgr enable . . . . .	121
debug pktmgr disable. . . . .	121
debug pktmgr stats . . . . .	122
debug pktmgr (stats pkt-errors) . . . . .	122
clear nsm ipc stats . . . . .	122
clear nsm server ipc-stats . . . . .	122
snmp restart nsm . . . . .	123
<b>IPI-BRIDGE . . . . .</b>	<b>123</b>
Configure enable . . . . .	123
Configure protocol . . . . .	123
Configure instance name. . . . .	124
Configure disable dynamic learning. . . . .	124
Configure I2 protocol destination mac . . . . .	125
Configure spanning tree protocol status . . . . .	126
Configure disable mac learning . . . . .	126
Configure interface name. . . . .	127
clear mac address-table (multicast) cvlan VID svlan VID bridge <1-32> . . . . .	128
clear mac address-table (multicast) (interface IFNAME) (address MACADDR) (vlan VID) bridge <1-32> . . . . .	128

---

---

clear mac address-table dynamic cvlan VID svlan VID bridge <1-32> . . . . .	129
clear mac address-table dynamic (interface IFNAME ) (address MACADDR ) (vlan VID ) bridge <1-32> . . . . .	130
clear allowed-ethertype statistics (IFNAME ) . . . . .	130
clear mac address-table dynamic interface IFNAME instance INST bridge <1-32> . . . . .	130
<b>IPI-VLAN . . . . .</b>	<b>131</b>
Configure disable mac learning . . . . .	131
Configure vlan id . . . . .	132
Configure type . . . . .	133
Configure instance name . . . . .	134
Configure instance type . . . . .	135
Configure secondary vlan . . . . .	135
Configure mac address . . . . .	136
Configure ipv4 address . . . . .	137
Configure ether type . . . . .	137
Configure group id . . . . .	138
Configure port name . . . . .	139
Configure vlan-reservation vlan-id . . . . .	139
Configure disable vlan classifier feature . . . . .	140
Configure disable port security . . . . .	140
Configure vlan xlate 1 . . . . .	140
Configure table name . . . . .	141
Configure cvlan cfi . . . . .	141
Configure untagged ep . . . . .	143
<b>IPI-PORT-VLAN . . . . .</b>	<b>144</b>
Configure isolated vlan id . . . . .	144
Configure cvlan registration table . . . . .	145
Configure interface mode . . . . .	145
Configure name . . . . .	146
Configure acceptable frame type . . . . .	146
Configure switched-vlan acceptable-frame-type . . . . .	147
Configure disable native vlan . . . . .	148
Configure remove default vlan . . . . .	148
Configure ingress filter . . . . .	149
Configure vlan id . . . . .	150
Configure vlans vlan-id . . . . .	150
Configure vlans vlan-id . . . . .	151
Configure vlans vlan-id . . . . .	152
Configure native vlan id . . . . .	152
Configure translated svlan id . . . . .	153
Configure original svlan id . . . . .	154
Configure cvlan id . . . . .	155
Configure svlan id . . . . .	156
Configure logging . . . . .	157
Configure mode . . . . .	157
Configure port-security mode . . . . .	158
Configure maximum limit . . . . .	158

---

Configure mac address . . . . .	159
Configure vlan-mapping cvlan-id . . . . .	160
Configure vlan-mapping svlan-id . . . . .	160
Configure cvlan-svlan-mappings svlan-id . . . . .	161
Configure private-vlan mode . . . . .	162
Configure associate vlan id . . . . .	163
Configure mapping vlan id . . . . .	163
Configure association trunk vlan id . . . . .	164
Configure instance name . . . . .	165
IPI-VLAN-XC . . . . .	166
Configure xconnect name . . . . .	166
Configure disable . . . . .	166
Configure port endpoint 1 . . . . .	167
Configure backup endpoint 1 . . . . .	167
Configure backup endpoint 2 . . . . .	168
Configure revertive . . . . .	168
Configure link fault pass through enable . . . . .	169
Configure vlan endpoint 1 . . . . .	169
Configure outer vlan range . . . . .	170
Configure inner vlan range . . . . .	171
clear cross-connect counters (NAME ) . . . . .	171
IPI-XSTP . . . . .	172
Configure ageing time . . . . .	172
Configure instance name . . . . .	172
Configure enable cisco interoperability . . . . .	173
Configure forwarding delay . . . . .	174
Configure hello time . . . . .	174
Configure max age . . . . .	175
Configure max hops . . . . .	176
Configure bridge priority . . . . .	176
Configure transmit hold count . . . . .	177
Configure enable bpdu filter . . . . .	178
Configure enable bpdu guard . . . . .	178
Configure enable error disable timeout . . . . .	179
Configure force version . . . . .	180
Configure path cost method . . . . .	181
Configure bridge type . . . . .	181
Configure disable spanning tree . . . . .	182
Configure network-instances instance-name . . . . .	183
Configure bridge forwarding . . . . .	184
Configure enable shutdown . . . . .	185
Configure network-instances instance-name . . . . .	186
Configure region name . . . . .	187
Configure revision number . . . . .	187
Configure vlan id . . . . .	188
Configure disable spanning tree . . . . .	189
Configure name . . . . .	189

---

---

Configure instance id . . . . .	190
Configure network-instances instance-name . . . . .	191
Configure instance type . . . . .	192
Configure instance id . . . . .	193
Configure mst-instance bridge-priority . . . . .	193
Configure mst-instance bridge-priority . . . . .	194
Configure interfaces name . . . . .	195
Configure interfaces name . . . . .	196
Configure interfaces name . . . . .	197
Configure interfaces name . . . . .	198
Configure path cost . . . . .	199
Configure interface path-cost . . . . .	200
Configure port priority . . . . .	201
Configure interface port-priority . . . . .	202
Configure vlans vlan-id . . . . .	203
Configure vlan bridge-priority . . . . .	203
Configure port-bridge path-cost . . . . .	204
Configure port-bridge port-priority . . . . .	205
Configure vlan path-cost . . . . .	206
Configure vlan port-priority . . . . .	207
Configure vlan vlan-id . . . . .	208
Configure interface hello-time . . . . .	209
Configure port configuration . . . . .	209
Configure enable automatic edge detection . . . . .	210
Configure bpdu guard . . . . .	210
Configure bpdu filter . . . . .	211
Configure enable root guard . . . . .	211
Configure link type . . . . .	212
Configure enable restricted domain role . . . . .	212
Configure enable restricted role . . . . .	213
Configure enable restricted tcn . . . . .	213
Configure enable instance restricted tcn . . . . .	214
Configure mst-instance enable-instance-restricted-tcn . . . . .	214
Configure enable instance restricted role . . . . .	215
Configure mst-instance enable-instance-restricted-role . . . . .	216
Configure vlan enable-restricted-role . . . . .	216
Configure vlan enable-restricted-tcn . . . . .	217
Configure customer-spanning-tree bridge-priority . . . . .	218
Configure customer-spanning-tree max-age . . . . .	218
Configure customer-spanning-tree hello-time . . . . .	219
Configure forward delay . . . . .	220
Configure customer-spanning-tree transmit-hold-count . . . . .	220
Configure customer-edge path-cost . . . . .	221
Configure customer-edge port-priority . . . . .	222
Configure svlan id . . . . .	222
Configure vlan port-priority . . . . .	223
Configure options . . . . .	224

---

---

debug (mstp protocol mstp protocol detail mstp timer mstp timer detail mstp packet tx mstp packet rx mstp cli mstp bpdu mstp mceec mstp all) . . . . .	224
no debug (mstp protocol mstp protocol detail mstp timer mstp timer detail mstp packet tx mstp packet rx mstp cli mstp bpdu mstp mceec mstp all) . . . . .	225
clear spanning-tree detected protocols bridge <1-32> . . . . .	225
clear spanning-tree detected protocols interface INTERFACE . . . . .	225
clear spanning-tree statistics (spbm <1-63>) bridge <1-32> . . . . .	226
clear spanning-tree statistics interface IFNAME vlan <2-4094> bridge <1-32>. . . . .	226
clear spanning-tree statistics interface IFNAME bridge <1-32>. . . . .	227
clear spanning-tree statistics bridge <1-32> . . . . .	227
clear spanning-tree statistics vlan <2-4094> bridge <1-32> . . . . .	227
clear spanning-tree statistics interface IFNAME (spbm <1-63>) bridge <1-32> . . . . .	228
snmp restart mstp . . . . .	228
<b>IPI-IF-AGGREGATE . . . . .</b>	<b>228</b>
Configure aggregate id . . . . .	228
Configure lacp mode . . . . .	229
Configure min links . . . . .	230
Configure min bandwidth . . . . .	230
<b>IPI-LACP . . . . .</b>	<b>231</b>
Configure system priority . . . . .	231
Configure options . . . . .	231
Configure port priority . . . . .	232
Configure timeout. . . . .	232
Configure bridge type. . . . .	233
Configure force up . . . . .	234
Configure agg force up . . . . .	234
snmp restart lacp . . . . .	235
clear lacp (<1-65535> ) counters . . . . .	235
debug lacp (event cli timer packet rx tx sync ha all) . . . . .	235
no debug lacp (event cli timer packet rx tx sync ha all) . . . . .	235
<b>IPI-LLDPV2 . . . . .</b>	<b>236</b>
Configure enable . . . . .	236
Configure notification interval. . . . .	236
Configure port description . . . . .	237
Configure system description. . . . .	237
Configure system name. . . . .	238
Configure system capabilities . . . . .	238
Configure management address . . . . .	238
Configure port vlan id. . . . .	239
Configure port protocol vlan id . . . . .	239
Configure vlan name . . . . .	240
Configure protocol identifier . . . . .	240
Configure vid digest . . . . .	241
Configure management vlan id . . . . .	241
Configure link aggregation . . . . .	242
Configure dcb exchange . . . . .	242
Configure mac phy. . . . .	243

---

Configure max mtu size . . . . .	243
Configure locally assigned chassis id . . . . .	244
Configure options . . . . .	244
Configure disable lldp agent . . . . .	244
Configure agent circuit id . . . . .	245
Configure med device type . . . . .	245
Configure local name . . . . .	246
Configure agent type . . . . .	246
Configure enable tx rx . . . . .	247
Configure dcbx enable . . . . .	248
Configure reinit delay . . . . .	248
Configure message tx interval . . . . .	249
Configure message tx hold multiplier . . . . .	250
Configure message fast tx . . . . .	250
Configure tx credit max . . . . .	251
Configure tx fast init . . . . .	252
Configure neighbor timer . . . . .	253
Configure port timer . . . . .	254
Configure port address . . . . .	255
Configure chassis id . . . . .	255
Configure port id . . . . .	256
Configure name . . . . .	257
Configure basic-management system-description . . . . .	258
Configure basic-management system-name . . . . .	258
Configure basic-management system-capabilities . . . . .	259
Configure basic-management management-address . . . . .	260
Configure ieee-8021-org-specific port-vlan-id . . . . .	261
Configure ieee-8021-org-specific port-protocol-vlan-id . . . . .	261
Configure ieee-8021-org-specific vlan-name . . . . .	262
Configure ieee-8021-org-specific protocol-identifier . . . . .	263
Configure ieee-8021-org-specific vid-digest . . . . .	264
Configure ieee-8021-org-specific management-vlan-id . . . . .	265
Configure ieee-8021-org-specific link-aggregation . . . . .	265
Configure ieee-8021-org-specific dcb-exchange . . . . .	266
Configure ieee-8023-org-specific mac-phy . . . . .	267
Configure ieee-8023-org-specific max-mtu-size . . . . .	268
Configure network policy . . . . .	268
Configure location . . . . .	269
Configure inventory . . . . .	270
Configure media capabilities . . . . .	271
debug lldp (event rx tx message ha all) . . . . .	271
no debug lldp (event rx tx message ha all) . . . . .	272
clear lldp counters ((IFNAME )). . . . .	272
snmp restart lldp . . . . .	272
<b>IPI-RIB . . . . .</b>	<b>273</b>
Configure fib retain . . . . .	273
Configure max ecmp paths . . . . .	273

---

Configure max static routes . . . . .	273
Configure max fib routes . . . . .	274
Configure ipv4 enable bfd all interfaces. . . . .	274
Configure ipv6 enable bfd all interfaces. . . . .	275
Configure rib options . . . . .	275
Configure ipv4 routing options . . . . .	276
Configure ipv6 routing options . . . . .	276
Configure interface name. . . . .	276
Configure bfd state. . . . .	277
Configure description. . . . .	277
Configure destination prefix . . . . .	278
Configure distance . . . . .	279
Configure gateway address . . . . .	280
Configure route bfd-state . . . . .	281
Configure track id. . . . .	281
Configure interface-routes interface-name . . . . .	282
Configure interface-route description. . . . .	283
Configure gateway-interface-routes interface-name . . . . .	283
Configure gateway-interface-route description . . . . .	284
Configure source prefix . . . . .	285
Configure ipv4 enable bfd . . . . .	286
Configure ipv6 enable bfd . . . . .	286
snmp restart rib . . . . .	287
clear ip route kernel . . . . .	287
clear ip kernel route . . . . .	287
clear ipv6 route kernel . . . . .	288
clear ip route * . . . . .	288
clear ip route A.B.C.D/M . . . . .	288
clear ipv4 route * . . . . .	288
clear ipv4 route A.B.C.D/M. . . . .	288
clear ipv6 route * . . . . .	289
clear ipv6 route X:X::X:X/M . . . . .	289
debug rib (all events packet packet send packet rcv packet detail packet send detail packet rcv detail nsm bfd monitor hal events hal ipc) . . . . .	289
no debug rib (all events packet packet send packet rcv packet detail packet send detail packet rcv detail nsm bfd monitor hal events hal ipc). . . . .	289
debug ip routing (all add-route delete-route mod-route) . . . . .	290
no debug ip routing (all add-route delete-route mod-route) . . . . .	290
debug ipv6 routing (all add-route delete-route mod-route). . . . .	290
no debug ipv6 routing (all add-route delete-route mod-route) . . . . .	291
IPI-RIB-VRF . . . . .	291
Configure ipv4 enable bfd all interfaces. . . . .	291
Configure ipv6 enable bfd all interfaces. . . . .	292
Configure enable global table lookup. . . . .	292
Configure interface name. . . . .	293
Configure track id. . . . .	294
Configure bfd state. . . . .	295

---

Configure instance type . . . . .	296
Configure description . . . . .	296
Configure instance name . . . . .	298
Configure destination prefix . . . . .	299
Configure distance . . . . .	300
Configure source prefix . . . . .	301
Configure destination prefix . . . . .	302
Configure enable ipv6 global table lookup . . . . .	303
Configure gateway address . . . . .	304
Configure gateway address . . . . .	305
Configure route bfd-state . . . . .	305
Configure out-interfaces interface-name . . . . .	306
Configure out-interface description . . . . .	307
Configure interface-routes interface-name . . . . .	308
Configure interface-route description . . . . .	309
Configure protocol type . . . . .	310
clear ip route vrf NAME * . . . . .	311
clear ip route vrf NAME A.B.C.D/M . . . . .	311
clear ipv4 route vrf NAME * . . . . .	312
clear ipv4 route vrf NAME A.B.C.D/M . . . . .	312
clear ipv6 route vrf NAME * . . . . .	312
clear ipv6 route vrf NAME X:X::X:X/M . . . . .	313
IPI-OSPF . . . . .	313
Configure area interface config mode . . . . .	313
Configure enable multi instance capability . . . . .	313
Configure grace period . . . . .	314
Configure max grace period . . . . .	314
Configure disable all neighbors . . . . .	315
Configure disable neighbor . . . . .	315
Configure ospf id . . . . .	316
Configure router id . . . . .	316
Configure process router-id . . . . .	317
Configure flood reduction . . . . .	317
Configure rfc1583 compatibility . . . . .	318
Configure database summary . . . . .	318
Configure bfd enable all interfaces . . . . .	319
Configure log adjacency changes . . . . .	319
Configure shutdown . . . . .	320
Configure area border type . . . . .	320
Configure reference bandwidth . . . . .	321
Configure max database descriptors . . . . .	321
Configure p2p rfc incompatible . . . . .	322
Configure context name . . . . .	322
Configure passive interface all . . . . .	323
Configure passive mode . . . . .	323
Configure address . . . . .	324
Configure originate . . . . .	325

---

---

Configure route map . . . . .	325
Configure disable graceful restart . . . . .	326
Configure disable opaque lsa . . . . .	327
Configure enable vrf lite . . . . .	327
Configure link local signaling . . . . .	328
Configure maximum areas number . . . . .	328
Configure disable advertise . . . . .	329
Configure authentication type . . . . .	330
Configure default cost . . . . .	330
Configure shortcut . . . . .	331
Configure name . . . . .	332
Configure cost . . . . .	332
Configure network type . . . . .	333
Configure passive . . . . .	334
Configure priority . . . . .	335
Configure area id . . . . .	336
Configure enabled . . . . .	336
Configure filter out . . . . .	337
Configure dead interval . . . . .	338
Configure hello interval . . . . .	339
Configure retransmission interval . . . . .	340
Configure no summary . . . . .	341
Configure is stub . . . . .	342
Configure nssa enable . . . . .	342
Configure stability interval . . . . .	343
Configure filter-in name . . . . .	345
Configure filter-out name . . . . .	346
Configure filter-in name . . . . .	346
Configure filter-out name . . . . .	347
Configure ip address . . . . .	348
Configure host cost . . . . .	349
Configure instance id . . . . .	350
Configure area-ranges address . . . . .	350
Configure remote router id . . . . .	351
Configure fall over . . . . .	352
Configure key . . . . .	353
Configure authentication authentication-type . . . . .	354
Configure message digest id . . . . .	354
Configure transmit delay . . . . .	356
Configure limit type . . . . .	357
Configure exit interval . . . . .	358
Configure keep all paths . . . . .	358
Configure fast-reroute route-map . . . . .	359
Configure idx . . . . .	360
Configure default distance . . . . .	360
Configure intra area distance . . . . .	361
Configure access control list . . . . .	362

---

Configure summary-addresses address . . . . .	363
Configure not advertise . . . . .	363
Configure tag . . . . .	364
Configure filter-in access-control-list . . . . .	365
Configure access control list isis . . . . .	365
Configure access control list bgp . . . . .	366
Configure access control list rip . . . . .	366
Configure access control list static. . . . .	367
Configure access control list connected . . . . .	368
Configure access control list kernel . . . . .	368
Configure ospf process id . . . . .	369
Configure primary domain id address . . . . .	370
Configure primary domain id hex. . . . .	370
Configure secondary domain id address . . . . .	371
Configure secondary domain id hex . . . . .	372
Configure neighbors address. . . . .	373
Configure poll interval . . . . .	373
Configure termination hold interval . . . . .	374
Configure min arrival interval . . . . .	375
Configure max delay . . . . .	375
Configure min delay . . . . .	376
Configure default metric. . . . .	377
Configure protocol . . . . .	378
Configure metric. . . . .	378
Configure ospf-processes ospf-process-id . . . . .	379
Configure metric type. . . . .	380
Configure isis process id . . . . .	381
Configure isis-process metric. . . . .	381
Configure include stub . . . . .	382
Configure enable max router lsa . . . . .	383
Configure on startup include stub . . . . .	384
Configure max on startup. . . . .	385
Configure ospfv2-processes ospf-process-id. . . . .	385
Configure ospfv2-processes ospf-process-id. . . . .	386
Configure multi-areas area-id . . . . .	387
Configure neighbor . . . . .	387
Configure rate limit. . . . .	388
Configure bfd . . . . .	390
Configure retransmission. . . . .	392
Configure debug bfd . . . . .	392
Configure debug rate-limit . . . . .	393
Configure route . . . . .	393
Configure rib . . . . .	393
Configure nsm . . . . .	394
Configure nfsm. . . . .	394
Configure lsa . . . . .	394
Configure ifsm . . . . .	395

Configure events . . . . .	395
Configure debug retransmission . . . . .	396
Configure lfa. . . . .	396
Configure policy . . . . .	396
Configure redistribute. . . . .	397
Configure graceful restart . . . . .	397
Configure packet hello . . . . .	398
Configure packet dd. . . . .	398
Configure packet ls request . . . . .	398
Configure packet ls update . . . . .	399
Configure packet ls ack . . . . .	399
clear ip ospf <0-65535> process . . . . .	399
clear ip ospf process . . . . .	400
restart ip ospf graceful (grace-period <2-1800> ) . . . . .	400
snmp restart ospf . . . . .	400
debug ospf all. . . . .	400
no debug ospf all . . . . .	401
debug ospf bfd . . . . .	401
no debug ospf bfd . . . . .	401
debug ospf database-timer rate-limit . . . . .	401
no debug ospf database-timer rate-limit . . . . .	401
debug ospf route ({spf ia ase install spf-terse }) . . . . .	402
no debug ospf route ({spf ia ase install spf-terse }) . . . . .	402
debug ospf rib ({interface redistribute }) . . . . .	402
no debug ospf rib ({interface redistribute }) . . . . .	402
debug ospf packet ({send rcv detail }) . . . . .	403
no debug ospf packet ({send rcv detail }) . . . . .	403
debug ospf packet hello ({send rcv detail }) . . . . .	403
no debug ospf packet hello ({send rcv detail }) . . . . .	404
debug ospf packet dd ({send rcv detail }) . . . . .	404
no debug ospf packet dd ({send rcv detail }) . . . . .	404
debug ospf packet ls-request ({send rcv detail }) . . . . .	404
no debug ospf packet ls-request ({send rcv detail }) . . . . .	405
debug ospf packet ls-update ({send rcv detail }) . . . . .	405
no debug ospf packet ls-update ({send rcv detail }) . . . . .	405
debug ospf packet ls-ack ({send rcv detail }) . . . . .	406
no debug ospf packet ls-ack ({send rcv detail }) . . . . .	406
debug ospf nsm ({interface redistribute }) . . . . .	406
no debug ospf nsm ({interface redistribute }) . . . . .	406
debug ospf nsm ({status events timers }) . . . . .	407
no debug ospf nsm ({status events timers }) . . . . .	407
debug ospf lsa ({generate flooding install refresh maxage }) . . . . .	407
no debug ospf lsa ({generate flooding install refresh maxage }) . . . . .	408
debug ospf ifsm ({status events timers }) . . . . .	408
no debug ospf ifsm ({status events timers }) . . . . .	408
debug ospf events ({abr nssa asbr vlink lsa os router }) . . . . .	408
no debug ospf events ({abr nssa asbr vlink lsa os router }) . . . . .	409

---

debug ip ospf all . . . . .	409
no debug ip ospf all . . . . .	409
debug ip ospf retransmission . . . . .	410
no debug ip ospf retransmission . . . . .	410
debug ip ospf lfa . . . . .	410
no debug ip ospf lfa . . . . .	410
debug ip ospf policy . . . . .	410
no debug ip ospf policy . . . . .	411
debug ip ospf redistribute ({{detail terse}}) . . . . .	411
no debug ip ospf redistribute ({{detail terse}}) . . . . .	411
debug ip ospf graceful-restart ({{detail terse}}) . . . . .	411
no debug ip ospf graceful-restart ({{detail terse}}) . . . . .	412
<b>IPI-OSPF-INTERFACE . . . . .</b>	<b>412</b>
Configure cost . . . . .	412
Configure priority . . . . .	413
Configure mtu ignore . . . . .	413
Configure network type . . . . .	414
Configure disable all ospf . . . . .	414
Configure mtu . . . . .	414
Configure enable flood reduction . . . . .	415
Configure enable demand circuit . . . . .	415
Configure enable bfd . . . . .	416
Configure disable fast reroute . . . . .	416
Configure message digest id . . . . .	417
Configure name . . . . .	418
Configure authentication type . . . . .	419
Configure authentication authentication-type . . . . .	419
Configure key . . . . .	420
Configure authentication key . . . . .	421
Configure authentication key . . . . .	421
Configure authentication authentication-type . . . . .	422
Configure message digest encryption type . . . . .	422
Configure filter out . . . . .	423
Configure lsa filter-out . . . . .	424
Configure lsa filter-out . . . . .	425
Configure dead interval . . . . .	425
Configure timers dead-interval . . . . .	426
Configure hello interval . . . . .	427
Configure timers hello-interval . . . . .	427
Configure retransmission interval . . . . .	428
Configure timers retransmission-interval . . . . .	429
Configure timers dead-interval . . . . .	429
Configure timers hello-interval . . . . .	430
Configure timers retransmission-interval . . . . .	431
Configure transmit delay . . . . .	431
Configure resync timeout . . . . .	432
Configure interface address . . . . .	432

---

---

Configure address priority . . . . .	433
Configure address mtu-ignore . . . . .	434
Configure message digest key . . . . .	434
Configure message-digests message-digest-id . . . . .	435
Configure authentication authentication-type . . . . .	436
Configure authentication authentication-type . . . . .	437
Configure authentication key . . . . .	438
Configure authentication key . . . . .	438
Configure authentication key . . . . .	439
Configure authentication authentication-type . . . . .	439
Configure message-digests message-digest-id . . . . .	440
Configure timers dead-interval . . . . .	441
Configure timers hello-interval . . . . .	442
Configure timers retransmission-interval . . . . .	443
Configure timers transmit-delay . . . . .	443
Configure timers resync-timeout . . . . .	444
Configure lsa filter-out . . . . .	445
Configure lsa filter-out . . . . .	446
Configure lsa filter-out . . . . .	447
<b>IPI-OSPFV3 . . . . .</b>	<b>447</b>
Configure display route on single line . . . . .	447
Configure grace period . . . . .	448
Configure controlled restarts only . . . . .	448
Configure max grace period . . . . .	449
Configure disable all neighbors . . . . .	449
Configure disable neighbor . . . . .	450
Configure vrf name . . . . .	450
Configure ospfv3 id . . . . .	451
Configure router id . . . . .	451
Configure bfd enable all interfaces . . . . .	452
Configure database summary . . . . .	452
Configure area border type . . . . .	453
Configure default metric . . . . .	453
Configure shutdown . . . . .	454
Configure log adjacency changes . . . . .	454
Configure reference bandwidth . . . . .	455
Configure max database descriptors . . . . .	455
Configure default distance . . . . .	456
Configure intra area distance . . . . .	456
Configure disable graceful restart . . . . .	457
Configure exponential max delay . . . . .	458
Configure all interfaces . . . . .	458
Configure name . . . . .	459
Configure address . . . . .	460
Configure translate tag . . . . .	460
Configure not advertise . . . . .	461
Configure summary-address translate-tag . . . . .	462

---

---

Configure all tag . . . . .	462
Configure originate . . . . .	463
Configure route map . . . . .	464
Configure access control list . . . . .	465
Configure protocol . . . . .	465
Configure ospf process id . . . . .	466
Configure routing-protocols protocol . . . . .	467
Configure metric . . . . .	468
Configure ospf-processes ospf-process-id . . . . .	469
Configure metric type . . . . .	469
Configure default cost . . . . .	470
Configure no summary . . . . .	471
Configure enable . . . . .	472
Configure area id . . . . .	473
Configure remote router id . . . . .	473
Configure bfd fall over . . . . .	474
Configure instance id . . . . .	475
Configure authentication cryptomap . . . . .	476
Configure dead interval . . . . .	476
Configure address-ranges address . . . . .	478
Configure address-range not-advertise . . . . .	479
Configure address-ranges address . . . . .	479
Configure address-range not-advertise . . . . .	480
Configure summary-addresses address . . . . .	481
Configure summary-address not-advertise . . . . .	482
Configure tag . . . . .	482
Configure default-information originate . . . . .	483
Configure always advertise default route . . . . .	484
Configure protocol af . . . . .	485
Configure route tag . . . . .	486
Configure ospfv2 process id . . . . .	487
Configure ospf-process metric . . . . .	487
Configure retransmission . . . . .	489
Configure bfd . . . . .	490
Configure debug bfd . . . . .	491
Configure debug retransmission . . . . .	492
Configure events . . . . .	492
Configure ifsm . . . . .	492
Configure lsa . . . . .	493
Configure nsm . . . . .	493
Configure nsm . . . . .	494
Configure rib . . . . .	494
Configure route . . . . .	494
Configure packet hello . . . . .	495
Configure packet dd . . . . .	495
Configure packet ls request . . . . .	496
Configure packet ls update . . . . .	496

---

---

Configure packet ls ack	496
debug ipv6 ospf	497
no debug ipv6 ospf	497
debug ipv6 ospf all	497
no debug ipv6 ospf all	497
debug ipv6 ospf bfd	498
no debug ipv6 ospf bfd	498
debug ipv6 ospf retransmission	498
no debug ipv6 ospf retransmission	498
debug ipv6 ospf events ({abr asbr vlink os router nssa})	498
no debug ipv6 ospf events ({abr asbr vlink os router nssa})	499
debug ipv6 ospf ifsm ({status events timers})	499
no debug ipv6 ospf ifsm ({status events timers})	499
debug ipv6 ospf lsa ({generate flooding install refresh maxage})	499
no debug ipv6 ospf lsa ({generate flooding install refresh maxage})	500
debug ipv6 ospf n fsm ({status events timers})	500
no debug ipv6 ospf n fsm ({status events timers})	500
debug ipv6 ospf nsm ({interface redistribute})	501
no debug ipv6 ospf nsm ({interface redistribute})	501
debug ipv6 ospf packet ({send recv detail})	501
no debug ipv6 ospf packet ({send recv detail})	501
debug ipv6 ospf packet hello ({send recv detail})	502
no debug ipv6 ospf packet hello ({send recv detail})	502
debug ipv6 ospf packet dd ({send recv detail})	502
no debug ipv6 ospf packet dd ({send recv detail})	503
debug ipv6 ospf packet ls-request ({send recv detail})	503
no debug ipv6 ospf packet ls-request ({send recv detail})	503
debug ipv6 ospf packet ls-update ({send recv detail})	503
no debug ipv6 ospf packet ls-update ({send recv detail})	504
debug ipv6 ospf packet ls-ack ({send recv detail})	504
no debug ipv6 ospf packet ls-ack ({send recv detail})	504
debug ipv6 ospf rib ({interface redistribute})	505
no debug ipv6 ospf rib ({interface redistribute})	505
debug ipv6 ospf route ({spf ia ase install})	505
no debug ipv6 ospf route ({spf ia ase install})	505
clear ipv6 ospf (WORD ) process	506
restart ipv6 ospf graceful (grace-period <2-1800>)	506
snmp restart ospf6	506
<b>IPI-OSPFV3-INTERFACE</b>	<b>507</b>
Configure shutdown	507
Configure enable link lsa suppression	507
Configure enable bfd	508
Configure interface name	508
Configure instance id	509
Configure instance enable-bfd	510
Configure instance enable-bfd	510
Configure network type	511

---

---

Configure cost . . . . .	512
Configure priority . . . . .	512
Configure mtu . . . . .	513
Configure mtu ignore . . . . .	514
Configure authentication cryptomap . . . . .	514
Configure area id . . . . .	515
Configure ospfv3 id . . . . .	516
Configure router area-id . . . . .	517
Configure router ospfv3-id . . . . .	518
Configure dead interval . . . . .	518
Configure hello interval . . . . .	519
Configure transmission delay . . . . .	520
Configure retransmission interval . . . . .	521
Configure address . . . . .	522
Configure neighbors-static address . . . . .	522
Configure poll interval . . . . .	523
IPI-BGP . . . . .	524
Configure action name . . . . .	524
Configure action standard number . . . . .	525
Configure action name standard . . . . .	526
Configure list type . . . . .	527
Configure name . . . . .	527
Configure action expanded . . . . .	528
Configure expanded type . . . . .	529
Configure extended action number . . . . .	530
Configure extended action . . . . .	530
Configure action . . . . .	531
Configure value . . . . .	532
Configure access list name . . . . .	533
Configure enable aggregate nexthop . . . . .	533
Configure enable path select . . . . .	534
Configure disable adj out . . . . .	534
Configure disable rfc7606 error handling . . . . .	535
Configure enable bogon filtering . . . . .	535
Configure enable extended asn capability . . . . .	535
Configure enable nexthop tracking . . . . .	536
Configure nexthop tracking delay . . . . .	536
Configure enable rfc 1771 strict origin . . . . .	537
Configure options . . . . .	537
restart bgp graceful . . . . .	538
clear bgp statistics . . . . .	538
snmp restart bgp . . . . .	538
debug bgp (all nht nsm fsm events filters keepalives updates in updates out dampening bfd rib normal add-path adj-out route-scan packet-send packet-received)	538
no debug bgp (all nht nsm fsm events filters keepalives updates in updates out dampening bfd rib normal add-path adj-out route-scan packet-send packet-received)	539
no debug all bgp . . . . .	539

---

---

IPI-BGP-INSTANCE	539
Configure no external fail over	539
Configure no best path tie break	540
Configure inbound route filter disable	540
Configure external route leak disable	541
Configure no client route reflection	541
Configure med type	542
Configure bgp as	542
Configure bgp-instances bgp-as	543
Configure router id	543
Configure cluster id	544
Configure local preference	544
Configure graceful shutdown capable	545
Configure graceful shutdown	545
Configure graceful shutdown local preference	546
Configure log neighbor changes	546
Configure scan interval	547
Configure best path dont compare originator	548
Configure enable deterministic med	548
Configure enforce first as for ebgp	549
Configure local as count	549
Configure bgp-instance med-type	550
Configure multi path relax	550
Configure ignore aigp for bestpath	551
Configure identifier	551
Configure peer as number	552
Configure enable graceful restart	552
Configure restart time	553
Configure stale path max retention time	554
Configure route selection max defer time	554
Configure graceful reset	555
Configure keep alive	556
Configure always compare med	556
Configure ignore as path length	557
Configure best path compare confed	557
Configure external compare router id	558
Configure source ip prefix	559
Configure access list name	559
IPI-BGP-ADDRESS-FAMILY	560
Configure additional paths mode	560
Configure additional path select all	561
Configure additional paths best select count	561
Configure no client route reflection	562
Configure enable auto summary	563
Configure enable network igp sync	564
Configure map name	564
Configure table map filter	565

---

Configure enable igp sync . . . . .	566
Configure backdoor . . . . .	567
Configure bgp as . . . . .	568
Configure aggregate address . . . . .	569
Configure aggregate type . . . . .	569
Configure afi. . . . .	570
Configure safi. . . . .	571
Configure aggregate-address-list aggregate-type . . . . .	572
Configure local . . . . .	573
Configure ebgp max path. . . . .	574
Configure maximum-paths ebgp-max-path . . . . .	575
Configure ibgp max path . . . . .	575
Configure maximum-paths ibgp-max-path . . . . .	576
Configure eibgp max path . . . . .	577
Configure enable dampening. . . . .	578
Configure route-flap-dampenings enable-dampening . . . . .	579
Configure reach half life. . . . .	579
Configure route-flap-dampening reach-half-life . . . . .	580
Configure max suppress time . . . . .	581
Configure reuse penalty. . . . .	582
Configure unreachable half life. . . . .	583
Configure suppress penalty . . . . .	585
Configure dampening rmap name . . . . .	586
Configure route-flap-dampening dampening-rmap-name . . . . .	587
Configure protocol type . . . . .	588
Configure redistribute route map name . . . . .	589
Configure route-redistribute-list redistribute-route-map-name . . . . .	590
Configure afi. . . . .	590
Configure redistribute ospf route map . . . . .	591
clear ip bgp (A.B.C.D X::X::X WORD) (description LINE ) . . . . .	592
<b>IPI-BGP-PEER-GROUP . . . . .</b>	<b>593</b>
Configure optional as . . . . .	593
Configure peer group tag. . . . .	593
Configure bgp as . . . . .	594
Configure peer group range. . . . .	595
Configure group limit . . . . .	596
Configure enable peer bfd . . . . .	596
Configure enable peer bfd multihop. . . . .	597
Configure auth key encrypt . . . . .	597
Configure password. . . . .	598
Configure additional paths mode . . . . .	599
Configure additional path select all . . . . .	600
Configure additional paths best select count . . . . .	601
Configure activate . . . . .	602
Configure afi. . . . .	602
Configure safi. . . . .	603
Configure default peer route map name . . . . .	604

---

Configure peer route map orig name . . . . .	605
Configure weight . . . . .	606
Configure route server client . . . . .	607
Configure next hop self . . . . .	608
Configure peer route reflector . . . . .	608
Configure address-family peer-route-reflector . . . . .	609
Configure peer remove private as . . . . .	610
Configure no send community . . . . .	611
Configure no send community type . . . . .	612
Configure neighbor attribute unchanged . . . . .	613
Configure address-family neighbor-attribute-unchanged . . . . .	614
Configure orf prefix capability . . . . .	614
Configure peer allow ebgp vpn . . . . .	615
Configure allow as number . . . . .	616
Configure address-family allow-as-number . . . . .	617
Configure capability graceful restart . . . . .	618
Configure address-family capability-graceful-restart . . . . .	619
Configure address-family capability-graceful-restart . . . . .	620
Configure prefix count . . . . .	621
Configure stop update . . . . .	622
Configure maximum-prefix stop-update . . . . .	623
Configure maximum prefix warning . . . . .	624
Configure threshold percentage . . . . .	625
Configure warning only . . . . .	626
Configure unsuppress route map name . . . . .	627
Configure access list identifier . . . . .	628
Configure safi . . . . .	629
Configure as access list identifier . . . . .	630
Configure route map name . . . . .	631
Configure peer as . . . . .	632
Configure graceful shut . . . . .	633
Configure graceful shutdown timer . . . . .	633
Configure peer restart time . . . . .	634
Configure peer description . . . . .	635
Configure peer connect interval . . . . .	635
Configure peer as origin interval . . . . .	636
Configure min route advertisement interval . . . . .	637
Configure enable dynamic capability . . . . .	638
Configure collide established . . . . .	638
Configure source identifier . . . . .	639
Configure enforce multi hop . . . . .	640
Configure neighbor override capability . . . . .	640
Configure neighbor strict capability match . . . . .	641
Configure disallow infinite hold time . . . . .	641
Configure disable capability negotiation . . . . .	642
Configure neighbor passive . . . . .	643
Configure peer shutdown description . . . . .	643

---

---

Configure peer port . . . . .	644
Configure bgp version . . . . .	645
Configure enable ext opt param len . . . . .	645
Configure tcp adjust mss . . . . .	646
Configure keep alive . . . . .	647
Configure enabled . . . . .	648
Configure maximum hop count . . . . .	648
Configure peer local as . . . . .	649
Configure no prepend local as . . . . .	650
Configure admin status . . . . .	651
Configure aigp send med . . . . .	652
Configure send cost community id . . . . .	653
Configure enable transitive . . . . .	654
clear bgp peer-group WORD l2vpn evpn soft (out in ) . . . . .	655
<b>IPI-BGP-PEER . . . . .</b>	<b>655</b>
Configure enable peer bfd . . . . .	655
Configure bgp as . . . . .	656
Configure enable peer bfd multihop . . . . .	657
Configure peer address . . . . .	657
Configure interface name . . . . .	658
Configure mapped peer group tag . . . . .	658
Configure peer mapped-peer-group-tag . . . . .	659
Configure tcp adjust mss . . . . .	660
Configure auth key encrypt . . . . .	660
Configure password . . . . .	661
Configure bgp-password auth-key-encrypt . . . . .	662
Configure bgp-password auth-key-encrypt . . . . .	663
Configure additional paths mode . . . . .	664
Configure additional path select all . . . . .	664
Configure additional paths best select count . . . . .	665
Configure activate . . . . .	666
Configure afi . . . . .	667
Configure safi . . . . .	668
Configure address-family activate . . . . .	669
Configure address-family activate . . . . .	669
Configure address-family activate . . . . .	670
Configure de activate . . . . .	671
Configure address-family de-activate . . . . .	672
Configure address-family de-activate . . . . .	673
Configure address-family de-activate . . . . .	674
Configure address-family de-activate . . . . .	674
Configure address-family de-activate . . . . .	675
Configure default peer route map name . . . . .	676
Configure address-family default-peer-route-map-name . . . . .	677
Configure peer route map orig name . . . . .	678
Configure weight . . . . .	679
Configure address-family weight . . . . .	680

---

---

Configure route server client . . . . .	681
Configure address-family route-server-client . . . . .	681
Configure next hop self . . . . .	682
Configure address-family next-hop-self . . . . .	683
Configure peer route reflector . . . . .	684
Configure address-family peer-route-reflector . . . . .	685
Configure address-family peer-route-reflector . . . . .	686
Configure address-family peer-route-reflector . . . . .	687
Configure peer remove private as . . . . .	688
Configure address-family peer-remove-private-as . . . . .	688
Configure no send community . . . . .	689
Configure no send community type . . . . .	690
Configure neighbor attribute unchanged . . . . .	691
Configure address-family neighbor-attribute-unchanged . . . . .	692
Configure address-family neighbor-attribute-unchanged . . . . .	693
Configure address-family neighbor-attribute-unchanged . . . . .	693
Configure orf prefix capability . . . . .	694
Configure address-family orf-prefix-capability . . . . .	695
Configure peer allow ebgp vpn . . . . .	696
Configure allow as number . . . . .	697
Configure address-family allow-as-number . . . . .	698
Configure address-family allow-as-number . . . . .	699
Configure address-family allow-as-number . . . . .	700
Configure capability graceful restart . . . . .	701
Configure address-family capability-graceful-restart . . . . .	702
Configure address-family capability-graceful-restart . . . . .	703
Configure extended nexthop encode . . . . .	704
Configure address-family capability-graceful-restart . . . . .	705
Configure prefix count . . . . .	705
Configure maximum-prefixes prefix-count . . . . .	706
Configure stop update . . . . .	707
Configure maximum-prefix stop-update . . . . .	708
Configure maximum-prefix stop-update . . . . .	709
Configure maximum prefix warning . . . . .	710
Configure maximum-prefix maximum-prefix-warning . . . . .	711
Configure threshold percentage . . . . .	712
Configure maximum-prefix threshold-percentage . . . . .	713
Configure warning only . . . . .	714
Configure maximum-prefix warning-only . . . . .	716
Configure unsuppress route map name . . . . .	717
Configure address-family unsuppress-route-map-name . . . . .	718
Configure access list identifier . . . . .	718
Configure filter direction . . . . .	719
Configure prefix list name . . . . .	720
Configure prefix filter direction . . . . .	722
Configure as access list identifier . . . . .	723
Configure as list direction . . . . .	724

---

---

Configure route map name . . . . .	725
Configure route map direction . . . . .	726
Configure peer port . . . . .	727
Configure min route advertisement interval . . . . .	727
Configure peer as origin interval . . . . .	728
Configure collide established . . . . .	729
Configure peer description . . . . .	729
Configure disallow infinite hold time . . . . .	730
Configure disable capability negotiation . . . . .	731
Configure enforce multi hop . . . . .	731
Configure graceful shut . . . . .	732
Configure graceful shutdown timer . . . . .	733
Configure neighbor override capability . . . . .	733
Configure neighbor passive . . . . .	734
Configure peer restart time . . . . .	735
Configure peer shutdown . . . . .	735
Configure neighbor strict capability match . . . . .	736
Configure source identifier . . . . .	737
Configure bgp version . . . . .	737
Configure enable ext opt param len . . . . .	738
Configure peer connect interval . . . . .	739
Configure peer as . . . . .	739
Configure peer peer-as . . . . .	740
Configure peer peer-as . . . . .	741
Configure peer peer-as . . . . .	741
Configure peer graceful-shut . . . . .	742
Configure peer graceful-shutdown-timer . . . . .	743
Configure peer peer-restart-time . . . . .	743
Configure peer peer-description . . . . .	744
Configure peer peer-connect-interval . . . . .	745
Configure peer peer-as-origin-interval . . . . .	745
Configure peer min-route-advertisement-interval . . . . .	746
Configure enable dynamic capability . . . . .	747
Configure peer collide-established . . . . .	747
Configure peer source-identifier . . . . .	748
Configure peer enforce-multi-hop . . . . .	749
Configure peer neighbor-override-capability . . . . .	749
Configure peer neighbor-strict-capability-match . . . . .	750
Configure peer disallow-infinite-hold-time . . . . .	751
Configure peer disable-capability-negotiation . . . . .	751
Configure peer neighbor-passive . . . . .	752
Configure peer shutdown description . . . . .	753
Configure peer peer-port . . . . .	753
Configure peer bgp-version . . . . .	754
Configure peer enable-ext-opt-param-len . . . . .	755
Configure peer tcp-adjust-mss . . . . .	755
Configure hold time . . . . .	756

---

Configure keep alive	757
Configure enabled	758
Configure maximum hop count	758
Configure ebgp-multihop enabled	759
Configure ebgp-multihop enabled	760
Configure peer local as	761
Configure local-as peer-local-as	761
Configure no prepend local as	762
Configure replace local as	763
Configure admin status	764
Configure aigp send med.	765
Configure send cost community id	766
Configure enable transitive	767
clear ip bgp * (description LINE )	768
clear bgp * l2vpn evpn soft (out in )	768
clear bgp <1-4294967295> l2vpn evpn soft (out in )	769
clear bgp (A.B.C.D X::X::X WORD) l2vpn evpn soft (out in )	769
<b>IPI-BGP-ADDRESS-FAMILY-VRF</b>	<b>770</b>
Configure enable auto summary	770
Configure enable network igp sync	770
Configure map name	771
Configure table map filter	772
Configure local	773
Configure enable igp sync	774
Configure ebgp max path	775
Configure bgp as	776
Configure ibgp max path	776
Configure optional as	777
Configure auth key encrypt	778
Configure afi	779
Configure multipath relax	780
Configure graceful shutdown	781
Configure graceful shutdown capable	782
Configure graceful shutdown local preference	782
Configure additional path select all	783
Configure additional paths mode	784
Configure additional paths best select count	785
Configure protocol type	785
Configure redistribute route map name	786
Configure ospf instance number	787
Configure redistribute ospf route map	788
Configure peer as	789
Configure source identifier	790
Configure bgp version	791
Configure peer connection interval	792
Configure hold time	793
Configure enforce multihop	794

---

Configure peer shutdown . . . . .	795
Configure peer group tag . . . . .	796
Configure peer group range . . . . .	797
Configure safi . . . . .	798
Configure group limit . . . . .	799
Configure vrf name . . . . .	799
Configure peer-group source-identifier . . . . .	800
Configure peer-group bgp-version . . . . .	801
Configure peer-group peer-connection-interval . . . . .	802
Configure keep alive . . . . .	803
Configure peer-group enforce-multihop . . . . .	804
Configure peer shutdown description . . . . .	805
Configure enabled . . . . .	806
Configure maximum hop count . . . . .	807
Configure neighbor passive . . . . .	808
Configure disable capability negotiation . . . . .	809
Configure enable dynamic capability . . . . .	810
Configure min route advertisement interval . . . . .	811
Configure peer as origin interval . . . . .	812
Configure neighbor as override . . . . .	813
Configure peer description . . . . .	814
Configure peer restart time . . . . .	815
Configure site origin identifier . . . . .	816
Configure graceful shut . . . . .	817
Configure graceful shut timer . . . . .	817
Configure bgp port . . . . .	818
Configure enable ext opt param len . . . . .	819
Configure peer-group additional-paths-mode . . . . .	820
Configure peer-group additional-path-select-all . . . . .	821
Configure peer-group additional-paths-best-select-count . . . . .	822
Configure tcp adjust mss . . . . .	823
Configure enable peer bfd . . . . .	824
Configure enable peer bfd multihop . . . . .	825
Configure activate . . . . .	825
Configure default peer route map name . . . . .	826
Configure peer route map orig name . . . . .	827
Configure weight . . . . .	828
Configure peer-group weight . . . . .	829
Configure peer route reflector . . . . .	830
Configure peer remove private as . . . . .	831
Configure no send community . . . . .	832
Configure no send community type . . . . .	833
Configure neighbor attribute unchanged . . . . .	834
Configure peer-group neighbor-attribute-unchanged . . . . .	835
Configure orf prefix capability . . . . .	836
Configure peer allow ebgp vpn . . . . .	837
Configure allow as number . . . . .	837

---

---

Configure capability graceful restart . . . . .	839
Configure prefix count . . . . .	839
Configure stop update . . . . .	840
Configure maximum prefix warning . . . . .	842
Configure threshold percentage . . . . .	843
Configure warning only . . . . .	844
Configure unsuppress route map name . . . . .	845
Configure access list identifier . . . . .	846
Configure as access list identifier . . . . .	847
Configure prefix list name . . . . .	848
Configure route map name . . . . .	849
Configure peer address . . . . .	850
Configure password . . . . .	851
Configure vrf-peer neighbor-passive . . . . .	852
Configure vrf-peer disable-capability-negotiation . . . . .	853
Configure vrf-peer enable-dynamic-capability . . . . .	854
Configure vrf-peer min-route-advertisement-interval . . . . .	855
Configure vrf-peer peer-as-origin-interval . . . . .	856
Configure vrf-peer neighbor-as-override . . . . .	857
Configure peer interface name . . . . .	858
Configure vrf-peer peer-description . . . . .	858
Configure vrf-peer peer-restart-time . . . . .	859
Configure vrf-peer site-origin-identifier . . . . .	860
Configure vrf-peer graceful-shut . . . . .	861
Configure vrf-peer graceful-shut-timer . . . . .	862
Configure vrf-peer bgp-port . . . . .	863
Configure vrf-peer enable-ext-opt-param-len . . . . .	864
Configure vrf-peer additional-paths-mode . . . . .	865
Configure vrf-peer additional-path-select-all . . . . .	866
Configure vrf-peer additional-paths-best-select-count . . . . .	866
Configure vrf-peer tcp-adjust-mss . . . . .	867
Configure vrf-peer enable-peer-bfd . . . . .	868
Configure vrf-peer enable-peer-bfd-multihop . . . . .	869
Configure vrf-peer activate . . . . .	870
Configure de activate . . . . .	871
Configure vrf-peer default-peer-route-map-name . . . . .	872
Configure vrf-peer peer-route-map-origin-name . . . . .	873
Configure vrf-peer weight . . . . .	874
Configure vrf-peer weight . . . . .	875
Configure vrf-peer peer-route-reflector . . . . .	876
Configure vrf-peer peer-remove-private-as . . . . .	877
Configure vrf-peer no-send-community . . . . .	878
Configure vrf-peer no-send-community-type . . . . .	878
Configure vrf-peer neighbor-attribute-unchanged . . . . .	879
Configure vrf-peer neighbor-attribute-unchanged . . . . .	880
Configure vrf-peer orf-prefix-capability . . . . .	881
Configure vrf-peer peer-allow-ebgp-vpn . . . . .	882

---

---

Configure vrf-peer allow-as-number . . . . .	883
Configure vrf-peer capability-graceful-restart. . . . .	884
Configure mapped peer group tag af. . . . .	885
Configure maximum-prefixes prefix-count . . . . .	886
Configure maximum-prefix stop-update. . . . .	887
Configure maximum-prefix maximum-prefix-warning . . . . .	888
Configure maximum-prefix threshold-percentage . . . . .	889
Configure maximum-prefix warning-only . . . . .	890
Configure vrf-peer unsuppress-route-map-name. . . . .	891
Configure filter direction . . . . .	892
Configure as list direction. . . . .	893
Configure prefix filter direction . . . . .	894
Configure route map direction . . . . .	895
Configure identifier. . . . .	896
Configure peer as number . . . . .	897
Configure enable dampening. . . . .	898
Configure reach half life. . . . .	899
Configure max suppress time . . . . .	900
Configure unreachable half life. . . . .	901
Configure dampening rmap name . . . . .	902
Configure ebgp-multihop enabled . . . . .	903
Configure ebgp-multihop enabled . . . . .	904
Configure peer local as . . . . .	905
Configure no prepend local as . . . . .	906
Configure backdoor . . . . .	907
Configure local network prefix . . . . .	908
Configure local-as peer-local-as . . . . .	909
Configure replace local as . . . . .	910
clear ip bgp all vrf (VRFNAME all default) (description LINE). . . . .	912
clear ip bgp vrf WORD (A.B.C.D X::X::X WORD WORD) (description LINE). . . . .	912
<b>IPI-BGP-VRF . . . . .</b>	<b>913</b>
Configure rd string . . . . .	913
Configure import map . . . . .	913
Configure export map . . . . .	914
Configure direction. . . . .	915
<b>IPI-BFD . . . . .</b>	<b>915</b>
Configure notification enabled . . . . .	915
Configure echo mode enabled. . . . .	916
Configure slow tx interval. . . . .	916
Configure detection multiplier . . . . .	917
Configure remote address . . . . .	917
Configure key string . . . . .	918
Configure options. . . . .	919
snmp restart bfd . . . . .	919
debug bfd (events packets ipc-error ipc-event session nsm all) . . . . .	919
no debug bfd (events packets ipc-error ipc-event session nsm all) . . . . .	920
<b>IPI-BFD-INTERFACE . . . . .</b>	<b>920</b>

---

---

Configure bfd disabled . . . . .	920
Configure bfd session type . . . . .	921
Configure detection multiplier . . . . .	921
Configure ipv4 source . . . . .	922
Configure name . . . . .	922
Configure required minimum tx interval . . . . .	923
Configure key string . . . . .	923
Configure session type . . . . .	924
Configure administrative down . . . . .	925
Configure non persistent . . . . .	926
IPI-VRRP . . . . .	926
Configure disable virtual router mac address . . . . .	926
Configure vrrp v2 compatible . . . . .	927
Configure ipv4 exclude pseudo header . . . . .	927
Configure options . . . . .	928
Configure debug options . . . . .	928
Configure interface name . . . . .	928
Configure disable preempt mode . . . . .	929
Configure disable accept mode . . . . .	930
Configure virtual router id . . . . .	930
Configure interface ipv4-exclude-pseudo-header . . . . .	931
Configure authentication data . . . . .	932
Configure primary ip address . . . . .	932
Configure mlag active standby . . . . .	933
Configure priority . . . . .	933
Configure preempt delay . . . . .	934
Configure advertisement interval . . . . .	935
Configure enable . . . . .	936
Configure ip address owner . . . . .	936
Configure interface tracking name . . . . .	937
Configure tracking id . . . . .	938
Configure interfaces interface-name . . . . .	939
Configure interface disable-preempt-mode . . . . .	939
Configure interface disable-accept-mode . . . . .	940
Configure interface primary-ip-address . . . . .	941
Configure interface priority . . . . .	941
Configure interface preempt-delay . . . . .	942
Configure interface advertisement-interval . . . . .	943
Configure protocol-enable enable . . . . .	944
Configure virtual ip address . . . . .	944
Configure virtual-ip-address ip-address-owner . . . . .	945
Configure priority decrement . . . . .	946
Configure decrement . . . . .	947
snmp restart vrrp . . . . .	948
clear vrrp global statistics . . . . .	948
clear vrrp ipv4 statistics . . . . .	948
clear vrrp ipv6 statistics . . . . .	948

---

---

clear vrrp ipv4 statistics <1-255> IFNAME . . . . .	948
clear vrrp ipv6 statistics <1-255> IFNAME . . . . .	949
debug vrrp . . . . .	949
no debug vrrp . . . . .	949
debug vrrp (all packet events packet send packet recv) . . . . .	950
no debug vrrp (all packet events packet send packet recv) . . . . .	950
IPI-PREFIX-LIST . . . . .	950
Configure prefix list name . . . . .	950
Configure prefix list type . . . . .	951
Configure description . . . . .	951
Configure prefix addr . . . . .	952
Configure sequence id . . . . .	952
Configure maximum prefix length match . . . . .	953
Configure minimum prefix length match . . . . .	954
Configure action . . . . .	955
Configure entry maximum-prefix-length-match . . . . .	956
Configure exact prefix length match . . . . .	957
Configure ipv6 prefix addr . . . . .	958
Configure ipv6 ipv6-prefix-addr . . . . .	959
Configure entry maximum-prefix-length-match . . . . .	959
Configure entry minimum-prefix-length-match . . . . .	960
Configure entry minimum-prefix-length-match . . . . .	961
Configure entry maximum-prefix-length-match . . . . .	962
Configure disable ipv4 sequence display . . . . .	963
Configure disable ipv6 sequence display . . . . .	964
clear ip prefix-list . . . . .	964
clear ipv6 prefix-list . . . . .	964
clear ip prefix-list WORD (A.B.C.D/M ) . . . . .	964
clear ipv6 prefix-list WORD (X:X::X:X/M ) . . . . .	965
IPI-ISIS . . . . .	965
Configure vrf name . . . . .	965
Configure instance . . . . .	966
Configure disable gr capability . . . . .	966
Configure isis-instance disable-gr-capability . . . . .	967
Configure disable adjacency check . . . . .	967
Configure authentication send only . . . . .	968
Configure isis-instance authentication-send-only . . . . .	968
Configure distance . . . . .	969
Configure dynamic host name . . . . .	969
Configure ignore lsp errors . . . . .	970
Configure lfa hold timer . . . . .	970
Configure protocol topology . . . . .	971
Configure level capability . . . . .	971
Configure isis-instance authentication-send-only . . . . .	972
Configure incremental spf levels . . . . .	972
Configure priority tag . . . . .	973
Configure enable bfd all interfaces . . . . .	973

---

---

Configure maximum area addresses . . . . .	974
Configure context name . . . . .	974
Configure area password . . . . .	975
Configure sequence number packet . . . . .	976
Configure net . . . . .	976
Configure domain password . . . . .	977
Configure domain snp . . . . .	978
Configure style . . . . .	978
Configure level number . . . . .	979
Configure metric style . . . . .	979
Configure metric style . . . . .	980
Configure metric style . . . . .	981
Configure metric level-number . . . . .	981
Configure lsp refresh interval . . . . .	982
Configure lsp lifetime interval . . . . .	983
Configure enable . . . . .	983
Configure level 1 acl . . . . .	984
Configure level-2-into-1-redistributes enable . . . . .	985
Configure level 2 acl . . . . .	985
Configure originate . . . . .	986
Configure route map name . . . . .	987
Configure afi name . . . . .	987
Configure address-family-ipv6 afi-name . . . . .	988
Configure address-family-ipv6 disable-adjacency-check . . . . .	988
Configure administrative distance . . . . .	989
Configure ipv6 metric value . . . . .	990
Configure prefix . . . . .	991
Configure level . . . . .	991
Configure multi-topologies level . . . . .	992
Configure multi-topologies level . . . . .	993
Configure multi-topologies level . . . . .	993
Configure multi-topologies level . . . . .	994
Configure multi-topologies level . . . . .	995
Configure access list name . . . . .	995
Configure set bit on boot . . . . .	996
Configure enabled . . . . .	997
Configure level-1-into-2-redistributes enable . . . . .	998
Configure redistribute-level-1-into-2 level-1-acl . . . . .	998
Configure level-2-into-1-redistributes enable . . . . .	999
Configure redistribute-level-2-into-1 level-2-acl . . . . .	1000
Configure default-route-informations originate . . . . .	1000
Configure default-route-information route-map-name . . . . .	1001
Configure metric value . . . . .	1002
Configure metric . . . . .	1003
Configure id . . . . .	1003
Configure metric type . . . . .	1004
Configure passive interface all . . . . .	1005

---

Configure name . . . . .	1006
Configure disable-passive-interfaces name . . . . .	1006
Configure hold timer . . . . .	1007
Configure max fib . . . . .	1008
Configure level type . . . . .	1008
Configure algo number . . . . .	1009
Configure flexalgo metric-type . . . . .	1009
Configure calculation type . . . . .	1010
Configure priority . . . . .	1011
Configure exclude minimum bandwidth . . . . .	1011
Configure exclude maximum delay . . . . .	1012
Configure enable intf group mode bw calc. . . . .	1013
Configure reference bandwidth . . . . .	1013
Configure granularity bandwidth . . . . .	1014
Configure enable advertise definition . . . . .	1015
Configure enable participate . . . . .	1015
Configure enable fast reroute . . . . .	1016
Configure enable remote lfa . . . . .	1016
Configure enable ti lfa . . . . .	1017
Configure enable prefix metric flag . . . . .	1018
Configure fapm metric . . . . .	1018
Configure affinity eag exclude any . . . . .	1019
Configure affinity eag include any . . . . .	1020
Configure affinity eag include all . . . . .	1020
Configure affinity eag reverse exclude any . . . . .	1021
Configure affinity eag reverse include any . . . . .	1021
Configure affinity eag reverse include all . . . . .	1022
Configure affinity ag exclude any . . . . .	1023
Configure affinity ag include any . . . . .	1023
Configure affinity ag include all . . . . .	1024
Configure affinity ag reverse exclude any . . . . .	1025
Configure affinity ag reverse include any . . . . .	1025
Configure affinity ag reverse include all . . . . .	1026
Configure threshold metric . . . . .	1027
Configure flexalgo-microloop-avoidance enable . . . . .	1027
Configure options . . . . .	1028
Configure enable hello . . . . .	1029
clear clns is-neighbors System-ID . . . . .	1029
clear clns neighbors . . . . .	1029
clear ip isis (WORD ) route (redistribution all) . . . . .	1029
clear ipv6 isis (WORD ) route (redistribution all) . . . . .	1030
clear isis (WORD ) process . . . . .	1030
clear isis counter . . . . .	1030
clear isis adjacency * (vrf VRFNAME ) . . . . .	1031
clear isis WORD adjacency * (vrf VRFNAME ) . . . . .	1031
clear isis WORD adjacency (IFNAME ) (vrf VRFNAME ) . . . . .	1031
clear isis adjacency (IFNAME ) (vrf VRFNAME ) . . . . .	1032

---

---

clear isis WORD adjacency system-id XXXX.XXXX.XXXX (vrf VRFNAME))	1032
clear isis adjacency system-id XXXX.XXXX.XXXX (vrf VRFNAME))	1032
snmp restart isis	1033
debug isis (ifsm nfsm pdu lsp spf events nsm checksum authentication local- updates protocol-errors bfd rib lfa ofib asla flexalgo all)	1033
no debug isis (ifsm nfsm pdu lsp spf events nsm checksum authentication local- updates protocol-errors bfd rib lfa ofib asla flexalgo all)	1033
debug isis spf-trace	1034
no debug isis spf-trace	1034
debug isis hello	1034
no debug isis hello	1034
debug isis hello interface IFNAME	1034
no debug isis hello interface IFNAME	1035
debug isis hello System-ID	1035
no debug isis hello System-ID	1035
no debug all isis	1036
<b>IPI-ISIS-LSP</b>	1036
Configure spf max delay	1036
Configure lsp max wait interval	1037
Configure lsp mtu size	1037
Configure wait timer	1038
Configure restart timer	1039
Configure instance	1039
Configure type	1040
Configure mode	1041
Configure key chain	1041
<b>IPI-ISIS-EXTENDED</b>	1042
Configure name	1042
Configure enable all prefixes	1043
Configure preference index	1044
Configure grace period	1045
Configure enable helper only	1045
Configure suppress adjacency	1046
restart isis graceful (grace-period <1-65535> )	1046
<b>IPI-ISIS-INTERFACE</b>	1046
Configure minimal	1046
Configure name	1047
Configure send only	1047
Configure interface send-only	1048
Configure interface minimal	1048
Configure interface send-only	1049
Configure maximum bandwidth flex algo	1049
Configure disable asla usage flex algo	1050
Configure disable padding	1050
Configure interface-parameters disable-padding	1051
Configure network type	1052
Configure circuit type	1052

---

Configure ipv4 instance tag . . . . .	1053
Configure ipv6 instance tag . . . . .	1053
Configure lsp interval . . . . .	1054
Configure retransmit interval . . . . .	1055
Configure mesh group id . . . . .	1055
Configure enable . . . . .	1056
Configure disable . . . . .	1056
Configure disable level 1 . . . . .	1057
Configure disable level 2 . . . . .	1058
Configure hello interval . . . . .	1058
Configure hello multiplier . . . . .	1059
Configure csnp interval . . . . .	1060
Configure priority . . . . .	1060
Configure metric . . . . .	1061
Configure password . . . . .	1062
Configure tag . . . . .	1063
Configure wide metric . . . . .	1063
Configure restart hello interval . . . . .	1064
Configure te minimum delay . . . . .	1065
Configure te maximum delay . . . . .	1065
Configure te minimum delay flex algo . . . . .	1066
Configure te maximum delay flex algo . . . . .	1067
Configure mode . . . . .	1068
Configure key chain . . . . .	1068
clear isis interface counter (IFNAME) . . . . .	1069
<b>IPI-KEYCHAIN . . . . .</b>	<b>1069</b>
Configure name . . . . .	1069
Configure key id . . . . .	1070
Configure key string . . . . .	1070
Configure encrypted . . . . .	1071
Configure start date time for accept . . . . .	1072
Configure start date time for send . . . . .	1073
<b>IPI-PIM . . . . .</b>	<b>1074</b>
Configure bfd . . . . .	1074
<b>IPI-PIM-IPV4 . . . . .</b>	<b>1074</b>
Configure router id . . . . .	1074
Configure join prune interval . . . . .	1075
Configure ecmp bundle . . . . .	1075
Configure enable bfd all interfaces . . . . .	1076
Configure register reachability check . . . . .	1076
Configure rate limit . . . . .	1077
Configure suppress interval . . . . .	1077
Configure keep alive interval . . . . .	1078
Configure source address . . . . .	1079
Configure accept register . . . . .	1079
Configure ignore rp set priority . . . . .	1080
Configure cisco bsr interop enable . . . . .	1081

---

Configure access control list . . . . .	1081
Configure cisco register checksum enable . . . . .	1082
Configure vrf name . . . . .	1083
Configure enable . . . . .	1083
Configure range policy . . . . .	1084
Configure member rp address . . . . .	1085
Configure rp address . . . . .	1085
Configure override dynamically learned rp . . . . .	1086
Configure static-rp-default access-control-list . . . . .	1087
Configure static-rp-default override-dynamically-learned-rp . . . . .	1088
Configure interface name . . . . .	1088
Configure hash mask length . . . . .	1089
Configure priority . . . . .	1090
Configure bsr-candidate interface-name . . . . .	1091
Configure rp-candidates interface-name . . . . .	1091
Configure advertisement interval . . . . .	1092
Configure originator id . . . . .	1093
Configure group address . . . . .	1094
Configure address . . . . .	1095
Configure mesh group . . . . .	1095
Configure default peer . . . . .	1096
Configure prefix list . . . . .	1097
Configure peer source-address . . . . .	1098
Configure password . . . . .	1099
Configure options . . . . .	1099
Configure passive enable . . . . .	1100
Configure pim mode . . . . .	1101
Configure bsr border . . . . .	1101
Configure dr priority . . . . .	1102
Configure hello interval . . . . .	1102
Configure hello holdtime . . . . .	1103
Configure exclude generated id . . . . .	1103
Configure unicast bootstrap router . . . . .	1104
Configure neighbor access control list filter . . . . .	1104
Configure state refresh origination interval . . . . .	1105
Configure name . . . . .	1106
Configure propagation delay . . . . .	1106
Configure enable bfd . . . . .	1107
Configure virtual router id . . . . .	1107
Configure vrrp virtual-router-id . . . . .	1108
snmp restart pim . . . . .	1109
clear ip pim (vrf NAME ) (sparse-mode) bsr rp-set * . . . . .	1109
clear ip mroute (vrf NAME ) * pim (dense-mode sparse-mode) . . . . .	1109
clear ip mroute (vrf NAME ) A.B.C.D pim sparse-mode . . . . .	1110
clear ip mroute (vrf NAME ) A.B.C.D A.B.C.D pim (dense-mode sparse-mode) . . . . .	1110
clear ip msdp (vrf NAME ) peer (A.B.C.D ) . . . . .	1111
clear ip msdp (vrf NAME ) sa-cache (A.B.C.D ) . . . . .	1111

---

debug ip pim (vrf NAME ) (all events packet packet in packet out state mfc timer timer hello timer bsr timer joinprune timer hello ht timer hello nlt timer hello tht timer joinprune jt timer joinprune et timer joinprune ppt timer joinprune kat timer joinprune ot timer assert timer register timer bsr bst timer bsr crp mib nsm nexthop mtrace msdp). . . . .	1111
no debug ip pim (vrf NAME ) (all events packet packet in packet out state mfc timer timer hello timer bsr timer joinprune timer hello ht timer hello nlt timer hello tht timer joinprune jt timer joinprune et timer joinprune ppt timer joinprune kat timer joinprune ot timer assert timer register timer bsr bst timer bsr crp mib nsm nexthop mtrace msdp). . . . .	1112
debug ip pim (vrf NAME ). . . . .	1113
no debug ip pim (vrf NAME ) . . . . .	1113
IPI-PIM-IPV6 . . . . .	1113
Configure router id . . . . .	1113
Configure join prune interval . . . . .	1114
Configure ecmp bundle . . . . .	1114
Configure enable bfd all interfaces . . . . .	1115
Configure register reachability check. . . . .	1115
Configure rate limit. . . . .	1116
Configure suppress interval . . . . .	1117
Configure keep alive interval . . . . .	1117
Configure source address . . . . .	1118
Configure accept register. . . . .	1119
Configure ignore rp set priority. . . . .	1119
Configure cisco bsr interop enable . . . . .	1120
Configure access control list . . . . .	1120
Configure cisco register checksum enable . . . . .	1121
Configure vrf name . . . . .	1122
Configure enable . . . . .	1123
Configure range policy. . . . .	1123
Configure member rp address . . . . .	1124
Configure embed rp . . . . .	1124
Configure rp address . . . . .	1125
Configure override dynamically learned rp . . . . .	1126
Configure static-rp-default access-control-list . . . . .	1127
Configure static-rp-default override-dynamically-learned-rp . . . . .	1127
Configure interface name. . . . .	1128
Configure hash mask length . . . . .	1129
Configure priority . . . . .	1130
Configure bsr-candidate interface-name . . . . .	1131
Configure rp-candidates interface-name . . . . .	1131
Configure advertisement interval . . . . .	1132
Configure options. . . . .	1133
Configure passive enable . . . . .	1134
Configure pim mode. . . . .	1134
Configure bsr border . . . . .	1135
Configure dr priority . . . . .	1135
Configure hello interval . . . . .	1136
Configure hello holdtime . . . . .	1136
Configure exclude generated id . . . . .	1137

---

---

Configure unicast bootstrap router . . . . .	1137
Configure neighbor access control list filter . . . . .	1138
Configure state refresh origination interval . . . . .	1139
Configure name . . . . .	1139
Configure propagation delay . . . . .	1140
Configure enable bfd . . . . .	1140
clear ipv6 pim (vrf NAME ) (sparse-mode) bsr rp-set * . . . . .	1141
clear ipv6 mroute (vrf NAME ) * pim (dense-mode sparse-mode) . . . . .	1141
clear ipv6 mroute (vrf NAME ) X:X::X:X pim sparse-mode . . . . .	1142
clear ipv6 mroute (vrf NAME ) X:X::X:X X:X::X:X pim (dense-mode sparse-mode) . . . . .	1142
debug pim bfd . . . . .	1143
no debug pim bfd . . . . .	1143
debug ipv6 pim (vrf NAME ) (all events packet packet in packet out state mfc timer timer hello timer bsr timer joinprune timer hello ht timer hello nlt timer hello tht timer joinprune jt timer joinprune et timer joinprune ppt timer joinprune kat timer joinprune ot timer assert timer register timer bsr bst timer bsr crp mib nsm nexthop mtrace) . . . . .	1143
no debug ipv6 pim (vrf NAME ) (all events packet packet in packet out state mfc timer timer hello timer bsr timer joinprune timer hello ht timer hello nlt timer hello tht timer joinprune jt timer joinprune et timer joinprune ppt timer joinprune kat timer joinprune ot timer assert timer register timer bsr bst timer bsr crp mib nsm nexthop mtrace) . . . . .	1144
debug ipv6 pim (vrf NAME ) . . . . .	1144
no debug ipv6 pim (vrf NAME ) . . . . .	1144
IPI-VXLAN . . . . .	1145
Configure mac address . . . . .	1145
Configure enable vxlan . . . . .	1145
Configure vtep ipv4 . . . . .	1146
Configure mac ageing timer . . . . .	1146
Configure arp nd refresh timer . . . . .	1147
Configure maximum cache disable count . . . . .	1147
Configure disable arp storm control for cpu . . . . .	1147
Configure traffic direction . . . . .	1148
Configure tenant type . . . . .	1148
Configure bridge vlan id . . . . .	1149
Configure vrf name . . . . .	1150
Configure map network . . . . .	1150
Configure mac hold timer . . . . .	1151
Configure tenant description . . . . .	1151
Configure irb name . . . . .	1152
Configure irb advertise host route . . . . .	1152
Configure vxlan identifier . . . . .	1153
Configure untagged interface name . . . . .	1153
Configure default access interface . . . . .	1154
Configure admin shutdown . . . . .	1154
Configure description . . . . .	1155
Configure dynamic learning disable . . . . .	1155
Configure access mac hold time . . . . .	1156
Configure arp nd flood suppress . . . . .	1156
Configure garp gna enable . . . . .	1157

---

---

Configure untagged-access-interface mac-address . . . . .	1157
Configure arp cache disable . . . . .	1158
Configure nd cache disable . . . . .	1159
Configure map vxlan-identifier . . . . .	1159
Configure map tenant-description . . . . .	1160
Configure ipv4 address . . . . .	1161
Configure ipv6 address . . . . .	1161
Configure profile map type. . . . .	1162
Configure vlan identifier . . . . .	1163
Configure tag protocol identifier . . . . .	1163
Configure interface name. . . . .	1164
Configure tagged-access-interface description . . . . .	1164
Configure tagged-access-interface dynamic-learning-disable . . . . .	1165
Configure tagged-access-interface access-mac-hold-time . . . . .	1165
Configure tagged-access-interface arp-nd-flood-suppress . . . . .	1166
Configure tagged-access-interface garp-gna-enable. . . . .	1167
Configure tagged-access-interface mac-address . . . . .	1167
Configure cache arp-cache-disable . . . . .	1168
Configure cache nd-cache-disable . . . . .	1168
Configure map vxlan-identifier . . . . .	1169
Configure map tenant-description . . . . .	1170
Configure host-macs-ipv4 mac-address . . . . .	1170
Configure host-macs-ipv6 mac-address . . . . .	1171
Configure profile name. . . . .	1172
Configure inner vlan identifier . . . . .	1173
Configure double-tagged-access-interface tag-protocol-identifier . . . . .	1173
Configure double-tagged-access-interface admin-shutdown. . . . .	1174
Configure double-tagged-access-interface description . . . . .	1174
Configure double-tagged-access-interface dynamic-learning-disable . . . . .	1175
Configure double-tagged-access-interface access-mac-hold-time . . . . .	1176
Configure double-tagged-access-interface arp-nd-flood-suppress . . . . .	1176
Configure double-tagged-access-interface garp-gna-enable. . . . .	1177
Configure double-tagged-access-interface mac-address . . . . .	1177
Configure map vxlan-identifier . . . . .	1178
Configure map tenant-description . . . . .	1179
Configure cache arp-cache-disable . . . . .	1179
Configure cache nd-cache-disable . . . . .	1180
Configure host-macs-ipv4 mac-address . . . . .	1181
Configure host-macs-ipv6 mac-address . . . . .	1182
Configure access-interface-qos-type-mappings profile-map-type . . . . .	1182
Configure access if . . . . .	1183
clear mac address-table dynamic vxlan. . . . .	1184
clear mac address-table dynamic vxlan vnid <1-16777215> (address MACADDR ) . . . . .	1184
clear nvo vxlan tunnels . . . . .	1184
clear nvo vxlan tunnels dst-ip A.B.C.D. . . . .	1185
clear nvo vxlan mac-stale-entries (vnid <1-16777215> ) . . . . .	1185
clear nvo vxlan counters access-port port IFNAME . . . . .	1185

---

---

clear nvo vxlan counters access-port port-vlan IFNAME VLAN_RANGE . . . . .	1185
clear nvo vxlan counters access-port port-vlan IFNAME outer-vlan <2-4094> inner-vlan <2-4094> . . . . .	1186
clear nvo vxlan counters access-port all . . . . .	1186
clear nvo vxlan counters network-port dst A.B.C.D . . . . .	1187
clear nvo vxlan counters network-port all . . . . .	1187
<b>IPI-ETHERNET-VPN . . . . .</b>	<b>1187</b>
Configure esi hold time . . . . .	1187
Configure enable vxlan multihoming . . . . .	1188
Configure global enable-vxlan-multihoming . . . . .	1188
Configure enable irb . . . . .	1188
Configure enable evpn etree . . . . .	1189
Configure mac address . . . . .	1189
Configure gateway mac . . . . .	1190
Configure name . . . . .	1190
Configure system mac . . . . .	1191
Configure service type . . . . .	1191
<b>IPI-TFO . . . . .</b>	<b>1192</b>
Configure admin status . . . . .	1192
Configure link type . . . . .	1192
Configure fog id . . . . .	1192
Configure group id . . . . .	1193
Configure failover trigger count . . . . .	1194
clear tfo counter . . . . .	1194
clear tfo counter fog <1-64> . . . . .	1194
<b>IPI-LOGGING . . . . .</b>	<b>1195</b>
Configure severity level . . . . .	1195
Configure enable logging . . . . .	1195
Configure console-logging severity-level . . . . .	1196
Configure max file size . . . . .	1196
Configure file name . . . . .	1197
Configure debug-logfile max-file-size . . . . .	1197
Configure enable syslog . . . . .	1198
Configure timestamp granularity . . . . .	1198
Configure cli timestamp . . . . .	1199
Configure disable all modules debug . . . . .	1199
no debug all . . . . .	1199
clear debug logfile . . . . .	1200
clear logging logfile . . . . .	1200
remove file (techsupport) (all FILENAME) . . . . .	1200
<b>IPI-LOGGING-REMOTE . . . . .</b>	<b>1200</b>
Configure enable . . . . .	1200
Configure enable rsyslog . . . . .	1201
Configure port . . . . .	1201
Configure severity . . . . .	1202
Configure disable default instance . . . . .	1203
Configure remote server facility . . . . .	1203

---

Configure remote authpriv facility . . . . .	1204
<b>IPI-LOGGING-CLI . . . . .</b>	<b>1204</b>
Configure enable logging . . . . .	1204
Configure max session limit . . . . .	1204
<b>IPI-EVENT-MANAGER . . . . .</b>	<b>1205</b>
Configure feature . . . . .	1205
Configure event pattern . . . . .	1205
Configure action script . . . . .	1206
Configure action name . . . . .	1207
clear event-manager statistics all . . . . .	1207
clear event-manager statistics policy NAME . . . . .	1207
<b>IPI-LOGGING-FAULT-MANAGEMENT . . . . .</b>	<b>1208</b>
Configure enable fault management . . . . .	1208
fault-management flush-db . . . . .	1208
fault-management shelve ALARM-TYPE . . . . .	1208
fault-management close ACTIVE-ALARM-ID . . . . .	1209
<b>IPI-DHCP . . . . .</b>	<b>1209</b>
Configure disable dhcp feature . . . . .	1209
<b>IPI-RADIUS . . . . .</b>	<b>1210</b>
Configure vrf name . . . . .	1210
Configure timeout . . . . .	1210
Configure sequence number . . . . .	1211
Configure secret key string . . . . .	1212
Configure accounting port . . . . .	1212
Configure host address . . . . .	1213
Configure authentication port . . . . .	1214
Configure key type . . . . .	1215
Configure server timeout . . . . .	1216
Configure server timeout . . . . .	1218
Configure server timeout . . . . .	1219
Configure server authentication-port . . . . .	1220
Configure server accounting-port . . . . .	1220
Configure server timeout . . . . .	1221
Configure server timeout . . . . .	1222
Configure server accounting-port . . . . .	1223
Configure server timeout . . . . .	1224
Configure server timeout . . . . .	1225
Configure enable . . . . .	1226
clear radius-server counters (vrf management ) . . . . .	1226
clear radius-server host (A.B.C.D X:X::X:X HOSTNAME) counters (vrf (management all)) . . . . .	1227
debug radius . . . . .	1227
no debug radius . . . . .	1227
<b>IPI-USER-MANAGEMENT . . . . .</b>	<b>1227</b>
Configure enable . . . . .	1227
Configure disable default user . . . . .	1228
Configure username . . . . .	1228

---

---

Configure role . . . . .	1229
Configure password . . . . .	1229
Configure password hashed . . . . .	1230
Configure rbac role . . . . .	1230
Configure user password . . . . .	1231
Configure user password-hashed . . . . .	1231
Configure user password . . . . .	1232
Configure user password-hashed . . . . .	1232
debug user-mgmt . . . . .	1233
no debug user-mgmt . . . . .	1233
<b>IPI-SSH . . . . .</b>	<b>1233</b>
Configure enable . . . . .	1233
Configure vrf name . . . . .	1234
Configure vrf enable . . . . .	1234
Configure port . . . . .	1235
Configure max login attempts . . . . .	1235
Configure session limit . . . . .	1236
Configure default algorithm . . . . .	1236
Configure chacha20 poly1305 . . . . .	1237
Configure curve25519 sha256 libssh org . . . . .	1238
Configure umac 128 etm . . . . .	1240
Configure public key . . . . .	1241
debug ssh server . . . . .	1242
no debug ssh server . . . . .	1242
clear ssh hosts . . . . .	1242
ssh keygen host dsa (vrf (NAME management)) (force) . . . . .	1243
ssh keygen host rsa (length <1024-4096> ) (vrf (NAME management)) (force) . . . . .	1243
ssh keygen host ecdsa (length (256 384 521) ) (vrf (NAME management)) (force) . . . . .	1244
ssh keygen host ed25519 (vrf (NAME management)) (force) . . . . .	1244
clear ssh host-key ((dsa rsa ecdsa ed25519) ) (vrf (NAME management)) . . . . .	1245
username USERNAME keypair rsa (length <1024-4096> ) (force) . . . . .	1245
username USERNAME keypair dsa (force) . . . . .	1245
clear ssh keypair user USERNAME . . . . .	1246
<b>IPI-TELNET . . . . .</b>	<b>1246</b>
Configure enable . . . . .	1246
Configure vrf name . . . . .	1247
Configure vrf enable . . . . .	1247
Configure port . . . . .	1247
Configure session limit . . . . .	1248
debug telnet server . . . . .	1249
no debug telnet server . . . . .	1249
<b>IPI-NTP . . . . .</b>	<b>1249</b>
Configure feature enable . . . . .	1249
Configure vrf name . . . . .	1249
Configure enable ntp . . . . .	1250
Configure vrf enable-ntp . . . . .	1250
Configure enable logging . . . . .	1251

---

Configure enable local master . . . . .	1251
Configure local stratum . . . . .	1252
Configure enable ntp auth . . . . .	1253
Configure ntp trusted keys . . . . .	1253
Configure ntp request key . . . . .	1254
Configure key id . . . . .	1254
Configure key value . . . . .	1255
Configure prefer . . . . .	1256
Configure server address . . . . .	1257
Configure peer address . . . . .	1258
Configure peer peer-address . . . . .	1259
Configure minimum pkt spacing . . . . .	1259
Configure netmask . . . . .	1260
Configure access options . . . . .	1260
Configure client ip address . . . . .	1261
Configure access-control-entry client-ip-address . . . . .	1262
Configure enable . . . . .	1262
clear ntp statistics (all-peers io local memory) . . . . .	1263
ntp sync-retry (vrf (management NAME)) . . . . .	1263
debug ntp . . . . .	1263
no debug ntp . . . . .	1263
IPI-AAA . . . . .	1264
Configure authentication method rule . . . . .	1264
Configure vrf name . . . . .	1264
Configure vrf authentication-method-rule . . . . .	1265
Configure vrf authentication-method-rule . . . . .	1265
Configure accounting method rule . . . . .	1266
Configure vrf accounting-method-rule . . . . .	1266
Configure authorization method rule . . . . .	1267
Configure vrf authorization-method-rule . . . . .	1267
Configure error enable . . . . .	1268
Configure enable fallback . . . . .	1268
Configure group type . . . . .	1269
Configure host address . . . . .	1269
Configure group name . . . . .	1270
Configure aaa-authentication-console authentication-method-rule . . . . .	1271
Configure aaa-authentication-console authentication-method-rule . . . . .	1271
Configure aaa-authentication-console authentication-method-rule . . . . .	1272
Configure aaa-authentication-console authentication-method-rule . . . . .	1272
Configure aaa-authentication-console authorization-method-rule . . . . .	1272
Configure aaa-authentication-console authorization-method-rule . . . . .	1273
Configure aaa-authentication-console accounting-method-rule . . . . .	1273
Configure aaa-authentication-console accounting-method-rule . . . . .	1274
Configure user non existent . . . . .	1274
Configure authentication max failure attempts . . . . .	1274
Configure local user unlock timeout . . . . .	1275
Configure enable . . . . .	1275

---

---

Configure numeric count . . . . .	1276
Configure uppercase count . . . . .	1276
Configure lowercase count . . . . .	1277
Configure special count . . . . .	1277
Configure history . . . . .	1278
Configure maxsequence . . . . .	1278
Configure disable usercheck . . . . .	1278
Configure maxrepeat . . . . .	1279
Configure min length . . . . .	1279
Configure role . . . . .	1280
Configure user . . . . .	1280
Configure debug enable. . . . .	1281
debug aaa . . . . .	1281
no debug aaa . . . . .	1282
clear aaa local user lockout username USERNAME . . . . .	1282
IPI-DHCP-RELAY . . . . .	1282
Configure disable dhcpv4 relay . . . . .	1282
Configure disable dhcpv6 relay . . . . .	1283
Configure ipv4 relay interface . . . . .	1283
Configure ipv4 uplink interface. . . . .	1284
Configure ipv4 group name . . . . .	1284
Configure ipv6 relay interface . . . . .	1285
Configure ipv6 uplink interface. . . . .	1285
Configure ipv6 group name . . . . .	1286
Configure interface type. . . . .	1286
Configure interface type v6 . . . . .	1287
Configure link selection source ip . . . . .	1288
Configure enable option82. . . . .	1288
Configure ip address . . . . .	1289
Configure dhcpv4 server global vrf . . . . .	1289
Configure vrf name . . . . .	1290
Configure ipv6 address . . . . .	1291
Configure dhcpv6 server global vrf . . . . .	1291
Configure ipv6-dhcp-server dhcpv6-server-global-vrf . . . . .	1292
Configure enable dhcpv6 pd route injection. . . . .	1293
Configure remote id . . . . .	1293
Configure vrf remote-id . . . . .	1294
Configure vrf remote-id . . . . .	1294
Configure vrf remote-id . . . . .	1295
Configure enable option82 always on . . . . .	1295
Configure vrf enable-option82-always-on . . . . .	1296
Configure subscriber id . . . . .	1297
Configure group6 name . . . . .	1297
Configure group name . . . . .	1298
Configure vrf link-selection-source-ip. . . . .	1298
Configure vrf enable-option82 . . . . .	1299
Configure vrf enable-dhcpv6-pd-route-injection. . . . .	1299

---

---

Configure enable dhcpv6 duplicate clients	1300
Configure vrf subscriber-id	1300
Configure interface direction	1301
Configure interface direction v6	1302
Configure ipv4-dhcp-servers ip-address	1302
Configure ipv4-dhcp-server ip-address	1303
Configure ipv6-dhcp-servers ipv6-address	1304
Configure ipv6-dhcp-server ipv6-address	1304
Configure dhcp-groups group-name	1305
Configure server	1306
Configure dhcpv6-groups group6-name	1306
Configure dhcpv6-group server	1307
clear ip dhcp relay statistics	1308
clear ip dhcp relay option statistics	1308
clear ipv6 dhcp pd-route (vrf NAME )	1308
<b>IPI-DNS-RELAY</b>	<b>1308</b>
Configure enable dns feature	1308
Configure dns-relay enable-dns-feature	1309
Configure enable dnsv4 relay	1309
Configure dns-relay enable-dnsv4-relay	1309
Configure enable dnsv6 relay	1310
Configure dns-relay enable-dnsv6-relay	1310
Configure dns server v4 addr	1311
Configure dns server v6 addr	1311
Configure name	1311
Configure interface enable-dnsv6-relay	1312
Configure dns relay uplink	1312
Configure dns relay v6 uplink	1313
Configure vrf name	1313
Configure vrf dns-server-v6-addr	1314
<b>IPI-DNS-CLIENT</b>	<b>1314</b>
Configure default domain name	1314
Configure lookup enabled	1315
Configure vrf name	1315
Configure address	1316
Configure domain name	1316
Configure ipv6 address	1317
Configure ipv4 address	1318
Configure hostname	1318
Configure host-entry ipv6-address	1319
Configure enable	1319
debug dns client	1320
no debug dns client	1320
<b>IPI-DHCP-CLIENT</b>	<b>1320</b>
Configure request ipv4 dns	1320
Configure request log server	1321
Configure request host name	1321

---

---

Configure request ntp server . . . . .	1322
Configure request ipv6 dns . . . . .	1322
Configure request ipv6 domain list. . . . .	1323
Configure request ipv6 ntp server . . . . .	1323
Configure request ipv6 rapid commit . . . . .	1324
Configure request ipv6 vendor opts . . . . .	1324
Configure ipv6 information request . . . . .	1325
Configure ipv6 dad wait time . . . . .	1325
Configure ipv6 client duid type. . . . .	1326
Configure ipv6 max delegated prefix . . . . .	1326
Configure request ipv6 prefix . . . . .	1327
Configure suffix ipv6 addr . . . . .	1327
<b>IPI-DHCP-SERVER . . . . .</b>	<b>1328</b>
Configure enable ipv4 server . . . . .	1328
Configure enable ipv6 server . . . . .	1329
Configure pool6 name . . . . .	1329
Configure pool name . . . . .	1330
Configure max lease time . . . . .	1331
Configure default lease time . . . . .	1331
Configure rapid commit . . . . .	1332
Configure preference . . . . .	1332
Configure vrf name . . . . .	1333
Configure vrf preference . . . . .	1333
Configure vrf max-lease-time. . . . .	1334
Configure vrf default-lease-time. . . . .	1334
Configure dhcp-pools pool-name. . . . .	1335
Configure host name . . . . .	1335
Configure routers . . . . .	1336
Configure ntp server . . . . .	1337
Configure boot file . . . . .	1337
Configure tftp server . . . . .	1338
Configure log server. . . . .	1339
Configure dns server . . . . .	1339
Configure netmask. . . . .	1340
Configure high address in range . . . . .	1341
Configure dhcp6-pools pool6-name. . . . .	1342
Configure domain name. . . . .	1342
Configure vendor options. . . . .	1343
Configure dhcp6-pool ntp-server . . . . .	1344
Configure dhcp6-pool dns-server. . . . .	1344
Configure ipv6 netmask. . . . .	1345
Configure low address in range . . . . .	1346
Configure temporary address . . . . .	1347
Configure ipv6 prefix netmask . . . . .	1347
<b>IPI-SFLOW . . . . .</b>	<b>1348</b>
Configure enabled . . . . .	1348
Configure source address . . . . .	1349

---

---

Configure cpu rate limit . . . . .	1349
Configure vrf name . . . . .	1350
Configure max entries . . . . .	1350
Configure rate limit. . . . .	1351
Configure options. . . . .	1351
clear access-list log-cache. . . . .	1352
debug sflow (agent sampling polling all) . . . . .	1352
no debug sflow (agent sampling polling all). . . . .	1352
<b>IPI-SFLOW-INTERFACE . . . . .</b>	<b>1353</b>
Configure enabled . . . . .	1353
Configure polling interval . . . . .	1353
Configure collector id . . . . .	1354
Configure sample size . . . . .	1355
Configure name . . . . .	1355
clear sflow statistics (interface IFNAME ) . . . . .	1356
<b>IPI-WATCHDOG . . . . .</b>	<b>1356</b>
Configure watchdog disabled. . . . .	1356
Configure keepalive interval. . . . .	1357
Configure module watchdog status disabled . . . . .	1357
clear cores (WORD ) . . . . .	1358
sys-update un-install . . . . .	1358
sys-container (raon) (install update) file FILENAME . . . . .	1358
sys-container (raon) un-install . . . . .	1359
sys-container (raon) (start stop restart) . . . . .	1359
sys-container (raon) get URL (source-interface IFNAME ) . . . . .	1359
sys-container (raon) remove file FILENAME . . . . .	1360
sys-container (raon) verify image FILEPATH signature FILEPATH . . . . .	1360
sys-container cancel download . . . . .	1361
<b>IPI-MRIB-IPV4 . . . . .</b>	<b>1361</b>
Configure options . . . . .	1361
Configure multicast routing enable . . . . .	1362
Configure maximum routes . . . . .	1362
Configure warning threshold . . . . .	1363
Configure ttl threshold . . . . .	1364
debug ip mrib (vrf WORD ) (all event vif mrt stats fib-msg register-msg nsm-msg mrib- msg mtrace mtrace-detail) . . . . .	1364
no debug ip mrib (vrf WORD ) (all event vif mrt stats fib-msg register-msg nsm-msg mrib- msg mtrace mtrace-detail) . . . . .	1365
clear ip mroute (vrf NAME ) * . . . . .	1365
clear ip mroute (vrf NAME ) A.B.C.D . . . . .	1365
clear ip mroute (vrf NAME ) A.B.C.D A.B.C.D . . . . .	1366
clear ip mroute (vrf NAME ) statistics * . . . . .	1366
clear ip mroute (vrf NAME ) statistics A.B.C.D . . . . .	1367
clear ip mroute (vrf NAME ) statistics A.B.C.D A.B.C.D . . . . .	1367
snmp restart mrib . . . . .	1367
<b>IPI-MRIB-IPV6 . . . . .</b>	<b>1368</b>
Configure options . . . . .	1368

---

---

Configure multicast routing enable	1368
Configure maximum routes	1369
Configure warning threshold	1369
debug ipv6 mrib (vrf WORD ) (all event vif mrt stats fib-msg register-msg nsm-msg mrib- msg mtrace mtrace-detail)	1370
no debug ipv6 mrib (vrf WORD ) (all event vif mrt stats fib-msg register-msg nsm-msg mrib- msg mtrace mtrace-detail)	1371
clear ipv6 mroute (vrf NAME ) *	1371
clear ipv6 mroute (vrf NAME ) X:X::X:X	1371
clear ipv6 mroute (vrf NAME ) X:X::X:X X:X::X:X	1372
clear ipv6 mroute (vrf NAME ) statistics *	1372
clear ipv6 mroute (vrf NAME ) statistics X:X::X:X	1373
clear ipv6 mroute (vrf NAME ) statistics X:X::X:X X:X::X:X	1373
<b>IPI-IGMP</b>	<b>1373</b>
Configure disable ssm map	1373
Configure disable tos check	1374
Configure limit exception acl	1374
Configure member limit	1375
Configure source	1376
Configure options	1377
debug ip igmp (vrf NAME ) (all decode encode events fsm tib)	1377
no debug ip igmp (vrf NAME ) (all decode encode events fsm tib)	1377
clear ip igmp (vrf NAME )	1378
clear ip igmp (vrf NAME ) group *	1378
clear ip igmp (vrf NAME ) group A.B.C.D IFNAME	1379
clear ip igmp (vrf NAME ) interface IFNAME	1379
clear ip igmp (vrf NAME ) group A.B.C.D	1379
<b>IPI-IGMP-INTERFACE</b>	<b>1380</b>
Configure enabled	1380
Configure last member query count	1380
Configure last member query interval	1381
Configure querier timeout	1381
Configure query interval	1382
Configure query max response time	1383
Configure startup query interval	1383
Configure startup query count	1384
Configure robustness variable	1384
Configure version	1385
Configure require router alert option	1385
Configure allow offlink host	1386
Configure enable proxy service	1386
Configure mroute proxy interface	1387
Configure unsolicited report interval	1387
Configure limit exception acl	1388
Configure member limit	1389
Configure access group name	1389
Configure immediate leave groups list	1390

---

---

Configure group address . . . . .	1390
Configure source . . . . .	1391
Configure name . . . . .	1392
Configure ssm-join-groups source . . . . .	1392
<b>IPI-IGMP-SNOOPING</b> . . . . .	<b>1393</b>
Configure disable igmp snooping . . . . .	1393
Configure disable report suppression . . . . .	1393
Configure unknown multicast action . . . . .	1394
Configure options . . . . .	1394
Configure igmp snooping . . . . .	1395
Configure report suppression . . . . .	1395
Configure enable fast leave . . . . .	1396
Configure mrouter interface name . . . . .	1396
Configure enable querier . . . . .	1397
Configure name . . . . .	1397
Configure interface enable-fast-leave . . . . .	1398
Configure interface report-suppression . . . . .	1398
Configure interface mrouter-interface-name . . . . .	1399
Configure interface enable-querier . . . . .	1399
Configure source address . . . . .	1400
Configure group address . . . . .	1400
clear igmp snooping group A.B.C.D IFNAME . . . . .	1401
clear igmp snooping interface IFNAME . . . . .	1402
clear igmp snooping group * . . . . .	1402
clear igmp snooping . . . . .	1402
clear igmp snooping group A.B.C.D . . . . .	1402
debug igmp snooping (decode encode events fsm tib all) . . . . .	1403
no debug igmp snooping (decode encode events fsm tib all) . . . . .	1403
<b>IPI-MLD-SNOOPING</b> . . . . .	<b>1403</b>
Configure disable mld snooping . . . . .	1403
Configure disable report suppression . . . . .	1404
Configure options . . . . .	1404
Configure report suppression . . . . .	1404
Configure mld snooping . . . . .	1405
Configure enable fast leave . . . . .	1405
Configure name . . . . .	1406
Configure mrouter interface name . . . . .	1406
Configure enable querier . . . . .	1407
debug mld snooping (decode encode events fsm tib all) . . . . .	1407
no debug mld snooping (decode encode events fsm tib all) . . . . .	1408
clear mld snooping group X:X::X:X IFNAME . . . . .	1408
clear mld snooping interface IFNAME . . . . .	1408
clear mld snooping group X:X::X:X . . . . .	1409
clear mld snooping group * . . . . .	1409
clear mld snooping . . . . .	1409
<b>IPI-MLD</b> . . . . .	<b>1409</b>
Configure disable ssm map . . . . .	1409

---

---

Configure limit exception acl . . . . .	1410
Configure member limit . . . . .	1411
Configure source . . . . .	1411
Configure debug options . . . . .	1412
debug ipv6 mld (vrf NAME ) (all decode encode events fsm tib) . . . . .	1413
no debug ipv6 mld (vrf NAME ) (all decode encode events fsm tib) . . . . .	1413
clear ipv6 mld (vrf NAME ) . . . . .	1413
clear ipv6 mld (vrf NAME ) group * . . . . .	1414
clear ipv6 mld (vrf NAME ) group X:X::X:X IFNAME . . . . .	1414
clear ipv6 mld (vrf NAME ) interface IFNAME . . . . .	1414
clear ipv6 mld (vrf NAME ) group X:X::X:X . . . . .	1415
<b>IPI-MLD-INTERFACE . . . . .</b>	<b>1415</b>
Configure enabled . . . . .	1415
Configure last member query count . . . . .	1416
Configure last member query interval . . . . .	1416
Configure querier timeout . . . . .	1417
Configure query interval . . . . .	1417
Configure query max response time . . . . .	1418
Configure startup query interval . . . . .	1419
Configure startup query count . . . . .	1419
Configure robustness variable . . . . .	1420
Configure version . . . . .	1420
Configure enable proxy service . . . . .	1421
Configure mroute proxy interface . . . . .	1421
Configure unsolicited report interval . . . . .	1422
Configure limit exception acl . . . . .	1423
Configure member limit . . . . .	1423
Configure access group name . . . . .	1424
Configure immediate leave groups list . . . . .	1425
Configure group address . . . . .	1425
Configure source . . . . .	1426
<b>IPI-ROUTEMAP . . . . .</b>	<b>1427</b>
Configure action . . . . .	1427
Configure continue to next sequence . . . . .	1427
Configure next sequence number . . . . .	1428
Configure interface name . . . . .	1428
Configure metric . . . . .	1429
Configure tag . . . . .	1429
Configure route type . . . . .	1430
Configure as path name . . . . .	1431
Configure route origin . . . . .	1431
Configure community identifier . . . . .	1432
Configure extended community identifier . . . . .	1433
Configure match type . . . . .	1434
Configure ip access list name . . . . .	1434
Configure ip prefix list name . . . . .	1435
Configure peer access list name . . . . .	1436

---

Configure next hop prefix list name . . . . .	1436
Configure next hop access list name . . . . .	1437
Configure ipv6 address access list name . . . . .	1438
Configure ipv6 prefix list name . . . . .	1438
Configure routemap name . . . . .	1439
Configure sequence id . . . . .	1440
Configure next hop match string . . . . .	1440
Configure large community number match . . . . .	1441
Configure metric value . . . . .	1442
Configure forward interface type . . . . .	1442
Configure route tag . . . . .	1443
Configure weight . . . . .	1443
Configure local preference . . . . .	1444
Configure route origin type . . . . .	1445
Configure metric type . . . . .	1445
Configure aigp metric . . . . .	1446
Configure level type . . . . .	1446
Configure enable as path tag . . . . .	1447
Configure atomic aggregate . . . . .	1448
Configure delete community value . . . . .	1448
Configure bgp originator id . . . . .	1449
Configure as path prepend . . . . .	1449
Configure ext community site of origin . . . . .	1450
Configure ext community color . . . . .	1451
Configure ip nexthop address . . . . .	1451
Configure use peer address . . . . .	1452
Configure vpv4 nexthop address . . . . .	1452
Configure ipv6 nexthop address . . . . .	1453
Configure local ipv6 nexthop address . . . . .	1454
Configure aggregator ip address . . . . .	1454
Configure ext community rt . . . . .	1455
Configure cost value . . . . .	1456
Configure max suppress time limit . . . . .	1456
Configure unreachable half life time . . . . .	1458
Configure enable dampening . . . . .	1459
Configure community with as number . . . . .	1460
Configure large community number set . . . . .	1460
<b>IPI-DCB . . . . .</b>	<b>1461</b>
Configure dcb enabled . . . . .	1461
Configure bridge id . . . . .	1461
Configure enable ets . . . . .	1462
Configure enable application priority . . . . .	1462
Configure enable pfc . . . . .	1463
Configure enabled . . . . .	1463
Configure priority value . . . . .	1464
Configure qcn mode . . . . .	1465
Configure enable . . . . .	1466

---

---

IPI-DCB-INTERFACE	1466
Configure pfc mode	1466
Configure ets mode	1467
Configure priority value	1467
Configure name	1468
Configure cnpv value	1469
Configure weight	1470
Configure accept peer config	1470
Configure advertise local config	1471
Configure cap.	1472
Configure link delay allowance	1472
Configure enhanced-transmission-selection advertise-local-config	1473
Configure enhanced-transmission-selection accept-peer-config	1473
Configure max traffic class groups	1474
Configure bandwidth percentage	1475
Configure enabled	1475
Configure application-priority advertise-local-config	1476
Configure protocol type	1476
Configure service name	1477
Configure ether name	1478
Configure ether value.	1479
IPI-RIP	1480
Configure options	1480
Configure split horizon	1480
Configure name	1480
Configure disable receive packet	1481
Configure disable send packet	1481
Configure receive version	1482
Configure send version	1482
Configure auth mode	1483
Configure auth string	1483
Configure auth keychain	1484
Configure rip enabled.	1484
Configure bfd enable	1485
Configure receive buffer size	1485
Configure passive interfaces	1485
Configure static routes	1486
Configure neighbors	1486
Configure neighbor fall over bfd	1487
Configure enable cisco metric behavior	1487
Configure default metric	1487
Configure version	1488
Configure distance	1488
Configure network interfaces	1489
Configure network routes	1489
Configure access list name	1489
Configure route table update interval	1490

---

---

Configure warning threshold percentage . . . . .	1491
Configure route type . . . . .	1491
Configure route map . . . . .	1492
Configure metric. . . . .	1492
Configure redistribute-policy route-map. . . . .	1493
Configure originate. . . . .	1493
Configure direction. . . . .	1494
Configure distribute-filter-list direction . . . . .	1495
Configure distribute-prefix-list direction . . . . .	1495
Configure offset-list metric . . . . .	1496
Configure distribute-filter-list direction . . . . .	1496
Configure distribute-prefix-list direction . . . . .	1497
clear ip rip route (kernel connected static ospf isis bgp rip all). . . . .	1498
clear ip rip route A.B.C.D/M . . . . .	1498
clear ip rip statistics (IFNAME ) . . . . .	1498
snmp restart rip . . . . .	1499
debug rip (all events packet send packet recv packet packet detail nsm rib bfd). . . . .	1499
no debug rip (all events packet send packet recv packet packet detail nsm rib bfd) . . . . .	1499
<b>IPI-RIP-VRF . . . . .</b>	<b>1500</b>
Configure vrf name . . . . .	1500
Configure enable cisco metric behavior. . . . .	1500
Configure default metric. . . . .	1501
Configure version. . . . .	1501
Configure distance. . . . .	1502
Configure network interfaces . . . . .	1502
Configure network routes. . . . .	1503
Configure access list name . . . . .	1503
Configure route type . . . . .	1504
Configure route map . . . . .	1505
Configure metric. . . . .	1506
Configure redistribute-policy route-map. . . . .	1506
Configure originate. . . . .	1507
Configure direction. . . . .	1508
Configure distribute-filter-list direction . . . . .	1508
Configure distribute-prefix-list direction . . . . .	1509
Configure name . . . . .	1510
Configure distribute-filter-list direction . . . . .	1511
Configure distribute-prefix-list direction . . . . .	1512
clear ip rip route vrf NAME A.B.C.D/M . . . . .	1512
clear ip rip route vrf NAME * . . . . .	1513
<b>IPI-SNMP . . . . .</b>	<b>1513</b>
Configure enable link down trap . . . . .	1513
Configure enable link up trap . . . . .	1514
Configure include interface name . . . . .	1514
Configure server-traps enable-link-down-trap . . . . .	1515
Configure server-traps enable-link-down-trap . . . . .	1515
Configure server-traps enable-link-up-trap . . . . .	1515

---

Configure server-traps enable-link-up-trap . . . . .	1516
Configure enable traps. . . . .	1516
Configure enable trap cache . . . . .	1517
Configure timeout. . . . .	1517
Configure disable ping . . . . .	1518
Configure max count . . . . .	1518
debug (snmp send snmp receive snmp process snmp xdump snmp error-string snmp detail snmp snmp all) . . . . .	1519
no debug (snmp send snmp receive snmp process snmp xdump snmp error-string snmp detail snmp snmp all) . . . . .	1519
<b>IPI-SNMP-SERVER</b> . . . . .	<b>1519</b>
Configure vrf name . . . . .	1519
Configure system contact . . . . .	1520
Configure system location . . . . .	1520
Configure tcp session enabled. . . . .	1521
Configure disable default instance. . . . .	1522
Configure ent ipi iftable . . . . .	1522
<b>IPI-SNMP-SERVER-EXTENDED</b> . . . . .	<b>1522</b>
Configure include directive. . . . .	1522
Configure enable . . . . .	1523
Configure filter type . . . . .	1523
Configure engine id . . . . .	1524
Configure smux port enable. . . . .	1524
Configure host name . . . . .	1525
Configure notification type . . . . .	1526
Configure snmp version. . . . .	1527
Configure snmpv3 auth type . . . . .	1528
Configure community . . . . .	1529
Configure snmpv3 user . . . . .	1530
Configure udp port . . . . .	1531
Configure user name . . . . .	1532
Configure authentication type . . . . .	1533
Configure user type . . . . .	1534
Configure encryption type . . . . .	1535
Configure authentication password . . . . .	1536
Configure privilege type . . . . .	1537
Configure privilege password. . . . .	1538
Configure vrf name . . . . .	1539
Configure user user-name . . . . .	1540
Configure user user-type . . . . .	1540
Configure context name. . . . .	1541
Configure acl name . . . . .	1542
Configure community name . . . . .	1542
Configure snmp group . . . . .	1543
Configure access privileges . . . . .	1544
Configure access . . . . .	1544
Configure community context . . . . .	1545

---

Configure group name . . . . .	1546
Configure group version . . . . .	1547
Configure context . . . . .	1548
Configure snmpv3 group auth type . . . . .	1548
debug snmp-server . . . . .	1549
no debug snmp-server . . . . .	1550
IPI-QOS . . . . .	1550
Configure enable qos . . . . .	1550
Configure name . . . . .	1550
Configure color . . . . .	1551
Configure dscp-to-queue-profiles name . . . . .	1552
Configure dscp value . . . . .	1552
Configure queue id . . . . .	1553
Configure queue-color-to-cos-profiles name . . . . .	1554
Configure cos value . . . . .	1554
Configure queue-to-precedence-profiles name . . . . .	1555
Configure precedence value . . . . .	1556
Configure precedence-to-queue-profiles name . . . . .	1557
Configure precedence-to-queue queue-id . . . . .	1557
Configure queue-color-to-dscp-profiles name . . . . .	1558
Configure queue-color-to-dscps color . . . . .	1559
Configure cos . . . . .	1559
Configure dei . . . . .	1560
Configure dscp . . . . .	1560
Configure type . . . . .	1561
Configure match criteria . . . . .	1561
Configure class-maps name . . . . .	1562
Configure class-maps name . . . . .	1563
Configure class-maps name . . . . .	1563
Configure class-maps name . . . . .	1564
Configure reference description . . . . .	1565
Configure access control list name . . . . .	1565
Configure ethertype . . . . .	1566
Configure traffic type . . . . .	1566
Configure match-any-conditions cos . . . . .	1567
Configure inner cos . . . . .	1568
Configure vlan . . . . .	1568
Configure vlan id . . . . .	1569
Configure inner vlan . . . . .	1569
Configure inner vlan id . . . . .	1570
Configure rtp . . . . .	1571
Configure match-any-conditions dscp . . . . .	1571
Configure precedence . . . . .	1572
Configure packet protocol . . . . .	1573
Configure source mac . . . . .	1573
Configure destination mac . . . . .	1574
Configure port type . . . . .	1574

---

---

Configure ethertype all . . . . .	1575
Configure traffic type all . . . . .	1576
Configure cos all . . . . .	1576
Configure inner cos all . . . . .	1577
Configure vlan all . . . . .	1578
Configure inner vlan all . . . . .	1578
Configure rtp all . . . . .	1579
Configure dscp all . . . . .	1579
Configure precedence all . . . . .	1580
Configure packet protocol all . . . . .	1581
Configure source mac all . . . . .	1581
Configure destination mac all . . . . .	1582
Configure port all . . . . .	1583
Configure class-maps name . . . . .	1583
Configure class-map-queuing reference-description . . . . .	1584
Configure qos group . . . . .	1584
Configure vlan queue . . . . .	1585
Configure match-conditions cos . . . . .	1586
Configure policy map name . . . . .	1586
Configure policy-maps policy-map-name . . . . .	1587
Configure policy-maps policy-map-name . . . . .	1587
Configure policy-maps policy-map-name . . . . .	1588
Configure policy-maps policy-map-name . . . . .	1589
Configure policy-map reference-description . . . . .	1589
Configure class map name . . . . .	1590
Configure classes class-map-name . . . . .	1590
Configure classes class-map-name . . . . .	1591
Configure classes class-map-name . . . . .	1592
Configure classes class-map-name . . . . .	1593
Configure classes class-map-name . . . . .	1593
Configure child service policy name . . . . .	1594
Configure class reference-description . . . . .	1595
Configure lossless . . . . .	1595
Configure weighted round robin queue weight . . . . .	1596
Configure strict priority enabled . . . . .	1597
Configure weight . . . . .	1598
Configure min threshold . . . . .	1599
Configure max threshold . . . . .	1600
Configure threshold unit . . . . .	1602
Configure drop probability . . . . .	1603
Configure max threshold type . . . . .	1605
Configure rate value . . . . .	1606
Configure rate type . . . . .	1607
Configure rate unit . . . . .	1607
Configure shapes rate-value . . . . .	1608
Configure priority . . . . .	1609
Configure precedence remark . . . . .	1610

---

---

Configure qos-mode cos-value . . . . .	1611
Configure cos remark only bridged . . . . .	1612
Configure dscp value remark . . . . .	1612
Configure dscp remark only bridged . . . . .	1613
Configure qos-mode queue-id . . . . .	1614
Configure queue remark only bridged . . . . .	1615
Configure qos-mode qos-group . . . . .	1616
Configure non unicast queue weight . . . . .	1616
Configure enabled . . . . .	1617
Configure statistics enabled . . . . .	1617
Configure block size . . . . .	1618
clear qos statistics (interface IFNAME) ((type qos type qos input type qos output type queuing type all)) . . . . .	1618
<b>IPI-QOS-IF . . . . .</b>	<b>1619</b>
Configure untagged priority . . . . .	1619
Configure trust dscp . . . . .	1619
Configure cos . . . . .	1620
Configure dei . . . . .	1620
Configure dscp . . . . .	1621
Configure name . . . . .	1621
Configure rate . . . . .	1622
Configure cos to queue . . . . .	1623
Configure dscp to queue . . . . .	1623
Configure precedence to queue . . . . .	1624
Configure queue color to cos . . . . .	1625
Configure queue color to dscp . . . . .	1625
Configure queue to precedence . . . . .	1626
Configure type qos policy map name . . . . .	1626
Configure egress type-qos-policy-map-name . . . . .	1627
Configure type queuing policy map name . . . . .	1628
<b>IPI-MCEC . . . . .</b>	<b>1628</b>
Configure options . . . . .	1628
Configure system number . . . . .	1629
Configure address . . . . .	1629
Configure priority . . . . .	1629
Configure hello timeout . . . . .	1630
Configure interface . . . . .	1630
Configure hlgig . . . . .	1631
Configure vrf . . . . .	1631
Configure interface mode . . . . .	1632
Configure revertive timer . . . . .	1632
Configure enable non revertive . . . . .	1633
debug mcec (hello info timer event cli mac-sync stp all) . . . . .	1633
no debug mcec (hello info timer event cli mac-sync stp all) . . . . .	1634
clear mcec statistics . . . . .	1634
reload-trigger-mcec-notification . . . . .	1634
<b>IPI-MLAG . . . . .</b>	<b>1634</b>

---

---

Configure mlag id . . . . .	1634
reload-trigger-save-mlag-info . . . . .	1635
<b>IPI-PLATFORM . . . . .</b>	<b>1635</b>
Configure enable cmm . . . . .	1635
Configure enable ddm . . . . .	1636
Configure warning repeat . . . . .	1636
Configure locator led enable . . . . .	1636
Configure ddm monitor time interval . . . . .	1637
Configure service unsupported transceiver . . . . .	1637
Configure enable ddm monitor . . . . .	1638
Configure system 15min load avg alarm . . . . .	1638
Configure alarm threshold . . . . .	1639
Configure monitor port . . . . .	1639
Configure poe enable . . . . .	1640
Configure transceiver code . . . . .	1640
Configure wavelength . . . . .	1641
Configure tx disable . . . . .	1641
Configure edfa operating mode . . . . .	1642
Configure edfa target output power . . . . .	1642
Configure edfa target gain . . . . .	1643
Configure tx cdr bypass . . . . .	1643
Configure rx cdr bypass . . . . .	1644
Configure interval . . . . .	1644
Configure read threshold . . . . .	1645
Configure write threshold . . . . .	1645
Configure temperature policy . . . . .	1645
Configure sensor id . . . . .	1646
Configure value . . . . .	1646
clear ddm transceiver alarm all . . . . .	1647
clear ddm transceiver alarm . . . . .	1647
debug ddm . . . . .	1648
no debug ddm . . . . .	1648
debug cmm . . . . .	1648
no debug cmm . . . . .	1648
<b>IPI-PLATFORM-PROFILE . . . . .</b>	<b>1648</b>
Configure route mode . . . . .	1648
Configure egress ipv6 . . . . .	1649
Configure ingress ipv6 acl . . . . .	1649
Configure ingress ipv4 custom0 . . . . .	1650
Configure ingress arp . . . . .	1650
Configure ingress mirror . . . . .	1651
Configure ingress bfd . . . . .	1651
Configure ipsg ipv6 . . . . .	1652
Configure isolation . . . . .	1652
Configure profile . . . . .	1653
Configure forwarding-profiles profile . . . . .	1653
Configure forwarding-profiles profile . . . . .	1654

---

Configure forwarding-profiles profile . . . . .	1654
Configure forwarding-profiles profile . . . . .	1655
Configure mpls ip payload . . . . .	1655
Configure mpls label based . . . . .	1656
Configure enable . . . . .	1656
Configure load-balance mpls-label-based . . . . .	1656
Configure load-balance mpls-ip-payload . . . . .	1657
Configure hash . . . . .	1657
Configure macro flow based . . . . .	1658
Configure vlan based . . . . .	1658
Configure symmetric . . . . .	1659
Configure src ipv6 address based . . . . .	1660
Configure queue name . . . . .	1660
Configure monitor . . . . .	1661
Configure lossy . . . . .	1662
Configure rate . . . . .	1662
Configure rate-limits queue-name . . . . .	1663
Configure rate-limits queue-name . . . . .	1664
Configure rate-limits queue-name . . . . .	1664
Configure rate-limits queue-name . . . . .	1665
Configure rate-limits queue-name . . . . .	1666
Configure rate-limits queue-name . . . . .	1667
Configure rate-limits queue-name . . . . .	1667
Configure rate-limits queue-name . . . . .	1668
Configure rate-limits queue-name . . . . .	1669
Configure rate-limits queue-name . . . . .	1670
Configure rate-limits queue-name . . . . .	1670
cpu-q-default rate <0-100000> . . . . .	1671
no cpu-q-default rate . . . . .	1672
<b>IPI-PLATFORM-PROFILE-EXTENDED . . . . .</b>	<b>1672</b>
Configure enable mac ageing timer . . . . .	1672
Configure soc . . . . .	1672
Configure lpm banks . . . . .	1673
Configure ep vlan xlate banks . . . . .	1674
Configure outer I3 header . . . . .	1674
Configure dest mac based . . . . .	1675
Configure src ip based . . . . .	1675
Configure src mac based . . . . .	1676
Configure src ip address based . . . . .	1677
Configure disable vxlan . . . . .	1678
Configure type . . . . .	1678
<b>IPI-PLATFORM-CMIS . . . . .</b>	<b>1679</b>
Configure fp port . . . . .	1679
Configure application . . . . .	1679
Configure service disable . . . . .	1680
Configure custom app host id . . . . .	1680
Configure custom app media id . . . . .	1681

---

Configure type . . . . .	1681
Configure location . . . . .	1682
Configure checker type . . . . .	1682
Configure checker location . . . . .	1683
Configure loopback type . . . . .	1683
Configure lane number . . . . .	1684
Configure id . . . . .	1685
Configure high alarm . . . . .	1685
Configure low alarm . . . . .	1686
Configure high warning . . . . .	1687
Configure low warning . . . . .	1688
Configure tx input equalizer target . . . . .	1688
Configure rx output equalizer pre cursor target . . . . .	1689
Configure rx output equalizer post cursor target . . . . .	1690
Configure rx output amplitude target . . . . .	1691
Configure tx cdr bypass . . . . .	1691
Configure rx cdr bypass . . . . .	1692
Configure generator type . . . . .	1693
Configure generator location . . . . .	1693
Configure checker type . . . . .	1694
Configure checker location . . . . .	1695
Configure loopback type . . . . .	1695
Configure lanes lane-number . . . . .	1696
Configure channel . . . . .	1696
Configure grid . . . . .	1697
Configure fine tune freq . . . . .	1698
Configure output power . . . . .	1698
Configure thresholds id . . . . .	1699
Configure threshold high-alarm . . . . .	1700
Configure threshold low-alarm . . . . .	1701
Configure threshold high-warning . . . . .	1701
Configure threshold low-warning . . . . .	1702
Configure laser channel . . . . .	1703
Configure laser grid . . . . .	1703
Configure laser fine-tune-freq . . . . .	1704
Configure laser output-power . . . . .	1704
Configure thresholds id . . . . .	1705
Configure threshold high-alarm . . . . .	1706
Configure threshold low-alarm . . . . .	1706
Configure threshold high-warning . . . . .	1707
Configure threshold low-warning . . . . .	1707
Configure signal-integrity tx-input-equalizer-target . . . . .	1708
Configure signal-integrity rx-output-equalizer-pre-cursor-target . . . . .	1708
Configure signal-integrity rx-output-equalizer-post-cursor-target . . . . .	1709
Configure signal-integrity rx-output-amplitude-target . . . . .	1710
Configure signal-integrity tx-cdr-bypass . . . . .	1710
Configure signal-integrity rx-cdr-bypass . . . . .	1711

---

tibit-olt-microplug set interface IFNAME management-vlan-tpid (0x8100 0x88a8) . . . . .	1711
tibit-olt-microplug set interface IFNAME management-vlan-id <1-4094> . . . . .	1712
tibit-olt-microplug set interface IFNAME ethernet-mac-address XX:XX:XX:XX:XX:XX . . . . .	1712
tibit-olt-microplug set interface IFNAME next-active-firmware-bank-id <0-3> . . . . .	1712
tibit-olt-microplug reboot interface IFNAME . . . . .	1713
<b>IPI-PLATFORM-TRANSCEIVER-SMART-SFP</b> . . . . .	<b>1713</b>
Configure xcvr loopback remote . . . . .	1713
xcvr IFNAME tx-disable <1-256> remote . . . . .	1714
xcvr IFNAME reset remote . . . . .	1714
<b>IPI-AUTHENTICATION</b> . . . . .	<b>1714</b>
Configure mac authentication . . . . .	1714
Configure dot1x authentication . . . . .	1715
Configure dot1x control . . . . .	1715
Configure protocol version . . . . .	1716
Configure quiet period . . . . .	1716
Configure max reauth value . . . . .	1717
Configure interval period . . . . .	1717
Configure reauthentication period . . . . .	1718
Configure enable reauthentication . . . . .	1719
Configure enable mac auth bypass . . . . .	1719
Configure supplicant timeout . . . . .	1720
Configure server timeout . . . . .	1720
Configure mac control . . . . .	1721
Configure mac mode . . . . .	1721
Configure dynamic vlan creation . . . . .	1722
Configure mac address aging . . . . .	1722
Configure options . . . . .	1723
dot1x initialize interface IFNAME . . . . .	1723
snmp restart auth . . . . .	1724
debug dot1x (event timer packet nsm all) . . . . .	1724
no debug dot1x (event timer packet nsm all) . . . . .	1724
<b>IPI-AUTHENTICATION-RADIUS</b> . . . . .	<b>1725</b>
Configure port . . . . .	1725
Configure timeout . . . . .	1725
Configure retransmit max retries . . . . .	1726
Configure key string . . . . .	1726
Configure encryption key . . . . .	1727
Configure host address . . . . .	1727
Configure host port . . . . .	1728
Configure host timeout . . . . .	1728
Configure host retransmit max retries . . . . .	1729
Configure host key-string . . . . .	1729
Configure host encryption-key . . . . .	1730
<b>IPI-ACL</b> . . . . .	<b>1730</b>
Configure type . . . . .	1730
Configure name . . . . .	1731
Configure acl-sets type . . . . .	1731

---

Configure acl-sets type . . . . .	1732
Configure description . . . . .	1732
Configure ipv6 disable default icmpv6 rule . . . . .	1733
Configure acl-set ipv6-disable-default-icmpv6-rule . . . . .	1733
Configure starting sequence number . . . . .	1734
Configure forwarding action default . . . . .	1735
Configure redirect interface name . . . . .	1735
Configure sequence id . . . . .	1737
Configure forwarding action . . . . .	1738
Configure protocol tcp . . . . .	1740
Configure source address . . . . .	1741
Configure destination address . . . . .	1743
Configure destination port operator . . . . .	1744
Configure tcp destination port . . . . .	1746
Configure precedence . . . . .	1748
Configure lower destination port in range . . . . .	1750
Configure upper destination port in range . . . . .	1752
Configure tcp flags . . . . .	1753
Configure source port operator . . . . .	1755
Configure tcp source port . . . . .	1757
Configure vlan id . . . . .	1759
Configure inner vlan id . . . . .	1761
Configure dscp . . . . .	1763
Configure monitor action . . . . .	1765
Configure ipv4 redirect-interface-name . . . . .	1767
Configure ipv4 redirect-interface-name . . . . .	1769
Configure ipv4 redirect-interface-name . . . . .	1771
Configure lower source port in range . . . . .	1773
Configure upper source port in range . . . . .	1775
Configure ipv4 redirect-interface-name . . . . .	1777
Configure ipv4 redirect-interface-name . . . . .	1779
Configure ipv4 redirect-interface-name . . . . .	1781
Configure ipv4 redirect-interface-name . . . . .	1783
Configure ipv4 redirect-interface-name . . . . .	1785
Configure ipv4 redirect-interface-name . . . . .	1787
Configure ipv4 redirect-interface-name . . . . .	1789
Configure protocol udp . . . . .	1790
Configure ipv4 redirect-interface-name . . . . .	1792
Configure ipv4 redirect-interface-name . . . . .	1793
Configure fragments . . . . .	1795
Configure ipv4 redirect-interface-name . . . . .	1796
Configure ipv4 redirect-interface-name . . . . .	1798
Configure udp destination port . . . . .	1799
Configure ipv4 redirect-interface-name . . . . .	1801
Configure ipv4 redirect-interface-name . . . . .	1802
Configure ipv4 redirect-interface-name . . . . .	1804
Configure ipv4 redirect-interface-name . . . . .	1806

---

Configure ipv4 redirect-interface-name . . . . .	1807
Configure udp source port . . . . .	1809
Configure ipv4 redirect-interface-name . . . . .	1811
Configure ipv4 redirect-interface-name . . . . .	1813
Configure ipv4 redirect-interface-name . . . . .	1815
Configure ipv4 redirect-interface-name . . . . .	1817
Configure ipv4 redirect-interface-name . . . . .	1819
Configure ipv4 redirect-interface-name . . . . .	1821
Configure ipv4 redirect-interface-name . . . . .	1822
Configure ipv4 redirect-interface-name . . . . .	1824
Configure ipv4 redirect-interface-name . . . . .	1826
Configure ipv4 redirect-interface-name . . . . .	1827
Configure ipv4 redirect-interface-name . . . . .	1829
Configure ipv4 redirect-interface-name . . . . .	1831
Configure ipv4 redirect-interface-name . . . . .	1833
Configure ipv4 redirect-interface-name . . . . .	1835
Configure ipv4 redirect-interface-name . . . . .	1837
Configure ipv4 redirect-interface-name . . . . .	1839
Configure ipv4 redirect-interface-name . . . . .	1840
Configure protocol icmp . . . . .	1842
Configure icmp message . . . . .	1844
Configure ipv4 redirect-interface-name . . . . .	1846
Configure ipv4 redirect-interface-name . . . . .	1848
Configure ipv4 redirect-interface-name . . . . .	1850
Configure ipv4 redirect-interface-name . . . . .	1852
Configure icmp type . . . . .	1853
Configure icmp code . . . . .	1855
Configure ipv4 redirect-interface-name . . . . .	1857
Configure ipv4 redirect-interface-name . . . . .	1859
Configure ipv4 redirect-interface-name . . . . .	1860
Configure ipv4 redirect-interface-name . . . . .	1862
Configure ipv4 redirect-interface-name . . . . .	1863
Configure ipv4 redirect-interface-name . . . . .	1865
Configure ipv4 redirect-interface-name . . . . .	1867
Configure ipv4 redirect-interface-name . . . . .	1868
Configure ipv4 redirect-interface-name . . . . .	1870
Configure ipv4 redirect-interface-name . . . . .	1871
Configure protocol name . . . . .	1873
Configure ipv4 redirect-interface-name . . . . .	1874
Configure ipv4 redirect-interface-name . . . . .	1876
Configure ipv4 redirect-interface-name . . . . .	1877
Configure ipv4 redirect-interface-name . . . . .	1879
Configure ipv4 redirect-interface-name . . . . .	1880
Configure fragment monitor action . . . . .	1882
Configure standard-acl-sets type . . . . .	1883
Configure standard-acl-sets type . . . . .	1883
Configure ipv4-acl-entry source-address . . . . .	1884

---

IPI-ACL-IPV6 .....	1885
Configure redirect interface name .....	1885
Configure name .....	1886
Configure type .....	1888
Configure sequence id .....	1890
Configure forwarding action .....	1892
Configure protocol tcp .....	1894
Configure source address .....	1896
Configure lower source port in range .....	1899
Configure upper source port in range .....	1901
Configure destination address .....	1903
Configure protocol udp .....	1905
Configure destination port operator .....	1907
Configure lower destination port in range .....	1909
Configure fragments .....	1911
Configure source port operator .....	1912
Configure udp source port .....	1914
Configure upper destination port in range .....	1916
Configure dscp .....	1919
Configure udp destination port .....	1921
Configure flow label .....	1923
Configure protocol icmp .....	1925
Configure icmp message .....	1926
Configure icmp type .....	1928
Configure icmp code .....	1930
Configure vlan id .....	1932
Configure inner vlan id .....	1934
Configure monitor action .....	1936
Configure ipv6 redirect-interface-name .....	1937
Configure protocol sctp .....	1939
Configure ipv6 redirect-interface-name .....	1941
Configure sctp destination port .....	1943
Configure ipv6 redirect-interface-name .....	1945
Configure sctp source port .....	1947
Configure ipv6 redirect-interface-name .....	1948
Configure ipv6 redirect-interface-name .....	1950
Configure ipv6 redirect-interface-name .....	1953
Configure ipv6 redirect-interface-name .....	1955
Configure ipv6 redirect-interface-name .....	1957
Configure protocol name .....	1959
Configure ipv6 redirect-interface-name .....	1961
Configure fragment monitor action .....	1962
Configure ipv6-acl-entry source-address .....	1963
IPI-ACL-ARP .....	1964
Configure source mac any .....	1964
Configure name .....	1966
Configure type .....	1967

---

---

Configure source mac host . . . . .	1969
Configure sequence id . . . . .	1970
Configure forwarding action . . . . .	1972
Configure source mac address . . . . .	1973
Configure arp packet type . . . . .	1975
Configure source ip address . . . . .	1977
Configure vlan id . . . . .	1978
Configure inner vlan id . . . . .	1980
Configure source mac mask . . . . .	1981
<b>IPI-ACL-MAC . . . . .</b>	<b>1983</b>
Configure source mac any . . . . .	1983
Configure name . . . . .	1984
Configure type . . . . .	1985
Configure source mac host . . . . .	1987
Configure sequence id . . . . .	1988
Configure forwarding action . . . . .	1990
Configure source mac address . . . . .	1991
Configure source mac mask . . . . .	1993
Configure destination mac address . . . . .	1995
Configure destination mac any . . . . .	1996
Configure destination mac host . . . . .	1998
Configure destination mac mask . . . . .	1999
Configure arp packet type . . . . .	2001
Configure cos value . . . . .	2002
Configure vlan id . . . . .	2004
Configure inner vlan id . . . . .	2005
Configure monitor action . . . . .	2007
Configure mac source-mac-address . . . . .	2008
Configure ethertype . . . . .	2010
Configure mac monitor-action . . . . .	2011
Configure mac monitor-action . . . . .	2013
Configure mac monitor-action . . . . .	2014
Configure mac monitor-action . . . . .	2016
Configure mac monitor-action . . . . .	2017
Configure mac monitor-action . . . . .	2019
Configure mac monitor-action . . . . .	2021
Configure mac monitor-action . . . . .	2022
<b>IPI-ACL-PORTS . . . . .</b>	<b>2024</b>
Configure acl name . . . . .	2024
Configure name . . . . .	2025
Configure acl type . . . . .	2026
Configure time range . . . . .	2026
Configure interfaces name . . . . .	2027
Configure interfaces name . . . . .	2028
Configure access-group time-range . . . . .	2029
Configure interfaces name . . . . .	2029
Configure access-group time-range . . . . .	2030

---

---

Configure interfaces name . . . . .	2031
Configure access-group time-range . . . . .	2032
Configure interfaces name . . . . .	2032
Configure access-group time-range . . . . .	2033
Configure ingress-acl-set acl-name . . . . .	2034
Configure ingress-acl-set acl-name . . . . .	2034
Configure egress-acl-set acl-name . . . . .	2035
Configure egress-acl-set acl-name . . . . .	2035
clear access-list counters . . . . .	2036
clear access-list NAME counters . . . . .	2036
clear ip access-list counters . . . . .	2037
clear ip access-list NAME counters . . . . .	2037
clear ipv6 access-list counters . . . . .	2037
clear ipv6 access-list NAME counters . . . . .	2037
clear mac access-list counters . . . . .	2038
clear mac access-list NAME counters . . . . .	2038
clear arp access-list counters . . . . .	2038
clear arp access-list NAME counters . . . . .	2038
<b>IPI-DHCP-SNOOPING . . . . .</b>	<b>2039</b>
Configure options . . . . .	2039
Configure snooping enable . . . . .	2039
Configure verify mac address . . . . .	2040
Configure option 82 enable . . . . .	2040
Configure write delay . . . . .	2041
Configure strict validation . . . . .	2041
Configure vlan range . . . . .	2042
Configure enable . . . . .	2042
Configure validate . . . . .	2043
Configure bridge id . . . . .	2043
Configure if name . . . . .	2044
Configure mac address . . . . .	2045
ip dhcp snooping database bridge WORD . . . . .	2046
renew ip dhcp snooping binding database bridge WORD . . . . .	2046
ip dhcp snooping source database bridge WORD . . . . .	2046
renew ip dhcp snooping source binding database bridge WORD . . . . .	2047
clear ip dhcp snooping source binding bridge WORD . . . . .	2047
clear ip dhcp snooping binding bridge WORD . . . . .	2047
debug ip dhcp snooping (event rx tx packet all) . . . . .	2047
no debug ip dhcp snooping (event rx tx packet all) . . . . .	2048
<b>IPI-DHCP-SNOOPING-INTERFACE . . . . .</b>	<b>2048</b>
Configure snooping trust . . . . .	2048
Configure verify snooping vlan . . . . .	2049
Configure verify access group mode . . . . .	2049
clear hsl ipc-stat VALUE VALUE . . . . .	2050
clear hsl ipc-stat . . . . .	2050
clear hsl mlag mac-sync-count . . . . .	2050
clear hardware-discard-counters . . . . .	2051

---

---

clear hsl fdb debug-counters . . . . .	2051
clear hsl system-cpu-stats . . . . .	2051
<b>IPI-UNICAST-RPF . . . . .</b>	<b>2051</b>
Configure enable route lookup . . . . .	2051
Configure source reachability mode . . . . .	2052
<b>IPI-OSPF-INTERFACE-TRACKING . . . . .</b>	<b>2052</b>
Configure event name . . . . .	2052
Configure event neighbor ip address . . . . .	2053
Configure name . . . . .	2053
<b>IPI-PORT-MIRROR . . . . .</b>	<b>2054</b>
Configure id . . . . .	2054
Configure enabled . . . . .	2055
Configure session enabled . . . . .	2055
Configure description . . . . .	2055
Configure source vlan . . . . .	2056
Configure interface name . . . . .	2057
Configure reflector interface name . . . . .	2057
Configure direction . . . . .	2058
<b>IPI-RIPNG . . . . .</b>	<b>2059</b>
Configure options . . . . .	2059
Configure split horizon . . . . .	2059
Configure name . . . . .	2060
Configure enabled . . . . .	2060
Configure metric offset . . . . .	2060
Configure ripng enabled . . . . .	2061
Configure enable cisco metric behavior . . . . .	2061
Configure instance enable-cisco-metric-behavior . . . . .	2062
Configure passive interfaces . . . . .	2062
Configure distance . . . . .	2063
Configure static routes . . . . .	2063
Configure aggregate prefixes . . . . .	2063
Configure default metric . . . . .	2064
Configure originate default route . . . . .	2064
Configure receive buffer size . . . . .	2065
Configure route type . . . . .	2065
Configure route map . . . . .	2066
Configure metric . . . . .	2066
Configure redistribute-policy route-map . . . . .	2067
Configure route table update interval . . . . .	2067
Configure address . . . . .	2068
Configure type . . . . .	2068
Configure access list name . . . . .	2069
Configure direction . . . . .	2070
Configure list name . . . . .	2071
Configure offset-list metric . . . . .	2071
Configure distribute-list direction . . . . .	2072
Configure distribute-prefix-list direction . . . . .	2073

---

---

debug ipv6 rip (all events packet send packet recv packet packet detail nsm rib) . . . . .	2073
no debug ipv6 rip (all events packet send packet recv packet packet detail nsm rib) . . .	2073
clear ipv6 rip route (kernel connected static isis ospf6 bgp rip all) . . . . .	2074
clear ipv6 rip route X:X:X/M . . . . .	2074
<b>IPI-RIPNG-VRF . . . . .</b>	<b>2074</b>
Configure vrf name . . . . .	2074
Configure enable cisco metric behavior . . . . .	2075
Configure vrf enable-cisco-metric-behavior . . . . .	2075
Configure passive interfaces . . . . .	2076
Configure distance . . . . .	2076
Configure static routes . . . . .	2077
Configure aggregate prefixes . . . . .	2077
Configure default metric . . . . .	2078
Configure originate default route . . . . .	2079
Configure receive buffer size . . . . .	2079
Configure route type . . . . .	2080
Configure route map . . . . .	2080
Configure metric . . . . .	2081
Configure redistribute-policy route-map . . . . .	2082
Configure route table update interval . . . . .	2082
Configure address . . . . .	2083
Configure type . . . . .	2084
Configure access list name . . . . .	2085
Configure direction . . . . .	2086
Configure list name . . . . .	2087
Configure offset-list metric . . . . .	2087
Configure distribute-list direction . . . . .	2088
Configure distribute-prefix-list direction . . . . .	2089
<b>IPI-ARP . . . . .</b>	<b>2090</b>
Configure ip address . . . . .	2090
Configure respond to arp request . . . . .	2090
Configure enable . . . . .	2091
Configure enable proxy arp . . . . .	2091
Configure enable local proxy arp . . . . .	2092
Configure enable ip redirects . . . . .	2092
Configure arp ageing timeout . . . . .	2093
Configure arp reachable time . . . . .	2093
debug ip arp event . . . . .	2094
no debug ip arp event . . . . .	2094
clear arp (A.B.C.D) (vrf (all VRFNAME default)) . . . . .	2094
clear arp IFNAME (vrf (all VRFNAME default)) . . . . .	2094
<b>IPI-NEIGHBOR-DISCOVERY . . . . .</b>	<b>2095</b>
Configure interface name . . . . .	2095
Configure ipv6 address . . . . .	2095
Configure enable . . . . .	2096
Configure nd ageing timeout . . . . .	2096
Configure nd reachable time . . . . .	2097

Configure no ip unreachable . . . . .	2097
Configure no ipv6 unreachable . . . . .	2098
debug ipv6 nd event. . . . .	2098
no debug ipv6 nd event . . . . .	2099
clear ipv6 neighbors (X:X::X:X/M ) (vrf (all VRFNAME default )) . . . . .	2099
clear ipv6 neighbors IFNAME (vrf (all VRFNAME default )) . . . . .	2099
<b>IPI-USER-SESSION-MANAGEMENT . . . . .</b>	<b>2100</b>
Configure console id . . . . .	2100
Configure privilege level. . . . .	2100
Configure command history max limit . . . . .	2101
Configure seconds . . . . .	2101
Configure minutes . . . . .	2102
Configure vty id . . . . .	2102
Configure vty command-history-max-limit . . . . .	2103
Configure timeout seconds . . . . .	2103
Configure timeout minutes . . . . .	2104
clear line WORD . . . . .	2105
mem-info imi monitor-start . . . . .	2105
mem-info imi monitor-stop . . . . .	2105
<b>IPI-IPV6-ROUTER-ADV . . . . .</b>	<b>2106</b>
Configure suppress ra . . . . .	2106
Configure suppress ra mtu. . . . .	2106
Configure managed flag. . . . .	2107
Configure other config flag. . . . .	2107
Configure current hop limit. . . . .	2108
Configure link mtu . . . . .	2108
Configure dad attempts . . . . .	2109
Configure off link . . . . .	2109
Configure no auto configuration. . . . .	2110
Configure valid lifetime. . . . .	2110
Configure preferred lifetime . . . . .	2111
Configure ipv6 address . . . . .	2112
Configure name . . . . .	2112
Configure ipv6-prefix off-link . . . . .	2113
Configure ipv6-prefix no-auto-configuration. . . . .	2114
Configure ipv6-prefix no-auto-configuration. . . . .	2115
Configure reachable time. . . . .	2116
Configure retransmission time . . . . .	2117
Configure router lifetime. . . . .	2117
Configure max ra interval. . . . .	2118
<b>IPI-ERPSV2 . . . . .</b>	<b>2119</b>
Configure ring name . . . . .	2119
Configure east interface. . . . .	2119
Configure west interface . . . . .	2120
Configure description . . . . .	2120
Configure profile name. . . . .	2121
Configure wait to restore timer . . . . .	2121

---

Configure hold off timer . . . . .	2122
Configure guard time . . . . .	2123
Configure protection mode. . . . .	2123
Configure name . . . . .	2124
Configure erp-instance ring-name . . . . .	2124
Configure mapped profile name. . . . .	2125
Configure ring type. . . . .	2125
Configure enable tcn propagation . . . . .	2126
Configure tcn to instances . . . . .	2126
Configure non virtual channel . . . . .	2127
Configure ring id. . . . .	2127
Configure erp-instance description . . . . .	2128
Configure associate ring name . . . . .	2128
Configure owner port id . . . . .	2129
Configure neighbor port id . . . . .	2130
Configure next neighbor port id . . . . .	2130
Configure non owner . . . . .	2131
Configure level. . . . .	2131
Configure vlan id . . . . .	2132
Configure data vlan . . . . .	2133
Configure attached instance . . . . .	2133
Configure options. . . . .	2134
g8032 erp-instance (INSTANCENAME all) (force-switch manual-switch) (east- interface west-interface). . . . .	2134
clear g8032 erp-instance (INSTANCENAME all). . . . .	2135
clear g8032 aps-statistics INSTANCENAME . . . . .	2135
debug g8032 (all tx rx fsm timers events external hal). . . . .	2136
no debug g8032 (all tx rx fsm timers events external hal) . . . . .	2136
IPI-CFM . . . . .	2136
Configure cache enable. . . . .	2136
Configure cache size . . . . .	2137
Configure options. . . . .	2137
Configure type . . . . .	2138
Configure ma name . . . . .	2138
Configure bridge id. . . . .	2139
Configure md name . . . . .	2140
Configure mip creation. . . . .	2141
Configure inner vlan id. . . . .	2141
Configure link level ma. . . . .	2142
Configure mip interface name . . . . .	2143
Configure evpn id. . . . .	2143
Configure ccm interval. . . . .	2144
Configure static rmep identifiers . . . . .	2145
Configure mep id . . . . .	2145
Configure direction. . . . .	2146
Configure bw mapped interface . . . . .	2147
Configure enable cc multicast . . . . .	2148

---

---

Configure lowest fault priority defect . . . . .	2149
clear ethernet cfm maintenance-points remote domain DOMAIN_NAME . . . . .	2150
clear ethernet cfm statistics . . . . .	2150
clear ethernet cfm statistics mep <1-8191> domain DOMAIN_NAME ma MA_NAME . . . . .	2151
cfm snmp restart . . . . .	2151
debug ethernet cfm (events rx tx loopback traceroute all) . . . . .	2151
no debug ethernet cfm (events rx tx loopback traceroute all) . . . . .	2152
clear ethernet cfm traceroute-cache . . . . .	2152
<b>IPI-CFM-Y1731</b> . . . . .	<b>2152</b>
Configure enable status . . . . .	2152
Configure interval . . . . .	2153
<b>IPI-UDLD</b> . . . . .	<b>2154</b>
Configure enable . . . . .	2154
Configure message time . . . . .	2154
Configure options . . . . .	2155
Configure mode . . . . .	2155
Configure administrative state . . . . .	2156
debug udd (event packet timer nsm hal all) . . . . .	2156
no debug udd (event packet timer nsm hal all) . . . . .	2156
<b>IPI-EFM</b> . . . . .	<b>2157</b>
Configure link monitor off . . . . .	2157
Configure remote loopback start . . . . .	2157
Configure enable . . . . .	2158
Configure mode . . . . .	2158
Configure link lost timeout . . . . .	2159
Configure pdu min rate . . . . .	2159
Configure pdu max rate . . . . .	2160
Configure unidirectional link support . . . . .	2160
Configure remote loopback support . . . . .	2161
Configure remote loopback timeout . . . . .	2161
Configure link monitor support . . . . .	2162
Configure link monitor event log size . . . . .	2162
Configure disable port on remote failure events . . . . .	2163
Configure options . . . . .	2163
debug ethernet oam (event rx tx all) . . . . .	2163
no debug ethernet oam (event rx tx all) . . . . .	2164
clear ethernet oam statistics interface IFNAME . . . . .	2164
<b>IPI-ROLE-BASED-ACCESS-CONTROL</b> . . . . .	<b>2164</b>
Configure policy name . . . . .	2164
Configure command mode . . . . .	2165
Configure rule name . . . . .	2166
Configure rule type . . . . .	2166
Configure role name . . . . .	2167
Configure default policy . . . . .	2168
Configure policies policy-name . . . . .	2168
Configure enable . . . . .	2169
<b>IPI-PORT-BREAKOUT</b> . . . . .	<b>2169</b>

---

Configure interface . . . . .	2169
Configure mode . . . . .	2170
Configure breakouts interface . . . . .	2170
Configure breakouts interface . . . . .	2171
Configure breakouts interface . . . . .	2171
Configure breakouts interface . . . . .	2172
Configure port group . . . . .	2172
Configure name . . . . .	2173
<b>IPI-SOURCE-INTERFACE . . . . .</b>	<b>2174</b>
Configure vrf name . . . . .	2174
Configure interface name. . . . .	2174
<b>IPI-TACACS . . . . .</b>	<b>2175</b>
Configure feature enable . . . . .	2175
Configure vrf name . . . . .	2176
Configure key type . . . . .	2176
Configure timeout. . . . .	2177
Configure host address . . . . .	2177
Configure secret key string . . . . .	2178
Configure port . . . . .	2179
Configure sequence number . . . . .	2180
Configure server timeout . . . . .	2180
Configure server port . . . . .	2181
Configure server timeout . . . . .	2182
Configure server timeout . . . . .	2183
Configure enable . . . . .	2184
clear tacacs-server counters (vrf (management NAME all )) . . . . .	2185
clear tacacs-server (A.B.C.D X:X::X:X HOSTNAME) counters (vrf (management NAME all ))	2185
debug tacacs+ . . . . .	2185
no debug tacacs+ . . . . .	2186
<b>IPI-TIME-RANGE . . . . .</b>	<b>2186</b>
Configure name . . . . .	2186
Configure absolute start time . . . . .	2186
Configure relative start time . . . . .	2187
Configure absolute end time . . . . .	2187
Configure relative end time . . . . .	2188
Configure frequency. . . . .	2188
crypto pki generate rsa common-name ipv4 IPv4ADDR . . . . .	2189
<b>IPI-IP-SLA . . . . .</b>	<b>2189</b>
Configure identifier . . . . .	2189
Configure host . . . . .	2190
Configure frequency. . . . .	2190
Configure timeout. . . . .	2191
Configure threshold . . . . .	2192
Configure vrf name . . . . .	2192
clear ip sla statistics (<1-65535> ) . . . . .	2193
<b>IPI-OBJECT-TRACKING . . . . .</b>	<b>2193</b>

Configure tracker id . . . . .	2193
Configure delay down . . . . .	2194
Configure delay up . . . . .	2194
Configure select option . . . . .	2195
Configure track id . . . . .	2195
IPI-ELK . . . . .	2196
Configure password . . . . .	2196
Configure certificate path . . . . .	2197
service enable metricbeat (vrf management) . . . . .	2197
service enable filebeat (vrf management) . . . . .	2197
service disable metricbeat (vrf management) . . . . .	2198
service disable filebeat (vrf management) . . . . .	2198
IPI-IPSEC . . . . .	2198
Configure transform set name . . . . .	2198
Configure transform set mode . . . . .	2199
Configure ah authentication . . . . .	2199
Configure ah-auth ah-authentication . . . . .	2200
Configure esp encryption . . . . .	2200
Configure esp authentication . . . . .	2201
Configure name . . . . .	2202
Configure sequence id . . . . .	2202
Configure transform-sets transform-set-name . . . . .	2203
Configure peer . . . . .	2204
Configure security parameter index . . . . .	2205
IPI-HOST . . . . .	2206
Configure disable service advanced vty . . . . .	2206
Configure service passwd encryption . . . . .	2206
Configure system-host service-passwd-encryption . . . . .	2207
Configure passwd encrypted . . . . .	2207
Configure banner motd . . . . .	2207
Configure banner motd file . . . . .	2208
Configure service term length . . . . .	2208
Configure disable default autoenable . . . . .	2209
CHAPTER 2   PYANG Tree . . . . .	2211
module: ipi-aaa . . . . .	2211
module: ipi-acl . . . . .	2214
module: ipi-alarms . . . . .	2226
module: ipi-arp . . . . .	2227
module: ipi-authentication-radius . . . . .	2229
module: ipi-authentication . . . . .	2231
module: ipi-bfd . . . . .	2234
module: ipi-bgp-vrf . . . . .	2241
module: ipi-bgp . . . . .	2244
module: ipi-bridge-domain . . . . .	2298
module: ipi-bridge . . . . .	2299
module: ipi-cfm . . . . .	2302

---

module: ipi-cross-connect	2308
module: ipi-crypto	2308
module: ipi-customstats	2309
module: ipi-dcb	2311
module: ipi-delay-profile	2315
module: ipi-dhcp	2317
module: ipi-dns-client	2330
module: ipi-dns-relay	2331
module: ipi-efm	2333
module: ipi-elk	2334
module: ipi-enhanced-pbr	2335
module: ipi-erpsv2	2338
module: ipi-ethernet-vpn	2343
module: ipi-event-manager	2345
module: ipi-evpn-mpls	2347
module: ipi-evpn-srv6	2350
module: ipi-g8031	2352
module: ipi-global-te	2356
module: ipi-host	2357
module: ipi-hwtable	2357
module: ipi-if-aggregate	2358
module: ipi-if-ethernet	2359
module: ipi-if-extended	2361
module: ipi-if-flowspec	2369
module: ipi-if-ip	2370
module: ipi-igmp-snooping	2373
module: ipi-igmp	2375
module: ipi-igp-te	2381
module: ipi-interface	2386
module: ipi-ip-sla	2388
module: ipi-ipsec	2390
module: ipi-ipv6-router-adv	2392
module: ipi-isis	2394
module: ipi-keychain	2424
module: ipi-l2vpn-vpls	2426
module: ipi-l2vpn-vpws	2434
module: ipi-lacp	2442
module: ipi-ldp	2446
module: ipi-lldpv2	2460
module: ipi-logging	2467
module: ipi-management-server	2470
module: ipi-mcec	2473
module: ipi-mlag	2477
module: ipi-mld-snooping	2478
module: ipi-mld	2479
module: ipi-mpls-bfd	2485
module: ipi-mpls-rib	2487

---

module: ipi-mpls	2496
module: ipi-mrib	2501
module: ipi-neighbor-discovery	2508
module: ipi-network-instance	2510
module: ipi-network-services-manager	2510
module: ipi-ntp	2512
module: ipi-object-tracking	2515
module: ipi-ospf-interface-tracking	2516
module: ipi-ospf	2517
module: ipi-ospfv3	2550
module: ipi-pbr	2578
module: ipi-pcep	2579
module: ipi-pim	2586
module: ipi-ping	2607
module: ipi-platform-port	2609
module: ipi-platform-transceiver-smart-sfp	2610
module: ipi-platform	2611
module: ipi-port-breakout	2690
module: ipi-port-mirror	2691
module: ipi-port-vlan	2694
module: ipi-prefix-list	2698
module: ipi-ptp	2700
module: ipi-qos-if	2712
module: ipi-qos	2717
module: ipi-radius	2730
module: ipi-ras	2731
module: ipi-rib-vrf	2732
module: ipi-rib	2740
module: ipi-rip	2746
module: ipi-ripng	2756
module: ipi-role-based-access-control	2765
module: ipi-routemap	2767
module: ipi-rsvp	2772
module: ipi-seamless-bfd	2799
module: ipi-segment-routing	2800
module: ipi-service-map	2813
module: ipi-sflow-interface	2814
module: ipi-sflow-ipfix	2815
module: ipi-sflow	2816
module: ipi-snmp-server-extended	2818
module: ipi-snmp-server	2823
module: ipi-snmp	2824
module: ipi-source-interface	2825
module: ipi-ssh	2826
module: ipi-streaming-telemetry	2831
module: ipi-synce	2834
module: ipi-sys-mgmt	2837

---

module: ipi-sys-notifications . . . . .	2838
module: ipi-sys-update . . . . .	2838
module: ipi-system . . . . .	2841
module: ipi-tacacs . . . . .	2841
module: ipi-telnet . . . . .	2843
module: ipi-tfo . . . . .	2844
module: ipi-time-range . . . . .	2845
module: ipi-twamp . . . . .	2846
module: ipi-udld . . . . .	2853
module: ipi-unicast-rpf . . . . .	2854
module: ipi-user-management . . . . .	2855
module: ipi-user-session-management . . . . .	2856
module: ipi-vlan-xc . . . . .	2857
module: ipi-vlan . . . . .	2860
module: ipi-vrf . . . . .	2864
module: ipi-vrrp . . . . .	2865
module: ipi-vxlan . . . . .	2874
module: ipi-watchdog . . . . .	2885
module: ipi-xstp . . . . .	2887

---

# Preface

---

This document describes the OcNOS commands for NetConf.

---

## IP Maestro Support

Monitor devices running OcNOS Release 6.3.4-70 and above using IP Maestro software.

---

## Audience

This guide is intended for network administrators and other engineering professionals who configure and manage NetConf for OcNOS.

---

## Conventions

Table P-1 shows the conventions used in this guide.

**Table P-1: Conventions**

Convention	Description
<i>Italics</i>	Emphasized terms; titles of books
Note:	Special instructions, suggestions, or warnings
<code>monospaced type</code>	Code elements such as XML tags, commands, parameters, files, and directories

---

## Related Documentation

For information about installing OcNOS, see the *Installation Guide* for your platform.

---

## Feature Availability

The features described in this document are available depending upon the OcNOS SKU that you purchased. See the *Application Notes* for a description of the OcNOS SKUs.

---

## Support

For support-related questions, contact [support@ipinfusion.com](mailto:support@ipinfusion.com).

---

## Comments

If you have comments, or need to report a problem with the content, contact [techpubs@ipinfusion.com](mailto:techpubs@ipinfusion.com).

---

## CHAPTER 1 NetConf Reference

---

---

### IPI-MANAGEMENT-SERVER

---

#### Configure feature enabled

Enable callhome feature on the NETCONF server

This command is supported when following feature are enabled NETCONF feature

Attribute Name: feature-enabled

Attribute Type: empty

#### Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <callhome>
  <config>
    </feature-enabled>
  </config>
</callhome>
</netconf-server>
```

#### Command Syntax

```
feature netconf callhome enable
```

---

#### Configure management port

Interface to be used to connect the callhome server

This command is supported when following feature are enabled NETCONF feature

Attribute Name: management-port

Attribute Type: string

Default Value: eth0

Attribute Range: 1-49

#### Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <callhome>
  <config>
    <management-port>IFNAME</management-port> <!-- operation="delete"-->
  </config>
</callhome>
</netconf-server>
```

#### Command Syntax

```
management-port IFNAME
```

---

## Configure port

Callhome server listening port number

This command is supported when following feature are enabled NETCONF feature

Attribute Name: port

Attribute Type: inet:port-number

Default Value: 4334

Attribute Range: 1-65535

Attribute Name: address

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <callhome>
    <netconf-clients>
      <netconf-client>
        <name>WORD</name>
        <config>
          <name>WORD</name>
          <address>A.B.C.D|X:X::X:X|HOSTNAME</address>
        </config>
        <port>1</port>
      </netconf-client>
    </netconf-clients>
  </callhome>
</netconf-server>
```

### Command Syntax

```
callhome server WORD (A.B.C.D|X:X::X:X|HOSTNAME) (port <1-65535>|)
```

---

## Configure enable

specifies whether server will reconnect after client closes the session

This command is supported when following feature are enabled NETCONF feature

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <callhome>
    <reconnect>
      <config>
        </enable>
      </config>
    </reconnect>
  </callhome>
</netconf-server>
```

```
</reconnect>
</callhome>
</netconf-server>
```

## Command Syntax

```
reconnect enable
```

---

## Configure retry max attempts

Specifies the number of retry attempts the server should attempt to the callhome server before giving up. Set 0 to retry infinitely.

This command is supported when following feature are enabled NETCONF feature

Attribute Name: retry-max-attempts

Attribute Type: uint8

Default Value: 3

Attribute Range: 0-255

## Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <callhome>
  <reconnect>
  <config>
    <retry-max-attempts>0</retry-max-attempts> <!-- operation="delete"-->
  </config>
  </reconnect>
  </callhome>
</netconf-server>
```

## Command Syntax

```
retry-max-attempts <0-255>
```

---

## Configure retry interval

Specifies the number of seconds to wait after a connect attempt to the callhome server has failed

This command is supported when following feature are enabled NETCONF feature

Attribute Name: retry-interval

Attribute Type: uint32

Default Value: 300

Attribute Range: 1-86400

## Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <callhome>
  <reconnect>
  <config>
    <retry-interval>1</retry-interval> <!-- operation="delete"-->
  </config>
  </reconnect>
  </callhome>
</netconf-server>
```

```
</config>
</reconnect>
</callhome>
</netconf-server>
```

## Command Syntax

```
retry-interval <1-86400>
```

---

## Configure translation mode

Enable/disable NETCONF translation

This command is supported when following feature are enabled NETCONF translation feature,NETCONF feature

Attribute Name: translation-mode

Attribute Type: enum (openconfig)

### Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <netconf-translation>
    <config>
      <translation-mode>openconfig</translation-mode> <!-- operation="delete"-->
    </config>
  </netconf-translation>
</netconf-server>
```

## Command Syntax

```
netconf translation (openconfig)
```

---

## Configure debug enable

Enable debugging info for callhome

This command is supported when following feature are enabled NETCONF feature

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <debug>
    <config>
      </enable><!-- operation="delete"-->
    </config>
  </debug>
</netconf-server>
```

## Command Syntax

```
debug callhome
```

---

## Configure feature netconf ssh

Use this attribute to enable or disable NETCONF SSH feature.

Attribute Name: feature-netconf-ssh

Attribute Type: boolean

### Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <netconf-ssh-config>
    <config>
      <feature-netconf-ssh>true</feature-netconf-ssh> <!-- operation="delete"-->
    </config>
  </netconf-ssh-config>
</netconf-server>
```

### Command Syntax

```
feature netconf-ssh (vrf (management|NAME) |)
```

---

## Configure vrf name

Use this attribute to enable or disable NETCONF SSH feature.

Attribute Name: feature-netconf-ssh

Attribute Type: boolean

### Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <netconf-ssh-config>
    <config>
      <feature-netconf-ssh>true</feature-netconf-ssh> <!-- operation="delete"-->
    </config>
  </netconf-ssh-config>
</netconf-server>
```

## Command Syntax

```
no feature netconf-ssh (vrf (management|NAME) |)
```

## Configure feature netconf tls

Use this attribute to enable or disable NETCONF TLS feature.

Attribute Name: feature-netconf-tls

Attribute Type: boolean

### Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <netconf-tls-config>
    <config>
      <feature-netconf-tls>true</feature-netconf-tls> <!-- operation="delete"-->
    </config>
  </netconf-tls-config>
</netconf-server>
```

## Command Syntax

```
feature netconf-tls (vrf (management|NAME) |)
```

## Configure netconf-tls-config feature-netconf-tls

Use this attribute to enable or disable NETCONF TLS feature.

Attribute Name: feature-netconf-tls

Attribute Type: boolean

### Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <netconf-tls-config>
    <config>
      <feature-netconf-tls>true</feature-netconf-tls> <!-- operation="delete"-->
    </config>
  </netconf-tls-config>
</netconf-server>
```

```

</vrf>
</vrfs>
</netconf-server>

```

## Command Syntax

```
no feature netconf-tls (vrf (management|NAME) |)
```

---

## Configure ssh port

Use this attribute to set the ssh-port number on which the NETCONF server listens for connections. The default port on which the netconf-ssh server listens is 830.

This command is supported when following feature are enabled Virtual routing and forwarding, NETCONF feature

Attribute Name: ssh-port

Attribute Type: uint32

Attribute Range: 1024-65535

## Netconf edit-config payload

```

<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <netconf-ssh-config>
    <config>
      <ssh-port>1024</ssh-port> <!-- operation="delete"-->
    </config>
  </netconf-ssh-config>
</netconf-server>

```

## Command Syntax

```
netconf server ssh-port <1024-65535> (vrf (management|NAME) |)
```

---

## Configure tls port

Use this attribute to set the tls-port number on which the NETCONF server listens for connections. The default port on which the netconf-tls server listens is 6513.

This command is supported when following feature are enabled Virtual routing and forwarding, NETCONF feature

Attribute Name: tls-port

Attribute Type: uint32

Attribute Range: 1024-65535

## Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <netconf-tls-config>
    <config>
      <tls-port>1024</tls-port> <!-- operation="delete"-->
    </config>
  </netconf-tls-config>
</netconf-server>
```

## Command Syntax

```
netconf server tls-port <1024-65535> (vrf (management|NAME) |)
```

## Configure notification-cache feature-enabled

Enable notification cache feature on the NETCONF server

This command is supported when following feature are enabled NETCONF feature

Attribute Name: feature-enabled

Attribute Type: empty

## Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <notification-cache>
    <config>
      </feature-enabled>
    </config>
  </notification-cache>
</netconf-server>
```

## Command Syntax

```
feature netconf notification-cache enable
```

## Configure max cache notifications

Specifies the maximum number of notifications those can be stored in cache. Set 0 for infinite notifications.

This command is supported when following feature are enabled NETCONF feature

Attribute Name: max-cache-notifications

Attribute Type: uint16

Default Value: 100

---

Attribute Range: 0-10000

### Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <notification-cache>
    <config>
      <max-cache-notifications>0</max-cache-notifications> <!-- operation="delete"-->
    </config>
  </notification-cache>
</netconf-server>
```

### Command Syntax

```
max-cache-notifications <0-10000>
```

---

## Configure cache period

Specifies the number of seconds, cmdl store notification messages in cache since it started

This command is supported when following feature are enabled NETCONF feature

Attribute Name: cache-period

Attribute Type: uint32

Default Value: 1200

Attribute Range: 1-3600

### Netconf edit-config payload

```
<netconf-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-server">
  <notification-cache>
    <config>
      <cache-period>1</cache-period> <!-- operation="delete"-->
    </config>
  </notification-cache>
</netconf-server>
```

### Command Syntax

```
cache-period <1-3600>
```

---

## IPI-STREAMING-TELEMETRY

---

### Configure feature enabled

Use this attribute to enable or disable Telemetry feature

This command is supported when following feature are enabled Virtual routing and forwarding

Attribute Name: feature-enabled

Attribute Type: empty

## Netconf edit-config payload

```

<telemetry-system xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-streaming-
telemetry">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <streaming-telemetry>
    <config>
      </feature-enabled><!-- operation="delete"-->
    </config>
  </streaming-telemetry>
</telemetry-system>

```

## Command Syntax

```
feature streaming-telemetry (vrf (management|NAME) |)
```

---

## Configure retry interval

If the grpc-tunnel-server is unreachable, the gnmi-server retries to connect with gnmi-client after the retry-interval

This command is supported when following feature are enabled Virtual routing and forwarding

Attribute Name: retry-interval

Attribute Type: uint32

Default Value: 60

Attribute Range: 30-3000

## Netconf edit-config payload

```

<telemetry-system xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-streaming-
telemetry">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <streaming-telemetry>
    <config>
      <retry-interval>30</retry-interval> <!-- operation="delete"-->
    </config>
  </streaming-telemetry>
</telemetry-system>

```

## Command Syntax

```
grpc-tunnel-server retry-interval <30-3000> (vrf (management|NAME) |)
```

---

## Configure gnmi severity

device's debug telemetry severity level

This command is supported when following feature are enabled Virtual routing and forwarding

Attribute Name: gnmi-severity

Attribute Type: enum (debug|info|warning|error|fatal|panic|d-panic)

Default Value: error

Attribute Name: gnmi-debug

Attribute Type: empty

## Netconf edit-config payload

```
<telemetry-system xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-streaming-
telemetry">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    <streaming-telemetry>
    <debug>
    <config>
      </gnmi-debug><!-- operation="delete"-->
      <gnmi-severity>error</gnmi-severity> <!-- operation="delete"-->
    </config>
    </debug>
  </streaming-telemetry>
</vrf>
</vrfs>
</telemetry-system>
```

## Command Syntax

```
debug telemetry gnmi enable severity (debug|info|warning|error|fatal|panic|d-panic)
(vrf (management|NAME) |)
```

---

## Configure gnmi debug

Enable or Disable device's debug telemetry

This command is supported when following feature are enabled Virtual routing and forwarding

Attribute Name: gnmi-debug

Attribute Type: empty

## Netconf edit-config payload

```

<telemetry-system xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-streaming-
telemetry">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <streaming-telemetry>
    <debug>
      <config>
        </gnmi-debug><!-- operation="delete"-->
      </config>
    </debug>
  </streaming-telemetry>
</telemetry-system>

```

## Command Syntax

```
debug telemetry gnmi enable (vrf (management|NAME)|)
```

## Configure name

Reference to the identifier of the subscription itself. The id will be the handle to refer to the subscription once created

Attribute Name: name

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```

<telemetry-system xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-streaming-
telemetry">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <subscriptions>
    <persistent-subscriptions>
      <persistent-subscription> <!-- operation="delete"-->
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
      </persistent-subscription>
    </persistent-subscriptions>
  </subscriptions>
</telemetry-system>

```

```

</vrf>
</vrfs>
</telemetry-system>

```

## Command Syntax

```
subscription-name NAME (vrf (management|NAME)|)
```

---

## Configure encoding

Selection of the specific encoding or RPC framework for telemetry messages to and from the network element. The encoding method controls specifically the wire format of the telemetry data, and also controls which RPC framework may be in use to exchange telemetry data

This command is supported when following feature are enabled Virtual routing and forwarding

Attribute Name: encoding

Attribute Type: enum (json-ietf|json|proto)

## Netconf edit-config payload

```

<telemetry-system xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-streaming-
telemetry">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <subscriptions>
    <persistent-subscriptions>
      <persistent-subscription>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
        <encoding>json-ietf</encoding> <!-- operation="delete"-->
      </persistent-subscription>
    </persistent-subscriptions>
  </subscriptions>
</telemetry-system>

```

## Command Syntax

```
encoding (json-ietf|json|proto)
```

---

## Configure sensor group

Reference to the telemetry sensor group name

This command is supported when following feature are enabled Virtual routing and forwarding

Attribute Name: sensor-group

Attribute Type: string

Attribute Range: 1-64

Attribute Name: sample-interval

Attribute Type: uint64

Attribute Range: 10-3600

### Netconf edit-config payload

```

<telemetry-system xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-streaming-
telemetry">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <subscriptions>
    <persistent-subscriptions>
      <persistent-subscription>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
        <sensor-profiles>
          <sensor-profile> <!-- operation="delete"-->
            <sensor-group>SENSOR-GROUP-NAME</sensor-group>
            <config>
              <sensor-group>WORD</sensor-group>
              <sample-interval>10</sample-interval>
            </config>
          </sensor-profile>
        </sensor-profiles>
      </persistent-subscription>
    </persistent-subscriptions>
  </subscriptions>
</telemetry-system>

```

### Command Syntax

```
sensor-group SENSOR-GROUP-NAME sample-interval <10-3600>
```

### Configure group id

The destination group id references a configured group of destinations for the telemetry stream

This command is supported when following feature are enabled Virtual routing and forwarding

Attribute Name: group-id

Attribute Type: string

Attribute Range: 1-64

### Netconf edit-config payload

```
<telemetry-system xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-streaming-
telemetry">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <subscriptions>
    <persistent-subscriptions>
      <persistent-subscription>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
        <destination-groups>
          <destination-group <!-- operation="delete"-->
            <group-id>GRPC-GROUP-NAME</group-id>
            <config>
              <group-id>WORD</group-id>
            </config>
          </destination-group>
        </destination-groups>
      </persistent-subscription>
    </persistent-subscriptions>
  </subscriptions>
</telemetry-system>
```

### Command Syntax

```
destination-group GRPC-GROUP-NAME
```

---

## Configure sensor group id

Name or identifier for the sensor group itself. Will be referenced by other configuration specifying a sensor group

Attribute Name: sensor-group-id

Attribute Type: string

Attribute Range: 1-64

### Netconf edit-config payload

```
<telemetry-system xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-streaming-
telemetry">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
```

```

    <config>
      <vrf-name>management</vrf-name>
    </config>
  </sensor-groups>
</sensor-group> <!-- operation="delete"-->
  <sensor-group-id>SENSOR-NAME</sensor-group-id>
  <config>
    <sensor-group-id>WORD</sensor-group-id>
  </config>
</sensor-group>
</sensor-groups>
</vrf>
</vrfs>
</telemetry-system>

```

## Command Syntax

```
sensor-group SENSOR-NAME (vrf (management|NAME) |)
```

---

## Configure path

Reference to the path of interest

This command is supported when following feature are enabled Virtual routing and forwarding

Attribute Name: path

Attribute Type: string

## Netconf edit-config payload

```

<telemetry-system xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-streaming-
telemetry">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </sensor-groups>
    <sensor-group>
      <sensor-group-id>SENSOR-NAME</sensor-group-id>
      <config>
        <sensor-group-id>WORD</sensor-group-id>
      </config>
      <sensor-paths>
        <sensor-path> <!-- operation="delete"-->
          <path>SENSOR-PATH</path>
          <config>
            <path>WORD</path>
          </config>
        </sensor-path>
      </sensor-paths>
    </sensor-group>

```

```

</sensor-groups>
</vrf>
</vrfs>
</telemetry-system>

```

## Command Syntax

```
sensor-path SENSOR-PATH
```

---

## Configure vrf name

Unique identifier for the destination group

Attribute Name: group-id

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```

<telemetry-system xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-streaming-
telemetry">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    <destination-groups>
    <destination-group> <!-- operation="delete"-->
      <group-id>TUNNEL-NAME</group-id>
      <config>
        <group-id>WORD</group-id>
      </config>
    </destination-group>
    </destination-groups>
  </vrfs>
</telemetry-system>

```

## Command Syntax

```
destination-group TUNNEL-NAME (vrf (management|NAME) |)
```

---

## Configure destination port

Reference to the port number of the stream destination

This command is supported when following feature are enabled Virtual routing and forwarding

Attribute Name: destination-port

Attribute Type: uint16

Attribute Range: 1-65535

## Netconf edit-config payload

```

<telemetry-system xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-streaming-
telemetry">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <destination-groups>
    <destination-group>
      <group-id>TUNNEL-NAME</group-id>
      <config>
        <group-id>WORD</group-id>
      </config>
      <destinations>
        <destination> <!-- operation="delete"-->
          <destination-port>1</destination-port>
          <config>
            <destination-port>1</destination-port>
            <destination-address>A.B.C.D</destination-address>
          </config>
          <destination-address>A.B.C.D</destination-address>
        </destination>
      </destinations>
    </destination-group>
  </destination-groups>
</telemetry-system>

```

## Command Syntax

```
tunnel-server ip A.B.C.D port <1-65535>
```

---

# IPI-MANAGEMENT-SERVER-NOTIFICATION

---

## Configure severity

If notification enabled, all the notifications having severity higher than or equal to this severity allowed. If notification disabled, all the notifications having severity lower than or equal to this severity not allowed

Attribute Name: severity

Attribute Type: enum (all|info|warning|minor|major|critical)

Default Value: all

Attribute Name: enable

Attribute Type: enum (disable|enable)

## Netconf edit-config payload

```
<management-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-management-
server">
  <module-notifications>
  <module-notification>
    <module-name>auth</module-name>
    <config>
      <module-name>auth</module-name>
      <enable>enable</enable>
    </config>
    <severity>all</severity>
  </module-notification>
</module-notifications>
</management-server>
```

## Command Syntax

```
module
  (auth|bgp|cmm|hostp|hsl|isis|lag|l2mrib|mstp|mrrib|nsm|onm|oam|ospf|ospf6|rip|pim
  |rib|vrrp|sflow|pserv|cml|ndd|ripng|vlog|all|udld) notification (disable|enable)
  (severity (all|info|warning|minor|major|critical) |)
```

---

## IPI-VRF

---

### Configure instance name

Network Instance Name. For VRF and MAC VRF, instance name can be up to 32 chars long. For VPWS and VPLS instances, instance name can be up to 128 chars long. For L2NI (bridge) instance, instance name has to be a number between (1-32). For Cross-Connect, instance name can be up to 30 chars long. For Bridge-domain, instance, instance name has to be a number between (1-2147483647).

Attribute Name: instance-name

Attribute Type: string

Attribute Name: vrf-name

Attribute Type: string

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance> <!-- operation="delete"-->
    <instance-type>vrf</instance-type>
    <config>
      <instance-type>vrf</instance-type>
      <instance-name>WORD</instance-name>
    </config>
    <instance-name>WORD</instance-name>
  </vrf>
</config>
  <vrf-name>WORD</vrf-name>
```

```

</config>
</vrf>
</network-instance>
</network-instances>

```

## Command Syntax

```
ip vrf WORD
```

---

## Configure instance type

Network Instance Name. For VRF and MAC VRF, instance name can be up to 32 chars long. For VPWS and VPLS instances, instance name can be up to 128 chars long. For L2NI (bridge) instance, instance name has to be a number between (1-32). For Cross-Connect, instance name can be up to 30 chars long. For Bridge-domain, instance, instance name has to be a number between (1-2147483647).

Attribute Name: instance-name

Attribute Type: string

Attribute Name: vrf-name

Attribute Type: string

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance> <!-- operation="delete"-->
    <instance-type>mac-vrf</instance-type>
    <config>
      <instance-type>mac-vrf</instance-type>
      <instance-name>WORD</instance-name>
    </config>
    <instance-name>WORD</instance-name>
  </network-instance>
</network-instances>

```

## Command Syntax

```
mac vrf WORD
```

---

## Configure description

VRF-specific description

Attribute Name: description

Attribute Type: string

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>WORD</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <config>
        <description>LINE</description> <!-- operation="delete"-->
      </config>
    </vrf>
  </network-instance>
</network-instances>

```

### Command Syntax

```
description LINE
```

---

## Configure router id

VRF Router ID

Attribute Name: router-id

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>WORD</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <config>
        <router-id>A.B.C.D</router-id> <!-- operation="delete"-->
      </config>
    </vrf>
  </network-instance>
</network-instances>

```

### Command Syntax

```
router-id A.B.C.D
```

---

## Configure evpn layer3 network id

L3 EVPN Identifier

Attribute Name: evpn-layer3-network-id

Attribute Type: uint32

Attribute Range: 1-16777215

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>WORD</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <config>
        <evpn-layer3-network-id>1</evpn-layer3-network-id> <!--
operation="delete"-->
      </config>
    </vrf>
  </network-instance>
</network-instances>
```

### Command Syntax

```
l3vni <1-16777215>
```

---

## Configure snmp context name

Use this attribute to set the SNMP context for VRF.

This command is supported when following feature are enabled SNMP feature

Attribute Name: snmp-context-name

Attribute Type: string

Attribute Range: 1-32

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>WORD</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
```

```

    <snmp>
    <config>
        <snmp-context-name>WORD</snmp-context-name> <!-- operation="delete"-->
    </config>
</snmp>
</vrf>
</network-instance>
</network-instances>

```

### Command Syntax

```
snmp context-name WORD
```

---

## clear router-id

### Netconf RPC payload

```
<clear-default-router-id xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf"/>
```

### Command Syntax

```
clear router-id
```

---

## clear router-id vrf (VRFNAME|)

Attribute Name: vrfName

Attribute Type: string

### Netconf RPC payload

```

<clear-vrf-router-id xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
  <vrfName>VRFNAME</vrfName>
</clear-vrf-router-id>

```

### Command Syntax

```
clear router-id vrf (VRFNAME|)
```

---

## IPI-INTERFACE

---

### Configure name

The textual name of the interface. The value of this object should be the name of the interface as assigned by the local device and should be suitable for use in commands entered at the device's 'console'. This might be a text name, such as 'le0' or a simple port number, such as '1', depending on the interface naming syntax of the device. If several entries in the ifTable together represent a single interface as named by the device, then each will have the same value of name. Note that for an agent which responds to SNMP queries concerning an interface on some other (proxied) device, then the value of name for such an interface is the proxied device's local name for it. If there is no local name, or this object is otherwise not applicable, then this object contains a zero-length string.

Attribute Name: name

Attribute Type: string

Attribute Range: 1-33

Attribute Name: enable-switchport

Attribute Type: uint8

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface> <!-- operation="delete"-->
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
    </enable-switchport>
  </config>
</interface>
</interfaces>
```

### Command Syntax

```
interface IFNAME (switchport|)
```

---

## Configure enable switchport

This attribute is used to set the mode of the Hybrid Switch Router feature to switched only. All interfaces are configured routed by default

Attribute Name: enable-switchport

Attribute Type: empty

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  </enable-switchport><!-- operation="delete"-->
</interface>
</interfaces>
```

### Command Syntax

```
switchport
```

---

## Configure vrf name

This attribute is used to associates an interface with a VRF

Attribute Name: vrf-name

Attribute Type: string

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
```

```

<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <vrf-name>WORD</vrf-name> <!-- operation="delete"-->
</interface>
</interfaces>

```

### Command Syntax

```
ip vrf forwarding WORD
```

---

## Configure vr name

This attribute is used to associates an interface with a VR

Attribute Name: vr-name

Attribute Type: string

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <vr-name>WORD</vr-name> <!-- operation="delete"-->
</interface>
</interfaces>

```

### Command Syntax

```
virtual-router forwarding WORD
```

---

## Configure mtu

This attribute is used to set mtu value to interface. The size of the largest packet which can be sent/received on the interface, specified in octets. For interfaces that are used for transmitting network datagrams, this is the size of the largest network datagram that can be sent on the interface.

Attribute Name: mtu

Attribute Type: uint32

Attribute Range: 64-65535

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>

```

```

    <mtu>64</mtu> <!-- operation="delete"-->
</interface>
</interfaces>

```

## Command Syntax

```
mtu <64-65535>
```

---

## Configure allow first frame

This Object is used to allow or drop first frame on L2 movement actions

Attribute Name: allow-first-frame

Attribute Type: empty

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  </allow-first-frame><!-- operation="delete"-->
</interface>
</interfaces>

```

## Command Syntax

```
l2 move-allow-first-frame
```

---

## Configure dot1ad ether type

This attribute is used to configure the ethertype value for the interface in the format 0xhhhh. Currently supported values are 0x8100 (default) or 0x88a8 or 0x9100 or 0x9200.

Attribute Name: dot1ad-ether-type

Attribute Type: string

Attribute Range: 6-6

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <dot1ad-ether-type>ETHERTYPE</dot1ad-ether-type> <!-- operation="delete"-->
</interface>
</interfaces>

```

---

## Command Syntax

```
dot1ad ethertype ETHERTYPE
```

---

## Configure description

Use this attribute to set description for the interface

Attribute Name: description

Attribute Type: string

Attribute Range: 1-128

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <description>1</description> <!-- operation="delete"-->
  </interface>
</interfaces>
```

## Command Syntax

```
description LINE
```

---

## Configure shutdown

Use this attribute to enable the selected interface. This leaf contains the configured, desired state of the interface. The testing(3) state indicates that no operational packets can be passed. When a managed system initializes, all interfaces start with ifAdminStatus in the down(2) state. As a result of either explicit management action or per configuration information retained by the managed system, ifAdminStatus is then changed to either the up(1) or testing(3) states (or remains in the down(2) state).

Attribute Name: shutdown

Attribute Type: empty

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    </shutdown><!-- operation="delete"-->
  </interface>
</interfaces>
```

## Command Syntax

```
shutdown
```

---

## Configure if loopback

This attribute is used to enable port loopback

Attribute Name: if-loopback

Attribute Type: enum (tx|rx)

Attribute Name: if-loopback-level

Attribute Type: enum (mac|phy)

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <interface-loopback>
    <config>
      <if-loopback-level>mac</if-loopback-level>
      <if-loopback>tx</if-loopback>
    </config>
    </interface-loopback>
  </interface>
</interfaces>
```

### Command Syntax

```
loopback (tx|rx) (mac|phy)
```

---

## clear interface (IFNAME|) counters

Attribute Name: name

Attribute Type: string

### Netconf RPC payload

```
<clear-interface-counters xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
interface">
  <name>IFNAME</name>
</clear-interface-counters>
```

### Command Syntax

```
clear interface (IFNAME|) counters
```

---

## IPI-IF-ETHERNET

---

### Configure duplex mode

Use this attribute to set the duplex mode for the interface. Auto-negotiation if enabled, is turned off when duplex mode is set for the interface. When auto-negotiation is enabled, the interface should negotiate the duplex mode directly (typically full-duplex).

Attribute Name: duplex-mode

Attribute Type: enum (half|full)

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ethernet">
      <config>
        <duplex-mode>half</duplex-mode> <!-- operation="delete"-->
      </config>
    </ethernet>
  </interface>
</interfaces>
```

### Command Syntax

```
duplex (half|full)
```

---

### Configure mac address

Use this attribute to set the mac address for an interface. If not specified, the corresponding operational state leaf is expected to show the system-assigned MAC address.

Attribute Name: mac-address

Attribute Type: string

Attribute Range: 1-20

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ethernet">
      <config>
        <mac-address>MAC</mac-address> <!-- operation="delete"-->
      </config>
    </ethernet>
  </interface>
</interfaces>
```

```

    </config>
  </ethernet>
</interface>
</interfaces>

```

## Command Syntax

```
mac-address (MAC|use-physical)
```

---

## Configure secondary mac address

Use this attribute to set the secondary mac address for an interface to terminate L3 packets.

Attribute Name: secondary-mac-address

Attribute Type: empty

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ethernet">
      <config>
        </secondary-mac-address><!-- operation="delete"-->
      </config>
    </ethernet>
  </interface>
</interfaces>

```

## Command Syntax

```
mac-address secondary peer-mlag
```

---

## Configure port speed

This attribute is used to set the link speed for the interface. To enable auto-negotiation for the interface, set this attribute to value auto. When auto-negotiation is enabled, it is expected that the interface will select the highest speed available based on negotiation. When auto-negotiation is not enabled, sets the link speed to a fixed value -- supported values are defined by IF\_INTERFACE\_SPEED\_T enum. When limited auto-negotiation is required, select the speed after the auto option. With this only the specified speed will be advertised and interface will negotiate with peer with that speed only.

Attribute Name: port-speed

Attribute Type: enum (10m|100m|1g|2.5g|10g|20g|25g|40g|50g|100g|200g|400g|auto|auto 10m|auto 100m|auto 1g)

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>

```

```

    <name>IFNAME</name>
  </config>
<ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ethernet">
  <config>
    <port-speed>10m</port-speed> <!-- operation="delete"-->
  </config>
</ethernet>
</interface>
</interfaces>

```

## Command Syntax

```

speed (10m|100m|1g|2.5g|10g|20g|25g|40g|50g|100g|200g|400g|auto|auto 10m|auto
100m|auto 1g)

```

## Configure enable rcv

The textual name of the interface. The value of this object should be the name of the interface as assigned by the local device and should be suitable for use in commands entered at the device's 'console'. This might be a text name, such as 'le0' or a simple port number, such as '1', depending on the interface naming syntax of the device. If several entries in the ifTable together represent a single interface as named by the device, then each will have the same value of name. Note that for an agent which responds to SNMP queries concerning an interface on some other (proxied) device, then the value of name for such an interface is the proxied device's local name for it. If there is no local name, or this object is otherwise not applicable, then this object contains a zero-length string.

Attribute Name: name

Attribute Type: string

Attribute Name: enable-rcv

Attribute Type: enum (off|on)

Attribute Name: enable-snd

Attribute Type: enum (off|on)

## Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
  </interface>
</interfaces>

```

---

## Command Syntax

```
flowcontrol both
```

---

## Configure enable rcv

This attribute is used to show flow control on receive

This command is supported when following feature are enabled L2 feature

Attribute Name: enable-rcv

Attribute Type: enum (off|on)

Default Value: off

## Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ethernet">
      <flow-control>
        <config>
          <enable-rcv>off</enable-rcv> <!-- operation="delete"-->
        </config>
      </flow-control>
    </ethernet>
  </interface>
</interfaces>
```

## Command Syntax

```
flowcontrol receive (off|on)
```

---

## Configure enable snd

This attribute is used to show flow control on send

This command is supported when following feature are enabled L2 feature

Attribute Name: enable-snd

Attribute Type: enum (off|on)

Default Value: off

## Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
  </interface>
</interfaces>
```

```

<ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ethernet">
  <flow-control>
    <config>
      <enable-snd>off</enable-snd> <!-- operation="delete"-->
    </config>
  </flow-control>
</ethernet>
</interface>
</interfaces>

```

### Command Syntax

```
flowcontrol send (off|on)
```

---

## IPI-IF-IP

---

### Configure primary ip addr

Use this attribute to specify that an IP address and prefix length will be used by this interface. If the secondary parameter is not specified, this attribute overwrites the primary IP address. If the secondary parameter is specified, this attribute adds a new IP address to the interface. The secondary address cannot be configured in the absence of a primary IP address. The primary address cannot be removed when a secondary address is present.

Attribute Name: primary-ip-addr

Attribute Type: string

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ipv4 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
      <config>
        <primary-ip-addr>A.B.C.D/M|A.B.C.D A.B.C.D</primary-ip-addr> <!--
operation="delete"-->
      </config>
    </ipv4>
  </interface>
</interfaces>

```

### Command Syntax

```
ip address (A.B.C.D/M|A.B.C.D A.B.C.D)
```

---

### Configure enable dhcp ip address

Use this attribute to specify that a DHCP client will be used to obtain an IP address for an interface.

Attribute Name: enable-dhcp-ip-address

Attribute Type: empty

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <ipv4 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
    <config>
      </enable-dhcp-ip-address><!-- operation="delete"-->
    </config>
  </ipv4>
</interface>
</interfaces>
```

### Command Syntax

```
ip address dhcp
```

---

## Configure ip addr label

Label of this address.

Attribute Name: ip-addr-label

Attribute Type: string

Default Value: NULL

Attribute Name: primary-ip-addr

Attribute Type: string

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <ipv4 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
    <config>
      <primary-ip-addr>A.B.C.D/M|A.B.C.D A.B.C.D</primary-ip-addr> <!--
operation="delete"-->
      <ip-addr-label>LINE</ip-addr-label> <!-- operation="delete"-->
    </config>
  </ipv4>
</interface>
</interfaces>
```

### Command Syntax

```
ip address (A.B.C.D/M|A.B.C.D A.B.C.D) label LINE
```

---

## Configure ipv4 unnumbered if name

This attribute is used to Enable IP processing without an explicit address

Attribute Name: ipv4-unnumbered-if-name

Attribute Type: string

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ipv4 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
      <config>
        <ipv4-unnumbered-if-name>IFNAME</ipv4-unnumbered-if-name> <!--
operation="delete"-->
      </config>
    </ipv4>
  </interface>
</interfaces>
```

### Command Syntax

```
ip unnumbered IFNAME
```

---

## Configure remote address

This attribute is used to set the remote address of the PPP link

Attribute Name: remote-address

Attribute Type: string

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ipv4 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
      <config>
        <remote-address>A.B.C.D/M</remote-address> <!-- operation="delete"-->
      </config>
    </ipv4>
  </interface>
</interfaces>
```

### Command Syntax

```
ip remote-address A.B.C.D/M
```

---

## Configure primary anycast

Use this attribute to set the anycast flag for the IPv4 primary address of an interface.

Attribute Name: primary-anycast

Attribute Type: empty

Attribute Name: primary-ip-addr

Attribute Type: string

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ipv4 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
      <config>
        <primary-ip-addr>A.B.C.D/M|A.B.C.D A.B.C.D</primary-ip-addr> <!--
operation="delete"-->
        </primary-anycast><!-- operation="delete"-->
      </config>
    </ipv4>
  </interface>
</interfaces>
```

### Command Syntax

```
ip address (A.B.C.D/M|A.B.C.D A.B.C.D) anycast
```

---

## Configure ip address

Use this attribute to specify a secondary IP address that will be used by this interface. The secondary address cannot be configured in the absence of a primary IP address. The primary address cannot be removed when a secondary address is present.

Attribute Name: ip-address

Attribute Type: string

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ipv4 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
      <secondary-addresses> <!-- operation="delete"-->
        <ip-address>A.B.C.D/M|A.B.C.D A.B.C.D</ip-address>
      </config>
      <ip-address>A.B.C.D/M|A.B.C.D A.B.C.D</ip-address>
    </ipv4>
  </interface>
</interfaces>
```

```

    </config>
  </secondary-addresses>
</ipv4>
</interface>
</interfaces>

```

### Command Syntax

```
ip address (A.B.C.D/M|A.B.C.D A.B.C.D) secondary
```

---

## Configure ip label

Use this attribute to specify a descriptive label for this IPv4 address.

Attribute Name: ip-label

Attribute Type: string

Default Value: NULL

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ipv4 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
      <secondary-addresses>
        <ip-address>A.B.C.D/M|A.B.C.D A.B.C.D</ip-address>
        <config>
          <ip-address>A.B.C.D/M</ip-address>
        </config>
        <ip-label>LINE</ip-label> <!-- operation="delete"-->
      </secondary-addresses>
    </ipv4>
  </interface>
</interfaces>

```

### Command Syntax

```
ip address (A.B.C.D/M|A.B.C.D A.B.C.D) secondary label LINE
```

---

## Configure secondary anycast

Use this attribute to set the anycast flag for the IPv4 secondary address of an interface.

Attribute Name: secondary-anycast

Attribute Type: empty

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>

```

```

<name>IFNAME</name>
<config>
  <name>IFNAME</name>
</config>
<ipv4 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
<secondary-addresses>
  <ip-address>A.B.C.D/M|A.B.C.D A.B.C.D</ip-address>
  <config>
    <ip-address>A.B.C.D/M</ip-address>
  </config>
  </secondary-anycast><!-- operation="delete"-->
</secondary-addresses>
</ipv4>
</interface>
</interfaces>

```

## Command Syntax

```
ip address (A.B.C.D/M|A.B.C.D A.B.C.D) secondary anycast
```

---

## Configure enable auto config

Use this attribute to enable autoconfiguration of IPv6 address in host interface. IPv6 address are formed using the Prefix learned from RA and suffix formed using EUI-64 method.

Attribute Name: enable-auto-config

Attribute Type: boolean

Attribute Name: max-autoconfig-address

Attribute Type: uint8

Attribute Range: 1-64

## Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <ipv6 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
  <config>
    <max-autoconfig-address>1</max-autoconfig-address> <!--
operation="delete"-->
    <enable-auto-config>true</enable-auto-config> <!-- operation="delete"-->
  </config>
</ipv6>
</interface>
</interfaces>

```

## Command Syntax

```
ipv6 address autoconfig (max-address <1-64>|)
```

---

## Configure ipv6 unnumbered if name

Use this attribute to enable IP processing without an explicit address

This command is supported when following feature are enabled IPV6 feature

Attribute Name: ipv6-unnumbered-if-name

Attribute Type: string

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ipv6 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
      <config>
        <ipv6-unnumbered-if-name>IFNAME</ipv6-unnumbered-if-name> <!--
operation="delete"-->
      </config>
    </ipv6>
  </interface>
</interfaces>
```

### Command Syntax

```
ipv6 unnumbered IFNAME
```

---

## Configure enable dhcp ipv6 address

Use this attribute to specify that a DHCP client will be used to obtain an IP address for an interface.

This command is supported when following feature are enabled IPV6 feature

Attribute Name: enable-dhcp-ipv6-address

Attribute Type: empty

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ipv6 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
      <config>
        </enable-dhcp-ipv6-address><!-- operation="delete"-->
      </config>
    </ipv6>
  </interface>
</interfaces>
```

## Command Syntax

```
ipv6 address dhcp
```

---

## Configure enable dhcp temporary ipv6 address

Use this attribute to specify that a DHCP client will be used to obtain an temporary IP address for an interface.

This command is supported when following feature are enabled IPV6 feature

Attribute Name: enable-dhcp-temporary-ipv6-address

Attribute Type: empty

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ipv6 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
      <config>
        </enable-dhcp-temporary-ipv6-address><!-- operation="delete"-->
      </config>
    </ipv6>
  </interface>
</interfaces>
```

## Command Syntax

```
ipv6 address dhcp temporary
```

---

## Configure dhcp address prefix length

Use this attribute to configure the prefix length for the dynamically learnt ipv6 address

This command is supported when following feature are enabled IPV6 feature

Attribute Name: dhcp-address-prefix-length

Attribute Type: uint8

Attribute Range: 1-128

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ipv6 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
      <config>
        <dhcp-address-prefix-length>1</dhcp-address-prefix-length> <!--
operation="delete"-->
```

```

    </config>
  </ipv6>
</interface>
</interfaces>

```

## Command Syntax

```
ipv6 dhcp address-prefix-length <1-128>
```

---

## Configure ipv6 address

Use this attribute to set the IPv6 address of an interface

This command is supported when following feature are enabled IPV6 feature

Attribute Name: ipv6-address

Attribute Type: string

## Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ipv6 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
      <addresses> <!-- operation="delete"-->
        <ipv6-address>X:X::X:X/M</ipv6-address>
        <config>
          <ipv6-address>X:X::X:X/M</ipv6-address>
        </config>
      </addresses>
    </ipv6>
  </interface>
</interfaces>

```

## Command Syntax

```
ipv6 address X:X::X:X/M
```

---

## Configure anycast

Use this attribute to set the anycast flag for the IPv6 address of an interface. Anycast flag cannot be deleted for an IPv6 address once set. Please delete IPv6 address and reconfigure to remove anycast property.

This command is supported when following feature are enabled IPV6 feature

Attribute Name: anycast

Attribute Type: empty

## Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>

```

```

<name>IFNAME</name>
<config>
  <name>IFNAME</name>
</config>
<ipv6 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
  <addresses>
    <ipv6-address>X:X::X:X/M</ipv6-address>
    <config>
      <ipv6-address>X:X::X:X/M</ipv6-address>
    </config>
    </anycast><!-- operation="delete"-->
  </addresses>
</ipv6>
</interface>
</interfaces>

```

### Command Syntax

```
ipv6 address X:X::X:X/M anycast
```

---

## Configure disable ip forwarding

Enable IP forwarding for the router

Attribute Name: disable-ip-forwarding

Attribute Type: uint8

### Netconf edit-config payload

```

<ip-global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
  <config>
    </disable-ip-forwarding><!-- operation="delete"-->
  </config>
</ip-global>

```

### Command Syntax

```
no ip forwarding
```

---

## Configure disable ipv6 forwarding

Enable IPv6 forwarding for the router

Attribute Name: disable-ipv6-forwarding

Attribute Type: uint8

### Netconf edit-config payload

```

<ip-global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
  <config>
    </disable-ipv6-forwarding><!-- operation="delete"-->
  </config>
</ip-global>

```

---

## Command Syntax

```
no ipv6 forwarding
```

---

## Configure router id

Router id of the router - an unsigned 32-bit integer expressed in dotted quad notation

Attribute Name: router-id

Attribute Type: string

### Netconf edit-config payload

```
<ip-global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
  <config>
    <router-id>A.B.C.D</router-id> <!-- operation="delete"-->
  </config>
</ip-global>
```

## Command Syntax

```
router-id A.B.C.D
```

---

## Configure enable auto router id selection

Turn on Automatic Selection of Router ID

Attribute Name: enable-auto-router-id-selection

Attribute Type: empty

### Netconf edit-config payload

```
<ip-global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
  <config>
    </enable-auto-router-id-selection><!-- operation="delete"-->
  </config>
</ip-global>
```

## Command Syntax

```
automatic-router-id-selection enable
```

---

## Configure default vrf enable icmp broadcast

This attribute is used to control ICMP echo broadcast reply. It ignores ICMP echo broadcast when set to true

Attribute Name: default-vrf-enable-icmp-broadcast

Attribute Type: empty

### Netconf edit-config payload

```
<ip-global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
  <config>
    </default-vrf-enable-icmp-broadcast><!-- operation="delete"-->
  </config>
```

```
</ip-global>
```

## Command Syntax

```
ip icmp-broadcast
```

---

## Configure disable ip vrf forwarding

Turn on IP forwarding for the VRF instance

Attribute Name: disable-ip-vrf-forwarding

Attribute Type: uint8

### Netconf edit-config payload

```
<ip-global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
<vrf>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  </disable-ip-vrf-forwarding><!-- operation="delete"-->
</vrf>
</ip-global>
```

## Command Syntax

```
no ip forwarding vrf NAME
```

---

## Configure disable ipv6 vrf forwarding

Turn on IPv6 forwarding for the VRF instance

Attribute Name: disable-ipv6-vrf-forwarding

Attribute Type: uint8

### Netconf edit-config payload

```
<ip-global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
<vrf>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  </disable-ipv6-vrf-forwarding><!-- operation="delete"-->
</vrf>
</ip-global>
```

## Command Syntax

```
no ipv6 forwarding vrf NAME
```

---

## Configure enable icmp broadcast

This attribute is used to control ICMP echo broadcast reply for VRF instance. It ignores ICMP echo broadcast when set to true

This command is supported when following feature are enabled Virtual routing and forwarding

Attribute Name: enable-icmp-broadcast

Attribute Type: empty

### Netconf edit-config payload

```
<ip-global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ip">
  <vrf>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
    </enable-icmp-broadcast><!-- operation="delete"-->
  </vrf>
</ip-global>
```

### Command Syntax

```
ip icmp-broadcast vrf NAME
```

---

## IPI-IF-EXTENDED

---

### Configure protected port

Attribute to change port protectedtype value

Attribute Name: protected-port

Attribute Type: enum (community|isolated|promiscuous)

Default Value: promiscuous

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
      <config>
        <protected-port>promiscuous</protected-port>
      </config>
    </extended>
  </interface>
</interfaces>
```

---

## Command Syntax

```
switchport protected (isolated|promiscuous)
```

---

## Configure name

Attribute to change port protectedtype value

Attribute Name: protected-port

Attribute Type: enum (community|isolated|promiscuous)

Default Value: promiscuous

## Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
  <config>
    <protected-port>promiscuous</protected-port>
  </config>
</extended>
</interface>
</interfaces>
```

## Command Syntax

```
switchport protected (community|isolated|promiscuous)
```

---

## Configure extended protected-port

Attribute to change port protectedtype value

Attribute Name: protected-port

Attribute Type: enum (community|isolated|promiscuous)

Default Value: promiscuous

## Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
  <config>
    <protected-port>promiscuous</protected-port>
  </config>
</extended>
```

```
</interface>
</interfaces>
```

## Command Syntax

```
switchport protected (community|promiscuous)
```

---

## Configure link flap error disable

This object specifies whether the interface is enabled for link-flap error-disable or not. If this is '0', then interface is not enabled. Otherwise it is enabled.

Attribute Name: link-flap-error-disable

Attribute Type: uint8

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <config>
      </link-flap-error-disable><!-- operation="delete"-->
    </config>
  </extended>
</interface>
</interfaces>
```

## Command Syntax

```
no link-flap errdisable
```

---

## Configure storm control error disable

This attribute specifies whether the interface is enabled for storm-control error-disable or not. If this is not set, then the interface is not enabled. Otherwise it is enabled.

Attribute Name: storm-control-error-disable

Attribute Type: uint8

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <config>
      </storm-control-error-disable><!-- operation="delete"-->
    </config>
  </extended>
</interface>
</interfaces>
```

```

    </config>
  </extended>
</interface>
</interfaces>

```

### Command Syntax

```
no storm-control errdisable
```

---

## Configure mac move limit error disable

This object specifies whether the interface is enabled for mac-move-limit error-disable or not. If this is '0', then interface is not enabled. Otherwise it is enabled.

Attribute Name: mac-move-limit-error-disable

Attribute Type: uint8

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
      <config>
        </mac-move-limit-error-disable><!-- operation="delete"-->
      </config>
    </extended>
  </interface>
</interfaces>

```

### Command Syntax

```
no mac-move-limit errdisable
```

---

## Configure disable snmp trap link status

This Object is used to set the snmp trap link status in an interface

Attribute Name: disable-snmp-trap-link-status

Attribute Type: uint8

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
      <config>

```

```

        </disable-snmp-trap-link-status><!-- operation="delete"-->
    </config>
</extended>
</interface>
</interfaces>

```

### Command Syntax

```
no snmp trap link-status
```

---

## Configure mac move priority

This object used to set the priority of mac-move of an interface

Attribute Name: mac-move-priority

Attribute Type: uint32

Attribute Range: 1-255

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
      <config>
        <mac-move-priority>1</mac-move-priority> <!-- operation="delete"-->
      </config>
    </extended>
  </interface>
</interfaces>

```

### Command Syntax

```
mac-move-limit priority <1-255>
```

---

## Configure mau default type

This attribute is used to set the mau type in an interface

Attribute Name: mau-default-type

Attribute Type: enum

(dot3MauType10BaseTHD|dot3MauType10BaseTFD|dot3MauType100BaseTXHD|dot3MauType100BaseTXFD|dot3MauType1000BaseXHD|dot3MauType1000BaseXFD|dot3MauType10GigBaseCX4|dot3MauType10GbaseKX4|dot3MauType10GbaseKR|dot3MauType40GbaseCR4)

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>

```

```

    <name>IFNAME</name>
  </config>
  <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <config>
      <mau-default-type>dot3MauType10BaseTHD</mau-default-type> <!--
operation="delete"-->
    </config>
  </extended>
</interface>
</interfaces>

```

## Command Syntax

```

mau-default-type
(dot3MauType10BaseTHD|dot3MauType10BaseTFD|dot3MauType100BaseTXHD|dot3MauType100
BaseTXFD|dot3MauType1000BaseXHD|dot3MauType1000BaseXFD|dot3MauType10GigBaseCX4|d
ot3MauType10GbaseKX4|dot3MauType10GbaseKR|dot3MauType40GbaseCR4)

```

---

## Configure debounce time

Use this attribute to set the interface debounce timer value

Attribute Name: debounce-time

Attribute Type: uint16

Attribute Range: 250-5000

## Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
      <config>
        <debounce-time>250</debounce-time> <!-- operation="delete"-->
      </config>
    </extended>
  </interface>
</interfaces>

```

## Command Syntax

```

debounce-time <250-5000>

```

---

## Configure ucmp port

To enable UCMP support.

Attribute Name: ucmp-port

Attribute Type: enum (enable)

---

## Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <config>
      <ucmp-port>enable</ucmp-port> <!-- operation="delete"-->
    </config>
  </extended>
</interface>
</interfaces>
```

## Command Syntax

```
ucmp (enable)
```

---

## Configure enable re routing

Enable re-routing when the bandwidth crosses down the minimum bandwidth

Attribute Name: enable-re-routing

Attribute Type: empty

## Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <bandwidth-management>
      <config>
        </enable-re-routing><!-- operation="delete"-->
      </config>
    </bandwidth-management>
  </extended>
</interface>
</interfaces>
```

## Command Syntax

```
re-routing
```

---

## Configure enable speed

This object is used to enable port-monitoring for the specified parameters, average speed of the interface

Attribute Name: enable-speed

Attribute Type: empty

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <port-monitor>
      <config>
        </enable-speed><!-- operation="delete"-->
      </config>
    </port-monitor>
  </extended>
</interface>
</interfaces>
```

### Command Syntax

```
monitor speed
```

---

## Configure enable queue drops

This object is used to enable queue-drops of the interface

Attribute Name: enable-queue-drops

Attribute Type: empty

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <port-monitor>
      <config>
        </enable-queue-drops><!-- operation="delete"-->
      </config>
    </port-monitor>
  </extended>
</interface>
</interfaces>
```

### Command Syntax

```
monitor queue-drops
```

---

## Configure warning threshold

This object is used to specify warning threshold for port speed monitor. Warning threshold must be greater than recovery threshold. Default value of warning-threshold is 90.

Attribute Name: warning-threshold

Attribute Type: uint8

Attribute Range: 1-100

Attribute Name: recovery-threshold

Attribute Type: uint8

Attribute Range: 1-100

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
      <port-monitor>
        <port-monitor-threshold>
          <config>
            <recovery-threshold>1</recovery-threshold>
            <warning-threshold>1</warning-threshold>
          </config>
        </port-monitor-threshold>
      </port-monitor>
    </extended>
  </interface>
</interfaces>
```

### Command Syntax

```
monitor speed threshold warning <1-100> recovery <1-100>
```

---

## Configure aclif type

Use this attribute to set the Hardware timestamp

Attribute Name: aclif-type

Attribute Type: enum (failover|no-failover)

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
  </interface>
</interfaces>
```

```

    <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <aclif>
    <config>
        <aclif-type>failover</aclif-type> <!-- operation="delete"-->
    </config>
    </aclif>
    </extended>
    </interface>
    </interfaces>

```

### Command Syntax

```
aclif (failover|no-failover)
```

---

## Configure linkup debounce time

Link debounce timer value for down-up transition

Attribute Name: linkup-debounce-time

Attribute Type: uint16

Attribute Range: 0-5000

Attribute Name: linkdown-debounce-time

Attribute Type: uint16

Attribute Range: 0-5000

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
    <name>IFNAME</name>
    <config>
        <name>IFNAME</name>
    </config>
    <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <link-debounce-time>
    <config>
        <linkdown-debounce-time>0</linkdown-debounce-time>
        <linkup-debounce-time>0</linkup-debounce-time>
    </config>
    </link-debounce-time>
    </extended>
    </interface>
    </interfaces>

```

### Command Syntax

```
link-debounce-time <0-5000> <0-5000>
```

---

## Configure l2cp type

This attribute is used to configure the layer2 control-protocol type

Attribute Name: l2cp-type

Attribute Type: enum (stp|lacp|dot1x|lldp|efm|elmi)

Attribute Name: protocol-process

Attribute Type: enum (peer|tunnel|discard)

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <extended xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
      <l2-control-protocol> <!-- operation="delete"-->
        <l2cp-type>stp</l2cp-type>
        <config>
          <l2cp-type>stp</l2cp-type>
          <protocol-process>peer</protocol-process>
        </config>
      </l2-control-protocol>
    </extended>
  </interface>
</interfaces>
```

### Command Syntax

```
l2protocol (stp|lacp|dot1x|lldp|efm|elmi) (peer|tunnel|discard)
```

---

## Configure forward err correction

This Object is used to set forward-error-correction to interface

Attribute Name: forward-err-correction

Attribute Type: enum (off|on|auto|on cl74|on cl91)

Default Value: auto

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ethernet">
      <extended-ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
        <config>
          <forward-err-correction>auto</forward-err-correction> <!--
operation="delete"-->
        </config>
      </extended-ethernet>
    </ethernet>
  </interface>
</interfaces>
```

```

    </extended-ethernet>
  </ethernet>
</interface>
</interfaces>

```

## Command Syntax

```
fec (off|on|auto|on cl74|on cl91)
```

---

## Configure load interval

This attribute is used to configure load interval period in multiples of 30 seconds

Attribute Name: load-interval

Attribute Type: uint16

Default Value: 300

Attribute Range: 30-300

## Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ethernet">
      <extended-ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
        <config>
          <load-interval>30</load-interval> <!-- operation="delete"-->
        </config>
      </extended-ethernet>
    </ethernet>
  </interface>
</interfaces>

```

## Command Syntax

```
load-interval <30-300>
```

---

## Configure bcast value

This attribute is used to set the storm control configuration, Set Broadcast Rate Limiting of layer2 Interface

This command is supported when following feature are enabled rate limit feature

Attribute Name: bcast-value

Attribute Type: union

Attribute Name: bcast-rate-limit-format

Attribute Type: enum (level|kpbs|mbps|gbps|fps)

Attribute Name: bcast-burst-value

Attribute Type: uint32

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ethernet">
    <storm-control xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
      <broadcast>
        <config>
          <bcast-rate-limit-format>0</bcast-rate-limit-format>
          <bcast-burst-value>32</bcast-burst-value>
          <bcast-value>LEVEL</bcast-value>
        </config>
      </broadcast>
    </storm-control>
  </ethernet>
</interface>
</interfaces>
```

### Command Syntax

```
storm-control broadcast level LEVEL (burst-size <32-128000>|)
```

---

## Configure bcast rate limit format

This attribute is used to set the storm control configuration, Set the format for units in kbps|mbps|gbps or level for threshold percentage

This command is supported when following feature are enabled rate limit feature

Attribute Name: bcast-rate-limit-format

Attribute Type: enum (level|kbps|mbps|gbps|fps)

Attribute Name: bcast-value

Attribute Type: union

Attribute Name: bcast-burst-value

Attribute Type: uint32

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ethernet">
    <storm-control xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
```

```

    <broadcast>
    <config>
        <bcast-value>0</bcast-value>
        <bcast-burst-value>32</bcast-burst-value>
        <bcast-rate-limit-format>level</bcast-rate-limit-format>
    </config>
</broadcast>
</storm-control>
</ethernet>
</interface>
</interfaces>

```

## Command Syntax

```

storm-control broadcast <0-4294967294> (kbps|mbps|gbps|fps) (burst-size <32-
128000>|)

```

---

## Configure mcast value

This attribute is used to set the storm control configuration, Set Multicast Rate Limiting of layer2 Interface

This command is supported when following feature are enabled rate limit feature

Attribute Name: mcast-value

Attribute Type: union

Attribute Name: mcast-rate-limit-format

Attribute Type: enum (level|kbps|mbps|gbps|fps)

Attribute Name: mcast-burst-value

Attribute Type: uint32

## Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
    <name>IFNAME</name>
    <config>
        <name>IFNAME</name>
    </config>
    <ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ethernet">
        <storm-control xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
            <multicast>
                <config>
                    <mcast-rate-limit-format>0</mcast-rate-limit-format>
                    <mcast-burst-value>32</mcast-burst-value>
                    <mcast-value>LEVEL</mcast-value>
                </config>
            </multicast>
        </storm-control>
    </ethernet>
</interface>
</interfaces>

```

## Command Syntax

```
storm-control multicast level LEVEL (burst-size <32-128000>|)
```

---

## Configure mcast rate limit format

This attribute is used to set the storm control configuration, Set the format for units in kbps|mbps|gbps or level for threshold percentage

This command is supported when following feature are enabled rate limit feature

Attribute Name: mcast-rate-limit-format

Attribute Type: enum (level|kbps|mbps|gbps|fps)

Attribute Name: mcast-value

Attribute Type: union

Attribute Name: mcast-burst-value

Attribute Type: uint32

## Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ethernet">
      <storm-control xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
        <multicast>
          <config>
            <mcast-value>0</mcast-value>
            <mcast-burst-value>32</mcast-burst-value>
            <mcast-rate-limit-format>level</mcast-rate-limit-format>
          </config>
        </multicast>
      </storm-control>
    </ethernet>
  </interface>
</interfaces>
```

## Command Syntax

```
storm-control multicast <0-4294967294> (kbps|mbps|gbps|fps) (burst-size <32-128000>|)
```

---

## Configure dlf bcast value

This attribute is used to set the storm control configuration,Set DLF Broadcast Rate Limiting of layer2 Interface

This command is supported when following feature are enabled rate limit feature

Attribute Name: dlf-bcast-value

Attribute Type: union

Attribute Name: dlf-bcast-rate-limit-format

Attribute Type: enum (level|kbps|mbps|gbps|fps)

Attribute Name: dlf-bcast-burst-value

Attribute Type: uint32

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ethernet">
      <storm-control xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
        <dlf-broadcast>
          <config>
            <dlf-bcast-rate-limit-format>0</dlf-bcast-rate-limit-format>
            <dlf-bcast-burst-value>32</dlf-bcast-burst-value>
            <dlf-bcast-value>LEVEL</dlf-bcast-value>
          </config>
        </dlf-broadcast>
      </storm-control>
    </ethernet>
  </interface>
</interfaces>
```

### Command Syntax

```
storm-control dlf level LEVEL (burst-size <32-128000>|)
```

---

## Configure dlf bcast rate limit format

This attribute is used to set the storm control configuration, Set the format for units in kbps|mbps|gbps or level for threshold percentage

This command is supported when following feature are enabled rate limit feature

Attribute Name: dlf-bcast-rate-limit-format

Attribute Type: enum (level|kbps|mbps|gbps|fps)

Attribute Name: dlf-bcast-value

Attribute Type: union

Attribute Name: dlf-bcast-burst-value

Attribute Type: uint32

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
```

```

<config>
  <name>IFNAME</name>
</config>
<ethernet xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-ethernet">
  <storm-control xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <dlf-broadcast>
      <config>
        <dlf-bcast-value>0</dlf-bcast-value>
        <dlf-bcast-burst-value>32</dlf-bcast-burst-value>
        <dlf-bcast-rate-limit-format>level</dlf-bcast-rate-limit-format>
      </config>
    </dlf-broadcast>
  </storm-control>
</ethernet>
</interface>
</interfaces>

```

### Command Syntax

```
storm-control dlf <0-4294967294> (kbps|mbps|gbps|fps) (burst-size <32-128000>|)
```

---

## Configure error disable stp bpdu guard

This object is used to configure error disable STP BPDU Guard

Attribute Name: error-disable-stp-bpdu-guard

Attribute Type: boolean

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <error-disable>
      <config>
        <error-disable-stp-bpdu-guard>true</error-disable-stp-bpdu-guard> <!--
operation="delete"-->
      </config>
    </error-disable>
  </global>
</interfaces>

```

### Command Syntax

```
no errdisable cause stp-bpdu-guard
```

---

## Configure reason

This object is to enable various error-disable reasons like lag-mismatch, stp-bpdu-guard, link-flap and loopback-detection. As the datatype is BITS, 0th bit corresponds to lag-mismatch, 1st bit corresponds to stp-bpdu-guard, 2nd bit corresponds to link-flap

Attribute Name: reason

Attribute Type: bits (lag-mismatch|link-flap|mac-move-limit|storm-control)

Attribute Name: error-disable-stp-bpdu-guard

Attribute Type: boolean

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <error-disable>
      <config>
        <error-disable-stp-bpdu-guard>true</error-disable-stp-bpdu-guard> <!--
operation="delete"-->
        <reason>lag-mismatch</reason> <!-- operation="delete"-->
      </config>
    </error-disable>
  </global>
</interfaces>
```

### Command Syntax

```
errdisable cause stp-bpdu-guard {lag-mismatch|link-flap|mac-move-limit|storm-
control}
```

---

## Configure link flap timer interval

This object is configure timer interval for link-flap timer

Attribute Name: link-flap-timer-interval

Attribute Type: uint32

Attribute Range: 1-1800

Attribute Name: link-flap-max-count

Attribute Type: uint32

Attribute Range: 1-100

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <error-disable>
      <config>
        <link-flap-max-count>1</link-flap-max-count> <!-- operation="delete"-->
        <link-flap-timer-interval>1</link-flap-timer-interval> <!--
operation="delete"-->
      </config>
    </error-disable>
  </global>
</interfaces>
```

### Command Syntax

```
errdisable link-flap-setting max-flaps <1-100> time <1-1800>
```

---

## Configure storm control timer interval

This attribute is configure timer interval for storm-control timer

Attribute Name: storm-control-timer-interval

Attribute Type: uint32

Attribute Range: 1-1800

Attribute Name: storm-control-max-count

Attribute Type: uint32

Attribute Range: 1-100

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <error-disable>
      <config>
        <storm-control-max-count>1</storm-control-max-count> <!-- operation="delete"-->
->
          <storm-control-timer-interval>1</storm-control-timer-interval> <!--
operation="delete"-->
        </config>
      </error-disable>
    </global>
  </interfaces>
```

### Command Syntax

```
errdisable storm-control discard-hit <1-100> time <1-1800>
```

---

## Configure error-disable reason

This object is to enable various error-disable reasons like lag-mismatch, stp-bpdu-guard, link-flap and loopback-detection. As the datatype is BITS, 0th bit corresponds to lag-mismatch, 1st bit corresponds to stp-bpdu-guard, 2nd bit corresponds to link-flap

Attribute Name: reason

Attribute Type: bits (lag-mismatch|link-flap|mac-move-limit|storm-control)

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <error-disable>
      <config>
        <reason>lag-mismatch</reason> <!-- operation="delete"-->
      </config>
    </error-disable>
  </global>
</interfaces>
```

## Command Syntax

```
errdisable cause {lag-mismatch|link-flap|mac-move-limit|storm-control}
```

---

## Configure error-disable error-disable-stp-bpdu-guard

This object is used to configure error disable STP BPDU Guard

Attribute Name: error-disable-stp-bpdu-guard

Attribute Type: boolean

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <error-disable>
      <config>
        <error-disable-stp-bpdu-guard>true</error-disable-stp-bpdu-guard> <!--
operation="delete"-->
      </config>
    </error-disable>
  </global>
</interfaces>
```

## Command Syntax

```
errdisable cause stp-bpdu-guard
```

---

## Configure timeout interval

This object is to configure timeout for error-disable automatic recovery timer

Attribute Name: timeout-interval

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-1000000

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <error-disable>
      <config>
        <timeout-interval>0</timeout-interval> <!-- operation="delete"-->
      </config>
    </error-disable>
  </global>
</interfaces>
```

## Command Syntax

```
errdisable timeout interval <0-1000000>
```

---

## Configure mac move limit

This object configures threshold for mac movement

Attribute Name: mac-move-limit

Attribute Type: uint32

Default Value: 100

Attribute Range: 1-1000

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <error-disable>
      <config>
        <mac-move-limit>1</mac-move-limit> <!-- operation="delete"-->
      </config>
    </error-disable>
  </global>
</interfaces>
```

### Command Syntax

```
errdisable mac-move-limit <1-1000>
```

---

## Configure mode

This attribute is used to unset the tunnel mode

This command is supported when following feature are enabled tunnel feature

Attribute Name: mode

Attribute Type: enum (vxlan)

Default Value: vxlan

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <tunnel xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
      <config>
        <mode>vxlan</mode> <!-- operation="delete"-->
      </config>
    </tunnel>
  </interface>
</interfaces>
```

## Command Syntax

```
tunnel mode (vxlan)
```

---

## Configure src

This attribute is used to set tunnel source

This command is supported when following feature are enabled tunnel feature

Attribute Name: src

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <tunnel xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
  <config>
    <src>A.B.C.D</src> <!-- operation="delete"-->
  </config>
</tunnel>
</interface>
</interfaces>
```

## Command Syntax

```
tunnel source A.B.C.D
```

---

## Configure multicast interface

This attribute is used to configure egress multicast interface for tunnel

This command is supported when following feature are enabled tunnel feature

Attribute Name: multicast-interface

Attribute Type: string

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <tunnel xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
  <config>
    <multicast-interface>IFNAME</multicast-interface> <!--
operation="delete"-->
  </config>
```

```

</tunnel>
</interface>
</interfaces>

```

## Command Syntax

```
tunnel egress-multicast-interface IFNAME
```

---

## Configure dst

This attribute is used to set destination of tunnel packets

This command is supported when following feature are enabled tunnel feature

Attribute Name: dst

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <tunnel xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
  <config>
    <dst>A.B.C.D</dst> <!-- operation="delete"-->
  </config>
</tunnel>
</interface>
</interfaces>

```

## Command Syntax

```
tunnel destination A.B.C.D
```

---

## Configure checksum enable

This attribute is used to enable end to end checksumming of packets

This command is supported when following feature are enabled tunnel feature

Attribute Name: checksum-enable

Attribute Type: empty

## Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <tunnel xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">

```

```

    <config>
      </checksum-enable><!-- operation="delete"-->
    </config>
  </tunnel>
</interface>
</interfaces>

```

### Command Syntax

```
tunnel checksum
```

---

## Configure tos byte

This attribute is used to set type of service byte

This command is supported when following feature are enabled tunnel feature

Attribute Name: tos-byte

Attribute Type: uint16

Attribute Range: 0-255

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <tunnel xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
      <config>
        <tos-byte>0</tos-byte> <!-- operation="delete"-->
      </config>
    </tunnel>
  </interface>
</interfaces>

```

### Command Syntax

```
tunnel tos <0-255>
```

---

## Configure ttl

This attribute is used to set time to live

This command is supported when following feature are enabled tunnel feature

Attribute Name: ttl

Attribute Type: uint16

Attribute Range: 1-255

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">

```

```

<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <tunnel xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <config>
      <ttl>1</ttl> <!-- operation="delete"-->
    </config>
  </tunnel>
</interface>
</interfaces>

```

### Command Syntax

```
tunnel ttl <1-255>
```

---

## Configure path mtu enable

This attribute is used to enable Path MTU Discovery on tunnel

This command is supported when following feature are enabled tunnel feature

Attribute Name: path-mtu-enable

Attribute Type: empty

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <tunnel xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
      <config>
        </path-mtu-enable><!-- operation="delete"-->
      </config>
    </tunnel>
  </interface>
</interfaces>

```

### Command Syntax

```
tunnel path-mtu-discovery
```

---

## Configure dst mac address

This attribute is used to set next Hop Destination MAC Address of Tunnel Packets

This command is supported when following feature are enabled tunnel feature

Attribute Name: dst-mac-address

Attribute Type: string

## Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <tunnel xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <config>
      <dst-mac-address>MAC</dst-mac-address> <!-- operation="delete"-->
    </config>
  </tunnel>
</interface>
</interfaces>
```

## Command Syntax

```
tunnel dmac MAC
```

---

## Configure gre key

This attribute is used to set the gre-key for tunnel

This command is supported when following feature are enabled tunnel feature

Attribute Name: gre-key

Attribute Type: union

## Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <tunnel xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
    <config>
      <gre-key>IF_TUNNEL_KEY_T</gre-key>
    </config>
  </tunnel>
</interface>
</interfaces>
```

## Command Syntax

```
tunnel key (A.B.C.D|<0-4294967295>)
```

---

## Configure hit based ageing

Use this attribute to set the mac ageing src or dst-src

Attribute Name: hit-based-ageing

Attribute Type: enum (src|dst-src)

### Netconf edit-config payload

```
<mac-ageing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-extended">
  <config>
    <hit-based-ageing>src</hit-based-ageing> <!-- operation="delete"-->
  </config>
</mac-ageing>
```

### Command Syntax

```
mac-ageing (src|dst-src)
```

---

## clear interface (IFNAME|) cpu counters

Attribute Name: if-name

Attribute Type: string

### Netconf RPC payload

```
<clear-interface-cpu-counters xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
if-extended">
  <if-name>IFNAME</if-name>
</clear-interface-cpu-counters>
```

### Command Syntax

```
clear interface (IFNAME|) cpu counters
```

---

## clear interface (IFNAME|) fec

Attribute Name: if-name

Attribute Type: string

### Netconf RPC payload

```
<clear-interface-forward-error-correction-counters xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-if-extended">
  <if-name>IFNAME</if-name>
</clear-interface-forward-error-correction-counters>
```

### Command Syntax

```
clear interface (IFNAME|) fec
```

---

## clear interface IFNAME error-disable

Attribute Name: if-name

Attribute Type: string

### Netconf RPC payload

```
<clear-interface-error-disable xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
if-extended">
```

```
<if-name>IFNAME</if-name>
</clear-interface-error-disable>
```

## Command Syntax

```
clear interface IFNAME error-disable
```

---

## clear l2protocol interface (IFNAME|) counters (peer|tunnel|discard|tunnel-discard|)

Attribute Name: if-name

Attribute Type: string

Attribute Name: protocol

Attribute Type: enum (peer|tunnel|discard|tunnel-discard|all)

Default Value: all

### Netconf RPC payload

```
<clear-l2protocol-interface-counter xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-if-extended">
  <if-name>IFNAME</if-name>
  <protocol>all</protocol>
</clear-l2protocol-interface-counter>
```

## Command Syntax

```
clear l2protocol interface (IFNAME|) counters (peer|tunnel|discard|tunnel-discard|)
```

---

# IPI-SYSTEM

---

## Configure hostname

Use this command to set the network name for the device. OcnOS uses this name in system prompts and default configuration filenames. Setting a host name using this command also sets the host name in the kernel. After giving the hostname command, you must write to memory using the write command. If you do not write to memory, the change made by this command (the new host name) is not set after the device reboots.

Attribute Name: hostname

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```
<system-info xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-system">
  <config>
    <hostname>WORD</hostname> <!-- operation="delete"-->
  </config>
</system-info>
```

---

## Command Syntax

```
hostname WORD
```

---

## Configure timezone name

The attribute display timezone name used for the system

Attribute Name: timezone-name

Attribute Type: string

### Netconf edit-config payload

```
<system-info xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-system">
  <clock>
    <config>
      <timezone-name>WORD</timezone-name> <!-- operation="delete"-->
    </config>
  </clock>
</system-info>
```

## Command Syntax

```
clock timezone WORD
```

---

# IPI-NETWORK-SERVICES-MANAGER

---

## Configure options

Use this attribute to debug nsm

Attribute Name: options

Attribute Type: bits (addressmonitor|bfd|events|hal events|hal ipc|linkmonitor|packet|packet detail|packet rcv|packet rcv detail|packet send|packet send detail|vxlan|ipsec|all)

### Netconf edit-config payload

```
<network-services-manager xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
services-manager">
  <debug>
    <nsm>
      <config>
        <options>addressmonitor</options> <!-- operation="delete"-->
      </config>
    </nsm>
  </debug>
</network-services-manager>
```

## Command Syntax

```
debug nsm ((addressmonitor|bfd|events|hal events|hal ipc|linkmonitor|packet|packet
  detail|packet rcv|packet rcv detail|packet send|packet send
  detail|vxlan|ipsec|all)|)
```

---

## Configure pkt-mgr options

Use this attribute to debug vlan packet

Attribute Name: options

Attribute Type: bits (l2 protocol cfm|l2 protocol eapol|l2 protocol efm|l2 protocol igmp-snoop|l2 protocol lacp|l2 protocol lldp|l2 protocol mldp-snoop|l2 protocol mstp|l2 protocol ptp|l2 protocol all)

### Netconf edit-config payload

```
<network-services-manager xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-services-manager">
  <debug>
    <pkt-mgr>
      <config>
        <options>l2 protocol cfm</options> <!-- operation="delete"-->
      </config>
    </pkt-mgr>
  </debug>
</network-services-manager>
```

### Command Syntax

```
debug pktmgr (l2 protocol cfm|l2 protocol eapol|l2 protocol efm|l2 protocol igmp-
snoop|l2 protocol lacp|l2 protocol lldp|l2 protocol mldp-snoop|l2 protocol
mstp|l2 protocol ptp|l2 protocol all)
```

---

## Configure module name

Use this attribute to set debug HSL module

This command is supported when following feature are enabled HSL feature

Attribute Name: module-name

Attribute Type: enum

(general|ifmgr|bridge|msg|fib|fdb|devdrv|pktdrv|platform|pbr|bfd|lacp|qos|helper|rbridge|nvo|ofl|mلاغ|srv6|ptp|extphy)

Attribute Name: level

Attribute Type: bits (all|default|info|debug|warn|error|fatal|admin|counter|pkt)

### Netconf edit-config payload

```
<network-services-manager xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-services-manager">
  <debug>
    <hsl>
      <hsl-module> <!-- operation="delete"-->
        <module-name>general</module-name>
      <config>
        <module-name>general</module-name>
        <level>all</level>
      </config>
    </hsl-module>
  </hsl>
</debug>
```

---

```
</network-services-manager>
```

## Command Syntax

```
debug hsl
  (general|ifmgr|bridge|msg|fib|fdb|devdrv|pktdrv|platform|pbr|bfd|lacp|qos|helper
  |rbridge|nvo|ofl|mlag|srv6|ptp|extphy)
  {all|default|info|debug|warn|error|fatal|admin|counter|pkt}
```

---

## debug nsm ((addressmonitor|bfd|events|hal events|hal ipc|linkmonitor|packet|packet detail|packet rcv|packet rcv detail|packet send|packet send detail|vxlan|ipsec|all))

Attribute Name: terminal-debug-options

Attribute Type: bits (addressmonitor|bfd|events|hal events|hal ipc|linkmonitor|packet|packet detail|packet rcv|packet rcv detail|packet send|packet send detail|vxlan|ipsec|all)

### Netconf RPC payload

```
<nsm-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
services-manager">
  <terminal-debug-options>addressmonitor</terminal-debug-options>
</nsm-terminal-debug-on>
```

## Command Syntax

```
debug nsm ((addressmonitor|bfd|events|hal events|hal ipc|linkmonitor|packet|packet
  detail|packet rcv|packet rcv detail|packet send|packet send
  detail|vxlan|ipsec|all))
```

---

## no debug nsm ((addressmonitor|bfd|events|hal events|hal ipc|linkmonitor|packet|packet detail|packet rcv|packet rcv detail|packet send|packet send detail|vxlan|ipsec|all))

Attribute Name: terminal-debug-options

Attribute Type: bits (addressmonitor|bfd|events|hal events|hal ipc|linkmonitor|packet|packet detail|packet rcv|packet rcv detail|packet send|packet send detail|vxlan|ipsec|all)

### Netconf RPC payload

```
<nsm-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
services-manager">
  <terminal-debug-options>addressmonitor</terminal-debug-options>
</nsm-terminal-debug-off>
```

## Command Syntax

```
no debug nsm ((addressmonitor|bfd|events|hal events|hal
  ipc|linkmonitor|packet|packet detail|packet rcv|packet rcv detail|packet
  send|packet send detail|vxlan|ipsec|all))
```

---

## debug hsl

**(general|ifmgr|bridge|msg|fib|fdb|devdrv|pktdrv|platform|pbr|bfd|lcp|qos|helper|rbridge|nvo|ofl|mlag|srv6|ptp|extphy)**  
**{all|default|info|debug|warn|error|fatal|admin|counter|pkt}**

Attribute Name: module-name

Attribute Type: enum

(general|ifmgr|bridge|msg|fib|fdb|devdrv|pktdrv|platform|pbr|bfd|lcp|qos|helper|rbridge|nvo|ofl|mlag|srv6|ptp|extphy)

Attribute Name: level

Attribute Type: bits (all|default|info|debug|warn|error|fatal|admin|counter|pkt)

### Netconf RPC payload

```
<hsl-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
services-manager">
  <module-name>general</module-name>
  <level>all</level>
</hsl-terminal-debug-on>
```

### Command Syntax

```
debug hsl
  (general|ifmgr|bridge|msg|fib|fdb|devdrv|pktdrv|platform|pbr|bfd|lcp|qos|helper
  |rbridge|nvo|ofl|mlag|srv6|ptp|extphy)
  {all|default|info|debug|warn|error|fatal|admin|counter|pkt}
```

---

## no debug hsl

**(general|ifmgr|bridge|msg|fib|fdb|devdrv|pktdrv|platform|pbr|bfd|lcp|qos|helper|rbridge|nvo|ofl|mlag|srv6|ptp|extphy)**  
**{all|default|info|debug|warn|error|fatal|admin|counter|pkt}**

Attribute Name: module-name

Attribute Type: enum

(general|ifmgr|bridge|msg|fib|fdb|devdrv|pktdrv|platform|pbr|bfd|lcp|qos|helper|rbridge|nvo|ofl|mlag|srv6|ptp|extphy)

Attribute Name: level

Attribute Type: bits (all|default|info|debug|warn|error|fatal|admin|counter|pkt)

### Netconf RPC payload

```
<hsl-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
services-manager">
  <module-name>general</module-name>
  <level>all</level>
</hsl-terminal-debug-off>
```

### Command Syntax

```
no debug hsl
  (general|ifmgr|bridge|msg|fib|fdb|devdrv|pktdrv|platform|pbr|bfd|lcp|qos|helper
```

```
|rbridge|nvo|ofl|mlag|srv6|ptp|extphy)
{all|default|info|debug|warn|error|fatal|admin|counter|pkt}
```

---

## **debug pktmgr (l2 protocol cfm|l2 protocol eapol|l2 protocol efm|l2 protocol igmp-snoop|l2 protocol lacp|l2 protocol lldp|l2 protocol mldp-snoop|l2 protocol mstp|l2 protocol ptp|l2 protocol all)**

Attribute Name: terminal-debug-options

Attribute Type: bits (l2 protocol cfm|l2 protocol eapol|l2 protocol efm|l2 protocol igmp-snoop|l2 protocol lacp|l2 protocol lldp|l2 protocol mldp-snoop|l2 protocol mstp|l2 protocol ptp|l2 protocol all)

### **Netconf RPC payload**

```
<pktmgr-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
network-services-manager">
  <terminal-debug-options>l2 protocol cfm</terminal-debug-options>
</pktmgr-terminal-debug-on>
```

### **Command Syntax**

```
debug pktmgr (l2 protocol cfm|l2 protocol eapol|l2 protocol efm|l2 protocol igmp-
snoop|l2 protocol lacp|l2 protocol lldp|l2 protocol mldp-snoop|l2 protocol
mstp|l2 protocol ptp|l2 protocol all)
```

---

## **no debug pktmgr**

### **Netconf RPC payload**

```
<pktmgr-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
network-services-manager"/>
```

### **Command Syntax**

```
no debug pktmgr
```

---

## **debug pktmgr enable**

### **Netconf RPC payload**

```
<pktmgr-debug-statistics-enable xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
network-services-manager"/>
```

### **Command Syntax**

```
debug pktmgr enable
```

---

## **debug pktmgr disable**

### **Netconf RPC payload**

```
<pktmgr-debug-statistics-disable xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-network-services-manager"/>
```

---

## Command Syntax

```
debug pktmgr disable
```

---

## debug pktmgr stats

### Netconf RPC payload

```
<pktmgr-debug-statistics-get xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-services-manager"/>
```

### Command Syntax

```
debug pktmgr stats
```

---

## debug pktmgr (stats|pkt-errors)

Attribute Name: debug-error-statistics

Attribute Type: enum (stats|pkt-errors)

### Netconf RPC payload

```
<pktmgr-debug-error-statistics-get xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-services-manager">
  <debug-error-statistics>stats</debug-error-statistics>
</pktmgr-debug-error-statistics-get>
```

### Command Syntax

```
debug pktmgr (stats|pkt-errors)
```

---

## clear nsm ipc stats

### Netconf RPC payload

```
<clear-nsm-ipc-statistics xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-services-manager"/>
```

### Command Syntax

```
clear nsm ipc stats
```

---

## clear nsm server ipc-stats

### Netconf RPC payload

```
<clear-nsm-server-ipc-statistics xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-services-manager"/>
```

### Command Syntax

```
clear nsm server ipc-stats
```

---

## snmp restart nsm

### Netconf RPC payload

```
<nsm-snmp-restart xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-services-manager"/>
```

### Command Syntax

```
snmp restart nsm
```

---

## IPI-BRIDGE

### Configure enable

Use this attribute to enable global bridge vlan check

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```
<global-bridge-vlan-check xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
  <global>
    <config>
      </enable><!-- operation="delete"-->
    </config>
  </global>
</global-bridge-vlan-check>
```

### Command Syntax

```
global-bridge-vlan-check enable
```

---

## Configure protocol

Bridge protocol type

Attribute Name: protocol

Attribute Type: enum (ieee|ieee vlan-bridge|rstp|rstp vlan-bridge|mstp|provider-rstp|provider-mstp|rpvst+|rstp ring|mstp ring|provider-rstp edge|provider-mstp edge|rstp vlan-bridge ring|evb|svlan-evb)

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
```

```

    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <config>
        <protocol>ieee</protocol>
    </config>
</bridge>
</network-instance>
</network-instances>

```

## Command Syntax

```

bridge <1-32> protocol (ieee|ieee vlan-bridge|rstp|rstp vlan-
    bridge|mstp|rpvst+|rstp ring|mstp ring|rstp vlan-bridge ring|evb|svlan-evb)

```

---

## Configure instance name

Bridge protocol type

Attribute Name: protocol

Attribute Type: enum (ieee|ieee vlan-bridge|rstp|rstp vlan-bridge|mstp|provider-rstp|provider-mstp|rpvst+|rstp ring|mstp ring|provider-rstp edge|provider-mstp edge|rstp vlan-bridge ring|evb|svlan-evb)

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
    <network-instance>
        <instance-name>1</instance-name>
        <config>
            <instance-name>WORD</instance-name>
            <instance-type>l2ni</instance-type>
        </config>
        <instance-type>l2ni</instance-type>
        <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
        <config>
            <protocol>ieee</protocol>
        </config>
    </bridge>
</network-instance>
</network-instances>

```

## Command Syntax

```

bridge <1-32> protocol (ieee|ieee vlan-bridge|rstp|rstp vlan-bridge|mstp|provider-
    rstp|provider-mstp|rpvst+|rstp ring|mstp ring|provider-rstp edge|provider-mstp
    edge|rstp vlan-bridge ring|evb|svlan-evb)

```

---

## Configure disable dynamic learning

Network Instance Name. For VRF and MAC VRF, instance name can be up to 32 chars long. For VPWS and VPLS instances, instance name can be up to 128 chars long. For L2NI (bridge) instance, instance name has to be a number between (1-32). For Cross-Connect, instance name can be up to 30 chars long. For Bridge-domain, instance, instance name has to be a number between (1-2147483647).

Attribute Name: instance-name

Attribute Type: string

Attribute Name: disable-dynamic-learning

Attribute Type: empty

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-type>vrf</instance-type>
    <config>
      <instance-type>vrf</instance-type>
      <instance-name>WORD</instance-name>
    </config>
    <instance-name>WORD</instance-name>
  <bridge>
  <config>
    </disable-dynamic-learning>
  </config>
</bridge>
</network-instance>
</network-instances>
```

### Command Syntax

```
no bridge <1-32> acquire
```

---

## Configure I2 protocol destination mac

This attribute changes L2 protocol destination MAC

Attribute Name: l2-protocol-destination-mac

Attribute Type: string

Default Value: 0100.C2CD.CDD0

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <config>
      <l2-protocol-destination-mac>XXXX.XXXX.XXXX</l2-protocol-destination-mac>
<!-- operation="delete"-->
    </config>
  </bridge>
</network-instance>
```

```
</network-instances>
```

## Command Syntax

```
bridge <1-32> l2protocol encapsulation dest-mac XXXX.XXXX.XXXX
```

---

## Configure spanning tree protocol status

Attribute specifies to enable/disable Spanning Tree Protocol on a interface

Attribute Name: spanning-tree-protocol-status

Attribute Type: enum (enable|disable)

## Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <bridge-ports>
        <interface>
          <name>WORD</name>
          <config>
            <name>WORD</name>
          </config>
          <spanning-tree-protocol-status>enable</spanning-tree-protocol-status>
        </interface>
      </bridge-ports>
    </bridge>
  </network-instance>
</network-instances>
```

## Command Syntax

```
bridge-group <1-32> (spanning-tree (enable|disable) |)
```

---

## Configure disable mac learning

Use this attribute to disable MAC learning on a interface

Attribute Name: disable-mac-learning

Attribute Type: uint8

## Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
```

```

<instance-name>1</instance-name>
<config>
  <instance-name>WORD</instance-name>
  <instance-type>vrf</instance-type>
</config>
  <instance-type>l2ni</instance-type>
<bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
<fdb>
<interfaces>
<interface>
  <interface-name>IFNAME</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
    </disable-mac-learning><!-- operation="delete"-->
  </interface>
</interfaces>
</fdb>
</bridge>
</network-instance>
</network-instances>

```

## Command Syntax

```
no mac-address-table learning bridge <1-32> interface IFNAME
```

---

## Configure interface name

The textual name of the interface

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

Attribute Name: action

Attribute Type: enum (discard|forward)

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
      <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <fdb>
    <static-mac-table>
    <entry>

```

```

    <mac-address>XXXX.XXXX.XXXX</mac-address>
  <config>
    <mac-address>XXXX.XXXX.XXXX</mac-address>
    <action>discard</action>
  </config>
  <interface-name>IFNAME</interface-name>
</entry>
</static-mac-table>
</fdb>
</bridge>
</network-instance>
</network-instances>

```

### Command Syntax

```
bridge <1-32> address XXXX.XXXX.XXXX (discard|forward) IFNAME
```

---

### clear mac address-table (multicast) cvlan VID svlan VID bridge <1-32>

Attribute Name: mac-type

Attribute Type: enum (multicast)

Attribute Name: cvlan-id

Attribute Type: uint16

Attribute Name: svlan-id

Attribute Type: uint16

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```

<bridge-clear-provider-edge-mac-address-table xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-bridge">
  <mac-type>multicast</mac-type>
  <cvlan-id>VID</cvlan-id>
  <svlan-id>VID</svlan-id>
  <bridge-id>1</bridge-id>
</bridge-clear-provider-edge-mac-address-table>

```

### Command Syntax

```
clear mac address-table (multicast) cvlan VID svlan VID bridge <1-32>
```

---

### clear mac address-table (multicast) (interface IFNAME|) (address MACADDR|) (vlan VID|) bridge <1-32>

Attribute Name: mac-type

Attribute Type: enum (multicast)

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

Attribute Name: mac-address

Attribute Type: string

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```
<bridge-clear-mac-address-table xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
  <mac-type>multicast</mac-type>
  <interface-name>IFNAME</interface-name>
  <mac-address>MACADDR</mac-address>
  <vlan-id>VID</vlan-id>
  <bridge-id>1</bridge-id>
</bridge-clear-mac-address-table>
```

### Command Syntax

```
clear mac address-table (multicast) (interface IFNAME|) (address MACADDR|) (vlan
  VID|) bridge <1-32>
```

---

## clear mac address-table dynamic cvlan VID svlan VID bridge <1-32>

Attribute Name: cvlan-id

Attribute Type: uint16

Attribute Name: svlan-id

Attribute Type: uint16

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```
<bridge-clear-provider-edge-dynamic-mac-address-table xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-bridge">
  <cvlan-id>VID</cvlan-id>
  <svlan-id>VID</svlan-id>
  <bridge-id>1</bridge-id>
</bridge-clear-provider-edge-dynamic-mac-address-table>
```

### Command Syntax

```
clear mac address-table dynamic cvlan VID svlan VID bridge <1-32>
```

---

## clear mac address-table dynamic (interface IFNAME|) (address MACADDR|) (vlan VID|) bridge <1-32>

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

Attribute Name: mac-address

Attribute Type: string

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```
<bridge-clear-dynamic-mac-address-table xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
  <interface-name>IFNAME</interface-name>
  <mac-address>MACADDR</mac-address>
  <vlan-id>VID</vlan-id>
  <bridge-id>1</bridge-id>
</bridge-clear-dynamic-mac-address-table>
```

### Command Syntax

```
clear mac address-table dynamic (interface IFNAME|) (address MACADDR|) (vlan VID|)
bridge <1-32>
```

---

## clear allowed-ethertype statistics (IFNAME|)

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

### Netconf RPC payload

```
<bridge-clear-allowed-ethertype-stats xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
  <interface-name>IFNAME</interface-name>
</bridge-clear-allowed-ethertype-stats>
```

### Command Syntax

```
clear allowed-ethertype statistics (IFNAME|)
```

---

## clear mac address-table dynamic interface IFNAME instance INST bridge <1-32>

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

Attribute Name: instance-id

Attribute Type: uint32

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```

<bridge-clear-mstp-port-dynamic-mac-address-table xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-bridge">
  <interface-name>IFNAME</interface-name>
  <instance-id>INST</instance-id>
  <bridge-id>1</bridge-id>
</bridge-clear-mstp-port-dynamic-mac-address-table>

```

### Command Syntax

```
clear mac address-table dynamic interface IFNAME instance INST bridge <1-32>
```

---

## IPI-VLAN

---

### Configure disable mac learning

Use attribute to disable mac address learning

Attribute Name: disable-mac-learning

Attribute Type: uint8

### Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <vlans xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan">
        <vlan>
          <vlan-id>VLAN_RANGE</vlan-id>
          <config>
            <vlan-id>VLAN_RANGE</vlan-id>
          </config>
          </disable-mac-learning><!-- operation="delete"-->
        </vlan>
      </vlans>
    </bridge>
  </network-instance>
</network-instances>

```

```

</bridge>
</network-instance>
</network-instances>

```

## Command Syntax

```
no mac-address-table learning bridge <1-32> vlan VLAN_RANGE
```

---

## Configure vlan id

Vlan identifier

Attribute Name: vlan-id

Attribute Type: string

Attribute Range: 2-4094

Attribute Name: type

Attribute Type: enum (customer)

Attribute Name: name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: state

Attribute Type: enum (disable|enable)

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <vlans xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan">
        <vlan <!-- operation="delete"-->
          <vlan-id>VLAN_RANGE</vlan-id>
          <config>
            <vlan-id>VLAN_RANGE</vlan-id>
          </config>
          <customer-vlan>
            <config>
              <type>customer</type>
              <name>WORD</name>
              <state>disable</state>
            </config>
          </customer-vlan>
        </vlan>
      </vlans>
    </bridge>
  </network-instance>
</network-instances>

```

```

    </vlans>
  </bridge>
</network-instance>
</network-instances>

```

## Command Syntax

```

vlan VLAN_RANGE (type (customer)|) bridge <1-32> (name WORD|) (state
(disable|enable)|)

```

---

## Configure type

Vlan identifier

Attribute Name: vlan-id

Attribute Type: string

Attribute Range: 2-4094

Attribute Name: type

Attribute Type: enum (point-point|multipoint-multipoint|rooted-multipoint)

Attribute Name: state

Attribute Type: enum (disable|enable)

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
  <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <vlans xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan">
      <vlan <!-- operation="delete"-->
        <vlan-id>VLAN_RANGE</vlan-id>
        <config>
          <vlan-id>VLAN_RANGE</vlan-id>
        </config>
        <service-vlan>
          <config>
            <type>point-point</type>
            <state>disable</state>
          </config>
        </service-vlan>
      </vlan>
    </vlans>
  </bridge>
</network-instance>

```

```
</network-instances>
```

## Command Syntax

```
vlan VLAN_RANGE type service (point-point|multipoint-multipoint|rooted-multipoint)
  bridge <1-32> (state (disable|enable)|)
```

---

## Configure instance name

Vlan identifier

Attribute Name: vlan-id

Attribute Type: string

Attribute Range: 2-4094

Attribute Name: type

Attribute Type: enum (point-point|multipoint-multipoint|rooted-multipoint)

Attribute Name: name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: state

Attribute Type: enum (disable|enable)

## Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <vlans xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan">
        <vlan> <!-- operation="delete"-->
          <vlan-id>VLAN_RANGE</vlan-id>
          <config>
            <vlan-id>VLAN_RANGE</vlan-id>
          </config>
          <service-vlan>
            <config>
              <type>point-point</type>
              <name>WORD</name>
              <state>disable</state>
            </config>
          </service-vlan>
        </vlan>
      </vlans>
    </bridge>
  </network-instance>
</network-instances>
```

```

    </bridge>
  </network-instance>
</network-instances>

```

## Command Syntax

```

vlan VLAN_RANGE type service (point-point|multipoint-multipoint|rooted-multipoint)
  bridge <1-32> name WORD (state (disable|enable)|)

```

---

## Configure instance type

private vlan type

Attribute Name: type

Attribute Type: enum (community|isolated|primary)

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <vlans xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan">
        <vlan>
          <vlan-id>VLAN_RANGE</vlan-id>
          <config>
            <vlan-id>VLAN_RANGE</vlan-id>
          </config>
          <private-vlan>
            <config>
              <type>community</type>
            </config>
          </private-vlan>
        </vlan>
      </vlans>
    </bridge>
  </network-instance>
</network-instances>

```

## Command Syntax

```

private-vlan <2-4094> (community|isolated|primary) bridge <1-32>

```

---

## Configure secondary vlan

Use this attribute to configure associated secondary vlan for private vlan

Attribute Name: secondary-vlan

Attribute Type: string

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <vlans xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan">
        <vlan>
          <vlan-id>VLAN_RANGE</vlan-id>
          <config>
            <vlan-id>VLAN_RANGE</vlan-id>
          </config>
          <private-vlan>
            <association>
              <config>
                <secondary-vlan>VLAN_ID</secondary-vlan> <!-- operation="delete"-->
              </config>
            </association>
          </private-vlan>
        </vlan>
      </vlans>
    </bridge>
  </network-instance>
</network-instances>
```

### Command Syntax

```
private-vlan <2-4094> association add VLAN_ID bridge <1-32>
```

---

## Configure mac address

Use this attribute to configure classifier for given MAC address

This command is supported when following feature are enabled VLAN Classifier feature

Attribute Name: mac-address

Attribute Type: string

### Netconf edit-config payload

```
<vlan-classifier xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan">
  <classifier-rules>
    <classifier-rule>
      <rule-id>1</rule-id>
      <config>
        <rule-id>1</rule-id>
```

```

    </config>
  <rule-criteria>
    <config>
      <mac-address>WORD</mac-address> <!-- operation="delete"-->
    </config>
  </rule-criteria>
</classifier-rule>
</classifier-rules>
</vlan-classifier>

```

### Command Syntax

```
vlan classifier rule <1-256> mac WORD
```

---

## Configure ipv4 address

Use this attribute to configure classifier for given IPv4 address

This command is supported when following feature are enabled VLAN Classifier feature

Attribute Name: ipv4-address

Attribute Type: string

### Netconf edit-config payload

```

<vlan-classifier xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan">
  <classifier-rules>
    <classifier-rule>
      <rule-id>1</rule-id>
      <config>
        <rule-id>1</rule-id>
      </config>
    <rule-criteria>
      <config>
        <ipv4-address>A.B.C.D/M</ipv4-address> <!-- operation="delete"-->
      </config>
    </rule-criteria>
  </classifier-rule>
</classifier-rules>
</vlan-classifier>

```

### Command Syntax

```
vlan classifier rule <1-256> ipv4 A.B.C.D/M
```

---

## Configure ether type

Use this attribute to configure classifier for protocols based on Ethertype value

This command is supported when following feature are enabled VLAN Classifier feature

Attribute Name: ether-type

Attribute Type: union

## Netconf edit-config payload

```
<vlan-classifier xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan">
<classifier-rules>
<classifier-rule>
  <rule-id>1</rule-id>
  <config>
    <rule-id>1</rule-id>
  </config>
</rule-criteria>
<config>
  <ether-type>VLAN_CLASSIFIER_ETHERTYPE_T</ether-type>
</config>
</rule-criteria>
</classifier-rule>
</classifier-rules>
</vlan-classifier>
```

## Command Syntax

```
vlan classifier rule <1-256> proto
  (ETHERTYPE|ip|x25|arp|g8bpqx25|ieeeppup|ieeeaddrtrans|dec|decnadamload|decnare
  moteconsole|decnارouting|declat|decdiagnostics|rarp|atalkddp|atalkaarp|ipx|ipv6
  |atmmulti|pppdiscovery|pppsession|atmtransport)
```

---

## Configure group id

Classifier group ID

Attribute Name: group-id

Attribute Type: uint8

Attribute Range: 1-16

## Netconf edit-config payload

```
<vlan-classifier xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan">
<classifier-groups>
<classifier-group> <!-- operation="delete"-->
  <rule-id>1</rule-id>
  <config>
    <rule-id>1</rule-id>
    <group-id>1</group-id>
  </config>
  <group-id>1</group-id>
</classifier-group>
</classifier-groups>
</vlan-classifier>
```

## Command Syntax

```
vlan classifier group <1-16> add rule <1-256>
```

---

## Configure port name

VLAN classifier group ID

Attribute Name: group-id

Attribute Type: uint8

Attribute Range: 1-16

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 2-4094

### Netconf edit-config payload

```
<vlan-classifier xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan">
  <ports>
    <port> <!-- operation="delete"-->
      <group-id>1</group-id>
      <config>
        <group-id>1</group-id>
        <port-name>WORD</port-name>
        <vlan-id>2</vlan-id>
      </config>
      <port-name>WORD</port-name>
    </port>
  </ports>
</vlan-classifier>
```

### Command Syntax

```
vlan classifier activate <1-16> vlan <2-4094>
```

---

## Configure vlan-reservation vlan-id

Use attribute to reserve vlan

This command is supported when following feature are enabled Flexport Feature and following feature are disabled dune feature

Attribute Name: vlan-id

Attribute Type: string

Attribute Range: 2-4094

### Netconf edit-config payload

```
<vlan-reservation xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan">
  <config>
    <vlan-id>VLAN_RANGE</vlan-id> <!-- operation="delete"-->
  </config>
</vlan-reservation>
```

### Command Syntax

```
vlan-reservation VLAN_RANGE
```

---

## Configure disable vlan classifier feature

Use this command to enable or disable VLAN classifier feature.

Attribute Name: disable-vlan-classifier-feature

Attribute Type: uint8

### Netconf edit-config payload

```
<layer2-global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan">
  <config>
    </disable-vlan-classifier-feature><!-- operation="delete"-->
  </config>
</layer2-global>
```

### Command Syntax

```
no feature vlan classifier
```

---

## Configure disable port security

Use this attribute to disable or enable port-security globally.

Attribute Name: disable-port-security

Attribute Type: uint8

### Netconf edit-config payload

```
<layer2-global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan">
  <config>
    </disable-port-security>
  </config>
</layer2-global>
```

### Command Syntax

```
port-security disable
```

---

## Configure vlan xlate 1

Use this attribute to set vlan xlate

Attribute Name: vlan-xlate-1

Attribute Type: empty

### Netconf edit-config payload

```
<layer2-global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan">
  <config>
    </vlan-xlate-1><!-- operation="delete"-->
  </config>
</layer2-global>
```

### Command Syntax

```
vlan-xlate-1 large
```

---

## Configure table name

Use this to configure the name of the CVLAN registration table.

Attribute Name: table-name

Attribute Type: string

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>WORD</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
  <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <cvlan-registration-tables xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
vlan">
      <cvlan-registration-table> <!-- operation="delete"-->
        <table-name>WORD</table-name>
        <config>
          <table-name>WORD</table-name>
        </config>
      </cvlan-registration-table>
    </cvlan-registration-tables>
  </bridge>
</network-instance>
</network-instances>
```

### Command Syntax

```
cvlan registration table WORD bridge <1-32>
```

---

## Configure cvlan cfi

Canonical Format Indicator in the DEI field of the CTAG

This command is supported when following feature are enabled VLAN feature, Provider Bridging feature

Attribute Name: cvlan-cfi

Attribute Type: uint8

Attribute Range: 0-1

Attribute Name: translated-cvlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: svlan-cos

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: svlan-cfi

Attribute Type: uint8

Attribute Range: 0-1

Attribute Name: cvlan-cos

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>WORD</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <cvlan-registration-tables xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
vlan">
        <cvlan-registration-table>
          <table-name>WORD</table-name>
          <config>
            <table-name>WORD</table-name>
          </config>
          <cvlan-mappings>
            <cvlan-mapping>
              <cvlan-id>VLAN_RANGE2</cvlan-id>
              <config>
                <cvlan-id>VLAN_RANGE2</cvlan-id>
                <svlan-id>1</svlan-id>
                <translated-cvlan-id>1</translated-cvlan-id>
                <svlan-cos>0</svlan-cos>
                <svlan-cfi>0</svlan-cfi>
                <cvlan-cos>0</cvlan-cos>
              </config>
              <svlan-id>1</svlan-id>
              <cvlan-cfi>0</cvlan-cfi>
            </cvlan-mapping>
          </cvlan-mappings>
        </cvlan-registration-table>
      </cvlan-registration-tables>
    </bridge>
  </network-instance>
</network-instances>

```

## Command Syntax

```
cvlan VLAN_RANGE2 cvlan <1-4094> svlan <1-4094> ({ scos <0-7>| scfi <0-1>| ccos <0-7>| ccfi <0-1> }|)
```

---

## Configure untagged ep

Customer/provider edge port is untagged for specified CVLAN

This command is supported when following feature are enabled VLAN feature, Provider Bridging feature

Attribute Name: untagged-ep

Attribute Type: bits (default|untagged-pep|untagged-cep)

Attribute Name: svlan-cos

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: svlan-cfi

Attribute Type: uint8

Attribute Range: 0-1

Attribute Name: cvlan-cos

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: cvlan-cfi

Attribute Type: uint8

Attribute Range: 0-1

## Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>WORD</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
  <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <cvlan-registration-tables xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
vlan">
      <cvlan-registration-table>
        <table-name>WORD</table-name>
        <config>
          <table-name>WORD</table-name>
        </config>
        <cvlan-mappings>
          <cvlan-mapping>
            <cvlan-id>VLAN_RANGE2</cvlan-id>
```

```

    <config>
      <cvlan-id>VLAN_RANGE2</cvlan-id>
      <svlan-id>1</svlan-id>
      <svlan-cos>0</svlan-cos>
      <svlan-cfi>0</svlan-cfi>
      <cvlan-cos>0</cvlan-cos>
      <cvlan-cfi>0</cvlan-cfi>
    </config>
    <svlan-id>1</svlan-id>
    <untagged-ep>untagged-pep</untagged-ep>
  </cvlan-mapping>
</cvlan-mappings>
</cvlan-registration-table>
</cvlan-registration-tables>
</bridge>
</network-instance>
</network-instances>

```

### Command Syntax

```

cvlan VLAN_RANGE2 svlan <1-4094> ({ scos <0-7>| scfi <0-1>| ccos <0-7>| ccfi <0-1>|
  untagged-pep|untagged-cep })

```

---

## IPI-PORT-VLAN

---

### Configure isolated vlan id

Isolated VLAN identifier

Attribute Name: isolated-vlan-id

Attribute Type: string

Attribute Range: 2-4094,2-4094

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
      <global>
        <config>
          <isolated-vlan-id>2</isolated-vlan-id> <!-- operation="delete"-->
        </config>
      </global>
    </port-vlan>
  </interface>
</interfaces>

```

## Command Syntax

```
switchport (provider-network) isolated-vlan WORD
```

---

## Configure cvlan registration table

cvlan registration table

Attribute Name: cvlan-registration-table

Attribute Type: string

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
      <global>
        <config>
          <cvlan-registration-table>WORD</cvlan-registration-table> <!--
operation="delete"-->
        </config>
      </global>
    </port-vlan>
  </interface>
</interfaces>

```

## Command Syntax

```
switchport (customer-edge) vlan registration WORD
```

---

## Configure interface mode

Set the interface to access or trunk or hybrid mode for VLANs

Attribute Name: interface-mode

Attribute Type: enum (access|hybrid|trunk|customer-network|provider-network|sbp|uap|customer-edge access|customer-edge hybrid|customer-edge trunk)

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
      <switched-vlans>
        <switched-vlan> <!-- operation="delete"-->
          <interface-mode>access</interface-mode>
        </switched-vlan>
      </switched-vlans>
    </port-vlan>
  </interface>
</interfaces>

```

```

    <config>
      <interface-mode>access</interface-mode>
    </config>
  </switched-vlan>
</switched-vlans>
</port-vlan>
</interface>
</interfaces>

```

### Command Syntax

```

switchport mode (access|hybrid|trunk|provider-network|customer-edge
access|customer-edge hybrid|customer-edge trunk)

```

---

## Configure name

Set the interface to access or trunk or hybrid mode for VLANs

Attribute Name: interface-mode

Attribute Type: enum (access|hybrid|trunk|customer-network|provider-network|sbp|uap|customer-edge access|customer-edge hybrid|customer-edge trunk)

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
      <switched-vlans>
        <switched-vlan> <!-- operation="delete"-->
          <interface-mode>access</interface-mode>
          <config>
            <interface-mode>access</interface-mode>
          </config>
        </switched-vlan>
      </switched-vlans>
    </port-vlan>
  </interface>
</interfaces>

```

### Command Syntax

```

switchport mode (customer-network)

```

---

## Configure acceptable frame type

Use this attribute to set the interface acceptable frame types. This processing occurs after VLAN classification

Attribute Name: acceptable-frame-type

Attribute Type: enum (vlan-tagged|all)

**Netconf edit-config payload**

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
  <switched-vlans>
  <switched-vlan>
    <interface-mode>access</interface-mode>
    <config>
      <interface-mode>access</interface-mode>
    </config>
    <acceptable-frame-type>all</acceptable-frame-type> <!--
operation="delete"-->
  </switched-vlan>
</switched-vlans>
</port-vlan>
</interface>
</interfaces>

```

**Command Syntax**

```
switchport mode (hybrid) acceptable-frame-type (vlan-tagged|all)
```

**Configure switched-vlan acceptable-frame-type**

Use this attribute to set the interface acceptable frame types. This processing occurs after VLAN classification

Attribute Name: acceptable-frame-type

Attribute Type: enum (vlan-tagged|all)

**Netconf edit-config payload**

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
  <switched-vlans>
  <switched-vlan>
    <interface-mode>access</interface-mode>
    <config>
      <interface-mode>access</interface-mode>
    </config>
    <acceptable-frame-type>all</acceptable-frame-type> <!--
operation="delete"-->
  </switched-vlan>
</switched-vlans>

```

```

</port-vlan>
</interface>
</interfaces>

```

## Command Syntax

```
switchport mode (customer-edge hybrid) acceptable-frame-type (vlan-tagged|all)
```

---

## Configure disable native vlan

Use this attribute to disable native VLAN for the port. Untagged frames will be dropped.

Attribute Name: disable-native-vlan

Attribute Type: uint8

## Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
  <switched-vlans>
  <switched-vlan>
    <interface-mode>access</interface-mode>
    <config>
      <interface-mode>access</interface-mode>
    </config>
    </disable-native-vlan><!-- operation="delete"-->
  </switched-vlan>
  </switched-vlans>
</port-vlan>
</interface>
</interfaces>

```

## Command Syntax

```
switchport mode (trunk) disable-native-vlan
```

---

## Configure remove default vlan

Use this attribute to remove default VLAN for the port. Untagged frames will be dropped.

Attribute Name: remove-default-vlan

Attribute Type: uint8

## Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>

```

```

    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
    <switched-vlans>
      <switched-vlan>
        <interface-mode>access</interface-mode>
        <config>
          <interface-mode>access</interface-mode>
        </config>
        </remove-default-vlan><!-- operation="delete"-->
      </switched-vlan>
    </switched-vlans>
  </port-vlan>
</interface>
</interfaces>

```

## Command Syntax

```
switchport mode (trunk) remove-default-vlan
```

---

## Configure ingress filter

Use this attribute to set the switching characteristics of the interface as hybrid, and classify both tagged and untagged frames. Received frames are classified based on the VLAN characteristics, then accepted or discarded based on the specified filtering criteria.

Attribute Name: ingress-filter

Attribute Type: enum (disable|enable)

## Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
      <switched-vlans>
        <switched-vlan>
          <interface-mode>access</interface-mode>
          <config>
            <interface-mode>access</interface-mode>
          </config>
          <ingress-filter>disable</ingress-filter> <!-- operation="delete"-->
        </switched-vlan>
      </switched-vlans>
    </port-vlan>
  </interface>
</interfaces>

```

## Command Syntax

```
switchport mode (access|hybrid|trunk|customer-network|provider-
network|sbp|uap|customer-edge access|customer-edge hybrid|customer-edge trunk)
ingress-filter (disable|enable)
```

---

## Configure vlan id

Default VLAN identifier

Attribute Name: vlan-id

Attribute Type: uint16

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
  <switched-vlans>
  <switched-vlan>
    <interface-mode>access</interface-mode>
    <config>
      <interface-mode>access</interface-mode>
    </config>
    <vlans>
    <config>
      <vlan-id>2</vlan-id> <!-- operation="delete"-->
    </config>
    </vlans>
  </switched-vlan>
  </switched-vlans>
  </port-vlan>
</interface>
</interfaces>
```

## Command Syntax

```
switchport (access|hybrid) vlan <2-4094>
```

---

## Configure vlans vlan-id

Default VLAN identifier

Attribute Name: vlan-id

Attribute Type: uint16

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
```

```

<name>IFNAME</name>
<config>
  <name>IFNAME</name>
</config>
<port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
<switched-vlans>
<switched-vlan>
  <interface-mode>access</interface-mode>
  <config>
    <interface-mode>access</interface-mode>
  </config>
  <vlans>
  <config>
    <vlan-id>2</vlan-id> <!-- operation="delete"-->
  </config>
</vlans>
</switched-vlan>
</switched-vlans>
</port-vlan>
</interface>
</interfaces>

```

## Command Syntax

```
switchport (customer-network) vlan <2-4094>
```

---

## Configure vlans vlan-id

Default VLAN identifier

Attribute Name: vlan-id

Attribute Type: uint16

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
<switched-vlans>
<switched-vlan>
  <interface-mode>access</interface-mode>
  <config>
    <interface-mode>access</interface-mode>
  </config>
  <vlans>
  <config>
    <vlan-id>2</vlan-id> <!-- operation="delete"-->
  </config>

```

```

    </vlans>
  </switched-vlan>
</switched-vlans>
</port-vlan>
</interface>
</interfaces>

```

### Command Syntax

```
switchport (customer-edge access) vlan <2-4094>
```

---

## Configure vlans vlan-id

Default VLAN identifier

Attribute Name: vlan-id

Attribute Type: uint16

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
      <switched-vlans>
        <switched-vlan>
          <interface-mode>access</interface-mode>
          <config>
            <interface-mode>access</interface-mode>
          </config>
          <vlans>
            <config>
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
            </config>
          </vlans>
        </switched-vlan>
      </switched-vlans>
    </port-vlan>
  </interface>
</interfaces>

```

### Command Syntax

```
switchport (customer-edge hybrid) vlan <1-4094>
```

---

## Configure native vlan id

Native VLAN ID

Attribute Name: native-vlan-id

Attribute Type: uint16

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
  <switched-vlans>
  <switched-vlan>
    <interface-mode>access</interface-mode>
    <config>
      <interface-mode>access</interface-mode>
    </config>
    <vlans>
    <config>
      <native-vlan-id>2</native-vlan-id> <!-- operation="delete"-->
    </config>
    </vlans>
  </switched-vlan>
  </switched-vlans>
  </port-vlan>
</interface>
</interfaces>
```

### Command Syntax

```
switchport (trunk) native vlan <2-4094>
```

---

## Configure translated svlan id

Specifies translated service VLAN identifier

Attribute Name: translated-svlan-id

Attribute Type: uint16

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
  <switched-vlans>
  <switched-vlan>
    <interface-mode>access</interface-mode>
    <config>
      <interface-mode>access</interface-mode>
    </config>
  </switched-vlan>
  </switched-vlans>
  </port-vlan>
</interface>
</interfaces>
```

```

</config>
<svlan-translations>
<svlan-translation>
  <original-svlan-id>VLAN_ID</original-svlan-id>
  <config>
    <original-svlan-id>VLAN_ID</original-svlan-id>
  </config>
  <translated-svlan-id>VLAN_ID</translated-svlan-id> <!--
operation="delete"-->
</svlan-translation>
</svlan-translations>
</switched-vlan>
</switched-vlans>
</port-vlan>
</interface>
</interfaces>

```

## Command Syntax

```
switchport (customer-network) vlan translation svlan VLAN_ID svlan VLAN_ID
```

---

## Configure original svlan id

Specifies translated service VLAN identifier

Attribute Name: translated-svlan-id

Attribute Type: uint16

Attribute Name: translated-cvlan-id

Attribute Type: uint16

Attribute Range: 1-4094

## Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
<switched-vlans>
<switched-vlan>
  <interface-mode>access</interface-mode>
  <config>
    <interface-mode>access</interface-mode>
  </config>
  <svlan-translations>
  <svlan-translation>
    <original-svlan-id>VLAN_ID</original-svlan-id>
    <config>
      <original-svlan-id>VLAN_ID</original-svlan-id>

```

```

    <translated-cvlan-id>1</translated-cvlan-id> <!-- operation="delete"-->
>
    </config>
    <translated-svlan-id>VLAN_ID</translated-svlan-id> <!--
operation="delete"-->
    </svlan-translation>
  </svlan-translations>
</switched-vlan>
</switched-vlans>
</port-vlan>
</interface>
</interfaces>

```

## Command Syntax

```

switchport (customer-network) vlan translation svlan VLAN_ID cvlan <1-4094> svlan
VLAN_ID

```

---

## Configure cvlan id

Specifies translated service VLAN identifier

Attribute Name: translated-svlan-id

Attribute Type: uint16

Attribute Range: 1-4094

## Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
  <switched-vlans>
  <switched-vlan>
    <interface-mode>access</interface-mode>
    <config>
      <interface-mode>access</interface-mode>
    </config>
    <cvlan-svlan-translations>
    <cvlan-svlan-translation>
      <svlan-id>1</svlan-id>
      <config>
        <svlan-id>1</svlan-id>
        <cvlan-id>1</cvlan-id>
      </config>
      <cvlan-id>1</cvlan-id>
      <translated-svlan-id>1</translated-svlan-id>
    </cvlan-svlan-translation>
  </cvlan-svlan-translations>

```

```

</switched-vlan>
</switched-vlans>
</port-vlan>
</interface>
</interfaces>

```

## Command Syntax

```

switchport (customer-network) vlan translation cvlan <1-4094> svlan <1-4094> svlan
<1-4094>

```

---

## Configure svlan id

Specifies translated service VLAN identifier

Attribute Name: translated-svlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: translated-cvlan-id

Attribute Type: uint16

Attribute Range: 1-4094

## Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
      <switched-vlans>
        <switched-vlan>
          <interface-mode>access</interface-mode>
          <config>
            <interface-mode>access</interface-mode>
          </config>
          <cvlan-svlan-translations>
            <cvlan-svlan-translation>
              <svlan-id>1</svlan-id>
              <config>
                <svlan-id>1</svlan-id>
                <cvlan-id>1</cvlan-id>
                <translated-cvlan-id>1</translated-cvlan-id> <!-- operation="delete"-->
              </config>
            </cvlan-svlan-translation>
          </cvlan-svlan-translations>
        </switched-vlan>
      </switched-vlans>
    </port-vlan>
  </interface>
</interfaces>

```

```

</switched-vlan>
</switched-vlans>
</port-vlan>
</interface>
</interfaces>

```

### Command Syntax

```

switchport (customer-network) vlan translation cvlan <1-4094> svlan <1-4094> cvlan
<1-4094> svlan <1-4094>

```

---

## Configure logging

port security logging

Attribute Name: logging

Attribute Type: uint8

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
  <port-security>
  <config>
    </logging><!-- operation="delete"-->
  </config>
</port-security>
</port-vlan>
</interface>
</interfaces>

```

### Command Syntax

```

switchport port-security logging enable

```

---

## Configure mode

port security mode type

Attribute Name: mode

Attribute Type: enum (static|default)

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>

```

```
</config>
<port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
  <port-security>
    <config>
      <mode>2</mode>
    </config>
  </port-security>
</port-vlan>
</interface>
</interfaces>
```

## Command Syntax

```
switchport port-security
```

---

## Configure port-security mode

port security mode type

Attribute Name: mode

Attribute Type: enum (static|default)

## Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
      <port-security>
        <config>
          <mode>static</mode>
        </config>
      </port-security>
    </port-vlan>
  </interface>
</interfaces>
```

## Command Syntax

```
switchport port-security (static)
```

---

## Configure maximum limit

Maximum limit for port security

Attribute Name: maximum-limit

Attribute Type: uint16

Default Value: 1

Attribute Range: 1-1000

## Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
  <port-security>
  <config>
    <maximum-limit>1</maximum-limit> <!-- operation="delete"-->
  </config>
</port-security>
</port-vlan>
</interface>
</interfaces>
```

## Command Syntax

```
switchport port-security maximum <1-1000>
```

## Configure mac address

Use this attribute to configure the static forwarding entry for port-security

This command is supported when following feature are enabled Provider bridging feature

Attribute Name: mac-address

Attribute Type: string

## Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
  <port-security>
  <secure-mac>
  <default-vlan-mappings>
  <default-vlan-mapping> <!-- operation="delete"-->
    <mac-address>XXXX.XXXX.XXXX</mac-address>
    <config>
      <mac-address>XXXXX.XXXX.XXXX</mac-address>
    </config>
  </default-vlan-mapping>
</default-vlan-mappings>
</secure-mac>
</port-security>
</port-vlan>
```

```
</interface>
</interfaces>
```

## Command Syntax

```
switchport port-security mac-address XXXX.XXXX.XXXX
```

---

## Configure vlan-mapping cvlan-id

Use this attribute to configure the port-security with static forwarding entry and CVLAN ID

This command is supported when following feature are enabled Provider bridging feature

Attribute Name: cvlan-id

Attribute Type: uint16

## Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
  <port-security>
  <secure-mac>
  <vlan-mappings>
  <vlan-mapping>
    <mac-address>XXXX.XXXX.XXXX</mac-address>
    <config>
      <mac-address>XXXX.XXXX.XXXX</mac-address>
    </config>
    <cvlan-id>2</cvlan-id> <!-- operation="delete"-->
  </vlan-mapping>
  </vlan-mappings>
  </secure-mac>
  </port-security>
  </port-vlan>
</interface>
</interfaces>
```

## Command Syntax

```
switchport port-security mac-address XXXX.XXXX.XXXX vlanId <2-4094>
```

---

## Configure vlan-mapping svlan-id

Use this attribute to configure the port-security with static forwarding entry and SVLAN ID

This command is supported when following feature are enabled Provider bridging feature

Attribute Name: svlan-id

Attribute Type: uint16

**Netconf edit-config payload**

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
  <port-security>
  <secure-mac>
  <vlan-mappings>
  <vlan-mapping>
    <mac-address>XXXX.XXXX.XXXX</mac-address>
    <config>
      <mac-address>XXXX.XXXX.XXXX</mac-address>
    </config>
    <svlan-id>2</svlan-id> <!-- operation="delete"-->
  </vlan-mapping>
</vlan-mappings>
</secure-mac>
</port-security>
</port-vlan>
</interface>
</interfaces>
```

**Command Syntax**

```
switchport port-security mac-address XXXX.XXXX.XXXX svlanId <2-4094>
```

**Configure cvlan-svlan-mappings svlan-id**

Use this attribute to configure the port-security with static forwarding entry and SVLAN ID

This command is supported when following feature are enabled Provider bridging feature

Attribute Name: svlan-id

Attribute Type: uint16

**Netconf edit-config payload**

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
  <name>IFNAME</name>
  <config>
    <name>IFNAME</name>
  </config>
  <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
  <port-security>
  <secure-mac>
  <cvlan-svlan-mappings>
  <cvlan-svlan-mapping> <!-- operation="delete"-->
    <svlan-id>2</svlan-id>
```

```

    <config>
      <svlan-id>2</svlan-id>
      <cvlan-id>2</cvlan-id>
      <mac-address>XXXX.XXXX.XXXX</mac-address>
    </config>
    <cvlan-id>2</cvlan-id>
    <mac-address>XXXX.XXXX.XXXX</mac-address>
  </cvlan-svlan-mapping>
</cvlan-svlan-mappings>
</secure-mac>
</port-security>
</port-vlan>
</interface>
</interfaces>

```

### Command Syntax

```
switchport port-security mac-address XXXX.XXXX.XXXX vlanId <2-4094> svlanId <2-4094>
```

---

## Configure private-vlan mode

Use this attribute to make a layer2 port as a host port or promiscuous port or pvlan-trunk port

This command is supported when following feature are enabled Private VLAN feature

Attribute Name: mode

Attribute Type: enum (host|promiscuous)

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
      <private-vlan>
        <config>
          <mode>host</mode>
        </config>
      </private-vlan>
    </port-vlan>
  </interface>
</interfaces>

```

### Command Syntax

```
switchport mode private-vlan (host|promiscuous)
```

---

## Configure associate vlan id

Private VLAN Association

Attribute Name: associate-vlan-id

Attribute Type: uint16

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
      <private-vlan>
        <associations>
          <association>
            <vlan-id>2</vlan-id>
            <config>
              <vlan-id>2</vlan-id>
            </config>
            <associate-vlan-id>2</associate-vlan-id>
          </association>
        </associations>
      </private-vlan>
    </port-vlan>
  </interface>
</interfaces>
```

### Command Syntax

```
switchport private-vlan host-association <2-4094> add <2-4094>
```

---

## Configure mapping vlan id

Primary vlan identifier

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Name: mapping-vlan-id

Attribute Type: string

Attribute Range: 2-4094

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
```

```

</config>
<port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
<private-vlan>
<associations>
<association> <!-- operation="delete"-->
    <vlan-id>2</vlan-id>
    <config>
        <vlan-id>2</vlan-id>
        <mapping-vlan-id>VLAN_ID</mapping-vlan-id>
    </config>
</association>
</associations>
</private-vlan>
</port-vlan>
</interface>
</interfaces>

```

## Command Syntax

```
switchport private-vlan mapping <2-4094> add VLAN_ID
```

---

## Configure association trunk vlan id

private-vlan Mapping

Attribute Name: association-trunk-vlan-id

Attribute Type: uint16

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
<interface>
    <name>IFNAME</name>
    <config>
        <name>IFNAME</name>
    </config>
    <port-vlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
    <private-vlan>
    <associations>
    <association>
        <vlan-id>2</vlan-id>
        <config>
            <vlan-id>2</vlan-id>
        </config>
        <association-trunk-vlan-id>2</association-trunk-vlan-id>
    </association>
    </associations>
    </private-vlan>
    </port-vlan>
    </interface>
</interfaces>

```

## Command Syntax

```
switchport private-vlan association-trunk <2-4094> <2-4094>
```

## Configure instance name

Specifies VLAN identifier for static MAC entry in case of provider-network VLAN will be considered as service VLAN

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 2-4094

Attribute Name: action

Attribute Type: enum (discard|forward)

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

## Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <vlan-static-fdb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-vlan">
        <entries>
          <entry>
            <vlan-id>2</vlan-id>
            <config>
              <vlan-id>2</vlan-id>
              <mac-address>XXXX.XXXX.XXXX</mac-address>
              <action>discard</action>
              <interface-name>IFNAME</interface-name>
            </config>
            <mac-address>XXXX.XXXX.XXXX</mac-address>
          </entry>
        </entries>
      </vlan-static-fdb>
    </bridge>
  </network-instance>
</network-instances>
```

## Command Syntax

```
bridge <1-32> address XXXX.XXXX.XXXX (discard|forward) IFNAME vlan <2-4094>
```

---

## IPI-VLAN-XC

---

### Configure xconnect name

This attribute uniquely identifies a cross connect on the device

This command is supported when following feature are enabled VLAN XC support enabled

Attribute Name: xconnect-name

Attribute Type: string

Attribute Range: 1-30

### Netconf edit-config payload

```
<cross-connects xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan-xc">
  <cross-connect> <!-- operation="delete"-->
    <xconnect-name>WORD</xconnect-name>
  </cross-connect>
</cross-connects>
```

### Command Syntax

```
cross-connect WORD
```

---

### Configure disable

Disable this cross connect

This command is supported when following feature are enabled VLAN XC support enabled

Attribute Name: disable

Attribute Type: empty

### Netconf edit-config payload

```
<cross-connects xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan-xc">
  <cross-connect>
    <xconnect-name>WORD</xconnect-name>
  </cross-connect>
  <disable><!-- operation="delete"-->
  </disable>
</cross-connects>
```

### Command Syntax

```
disable
```

---

## Configure port endpoint 1

Configure port endpoint-1

This command is supported when following feature are enabled VLAN XC support enabled

Attribute Name: port-endpoint-1

Attribute Type: string

Attribute Name: port-endpoint-2

Attribute Type: string

### Netconf edit-config payload

```
<cross-connects xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan-xc">
  <cross-connect>
    <xconnect-name>WORD</xconnect-name>
    <config>
      <xconnect-name>WORD</xconnect-name>
    </config>
  <cross-connect-port>
    <config>
      <port-endpoint-2>IFNAME</port-endpoint-2>
      <port-endpoint-1>IFNAME</port-endpoint-1>
    </config>
  </cross-connect-port>
</cross-connect>
</cross-connects>
```

### Command Syntax

```
ep1 IFNAME ep2 IFNAME
```

---

## Configure backup endpoint 1

Configure backup endpoint-1

This command is supported when following feature are enabled VLAN XC support enabled

Attribute Name: backup-endpoint-1

Attribute Type: string

### Netconf edit-config payload

```
<cross-connects xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan-xc">
  <cross-connect>
    <xconnect-name>WORD</xconnect-name>
    <config>
      <xconnect-name>WORD</xconnect-name>
    </config>
  <cross-connect-port-specific>
    <config>
      <backup-endpoint-1>IFNAME</backup-endpoint-1> <!-- operation="delete"-->
    </config>
```

```

</cross-connect-port-specific>
</cross-connect>
</cross-connects>

```

## Command Syntax

```
backup ep1 IFNAME
```

---

## Configure backup endpoint 2

Configure backup endpoint-2

This command is supported when following feature are enabled VLAN XC support enabled

Attribute Name: backup-endpoint-2

Attribute Type: string

### Netconf edit-config payload

```

<cross-connects xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan-xc">
<cross-connect>
  <xconnect-name>WORD</xconnect-name>
  <config>
    <xconnect-name>WORD</xconnect-name>
  </config>
<cross-connect-port-specific>
<config>
  <backup-endpoint-2>IFNAME</backup-endpoint-2> <!-- operation="delete"-->
</config>
</cross-connect-port-specific>
</cross-connect>
</cross-connects>

```

## Command Syntax

```
backup ep2 IFNAME
```

---

## Configure revertive

Enable revertive operation for this XC

This command is supported when following feature are enabled VLAN XC support enabled

Attribute Name: revertive

Attribute Type: empty

### Netconf edit-config payload

```

<cross-connects xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan-xc">
<cross-connect>
  <xconnect-name>WORD</xconnect-name>
  <config>
    <xconnect-name>WORD</xconnect-name>
  </config>
<cross-connect-port-specific>

```

```

<config>
  </revertive><!-- operation="delete"-->
</config>
</cross-connect-port-specific>
</cross-connect>
</cross-connects>

```

### Command Syntax

```
cross-connect switchover type revertive
```

---

## Configure link fault pass through enable

Configure link fault pass through

This command is supported when following feature are enabled VLAN XC support enabled

Attribute Name: link-fault-pass-through-enable

Attribute Type: empty

### Netconf edit-config payload

```

<cross-connects xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan-xc">
  <cross-connect>
    <xconnect-name>WORD</xconnect-name>
    <config>
      <xconnect-name>WORD</xconnect-name>
    </config>
  <cross-connect-port-specific>
    <config>
      </link-fault-pass-through-enable><!-- operation="delete"-->
    </config>
  </cross-connect-port-specific>
</cross-connect>
</cross-connects>

```

### Command Syntax

```
link-fault-pass-through enable
```

---

## Configure vlan endpoint 1

Configure vlan endpoint-1

This command is supported when following feature are enabled VLAN XC support enabled

Attribute Name: vlan-endpoint-1

Attribute Type: string

Attribute Name: vlan-endpoint-2

Attribute Type: string

### Netconf edit-config payload

```
<cross-connects xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan-xc">
```

```

<cross-connect>
  <xconnect-name>WORD</xconnect-name>
  <config>
    <xconnect-name>WORD</xconnect-name>
  </config>
<cross-connect-vlan>
<config>
  <vlan-endpoint-2>IFNAME</vlan-endpoint-2>
  <vlan-endpoint-1>IFNAME</vlan-endpoint-1>
</config>
</cross-connect-vlan>
</cross-connect>
</cross-connects>

```

### Command Syntax

```
vlan ep1 IFNAME ep2 IFNAME
```

---

## Configure outer vlan range

Use this attribute to set the outer vlan id for XC.

Attribute Name: outer-vlan-range

Attribute Type: string

### Netconf edit-config payload

```

<cross-connects xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan-xc">
<cross-connect>
  <xconnect-name>WORD</xconnect-name>
  <config>
    <xconnect-name>WORD</xconnect-name>
  </config>
<cross-connect-vlan>
<vlan-xc-entries>
<vlan-xc-entry> <!-- operation="delete"-->
  <inner-vlan-range>WORD</inner-vlan-range>
  <config>
    <inner-vlan-range>WORD</inner-vlan-range>
    <outer-vlan-range>WORD</outer-vlan-range>
  </config>
  <outer-vlan-range>WORD</outer-vlan-range>
</vlan-xc-entry>
</vlan-xc-entries>
</cross-connect-vlan>
</cross-connect>
</cross-connects>

```

### Command Syntax

```
outer-vlan WORD
```

---

## Configure inner vlan range

Use this attribute to set the inner vlan id for XC.

This command is supported when following feature are enabled VLAN XC support enabled

Attribute Name: inner-vlan-range

Attribute Type: string

### Netconf edit-config payload

```
<cross-connects xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vlan-xc">
  <cross-connect>
    <xconnect-name>WORD</xconnect-name>
    <config>
      <xconnect-name>WORD</xconnect-name>
    </config>
  <cross-connect-vlan>
  <vlan-xc-entries>
  <vlan-xc-entry>
    <inner-vlan-range>WORD</inner-vlan-range>
    <config>
      <inner-vlan-range>WORD</inner-vlan-range>
      <outer-vlan-range>WORD</outer-vlan-range>
    </config>
    <outer-vlan-range>WORD</outer-vlan-range>
  </vlan-xc-entry>
</vlan-xc-entries>
</cross-connect-vlan>
</cross-connect>
</cross-connects>
```

### Command Syntax

```
outer-vlan WORD inner-vlan WORD
```

---

## clear cross-connect counters (NAME|)

Attribute Name: xc-name

Attribute Type: string

### Netconf RPC payload

```
<clear-cross-connect-counters xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
vlan-xc">
  <xc-name>NAME</xc-name>
</clear-cross-connect-counters>
```

### Command Syntax

```
clear cross-connect counters (NAME|)
```

---

## IPI-XSTP

---

### Configure ageing time

Use this attribute to specify the aging-out time for a learned MAC address. The learned MAC address persists until this specified time. Setting value to 0 would disable ageing of the bridge.

Attribute Name: ageing-time

Attribute Type: union

Default Value: 300

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <config>
          <ageing-time>300</ageing-time> <!-- operation="delete"-->
        </config>
      </stp>
    </bridge>
  </network-instance>
</network-instances>
```

### Command Syntax

```
bridge <1-32> ageing disable
```

---

### Configure instance name

Use this attribute to specify the aging-out time for a learned MAC address. The learned MAC address persists until this specified time. Setting value to 0 would disable ageing of the bridge.

Attribute Name: ageing-time

Attribute Type: union

Default Value: 300

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
```

```

<config>
  <instance-name>WORD</instance-name>
  <instance-type>l2ni</instance-type>
</config>
  <instance-type>l2ni</instance-type>
<bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
  <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
    <config>
      <ageing-time>300</ageing-time> <!-- operation="delete"-->
    </config>
  </stp>
</bridge>
</network-instance>
</network-instances>

```

### Command Syntax

```
bridge <1-32> ageing-time (0|<10-1000000>)
```

---

## Configure enable cisco interoperability

Use this attribute to enable/disable Cisco interoperability for MSTP (Multiple Spanning Tree Protocol). If Cisco interoperability is required, all devices in the switched LAN must be Cisco-interoperability enabled. When router interoperates with Cisco, the only criteria used to classify a region are the region name and revision level. VLAN-to-instance mapping is not used to classify regions when interoperating with Cisco.

Attribute Name: enable-cisco-interoperability

Attribute Type: empty

### Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <config>
          </enable-cisco-interoperability><!-- operation="delete"-->
        </config>
      </stp>
    </bridge>
  </network-instance>
</network-instances>

```

### Command Syntax

```
bridge <1-32> cisco-interoperability enable
```

---

## Configure forwarding delay

Use this attribute to set the time (in seconds) after which (if this bridge is the root bridge) each port changes states to learning and forwarding. This value is used by all instances

Attribute Name: forwarding-delay

Attribute Type: uint8

Default Value: 15

Attribute Range: 4-30

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <config>
          <forwarding-delay>4</forwarding-delay> <!-- operation="delete"-->
        </config>
      </stp>
    </bridge>
  </network-instance>
</network-instances>
```

### Command Syntax

```
bridge <1-32> forward-time <4-30>
```

---

## Configure hello time

Use this attribute to set the hello-time, the time in seconds after which (if this bridge is the root bridge) all the bridges in a bridged LAN exchange Bridge Protocol Data Units (BPDUs). A very low value of this parameter leads to excessive traffic on the network, while a higher value delays the detection of topology change. This value is used by all instances. Configure the bridge instance name before using this attribute. The allowable range of values is 1-10 seconds. However, make sure that the value of hello time is always greater than the value of hold time (2 seconds by default)

Attribute Name: hello-time

Attribute Type: uint8

Default Value: 2

Attribute Range: 1-10

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <config>
          <hello-time>1</hello-time> <!-- operation="delete"-->
        </config>
      </stp>
    </bridge>
  </network-instance>
</network-instances>

```

## Command Syntax

```
bridge <1-32> hello-time <1-10>
```

## Configure max age

Use this attribute to set the maximum age for a bridge. This value is used by all instances. Maximum age is the maximum time in seconds for which (if a bridge is the root bridge) a message is considered valid. This prevents the frames from looping indefinitely. The value of maximum age should be greater than twice the value of hello time plus 1, but less than twice the value of forward delay minus 1. The allowable range for max-age is 6-40 seconds. Configure this value sufficiently high, so that a frame generated by root can be propagated to the leaf nodes without exceeding the maximum age.

Attribute Name: max-age

Attribute Type: uint8

Default Value: 20

Attribute Range: 6-40

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <config>

```

```

        <max-age>6</max-age> <!-- operation="delete"-->
    </config>
</stp>
</bridge>
</network-instance>
</network-instances>

```

## Command Syntax

```
bridge <1-32> max-age <6-40>
```

---

## Configure max hops

Use this attribute to specify the maximum allowed hops for a BPDU in an MST region. This parameter is used by all the instances of the MST. Specifying the maximum hops for a BPDU prevents the messages from looping indefinitely in the network. When a bridge receives an MST BPDU that has exceeded the allowed maximum hops, it discards the BPDU.

Attribute Name: max-hops

Attribute Type: uint8

Default Value: 20

Attribute Range: 1-40

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <config>
          <max-hops>l</max-hops> <!-- operation="delete"-->
        </config>
      </stp>
    </bridge>
  </network-instance>
</network-instances>

```

## Command Syntax

```
bridge <1-32> max-hops <1-40>
```

---

## Configure bridge priority

Use this attribute to set the bridge priority for the common instance. Using a lower priority indicates a greater likelihood of the bridge becoming root. The priority values can be set only in increments of 4096.

Attribute Name: bridge-priority

Attribute Type: uint32

Default Value: 32768

Attribute Range: 0-61440

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <config>
          <bridge-priority>0</bridge-priority> <!-- operation="delete"-->
        </config>
      </stp>
    </bridge>
  </network-instance>
</network-instances>
```

### Command Syntax

```
bridge <1-32> priority <0-61440>
```

---

## Configure transmit hold count

Use this attribute to set the maximum number of transmissions of BPDUs by the transmit state machine

Attribute Name: transmit-hold-count

Attribute Type: uint8

Default Value: 6

Attribute Range: 1-10

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <config>
```

```

        <transmit-hold-count>1</transmit-hold-count> <!-- operation="delete"-->
    >
        </config>
    </stp>
</bridge>
</network-instance>
</network-instances>

```

### Command Syntax

```
bridge <1-32> transmit-holdcount <1-10>
```

---

## Configure enable bpdu filter

All ports that have their BPDU filter set to default take the same value of BPDU filter as that of the bridge. The Spanning Tree Protocol sends BPDUs from all ports. Enabling the BPDU Filter feature ensures that PortFast-enabled ports do not transmit or receive any BPDUs.

Attribute Name: enable-bpdu-filter

Attribute Type: empty

### Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <global>
          <config>
            </enable-bpdu-filter><!-- operation="delete"-->
          </config>
        </global>
      </stp>
    </bridge>
  </network-instance>
</network-instances>

```

### Command Syntax

```
bridge <1-32> spanning-tree portfast bpdu-filter
```

---

## Configure enable bpdu guard

Use this attribute to set the portfast BPDU (Bridge Protocol Data Unit) guard or filter for the bridge

Attribute Name: enable-bpdu-guard

Attribute Type: empty

## Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <global>
          <config>
            </enable-bpdu-guard><!-- operation="delete"-->
          </config>
        </global>
      </stp>
    </bridge>
  </network-instance>
</network-instances>
```

## Command Syntax

```
bridge <1-32> spanning-tree portfast bpdu-guard
```

---

## Configure enable error disable timeout

Use this attribute to enable the error-disable-timeout facility, which sets a timeout for ports that are disabled due to the BPDU guard feature. The BPDU guard feature shuts down the port on receiving a BPDU on a BPDU-guard enabled port. This attribute associates a timer with the feature such that the port gets enabled back without manual intervention after a set interval.

Attribute Name: enable-error-disable-timeout

Attribute Type: empty

## Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <global>
          <config>
            </enable-error-disable-timeout><!-- operation="delete"-->
          </config>
        </global>
      </stp>
    </bridge>
  </network-instance>
</network-instances>
```

```

    </global>
  </stp>
</bridge>
</network-instance>
</network-instances>

```

## Command Syntax

```
bridge <1-32> spanning-tree errdisable-timeout enable
```

---

## Configure force version

Use this attribute to set the version for the bridge. A version identifier of less than a value of 2 enforces the spanning tree protocol. Although the attribute supports an input range of 0-4, for RSTP, the valid range is 0-2. When the force-version is set for a bridge, all ports of the bridge have the same spanning tree version set.

Attribute Name: force-version

Attribute Type: uint8

Default Value: 0

Attribute Range: 0-4

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <global>
          <config>
            <force-version>0</force-version> <!-- operation="delete"-->
          </config>
        </global>
      </stp>
    </bridge>
  </network-instance>
</network-instances>

```

## Command Syntax

```
bridge <1-32> spanning-tree force-version <0-4>
```

---

## Configure path cost method

Use this attribute to set a spanning-tree path cost method. If the short parameter is used, the switch uses a value for the default path cost a number in the range 1 through 65,535. If the long parameter is used, the switch uses a value for the default path cost a number in the range 1 through 200,000,000.

Attribute Name: path-cost-method

Attribute Type: enum (short|long|default)

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <global>
          <config>
            <path-cost-method>default</path-cost-method> <!-- operation="delete"-->
          </config>
        </global>
      </stp>
    </bridge>
  </network-instance>
</network-instances>
```

### Command Syntax

```
bridge <1-32> spanning-tree pathcost method (short|long)
```

---

## Configure bridge type

Network Instance Name. For VRF and MAC VRF, instance name can be up to 32 chars long. For VPWS and VPLS instances, instance name can be up to 128 chars long. For L2NI (bridge) instance, instance name has to be a number between (1-32). For Cross-Connect, instance name can be up to 30 chars long. For Bridge-domain, instance, instance name has to be a number between (1-2147483647).

Attribute Name: instance-name

Attribute Type: string

Attribute Name: bridge-type

Attribute Type: enum (spanning-tree|rapid-spanning-tree|multiple-spanning-tree|rapid-pervlan-spanning-tree)

Attribute Name: disable-spanning-tree

Attribute Type: uint8

**Netconf edit-config payload**

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance> <!-- operation="delete"-->
    <instance-type>l2ni</instance-type>
    <config>
      <instance-type>l2ni</instance-type>
      <instance-name>WORD</instance-name>
    </config>
    <instance-name>WORD</instance-name>
  <stp>
  <global>
  <bridge-admins>
  <bridge-admin>
    <bridge-type>spanning-tree</bridge-type>
    </disable-spanning-tree>
  </bridge-admin>
</bridge-admins>
</global>
</stp>
</network-instance>
</network-instances>

```

**Command Syntax**

```

no bridge <1-32> (rapid-spanning-tree|multiple-spanning-tree|rapid-pervlan-
spanning-tree) enable

```

**Configure disable spanning tree**

Network Instance Name. For VRF and MAC VRF, instance name can be up to 32 chars long. For VPWS and VPLS instances, instance name can be up to 128 chars long. For L2NI (bridge) instance, instance name has to be a number between (1-32). For Cross-Connect, instance name can be up to 30 chars long. For Bridge-domain, instance, instance name has to be a number between (1-2147483647).

Attribute Name: instance-name

Attribute Type: string

Attribute Name: bridge-type

Attribute Type: enum (spanning-tree|rapid-spanning-tree|multiple-spanning-tree|rapid-pervlan-spanning-tree)

Attribute Name: disable-spanning-tree

Attribute Type: uint8

Attribute Name: bridge-forwarding

Attribute Type: enum (bridge-blocked|bridge-forward)

Default Value: bridge-blocked

**Netconf edit-config payload**

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance> <!-- operation="delete"-->

```

```

<instance-type>l2ni</instance-type>
<config>
  <instance-type>l2ni</instance-type>
  <instance-name>WORD</instance-name>
</config>
<instance-name>WORD</instance-name>
<stp>
<global>
<bridge-admins>
<bridge-admin>
  <bridge-type>spanning-tree</bridge-type>
  </disable-spanning-tree>
  <config>
    <bridge-forwarding>bridge-blocked</bridge-forwarding>
  </config>
</bridge-admin>
</bridge-admins>
</global>
</stp>
</network-instance>
</network-instances>

```

## Command Syntax

```
no bridge <1-32> (rapid-spanning-tree|multiple-spanning-tree|rapid-pervlan-
spanning-tree) enable (bridge-blocked|bridge-forward)
```

---

## Configure network-instances instance-name

Network Instance Name. For VRF and MAC VRF, instance name can be up to 32 chars long. For VPWS and VPLS instances, instance name can be up to 128 chars long. For L2NI (bridge) instance, instance name has to be a number between (1-32). For Cross-Connect, instance name can be up to 30 chars long. For Bridge-domain, instance, instance name has to be a number between (1-2147483647).

Attribute Name: instance-name

Attribute Type: string

Attribute Name: bridge-type

Attribute Type: enum (spanning-tree|rapid-spanning-tree|multiple-spanning-tree|rapid-pervlan-spanning-tree)

Attribute Name: disable-spanning-tree

Attribute Type: uint8

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance> <!-- operation="delete"-->
    <instance-type>l2ni</instance-type>
    <config>
      <instance-type>l2ni</instance-type>
      <instance-name>WORD</instance-name>
    </config>
  </network-instance>
</network-instances>

```

```

    <instance-name>WORD</instance-name>
  <stp>
  <global>
  <bridge-admins>
  <bridge-admin>
    <bridge-type>spanning-tree</bridge-type>
    </disable-spanning-tree>
  </bridge-admin>
</bridge-admins>
</global>
</stp>
</network-instance>
</network-instances>

```

## Command Syntax

```
no bridge <1-32> spanning-tree enable
```

---

## Configure bridge forwarding

Network Instance Name. For VRF and MAC VRF, instance name can be up to 32 chars long. For VPWS and VPLS instances, instance name can be up to 128 chars long. For L2NI (bridge) instance, instance name has to be a number between (1-32). For Cross-Connect, instance name can be up to 30 chars long. For Bridge-domain, instance, instance name has to be a number between (1-2147483647).

Attribute Name: instance-name

Attribute Type: string

Attribute Name: bridge-type

Attribute Type: enum (spanning-tree|rapid-spanning-tree|multiple-spanning-tree|rapid-pervlan-spanning-tree)

Attribute Name: disable-spanning-tree

Attribute Type: uint8

Attribute Name: bridge-forwarding

Attribute Type: enum (bridge-blocked|bridge-forward)

Default Value: bridge-blocked

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance> <!-- operation="delete"-->
    <instance-type>l2ni</instance-type>
    <config>
      <instance-type>l2ni</instance-type>
      <instance-name>WORD</instance-name>
    </config>
    <instance-name>WORD</instance-name>
  <stp>
  <global>
  <bridge-admins>
  <bridge-admin>

```

```

    <bridge-type>spanning-tree</bridge-type>
    </disable-spanning-tree>
    <config>
        <bridge-forwarding>bridge-blocked</bridge-forwarding>
    </config>
</bridge-admin>
</bridge-admins>
</global>
</stp>
</network-instance>
</network-instances>

```

## Command Syntax

```
no bridge <1-32> spanning-tree enable (bridge-blocked|bridge-forward)
```

---

## Configure enable shutdown

Network Instance Name. For VRF and MAC VRF, instance name can be up to 32 chars long. For VPWS and VPLS instances, instance name can be up to 128 chars long. For L2NI (bridge) instance, instance name has to be a number between (1-32). For Cross-Connect, instance name can be up to 30 chars long. For Bridge-domain, instance, instance name has to be a number between (1-2147483647).

Attribute Name: instance-name

Attribute Type: string

Attribute Name: enable-shutdown

Attribute Type: uint8

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance> <!-- operation="delete"-->
    <instance-type>l2ni</instance-type>
    <config>
      <instance-type>l2ni</instance-type>
      <instance-name>WORD</instance-name>
    </config>
    <instance-name>WORD</instance-name>
  </network-instance>
</network-instances>

```

## Command Syntax

```
bridge shutdown <1-32>
```

---

## Configure network-instances instance-name

Network Instance Name. For VRF and MAC VRF, instance name can be up to 32 chars long. For VPWS and VPLS instances, instance name can be up to 128 chars long. For L2NI (bridge) instance, instance name has to be a number between (1-32). For Cross-Connect, instance name can be up to 30 chars long. For Bridge-domain, instance, instance name has to be a number between (1-2147483647).

Attribute Name: instance-name

Attribute Type: string

Attribute Name: enable-shutdown

Attribute Type: uint8

Attribute Name: bridge-forwarding

Attribute Type: enum (bridge-blocked|bridge-forward)

Default Value: bridge-blocked

## Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance> <!-- operation="delete"-->
    <instance-type>l2ni</instance-type>
    <config>
      <instance-type>l2ni</instance-type>
      <instance-name>WORD</instance-name>
    </config>
    <instance-name>WORD</instance-name>
  <stp>
  <global>
  <bridge-shutdowns>
  <bridge-shutdown>
    </enable-shutdown>
  <config>
    <bridge-forwarding>bridge-blocked</bridge-forwarding>
  </config>
  </bridge-shutdown>
  </bridge-shutdowns>
  </global>
  </stp>
  </network-instance>
</network-instances>
```

## Command Syntax

```
bridge shutdown <1-32> (bridge-blocked|bridge-forward)
```

---

## Configure region name

Use this attribute to create an MST region and specify its name. MST bridges of a region form different spanning trees for different VLANs.

Attribute Name: region-name

Attribute Type: string

Default Value: Default

Attribute Range: 1-32

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <mstp>
          <config>
            <region-name>REGION_NAME</region-name> <!-- operation="delete"-->
          </config>
        </mstp>
      </stp>
    </bridge>
  </network-instance>
</network-instances>
```

### Command Syntax

```
bridge <1-32> region REGION_NAME
```

---

## Configure revision number

Use this attribute to specify the number for configuration information.

Attribute Name: revision-number

Attribute Type: uint16

Attribute Range: 0-65535

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
```

```

    <instance-name>WORD</instance-name>
    <instance-type>l2ni</instance-type>
</config>
    <instance-type>l2ni</instance-type>
<bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <mstp>
            <config>
                <revision-number>0</revision-number> <!-- operation="delete"-->
            </config>
        </mstp>
    </stp>
</bridge>
</network-instance>
</network-instances>

```

## Command Syntax

```
bridge <1-32> revision <0-65535>
```

---

## Configure vlan id

Use this attribute to simultaneously add multiple VLANs for the corresponding instance of a bridge. The VLANs must be created before being associated with an MST instance (MSTI). If the VLAN range is not specified, the MSTI will not be created.

Attribute Name: vlan-id

Attribute Type: uint16

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
    <network-instance>
        <instance-name>1</instance-name>
        <config>
            <instance-name>WORD</instance-name>
            <instance-type>vrf</instance-type>
        </config>
        <instance-type>l2ni</instance-type>
        <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
            <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
                <mstp>
                    <mst-instances>
                        <te-mst-instance>
                            <config>
                                <vlan-id>VLANID</vlan-id> <!-- operation="delete"-->
                            </config>
                        </te-mst-instance>
                    </mst-instances>
                </mstp>
            </stp>

```

```

</bridge>
</network-instance>
</network-instances>

```

## Command Syntax

```
bridge <1-32> te-msti vlan VLANID
```

---

## Configure disable spanning tree

Use this attribute to disable spanning tree for TE MSTI instance

Attribute Name: disable-spanning-tree

Attribute Type: uint8

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <mstp>
          <mst-instances>
            <te-mst-instance>
              <config>
                </disable-spanning-tree><!-- operation="delete"-->
              </config>
            </te-mst-instance>
          </mst-instances>
        </mstp>
      </stp>
    </bridge>
  </network-instance>
</network-instances>

```

## Command Syntax

```
no bridge <1-32> te-msti
```

---

## Configure name

The textual name of the interface

Attribute Name: name

Attribute Type: string

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
  <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
      <mstp>
        <mst-instances>
          <te-mst-instance>
            <interfaces>
              <interface <!-- operation="delete"-->
                <name>WORD</name>
                <config>
                  <name>WORD</name>
                </config>
              </interface>
            </interfaces>
          </te-mst-instance>
        </mst-instances>
      </mstp>
    </stp>
  </bridge>
</network-instance>
</network-instances>

```

## Command Syntax

```
bridge-group <1-32> instance te-msti
```

---

## Configure instance id

Network Instance Name. For VRF and MAC VRF, instance name can be up to 32 chars long. For VPWS and VPLS instances, instance name can be up to 128 chars long. For L2NI (bridge) instance, instance name has to be a number between (1-32). For Cross-Connect, instance name can be up to 30 chars long. For Bridge-domain, instance, instance name has to be a number between (1-2147483647).

Attribute Name: instance-name

Attribute Type: string

Attribute Name: instance-id

Attribute Type: union

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance> <!-- operation="delete"-->

```

```

    <instance-type>l2ni</instance-type>
  <config>
    <instance-type>l2ni</instance-type>
    <instance-name>WORD</instance-name>
  </config>
  <instance-name>WORD</instance-name>
</stp>
</mstp>
</mst-instaces>
</mst-instance>
</mst-instaces>
</mstp>
</stp>
</network-instance>
</network-instaces>

```

## Command Syntax

```
bridge <1-32> instance <1-63>
```

---

## Configure network-instaces instance-name

Network Instance Name. For VRF and MAC VRF, instance name can be up to 32 chars long. For VPWS and VPLS instances, instance name can be up to 128 chars long. For L2NI (bridge) instance, instance name has to be a number between (1-32). For Cross-Connect, instance name can be up to 30 chars long. For Bridge-domain, instance, instance name has to be a number between (1-2147483647).

Attribute Name: instance-name

Attribute Type: string

Attribute Name: instance-id

Attribute Type: uint16

## Netconf edit-config payload

```

<network-instaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance> <!-- operation="delete"-->
    <instance-type>l2ni</instance-type>
    <config>
      <instance-type>l2ni</instance-type>
      <instance-name>WORD</instance-name>
    </config>
    <instance-name>WORD</instance-name>
  </network-instance>
</network-instaces>

```

```

</mstp>
</stp>
</network-instance>
</network-instances>

```

## Command Syntax

```
bridge <1-32> instance <1-62>
```

---

## Configure instance type

Use this attribute to simultaneously add multiple VLANs for the corresponding instance of a bridge. The VLANs must be created before being associated with an MST instance (MSTI). If the VLAN range is not specified, the MSTI will not be created.

Attribute Name: vlan-id

Attribute Type: string

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <mstp>
          <mst-instances>
            <mst-instance>
              <instance-id>MSTP_INSTANCE_T</instance-id>
              <config>
                <instance-id>MSTP_INSTANCE_T</instance-id>
                </config>
                <vlan-id>VLAN_RANGE</vlan-id> <!-- operation="delete"-->
              </mst-instance>
            </mst-instances>
          </mstp>
        </stp>
      </bridge>
    </network-instance>
  </network-instances>

```

## Command Syntax

```
bridge <1-32> instance <1-63> vlan VLAN_RANGE
```

---

## Configure instance id

Use this attribute to simultaneously add multiple VLANs for the corresponding instance of a bridge. The VLANs must be created before being associated with an MST instance (MSTI). If the VLAN range is not specified, the MSTI will not be created.

Attribute Name: vlan-id

Attribute Type: string

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <mstp>
          <mst-instances>
            <mst-instance>
              <instance-id>MSTP_INSTANCE_T</instance-id>
              <config>
                <instance-id>MSTP_INSTANCE_T</instance-id>
                </config>
                <vlan-id>VLAN_RANGE</vlan-id> <!-- operation="delete"-->
              </mst-instance>
            </mst-instances>
          </mstp>
        </stp>
      </bridge>
    </network-instance>
  </network-instances>
```

### Command Syntax

```
bridge <1-32> instance <1-62> vlan VLAN_RANGE
```

---

## Configure mst-instance bridge-priority

Use this attribute to set the bridge instance priority.

Attribute Name: bridge-priority

Attribute Type: uint32

Default Value: 32768

Attribute Range: 0-61440

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <mstp>
          <mst-instances>
            <mst-instance>
              <instance-id>MSTP_INSTANCE_T</instance-id>
              <config>
                <instance-id>MSTP_INSTANCE_T</instance-id>
              </config>
              <bridge-priority>0</bridge-priority> <!-- operation="delete"-->
            </mst-instance>
          </mst-instances>
        </mstp>
      </stp>
    </bridge>
  </network-instance>
</network-instances>

```

## Command Syntax

```
bridge <1-32> instance <1-63> priority <0-61440>
```

## Configure mst-instance bridge-priority

Use this attribute to set the bridge instance priority.

Attribute Name: bridge-priority

Attribute Type: uint32

Default Value: 32768

Attribute Range: 0-61440

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>l2ni</instance-type>

```

```

<bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
  <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
    <mstp>
      <mst-instances>
        <mst-instance>
          <instance-id>MSTP_INSTANCE_T</instance-id>
          <config>
            <instance-id>MSTP_INSTANCE_T</instance-id>
          </config>
          <bridge-priority>0</bridge-priority> <!-- operation="delete"-->
        </mst-instance>
      </mst-instances>
    </mstp>
  </stp>
</bridge>
</network-instance>
</network-instances>

```

### Command Syntax

```
bridge <1-32> instance <1-62> priority <0-61440>
```

---

## Configure interfaces name

The textual name of the interface

Attribute Name: name

Attribute Type: string

### Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
  <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
      <mstp>
        <mst-instances>
          <mst-instance>
            <instance-id>MSTP_INSTANCE_T</instance-id>
            <config>
              <instance-id>MSTP_INSTANCE_T</instance-id>
            </config>
            <interfaces>
              <interface> <!-- operation="delete"-->
                <name>WORD</name>

```

```

        <config>
            <name>WORD</name>
        </config>
    </interface>
</interfaces>
</mst-instance>
</mst-instances>
</mstp>
</stp>
</bridge>
</network-instance>
</network-instances>

```

## Command Syntax

```
bridge-group <1-32> instance <1-63>
```

---

## Configure interfaces name

The textual name of the interface

Attribute Name: name

Attribute Type: string

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
  <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
      <mstp>
        <mst-instances>
          <mst-instance>
            <instance-id>MSTP_INSTANCE_T</instance-id>
            <config>
              <instance-id>MSTP_INSTANCE_T</instance-id>
            </config>
            <interfaces>
              <interface <!-- operation="delete"-->
                <name>WORD</name>
                <config>
                  <name>WORD</name>
                </config>
              </interface>
            </interfaces>
          </mst-instance>
        </mst-instances>
      </stp>
    </bridge>
  </network-instance>
</network-instances>

```

```

    </mst-instance>
  </mst-instances>
</mstp>
</stp>
</bridge>
</network-instance>
</network-instances>

```

## Command Syntax

```
bridge-group <1-32> instance <1-62>
```

---

## Configure interfaces name

The textual name of the interface

Attribute Name: name

Attribute Type: string

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
  <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
      <mstp>
        <mst-instances>
          <mst-instance>
            <instance-id>4092</instance-id>
            <config>
              <instance-id>4092</instance-id>
            </config>
            <interfaces>
              <interface <!-- operation="delete"-->
                <name>WORD</name>
                <config>
                  <name>WORD</name>
                </config>
              </interface>
            </interfaces>
          </mst-instance>
        </mst-instances>
      </mstp>
    </stp>
  </bridge>

```

```
</network-instance>
</network-instances>
```

## Command Syntax

```
bridge-group <1-32> instance spbm
```

---

## Configure interfaces name

The textual name of the interface

Attribute Name: name

Attribute Type: string

## Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <mstp>
          <mst-instances>
            <mst-instance>
              <instance-id>4093</instance-id>
              <config>
                <instance-id>4093</instance-id>
              </config>
              <interfaces>
                <interface> <!-- operation="delete"-->
                  <name>WORD</name>
                  <config>
                    <name>WORD</name>
                  </config>
                </interface>
              </interfaces>
            </mst-instance>
          </mst-instances>
        </mstp>
      </stp>
    </bridge>
  </network-instance>
</network-instances>
```

## Command Syntax

```
bridge-group <1-32> instance spbv
```

---

## Configure path cost

Use this attribute to set a path cost for a multiple spanning tree instance. Before using this attribute, you must explicitly add an MST instance to a port using the bridge-group instance attribute.

Attribute Name: path-cost

Attribute Type: uint32

Default Value: 20000000

Attribute Range: 1-200000000

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <mstp>
          <mst-instances>
            <mst-instance>
              <instance-id>MSTP_INSTANCE_T</instance-id>
              <config>
                <instance-id>MSTP_INSTANCE_T</instance-id>
                </config>
                <interfaces>
                  <interface>
                    <name>WORD</name>
                    <config>
                      <name>WORD</name>
                      </config>
                      <path-cost>1</path-cost> <!-- operation="delete"-->
                    </interface>
                  </interfaces>
                </mst-instance>
              </mst-instances>
            </mstp>
          </stp>
        </bridge>
      </network-instance>
    </network-instances>
```

### Command Syntax

```
bridge-group <1-32> instance <1-63> path-cost <1-200000000>
```

## Configure interface path-cost

Use this attribute to set a path cost for a multiple spanning tree instance. Before using this attribute, you must explicitly add an MST instance to a port using the bridge-group instance attribute.

Attribute Name: path-cost

Attribute Type: uint32

Default Value: 20000000

Attribute Range: 1-200000000

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <mstp>
          <mst-instances>
            <mst-instance>
              <instance-id>MSTP_INSTANCE_T</instance-id>
              <config>
                <instance-id>MSTP_INSTANCE_T</instance-id>
                </config>
                <interfaces>
                  <interface>
                    <name>WORD</name>
                    <config>
                      <name>WORD</name>
                      </config>
                      <path-cost>1</path-cost> <!-- operation="delete"-->
                    </interface>
                  </interfaces>
                </mst-instance>
              </mst-instances>
            </mstp>
          </stp>
        </bridge>
      </network-instance>
    </network-instances>
```

### Command Syntax

```
bridge-group <1-32> instance <1-62> path-cost <1-200000000>
```

---

## Configure port priority

Use this attribute to set the bridge instance priority. The Multiple Spanning Tree Protocol uses port priority as a tiebreaker to determine which port should forward frames for a particular instance on a LAN, or which port should be the root port for an instance. A lower value implies a better priority. In the case of the same priority, the interface index will serve as the tiebreaker, with the lower-numbered interface being preferred over others.

Attribute Name: port-priority

Attribute Type: int16

Default Value: 128

Attribute Range: 0-240

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <mstp>
          <mst-instances>
            <mst-instance>
              <instance-id>MSTP_INSTANCE_T</instance-id>
              <config>
                <instance-id>MSTP_INSTANCE_T</instance-id>
              </config>
              <interfaces>
                <interface>
                  <name>WORD</name>
                  <config>
                    <name>WORD</name>
                  </config>
                  <port-priority>0</port-priority> <!-- operation="delete"-->
                </interface>
              </interfaces>
            </mst-instance>
          </mst-instances>
        </mstp>
      </stp>
    </bridge>
  </network-instance>
</network-instances>
```

### Command Syntax

```
bridge-group <1-32> instance <1-63> priority <0-240>
```

---

## Configure interface port-priority

Use this attribute to set the bridge instance priority. The Multiple Spanning Tree Protocol uses port priority as a tiebreaker to determine which port should forward frames for a particular instance on a LAN, or which port should be the root port for an instance. A lower value implies a better priority. In the case of the same priority, the interface index will serve as the tiebreaker, with the lower-numbered interface being preferred over others.

Attribute Name: port-priority

Attribute Type: int16

Default Value: 128

Attribute Range: 0-240

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <mstp>
          <mst-instances>
            <mst-instance>
              <instance-id>MSTP_INSTANCE_T</instance-id>
              <config>
                <instance-id>MSTP_INSTANCE_T</instance-id>
              </config>
              <interfaces>
                <interface>
                  <name>WORD</name>
                  <config>
                    <name>WORD</name>
                  </config>
                  <port-priority>0</port-priority> <!-- operation="delete"-->
                </interface>
              </interfaces>
            </mst-instance>
          </mst-instances>
        </mstp>
      </stp>
    </bridge>
  </network-instance>
</network-instances>
```

### Command Syntax

```
bridge-group <1-32> instance <1-62> priority <0-240>
```

---

## Configure vlans vlan-id

Vlan ID

This command is supported when following feature are enabled rpvt feature

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 2-4094

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
    <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
      <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <rapid-pvst>
          <vlans>
            <vlan> <!-- operation="delete"-->
              <vlan-id>2</vlan-id>
              <config>
                <vlan-id>2</vlan-id>
              </config>
            </vlan>
          </vlans>
        </rapid-pvst>
      </stp>
    </bridge>
  </network-instance>
</network-instances>
```

### Command Syntax

```
bridge <1-32> vlan <2-4094>
```

---

## Configure vlan bridge-priority

Use this attribute to set the bridge instance priority.

This command is supported when following feature are enabled rpvt feature

Attribute Name: bridge-priority

Attribute Type: uint32

Default Value: 32768

Attribute Range: 0-61440

## Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
  <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <stp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
      <rapid-pvst>
        <vlans>
          <vlan>
            <vlan-id>2</vlan-id>
            <config>
              <vlan-id>2</vlan-id>
            </config>
            <bridge-priority>0</bridge-priority> <!-- operation="delete"-->
          </vlan>
        </vlans>
      </rapid-pvst>
    </stp>
  </bridge>
</network-instance>
</network-instances>
```

## Command Syntax

```
bridge <1-32> vlan <2-4094> priority <0-61440>
```

---

## Configure port-bridge path-cost

Use this attribute to set the cost of a path. Before you can use this attribute to set a path-cost in a VLAN configuration, you must explicitly add an MST instance to a port using the bridge-group instance attribute..

Attribute Name: path-cost

Attribute Type: uint32

Default Value: 20000000

Attribute Range: 1-200000000

## Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
```

```

    <instance-type>l2ni</instance-type>
  <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <bridge-ports>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <mstp-port xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
          <port-bridge>
            <config>
              <path-cost>1</path-cost> <!-- operation="delete"-->
            </config>
          </port-bridge>
        </mstp-port>
      </interface>
    </bridge-ports>
  </bridge>
</network-instance>
</network-instances>

```

### Command Syntax

```
bridge-group <1-32> path-cost <1-200000000>
```

---

## Configure port-bridge port-priority

Use this attribute to set the port priority for a bridge group. The Multiple Spanning Tree Protocol uses port priority as a tiebreaker to determine which port should forward frames for a particular instance on a LAN, or which port should be the root port for an instance. A lower value implies a better priority. In the case of the same priority, the interface index will serve as the tiebreaker, with the lower-numbered interface being preferred over others.

Attribute Name: port-priority

Attribute Type: int16

Default Value: 128

Attribute Range: 0-240

### Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
  <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <bridge-ports>
      <interface>
        <name>WORD</name>

```

```

    <config>
      <name>WORD</name>
    </config>
  <mstp-port xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
    <port-bridge>
      <config>
        <port-priority>0</port-priority> <!-- operation="delete"-->
      </config>
    </port-bridge>
  </mstp-port>
</interface>
</bridge-ports>
</bridge>
</network-instance>
</network-instances>

```

## Command Syntax

```
bridge-group <1-32> priority <0-240>
```

---

## Configure vlan path-cost

Use this attribute to set the bridge path cost.

This command is supported when following feature are enabled rpvst feature

Attribute Name: path-cost

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-200000000

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>1</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
  <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <bridge-ports>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
      <vlan-port xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
        <vlans>
          <vlan>

```

```

        <vlan-id>2</vlan-id>
        <config>
            <vlan-id>2</vlan-id>
        </config>
        <path-cost>1</path-cost> <!-- operation="delete"-->
    </vlan>
</vlans>
</vlan-port>
</interface>
</bridge-ports>
</bridge>
</network-instance>
</network-instances>

```

## Command Syntax

```
bridge-group <1-32> vlan <2-4094> path-cost <1-200000000>
```

---

## Configure vlan port-priority

Use this attribute to set the port instance priority.

This command is supported when following feature are enabled rpvst feature

Attribute Name: port-priority

Attribute Type: uint8

Default Value: 128

Attribute Range: 0-240

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
  <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <bridge-ports>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <vlan-port xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
          <vlans>
            <vlan>
              <vlan-id>2</vlan-id>
            <config>

```

```

        <vlan-id>2</vlan-id>
      </config>
    <port-priority>0</port-priority> <!-- operation="delete"-->
  </vlan>
</vlans>
</vlan-port>
</interface>
</bridge-ports>
</bridge>
</network-instance>
</network-instances>

```

## Command Syntax

```
bridge-group <1-32> vlan <2-4094> priority <0-240>
```

---

## Configure vlan vlan-id

Vlan ID

This command is supported when following feature are enabled rpvst feature

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 2-4094

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>l</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>l2ni</instance-type>
    </config>
    <instance-type>l2ni</instance-type>
  <bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bridge">
    <bridge-ports>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <vlan-port xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
          <vlans>
            <vlan>
              <vlan-id>2</vlan-id>
              <config>
                <vlan-id>2</vlan-id>
              </config>
            </vlan>
          </vlans>

```

```

    </vlan-port>
  </interface>
</bridge-ports>
</bridge>
</network-instance>
</network-instances>

```

### Command Syntax

```
bridge-group <1-32> vlan <2-4094>
```

---

## Configure interface hello-time

Use this attribute to set the hello-time, the time in seconds after which (if this bridge is the root bridge) all the default bridges in a bridged LAN exchange Bridge Protocol Data Units (BPDUs). A very low value of this parameter leads to excessive traffic on the network, while a higher value delays the detection of topology change. This value is used by all instances.

Attribute Name: hello-time

Attribute Type: uint8

Default Value: 2

Attribute Range: 1-10

### Netconf edit-config payload

```

<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <hello-time>1</hello-time> <!-- operation="delete"-->
    </interface>
  </interfaces>
</xstp>

```

### Command Syntax

```
spanning-tree hello-time <1-10>
```

---

## Configure port configuration

Use this attribute to set a port as an edge-port and to enable rapid transitions.

Attribute Name: port-configuration

Attribute Type: enum (edgeport|portfast)

Default Value: portfast

### Netconf edit-config payload

```

<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <interfaces>

```

```

<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <port-configuration>portfast</port-configuration> <!-- operation="delete"-->
</interface>
</interfaces>
</xstp>

```

### Command Syntax

```
spanning-tree (edgeport|portfast)
```

---

## Configure enable automatic edge detection

Use this attribute to enable automatic edge detection.

Attribute Name: enable-automatic-edge-detection

Attribute Type: empty

### Netconf edit-config payload

```

<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </enable-automatic-edge-detection><!-- operation="delete"-->
</interface>
</interfaces>
</xstp>

```

### Command Syntax

```
spanning-tree autoedge
```

---

## Configure bpdu guard

Use this attribute to set the portfast BPDU (Bridge Protocol Data Unit) guard or filter for the bridge. When the BPDU guard feature is set for a bridge, all portfast-enabled ports of the bridge that have the BPDU guard set to default shut down the port on receiving a BPDU. In this case, the BPDU is not processed. You can configure the errdisable-timeout feature to enable the port after the specified time interval.

Attribute Name: bpdu-guard

Attribute Type: enum (enable|disable|default)

Default Value: default

### Netconf edit-config payload

```

<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>

```

```

<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <bpdu-guard>default</bpdu-guard> <!-- operation="delete"-->
</interface>
</interfaces>
</xstp>

```

### Command Syntax

```
spanning-tree bpdu-guard (enable|disable|default)
```

---

## Configure bpdu filter

Use this attribute to set the portfast BPDU (Bridge Protocol Data Unit) guard or filter for the bridge. All ports that have their BPDU filter set to default take the same value of BPDU filter as that of the bridge. The Spanning Tree Protocol sends BPDUs from all ports. Enabling the BPDU Filter feature ensures that PortFast-enabled ports do not transmit or receive any BPDUs

Attribute Name: bpdu-filter

Attribute Type: enum (enable|disable|default)

Default Value: default

### Netconf edit-config payload

```

<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <bpdu-filter>default</bpdu-filter> <!-- operation="delete"-->
    </interface>
  </interfaces>
</xstp>

```

### Command Syntax

```
spanning-tree bpdu-filter (enable|disable|default)
```

---

## Configure enable root guard

Use this attribute to enable the root guard feature for the port. This feature disables reception of superior BPDUs. The root guard feature makes sure that the port on which it is enabled is a designated port. If the root guard enabled port receives a superior BPDU, it goes to a Listening state (for STP) or discarding state (for RSTP and MSTP).

Attribute Name: enable-root-guard

Attribute Type: empty

## Netconf edit-config payload

```
<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </enable-root-guard><!-- operation="delete"-->
</interface>
</interfaces>
</xstp>
```

## Command Syntax

```
spanning-tree guard root
```

---

## Configure link type

Use this attribute to enable or disable point-to-point or shared link types. RSTP has a backward-compatible STP , spanning-tree link-type shared. An alternative is the spanning-tree force-version 0

Attribute Name: link-type

Attribute Type: enum (shared|point-to-point|auto)

Default Value: point-to-point

## Netconf edit-config payload

```
<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <link-type>point-to-point</link-type> <!-- operation="delete"-->
</interface>
</interfaces>
</xstp>
```

## Command Syntax

```
spanning-tree link-type (shared|point-to-point|auto)
```

---

## Configure enable restricted domain role

Use this attribute to set the restricted-domain-role value of the port to TRUE.

Attribute Name: enable-restricted-domain-role

Attribute Type: empty

---

## Netconf edit-config payload

```
<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </enable-restricted-domain-role><!-- operation="delete"-->
</interface>
</interfaces>
</xstp>
```

## Command Syntax

```
spanning-tree restricted-domain-role
```

---

## Configure enable restricted role

Use this attribute to set the restricted-role value of the port to TRUE

Attribute Name: enable-restricted-role

Attribute Type: empty

## Netconf edit-config payload

```
<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </enable-restricted-role><!-- operation="delete"-->
</interface>
</interfaces>
</xstp>
```

## Command Syntax

```
spanning-tree restricted-role
```

---

## Configure enable restricted tcn

Use this attribute to set the restricted TCN value of the port to TRUE

Attribute Name: enable-restricted-tcn

Attribute Type: empty

## Netconf edit-config payload

```
<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>
<interface>
```

```

    <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</enable-restricted-tcn><!-- operation="delete"-->
</interface>
</interfaces>
</xstp>

```

### Command Syntax

```
spanning-tree restricted-tcn
```

---

## Configure enable instance restricted tcn

Use this attribute to set the restricted TCN value for the instance to TRUE

Attribute Name: enable-instance-restricted-tcn

Attribute Type: uint8

### Netconf edit-config payload

```

<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <mstp>
      <mst-instances>
        <mst-instance>
          <instance-id>MSTP_INSTANCE_T</instance-id>
          <config>
            <instance-id>MSTP_INSTANCE_T</instance-id>
            </enable-instance-restricted-tcn><!-- operation="delete"-->
          </config>
        </mst-instance>
      </mst-instances>
    </mstp>
  </interface>
</interfaces>
</xstp>

```

### Command Syntax

```
spanning-tree instance <1-63> restricted-tcn
```

---

## Configure mst-instance enable-instance-restricted-tcn

Use this attribute to set the restricted TCN value for the instance to TRUE

Attribute Name: enable-instance-restricted-tcn

Attribute Type: uint8

### Netconf edit-config payload

```
<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</mstp>
<mst-instances>
<mst-instance>
  <instance-id>MSTP_INSTANCE_T</instance-id>
  <config>
    <instance-id>MSTP_INSTANCE_T</instance-id>
    </enable-instance-restricted-tcn><!-- operation="delete"-->
  </config>
</mst-instance>
</mst-instances>
</mstp>
</interface>
</interfaces>
</xstp>
```

### Command Syntax

```
spanning-tree instance <1-62> restricted-tcn
```

---

## Configure enable instance restricted role

Use this attribute to set the restricted role value for the instance to TRUE

Attribute Name: enable-instance-restricted-role

Attribute Type: uint8

### Netconf edit-config payload

```
<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</mstp>
<mst-instances>
<mst-instance>
  <instance-id>MSTP_INSTANCE_T</instance-id>
  <config>
    <instance-id>MSTP_INSTANCE_T</instance-id>
  </config>
</mst-instance>
</mst-instances>
</mstp>
</interface>
</interfaces>
</xstp>
```

```

        </enable-instance-restricted-role><!-- operation="delete"-->
</mst-instance>
</mst-instances>
</mstp>
</interface>
</interfaces>
</xstp>

```

## Command Syntax

```
spanning-tree instance <1-63> restricted-role
```

---

## Configure mst-instance enable-instance-restricted-role

Use this attribute to set the restricted role value for the instance to TRUE

Attribute Name: enable-instance-restricted-role

Attribute Type: uint8

## Netconf edit-config payload

```

<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</mstp>
<mst-instances>
<mst-instance>
  <instance-id>MSTP_INSTANCE_T</instance-id>
  <config>
    <instance-id>MSTP_INSTANCE_T</instance-id>
    </enable-instance-restricted-role><!-- operation="delete"-->
  </config>
</mst-instance>
</mst-instances>
</mstp>
</interface>
</interfaces>
</xstp>

```

## Command Syntax

```
spanning-tree instance <1-62> restricted-role
```

---

## Configure vlan enable-restricted-role

Use this attribute to set the restricted role value for the instance to TRUE

This command is supported when following feature are enabled rpvst feature

Attribute Name: enable-restricted-role

Attribute Type: empty

### Netconf edit-config payload

```
<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</interfaces>
<rapid-pvst>
<vlangs>
<vlang>
  <vlang-id>2</vlang-id>
  <config>
    <vlang-id>2</vlang-id>
  </config>
</vlang>
</vlangs>
</rapid-pvst>
</xstp>
```

### Command Syntax

```
spanning-tree vlan <2-4094> restricted-role
```

---

## Configure vlang enable-restricted-tcn

Use this attribute to set the restricted TCN value for the instance to TRUE

This command is supported when following feature are enabled rpvst feature

Attribute Name: enable-restricted-tcn

Attribute Type: empty

### Netconf edit-config payload

```
<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</interfaces>
<rapid-pvst>
<vlangs>
<vlang>
  <vlang-id>2</vlang-id>
  <config>
    <vlang-id>2</vlang-id>
  </config>
</vlang>
</vlangs>
</rapid-pvst>
</xstp>
```

```

    </config>
      </enable-restricted-tcn><!-- operation="delete"-->
</vlan>
</vlans>
</rapid-pvst>
</interface>
</interfaces>
</xstp>

```

### Command Syntax

```
spanning-tree vlan <2-4094> restricted-tcn
```

---

## Configure customer-spanning-tree bridge-priority

Use this attribute to set the bridge priority for the common instance. Using a lower priority indicates a greater likelihood of the bridge becoming root. The priority values can be set only in increments of 4096.

This command is supported when following feature are enabled provider bridge feature

Attribute Name: bridge-priority

Attribute Type: uint16

Default Value: 61440

Attribute Range: 0-61440

### Netconf edit-config payload

```

<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<customer-spanning-tree>
<config>
  <bridge-priority>0</bridge-priority> <!-- operation="delete"-->
</config>
</customer-spanning-tree>
</interface>
</interfaces>
</xstp>

```

### Command Syntax

```
customer-spanning-tree priority <0-61440>
```

---

## Configure customer-spanning-tree max-age

Use this attribute to set the maximum age for a bridge. This value is used by all instances. Maximum age is the maximum time in seconds for which (if a bridge is the root bridge) a message is considered valid. This prevents the frames from looping indefinitely. The value of maximum age should be greater than twice the value of hello time plus 1, but less than twice the value of forward delay minus 1. The allowable range for max-age is 6-40 seconds. Configure

this value sufficiently high, so that a frame generated by root can be propagated to the leaf nodes without exceeding the maximum age.

This command is supported when following feature are enabled provider bridge feature

Attribute Name: max-age

Attribute Type: uint8

Default Value: 20

Attribute Range: 6-40

### Netconf edit-config payload

```
<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <customer-spanning-tree>
    <config>
      <max-age>6</max-age> <!-- operation="delete"-->
    </config>
    </customer-spanning-tree>
  </interface>
</interfaces>
</xstp>
```

### Command Syntax

```
customer-spanning-tree max-age <6-40>
```

---

## Configure customer-spanning-tree hello-time

Use this attribute to set the hello-time, the time in seconds after which (if this bridge is the root bridge) all the bridges in a bridged LAN exchange Bridge Protocol Data Units (BPDUs). A very low value of this parameter leads to excessive traffic on the network, while a higher value delays the detection of topology change. This value is used by all instances. Configure the bridge instance name before using this attribute. The allowable range of values is 1-10 seconds. However, make sure that the value of hello time is always greater than the value of hold time (2 seconds by default)

This command is supported when following feature are enabled provider bridge feature

Attribute Name: hello-time

Attribute Type: uint8

Default Value: 2

Attribute Range: 1-10

### Netconf edit-config payload

```
<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <interfaces>
    <interface>
      <name>WORD</name>
```

```

    <config>
      <name>WORD</name>
    </config>
  <customer-spanning-tree>
    <config>
      <hello-time>1</hello-time> <!-- operation="delete"-->
    </config>
  </customer-spanning-tree>
</interface>
</interfaces>
</xstp>

```

### Command Syntax

```
customer-spanning-tree hello-time <1-10>
```

---

## Configure forward delay

Use this attribute to set the time (in seconds) after which (if this bridge is the root bridge) each port changes states to learning and forwarding. This value is used by all instances

This command is supported when following feature are enabled provider bridge feature

Attribute Name: forward-delay

Attribute Type: uint8

Default Value: 15

Attribute Range: 4-30

### Netconf edit-config payload

```

<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <customer-spanning-tree>
      <config>
        <forward-delay>4</forward-delay> <!-- operation="delete"-->
      </config>
    </customer-spanning-tree>
  </interface>
</interfaces>
</xstp>

```

### Command Syntax

```
customer-spanning-tree forward-time <4-30>
```

---

## Configure customer-spanning-tree transmit-hold-count

Use this attribute to set the maximum number of transmissions of BPDUs by the transmit state machine

This command is supported when following feature are enabled provider bridge feature

Attribute Name: transmit-hold-count

Attribute Type: uint8

Default Value: 6

Attribute Range: 1-10

### Netconf edit-config payload

```
<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <customer-spanning-tree>
    <config>
      <transmit-hold-count>1</transmit-hold-count> <!-- operation="delete"-->
    </config>
    </customer-spanning-tree>
  </interface>
</interfaces>
</xstp>
```

### Command Syntax

```
customer-spanning-tree transmit-holdcount <1-10>
```

---

## Configure customer-edge path-cost

Use this attribute to set the bridge path cost.

This command is supported when following feature are enabled provider bridge feature

Attribute Name: path-cost

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-200000000

### Netconf edit-config payload

```
<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <customer-spanning-tree>
    <customer-edge>
    <config>
```

```

        <path-cost>1</path-cost> <!-- operation="delete"-->
</config>
</customer-edge>
</customer-spanning-tree>
</interface>
</interfaces>
</xstp>

```

### Command Syntax

```
customer-spanning-tree customer-edge path-cost <1-200000000>
```

---

## Configure customer-edge port-priority

Use this attribute to set the port instance priority.

This command is supported when following feature are enabled provider bridge feature

Attribute Name: port-priority

Attribute Type: uint8

Default Value: 128

Attribute Range: 0-240

### Netconf edit-config payload

```

<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>
<interface>
    <name>WORD</name>
    <config>
        <name>WORD</name>
    </config>
</customer-spanning-tree>
<customer-edge>
<config>
    <port-priority>0</port-priority> <!-- operation="delete"-->
</config>
</customer-edge>
</customer-spanning-tree>
</interface>
</interfaces>
</xstp>

```

### Command Syntax

```
customer-spanning-tree customer-edge priority <0-240>
```

---

## Configure svlan id

Use this attribute to set the bridge path cost.

This command is supported when following feature are enabled provider bridge feature

Attribute Name: path-cost

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-200000000

### Netconf edit-config payload

```
<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<customer-spanning-tree>
<provider-edge>
<vlans>
<vlan>
  <svlan-id>0</svlan-id>
  <config>
    <svlan-id>2</svlan-id>
  </config>
  <path-cost>1</path-cost> <!-- operation="delete"-->
</vlan>
</vlans>
</provider-edge>
</customer-spanning-tree>
</interface>
</interfaces>
</xstp>
```

### Command Syntax

```
customer-spanning-tree provider-edge svlan <2-4094> path-cost <1-200000000>
```

---

## Configure vlan port-priority

Use this attribute to set the port instance priority.

This command is supported when following feature are enabled provider bridge feature

Attribute Name: port-priority

Attribute Type: uint8

Default Value: 128

Attribute Range: 0-240

### Netconf edit-config payload

```
<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
```

```

        <name>WORD</name>
    </config>
<customer-spanning-tree>
<provider-edge>
<vlans>
<vlan>
    <svlan-id>0</svlan-id>
    <config>
        <svlan-id>2</svlan-id>
    </config>
    <port-priority>0</port-priority> <!-- operation="delete"-->
</vlan>
</vlans>
</provider-edge>
</customer-spanning-tree>
</interface>
</interfaces>
</xstp>

```

### Command Syntax

```
customer-spanning-tree provider-edge svlan <2-4094> priority <0-240>
```

---

## Configure options

Debug configuration flag

Attribute Name: options

Attribute Type: bits (mstp protocol|mstp protocol detail|mstp timer|mstp timer detail|mstp packet tx|mstp packet rx|mstp cli|mstp bpdu|mstp mcec|mstp all)

### Netconf edit-config payload

```

<xstp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<mstp>
<debug>
<config>
    <options>mstp protocol</options> <!-- operation="delete"-->
</config>
</debug>
</mstp>
</xstp>

```

### Command Syntax

```
debug (mstp protocol|mstp protocol detail|mstp timer|mstp timer detail|mstp packet
tx|mstp packet rx|mstp cli|mstp bpdu|mstp mcec|mstp all)
```

---

## debug (mstp protocol|mstp protocol detail|mstp timer|mstp timer detail|mstp packet tx|mstp packet rx|mstp cli|mstp bpdu|mstp mcec|mstp all)

Attribute Name: terminal-debug-options

Attribute Type: bits (mstp protocol|mstp protocol detail|mstp timer|mstp timer detail|mstp packet tx|mstp packet rx|mstp cli|mstp bpdu|mstp mcec|mstp all)

### Netconf RPC payload

```
<mstp-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<terminal-debug-options>mstp protocol</terminal-debug-options>
</mstp-terminal-debug-on>
```

### Command Syntax

```
debug (mstp protocol|mstp protocol detail|mstp timer|mstp timer detail|mstp packet
tx|mstp packet rx|mstp cli|mstp bpdu|mstp mcec|mstp all)
```

---

## no debug (mstp protocol|mstp protocol detail|mstp timer|mstp timer detail|mstp packet tx|mstp packet rx|mstp cli|mstp bpdu|mstp mcec|mstp all)

Attribute Name: terminal-debug-options

Attribute Type: bits (mstp protocol|mstp protocol detail|mstp timer|mstp timer detail|mstp packet tx|mstp packet rx|mstp cli|mstp bpdu|mstp mcec|mstp all)

### Netconf RPC payload

```
<mstp-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
<terminal-debug-options>mstp protocol</terminal-debug-options>
</mstp-terminal-debug-off>
```

### Command Syntax

```
no debug (mstp protocol|mstp protocol detail|mstp timer|mstp timer detail|mstp
packet tx|mstp packet rx|mstp cli|mstp bpdu|mstp mcec|mstp all)
```

---

## clear spanning-tree detected protocols bridge <1-32>

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```
<clear-spanning-tree-detected-protocols-per-bridge xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-xstp">
<bridge-id>1</bridge-id>
</clear-spanning-tree-detected-protocols-per-bridge>
```

### Command Syntax

```
clear spanning-tree detected protocols bridge <1-32>
```

---

## clear spanning-tree detected protocols interface INTERFACE

Attribute Name: interface-name

Attribute Type: string

## Netconf RPC payload

```
<clear-spanning-tree-detected-protocols-per-interface xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <interface-name>INTERFACE</interface-name>
</clear-spanning-tree-detected-protocols-per-interface>
```

## Command Syntax

```
clear spanning-tree detected protocols interface INTERFACE
```

---

## clear spanning-tree statistics (spbm|<1-63>) bridge <1-32>

Attribute Name: mst-instance-id

Attribute Type: union

Attribute Name: bridge-id

Attribute Type: string

## Netconf RPC payload

```
<clear-spanning-tree-statistics-per-instance-and-bridge xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <mst-instance-id>MSTP_INSTANCE_SPBM_TYPE_T</mst-instance-id>
  <bridge-id>1</bridge-id>
</clear-spanning-tree-statistics-per-instance-and-bridge>
```

## Command Syntax

```
clear spanning-tree statistics (spbm|<1-63>) bridge <1-32>
```

---

## clear spanning-tree statistics interface IFNAME vlan <2-4094> bridge <1-32>

Attribute Name: interface-name

Attribute Type: string

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 2-4094

Attribute Name: bridge-id

Attribute Type: string

## Netconf RPC payload

```
<clear-spanning-tree-statistics-per-interface-vlan-and-bridge xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <interface-name>IFNAME</interface-name>
  <vlan-id>2</vlan-id>
  <bridge-id>1</bridge-id>
</clear-spanning-tree-statistics-per-interface-vlan-and-bridge>
```

## Command Syntax

```
clear spanning-tree statistics interface IFNAME vlan <2-4094> bridge <1-32>
```

---

## clear spanning-tree statistics interface IFNAME bridge <1-32>

Attribute Name: interface-name

Attribute Type: string

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```
<clear-spanning-tree-statistics-per-interface-and-bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <interface-name>IFNAME</interface-name>
  <bridge-id>1</bridge-id>
</clear-spanning-tree-statistics-per-interface-and-bridge>
```

### Command Syntax

```
clear spanning-tree statistics interface IFNAME bridge <1-32>
```

---

## clear spanning-tree statistics bridge <1-32>

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```
<clear-spanning-tree-statistics-per-bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <bridge-id>1</bridge-id>
</clear-spanning-tree-statistics-per-bridge>
```

### Command Syntax

```
clear spanning-tree statistics bridge <1-32>
```

---

## clear spanning-tree statistics vlan <2-4094> bridge <1-32>

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 2-4094

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```
<clear-spanning-tree-statistics-per-vlan-and-bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <vlan-id>2</vlan-id>
  <bridge-id>1</bridge-id>
</clear-spanning-tree-statistics-per-vlan-and-bridge>
```

---

## Command Syntax

```
clear spanning-tree statistics vlan <2-4094> bridge <1-32>
```

---

## clear spanning-tree statistics interface IFNAME (spbm|<1-63>) bridge <1-32>

Attribute Name: interface-name

Attribute Type: string

Attribute Name: mst-instance-id

Attribute Type: union

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```
<clear-spanning-tree-statistics-per-interface-instance-and-bridge xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp">
  <interface-name>IFNAME</interface-name>
  <mst-instance-id>MSTP_INSTANCE_SPBM_TYPE_T</mst-instance-id>
  <bridge-id>1</bridge-id>
</clear-spanning-tree-statistics-per-interface-instance-and-bridge>
```

## Command Syntax

```
clear spanning-tree statistics interface IFNAME (spbm|<1-63>) bridge <1-32>
```

---

## snmp restart mstp

### Netconf RPC payload

```
<mstp-snmp-restart xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-xstp"/>
```

## Command Syntax

```
snmp restart mstp
```

---

## IPI-IF-AGGREGATE

---

### Configure aggregate id

Channel group identifier

Attribute Name: aggregate-id

Attribute Type: uint16

Attribute Range: 1-16383

Attribute Name: agg-type

Attribute Type: enum (lacp|static)

Attribute Name: lacp-mode

Attribute Type: enum (passive|active)

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <member-aggregation xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-
aggregate">
      <config>
        <agg-type>2</agg-type>
        <lacp-mode>1</lacp-mode>
        <aggregate-id>1</aggregate-id>
      </config>
    </member-aggregation>
  </interface>
</interfaces>
```

### Command Syntax

```
static-channel-group <1-16383>
```

---

## Configure lacp mode

Use this command to add a port to a channel group specified by the channel group number (1-12). This command enables link aggregation on a port, so that it may be selected for aggregation by the local system.

Attribute Name: lacp-mode

Attribute Type: enum (passive|active)

Attribute Name: agg-type

Attribute Type: enum (lacp|static)

Attribute Name: aggregate-id

Attribute Type: uint16

Attribute Range: 1-16383

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <member-aggregation xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-
aggregate">
      <config>
        <agg-type>1</agg-type>
        <aggregate-id>1</aggregate-id>
        <lacp-mode>passive</lacp-mode>
      </config>
    </member-aggregation>
  </interface>
</interfaces>
```

```

    </config>
  </member-aggregation>
</interface>
</interfaces>

```

## Command Syntax

```
channel-group <1-16383> mode (passive|active)
```

---

## Configure min links

Minimum number of active links required in this aggregator

Attribute Name: min-links

Attribute Type: uint8

Attribute Range: 2-32

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <aggregator xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-aggregate">
      <config>
        <min-links>2</min-links> <!-- operation="delete"-->
      </config>
    </aggregator>
  </interface>
</interfaces>

```

## Command Syntax

```
port-channel min-links <2-32>
```

---

## Configure min bandwidth

Minimum number of bandwidth required in this aggregator

Attribute Name: min-bandwidth

Attribute Type: string

### Netconf edit-config payload

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <aggregator xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-if-aggregate">

```

```

    <config>
      <min-bandwidth>BANDWIDTH</min-bandwidth> <!-- operation="delete"-->
    </config>
  </aggregator>
</interface>
</interfaces>

```

### Command Syntax

```
port-channel min-bandwidth BANDWIDTH
```

---

## IPI-LACP

---

### Configure system priority

Use this attribute to the system priority of this switch. This priority is used for determining the system that is responsible for resolving conflicts in the choice of aggregation groups. A lower numerical value has a higher priority.

Attribute Name: system-priority

Attribute Type: uint32

Default Value: 32768

Attribute Range: 0-65535

### Netconf edit-config payload

```

<lacp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lacp">
  <global>
    <config>
      <system-priority>0</system-priority> <!-- operation="delete"-->
    </config>
  </global>
</lacp>

```

### Command Syntax

```
lacp system-priority <0-65535>
```

---

## Configure options

This attribute returns the terminal debug options which are enabled

Attribute Name: options

Attribute Type: bits (event|cli|timer|packet|rx|tx|sync|ha|all)

### Netconf edit-config payload

```

<lacp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lacp">
  <debug>
    <config>
      <options>event</options> <!-- operation="delete"-->
    </config>

```

```
</debug>
</lacp>
```

## Command Syntax

```
debug lacp (event|cli|timer|packet|rx|tx|sync|ha|all)
```

---

## Configure port priority

Use this attribute to set the priority of a channel. Channels are selected for aggregation based on their priority with the higher priority (numerically lower) channels selected first

Attribute Name: port-priority

Attribute Type: uint32

Default Value: 32768

Attribute Range: 1-65535

## Netconf edit-config payload

```
<lacp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lacp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<member-aggregation>
<config>
  <port-priority>1</port-priority> <!-- operation="delete"-->
</config>
</member-aggregation>
</interface>
</interfaces>
</lacp>
```

## Command Syntax

```
lacp port-priority <1-65535>
```

---

## Configure timeout

Use this attribute to set either a short or long timeout value on a port. The timeout value is the number of seconds before invalidating a received LACP data unit (DU). If the LACP\_timeout bit (encoded in Actor\_State and Partner\_State fields) is set to 1, the short timeout takes effect; if set to 0, the long timeout takes effect.

Attribute Name: timeout

Attribute Type: enum (long|short)

Default Value: long

## Netconf edit-config payload

```
<lacp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lacp">
<interfaces>
```

```

<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<member-aggregation>
<config>
  <timeout>long</timeout> <!-- operation="delete"-->
</config>
</member-aggregation>
</interface>
</interfaces>
</lacp>

```

### Command Syntax

```
lacp timeout (long|short)
```

---

## Configure bridge type

Use this attribute to set the address type to use for sending LACPDUs (Link Aggregation Control Protocol Data Units).

Attribute Name: bridge-type

Attribute Type: enum (customer-bridge-group-address|multicast-group-address|non-tmpr-group-address)

Default Value: multicast-group-address

### Netconf edit-config payload

```

<lacp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lacp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<member-aggregation>
<config>
  <bridge-type>multicast-group-address</bridge-type> <!-- operation="delete"-->
</config>
</member-aggregation>
</interface>
</interfaces>
</lacp>

```

### Command Syntax

```
lacp destination-mac (customer-bridge-group-address|multicast-group-address|non-
tmpr-group-address)
```

---

## Configure force up

Use this attribute to enable the port as force-up in a channel group. Setting this attribute makes the port logically operational even if link aggregation goes down.

Attribute Name: force-up

Attribute Type: empty

### Netconf edit-config payload

```
<lacp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lacp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <member-aggregation>
        <config>
          </force-up><!-- operation="delete"-->
        </config>
      </member-aggregation>
    </interface>
  </interfaces>
</lacp>
```

### Command Syntax

```
lacp force-up
```

---

## Configure agg force up

Use this attribute to enable the port as lacp agg force-up

Attribute Name: agg-force-up

Attribute Type: empty

### Netconf edit-config payload

```
<lacp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lacp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <member-aggregation>
        <config>
          </agg-force-up><!-- operation="delete"-->
        </config>
      </member-aggregation>
    </interface>
  </interfaces>
```

```
</lacp>
```

### Command Syntax

```
lacp agg force-up
```

---

## snmp restart lacp

### Netconf RPC payload

```
<lacp-snmp-restart xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lacp"/>
```

### Command Syntax

```
snmp restart lacp
```

---

## clear lacp (<1-65535>|) counters

Attribute Name: aggregate-id

Attribute Type: uint16

Attribute Range: 1-65535

### Netconf RPC payload

```
<clear-lacp-counters xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lacp">  
<aggregate-id>1</aggregate-id>  
</clear-lacp-counters>
```

### Command Syntax

```
clear lacp (<1-65535>|) counters
```

---

## debug lacp (event|cli|timer|packet|rx|tx|sync|ha|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (event|cli|timer|packet|rx|tx|sync|ha|all)

### Netconf RPC payload

```
<lacp-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lacp">  
<terminal-debug-options>event</terminal-debug-options>  
</lacp-terminal-debug-on>
```

### Command Syntax

```
debug lacp (event|cli|timer|packet|rx|tx|sync|ha|all)
```

---

## no debug lacp (event|cli|timer|packet|rx|tx|sync|ha|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (event|cli|timer|packet|rx|tx|sync|ha|all)

---

## Netconf RPC payload

```
<lacp-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lacp">
  <terminal-debug-options>event</terminal-debug-options>
</lacp-terminal-debug-off>
```

## Command Syntax

```
no debug lacp (event|cli|timer|packet|rx|tx|sync|ha|all)
```

---

# IPI-LLDPV2

---

## Configure enable

Enable or disable the LLDP protocol at node level

Attribute Name: enable

Attribute Type: empty

## Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <global>
  <config>
    </enable><!-- operation="delete"-->
  </config>
</global>
</lldp>
```

## Command Syntax

```
lldp run
```

---

## Configure notification interval

This object controls the interval between transmission of LLDP notifications during normal transmission periods

Attribute Name: notification-interval

Attribute Type: uint16

Default Value: 30

Attribute Range: 5-3600

## Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <global>
  <config>
    <notification-interval>5</notification-interval> <!-- operation="delete"-->
  </config>
</global>
</lldp>
```

---

## Command Syntax

```
lldp notification-interval <5-3600>
```

---

## Configure port description

This attribute specifies to include basic management port description information in LLDP TLV

Attribute Name: port-description

Attribute Type: empty

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <global>
    <global-tlv-control>
      <global-basic-management>
        <config>
          </port-description><!-- operation="delete"-->
        </config>
      </global-basic-management>
    </global-tlv-control>
  </global>
</lldp>
```

## Command Syntax

```
lldp tlv-select basic-mgmt port-description
```

---

## Configure system description

This attribute specifies to include basic management system description information in LLDP TLV

Attribute Name: system-description

Attribute Type: empty

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <global>
    <global-tlv-control>
      <global-basic-management>
        <config>
          </system-description><!-- operation="delete"-->
        </config>
      </global-basic-management>
    </global-tlv-control>
  </global>
</lldp>
```

## Command Syntax

```
lldp tlv-select basic-mgmt system-description
```

---

## Configure system name

This attribute specifies to include basic management system name information in LLDP TLV

Attribute Name: system-name

Attribute Type: empty

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <global>
    <global-tlv-control>
      <global-basic-management>
        <config>
          </system-name><!-- operation="delete"-->
        </config>
      </global-basic-management>
    </global-tlv-control>
  </global>
</lldp>
```

### Command Syntax

```
lldp tlv-select basic-mgmt system-name
```

---

## Configure system capabilities

This attribute specifies to include basic management system capabilities information in LLDP TLV

Attribute Name: system-capabilities

Attribute Type: empty

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <global>
    <global-tlv-control>
      <global-basic-management>
        <config>
          </system-capabilities><!-- operation="delete"-->
        </config>
      </global-basic-management>
    </global-tlv-control>
  </global>
</lldp>
```

### Command Syntax

```
lldp tlv-select basic-mgmt system-capabilities
```

---

## Configure management address

This attribute specifies to include basic management management-address information in LLDP TLV

Attribute Name: management-address

Attribute Type: empty

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <global>
    <global-tlv-control>
      <global-basic-management>
        <config>
          </management-address><!-- operation="delete"-->
        </config>
      </global-basic-management>
    </global-tlv-control>
  </global>
</lldp>
```

### Command Syntax

```
lldp tlv-select basic-mgmt management-address
```

---

## Configure port vlan id

This attribute specifies to include ieee-8021-org-specific port vlan-id information in LLDP TLV

Attribute Name: port-vlan-id

Attribute Type: empty

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <global>
    <global-tlv-control>
      <global-ieee-8021-org-specific>
        <config>
          </port-vlan-id><!-- operation="delete"-->
        </config>
      </global-ieee-8021-org-specific>
    </global-tlv-control>
  </global>
</lldp>
```

### Command Syntax

```
lldp tlv-select ieee-8021-org-specific port-vlanid
```

---

## Configure port protocol vlan id

This attribute specifies to include ieee-8021-org-specific port protocol vlan-id information in LLDP TLV

Attribute Name: port-protocol-vlan-id

Attribute Type: empty

---

## Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <global>
    <global-tlv-control>
      <global-ieee-8021-org-specific>
        <config>
          </port-protocol-vlan-id><!-- operation="delete"-->
        </config>
      </global-ieee-8021-org-specific>
    </global-tlv-control>
  </global>
</lldp>
```

## Command Syntax

```
lldp tlv-select ieee-8021-org-specific port-ptcl-vlanid
```

---

## Configure vlan name

This attribute specifies to include ieee-8021-org-specific vlan name information in LLDP TLV

Attribute Name: vlan-name

Attribute Type: empty

## Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <global>
    <global-tlv-control>
      <global-ieee-8021-org-specific>
        <config>
          </vlan-name><!-- operation="delete"-->
        </config>
      </global-ieee-8021-org-specific>
    </global-tlv-control>
  </global>
</lldp>
```

## Command Syntax

```
lldp tlv-select ieee-8021-org-specific vlan-name
```

---

## Configure protocol identifier

This attribute specifies to include ieee-8021-org-specific protocol identifier information in LLDP TLV

Attribute Name: protocol-identifier

Attribute Type: empty

## Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <global>
    <global-tlv-control>
```

```

<global-ieee-8021-org-specific>
<config>
  </protocol-identifier><!-- operation="delete"-->
</config>
</global-ieee-8021-org-specific>
</global-tlv-control>
</global>
</lldp>

```

### Command Syntax

```
lldp tlv-select ieee-8021-org-specific ptcl-identity
```

---

## Configure vid digest

This attribute specifies to include ieee-8021-org-specific vid usage digest information in LLDP TLV

Attribute Name: vid-digest

Attribute Type: empty

### Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<global>
<global-tlv-control>
<global-ieee-8021-org-specific>
<config>
  </vid-digest><!-- operation="delete"-->
</config>
</global-ieee-8021-org-specific>
</global-tlv-control>
</global>
</lldp>

```

### Command Syntax

```
lldp tlv-select ieee-8021-org-specific vid-digest
```

---

## Configure management vlan id

This attribute specifies to include ieee-8021-org-specific management vlan-id information in LLDP TLV

Attribute Name: management-vlan-id

Attribute Type: empty

### Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<global>
<global-tlv-control>
<global-ieee-8021-org-specific>
<config>
  </management-vlan-id><!-- operation="delete"-->
</config>

```

```
</global-ieee-8021-org-specific>  
</global-tlv-control>  
</global>  
</lldp>
```

### Command Syntax

```
lldp tlv-select ieee-8021-org-specific mgmt-vid
```

---

## Configure link aggregation

This attribute specifies to include ieee-8021-org-specific link aggregation information in LLDP TLV

Attribute Name: link-aggregation

Attribute Type: empty

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">  
<global>  
<global-tlv-control>  
<global-ieee-8021-org-specific>  
<config>  
  </link-aggregation><!-- operation="delete"-->  
</config>  
</global-ieee-8021-org-specific>  
</global-tlv-control>  
</global>  
</lldp>
```

### Command Syntax

```
lldp tlv-select ieee-8021-org-specific link-agg
```

---

## Configure dcb exchange

This attribute specifies to include ieee-8021-org-specific data center bridging information in LLDP TLV

Attribute Name: dcb-exchange

Attribute Type: empty

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">  
<global>  
<global-tlv-control>  
<global-ieee-8021-org-specific>  
<config>  
  </dcb-exchange><!-- operation="delete"-->  
</config>  
</global-ieee-8021-org-specific>  
</global-tlv-control>  
</global>  
</lldp>
```

---

## Command Syntax

```
lldp tlv-select ieee-8021-org-specific data-center-bridging
```

---

## Configure mac phy

This attribute specifies to include ieee-8023-org-specific MAC or PHY information in LLDP TLV

Attribute Name: mac-phy

Attribute Type: empty

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <global>
    <global-tlv-control>
      <global-ieee-8023-org-specific>
        <config>
          </mac-phy><!-- operation="delete"-->
        </config>
      </global-ieee-8023-org-specific>
    </global-tlv-control>
  </global>
</lldp>
```

## Command Syntax

```
lldp tlv-select ieee-8023-org-specific mac-phy
```

---

## Configure max mtu size

This attribute specifies to include ieee-8023-org-specific maximum mtu size information in LLDP TLV

Attribute Name: max-mtu-size

Attribute Type: empty

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <global>
    <global-tlv-control>
      <global-ieee-8023-org-specific>
        <config>
          </max-mtu-size><!-- operation="delete"-->
        </config>
      </global-ieee-8023-org-specific>
    </global-tlv-control>
  </global>
</lldp>
```

## Command Syntax

```
lldp tlv-select ieee-8023-org-specific max-mtu-size
```

---

## Configure locally assigned chassis id

This attribute used to identify the chassis component associated with the local system

Attribute Name: locally-assigned-chassis-id

Attribute Type: string

Default Value: NULL

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <global>
    <management-if>
      <config>
        <locally-assigned-chassis-id>NAME</locally-assigned-chassis-id> <!--
operation="delete"-->
      </config>
    </management-if>
  </global>
</lldp>
```

### Command Syntax

```
set lldp chassis locally-assigned NAME
```

---

## Configure options

This attribute returns the terminal debug options which are enabled

Attribute Name: options

Attribute Type: bits (event|rx|tx|message|ha|all)

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <debug>
    <config>
      <options>event</options> <!-- operation="delete"-->
    </config>
  </debug>
</lldp>
```

### Command Syntax

```
debug lldp (event|rx|tx|message|ha|all)
```

---

## Configure disable lldp agent

Use this attribute to disable LLDP on interface when it is enabled globally

Attribute Name: disable-lldp-agent

Attribute Type: uint8

---

## Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </disable-lldp-agent><!-- operation="delete"-->
</interface>
</interfaces>
</lldp>
```

## Command Syntax

```
lldp disable default-agent
```

---

## Configure agent circuit id

DHCP agent circuit ID association on interface

Attribute Name: agent-circuit-id

Attribute Type: string

Default Value: NULL

## Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <agent-circuit-id>VALUE</agent-circuit-id> <!-- operation="delete"-->
</interface>
</interfaces>
</lldp>
```

## Command Syntax

```
set lldp agt-circuit-id VALUE
```

---

## Configure med device type

LLDP-MED type of interface. Class-0 is not defined, Class-1 is for generic endpoints and is applicable to all endpoints that require the base LLDP discovery services. Class-2 is for media endpoints and it includes endpoints that have IP media capabilities. Class-3 is for communication endpoints i.e., devices acting as end user communication appliances. Class-4 is for Network Connectivity Device. Class 5-255 are Reserved

Attribute Name: med-device-type

Attribute Type: enum (ep-class1|ep-class2|ep-class3|net-connect)

---

## Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <med-device-type>ep-class1</med-device-type> <!-- operation="delete"-->
</interface>
</interfaces>
</lldp>
```

## Command Syntax

```
set lldp med-devtype (ep-class1|ep-class2|ep-class3|net-connect)
```

---

## Configure local name

Interface sub type with local name

Attribute Name: local-name

Attribute Type: string

## Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <local-name>NAME</local-name> <!-- operation="delete"-->
</interface>
</interfaces>
</lldp>
```

## Command Syntax

```
set lldp locally-assigned NAME
```

---

## Configure agent type

LLDP agent type on this interface

Attribute Name: agent-type

Attribute Type: enum (non-tpmr-bridge|customer-bridge|default)

## Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
```

```

    <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</agents>
<agent> <!-- operation="delete"-->
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

## Command Syntax

```
lldp-agent (non-tpmr-bridge|customer-bridge|)
```

---

## Configure enable tx rx

Enables interface with LLDP protocol and specifies to send and(or) receive packets on interface

Attribute Name: enable-tx-rx

Attribute Type: enum (rxonly|txonly|txrx)

Default Value: rxonly

## Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
  <agents>
    <agent>
      <agent-type>default</agent-type>
      <config>
        <agent-type>default</agent-type>
      </config>
      <enable-tx-rx>rxonly</enable-tx-rx> <!-- operation="delete"-->
    </agent>
  </agents>
</lldp>

```

## Command Syntax

```
set lldp enable (rxonly|txonly|txrx)
```

---

## Configure dcbx enable

Use this attribute to enable/disable DCBX on the given interface

Attribute Name: dcbx-enable

Attribute Type: empty

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <agents>
      <agent>
        <agent-type>default</agent-type>
        <config>
          <agent-type>default</agent-type>
        </config>
        </dcbx-enable><!-- operation="delete"-->
      </agent>
    </agents>
  </interface>
</interfaces>
</lldp>
```

### Command Syntax

```
dcbx enable
```

---

## Configure reinit delay

The minimum time interval an LLDP port waits before re-initializing an LLDP transmission

Attribute Name: reinit-delay

Attribute Type: uint32

Default Value: 2

Attribute Range: 1-10

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <agents>
```

```

<agent>
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
  <transmit>
    <config>
      <reinit-delay>1</reinit-delay> <!-- operation="delete"-->
    </config>
  </transmit>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

## Command Syntax

```
set lldp timer reinit-delay <1-10>
```

---

## Configure message tx interval

The delay between successive LLDP frame transmissions during normal transmission periods

Attribute Name: message-tx-interval

Attribute Type: uint32

Default Value: 30

Attribute Range: 5-3600

## Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
  <agents>
    <agent>
      <agent-type>default</agent-type>
      <config>
        <agent-type>default</agent-type>
      </config>
      <transmit>
        <config>
          <message-tx-interval>5</message-tx-interval> <!-- operation="delete"-->
        </config>
      </transmit>
    </agent>
  </agents>

```

```

</interface>
</interfaces>
</lldp>

```

## Command Syntax

```
set lldp timer msg-tx-interval <5-3600>
```

---

## Configure message tx hold multiplier

Multiplier of message-tx-interval to determine the Time To Live (TTL) that is carried in LLDP frames transmitted by the LLDP agent

Attribute Name: message-tx-hold-multiplier

Attribute Type: uint32

Default Value: 4

Attribute Range: 1-100

## Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
  <agents>
    <agent>
      <agent-type>default</agent-type>
      <config>
        <agent-type>default</agent-type>
      </config>
      <transmit>
        <config>
          <message-tx-hold-multiplier>1</message-tx-hold-multiplier> <!--
operation="delete"-->
        </config>
      </transmit>
    </agent>
  </agents>
</interface>
</interfaces>
</lldp>

```

## Command Syntax

```
set lldp msg-tx-hold <1-100>
```

---

## Configure message fast tx

The interval at which LLDP frames are transmitted on behalf of LLDP agent during fast transmission periods

Attribute Name: message-fast-tx

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-3600

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<agents>
<agent>
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
  <transmit>
  <config>
    <message-fast-tx>1</message-fast-tx> <!-- operation="delete"-->
  </config>
</transmit>
</agent>
</agents>
</interface>
</interfaces>
</lldp>
```

### Command Syntax

```
set lldp timer msg-fast-tx <1-3600>
```

---

## Configure tx credit max

The maximum number of consecutive LLDPDUs that can be transmitted at any time

Attribute Name: tx-credit-max

Attribute Type: uint32

Default Value: 5

Attribute Range: 1-10

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
```

```

        <name>WORD</name>
    </config>
</agents>
<agent>
    <agent-type>default</agent-type>
    <config>
        <agent-type>default</agent-type>
    </config>
    <transmit>
    <config>
        <tx-credit-max>1</tx-credit-max> <!-- operation="delete"-->
    </config>
</transmit>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

### Command Syntax

```
set lldp tx-max-credit <1-10>
```

---

## Configure tx fast init

The number of LLDPDUs to send during the fast transmission periods

Attribute Name: tx-fast-init

Attribute Type: uint32

Default Value: 4

Attribute Range: 1-8

### Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
    <name>WORD</name>
    <config>
        <name>WORD</name>
    </config>
</interface>
</interfaces>
<agent>
    <agent-type>default</agent-type>
    <config>
        <agent-type>default</agent-type>
    </config>
    <transmit>
    <config>
        <tx-fast-init>1</tx-fast-init> <!-- operation="delete"-->
    </config>
</transmit>
</agent>
</lldp>

```

```

</transmit>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

## Command Syntax

```
set lldp tx-fast-init <1-8>
```

---

## Configure neighbor timer

This attribute configures timer to discard received message when remote table is full

Attribute Name: neighbor-timer

Attribute Type: uint32

Attribute Range: 1-65535

Attribute Name: neighbor-limit

Attribute Type: uint32

Attribute Range: 1-65535

## Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lllvpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</interfaces>
<agents>
<agent>
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
  <receive>
    <config>
      <neighbor-limit>1</neighbor-limit> <!-- operation="delete"-->
      <neighbor-timer>1</neighbor-timer> <!-- operation="delete"-->
    </config>
  </receive>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

## Command Syntax

```
set lldp too-many-neighbors limit <1-65535> discard received-info timer <1-65535>
```

---

## Configure port timer

This attribute configures timer to discard or delete existing info for received message port MAC when the remote table is full

Attribute Name: port-timer

Attribute Type: uint32

Attribute Range: 1-65535

Attribute Name: neighbor-limit

Attribute Type: uint32

Attribute Range: 1-65535

Attribute Name: port-mac

Attribute Type: string

## Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
  <agents>
    <agent>
      <agent-type>default</agent-type>
      <config>
        <agent-type>default</agent-type>
      </config>
      <receive>
        <config>
          <neighbor-limit>1</neighbor-limit> <!-- operation="delete"-->
          <port-mac>MAC</port-mac> <!-- operation="delete"-->
          <port-timer>1</port-timer> <!-- operation="delete"-->
        </config>
      </receive>
    </agent>
  </agents>
</lldp>
```

## Command Syntax

```
set lldp too-many-neighbors limit <1-65535> discard existing-info MAC timer <1-65535>
```

---

## Configure port address

This attribute specifies sub type of the Management Address TLV. Can be configured as mac-addresss or ip-address

Attribute Name: port-address

Attribute Type: enum (mac-address|ip-address)

Default Value: mac-address

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <agents>
      <agent>
        <agent-type>default</agent-type>
        <config>
          <agent-type>default</agent-type>
        </config>
        <agent-tlv>
          <config>
            <port-address>mac-address</port-address> <!-- operation="delete"-->
          </config>
        </agent-tlv>
      </agent>
    </agents>
  </interface>
</interfaces>
</lldp>
```

### Command Syntax

```
set lldp management-address-tlv (mac-address|ip-address)
```

---

## Configure chassis id

This attribute specifies chassis ID subtype for the LLDP agent on a port. Can be configured as if-alias or ip-address or mac-address or if-name or locally-assgined name

Attribute Name: chassis-id

Attribute Type: enum (if-alias|ip-address|mac-address|if-name|locally-assigned)

Default Value: mac-address

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
    <interface>
```

```

    <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</agents>
<agent>
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
  <agent-tlv>
  <config>
    <chassis-id>mac-address</chassis-id> <!-- operation="delete"-->
  </config>
</agent-tlv>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

## Command Syntax

```
set lldp chassis-id-tlv (if-alias|ip-address|mac-address|if-name|locally-assigned)
```

---

## Configure port id

This attribute specifies sub type of the port id TLV. Can be configured as if-alias or mac-address or ip-address or if-name or agent-circuit-id or locally assigned name

Attribute Name: port-id

Attribute Type: enum (if-alias|mac-address|ip-address|if-name|agt-circuit-id|locally-assigned)

Default Value: mac-address

## Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
  <interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  </interface>
</interfaces>
<agents>
<agent>
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
  <agent-tlv>
  <config>
    <port-id>mac-address</port-id> <!-- operation="delete"-->
  </config>
</agent-tlv>
</agent>
</agents>

```

```

    </config>
  </agent-tlv>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

## Command Syntax

```

set lldp port-id-tlv (if-alias|mac-address|ip-address|if-name|agt-circuit-
id|locally-assigned)

```

---

## Configure name

This attribute specifies to include basic management port description information in LLDP TLV

Attribute Name: port-description

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

## Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
  <agent>
    <agent-type>default</agent-type>
    <config>
      <agent-type>default</agent-type>
    </config>
    <tlv-control>
      <basic-management>
        <config>
          <port-description>not-set</port-description> <!-- operation="delete"-->
        </config>
      </basic-management>
    </tlv-control>
  </agent>
</lldp>

```

## Command Syntax

```

lldp tlv basic-mgmt port-description (select|unselect)

```

---

## Configure basic-management system-description

This attribute specifies to include basic management system description information in LLDP TLV

Attribute Name: system-description

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <agents>
      <agent>
        <agent-type>default</agent-type>
        <config>
          <agent-type>default</agent-type>
        </config>
        <tlv-control>
          <basic-management>
            <config>
              <system-description>not-set</system-description> <!-- operation="delete"-
->
            </config>
          </basic-management>
        </tlv-control>
      </agent>
    </agents>
  </interface>
</interfaces>
</lldp>
```

### Command Syntax

```
lldp tlv basic-mgmt system-description (select|unselect)
```

---

## Configure basic-management system-name

This attribute specifies to include basic management system name information in LLDP TLV

Attribute Name: system-name

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
```

```

<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</interfaces>
<agents>
<agent>
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
  <tlv-control>
  <basic-management>
  <config>
    <system-name>not-set</system-name> <!-- operation="delete"-->
  </config>
</basic-management>
</tlv-control>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

## Command Syntax

```
lldp tlv basic-mgmt system-name (select|unselect)
```

## Configure basic-management system-capabilities

This attribute specifies to include basic management system capabilities information in LLDP TLV

Attribute Name: system-capabilities

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

### Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</interfaces>
<agents>
<agent>
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
</agent>
</agents>
</lldp>

```

```

    <tlv-control>
    <basic-management>
    <config>
      <system-capabilities>not-set</system-capabilities> <!--
operation="delete"-->
    </config>
  </basic-management>
</tlv-control>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

### Command Syntax

```
lldp tlv basic-mgmt system-capabilities (select|unselect)
```

---

## Configure basic-management management-address

This attribute specifies to include basic management management-address information in LLDP TLV

Attribute Name: management-address

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

### Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</agents>
<agent>
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
  <tlv-control>
  <basic-management>
  <config>
    <management-address>not-set</management-address> <!-- operation="delete"-
->
  </config>
</basic-management>
</tlv-control>
</agent>
</agents>
</interface>

```

```
</interfaces>
</lldp>
```

## Command Syntax

```
lldp tlv basic-mgmt management-address (select|unselect)
```

---

## Configure ieee-8021-org-specific port-vlan-id

This attribute specifies to include ieee-8021-org-specific port vlan-id information in LLDP TLV

Attribute Name: port-vlan-id

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<agents>
<agent>
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
  <tlv-control>
    <ieee-8021-org-specific>
      <config>
        <port-vlan-id>not-set</port-vlan-id> <!-- operation="delete"-->
      </config>
    </ieee-8021-org-specific>
  </tlv-control>
</agent>
</agents>
</interface>
</interfaces>
</lldp>
```

## Command Syntax

```
lldp tlv ieee-8021-org-specific port-vlanid (select|unselect)
```

---

## Configure ieee-8021-org-specific port-protocol-vlan-id

This attribute specifies to include ieee-8021-org-specific port protocol vlan-id information in LLDP TLV

Attribute Name: port-protocol-vlan-id

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<agents>
<agent>
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
  <tlv-control>
    <ieee-8021-org-specific>
      <config>
        <port-protocol-vlan-id>not-set</port-protocol-vlan-id> <!--
operation="delete"-->
      </config>
    </ieee-8021-org-specific>
  </tlv-control>
</agent>
</agents>
</interface>
</interfaces>
</lldp>
```

### Command Syntax

```
lldp tlv ieee-8021-org-specific port-ptcl-vlanid (select|unselect)
```

---

## Configure ieee-8021-org-specific vlan-name

This attribute specifies to include ieee-8021-org-specific vlan name information in LLDP TLV

Attribute Name: vlan-name

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<agents>
```

```

<agent>
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
  <tlv-control>
    <ieee-8021-org-specific>
      <config>
        <vlan-name>not-set</vlan-name> <!-- operation="delete"-->
      </config>
    </ieee-8021-org-specific>
  </tlv-control>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

## Command Syntax

```
lldp tlv ieee-8021-org-specific vlan-name (select|unselect)
```

---

## Configure ieee-8021-org-specific protocol-identifier

This attribute specifies to include ieee-8021-org-specific protocol identifier information in LLDP TLV

Attribute Name: protocol-identifier

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

## Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
  <agents>
    <agent>
      <agent-type>default</agent-type>
      <config>
        <agent-type>default</agent-type>
      </config>
      <tlv-control>
        <ieee-8021-org-specific>
          <config>
            <protocol-identifier>not-set</protocol-identifier> <!--
operation="delete"-->
          </config>
        </ieee-8021-org-specific>
      </tlv-control>
    </agent>
  </agents>
</lldp>

```

```

</tlv-control>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

### Command Syntax

```
lldp tlv ieee-8021-org-specific ptcl-identity (select|unselect)
```

---

## Configure ieee-8021-org-specific vid-digest

This attribute specifies to include ieee-8021-org-specific vid usage digest information in LLDP TLV

Attribute Name: vid-digest

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

### Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</agents>
<agent>
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
  <tlv-control>
  <ieee-8021-org-specific>
  <config>
    <vid-digest>not-set</vid-digest> <!-- operation="delete"-->
  </config>
</ieee-8021-org-specific>
</tlv-control>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

### Command Syntax

```
lldp tlv ieee-8021-org-specific vid-digest (select|unselect)
```

---

## Configure ieee-8021-org-specific management-vlan-id

This attribute specifies to include ieee-8021-org-specific management vlan-id information in LLDP TLV

Attribute Name: management-vlan-id

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <agents>
      <agent>
        <agent-type>default</agent-type>
        <config>
          <agent-type>default</agent-type>
        </config>
        <tlv-control>
          <ieee-8021-org-specific>
            <config>
              <management-vlan-id>not-set</management-vlan-id> <!-- operation="delete"-
->
            </config>
          </ieee-8021-org-specific>
        </tlv-control>
      </agent>
    </agents>
  </interface>
</interfaces>
</lldp>
```

### Command Syntax

```
lldp tlv ieee-8021-org-specific mgmt-vid (select|unselect)
```

---

## Configure ieee-8021-org-specific link-aggregation

This attribute specifies to include ieee-8021-org-specific link aggregation information in LLDP TLV

Attribute Name: link-aggregation

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

### Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
```

```

<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</interfaces>
<agents>
<agent>
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
  <tlv-control>
  <ieee-8021-org-specific>
  <config>
    <link-aggregation>not-set</link-aggregation> <!-- operation="delete"-->
  </config>
</ieee-8021-org-specific>
</tlv-control>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

## Command Syntax

```
lldp tlv ieee-8021-org-specific link-agg (select|unselect)
```

---

## Configure ieee-8021-org-specific dcb-exchange

This attribute specifies to include ieee-8021-org-specific data center bridging information in LLDP TLV

Attribute Name: dcb-exchange

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

### Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</interfaces>
<agents>
<agent>
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
</agent>
</agents>
</lldp>

```

```

    <tlv-control>
    <ieee-8021-org-specific>
    <config>
        <dcb-exchange>not-set</dcb-exchange> <!-- operation="delete"-->
    </config>
</ieee-8021-org-specific>
</tlv-control>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

### Command Syntax

```
lldp tlv ieee-8021-org-specific data-center-bridging (select|unselect)
```

---

## Configure ieee-8023-org-specific mac-phy

This attribute specifies to include ieee-8023-org-specific MAC or PHY information in LLDP TLV

Attribute Name: mac-phy

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

### Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
    <name>WORD</name>
    <config>
        <name>WORD</name>
    </config>
<agents>
<agent>
    <agent-type>default</agent-type>
    <config>
        <agent-type>default</agent-type>
    </config>
    <tlv-control>
    <ieee-8023-org-specific>
    <config>
        <mac-phy>not-set</mac-phy> <!-- operation="delete"-->
    </config>
</ieee-8023-org-specific>
</tlv-control>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

---

## Command Syntax

```
lldp tlv ieee-8023-org-specific mac-phy (select|unselect)
```

---

## Configure ieee-8023-org-specific max-mtu-size

This attribute specifies to include ieee-8023-org-specific maximum mtu size information in LLDP TLV

Attribute Name: max-mtu-size

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

## Netconf edit-config payload

```
<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <agents>
      <agent>
        <agent-type>default</agent-type>
        <config>
          <agent-type>default</agent-type>
        </config>
        <tlv-control>
          <ieee-8023-org-specific>
            <config>
              <max-mtu-size>not-set</max-mtu-size> <!-- operation="delete"-->
            </config>
          </ieee-8023-org-specific>
        </tlv-control>
      </agent>
    </agents>
  </interface>
</interfaces>
</lldp>
```

## Command Syntax

```
lldp tlv ieee-8023-org-specific max-mtu-size (select|unselect)
```

---

## Configure network policy

Network policy information configured on the port for connected media endpoint. Following network policy will be supported VLAN ID, Priority Tagging, VLAN DSCP

Attribute Name: network-policy

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

**Netconf edit-config payload**

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</interfaces>
<agents>
<agent>
  <agent-type>default</agent-type>
  <config>
    <agent-type>default</agent-type>
  </config>
  <tlv-control>
  <tlv-media-capabilities>
  <config>
    <network-policy>not-set</network-policy> <!-- operation="delete"-->
  </config>
</tlv-media-capabilities>
</tlv-control>
</agent>
</agents>
</lldp>

```

**Command Syntax**

```
lldp tlv med network-policy (select|unselect)
```

**Configure location**

Media Tlv type Location information configured for the port

Attribute Name: location

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

**Netconf edit-config payload**

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</interfaces>
<agents>
<agent>
  <agent-type>default</agent-type>

```

```

    <config>
      <agent-type>default</agent-type>
    </config>
  <tlv-control>
    <tlv-media-capabilities>
      <config>
        <location>not-set</location> <!-- operation="delete"-->
      </config>
    </tlv-media-capabilities>
  </tlv-control>
</agent>
</agents>
</interface>
</interfaces>
</lldp>

```

## Command Syntax

```
lldp tlv med location (select|unselect)
```

---

## Configure inventory

Includes the TLV for information like hardware revision, software revision etc based on the current hardware platform and the software version

Attribute Name: inventory

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

## Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
  <agent>
    <agent-type>default</agent-type>
    <config>
      <agent-type>default</agent-type>
    </config>
    <tlv-control>
      <tlv-media-capabilities>
        <config>
          <inventory>not-set</inventory> <!-- operation="delete"-->
        </config>
      </tlv-media-capabilities>
    </tlv-control>
  </agent>

```

```

</agents>
</interface>
</interfaces>
</lldp>

```

## Command Syntax

```
lldp tlv med inventory (select|unselect)
```

---

## Configure media capabilities

Includes various media-capabilities of the box for the neighbor

Attribute Name: media-capabilities

Attribute Type: enum (not-set|select|unselect)

Default Value: not-set

## Netconf edit-config payload

```

<lldp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
  <agent>
    <agent-type>default</agent-type>
    <config>
      <agent-type>default</agent-type>
    </config>
    <tlv-control>
      <tlv-media-capabilities>
        <config>
          <media-capabilities>not-set</media-capabilities> <!-- operation="delete"-
->
        </config>
      </tlv-media-capabilities>
    </tlv-control>
  </agent>
</agents>
</interface>
</interfaces>
</lldp>

```

## Command Syntax

```
lldp tlv med media-capabilities (select|unselect)
```

---

## debug lldp (event|rx|tx|message|ha|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (event|rx|tx|message|ha|all)

### Netconf RPC payload

```
<lldp-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <terminal-debug-options>event</terminal-debug-options>
</lldp-terminal-debug-on>
```

### Command Syntax

```
debug lldp (event|rx|tx|message|ha|all)
```

---

## no debug lldp (event|rx|tx|message|ha|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (event|rx|tx|message|ha|all)

### Netconf RPC payload

```
<lldp-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
lldpv2">
  <terminal-debug-options>event</terminal-debug-options>
</lldp-terminal-debug-off>
```

### Command Syntax

```
no debug lldp (event|rx|tx|message|ha|all)
```

---

## clear lldp counters ((IFNAME|))

Attribute Name: interface-name

Attribute Type: string

### Netconf RPC payload

```
<clear-lldp-counter xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2">
  <interface-name>IFNAME</interface-name>
</clear-lldp-counter>
```

### Command Syntax

```
clear lldp counters ((IFNAME|))
```

---

## snmp restart lldp

### Netconf RPC payload

```
<lldp-snmp-restart xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-lldpv2"/>
```

### Command Syntax

```
snmp restart lldp
```

---

## IPI-RIB

---

### Configure fib retain

Use this attribute to configure retain time for stale routes (forever or specific time in seconds) in FIB after RIB restarts

Attribute Name: fib-retain

Attribute Type: union

Default Value: 60

#### Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <global>
    <config>
      <fib-retain>60</fib-retain> <!-- operation="delete"-->
    </config>
  </global>
</routing>
```

#### Command Syntax

```
fib retain (time <1-65535>|forever|)
```

---

### Configure max ecmp paths

Use this attribute to set the maximum number of paths to install in the FIB (Forwarding Information Base) for the ECMP (Equal-Cost MultiPath) feature.

Attribute Name: max-ecmp-paths

Attribute Type: uint8

Default Value: 8

Attribute Range: 1-64

#### Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <global>
    <config>
      <max-ecmp-paths>1</max-ecmp-paths> <!-- operation="delete"-->
    </config>
  </global>
</routing>
```

#### Command Syntax

```
maximum-paths <1-64>
```

---

### Configure max static routes

Use this attribute to set the maximum number of static routes.

Attribute Name: max-static-routes

Attribute Type: uint32

Default Value: 4294967294

Attribute Range: 1-4294967294

### Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <global>
    <config>
      <max-static-routes>1</max-static-routes> <!-- operation="delete"-->
    </config>
  </global>
</routing>
```

### Command Syntax

```
max-static-routes <1-4294967294>
```

---

## Configure max fib routes

Use this attribute to set the maximum number of FIB (Forwarding Information Base) routes excluding kernel, connected, and static routes.

Attribute Name: max-fib-routes

Attribute Type: uint32

Attribute Range: 1-16384

### Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <global>
    <config>
      <max-fib-routes>1</max-fib-routes> <!-- operation="delete"-->
    </config>
  </global>
</routing>
```

### Command Syntax

```
max-fib-routes <1-16384>
```

---

## Configure ipv4 enable bfd all interfaces

Use this attribute to enable static BFD on all interfaces.

Attribute Name: ipv4-enable-bfd-all-interfaces

Attribute Type: empty

### Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <global>
```

```

<config>
  </ipv4-enable-bfd-all-interfaces><!-- operation="delete"-->
</config>
</global>
</routing>

```

### Command Syntax

```
ip bfd static all-interfaces
```

---

## Configure ipv6 enable bfd all interfaces

Use this attribute to enable ipv6 static BFD on all interfaces.

Attribute Name: ipv6-enable-bfd-all-interfaces

Attribute Type: empty

### Netconf edit-config payload

```

<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <global>
    <config>
      </ipv6-enable-bfd-all-interfaces><!-- operation="delete"-->
    </config>
  </global>
</routing>

```

### Command Syntax

```
ipv6 bfd static all-interfaces
```

---

## Configure rib options

Use this attribute to debug the ribd process.

Attribute Name: rib-options

Attribute Type: bits (all|events|packet|packet send|packet rcv|packet detail|packet send detail|packet rcv detail|nsm|bfd|monitor|hal events)

### Netconf edit-config payload

```

<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <debug>
    <config>
      <rib-options>all</rib-options> <!-- operation="delete"-->
    </config>
  </debug>
</routing>

```

### Command Syntax

```
debug rib (all|events|packet|packet send|packet rcv|packet detail|packet send detail|packet rcv detail|nsm|bfd|monitor|hal events)
```

---

## Configure ipv4 routing options

Use this attribute to debug ip route.

Attribute Name: ipv4-routing-options

Attribute Type: bits (all|add-route|delete-route|mod-route)

### Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <debug>
  <config>
    <ipv4-routing-options>all</ipv4-routing-options> <!-- operation="delete"-->
  </config>
</debug>
</routing>
```

### Command Syntax

```
debug ip routing (all|add-route|delete-route|mod-route)
```

---

## Configure ipv6 routing options

Use this attribute to debug ipv6 route.

Attribute Name: ipv6-routing-options

Attribute Type: bits (all|add-route|delete-route|mod-route)

### Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <debug>
  <config>
    <ipv6-routing-options>all</ipv6-routing-options> <!-- operation="delete"-->
  </config>
</debug>
</routing>
```

### Command Syntax

```
debug ipv6 routing (all|add-route|delete-route|mod-route)
```

---

## Configure interface name

Use this attribute to create an IPv4 static route where nexthop is interface name.

Attribute Name: interface-name

Attribute Type: string

### Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <static-routes>
  <ipv4>
  <route-vrfs>
```

```

<route-vrf> <!-- operation="delete"-->
  <interface-name>IFNAME</interface-name>
  <config>
    <interface-name>IFNAME</interface-name>
    <gateway-address>A.B.C.D</gateway-address>
    <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
  </config>
  <gateway-address>A.B.C.D</gateway-address>
  <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
</route-vrf>
</route-vrfs>
</ipv4>
</static-routes>
</routing>

```

### Command Syntax

```
ip route (A.B.C.D/M|A.B.C.D A.B.C.D) A.B.C.D IFNAME
```

---

## Configure bfd state

Use this attribute to set fall-over detection.

Attribute Name: bfd-state

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```

<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <static-routes>
    <ipv4>
      <routes>
        <route>
          <gateway-address>A.B.C.D</gateway-address>
          <config>
            <gateway-address>A.B.C.D</gateway-address>
            <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
          </config>
          <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
          <bfd-state>disable</bfd-state> <!-- operation="delete"-->
        </route>
      </routes>
    </ipv4>
  </static-routes>
</routing>

```

### Command Syntax

```
ip static A.B.C.D/M A.B.C.D fall-over-bfd (disable|enable)
```

---

## Configure description

Use this attribute to set description of the static route.

Attribute Name: description

Attribute Type: string

Attribute Name: distance

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-255

Attribute Name: tag

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

Attribute Name: track-id

Attribute Type: uint16

Attribute Range: 1-500

### Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <static-routes>
    <ipv4>
      <routes>
        <route>
          <gateway-address>A.B.C.D</gateway-address>
          <config>
            <gateway-address>A.B.C.D</gateway-address>
            <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
            <distance>1</distance> <!-- operation="delete"-->
            <tag>0</tag> <!-- operation="delete"-->
            <track-id>1</track-id> <!-- operation="delete"-->
          </config>
          <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
          <description>LINE</description> <!-- operation="delete"-->
        </route>
      </routes>
    </ipv4>
  </static-routes>
</routing>
```

### Command Syntax

```
ip route (A.B.C.D/M|A.B.C.D A.B.C.D) A.B.C.D (<1-255>|) (tag <0-4294967295>|)
(track <1-500>|) (description LINE|)
```

---

## Configure destination prefix

Use this attribute to set description of the static route.

Attribute Name: description

Attribute Type: string

Attribute Name: distance

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-255

Attribute Name: tag

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

Attribute Name: track-id

Attribute Type: uint16

Attribute Range: 1-500

### Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <static-routes>
    <ipv4>
      <interface-routes>
        <interface-route>
          <interface-name>IFNAME</interface-name>
          <config>
            <interface-name>IFNAME</interface-name>
            <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
            <distance>1</distance> <!-- operation="delete"-->
            <tag>0</tag> <!-- operation="delete"-->
            <track-id>1</track-id> <!-- operation="delete"-->
          </config>
          <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
          <description>LINE</description> <!-- operation="delete"-->
        </interface-route>
      </interface-routes>
    </ipv4>
  </static-routes>
</routing>
```

### Command Syntax

```
ip route (A.B.C.D/M|A.B.C.D A.B.C.D) IFNAME (<1-255>|) (tag <0-4294967295>|) (track
<1-500>|) (description LINE|)
```

---

## Configure distance

Use this attribute to configure administrative distance for mroute.

Attribute Name: distance

Attribute Type: uint32

Attribute Range: 0-255

Attribute Name: gateway-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <static-routes>
    <ipv4>
      <multicast-routes>
        <multicast-route>
          <protocol-type>default</protocol-type>
          <config>
            <protocol-type>default</protocol-type>
            <source-prefix>A.B.C.D/M</source-prefix>
            <gateway-address>A.B.C.D</gateway-address>
          </config>
          <source-prefix>A.B.C.D/M</source-prefix>
          <distance>0</distance>
        </multicast-route>
      </multicast-routes>
    </ipv4>
  </static-routes>
</routing>
```

### Command Syntax

```
ip mroute A.B.C.D/M ((static|rip|ospf|bgp|isis)|) A.B.C.D (<0-255>|)
```

---

## Configure gateway address

Use this attribute to create an IPv6 static route for a subnet.

This command is supported when following feature are enabled ipv6 feature

Attribute Name: gateway-address

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <static-routes>
    <ipv6>
      <routes>
        <route> <!-- operation="delete"-->
          <gateway-address>X:X::X:X</gateway-address>
          <config>
            <gateway-address>X:X::X:X</gateway-address>
            <destination-prefix>X:X::X:X/M</destination-prefix>
          </config>
          <destination-prefix>X:X::X:X/M</destination-prefix>
        </route>
      </routes>
    </ipv6>
  </static-routes>
</routing>
```

## Command Syntax

```
ipv6 route X:X::X:X/M X:X::X:X
```

---

## Configure route bfd-state

Use this attribute to set fall-over detection.

Attribute Name: bfd-state

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <static-routes>
    <ipv6>
      <routes>
        <route>
          <gateway-address>X:X::X:X</gateway-address>
          <config>
            <gateway-address>X:X::X:X</gateway-address>
            <destination-prefix>X:X::X:X/M</destination-prefix>
          </config>
          <destination-prefix>X:X::X:X/M</destination-prefix>
          <bfd-state>disable</bfd-state> <!-- operation="delete"-->
        </route>
      </routes>
    </ipv6>
  </static-routes>
</routing>
```

## Command Syntax

```
ipv6 static X:X::X:X/M X:X::X:X fall-over-bfd (disable|enable)
```

---

## Configure track id

Use this attribute to set description of the static route.

This command is supported when following feature are enabled ipv6 feature

Attribute Name: description

Attribute Type: string

Attribute Name: distance

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-255

Attribute Name: track-id

Attribute Type: uint16

Attribute Range: 1-500

**Netconf edit-config payload**

```

<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <static-routes>
    <ipv6>
      <routes>
        <route>
          <gateway-address>X:X::X:X</gateway-address>
          <config>
            <gateway-address>X:X::X:X</gateway-address>
            <destination-prefix>X:X::X:X/M</destination-prefix>
            <distance>1</distance> <!-- operation="delete"-->
            <track-id>1</track-id> <!-- operation="delete"-->
          </config>
          <destination-prefix>X:X::X:X/M</destination-prefix>
          <description>LINE</description> <!-- operation="delete"-->
        </route>
      </routes>
    </ipv6>
  </static-routes>
</routing>

```

**Command Syntax**

```
ipv6 route X:X::X:X/M X:X::X:X (<1-255>|) (track <1-500>|) (description LINE|)
```

**Configure interface-routes interface-name**

Use this attribute to create an IPv6 static route where nextthop is interface name.

This command is supported when following feature are enabled ipv6 feature

Attribute Name: interface-name

Attribute Type: string

**Netconf edit-config payload**

```

<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <static-routes>
    <ipv6>
      <interface-routes>
        <interface-route> <!-- operation="delete"-->
          <interface-name>IFNAME</interface-name>
          <config>
            <interface-name>IFNAME</interface-name>
            <destination-prefix>X:X::X:X/M</destination-prefix>
          </config>
          <destination-prefix>X:X::X:X/M</destination-prefix>
        </interface-route>
      </interface-routes>
    </ipv6>
  </static-routes>
</routing>

```

## Command Syntax

```
ipv6 route X:X::X:X/M IFNAME
```

---

## Configure interface-route description

Use this attribute to set description of the static route.

This command is supported when following feature are enabled ipv6 feature

Attribute Name: description

Attribute Type: string

Attribute Name: distance

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-255

Attribute Name: track-id

Attribute Type: uint16

Attribute Range: 1-500

## Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <static-routes>
    <ipv6>
      <interface-routes>
        <interface-route>
          <interface-name>IFNAME</interface-name>
          <config>
            <interface-name>IFNAME</interface-name>
            <destination-prefix>X:X::X:X/M</destination-prefix>
            <distance>1</distance> <!-- operation="delete"-->
            <track-id>1</track-id> <!-- operation="delete"-->
          </config>
          <destination-prefix>X:X::X:X/M</destination-prefix>
          <description>LINE</description> <!-- operation="delete"-->
        </interface-route>
      </interface-routes>
    </ipv6>
  </static-routes>
</routing>
```

## Command Syntax

```
ipv6 route X:X::X:X/M IFNAME (<1-255>|) (track <1-500>|) (description LINE|)
```

---

## Configure gateway-interface-routes interface-name

Use this attribute to create an IPv6 static route where nexthop is interface name and ipv6 prefix.

This command is supported when following feature are enabled ipv6 feature

Attribute Name: interface-name

Attribute Type: string

### Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
<static-routes>
<ipv6>
<gateway-interface-routes>
<gateway-interface-route> <!-- operation="delete"-->
  <interface-name>IFNAME</interface-name>
  <config>
    <interface-name>IFNAME</interface-name>
    <gateway-address>X:X::X:X</gateway-address>
    <destination-prefix>X:X::X:X/M</destination-prefix>
  </config>
  <gateway-address>X:X::X:X</gateway-address>
  <destination-prefix>X:X::X:X/M</destination-prefix>
</gateway-interface-route>
</gateway-interface-routes>
</ipv6>
</static-routes>
</routing>
```

### Command Syntax

```
ipv6 route X:X::X:X/M X:X::X:X IFNAME
```

---

## Configure gateway-interface-route description

Use this attribute to set description of the static route.

This command is supported when following feature are enabled ipv6 feature

Attribute Name: description

Attribute Type: string

Attribute Name: distance

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-255

Attribute Name: track-id

Attribute Type: uint16

Attribute Range: 1-500

### Netconf edit-config payload

```
<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
<static-routes>
<ipv6>
<gateway-interface-routes>
<gateway-interface-route>
```

```

<interface-name>IFNAME</interface-name>
<config>
  <interface-name>IFNAME</interface-name>
  <gateway-address>X:X::X:X</gateway-address>
  <destination-prefix>X:X::X:X/M</destination-prefix>
  <distance>1</distance> <!-- operation="delete"-->
  <track-id>1</track-id> <!-- operation="delete"-->
</config>
<gateway-address>X:X::X:X</gateway-address>
<destination-prefix>X:X::X:X/M</destination-prefix>
<description>LINE</description> <!-- operation="delete"-->
</gateway-interface-route>
</gateway-interface-routes>
</ipv6>
</static-routes>
</routing>

```

## Command Syntax

```

ipv6 route X:X::X:X/M X:X::X:X IFNAME (<1-255>|) (track <1-500>|) (description
LINE|)

```

---

## Configure source prefix

Use this attribute to configure administrative distance for mroute.

This command is supported when following feature are enabled ipv6 feature

Attribute Name: distance

Attribute Type: uint32

Attribute Range: 0-255

Attribute Name: gateway-mroute

Attribute Type: inet:ipv6-address

## Netconf edit-config payload

```

<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <static-routes>
  <ipv6>
  <multicast-routes>
  <multicast-route>
    <protocol-type>default</protocol-type>
    <config>
      <protocol-type>default</protocol-type>
      <source-prefix>X:X::X:X/M</source-prefix>
    </config>
    <source-prefix>X:X::X:X/M</source-prefix>
  </multicast-route>
  </multicast-routes>
  </ipv6>
  </static-routes>
</routing>

```

```

</nexthop>
</multicast-route>
</multicast-routes>
</ipv6>
</static-routes>
</routing>

```

## Command Syntax

```
ipv6 mroute X:X::X:X/M ((static|rip|ospf|bgp|isis)|) X:X::X:X (<0-255>|)
```

---

## Configure ipv4 enable bfd

Use this attribute to enable or disable Bidirectional Forwarding Detection static routes.

This command is supported when following feature are enabled bfd feature

Attribute Name: ipv4-enable-bfd

Attribute Type: enum (enable|disable)

## Netconf edit-config payload

```

<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <bfd>
      <config>
        <ipv4-enable-bfd>enable</ipv4-enable-bfd> <!-- operation="delete"-->
      </config>
    </bfd>
  </interface>
</interfaces>
</routing>

```

## Command Syntax

```
ip static bfd (enable|disable)
```

---

## Configure ipv6 enable bfd

Use this attribute to enable or disable Bidirectional Forwarding Detection static routes.

This command is supported when following feature are enabled bfd feature

Attribute Name: ipv6-enable-bfd

Attribute Type: enum (enable|disable)

## Netconf edit-config payload

```

<routing xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <interfaces>

```

```
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<bfd>
<config>
  <ipv6-enable-bfd>enable</ipv6-enable-bfd> <!-- operation="delete"-->
</config>
</bfd>
</interface>
</interfaces>
</routing>
```

### Command Syntax

```
ipv6 static bfd (enable|disable)
```

---

## snmp restart rib

### Netconf RPC payload

```
<rib-snmp-restart xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib"/>
```

### Command Syntax

```
snmp restart rib
```

---

## clear ip route kernel

### Netconf RPC payload

```
<clear-ip-stale-kernel-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib"/>
```

### Command Syntax

```
clear ip route kernel
```

---

## clear ip kernel route

### Netconf RPC payload

```
<clear-ip-kernel-route xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib"/>
```

### Command Syntax

```
clear ip kernel route
```

---

## clear ipv6 route kernel

### Netconf RPC payload

```
<clear-ipv6-stale-kernel-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib"/>
```

### Command Syntax

```
clear ipv6 route kernel
```

---

## clear ip route \*

### Netconf RPC payload

```
<clear-ip-route-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib"/>
```

### Command Syntax

```
clear ip route *
```

---

## clear ip route A.B.C.D/M

Attribute Name: prefix-address

Attribute Type: string

### Netconf RPC payload

```
<clear-ip-route xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">  
<prefix-address>A.B.C.D/M</prefix-address>  
</clear-ip-route>
```

### Command Syntax

```
clear ip route A.B.C.D/M
```

---

## clear ipv4 route \*

### Netconf RPC payload

```
<clear-ipv4-route-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib"/>
```

### Command Syntax

```
clear ipv4 route *
```

---

## clear ipv4 route A.B.C.D/M

Attribute Name: prefix-address

Attribute Type: string

### Netconf RPC payload

```
<clear-ipv4-route xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">  
<prefix-address>A.B.C.D/M</prefix-address>
```

---

```
</clear-ipv4-route>
```

### Command Syntax

```
clear ipv4 route A.B.C.D/M
```

---

## clear ipv6 route \*

### Netconf RPC payload

```
<clear-ipv6-route-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib"/>
```

### Command Syntax

```
clear ipv6 route *
```

---

## clear ipv6 route X:X::X:X/M

Attribute Name: prefix-ipv6-address

Attribute Type: string

### Netconf RPC payload

```
<clear-ipv6-route xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
<prefix-ipv6-address>X:X::X:X/M</prefix-ipv6-address>
</clear-ipv6-route>
```

### Command Syntax

```
clear ipv6 route X:X::X:X/M
```

---

## debug rib (all|events|packet|packet send|packet rcv|packet detail|packet send detail|packet rcv detail|nsm|bfd|monitor|hal events|hal ipc)

Attribute Name: terminal-debug-options

Attribute Type: bits (all|events|packet|packet send|packet rcv|packet detail|packet send detail|packet rcv detail|nsm|bfd|monitor|hal events|hal ipc)

### Netconf RPC payload

```
<rib-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
<terminal-debug-options>all</terminal-debug-options>
</rib-terminal-debug-on>
```

### Command Syntax

```
debug rib (all|events|packet|packet send|packet rcv|packet detail|packet send
detail|packet rcv detail|nsm|bfd|monitor|hal events|hal ipc)
```

---

## no debug rib (all|events|packet|packet send|packet rcv|packet detail|packet send detail|packet rcv detail|nsm|bfd|monitor|hal events|hal ipc)

Attribute Name: terminal-debug-options

---

Attribute Type: bits (all|events|packet|packet send|packet recv|packet detail|packet send detail|packet recv detail|nsm|bfd|monitor|hal events|hal ipc)

### Netconf RPC payload

```
<rib-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <terminal-debug-options>all</terminal-debug-options>
</rib-terminal-debug-off>
```

### Command Syntax

```
no debug rib (all|events|packet|packet send|packet recv|packet detail|packet send
  detail|packet recv detail|nsm|bfd|monitor|hal events|hal ipc)
```

---

## debug ip routing (all|add-route|delete-route|mod-route)

Attribute Name: terminal-debug-options

Attribute Type: bits (all|add-route|delete-route|mod-route)

### Netconf RPC payload

```
<rib-terminal-debug-ipv4-routing-on xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-rib">
  <terminal-debug-options>all</terminal-debug-options>
</rib-terminal-debug-ipv4-routing-on>
```

### Command Syntax

```
debug ip routing (all|add-route|delete-route|mod-route)
```

---

## no debug ip routing (all|add-route|delete-route|mod-route)

Attribute Name: terminal-debug-options

Attribute Type: bits (all|add-route|delete-route|mod-route)

### Netconf RPC payload

```
<rib-terminal-debug-ipv4-routing-off xmlns="http://www.ipinfusion.com/yang/
ocnos/ipi-rib">
  <terminal-debug-options>all</terminal-debug-options>
</rib-terminal-debug-ipv4-routing-off>
```

### Command Syntax

```
no debug ip routing (all|add-route|delete-route|mod-route)
```

---

## debug ipv6 routing (all|add-route|delete-route|mod-route)

Attribute Name: terminal-debug-options

Attribute Type: bits (all|add-route|delete-route|mod-route)

### Netconf RPC payload

```
<rib-terminal-debug-ipv6-routing-on xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-rib">
  <terminal-debug-options>all</terminal-debug-options>
```

```
</rib-terminal-debug-ipv6-routing-on>
```

## Command Syntax

```
debug ipv6 routing (all|add-route|delete-route|mod-route)
```

---

## no debug ipv6 routing (all|add-route|delete-route|mod-route)

Attribute Name: terminal-debug-options

Attribute Type: bits (all|add-route|delete-route|mod-route)

## Netconf RPC payload

```
<rib-terminal-debug-ipv6-routing-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib">
  <terminal-debug-options>all</terminal-debug-options>
</rib-terminal-debug-ipv6-routing-off>
```

## Command Syntax

```
no debug ipv6 routing (all|add-route|delete-route|mod-route)
```

---

# IPI-RIB-VRF

---

## Configure ipv4 enable bfd all interfaces

Use this attribute to enable static BFD on all interfaces.

Attribute Name: ipv4-enable-bfd-all-interfaces

Attribute Type: empty

## Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
        <config>
          <ipv4-enable-bfd-all-interfaces><!-- operation="delete"-->
        </config>
      </global>
    </vrf>
  </network-instance>
</network-instances>
```

## Command Syntax

```
ip bfd vrf NAME static all-interfaces
```

## Configure ipv6 enable bfd all interfaces

Use this attribute to enable ipv6 static BFD on all interfaces.

Attribute Name: ipv6-enable-bfd-all-interfaces

Attribute Type: empty

## Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <global xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
        <config>
          </ipv6-enable-bfd-all-interfaces><!-- operation="delete"-->
        </config>
      </global>
    </vrf>
  </network-instance>
</network-instances>
```

## Command Syntax

```
ipv6 bfd vrf NAME static all-interfaces
```

## Configure enable global table lookup

Use this attribute to create an IPv4 vrf static route with gateway in default vrf table.

Attribute Name: enable-global-table-lookup

Attribute Type: empty

## Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
```

```

<vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
  <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
    <ipv4>
      <gateway-interface-routes-global>
        <gateway-interface-route-global> <!-- operation="delete"-->
          </enable-global-table-lookup>
          <config>
            </enable-global-table-lookup>
            <interface-name>IFNAME</interface-name>
            <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
          </config>
          <interface-name>IFNAME</interface-name>
          <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
        </gateway-interface-route-global>
      </gateway-interface-routes-global>
    </ipv4>
  </static-routes>
</vrf>
</network-instance>
</network-instances>

```

## Command Syntax

```
ip route vrf NAME (A.B.C.D/M|A.B.C.D A.B.C.D) IFNAME global
```

---

## Configure interface name

Use this attribute to create an IPv4 static route where nexthop is a global interface.

Attribute Name: interface-name

Attribute Type: string

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
  <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
    <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
      <ipv4>
        <gateway-interface-routes-global>
          <gateway-interface-route-global>
            </enable-global-table-lookup>
          <config>
            </enable-global-table-lookup><!-- operation="delete"-->
            <interface-name>IFNAME</interface-name>

```

```

        <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
    </config>
    <interface-name>IFNAME</interface-name>
    <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
</gateway-interface-route-global>
</gateway-interface-routes-global>
</ipv4>
</static-routes>
</vrf>
</network-instance>
</network-instances>

```

## Command Syntax

```
ip route vrf NAME (A.B.C.D/M|A.B.C.D A.B.C.D) IFNAME global IFNAME
```

---

## Configure track id

Use this attribute to track a object.

Attribute Name: track-id

Attribute Type: uint16

Attribute Range: 1-500

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
        <ipv4>
          <gateway-interface-routes-global>
            <gateway-interface-route-global>
              </enable-global-table-lookup>
            <config>
              </enable-global-table-lookup><!-- operation="delete"-->
              <interface-name>IFNAME</interface-name>
              <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
            </config>
            <interface-name>IFNAME</interface-name>
            <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
            <track-id>1</track-id> <!-- operation="delete"-->
          </gateway-interface-route-global>
        </gateway-interface-routes-global>
      </ipv4>
    </vrf>
  </network-instance>
</network-instances>

```

```

</static-routes>
</vrf>
</network-instance>
</network-instances>

```

## Command Syntax

```
ip route vrf NAME (A.B.C.D/M|A.B.C.D A.B.C.D) IFNAME global track <1-500>
```

---

## Configure bfd state

Use this attribute to set fall-over detection.

Attribute Name: bfd-state

Attribute Type: enum (disable|enable)

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
        <ipv4>
          <routes>
            <route>
              <gateway-address>A.B.C.D</gateway-address>
              <config>
                <gateway-address>A.B.C.D</gateway-address>
                <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
              </config>
              <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
              <bfd-state>disable</bfd-state> <!-- operation="delete"-->
            </route>
          </routes>
        </ipv4>
      </static-routes>
    </vrf>
  </network-instance>
</network-instances>

```

## Command Syntax

```
ip static vrf NAME A.B.C.D/M A.B.C.D fall-over-bfd (disable|enable)
```

---

## Configure instance type

Use this attribute to create an IPv4 static route where nexthop is interface name.

Attribute Name: interface-name

Attribute Type: string

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
        <ipv4>
          <routes>
            <route>
              <gateway-address>A.B.C.D</gateway-address>
              <config>
                <gateway-address>A.B.C.D</gateway-address>
                <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
              </config>
                <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
            <gateway-interface-routes>
              <gateway-interface-route <!-- operation="delete"-->
                <interface-name>IFNAME</interface-name>
                <config>
                  <interface-name>IFNAME</interface-name>
                </config>
              </gateway-interface-route>
            </gateway-interface-routes>
          </route>
        </routes>
      </ipv4>
    </static-routes>
  </vrf>
</network-instance>
</network-instances>
```

### Command Syntax

```
ip route vrf NAME A.B.C.D/M A.B.C.D IFNAME
```

---

## Configure description

Use this attribute to set description of the static route.

Attribute Name: description

Attribute Type: string

Attribute Name: distance

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-255

Attribute Name: tag

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

Attribute Name: track-id

Attribute Type: uint16

Attribute Range: 1-500

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
        <ipv4>
          <routes>
            <route>
              <gateway-address>A.B.C.D</gateway-address>
              <config>
                <gateway-address>A.B.C.D</gateway-address>
                <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
              </config>
              <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
            <gateway-interface-routes>
              <gateway-interface-route>
                <interface-name>IFNAME</interface-name>
                <config>
                  <interface-name>IFNAME</interface-name>
                  <distance>1</distance> <!-- operation="delete"-->
                  <tag>0</tag> <!-- operation="delete"-->
                  <track-id>1</track-id> <!-- operation="delete"-->
                </config>
                <description>LINE</description> <!-- operation="delete"-->
              </gateway-interface-route>
            </gateway-interface-routes>
          </ipv4>
        </static-routes>
      </vrf>
    </network-instance>
  </network-instances>
```

```

    </gateway-interface-routes>
  </route>
</routes>
</ipv4>
</static-routes>
</vrf>
</network-instance>
</network-instances>

```

## Command Syntax

```
ip route vrf NAME (A.B.C.D/M|A.B.C.D A.B.C.D) A.B.C.D IFNAME (<1-255>|) (tag <0-4294967295>|) (track <1-500>|) (description LINE|)
```

---

## Configure instance name

Use this attribute to create an IPv4 vrf static route with gateway in default vrf table.

Attribute Name: enable-global-table-lookup

Attribute Type: empty

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
  <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
    <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
      <ipv4>
        <routes>
          <route>
            <gateway-address>A.B.C.D</gateway-address>
            <config>
              <gateway-address>A.B.C.D</gateway-address>
              <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
            </config>
            <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
          <interface-routes-global>
            <interface-route-global> <!-- operation="delete"-->
              </enable-global-table-lookup>
            <config>
              </enable-global-table-lookup>
              <interface-name>IFNAME</interface-name>
            </config>
            <interface-name>IFNAME</interface-name>
          </interface-route-global>

```

```

    </interface-routes-global>
  </route>
</routes>
</ipv4>
</static-routes>
</vrf>
</network-instance>
</network-instances>

```

## Command Syntax

```
ip route vrf NAME (A.B.C.D/M|A.B.C.D A.B.C.D) A.B.C.D IFNAME global
```

---

## Configure destination prefix

Use this attribute to track a object.

Attribute Name: track-id

Attribute Type: uint16

Attribute Range: 1-500

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
        <ipv4>
          <routes>
            <route>
              <gateway-address>A.B.C.D</gateway-address>
              <config>
                <gateway-address>A.B.C.D</gateway-address>
                <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
              </config>
              <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
            </interface-routes-global>
            <interface-route-global>
              </enable-global-table-lookup>
              <config>
                </enable-global-table-lookup><!-- operation="delete"-->
                <interface-name>IFNAME</interface-name>
              </config>
              <interface-name>IFNAME</interface-name>
              <track-id>1</track-id> <!-- operation="delete"-->
            </interface-route-global>
          </routes>
        </ipv4>
      </static-routes>
    </vrf>
  </network-instance>
</network-instances>

```

```

        </interface-route-global>
    </interface-routes-global>
</route>
</routes>
</ipv4>
</static-routes>
</vrf>
</network-instance>
</network-instances>

```

## Command Syntax

```
ip route vrf NAME (A.B.C.D/M|A.B.C.D A.B.C.D) A.B.C.D IFNAME global track <1-500>
```

---

## Configure distance

Use this attribute to set description of the static route.

Attribute Name: description

Attribute Type: string

Attribute Name: distance

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-255

Attribute Name: tag

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

Attribute Name: track-id

Attribute Type: uint16

Attribute Range: 1-500

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
        <ipv4>
          <interface-routes>
            <interface-route>

```

```

    <interface-name>IFNAME</interface-name>
    <config>
      <interface-name>IFNAME</interface-name>
      <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
      <distance>1</distance> <!-- operation="delete"-->
      <tag>0</tag> <!-- operation="delete"-->
      <track-id>1</track-id> <!-- operation="delete"-->
    </config>
    <destination-prefix>A.B.C.D/M|A.B.C.D A.B.C.D</destination-prefix>
    <description>LINE</description> <!-- operation="delete"-->
  </interface-route>
</interface-routes>
</ipv4>
</static-routes>
</vrf>
</network-instance>
</network-instances>

```

## Command Syntax

```

ip route vrf NAME (A.B.C.D/M|A.B.C.D A.B.C.D) IFNAME (<1-255>|) (tag <0-4294967295>|) (track <1-500>|) (description LINE|)

```

---

## Configure source prefix

Use this attribute to configure administrative distance for mroute.

Attribute Name: distance

Attribute Type: uint32

Attribute Range: 0-255

Attribute Name: gateway-address

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
  <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
    <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
      <ipv4>
        <multicast-routes>
          <multicast-route>
            <protocol-type>default</protocol-type>
          </multicast-route>
        </multicast-routes>
      </ipv4>
    </static-routes>
  </vrf>
</network-instance>
</network-instances>

```

```

        <protocol-type>default</protocol-type>
        <source-prefix>A.B.C.D/M</source-prefix>
        <gateway-address>A.B.C.D</gateway-address>
    </config>
    <source-prefix>A.B.C.D/M</source-prefix>
    <distance>0</distance>
</multicast-route>
</multicast-routes>
</ipv4>
</static-routes>
</vrf>
</network-instance>
</network-instances>

```

## Command Syntax

```
ip mroute vrf NAME A.B.C.D/M ((static|rip|ospf|bgp|isis)|) A.B.C.D (<0-255>|)
```

---

## Configure destination prefix

Network Instance Type

Attribute Name: instance-type

Attribute Type: enum (vrf|mac-vrf|l2ni|vpls|vpws|evpn|cross-connect|bridge-domain)

Attribute Name: destination-prefix

Attribute Type: string

Attribute Name: interface-name

Attribute Type: string

Attribute Name: enable-ipv6-global-table-lookup

Attribute Type: empty

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance> <!-- operation="delete"-->
    <instance-type>vrf</instance-type>
    <config>
      <instance-type>vrf</instance-type>
      <instance-name>WORD</instance-name>
    </config>
    <instance-name>WORD</instance-name>
  </network-instance>
</network-instances>
<static-routes>
<ipv6>
<interface-routes-global>
<interface-route-global>
  <destination-prefix>X:X::X:X/M</destination-prefix>
  <interface-name>IFNAME</interface-name>
  </enable-ipv6-global-table-lookup>
</interface-route-global>

```

```

    </interface-routes-global>
  </ipv6>
</static-routes>
</network-instance>
</network-instances>

```

## Command Syntax

```
ipv6 route vrf NAME X:X::X:X/M IFNAME global
```

---

## Configure enable ipv6 global table lookup

Use this attribute to track a object.

Attribute Name: track-id

Attribute Type: uint16

Attribute Range: 1-500

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
        <ipv6>
          <interface-routes-global>
            <interface-route-global>
              </enable-ipv6-global-table-lookup>
              <config>
                </enable-ipv6-global-table-lookup><!-- operation="delete"-->
                <interface-name>IFNAME</interface-name>
                <destination-prefix>X:X::X:X/M</destination-prefix>
              </config>
              <interface-name>IFNAME</interface-name>
              <destination-prefix>X:X::X:X/M</destination-prefix>
              <track-id>1</track-id> <!-- operation="delete"-->
            </interface-route-global>
          </interface-routes-global>
        </ipv6>
      </static-routes>
    </vrf>
  </network-instance>
</network-instances>

```

## Command Syntax

```
ipv6 route vrf NAME X:X::X:X/M IFNAME global track <1-500>
```

---

## Configure gateway address

Network Instance Type

Attribute Name: instance-type

Attribute Type: enum (vrf|mac-vrf|l2ni|vpls|vpws|evpn|cross-connect|bridge-domain)

Attribute Name: destination-prefix

Attribute Type: string

Attribute Name: gateway-address

Attribute Type: inet:ipv6-address

Attribute Name: interface-name

Attribute Type: string

Attribute Name: enable-ipv6-global-table-lookup

Attribute Type: empty

## Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance> <!-- operation="delete"-->
    <instance-type>vrf</instance-type>
    <config>
      <instance-type>vrf</instance-type>
      <instance-name>WORD</instance-name>
    </config>
    <instance-name>WORD</instance-name>
  <static-routes>
    <ipv6>
      <gateway-interface-routes-global>
      <gateway-interface-route-global>
        <destination-prefix>X:X::X:X/M</destination-prefix>
        <gateway-address>X:X::X:X</gateway-address>
        <interface-name>IFNAME</interface-name>
        </enable-ipv6-global-table-lookup>
        </gateway-interface-route-global>
      </gateway-interface-routes-global>
    </ipv6>
  </static-routes>
</network-instance>
</network-instances>
```

## Command Syntax

```
ipv6 route vrf NAME X:X::X:X/M X:X::X:X IFNAME global
```

---

## Configure gateway address

Use this attribute to track a object.

Attribute Name: track-id

Attribute Type: uint16

Attribute Range: 1-500

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
  <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
    <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
      <ipv6>
        <gateway-interface-routes-global>
          <gateway-interface-route-global>
            </enable-ipv6-global-table-lookup>
            <config>
              </enable-ipv6-global-table-lookup><!-- operation="delete"-->
              <interface-name>IFNAME</interface-name>
              <gateway-address>X:X::X:X</gateway-address>
              <destination-prefix>X:X::X:X/M</destination-prefix>
            </config>
            <interface-name>IFNAME</interface-name>
            <gateway-address>X:X::X:X</gateway-address>
            <destination-prefix>X:X::X:X/M</destination-prefix>
            <track-id>1</track-id> <!-- operation="delete"-->
          </gateway-interface-route-global>
        </gateway-interface-routes-global>
      </ipv6>
    </static-routes>
  </vrf>
</network-instance>
</network-instances>
```

### Command Syntax

```
ipv6 route vrf NAME X:X::X:X/M X:X::X:X IFNAME global track <1-500>
```

---

## Configure route bfd-state

Use this attribute to set fall-over detection.

Attribute Name: bfd-state

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
        <ipv6>
          <routes>
            <route>
              <gateway-address>X:X::X:X</gateway-address>
              <config>
                <gateway-address>X:X::X:X</gateway-address>
                <destination-prefix>X:X::X:X/M</destination-prefix>
              </config>
              <destination-prefix>X:X::X:X/M</destination-prefix>
              <bfd-state>disable</bfd-state> <!-- operation="delete"-->
            </route>
          </routes>
        </ipv6>
      </static-routes>
    </vrf>
  </network-instance>
</network-instances>
```

### Command Syntax

```
ipv6 static vrf NAME X:X::X:X/M X:X::X:X fall-over-bfd (disable|enable)
```

---

## Configure out-interfaces interface-name

Use this attribute to create an IPv6 static route where nexthop is interface name.

Attribute Name: interface-name

Attribute Type: string

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
```

```

</config>
  <instance-type>vrf</instance-type>
<vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
  <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
    <ipv6>
      <routes>
        <route>
          <gateway-address>X:X::X:X</gateway-address>
          <config>
            <gateway-address>X:X::X:X</gateway-address>
            <destination-prefix>X:X::X:X/M</destination-prefix>
          </config>
          <destination-prefix>X:X::X:X/M</destination-prefix>
        <out-interfaces>
          <out-interface> <!-- operation="delete"-->
            <interface-name>IFNAME</interface-name>
            <config>
              <interface-name>IFNAME</interface-name>
            </config>
          </out-interface>
        </out-interfaces>
      </route>
    </routes>
  </ipv6>
</static-routes>
</vrf>
</network-instance>
</network-instances>

```

## Command Syntax

```
ipv6 route vrf NAME X:X::X:X/M X:X::X:X IFNAME
```

---

## Configure out-interface description

Use this attribute to set description of the static route.

This command is supported when following feature are enabled ipv6 feature

Attribute Name: description

Attribute Type: string

Attribute Name: track-id

Attribute Type: uint16

Attribute Range: 1-500

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>

```

```

    <instance-name>WORD</instance-name>
    <instance-type>vrf</instance-type>
</config>
    <instance-type>vrf</instance-type>
<vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
    <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
    <ipv6>
    <routes>
    <route>
        <gateway-address>X:X::X:X</gateway-address>
        <config>
            <gateway-address>X:X::X:X</gateway-address>
            <destination-prefix>X:X::X:X/M</destination-prefix>
        </config>
        <destination-prefix>X:X::X:X/M</destination-prefix>
    <out-interfaces>
    <out-interface>
        <interface-name>IFNAME</interface-name>
        <config>
            <interface-name>IFNAME</interface-name>
            <track-id>1</track-id> <!-- operation="delete"-->
        </config>
            <description>LINE</description> <!-- operation="delete"-->
        </out-interface>
    </out-interfaces>
    </route>
    </routes>
    </ipv6>
    </static-routes>
    </vrf>
</network-instance>
</network-instances>

```

## Command Syntax

```
ipv6 route vrf NAME X:X::X:X/M X:X::X:X IFNAME (track <1-500>|) (description LINE|)
```

---

## Configure interface-routes interface-name

Use this attribute to create an IPv6 static route where nexthop is interface name.

This command is supported when following feature are enabled ipv6 feature

Attribute Name: interface-name

Attribute Type: string

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
    <network-instance>
        <instance-name>NAME</instance-name>
        <config>

```

```

    <instance-name>WORD</instance-name>
    <instance-type>vrf</instance-type>
</config>
    <instance-type>vrf</instance-type>
<vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
    <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
    <ipv6>
    <interface-routes>
    <interface-route> <!-- operation="delete"-->
        <interface-name>IFNAME</interface-name>
        <config>
            <interface-name>IFNAME</interface-name>
            <destination-prefix>X:X::X:X/M</destination-prefix>
        </config>
        <destination-prefix>X:X::X:X/M</destination-prefix>
    </interface-route>
    </interface-routes>
</ipv6>
</static-routes>
</vrf>
</network-instance>
</network-instances>

```

## Command Syntax

```
ipv6 route vrf NAME X:X::X:X/M IFNAME
```

---

## Configure interface-route description

Use this attribute to set description of the static route.

This command is supported when following feature are enabled ipv6 feature

Attribute Name: description

Attribute Type: string

Attribute Name: track-id

Attribute Type: uint16

Attribute Range: 1-500

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
    <network-instance>
        <instance-name>NAME</instance-name>
        <config>
            <instance-name>WORD</instance-name>
            <instance-type>vrf</instance-type>
        </config>
        <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
        <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">

```

```

<ipv6>
<interface-routes>
<interface-route>
  <interface-name>IFNAME</interface-name>
  <config>
    <interface-name>IFNAME</interface-name>
    <destination-prefix>X:X::X:X/M</destination-prefix>
    <track-id>1</track-id> <!-- operation="delete"-->
  </config>
  <destination-prefix>X:X::X:X/M</destination-prefix>
  <description>LINE</description> <!-- operation="delete"-->
</interface-route>
</interface-routes>
</ipv6>
</static-routes>
</vrf>
</network-instance>
</network-instances>

```

## Command Syntax

```
ipv6 route vrf NAME X:X::X:X/M IFNAME (track <1-500>|) (description LINE|)
```

---

## Configure protocol type

Use this attribute to configure administrative distance for mroute.

This command is supported when following feature are enabled ipv6 feature

Attribute Name: distance

Attribute Type: uint32

Attribute Range: 0-255

Attribute Name: gateway-mroute

Attribute Type: inet:ipv6-address

## Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>NAME</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
  <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
    <static-routes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
      <ipv6>
        <multicast-routes>
          <multicast-route>
            <protocol-type>default</protocol-type>

```

```

    <config>
      <protocol-type>default</protocol-type>
      <source-prefix>X:X::X:X/M</source-prefix>
    </config>
    <source-prefix>X:X::X:X/M</source-prefix>
    <nexthop>
    <config>
      <gateway-mroute>X:X::X:X</gateway-mroute>
      <distance>0</distance>
    </config>
  </nexthop>
</multicast-route>
</multicast-routes>
</ipv6>
</static-routes>
</vrf>
</network-instance>
</network-instances>

```

### Command Syntax

```
ipv6 mroute vrf NAME X:X::X:X/M ((static|rip|ospf|bgp|isis)|) X:X::X:X (<0-255>|)
```

---

### clear ip route vrf NAME \*

Attribute Name: vrf-name

Attribute Type: string

#### Netconf RPC payload

```

<clear-ip-vrf-route-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-
vrf">
  <vrf-name>NAME</vrf-name>
</clear-ip-vrf-route-all>

```

### Command Syntax

```
clear ip route vrf NAME *
```

---

### clear ip route vrf NAME A.B.C.D/M

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: prefix-address

Attribute Type: string

#### Netconf RPC payload

```

<clear-ip-vrf-route xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
  <vrf-name>NAME</vrf-name>
  <prefix-address>A.B.C.D/M</prefix-address>
</clear-ip-vrf-route>

```

---

## Command Syntax

```
clear ip route vrf NAME A.B.C.D/M
```

---

## clear ipv4 route vrf NAME \*

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<clear-ipv4-vrf-route-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-
vrf">
  <vrf-name>NAME</vrf-name>
</clear-ipv4-vrf-route-all>
```

## Command Syntax

```
clear ipv4 route vrf NAME *
```

---

## clear ipv4 route vrf NAME A.B.C.D/M

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: prefix-address

Attribute Type: string

### Netconf RPC payload

```
<clear-ipv4-vrf-route xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
  <vrf-name>NAME</vrf-name>
  <prefix-address>A.B.C.D/M</prefix-address>
</clear-ipv4-vrf-route>
```

## Command Syntax

```
clear ipv4 route vrf NAME A.B.C.D/M
```

---

## clear ipv6 route vrf NAME \*

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<clear-ipv6-vrf-route-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-
vrf">
  <vrf-name>NAME</vrf-name>
</clear-ipv6-vrf-route-all>
```

## Command Syntax

```
clear ipv6 route vrf NAME *
```

---

## clear ipv6 route vrf NAME X:X::X:X/M

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: prefix-ipv6-address

Attribute Type: string

### Netconf RPC payload

```
<clear-ipv6-vrf-route xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rib-vrf">
  <vrf-name>NAME</vrf-name>
  <prefix-ipv6-address>X:X::X:X/M</prefix-ipv6-address>
</clear-ipv6-vrf-route>
```

### Command Syntax

```
clear ipv6 route vrf NAME X:X::X:X/M
```

---

## IPI-OSPF

---

### Configure area interface config mode

Use this attribute to set the OSPF area interface mode operation. Enabling this makes OSPF compatible with OpenConfig datamodel.

Attribute Name: area-interface-config-mode

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <global>
    <config>
      </area-interface-config-mode><!-- operation="delete"-->
    </config>
  </global>
</ospfv2>
```

### Command Syntax

```
ospf area-interface-config-mode
```

---

### Configure enable multi instance capability

Use this attribute to enable OSPF multiple instances capability.

Attribute Name: enable-multi-instance-capability

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
```

```

<global>
<config>
  </enable-multi-instance-capability><!-- operation="delete"-->
</config>
</global>
</ospfv2>

```

### Command Syntax

```
enable ext-ospf-multi-inst
```

---

## Configure grace period

Use this attribute to set the grace period for restarting the router OSPF.

This command is supported when following feature are enabled Restart capability

Attribute Name: grace-period

Attribute Type: uint16

Default Value: 120

Attribute Range: 2-1800

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<global>
<graceful-restart>
<config>
  <grace-period>2</grace-period> <!-- operation="delete"-->
</config>
</graceful-restart>
</global>
</ospfv2>

```

### Command Syntax

```
ospf restart grace-period <2-1800>
```

---

## Configure max grace period

Use this attribute to set the maximum grace period. Act as helper only if received grace-period is less than this value.

This command is supported when following feature are enabled Restart capability

Attribute Name: max-grace-period

Attribute Type: uint16

Attribute Range: 2-1800

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<global>
<graceful-restart>
<helper>

```

```
<config>
  <max-grace-period>2</max-grace-period> <!-- operation="delete"-->
</config>
</helper>
</graceful-restart>
</global>
</ospfv2>
```

### Command Syntax

```
ospf restart helper max-grace-period <2-1800>
```

---

## Configure disable all neighbors

Use this attribute to prevent the router OSPF from acting as helper for any neighbor.

This command is supported when following feature are enabled Restart capability

Attribute Name: disable-all-neighbors

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <global>
    <graceful-restart>
      <helper>
        <config>
          </disable-all-neighbors><!-- operation="delete"-->
        </config>
      </helper>
    </graceful-restart>
  </global>
</ospfv2>
```

### Command Syntax

```
ospf restart helper never
```

---

## Configure disable neighbor

Use this attribute to set the neighbor router-id for which never act as helper.

This command is supported when following feature are enabled Restart capability

Attribute Name: disable-neighbor

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <global>
    <graceful-restart>
      <helper>
        <config>
```

```

    <disable-neighbor>A.B.C.D</disable-neighbor> <!-- operation="delete"-->
</config>
</helper>
</graceful-restart>
</global>
</ospfv2>

```

### Command Syntax

```
ospf restart helper never router-id A.B.C.D
```

---

## Configure ospf id

Use this attribute to set the OSPF process ID.

Attribute Name: ospf-id

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: vrf-name

Attribute Type: string

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process> <!-- operation="delete"-->
    <ospf-id>0</ospf-id>
    <config>
        <ospf-id>0</ospf-id>
        <vrf-name>WORD</vrf-name>
    </config>
</process>
</processes>
</ospfv2>

```

### Command Syntax

```
router ospf (<0-65535>|) (WORD|)
```

---

## Configure router id

Use this attribute to set a router ID for the OSPF process. Configure each router OSPF with an unique router ID.

Attribute Name: router-id

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
    <ospf-id>0</ospf-id>
    <config>

```

```

    <ospf-id>0</ospf-id>
  </config>
  <router-id>A.B.C.D</router-id> <!-- operation="delete"-->
</process>
</processes>
</ospfv2>

```

### Command Syntax

```
router-id A.B.C.D
```

---

## Configure process router-id

Use this attribute to set a router ID for the OSPF process. Configure each router OSPF with an unique router ID.

Attribute Name: router-id

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
  <process>
    <ospf-id>0</ospf-id>
    <config>
      <ospf-id>0</ospf-id>
    </config>
    <router-id>A.B.C.D</router-id> <!-- operation="delete"-->
  </process>
</processes>
</ospfv2>

```

### Command Syntax

```
ospf router-id A.B.C.D
```

---

## Configure flood reduction

Use this attribute to enable flood reduction on all OSPF interfaces.

Attribute Name: flood-reduction

Attribute Type: empty

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
  <process>
    <ospf-id>0</ospf-id>
    <config>
      <ospf-id>0</ospf-id>
    </config>
    </flood-reduction><!-- operation="delete"-->
  </process>

```

```
</processes>
</ospfv2>
```

## Command Syntax

```
ospf flood-reduction
```

---

## Configure rfc1583 compatibility

Use this attribute to restore the method used to calculate summary route costs per RFC 1583.

Attribute Name: rfc1583-compatibility

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
  </rfc1583-compatibility><!-- operation="delete"-->
</process>
</processes>
</ospfv2>
```

## Command Syntax

```
compatible rfc1583
```

---

## Configure database summary

Use this attribute to enable the database summary list optimization.

Attribute Name: database-summary

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
  </database-summary><!-- operation="delete"-->
</process>
</processes>
</ospfv2>
```

---

## Command Syntax

```
enable db-summary-opt
```

---

## Configure bfd enable all interfaces

Use this attribute to enable Bidirectional Forwarding Detection (BFD) on all interfaces.

Attribute Name: bfd-enable-all-interfaces

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
      </bfd-enable-all-interfaces><!-- operation="delete"-->
    </process>
  </processes>
</ospfv2>
```

## Command Syntax

```
bfd all-interfaces
```

---

## Configure log adjacency changes

Use this attribute for the router to send a SYSLOG message when an OSPF neighbor goes up or down.

Attribute Name: log-adjacency-changes

Attribute Type: enum (brief|detail)

Default Value: brief

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
        <log-adjacency-changes>brief</log-adjacency-changes> <!-- operation="delete"-->
      </config>
    </process>
  </processes>
</ospfv2>
```

## Command Syntax

```
log-adjacency-changes (brief|detail|)
```

---

## Configure shutdown

Use this attribute to shutdown OSPF process.

Attribute Name: shutdown

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
      </shutdown><!-- operation="delete"-->
    </process>
  </processes>
</ospfv2>
```

### Command Syntax

```
shutdown
```

---

## Configure area border type

Use this attribute to set an OSPF Area Border Router (ABR) type.

Attribute Name: area-border-type

Attribute Type: enum (standard|cisco|ibm|shortcut)

Default Value: cisco

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
        <area-border-type>cisco</area-border-type> <!-- operation="delete"-->
      </config>
    </process>
  </processes>
</ospfv2>
```

### Command Syntax

```
ospf abr-type (standard|cisco|ibm|shortcut|)
```

---

## Configure reference bandwidth

Use this attribute to control how OSPF calculates the default metric for the interface.

Attribute Name: reference-bandwidth

Attribute Type: uint32

Default Value: 100

Attribute Range: 1-4294967

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
        </config>
        <reference-bandwidth>1</reference-bandwidth> <!-- operation="delete"-->
      </process>
    </processes>
  </ospfv2>
```

### Command Syntax

```
auto-cost reference-bandwidth <1-4294967>
```

---

## Configure max database descriptors

Use this attribute to limit the number of Database Descriptors (DD) that can be processed concurrently.

Attribute Name: max-database-descriptors

Attribute Type: uint16

Default Value: 64

Attribute Range: 1-65535

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
        </config>
        <max-database-descriptors>1</max-database-descriptors> <!-- operation="delete"-->
      </process>
    </processes>
  </ospfv2>
```

---

## Command Syntax

```
max-concurrent-dd <1-65535>
```

---

## Configure p2p rfc incompatible

Use this attribute to enable unicast packet on point-point interface.

Attribute Name: p2p-rfc-incompatible

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
      </p2p-rfc-incompatible><!-- operation="delete"-->
    </process>
  </processes>
</ospfv2>
```

## Command Syntax

```
ospf point-point rfc-incompatible
```

---

## Configure context name

Use this attribute to set the SNMP context name for OSPF instance.

Attribute Name: context-name

Attribute Type: string

Attribute Range: 1-32

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
        <context-name>WORD</context-name> <!-- operation="delete"-->
      </config>
    </process>
  </processes>
</ospfv2>
```

## Command Syntax

```
snmp context-name WORD
```

---

## Configure passive interface all

Use this attribute to set all interfaces as passive.

Attribute Name: passive-interface-all

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <passive-interfaces>
      <config>
        </passive-interface-all><!-- operation="delete"-->
      </config>
    </passive-interfaces>
  </process>
</processes>
</ospfv2>
```

### Command Syntax

```
passive-interface
```

---

## Configure passive mode

Use this attribute to define the passive mode.

Attribute Name: passive-mode

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <passive-interfaces>
      <passive-interface>
        <name>IFNAME</name>
        <config>
          <name>WORD</name>
        </config>
        <passive-mode>enable</passive-mode> <!-- operation="delete"-->
      </passive-interface>
    </passive-interfaces>
  </process>
</processes>
</ospfv2>
```

```

</passive-interfaces>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
passive-interface IFNAME (disable|enable)
```

---

## Configure address

Use this attribute to set interface address as passive.

Attribute Name: address

Attribute Type: inet:ipv4-address

Attribute Name: passive-mode

Attribute Type: enum (enable)

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<passive-interfaces>
<passive-interface>
  <name>IFNAME</name>
  <config>
    <name>WORD</name>
  </config>
  <passive-addresses>
  <passive-address> <!-- operation="delete"-->
    <address>A.B.C.D</address>
    <config>
      <address>A.B.C.D</address>
      <passive-mode>enable</passive-mode>
    </config>
  </passive-address>
</passive-addresses>
</passive-interface>
</passive-interfaces>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
passive-interface IFNAME A.B.C.D (enable)
```

---

## Configure originate

Use this attribute to create a default external route into an OSPF routing domain. The system acts like an Autonomous System Boundary Router (ASBR) when you use the default-information originate command to redistribute routes into an OSPF routing domain. An ASBR does not by default generate a default route into the OSPF routing domain

Attribute Name: originate

Attribute Type: uint8

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <default-information>
      <config>
        </originate><!-- operation="delete"-->
      </config>
    </default-information>
  </process>
</processes>
</ospfv2>
```

### Command Syntax

```
default-information originate
```

---

## Configure route map

Use this attribute to set route-map instance.

Attribute Name: route-map

Attribute Type: string

Attribute Name: originate

Attribute Type: empty

Attribute Name: always-advertise-default-route

Attribute Type: empty

Attribute Name: metric

Attribute Type: uint32

Default Value: 10

Attribute Range: 0-16777214

Attribute Name: metric-type

Attribute Type: enum (1|2)

Default Value: 2

**Netconf edit-config payload**

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<default-information>
<config>
  </originate><!-- operation="delete"-->
  </always-advertise-default-route><!-- operation="delete"-->
  <metric>0</metric> <!-- operation="delete"-->
  <metric-type>2</metric-type> <!-- operation="delete"-->
  <route-map>WORD</route-map> <!-- operation="delete"-->
</config>
</default-information>
</process>
</processes>
</ospfv2>

```

**Command Syntax**

```

default-information originate { always| metric <0-16777214>| metric-type (1|2)|
route-map WORD }

```

**Configure disable graceful restart**

Graceful OSPF Restart.

Attribute Name: disable-graceful-restart

Attribute Type: empty

**Netconf edit-config payload**

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<capability>
<config>
  </disable-graceful-restart><!-- operation="delete"-->
</config>
</capability>
</process>
</processes>
</ospfv2>

```

---

## Command Syntax

```
no capability restart graceful
```

---

## Configure disable opaque lsa

Use this attribute to enable opaque-LSAs which are Type 9, 10 and 11 LSAs.

Attribute Name: disable-opaque-lsa

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <capability>
      <config>
        </disable-opaque-lsa><!-- operation="delete"-->
      </config>
    </capability>
  </process>
</processes>
</ospfv2>
```

## Command Syntax

```
no capability opaque
```

---

## Configure enable vrf lite

Use this attribute to enable VRF-lite feature.

Attribute Name: enable-vrf-lite

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <capability>
      <config>
        </enable-vrf-lite><!-- operation="delete"-->
      </config>
    </capability>
  </processes>
</ospfv2>
```

```
</process>  
</processes>  
</ospfv2>
```

## Command Syntax

```
capability vrf-lite
```

---

## Configure link local signaling

Use this attribute to enable link-local signaling feature.

Attribute Name: link-local-signaling

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">  
<processes>  
<process>  
  <ospf-id>0</ospf-id>  
  <config>  
    <ospf-id>0</ospf-id>  
  </config>  
<capability>  
<config>  
  </link-local-signaling><!-- operation="delete"-->  
</config>  
</capability>  
</process>  
</processes>  
</ospfv2>
```

## Command Syntax

```
capability lls
```

---

## Configure maximum areas number

Use this attribute to set the maximum number of OSPF areas (excluding Backbone Area).

Attribute Name: maximum-areas-number

Attribute Type: uint32

Attribute Range: 1-4294967294

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">  
<processes>  
<process>  
  <ospf-id>0</ospf-id>  
  <config>  
    <ospf-id>0</ospf-id>
```

```

    </config>
  <areas>
  <config>
    <maximum-areas-number>1</maximum-areas-number> <!-- operation="delete"-->
  </config>
  </areas>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
maximum-area <1-4294967294>
```

---

## Configure disable advertise

Use this attribute to disable the advertisement of these routes.

Attribute Name: disable-advertise

Attribute Type: empty

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
  <process>
    <ospf-id>0</ospf-id>
    <config>
      <ospf-id>0</ospf-id>
    </config>
  <areas>
  <area>
    <area-id>OSPF_AREA_T</area-id>
    <config>
      <area-id>OSPF_AREA_T</area-id>
    </config>
    <area-ranges>
    <area-range>
      <address>A.B.C.D/M|A.B.C.D A.B.C.D</address>
      <config>
        <address>A.B.C.D/M|A.B.C.D A.B.C.D</address>
      </config>
      </disable-advertise><!-- operation="delete"-->
    </area-range>
  </area-ranges>
  </area>
  </areas>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
area (A.B.C.D|<0-4294967295>) range (A.B.C.D/M|A.B.C.D A.B.C.D) not-advertise
```

---

## Configure authentication type

Use this attribute to set the area authentication type.

Attribute Name: authentication-type

Attribute Type: enum (authentication|authentication message-digest)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPF_AREA_T</area-id>
      <config>
        <area-id>OSPF_AREA_T</area-id>
        <authentication-type>authentication</authentication-type> <!--
operation="delete"-->
      </config>
    </area>
  </areas>
</ospfv2>
```

## Command Syntax

```
area (authentication|authentication message-digest)
```

---

## Configure default cost

Use this attribute to set the summary-default cost of a NSSA or stub area.

Attribute Name: default-cost

Attribute Type: uint32

Attribute Range: 0-16777215

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
```

```

        <ospf-id>0</ospf-id>
    </config>
</areas>
<area>
    <area-id>OSPF_AREA_T</area-id>
    <config>
        <area-id>OSPF_AREA_T</area-id>
    </config>
    <default-cost>0</default-cost> <!-- operation="delete"-->
</area>
</areas>
</process>
</processes>
</ospfv2>

```

### Command Syntax

```
area default-cost <0-16777215>
```

---

## Configure shortcut

Use this attribute to set the area shortcutting mode.

Attribute Name: shortcut

Attribute Type: enum (default|enable|disable)

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
    <ospf-id>0</ospf-id>
    <config>
        <ospf-id>0</ospf-id>
    </config>
</process>
</processes>
</ospfv2>

```

### Command Syntax

```
area shortcut (default|enable|disable)
```

---

## Configure name

Use this attribute to set the interface to enable OSPF area.

Attribute Name: name

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPF_AREA_T</area-id>
      <config>
        <area-id>OSPF_AREA_T</area-id>
      </config>
      <interfaces>
        <interface> <!-- operation="delete"-->
          <name>IFNAME</name>
          <config>
            <name>WORD</name>
          </config>
        </interface>
      </interfaces>
    </area>
  </areas>
</ospfv2>
```

### Command Syntax

```
area interface IFNAME
```

---

## Configure cost

Use this attribute to explicitly specify the cost of the link-state metric in a router-LSA.

Attribute Name: cost

Attribute Type: uint16

Default Value: 10

Attribute Range: 1-65535

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
```

```

<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<areas>
<area>
  <area-id>OSPF_AREA_T</area-id>
  <config>
    <area-id>OSPF_AREA_T</area-id>
  </config>
  <interfaces>
  <interface>
    <name>IFNAME</name>
    <config>
      <name>WORD</name>
    </config>
    <cost>1</cost> <!-- operation="delete"-->
  </interface>
</interfaces>
</area>
</areas>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
area interface IFNAME cost <1-65535>
```

---

## Configure network type

Use this attribute to set the area interface network type.

Attribute Name: network-type

Attribute Type: enum (point-to-point|broadcast|non-broadcast|point-to-multipoint|point-to-multipoint non-broadcast)

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<areas>
<area>
  <area-id>OSPF_AREA_T</area-id>
  <config>
    <area-id>OSPF_AREA_T</area-id>

```

```

</config>
<interfaces>
<interface>
  <name>IFNAME</name>
  <config>
    <name>WORD</name>
  </config>
  <network-type>point-to-point</network-type> <!-- operation="delete"-->
</interface>
</interfaces>
</area>
</areas>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```

area interface IFNAME network-type (point-to-point|broadcast|non-broadcast|point-
to-multipoint|point-to-multipoint non-broadcast)

```

---

## Configure passive

Use this attribute to set area interface as passive.

Attribute Name: passive

Attribute Type: empty

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<areas>
<area>
  <area-id>OSPF_AREA_T</area-id>
  <config>
    <area-id>OSPF_AREA_T</area-id>
  </config>
<interfaces>
<interface>
  <name>IFNAME</name>
  <config>
    <name>WORD</name>
  </config>
  </passive><!-- operation="delete"-->
</interface>
</interfaces>

```

```

</area>
</areas>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
area interface IFNAME passive
```

---

## Configure priority

Use this attribute to set the router priority to determine the designated router (DR) for the network.

Attribute Name: priority

Attribute Type: uint8

Default Value: 1

Attribute Range: 0-255

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPF_AREA_T</area-id>
      <config>
        <area-id>OSPF_AREA_T</area-id>
      </config>
      <interfaces>
        <interface>
          <name>IFNAME</name>
          <config>
            <name>WORD</name>
          </config>
          <priority>0</priority> <!-- operation="delete"-->
        </interface>
      </interfaces>
    </area>
  </areas>
</ospfv2>

```

## Command Syntax

```
area interface IFNAME priority <0-255>
```

---

## Configure area id

Use this attribute to configure authentication on this interface.

Attribute Name: authentication-type

Attribute Type: enum (null|simple|message-digest)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPF_AREA_T</area-id>
      <config>
        <area-id>OSPF_AREA_T</area-id>
      </config>
      <interfaces>
        <interface>
          <name>IFNAME</name>
          <config>
            <name>WORD</name>
          </config>
          <authentication-type>simple</authentication-type> <!--
operation="delete"-->
        </interface>
      </interfaces>
    </area>
  </areas>
</ospfv2>
```

### Command Syntax

```
area interface IFNAME authentication (null|message-digest|)
```

---

## Configure enabled

Use this attribute to enable Bidirectional Forwarding Detection (BFD).

This command is supported when following feature are enabled Bidirectional Forwarding Detection (BFD)

Attribute Name: enabled

Attribute Type: enum (enable|disable)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
```

```

<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
</process>
<areas>
<area>
  <area-id>OSPF_AREA_T</area-id>
  <config>
    <area-id>OSPF_AREA_T</area-id>
  </config>
  <interfaces>
  <interface>
    <name>IFNAME</name>
    <config>
      <name>WORD</name>
    </config>
    <enable-bfd>
    <config>
      <enabled>enable</enabled> <!-- operation="delete"-->
    </config>
  </enable-bfd>
</interface>
</interfaces>
</area>
</areas>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
area interface IFNAME bfd (disable|)
```

---

## Configure filter out

Use this attribute to turn on the LSA database-filter for a particular interface. OSPF floods new LSAs over all interfaces in an area, except the interface on which the LSA arrives. This redundancy ensures robust flooding. However, too much redundancy can waste bandwidth and might lead to excessive link and CPU usage in certain topologies, resulting in destabilizing the network. To avoid this, use this attribute to block flooding of LSAs over specified interfaces.

Attribute Name: filter-out

Attribute Type: empty

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>

```

```

        <ospf-id>0</ospf-id>
    </config>
</areas>
<area>
    <area-id>OSPF_AREA_T</area-id>
    <config>
        <area-id>OSPF_AREA_T</area-id>
    </config>
    <interfaces>
    <interface>
        <name>IFNAME</name>
        <config>
            <name>WORD</name>
        </config>
        <lsa-filter>
        <config>
            </filter-out><!-- operation="delete"-->
        </config>
    </lsa-filter>
    </interface>
</interfaces>
</area>
</areas>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
area interface IFNAME database-filter all out
```

---

## Configure dead interval

Use this attribute to set the interval during which the router waits to receive an OSPF hello packet from the neighbor before declaring the neighbor down.

Attribute Name: dead-interval

Attribute Type: uint16

Attribute Range: 1-65535

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
  <process>
    <ospf-id>0</ospf-id>
    <config>
      <ospf-id>0</ospf-id>
    </config>
  </process>
</processes>
<area>
  <area-id>OSPF_AREA_T</area-id>

```

```

<config>
  <area-id>OSPF_AREA_T</area-id>
</config>
<interfaces>
<interface>
  <name>IFNAME</name>
  <config>
    <name>WORD</name>
  </config>
  <timers>
  <config>
    <dead-interval>1</dead-interval> <!-- operation="delete"-->
  </config>
  </timers>
</interface>
</interfaces>
</area>
</areas>
</process>
</processes>
</ospfv2>

```

### Command Syntax

```
area interface IFNAME dead-interval <1-65535>
```

---

## Configure hello interval

Use this attribute to specify the interval between hello packets.

Attribute Name: hello-interval

Attribute Type: uint16

Default Value: 10

Attribute Range: 1-65535

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
</process>
</processes>
<areas>
<area>
  <area-id>OSPF_AREA_T</area-id>
  <config>
    <area-id>OSPF_AREA_T</area-id>
  </config>
</area>
</areas>
</ospfv2>

```

```

<interface>
  <name>IFNAME</name>
  <config>
    <name>WORD</name>
  </config>
  <timers>
    <config>
      <hello-interval>1</hello-interval> <!-- operation="delete"-->
    </config>
  </timers>
</interface>
</interfaces>
</area>
</areas>
</process>
</processes>
</ospfv2>

```

### Command Syntax

```
area interface IFNAME hello-interval <1-65535>
```

---

## Configure retransmission interval

Use this attribute to specify the time between link-state advertisement (LSA) retransmissions for adjacencies belonging to the interface.

Attribute Name: retransmission-interval

Attribute Type: uint16

Default Value: 5

Attribute Range: 1-3600

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPF_AREA_T</area-id>
      <config>
        <area-id>OSPF_AREA_T</area-id>
      </config>
    </area>
  </areas>
  <interfaces>
    <interface>
      <name>IFNAME</name>
      <config>

```

```

        <name>WORD</name>
    </config>
    <timers>
    <config>
        <retransmission-interval>1</retransmission-interval> <!--
operation="delete"-->
    </config>
</timers>
</interface>
</interfaces>
</area>
</areas>
</process>
</processes>
</ospfv2>

```

### Command Syntax

```
area interface IFNAME retransmit-interval <1-3600>
```

---

## Configure no summary

Use this attribute to set the OSPF area stub with no-summary, this will prevent an ABR from sending summary link state advertisements into the stub area.

Attribute Name: no-summary

Attribute Type: empty

Attribute Name: is-stub

Attribute Type: empty

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
        </config>
      <areas>
        <area>
          <area-id>OSPF_AREA_T</area-id>
          <config>
            <area-id>OSPF_AREA_T</area-id>
            </config>
            <stub>
              <config>
                </is-stub><!-- operation="delete"-->
                </no-summary><!-- operation="delete"-->
              </config>
            </stub>
          </area>
        </areas>
      </process>
    </processes>
  </ospfv2>

```

```
</areas>
</process>
</processes>
</ospfv2>
```

## Command Syntax

```
area stub no-summary
```

---

## Configure is stub

Use this attribute to set the OSPF area as stub.

Attribute Name: is-stub

Attribute Type: empty

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPF_AREA_T</area-id>
      <config>
        <area-id>OSPF_AREA_T</area-id>
        </config>
        <stub>
          <config>
            </is-stub><!-- operation="delete"-->
          </config>
        </stub>
      </config>
    </area>
  </areas>
</ospfv2>
```

## Command Syntax

```
area stub
```

---

## Configure nssa enable

Use this attribute to enable the OSPF area as NSSA.

This command is supported when following feature are enabled Not-So-Stubby Area (NSSA)

Attribute Name: nssa-enable

Attribute Type: enum (nssa)

**Netconf edit-config payload**

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<areas>
<area>
  <area-id>OSPF_AREA_T</area-id>
  <config>
    <area-id>OSPF_AREA_T</area-id>
  </config>
  <nssas>
  <nssa> <!-- operation="delete"-->
    <nssa-enable>nssa</nssa-enable>
    <config>
      <nssa-enable>nssa</nssa-enable>
    </config>
  </nssa>
</nssas>
</area>
</areas>
</process>
</processes>
</ospfv2>

```

**Command Syntax**

```
area (nssa)
```

**Configure stability interval**

Use this attribute to set route-map instance.

This command is supported when following feature are enabled Not-So-Stubby Area (NSSA)

Attribute Name: route-map

Attribute Type: string

Attribute Name: no-summary

Attribute Type: empty

Attribute Name: stability-interval

Attribute Type: uint32

Default Value: 40

Attribute Range: 0-2147483647

Attribute Name: translator-role

Attribute Type: enum (never|always|candidate)

Attribute Name: no-redistribution

Attribute Type: empty

Attribute Name: default-information-originate

Attribute Type: empty

Attribute Name: metric

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-16777214

Attribute Name: metric-type

Attribute Type: enum (1|2)

Default Value: 2

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <areas>
      <area>
        <area-id>OSPF_AREA_T</area-id>
        <config>
          <area-id>OSPF_AREA_T</area-id>
          </config>
          <nssas>
            <nssa>
              <nssa-enable>nssa</nssa-enable>
              <config>
                <nssa-enable>nssa</nssa-enable>
                </no-summary>
                <stability-interval>0</stability-interval>
                <translator-role>never</translator-role>
                </no-redistribution>
                </default-information-originate>
                <metric>0</metric>
                <metric-type>2</metric-type>
              </config>
              <route-map>WORD</route-map>
            </nssa>
          </nssas>
        </area>
      </areas>
    </process>
  </processes>
```

```
</ospfv2>
```

## Command Syntax

```
area (nssa) { no-summary| stability-interval <0-2147483647>| translator-role
  (never|always|candidate)| no-redistribution| default-information-originate|
  metric <0-16777214>| metric-type (1|2)| route-map WORD }
```

---

## Configure filter-in name

Use this attribute to set name of the prefix list.

This command is supported when following feature are enabled Access-Control List (ACL)

Attribute Name: name

Attribute Type: string

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPF_AREA_T</area-id>
      <config>
        <area-id>OSPF_AREA_T</area-id>
        <filter-list>
          <prefix-list>
            <filter-in>
              <config>
                <name>WORD</name> <!-- operation="delete"-->
              </config>
            </filter-in>
          </prefix-list>
        </filter-list>
      </config>
    </area>
  </areas>
</ospfv2>
```

## Command Syntax

```
area filter-list prefix WORD in
```

---

## Configure filter-out name

Use this attribute to set name of the prefix list.

This command is supported when following feature are enabled Access-Control List (ACL)

Attribute Name: name

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPF_AREA_T</area-id>
      <config>
        <area-id>OSPF_AREA_T</area-id>
        <filter-list>
          <prefix-list>
            <filter-out>
              <config>
                <name>WORD</name> <!-- operation="delete"-->
              </config>
            </filter-out>
          </prefix-list>
        </filter-list>
      </config>
    </area>
  </areas>
</ospfv2>
```

### Command Syntax

```
area filter-list prefix WORD out
```

---

## Configure filter-in name

Use this attribute to set name of the access control list.

This command is supported when following feature are enabled Access-Control List (ACL)

Attribute Name: name

Attribute Type: string

**Netconf edit-config payload**

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<areas>
<area>
  <area-id>OSPF_AREA_T</area-id>
  <config>
    <area-id>OSPF_AREA_T</area-id>
  </config>
  <filter-list>
  <access-control-list>
  <filter-in>
  <config>
    <name>WORD</name> <!-- operation="delete"-->
  </config>
</filter-in>
</access-control-list>
</filter-list>
</area>
</areas>
</process>
</processes>
</ospfv2>

```

**Command Syntax**

```
area filter-list access WORD in
```

**Configure filter-out name**

Use this attribute to set name of the access control list.

This command is supported when following feature are enabled Access-Control List (ACL)

Attribute Name: name

Attribute Type: string

**Netconf edit-config payload**

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<areas>

```

```

<area>
  <area-id>OSPF_AREA_T</area-id>
  <config>
    <area-id>OSPF_AREA_T</area-id>
  </config>
  <filter-list>
  <access-control-list>
  <filter-out>
  <config>
    <name>WORD</name> <!-- operation="delete"-->
  </config>
</filter-out>
</access-control-list>
</filter-list>
</area>
</areas>
</process>
</processes>
</ospfv2>

```

### Command Syntax

```
area filter-list access WORD out
```

---

## Configure ip address

Use this attribute to set the OSPF area ID.

Attribute Name: area-id

Attribute Type: inet:ipv4-address

Attribute Name: ip-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
  <process>
    <ospf-id>0</ospf-id>
    <config>
      <ospf-id>0</ospf-id>
    </config>
  </process>
</processes>
<areas>
<area> <!-- operation="delete"-->
  <area-id>OSPF_AREA_T</area-id>
  <config>
    <area-id>OSPF_AREA_T</area-id>
  </config>
</area>
</areas>
<hosts>
<host>
  <ip-address>A.B.C.D</ip-address>
</host>
</hosts>
</ospfv2>

```

```

    </host>
  </hosts>
</area>
</areas>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
host A.B.C.D area
```

---

## Configure host cost

Use this attribute to set the stub host cost.

Attribute Name: cost

Attribute Type: uint16

Attribute Range: 0-65535

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPF_AREA_T</area-id>
      <config>
        <area-id>OSPF_AREA_T</area-id>
      </config>
      <hosts>
        <host>
          <ip-address>A.B.C.D</ip-address>
          <config>
            <ip-address>A.B.C.D</ip-address>
          </config>
          <cost>0</cost>
        </host>
      </hosts>
    </area>
  </areas>
</ospfv2>

```

## Command Syntax

```
host A.B.C.D area cost <0-65535>
```

---

## Configure instance id

Use this attribute to set the instance ID. Use this command with OSPF multiple-instance support enabled.

Attribute Name: instance-id

Attribute Type: uint8

Attribute Range: 0-255

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <areas>
      <area>
        <area-id>OSPF_AREA_T</area-id>
        <config>
          <area-id>OSPF_AREA_T</area-id>
        </config>
        <networks>
          <network>
            <prefix>A.B.C.D/M|A.B.C.D A.B.C.D</prefix>
            <config>
              <prefix>A.B.C.D/M|A.B.C.D A.B.C.D</prefix>
            </config>
            <instance-id>0</instance-id>
          </network>
        </networks>
      </area>
    </areas>
  </process>
</processes>
</ospfv2>
```

### Command Syntax

```
network (A.B.C.D/M|A.B.C.D A.B.C.D) area (instance-id <0-255>|)
```

---

## Configure area-ranges address

Use this attribute to summarize routes matching address/mask (border routers only).

Attribute Name: address

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
```

```

<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
</areas>
<area>
  <area-id>OSPF_AREA_T</area-id>
  <config>
    <area-id>OSPF_AREA_T</area-id>
  </config>
  <area-ranges>
  <area-range> <!-- operation="delete"-->
    <address>A.B.C.D/M|A.B.C.D A.B.C.D</address>
    <config>
      <address>A.B.C.D/M|A.B.C.D A.B.C.D</address>
    </config>
  </area-range>
</area-ranges>
</area>
</areas>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
area range (A.B.C.D/M|A.B.C.D A.B.C.D)
```

---

## Configure remote router id

Use this attribute to set the interface IP address of the neighbor.

Attribute Name: remote-router-id

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
  <process>
    <ospf-id>0</ospf-id>
    <config>
      <ospf-id>0</ospf-id>
    </config>
  </areas>
  <area>
    <area-id>OSPF_AREA_T</area-id>
    <config>
      <area-id>OSPF_AREA_T</area-id>
    </config>
  </virtual-links>

```

```

<virtual-link> <!-- operation="delete"-->
  <remote-router-id>A.B.C.D</remote-router-id>
  <config>
    <remote-router-id>A.B.C.D</remote-router-id>
  </config>
</virtual-link>
</virtual-links>
</area>
</areas>
</process>
</processes>
</ospfv2>

```

### Command Syntax

```
area virtual-link A.B.C.D
```

---

## Configure fall over

Fall-over detection with Bidirectional Forwarding Detection (BFD).

Attribute Name: fall-over

Attribute Type: empty

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPF_AREA_T</area-id>
      <config>
        <area-id>OSPF_AREA_T</area-id>
      </config>
      <virtual-links>
        <virtual-link>
          <remote-router-id>A.B.C.D</remote-router-id>
          <config>
            <remote-router-id>A.B.C.D</remote-router-id>
          </config>
          <bfd>
            <config>
              </fall-over><!-- operation="delete"-->
            </config>
          </bfd>
        </virtual-link>
      </virtual-links>
    </area>
  </areas>
</ospfv2>

```

```

</area>
</areas>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
area virtual-link A.B.C.D fall-over bfd
```

---

## Configure key

Use this attribute to set the authentication password (key).

Attribute Name: key

Attribute Type: string

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPF_AREA_T</area-id>
      <config>
        <area-id>OSPF_AREA_T</area-id>
        <virtual-links>
          <virtual-link>
            <remote-router-id>A.B.C.D</remote-router-id>
            <config>
              <remote-router-id>A.B.C.D</remote-router-id>
            </config>
            <authentication>
              <config>
                <key>WORD</key> <!-- operation="delete" -->
              </config>
            </authentication>
          </virtual-link>
        </virtual-links>
      </config>
    </area>
  </areas>
</ospfv2>

```

## Command Syntax

```
area virtual-link A.B.C.D authentication-key WORD
```

## Configure authentication authentication-type

Use this attribute to configure authentication on this interface.

Attribute Name: authentication-type

Attribute Type: enum (null|simple|message-digest)

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPF_AREA_T</area-id>
      <config>
        <area-id>OSPF_AREA_T</area-id>
      </config>
      <virtual-links>
        <virtual-link>
          <remote-router-id>A.B.C.D</remote-router-id>
          <config>
            <remote-router-id>A.B.C.D</remote-router-id>
          </config>
          <authentication>
            <config>
              <authentication-type>simple</authentication-type> <!--
operation="delete"-->
            </config>
          </authentication>
        </virtual-link>
      </virtual-links>
    </area>
  </areas>
</ospfv2>
```

## Command Syntax

```
area virtual-link A.B.C.D authentication (null|message-digest|)
```

## Configure message digest id

Use this attribute to set the authentication message digest key ID.

Attribute Name: message-digest-id

Attribute Type: uint8

Attribute Range: 1-255

Attribute Name: message-digest-encryption-type

Attribute Type: enum (md5)

Attribute Name: message-digest-key

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPF_AREA_T</area-id>
      <config>
        <area-id>OSPF_AREA_T</area-id>
      </config>
      <virtual-links>
        <virtual-link>
          <remote-router-id>A.B.C.D</remote-router-id>
          <config>
            <remote-router-id>A.B.C.D</remote-router-id>
          </config>
          <authentication>
            <message-digests>
              <message-digest> <!-- operation="delete"-->
                <message-digest-id>1</message-digest-id>
                <config>
                  <message-digest-id>1</message-digest-id>
                  <message-digest-encryption-type>md5</message-digest-encryption-type>
                  <message-digest-key>WORD</message-digest-key>
                </config>
              </message-digest>
            </message-digests>
          </authentication>
        </virtual-link>
      </virtual-links>
    </area>
  </areas>
</ospfv2>
```

## Command Syntax

```
area virtual-link A.B.C.D message-digest-key <1-255> (md5) WORD
```

---

## Configure transmit delay

Dead router detection time. Interval during which no packets are received and after which the router acknowledges a neighboring router as off-line.

Attribute Name: dead-interval

Attribute Type: uint16

Attribute Range: 1-65535

Attribute Name: hello-interval

Attribute Type: uint16

Default Value: 10

Attribute Range: 1-65535

Attribute Name: transmit-delay

Attribute Type: uint16

Default Value: 1

Attribute Range: 1-3600

Attribute Name: retransmission-interval

Attribute Type: uint16

Default Value: 5

Attribute Range: 1-3600

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPF_AREA_T</area-id>
      <config>
        <area-id>OSPF_AREA_T</area-id>
      </config>
    </area>
  </areas>
  <virtual-links>
    <virtual-link>
      <remote-router-id>A.B.C.D</remote-router-id>
      <config>
        <remote-router-id>A.B.C.D</remote-router-id>
      </config>
    </virtual-link>
  </virtual-links>
</ospfv2>
```

```

    <config>
      <hello-interval>1</hello-interval> <!-- operation="delete"-->
      <transmit-delay>1</transmit-delay> <!-- operation="delete"-->
      <retransmission-interval>1</retransmission-interval> <!--
operation="delete"-->
      <dead-interval>1</dead-interval> <!-- operation="delete"-->
    </config>
  </timers>
</virtual-link>
</virtual-links>
</area>
</areas>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```

area virtual-link A.B.C.D { dead-interval <1-65535>| hello-interval <1-65535>|
  transmit-delay <1-3600>| retransmit-interval <1-3600> }

```

---

## Configure limit type

Use this attribute to set the limit type. Soft limit: Warning message appears if the number of LSAs exceeds the specified value; Hard limit: Shutdown occurs if the number of LSAs exceeds the specified value. Default value is 2.

Attribute Name: limit-type

Attribute Type: enum (soft|hard)

Attribute Name: max-limit

Attribute Type: uint32

Attribute Range: 0-4294967294

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <lsdb>
    <overflow>
      <normal-lsa>
        <config>
          <max-limit>0</max-limit>
          <limit-type>hard</limit-type>
        </config>
      </normal-lsa>
    </overflow>
  </lsdb>

```

```

</process>
</processes>
</ospfv2>

```

## Command Syntax

```
overflow database <0-4294967294> ((soft|hard|))
```

---

## Configure exit interval

Use this attribute to set the number of seconds the router waits before trying to exit the database overflow state. If this parameter is 0, the router exits the overflow state only after an explicit administrator command. Default value is 0.

This command is supported when following feature are enabled OSPF DataBase (DB) overflow

Attribute Name: exit-interval

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: max-limit

Attribute Type: uint32

Attribute Range: 0-2147483647

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <lsdb>
    <overflow>
      <external-lsa>
        <config>
          <max-limit>0</max-limit>
          <exit-interval>0</exit-interval>
        </config>
      </external-lsa>
    </overflow>
  </lsdb>
</ospfv2>

```

## Command Syntax

```
overflow database external <0-2147483647> <0-65535>
```

---

## Configure keep all paths

Use this attribute to enable fast rerouting on all OSPF interfaces.

This command is supported when following feature are enabled OSPF Loop Free Alternate (LFA)

Attribute Name: keep-all-paths

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <lfa>
      <fast-reroute>
        <config>
          </keep-all-paths><!-- operation="delete"-->
        </config>
      </fast-reroute>
    </lfa>
  </process>
</processes>
</ospfv2>
```

### Command Syntax

```
fast-reroute keep-all-paths
```

---

## Configure fast-reroute route-map

Use this attribute to set route-map for FRR.

This command is supported when following feature are enabled OSPF Loop Free Alternate (LFA)

Attribute Name: route-map

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <lfa>
      <fast-reroute>
        <config>
          <route-map>WORD</route-map> <!-- operation="delete"-->
        </config>
      </fast-reroute>
    </lfa>
```

```

</process>
</processes>
</ospfv2>

```

## Command Syntax

```
fast-reroute per-prefix route-map WORD
```

---

## Configure idx

Use this attribute to set the tie breaking index. A lower value has higher preference.

This command is supported when following feature are enabled OSPF Loop Free Alternate (LFA)

Attribute Name: idx

Attribute Type: uint8

Attribute Range: 1-255

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<lfa>
<fast-reroute>
<tie-breaks>
<tie-break>
  <type>primary-path</type>
  <config>
    <type>primary-path</type>
  </config>
  <idx>1</idx> <!-- operation="delete"-->
</tie-break>
</tie-breaks>
</fast-reroute>
</lfa>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
fast-reroute tie-break (primary-path|node-protecting|interface-disjoint|broadcast-
interface-disjoint|downstream-path|secondary-path) index <1-255>
```

---

## Configure default distance

Use this attribute to specifies a default administrative distance used when no other specification exists for a routing information source.

Attribute Name: default-distance

Attribute Type: uint8

Attribute Range: 1-255

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
      <administrative-distance>
        <config>
          <default-distance>1</default-distance> <!-- operation="delete"-->
        </config>
      </administrative-distance>
    </process>
  </processes>
</ospfv2>
```

### Command Syntax

```
distance <1-255>
```

---

## Configure intra area distance

Use this attribute to set the distance for all routes within an area.

Attribute Name: intra-area-distance

Attribute Type: uint8

Attribute Range: 1-255

Attribute Name: inter-area-distance

Attribute Type: uint8

Attribute Range: 1-255

Attribute Name: external-routes-distance

Attribute Type: uint8

Attribute Range: 1-255

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <administrative-distance>
```

```

<ospf>
<config>
  <inter-area-distance>1</inter-area-distance> <!-- operation="delete"-->
  <external-routes-distance>1</external-routes-distance> <!--
operation="delete"-->
  <intra-area-distance>1</intra-area-distance> <!-- operation="delete"-->
</config>
</ospf>
</administrative-distance>
</process>
</processes>
</ospfv2>

```

### Command Syntax

```
distance ospf { intra-area <1-255>| inter-area <1-255>| external <1-255> }
```

---

## Configure access control list

Use this attribute to specifies administrative distance network ACL.

Attribute Name: access-control-list

Attribute Type: string

Attribute Name: distance

Attribute Type: uint8

Attribute Range: 1-255

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<administrative-distance>
<networks>
<network>
  <prefix>A.B.C.D/M</prefix>
  <config>
    <prefix>A.B.C.D/M</prefix>
    <distance>1</distance>
  </config>
  <access-control-list>WORD</access-control-list>
</network>
</networks>
</administrative-distance>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
distance <1-255> A.B.C.D/M (WORD|)
```

---

## Configure summary-addresses address

Use this attribute to summarize or suppress external routes with the specified address range.

Attribute Name: address

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <summary-addresses>
    <summary-address> <!-- operation="delete"-->
      <address>A.B.C.D/M|A.B.C.D A.B.C.D</address>
    <config>
      <address>A.B.C.D/M|A.B.C.D A.B.C.D</address>
    </config>
    </summary-address>
  </summary-addresses>
</process>
</processes>
</ospfv2>
```

## Command Syntax

```
summary-address (A.B.C.D/M|A.B.C.D A.B.C.D)
```

---

## Configure not advertise

Use this attribute to suppress routes that match the address range.

Attribute Name: not-advertise

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <summary-addresses>
    <summary-address>
```

```

    <address>A.B.C.D/M|A.B.C.D A.B.C.D</address>
  </config>
  <address>A.B.C.D/M</address>
</config>
  </not-advertise><!-- operation="delete"-->
</summary-address>
</summary-addresses>
</process>
</processes>
</ospfv2>

```

### Command Syntax

```
summary-address (A.B.C.D/M|A.B.C.D A.B.C.D) not-advertise
```

---

## Configure tag

Use this attribute to set the tag value to use as a match value for controlling redistribution via route maps.

Attribute Name: tag

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <summary-addresses>
      <summary-address>
        <address>A.B.C.D/M|A.B.C.D A.B.C.D</address>
        <config>
          <address>A.B.C.D/M</address>
        </config>
        <tag>0</tag> <!-- operation="delete"-->
      </summary-address>
    </summary-addresses>
  </process>
</processes>
</ospfv2>

```

### Command Syntax

```
summary-address (A.B.C.D/M|A.B.C.D A.B.C.D) tag <0-4294967295>
```

---

## Configure filter-in access-control-list

Use this attribute to set the access control list name in distribution list.

This command is supported when following feature are enabled Access-Control List (ACL)

Attribute Name: access-control-list

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
        </config>
      <distribute-list>
        <filter-in>
          <config>
            <access-control-list>WORD</access-control-list> <!-- operation="delete"-->
          </config>
        </filter-in>
      </distribute-list>
    </process>
  </processes>
</ospfv2>
```

### Command Syntax

```
distribute-list WORD in
```

---

## Configure access control list isis

Use this attribute to set the access control list name for ISIS protocol.

This command is supported when following feature are enabled Access-Control List (ACL)

Attribute Name: access-control-list-isis

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
        </config>
      <distribute-list>
        <filter-out>
          <config>
```

```

        <access-control-list-isis>WORD</access-control-list-isis> <!--
operation="delete"-->
    </config>
</filter-out>
</distribute-list>
</process>
</processes>
</ospfv2>

```

### Command Syntax

```
distribute-list WORD out isis
```

---

## Configure access control list bgp

Use this attribute to set the access control list name for BGP protocol.

This command is supported when following feature are enabled Access-Control List (ACL)

Attribute Name: access-control-list-bgp

Attribute Type: string

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <distribute-list>
    <filter-out>
    <config>
      <access-control-list-bgp>WORD</access-control-list-bgp> <!--
operation="delete"-->
    </config>
  </filter-out>
</distribute-list>
</process>
</processes>
</ospfv2>

```

### Command Syntax

```
distribute-list WORD out bgp
```

---

## Configure access control list rip

Use this attribute to set the access control list name for RIP protocol.

This command is supported when following feature are enabled Access-Control List (ACL)

Attribute Name: access-control-list-rip

Attribute Type: string

**Netconf edit-config payload**

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<distribute-list>
<filter-out>
<config>
  <access-control-list-rip>WORD</access-control-list-rip> <!--
operation="delete"-->
</config>
</filter-out>
</distribute-list>
</process>
</processes>
</ospfv2>

```

**Command Syntax**

```
distribute-list WORD out rip
```

**Configure access control list static**

Use this attribute to set the access control list name for static routes.

This command is supported when following feature are enabled Access-Control List (ACL)

Attribute Name: access-control-list-static

Attribute Type: string

**Netconf edit-config payload**

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<distribute-list>
<filter-out>
<config>
  <access-control-list-static>WORD</access-control-list-static> <!--
operation="delete"-->
</config>
</filter-out>
</distribute-list>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
distribute-list WORD out static
```

---

## Configure access control list connected

Use this attribute to set the access control list name for connected networks.

This command is supported when following feature are enabled Access-Control List (ACL)

Attribute Name: access-control-list-connected

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
      <distribute-list>
        <filter-out>
          <config>
            <access-control-list-connected>WORD</access-control-list-connected> <!--
operation="delete"-->
          </config>
        </filter-out>
      </distribute-list>
    </process>
  </processes>
</ospfv2>
```

## Command Syntax

```
distribute-list WORD out connected
```

---

## Configure access control list kernel

Use this attribute to set the access control list name for KERNEL routes.

This command is supported when following feature are enabled Access-Control List (ACL)

Attribute Name: access-control-list-kernel

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
</ospfv2>
```

```

    </config>
  <distributed-list>
  <filter-out>
  <config>
    <access-control-list-kernel>WORD</access-control-list-kernel> <!--
operation="delete"-->
  </config>
</filter-out>
</distributed-list>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
distribute-list WORD out kernel
```

---

## Configure ospf process id

Use this attribute to set the OSPF ID in distribution list filter out.

This command is supported when following feature are enabled Access-Control List (ACL)

Attribute Name: ospf-process-id

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: access-control-list-out-ospf

Attribute Type: string

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
  <process>
    <ospf-id>0</ospf-id>
    <config>
      <ospf-id>0</ospf-id>
    </config>
  <distributed-list>
  <filter-out>
  <ospfv2-processes>
  <ospfv2-process>
    <ospf-process-id>0</ospf-process-id>
    <config>
      <ospf-process-id>0</ospf-process-id>
      <access-control-list-out-ospf>WORD</access-control-list-out-ospf> <!--
operation="delete"-->
    </config>
  </ospfv2-process>
</ospfv2-processes>
</filter-out>
</distributed-list>

```

```

</process>
</processes>
</ospfv2>

```

## Command Syntax

```

distribute-list WORD out ospf (<0-65535>|)

```

---

## Configure primary domain id address

Use this attribute to set the domain ID in IPv4 address format.

This command is supported when following feature are enabled OSPF Virtual Routing and Forwarding (VRF)

Attribute Name: primary-domain-id-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <domain-id>
      <primary-domain>
        <config>
          <primary-domain-id-address>A.B.C.D</primary-domain-id-address> <!--
operation="delete"-->
        </config>
      </primary-domain>
    </domain-id>
  </process>
</processes>
</ospfv2>

```

## Command Syntax

```

domain-id A.B.C.D

```

---

## Configure primary domain id hex

Use this attribute to set domain ID in hexadecimal.

This command is supported when following feature are enabled OSPF Virtual Routing and Forwarding (VRF)

Attribute Name: primary-domain-id-hex

Attribute Type: string

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>

```

```

<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
</process>
<domain-id>
<primary-domain>
<hexes>
<hex> <!-- operation="delete"-->
  <primary-domain-id-hex>HEX_DATA</primary-domain-id-hex>
  <config>
    <primary-domain-id-hex>OSPF_DOMAIN_ID_HEX_STRING_T</primary-domain-id-hex>
    <primary-hex-type>type-as</primary-hex-type>
  </config>
  <primary-hex-type>type-as</primary-hex-type>
</hex>
</hexes>
</primary-domain>
</domain-id>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
domain-id type (type-as|type-as4|type-back-comp|type-ip) value HEX_DATA
```

---

## Configure secondary domain id address

Use this attribute to set the secondary domain ID in IPv4 address format.

This command is supported when following feature are enabled OSPF Virtual Routing and Forwarding (VRF)

Attribute Name: secondary-domain-id-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
  <process>
    <ospf-id>0</ospf-id>
    <config>
      <ospf-id>0</ospf-id>
    </config>
  </process>
  <secondary-domain>
  <addresses>
  <address> <!-- operation="delete"-->
    <secondary-domain-id-address>A.B.C.D</secondary-domain-id-address>
  </address>
  <config>
    <secondary-domain-id-address>A.B.C.D</secondary-domain-id-address>
  </config>

```

```

</address>
</addresses>
</secondary-domain>
</domain-id>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
domain-id A.B.C.D secondary
```

---

## Configure secondary domain id hex

Use this attribute to set secondary domain ID in hexadecimal.

This command is supported when following feature are enabled OSPF Virtual Routing and Forwarding (VRF)

Attribute Name: secondary-domain-id-hex

Attribute Type: string

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<domain-id>
<secondary-domain>
<hexes>
<hex> <!-- operation="delete"-->
  <secondary-domain-id-hex>HEX_DATA</secondary-domain-id-hex>
<config>
  <secondary-domain-id-hex>OSPF_DOMAIN_ID_HEX_STRING_T</secondary-domain-id-
hex>
  <secondary-hex-type>type-as</secondary-hex-type>
</config>
  <secondary-hex-type>type-as</secondary-hex-type>
</hex>
</hexes>
</secondary-domain>
</domain-id>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
domain-id type (type-as|type-as4|type-back-comp|type-ip) value HEX_DATA secondary
```

---

## Configure neighbors address

Use this attribute to set the interface IP address of the neighbor.

Attribute Name: address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <neighbors>
      <neighbor> <!-- operation="delete"-->
        <address>A.B.C.D</address>
        <config>
          <address>A.B.C.D</address>
        </config>
      </neighbor>
    </neighbors>
  </process>
</processes>
</ospfv2>
```

### Command Syntax

```
neighbor A.B.C.D
```

---

## Configure poll interval

Use this attribute to set the router cost for point-to-multipoint neighbor.

Attribute Name: cost

Attribute Type: uint16

Default Value: 10

Attribute Range: 1-65535

Attribute Name: priority

Attribute Type: uint8

Default Value: 0

Attribute Range: 0-255

Attribute Name: poll-interval

Attribute Type: uint32

Default Value: 120

Attribute Range: 1-2147483647

**Netconf edit-config payload**

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<neighbors>
<neighbor>
  <address>A.B.C.D</address>
  <config>
    <address>A.B.C.D</address>
    <priority>0</priority> <!-- operation="delete"-->
    <poll-interval>1</poll-interval> <!-- operation="delete"-->
  </config>
  <cost>1</cost> <!-- operation="delete"-->
</neighbor>
</neighbors>
</process>
</processes>
</ospfv2>

```

**Command Syntax**

```
neighbor A.B.C.D { cost <1-65535>| priority <0-255>| poll-interval <1-2147483647> }
```

**Configure termination hold interval**

Use this attribute to set the LFA termination hold on interval. It represents the delay of primary route installation (to avoid micro loop) after a failover.

Attribute Name: termination-hold-interval

Attribute Type: uint32

Default Value: 6000

Attribute Range: 100-100000

**Netconf edit-config payload**

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<timers>
<lfa>
<config>
  <termination-hold-interval>100</termination-hold-interval> <!--
operation="delete"-->

```

```

</config>
</lfa>
</timers>
</process>
</processes>
</ospfv2>

```

### Command Syntax

```
fast-reroute terminate-hold-on interval <100-100000>
```

---

## Configure min arrival interval

Use this attribute to set the minimum interval to accept the same link-state advertisement (LSA) from OSPF neighbors.

Attribute Name: min-arrival-interval

Attribute Type: uint32

Default Value: 1000

Attribute Range: 0-600000

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <lsa>
    <config>
      <min-arrival-interval>0</min-arrival-interval> <!-- operation="delete"-->
    </config>
  </lsa>
</ospfv2>

```

### Command Syntax

```
timers lsa arrival <0-600000>
```

---

## Configure max delay

Use this attribute to set the maximum wait time in milliseconds between generation of the same LSA.

Attribute Name: max-delay

Attribute Type: uint32

Attribute Range: 1-600000

**Netconf edit-config payload**

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
<timers>
<lsa>
<delays>
<delay> <!-- operation="delete"-->
  <max-delay>1</max-delay>
  <config>
    <max-delay>1</max-delay>
    <min-delay>1</min-delay>
    <start-delay>0</start-delay>
  </config>
  <min-delay>1</min-delay>
  <start-delay>0</start-delay>
</delay>
</delays>
</lsa>
</timers>
</process>
</processes>
</ospfv2>

```

**Command Syntax**

```
timers throttle lsa all <0-600000> <1-600000> <1-600000>
```

**Configure min delay**

Use this attribute to set the maximum delay between receiving a change to SPF calculation.

Attribute Name: max-delay

Attribute Type: uint32

Attribute Range: 0-2147483647

Attribute Name: min-delay

Attribute Type: uint32

Attribute Range: 0-2147483647

**Netconf edit-config payload**

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>

```

```

        <ospf-id>0</ospf-id>
    </config>
</timers>
<spf>
<delay>
<config>
    <min-delay>0</min-delay>
    <max-delay>0</max-delay>
</config>
</delay>
</spf>
</timers>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
timers spf exp <0-2147483647> <0-2147483647>
```

---

## Configure default metric

Use this attribute to set a default metric for OSPF. A default metric facilitates redistributing routes with incompatible metrics. If the metrics do not convert, the default metric provides an alternative. Use this attribute to use the same metric value for all redistributed routes. Use this attribute in conjunction with the redistribute command.

Attribute Name: default-metric

Attribute Type: uint32

Default Value: 2

Attribute Range: 1-16777214

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
    <ospf-id>0</ospf-id>
    <config>
        <ospf-id>0</ospf-id>
    </config>
<redistribute>
<config>
    <default-metric>1</default-metric> <!-- operation="delete"-->
</config>
</redistribute>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
default-metric <1-16777214>
```

---

## Configure protocol

This attribute redistributes routes from a routing protocol, static route, or kernel route into an OSPF routing table.

Attribute Name: protocol

Attribute Type: enum (kernel|connected|static|rip|ospf|bgp|isis)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    </process>
  </processes>
  <redistribute>
    <routing-protocols>
      <routing-protocol> <!-- operation="delete"-->
        <protocol>kernel</protocol>
        <config>
          <protocol>kernel</protocol>
        </config>
      </routing-protocol>
    </routing-protocols>
  </redistribute>
</ospfv2>
```

### Command Syntax

```
redistribute (kernel|connected|static|rip|ospf|bgp|isis)
```

---

## Configure metric

Use this attribute to set metric value.

Attribute Name: metric

Attribute Type: uint32

Attribute Range: 0-16777214

Attribute Name: metric-type

Attribute Type: enum (1|2)

Attribute Name: route-map

Attribute Type: string

Attribute Name: tag

Attribute Type: uint32

Attribute Range: 0-4294967295

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```

redistribute (kernel|connected|static|rip|ospf|bgp|isis) { metric <0-16777214>|
metric-type (1|2)| route-map WORD| tag <0-4294967295> }

```

## Configure ospf-processes ospf-process-id

This attribute redistributes routes from an instance of OSPF into another OSPF routing table.

Attribute Name: ospf-process-id

Attribute Type: uint16

Attribute Range: 0-65535

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
</process>
</processes>
</ospfv2>

```

```

    <config>
      <ospf-process-id>0</ospf-process-id>
    </config>
  </ospf-process>
</ospf-processes>
</redistribute>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
redistribute ospf <0-65535>
```

---

## Configure metric type

Use this attribute to set metric value.

Attribute Name: metric

Attribute Type: uint32

Attribute Range: 0-16777214

Attribute Name: metric-type

Attribute Type: enum (1|2)

Attribute Name: route-map

Attribute Type: string

Attribute Name: tag

Attribute Type: uint32

Attribute Range: 0-4294967295

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
        </config>
      <redistribute>
        <ospf-processes>
          <ospf-process>
            <ospf-process-id>0</ospf-process-id>
            <config>
              <ospf-process-id>0</ospf-process-id>
              <metric-type>1</metric-type> <!-- operation="delete"-->
              <route-map>WORD</route-map> <!-- operation="delete"-->
              <tag>0</tag> <!-- operation="delete"-->
            </config>
            <metric>0</metric> <!-- operation="delete"-->
          </ospf-process>
        </ospf-processes>
      </redistribute>
    </process>
  </processes>
</ospfv2>

```

```

</ospf-process>
</ospf-processes>
</redistribute>
</process>
</processes>
</ospfv2>

```

### Command Syntax

```

redistribute ospf <0-65535> { metric <0-16777214>| metric-type (1|2)| route-map
WORD| tag <0-4294967295> }

```

---

## Configure isis process id

This attribute redistributes routes from an instance of IS-IS into an OSPF routing table.

Attribute Name: isis-process-id

Attribute Type: string

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<processes>
<process>
  <ospf-id>0</ospf-id>
  <config>
    <ospf-id>0</ospf-id>
  </config>
</redistribute>
<isis-processes>
<isis-process> <!-- operation="delete"-->
  <isis-process-id>WORD</isis-process-id>
  <config>
    <isis-process-id>WORD</isis-process-id>
  </config>
</isis-process>
</isis-processes>
</redistribute>
</process>
</processes>
</ospfv2>

```

### Command Syntax

```

redistribute isis WORD

```

---

## Configure isis-process metric

Use this attribute to set metric value.

Attribute Name: metric

Attribute Type: uint32

Attribute Range: 0-16777214

Attribute Name: metric-type

Attribute Type: enum (1|2)

Attribute Name: route-map

Attribute Type: string

Attribute Name: tag

Attribute Type: uint32

Attribute Range: 0-4294967295

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <redistribute>
    <isis-processes>
    <isis-process>
      <isis-process-id>WORD</isis-process-id>
      <config>
        <isis-process-id>WORD</isis-process-id>
        <metric-type>1</metric-type> <!-- operation="delete"-->
        <route-map>WORD</route-map> <!-- operation="delete"-->
        <tag>0</tag> <!-- operation="delete"-->
      </config>
      <metric>0</metric> <!-- operation="delete"-->
    </isis-process>
  </isis-processes>
</redistribute>
</process>
</processes>
</ospfv2>
```

### Command Syntax

```
redistribute isis WORD { metric <0-16777214>| metric-type (1|2)| route-map WORD|
tag <0-4294967295> }
```

---

## Configure include stub

Use this attribute to set the metric of a stub link in the router LSA to the default max metric.

This command is supported when following feature are enabled Generate lsa with max-metric

Attribute Name: include-stub

Attribute Type: empty

Attribute Name: enable-max-router-lsa

Attribute Type: empty

Attribute Name: max-external-lsa

Attribute Type: uint32

Attribute Range: 1-16777215

Attribute Name: max-summary-lsa

Attribute Type: uint32

Attribute Range: 1-16777215

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <max-metric>
      <config>
        </enable-max-router-lsa>
        <max-external-lsa>1</max-external-lsa>
        <max-summary-lsa>1</max-summary-lsa>
        </include-stub>
      </config>
    </max-metric>
  </process>
</processes>
</ospfv2>
```

### Command Syntax

```
max-metric router-lsa { external-lsa (<1-16777215>|)| summary-lsa (<1-16777215>|)|
  include-stub }
```

---

## Configure enable max router lsa

Use this attribute to set the metric in the router LSA to the default max metric.

This command is supported when following feature are enabled Generate lsa with max-metric

Attribute Name: enable-max-router-lsa

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <max-metric>
```

```

<config>
  </enable-max-router-lsa>
</config>
</max-metric>
</process>
</processes>
</ospfv2>

```

## Command Syntax

```
max-metric router-lsa
```

---

## Configure on startup include stub

Use this attribute to set the metric of a stub link in the router LSA to the default max metric.

This command is supported when following feature are enabled Generate lsa with max-metric

Attribute Name: on-startup-include-stub

Attribute Type: empty

Attribute Name: max-on-startup

Attribute Type: uint32

Attribute Range: 5-86400

Attribute Name: max-on-startup-external-lsa

Attribute Type: uint32

Attribute Range: 1-16777215

Attribute Name: max-on-startup-summary-lsa

Attribute Type: uint32

Attribute Range: 1-16777215

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <processes>
    <process>
      <ospf-id>0</ospf-id>
      <config>
        <ospf-id>0</ospf-id>
      </config>
    <max-metric-on-startup>
      <config>
        <max-on-startup>5</max-on-startup>
        <max-on-startup-external-lsa>1</max-on-startup-external-lsa>
        <max-on-startup-summary-lsa>1</max-on-startup-summary-lsa>
        </on-startup-include-stub>
      </config>
    </max-metric-on-startup>
  </process>
</processes>

```

```
</ospfv2>
```

## Command Syntax

```
max-metric router-lsa on-startup <5-86400> { external-lsa (<1-16777215>|)| summary-  
lsa (<1-16777215>|)| include-stub }
```

---

## Configure max on startup

Use this attribute to set the metric for router LSA on-startup for the transit link to the default max metric.

This command is supported when following feature are enabled Generate lsa with max-metric

Attribute Name: max-on-startup

Attribute Type: uint32

Attribute Range: 5-86400

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">  
<processes>  
<process>  
  <ospf-id>0</ospf-id>  
  <config>  
    <ospf-id>0</ospf-id>  
  </config>  
<max-metric-on-startup>  
<config>  
  <max-on-startup>5</max-on-startup>  
</config>  
</max-metric-on-startup>  
</process>  
</processes>  
</ospfv2>
```

## Command Syntax

```
max-metric router-lsa on-startup <5-86400>
```

---

## Configure ospfv2-processes ospf-process-id

Use this attribute to set the OSPF process ID in which to enable multi-area adjacency.

Attribute Name: ospf-process-id

Attribute Type: uint16

Attribute Range: 0-65535

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">  
<multi-area-interfaces>  
<multi-area-interface>  
  <name>WORD</name>  
  <config>
```

```

        <name>WORD</name>
    </config>
</ospfv2-processes>
<ospfv2-process> <!-- operation="delete"-->
    <ospf-process-id>0</ospf-process-id>
    <config>
        <ospf-process-id>0</ospf-process-id>
    </config>
</ospfv2-process>
</ospfv2-processes>
</multi-area-interface>
</multi-area-interfaces>
</ospfv2>

```

### Command Syntax

```
ip ospf <0-65535>
```

---

## Configure ospfv2-processes ospf-process-id

Use this attribute to set the OSPF process ID in which to enable multi-area adjacency.

Attribute Name: ospf-process-id

Attribute Type: uint16

Attribute Range: 0-65535

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<multi-area-interfaces>
<multi-area-interface>
    <name>WORD</name>
    <config>
        <name>WORD</name>
    </config>
</multi-area-interface>
</multi-area-interfaces>
</ospfv2>

```

### Command Syntax

```
ip ospf <0-65535>
```

---

## Configure multi-areas area-id

Use this attribute to set the OSPF area ID in which to enable multi-area adjacency.

This command is supported when following feature are enabled HAVE\_OSPF\_MULTI\_AREA

Attribute Name: area-id

Attribute Type: union

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <multi-area-interfaces>
    <multi-area-interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </multi-area-interface>
  </multi-area-interfaces>
  <ospfv2-processes>
    <ospfv2-process>
      <ospf-process-id>0</ospf-process-id>
      <config>
        <ospf-process-id>0</ospf-process-id>
      </config>
      <multi-areas>
        <multi-area> <!-- operation="delete"-->
          <area-id>OSPF_AREA_T</area-id>
          <config>
            <area-id>OSPF_AREA_T</area-id>
          </config>
        </multi-area>
      </multi-areas>
    </ospfv2-process>
  </ospfv2-processes>
</multi-area-interface>
</multi-area-interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf <0-65535> multi-area (A.B.C.D|<0-4294967295>)
```

---

## Configure neighbor

Use this attribute to set the OSPF area ID in which to enable multi-area adjacency.

This command is supported when following feature are enabled HAVE\_OSPF\_MULTI\_AREA

Attribute Name: area-id

Attribute Type: union

Attribute Name: neighbor

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<multi-area-interfaces>
<multi-area-interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</multi-area-interface>
</multi-area-interfaces>
<ospfv2-processes>
<ospfv2-process>
  <ospf-process-id>0</ospf-process-id>
  <config>
    <ospf-process-id>0</ospf-process-id>
  </config>
  <multi-areas-neighbors>
  <multi-area-neighbor> <!-- operation="delete"-->
    <area-id>OSPF_AREA_T</area-id>
    <config>
      <area-id>OSPF_AREA_T</area-id>
      <neighbor>A.B.C.D</neighbor>
    </config>
  </multi-area-neighbor>
</multi-areas-neighbors>
</ospfv2-process>
</ospfv2-processes>
</multi-area-interface>
</multi-area-interfaces>
</ospfv2>
```

## Command Syntax

```
ip ospf <0-65535> multi-area (A.B.C.D|<0-4294967295>) neighbor A.B.C.D
```

---

## Configure rate limit

Use this attribute to enable OSPF Database Timers Rate Limiting Values for LSA Throttling debug.

Attribute Name: rate-limit

Attribute Type: uint8

Attribute Name: bfd

Attribute Type: empty

Attribute Name: route

Attribute Type: bits (spf|ia|ase|install|spf-terse)

Attribute Name: rib

Attribute Type: bits (interface|redistribute)

Attribute Name: nsm

Attribute Type: bits (interface|redistribute)

Attribute Name: n fsm

Attribute Type: bits (status|events|timers)

Attribute Name: lsa

Attribute Type: bits (generate|flooding|install|refresh|maxage)

Attribute Name: ifsm

Attribute Type: bits (status|events|timers)

Attribute Name: events

Attribute Type: bits (abr|nssa|asbr|vlink|lsa|os|router)

Attribute Name: retransmission

Attribute Type: empty

Attribute Name: policy

Attribute Type: empty

Attribute Name: redistribute

Attribute Type: bits (detail|terse)

Attribute Name: graceful-restart

Attribute Type: bits (detail|terse)

Attribute Name: packet-hello

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-dd

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-ls-request

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-ls-update

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-ls-ack

Attribute Type: bits (send|recv|detail)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    </bfd><!-- operation="delete"-->
    <route>spf</route> <!-- operation="delete"-->
    <rib>interface</rib> <!-- operation="delete"-->
    <nsm>interface</nsm> <!-- operation="delete"-->
    <n fsm>status</n fsm> <!-- operation="delete"-->
    <lsa>generate</lsa> <!-- operation="delete"-->
    <ifsm>status</ifsm> <!-- operation="delete"-->
    <events>abr</events> <!-- operation="delete"-->
    </retransmission><!-- operation="delete"-->
    </policy><!-- operation="delete"-->
```

```

    <redistribute>detail</redistribute> <!-- operation="delete"-->
    <graceful-restart>detail</graceful-restart> <!-- operation="delete"-->
    <packet-hello>send</packet-hello> <!-- operation="delete"-->
    <packet-dd>send</packet-dd> <!-- operation="delete"-->
    <packet-ls-request>send</packet-ls-request> <!-- operation="delete"-->
    <packet-ls-update>send</packet-ls-update> <!-- operation="delete"-->
    <packet-ls-ack>send</packet-ls-ack> <!-- operation="delete"-->
    </rate-limit><!-- operation="delete"-->
</config>
</debug>
</ospfv2>

```

## Command Syntax

```
debug ospf
```

---

## Configure bfd

Use this attribute to enable OSPF Database Timers Rate Limiting Values for LSA Throttling debug.

Attribute Name: rate-limit

Attribute Type: uint8

Attribute Name: bfd

Attribute Type: empty

Attribute Name: route

Attribute Type: bits (spf|ia|ase|install|spf-terse)

Attribute Name: rib

Attribute Type: bits (interface|redistribute)

Attribute Name: nsm

Attribute Type: bits (interface|redistribute)

Attribute Name: nasm

Attribute Type: bits (status|events|timers)

Attribute Name: lsa

Attribute Type: bits (generate|flooding|install|refresh|maxage)

Attribute Name: ifsm

Attribute Type: bits (status|events|timers)

Attribute Name: events

Attribute Type: bits (abr|nssa|asbr|vlink|lsa|os|router)

Attribute Name: retransmission

Attribute Type: empty

Attribute Name: policy

Attribute Type: empty

Attribute Name: redistribute

Attribute Type: bits (detail|terse)

Attribute Name: graceful-restart

Attribute Type: bits (detail|terse)

Attribute Name: packet-hello

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-dd

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-ls-request

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-ls-update

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-ls-ack

Attribute Type: bits (send|recv|detail)

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    </bfd><!-- operation="delete"-->
    <route>spf</route> <!-- operation="delete"-->
    <rib>interface</rib> <!-- operation="delete"-->
    <nsm>interface</nsm> <!-- operation="delete"-->
    <nfsm>status</nfsm> <!-- operation="delete"-->
    <lsa>generate</lsa> <!-- operation="delete"-->
    <ifsm>status</ifsm> <!-- operation="delete"-->
    <events>abr</events> <!-- operation="delete"-->
    </retransmission><!-- operation="delete"-->
    </policy><!-- operation="delete"-->
    <redistribute>detail</redistribute> <!-- operation="delete"-->
    <graceful-restart>detail</graceful-restart> <!-- operation="delete"-->
    <packet-hello>send</packet-hello> <!-- operation="delete"-->
    <packet-dd>send</packet-dd> <!-- operation="delete"-->
    <packet-ls-request>send</packet-ls-request> <!-- operation="delete"-->
    <packet-ls-update>send</packet-ls-update> <!-- operation="delete"-->
    <packet-ls-ack>send</packet-ls-ack> <!-- operation="delete"-->
    </rate-limit><!-- operation="delete"-->
  </config>
</debug>
</ospfv2>
```

## Command Syntax

```
debug ospf all
```

---

## Configure retransmission

Use this attribute to enable OSPF Debug retransmission information debug.

Attribute Name: retransmission

Attribute Type: uint8

Attribute Name: policy

Attribute Type: empty

Attribute Name: redistribute

Attribute Type: bits (detail|terse)

Attribute Name: graceful-restart

Attribute Type: bits (detail|terse)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    </policy><!-- operation="delete"-->
    <redistribute>detail</redistribute> <!-- operation="delete"-->
    <graceful-restart>detail</graceful-restart> <!-- operation="delete"-->
    </retransmission><!-- operation="delete"-->
  </config>
</debug>
</ospfv2>
```

### Command Syntax

```
debug ip ospf all
```

---

## Configure debug bfd

Use this attribute to enable Bidirectional Forwarding Detection (BFD) debug.

Attribute Name: bfd

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    </bfd><!-- operation="delete"-->
  </config>
</debug>
</ospfv2>
```

### Command Syntax

```
debug ospf bfd
```

---

## Configure debug rate-limit

Use this attribute to enable OSPF Database Timers Rate Limiting Values for LSA Throttling debug.

Attribute Name: rate-limit

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    </rate-limit><!-- operation="delete"-->
  </config>
</debug>
</ospfv2>
```

### Command Syntax

```
debug ospf database-timer rate-limit
```

---

## Configure route

Use this attribute to enable OSPF route information debug.

Attribute Name: route

Attribute Type: bits (spf|ia|ase|install|spf-terse)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    <route>spf</route> <!-- operation="delete"-->
  </config>
</debug>
</ospfv2>
```

### Command Syntax

```
debug ospf route ({spf|ia|ase|install|spf-terse}|)
```

---

## Configure rib

Use this attribute to enable OSPF RIB information debug.

Attribute Name: rib

Attribute Type: bits (interface|redistribute)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    <rib>interface</rib> <!-- operation="delete"-->
  </config>
</debug>
</ospfv2>
```

```
</config>  
</debug>  
</ospfv2>
```

### Command Syntax

```
debug ospf rib ({interface|redistribute|})
```

---

## Configure nsm

Use this attribute to enable OSPF NSM information debug.

Attribute Name: nsm

Attribute Type: bits (interface|redistribute)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">  
<debug>  
<config>  
  <nsm>interface</nsm> <!-- operation="delete"-->  
</config>  
</debug>  
</ospfv2>
```

### Command Syntax

```
debug ospf nsm ({interface|redistribute|})
```

---

## Configure nfsm

Use this attribute to enable OSPF Neighbor State Machine debug.

Attribute Name: nfsm

Attribute Type: bits (status|events|timers)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">  
<debug>  
<config>  
  <nfsm>status</nfsm> <!-- operation="delete"-->  
</config>  
</debug>  
</ospfv2>
```

### Command Syntax

```
debug ospf nfsm ({status|events|timers|})
```

---

## Configure lsa

Use this attribute to enable OSPF Link State Advertisement debug.

Attribute Name: lsa

Attribute Type: bits (generate|flooding|install|refresh|maxage)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    <lsa>generate</lsa> <!-- operation="delete"-->
  </config>
</debug>
</ospfv2>
```

### Command Syntax

```
debug ospf lsa ({generate|flooding|install|refresh|maxage}|)
```

---

## Configure ifsm

Use this attribute to enable OSPF Interface State Machine debug.

Attribute Name: ifsm

Attribute Type: bits (status|events|timers)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    <ifsm>status</ifsm> <!-- operation="delete"-->
  </config>
</debug>
</ospfv2>
```

### Command Syntax

```
debug ospf ifsm ({status|events|timers}|)
```

---

## Configure events

Use this attribute to enable OSPF events information debug.

Attribute Name: events

Attribute Type: bits (abr|nssa|asbr|vlink|lsa|os|router)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    <events>abr</events> <!-- operation="delete"-->
  </config>
</debug>
</ospfv2>
```

---

## Command Syntax

```
debug ospf events ({abr|nssa|asbr|vlink|lsa|os|router}|)
```

---

## Configure debug retransmission

Use this attribute to enable OSPF Debug retransmission information debug.

Attribute Name: retransmission

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
    <config>
      </retransmission><!-- operation="delete"-->
    </config>
  </debug>
</ospfv2>
```

## Command Syntax

```
debug ip ospf retransmission
```

---

## Configure lfa

Use this attribute to enable OSPF LFA route install details debug.

Attribute Name: lfa

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
    <config>
      </lfa><!-- operation="delete"-->
    </config>
  </debug>
</ospfv2>
```

## Command Syntax

```
debug ip ospf lfa
```

---

## Configure policy

Use this attribute to enable OSPF policy information debug.

Attribute Name: policy

Attribute Type: empty

---

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    </policy><!-- operation="delete"-->
  </config>
</debug>
</ospfv2>
```

## Command Syntax

```
debug ip ospf policy
```

---

## Configure redistribute

Use this attribute to enable OSPF redistribute information debug.

Attribute Name: redistribute

Attribute Type: bits (detail|terse)

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    <redistribute>detail</redistribute> <!-- operation="delete"-->
  </config>
</debug>
</ospfv2>
```

## Command Syntax

```
debug ip ospf redistribute ({{detail|terse}})
```

---

## Configure graceful restart

Use this attribute to enable OSPF graceful-restart debug.

Attribute Name: graceful-restart

Attribute Type: bits (detail|terse)

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    <graceful-restart>detail</graceful-restart> <!-- operation="delete"-->
  </config>
</debug>
</ospfv2>
```

## Command Syntax

```
debug ip ospf graceful-restart ({{detail|terse}})
```

---

## Configure packet hello

OSPF Hello

Attribute Name: packet-hello

Attribute Type: bits (send|recv|detail)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    <packet-hello>send</packet-hello> <!-- operation="delete"-->
  </config>
</debug>
</ospfv2>
```

### Command Syntax

```
debug ospf packet hello ({send|recv|detail}|)
```

---

## Configure packet dd

OSPF Database Description

Attribute Name: packet-dd

Attribute Type: bits (send|recv|detail)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    <packet-dd>send</packet-dd> <!-- operation="delete"-->
  </config>
</debug>
</ospfv2>
```

### Command Syntax

```
debug ospf packet dd ({send|recv|detail}|)
```

---

## Configure packet ls request

OSPF Link State Request

Attribute Name: packet-ls-request

Attribute Type: bits (send|recv|detail)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
  <config>
    <packet-ls-request>send</packet-ls-request> <!-- operation="delete"-->
  </config>
</debug>
</ospfv2>
```

```
</config>
</debug>
</ospfv2>
```

## Command Syntax

```
debug ospf packet ls-request ({send|rcv|detail|})
```

---

## Configure packet ls update

OSPF Link State Update

Attribute Name: packet-ls-update

Attribute Type: bits (send|rcv|detail)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
    <config>
      <packet-ls-update>send</packet-ls-update> <!-- operation="delete"-->
    </config>
  </debug>
</ospfv2>
```

## Command Syntax

```
debug ospf packet ls-update ({send|rcv|detail|})
```

---

## Configure packet ls ack

OSPF Link State Acknowledgment

Attribute Name: packet-ls-ack

Attribute Type: bits (send|rcv|detail)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <debug>
    <config>
      <packet-ls-ack>send</packet-ls-ack> <!-- operation="delete"-->
    </config>
  </debug>
</ospfv2>
```

## Command Syntax

```
debug ospf packet ls-ack ({send|rcv|detail|})
```

---

## clear ip ospf <0-65535> process

Attribute Name: process-id

Attribute Type: uint16

---

Attribute Range: 0-65535

### Netconf RPC payload

```
<ospfv2-clear-process xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <process-id>0</process-id>
</ospfv2-clear-process>
```

### Command Syntax

```
clear ip ospf <0-65535> process
```

---

## clear ip ospf process

### Netconf RPC payload

```
<ospfv2-clear-process-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf"/>
```

### Command Syntax

```
clear ip ospf process
```

---

## restart ip ospf graceful (grace-period <2-1800>|)

Attribute Name: grace-period

Attribute Type: uint16

Attribute Range: 2-1800

### Netconf RPC payload

```
<ospfv2-restart-graceful xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <grace-period>2</grace-period>
</ospfv2-restart-graceful>
```

### Command Syntax

```
restart ip ospf graceful (grace-period <2-1800>|)
```

---

## snmp restart ospf

### Netconf RPC payload

```
<ospfv2-snmp-restart xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf"/>
```

### Command Syntax

```
snmp restart ospf
```

---

## debug ospf all

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-ospf-all-on xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospf"/>
```

---

## Command Syntax

```
debug ospf all
```

---

## no debug ospf all

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-ospf-all-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf"/>
```

### Command Syntax

```
no debug ospf all
```

---

## debug ospf bfd

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-bfd-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf"/>
```

### Command Syntax

```
debug ospf bfd
```

---

## no debug ospf bfd

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-bfd-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf"/>
```

### Command Syntax

```
no debug ospf bfd
```

---

## debug ospf database-timer rate-limit

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-rate-limit-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf"/>
```

### Command Syntax

```
debug ospf database-timer rate-limit
```

---

## no debug ospf database-timer rate-limit

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-rate-limit-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf"/>
```

---

## Command Syntax

```
no debug ospf database-timer rate-limit
```

---

## debug ospf route ({spf|ia|ase|install|spf-terse|})

Attribute Name: route

Attribute Type: bits (spf|ia|ase|install|spf-terse)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-route-on xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-ospf">
  <route>spf</route>
</ipi-ospf-debug_ospfv2-terminal-debug-route-on>
```

## Command Syntax

```
debug ospf route ({spf|ia|ase|install|spf-terse|})
```

---

## no debug ospf route ({spf|ia|ase|install|spf-terse|})

Attribute Name: route

Attribute Type: bits (spf|ia|ase|install|spf-terse)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-route-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <route>spf</route>
</ipi-ospf-debug_ospfv2-terminal-debug-route-off>
```

## Command Syntax

```
no debug ospf route ({spf|ia|ase|install|spf-terse|})
```

---

## debug ospf rib ({interface|redistribute|})

Attribute Name: rib

Attribute Type: bits (interface|redistribute)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-rib-on xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-ospf">
  <rib>interface</rib>
</ipi-ospf-debug_ospfv2-terminal-debug-rib-on>
```

## Command Syntax

```
debug ospf rib ({interface|redistribute|})
```

---

## no debug ospf rib ({interface|redistribute|})

Attribute Name: rib

---

Attribute Type: bits (interface|redistribute)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-rib-off xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-ospf">
  <rib>interface</rib>
</ipi-ospf-debug_ospfv2-terminal-debug-rib-off>
```

### Command Syntax

```
no debug ospf rib ({interface|redistribute|})
```

---

## debug ospf packet ({send|recv|detail|})

Attribute Name: all

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-packet-all-on xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <all>send</all>
</ipi-ospf-debug_ospfv2-terminal-debug-packet-all-on>
```

### Command Syntax

```
debug ospf packet ({send|recv|detail|})
```

---

## no debug ospf packet ({send|recv|detail|})

Attribute Name: all

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-packet-all-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <all>send</all>
</ipi-ospf-debug_ospfv2-terminal-debug-packet-all-off>
```

### Command Syntax

```
no debug ospf packet ({send|recv|detail|})
```

---

## debug ospf packet hello ({send|recv|detail|})

Attribute Name: hello

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-packet-hello-on xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <hello>send</hello>
</ipi-ospf-debug_ospfv2-terminal-debug-packet-hello-on>
```

---

## Command Syntax

```
debug ospf packet hello ({send|recv|detail}|)
```

---

## no debug ospf packet hello ({send|recv|detail}|)

Attribute Name: hello

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-packet-hello-off xmlns="http://  
www.ipinfusion.com/yang/ocnos/ipi-ospf">  
  <hello>send</hello>  
</ipi-ospf-debug_ospfv2-terminal-debug-packet-hello-off>
```

## Command Syntax

```
no debug ospf packet hello ({send|recv|detail}|)
```

---

## debug ospf packet dd ({send|recv|detail}|)

Attribute Name: dd

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-packet-dd-on xmlns="http://  
www.ipinfusion.com/yang/ocnos/ipi-ospf">  
  <dd>send</dd>  
</ipi-ospf-debug_ospfv2-terminal-debug-packet-dd-on>
```

## Command Syntax

```
debug ospf packet dd ({send|recv|detail}|)
```

---

## no debug ospf packet dd ({send|recv|detail}|)

Attribute Name: dd

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-packet-dd-off xmlns="http://  
www.ipinfusion.com/yang/ocnos/ipi-ospf">  
  <dd>send</dd>  
</ipi-ospf-debug_ospfv2-terminal-debug-packet-dd-off>
```

## Command Syntax

```
no debug ospf packet dd ({send|recv|detail}|)
```

---

## debug ospf packet ls-request ({send|recv|detail}|)

Attribute Name: ls-request

---

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-packet-ls-request-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <ls-request>send</ls-request>
</ipi-ospf-debug_ospfv2-terminal-debug-packet-ls-request-on>
```

### Command Syntax

```
debug ospf packet ls-request ({send|recv|detail}|)
```

---

## no debug ospf packet ls-request ({send|recv|detail}|)

Attribute Name: ls-request

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-packet-ls-request-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <ls-request>send</ls-request>
</ipi-ospf-debug_ospfv2-terminal-debug-packet-ls-request-off>
```

### Command Syntax

```
no debug ospf packet ls-request ({send|recv|detail}|)
```

---

## debug ospf packet ls-update ({send|recv|detail}|)

Attribute Name: ls-update

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-packet-ls-update-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <ls-update>send</ls-update>
</ipi-ospf-debug_ospfv2-terminal-debug-packet-ls-update-on>
```

### Command Syntax

```
debug ospf packet ls-update ({send|recv|detail}|)
```

---

## no debug ospf packet ls-update ({send|recv|detail}|)

Attribute Name: ls-update

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-packet-ls-update-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <ls-update>send</ls-update>
</ipi-ospf-debug_ospfv2-terminal-debug-packet-ls-update-off>
```

---

## Command Syntax

```
no debug ospf packet ls-update ({send|recv|detail}|)
```

---

## debug ospf packet ls-ack ({send|recv|detail}|)

Attribute Name: ls-ack

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-packet-ls-ack-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <ls-ack>send</ls-ack>
</ipi-ospf-debug_ospfv2-terminal-debug-packet-ls-ack-on>
```

## Command Syntax

```
debug ospf packet ls-ack ({send|recv|detail}|)
```

---

## no debug ospf packet ls-ack ({send|recv|detail}|)

Attribute Name: ls-ack

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-packet-ls-ack-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <ls-ack>send</ls-ack>
</ipi-ospf-debug_ospfv2-terminal-debug-packet-ls-ack-off>
```

## Command Syntax

```
no debug ospf packet ls-ack ({send|recv|detail}|)
```

---

## debug ospf nsm ({interface|redistribute}|)

Attribute Name: nsm

Attribute Type: bits (interface|redistribute)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-nsm-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <nsm>interface</nsm>
</ipi-ospf-debug_ospfv2-terminal-debug-nsm-on>
```

## Command Syntax

```
debug ospf nsm ({interface|redistribute}|)
```

---

## no debug ospf nsm ({interface|redistribute}|)

Attribute Name: nsm

Attribute Type: bits (interface|redistribute)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-nsm-off xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-ospf">
  <nsm>interface</nsm>
</ipi-ospf-debug_ospfv2-terminal-debug-nsm-off>
```

### Command Syntax

```
no debug ospf nsm ({interface|redistribute|})
```

---

## debug ospf nfsm ({status|events|timers|})

Attribute Name: nfsm

Attribute Type: bits (status|events|timers)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-nfsm-on xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-ospf">
  <nfsm>status</nfsm>
</ipi-ospf-debug_ospfv2-terminal-debug-nfsm-on>
```

### Command Syntax

```
debug ospf nfsm ({status|events|timers|})
```

---

## no debug ospf nfsm ({status|events|timers|})

Attribute Name: nfsm

Attribute Type: bits (status|events|timers)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-nfsm-off xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-ospf">
  <nfsm>status</nfsm>
</ipi-ospf-debug_ospfv2-terminal-debug-nfsm-off>
```

### Command Syntax

```
no debug ospf nfsm ({status|events|timers|})
```

---

## debug ospf lsa ({generate|flooding|install|refresh|maxage|})

Attribute Name: lsa

Attribute Type: bits (generate|flooding|install|refresh|maxage)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-lsa-on xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-ospf">
  <lsa>generate</lsa>
</ipi-ospf-debug_ospfv2-terminal-debug-lsa-on>
```

---

## Command Syntax

```
debug ospf lsa ({generate|flooding|install|refresh|maxage|})
```

---

## no debug ospf lsa ({generate|flooding|install|refresh|maxage|})

Attribute Name: lsa

Attribute Type: bits (generate|flooding|install|refresh|maxage)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-lsa-off xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-ospf">
  <lsa>generate</lsa>
</ipi-ospf-debug_ospfv2-terminal-debug-lsa-off>
```

## Command Syntax

```
no debug ospf lsa ({generate|flooding|install|refresh|maxage|})
```

---

## debug ospf ifsm ({status|events|timers|})

Attribute Name: ifsm

Attribute Type: bits (status|events|timers)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-ifsm-on xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-ospf">
  <ifsm>status</ifsm>
</ipi-ospf-debug_ospfv2-terminal-debug-ifsm-on>
```

## Command Syntax

```
debug ospf ifsm ({status|events|timers|})
```

---

## no debug ospf ifsm ({status|events|timers|})

Attribute Name: ifsm

Attribute Type: bits (status|events|timers)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-ifsm-off xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-ospf">
  <ifsm>status</ifsm>
</ipi-ospf-debug_ospfv2-terminal-debug-ifsm-off>
```

## Command Syntax

```
no debug ospf ifsm ({status|events|timers|})
```

---

## debug ospf events ({abr|nssa|asbr|vlink|lsa|os|router|})

Attribute Name: events

---

Attribute Type: bits (abr|nssa|asbr|vlink|lsa|os|router)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-events-on xmlns="http://  
www.ipinfusion.com/yang/ocnos/ipi-ospf">  
  <events>abr</events>  
</ipi-ospf-debug_ospfv2-terminal-debug-events-on>
```

### Command Syntax

```
debug ospf events ({abr|nssa|asbr|vlink|lsa|os|router}|)
```

---

## no debug ospf events ({abr|nssa|asbr|vlink|lsa|os|router}|)

Attribute Name: events

Attribute Type: bits (abr|nssa|asbr|vlink|lsa|os|router)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-events-off xmlns="http://  
www.ipinfusion.com/yang/ocnos/ipi-ospf">  
  <events>abr</events>  
</ipi-ospf-debug_ospfv2-terminal-debug-events-off>
```

### Command Syntax

```
no debug ospf events ({abr|nssa|asbr|vlink|lsa|os|router}|)
```

---

## debug ip ospf all

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-all-on xmlns="http://www.ipinfusion.com/  
yang/ocnos/ipi-ospf"/>
```

### Command Syntax

```
debug ip ospf all
```

---

## no debug ip ospf all

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-all-off xmlns="http://www.ipinfusion.com/  
yang/ocnos/ipi-ospf"/>
```

### Command Syntax

```
no debug ip ospf all
```

---

## debug ip ospf retransmission

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-retransmission-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf"/>
```

### Command Syntax

```
debug ip ospf retransmission
```

---

## no debug ip ospf retransmission

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-retransmission-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf"/>
```

### Command Syntax

```
no debug ip ospf retransmission
```

---

## debug ip ospf lfa

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-lfa-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf"/>
```

### Command Syntax

```
debug ip ospf lfa
```

---

## no debug ip ospf lfa

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-lfa-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf"/>
```

### Command Syntax

```
no debug ip ospf lfa
```

---

## debug ip ospf policy

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-policy-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf"/>
```

### Command Syntax

```
debug ip ospf policy
```

---

## no debug ip ospf policy

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-policy-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf"/>
```

### Command Syntax

```
no debug ip ospf policy
```

---

## debug ip ospf redistribute ({detail|terse})

Attribute Name: redistribute

Attribute Type: bits (detail|terse)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-redistribute-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">  
  <redistribute>detail</redistribute>  
</ipi-ospf-debug_ospfv2-terminal-debug-redistribute-on>
```

### Command Syntax

```
debug ip ospf redistribute ({detail|terse})
```

---

## no debug ip ospf redistribute ({detail|terse})

Attribute Name: redistribute

Attribute Type: bits (detail|terse)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-redistribute-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">  
  <redistribute>detail</redistribute>  
</ipi-ospf-debug_ospfv2-terminal-debug-redistribute-off>
```

### Command Syntax

```
no debug ip ospf redistribute ({detail|terse})
```

---

## debug ip ospf graceful-restart ({detail|terse})

Attribute Name: graceful-restart

Attribute Type: bits (detail|terse)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-graceful-restart-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">  
  <graceful-restart>detail</graceful-restart>  
</ipi-ospf-debug_ospfv2-terminal-debug-graceful-restart-on>
```

## Command Syntax

```
debug ip ospf graceful-restart ({detail|terse}|)
```

## no debug ip ospf graceful-restart ({detail|terse}|)

Attribute Name: graceful-restart

Attribute Type: bits (detail|terse)

### Netconf RPC payload

```
<ipi-ospf-debug_ospfv2-terminal-debug-graceful-restart-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <graceful-restart>detail</graceful-restart>
</ipi-ospf-debug_ospfv2-terminal-debug-graceful-restart-off>
```

## Command Syntax

```
no debug ip ospf graceful-restart ({detail|terse}|)
```

# IPI-OSPF-INTERFACE

## Configure cost

Use this attribute to explicitly specify the cost of the link-state metric in a router-LSA.

Attribute Name: cost

Attribute Type: uint16

Default Value: 1

Attribute Range: 1-65535

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <cost>1</cost> <!-- operation="delete"-->
    </interface>
  </interfaces>
</ospfv2>
```

## Command Syntax

```
ip ospf cost <1-65535>
```

---

## Configure priority

Use this attribute to set the router priority to determine the designated router (DR) for the network.

Attribute Name: priority

Attribute Type: uint8

Default Value: 1

Attribute Range: 0-255

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <priority>0</priority> <!-- operation="delete"-->
    </interface>
  </interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf priority <0-255>
```

---

## Configure mtu ignore

Use this attribute to configure OSPF so that it does not check the MTU size during DD (Database Description) exchange.

Attribute Name: mtu-ignore

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </mtu-ignore><!-- operation="delete"-->
    </interface>
  </interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf mtu-ignore
```

---

## Configure network type

Use this attribute to set the interface network type.

Attribute Name: network-type

Attribute Type: enum (point-to-point|broadcast|non-broadcast|point-to-multipoint|point-to-multipoint non-broadcast)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <network-type>point-to-point</network-type> <!-- operation="delete"-->
    </interface>
  </interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf network (point-to-point|broadcast|non-broadcast|point-to-multipoint|point-
to-multipoint non-broadcast)
```

---

## Configure disable all ospf

Use this attribute to completely disable OSPF packet processing on an interface.

Attribute Name: disable-all-ospf

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </disable-all-ospf><!-- operation="delete"-->
    </interface>
  </interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf disable all
```

---

## Configure mtu

Use this attribute to set MTU size for OSPF to construct packets based on this value.

Attribute Name: mtu

Attribute Type: uint16

Default Value: 576

Attribute Range: 576-65535

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <mtu>576</mtu> <!-- operation="delete"-->
</interface>
</interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf mtu <576-65535>
```

---

## Configure enable flood reduction

Use this attribute to enable flood reduction on an interface.

Attribute Name: enable-flood-reduction

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </enable-flood-reduction><!-- operation="delete"-->
</interface>
</interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf flood-reduction
```

---

## Configure enable demand circuit

Use this attribute to enable Hello Suppression and LSA Suppression sent on OSPF interface.

Attribute Name: enable-demand-circuit

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </enable-demand-circuit><!-- operation="delete"-->
    </interface>
  </interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf demand-circuit
```

---

## Configure enable bfd

Use this attribute to enable Bidirectional Forwarding Detection (BFD).

Attribute Name: enable-bfd

Attribute Type: enum (enable|disable)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <enable-bfd>enable</enable-bfd> <!-- operation="delete"-->
    </interface>
  </interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf bfd (disable|)
```

---

## Configure disable fast reroute

Use this attribute to prohibit the interface from being used as the next hop in a repair path.

Attribute Name: disable-fast-reroute

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
```

```

<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </disable-fast-reroute><!-- operation="delete"-->
</interface>
</interfaces>
</ospfv2>

```

## Command Syntax

```
ip ospf fast-reroute per-prefix candidate disable
```

---

## Configure message digest id

Use this attribute to set the authentication message digest key ID.

Attribute Name: message-digest-id

Attribute Type: uint8

Attribute Range: 1-255

Attribute Name: message-digest-encryption-type

Attribute Type: enum (md5)

Attribute Name: message-digest-key

Attribute Type: string

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <addresses>
  <address>
    <interface-address>A.B.C.D</interface-address>
    <config>
      <interface-address>A.B.C.D</interface-address>
    </config>
    <authentication>
    <message-digests>
    <message-digest>
      <message-digest-id>1</message-digest-id>
    <config>
      <message-digest-id>1</message-digest-id>
      <message-digest-encryption-type>md5</message-digest-encryption-type>
      <message-digest-key>WORD</message-digest-key>
    </config>
  </address>
  </addresses>
</interface>
</interfaces>
</ospfv2>

```

```

        </config>
    </message-digest>
</message-digests>
</authentication>
</address>
</addresses>
</interface>
</interfaces>
</ospfv2>

```

## Command Syntax

```
ip ospf A.B.C.D message-digest-key <1-255> (md5) WORD
```

---

## Configure name

Use this attribute to set the authentication message digest key ID.

Attribute Name: message-digest-id

Attribute Type: uint8

Attribute Range: 1-255

Attribute Name: message-digest-encryption-type

Attribute Type: enum (md5)

Attribute Name: message-digest-key

Attribute Type: string

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <authentication>
        <message-digests>
          <message-digest>
            <message-digest-id>1</message-digest-id>
            <config>
              <message-digest-id>1</message-digest-id>
              <message-digest-encryption-type>md5</message-digest-encryption-type>
              <message-digest-key>WORD</message-digest-key>
            </config>
          </message-digest>
        </message-digests>
      </authentication>
    </interface>
  </interfaces>
</ospfv2>

```

## Command Syntax

```
ip ospf message-digest-key <1-255> (md5) WORD
```

---

## Configure authentication type

Use this attribute to configure authentication on this interface.

Attribute Name: authentication-type

Attribute Type: enum (null|simple|message-digest)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <addresses>
  <address>
    <interface-address>A.B.C.D</interface-address>
    <config>
      <interface-address>A.B.C.D</interface-address>
    </config>
    <authentication>
    <config>
      <authentication-type>simple</authentication-type> <!--
operation="delete"-->
    </config>
    </authentication>
  </address>
</addresses>
</interface>
</interfaces>
</ospfv2>
```

## Command Syntax

```
ip ospf A.B.C.D authentication (null|message-digest|)
```

---

## Configure authentication authentication-type

Use this attribute to configure authentication on this interface.

Attribute Name: authentication-type

Attribute Type: enum (null|simple|message-digest)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
```

```

    <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <authentication>
  <config>
    <authentication-type>simple</authentication-type> <!--
operation="delete"-->
  </config>
</authentication>
</interface>
</interfaces>
</ospfv2>

```

## Command Syntax

```
ip ospf authentication (null|message-digest|)
```

---

## Configure key

Use this attribute to set the authentication password (key).

Attribute Name: key

Attribute Type: string

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
  <interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
    <addresses>
    <address>
      <interface-address>A.B.C.D</interface-address>
      <config>
        <interface-address>A.B.C.D</interface-address>
      </config>
      <authentication>
      <config>
        <key>WORD</key> <!-- operation="delete"-->
      </config>
    </authentication>
  </address>
</addresses>
</interface>
</interfaces>
</ospfv2>

```

---

## Command Syntax

```
ip ospf A.B.C.D authentication-key WORD
```

---

## Configure authentication key

Use this attribute to set the authentication password (key).

Attribute Name: key

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <authentication>
  <config>
    <key>WORD</key> <!-- operation="delete"-->
  </config>
</authentication>
</interface>
</interfaces>
</ospfv2>
```

## Command Syntax

```
ip ospf authentication-key WORD
```

---

## Configure authentication key

Use this attribute to set the authentication password (key).

Attribute Name: key

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <authentication>
  <config>
    <key>WORD</key> <!-- operation="delete"-->
  </config>
</authentication>
```

```
</interface>  
</interfaces>  
</ospfv2>
```

## Command Syntax

```
ip ospf authentication-key WORD
```

---

## Configure authentication authentication-type

Use this attribute to configure authentication on this interface.

Attribute Name: authentication-type

Attribute Type: enum (null|simple|message-digest)

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">  
<interfaces>  
<interface>  
  <name>WORD</name>  
  <config>  
    <name>WORD</name>  
    </config>  
    <authentication>  
    <config>  
      <authentication-type>simple</authentication-type> <!--  
operation="delete"-->  
    </config>  
  </authentication>  
</interface>  
</interfaces>  
</ospfv2>
```

## Command Syntax

```
ip ospf authentication (null|message-digest|)
```

---

## Configure message digest encryption type

Use this attribute to set the authentication message digest key ID.

Attribute Name: message-digest-id

Attribute Type: uint8

Attribute Range: 1-255

Attribute Name: message-digest-encryption-type

Attribute Type: enum (md5)

Attribute Name: message-digest-key

Attribute Type: string

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <authentication>
  <message-digests>
  <message-digest> <!-- operation="delete"-->
    <message-digest-id>1</message-digest-id>
    <config>
      <message-digest-id>1</message-digest-id>
      <message-digest-encryption-type>md5</message-digest-encryption-type>
      <message-digest-key>WORD</message-digest-key>
    </config>
  </message-digest>
</message-digests>
</authentication>
</interface>
</interfaces>
</ospfv2>
```

## Command Syntax

```
ip ospf message-digest-key <1-255> (md5) WORD
```

---

## Configure filter out

Use this attribute to turn on the LSA database-filter for a particular interface. OSPF floods new LSAs over all interfaces in an area, except the interface on which the LSA arrives. This redundancy ensures robust flooding. However, too much redundancy can waste bandwidth and might lead to excessive link and CPU usage in certain topologies, resulting in destabilizing the network. To avoid this, use this attribute to block flooding of LSAs over specified interfaces.

Attribute Name: filter-out

Attribute Type: empty

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <addresses>
  <address>
    <interface-address>A.B.C.D</interface-address>
  </address>
  <config>
    <interface-address>A.B.C.D</interface-address>
  </config>
</interface>
</interfaces>
</ospfv2>
```

```

    </config>
    <database-filter>
    <lsa>
    <config>
        </filter-out><!-- operation="delete"-->
    </config>
    </lsa>
</database-filter>
</address>
</addresses>
</interface>
</interfaces>
</ospfv2>

```

## Command Syntax

```
ip ospf A.B.C.D database-filter all out
```

---

## Configure lsa filter-out

Use this attribute to turn on the LSA database-filter for a particular interface. OSPF floods new LSAs over all interfaces in an area, except the interface on which the LSA arrives. This redundancy ensures robust flooding. However, too much redundancy can waste bandwidth and might lead to excessive link and CPU usage in certain topologies, resulting in destabilizing the network. To avoid this, use this attribute to block flooding of LSAs over specified interfaces.

Attribute Name: filter-out

Attribute Type: empty

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
    <name>WORD</name>
    <config>
        <name>WORD</name>
    </config>
    <addresses>
    <address>
        <interface-address>A.B.C.D</interface-address>
        <config>
            <interface-address>A.B.C.D</interface-address>
        </config>
        <database-filter>
        <lsa>
        <config>
            </filter-out><!-- operation="delete"-->
        </config>
        </lsa>
    </database-filter>
    </address>
</addresses>

```

```

</interface>
</interfaces>
</ospfv2>

```

## Command Syntax

```
ip ospf database-filter all out
```

---

## Configure lsa filter-out

Use this attribute to turn on the LSA database-filter for a particular interface. OSPF floods new LSAs over all interfaces in an area, except the interface on which the LSA arrives. This redundancy ensures robust flooding. However, too much redundancy can waste bandwidth and might lead to excessive link and CPU usage in certain topologies, resulting in destabilizing the network. To avoid this, use this attribute to block flooding of LSAs over specified interfaces.

Attribute Name: filter-out

Attribute Type: empty

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <database-filter>
  <lsa>
  <config>
    </filter-out><!-- operation="delete"-->
  </config>
</lsa>
</database-filter>
</interface>
</interfaces>
</ospfv2>

```

## Command Syntax

```
ip ospf database-filter all out
```

---

## Configure dead interval

Use this attribute to set the interval during which the router waits to receive an OSPF hello packet from the neighbor before declaring the neighbor down.

Attribute Name: dead-interval

Attribute Type: uint16

Attribute Range: 1-65535

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
```

```

<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <addresses>
  <address>
    <interface-address>A.B.C.D</interface-address>
    <config>
      <interface-address>A.B.C.D</interface-address>
    </config>
    <timers>
    <config>
      <dead-interval>1</dead-interval> <!-- operation="delete"-->
    </config>
  </timers>
</address>
</addresses>
</interface>
</interfaces>
</ospfv2>

```

## Command Syntax

```
ip ospf A.B.C.D dead-interval <1-65535>
```

---

## Configure timers dead-interval

Use this attribute to set the interval during which the router waits to receive an OSPF hello packet from the neighbor before declaring the neighbor down.

Attribute Name: dead-interval

Attribute Type: uint16

Attribute Range: 1-65535

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <timers>
  <config>
    <dead-interval>1</dead-interval> <!-- operation="delete"-->
  </config>
</timers>
</interface>
</interfaces>

```

```
</ospfv2>
```

## Command Syntax

```
ip ospf dead-interval <1-65535>
```

---

## Configure hello interval

Use this attribute to specify the interval between hello packets.

Attribute Name: hello-interval

Attribute Type: uint16

Default Value: 10

Attribute Range: 1-65535

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <addresses>
        <address>
          <interface-address>A.B.C.D</interface-address>
          <config>
            <interface-address>A.B.C.D</interface-address>
          </config>
          <timers>
            <config>
              <hello-interval>1</hello-interval> <!-- operation="delete"-->
            </config>
          </timers>
        </address>
      </addresses>
    </interface>
  </interfaces>
</ospfv2>
```

## Command Syntax

```
ip ospf A.B.C.D hello-interval <1-65535>
```

---

## Configure timers hello-interval

Use this attribute to specify the interval between hello packets.

Attribute Name: hello-interval

Attribute Type: uint16

Default Value: 10

Attribute Range: 1-65535

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <timers>
  <config>
    <hello-interval>1</hello-interval> <!-- operation="delete"-->
  </config>
</timers>
</interface>
</interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf hello-interval <1-65535>
```

---

## Configure retransmission interval

Use this attribute to specify the time between link-state advertisement (LSA) retransmissions for adjacencies belonging to the interface.

Attribute Name: retransmission-interval

Attribute Type: uint16

Default Value: 5

Attribute Range: 1-3600

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <addresses>
  <address>
    <interface-address>A.B.C.D</interface-address>
    <config>
      <interface-address>A.B.C.D</interface-address>
    </config>
  <timers>
  <config>
    <retransmission-interval>1</retransmission-interval> <!--
operation="delete"-->
```

```

    </config>
  </timers>
</address>
</addresses>
</interface>
</interfaces>
</ospfv2>

```

## Command Syntax

```
ip ospf A.B.C.D retransmit-interval <1-3600>
```

---

## Configure timers retransmission-interval

Use this attribute to specify the time between link-state advertisement (LSA) retransmissions for adjacencies belonging to the interface.

Attribute Name: retransmission-interval

Attribute Type: uint16

Default Value: 5

Attribute Range: 1-3600

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
        </config>
        <timers>
          <config>
            <retransmission-interval>1</retransmission-interval> <!--
operation="delete"-->
          </config>
        </timers>
      </interface>
    </interfaces>
  </ospfv2>

```

## Command Syntax

```
ip ospf retransmit-interval <1-3600>
```

---

## Configure timers dead-interval

Use this attribute to set the interval during which the router waits to receive an OSPF hello packet from the neighbor before declaring the neighbor down.

Attribute Name: dead-interval

Attribute Type: uint16

---

Attribute Range: 1-65535

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <timers>
  <config>
    <dead-interval>1</dead-interval> <!-- operation="delete"-->
  </config>
</timers>
</interface>
</interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf dead-interval <1-65535>
```

---

## Configure timers hello-interval

Use this attribute to specify the interval between hello packets.

Attribute Name: hello-interval

Attribute Type: uint16

Default Value: 10

Attribute Range: 1-65535

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <timers>
  <config>
    <hello-interval>1</hello-interval> <!-- operation="delete"-->
  </config>
</timers>
</interface>
</interfaces>
</ospfv2>
```

---

## Command Syntax

```
ip ospf hello-interval <1-65535>
```

---

## Configure timers retransmission-interval

Use this attribute to specify the time between link-state advertisement (LSA) retransmissions for adjacencies belonging to the interface.

Attribute Name: retransmission-interval

Attribute Type: uint16

Default Value: 5

Attribute Range: 1-3600

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
        </config>
        <timers>
          <config>
            <retransmission-interval>1</retransmission-interval> <!--
operation="delete"-->
          </config>
        </timers>
      </interface>
    </interfaces>
  </ospfv2>
```

## Command Syntax

```
ip ospf retransmit-interval <1-3600>
```

---

## Configure transmit delay

Use this attribute to set the estimated time it takes to transmit a link-state-update packet on the interface.

Attribute Name: transmit-delay

Attribute Type: uint16

Default Value: 1

Attribute Range: 1-3600

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
```

```

<config>
  <name>WORD</name>
</config>
<timers>
<config>
  <transmit-delay>1</transmit-delay> <!-- operation="delete"-->
</config>
</timers>
</interface>
</interfaces>
</ospfv2>

```

### Command Syntax

```
ip ospf transmit-delay <1-3600>
```

---

## Configure resync timeout

Use this attribute to configure the interval after which adjacency is reset if oob-resync is not started.

Attribute Name: resync-timeout

Attribute Type: uint16

Default Value: 40

Attribute Range: 1-65535

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <timers>
  <config>
    <resync-timeout>1</resync-timeout> <!-- operation="delete"-->
  </config>
</timers>
</interface>
</interfaces>
</ospfv2>

```

### Command Syntax

```
ip ospf resync-timeout <1-65535>
```

---

## Configure interface address

Use this attribute to explicitly specify the cost of the link-state metric in a router-LSA.

Attribute Name: cost

Attribute Type: uint16

Default Value: 1

Attribute Range: 1-65535

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <addresses>
  <address>
    <interface-address>A.B.C.D</interface-address>
    <config>
      <interface-address>A.B.C.D</interface-address>
    </config>
    <cost>1</cost> <!-- operation="delete"-->
  </address>
</addresses>
</interface>
</interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf A.B.C.D cost <1-65535>
```

---

## Configure address priority

Use this attribute to set the router priority to determine the designated router (DR) for the network.

Attribute Name: priority

Attribute Type: uint8

Default Value: 1

Attribute Range: 0-255

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <addresses>
  <address>
    <interface-address>A.B.C.D</interface-address>
```

```

    <config>
      <interface-address>A.B.C.D</interface-address>
    </config>
    <priority>0</priority> <!-- operation="delete"-->
  </address>
</addresses>
</interface>
</interfaces>
</ospfv2>

```

### Command Syntax

```
ip ospf A.B.C.D priority <0-255>
```

---

## Configure address mtu-ignore

Use this attribute to configure OSPF so that it does not check the MTU size during DD (Database Description) exchange.

Attribute Name: mtu-ignore

Attribute Type: empty

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <addresses>
        <address>
          <interface-address>A.B.C.D</interface-address>
          <config>
            <interface-address>A.B.C.D</interface-address>
          </config>
          </mtu-ignore><!-- operation="delete"-->
        </address>
      </addresses>
    </interface>
  </interfaces>
</ospfv2>

```

### Command Syntax

```
ip ospf A.B.C.D mtu-ignore
```

---

## Configure message digest key

Use this attribute to set the authentication message digest key ID.

Attribute Name: message-digest-id

Attribute Type: uint8

Attribute Range: 1-255

Attribute Name: message-digest-encryption-type

Attribute Type: enum (md5)

Attribute Name: message-digest-key

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <addresses>
        <address>
          <interface-address>A.B.C.D</interface-address>
          <config>
            <interface-address>A.B.C.D</interface-address>
          </config>
          <authentication>
            <message-digests>
              <message-digest>
                <message-digest-id>1</message-digest-id>
                <config>
                  <message-digest-id>1</message-digest-id>
                  <message-digest-encryption-type>md5</message-digest-encryption-type>
                  <message-digest-key>WORD</message-digest-key>
                </config>
              </message-digest>
            </message-digests>
          </authentication>
        </address>
      </addresses>
    </interface>
  </interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf A.B.C.D message-digest-key <1-255> (md5) WORD
```

## Configure message-digests message-digest-id

Use this attribute to set the authentication message digest key ID.

Attribute Name: message-digest-id

Attribute Type: uint8

Attribute Range: 1-255

Attribute Name: message-digest-encryption-type

Attribute Type: enum (md5)

Attribute Name: message-digest-key

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <authentication>
        <message-digests>
          <message-digest>
            <message-digest-id>1</message-digest-id>
            <config>
              <message-digest-id>1</message-digest-id>
              <message-digest-encryption-type>md5</message-digest-encryption-type>
              <message-digest-key>WORD</message-digest-key>
            </config>
          </message-digest>
        </message-digests>
      </authentication>
    </interface>
  </interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf message-digest-key <1-255> (md5) WORD
```

---

## Configure authentication authentication-type

Use this attribute to configure authentication on this interface.

Attribute Name: authentication-type

Attribute Type: enum (null|simple|message-digest)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
</ospfv2>
```

```

<addresses>
<address>
  <interface-address>A.B.C.D</interface-address>
  <config>
    <interface-address>A.B.C.D</interface-address>
  </config>
  <authentication>
  <config>
    <authentication-type>simple</authentication-type> <!--
operation="delete"-->
  </config>
</authentication>
</address>
</addresses>
</interface>
</interfaces>
</ospfv2>

```

### Command Syntax

```
ip ospf A.B.C.D authentication (null|message-digest|)
```

---

## Configure authentication authentication-type

Use this attribute to configure authentication on this interface.

Attribute Name: authentication-type

Attribute Type: enum (null|simple|message-digest)

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <authentication>
  <config>
    <authentication-type>simple</authentication-type> <!--
operation="delete"-->
  </config>
</authentication>
</interface>
</interfaces>
</ospfv2>

```

### Command Syntax

```
ip ospf authentication (null|message-digest|)
```

---

## Configure authentication key

Use this attribute to set the authentication password (key).

Attribute Name: key

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <addresses>
  <address>
    <interface-address>A.B.C.D</interface-address>
    <config>
      <interface-address>A.B.C.D</interface-address>
    </config>
    <authentication>
    <config>
      <key>WORD</key> <!-- operation="delete"-->
    </config>
  </authentication>
</address>
</addresses>
</interface>
</interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf A.B.C.D authentication-key WORD
```

---

## Configure authentication key

Use this attribute to set the authentication password (key).

Attribute Name: key

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
```

```

    <authentication>
    <config>
        <key>WORD</key> <!-- operation="delete"-->
    </config>
</authentication>
</interface>
</interfaces>
</ospfv2>

```

### Command Syntax

```
ip ospf authentication-key WORD
```

---

## Configure authentication key

Use this attribute to set the authentication password (key).

Attribute Name: key

Attribute Type: string

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
    <name>WORD</name>
    <config>
        <name>WORD</name>
    </config>
    <addresses>
    <address>
        <interface-address>A.B.C.D</interface-address>
        <config>
            <interface-address>A.B.C.D</interface-address>
        </config>
        <authentication>
        <config>
            <key>WORD</key> <!-- operation="delete"-->
        </config>
    </authentication>
    </address>
</addresses>
</interface>
</interfaces>
</ospfv2>

```

### Command Syntax

```
ip ospf A.B.C.D authentication-key WORD
```

---

## Configure authentication authentication-type

Use this attribute to configure authentication on this interface.

Attribute Name: authentication-type

Attribute Type: enum (null|simple|message-digest)

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <addresses>
        <address>
          <interface-address>A.B.C.D</interface-address>
          <config>
            <interface-address>A.B.C.D</interface-address>
          </config>
          <authentication>
            <config>
              <authentication-type>simple</authentication-type> <!--
operation="delete"-->
            </config>
          </authentication>
        </address>
      </addresses>
    </interface>
  </interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf A.B.C.D authentication (null|message-digest|)
```

---

## Configure message-digests message-digest-id

Use this attribute to set the authentication message digest key ID.

Attribute Name: message-digest-id

Attribute Type: uint8

Attribute Range: 1-255

Attribute Name: message-digest-encryption-type

Attribute Type: enum (md5)

Attribute Name: message-digest-key

Attribute Type: string

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
```

```

<name>WORD</name>
<config>
  <name>WORD</name>
</config>
<addresses>
<address>
  <interface-address>A.B.C.D</interface-address>
  <config>
    <interface-address>A.B.C.D</interface-address>
  </config>
  <authentication>
  <message-digests>
  <message-digest> <!-- operation="delete"-->
    <message-digest-id>1</message-digest-id>
    <config>
      <message-digest-id>1</message-digest-id>
      <message-digest-encryption-type>md5</message-digest-encryption-type>
      <message-digest-key>WORD</message-digest-key>
    </config>
    </message-digest>
  </message-digests>
</authentication>
</address>
</addresses>
</interface>
</interfaces>
</ospfv2>

```

## Command Syntax

```
ip ospf A.B.C.D message-digest-key <1-255> (md5) WORD
```

---

## Configure timers dead-interval

Use this attribute to set the interval during which the router waits to receive an OSPF hello packet from the neighbor before declaring the neighbor down.

Attribute Name: dead-interval

Attribute Type: uint16

Attribute Range: 1-65535

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <addresses>
  <address>

```

```

    <interface-address>A.B.C.D</interface-address>
  <config>
    <interface-address>A.B.C.D</interface-address>
  </config>
  <timers>
  <config>
    <dead-interval>1</dead-interval> <!-- operation="delete"-->
  </config>
</timers>
</address>
</addresses>
</interface>
</interfaces>
</ospfv2>

```

## Command Syntax

```
ip ospf A.B.C.D dead-interval <1-65535>
```

---

## Configure timers hello-interval

Use this attribute to specify the interval between hello packets.

Attribute Name: hello-interval

Attribute Type: uint16

Default Value: 10

Attribute Range: 1-65535

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
  <interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
    <addresses>
    <address>
      <interface-address>A.B.C.D</interface-address>
      <config>
        <interface-address>A.B.C.D</interface-address>
      </config>
      <timers>
      <config>
        <hello-interval>1</hello-interval> <!-- operation="delete"-->
      </config>
    </timers>
    </address>
  </addresses>
  </interface>

```

```
</interfaces>
</ospfv2>
```

## Command Syntax

```
ip ospf A.B.C.D hello-interval <1-65535>
```

---

## Configure timers retransmission-interval

Use this attribute to specify the time between link-state advertisement (LSA) retransmissions for adjacencies belonging to the interface.

Attribute Name: retransmission-interval

Attribute Type: uint16

Default Value: 5

Attribute Range: 1-3600

## Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <addresses>
  <address>
    <interface-address>A.B.C.D</interface-address>
    <config>
      <interface-address>A.B.C.D</interface-address>
    </config>
    <timers>
    <config>
      <retransmission-interval>1</retransmission-interval> <!--
operation="delete"-->
    </config>
    </timers>
  </address>
</addresses>
</interface>
</interfaces>
</ospfv2>
```

## Command Syntax

```
ip ospf A.B.C.D retransmit-interval <1-3600>
```

---

## Configure timers transmit-delay

Use this attribute to set the estimated time it takes to transmit a link-state-update packet on the interface.

Attribute Name: transmit-delay

Attribute Type: uint16

Default Value: 1

Attribute Range: 1-3600

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <addresses>
        <address>
          <interface-address>A.B.C.D</interface-address>
          <config>
            <interface-address>A.B.C.D</interface-address>
          </config>
          <timers>
            <config>
              <transmit-delay>1</transmit-delay> <!-- operation="delete"-->
            </config>
          </timers>
        </address>
      </addresses>
    </interface>
  </interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf A.B.C.D transmit-delay <1-3600>
```

---

## Configure timers resync-timeout

Use this attribute to configure the interval after which adjacency is reset if oob-resync is not started.

Attribute Name: resync-timeout

Attribute Type: uint16

Default Value: 40

Attribute Range: 1-65535

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
</ospfv2>
```

```

</config>
<addresses>
<address>
  <interface-address>A.B.C.D</interface-address>
  <config>
    <interface-address>A.B.C.D</interface-address>
  </config>
  <timers>
  <config>
    <resync-timeout>1</resync-timeout> <!-- operation="delete"-->
  </config>
</timers>
</address>
</addresses>
</interface>
</interfaces>
</ospfv2>

```

### Command Syntax

```
ip ospf A.B.C.D resync-timeout <1-65535>
```

---

## Configure lsa filter-out

Use this attribute to turn on the LSA database-filter for a particular interface. OSPF floods new LSAs over all interfaces in an area, except the interface on which the LSA arrives. This redundancy ensures robust flooding. However, too much redundancy can waste bandwidth and might lead to excessive link and CPU usage in certain topologies, resulting in destabilizing the network. To avoid this, use this attribute to block flooding of LSAs over specified interfaces.

Attribute Name: filter-out

Attribute Type: empty

### Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <addresses>
  <address>
    <interface-address>A.B.C.D</interface-address>
    <config>
      <interface-address>A.B.C.D</interface-address>
    </config>
    <database-filter>
    <lsa>
    <config>
      </filter-out><!-- operation="delete"-->
    </config>
  </address>
</addresses>
</interface>
</interfaces>
</ospfv2>

```

```

    </lsa>
  </database-filter>
</address>
</addresses>
</interface>
</interfaces>
</ospfv2>

```

## Command Syntax

```
ip ospf A.B.C.D database-filter all out
```

---

## Configure lsa filter-out

Use this attribute to turn on the LSA database-filter for a particular interface. OSPF floods new LSAs over all interfaces in an area, except the interface on which the LSA arrives. This redundancy ensures robust flooding. However, too much redundancy can waste bandwidth and might lead to excessive link and CPU usage in certain topologies, resulting in destabilizing the network. To avoid this, use this attribute to block flooding of LSAs over specified interfaces.

Attribute Name: filter-out

Attribute Type: empty

## Netconf edit-config payload

```

<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
        </config>
        <addresses>
          <address>
            <interface-address>A.B.C.D</interface-address>
            <config>
              <interface-address>A.B.C.D</interface-address>
            </config>
            <database-filter>
              <lsa>
                <config>
                  </filter-out><!-- operation="delete"-->
                </config>
              </lsa>
            </database-filter>
          </address>
        </addresses>
      </interface>
    </interfaces>
  </ospfv2>

```

## Command Syntax

```
ip ospf database-filter all out
```

---

## Configure lsa filter-out

Use this attribute to turn on the LSA database-filter for a particular interface. OSPF floods new LSAs over all interfaces in an area, except the interface on which the LSA arrives. This redundancy ensures robust flooding. However, too much redundancy can waste bandwidth and might lead to excessive link and CPU usage in certain topologies, resulting in destabilizing the network. To avoid this, use this attribute to block flooding of LSAs over specified interfaces.

Attribute Name: filter-out

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <addresses>
        <address>
          <interface-address>A.B.C.D</interface-address>
          <config>
            <interface-address>A.B.C.D</interface-address>
          </config>
          <database-filter>
            <lsa>
              <config>
                </filter-out><!-- operation="delete"-->
              </config>
            </lsa>
          </database-filter>
        </address>
      </addresses>
    </interface>
  </interfaces>
</ospfv2>
```

### Command Syntax

```
ip ospf A.B.C.D database-filter all out
```

---

## IPI-OSPFV3

---

### Configure display route on single line

Use this attribute to display the output of the show ipv6 ospf route command with each route entry in a singleline.

Attribute Name: display-route-on-single-line

Attribute Type: empty

---

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <global>
  <config>
    </display-route-on-single-line><!-- operation="delete"-->
  </config>
</global>
</ospfv3>
```

### Command Syntax

```
ipv6 ospf display route single-line
```

---

## Configure grace period

Use this attribute to enable the graceful restart feature and set the grace period for restarting the router

This command is supported when following feature are enabled Restart capability

Attribute Name: grace-period

Attribute Type: uint16

Default Value: 120

Attribute Range: 2-1800

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <global>
  <graceful-restart>
  <config>
    <grace-period>2</grace-period> <!-- operation="delete"-->
  </config>
</graceful-restart>
</global>
</ospfv3>
```

### Command Syntax

```
ipv6 ospf restart grace-period <2-1800>
```

---

## Configure controlled restarts only

Use this attribute to enable the graceful restart controlled restarts only for the router

This command is supported when following feature are enabled Restart capability

Attribute Name: controlled-restarts-only

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <global>
  <graceful-restart>
```

```

<config>
  </controlled-restarts-only><!-- operation="delete"-->
</config>
</graceful-restart>
</global>
</ospfv3>

```

### Command Syntax

```
ipv6 ospf restart planned-only
```

---

## Configure max grace period

Use this attribute to set the maximum grace period to act as helper. i.e Help only if received grace-period is less than set value.

This command is supported when following feature are enabled Restart capability

Attribute Name: max-grace-period

Attribute Type: uint16

Attribute Range: 2-1800

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<global>
<graceful-restart>
<helper>
<config>
  <max-grace-period>2</max-grace-period> <!-- operation="delete"-->
</config>
</helper>
</graceful-restart>
</global>
</ospfv3>

```

### Command Syntax

```
ipv6 ospf restart helper max-grace-period <2-1800>
```

---

## Configure disable all neighbors

Use this attribute to set disable acting as helper for all neighbors.

This command is supported when following feature are enabled Restart capability

Attribute Name: disable-all-neighbors

Attribute Type: empty

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<global>
<graceful-restart>
<helper>

```

```
<config>
  </disable-all-neighbors><!-- operation="delete"-->
</config>
</helper>
</graceful-restart>
</global>
</ospfv3>
```

## Command Syntax

```
ipv6 ospf restart helper never
```

---

## Configure disable neighbor

Use this attribute to set disable acting as helper for specified neighbor.

This command is supported when following feature are enabled Restart capability

Attribute Name: disable-neighbor

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <global>
    <graceful-restart>
      <helper>
        <config>
          <disable-neighbor>A.B.C.D</disable-neighbor> <!-- operation="delete"-->
        </config>
      </helper>
    </graceful-restart>
  </global>
</ospfv3>
```

## Command Syntax

```
ipv6 ospf restart helper never router-id A.B.C.D
```

---

## Configure vrf name

VRF Name to associate with this instance

Attribute Name: vrf-name

Attribute Type: string

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    </process>
  </processes>
</ospfv3>
```

```

    </config>
    <vrf-name>WORD</vrf-name>
</process>
</processes>
</ospfv3>

```

### Command Syntax

```
router ipv6 vrf ospf WORD
```

---

## Configure ospfv3 id

Use this attribute to set the OSPFv3 process ID

Attribute Name: ospfv3-id

Attribute Type: string

Attribute Range: 0-254

Attribute Name: vrf-name

Attribute Type: string

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process> <!-- operation="delete"-->
    <ospfv3-id>WORD</ospfv3-id>
    <config>
        <ospfv3-id>0</ospfv3-id>
        <vrf-name>WORD</vrf-name>
    </config>
</process>
</processes>
</ospfv3>

```

### Command Syntax

```
router ipv6 ospf (WORD|) (WORD|)
```

---

## Configure router id

Use this attribute to set a router ID for the OSPFv3 process. Configure each router OSPFv3 with an unique router ID

Attribute Name: router-id

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
    <ospfv3-id>WORD</ospfv3-id>
    <config>
        <ospfv3-id>0</ospfv3-id>

```

```

    </config>
    <router-id>A.B.C.D</router-id> <!-- operation="delete"-->
</process>
</processes>
</ospfv3>

```

### Command Syntax

```
router-id A.B.C.D
```

---

## Configure bfd enable all interfaces

Use this attribute to enable Bidirectional Forwarding Detection (BFD) on all interfaces.

Attribute Name: bfd-enable-all-interfaces

Attribute Type: empty

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
    <ospfv3-id>WORD</ospfv3-id>
    <config>
        <ospfv3-id>0</ospfv3-id>
    </config>
    </bfd-enable-all-interfaces><!-- operation="delete"-->
</process>
</processes>
</ospfv3>

```

### Command Syntax

```
bfd all-interfaces
```

---

## Configure database summary

Use this attribute to enable the database summary list optimization for OSPFv3.

Attribute Name: database-summary

Attribute Type: empty

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
    <ospfv3-id>WORD</ospfv3-id>
    <config>
        <ospfv3-id>0</ospfv3-id>
    </config>
    </database-summary><!-- operation="delete"-->
</process>
</processes>

```

---

```
</ospfv3>
```

## Command Syntax

```
enable db-summary-opt
```

---

## Configure area border type

Use this attribute to set an OSPFv3 Area Border Router (ABR) type.

Attribute Name: area-border-type

Attribute Type: enum (standard|cisco|ibm)

Default Value: cisco

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
      <area-border-type>cisco</area-border-type> <!-- operation="delete"-->
    </process>
  </processes>
</ospfv3>
```

## Command Syntax

```
abr-type (standard|cisco|ibm)
```

---

## Configure default metric

Use this attribute to set a default metric for OSPFv3.

Attribute Name: default-metric

Attribute Type: uint32

Default Value: 20

Attribute Range: 1-16777214

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
      <default-metric>1</default-metric> <!-- operation="delete"-->
    </process>
  </processes>
</ospfv3>
```

```
</ospfv3>
```

## Command Syntax

```
default-metric <1-16777214>
```

---

## Configure shutdown

Use this attribute to specify an OSPFv3 shutdown

Attribute Name: shutdown

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
      </shutdown><!-- operation="delete"-->
    </process>
  </processes>
</ospfv3>
```

## Command Syntax

```
shutdown
```

---

## Configure log adjacency changes

Use this attribute for the the router to send a SYSLOG message when an OSPFv3 neighbor goes up or down.

Attribute Name: log-adjacency-changes

Attribute Type: enum (brief|detail)

Default Value: brief

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
      <log-adjacency-changes>brief</log-adjacency-changes> <!-- operation="delete"-->
    </process>
  </processes>
</ospfv3>
```

## Command Syntax

```
log-adjacency-changes (brief|detail|)
```

## Configure reference bandwidth

Use this attribute to control how OSPFv3 calculates the default metric for the interface.

Attribute Name: reference-bandwidth

Attribute Type: uint32

Default Value: 100

Attribute Range: 1-4294967

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
      <reference-bandwidth>1</reference-bandwidth> <!-- operation="delete"-->
    </process>
  </processes>
</ospfv3>
```

## Command Syntax

```
auto-cost reference-bandwidth <1-4294967>
```

## Configure max database descriptors

Use this attribute to limit the number of Database Descriptors (DD) that can be processed concurrently.

Attribute Name: max-database-descriptors

Attribute Type: uint16

Default Value: 5

Attribute Range: 1-65535

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
      <max-database-descriptors>1</max-database-descriptors> <!-- operation="delete"-->
    </process>
  </processes>
</ospfv3>
```

```
</processes>
</ospfv3>
```

## Command Syntax

```
max-concurrent-dd <1-65535>
```

---

## Configure default distance

Default administrative distance value

Attribute Name: default-distance

Attribute Type: uint8

Default Value: 110

Attribute Range: 1-254

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    <administrative-distance>
      <config>
        <default-distance>1</default-distance> <!-- operation="delete"-->
      </config>
    </administrative-distance>
  </process>
</processes>
</ospfv3>
```

## Command Syntax

```
distance <1-254>
```

---

## Configure intra area distance

Administrative distance for intra-area routes

Attribute Name: intra-area-distance

Attribute Type: uint8

Default Value: 110

Attribute Range: 1-254

Attribute Name: inter-area-distance

Attribute Type: uint8

Default Value: 110

Attribute Range: 1-254

Attribute Name: external-routes-distance

Attribute Type: uint8

Default Value: 110

Attribute Range: 1-254

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
  <process>
    <ospfv3-id>WORD</ospfv3-id>
    <config>
      <ospfv3-id>0</ospfv3-id>
    </config>
  <administrative-distance>
  <ospf>
  <config>
    <inter-area-distance>1</inter-area-distance> <!-- operation="delete"-->
    <external-routes-distance>1</external-routes-distance> <!--
operation="delete"-->
    <intra-area-distance>1</intra-area-distance> <!-- operation="delete"-->
  </config>
</ospf>
</administrative-distance>
</process>
</processes>
</ospfv3>
```

### Command Syntax

```
distance ospfv3 { intra-area <1-254>| inter-area <1-254>| external <1-254> }
```

---

## Configure disable graceful restart

Graceful OSPFv3 Restart

Attribute Name: disable-graceful-restart

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
  <process>
    <ospfv3-id>WORD</ospfv3-id>
    <config>
      <ospfv3-id>0</ospfv3-id>
    </config>
  <capability>
  <config>
    </disable-graceful-restart><!-- operation="delete"-->
  </config>
```

```
</capability>  
</process>  
</processes>  
</ospfv3>
```

## Command Syntax

```
no capability restart
```

---

## Configure exponential max delay

Use this attribute to set the maximum SPF hold delay time in milliseconds

Attribute Name: exponential-max-delay

Attribute Type: uint32

Attribute Range: 0-2147483647

Attribute Name: exponential-min-delay

Attribute Type: uint32

Attribute Range: 0-2147483647

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">  
<processes>  
<process>  
  <ospfv3-id>WORD</ospfv3-id>  
  <config>  
    <ospfv3-id>0</ospfv3-id>  
    </config>  
<timers>  
<spf>  
<config>  
  <exponential-min-delay>0</exponential-min-delay>  
  <exponential-max-delay>0</exponential-max-delay>  
</config>  
</spf>  
</timers>  
</process>  
</processes>  
</ospfv3>
```

## Command Syntax

```
timers spf exp <0-2147483647> <0-2147483647>
```

---

## Configure all interfaces

Use this attribute to set all interfaces as passive

Attribute Name: all-interfaces

Attribute Type: empty

**Netconf edit-config payload**

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
<passive-interfaces>
<config>
  </all-interfaces><!-- operation="delete"-->
</config>
</passive-interfaces>
</process>
</processes>
</ospfv3>

```

**Command Syntax**

```
passive-interface
```

**Configure name**

Use this attribute to set interface as passive or not.

Attribute Name: name

Attribute Type: string

Attribute Range: 1-33

Attribute Name: passive-mode

Attribute Type: enum (disable|enable)

**Netconf edit-config payload**

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
<passive-interfaces>
<passive-interface> <!-- operation="delete"-->
  <name>IFNAME</name>
  <config>
    <name>WORD</name>
    <passive-mode>enable</passive-mode>
  </config>
</passive-interface>
</passive-interfaces>
</process>
</processes>

```

---

```
</ospfv3>
```

## Command Syntax

```
passive-interface IFNAME (disable|enable)
```

---

## Configure address

Use this attribute to summarize or suppress external routes with the specified address range.

Attribute Name: address

Attribute Type: string

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
        </config>
      <summary-addresses>
        <summary-address> <!-- operation="delete"-->
          <address>X:X::X:X/M</address>
          <config>
            <address>X:X::X:X/M</address>
          </config>
        </summary-address>
      </summary-addresses>
    </process>
  </processes>
</ospfv3>
```

## Command Syntax

```
summary-address X:X::X:X/M
```

---

## Configure translate tag

Use this attribute to set or unset translate tag to external routes with the specified address range.

Attribute Name: translate-tag

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

Attribute Name: all-tag

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

**Netconf edit-config payload**

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
<summary-addresses>
<summary-address>
  <address>X:X::X:X/M</address>
  <config>
    <address>X:X::X:X/M</address>
    <all-tag>0</all-tag> <!-- operation="delete" -->
  </config>
    <translate-tag>0</translate-tag> <!-- operation="delete" -->
  </summary-address>
</summary-addresses>
</process>
</processes>
</ospfv3>

```

**Command Syntax**

```
summary-address X:X::X:X/M all-tag <0-4294967295> translate-tag <0-4294967295>
```

**Configure not advertise**

Use this attribute to set or unset not advertise to summarize or suppress external routes with the specified address range.

Attribute Name: not-advertise

Attribute Type: empty

**Netconf edit-config payload**

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
<summary-addresses>
<summary-address>
  <address>X:X::X:X/M</address>
  <config>
    <address>X:X::X:X/M</address>
    </not-advertise><!-- operation="delete" -->
  </config>
  </summary-address>
</summary-addresses>

```

```

</process>
</processes>
</ospfv3>

```

## Command Syntax

```
summary-address X:X::X:X/M not-advertise
```

---

## Configure summary-address translate-tag

Use this attribute to set or unset translate tag to external routes with the specified address range.

Attribute Name: translate-tag

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

## Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
<summary-addresses>
<summary-address>
  <address>X:X::X:X/M</address>
  <config>
    <address>X:X::X:X/M</address>
    <translate-tag>0</translate-tag> <!-- operation="delete"-->
  </summary-address>
</summary-addresses>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```
summary-address X:X::X:X/M translate-tag <0-4294967295>
```

---

## Configure all tag

Use this attribute to set or unset all tag to summarize or suppress external routes with the specified address range.

Attribute Name: all-tag

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

## Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
<summary-addresses>
<summary-address>
  <address>X:X::X:X/M</address>
  <config>
    <address>X:X::X:X/M</address>
  </config>
  <all-tag>0</all-tag> <!-- operation="delete"-->
</summary-address>
</summary-addresses>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```
summary-address X:X::X:X/M all-tag <0-4294967295>
```

---

## Configure originate

Use this attribute to create a default external route into an OSPF routing domain. The system acts like an Autonomous System Boundary Router (ASBR) when you use the default-information originate command to redistribute routes into an OSPF routing domain. An ASBR does not by default generate a default route into the OSPF routing domain

Attribute Name: originate

Attribute Type: uint8

## Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
    <config>
      <default-information>
<config>
  </originate><!-- operation="delete"-->
</config>
</default-information>
</process>
</processes>
</ospfv3>

```

---

## Command Syntax

```
default-information originate
```

---

## Configure route map

Use this attribute to set route-map instance.

Attribute Name: route-map

Attribute Type: string

Attribute Range: 1-63

Attribute Name: originate

Attribute Type: empty

Attribute Name: always-advertise-default-route

Attribute Type: empty

Attribute Name: metric

Attribute Type: uint32

Default Value: 20

Attribute Range: 0-16777214

Attribute Name: metric-type

Attribute Type: enum (1|2)

Default Value: 2

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
        </config>
      <default-information>
        <config>
          </originate><!-- operation="delete"-->
          </always-advertise-default-route><!-- operation="delete"-->
          <metric>0</metric> <!-- operation="delete"-->
          <metric-type>2</metric-type> <!-- operation="delete"-->
          <route-map>WORD</route-map> <!-- operation="delete"-->
        </config>
      </default-information>
    </process>
  </processes>
</ospfv3>
```

## Command Syntax

```
default-information originate { always| metric <0-16777214>| metric-type (1|2)|
route-map WORD }
```

---

## Configure access control list

Use this attribute to set the access control list name in distribution list.

This command is supported when following feature are enabled HAVE\_ACL

Attribute Name: access-control-list

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
<distribute-list>
<filter-in>
<config>
  <access-control-list>WORD</access-control-list> <!-- operation="delete"-->
</config>
</filter-in>
</distribute-list>
</process>
</processes>
</ospfv3>
```

## Command Syntax

```
distribute-list WORD in
```

---

## Configure protocol

Use this attribute to import routes from other routing protocols, or from another OSPF instance, into OSPFv3 ASexternal-LSAs.

This command is supported when following feature are enabled HAVE\_ACL

Attribute Name: protocol

Attribute Type: enum (kernel|connected|static|rip|bgp|isis)

Attribute Name: access-control-list

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
<distribute-list>
<filter-out>
<routing-protocols>
<routing-protocol>
  <protocol>kernel</protocol>
  <config>
    <protocol>kernel</protocol>
    <access-control-list>WORD</access-control-list> <!-- operation="delete"-->
  </config>
</routing-protocol>
</routing-protocols>
</filter-out>
</distribute-list>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```
distribute-list WORD out (kernel|connected|static|rip|bgp|isis)
```

---

## Configure ospf process id

Use this attribute to filter networks in routing updates.

This command is supported when following feature are enabled HAVE\_ACL

Attribute Name: ospf-process-id

Attribute Type: string

Attribute Name: access-control-list

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
<distribute-list>

```

```

<filter-out>
<ospf-processes>
<ospf-process>
  <ospf-process-id>1-65535</ospf-process-id>
  <config>
    <ospf-process-id>WORD</ospf-process-id>
    <access-control-list>WORD</access-control-list> <!-- operation="delete"-->
  </config>
</ospf-process>
</ospf-processes>
</filter-out>
</distribute-list>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```
distribute-list WORD out ospf (WORD|)
```

---

## Configure routing-protocols protocol

Use this attribute to import routes from other routing protocols, or from another OSPF instance, into OSPFv3 ASexternal-LSAs.

Attribute Name: protocol

Attribute Type: enum (kernel|connected|static|rip|bgp|isis)

## Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
<redistribute>
<routing-protocols>
<routing-protocol> <!-- operation="delete"-->
  <protocol>kernel</protocol>
  <config>
    <protocol>kernel</protocol>
  </config>
</routing-protocol>
</routing-protocols>
</redistribute>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```
redistribute (kernel|connected|static|rip|bgp|isis)
```

---

## Configure metric

Use this attribute to inform the value of the metric for OSPFv3 default route.

Attribute Name: metric

Attribute Type: uint32

Default Value: 1

Attribute Range: 0-16777214

Attribute Name: metric-type

Attribute Type: enum (1|2)

Default Value: 2

Attribute Name: route-map

Attribute Type: string

Attribute Name: route-tag

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    <redistribute>
      <routing-protocols>
        <routing-protocol>
          <protocol>kernel</protocol>
          <config>
            <protocol>kernel</protocol>
            <metric-type>2</metric-type> <!-- operation="delete"-->
            <route-map>WORD</route-map> <!-- operation="delete"-->
            <route-tag>0</route-tag> <!-- operation="delete"-->
          </config>
          <metric>0</metric> <!-- operation="delete"-->
        </routing-protocol>
      </routing-protocols>
    </redistribute>
  </process>
</processes>
</ospfv3>
```

## Command Syntax

```
redistribute (kernel|connected|static|rip|bgp|isis) { metric <0-16777214>| metric-
  type (1|2)| route-map WORD| tag <0-4294967295> }
```

---

## Configure ospf-processes ospf-process-id

Use this attribute to specify OSPF routes.

Attribute Name: ospf-process-id

Attribute Type: string

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    </process>
  </processes>
  <redistribute>
    <ospf-process> <!-- operation="delete"-->
      <ospf-process-id>WORD</ospf-process-id>
      <config>
        <ospf-process-id>WORD</ospf-process-id>
      </config>
    </ospf-process>
  </redistribute>
</ospfv3>
```

## Command Syntax

```
redistribute ospf (WORD|)
```

---

## Configure metric type

Use this attribute to inform the value of the metric for OSPFv3 default route.

Attribute Name: metric

Attribute Type: uint32

Default Value: 1

Attribute Range: 0-16777214

Attribute Name: metric-type

Attribute Type: enum (1|2)

Default Value: 2

Attribute Name: route-map

Attribute Type: string

Attribute Name: route-tag

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    </process>
  </processes>
  <ospf-processes>
    <ospf-process>
      <ospf-process-id>WORD</ospf-process-id>
      <config>
        <ospf-process-id>WORD</ospf-process-id>
        <metric-type>2</metric-type> <!-- operation="delete"-->
        <route-map>WORD</route-map> <!-- operation="delete"-->
        <route-tag>0</route-tag> <!-- operation="delete"-->
      </config>
      <metric>0</metric> <!-- operation="delete"-->
    </ospf-process>
  </ospf-processes>
</ospfv3>
```

### Command Syntax

```
redistribute ospf (WORD|) { metric <0-16777214>| metric-type (1|2)| route-map WORD|
  tag <0-4294967295> }
```

---

## Configure default cost

Use this attribute to set the cost for default summary route sent into a stub area. If an area is configured as a stub, the OSPFv3 router originates one type-3 inter-area-prefix-LSA into the stub area. This attribute changes the metric for this LSA.

Attribute Name: default-cost

Attribute Type: uint32

Default Value: 1

Attribute Range: 0-16777215

**Netconf edit-config payload**

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
</process>
</processes>
</ospfv3>

```

**Command Syntax**

```
area (A.B.C.D|<0-4294967295>) default-cost <0-16777215>
```

**Configure no summary**

Use this attribute to do not inject inter-area routes into stub.

Attribute Name: no-summary

Attribute Type: empty

Attribute Name: enable

Attribute Type: empty

**Netconf edit-config payload**

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
</process>
</processes>
</ospfv3>

```

```

        </enable><!-- operation="delete"-->
        </no-summary><!-- operation="delete"-->
    </config>
</stub>
</area>
</areas>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```
area stub no-summary
```

---

## Configure enable

Use this attribute to define an area as a stub area on all routers.

Attribute Name: enable

Attribute Type: empty

## Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPFV3_AREA_T</area-id>
      <config>
        <area-id>OSPFV3_AREA_T</area-id>
        </config>
      <stub>
        <config>
          </enable>
        </config>
      </stub>
    </area>
  </areas>
</ospfv3>

```

## Command Syntax

```
area stub
```

---

## Configure area id

Use this attribute to set an area as a Not-So-Stubby-Area (NSSA).

Attribute Name: enable

Attribute Type: uint8

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPFV3_AREA_T</area-id>
      <config>
        <area-id>OSPFV3_AREA_T</area-id>
        <nssa>
          <config>
            </enable><!-- operation="delete"-->
          </config>
        </nssa>
      </config>
    </area>
  </areas>
</ospfv3>
```

### Command Syntax

```
area nssa
```

---

## Configure remote router id

Use this attribute to set the interface IP address of the neighbor.

Attribute Name: remote-router-id

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    </process>
  </processes>
</ospfv3>
```

```

<areas>
<area>
  <area-id>OSPFV3_AREA_T</area-id>
  <config>
    <area-id>OSPFV3_AREA_T</area-id>
  </config>
  <virtual-links>
  <virtual-link> <!-- operation="delete"-->
    <remote-router-id>A.B.C.D</remote-router-id>
    <config>
      <remote-router-id>A.B.C.D</remote-router-id>
    </config>
  </virtual-link>
</virtual-links>
</area>
</areas>
</process>
</processes>
</ospfv3>

```

### Command Syntax

```
area virtual-link A.B.C.D
```

---

## Configure bfd fall over

Use this attribute to enable BFD on a virtual-link.

Attribute Name: bfd-fall-over

Attribute Type: empty

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
<areas>
<area>
  <area-id>OSPFV3_AREA_T</area-id>
  <config>
    <area-id>OSPFV3_AREA_T</area-id>
  </config>
  <virtual-links>
  <virtual-link>
    <remote-router-id>A.B.C.D</remote-router-id>
    <config>
      <remote-router-id>A.B.C.D</remote-router-id>
    </config>
  </virtual-link>
</virtual-links>
</area>
</areas>
</process>
</processes>
</ospfv3>

```

```

        </bfd-fall-over><!-- operation="delete"-->
    </virtual-link>
</virtual-links>
</area>
</areas>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```
area virtual-link A.B.C.D fall-over bfd
```

---

## Configure instance id

The OSPFv3 instance.

Attribute Name: instance-id

Attribute Type: uint8

Default Value: 0

Attribute Range: 0-31,64-95

## Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
    <ospfv3-id>WORD</ospfv3-id>
    <config>
        <ospfv3-id>0</ospfv3-id>
    </config>
</process>
</processes>
<areas>
<area>
    <area-id>OSPFV3_AREA_T</area-id>
    <config>
        <area-id>OSPFV3_AREA_T</area-id>
    </config>
    <virtual-links>
<virtual-link>
    <remote-router-id>A.B.C.D</remote-router-id>
    <config>
        <remote-router-id>A.B.C.D</remote-router-id>
    </config>
    <instance-id>0</instance-id> <!-- operation="delete"-->
</virtual-link>
</virtual-links>
</area>
</areas>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```
area virtual-link A.B.C.D instance-id (<0-31>|<64-95>)
```

---

## Configure authentication cryptomap

Use this attribute to set the Crypto-map used to setup IPsec SA.

Attribute Name: authentication-cryptomap

Attribute Type: string

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPFV3_AREA_T</area-id>
      <config>
        <area-id>OSPFV3_AREA_T</area-id>
      </config>
      <virtual-links>
        <virtual-link>
          <remote-router-id>A.B.C.D</remote-router-id>
          <config>
            <remote-router-id>A.B.C.D</remote-router-id>
          </config>
          <authentication-cryptomap>WORD</authentication-cryptomap> <!--
operation="delete"-->
        </virtual-link>
      </virtual-links>
    </area>
  </areas>
</process>
</processes>
</ospfv3>
```

## Command Syntax

```
area virtual-link A.B.C.D authentication cryptomap WORD
```

---

## Configure dead interval

Use this command to set the amount of time that the router waits to receive an OSPF hello packet from the neighbor before declaring the neighbor down.

Attribute Name: dead-interval

Attribute Type: uint16

Default Value: 40

Attribute Range: 1-65535

Attribute Name: hello-interval

Attribute Type: uint16

Default Value: 10

Attribute Range: 1-65535

Attribute Name: transmission-delay

Attribute Type: uint16

Default Value: 1

Attribute Range: 1-1800

Attribute Name: retransmission-interval

Attribute Type: uint16

Default Value: 5

Attribute Range: 1-1800

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPFV3_AREA_T</area-id>
      <config>
        <area-id>OSPFV3_AREA_T</area-id>
        <virtual-links>
          <virtual-link>
            <remote-router-id>A.B.C.D</remote-router-id>
            <config>
              <remote-router-id>A.B.C.D</remote-router-id>
            </config>
            <timers>
              <config>
                <hello-interval>1</hello-interval> <!-- operation="delete"-->
                <transmission-delay>1</transmission-delay> <!-- operation="delete"-->
                <retransmission-interval>1</retransmission-interval> <!--
operation="delete"-->
                <dead-interval>1</dead-interval> <!-- operation="delete"-->
              </config>
            </timers>
          </virtual-link>
        </virtual-links>
      </config>
    </area>
  </areas>
</ospfv3>

```

```

</virtual-links>
</area>
</areas>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```

area virtual-link A.B.C.D { dead-interval <1-65535>| hello-interval <1-65535>|
  transmit-delay <1-1800>| retransmit-interval <1-1800> }

```

---

## Configure address-ranges address

Use this attribute to configure the OSPFv3 address range.

Attribute Name: address

Attribute Type: string

## Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    </process>
  </processes>
  <areas>
    <area>
      <area-id>OSPFV3_AREA_T</area-id>
      <config>
        <area-id>OSPFV3_AREA_T</area-id>
      </config>
      <address-ranges>
        <address-range> <!-- operation="delete"-->
          <address>X:X::X:X/M</address>
          <config>
            <address>X:X::X:X/M</address>
          </config>
        </address-range>
      </address-ranges>
    </area>
  </areas>
</ospfv3>

```

## Command Syntax

```

area range X:X::X:X/M

```

---

## Configure address-range not-advertise

Use this attribute to Specify to advertise / non-advertise the OSPFv3 address range.

Attribute Name: not-advertise

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    <areas>
      <area>
        <area-id>OSPFV3_AREA_T</area-id>
        <config>
          <area-id>OSPFV3_AREA_T</area-id>
          <address-ranges>
            <address-range>
              <address>X:X::X:X/M</address>
              <config>
                <address>X:X::X:X/M</address>
              </config>
              </not-advertise><!-- operation="delete"-->
            </address-range>
          </address-ranges>
        </config>
      </area>
    </areas>
  </process>
</processes>
</ospfv3>
```

### Command Syntax

```
area range X:X::X:X/M not-advertise
```

---

## Configure address-ranges address

Use this attribute to configure the OSPFv3 address range for IPv4 address family.

Attribute Name: address

Attribute Type: string

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
```

```

    <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
</address-family>
</ipv4>
</areas>
</area>
  <area-id>OSPFV3_AREA_T</area-id>
  <config>
    <area-id>OSPFV3_AREA_T</area-id>
  </config>
  <address-ranges>
    <address-range> <!-- operation="delete"-->
      <address>A.B.C.D/M</address>
      <config>
        <address>A.B.C.D/M</address>
      </config>
    </address-range>
  </address-ranges>
</area>
</areas>
</ipv4>
</address-family>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```
area (A.B.C.D|<0-4294967295>) range A.B.C.D/M
```

---

## Configure address-range not-advertise

Use this attribute to Specify to advertise / non-advertise the OSPFv3 address range for IPv4 address family.

Attribute Name: not-advertise

Attribute Type: empty

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    </process>
  </processes>
  <address-family>
    <ipv4>
      <areas>
        <area>

```

```

<area-id>OSPFV3_AREA_T</area-id>
<config>
  <area-id>OSPFV3_AREA_T</area-id>
</config>
<address-ranges>
<address-range>
  <address>A.B.C.D/M</address>
  <config>
    <address>A.B.C.D/M</address>
  </config>
  </not-advertise><!-- operation="delete"-->
</address-range>
</address-ranges>
</area>
</areas>
</ipv4>
</address-family>
</process>
</processes>
</ospfv3>

```

### Command Syntax

```
area range A.B.C.D/M not-advertise
```

---

## Configure summary-addresses address

Use this attribute to summarize or suppress external routes with the specified address range.

Attribute Name: address

Attribute Type: string

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
<address-family>
<ipv4>
<summary-addresses>
<summary-address> <!-- operation="delete"-->
  <address>A.B.C.D/M</address>
  <config>
    <address>A.B.C.D/M|A.B.C.D A.B.C.D</address>
  </config>
</summary-address>
</summary-addresses>
</ipv4>

```

```

</address-family>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```
summary-address A.B.C.D/M
```

---

## Configure summary-address not-advertise

Use this attribute to summarize or suppress external routes with the specified address range.

Attribute Name: not-advertise

Attribute Type: empty

## Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
<address-family>
<ipv4>
<summary-addresses>
<summary-address>
  <address>A.B.C.D/M</address>
  <config>
    <address>A.B.C.D/M</address>
  </config>
  </not-advertise><!-- operation="delete" -->
</summary-address>
</summary-addresses>
</ipv4>
</address-family>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```
summary-address A.B.C.D/M not-advertise
```

---

## Configure tag

Use this attribute to configure the Tag value to use as a match value for controlling redistribution via route maps.

Attribute Name: tag

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    <address-family>
      <ipv4>
        <summary-addresses>
          <summary-address>
            <address>A.B.C.D/M</address>
            <config>
              <address>A.B.C.D/M</address>
            </config>
            <tag>0</tag> <!-- operation="delete"-->
          </summary-address>
        </summary-addresses>
      </ipv4>
    </address-family>
  </process>
</processes>
</ospfv3>
```

### Command Syntax

```
summary-address A.B.C.D/M tag <0-4294967295>
```

---

## Configure default-information originate

Use this attribute to create a default external route into an OSPF routing domain. The system acts like an Autonomous System Boundary Router (ASBR) when you use the default-information originate command to redistribute routes into an OSPF routing domain. An ASBR does not by default generate a default route into the OSPF routing domain

Attribute Name: originate

Attribute Type: uint8

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    <address-family>
      <ipv4>
        <default-information>
```

```
<config>
  </originate><!-- operation="delete"-->
</config>
</default-information>
</ipv4>
</address-family>
</process>
</processes>
</ospfv3>
```

## Command Syntax

```
default-information originate
```

---

## Configure always advertise default route

Use this attribute to set route-map instance.

Attribute Name: route-map

Attribute Type: string

Attribute Range: 1-63

Attribute Name: originate

Attribute Type: empty

Attribute Name: always-advertise-default-route

Attribute Type: empty

Attribute Name: metric

Attribute Type: uint32

Default Value: 20

Attribute Range: 0-16777214

Attribute Name: metric-type

Attribute Type: enum (1|2)

Default Value: 2

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    </process>
  </processes>
  <default-information>
    <config>
      </originate><!-- operation="delete"-->
    </config>
  </default-information>
</ospfv3>
```

```

    </always-advertise-default-route><!-- operation="delete"-->
    <metric>0</metric> <!-- operation="delete"-->
    <metric-type>2</metric-type> <!-- operation="delete"-->
    <route-map>WORD</route-map> <!-- operation="delete"-->
</config>
</default-information>
</ipv4>
</address-family>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```

default-information originate { always| metric <0-16777214>| metric-type (1|2)|
route-map WORD }

```

---

## Configure protocol af

Use this attribute to import routes from other routing protocols, or from another OSPF instance, into OSPFv3 ASexternal-LSAs.

Attribute Name: protocol-af

Attribute Type: enum (kernel|connected|static|rip|bgp|isis)

## Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
    </config>
</address-family>
</ipv4>
</redistribute>
</routing-protocols>
<routing-protocol> <!-- operation="delete"-->
  <protocol-af>kernel</protocol-af>
  <config>
    <protocol-af>kernel</protocol-af>
  </config>
</routing-protocol>
</routing-protocols>
</redistribute>
</ipv4>
</address-family>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```
redistribute (kernel|connected|static|rip|bgp|isis)
```

---

## Configure route tag

Use this attribute to inform the value of the metric for OSPFv3 default route.

Attribute Name: metric

Attribute Type: uint32

Default Value: 1

Attribute Range: 0-16777214

Attribute Name: metric-type

Attribute Type: enum (1|2)

Default Value: 2

Attribute Name: route-map

Attribute Type: string

Attribute Name: route-tag

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
        </config>
      <address-family>
        <ipv4>
          <redistribute>
            <routing-protocols>
              <routing-protocol>
                <protocol-af>kernel</protocol-af>
                <config>
                  <protocol-af>kernel</protocol-af>
                  <metric-type>2</metric-type> <!-- operation="delete"-->
                  <route-map>WORD</route-map> <!-- operation="delete"-->
                  <route-tag>0</route-tag> <!-- operation="delete"-->
                </config>
                <metric>0</metric> <!-- operation="delete"-->
              </routing-protocol>
            </routing-protocols>
          </redistribute>
        </ipv4>
      </address-family>
    </process>
  </processes>
</ospfv3>
```

```

</address-family>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```

redistribute (kernel|connected|static|rip|bgp|isis) { metric <0-16777214>| metric-
type (1|2)| route-map WORD| tag <0-4294967295> }

```

---

## Configure ospfv2 process id

Use this attribute to specify OSPF routes.

Attribute Name: ospfv2-process-id

Attribute Type: uint16

Attribute Range: 0-65535

## Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<processes>
<process>
  <ospfv3-id>WORD</ospfv3-id>
  <config>
    <ospfv3-id>0</ospfv3-id>
  </config>
</address-family>
<ipv4>
<redistribute>
<ospf-processes>
<ospf-process> <!-- operation="delete"-->
  <ospfv2-process-id>0</ospfv2-process-id>
  <config>
    <ospfv2-process-id>0</ospfv2-process-id>
  </config>
</ospf-process>
</ospf-processes>
</redistribute>
</ipv4>
</address-family>
</process>
</processes>
</ospfv3>

```

## Command Syntax

```

redistribute ospf (<0-65535>|)

```

---

## Configure ospf-process metric

Use this attribute to inform the value of the metric for OSPFv3 default route.

Attribute Name: metric

Attribute Type: uint32

Default Value: 1

Attribute Range: 0-16777214

Attribute Name: metric-type

Attribute Type: enum (1|2)

Default Value: 2

Attribute Name: route-map

Attribute Type: string

Attribute Name: route-tag

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <processes>
    <process>
      <ospfv3-id>WORD</ospfv3-id>
      <config>
        <ospfv3-id>0</ospfv3-id>
      </config>
    <address-family>
      <ipv4>
        <redistribute>
          <ospf-processes>
            <ospf-process>
              <ospfv2-process-id>0</ospfv2-process-id>
              <config>
                <ospfv2-process-id>0</ospfv2-process-id>
                <metric-type>2</metric-type> <!-- operation="delete"-->
                <route-map>WORD</route-map> <!-- operation="delete"-->
                <route-tag>0</route-tag> <!-- operation="delete"-->
              </config>
              <metric>0</metric> <!-- operation="delete"-->
            </ospf-process>
          </ospf-processes>
        </redistribute>
      </ipv4>
    </address-family>
  </process>
</processes>
</ospfv3>
```

## Command Syntax

```
redistribute ospf (<0-65535>|) { metric <0-16777214>| metric-type (1|2)| route-map
WORD| tag <0-4294967295> }
```

---

## Configure retransmission

OSPFv3 retransmission information

Attribute Name: retransmission

Attribute Type: uint8

Attribute Name: bfd

Attribute Type: empty

Attribute Name: events

Attribute Type: bits (abr|asbr|vlink|os|router|nssa)

Attribute Name: ifsm

Attribute Type: bits (status|events|timers)

Attribute Name: isa

Attribute Type: bits (generate|flooding|install|refresh|maxage)

Attribute Name: n fsm

Attribute Type: bits (status|events|timers)

Attribute Name: nsm

Attribute Type: bits (interface|redistribute)

Attribute Name: route

Attribute Type: bits (spf|ia|ase|install)

Attribute Name: rib

Attribute Type: bits (interface|redistribute)

Attribute Name: packet-hello

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-dd

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-ls-request

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-ls-update

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-ls-ack

Attribute Type: bits (send|recv|detail)

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<debug>
```

```

<config>
  </bfd><!-- operation="delete"-->
  <events>abr</events> <!-- operation="delete"-->
  <ifsm>status</ifsm> <!-- operation="delete"-->
  <lsa>generate</lsa> <!-- operation="delete"-->
  <n fsm>status</n fsm> <!-- operation="delete"-->
  <nsm>interface</nsm> <!-- operation="delete"-->
  <route>spf</route> <!-- operation="delete"-->
  <rib>interface</rib> <!-- operation="delete"-->
  <packet-hello>send</packet-hello> <!-- operation="delete"-->
  <packet-dd>send</packet-dd> <!-- operation="delete"-->
  <packet-ls-request>send</packet-ls-request> <!-- operation="delete"-->
  <packet-ls-update>send</packet-ls-update> <!-- operation="delete"-->
  <packet-ls-ack>send</packet-ls-ack> <!-- operation="delete"-->
  </retransmission><!-- operation="delete"-->
</config>
</debug>
</ospfv3>

```

## Command Syntax

```
debug ipv6 ospf
```

---

## Configure bfd

OSPFv3 retransmission information

Attribute Name: retransmission

Attribute Type: uint8

Attribute Name: bfd

Attribute Type: empty

Attribute Name: events

Attribute Type: bits (abr|asbr|vlink|os|router|nssa)

Attribute Name: ifsm

Attribute Type: bits (status|events|timers)

Attribute Name: lsa

Attribute Type: bits (generate|flooding|install|refresh|maxage)

Attribute Name: n fsm

Attribute Type: bits (status|events|timers)

Attribute Name: nsm

Attribute Type: bits (interface|redistribute)

Attribute Name: route

Attribute Type: bits (spf|ia|ase|install)

Attribute Name: rib

Attribute Type: bits (interface|redistribute)

Attribute Name: packet-hello

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-dd

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-ls-request

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-ls-update

Attribute Type: bits (send|recv|detail)

Attribute Name: packet-ls-ack

Attribute Type: bits (send|recv|detail)

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <debug>
  <config>
    </bfd><!-- operation="delete"-->
    <events>abr</events> <!-- operation="delete"-->
    <ifsm>status</ifsm> <!-- operation="delete"-->
    <lsa>generate</lsa> <!-- operation="delete"-->
    <n fsm>status</n fsm> <!-- operation="delete"-->
    <nsm>interface</nsm> <!-- operation="delete"-->
    <route>spf</route> <!-- operation="delete"-->
    <rib>interface</rib> <!-- operation="delete"-->
    <packet-hello>send</packet-hello> <!-- operation="delete"-->
    <packet-dd>send</packet-dd> <!-- operation="delete"-->
    <packet-ls-request>send</packet-ls-request> <!-- operation="delete"-->
    <packet-ls-update>send</packet-ls-update> <!-- operation="delete"-->
    <packet-ls-ack>send</packet-ls-ack> <!-- operation="delete"-->
    </retransmission><!-- operation="delete"-->
  </config>
</debug>
</ospfv3>
```

### Command Syntax

```
debug ipv6 ospf all
```

---

## Configure debug bfd

Bidirectional Forwarding Detection (BFD)

Attribute Name: bfd

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <debug>
  <config>
```

```

    </bfd><!-- operation="delete"-->
</config>
</debug>
</ospfv3>

```

### Command Syntax

```
debug ipv6 ospf bfd
```

---

## Configure debug retransmission

OSPFv3 retransmission information

Attribute Name: retransmission

Attribute Type: empty

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<debug>
<config>
    </retransmission><!-- operation="delete"-->
</config>
</debug>
</ospfv3>

```

### Command Syntax

```
debug ipv6 ospf retransmission
```

---

## Configure events

OSPFv3 events information

Attribute Name: events

Attribute Type: bits (abr|asbr|vlink|os|router|nssa)

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<debug>
<config>
    <events>abr</events> <!-- operation="delete"-->
</config>
</debug>
</ospfv3>

```

### Command Syntax

```
debug ipv6 ospf events ({abr|asbr|vlink|os|router|nssa}|)
```

---

## Configure ifsm

Use this attribute to enable OSPFv3 Interface State Machine debug

Attribute Name: ifsm

Attribute Type: bits (status|events|timers)

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <debug>
  <config>
    <ifsm>status</ifsm> <!-- operation="delete"-->
  </config>
</debug>
</ospfv3>
```

### Command Syntax

```
debug ipv6 ospf ifsm ({status|events|timers|})
```

---

## Configure lsa

Use this attribute to enable OSPFv3 Link State Advertisement debug

Attribute Name: lsa

Attribute Type: bits (generate|flooding|install|refresh|maxage)

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <debug>
  <config>
    <lsa>generate</lsa> <!-- operation="delete"-->
  </config>
</debug>
</ospfv3>
```

### Command Syntax

```
debug ipv6 ospf lsa ({generate|flooding|install|refresh|maxage|})
```

---

## Configure nfsm

Use this attribute to enable OSPFv3 Neighbor State Machine debug

Attribute Name: nfsm

Attribute Type: bits (status|events|timers)

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <debug>
  <config>
    <nfsm>status</nfsm> <!-- operation="delete"-->
  </config>
</debug>
</ospfv3>
```

---

## Command Syntax

```
debug ipv6 ospf nsm ({status|events|timers|})
```

---

## Configure nsm

Use this attribute to enable OSPFv3 NSM information debug

Attribute Name: nsm

Attribute Type: bits (interface|redistribute)

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <debug>
    <config>
      <nsm>interface</nsm> <!-- operation="delete"-->
    </config>
  </debug>
</ospfv3>
```

## Command Syntax

```
debug ipv6 ospf nsm ({interface|redistribute|})
```

---

## Configure rib

Use this attribute to enable OSPFv3 RIB information debug

Attribute Name: rib

Attribute Type: bits (interface|redistribute)

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <debug>
    <config>
      <rib>interface</rib> <!-- operation="delete"-->
    </config>
  </debug>
</ospfv3>
```

## Command Syntax

```
debug ipv6 ospf rib ({interface|redistribute|})
```

---

## Configure route

Use this attribute to enable OSPFv3 route information debug

Attribute Name: route

Attribute Type: bits (spf|ia|ase|install)

---

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <debug>
  <config>
    <route>spf</route> <!-- operation="delete"-->
  </config>
</debug>
</ospfv3>
```

### Command Syntax

```
debug ipv6 ospf route ({spf|ia|ase|install}|)
```

---

## Configure packet hello

OSPFv3 Hello

Attribute Name: packet-hello

Attribute Type: bits (send|recv|detail)

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <debug>
  <config>
    <packet-hello>send</packet-hello> <!-- operation="delete"-->
  </config>
</debug>
</ospfv3>
```

### Command Syntax

```
debug ipv6 ospf packet hello ({send|recv|detail}|)
```

---

## Configure packet dd

OSPFv3 Database Description

Attribute Name: packet-dd

Attribute Type: bits (send|recv|detail)

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <debug>
  <config>
    <packet-dd>send</packet-dd> <!-- operation="delete"-->
  </config>
</debug>
</ospfv3>
```

### Command Syntax

```
debug ipv6 ospf packet dd ({send|recv|detail}|)
```

---

## Configure packet ls request

OSPFv3 Link State Request

Attribute Name: packet-ls-request

Attribute Type: bits (send|recv|detail)

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <debug>
  <config>
    <packet-ls-request>send</packet-ls-request> <!-- operation="delete"-->
  </config>
</debug>
</ospfv3>
```

### Command Syntax

```
debug ipv6 ospf packet ls-request ({send|recv|detail}|)
```

---

## Configure packet ls update

OSPFv3 Link State Update

Attribute Name: packet-ls-update

Attribute Type: bits (send|recv|detail)

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <debug>
  <config>
    <packet-ls-update>send</packet-ls-update> <!-- operation="delete"-->
  </config>
</debug>
</ospfv3>
```

### Command Syntax

```
debug ipv6 ospf packet ls-update ({send|recv|detail}|)
```

---

## Configure packet ls ack

OSPFv3 Link State Acknowledgment

Attribute Name: packet-ls-ack

Attribute Type: bits (send|recv|detail)

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <debug>
  <config>
    <packet-ls-ack>send</packet-ls-ack> <!-- operation="delete"-->
  </config>
</debug>
</ospfv3>
```

```
</config>  
</debug>  
</ospfv3>
```

### Command Syntax

```
debug ipv6 ospf packet ls-ack ({send|recv|detail}|)
```

---

## debug ipv6 ospf

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-ospf-on xmlns="http://  
www.ipinfusion.com/yang/ocnos/ipi-ospfv3"/>
```

### Command Syntax

```
debug ipv6 ospf
```

---

## no debug ipv6 ospf

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-ospf-off xmlns="http://  
www.ipinfusion.com/yang/ocnos/ipi-ospfv3"/>
```

### Command Syntax

```
no debug ipv6 ospf
```

---

## debug ipv6 ospf all

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-ospf-all-on xmlns="http://  
www.ipinfusion.com/yang/ocnos/ipi-ospfv3"/>
```

### Command Syntax

```
debug ipv6 ospf all
```

---

## no debug ipv6 ospf all

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-ospf-all-off xmlns="http://  
www.ipinfusion.com/yang/ocnos/ipi-ospfv3"/>
```

### Command Syntax

```
no debug ipv6 ospf all
```

---

## debug ipv6 ospf bfd

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-bfd-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3"/>
```

### Command Syntax

```
debug ipv6 ospf bfd
```

---

## no debug ipv6 ospf bfd

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-bfd-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3"/>
```

### Command Syntax

```
no debug ipv6 ospf bfd
```

---

## debug ipv6 ospf retransmission

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-retransmission-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3"/>
```

### Command Syntax

```
debug ipv6 ospf retransmission
```

---

## no debug ipv6 ospf retransmission

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-retransmission-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3"/>
```

### Command Syntax

```
no debug ipv6 ospf retransmission
```

---

## debug ipv6 ospf events ({abr|asbr|vlink|os|router|nssa})

Attribute Name: events

Attribute Type: bits (abr|asbr|vlink|os|router|nssa)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-events-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">  
  <events>abr</events>  
</ipi-ospfv3-debug_ospfv3-terminal-debug-events-on>
```

---

## Command Syntax

```
debug ipv6 ospf events ({abr|asbr|vlink|os|router|nssa|})
```

---

## no debug ipv6 ospf events ({abr|asbr|vlink|os|router|nssa|})

Attribute Name: events

Attribute Type: bits (abr|asbr|vlink|os|router|nssa)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-events-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <events>abr</events>
</ipi-ospfv3-debug_ospfv3-terminal-debug-events-off>
```

## Command Syntax

```
no debug ipv6 ospf events ({abr|asbr|vlink|os|router|nssa|})
```

---

## debug ipv6 ospf ifsm ({status|events|timers|})

Attribute Name: ifsm

Attribute Type: bits (status|events|timers)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-ifsm-on xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <ifsm>status</ifsm>
</ipi-ospfv3-debug_ospfv3-terminal-debug-ifsm-on>
```

## Command Syntax

```
debug ipv6 ospf ifsm ({status|events|timers|})
```

---

## no debug ipv6 ospf ifsm ({status|events|timers|})

Attribute Name: ifsm

Attribute Type: bits (status|events|timers)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-ifsm-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <ifsm>status</ifsm>
</ipi-ospfv3-debug_ospfv3-terminal-debug-ifsm-off>
```

## Command Syntax

```
no debug ipv6 ospf ifsm ({status|events|timers|})
```

---

## debug ipv6 ospf lsa ({generate|flooding|install|refresh|maxage|})

Attribute Name: lsa

---

Attribute Type: bits (generate|flooding|install|refresh|maxage)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-lsa-on xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-ospfv3">
  <lsa>generate</lsa>
</ipi-ospfv3-debug_ospfv3-terminal-debug-lsa-on>
```

### Command Syntax

```
debug ipv6 ospf lsa ({generate|flooding|install|refresh|maxage}|)
```

---

## no debug ipv6 ospf lsa ({generate|flooding|install|refresh|maxage}|)

Attribute Name: lsa

Attribute Type: bits (generate|flooding|install|refresh|maxage)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-lsa-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <lsa>generate</lsa>
</ipi-ospfv3-debug_ospfv3-terminal-debug-lsa-off>
```

### Command Syntax

```
no debug ipv6 ospf lsa ({generate|flooding|install|refresh|maxage}|)
```

---

## debug ipv6 ospf nfsm ({status|events|timers}|)

Attribute Name: nfsm

Attribute Type: bits (status|events|timers)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-nfsm-on xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <nfsm>status</nfsm>
</ipi-ospfv3-debug_ospfv3-terminal-debug-nfsm-on>
```

### Command Syntax

```
debug ipv6 ospf nfsm ({status|events|timers}|)
```

---

## no debug ipv6 ospf nfsm ({status|events|timers}|)

Attribute Name: nfsm

Attribute Type: bits (status|events|timers)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-nfsm-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <nfsm>status</nfsm>
</ipi-ospfv3-debug_ospfv3-terminal-debug-nfsm-off>
```

---

## Command Syntax

```
no debug ipv6 ospf nsm ({status|events|timers}|)
```

---

## debug ipv6 ospf nsm ({interface|redistribute}|)

Attribute Name: nsm

Attribute Type: bits (interface|redistribute)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-nsm-on xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-ospfv3">
  <nsm>interface</nsm>
</ipi-ospfv3-debug_ospfv3-terminal-debug-nsm-on>
```

## Command Syntax

```
debug ipv6 ospf nsm ({interface|redistribute}|)
```

---

## no debug ipv6 ospf nsm ({interface|redistribute}|)

Attribute Name: nsm

Attribute Type: bits (interface|redistribute)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-nsm-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <nsm>int</nsm>
</ipi-ospfv3-debug_ospfv3-terminal-debug-nsm-off>
```

## Command Syntax

```
no debug ipv6 ospf nsm ({interface|redistribute}|)
```

---

## debug ipv6 ospf packet ({send|recv|detail}|)

Attribute Name: all

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-packet-all-on xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <all>send</all>
</ipi-ospfv3-debug_ospfv3-terminal-debug-packet-all-on>
```

## Command Syntax

```
debug ipv6 ospf packet ({send|recv|detail}|)
```

---

## no debug ipv6 ospf packet ({send|recv|detail}|)

Attribute Name: all

---

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-packet-all-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <all>send</all>
</ipi-ospfv3-debug_ospfv3-terminal-debug-packet-all-off>
```

### Command Syntax

```
no debug ipv6 ospf packet ({send|recv|detail}|)
```

---

## debug ipv6 ospf packet hello ({send|recv|detail}|)

Attribute Name: hello

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-packet-hello-on xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <hello>send</hello>
</ipi-ospfv3-debug_ospfv3-terminal-debug-packet-hello-on>
```

### Command Syntax

```
debug ipv6 ospf packet hello ({send|recv|detail}|)
```

---

## no debug ipv6 ospf packet hello ({send|recv|detail}|)

Attribute Name: hello

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-packet-hello-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <hello>send</hello>
</ipi-ospfv3-debug_ospfv3-terminal-debug-packet-hello-off>
```

### Command Syntax

```
no debug ipv6 ospf packet hello ({send|recv|detail}|)
```

---

## debug ipv6 ospf packet dd ({send|recv|detail}|)

Attribute Name: dd

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-packet-dd-on xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <dd>send</dd>
</ipi-ospfv3-debug_ospfv3-terminal-debug-packet-dd-on>
```

---

## Command Syntax

```
debug ipv6 ospf packet dd ({send|recv|detail}|)
```

---

## no debug ipv6 ospf packet dd ({send|recv|detail}|)

Attribute Name: dd

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-packet-dd-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <dd>send</dd>
</ipi-ospfv3-debug_ospfv3-terminal-debug-packet-dd-off>
```

## Command Syntax

```
no debug ipv6 ospf packet dd ({send|recv|detail}|)
```

---

## debug ipv6 ospf packet ls-request ({send|recv|detail}|)

Attribute Name: ls-request

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-packet-ls-request-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <ls-request>send</ls-request>
</ipi-ospfv3-debug_ospfv3-terminal-debug-packet-ls-request-on>
```

## Command Syntax

```
debug ipv6 ospf packet ls-request ({send|recv|detail}|)
```

---

## no debug ipv6 ospf packet ls-request ({send|recv|detail}|)

Attribute Name: ls-request

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-packet-ls-request-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <ls-request>send</ls-request>
</ipi-ospfv3-debug_ospfv3-terminal-debug-packet-ls-request-off>
```

## Command Syntax

```
no debug ipv6 ospf packet ls-request ({send|recv|detail}|)
```

---

## debug ipv6 ospf packet ls-update ({send|recv|detail}|)

Attribute Name: ls-update

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-packet-ls-update-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <ls-update>send</ls-update>
</ipi-ospfv3-debug_ospfv3-terminal-debug-packet-ls-update-on>
```

### Command Syntax

```
debug ipv6 ospf packet ls-update ({send|recv|detail}|)
```

---

## no debug ipv6 ospf packet ls-update ({send|recv|detail}|)

Attribute Name: ls-update

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-packet-ls-update-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <ls-update>send</ls-update>
</ipi-ospfv3-debug_ospfv3-terminal-debug-packet-ls-update-off>
```

### Command Syntax

```
no debug ipv6 ospf packet ls-update ({send|recv|detail}|)
```

---

## debug ipv6 ospf packet ls-ack ({send|recv|detail}|)

Attribute Name: ls-ack

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-packet-ls-ack-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <ls-ack>send</ls-ack>
</ipi-ospfv3-debug_ospfv3-terminal-debug-packet-ls-ack-on>
```

### Command Syntax

```
debug ipv6 ospf packet ls-ack ({send|recv|detail}|)
```

---

## no debug ipv6 ospf packet ls-ack ({send|recv|detail}|)

Attribute Name: ls-ack

Attribute Type: bits (send|recv|detail)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-packet-ls-ack-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <ls-ack>send</ls-ack>
</ipi-ospfv3-debug_ospfv3-terminal-debug-packet-ls-ack-off>
```

---

## Command Syntax

```
no debug ipv6 ospf packet ls-ack ({send|recv|detail}|)
```

---

## debug ipv6 ospf rib ({interface|redistribute}|)

Attribute Name: rib

Attribute Type: bits (interface|redistribute)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-rib-on xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-ospfv3">
  <rib>interface</rib>
</ipi-ospfv3-debug_ospfv3-terminal-debug-rib-on>
```

## Command Syntax

```
debug ipv6 ospf rib ({interface|redistribute}|)
```

---

## no debug ipv6 ospf rib ({interface|redistribute}|)

Attribute Name: rib

Attribute Type: bits (interface|redistribute)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-rib-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <rib>interface</rib>
</ipi-ospfv3-debug_ospfv3-terminal-debug-rib-off>
```

## Command Syntax

```
no debug ipv6 ospf rib ({interface|redistribute}|)
```

---

## debug ipv6 ospf route ({spf|ia|ase|install}|)

Attribute Name: route

Attribute Type: bits (spf|ia|ase|install)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-route-on xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <route>spf</route>
</ipi-ospfv3-debug_ospfv3-terminal-debug-route-on>
```

## Command Syntax

```
debug ipv6 ospf route ({spf|ia|ase|install}|)
```

---

## no debug ipv6 ospf route ({spf|ia|ase|install}|)

Attribute Name: route

---

Attribute Type: bits (spf|ia|ase|install)

### Netconf RPC payload

```
<ipi-ospfv3-debug_ospfv3-terminal-debug-route-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <route>spf</route>
</ipi-ospfv3-debug_ospfv3-terminal-debug-route-off>
```

### Command Syntax

```
no debug ipv6 ospf route ({spf|ia|ase|install|})
```

---

## clear ipv6 ospf (WORD|) process

Attribute Name: process-id

Attribute Type: string

### Netconf RPC payload

```
<ipi-ospfv3-global_ospfv3-clear-process xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <process-id>WORD</process-id>
</ipi-ospfv3-global_ospfv3-clear-process>
```

### Command Syntax

```
clear ipv6 ospf (WORD|) process
```

---

## restart ipv6 ospf graceful (grace-period <2-1800>|)

Attribute Name: grace-period

Attribute Type: uint16

Attribute Range: 2-1800

### Netconf RPC payload

```
<ipi-ospfv3-global_ospfv3-graceful-restart xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <grace-period>2</grace-period>
</ipi-ospfv3-global_ospfv3-graceful-restart>
```

### Command Syntax

```
restart ipv6 ospf graceful (grace-period <2-1800>|)
```

---

## snmp restart ospf6

### Netconf RPC payload

```
<ipi-ospfv3-global_ospfv3-snmp-restart xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3"/>
```

### Command Syntax

```
snmp restart ospf6
```

---

## IPI-OSPFV3-INTERFACE

---

### Configure shutdown

Use this attribute to shutdown OSPFV3 on the interface

Attribute Name: shutdown

Attribute Type: empty

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <interfaces>
    <interface>
      <interface-name>WORD</interface-name>
      <config>
        <interface-name>WORD</interface-name>
      </config>
      </shutdown><!-- operation="delete"-->
    </interface>
  </interfaces>
</ospfv3>
```

### Command Syntax

```
ospfv3 shutdown
```

---

### Configure enable link lsa suppression

Use this attribute to enable or disable link LSA (type 8) suppression. A type 8 LSA gives information about link-local addresses and a list of IPv6 addresses on the link. If enabled and the interface type is not broadcast or NBMA, the router does not send type 8 link LSAs. This implies that other routers on the link determine the router's next-hop address using a mechanism other than the type 8 link LSA. This feature is implicitly disabled if the interface type is broadcast or NBMA.

Attribute Name: enable-link-lsa-suppression

Attribute Type: uint8

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <interfaces>
    <interface>
      <interface-name>WORD</interface-name>
      <config>
        <interface-name>WORD</interface-name>
      </config>
      <instances>
        <instance>
          <instance-id>0</instance-id>
          <config>
```

```

        <instance-id>0</instance-id>
    </config>
    </enable-link-lsa-suppression><!-- operation="delete"-->
</instance>
</instances>
</interface>
</interfaces>
</ospfv3>

```

### Command Syntax

```
ipv6 ospf link-lsa-suppression enable (instance-id (<0-31>|<64-95>))
```

---

## Configure enable bfd

Use this attribute to enable Bidirectional Forwarding Detection (BFD)

Attribute Name: enable-bfd

Attribute Type: boolean

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<interfaces>
<interface>
    <interface-name>WORD</interface-name>
    <config>
        <interface-name>WORD</interface-name>
    </config>
    <instances>
    <instance>
        <instance-id>0</instance-id>
        <config>
            <instance-id>0</instance-id>
        </config>
        <enable-bfd>true</enable-bfd> <!-- operation="delete"-->
    </instance>
</instances>
</interface>
</interfaces>
</ospfv3>

```

### Command Syntax

```
ipv6 ospf bfd (instance-id (<0-31>|<64-95>))
```

---

## Configure interface name

Use this attribute to enable Bidirectional Forwarding Detection (BFD)

Attribute Name: enable-bfd

Attribute Type: boolean

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<interfaces>
<interface>
  <interface-name>WORD</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <instances>
  <instance>
    <instance-id>0</instance-id>
    <config>
      <instance-id>0</instance-id>
    </config>
    <enable-bfd>true</enable-bfd> <!-- operation="delete"-->
  </instance>
</instances>
</interface>
</interfaces>
</ospfv3>
```

## Command Syntax

```
ipv6 ospf bfd disable (instance-id (<0-31>|<64-95>))|
```

---

## Configure instance id

Use this attribute to enable or disable link LSA (type 8) suppression. A type 8 LSA gives information about link-local addresses and a list of IPv6 addresses on the link. If enabled and the interface type is not broadcast or NBMA, the router does not send type 8 link LSAs. This implies that other routers on the link determine the router's next-hop address using a mechanism other than the type 8 link LSA. This feature is implicitly disabled if the interface type is broadcast or NBMA.

Attribute Name: enable-link-lsa-suppression

Attribute Type: uint8

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<interfaces>
<interface>
  <interface-name>WORD</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <instances>
  <instance>
    <instance-id>0</instance-id>
    <config>
      <instance-id>0</instance-id>
    </config>
    </enable-link-lsa-suppression><!-- operation="delete"-->
  </instance>
</instances>
</interface>
</interfaces>
</ospfv3>
```

```

    </instance>
  </instances>
</interface>
</interfaces>
</ospfv3>

```

### Command Syntax

```
ipv6 ospf link-lsa-suppression enable (instance-id (<0-31>|<64-95>)|)
```

---

## Configure instance enable-bfd

Use this attribute to enable Bidirectional Forwarding Detection (BFD)

Attribute Name: enable-bfd

Attribute Type: boolean

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <interfaces>
    <interface>
      <interface-name>WORD</interface-name>
      <config>
        <interface-name>WORD</interface-name>
      </config>
      <instances>
        <instance>
          <instance-id>0</instance-id>
          <config>
            <instance-id>0</instance-id>
            </config>
            <enable-bfd>>true</enable-bfd> <!-- operation="delete"-->
          </instance>
        </instances>
      </interface>
    </interfaces>
  </ospfv3>

```

### Command Syntax

```
ipv6 ospf bfd (instance-id (<0-31>|<64-95>)|)
```

---

## Configure instance enable-bfd

Use this attribute to enable Bidirectional Forwarding Detection (BFD)

Attribute Name: enable-bfd

Attribute Type: boolean

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <interfaces>

```

```

<interface>
  <interface-name>WORD</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <instances>
  <instance>
    <instance-id>0</instance-id>
    <config>
      <instance-id>0</instance-id>
    </config>
    <enable-bfd>true</enable-bfd> <!-- operation="delete"-->
  </instance>
</instances>
</interface>
</interfaces>
</ospfv3>

```

### Command Syntax

```
ipv6 ospf bfd disable (instance-id (<0-31>|<64-95>))|)
```

---

## Configure network type

Use this attribute to set an OSPFv3 network type.

Attribute Name: network-type

Attribute Type: enum (point-to-point|broadcast|non-broadcast|point-to-multipoint|point-to-multipoint non-broadcast)

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <interfaces>
  <interface>
    <interface-name>WORD</interface-name>
    <config>
      <interface-name>WORD</interface-name>
    </config>
    <instances>
    <instance>
      <instance-id>0</instance-id>
      <config>
        <instance-id>0</instance-id>
      </config>
      <network-type>point-to-point</network-type> <!-- operation="delete"-->
    </instance>
  </instances>
</interface>
</interfaces>
</ospfv3>

```

## Command Syntax

```
ipv6 ospf network (point-to-point|broadcast|non-broadcast|point-to-
multipoint|point-to-multipoint non-broadcast) (instance-id (<0-31>|<64-95>)|)
```

---

## Configure cost

Use this attribute to specify the link-cost described in LSAs. The cost (or metric) of an interface in OSPF indicates the overhead required to send packets across a certain interface. The value is taken to describe Link State information, and used for route calculation.

Attribute Name: cost

Attribute Type: uint16

Default Value: 1

Attribute Range: 1-65535

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<interfaces>
<interface>
  <interface-name>WORD</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <instances>
  <instance>
    <instance-id>0</instance-id>
    <config>
      <instance-id>0</instance-id>
    </config>
    <cost>1</cost> <!-- operation="delete"-->
  </instance>
</instances>
</interface>
</interfaces>
</ospfv3>
```

## Command Syntax

```
ipv6 ospf cost <1-65535> (instance-id (<0-31>|<64-95>)|)
```

---

## Configure priority

Use this attribute to set the router priority for determining the designated router (DR) for the network. A router with the higher router priority becomes the DR. If the priority is the same for two routers, the router with the higher router ID takes precedence. Only routers with a nonzero priority value are eligible to become the designated or backup designated router. Configure router priority for broadcast or NBMA networks only and not for point-to-point networks.

Attribute Name: priority

Attribute Type: uint8

Default Value: 1

Attribute Range: 0-255

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<interfaces>
<interface>
  <interface-name>WORD</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <instances>
  <instance>
    <instance-id>0</instance-id>
    <config>
      <instance-id>0</instance-id>
    </config>
    <priority>0</priority> <!-- operation="delete"-->
  </instance>
</instances>
</interface>
</interfaces>
</ospfv3>
```

### Command Syntax

```
ipv6 ospf priority <0-255> (instance-id (<0-31>|<64-95>))
```

---

## Configure mtu

Use this attribute to set MTU size for OSPFv3 to construct packets based on this value. Whenever OSPFv3 constructs packets, it uses interface MTU size as Maximum IP packet size. this attribute forces OSPFv3 to use the specified value overriding the actual interface MTU size.

Attribute Name: mtu

Attribute Type: uint16

Default Value: 1500

Attribute Range: 1280-65535

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<interfaces>
<interface>
  <interface-name>WORD</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <instances>
  <instance>
    <instance-id>0</instance-id>
    <config>
```

```

        <instance-id>0</instance-id>
    </config>
    <mtu>1280</mtu> <!-- operation="delete"-->
</instance>
</instances>
</interface>
</interfaces>
</ospfv3>

```

### Command Syntax

```
ipv6 ospf mtu <1280-65535> (instance-id (<0-31>|<64-95>))
```

---

## Configure mtu ignore

Use this attribute to ignore the MTU size during DD (Database Description) exchange. By default, during the DD exchange process, OSPFv3 checks the MTU size described in DD packets received from its neighbor, and if the MTU size does not match the interface MTU, the neighbor adjacency is not established. Using this command makes OSPFv3 ignore this check and allows establishing of adjacency regardless of MTU size in the DD packet.

Attribute Name: mtu-ignore

Attribute Type: empty

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<interfaces>
<interface>
    <interface-name>WORD</interface-name>
    <config>
        <interface-name>WORD</interface-name>
    </config>
    <instances>
    <instance>
        <instance-id>0</instance-id>
        <config>
            <instance-id>0</instance-id>
        </config>
        </mtu-ignore><!-- operation="delete"-->
    </instance>
</instances>
</interface>
</interfaces>
</ospfv3>

```

### Command Syntax

```
ipv6 ospf mtu-ignore (instance-id (<0-31>|<64-95>))
```

---

## Configure authentication cryptomap

Use this attribute to set the Crypto-map used to setup IPsec SA.

Attribute Name: authentication-cryptomap

Attribute Type: string

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<interfaces>
<interface>
  <interface-name>WORD</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <instances>
  <instance>
    <instance-id>0</instance-id>
    <config>
      <instance-id>0</instance-id>
    </config>
    <authentication-cryptomap>WORD</authentication-cryptomap> <!--
operation="delete"-->
  </instance>
</instances>
</interface>
</interfaces>
</ospfv3>
```

### Command Syntax

```
ipv6 ospf (instance-id (<0-31>|<64-95>)) authentication cryptomap WORD
```

---

## Configure area id

Use this attribute to enable OSPFv3 routing on an interface. Specify the process ID to configure multiple instances of OSPFv3. When running a single instance of OSPFv3, you do not need to specify a instance ID. When OSPFv3 receives a packet, it checks if the instance ID in the packet matches the instance ID of the receiving interface.

Attribute Name: area-id

Attribute Type: union

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<interfaces>
<interface>
  <interface-name>WORD</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <instances>
  <instance>
    <instance-id>0</instance-id>
    <config>
      <instance-id>0</instance-id>
    </config>
```

```

<router> <!-- operation="delete"-->
  <area-id>OSPFV3_AREA_T</area-id>
  <config>
    <area-id>OSPFV3_AREA_T</area-id>
    <ospfv3-id>WORD</ospfv3-id>
  </config>
  <ospfv3-id>WORD</ospfv3-id>
</router>
</routers>
</instance>
</instances>
</interface>
</interfaces>
</ospfv3>

```

## Command Syntax

```
ipv6 router ospf area (A.B.C.D|<0-4294967295>) (instance-id (<0-31>|<64-95>)|)
```

## Configure ospfv3 id

Use this attribute to enable OSPFv3 routing on an interface. Specify the process ID to configure multiple instances of OSPFv3. When running a single instance of OSPFv3, you do not need to specify a instance ID. When OSPFv3 receives a packet, it checks if the instance ID in the packet matches the instance ID of the receiving interface.

Attribute Name: area-id

Attribute Type: uint32

## Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <interfaces>
    <interface>
      <interface-name>WORD</interface-name>
      <config>
        <interface-name>WORD</interface-name>
      </config>
    <instances>
      <instance>
        <instance-id>0</instance-id>
        <config>
          <instance-id>0</instance-id>
        </config>
      <router>
        <!-- operation="delete"-->
        <area-id>OSPFV3_AREA_T</area-id>
        <config>
          <area-id>OSPFV3_AREA_T</area-id>
          <ospfv3-id>WORD</ospfv3-id>
        </config>
        <ospfv3-id>WORD</ospfv3-id>

```

```

    </router>
  </routers>
</instance>
</instances>
</interface>
</interfaces>
</ospfv3>

```

## Command Syntax

```
ipv6 router ospf area (instance-id (<0-31>|<64-95>)|)
```

---

## Configure router area-id

Use this attribute to enable OSPFv3 routing on an interface. Specify the process ID to configure multiple instances of OSPFv3. When running a single instance of OSPFv3, you do not need to specify a instance ID. When OSPFv3 receives a packet, it checks if the instance ID in the packet matches the instance ID of the receiving interface.

Attribute Name: area-id

Attribute Type: uint32

## Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <interfaces>
    <interface>
      <interface-name>WORD</interface-name>
      <config>
        <interface-name>WORD</interface-name>
      </config>
      <instances>
        <instance>
          <instance-id>0</instance-id>
          <config>
            <instance-id>0</instance-id>
          </config>
          <routers>
            <router>
              <area-id>OSPFV3_AREA_T</area-id>
              <config>
                <area-id>OSPFV3_AREA_T</area-id>
                <ospfv3-id>WORD</ospfv3-id>
              </config>
              <ospfv3-id>WORD</ospfv3-id>
            </router>
          </routers>
        </instance>
      </instances>
    </interface>
  </interfaces>
</ospfv3>

```

## Command Syntax

```
ipv6 router ospf tag WORD area (instance-id (<0-31>|<64-95>)|)
```

---

## Configure router ospfv3-id

Use this attribute to enable OSPFv3 routing on an interface. Specify the process ID to configure multiple instances of OSPFv3. When running a single instance of OSPFv3, you do not need to specify a instance ID. When OSPFv3 receives a packet, it checks if the instance ID in the packet matches the instance ID of the receiving interface.

Attribute Name: ospfv3-id

Attribute Type: string

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<interfaces>
<interface>
  <interface-name>WORD</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <instances>
  <instance>
    <instance-id>0</instance-id>
    <config>
      <instance-id>0</instance-id>
    </config>
    <routers>
    <router>
      <area-id>OSPFV3_AREA_T</area-id>
      <config>
        <area-id>OSPFV3_AREA_T</area-id>
        <ospfv3-id>WORD</ospfv3-id>
      </config>
      <ospfv3-id>WORD</ospfv3-id>
    </router>
  </routers>
</instance>
</instances>
</interface>
</interfaces>
</ospfv3>
```

## Command Syntax

```
ipv6 router ospf area tag WORD (instance-id (<0-31>|<64-95>)|)
```

---

## Configure dead interval

Use this attribute to set the amount of time that the router waits to receive an OSPF hello packet from the neighbor before declaring the neighbor down

Attribute Name: dead-interval

Attribute Type: uint16

Default Value: 40

Attribute Range: 1-65535

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<interfaces>
<interface>
  <interface-name>WORD</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <instances>
  <instance>
    <instance-id>0</instance-id>
    <config>
      <instance-id>0</instance-id>
    </config>
    <timers>
    <config>
      <dead-interval>1</dead-interval> <!-- operation="delete"-->
    </config>
  </timers>
</instance>
</instances>
</interface>
</interfaces>
</ospfv3>
```

### Command Syntax

```
ipv6 ospf dead-interval <1-65535> (instance-id (<0-31>|<64-95>)|)
```

---

## Configure hello interval

Use this attribute to set the interval between hello packets.

Attribute Name: hello-interval

Attribute Type: uint16

Attribute Range: 1-65535

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<interfaces>
<interface>
  <interface-name>WORD</interface-name>
  <config>
    <interface-name>WORD</interface-name>
```

```

</config>
<instances>
<instance>
  <instance-id>0</instance-id>
  <config>
    <instance-id>0</instance-id>
  </config>
  <timers>
  <config>
    <hello-interval>1</hello-interval> <!-- operation="delete"-->
  </config>
</timers>
</instance>
</instances>
</interface>
</interfaces>
</ospfv3>

```

### Command Syntax

```
ipv6 ospf hello-interval <1-65535> (instance-id (<0-31>|<64-95>)|)
```

---

## Configure transmission delay

Use this attribute to set the estimated time it takes to transmit a Link State Update packet over the interface.

Attribute Name: transmission-delay

Attribute Type: uint16

Default Value: 1

Attribute Range: 1-1800

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<interfaces>
<interface>
  <interface-name>WORD</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
<instances>
<instance>
  <instance-id>0</instance-id>
  <config>
    <instance-id>0</instance-id>
  </config>
  <timers>
  <config>
    <transmission-delay>1</transmission-delay> <!-- operation="delete"-->
  </config>
</timers>

```

```

</instance>
</instances>
</interface>
</interfaces>
</ospfv3>

```

### Command Syntax

```
ipv6 ospf transmit-delay <1-1800> (instance-id (<0-31>|<64-95>)|)
```

---

## Configure retransmission interval

Use this attribute to set the interval between retransmission of Link State Update packets.

Attribute Name: retransmission-interval

Attribute Type: uint16

Default Value: 5

Attribute Range: 1-1800

### Netconf edit-config payload

```

<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
<interfaces>
<interface>
  <interface-name>WORD</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <instances>
  <instance>
    <instance-id>0</instance-id>
    <config>
      <instance-id>0</instance-id>
    </config>
    <timers>
    <config>
      <retransmission-interval>1</retransmission-interval> <!--
operation="delete"-->
    </config>
    </timers>
  </instance>
</instances>
</interface>
</interfaces>
</ospfv3>

```

### Command Syntax

```
ipv6 ospf retransmit-interval <1-1800> (instance-id (<0-31>|<64-95>)|)
```

---

## Configure address

Static neighbor IPv6 link-local address

Attribute Name: address

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <interfaces>
    <interface>
      <interface-name>WORD</interface-name>
      <config>
        <interface-name>WORD</interface-name>
      </config>
      <instances>
        <instance>
          <instance-id>0</instance-id>
          <config>
            <instance-id>0</instance-id>
            </config>
            <neighbors-static>
              <neighbor-static <!-- operation="delete"-->
                <address>X:X::X:X</address>
                <config>
                  <address>X:X::X:X</address>
                </config>
              </neighbor-static>
            </neighbors-static>
          </instance>
        </instances>
      </interface>
    </interfaces>
  </ospfv3>
```

### Command Syntax

```
ipv6 ospf neighbor X:X::X:X (instance-id (<0-31>|<64-95>)|)
```

---

## Configure neighbors-static address

Static neighbor IPv6 link-local address

Attribute Name: address

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
  <interfaces>
    <interface>
      <interface-name>WORD</interface-name>
```

```

<config>
  <interface-name>WORD</interface-name>
</config>
<instances>
<instance>
  <instance-id>0</instance-id>
  <config>
    <instance-id>0</instance-id>
  </config>
  <neighbors-static>
  <neighbor-static> <!-- operation="delete"-->
    <address>X:X::X:X</address>
    <config>
      <address>X:X::X:X</address>
    </config>
  </neighbor-static>
</neighbors-static>
</instance>
</instances>
</interface>
</interfaces>
</ospfv3>

```

## Command Syntax

```
ipv6 ospf neighbor X:X::X:X (instance-id (<0-31>|<64-95>)|)
```

---

## Configure poll interval

Use this attribute to set the dead neighbor polling interval in seconds. It is recommended to set this value much higher than the hello interval. The default is 120 seconds.

Attribute Name: poll-interval

Attribute Type: uint32

Default Value: 120

Attribute Range: 0-4294967295

Attribute Name: cost

Attribute Type: uint16

Default Value: 10

Attribute Range: 1-65535

Attribute Name: priority

Attribute Type: uint8

Default Value: 0

Attribute Range: 0-255

## Netconf edit-config payload

```
<ospfv3 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ospfv3">
```

```

<interfaces>
<interface>
  <interface-name>WORD</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <instances>
  <instance>
    <instance-id>0</instance-id>
    <config>
      <instance-id>0</instance-id>
    </config>
    <neighbors-static>
    <neighbor-static>
      <address>X:X::X:X</address>
      <config>
        <address>X:X::X:X</address>
        <cost>1</cost> <!-- operation="delete"-->
        <priority>0</priority> <!-- operation="delete"-->
      </config>
      <poll-interval>0</poll-interval> <!-- operation="delete"-->
    </neighbor-static>
  </neighbors-static>
</instance>
</instances>
</interface>
</interfaces>
</ospfv3>

```

## Command Syntax

```

ipv6 ospf neighbor X:X::X:X { cost <1-65535>| priority <0-255>| poll-interval <0-4294967295> } (instance-id (<0-31>|<64-95>)|)

```

---

## IPI-BGP

---

### Configure action name

Use this attribute to specify a standard community list (1 to 99) that specifies BGP community attributes.

Attribute Name: action-name

Attribute Type: enum (deny|permit)

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<global>
<community-lists>
<numbered-lists>
<numbered-list>

```

```

    <standard-number>1</standard-number>
  </config>
  <standard-number>1</standard-number>
</config>
<action-for-any>
<config>
  <action-name>deny</action-name>
</config>
</action-for-any>
</numbered-list>
</numbered-lists>
</community-lists>
</global>
</bgp>

```

## Command Syntax

```
ip community-list <1-99> (deny|permit)
```

---

## Configure action standard number

Use this attribute to specify a standard community list (1 to 99) that specifies BGP community attributes.

Attribute Name: action-standard-number

Attribute Type: enum (deny|permit)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
    <community-lists>
      <numbered-lists>
        <numbered-list>
          <standard-number>1</standard-number>
          <config>
            <standard-number>1</standard-number>
          </config>
        </numbered-list>
      </numbered-lists>
      <action-list-values>
        <action-list-value <!-- operation="delete"-->
          <standard-number-value>AA:NN</standard-number-value>
          <config>
            <standard-number-value>WORD</standard-number-value>
            <action-standard-number>deny</action-standard-number>
          </config>
          <action-standard-number>deny</action-standard-number>
        </action-list-value>
      </action-list-values>
    </community-lists>
  </global>
</bgp>

```

## Command Syntax

```
ip community-list <1-99> (deny|permit) ((AA:NN|internet|local-AS|no-advertise|no-export))
```

---

## Configure action name standard

Use the community-lists to specify BGP community attributes. The community attribute is used for implementing policy routing. It is an optional, transitive attribute and facilitates transfer of local policies through different autonomous systems. It includes community values that are 32 bits long. There are two kinds of community-lists: expanded and standard. The standard community-list defines the community attributes in a specified format without regular expressions. The expanded community-list defines the community attributes with regular expressions. Use this attribute to add a standard community-list entry. The standard community-list is compiled into binary format and is directly compared with the BGP communities attribute in the BGP updates. The comparison is faster than the expanded community-list. Any community value that does not match the standard community value is automatically treated as expanded.

Attribute Name: action-name-standard

Attribute Type: enum (deny|permit)

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
    <community-lists>
      <standards>
        <standard>
          <name>WORD</name>
          <config>
            <name>WORD</name>
            <list-type>standard</list-type>
          </config>
          <list-type>standard</list-type>
        </standard>
      </standards>
      <action-values>
        <action-value> <!-- operation="delete"-->
          <community-value-standard>AA:NN</community-value-standard>
          <config>
            <community-value-standard>WORD</community-value-standard>
            <action-name-standard>deny</action-name-standard>
          </config>
          <action-name-standard>deny</action-name-standard>
        </action-value>
      </action-values>
    </community-lists>
  </global>
</bgp>
```

## Command Syntax

```
ip community-list WORD (deny|permit) ((AA:NN|internet|local-AS|no-advertise|no-export))
```

---

## Configure list type

Use this attribute to specify a standard community list (1 to 99) that specifies BGP community attributes.

Attribute Name: action-name

Attribute Type: enum (deny|permit)

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
    <community-lists>
      <standards>
        <standard>
          <name>WORD</name>
          <config>
            <name>WORD</name>
            <list-type>standard</list-type>
          </config>
          <list-type>standard</list-type>
        <action-for-any>
          <config>
            <action-name>deny</action-name>
          </config>
        </action-for-any>
      </standard>
    </standards>
  </community-lists>
</global>
</bgp>
```

### Command Syntax

```
ip community-list (standard) WORD (deny|permit)
```

---

## Configure name

Use the community-lists to specify BGP community attributes. The community attribute is used for implementing policy routing. It is an optional, transitive attribute and facilitates transfer of local policies through different autonomous systems. It includes community values that are 32 bits long. There are two kinds of community-lists: expanded and standard. The standard community-list defines the community attributes in a specified format without regular expressions. The expanded community-list defines the community attributes with regular expressions. Use this attribute to add a standard community-list entry. The standard community-list is compiled into binary format and is directly compared with the BGP communities attribute in the BGP updates. The comparison is faster than the expanded community-list. Any community value that does not match the standard community value is automatically treated as expanded.

Attribute Name: action-name-standard

Attribute Type: enum (deny|permit)

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
```

```

<community-lists>
<standards>
<standard>
  <name>WORD</name>
  <config>
    <name>WORD</name>
    <list-type>standard</list-type>
  </config>
  <list-type>standard</list-type>
</standard>
</standards>
</community-lists>
</global>
</bgp>

```

## Command Syntax

```

ip community-list (standard) WORD (deny|permit) ((AA:NN|internet|local-AS|no-
advertise|no-export))

```

---

## Configure action expanded

Community list extended type

Attribute Name: action-expanded

Attribute Type: enum (deny|permit)

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<global>
<community-lists>
<expanded-lists>
<expanded-list>
  <expanded-type>BGP_EXPANDED_LIST_TYPE_T</expanded-type>
  <config>
    <expanded-type>BGP_EXPANDED_LIST_TYPE_T</expanded-type>
    <list-type>expanded</list-type>
  </config>
  <list-type>expanded</list-type>
</expanded-list>
</expanded-lists>
</community-lists>
</global>
</bgp>

```

```

    <regular-expression-list>LINE</regular-expression-list>
  <config>
    <regular-expression-list>LINE</regular-expression-list>
    <action-expanded>deny</action-expanded>
  </config>
  <action-expanded>deny</action-expanded>
</action-value>
</action-values>
</expanded-list>
</expanded-lists>
</community-lists>
</global>
</bgp>

```

## Command Syntax

```
ip community-list <100-500> (deny|permit) LINE
```

---

## Configure expanded type

Community list extended type

Attribute Name: action-expanded

Attribute Type: enum (deny|permit)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
    <community-lists>
      <expanded-lists>
        <expanded-list>
          <expanded-type>BGP_EXPANDED_LIST_TYPE_T</expanded-type>
        <config>
          <expanded-type>BGP_EXPANDED_LIST_TYPE_T</expanded-type>
          <list-type>expanded</list-type>
        </config>
      </expanded-list>
    </expanded-lists>
  </global>
  <action-values>
    <action-value> <!-- operation="delete"-->
      <regular-expression-list>LINE</regular-expression-list>
      <config>
        <regular-expression-list>LINE</regular-expression-list>
        <action-expanded>deny</action-expanded>
      </config>
      <action-expanded>deny</action-expanded>
    </action-value>
  </action-values>
</expanded-list>
</expanded-lists>
</community-lists>
</global>

```

---

```
</bgp>
```

## Command Syntax

```
ip community-list (expanded) WORD (deny|permit) LINE
```

---

## Configure extended action number

Extended Community list type

Attribute Name: extended-action-number

Attribute Type: enum (deny|permit)

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<global>
<community-lists>
<extended-community>
<numbered-lists>
<numbered-list>
  <standard-number>1</standard-number>
  <config>
    <standard-number>1</standard-number>
  </config>
<action-values>
<action-value> <!-- operation="delete"-->
  <extended-value>LINE</extended-value>
  <config>
    <extended-value>LINE</extended-value>
    <extended-action-number>deny</extended-action-number>
  </config>
  <extended-action-number>deny</extended-action-number>
</action-value>
</action-values>
</numbered-list>
</numbered-lists>
</extended-community>
</community-lists>
</global>
</bgp>
```

## Command Syntax

```
ip extcommunity-list <1-99> (deny|permit) LINE
```

---

## Configure extended action

extcommunity Community list type

Attribute Name: extended-action

Attribute Type: enum (deny|permit)

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<global>
<community-lists>
<extended-community>
<standards>
<standard>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<action-values>
<action-value> <!-- operation="delete"-->
  <value>AA:NN</value>
  <config>
    <value>WORD</value>
    <route-target-soo>rt</route-target-soo>
    <extended-action>deny</extended-action>
  </config>
  <route-target-soo>rt</route-target-soo>
  <extended-action>deny</extended-action>
</action-value>
</action-values>
</standard>
</standards>
</extended-community>
</community-lists>
</global>
</bgp>

```

**Command Syntax**

```
ip extcommunity-list standard WORD (deny|permit) (rt|soo) AA:NN
```

**Configure action**

extcommunity Extended Community type

Attribute Name: action

Attribute Type: enum (deny|permit)

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<global>
<community-lists>
<extended-community>
<expanded-lists>
<expanded-list>
  <expanded-type>BGP_EXPANDED_LIST_TYPE_T</expanded-type>
  <config>
    <expanded-type>BGP_EXPANDED_LIST_TYPE_T</expanded-type>

```

```

    <list-type>expanded</list-type>
  </config>
  <list-type>expanded</list-type>
<action-values>
<action-value> <!-- operation="delete"-->
  <value>LINE</value>
  <config>
    <value>LINE</value>
    <action>deny</action>
  </config>
  <action>deny</action>
</action-value>
</action-values>
</expanded-list>
</expanded-lists>
</extended-community>
</community-lists>
</global>
</bgp>

```

## Command Syntax

```
ip extcommunity-list <100-500> (deny|permit) LINE
```

---

## Configure value

extcommunity Extended Community type

Attribute Name: action

Attribute Type: enum (deny|permit)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
  <community-lists>
  <extended-community>
  <expanded-lists>
  <expanded-list>
    <expanded-type>BGP_EXPANDED_LIST_TYPE_T</expanded-type>
    <config>
      <expanded-type>BGP_EXPANDED_LIST_TYPE_T</expanded-type>
      <list-type>expanded</list-type>
    </config>
    <list-type>expanded</list-type>
  </expanded-list>
  </expanded-lists>
  </extended-community>
  </community-lists>
  </global>
</bgp>

```

```

        <action>deny</action>
    </action-value>
</action-values>
</expanded-list>
</expanded-lists>
</extended-community>
</community-lists>
</global>
</bgp>

```

## Command Syntax

```
ip extcommunity-list (expanded) WORD (deny|permit) LINE
```

---

## Configure access list name

Use this attribute to define a BGP Autonomous System (AS) path access list. A named community list is a filter based on regular expressions. If the regular expression matches the specified string representing the AS path of the route, then the permit or deny condition applies. Use this attribute to define the BGP access list globally.

Attribute Name: access-list-name

Attribute Type: string

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
    <as-path-access-lists>
      <as-path-access-list> <!-- operation="delete"-->
        <access-list-regular-expression>LINE</access-list-regular-expression>
        <config>
          <access-list-regular-expression>LINE</access-list-regular-expression>
          <access-list-action>deny</access-list-action>
          <access-list-name>WORD</access-list-name>
        </config>
        <access-list-action>deny</access-list-action>
        <access-list-name>WORD</access-list-name>
      </as-path-access-list>
    </as-path-access-lists>
  </global>
</bgp>

```

## Command Syntax

```
ip as-path access-list WORD (deny|permit) LINE
```

---

## Configure enable aggregate nexthop

Use this attribute to set the BGP option to perform aggregation only when next-hop matches the specified IP address.

Attribute Name: enable-aggregate-nexthop

Attribute Type: empty

---

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
  <config>
    </enable-aggregate-nextthop><!-- operation="delete"-->
  </config>
</global>
</bgp>
```

## Command Syntax

```
bgp aggregate-nextthop-check
```

---

## Configure enable path select

Use this attribute to set RFC 1771 compatible path selection

Attribute Name: enable-path-select

Attribute Type: empty

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
  <config>
    </enable-path-select><!-- operation="delete"-->
  </config>
</global>
</bgp>
```

## Command Syntax

```
bgp rfc1771-path-select
```

---

## Configure disable adj out

Use this attribute to Disable BGP ADJ\_OUT.

Attribute Name: disable-adj-out

Attribute Type: empty

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
  <config>
    </disable-adj-out><!-- operation="delete"-->
  </config>
</global>
</bgp>
```

## Command Syntax

```
bgp disable-adj-out
```

---

## Configure disable rfc7606 error handling

Use this attribute to Disable RFC7606 revised error handling.

Attribute Name: disable-rfc7606-error-handling

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
    <config>
      </disable-rfc7606-error-handling><!-- operation="delete"-->
    </config>
  </global>
</bgp>
```

### Command Syntax

```
bgp disable-rfc7606-error-handling
```

---

## Configure enable bogon filtering

Use this attribute to enable BOGON filtering

Attribute Name: enable-bogon-filtering

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
    <config>
      </enable-bogon-filtering><!-- operation="delete"-->
    </config>
  </global>
</bgp>
```

### Command Syntax

```
bgp enable-bogon-filtering
```

---

## Configure enable extended asn capability

Use this attribute to configure a BGP router to send 4-octet ASN capabilities. If attempting to change the AS capability from 2 to 4 or 4 to 2, a prompt occurs to remove the VRF configuration (if it exists), and reconfiguration is required, because the route distinguisher (RD) configuration would have been created with the current (2 octet or 4 octet) capability, and must be reconfigured before attempting to change the capability. While loading from a saved configuration with AS4 capability and BGP VRF configuration, the capability will not be changed because of the above described reason.

Attribute Name: enable-extended-asn-capability

Attribute Type: empty

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
  <config>
    </enable-extended-asn-capability><!-- operation="delete"-->
  </config>
</global>
</bgp>
```

## Command Syntax

```
bgp extended-asn-cap
```

---

## Configure enable nexthop tracking

Use this attribute to enable nexthop address tracking. Nexthop address tracking is an event-driven notification system that monitors the status of routes installed in the Routing Information Base (RIB) and reports nexthop changes that affect internal BGP (iBGP) or external BGP (eBGP) prefixes directly to the BGP process. This improves the overall BGP convergence time, by allowing BGP to respond rapidly to nexthop changes for routes installed in the RIB. If nexthop tracking is enabled after certain routes are learned, the registration of all nexthops for selected BGP routes is done after the nexthop tracking feature is enabled. If nexthop tracking is disabled, and if there are still some selected BGP routes, BGP de-registers the nexthops of all selected BGP routes from NSM.

Attribute Name: enable-nexthop-tracking

Attribute Type: empty

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
  <config>
    </enable-nexthop-tracking><!-- operation="delete"-->
  </config>
</global>
</bgp>
```

## Command Syntax

```
bgp nexthop-trigger enable
```

---

## Configure nexthop tracking delay

Use this attribute to set the delay time for nexthop address tracking. This attribute configures the delay interval between routing table walks for nexthop delay tracking, after which BGP does a routing table scan on receiving a nexthop change trigger from NSM. The time period determines how long BGP waits before it walks the full BGP table to determine which prefixes are affected by the nexthop changes, after it receives the trigger from NSM about one or more nexthop changes.

Attribute Name: nexthop-tracking-delay

Attribute Type: uint8

Default Value: 5

Attribute Range: 1-100

---

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
  <config>
    <nexthop-tracking-delay>1</nexthop-tracking-delay> <!-- operation="delete"-->
  </config>
</global>
</bgp>
```

## Command Syntax

```
bgp nexthop-trigger delay <1-100>
```

---

## Configure enable rfc 1771 strict origin

Use this attribute to set the origin path attribute to IGP when the origin is a protocol such as RIP, OSPF, or ISIS as specified in RFC 1771. Otherwise, the origin is always set to incomplete which is the industry standard.

Attribute Name: enable-rfc-1771-strict-origin

Attribute Type: empty

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
  <config>
    </enable-rfc-1771-strict-origin><!-- operation="delete"-->
  </config>
</global>
</bgp>
```

## Command Syntax

```
bgp rfc1771-strict
```

---

## Configure options

Use this attribute to enable all BGP troubleshooting functions. Use this attribute without any parameters to turn on normal bgp debug information.

Attribute Name: options

Attribute Type: bits (all|nht|nsm|fsm|events|filters|keepalives|updates in|updates out|dampening|bfd|rib|normal|add-path|adj-out|route-scan|packet-send|packet-received)

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <global>
  <debug>
  <config>
    <options>all</options> <!-- operation="delete"-->
  </config>
</debug>
</global>
```

---

```
</bgp>
```

## Command Syntax

```
debug bgp (all|nht|nsm|fsm|events|filters|keepalives|updates in|updates
out|dampening|bfd|rib|normal|add-path|adj-out|route-scan|packet-send|packet-
received)
```

---

## restart bgp graceful

### Netconf RPC payload

```
<bgp-graceful-restart xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp"/>
```

### Command Syntax

```
restart bgp graceful
```

---

## clear bgp statistics

### Netconf RPC payload

```
<clear-bgp-statistics xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp"/>
```

### Command Syntax

```
clear bgp statistics
```

---

## snmp restart bgp

### Netconf RPC payload

```
<bgp-snmp-restart xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp"/>
```

### Command Syntax

```
snmp restart bgp
```

---

## debug bgp (all|nht|nsm|fsm|events|filters|keepalives|updates in|updates out|dampening|bfd|rib|normal|add-path|adj-out|route-scan|packet-send|packet-received)

Attribute Name: terminal-debug-options

Attribute Type: bits (all|nht|nsm|fsm|events|filters|keepalives|updates in|updates out|dampening|bfd|rib|normal|add-path|adj-out|route-scan|packet-send|packet-received)

### Netconf RPC payload

```
<bgp-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<terminal-debug-options>all</terminal-debug-options>
</bgp-debug-on>
```

---

## Command Syntax

```
debug bgp (all|nht|nsm|fsm|events|filters|keepalives|updates in|updates
out|dampening|bfd|rib|normal|add-path|adj-out|route-scan|packet-send|packet-
received)
```

---

## no debug bgp (all|nht|nsm|fsm|events|filters|keepalives|updates in|updates out|dampening|bfd|rib|normal|add-path|adj-out|route-scan|packet-send|packet-received)

Attribute Name: terminal-debug-options

Attribute Type: bits (all|nht|nsm|fsm|events|filters|keepalives|updates in|updates out|dampening|bfd|rib|normal|add-path|adj-out|route-scan|packet-send|packet-received)

### Netconf RPC payload

```
<bgp-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<terminal-debug-options>all</terminal-debug-options>
</bgp-debug-off>
```

## Command Syntax

```
no debug bgp (all|nht|nsm|fsm|events|filters|keepalives|updates in|updates
out|dampening|bfd|rib|normal|add-path|adj-out|route-scan|packet-send|packet-
received)
```

---

## no debug all bgp

### Netconf RPC payload

```
<bgp-all-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp"/>
```

## Command Syntax

```
no debug all bgp
```

---

# IPI-BGP-INSTANCE

---

## Configure no external fail over

Use this attribute to reset a BGP session immediately, if the interface used for BGP connection goes down.

Attribute Name: no-external-fail-over

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
<bgp-instance>
  <bgp-as>1</bgp-as>
</config>
```

```

    <bgp-as>1</bgp-as>
  </config>
  </no-external-fail-over><!-- operation="delete"-->
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
no bgp fast-external-failover
```

---

## Configure no best path tie break

Use this attribute to always select a preferred older route even when the `bestpathCompareRouterId` attribute is configured

Attribute Name: `no-best-path-tie-break`

Attribute Type: `uint8`

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      </no-best-path-tie-break><!-- operation="delete"-->
    </bgp-instance>
  </bgp-instances>
</bgp>

```

### Command Syntax

```
no bgp bestpath tie-break-on-age
```

---

## Configure inbound route filter disable

Use this attribute to enable the MPLS (Multiprotocol Label Switching) VPN/BGP inbound route filter. This attribute is used to control the installation of routing information into the BGP table. When a router runs MPLS VPN/BGP PE, it exchanges routing information with a routing distinguisher. By default, routing information that does not match the configured routing distinguisher value is not installed. When the local box has two VRFs where each routing distinguisher value is 10:100 and 20:200, routing information with routing distinguisher 10:200 is not installed into BGP table.

Attribute Name: `inbound-route-filter-disable`

Attribute Type: `uint8`

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>

```

```

    <bgp-as>1</bgp-as>
  </config>
  <bgp-as>1</bgp-as>
</config>
  </inbound-route-filter-disable><!-- operation="delete"-->
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
no bgp inbound-route-filter
```

---

## Configure external route leak disable

Use this attribute to disable external route leak.

Attribute Name: external-route-leak-disable

Attribute Type: uint8

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      </external-route-leak-disable><!-- operation="delete"-->
    </bgp-instance>
  </bgp-instances>
</bgp>

```

### Command Syntax

```
no bgp external-route-leak
```

---

## Configure no client route reflection

Use this attribute to configure routers as route reflectors. Route reflectors are used when all Interior Border Gateway Protocol (iBGP) speakers are not fully meshed. If the clients are fully meshed the route reflector is not required

Attribute Name: no-client-route-reflection

Attribute Type: uint8

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    </config>
      </no-client-route-reflection><!-- operation="delete"-->
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
no bgp client-to-client reflection
```

---

## Configure med type

Use this attribute to specify two MED (Multi Exit Discriminator) attributes, confed and missing-as-worst. The confed attribute enables MED comparison along paths learned from confederation peers. The MEDs are compared only if there is no external Autonomous System (an AS not within the confederation) in the path. If there is an external autonomous system in the path, the MED comparison is not made. The missing-as-worst to consider a missing MED attribute in a path as having a value of infinity, making the path without a MED value the least desirable path. If missing-as-worst is disabled, the missing MED is assigned the value of 0, making the path with the missing MED attribute the best path.

Attribute Name: med-type

Attribute Type: bits (confed|missing-as-worst|remove-recv-med|remove-send-med)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <med-type>3</med-type> <!-- operation="delete"-->
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
bgp bestpath med (confed) missing-as-worst
```

---

## Configure bgp as

Use this attribute to specify two MED (Multi Exit Discriminator) attributes, confed and missing-as-worst. The confed attribute enables MED comparison along paths learned from confederation peers. The MEDs are compared only if there is no external Autonomous System (an AS not within the confederation) in the path. If there is an external autonomous system in the path, the MED comparison is not made. The missing-as-worst to consider a missing MED attribute in a path as having a value of infinity, making the path without a MED value the least desirable path. If missing-as-worst is disabled, the missing MED is assigned the value of 0, making the path with the missing MED attribute the best path.

Attribute Name: med-type

Attribute Type: bits (confed|missing-as-worst|remove-recv-med|remove-send-med)

---

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <med-type>3</med-type> <!-- operation="delete"-->
</bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
bgp bestpath med (missing-as-worst) confed
```

---

## Configure bgp-instances bgp-as

Use this attribute to start a BGP process.

Attribute Name: bgp-as

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
<bgp-instance> <!-- operation="delete"-->
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
</bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
router bgp <1-4294967295>
```

---

## Configure router id

Use this attribute to manually configure a fixed router ID as a BGP router identifier. When this attribute is used to configure a fixed router ID, the current router identifier is overridden and the peers are reset.

Attribute Name: router-id

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
```

```

<bgp-instances>
<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <router-id>A.B.C.D</router-id> <!-- operation="delete"-->
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
bgp router-id A.B.C.D
```

---

## Configure cluster id

Use this attribute to configure the cluster ID if the BGP cluster has more than one route reflector. A cluster includes route reflectors and its clients. Usually, each cluster is identified by the router ID of its single route reflector but to increase redundancy sometimes a cluster may have more than one route reflector. All router reflectors in such a cluster are then identified by a cluster ID. The clusterId attribute is used to configure the 4 byte cluster ID for clusters with more than one route reflectors in an IPv4 address format.

Attribute Name: cluster-id

Attribute Type: union

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <cluster-id>BGP_CLUSTER_ID_T</cluster-id>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
bgp cluster-id (A.B.C.D|<1-4294967295>)
```

---

## Configure local preference

Use this attribute to change the default local preference value. Local preference indicates the preferred path when there are multiple paths to the same destination. The path having a higher preference is preferred. The preference is sent to all routers and access servers in the local autonomous system.

Attribute Name: local-preference

Attribute Type: uint32

Default Value: 100

Attribute Range: 0-4294967295

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <local-preference>0</local-preference> <!-- operation="delete"-->
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
bgp default local-preference <0-4294967295>
```

---

## Configure graceful shutdown capable

Use this attribute to enable the graceful shutdown capability at the router level and make available the graceful-shutdown related attributes at the router and BGP neighbor levels.

Attribute Name: graceful-shutdown-capable

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      </graceful-shutdown-capable><!-- operation="delete"-->
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
bgp g-shut-capable
```

---

## Configure graceful shutdown

Use this attribute to gracefully shut down all BGP IPv4 sessions under this router. The BGP graceful shutdown feature reduces packet loss during maintenance activity.

Attribute Name: graceful-shutdown

Attribute Type: empty

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  </graceful-shutdown><!-- operation="delete"-->
</bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
bgp g-shut
```

---

## Configure graceful shutdown local preference

Use this attribute to set the local preference of the router to use during graceful shutdown. The local preference value indicates the preferred path when there are multiple paths to the same destination in a single routing database. The path with a higher preference value is the preferred one. The preferred path is sent to all routers and access servers in the local autonomous system.

Attribute Name: graceful-shutdown-local-preference

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
    </config>
    <graceful-shutdown-local-preference>0</graceful-shutdown-local-preference>
  <!-- operation="delete"-->
</bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
bgp g-shut-local-preference <0-4294967295>
```

---

## Configure log neighbor changes

Use this attribute to enable logging of status change messages without turning on debug bgp attributes. Product has many logging services for neighbor status, including debug bgp fsm and debug bgp events. However, these attributes

cause system performance degradation. If you need to log neighbor status changes only, IP Infusion Inc. recommends turning off all debug attributes and using the `setLogNbrChanges` attribute instead.

Attribute Name: `log-neighbor-changes`

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      </log-neighbor-changes><!-- operation="delete"-->
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
bgp log-neighbor-changes
```

---

## Configure scan interval

Use this attribute to configure scanning intervals of BGP routers. This interval is the period after which router checks the validity of the routes in its database. To disable BGP scanning, set the scan-time interval to 0 seconds.

Attribute Name: `scan-interval`

Attribute Type: uint32

Default Value: 60

Attribute Range: 0-60

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
        </config>
        <scan-interval>0</scan-interval> <!-- operation="delete"-->
      </bgp-instance>
    </bgp-instances>
  </bgp>
```

### Command Syntax

```
bgp scan-time <0-60>
```

---

## Configure best path dont compare originator

Use this attribute to change the default bestpath selection by not comparing an originator-ID for an identical EBGP path

Attribute Name: best-path-dont-compare-originator

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      </best-path-dont-compare-originator><!-- operation="delete"-->
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
bgp bestpath dont-compare-originator-id
```

---

## Configure enable deterministic med

Use this attribute to compare the Multi Exit Discriminator (MED) variable when choosing among routes advertised by different peers in the same autonomous system. MED is compared after BGP attributes weight, local preference, AS-path and origin have been compared and are equal. For a correct comparison result, enable this attribute on all routers in a local AS. After enabling this attribute, all paths for the same prefix are grouped together and arranged according to their MED value. Based on this comparison, the best path is then chosen. This attribute compares MED variable when choosing routes advertised by different peers in the same AS, to compare MED, when choosing routes from neighbors in different ASs use the compareMed attribute. When the deterministicMed attribute is set, routes from the same AS are grouped together, and the best routes of each group are compared.

Attribute Name: enable-deterministic-med

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      </enable-deterministic-med><!-- operation="delete"-->
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
bgp deterministic-med
```

---

## Configure enforce first as for ebgp

Use this attribute to enforce the first AS for eBGP routes. This attribute specifies that any updates received from an external neighbor that do not have the neighbors configured Autonomous System (AS) at the beginning of the AS\_PATH in the received update must be denied. Enabling this feature adds to the security of the BGP network by not allowing traffic from unauthorized systems.

Attribute Name: enforce-first-as-for-ebgp

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      </enforce-first-as-for-ebgp><!-- operation="delete"-->
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
bgp enforce-first-as
```

---

## Configure local as count

Use this attribute to set the number of times the local-AS (Autonomous System) is to be prepended.

Attribute Name: local-as-count

Attribute Type: uint8

Attribute Range: 2-64

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
        <local-as-count>2</local-as-count> <!-- operation="delete"-->
      </config>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
bgp as-local-count <2-64>
```

---

## Configure bgp-instance med-type

Use this attribute to specify two MED (Multi Exit Discriminator) attributes, confed and missing-as-worst. The confed attribute enables MED comparison along paths learned from confederation peers. The MEDs are compared only if there is no external Autonomous System (an AS not within the confederation) in the path. If there is an external autonomous system in the path, the MED comparison is not made. The missing-as-worst to consider a missing MED attribute in a path as having a value of infinity, making the path without a MED value the least desirable path. If missing-as-worst is disabled, the missing MED is assigned the value of 0, making the path with the missing MED attribute the best path.

Attribute Name: med-type

Attribute Type: bits (confed|missing-as-worst|remove-recv-med|remove-send-med)

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <med-type>confed</med-type> <!-- operation="delete"-->
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
bgp bestpath med (confed|missing-as-worst|remove-recv-med|remove-send-med)
```

---

## Configure multi path relax

Use this attribute to relax the same AS-Path requirement so any candidate eBGP AS-Path with the same AS-path length might be used for eBGP load-balancing. This feature does not load-balance between eBGP and iBGP paths. Normally eBGP load-balancing requires the candidate routes to be equal-cost paths with identical BGP attributes having the same weight, Local-Pref, AS-Path (both the AS numbers and the AS pathlength), origin, MED, and different next-hop.

Attribute Name: multi-path-relax

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

```

    </config>
    </multi-path-relax><!-- operation="delete"-->
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
bgp bestpath as-path multipath-relax
```

---

## Configure ignore aigp for bestpath

Use this config to ignore aigp attr in BGP best-path selection algorithm.

Attribute Name: ignore-aigp-for-bestpath

Attribute Type: empty

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  </ignore-aigp-for-bestpath><!-- operation="delete"-->
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
bgp bestpath aigp ignore
```

---

## Configure identifier

Use this attribute to specify a BGP confederation identifier

Attribute Name: identifier

Attribute Type: uint32

Attribute Range: 1-4294967295

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <confederation>

```

```

    <config>
      <identifier>1</identifier> <!-- operation="delete"-->
    </config>
  </confederation>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp confederation identifier <1-4294967295>
```

---

## Configure peer as number

Use this attribute to specify peer AS number in BGP confederation

Attribute Name: peer-as-number

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
    <confederation>
      <config>
        <peer-as-number>1</peer-as-number> <!-- operation="delete"-->
      </config>
    </confederation>
  </bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp confederation peers .<1-4294967295>
```

---

## Configure enable graceful restart

Use this attribute to enable BGP graceful-restart capabilities. The restart-time parameter is used for setting the maximum time that a graceful-restart neighbor waits to come back up after a restart. This value is applied to all neighbors unless you explicitly override it by configuring the corresponding value on the neighbor. The stalepath-time parameter is used to set the maximum time to preserve stale paths from a gracefully restarted neighbor. All stalepaths, unless reinstated by the neighbor after a re-establishment, will be deleted at the expiration of this timer.

Attribute Name: enable-graceful-restart

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <graceful-restart>
  <config>
    </enable-graceful-restart><!-- operation="delete"-->
  </config>
</graceful-restart>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp graceful-restart
```

---

## Configure restart time

Use this attribute to enable BGP graceful-restart capabilities. The restart-time parameter is used for setting the maximum time that a graceful-restart neighbor waits to come back up after a restart. This value is applied to all neighbors unless you explicitly override it by configuring the corresponding value on the neighbor.

Attribute Name: restart-time

Attribute Type: uint32

Default Value: 90

Attribute Range: 1-3600

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <graceful-restart>
  <config>
    <restart-time>1</restart-time> <!-- operation="delete"-->
  </config>
</graceful-restart>
</bgp-instance>
</bgp-instances>
</bgp>

```

---

## Command Syntax

```
bgp graceful-restart restart-time <1-3600>
```

---

## Configure stale path max retention time

Use this attribute to enable BGP graceful-restart capabilities. The stalepath-time parameter is used to set the maximum time to preserve stale paths from a gracefully restarted neighbor. All stalepaths, unless reinstated by the neighbor after a re-establishment, will be deleted at the expiration of this timer.

Attribute Name: stale-path-max-retention-time

Attribute Type: uint32

Default Value: 360

Attribute Range: 1-3600

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <graceful-restart>
        <config>
          <stale-path-max-retention-time>1</stale-path-max-retention-time> <!--
operation="delete"-->
        </config>
      </graceful-restart>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
bgp graceful-restart stalepath-time <1-3600>
```

---

## Configure route selection max defer time

Use this attribute to specify the update-delay value for a graceful-restart capable router. The update-delay value is the maximum time a graceful-restart capable router, which is restarting, will defer route-selection and advertisements to all its graceful-restart capable neighbors. This maximum time starts from the instance the first neighbor attains established state after restart. The restarting router prematurely terminates this timer when end-of-rib markers are received from all its graceful-restart capable neighbors.

Attribute Name: route-selection-max-defer-time

Attribute Type: uint32

Default Value: 120

Attribute Range: 1-3600

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <graceful-restart>
  <config>
    <route-selection-max-defer-time>1</route-selection-max-defer-time> <!--
operation="delete"-->
  </config>
</graceful-restart>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp update-delay <1-3600>
```

---

## Configure graceful reset

Use this attribute to enable BGP graceful-restart capabilities. The restart-time parameter is used for setting the maximum time that a graceful-restart neighbor waits to come back up after a restart. This value is applied to all neighbors unless you explicitly override it by configuring the corresponding value on the neighbor.

Attribute Name: graceful-reset

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <graceful-restart>
  <config>
    </graceful-reset><!-- operation="delete"-->
  </config>
</graceful-restart>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp graceful-restart graceful-reset
```

---

## Configure keep alive

Use this attribute to globally set or reset the keepalive values for all the neighbors

Attribute Name: keep-alive

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: hold-time

Attribute Type: uint16

Attribute Range: 0-65535

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <timers>
        <config>
          <hold-time>0</hold-time>
          <keep-alive>0</keep-alive>
        </config>
      </timers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
timers bgp <0-65535> <0-65535>
```

---

## Configure always compare med

Use this attribute to compare the Multi Exit Discriminator (MED) for paths from neighbors in different autonomous systems. Multi Exit Discriminator (MED) is used in best path selection by BGP. MED is compared after BGP attributes weight, local preference, AS-path and origin have been compared and are equal. MED comparison is done only among paths from the same autonomous system (AS). Use compareMed attribute to allow comparison of MEDs from different ASs. The MED parameter is used to select the best path. A path with lower MED is preferred.

Attribute Name: always-compare-med

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
```

```

    <bgp-as>1</bgp-as>
  </config>
</route-selection>
<config>
  </always-compare-med><!-- operation="delete"-->
</config>
</route-selection>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
bgp always-compare-med
```

---

## Configure ignore as path length

Use this attribute to prevent the router from considering the autonomous system (AS) path length as a factor in the algorithm for choosing a best path route.

Attribute Name: ignore-as-path-length

Attribute Type: empty

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <route-selection>
        <config>
          </ignore-as-path-length><!-- operation="delete"-->
        </config>
      </route-selection>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

### Command Syntax

```
bgp bestpath as-path ignore
```

---

## Configure best path compare confed

Use this attribute to allow comparing of the confederation AS path length. This attribute specifies that the AS confederation path length must be used when available in the BGP best path decision process. It is effective only when bestpathAspath attribute has not been used.

Attribute Name: best-path-compare-confed

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <route-selection>
  <config>
    </best-path-compare-confed><!-- operation="delete"-->
  </config>
</route-selection>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp bestpath compare-confed-aspath
```

## Configure external compare router id

Use this attribute to compare router IDs for identical eBGP paths. When comparing similar routes from peers, the BGP router does not consider the router ID of the routes. By default, it selects the first received route. Use this attribute to include router ID in the selection process; similar routes are compared and the route with the lowest router ID is selected. The router IS is the highest IP address on the router, with preference given to loopback addresses. Router ID can be manually set by using the routerIpAddr attribute.

Attribute Name: external-compare-router-id

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <route-selection>
  <config>
    </external-compare-router-id><!-- operation="delete"-->
  </config>
</route-selection>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp bestpath compare-routerid
```

---

## Configure source ip prefix

Use this attribute to set the administrative distance for ip source prefix.

Attribute Name: source-ip-prefix

Attribute Type: string

Attribute Name: distance

Attribute Type: uint8

Attribute Range: 1-255

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <administrative-distances>
        <administrative-distance> <!-- operation="delete"-->
          <source-ip-prefix>A.B.C.D/M</source-ip-prefix>
          <config>
            <source-ip-prefix>A.B.C.D/M</source-ip-prefix>
            <distance>1</distance>
          </config>
        </administrative-distance>
      </administrative-distances>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
distance <1-255> A.B.C.D/M
```

---

## Configure access list name

Use this attribute to define an administrative distance along with ip source prefix and access list name.

Attribute Name: access-list-name

Attribute Type: string

Attribute Name: distance

Attribute Type: uint8

Attribute Range: 1-255

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
```

```

<bgp-as>1</bgp-as>
<config>
  <bgp-as>1</bgp-as>
</config>
<administrative-distances>
<administrative-distance>
  <source-ip-prefix>A.B.C.D/M</source-ip-prefix>
  <config>
    <source-ip-prefix>A.B.C.D/M</source-ip-prefix>
    <distance>1</distance>
  </config>
  <access-list-name>WORD</access-list-name>
</administrative-distance>
</administrative-distances>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
distance <1-255> A.B.C.D/M WORD
```

---

## IPI-BGP-ADDRESS-FAMILY

---

### Configure additional paths mode

Use this attribute to add additional paths in the BGP table

Attribute Name: additional-paths-mode

Attribute Type: bits (send-receive|receive|send)

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      <additional-paths-mode>send-receive</additional-paths-mode> <!--
operation="delete"-->

```

```
    </address-family>
  </address-families>
</bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
bgp additional-paths (send-receive|receive|send)
```

---

## Configure additional path select all

Use this attribute to select criteria to pick the paths

Attribute Name: additional-path-select-all

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
          <additional-path-select-all><!-- operation="delete"-->
        </address-family>
      </address-families>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
bgp additional-paths select all
```

---

## Configure additional paths best select count

Use this attribute to select best N paths

Attribute Name: additional-paths-best-select-count

Attribute Type: uint8

Attribute Range: 2-3

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      <additional-paths-best-select-count>2</additional-paths-best-select-
count> <!-- operation="delete"-->
    </address-family>
  </address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp additional-paths select best <2-3>
```

---

## Configure no client route reflection

Use this attribute to configure routers as route reflectors. Route reflectors are used when all Interior Border Gateway Protocol (iBGP) speakers are not fully meshed. If the clients are fully meshed the route reflector is not required.

Attribute Name: no-client-route-reflection

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>

```

```

        <afi>ipv4</afi>
        </no-client-route-reflection><!-- operation="delete"-->
    </address-family>
</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
no bgp client-to-client reflection
```

---

## Configure enable auto summary

Use this attribute to enable sending summarized routes by a BGP speaker to its peers. Auto-summary is used by a BGP router to advertise summarized routes to its peers. Auto-summary can be enabled if certain routes have already been advertised: in this case, configuring auto-summary advertises the summarized routes first, then corresponding non-summarized routes are withdrawn. If certain routes have already been advertised, and auto-summary is disabled, non-summarized routes are first advertised, then the corresponding summarized routes are withdrawn from all the connected peers.

Attribute Name: enable-auto-summary

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      </enable-auto-summary><!-- operation="delete"-->
    </address-family>
  </address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
auto-summary
```

---

## Configure enable network igp sync

Use this attribute to enable IGP synchronization for BGP static network routes

Attribute Name: enable-network-igp-sync

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
          </enable-network-igp-sync><!-- operation="delete"-->
        </address-family>
      </address-families>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
network synchronization
```

---

## Configure map name

Use this attribute to enable or disable suppression/modification of incoming BGP updates to IP RIB/FIB table installation. In a dedicated route reflector, all the routes it receives may not be required to be stored or only few selected routes need to be stored, because it may not lie in the data path. Table maps are particularly useful to attain this restriction. When map-name attribute is set, the route map referenced in the map-name attribute shall be used to set certain properties (such as the traffic index) of the routes for installation into the RIB. The route is always downloaded, regardless of whether it is permitted or denied by the route map.

Attribute Name: map-name

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
```

```

    <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
</address-families>
<address-family>
  <safi>unicast</safi>
  <config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <afi>ipv4</afi>
  <table-map>
  <config>
    <map-name>WORD</map-name>
  </config>
</table-map>
</address-family>
</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
table-map WORD
```

---

## Configure table map filter

When tableMapFilter attribute is given in the table map attribute, the route map referenced is used to control whether a BGP route is to be downloaded to the IP RIB (hence the filter). A BGP route is not downloaded to the RIB if it is denied by the route map.

Attribute Name: table-map-filter

Attribute Type: boolean

Attribute Name: map-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>

```

```

    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
  <table-map>
    <config>
      <map-name>WORD</map-name> <!-- operation="delete"-->
      <table-map-filter>true</table-map-filter> <!-- operation="delete"--
>
      </config>
    </table-map>
  </address-family>
</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
table-map WORD filter
```

---

## Configure enable igp sync

Use this attribute to enable IGP synchronization of Internal BGP (iBGP) learned routes with the Internal Gateway Protocol (IGP) system. Synchronization is used when a BGP router should not advertise routes learned from iBGP neighbors, unless those routes are also present in an IGP (for example, OSPF). Synchronization may be enabled when all the routers in an autonomous system do not speak BGP, and the autonomous system is a transit for other autonomous systems.

Attribute Name: enable-igp-sync

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
          </enable-igp-sync><!-- operation="delete"-->
        </address-family>
      </address-families>
    </bgp-instance>
  </bgp-instances>

```

```

</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

synchronization

---

## Configure backdoor

network address with backdoor for address family

Attribute Name: backdoor

Attribute Type: uint8

Attribute Name: network-rmap-name

Attribute Type: string

Default Value: NULL

Attribute Range: 1-63

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
    <network-lists>
    <network-list>
      <local-network-prefix>A.B.C.D</local-network-prefix>
      <config>
        <local-network-prefix>BGP_IP_NETWORK_T</local-network-prefix>
        <network-rmap-name>WORD</network-rmap-name>
      </config>
      </backdoor>
    </network-list>
  </network-lists>
</address-family>
</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
network (A.B.C.D | A.B.C.D/M) (route-map WORD|) (backdoor|)
```

---

## Configure bgp as

network address with backdoor for address family

Attribute Name: backdoor

Attribute Type: uint8

Attribute Name: network-rmap-name

Attribute Type: string

Default Value: NULL

Attribute Range: 1-63

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
        </address-family>
      </address-families>
      <network-lists>
        <network-list>
          <local-network-prefix>A.B.C.D</local-network-prefix>
          <config>
            <local-network-prefix>BGP_IP_NETWORK_T</local-network-prefix>
            <network-rmap-name>WORD</network-rmap-name>
          </config>
          </backdoor>
        </network-list>
      </network-lists>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
network (X:X::X:X/M) (route-map WORD|) (backdoor|)
```

---

## Configure aggregate address

Aggregates are used to minimize the size of routing tables. Aggregation combines the characteristics of several different routes and advertises a single route. The aggregate-address attribute creates an aggregate entry in the BGP routing table if any more-specific BGP routes are available in the specified range.

Attribute Name: aggregate-address

Attribute Type: union

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
          <aggregate-address-lists>
            <aggregate-address-list> <!-- operation="delete"-->
              <aggregate-address>CML_IP_PREFIX_T</aggregate-address>
              <config>
                <aggregate-address>CML_IP_PREFIX_T</aggregate-address>
              </config>
            </aggregate-address-list>
          </aggregate-address-lists>
        </address-family>
      </address-families>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
aggregate-address (A.B.C.D/M|A.B.C.D A.B.C.D|X:X::X:X/M)
```

---

## Configure aggregate type

The aggregate-type attribute creates an aggregate entry advertising the path for this route, consisting of all elements contained in all paths being summarized. Use this parameter to reduce the size of path information by listing the AS number only once, even if it was included in multiple paths that were aggregated.

Attribute Name: aggregate-type

Attribute Type: enum (as-set|summary-only|as-set-and-summary-only)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      <aggregate-address-lists>
      <aggregate-address-list>
        <aggregate-address>CML_IP_PREFIX_T</aggregate-address>
        <config>
          <aggregate-address>CML_IP_PREFIX_T</aggregate-address>
        </config>
        <aggregate-type>1</aggregate-type> <!-- operation="delete"-->
      </aggregate-address-list>
    </aggregate-address-lists>
  </address-family>
</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
aggregate-address as-set
```

## Configure afi

The `aggregate-type` attribute creates an aggregate entry advertising the path for this route, consisting of all elements contained in all paths being summarized. Use this parameter to reduce the size of path information by listing the AS number only once, even if it was included in multiple paths that were aggregated.

Attribute Name: `aggregate-type`

Attribute Type: enum (`as-set|summary-only|as-set-and-summary-only`)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>

```

```

</config>
<address-families>
<address-family>
  <safi>unicast</safi>
  <config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <afi>ipv4</afi>
<aggregate-address-lists>
<aggregate-address-list>
  <aggregate-address>CML_IP_PREFIX_T</aggregate-address>
  <config>
    <aggregate-address>CML_IP_PREFIX_T</aggregate-address>
  </config>
  <aggregate-type>2</aggregate-type> <!-- operation="delete"-->
</aggregate-address-list>
</aggregate-address-lists>
</address-family>
</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
aggregate-address summary-only
```

---

## Configure safi

The `aggregate-type` attribute creates an aggregate entry advertising the path for this route, consisting of all elements contained in all paths being summarized. Use this parameter to reduce the size of path information by listing the AS number only once, even if it was included in multiple paths that were aggregated.

Attribute Name: `aggregate-type`

Attribute Type: enum (`as-set|summary-only|as-set-and-summary-only`)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
  <address-families>
  <address-family>
    <safi>unicast</safi>
    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>

```

```

</config>
  <afi>ipv4</afi>
<aggregate-address-lists>
<aggregate-address-list>
  <aggregate-address>CML_IP_PREFIX_T</aggregate-address>
  <config>
    <aggregate-address>CML_IP_PREFIX_T</aggregate-address>
  </config>
  <aggregate-type>3</aggregate-type> <!-- operation="delete"-->
</aggregate-address-list>
</aggregate-address-lists>
</address-family>
</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
aggregate-address as-set summary-only
```

## Configure aggregate-address-list aggregate-type

The `aggregate-type` attribute creates an aggregate entry advertising the path for this route, consisting of all elements contained in all paths being summarized. Use this parameter to reduce the size of path information by listing the AS number only once, even if it was included in multiple paths that were aggregated.

Attribute Name: `aggregate-type`

Attribute Type: enum (`as-set`|`summary-only`|`as-set-and-summary-only`)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
    <aggregate-address-lists>
    <aggregate-address-list>
      <aggregate-address>CML_IP_PREFIX_T</aggregate-address>
      <config>
        <aggregate-address>CML_IP_PREFIX_T</aggregate-address>

```

```

        </config>
        <aggregate-type>3</aggregate-type> <!-- operation="delete"-->
    </aggregate-address-list>
</aggregate-address-lists>
</address-family>
</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
aggregate-address summary-only as-set
```

---

## Configure local

Use this attribute to define an administrative distance for local routes. Local routes are routes that is redistributed from another process. A distance is a rating of trustworthiness of a router. The higher the distance the lower the trust rating. If the administrative distance is changed, it could create inconsistency in the routing table and obstruct routing.

Attribute Name: local

Attribute Type: uint8

Attribute Range: 1-255

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
        </address-family>
      </address-families>
      <distances>
        <distance> <!-- operation="delete"-->
          <local>1</local>
          <config>
            <local>1</local>
            <ibgp>1</ibgp>
            <ebgp>1</ebgp>
          </config>
          <ibgp>1</ibgp>
          <ebgp>1</ebgp>
        </distance>
      </distances>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    </distances>
  </address-family>
</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
distance bgp <1-255> <1-255> <1-255>
```

---

## Configure ebgp max path

Use this attribute to set the number of equal-cost multi-path (ECMP) routes for eBGP. You can install multiple BGP paths to the same destination to balance the load on the forwarding path

Attribute Name: ebgp-max-path

Attribute Type: int32

Attribute Range: 2-64

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <afi>ipv4</afi>
          <maximum-paths>
            <config>
              <ebgp-max-path>2</ebgp-max-path> <!-- operation="delete"-->
            </config>
          </maximum-paths>
        </address-family>
      </address-families>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

### Command Syntax

```
max-paths ebgp <2-64>
```

---

## Configure maximum-paths ebgp-max-path

Use this attribute to set the number of equal-cost multi-path (ECMP) routes for eBGP. You can install multiple BGP paths to the same destination to balance the load on the forwarding path

Attribute Name: ebgp-max-path

Attribute Type: int32

Attribute Range: 2-64

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
          <maximum-paths>
            <config>
              <ebgp-max-path>2</ebgp-max-path> <!-- operation="delete"-->
            </config>
          </maximum-paths>
        </address-family>
      </address-families>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
max-paths ebgp <2-64>
```

---

## Configure ibgp max path

Use this attribute to set the number of equal-cost multi-path (ECMP) routes for iBGP. You can install multiple BGP paths to the same destination to balance the load on the forwarding path.

Attribute Name: ibgp-max-path

Attribute Type: int32

Attribute Range: 2-64

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
        <afi>ipv4</afi>
      <maximum-paths>
      <config>
        <ibgp-max-path>2</ibgp-max-path> <!-- operation="delete"-->
      </config>
    </maximum-paths>
    </address-family>
  </address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

**Command Syntax**

```
max-paths ibgp <2-64>
```

**Configure maximum-paths ibgp-max-path**

Use this attribute to set the number of equal-cost multi-path (ECMP) routes for iBGP. You can install multiple BGP paths to the same destination to balance the load on the forwarding path.

Attribute Name: ibgp-max-path

Attribute Type: int32

Attribute Range: 2-64

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>

```

```

    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
    <maximum-paths>
    <config>
      <ibgp-max-path>2</ibgp-max-path> <!-- operation="delete"-->
    </config>
  </maximum-paths>
</address-family>
</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
max-paths ibgp <2-64>
```

---

## Configure eibgp max path

Use this attribute to set the number of equal-cost multi-path (ECMP) routes for eiBGP. You can install multiple BGP paths to the same destination to balance the load on the forwarding path

Attribute Name: eibgp-max-path

Attribute Type: int32

Attribute Range: 2-64

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
          <maximum-paths>
            <config>
              <eibgp-max-path>2</eibgp-max-path> <!-- operation="delete"-->
            </config>
          </maximum-paths>
        </address-family>
      </address-families>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
max-paths eibgp <2-64>
```

---

## Configure enable dampening

This attribute enable BGP route dampening and set various parameters to default values.

Attribute Name: enable-dampening

Attribute Type: enum (enable-dampening)

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      <route-flap-dampenings>
      <route-flap-dampening> <!-- operation="delete"-->
        <enable-dampening>enable-dampening</enable-dampening>
        <config>
          <enable-dampening>enable-dampening</enable-dampening>
        </config>
      </route-flap-dampening>
    </route-flap-dampenings>
    </address-family>
  </address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp dampening
```

---

## Configure route-flap-dampenings enable-dampening

This attribute enable BGP route dampening and set various parameters to default values.

Attribute Name: enable-dampening

Attribute Type: enum (enable-dampening)

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
          <route-flap-dampenings>
            <route-flap-dampening> <!-- operation="delete"-->
              <enable-dampening>enable-dampening</enable-dampening>
            <config>
              <enable-dampening>enable-dampening</enable-dampening>
            </config>
          </route-flap-dampening>
        </route-flap-dampenings>
      </address-family>
    </address-families>
  </bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
bgp dampening
```

---

## Configure reach half life

Use this attribute to configure reachability half-life time for the penalty in minutes for the bgp route dampening. The time for the penalty to decrease to one-half of its current value.

Attribute Name: reach-half-life

Attribute Type: uint32

Default Value: 15

Attribute Range: 1-45

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      <route-flap-dampenings>
      <route-flap-dampening>
        <enable-dampening>enable-dampening</enable-dampening>
        <config>
          <enable-dampening>enable-dampening</enable-dampening>
        </config>
        <reach-half-life>1</reach-half-life> <!-- operation="delete"-->
      </route-flap-dampening>
    </route-flap-dampenings>
  </address-family>
</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

**Command Syntax**

```
bgp dampening <1-45>
```

**Configure route-flap-dampening reach-half-life**

Use this attribute to configure reachability half-life time for the penalty in minutes for the bgp route dampening. The time for the penalty to decrease to one-half of its current value.

Attribute Name: reach-half-life

Attribute Type: uint32

Default Value: 15

Attribute Range: 1-45

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>

```

```

<config>
  <bgp-as>1</bgp-as>
</config>
<address-families>
<address-family>
  <safi>unicast</safi>
  <config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <afi>ipv4</afi>
  <route-flap-dampenings>
  <route-flap-dampening>
    <enable-dampening>enable-dampening</enable-dampening>
    <config>
      <enable-dampening>enable-dampening</enable-dampening>
    </config>
    <reach-half-life>1</reach-half-life> <!-- operation="delete"-->
  </route-flap-dampening>
</route-flap-dampenings>
</address-family>
</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp dampening <1-45>
```

---

## Configure max suppress time

Use this attribute to configure the value to start suppressing a route for BGP route dampening. When the penalty for a route exceeds the suppress value, the route is suppressed

Attribute Name: max-suppress-time

Attribute Type: uint32

Attribute Range: 1-255

Attribute Name: reach-half-life

Attribute Type: uint32

Attribute Range: 1-45

Attribute Name: reuse-penalty

Attribute Type: uint32

Attribute Range: 1-20000

Attribute Name: suppress-penalty

Attribute Type: uint32

Attribute Range: 1-20000

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      <route-flap-dampenings>
      <route-flap-dampening>
        <enable-dampening>enable-dampening</enable-dampening>
        <config>
          <enable-dampening>enable-dampening</enable-dampening>
          <reach-half-life>1</reach-half-life> <!-- operation="delete"-->
          <reuse-penalty>1</reuse-penalty> <!-- operation="delete"-->
          <suppress-penalty>1</suppress-penalty> <!-- operation="delete"-->
        </config>
        <max-suppress-time>1</max-suppress-time> <!-- operation="delete"-->
      </route-flap-dampening>
    </route-flap-dampenings>
    </address-family>
  </address-families>
</bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
bgp dampening <1-45> <1-20000> <1-20000> <1-255>
```

---

## Configure reuse penalty

Use this attribute to configure the value to start suppressing a route for BGP route dampening. When the penalty for a route exceeds the suppress value, the route is suppressed

Attribute Name: max-suppress-time

Attribute Type: uint32

Attribute Range: 1-255

Attribute Name: reach-half-life

Attribute Type: uint32

Attribute Range: 1-45

Attribute Name: reuse-penalty

Attribute Type: uint32

Attribute Range: 1-20000

Attribute Name: suppress-penalty

Attribute Type: uint32

Attribute Range: 1-20000

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
          <route-flap-dampenings>
            <route-flap-dampening>
              <enable-dampening>enable-dampening</enable-dampening>
              <config>
                <enable-dampening>enable-dampening</enable-dampening>
                <reach-half-life>1</reach-half-life> <!-- operation="delete"-->
                <reuse-penalty>1</reuse-penalty> <!-- operation="delete"-->
                <suppress-penalty>1</suppress-penalty> <!-- operation="delete"-->
              </config>
              <max-suppress-time>1</max-suppress-time> <!-- operation="delete"-->
            </route-flap-dampening>
          </route-flap-dampenings>
        </address-family>
      </address-families>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
bgp dampening <1-45> <1-20000> <1-20000> <1-255>
```

## Configure unreachable half life

Use this attribute to configure un-reachability half-life time for the penalty in minutes for bgp route dampening. The dampening information is purged from the router once the penalty becomes less than half of the reuse limit.

Attribute Name: unreachable-half-life

Attribute Type: uint32

Attribute Range: 1-45

Attribute Name: reach-half-life

Attribute Type: uint32

Attribute Range: 1-45

Attribute Name: reuse-penalty

Attribute Type: uint32

Attribute Range: 1-20000

Attribute Name: suppress-penalty

Attribute Type: uint32

Attribute Range: 1-20000

Attribute Name: max-suppress-time

Attribute Type: uint32

Attribute Range: 1-255

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
        </address-family>
      </address-families>
      <route-flap-dampenings>
        <route-flap-dampening>
          <enable-dampening>enable-dampening</enable-dampening>
          <config>
            <enable-dampening>enable-dampening</enable-dampening>
            <reach-half-life>1</reach-half-life> <!-- operation="delete"-->
            <reuse-penalty>1</reuse-penalty> <!-- operation="delete"-->
            <suppress-penalty>1</suppress-penalty> <!-- operation="delete"-->
            <max-suppress-time>1</max-suppress-time> <!-- operation="delete"-->
          </config>
          <unreach-half-life>1</unreach-half-life> <!-- operation="delete"-->
        </route-flap-dampening>
      </route-flap-dampenings>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

```

    </address-family>
  </address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp dampening <1-45> <1-20000> <1-20000> <1-255> <1-45>
```

---

## Configure suppress penalty

Use this attribute to configure un-reachability half-life time for the penalty in minutes for bgp route dampening. The dampening information is purged from the router once the penalty becomes less than half of the reuse limit.

Attribute Name: unreach-half-life

Attribute Type: uint32

Attribute Range: 1-45

Attribute Name: reach-half-life

Attribute Type: uint32

Attribute Range: 1-45

Attribute Name: reuse-penalty

Attribute Type: uint32

Attribute Range: 1-20000

Attribute Name: suppress-penalty

Attribute Type: uint32

Attribute Range: 1-20000

Attribute Name: max-suppress-time

Attribute Type: uint32

Attribute Range: 1-255

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
        </address-family>
      </address-families>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    <afi>ipv4</afi>
  <route-flap-dampenings>
  <route-flap-dampening>
    <enable-dampening>enable-dampening</enable-dampening>
    <config>
      <enable-dampening>enable-dampening</enable-dampening>
      <reach-half-life>1</reach-half-life> <!-- operation="delete"-->
      <reuse-penalty>1</reuse-penalty> <!-- operation="delete"-->
      <suppress-penalty>1</suppress-penalty> <!-- operation="delete"-->
      <max-suppress-time>1</max-suppress-time> <!-- operation="delete"-->
    </config>
    <unreach-half-life>1</unreach-half-life> <!-- operation="delete"-->
  </route-flap-dampening>
</route-flap-dampenings>
</address-family>
</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp dampening <1-45> <1-20000> <1-20000> <1-255> <1-45>
```

## Configure dampening rmap name

Use this attribute to configure route map to specify criteria for dampening.

Attribute Name: dampening-rmap-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
        </address-family>
      </address-families>
      <route-flap-dampenings>
        <route-flap-dampening>
          <enable-dampening>enable-dampening</enable-dampening>
        </route-flap-dampening>
      </route-flap-dampenings>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    <config>
      <enable-dampening>enable-dampening</enable-dampening>
    </config>
    <dampening-rmap-name>WORD</dampening-rmap-name> <!--
operation="delete"-->
    </route-flap-dampening>
  </route-flap-dampenings>
</address-family>
</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp dampening route-map WORD
```

---

## Configure route-flap-dampening dampening-rmap-name

Use this attribute to configure route map to specify criteria for dampening.

Attribute Name: dampening-rmap-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
          <route-flap-dampenings>
            <route-flap-dampening>
              <enable-dampening>enable-dampening</enable-dampening>
            <config>
              <enable-dampening>enable-dampening</enable-dampening>
            </config>
            <dampening-rmap-name>WORD</dampening-rmap-name> <!--
operation="delete"-->
          </route-flap-dampening>
        </route-flap-dampenings>
      </address-family>
    </address-families>
  </bgp-instance>
</bgp-instances>

```

```

    </address-family>
  </address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp dampening route-map WORD
```

---

## Configure protocol type

Use this attribute to inject routes from one routing process into another. Redistribution is used by routing protocols to advertise routes that are learned by some other means, such as by another routing protocol or by static routes. Since all internal routes are dumped into BGP, careful filtering is applied to make sure that only routes to be advertised reach the internet, not everything. This attribute allows redistribution by injecting prefixes from one routing protocol into another routing protocol.

Attribute Name: protocol-type

Attribute Type: enum (kernel|connected|static|rip|ospf|isis|connected-host-routes)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
          <route-redistribute-lists>
            <route-redistribute-list> <!-- operation="delete"-->
              <protocol-type>kernel</protocol-type>
              <config>
                <protocol-type>kernel</protocol-type>
              </config>
            </route-redistribute-list>
          </route-redistribute-lists>
        </address-family>
      </address-families>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
redistribute (kernel|connected|static|rip|ospf|isis|connected-host-routes)
```

---

## Configure redist route map name

Use this attribute to configure route map to be used for redistributed routes.

Attribute Name: redist-route-map-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
          <route-redistribute-lists>
            <route-redistribute-list>
              <protocol-type>kernel</protocol-type>
              <config>
                <protocol-type>kernel</protocol-type>
              </config>
              <redist-route-map-name>WORD</redist-route-map-name> <!--
operation="delete"-->
            </route-redistribute-list>
          </route-redistribute-lists>
        </address-family>
      </address-families>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
redistribute (kernel|connected|static|rip|ospf|isis|connected-host-routes) route-
map WORD
```

---

## Configure route-redistribute-list redist-route-map-name

Use this attribute to configure route map to be used for redistributed routes.

Attribute Name: redist-route-map-name

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <afi>ipv4</afi>
          <route-redistribute-lists>
            <route-redistribute-list>
              <protocol-type>kernel</protocol-type>
              <config>
                <protocol-type>kernel</protocol-type>
              </config>
              <redist-route-map-name>WORD</redist-route-map-name> <!--
operation="delete"-->
            </route-redistribute-list>
          </route-redistribute-lists>
        </address-family>
      </address-families>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
redistribute (kernel|connected|static|rip|ospf|isis|connected-host-routes) route-
map WORD
```

---

## Configure afi

Use this attribute to start a BGP process.

Attribute Name: bgp-as

Attribute Type: uint32

Attribute Name: afi

Attribute Type: enum (ipv4|ipv6|vpn4|vpn6|rtfilter|2vpn|link-state)

Attribute Name: safi

Attribute Type: enum (unicast|multicast|labeled-unicast|2vpn-vpls|evpn|link-state|vpn-unicast|rtfilter-unicast|flowspec|flowspec-mpls-vpn)

Attribute Name: ospf-instance-number

Attribute Type: union

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance> <!-- operation="delete"-->
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-families>
        <address-family>
          <afi>ipv4</afi>
          <safi>unicast</safi>
          <bgp-redistributes-ospf>
            <bgp-redistribute-ospf>
              <ospf-instance-number>""</ospf-instance-number>
            </bgp-redistribute-ospf>
          </bgp-redistributes-ospf>
        </address-family>
      </address-families>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
redistribute (ospf) (WORD|<1-65535>)
```

---

## Configure redistribute ospf route map

Use this attribute to specify route map to redistribute routes from OSPF into BGP.

Attribute Name: redistribute-ospf-route-map

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
```

```

    <bgp-as>1</bgp-as>
  </config>
  <address-families>
  <address-family>
    <safi>unicast</safi>
    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
    <bgp-redistributes-ospf>
    <bgp-redistribute-ospf>
      <ospf-instance-number>""</ospf-instance-number>
      <config>
        <ospf-instance-number>""</ospf-instance-number>
      </config>
      <redistribute-ospf-route-map>WORD</redistribute-ospf-route-map> <!--
- operation="delete"-->
    </bgp-redistribute-ospf>
  </bgp-redistributes-ospf>
</address-family>
</address-families>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
redistribute (ospf) route-map WORD
```

## clear ip bgp (A.B.C.D|X:X::X:X|WORD) (description LINE|)

Attribute Name: arg

Attribute Type: union

Attribute Name: peer-reset-description

Attribute Type: string

Attribute Range: 1-255

### Netconf RPC payload

```

<ipi-bgp-address-family_clear-ip-bgp-peer xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <arg>A.B.C.D|X:X::X:X</arg>
  <peer-reset-description>1</peer-reset-description>
</ipi-bgp-address-family_clear-ip-bgp-peer>

```

### Command Syntax

```
clear ip bgp (A.B.C.D|X:X::X:X|WORD) (description LINE|)
```

---

## IPI-BGP-PEER-GROUP

---

### Configure optional as

Use this attribute to specify optional AS number of BGP dynamic peer-group

Attribute Name: optional-as

Attribute Type: uint32

Attribute Range: 1-4294967295

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <optional-as-lists>
            <optional-as-list> <!-- operation="delete"-->
              <optional-as>1</optional-as>
              <config>
                <optional-as>1</optional-as>
              </config>
            </optional-as-list>
          </optional-as-lists>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD optional-as <1-4294967295>
```

---

### Configure peer group tag

Creates a peer-group group. Neighbors with the same update policies are grouped into peer-group groups. This facilitates the updates of various policies, such as distribute and filter lists. The peer-group group is then configured easily with any of the neighbor attributes. Any changes made to the peer-group group affect all members.

Attribute Name: peer-group-tag

Attribute Type: string

Attribute Name: peer-group-range

Attribute Type: union

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group> <!-- operation="delete"-->
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
            <peer-group-range>0</peer-group-range>
          </config>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD peer-group
```

---

## Configure bgp as

Creates a peer-group group. Neighbors with the same update policies are grouped into peer-group groups. This facilitates the updates of various policies, such as distribute and filter lists. The peer-group group is then configured easily with any of the neighbor attributes. Any changes made to the peer-group group affect all members.

Attribute Name: peer-group-tag

Attribute Type: string

Attribute Name: peer-group-range

Attribute Type: union

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group> <!-- operation="delete"-->
```

```

    <peer-group-tag>WORD</peer-group-tag>
  <config>
    <peer-group-tag>WORD</peer-group-tag>
    <peer-group-range>A.B.C.D/M</peer-group-range>
  </config>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD peer-group range A.B.C.D/M
```

---

## Configure peer group range

Creates a peer-group group. Neighbors with the same update policies are grouped into peer-group groups. This facilitates the updates of various policies, such as distribute and filter lists. The peer-group group is then configured easily with any of the neighbor attributes. Any changes made to the peer-group group affect all members.

Attribute Name: peer-group-tag

Attribute Type: string

Attribute Name: peer-group-range

Attribute Type: union

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group <!-- operation="delete" -->
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
            <peer-group-range>X:X::X:X/M</peer-group-range>
          </config>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD peer-group range X:X::X:X/M
```

---

## Configure group limit

This attribute specifies maximum number of peer-groups in a dynamic peer-group

Attribute Name: group-limit

Attribute Type: uint8

Attribute Range: 1-200

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <group-limit>1</group-limit> <!-- operation="delete"-->
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD limit <1-200>
```

---

## Configure enable peer bfd

Enable bidirectional forwarding detection (BFD) for the BGP peer-group

Attribute Name: enable-peer-bfd

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
```

```

    <config>
      <peer-group-tag>WORD</peer-group-tag>
    </config>
  </enable-peer-bfd><!-- operation="delete"-->
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD fall-over bfd
```

---

## Configure enable peer bfd multihop

Enable bidirectional forwarding detection (BFD) for the BGP peer-group with multihop

Attribute Name: enable-peer-bfd-multihop

Attribute Type: uint8

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          </enable-peer-bfd-multihop><!-- operation="delete"-->
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD fall-over bfd multihop
```

---

## Configure auth key encrypt

Use this attribute to configure the authentication key to specify if the password is to be encrypted or not.

Attribute Name: auth-key-encrypt

Attribute Type: enum (0|1)

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <bgp-passwords>
      <bgp-password>
        <password>WORD</password>
        <config>
          <password>WORD</password>
        </config>
        <auth-key-encrypt>1</auth-key-encrypt>
      </bgp-password>
    </bgp-passwords>
    </peer-group>
  </peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

**Command Syntax**

```
neighbor WORD authentication-key (0|1) WORD
```

**Configure password**

Use this attribute to configure the authentication key to specify if the password is to be encrypted or not.

Attribute Name: auth-key-encrypt

Attribute Type: enum (0|1)

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>

```

```

    <config>
      <peer-group-tag>WORD</peer-group-tag>
    </config>
  <bgp-passwords>
    <bgp-password>
      <password>WORD</password>
      <config>
        <password>WORD</password>
      </config>
      <auth-key-encrypt>2</auth-key-encrypt>
    </bgp-password>
  </bgp-passwords>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD authentication-key WORD
```

---

## Configure additional paths mode

Adds additional paths in the BGP table

Attribute Name: additional-paths-mode

Attribute Type: bits (send-receive|receive|send|disable)

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
            </address-family>
          </address-families>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        <additional-paths-mode>send-receive</additional-paths-mode> <!--
operation="delete"-->
        </address-family>
    </address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD additional-paths (send-receive|receive|send|disable)
```

---

## Configure additional path select all

Attribute to select advertise additional path

Attribute Name: additional-path-select-all

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
          <afi>ipv4</afi>
        </additional-path-select-all><!-- operation="delete"-->
      </address-family>
    </address-families>
    </peer-group>
  </peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD advertise additional-paths all
```

---

## Configure additional paths best select count

Attribute to select best advertise additional path

Attribute Name: additional-paths-best-select-count

Attribute Type: uint8

Attribute Range: 2-3

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              <additional-paths-best-select-count>2</additional-paths-best-
select-count> <!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD advertise additional-paths best <2-3>
```

---

## Configure activate

Activate/Deactivate neighbor. This attribute enables or disables the exchange of AF information with a neighboring router.

Attribute Name: activate

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              </activate><!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD activate
```

---

## Configure afi

Activate/Deactivate neighbor. This attribute enables or disables the exchange of AF information with a neighboring router.

Attribute Name: activate

Attribute Type: uint8

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
        </activate><!-- operation="delete"-->
      </address-family>
    </address-families>
  </peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

**Command Syntax**

```
neighbor WORD activate
```

**Configure safi**

Activate/Deactivate neighbor. This attribute enables or disables the exchange of AF information with a neighboring router.

Attribute Name: activate

Attribute Type: uint8

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>

```

```

<peer-groups>
<peer-group>
  <peer-group-tag>WORD</peer-group-tag>
  <config>
    <peer-group-tag>WORD</peer-group-tag>
  </config>
  <address-families>
  <address-family>
    <safi>unicast</safi>
    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
    </activate><!-- operation="delete"-->
  </address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD activate
```

---

## Configure default peer route map name

This attribute allows a BGP local router to send the default route 0.0.0.0 to a neighbor for use as a default route for specified address-family.

Attribute Name: default-peer-route-map-name

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
    <address-families>
    <address-family>

```

```

        <safi>unicast</safi>
    </config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
</config>
    <afi>ipv4</afi>
    </default-peer-route-map-name><!-- operation="delete"-->
</address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD default-originate
```

---

## Configure peer route map orig name

This attribute configures route map to be used for a BGP local router to send the default route 0.0.0.0 to a neighbor for use as a default route for specified address-family. This attribute can be used with standard or extended access lists.

Attribute Name: peer-route-map-orig-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
            </address-family>
          </address-families>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        <peer-route-map-orig-name>WORD</peer-route-map-orig-name> <!--
operation="delete"-->
        </address-family>
    </address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD default-originate route-map WORD
```

---

## Configure weight

This attribute specifies a weight value, for specified address-family, to all routes learned from a neighbor for specified address-family. The route with the highest weight gets preference when the same prefix is learned from more than one peer. Unlike the local-preference attribute, the weight attribute is relevant only to the local router. When the weight is set for a peer group, all members of the peer group get the same weight. This attribute can also be used to assign a different weight to an individual peer-group member. When an individually-configured weight of a peer-group member is removed, its weight is reset to its peer groups weight.

Attribute Name: weight

Attribute Type: uint16

Default Value: 0

Attribute Range: 0-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
        <weight>0</weight> <!-- operation="delete"-->

```

```

        </address-family>
    </address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD weight <0-65535>
```

---

## Configure route server client

This attribute configures a neighbor as the route server client for specified address-family.

Attribute Name: route-server-client

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              </route-server-client><!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD route-server-client
```

---

## Configure next hop self

This attribute configure the router as the next hop for a BGP-speaking neighbor or peer-group group. This attribute allows a BGP router to change the nexthop information that is sent to the iBGP peer-group. The nexthop information is set to the IP address of the interface used to communicate with the neighbor.

Attribute Name: next-hop-self

Attribute Type: uint8

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
                </next-hop-self><!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD next-hop-self
```

---

## Configure peer route reflector

This attribute configures the router as a BGP route reflector and configure the specified neighbor as its client for specified address-family. Route reflectors are a solution for the explosion of iBGP peering within an autonomous

system. By route reflection the number of iBGP peers within an AS is reduced. Use this attribute to configure the local router as the route reflector and specify neighbors as its client. An AS can have more than one route reflector. One route reflector treats the other route reflector as another iBGP speaker.

Attribute Name: peer-route-reflector

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              </peer-route-reflector><!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD route-reflector-client
```

## Configure address-family peer-route-reflector

This attribute configures the router as a BGP route reflector and configure the specified neighbor as its client for specified address-family. Route reflectors are a solution for the explosion of iBGP peering within an autonomous system. By route reflection the number of iBGP peers within an AS is reduced. Use this attribute to configure the local router as the route reflector and specify neighbors as its client. An AS can have more than one route reflector. One route reflector treats the other route reflector as another iBGP speaker.

Attribute Name: peer-route-reflector

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
        </peer-route-reflector><!-- operation="delete"-->
      </address-family>
    </address-families>
  </peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD route-reflector-client
```

## Configure peer remove private as

This attribute removes the private Autonomous System (AS) number from outbound updates. Private AS numbers are not advertised to the Internet. This attribute is used with external BGP peers only. The router removes the AS numbers only if the update includes private AS numbers. If the update includes both private and public AS numbers, the system treats it as an error.

Attribute Name: peer-remove-private-as

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>

```

```

    <bgp-as>1</bgp-as>
  </config>
</peer-groups>
<peer-group>
  <peer-group-tag>WORD</peer-group-tag>
  <config>
    <peer-group-tag>WORD</peer-group-tag>
  </config>
</address-families>
<address-family>
  <safi>unicast</safi>
  <config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <afi>ipv4</afi>
  </peer-remove-private-as><!-- operation="delete"-->
</address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD remove-private-AS
```

---

## Configure no send community

This attribute specifies if a community attribute should be sent to a BGP neighbor for specified address-family. The community attribute groups destinations in a certain community and applies routing decisions according to those communities. By default, both standard and extended community attributes are sent to a neighbor

Attribute Name: no-send-community

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    </config>
  <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      </no-send-community><!-- operation="delete"-->
    </address-family>
  </address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
no neighbor WORD send-community
```

---

## Configure no send community type

This attribute specifies the type of community attribute to be sent to a BGP neighbor.

Attribute Name: no-send-community-type

Attribute Type: bits (both|standard|extended|large)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
        <address-families>
          <address-family>
            <safi>unicast</safi>
            <config>
              <safi>unicast</safi>
              <afi>ipv4</afi>
            </config>
            <afi>ipv4</afi>
          </address-family>
        </address-families>
      </peer-group>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        <no-send-community-type>both</no-send-community-type> <!--
operation="delete"-->
        </address-family>
    </address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
no neighbor WORD send-community (both|standard|extended|large)
```

---

## Configure neighbor attribute unchanged

This attribute advertises unchanged BGP AS path, next hop and med to the specified neighbor.

Attribute Name: neighbor-attribute-unchanged

Attribute Type: bits (as-path|next-hop|med)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              <neighbor-attribute-unchanged>14</neighbor-attribute-unchanged> <!--
- operation="delete"-->
            </address-family>
          </address-families>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD attribute-unchanged
```

---

## Configure address-family neighbor-attribute-unchanged

This attribute advertises unchanged BGP AS path, next hop and med to the specified neighbor.

Attribute Name: neighbor-attribute-unchanged

Attribute Type: bits (as-path|next-hop|med)

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
                <neighbor-attribute-unchanged>as-path</neighbor-attribute-
unchanged> <!-- operation="delete"-->
              </address-family>
            </address-families>
          </peer-group>
        </peer-groups>
      </bgp-instance>
    </bgp-instances>
  </bgp>
```

## Command Syntax

```
neighbor WORD attribute-unchanged {as-path|next-hop|med}
```

---

## Configure orf prefix capability

This attribute enables Outbound Router Filtering (ORF), and advertise the ORF capability to its neighbors. The ORFs send and receive capabilities to lessen the number of updates exchanged between neighbors. By filtering updates, this

option minimizes generating and processing of updates. The two routers exchange updates to maintain the ORF for each router.

Attribute Name: orf-prefix-capability

Attribute Type: bits (both|receive|send)

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
                <orf-prefix-capability>both</orf-prefix-capability> <!--
operation="delete"-->
              </address-family>
            </address-families>
          </peer-group>
        </peer-groups>
      </bgp-instance>
    </bgp-instances>
  </bgp>
```

### Command Syntax

```
neighbor WORD capability orf prefix-list (both|receive|send)
```

## Configure peer allow ebgp vpn

This attribute allows an eBGP neighbor to be a VPN peer. By default, BGP VPN functionality is allowed only for iBGP peers. Using the peer-allow-ebgp-vpn attribute allows the VPN connection to be established to an eBGP peer.

Attribute Name: peer-allow-ebgp-vpn

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
```

```

<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
        </peer-allow-ebgp-vpn><!-- operation="delete"-->
      </address-family>
    </address-families>
  </peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD allow-ebgp-vpn
```

---

## Configure allow as number

This attribute advertises prefixes (routes) even when the source of the prefixes is from the same Autonomous System (AS) number for specified address-family. Use this attribute in a scenario where two routers at different locations use the same Autonomous System number and are connected via an ISP. Once prefixes arrive from one branch at the ISP, they are tagged with the customers AS number. By default, when the ISP passes the prefixes to the other router, the prefixes are dropped if the other router uses the same AS number. Use this attribute to advertise the prefixes at the other side. Control the number of times an AS number is advertised by specifying a number. In a hub and spoke configuration in a VPN, a PE (Provider Edge) router advertises all prefixes containing duplicate AS numbers. Use this attribute to configure two VRFs on each PE router to receive and advertise prefixes. One of the VRFs receives prefixes with AS numbers from all PE routers and then advertises them to neighboring PE routers. The other VRF receives prefixes with AS numbers from the CE (Customer Edge) router and advertises them to all PE routers in the hub and spoke configuration.

Attribute Name: allow-as-number

Attribute Type: uint32

Default Value: 3

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
        <allow-as-number>1</allow-as-number> <!-- operation="delete"-->
      </address-family>
    </address-families>
  </peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD allowas-in <1-10>
```

## Configure address-family allow-as-number

This attribute advertises prefixes (routes) even when the source of the prefixes is from the same Autonomous System (AS) number for specified address-family. Use this attribute in a scenario where two routers at different locations use the same Autonomous System number and are connected via an ISP. Once prefixes arrive from one branch at the ISP, they are tagged with the customers AS number. By default, when the ISP passes the prefixes to the other router, the prefixes are dropped if the other router uses the same AS number. Use this attribute to advertise the prefixes at the other side. Control the number of times an AS number is advertised by specifying a number. In a hub and spoke configuration in a VPN, a PE (Provider Edge) router advertises all prefixes containing duplicate AS numbers. Use this attribute to configure two VRFs on each PE router to receive and advertise prefixes. One of the VRFs receives prefixes with AS numbers from all PE routers and then advertises them to neighboring PE routers. The other VRF receives prefixes with AS numbers from the CE (Customer Edge) router and advertises them to all PE routers in the hub and spoke configuration.

Attribute Name: allow-as-number

Attribute Type: uint32

Default Value: 3

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              <allow-as-number>1</allow-as-number> <!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD allowas-in <1-10>
```

---

## Configure capability graceful restart

This attribute configures the router to advertise the Graceful Restart Capability to the neighbors. This configuration indicates that the BGP speaker has the ability to preserve its forwarding state for the address family when BGP restarts. Use this attribute to advertise to the neighbor routers the capability of graceful restart.

Attribute Name: capability-graceful-restart

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
```

```

<config>
  <bgp-as>1</bgp-as>
</config>
<peer-groups>
<peer-group>
  <peer-group-tag>WORD</peer-group-tag>
  <config>
    <peer-group-tag>WORD</peer-group-tag>
  </config>
  <address-families>
  <address-family>
    <safi>unicast</safi>
    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
    </capability-graceful-restart><!-- operation="delete"-->
  </address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD capability graceful-restart
```

---

## Configure address-family capability-graceful-restart

This attribute configures the router to advertise the Graceful Restart Capability to the neighbors. This configuration indicates that the BGP speaker has the ability to preserve its forwarding state for the address family when BGP restarts. Use this attribute to advertise to the neighbor routers the capability of graceful restart.

Attribute Name: capability-graceful-restart

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>

```

```

        <peer-group-tag>WORD</peer-group-tag>
    </config>
<address-families>
<address-family>
    <safi>unicast</safi>
    <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
    </config>
        <afi>ipv4</afi>
        </capability-graceful-restart><!-- operation="delete"-->
    </address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD capability graceful-restart
```

## Configure address-family capability-graceful-restart

This attribute configures the router to advertise the Graceful Restart Capability to the neighbors. This configuration indicates that the BGP speaker has the ability to preserve its forwarding state for the address family when BGP restarts. Use this attribute to advertise to the neighbor routers the capability of graceful restart.

Attribute Name: capability-graceful-restart

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
    <bgp-instance>
        <bgp-as>1</bgp-as>
        <config>
            <bgp-as>1</bgp-as>
        </config>
        <peer-groups>
        <peer-group>
            <peer-group-tag>WORD</peer-group-tag>
            <config>
                <peer-group-tag>WORD</peer-group-tag>
            </config>
        <address-families>
        <address-family>
            <safi>unicast</safi>
            <config>
                <safi>unicast</safi>

```

```

        <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
    </capability-graceful-restart><!-- operation="delete"-->
</address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD capability graceful-restart
```

---

## Configure prefix count

Use this attribute to specify maximum number of prefixes that can be received from a neighbor

Attribute Name: prefix-count

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      <maximum-prefixes>
      <maximum-prefix> <!-- operation="delete"-->
        <prefix-count>1</prefix-count>
      <config>
        <prefix-count>1</prefix-count>

```

```

        </config>
      </maximum-prefix>
    </maximum-prefixes>
  </address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295>
```

---

## Configure stop update

Stop installing the routes when limit is exceeded.

Attribute Name: stop-update

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
            </address-family>
          </address-families>
          <maximum-prefixes>
            <maximum-prefix>
              <prefix-count>1</prefix-count>
              <config>
                <prefix-count>1</prefix-count>
              </config>
            </maximum-prefix>
          </maximum-prefixes>
          <stop-update>

```

```

        </maximum-prefix>
      </maximum-prefixes>
    </address-family>
  </address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295> stop-update
```

---

## Configure maximum-prefix stop-update

Stop installing the routes when limit is exceeded.

Attribute Name: stop-update

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
            </address-family>
          </address-families>
          <maximum-prefixes>
            <maximum-prefix>
              <prefix-count>1</prefix-count>
              <config>
                <prefix-count>1</prefix-count>
              </config>
            </maximum-prefix>
          </maximum-prefixes>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        </maximum-prefixes>
    </address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295> stop-update
```

---

## Configure maximum prefix warning

This attribute when enabled only give warning message when limit is exceeded. When it is not set and extra prefixes are received, the router ends the peering.

Attribute Name: maximum-prefix-warning

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
            </address-family>
          </address-families>
          <maximum-prefixes>
            <maximum-prefix>
              <prefix-count>1</prefix-count>
              <config>
                <prefix-count>1</prefix-count>
              </config>
            </maximum-prefix-warning>
          </maximum-prefix>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        </maximum-prefixes>
    </address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295> warning-only
```

---

## Configure threshold percentage

Threshold-value in percen. This attribute controls the number of prefixes that can be received from a neighbor. This attribute allows the configuration of a specified number of prefixes that a BGP router is allowed to receive from a neighbor. When the maximum-prefix-warning attribute is not set and extra prefixes are received, the router ends the peering.

Attribute Name: threshold-percentage

Attribute Type: uint8

Default Value: 75

Attribute Range: 1-100

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
            </address-family>
          </address-families>
          <maximum-prefixes>
            <maximum-prefix>
              <prefix-count>1</prefix-count>
            </maximum-prefix>
          </maximum-prefixes>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        <prefix-count>1</prefix-count>
    </config>
    <threshold-percentage>1</threshold-percentage>
</maximum-prefix>
</maximum-prefixes>
</address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295> <1-100>
```

---

## Configure warning only

Throw warning if exceeds threshold-value

Attribute Name: warning-only

Attribute Type: uint8

Attribute Name: threshold-percentage

Attribute Type: uint8

Default Value: 75

Attribute Range: 1-100

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
            </address-family>
          </address-families>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    <maximum-prefixes>
    <maximum-prefix>
      <prefix-count>1</prefix-count>
      <config>
        <prefix-count>1</prefix-count>
        <threshold-percentage>1</threshold-percentage>
      </config>
    </warning-only>
  </maximum-prefix>
</maximum-prefixes>
</address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295> <1-100> warning-only
```

---

## Configure unsuppress route map name

unsuppress map name. This attribute is used to selectively leak more-specific routes to a particular neighbor.

Attribute Name: unsuppress-route-map-name

Attribute Type: string

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
    </address-family>
    </address-families>
  </peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

```

        <unsuppress-route-map-name>WORD</unsuppress-route-map-name> <!--
operation="delete"-->
        </address-family>
    </address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD unsuppress-map WORD
```

---

## Configure access list identifier

Access List information

Attribute Name: access-list-identifier

Attribute Type: string

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
      <distribute-list-filters>
      <distribute-list-filter>
        <filter-direction>in</filter-direction>
        <config>
          <filter-direction>in</filter-direction>
        </config>
        <access-list-identifier>WORD</access-list-identifier>
      </distribute-list-filter>

```

```

        </distribute-list-filters>
    </address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD distribute-list WORD (in|out)
```

---

## Configure safi

Use this attribute to start a BGP process.

Attribute Name: bgp-as

Attribute Type: uint32

Attribute Name: afi

Attribute Type: enum (ipv4|ipv6|vpnv4|vpnv6|rtfilter|l2vpn|link-state)

Attribute Name: safi

Attribute Type: enum (unicast|multicast|labeled-unicast|l2vpn-vpls|evpn|link-state|vpn-unicast|rtfilter-unicast|flowspec|flowspec-mpls-vpn)

Attribute Name: peer-group-tag

Attribute Type: string

Attribute Range: 1-255

Attribute Name: prefix-list-name

Attribute Type: string

Attribute Name: prefix-filter-direction

Attribute Type: enum (in|out)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
<bgp-instance> <!-- operation="delete"-->
    <bgp-as>1</bgp-as>
    <config>
        <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
    <address-families>
    <address-family>
        <afi>ipv4</afi>
        <safi>unicast</safi>
        <peer-group-tag>WORD</peer-group-tag>

```

```

    <prefix-list-filters>
    <prefix-list-filter>
    <config>
        <prefix-list-name>WORD</prefix-list-name>
        <prefix-filter-direction>in</prefix-filter-direction>
    </config>
    </prefix-list-filter>
    </prefix-list-filters>
</address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD prefix-list WORD (in|out)
```

---

## Configure as access list identifier

Access-list number. This attribute sets a BGP filter. This attribute specifies an access list filter on updates based on the BGP autonomous system paths. Each filter is an access list based on regular expressions

Attribute Name: as-access-list-identifier

Attribute Type: string

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
    </address-family>
    </address-families>
  </bgp-instance>
</bgp-instances>
</bgp>

```

```

    <as-list-filter>
      <as-list-direction>in</as-list-direction>
      <config>
        <as-list-direction>in</as-list-direction>
      </config>
      <as-access-list-identifier>WORD</as-access-list-identifier>
    </as-list-filter>
  </as-list-filters>
</address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD filter-list WORD (in|out)
```

---

## Configure route map name

Use this attribute to apply a route map to incoming or outgoing routes. This attribute filters updates and modifies attributes. A route map is applied to inbound or outbound updates. Only the routes that pass the route map are sent or accepted in updates.

Attribute Name: route-map-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
        </peer-group>
      </peer-groups>
      <address-families>
        <address-family>
          <safi>unicast</safi>
          <config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
        </address-family>
      </address-families>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        <afi>ipv4</afi>
    <route-map-filters>
    <route-map-filter>
        <route-map-direction>in</route-map-direction>
        <config>
            <route-map-direction>in</route-map-direction>
        </config>
        <route-map-name>WORD</route-map-name>
    </route-map-filter>
</route-map-filters>
</address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD route-map WORD (in|out)
```

---

## Configure peer as

Autonomous system number of a neighbor. If the specified ASN matches the ASN number specified in the router bgp global configuration, the neighbor is identified as internal. If the ASN does no match, it is identified as external to the local AS.

Attribute Name: peer-as

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <peer-as>1</peer-as> <!-- operation="delete"-->
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>

```

---

```
</bgp>
```

## Command Syntax

```
neighbor WORD remote-as <1-4294967295>
```

---

## Configure graceful shut

Use this attribute to start a graceful shutdown for the BGP session of the specified BGP neighbor. The BGP session for this neighbor is shut down after the graceful shutdown timer expires. If there is no alternate path available for traffic to flow prior the actual shutdown of the BGP session, this path is made available for 60 seconds or for configured time after which the path is no longer available and traffic is dropped.

Attribute Name: graceful-shut

Attribute Type: empty

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          </graceful-shut><!-- operation="delete"-->
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD g-shut
```

---

## Configure graceful shutdown timer

Configure the value of the graceful shutdown timer. After the timer expires, the BGP session initiated for graceful shutdown is shut down.

Attribute Name: graceful-shutdown-timer

Attribute Type: uint32

Attribute Range: 10-65535

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
```

```

<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <graceful-shutdown-timer>10</graceful-shutdown-timer> <!--
operation="delete"-->
    </peer-group>
  </peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD g-shut-timer <10-65535>
```

---

## Configure peer restart time

Sets a different restart-time other than the global restart-time. This attribute takes precedence over the restart-time value specified using the grstSet attribute. The restart-time value is the maximum time that a graceful-restart neighbor waits to come back up after a restart. The default value is 120 seconds.

Attribute Name: peer-restart-time

Attribute Type: uint32

Attribute Range: 1-3600

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
      <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
          <peer-group-tag>WORD</peer-group-tag>
        </config>
        <peer-restart-time>1</peer-restart-time> <!-- operation="delete"-->
      </peer-group>
    </peer-groups>
  </bgp-instances>
</bgp>

```

```
</bgp-instance>  
</bgp-instances>  
</bgp>
```

## Command Syntax

```
neighbor WORD restart-time <1-3600>
```

---

## Configure peer description

Associates a description with a neighbor. This helps in identifying a neighbor quickly. It is useful for an ISP that has multiple neighbor relationships.

Attribute Name: peer-description

Attribute Type: string

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">  
<bgp-instances>  
  <bgp-instance>  
    <bgp-as>1</bgp-as>  
    <config>  
      <bgp-as>1</bgp-as>  
    </config>  
    <peer-groups>  
    <peer-group>  
      <peer-group-tag>WORD</peer-group-tag>  
      <config>  
        <peer-group-tag>WORD</peer-group-tag>  
        </config>  
      <peer-description>LINE</peer-description> <!-- operation="delete"-->  
    </peer-group>  
  </peer-groups>  
</bgp-instance>  
</bgp-instances>  
</bgp>
```

## Command Syntax

```
neighbor WORD description LINE
```

---

## Configure peer connect interval

This attribute sets the timers for a specific BGP neighbor. Keepalive messages are sent by a router to inform another router that the BGP connection between the two is still active. The keepalive interval is the period of time between each keepalive message sent by the router. The holdtime interval is the time the router waits to receive a keepalive message and if it does not receive a message for this period it declares the neighbor dead.

Attribute Name: peer-connect-interval

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-65535

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <peer-connect-interval>1</peer-connect-interval> <!--
operation="delete"-->
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD timers connect <1-65535>
```

---

## Configure peer as origin interval

Configures the minimum interval between the sending of AS-origination routing updates.

Attribute Name: peer-as-origin-interval

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-65535

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

```

        </config>
        <peer-as-origin-interval>1</peer-as-origin-interval> <!--
operation="delete"-->
        </peer-group>
    </peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD as-origination-interval <1-65535>
```

---

## Configure min route advertisement interval

Sets a minimum route advertisement interval between the sending of BGP routing updates. To reduce the flapping of routes to internet, a minimum advertisement interval is set, so that the BGP routing updates are sent only per interval seconds.

Attribute Name: min-route-advertisement-interval

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <min-route-advertisement-interval>0</min-route-advertisement-interval>
        <!-- operation="delete"-->
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD advertisement-interval <0-65535>
```

---

## Configure enable dynamic capability

Use this attribute to enable the dynamic capability for a specific peer-group. This attribute allows a BGP speaker to advertise or withdraw an address family capability to a peer-group in a non-disruptive manner.

Attribute Name: enable-dynamic-capability

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          </enable-dynamic-capability><!-- operation="delete"-->
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD capability dynamic
```

---

## Configure collide established

Include a neighbor already in an established state for conflict resolution when a TCP connection collision is detected.

Attribute Name: collide-established

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
```

```

    <config>
      <peer-group-tag>WORD</peer-group-tag>
    </config>
    </collide-established><!-- operation="delete"-->
  </peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD collide-established
```

---

## Configure source identifier

Allows internal BGP sessions to use any operational interface for TCP connections. This attribute can be used in conjunction with any specified interface on the router. The loopback interface is the interface that is most commonly used with this attribute. The use of loopback interface eliminates a dependency and BGP does not have to rely on the availability of a particular interface for making TCP connections.

Attribute Name: source-identifier

Attribute Type: string

Default Value: NULL

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <source-identifier>WORD</source-identifier> <!-- operation="delete"-->
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD update-source WORD
```

---

## Configure enforce multi hop

Turns on the enforcement of eBGP neighbors perform multihop.

Attribute Name: enforce-multi-hop

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          </enforce-multi-hop><!-- operation="delete"-->
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD enforce-multihop
```

---

## Configure neighbor override capability

Override a capability negotiation result and use locally configured values.

Attribute Name: neighbor-override-capability

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
```

```

        <peer-group-tag>WORD</peer-group-tag>
    </config>
    </neighbor-override-capability><!-- operation="delete"-->
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD override-capability
```

---

## Configure neighbor strict capability match

Close the BGP connection if capability value does not match the remote peer-group.

Attribute Name: neighbor-strict-capability-match

Attribute Type: empty

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          </neighbor-strict-capability-match><!-- operation="delete"-->
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD strict-capability-match
```

---

## Configure disallow infinite hold time

Disallow configuration of infinite hold-time. A hold-time of 0 seconds from the peer-group (during exchange of open messages) or the user (during configuration) will be rejected.

Attribute Name: disallow-infinite-hold-time

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      </disallow-infinite-hold-time><!-- operation="delete"-->
    </peer-group>
  </peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD disallow-infinite-holdtime
```

---

## Configure disable capability negotiation

Disable the capability negotiation. It allows compatibility with older BGP versions that have no capability parameters used in open messages between peer-groups.

Attribute Name: disable-capability-negotiation

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      </disable-capability-negotiation><!-- operation="delete"-->
    </peer-group>
  </peer-groups>
</bgp-instance>

```

```
</bgp-instances>  
</bgp>
```

## Command Syntax

```
neighbor WORD dont-capability-negotiate
```

---

## Configure neighbor passive

Sets a BGP neighbor as passive.

Attribute Name: neighbor-passive

Attribute Type: empty

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">  
<bgp-instances>  
  <bgp-instance>  
    <bgp-as>1</bgp-as>  
    <config>  
      <bgp-as>1</bgp-as>  
    </config>  
    <peer-groups>  
    <peer-group>  
      <peer-group-tag>WORD</peer-group-tag>  
      <config>  
        <peer-group-tag>WORD</peer-group-tag>  
      </config>  
      </neighbor-passive><!-- operation="delete"-->  
    </peer-group>  
  </peer-groups>  
</bgp-instance>  
</bgp-instances>  
</bgp>
```

## Command Syntax

```
neighbor WORD passive
```

---

## Configure peer shutdown description

Use this attribute to send shutdown communication message to inform peer the reason for the shutdown of the BGP session.

Attribute Name: peer-shutdown-description

Attribute Type: string

Attribute Range: 1-255

Attribute Name: peer-shutdown

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
        </peer-shutdown><!-- operation="delete"-->
      </config>
      <peer-shutdown-description>1</peer-shutdown-description> <!--
operation="delete"-->
    </peer-group>
  </peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD shutdown (description LINE|)
```

---

## Configure peer port

Sets the BGP port number of a neighbor.

Attribute Name: peer-port

Attribute Type: uint16

Default Value: 179

Attribute Range: 0-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
    </peer-group>
  </peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

```

        <peer-port>0</peer-port> <!-- operation="delete"-->
    </peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD port <0-65535>
```

---

## Configure bgp version

Configure router to accept only a particular BGP version. By default, the system uses BGP version 4 and on request dynamically negotiates down to version 2. Disables the routers version-negotiation capability and forces the router to use only a specified version with the neighbor.

Attribute Name: bgp-version

Attribute Type: uint8

Default Value: 4

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <bgp-version>(4)</bgp-version> <!-- operation="delete"-->
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD version (4)
```

---

## Configure enable ext opt param len

Use this attribute for a specific peer to encode extended optional parameter length.

Attribute Name: enable-ext-opt-param-len

Attribute Type: empty

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      </enable-ext-opt-param-len><!-- operation="delete"-->
    </peer-group>
  </peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD extended-optional-param
```

---

## Configure tcp adjust mss

Use this attribute to set the BGP TCP MSS value of a neighbor.

Attribute Name: tcp-adjust-mss

Attribute Type: uint16

Attribute Range: 40-1440

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
        <tcp-adjust-mss>40</tcp-adjust-mss> <!-- operation="delete"-->
      </config>
    </peer-group>
  </peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>
```

```

</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD tcp-mss <40-1440>
```

---

## Configure keep alive

Use this attribute to globally set or reset the keepalive values for all the neighbors

Attribute Name: keep-alive

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: hold-time

Attribute Type: uint16

Attribute Range: 0-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <timers>
      <config>
        <hold-time>0</hold-time>
        <keep-alive>0</keep-alive>
      </config>
    </timers>
    </peer-group>
  </peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD timers <0-65535> <0-65535>
```

---

## Configure enabled

Use this attribute to accept and attempt BGP connections to external peers on indirectly connected networks. Multihop is not established if the only route to the multihop peer is a default route. This avoids loop formation.

Attribute Name: enabled

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <ebgp-multihop>
            <config>
              </enabled>
            </config>
          </ebgp-multihop>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD ebgp-multihop
```

---

## Configure maximum hop count

Use this attribute to accept and attempt BGP connections to external peers on indirectly connected networks. Multihop is not established if the only route to the multihop peer is a default route. This avoids loop formation.

Attribute Name: enabled

Attribute Type: empty

Attribute Name: maximum-hop-count

Attribute Type: uint8

Attribute Range: 1-255

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
```

```

<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <ebgp-multihop>
      <config>
        <maximum-hop-count>1</maximum-hop-count> <!-- operation="delete"-->
        </enabled><!-- operation="delete"-->
      </config>
    </ebgp-multihop>
  </peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD ebgp-multihop <1-255>
```

---

## Configure peer local as

Specifies an AS (autonomous system) number to use with BGP neighbor.

Attribute Name: peer-local-as

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
      <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
          <peer-group-tag>WORD</peer-group-tag>
        </config>
      <local-as>

```

```

        <local-as-list> <!-- operation="delete"-->
            <peer-local-as>1</peer-local-as>
        </local-as-list>
    </local-as>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD local-as <1-4294967295>
```

---

## Configure no prepend local as

Specifies an AS (autonomous system) number to use with BGP neighbor.

Attribute Name: peer-local-as

Attribute Type: uint32

Attribute Range: 1-4294967295

Attribute Name: no-prepend-local-as

Attribute Type: empty

Attribute Name: replace-local-as

Attribute Type: empty

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <local-as>
            <local-as-list>
              <peer-local-as>1</peer-local-as>
            </local-as-list>
            <config>
              <peer-local-as>1</peer-local-as>
              </no-prepend-local-as>
            </config>
          </local-as>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        </replace-local-as>
    </config>
</local-as-list>
</local-as>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD local-as <1-4294967295> (no-prepend|) (replace-as|)
```

---

## Configure admin status

Enable or disable AIGP

Attribute Name: admin-status

Attribute Type: enum (disable|enable)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
            </address-family>
          </address-families>
          <aigp>
            <config>
              <admin-status>disable</admin-status> <!-- operation="delete"-->
            </config>
          </aigp>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD aigp (disable|enable)
```

---

## Configure aigp send med

Enable AIGP send multi exit discriminator.

Attribute Name: aigp-send-med

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
      <aigp>
      <config>
        </aigp-send-med><!-- operation="delete"-->
      </config>
    </aigp>
    </address-family>
  </address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD aigp send med
```

---

## Configure send cost community id

Send AIGP value in Cost community. And get the Community ID.

Attribute Name: send-cost-community-id

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: point-of-insertion

Attribute Type: enum (pre-bestpath|jigp-cost)

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
            </address-family>
          </address-families>
          <aigp>
            <cost-community>
              <config>
                <point-of-insertion>pre-bestpath</point-of-insertion>
                <send-cost-community-id>0</send-cost-community-id>
              </config>
            </cost-community>
          </aigp>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
```

```
</bgp>
```

## Command Syntax

```
neighbor WORD aigp send cost-community <0-255> poi (pre-bestpath|igp-cost)
```

---

## Configure enable transitive

Send AIGP value in Cost community and Enable Transitive Cost Community

Attribute Name: enable-transitive

Attribute Type: uint8

Attribute Name: send-cost-community-id

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: point-of-insertion

Attribute Type: enum (pre-bestpath|igp-cost)

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
            </address-family>
          </address-families>
          <aigp>
            <cost-community>
              <config>
                <send-cost-community-id>0</send-cost-community-id> <!--
operation="delete"-->
                <point-of-insertion>pre-bestpath</point-of-insertion> <!--
operation="delete"-->
                </enable-transitive><!-- operation="delete"-->
              </config>
            </cost-community>
          </aigp>
        </peer-group>
      </peer-groups>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

```

    </aigp>
  </address-family>
</address-families>
</peer-group>
</peer-groups>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```

neighbor WORD aigp send cost-community <0-255> poi (pre-bestpath|igp-cost)
transitive

```

---

## clear bgp peer-group WORD l2vpn evpn soft (out|in|)

Attribute Name: peer-group-tag

Attribute Type: string

Attribute Range: 1-255

Attribute Name: soft-reconfig

Attribute Type: enum (out|in|soft-only)

### Netconf RPC payload

```

<ipi-bgp-peer-group_clear-peer-group-l2vpn-evpn-soft-all xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <peer-group-tag>WORD</peer-group-tag>
  <soft-reconfig>soft-only</soft-reconfig>
</ipi-bgp-peer-group_clear-peer-group-l2vpn-evpn-soft-all>

```

### Command Syntax

```

clear bgp peer-group WORD l2vpn evpn soft (out|in|)

```

---

## IPI-BGP-PEER

---

### Configure enable peer bfd

Enable bidirectional forwarding detection (BFD) for the BGP peer

Attribute Name: enable-peer-bfd

Attribute Type: uint8

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>

```

```

    </config>
    <peers>
    <peer>
        <peer-address>A.B.C.D|X:X::X:X</peer-address>
        <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
        </config>
        </enable-peer-bfd><!-- operation="delete"-->
    </peer>
    </peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) fall-over bfd
```

---

## Configure bgp as

Enable bidirectional forwarding detection (BFD) for the BGP peer

Attribute Name: enable-peer-bfd

Attribute Type: uint8

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
    <bgp-instance>
        <bgp-as>1</bgp-as>
        <config>
            <bgp-as>1</bgp-as>
        </config>
        <peers>
        <peer>
            <peer-address>A.B.C.D|X:X::X:X</peer-address>
            <config>
                <peer-address>BGP_IP_ADDR_T</peer-address>
            </config>
            </enable-peer-bfd><!-- operation="delete"-->
        </peer>
        </peers>
    </bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD fall-over bfd
```

---

## Configure enable peer bfd multihop

Enable bidirectional forwarding detection (BFD) for the BGP peer with multihop

Attribute Name: enable-peer-bfd-multihop

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          </enable-peer-bfd-multihop><!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) fall-over bfd multihop
```

---

## Configure peer address

Enable bidirectional forwarding detection (BFD) for the BGP peer with multihop

Attribute Name: enable-peer-bfd-multihop

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
```

```

        <peer-address>BGP_IP_ADDR_T</peer-address>
    </config>
    </enable-peer-bfd-multihop><!-- operation="delete"-->
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD fall-over bfd multihop
```

---

## Configure interface name

Configure the interface name of a BGP neighbor.

Attribute Name: interface-name

Attribute Type: string

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <interface-name>WORD</interface-name> <!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) interface WORD
```

---

## Configure mapped peer group tag

Adds a neighbor to an existing peer group. Neighbors with the same update policies are grouped into peer groups. This facilitates the updates of various policies, such as distribute and filter lists. The peer group is then configured easily with any of the neighbor attributes. Any changes made to the peer group affect all members.

Attribute Name: mapped-peer-group-tag

Attribute Type: string

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <mapped-peer-group-tag>WORD</mapped-peer-group-tag> <!--
operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) peer-group WORD
```

---

## Configure peer mapped-peer-group-tag

Adds a neighbor to an existing peer group. Neighbors with the same update policies are grouped into peer groups. This facilitates the updates of various policies, such as distribute and filter lists. The peer group is then configured easily with any of the neighbor attributes. Any changes made to the peer group affect all members.

Attribute Name: mapped-peer-group-tag

Attribute Type: string

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

```

        <mapped-peer-group-tag>WORD</mapped-peer-group-tag> <!--
operation="delete"-->
    </peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD peergroup WORD
```

---

## Configure tcp adjust mss

Use this attribute to set the BGP TCP MSS value of a neighbor.

Attribute Name: tcp-adjust-mss

Attribute Type: uint16

Attribute Range: 40-1440

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <tcp-adjust-mss>40</tcp-adjust-mss> <!-- operation="delete"-->
    </peer>
  </peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD tcp-mss <40-1440>
```

---

## Configure auth key encrypt

Use this attribute to configure the authentication key to specify if the password is to be encrypted or not.

Attribute Name: auth-key-encrypt

Attribute Type: enum (0|1)

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <bgp-passwords>
            <bgp-password>
              <password>WORD</password>
              <config>
                <password>WORD</password>
              </config>
              <auth-key-encrypt>1</auth-key-encrypt>
            </bgp-password>
          </bgp-passwords>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

**Command Syntax**

```
neighbor (A.B.C.D|X:X::X:X) authentication-key (0|1) WORD
```

**Configure password**

Use this attribute to configure the authentication key to specify if the password is to be encrypted or not.

Attribute Name: auth-key-encrypt

Attribute Type: enum (0|1)

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>

```

```

    <config>
      <peer-address>BGP_IP_ADDR_T</peer-address>
    </config>
  <bgp-passwords>
    <bgp-password>
      <password>WORD</password>
      <config>
        <password>WORD</password>
      </config>
      <auth-key-encrypt>2</auth-key-encrypt>
    </bgp-password>
  </bgp-passwords>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) authentication-key WORD
```

---

## Configure bgp-password auth-key-encrypt

Use this attribute to configure the authentication key to specify if the password is to be encrypted or not.

Attribute Name: auth-key-encrypt

Attribute Type: enum (0|1)

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <bgp-passwords>
            <bgp-password>
              <password>WORD</password>
              <config>
                <password>WORD</password>
              </config>
              <auth-key-encrypt>1</auth-key-encrypt>
            </bgp-password>
          </peers>
        </peer>
      </bgp-instances>
    </bgp-instance>
  </bgp>

```

```

    </bgp-passwords>
  </peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD authentication-key (0|1) WORD
```

---

## Configure bgp-password auth-key-encrypt

Use this attribute to configure the authentication key to specify if the password is to be encrypted or not.

Attribute Name: auth-key-encrypt

Attribute Type: enum (0|1)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <bgp-passwords>
            <bgp-password>
              <password>WORD</password>
              <config>
                <password>WORD</password>
              </config>
              <auth-key-encrypt>2</auth-key-encrypt>
            </bgp-password>
          </bgp-passwords>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD authentication-key WORD
```

---

## Configure additional paths mode

Adds additional paths in the BGP table

Attribute Name: additional-paths-mode

Attribute Type: bits (send-receive|receive|send|disable)

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
                <additional-paths-mode>send-receive</additional-paths-mode> <!--
operation="delete"-->
              </address-family>
            </address-families>
          </peer>
        </peers>
      </bgp-instance>
    </bgp-instances>
  </bgp>
```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) additional-paths (send-receive|receive|send|disable)
```

---

## Configure additional path select all

Attribute to select advertise additional path

Attribute Name: additional-path-select-all

Attribute Type: uint8

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
        </additional-path-select-all><!-- operation="delete"-->
      </address-family>
    </address-families>
  </peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

**Command Syntax**

```
neighbor (A.B.C.D|X:X::X:X) advertise additional-paths all
```

**Configure additional paths best select count**

Attribute to select best advertise additional path

Attribute Name: additional-paths-best-select-count

Attribute Type: uint8

Attribute Range: 2-3

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>

```

```

</config>
<peers>
<peer>
  <peer-address>A.B.C.D|X:X::X:X</peer-address>
  <config>
    <peer-address>BGP_IP_ADDR_T</peer-address>
  </config>
  <address-families>
  <address-family>
    <safi>unicast</safi>
    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
    <additional-paths-best-select-count>2</additional-paths-best-
select-count> <!-- operation="delete"-->
  </address-family>
</address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) advertise additional-paths best <2-3>
```

---

## Configure activate

Activate/Deactivate neighbor. This attribute enables or disables the exchange of AF information with a neighboring router.

Attribute Name: activate

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
    </peer>
  </bgp-instance>
</bgp-instances>

```

```

    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      </activate><!-- operation="delete"-->
    </address-family>
  </address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD activate
```

---

## Configure afi

Activate/Deactivate neighbor. This attribute enables or disables the exchange of AF information with a neighboring router.

Attribute Name: activate

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
    </address-family>
  </address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

```

        </activate><!-- operation="delete"-->
    </address-family>
</address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD activate
```

## Configure safi

Activate/Deactivate neighbor. This attribute enables or disables the exchange of AF information with a neighboring router.

Attribute Name: activate

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
          <afi>ipv4</afi>
          </activate><!-- operation="delete"-->
        </address-family>
      </address-families>
    </peer>
  </peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) activate
```

---

## Configure address-family activate

Activate/Deactivate neighbor. This attribute enables or disables the exchange of AF information with a neighboring router.

Attribute Name: activate

Attribute Type: uint8

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
                </activate><!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) activate
```

---

## Configure address-family activate

Activate/Deactivate neighbor. This attribute enables or disables the exchange of AF information with a neighboring router.

Attribute Name: activate

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              </activate><!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD activate
```

---

## Configure address-family activate

Activate/Deactivate neighbor. This attribute enables or disables the exchange of AF information with a neighboring router.

Attribute Name: activate

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
```

```

<config>
  <bgp-as>1</bgp-as>
</config>
<peers>
<peer>
  <peer-address>A.B.C.D|X:X::X:X</peer-address>
  <config>
    <peer-address>BGP_IP_ADDR_T</peer-address>
  </config>
  <address-families>
  <address-family>
    <safi>unicast</safi>
    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
    </activate><!-- operation="delete"-->
  </address-family>
</address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) activate
```

---

## Configure de activate

Deactivate neighbor. This attribute disables the exchange of AF information with a neighboring router.

Attribute Name: de-activate

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
    </peer>
  </bgp-instance>
</bgp-instances>
</bgp>

```

```

    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      </de-activate><!-- operation="delete"-->
    </address-family>
  </address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD de-activate
```

---

## Configure address-family de-activate

Deactivate neighbor. This attribute disables the exchange of AF information with a neighboring router.

Attribute Name: de-activate

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      </de-activate><!-- operation="delete"-->
    </address-family>
  </peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

```

        </address-family>
    </address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD de-activate
```

---

## Configure address-family de-activate

Deactivate neighbor. This attribute disables the exchange of AF information with a neighboring router.

Attribute Name: de-activate

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              </de-activate><!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

---

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) de-activate
```

---

## Configure address-family de-activate

Deactivate neighbor. This attribute disables the exchange of AF information with a neighboring router.

Attribute Name: de-activate

Attribute Type: uint8

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
              </de-activate><!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) de-activate
```

---

## Configure address-family de-activate

Deactivate neighbor. This attribute disables the exchange of AF information with a neighboring router.

Attribute Name: de-activate

Attribute Type: uint8

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
        </de-activate><!-- operation="delete"-->
      </address-family>
    </address-families>
    </peer>
  </peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

**Command Syntax**

```
neighbor WORD de-activate
```

**Configure address-family de-activate**

Deactivate neighbor. This attribute disables the exchange of AF information with a neighboring router.

Attribute Name: de-activate

Attribute Type: uint8

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>

```

```

    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
        </de-activate><!-- operation="delete"-->
      </address-family>
    </address-families>
  </peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) de-activate
```

---

## Configure default peer route map name

This attribute allows a BGP local router to send the default route 0.0.0.0 to a neighbor for use as a default route for specified address-family.

Attribute Name: default-peer-route-map-name

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
      <peer>
        <peer-address>A.B.C.D|X:X::X:X</peer-address>
        <config>
          <peer-address>BGP_IP_ADDR_T</peer-address>
        </config>
        <address-families>
        <address-family>
          <safi>unicast</safi>

```

```

    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
    </default-peer-route-map-name><!-- operation="delete"-->
  </address-family>
</address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) default-originate
```

---

## Configure address-family default-peer-route-map-name

This attribute allows a BGP local router to send the default route 0.0.0.0 to a neighbor for use as a default route for specified address-family.

Attribute Name: default-peer-route-map-name

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              </default-peer-route-map-name><!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    </peer>
  </peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD default-originate
```

---

## Configure peer route map orig name

This attribute configures route map to be used for a BGP local router to send the default route 0.0.0.0 to a neighbor for use as a default route for specified address-family. This attribute can be used with standard or extended access lists.

Attribute Name: peer-route-map-orig-name

Attribute Type: string

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              <peer-route-map-orig-name>WORD</peer-route-map-orig-name> <!--
operation="delete"-->
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) default-originate route-map WORD
```

---

## Configure weight

This attribute specifies a weight value, for specified address-family, to all routes learned from a neighbor for specified address-family. The route with the highest weight gets preference when the same prefix is learned from more than one peer. Unlike the local-preference attribute, the weight attribute is relevant only to the local router. When the weight is set for a peer group, all members of the peer group get the same weight. This attribute can also be used to assign a different weight to an individual peer-group member. When an individually-configured weight of a peer-group member is removed, its weight is reset to its peer groups weight.

Attribute Name: weight

Attribute Type: uint16

Default Value: 0

Attribute Range: 0-65535

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
                <weight>0</weight> <!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) weight <0-65535>
```

---

## Configure address-family weight

This attribute specifies a weight value, for specified address-family, to all routes learned from a neighbor for specified address-family. The route with the highest weight gets preference when the same prefix is learned from more than one peer. Unlike the local-preference attribute, the weight attribute is relevant only to the local router. When the weight is set for a peer group, all members of the peer group get the same weight. This attribute can also be used to assign a different weight to an individual peer-group member. When an individually-configured weight of a peer-group member is removed, its weight is reset to its peer groups weight.

Attribute Name: weight

Attribute Type: uint16

Default Value: 0

Attribute Range: 0-65535

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
                <weight>0</weight> <!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD weight <0-65535>
```

---

## Configure route server client

This attribute configures a neighbor as the route server client for specified address-family.

Attribute Name: route-server-client

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
              </route-server-client><!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) route-server-client
```

---

## Configure address-family route-server-client

This attribute configures a neighbor as the route server client for specified address-family.

Attribute Name: route-server-client

Attribute Type: uint8

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
        </route-server-client><!-- operation="delete"-->
      </address-family>
    </address-families>
  </peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD route-server-client
```

---

## Configure next hop self

This attribute configure the router as the next hop for a BGP-speaking neighbor or peer group. This attribute allows a BGP router to change the nexthop information that is sent to the iBGP peer. The nexthop information is set to the IP address of the interface used to communicate with the neighbor.

Attribute Name: next-hop-self

Attribute Type: uint8

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
```

```

</config>
<peers>
<peer>
  <peer-address>A.B.C.D|X:X::X:X</peer-address>
  <config>
    <peer-address>BGP_IP_ADDR_T</peer-address>
  </config>
  <address-families>
  <address-family>
    <safi>unicast</safi>
    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
    </next-hop-self><!-- operation="delete"-->
  </address-family>
</address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) next-hop-self
```

---

## Configure address-family next-hop-self

This attribute configure the router as the next hop for a BGP-speaking neighbor or peer group. This attribute allows a BGP router to change the nexthop information that is sent to the iBGP peer. The nexthop information is set to the IP address of the interface used to communicate with the neighbor.

Attribute Name: next-hop-self

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
    </peer>
  </bgp-instance>
</bgp-instances>
</bgp>

```

```

    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      </next-hop-self><!-- operation="delete"-->
    </address-family>
  </address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD next-hop-self
```

---

## Configure peer route reflector

This attribute configures the router as a BGP route reflector and configure the specified neighbor as its client for specified address-family. Route reflectors are a solution for the explosion of iBGP peering within an autonomous system. By route reflection the number of iBGP peers within an AS is reduced. Use this attribute to configure the local router as the route reflector and specify neighbors as its client. An AS can have more than one route reflector. One route reflector treats the other route reflector as another iBGP speaker.

Attribute Name: peer-route-reflector

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>

```

```

        <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
    </peer-route-reflector><!-- operation="delete"-->
</address-family>
</address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) route-reflector-client
```

## Configure address-family peer-route-reflector

This attribute configures the router as a BGP route reflector and configure the specified neighbor as its client for specified address-family. Route reflectors are a solution for the explosion of iBGP peering within an autonomous system. By route reflection the number of iBGP peers within an AS is reduced. Use this attribute to configure the local router as the route reflector and specify neighbors as its client. An AS can have more than one route reflector. One route reflector treats the other route reflector as another iBGP speaker.

Attribute Name: peer-route-reflector

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
    <config>
      <peer-address>BGP_IP_ADDR_T</peer-address>
    </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
      <afi>ipv4</afi>
    </peer-route-reflector><!-- operation="delete"-->
  </address-family>

```

```

    </address-families>
  </peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) route-reflector-client
```

---

## Configure address-family peer-route-reflector

This attribute configures the router as a BGP route reflector and configure the specified neighbor as its client for specified address-family. Route reflectors are a solution for the explosion of iBGP peering within an autonomous system. By route reflection the number of iBGP peers within an AS is reduced. Use this attribute to configure the local router as the route reflector and specify neighbors as its client. An AS can have more than one route reflector. One route reflector treats the other route reflector as another iBGP speaker.

Attribute Name: peer-route-reflector

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
            </peer-route-reflector><!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>

```

---

```
</bgp>
```

## Command Syntax

```
neighbor WORD route-reflector-client
```

---

## Configure address-family peer-route-reflector

This attribute configures the router as a BGP route reflector and configure the specified neighbor as its client for specified address-family. Route reflectors are a solution for the explosion of iBGP peering within an autonomous system. By route reflection the number of iBGP peers within an AS is reduced. Use this attribute to configure the local router as the route reflector and specify neighbors as its client. An AS can have more than one route reflector. One route reflector treats the other route reflector as another iBGP speaker.

Attribute Name: peer-route-reflector

Attribute Type: uint8

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
              </peer-route-reflector><!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD route-reflector-client
```

---

## Configure peer remove private as

This attribute removes the private Autonomous System (AS) number from outbound updates. Private AS numbers are not advertised to the Internet. This attribute is used with external BGP peers only. The router removes the AS numbers only if the update includes private AS numbers. If the update includes both private and public AS numbers, the system treats it as an error.

Attribute Name: peer-remove-private-as

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              </peer-remove-private-as><!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) remove-private-AS
```

---

## Configure address-family peer-remove-private-as

This attribute removes the private Autonomous System (AS) number from outbound updates. Private AS numbers are not advertised to the Internet. This attribute is used with external BGP peers only. The router removes the AS numbers only if the update includes private AS numbers. If the update includes both private and public AS numbers, the system treats it as an error.

Attribute Name: peer-remove-private-as

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              </peer-remove-private-as><!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD remove-private-AS
```

---

## Configure no send community

This attribute specifies if a community attribute should be sent to a BGP neighbor for specified address-family. The community attribute groups destinations in a certain community and applies routing decisions according to those communities. By default, both standard and extended community attributes are sent to a neighbor

Attribute Name: no-send-community

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
```

```

    <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <peers>
  <peer>
    <peer-address>A.B.C.D|X:X::X:X</peer-address>
    <config>
      <peer-address>BGP_IP_ADDR_T</peer-address>
    </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      </no-send-community><!-- operation="delete"-->
    </address-family>
  </address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
no neighbor (A.B.C.D|X:X::X:X) send-community
```

---

## Configure no send community type

This attribute specifies the type of community attribute to be sent to a BGP neighbor.

Attribute Name: no-send-community-type

Attribute Type: bits (both|standard|extended|large)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
      <peer>
        <peer-address>A.B.C.D|X:X::X:X</peer-address>
        <config>
          <peer-address>BGP_IP_ADDR_T</peer-address>

```

```

    </config>
  <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      <no-send-community-type>both</no-send-community-type> <!--
operation="delete"-->
    </address-family>
  </address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
no neighbor (A.B.C.D|X:X::X:X) send-community (both|standard|extended|large)
```

---

## Configure neighbor attribute unchanged

This attribute advertises unchanged BGP AS path, next hop and med to the specified neighbor.

Attribute Name: neighbor-attribute-unchanged

Attribute Type: bits (as-path|next-hop|med)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
        <address-families>
          <address-family>
            <safi>unicast</safi>
            <config>
              <safi>unicast</safi>
              <afi>ipv4</afi>
            </config>
          </address-family>
        </address-families>
      </peer>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        <afi>ipv4</afi>
        <neighbor-attribute-unchanged>14</neighbor-attribute-unchanged> <!--
- operation="delete"-->
        </address-family>
    </address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) attribute-unchanged
```

## Configure address-family neighbor-attribute-unchanged

This attribute advertises unchanged BGP AS path, next hop and med to the specified neighbor.

Attribute Name: neighbor-attribute-unchanged

Attribute Type: bits (as-path|next-hop|med)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
          <afi>ipv4</afi>
          <neighbor-attribute-unchanged>as-path</neighbor-attribute-
unchanged> <!-- operation="delete"-->
        </address-family>
      </address-families>
    </peer>
  </peers>
</bgp-instance>
</bgp-instances>

```

---

```
</bgp>
```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) attribute-unchanged {as-path|next-hop|med}
```

---

## Configure address-family neighbor-attribute-unchanged

This attribute advertises unchanged BGP AS path, next hop and med to the specified neighbor.

Attribute Name: neighbor-attribute-unchanged

Attribute Type: bits (as-path|next-hop|med)

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
                <neighbor-attribute-unchanged>14</neighbor-attribute-unchanged> <!--
- operation="delete"-->
              </address-family>
            </address-families>
          </peer>
        </peers>
      </bgp-instance>
    </bgp-instances>
  </bgp>
```

## Command Syntax

```
neighbor WORD attribute-unchanged
```

---

## Configure address-family neighbor-attribute-unchanged

This attribute advertises unchanged BGP AS path, next hop and med to the specified neighbor.

Attribute Name: neighbor-attribute-unchanged

Attribute Type: bits (as-path|next-hop|med)

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
                <neighbor-attribute-unchanged>as-path</neighbor-attribute-
unchanged> <!-- operation="delete"-->
              </address-family>
            </address-families>
          </peer>
        </peers>
      </bgp-instance>
    </bgp-instances>
  </bgp>
```

### Command Syntax

```
neighbor WORD attribute-unchanged {as-path|next-hop|med}
```

---

## Configure orf prefix capability

This attribute enables Outbound Router Filtering (ORF), and advertise the ORF capability to its neighbors. The ORFs send and receive capabilities to lessen the number of updates exchanged between neighbors. By filtering updates, this option minimizes generating and processing of updates. The two routers exchange updates to maintain the ORF for each router.

Attribute Name: orf-prefix-capability

Attribute Type: bits (both|receive|send)

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
```

```

<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
          <afi>ipv4</afi>
          <orf-prefix-capability>both</orf-prefix-capability> <!--
operation="delete"-->
        </address-family>
      </address-families>
    </peer>
  </peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) capability orf prefix-list (both|receive|send)
```

## Configure address-family orf-prefix-capability

This attribute enables Outbound Router Filtering (ORF), and advertise the ORF capability to its neighbors. The ORFs send and receive capabilities to lessen the number of updates exchanged between neighbors. By filtering updates, this option minimizes generating and processing of updates. The two routers exchange updates to maintain the ORF for each router.

Attribute Name: orf-prefix-capability

Attribute Type: bits (both|receive|send)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>

```

```

    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
          <afi>ipv4</afi>
          <orf-prefix-capability>both</orf-prefix-capability> <!--
operation="delete"-->
        </address-family>
      </address-families>
    </peer>
  </peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD capability orf prefix-list (both|receive|send)
```

---

## Configure peer allow ebgp vpn

This attribute allows an eBGP neighbor to be a VPN peer. By default, BGP VPN functionality is allowed only for iBGP peers. Using the peer-allow-ebgp-vpn attribute allows the VPN connection to be established to an eBGP peer.

Attribute Name: peer-allow-ebgp-vpn

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
      <peer>
        <peer-address>A.B.C.D|X:X::X:X</peer-address>
        <config>
          <peer-address>BGP_IP_ADDR_T</peer-address>
        </config>
      <address-families>

```

```

    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
    </address-family>
  </address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) allow-ebgp-vpn
```

---

## Configure allow as number

This attribute advertises prefixes (routes) even when the source of the prefixes is from the same Autonomous System (AS) number for specified address-family. Use this attribute in a scenario where two routers at different locations use the same Autonomous System number and are connected via an ISP. Once prefixes arrive from one branch at the ISP, they are tagged with the customers AS number. By default, when the ISP passes the prefixes to the other router, the prefixes are dropped if the other router uses the same AS number. Use this attribute to advertise the prefixes at the other side. Control the number of times an AS number is advertised by specifying a number. In a hub and spoke configuration in a VPN, a PE (Provider Edge) router advertises all prefixes containing duplicate AS numbers. Use this attribute to configure two VRFs on each PE router to receive and advertise prefixes. One of the VRFs receives prefixes with AS numbers from all PE routers and then advertises them to neighboring PE routers. The other VRF receives prefixes with AS numbers from the CE (Customer Edge) router and advertises them to all PE routers in the hub and spoke configuration.

Attribute Name: allow-as-number

Attribute Type: uint32

Default Value: 3

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>

```

```

    </config>
  <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      <allow-as-number>1</allow-as-number> <!-- operation="delete"-->
    </address-family>
  </address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) allowas-in <1-10>
```

---

## Configure address-family allow-as-number

This attribute advertises prefixes (routes) even when the source of the prefixes is from the same Autonomous System (AS) number for specified address-family. Use this attribute in a scenario where two routers at different locations use the same Autonomous System number and are connected via an ISP. Once prefixes arrive from one branch at the ISP, they are tagged with the customers AS number. By default, when the ISP passes the prefixes to the other router, the prefixes are dropped if the other router uses the same AS number. Use this attribute to advertise the prefixes at the other side. Control the number of times an AS number is advertised by specifying a number. In a hub and spoke configuration in a VPN, a PE (Provider Edge) router advertises all prefixes containing duplicate AS numbers. Use this attribute to configure two VRFs on each PE router to receive and advertise prefixes. One of the VRFs receives prefixes with AS numbers from all PE routers and then advertises them to neighboring PE routers. The other VRF receives prefixes with AS numbers from the CE (Customer Edge) router and advertises them to all PE routers in the hub and spoke configuration.

Attribute Name: allow-as-number

Attribute Type: uint32

Default Value: 3

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>

```

```

<config>
  <peer-address>BGP_IP_ADDR_T</peer-address>
</config>
<address-families>
  <address-family>
    <safi>unicast</safi>
    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
    <allow-as-number>1</allow-as-number> <!-- operation="delete"-->
  </address-family>
</address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) allowas-in <1-10>
```

---

## Configure address-family allow-as-number

This attribute advertises prefixes (routes) even when the source of the prefixes is from the same Autonomous System (AS) number for specified address-family. Use this attribute in a scenario where two routers at different locations use the same Autonomous System number and are connected via an ISP. Once prefixes arrive from one branch at the ISP, they are tagged with the customers AS number. By default, when the ISP passes the prefixes to the other router, the prefixes are dropped if the other router uses the same AS number. Use this attribute to advertise the prefixes at the other side. Control the number of times an AS number is advertised by specifying a number. In a hub and spoke configuration in a VPN, a PE (Provider Edge) router advertises all prefixes containing duplicate AS numbers. Use this attribute to configure two VRFs on each PE router to receive and advertise prefixes. One of the VRFs receives prefixes with AS numbers from all PE routers and then advertises them to neighboring PE routers. The other VRF receives prefixes with AS numbers from the CE (Customer Edge) router and advertises them to all PE routers in the hub and spoke configuration.

Attribute Name: allow-as-number

Attribute Type: uint32

Default Value: 3

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
        <allow-as-number>1</allow-as-number> <!-- operation="delete"-->
      </address-family>
    </address-families>
  </peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD allowas-in <1-10>
```

---

## Configure address-family allow-as-number

This attribute advertises prefixes (routes) even when the source of the prefixes is from the same Autonomous System (AS) number for specified address-family. Use this attribute in a scenario where two routers at different locations use the same Autonomous System number and are connected via an ISP. Once prefixes arrive from one branch at the ISP, they are tagged with the customer's AS number. By default, when the ISP passes the prefixes to the other router, the prefixes are dropped if the other router uses the same AS number. Use this attribute to advertise the prefixes at the other side. Control the number of times an AS number is advertised by specifying a number. In a hub and spoke configuration in a VPN, a PE (Provider Edge) router advertises all prefixes containing duplicate AS numbers. Use this attribute to configure two VRFs on each PE router to receive and advertise prefixes. One of the VRFs receives prefixes with AS numbers from all PE routers and then advertises them to neighboring PE routers. The other VRF receives prefixes with AS numbers from the CE (Customer Edge) router and advertises them to all PE routers in the hub and spoke configuration.

Attribute Name: allow-as-number

Attribute Type: uint32

Default Value: 3

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>

```

```

</config>
<peers>
<peer>
  <peer-address>A.B.C.D|X:X::X:X</peer-address>
  <config>
    <peer-address>BGP_IP_ADDR_T</peer-address>
  </config>
  <address-families>
  <address-family>
    <safi>unicast</safi>
    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
    <allow-as-number>1</allow-as-number> <!-- operation="delete"-->
  </address-family>
</address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD allowas-in <1-10>
```

---

## Configure capability graceful restart

This attribute configures the router to advertise the Graceful Restart Capability to the neighbors. This configuration indicates that the BGP speaker has the ability to preserve its forwarding state for the address family when BGP restarts. Use this attribute to advertise to the neighbor routers the capability of graceful restart.

Attribute Name: capability-graceful-restart

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
    </peer>
  </bgp-instance>
</bgp-instances>
</bgp>

```

```

    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      </capability-graceful-restart><!-- operation="delete"-->
    </address-family>
  </address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) capability graceful-restart
```

## Configure address-family capability-graceful-restart

This attribute configures the router to advertise the Graceful Restart Capability to the neighbors. This configuration indicates that the BGP speaker has the ability to preserve its forwarding state for the address family when BGP restarts. Use this attribute to advertise to the neighbor routers the capability of graceful restart.

Attribute Name: capability-graceful-restart

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>

```

```

        <afi>ipv4</afi>
        </capability-graceful-restart><!-- operation="delete"-->
    </address-family>
</address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD capability graceful-restart
```

## Configure address-family capability-graceful-restart

This attribute configures the router to advertise the Graceful Restart Capability to the neighbors. This configuration indicates that the BGP speaker has the ability to preserve its forwarding state for the address family when BGP restarts. Use this attribute to advertise to the neighbor routers the capability of graceful restart.

Attribute Name: capability-graceful-restart

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
        </capability-graceful-restart><!-- operation="delete"-->
      </address-family>
    </address-families>
    </peer>
  </peers>
</bgp-instance>

```

```

</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) capability graceful-restart
```

---

## Configure extended nexthop encode

A BGP speaker that wishes to advertise an IPv6 next hop for IPv4 NLRI for VPN-IPv4 NLRI to a BGP peer as per this specification MUST use the Capability Advertisement procedures defined with the Extended Next Hop Encoding capability to determine whether its peer supports this for the NLRI AFI/SAFI pair(s) of interest.

Attribute Name: extended-nexthop-encode

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
          <afi>ipv4</afi>
          </extended-nexthop-encode><!-- operation="delete"-->
        </address-family>
      </address-families>
    </peer>
  </peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) capability extended-nexthop-encode
```

---

## Configure address-family capability-graceful-restart

This attribute configures the router to advertise the Graceful Restart Capability to the neighbors. This configuration indicates that the BGP speaker has the ability to preserve its forwarding state for the address family when BGP restarts. Use this attribute to advertise to the neighbor routers the capability of graceful restart.

Attribute Name: capability-graceful-restart

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
                </capability-graceful-restart><!-- operation="delete"-->
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) capability graceful-restart
```

---

## Configure prefix count

Use this attribute to specify maximum number of prefixes that can be received from a neighbor

Attribute Name: prefix-count

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
        <maximum-prefixes>
        <maximum-prefix> <!-- operation="delete"-->
          <prefix-count>1</prefix-count>
          <config>
            <prefix-count>1</prefix-count>
          </config>
        </maximum-prefix>
        </maximum-prefixes>
      </address-family>
    </address-families>
    </peer>
  </peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) maximum-prefix <1-4294967295>
```

## Configure maximum-prefixes prefix-count

Use this attribute to specify maximum number of prefixes that can be received from a neighbor

Attribute Name: prefix-count

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
        <maximum-prefixes>
        <maximum-prefix> <!-- operation="delete"-->
          <prefix-count>1</prefix-count>
          <config>
            <prefix-count>1</prefix-count>
          </config>
        </maximum-prefix>
        </maximum-prefixes>
      </address-family>
    </address-families>
  </peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295>
```

---

## Configure stop update

Stop installing the routes when limit is exceeded.

Attribute Name: stop-update

Attribute Type: uint8

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
```

```

<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
      <maximum-prefixes>
      <maximum-prefix>
        <prefix-count>1</prefix-count>
        <config>
          <prefix-count>1</prefix-count>
        </config>
        </stop-update>
      </maximum-prefix>
    </maximum-prefixes>
  </address-family>
</address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) maximum-prefix <1-4294967295> stop-update
```

---

## Configure maximum-prefix stop-update

Stop installing the routes when limit is exceeded.

Attribute Name: stop-update

Attribute Type: uint8

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>

```

```

<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <peers>
  <peer>
    <peer-address>A.B.C.D|X:X::X:X</peer-address>
    <config>
      <peer-address>BGP_IP_ADDR_T</peer-address>
    </config>
    <address-families>
    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
      <maximum-prefixes>
      <maximum-prefix>
        <prefix-count>1</prefix-count>
        <config>
          <prefix-count>1</prefix-count>
        </config>
        </stop-update>
      </maximum-prefix>
    </maximum-prefixes>
    </address-family>
  </address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) maximum-prefix <1-4294967295> stop-update
```

---

## Configure maximum-prefix stop-update

Stop installing the routes when limit is exceeded.

Attribute Name: stop-update

Attribute Type: uint8

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>

```

```

<bgp-as>1</bgp-as>
<config>
  <bgp-as>1</bgp-as>
</config>
<peers>
<peer>
  <peer-address>A.B.C.D|X:X::X:X</peer-address>
  <config>
    <peer-address>BGP_IP_ADDR_T</peer-address>
  </config>
  <address-families>
  <address-family>
    <safi>unicast</safi>
    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
    <maximum-prefixes>
    <maximum-prefix>
      <prefix-count>1</prefix-count>
      <config>
        <prefix-count>1</prefix-count>
      </config>
    </maximum-prefix>
    </maximum-prefixes>
  </address-family>
</address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295> stop-update
```

---

## Configure maximum prefix warning

This attribute when enabled only give warning message when limit is exceeded. When it is not set and extra prefixes are received, the router ends the peering.

Attribute Name: maximum-prefix-warning

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>

```

```

<bgp-as>1</bgp-as>
<config>
  <bgp-as>1</bgp-as>
</config>
<peers>
<peer>
  <peer-address>A.B.C.D|X:X::X:X</peer-address>
  <config>
    <peer-address>BGP_IP_ADDR_T</peer-address>
  </config>
  <address-families>
  <address-family>
    <safi>unicast</safi>
    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
    <maximum-prefixes>
    <maximum-prefix>
      <prefix-count>1</prefix-count>
      <config>
        <prefix-count>1</prefix-count>
      </config>
      </maximum-prefix-warning>
    </maximum-prefix>
    </maximum-prefixes>
  </address-family>
</address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) maximum-prefix <1-4294967295> warning-only
```

## Configure maximum-prefix maximum-prefix-warning

This attribute when enabled only give warning message when limit is exceeded. When it is not set and extra prefixes are received, the router ends the peering.

Attribute Name: maximum-prefix-warning

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>

```

```

<bgp-as>1</bgp-as>
<config>
  <bgp-as>1</bgp-as>
</config>
<peers>
<peer>
  <peer-address>A.B.C.D|X:X::X:X</peer-address>
  <config>
    <peer-address>BGP_IP_ADDR_T</peer-address>
  </config>
  <address-families>
  <address-family>
    <safi>unicast</safi>
    <config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <afi>ipv4</afi>
    <maximum-prefixes>
    <maximum-prefix>
      <prefix-count>1</prefix-count>
      <config>
        <prefix-count>1</prefix-count>
      </config>
      </maximum-prefix-warning>
    </maximum-prefix>
    </maximum-prefixes>
  </address-family>
</address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295> warning-only
```

---

## Configure threshold percentage

Threshold-value in percen. This attribute controls the number of prefixes that can be received from a neighbor. This attribute allows the configuration of a specified number of prefixes that a BGP router is allowed to receive from a neighbor. When the maximum-prefix-warning attribute is not set and extra prefixes are received, the router ends the peering.

Attribute Name: threshold-percentage

Attribute Type: uint8

Default Value: 75

Attribute Range: 1-100

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
      <peer>
        <peer-address>A.B.C.D|X:X::X:X</peer-address>
        <config>
          <peer-address>BGP_IP_ADDR_T</peer-address>
        </config>
        <address-families>
          <address-family>
            <safi>unicast</safi>
            <config>
              <safi>unicast</safi>
              <afi>ipv4</afi>
            </config>
            <afi>ipv4</afi>
            <maximum-prefixes>
              <maximum-prefix>
                <prefix-count>1</prefix-count>
                <config>
                  <prefix-count>1</prefix-count>
                </config>
                <threshold-percentage>1</threshold-percentage>
              </maximum-prefix>
            </maximum-prefixes>
          </address-family>
        </address-families>
      </peer>
    </peers>
  </bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) maximum-prefix <1-4294967295> <1-100>
```

## Configure maximum-prefix threshold-percentage

Threshold-value in percen. This attribute controls the number of prefixes that can be received from a neighbor. This attribute allows the configuration of a specified number of prefixes that a BGP router is allowed to receive from a neighbor. When the maximum-prefix-warning attribute is not set and extra prefixes are received, the router ends the peering.

Attribute Name: threshold-percentage

Attribute Type: uint8

Default Value: 75

Attribute Range: 1-100

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
              <maximum-prefixes>
                <maximum-prefix>
                  <prefix-count>1</prefix-count>
                  <config>
                    <prefix-count>1</prefix-count>
                  </config>
                    <threshold-percentage>1</threshold-percentage>
                  </maximum-prefix>
                </maximum-prefixes>
              </address-family>
            </address-families>
          </peer>
        </peers>
      </bgp-instance>
    </bgp-instances>
  </bgp>
```

### Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295> <1-100>
```

---

## Configure warning only

Throw warning if exceeds threshold-value

Attribute Name: warning-only

Attribute Type: uint8

Attribute Name: threshold-percentage

Attribute Type: uint8

Default Value: 75

Attribute Range: 1-100

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              <maximum-prefixes>
                <maximum-prefix>
                  <prefix-count>1</prefix-count>
                  <config>
                    <prefix-count>1</prefix-count>
                    <threshold-percentage>1</threshold-percentage>
                  </config>
                </maximum-prefix>
              </maximum-prefixes>
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) maximum-prefix <1-4294967295> <1-100> warning-only
```

---

## Configure maximum-prefix warning-only

Throw warning if exceeds threshold-value

Attribute Name: warning-only

Attribute Type: uint8

Attribute Name: threshold-percentage

Attribute Type: uint8

Default Value: 75

Attribute Range: 1-100

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
              <maximum-prefixes>
                <maximum-prefix>
                  <prefix-count>1</prefix-count>
                  <config>
                    <prefix-count>1</prefix-count>
                    <threshold-percentage>1</threshold-percentage>
                  </config>
                </warning-only>
              </maximum-prefix>
            </maximum-prefixes>
          </address-family>
        </address-families>
      </peer>
    </peers>
  </bgp-instance>
</bgp-instances>
</bgp>
```

```

</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295> <1-100> warning-only
```

---

## Configure unsuppress route map name

unsuppress map name. This attribute is used to selectively leak more-specific routes to a particular neighbor.

Attribute Name: unsuppress-route-map-name

Attribute Type: string

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
                <unsuppress-route-map-name>WORD</unsuppress-route-map-name> <!--
operation="delete"-->
              </address-family>
            </address-families>
          </peer>
        </peers>
      </bgp-instance>
    </bgp-instances>
  </bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) unsuppress-map WORD
```

---

## Configure address-family unsuppress-route-map-name

unsuppress map name. This attribute is used to selectively leak more-specific routes to a particular neighbor.

Attribute Name: unsuppress-route-map-name

Attribute Type: string

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
                <unsuppress-route-map-name>WORD</unsuppress-route-map-name> <!--
operation="delete"-->
              </address-family>
            </address-families>
          </peer>
        </peers>
      </bgp-instance>
    </bgp-instances>
  </bgp>
```

### Command Syntax

```
neighbor WORD unsuppress-map WORD
```

---

## Configure access list identifier

Access List information

Attribute Name: access-list-identifier

Attribute Type: string

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              <distribute-list-filters>
                <distribute-list-filter>
                  <filter-direction>in</filter-direction>
                  <config>
                    <filter-direction>in</filter-direction>
                  </config>
                  <access-list-identifier>WORD</access-list-identifier>
                </distribute-list-filter>
              </distribute-list-filters>
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) distribute-list WORD (in|out)
```

## Configure filter direction

Access List information

Attribute Name: access-list-identifier

Attribute Type: string

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <address-families>
      <address-family>
        <safi>unicast</safi>
        <config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <afi>ipv4</afi>
        <distribute-list-filters>
        <distribute-list-filter>
          <filter-direction>in</filter-direction>
          <config>
            <filter-direction>in</filter-direction>
          </config>
          <access-list-identifier>WORD</access-list-identifier>
        </distribute-list-filter>
        </distribute-list-filters>
      </address-family>
    </address-families>
    </peer>
  </peers>
</bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD distribute-list WORD (in|out)
```

---

## Configure prefix list name

This attribute specifies a prefix list for filtering BGP advertisements for specified address-family. Filtering by prefix list matches the prefixes of routes with those listed in the prefix list. If there is a match, the route is used. An empty prefix list permits all prefixes. If a given prefix does not match any entries of a prefix list, the route is denied access. When multiple entries of a prefix list match a prefix, the entry with the smallest sequence number is considered to be a real match. The router begins the search at the top of the prefix list, with the sequence number 1. Once a match or deny

occurs, the router does not need to go through the rest of the prefix list. For efficiency the most common matches or denies are listed at the top.

Attribute Name: prefix-list-name

Attribute Type: string

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
              <prefix-list-filters>
                <prefix-list-filter>
                  <prefix-filter-direction>in</prefix-filter-direction>
                  <config>
                    <prefix-filter-direction>in</prefix-filter-direction>
                  </config>
                    <prefix-list-name>WORD</prefix-list-name>
                </prefix-list-filter>
              </prefix-list-filters>
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) prefix-list WORD (in|out)
```

---

## Configure prefix filter direction

This attribute specifies a prefix list for filtering BGP advertisements for specified address-family. Filtering by prefix list matches the prefixes of routes with those listed in the prefix list. If there is a match, the route is used. An empty prefix list permits all prefixes. If a given prefix does not match any entries of a prefix list, the route is denied access. When multiple entries of a prefix list match a prefix, the entry with the smallest sequence number is considered to be a real match. The router begins the search at the top of the prefix list, with the sequence number 1. Once a match or deny occurs, the router does not need to go through the rest of the prefix list. For efficiency the most common matches or denials are listed at the top.

Attribute Name: prefix-list-name

Attribute Type: string

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
                <afi>ipv4</afi>
              <prefix-list-filters>
                <prefix-list-filter>
                  <prefix-filter-direction>in</prefix-filter-direction>
                  <config>
                    <prefix-filter-direction>in</prefix-filter-direction>
                  </config>
                    <prefix-list-name>WORD</prefix-list-name>
                </prefix-list-filter>
              </prefix-list-filters>
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD prefix-list WORD (in|out)
```

---

## Configure as access list identifier

Access-list number. This attribute sets a BGP filter. This attribute specifies an access list filter on updates based on the BGP autonomous system paths. Each filter is an access list based on regular expressions

Attribute Name: as-access-list-identifier

Attribute Type: string

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
            <as-list-filters>
              <as-list-filter>
                <as-list-direction>in</as-list-direction>
                <config>
                  <as-list-direction>in</as-list-direction>
                </config>
                <as-access-list-identifier>WORD</as-access-list-identifier>
              </as-list-filter>
            </as-list-filters>
          </address-family>
        </address-families>
      </peer>
    </peers>
  </bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) filter-list WORD (in|out)
```

---

## Configure as list direction

Access-list number. This attribute sets a BGP filter. This attribute specifies an access list filter on updates based on the BGP autonomous system paths. Each filter is an access list based on regular expressions

Attribute Name: as-access-list-identifier

Attribute Type: string

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
            <as-list-filters>
              <as-list-filter>
                <as-list-direction>in</as-list-direction>
                <config>
                  <as-list-direction>in</as-list-direction>
                </config>
                <as-access-list-identifier>WORD</as-access-list-identifier>
              </as-list-filter>
            </as-list-filters>
          </address-family>
        </address-families>
      </peer>
    </peers>
  </bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD filter-list WORD (in|out)
```

---

## Configure route map name

Use this attribute to apply a route map to incoming or outgoing routes. This attribute filters updates and modifies attributes. A route map is applied to inbound or outbound updates. Only the routes that pass the route map are sent or accepted in updates.

Attribute Name: route-map-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              <route-map-filters>
                <route-map-filter>
                  <route-map-direction>in</route-map-direction>
                  <config>
                    <route-map-direction>in</route-map-direction>
                  </config>
                  <route-map-name>WORD</route-map-name>
                </route-map-filter>
              </route-map-filters>
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
```

---

```
</bgp>
```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) route-map WORD (in|out)
```

---

## Configure route map direction

Use this attribute to apply a route map to incoming or outgoing routes. This attribute filters updates and modifies attributes. A route map is applied to inbound or outbound updates. Only the routes that pass the route map are sent or accepted in updates.

Attribute Name: route-map-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
              <afi>ipv4</afi>
              <route-map-filters>
                <route-map-filter>
                  <route-map-direction>in</route-map-direction>
                  <config>
                    <route-map-direction>in</route-map-direction>
                  </config>
                  <route-map-name>WORD</route-map-name>
                </route-map-filter>
              </route-map-filters>
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

```

</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD route-map WORD (in|out)
```

---

## Configure peer port

Sets the BGP port number of a neighbor.

Attribute Name: peer-port

Attribute Type: uint16

Default Value: 179

Attribute Range: 0-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <peer-port>0</peer-port> <!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD port <0-65535>
```

---

## Configure min route advertisement interval

Sets a minimum route advertisement interval between the sending of BGP routing updates. To reduce the flapping of routes to internet, a minimum advertisement interval is set, so that the BGP routing updates are sent only per interval seconds.

Attribute Name: min-route-advertisement-interval

Attribute Type: uint32

Attribute Range: 0-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <min-route-advertisement-interval>0</min-route-advertisement-interval>
<!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD advertisement-interval <0-65535>
```

## Configure peer as origin interval

Configures the minimum interval between the sending of AS-origination routing updates.

Attribute Name: peer-as-origin-interval

Attribute Type: uint32

Attribute Range: 1-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <peer-as-origin-interval>1</peer-as-origin-interval> <!--
operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    </peers>
  </bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD as-origination-interval <1-65535>
```

---

## Configure collide established

Include a neighbor already in an established state for conflict resolution when a TCP connection collision is detected.

Attribute Name: collide-established

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          </collide-established><!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD collide-established
```

---

## Configure peer description

Associates a description with a neighbor. This helps in identifying a neighbor quickly. It is useful for an ISP that has multiple neighbor relationships.

Attribute Name: peer-description

Attribute Type: string

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>

```

```

<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <peers>
  <peer>
    <peer-address>A.B.C.D|X:X::X:X</peer-address>
    <config>
      <peer-address>BGP_IP_ADDR_T</peer-address>
    </config>
    <peer-description>LINE</peer-description> <!-- operation="delete"-->
  </peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD description LINE
```

---

## Configure disallow infinite hold time

Disallow configuration of infinite hold-time. A hold-time of 0 seconds from the peer (during exchange of open messages) or the user (during configuration) will be rejected.

Attribute Name: disallow-infinite-hold-time

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
      <peer>
        <peer-address>A.B.C.D|X:X::X:X</peer-address>
        <config>
          <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          </disallow-infinite-hold-time><!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD disallow-infinite-holdtime
```

---

## Configure disable capability negotiation

Disable the capability negotiation. It allows compatibility with older BGP versions that have no capability parameters used in open messages between peers.

Attribute Name: disable-capability-negotiation

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          </disable-capability-negotiation><!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD dont-capability-negotiate
```

---

## Configure enforce multi hop

Turns on the enforcement of eBGP neighbors perform multihop.

Attribute Name: enforce-multi-hop

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

```

    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      </enforce-multi-hop><!-- operation="delete"-->
    </peer>
  </peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD enforce-multihop
```

---

## Configure graceful shut

Use this attribute to start a graceful shutdown for the BGP session of the specified BGP neighbor. The BGP session for this neighbor is shut down after the graceful shutdown timer expires. If there is no alternate path available for traffic to flow prior the actual shutdown of the BGP session, this path is made available for 60 seconds or for configured time after which the path is no longer available and traffic is dropped.

Attribute Name: graceful-shut

Attribute Type: empty

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
      <peer>
        <peer-address>A.B.C.D|X:X::X:X</peer-address>
        <config>
          <peer-address>BGP_IP_ADDR_T</peer-address>
        </config>
        </graceful-shut><!-- operation="delete"-->
      </peer>
    </peers>
  </bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD g-shut
```

---

## Configure graceful shutdown timer

Configure the value of the graceful shutdown timer. After the timer expires, the BGP session initiated for graceful shutdown is shut down.

Attribute Name: graceful-shutdown-timer

Attribute Type: uint32

Attribute Range: 10-65535

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <graceful-shutdown-timer>10</graceful-shutdown-timer> <!--
operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD g-shut-timer <10-65535>
```

---

## Configure neighbor override capability

Override a capability negotiation result and use locally configured values.

Attribute Name: neighbor-override-capability

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
```

```

    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      </neighbor-override-capability><!-- operation="delete"-->
    </peer>
  </peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD override-capability
```

---

## Configure neighbor passive

Sets a BGP neighbor as passive.

Attribute Name: neighbor-passive

Attribute Type: empty

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          </neighbor-passive><!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD passive
```

---

## Configure peer restart time

Sets a different restart-time other than the global restart-time. This attribute takes precedence over the restart-time value specified using the grstSet attribute. The restart-time value is the maximum time that a graceful-restart neighbor waits to come back up after a restart. The default value is 120 seconds.

Attribute Name: peer-restart-time

Attribute Type: uint32

Attribute Range: 1-3600

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <peer-restart-time>1</peer-restart-time> <!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD restart-time <1-3600>
```

---

## Configure peer shutdown

Disables a neighbor administratively. It will terminate any active session for a specified neighbor and clear all related routing information. In case a peer group is specified for shutdown, a large number of peering sessions could be terminated.

Attribute Name: peer-shutdown

Attribute Type: empty

Attribute Name: peer-shutdown-description

Attribute Type: string

Attribute Range: 1-255

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
```

```

    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
      <peer>
        <peer-address>A.B.C.D|X:X::X:X</peer-address>
        <config>
          <peer-address>BGP_IP_ADDR_T</peer-address>
          <peer-shutdown-description>1</peer-shutdown-description> <!--
operation="delete"-->
        </config>
        </peer-shutdown><!-- operation="delete"-->
      </peer>
    </peers>
  </bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD shutdown (description LINE|)
```

---

## Configure neighbor strict capability match

Close the BGP connection if capability value does not match the remote peer.

Attribute Name: neighbor-strict-capability-match

Attribute Type: empty

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
      <peer>
        <peer-address>A.B.C.D|X:X::X:X</peer-address>
        <config>
          <peer-address>BGP_IP_ADDR_T</peer-address>
        </config>
        </neighbor-strict-capability-match><!-- operation="delete"-->
      </peer>
    </peers>
  </bgp-instance>
</bgp-instances>
</bgp>

```

---

## Command Syntax

```
neighbor WORD strict-capability-match
```

---

## Configure source identifier

Allows internal BGP sessions to use any operational interface for TCP connections. This attribute can be used in conjunction with any specified interface on the router. The loopback interface is the interface that is most commonly used with this attribute. The use of loopback interface eliminates a dependency and BGP does not have to rely on the availability of a particular interface for making TCP connections.

Attribute Name: source-identifier

Attribute Type: string

Default Value: NULL

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <source-identifier>WORD</source-identifier> <!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD update-source WORD
```

---

## Configure bgp version

Configure router to accept only a particular BGP version. By default, the system uses BGP version 4 and on request dynamically negotiates down to version 2. Disables the routers version-negotiation capability and forces the router to use only a specified version with the neighbor.

Attribute Name: bgp-version

Attribute Type: uint8

Default Value: 4

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <bgp-version>(4)</bgp-version> <!-- operation="delete"-->
    </peer>
  </peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

**Command Syntax**

```
neighbor WORD version (4)
```

**Configure enable ext opt param len**

Use this attribute for a specific peer to encode extended optional parameter length.

Attribute Name: enable-ext-opt-param-len

Attribute Type: empty

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      </enable-ext-opt-param-len><!-- operation="delete"-->
    </peer>
  </peers>
</bgp-instance>
</bgp-instances>

```

---

```
</bgp>
```

## Command Syntax

```
neighbor WORD extended-optional-param
```

---

## Configure peer connect interval

This attribute sets the timers for a specific BGP neighbor. Keepalive messages are sent by a router to inform another router that the BGP connection between the two is still active. The keepalive interval is the period of time between each keepalive message sent by the router. The holdtime interval is the time the router waits to receive a keepalive message and if it does not receive a message for this period it declares the neighbor dead.

Attribute Name: peer-connect-interval

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-65535

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <peer-connect-interval>1</peer-connect-interval> <!--
operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD timers connect <1-65535>
```

---

## Configure peer as

Autonomous system number of a neighbor. If the specified ASN matches the ASN number specified in the router bgp global configuration, the neighbor is identified as internal. If the ASN does no match, it is identified as external to the local AS.

Attribute Name: peer-as

Attribute Type: union

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <peer-as>-2</peer-as>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD remote-as internal
```

---

## Configure peer peer-as

Autonomous system number of a neighbor. If the specified ASN matches the ASN number specified in the router bgp global configuration, the neighbor is identified as internal. If the ASN does no match, it is identified as external to the local AS.

Attribute Name: peer-as

Attribute Type: union

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <peer-as>-1</peer-as>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD remote-as external
```

---

## Configure peer peer-as

Autonomous system number of a neighbor. If the specified ASN matches the ASN number specified in the router bgp global configuration, the neighbor is identified as internal. If the ASN does no match, it is identified as external to the local AS.

Attribute Name: peer-as

Attribute Type: union

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <peer-as>1</peer-as>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) remote-as <1-4294967295>
```

---

## Configure peer peer-as

Autonomous system number of a neighbor. If the specified ASN matches the ASN number specified in the router bgp global configuration, the neighbor is identified as internal. If the ASN does no match, it is identified as external to the local AS.

Attribute Name: peer-as

Attribute Type: union

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
      <peer>
        <peer-address>A.B.C.D|X:X::X:X</peer-address>
        <config>
          <peer-address>BGP_IP_ADDR_T</peer-address>
        </config>
        <peer-as>1</peer-as> <!-- operation="delete"-->
      </peer>
    </peers>
  </bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) remote-as <1-4294967295>
```

---

## Configure peer graceful-shut

Use this attribute to start a graceful shutdown for the BGP session of the specified BGP neighbor. The BGP session for this neighbor is shut down after the graceful shutdown timer expires. If there is no alternate path available for traffic to flow prior the actual shutdown of the BGP session, this path is made available for 60 seconds or for configured time after which the path is no longer available and traffic is dropped.

Attribute Name: graceful-shut

Attribute Type: empty

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
      <peer>
        <peer-address>A.B.C.D|X:X::X:X</peer-address>
        <config>
          <peer-address>BGP_IP_ADDR_T</peer-address>
          </graceful-shut><!-- operation="delete"-->
        </config>
      </peer>
    </peers>
  </bgp-instance>
</bgp-instances>
</bgp>
```

```

    </peers>
  </bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) g-shut
```

---

## Configure peer graceful-shutdown-timer

Configure the value of the graceful shutdown timer. After the timer expires, the BGP session initiated for graceful shutdown is shut down.

Attribute Name: graceful-shutdown-timer

Attribute Type: uint32

Attribute Range: 10-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
            </config>
            <graceful-shutdown-timer>10</graceful-shutdown-timer> <!--
operation="delete"-->
          </peer>
        </peers>
      </bgp-instance>
    </bgp-instances>
  </bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) g-shut-timer <10-65535>
```

---

## Configure peer peer-restart-time

Sets a different restart-time other than the global restart-time. This attribute takes precedence over the restart-time value specified using the grstSet attribute. The restart-time value is the maximum time that a graceful-restart neighbor waits to come back up after a restart. The default value is 120 seconds.

Attribute Name: peer-restart-time

Attribute Type: uint32

Attribute Range: 1-3600

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <peer-restart-time>1</peer-restart-time> <!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) restart-time <1-3600>
```

---

## Configure peer peer-description

Associates a description with a neighbor. This helps in identifying a neighbor quickly. It is useful for an ISP that has multiple neighbor relationships.

Attribute Name: peer-description

Attribute Type: string

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
            <peer-description>LINE</peer-description> <!-- operation="delete"-->
          </config>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

```

    </peers>
  </bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) description LINE
```

---

## Configure peer peer-connect-interval

This attribute sets the timers for a specific BGP neighbor. Keepalive messages are sent by a router to inform another router that the BGP connection between the two is still active. The keepalive interval is the period of time between each keepalive message sent by the router. The holdtime interval is the time the router waits to receive a keepalive message and if it does not receive a message for this period it declares the neighbor dead.

Attribute Name: peer-connect-interval

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <peer-connect-interval>1</peer-connect-interval> <!--
operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) timers connect <1-65535>
```

---

## Configure peer peer-as-origin-interval

Configures the minimum interval between the sending of AS-origination routing updates.

Attribute Name: peer-as-origin-interval

Attribute Type: uint32

Attribute Range: 1-65535

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <peer-as-origin-interval>1</peer-as-origin-interval> <!--
operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) as-origination-interval <1-65535>
```

## Configure peer min-route-advertisement-interval

Sets a minimum route advertisement interval between the sending of BGP routing updates. To reduce the flapping of routes to internet, a minimum advertisement interval is set, so that the BGP routing updates are sent only per interval seconds.

Attribute Name: min-route-advertisement-interval

Attribute Type: uint32

Attribute Range: 0-65535

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
```

```

        <peer-address>BGP_IP_ADDR_T</peer-address>
    </config>
    <min-route-advertisement-interval>0</min-route-advertisement-interval>
<!-- operation="delete"-->
    </peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) advertisement-interval <0-65535>
```

---

## Configure enable dynamic capability

Use this attribute to enable the dynamic capability for a specific peer. This attribute allows a BGP speaker to advertise or withdraw an address family capability to a peer in a non-disruptive manner.

Attribute Name: enable-dynamic-capability

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          </enable-dynamic-capability><!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) capability dynamic
```

---

## Configure peer collide-established

Include a neighbor already in an established state for conflict resolution when a TCP connection collision is detected.

Attribute Name: collide-established

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          </collide-established><!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) collide-established
```

---

## Configure peer source-identifier

Allows internal BGP sessions to use any operational interface for TCP connections. This attribute can be used in conjunction with any specified interface on the router. The loopback interface is the interface that is most commonly used with this attribute. The use of loopback interface eliminates a dependency and BGP does not have to rely on the availability of a particular interface for making TCP connections.

Attribute Name: source-identifier

Attribute Type: string

Default Value: NULL

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

```

        </config>
        <source-identifier>WORD</source-identifier> <!-- operation="delete"-->
    </peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) update-source WORD
```

---

## Configure peer enforce-multi-hop

Turns on the enforcement of eBGP neighbors perform multihop.

Attribute Name: enforce-multi-hop

Attribute Type: empty

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          </enforce-multi-hop><!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) enforce-multihop
```

---

## Configure peer neighbor-override-capability

Override a capability negotiation result and use locally configured values.

Attribute Name: neighbor-override-capability

Attribute Type: empty

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          </neighbor-override-capability><!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

**Command Syntax**

```
neighbor (A.B.C.D|X:X::X:X) override-capability
```

**Configure peer neighbor-strict-capability-match**

Close the BGP connection if capability value does not match the remote peer.

Attribute Name: neighbor-strict-capability-match

Attribute Type: empty

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          </neighbor-strict-capability-match><!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```
</bgp>
```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) strict-capability-match
```

---

## Configure peer disallow-infinite-hold-time

Disallow configuration of infinite hold-time. A hold-time of 0 seconds from the peer (during exchange of open messages) or the user (during configuration) will be rejected.

Attribute Name: disallow-infinite-hold-time

Attribute Type: empty

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          </disallow-infinite-hold-time><!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) disallow-infinite-holdtime
```

---

## Configure peer disable-capability-negotiation

Disable the capability negotiation. It allows compatibility with older BGP versions that have no capability parameters used in open messages between peers.

Attribute Name: disable-capability-negotiation

Attribute Type: empty

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
```

```

<config>
  <bgp-as>1</bgp-as>
</config>
<peers>
<peer>
  <peer-address>A.B.C.D|X:X::X:X</peer-address>
  <config>
    <peer-address>BGP_IP_ADDR_T</peer-address>
  </config>
  </disable-capability-negotiation><!-- operation="delete"-->
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) dont-capability-negotiate
```

---

## Configure peer neighbor-passive

Sets a BGP neighbor as passive.

Attribute Name: neighbor-passive

Attribute Type: empty

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      </neighbor-passive><!-- operation="delete"-->
    </peer>
    </peers>
  </bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) passive
```

---

## Configure peer shutdown description

Use this attribute to send shutdown communication message to inform peer the reason for the shutdown of the BGP session.

Attribute Name: peer-shutdown-description

Attribute Type: string

Attribute Range: 1-255

Attribute Name: peer-shutdown

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
            </peer-shutdown><!-- operation="delete"-->
          </config>
            <peer-shutdown-description>1</peer-shutdown-description> <!--
operation="delete"-->
          </peer>
        </peers>
      </bgp-instance>
    </bgp-instances>
  </bgp>
```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) shutdown (description LINE|)
```

---

## Configure peer peer-port

Sets the BGP port number of a neighbor.

Attribute Name: peer-port

Attribute Type: uint16

Default Value: 179

Attribute Range: 0-65535

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
```

```

<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
      <peer>
        <peer-address>A.B.C.D|X:X::X:X</peer-address>
        <config>
          <peer-address>BGP_IP_ADDR_T</peer-address>
        </config>
        <peer-port>0</peer-port> <!-- operation="delete"-->
      </peer>
    </peers>
  </bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) port <0-65535>
```

---

## Configure peer bgp-version

Configure router to accept only a particular BGP version. By default, the system uses BGP version 4 and on request dynamically negotiates down to version 2. Disables the routers version-negotiation capability and forces the router to use only a specified version with the neighbor.

Attribute Name: bgp-version

Attribute Type: uint8

Default Value: 4

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <bgp-version>(4)</bgp-version> <!-- operation="delete"-->
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```
</bgp-instances>  
</bgp>
```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) version (4)
```

---

## Configure peer enable-ext-opt-param-len

Use this attribute for a specific peer to encode extended optional parameter length.

Attribute Name: enable-ext-opt-param-len

Attribute Type: empty

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">  
<bgp-instances>  
  <bgp-instance>  
    <bgp-as>1</bgp-as>  
    <config>  
      <bgp-as>1</bgp-as>  
    </config>  
    <peers>  
    <peer>  
      <peer-address>A.B.C.D|X:X::X:X</peer-address>  
      <config>  
        <peer-address>BGP_IP_ADDR_T</peer-address>  
      </config>  
      </enable-ext-opt-param-len><!-- operation="delete"-->  
    </peer>  
  </peers>  
</bgp-instance>  
</bgp-instances>  
</bgp>
```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) extended-optional-param
```

---

## Configure peer tcp-adjust-mss

Use this attribute to set the BGP TCP MSS value of a neighbor.

Attribute Name: tcp-adjust-mss

Attribute Type: uint16

Attribute Range: 40-1440

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">  
<bgp-instances>  
  <bgp-instance>
```

```

    <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <peers>
  <peer>
    <peer-address>A.B.C.D|X:X::X:X</peer-address>
    <config>
      <peer-address>BGP_IP_ADDR_T</peer-address>
    </config>
    <tcp-adjust-mss>40</tcp-adjust-mss> <!-- operation="delete"-->
  </peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) tcp-mss <40-1440>
```

---

## Configure hold time

Use this attribute to globally set or reset the holdtime values for all the neighbors.

Attribute Name: hold-time

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: keep-alive

Attribute Type: uint16

Attribute Range: 0-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
      <peer>
        <peer-address>A.B.C.D|X:X::X:X</peer-address>
        <config>
          <peer-address>BGP_IP_ADDR_T</peer-address>
        </config>
        <timers>
        <config>
          <keep-alive>0</keep-alive>
          <hold-time>0</hold-time>
        </config>
      </peer>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        </config>
    </timers>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD timers <0-65535> <0-65535>
```

---

## Configure keep alive

Use this attribute to globally set or reset the keepalive values for all the neighbors

Attribute Name: keep-alive

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: hold-time

Attribute Type: uint16

Attribute Range: 0-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <timers>
            <config>
              <hold-time>0</hold-time>
              <keep-alive>0</keep-alive>
            </config>
          </timers>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) timers <0-65535> <0-65535>
```

---

## Configure enabled

Use this attribute to accept and attempt BGP connections to external peers on indirectly connected networks. Multihop is not established if the only route to the multihop peer is a default route. This avoids loop formation.

Attribute Name: enabled

Attribute Type: empty

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <ebgp-multihop>
            <config>
              </enabled>
            </config>
          </ebgp-multihop>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) ebgp-multihop
```

---

## Configure maximum hop count

Use this attribute to accept and attempt BGP connections to external peers on indirectly connected networks. Multihop is not established if the only route to the multihop peer is a default route. This avoids loop formation.

Attribute Name: enabled

Attribute Type: empty

Attribute Name: maximum-hop-count

Attribute Type: uint8

Attribute Range: 1-255

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <ebgp-multihop>
      <config>
        <maximum-hop-count>1</maximum-hop-count> <!-- operation="delete"-->
        </enabled><!-- operation="delete"-->
      </config>
    </ebgp-multihop>
    </peer>
  </peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) ebgp-multihop <1-255>
```

## Configure ebgp-multihop enabled

Use this attribute to accept and attempt BGP connections to external peers on indirectly connected networks. Multihop is not established if the only route to the multihop peer is a default route. This avoids loop formation.

Attribute Name: enabled

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>

```

```

        </config>
        <ebgp-multihop>
        <config>
            </enabled>
        </config>
    </ebgp-multihop>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD ebgp-multihop
```

---

## Configure ebgp-multihop enabled

Use this attribute to accept and attempt BGP connections to external peers on indirectly connected networks. Multihop is not established if the only route to the multihop peer is a default route. This avoids loop formation.

Attribute Name: enabled

Attribute Type: empty

Attribute Name: maximum-hop-count

Attribute Type: uint8

Attribute Range: 1-255

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <ebgp-multihop>
            <config>
              <maximum-hop-count>1</maximum-hop-count> <!-- operation="delete"-->
              </enabled><!-- operation="delete"-->
            </config>
          </ebgp-multihop>
        </peer>
      </peers>
    </bgp-instance>

```

```

</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD ebgp-multihop <1-255>
```

---

## Configure peer local as

Specifies an AS (autonomous system) number to use with BGP neighbor.

Attribute Name: peer-local-as

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <local-as>
            <local-as-list> <!-- operation="delete"-->
              <peer-local-as>1</peer-local-as>
            <config>
              <peer-local-as>1</peer-local-as>
            </config>
            </local-as-list>
          </local-as>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) local-as <1-4294967295>
```

---

## Configure local-as peer-local-as

Specifies an AS (autonomous system) number to use with BGP neighbor.

Attribute Name: peer-local-as

Attribute Type: uint32

Attribute Range: 1-4294967295

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <local-as>
            <local-as-list> <!-- operation="delete"-->
              <peer-local-as>1</peer-local-as>
            <config>
              <peer-local-as>1</peer-local-as>
            </config>
            </local-as-list>
          </local-as>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD local-as <1-4294967295>
```

---

## Configure no prepend local as

Specifies an AS (autonomous system) number to use with BGP neighbor.

Attribute Name: peer-local-as

Attribute Type: uint32

Attribute Range: 1-4294967295

Attribute Name: no-prepend-local-as

Attribute Type: empty

Attribute Name: replace-local-as

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
```

```

<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <peers>
    <peer>
      <peer-address>A.B.C.D|X:X::X:X</peer-address>
      <config>
        <peer-address>BGP_IP_ADDR_T</peer-address>
      </config>
      <local-as>
      <local-as-list>
        <peer-local-as>1</peer-local-as>
        <config>
          <peer-local-as>1</peer-local-as>
          </no-prepend-local-as>
          </replace-local-as>
        </config>
      </local-as-list>
    </local-as>
    </peer>
  </peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) local-as <1-4294967295> (no-prepend|) (replace-as|)
```

---

## Configure replace local as

Specifies an AS (autonomous system) number to use with BGP neighbor.

Attribute Name: peer-local-as

Attribute Type: uint32

Attribute Range: 1-4294967295

Attribute Name: no-prepend-local-as

Attribute Type: empty

Attribute Name: replace-local-as

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>

```

```

<config>
  <bgp-as>1</bgp-as>
</config>
<peers>
<peer>
  <peer-address>A.B.C.D|X:X::X:X</peer-address>
  <config>
    <peer-address>BGP_IP_ADDR_T</peer-address>
  </config>
  <local-as>
  <local-as-list>
    <peer-local-as>1</peer-local-as>
    <config>
      <peer-local-as>1</peer-local-as>
      </no-prepend-local-as>
      </replace-local-as>
    </config>
  </local-as-list>
</local-as>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD local-as <1-4294967295> (no-prepend|) (replace-as|)
```

---

## Configure admin status

Enable or disable AIGP

Attribute Name: admin-status

Attribute Type: enum (disable|enable)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
      <peer>
        <peer-address>A.B.C.D|X:X::X:X</peer-address>
        <config>
          <peer-address>BGP_IP_ADDR_T</peer-address>
        </config>
      <address-families>

```

```

    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
    </address-family>
    <afi>ipv4</afi>
  </address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) aigp (disable|enable)
```

## Configure aigp send med

Enable AIGP send multi exit discriminator.

Attribute Name: aigp-send-med

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        </config>
        <afi>ipv4</afi>
    <aigp>
    <config>
        </aigp-send-med><!-- operation="delete"-->
    </config>
    </aigp>
</address-family>
</address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) aigp send med
```

---

## Configure send cost community id

Send AIGP value in Cost community. And get the Community ID.

Attribute Name: send-cost-community-id

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: point-of-insertion

Attribute Type: enum (pre-bestpath|igp-cost)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <peers>
        <peer>
          <peer-address>A.B.C.D|X:X::X:X</peer-address>
          <config>
            <peer-address>BGP_IP_ADDR_T</peer-address>
          </config>
          <address-families>
            <address-family>
              <safi>unicast</safi>
              <config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
              </config>
            </address-family>
          </address-families>
        </peer>
      </peers>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        <afi>ipv4</afi>
        <aigp>
        <cost-community>
        <config>
            <point-of-insertion>pre-bestpath</point-of-insertion>
            <send-cost-community-id>0</send-cost-community-id>
        </config>
        </cost-community>
    </aigp>
</address-family>
</address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) aigp send cost-community <0-255> poi (pre-bestpath|igp-
cost)
```

---

## Configure enable transitive

Send AIGP value in Cost community and Enable Transitive Cost Community

Attribute Name: enable-transitive

Attribute Type: uint8

Attribute Name: send-cost-community-id

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: point-of-insertion

Attribute Type: enum (pre-bestpath|igp-cost)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
    <bgp-instance>
        <bgp-as>1</bgp-as>
        <config>
            <bgp-as>1</bgp-as>
        </config>
        <peers>
        <peer>
            <peer-address>A.B.C.D|X:X::X:X</peer-address>
            <config>
                <peer-address>BGP_IP_ADDR_T</peer-address>
            </config>
        </peer>
        </peers>
    </bgp-instance>
</bgp-instances>
</bgp>

```

```

    <address-family>
      <safi>unicast</safi>
      <config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <afi>ipv4</afi>
    </address-family>
    <aigp>
      <cost-community>
        <config>
          <send-cost-community-id>0</send-cost-community-id> <!--
operation="delete"-->
          <point-of-insertion>pre-bestpath</point-of-insertion> <!--
operation="delete"-->
          </enable-transitive><!-- operation="delete"-->
        </config>
      </cost-community>
    </aigp>
  </address-families>
</peer>
</peers>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) aigp send cost-community <0-255> poi (pre-bestpath|igp-
cost) transitive
```

---

## clear ip bgp \* (description LINE|)

Attribute Name: peer-reset-description

Attribute Type: string

Attribute Range: 1-255

### Netconf RPC payload

```

<ipi-bgp-peer_clear-ip-bgp-all-peer xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-bgp">
  <peer-reset-description>l</peer-reset-description>
</ipi-bgp-peer_clear-ip-bgp-all-peer>

```

### Command Syntax

```
clear ip bgp * (description LINE|)
```

---

## clear bgp \* I2vpn evpn soft (out|in|)

Attribute Name: soft-reconfig

Attribute Type: enum (out|in|soft-only)

**Netconf RPC payload**

```
<ipi-bgp-peer_clear-bgp-l2vpn-evpn-soft-all xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-bgp">
  <soft-reconfig>soft-only</soft-reconfig>
</ipi-bgp-peer_clear-bgp-l2vpn-evpn-soft-all>
```

**Command Syntax**

```
clear bgp * l2vpn evpn soft (out|in|)
```

**clear bgp <1-4294967295> l2vpn evpn soft (out|in|)**

Attribute Name: peer-as

Attribute Type: uint32

Attribute Range: 1-4294967295

Attribute Name: soft-reconfig

Attribute Type: enum (out|in|soft-only)

**Netconf RPC payload**

```
<ipi-bgp-peer_clear-bgp-remote-as-l2vpn-evpn-soft-all xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <peer-as>1</peer-as>
  <soft-reconfig>soft-only</soft-reconfig>
</ipi-bgp-peer_clear-bgp-remote-as-l2vpn-evpn-soft-all>
```

**Command Syntax**

```
clear bgp <1-4294967295> l2vpn evpn soft (out|in|)
```

**clear bgp (A.B.C.D|X:X::X:X|WORD) l2vpn evpn soft (out|in|)**

Attribute Name: peer-address

Attribute Type: union

Attribute Name: soft-reconfig

Attribute Type: enum (out|in|soft-only)

**Netconf RPC payload**

```
<ipi-bgp-peer_clear-bgp-peer-address-l2vpn-evpn-soft xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <peer-address>BGP_IP_ADDR_T</peer-address>
  <soft-reconfig>soft-only</soft-reconfig>
</ipi-bgp-peer_clear-bgp-peer-address-l2vpn-evpn-soft>
```

**Command Syntax**

```
clear bgp (A.B.C.D|X:X::X:X|WORD) l2vpn evpn soft (out|in|)
```

---

## IPI-BGP-ADDRESS-FAMILY-VRF

---

### Configure enable auto summary

Use this attribute to enable sending summarized routes by a BGP speaker to its peers. Auto-summary is used by a BGP router to advertise summarized routes to its peers. Auto-summary can be enabled if certain routes have already been advertised: in this case, configuring auto-summary advertises the summarized routes first, then corresponding non-summarized routes are withdrawn. If certain routes have already been advertised, and auto-summary is disabled, non-summarized routes are first advertised, then the corresponding summarized routes are withdrawn from all the connected peers.

Attribute Name: enable-auto-summary

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </enable-auto-summary><!-- operation="delete"-->
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
auto-summary
```

---

### Configure enable network igp sync

Use this attribute to enable IGP synchronization for BGP static network routes

Attribute Name: enable-network-igp-sync

Attribute Type: uint8

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </enable-network-igp-sync><!-- operation="delete"-->
    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
network synchronization
```

---

## Configure map name

Use this attribute to enable or disable suppression/modification of incoming BGP updates to IP RIB/FIB table installation. In a dedicated route reflector, all the routes it receives may not be required to be stored or only few selected routes need to be stored, because it may not lie in the data path. Table maps are particularly useful to attain this restriction. When map-name attribute is set, the route map referenced in the map-name attribute shall be used to set certain properties (such as the traffic index) of the routes for installation into the RIB. The route is always downloaded, regardless of whether it is permitted or denied by the route map.

Attribute Name: map-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
```

```

<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
</table-map>
<config>
  <map-name>WORD</map-name>
</config>
</table-map>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
table-map WORD
```

---

## Configure table map filter

When tableMapFilter attribute is given in the table map attribute, the route map referenced is used to control whether a BGP route is to be downloaded to the IP RIB (hence the filter). A BGP route is not downloaded to the RIB if it is denied by the route map.

Attribute Name: table-map-filter

Attribute Type: boolean

Attribute Name: map-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
      <address-family-vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
          <safi>unicast</safi>

```

```

        <afi>ipv4</afi>
    </config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
    <table-map>
    <config>
        <map-name>WORD</map-name> <!-- operation="delete"-->
        <table-map-filter>true</table-map-filter> <!-- operation="delete"--
>
        </config>
    </table-map>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
table-map WORD filter
```

---

## Configure local

Use this attribute to specify distance value for local routes

Attribute Name: local

Attribute Type: uint8

Attribute Range: 1-255

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <distances>
            <distance> <!-- operation="delete"-->
              <local>1</local>
            </config>

```

```

        <local>1</local>
        <ibgp>1</ibgp>
        <ebgp>1</ebgp>
    </config>
    <ibgp>1</ibgp>
    <ebgp>1</ebgp>
</distance>
</distances>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
distance bgp <1-255> <1-255> <1-255>
```

---

## Configure enable igp sync

Use this attribute to enable IGP synchronization of Internal BGP (iBGP) learned routes with the Internal Gateway Protocol (IGP) system. Synchronization is used when a BGP router should not advertise routes learned from iBGP neighbors, unless those routes are also present in an IGP (for example, OSPF). Synchronization may be enabled when all the routers in an autonomous system do not speak BGP, and the autonomous system is a transit for other autonomous systems.

Attribute Name: enable-igp-sync

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
      </enable-igp-sync><!-- operation="delete"-->
    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>

```

```
</bgp-instances>
</bgp>
```

## Command Syntax

```
synchronization
```

---

## Configure ebgp max path

Use this attribute to set the number of equal-cost multi-path (ECMP) routes for eBGP. You can install multiple BGP paths to the same destination to balance the load on the forwarding path

Attribute Name: ebgp-max-path

Attribute Type: int32

Attribute Range: 2-64

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <maximum-paths>
            <config>
              <ebgp-max-path>2</ebgp-max-path> <!-- operation="delete"-->
            </config>
          </maximum-paths>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
max-paths ebgp <2-64>
```

---

## Configure bgp as

Use this attribute to set the number of equal-cost multi-path (ECMP) routes for eBGP. You can install multiple BGP paths to the same destination to balance the load on the forwarding path

Attribute Name: ebgp-max-path

Attribute Type: int32

Attribute Range: 2-64

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <maximum-paths>
            <config>
              <ebgp-max-path>2</ebgp-max-path> <!-- operation="delete"-->
            </config>
          </maximum-paths>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
max-paths ebgp <2-64>
```

---

## Configure ibgp max path

Use this attribute to set the number of equal-cost multi-path (ECMP) routes for iBGP. You can install multiple BGP paths to the same destination to balance the load on the forwarding path.

Attribute Name: ibgp-max-path

Attribute Type: int32

Attribute Range: 2-64

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <maximum-paths>
      <config>
        <ibgp-max-path>2</ibgp-max-path> <!-- operation="delete"-->
      </config>
      </maximum-paths>
    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
max-paths ibgp <2-64>
```

---

## Configure optional as

Use this attribute to specify optional AS for BGP dynamic peer-group

Attribute Name: optional-as

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>

```

```

<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
</peer-groups>
<peer-group>
  <peer-group-tag>WORD</peer-group-tag>
  <config>
    <peer-group-tag>WORD</peer-group-tag>
  </config>
  <optional-as-lists>
  <optional-as-list> <!-- operation="delete"-->
    <optional-as>1</optional-as>
    <config>
      <optional-as>1</optional-as>
    </config>
  </optional-as-list>
</optional-as-lists>
</peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD optional-as <1-4294967295>
```

---

## Configure auth key encrypt

Use this attribute to configure the authentication key to specify if the password is to be encrypted or not.

Attribute Name: auth-key-encrypt

Attribute Type: enum (0|1)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
<peer-groups>
<peer-group>
  <peer-group-tag>WORD</peer-group-tag>
  <config>
    <peer-group-tag>WORD</peer-group-tag>
  </config>
  <bgp-passwords>
  <bgp-password>
    <password>WORD</password>
    <config>
      <password>WORD</password>
    </config>
    <auth-key-encrypt>1</auth-key-encrypt>
  </bgp-password>
</bgp-passwords>
</peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD authentication-key (0|1) WORD
```

## Configure afi

Use this attribute to configure the authentication key to specify if the password is to be encrypted or not.

Attribute Name: auth-key-encrypt

Attribute Type: enum (0|1)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

<address-family-vrfs>
<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
<peer-groups>
<peer-group>
  <peer-group-tag>WORD</peer-group-tag>
  <config>
    <peer-group-tag>WORD</peer-group-tag>
  </config>
  <bgp-passwords>
  <bgp-password>
    <password>WORD</password>
    <config>
      <password>WORD</password>
    </config>
    <auth-key-encrypt>2</auth-key-encrypt>
  </bgp-password>
</bgp-passwords>
</peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD authentication-key WORD
```

---

## Configure multipath relax

This attribute to specifies a BGP as-path relax configuration.

Attribute Name: multipath-relax

Attribute Type: uint8

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
  </bgp-instance>
</bgp-instances>
</bgp>

```

```

</config>
<address-family-vrfs>
<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
  </multipath-relax><!-- operation="delete"-->
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp bestpath as-path multipath-relax
```

---

## Configure graceful shutdown

Gracefully shut down all sessions of the AFI/SAFI belonging to the vrf under this router. The BGP graceful shutdown feature reduces packet loss during maintenance activity.

Attribute Name: graceful-shutdown

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
      </graceful-shutdown><!-- operation="delete"-->
    </address-family-vrf>
  </address-family-vrfs>

```

```

</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp g-shut
```

---

## Configure graceful shutdown capable

This attribute to enable the graceful shutdown capability

Attribute Name: graceful-shutdown-capable

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
      </graceful-shutdown-capable><!-- operation="delete"-->
    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp g-shut-capable
```

---

## Configure graceful shutdown local preference

This attribute sets the local preference of the router to use during graceful shutdown. The local preference value indicates the preferred path when there are multiple paths to the same destination in a single routing database. The path with a higher preference value is the preferred one. The preferred path is sent to all routers and access servers in the local autonomous system.

Attribute Name: graceful-shutdown-local-preference

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <graceful-shutdown-local-preference>0</graceful-shutdown-local-
preference> <!-- operation="delete"-->
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
bgp g-shut-local-preference <0-4294967295>
```

---

## Configure additional path select all

Use this attribute to select criteria to pick the paths

Attribute Name: additional-path-select-all

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
```

```

<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
  </additional-path-select-all><!-- operation="delete"-->
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp additional-paths select all
```

---

## Configure additional paths mode

Use this attribute to add additional paths in the BGP table

Attribute Name: additional-paths-mode

Attribute Type: bits (send-receive|receive|send)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
      <additional-paths-mode>send-receive</additional-paths-mode> <!--
operation="delete"-->
    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>
</bgp-instances>

```

---

```
</bgp>
```

## Command Syntax

```
bgp additional-paths (send-receive|receive|send)
```

---

## Configure additional paths best select count

Use this attribute to select best N paths

Attribute Name: additional-paths-best-select-count

Attribute Type: uint8

Attribute Range: 2-3

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
            <additional-paths-best-select-count>2</additional-paths-best-select-
count> <!-- operation="delete"-->
          </address-family-vrf>
        </address-family-vrfs>
      </bgp-instance>
    </bgp-instances>
  </bgp>
```

## Command Syntax

```
bgp additional-paths select best <2-3>
```

---

## Configure protocol type

Use this attribute to inject routes from one routing process into another. Redistribution is used by routing protocols to advertise routes that are learned by some other means, such as by another routing protocol or by static routes. Since all internal routes are dumped into BGP, careful filtering is applied to make sure that only routes to be advertised reach the internet, not everything. This attribute allows redistribution by injecting prefixes from one routing protocol into another routing protocol.

Attribute Name: protocol-type

Attribute Type: enum (kernel|connected|static|rip|ospf|isis|connected-host-routes)

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <route-redistribute-lists>
            <route-redistribute-list> <!-- operation="delete"-->
              <protocol-type>kernel</protocol-type>
              <config>
                <protocol-type>kernel</protocol-type>
              </config>
            </route-redistribute-list>
          </route-redistribute-lists>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
redistribute (kernel|connected|static|rip|ospf|isis|connected-host-routes)
```

---

## Configure redist route map name

Use this attribute to configure route map to be used for redistributed routes.

Attribute Name: redist-route-map-name

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
```

```

<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <address-family-vrfs>
  <address-family-vrf>
    <vrf-name>WORD</vrf-name>
    <config>
      <vrf-name>WORD</vrf-name>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  <route-redirect-lists>
  <route-redirect-list>
    <protocol-type>kernel</protocol-type>
    <config>
      <protocol-type>kernel</protocol-type>
    </config>
    <redist-route-map-name>WORD</redist-route-map-name> <!--
operation="delete"-->
  </route-redirect-list>
</route-redirect-lists>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```

redistribute (kernel|connected|static|rip|ospf|isis|connected-host-routes) route-
map WORD

```

---

## Configure ospf instance number

Use this attribute to inject routes from one routing process into another. Redistribution is used by routing protocols to advertise routes that are learned by some other means, such as by another routing protocol or by static routes. Since all internal routes are dumped into BGP, careful filtering is applied to make sure that only routes to be advertised reach the internet, not everything. This attribute allows redistribution by injecting prefixes from one routing protocol into another routing protocol.

Attribute Name: ospf-instance-number

Attribute Type: union

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>

```

```

<config>
  <bgp-as>1</bgp-as>
</config>
<address-family-vrfs>
<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
  <bgp-redistribute-ospfs>
  <bgp-redistribute-ospf> <!-- operation="delete"-->
    <ospf-instance-number>""</ospf-instance-number>
    <config>
      <ospf-instance-number>""</ospf-instance-number>
    </config>
  </bgp-redistribute-ospf>
</bgp-redistribute-ospfs>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
redistribute (ospf) (WORD|<1-65535>)
```

---

## Configure redistribute ospf route map

Use this attribute to specify route map to redistribute routes from OSPF into BGP.

Attribute Name: redistribute-ospf-route-map

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
  <address-family-vrfs>
  <address-family-vrf>
    <vrf-name>WORD</vrf-name>
    <config>

```

```

        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
    </config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
    <bgp-redistribute-ospfs>
    <bgp-redistribute-ospf>
        <ospf-instance-number>""</ospf-instance-number>
    </config>
        <ospf-instance-number>""</ospf-instance-number>
    </config>
        <redistribute-ospf-route-map>WORD</redistribute-ospf-route-map> <!--
- operation="delete"-->
    </bgp-redistribute-ospf>
    </bgp-redistribute-ospfs>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
redistribute (ospf) route-map WORD
```

---

## Configure peer as

This attribute specifies a neighbors autonomous system number. If the specified ASN matches the ASN number specified in the router bgp global configuration, the neighbor is identified as internal. If the ASN does not match, it is identified as external to the local AS.

Attribute Name: peer-as

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
      <address-family-vrf>
        <vrf-name>WORD</vrf-name>
      </config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

</config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
</vrf-peers>
</vrf-peer>
  <peer-address>CML_IP_ADDR_T</peer-address>
  <config>
    <peer-address>CML_IP_ADDR_T</peer-address>
  </config>
  <peer-as>1</peer-as>
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) remote-as <1-4294967295>
```

---

## Configure source identifier

This attribute allows internal BGP sessions to use any operational interface for TCP connections. Use this attribute in conjunction with any specified interface on the router. The loopback interface is the interface that is most commonly used with this attribute. The use of loopback interface eliminates a dependency and BGP does not have to rely on the availability of a particular interface for making TCP connections.

Attribute Name: source-identifier

Attribute Type: string

Default Value: NULL

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    <vrf-peers>
    <vrf-peer>
      <peer-address>CML_IP_ADDR_T</peer-address>
      <config>
        <peer-address>CML_IP_ADDR_T</peer-address>
      </config>
      <source-identifier>WORD</source-identifier> <!--
operation="delete"-->
    </vrf-peer>
  </vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor update-source WORD
```

---

## Configure bgp version

BGP Version. This attribute configures router to accept only a particular BGP version. By default, the system uses BGP version 4 and on request dynamically negotiates down to version 2. Using this attribute disables the routers version-negotiation capability and forces the router to use only a specified version with the neighbor.

Attribute Name: bgp-version

Attribute Type: uint8

Default Value: 4

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </address-family-vrf>
      </address-family-vrfs>
      <vrf-peers>
        <vrf-peer>
          <peer-address>CML_IP_ADDR_T</peer-address>

```

```

    <config>
      <peer-address>CML_IP_ADDR_T</peer-address>
    </config>
    <bgp-version>(4)</bgp-version> <!-- operation="delete"-->
  </vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor version (4)
```

---

## Configure peer connection interval

Connect timer value. This attribute sets the timers for a specific BGP neighbor. Keepalive messages are sent by a router to inform another router that the BGP connection between the two is still active. The keepalive interval is the period of time between each keepalive message sent by the router. The holdtime interval is the time the router waits to receive a keepalive message and if it does not receive a message for this period it declares the neighbor dead.

Attribute Name: peer-connection-interval

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
            <config>
              <peer-address>CML_IP_ADDR_T</peer-address>

```

```

        </config>
        <peer-connection-interval>1</peer-connection-interval> <!--
operation="delete"-->
        </vrf-peer>
    </vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor timers connect <1-65535>
```

---

## Configure hold time

Use this attribute to globally set or reset the holdtime values for all the neighbors.

Attribute Name: hold-time

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: keep-alive

Attribute Type: uint16

Attribute Range: 0-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>

```

```

        <timers>
        <config>
            <keep-alive>0</keep-alive>
            <hold-time>0</hold-time>
        </config>
    </timers>
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor timers <0-65535> <0-65535>
```

---

## Configure enforce multihop

This attribute turns on the enforcement of eBGP neighbors perform multihop.

Attribute Name: enforce-multihop

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
    <bgp-instance>
        <bgp-as>1</bgp-as>
        <config>
            <bgp-as>1</bgp-as>
        </config>
        <address-family-vrfs>
        <address-family-vrf>
            <vrf-name>WORD</vrf-name>
            <config>
                <vrf-name>WORD</vrf-name>
                <safi>unicast</safi>
                <afi>ipv4</afi>
            </config>
                <safi>unicast</safi>
                <afi>ipv4</afi>
        </vrf-peers>
        <vrf-peer>
            <peer-address>CML_IP_ADDR_T</peer-address>
            <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
            </config>
            </enforce-multihop><!-- operation="delete"-->
        </vrf-peer>
    </bgp-instance>
</bgp-instances>
</bgp>

```

```

    </vrf-peers>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor enforce-multihop
```

---

## Configure peer shutdown

This attribute disables a neighbor administratively. Use this attribute to terminate any active session for a specified neighbor and clear all related routing information. In case a peer group is specified for shutdown, a large number of peering sessions could be terminated.

Attribute Name: peer-shutdown

Attribute Type: uint8

Attribute Name: peer-shutdown-description

Attribute Type: string

Attribute Range: 1-255

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
                <peer-shutdown-description>1</peer-shutdown-description> <!--
operation="delete"-->
              </config>
            </peer-shutdown><!-- operation="delete"-->
            </vrf-peer>
          </vrf-peers>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    </vrf-peer>
  </vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor shutdown (description LINE|)
```

---

## Configure peer group tag

Creates a peer group. Neighbors with the same update policies are grouped into peer groups. This facilitates the updates of various policies, such as distribute and filter lists. The peer group is then configured easily with any of the neighbor attributes. Any changes made to the peer group affect all members.

Attribute Name: peer-group-tag

Attribute Type: string

Attribute Name: peer-group-range

Attribute Type: union

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <peer-groups>
            <peer-group> <!-- operation="delete"-->
              <peer-group-tag>WORD</peer-group-tag>
              <config>
                <peer-group-tag>WORD</peer-group-tag>
                <peer-group-range>0</peer-group-range>
              </config>
            </peer-group>
          </peer-groups>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD peer-group
```

---

## Configure peer group range

this attribute creates a Dynamic peer group for address family. IPv4/IPv6 prefix range Must be specified to create dynamic peer group.

Attribute Name: peer-group-range

Attribute Type: union

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        <peer-groups>
          <peer-group>
            <peer-group-tag>WORD</peer-group-tag>
            <config>
              <peer-group-tag>WORD</peer-group-tag>
            </config>
            <peer-group-range>A.B.C.D/M</peer-group-range>
          </peer-group>
        </peer-groups>
      </address-family-vrf>
    </address-family-vrfs>
  </bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD peer-group range A.B.C.D/M
```

---

## Configure safi

this attribute creates a Dynamic peer group for address family. IPv4/IPv6 prefix range Must be specified to create dynamic peer group.

Attribute Name: peer-group-range

Attribute Type: union

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
          <peer-groups>
            <peer-group>
              <peer-group-tag>WORD</peer-group-tag>
              <config>
                <peer-group-tag>WORD</peer-group-tag>
              </config>
              <peer-group-range> (X:X::X:X/M) </peer-group-range>
            </peer-group>
          </peer-groups>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD peer-group range (X:X::X:X/M)
```

---

## Configure group limit

Use this attribute to specify max number of peers in a dynamic peer-group for address family

Attribute Name: group-limit

Attribute Type: uint8

Attribute Range: 1-200

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
      <address-family-vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <peer-groups>
      <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
          <peer-group-tag>WORD</peer-group-tag>
        </config>
        <group-limit>1</group-limit> <!-- operation="delete"-->
      </peer-group>
    </peer-groups>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD limit <1-200>
```

---

## Configure vrf name

This attribute specifies a neighbors autonomous system number. If the specified ASN matches the ASN number specified in the router bgp global configuration, the neighbor is identified as internal. If the ASN does not match, it is identified as external to the local AS.

Attribute Name: peer-as

Attribute Type: uint32

Attribute Range: 1-4294967295

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
      <address-family-vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <peer-groups>
      <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
          <peer-group-tag>WORD</peer-group-tag>
        </config>
        <peer-as>1</peer-as> <!-- operation="delete"-->
      </peer-group>
    </peer-groups>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD remote-as <1-4294967295>
```

---

## Configure peer-group source-identifier

This attribute allows internal BGP sessions to use any operational interface for TCP connections. Use this attribute in conjunction with any specified interface on the router. The loopback interface is the interface that is most commonly used with this attribute. The use of loopback interface eliminates a dependency and BGP does not have to rely on the availability of a particular interface for making TCP connections.

Attribute Name: source-identifier

Attribute Type: string

Default Value: NULL

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
      <address-family-vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <peer-groups>
      <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
          <peer-group-tag>WORD</peer-group-tag>
        </config>
        <source-identifier>WORD</source-identifier> <!--
operation="delete"-->
      </peer-group>
    </peer-groups>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD update-source WORD
```

---

## Configure peer-group bgp-version

**BGP Version.** This attribute configures router to accept only a particular BGP version. By default, the system uses BGP version 4 and on request dynamically negotiates down to version 2. Using this attribute disables the routers version-negotiation capability and forces the router to use only a specified version with the neighbor.

Attribute Name: bgp-version

Attribute Type: uint8

Default Value: 4

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <peer-groups>
      <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
          <peer-group-tag>WORD</peer-group-tag>
        </config>
        <bgp-version>(4)</bgp-version> <!-- operation="delete"-->
      </peer-group>
    </peer-groups>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD version (4)
```

## Configure peer-group peer-connection-interval

Connect timer value. This attribute sets the timers for a specific BGP neighbor. Keepalive messages are sent by a router to inform another router that the BGP connection between the two is still active. The keepalive interval is the period of time between each keepalive message sent by the router. The holdtime interval is the time the router waits to receive a keepalive message and if it does not receive a message for this period it declares the neighbor dead.

Attribute Name: peer-connection-interval

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-65535

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <peer-groups>
      <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
          <peer-group-tag>WORD</peer-group-tag>
        </config>
        <peer-connection-interval>1</peer-connection-interval> <!--
operation="delete"-->
      </peer-group>
    </peer-groups>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD timers connect <1-65535>
```

---

## Configure keep alive

Use this attribute to globally set or reset the holdtime values for all the neighbors.

Attribute Name: hold-time

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: keep-alive

Attribute Type: uint16

Attribute Range: 0-65535

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <peer-groups>
      <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
          <peer-group-tag>WORD</peer-group-tag>
        </config>
        <timers>
        <config>
          <keep-alive>0</keep-alive>
          <hold-time>0</hold-time>
        </config>
        </timers>
      </peer-group>
    </peer-groups>
    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

**Command Syntax**

```
neighbor WORD timers <0-65535> <0-65535>
```

**Configure peer-group enforce-multihop**

This attribute turns on the enforcement of eBGP neighbors perform multihop.

Attribute Name: enforce-multihop

Attribute Type: uint8

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">

```

```

<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      </enforce-multihop><!-- operation="delete"-->
    </peer-group>
  </peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD enforce-multihop
```

---

## Configure peer shutdown description

This attribute disables a neighbor administratively. Use this attribute to terminate any active session for a specified neighbor and clear all related routing information. In case a peer group is specified for shutdown, a large number of peering sessions could be terminated.

Attribute Name: peer-shutdown

Attribute Type: uint8

Attribute Name: peer-shutdown-description

Attribute Type: string

Attribute Range: 1-255

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>

```

```

<bgp-instance>
  <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
  <address-family-vrfs>
  <address-family-vrf>
    <vrf-name>WORD</vrf-name>
    <config>
      <vrf-name>WORD</vrf-name>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  <peer-groups>
  <peer-group>
    <peer-group-tag>WORD</peer-group-tag>
    <config>
      <peer-group-tag>WORD</peer-group-tag>
      <peer-shutdown-description>1</peer-shutdown-description> <!--
operation="delete"-->
    </config>
    </peer-shutdown><!-- operation="delete"-->
  </peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD shutdown (description LINE|)
```

---

## Configure enabled

Use this attribute to accept and attempt BGP connections to external peers on indirectly connected networks. Multihop is not established if the only route to the multihop peer is a default route. This avoids loop formation.

Attribute Name: enabled

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>

```

```

</config>
<address-family-vrfs>
<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
  <peer-groups>
  <peer-group>
    <peer-group-tag>WORD</peer-group-tag>
    <config>
      <peer-group-tag>WORD</peer-group-tag>
    </config>
    <ebgp-multihop>
    <config>
      </enabled>
    </config>
  </ebgp-multihop>
  </peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD ebgp-multihop
```

---

## Configure maximum hop count

Use this attribute to accept and attempt BGP connections to external peers on indirectly connected networks. Multihop is not established if the only route to the multihop peer is a default route. This avoids loop formation.

Attribute Name: enabled

Attribute Type: empty

Attribute Name: maximum-hop-count

Attribute Type: uint8

Attribute Range: 1-255

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>

```

```

<config>
  <bgp-as>1</bgp-as>
</config>
<address-family-vrfs>
<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
<peer-groups>
<peer-group>
  <peer-group-tag>WORD</peer-group-tag>
  <config>
    <peer-group-tag>WORD</peer-group-tag>
  </config>
  <ebgp-multihop>
  <config>
    <maximum-hop-count>1</maximum-hop-count> <!--
operation="delete"-->
    </enabled><!-- operation="delete"-->
  </config>
</ebgp-multihop>
</peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD ebgp-multihop <1-255>
```

---

## Configure neighbor passive

Use this attribute to set a BGP neighbor as passive.

Attribute Name: neighbor-passive

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
  <config>

```

```

    <bgp-as>1</bgp-as>
  </config>
</address-family-vrfs>
<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
  <peer-groups>
  <peer-group>
    <peer-group-tag>WORD</peer-group-tag>
    <config>
      <peer-group-tag>WORD</peer-group-tag>
    </config>
    </neighbor-passive><!-- operation="delete"-->
  </peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD passive
```

---

## Configure disable capability negotiation

Use this attribute to disable capability negotiation. The capability negotiation is performed by default. This attribute is used to allow compatibility with older BGP versions that have no capability parameters used in open messages between peers.

Attribute Name: disable-capability-negotiation

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
      <address-family-vrf>
        <vrf-name>WORD</vrf-name>

```

```

    <config>
      <vrf-name>WORD</vrf-name>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  <peer-groups>
  <peer-group>
    <peer-group-tag>WORD</peer-group-tag>
    <config>
      <peer-group-tag>WORD</peer-group-tag>
    </config>
    </disable-capability-negotiation><!-- operation="delete"-->
  </peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD dont-capability-negotiate
```

---

## Configure enable dynamic capability

Use this attribute to enable the dynamic capability for a specific peer. This attribute allows a BGP speaker to advertise or withdraw an address family capability to a peer in a non-disruptive manner.

Attribute Name: enable-dynamic-capability

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    <afi>ipv4</afi>
  <peer-groups>
  <peer-group>
    <peer-group-tag>WORD</peer-group-tag>
  <config>
    <peer-group-tag>WORD</peer-group-tag>
  </config>
    </enable-dynamic-capability><!-- operation="delete"-->
  </peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD capability dynamic
```

---

## Configure min route advertisement interval

Minimum route advertisement interval. Sets minimum interval between the sending of BGP routing updates. To reduce the flapping of routes to internet, a minimum advertisement interval is set, so that the BGP routing updates are sent only per interval seconds. BGP dampening can also be used to control the effects of flapping routes.

Attribute Name: min-route-advertisement-interval

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <min-route-advertisement-interval>0</min-route-advertisement-
interval> <!-- operation="delete"-->
    </peer-group>
  </peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD advertisement-interval <0-65535>
```

---

## Configure peer as origin interval

Time interval. This attribute adjust the interval of sending AS origination routing updates. This attribute is used to change the minimum interval between the sending of AS-origination routing updates.

Attribute Name: peer-as-origin-interval

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <peer-groups>
            <peer-group>
              <peer-group-tag>WORD</peer-group-tag>
            </peer-group>
          </peer-groups>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        <peer-group-tag>WORD</peer-group-tag>
    </config>
    <peer-as-origin-interval>1</peer-as-origin-interval> <!--
operation="delete"-->
    </peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD as-origination-interval <1-65535>
```

---

## Configure neighbor as override

Use this attribute to configure a PE router to override the Autonomous System Number (ASN) of a site with the ASN of a provider. BGP normally ignores the routes from the same AS. However, this attribute is used to override the customer's ASN in BGP, so that the customer CE accepts and installs routes from the same AS. Typically, this attribute is used when Customer Edge (CE) routers have the same ASN in some or all sites. As per BGP requirement, a BGP speaker rejects a route that has the same ASN as itself, in the AS\_PATH attribute. Thus the CE routers having the same ASN do not accept routes from each other. Set neighborAsOverrideAf attribute on the PE router removes the CE neighbors ASN from the AS\_PATH attribute allowing CE routers with the same ASN to accept routes from each other.

Attribute Name: neighbor-as-override

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <peer-groups>
            <peer-group>
              <peer-group-tag>WORD</peer-group-tag>
              <config>
                <peer-group-tag>WORD</peer-group-tag>

```

```

        </config>
        </neighbor-as-override><!-- operation="delete"-->
    </peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD as-override
```

---

## Configure peer description

Use this attribute to associate a description with a neighbor. This attribute helps in identifying a neighbor quickly. It is useful for an ISP that has multiple neighbor relationships.

Attribute Name: peer-description

Attribute Type: string

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <peer-description>LINE</peer-description> <!-- operation="delete"-->
    </peer-group>
  </peer-groups>
</address-family-vrf>

```

```

</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD description LINE
```

---

## Configure peer restart time

This attribute sets a different restart-time other than the global restart-time. This attribute takes precedence over the restart-time value specified using the graceful-restart-set attribute. The restart-time value is the maximum time that a graceful-restart neighbor waits to come back up after a restart. The default value is 120 seconds.

Attribute Name: peer-restart-time

Attribute Type: uint32

Attribute Range: 1-3600

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <peer-groups>
      <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
          <peer-group-tag>WORD</peer-group-tag>
        </config>
        <peer-restart-time>1</peer-restart-time> <!-- operation="delete"-->
      </peer-group>
    </peer-groups>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD restart-time <1-3600>
```

---

## Configure site origin identifier

Use this attribute to enable the site-of-origin (SOO) feature. If the customer AS is multi-homed to the ISP, this attribute ensures that the PE does not advertise the routes back to the same AS.

Attribute Name: site-origin-identifier

Attribute Type: string

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <peer-groups>
            <peer-group>
              <peer-group-tag>WORD</peer-group-tag>
              <config>
                <peer-group-tag>WORD</peer-group-tag>
              </config>
              <site-origin-identifier>AS:nn_or_IP:nn</site-origin-identifier> <!--
- operation="delete"-->
            </peer-group>
          </peer-groups>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD soo AS:nn_or_IP:nn
```

---

## Configure graceful shut

Use this attribute to start a graceful shutdown for the BGP session of the specified BGP neighbor. The BGP session for this neighbor is shut down after the graceful shutdown timer expires. If there is no alternate path available for traffic to flow prior the actual shutdown of the BGP session, this path is made available for 60 seconds or for configured time after which the path is no longer available and traffic is dropped.

Attribute Name: graceful-shut

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          </graceful-shut><!-- operation="delete"-->
        </peer-group>
      </peer-groups>
    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD g-shut
```

---

## Configure graceful shut timer

Use this attribute to configure the value of the graceful shutdown timer. After the timer expires, the BGP session initiated for graceful shutdown is shut down.

Attribute Name: graceful-shut-timer

Attribute Type: uint32

Attribute Range: 10-65535

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
      <address-family-vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <peer-groups>
      <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
          <peer-group-tag>WORD</peer-group-tag>
        </config>
        <graceful-shut-timer>10</graceful-shut-timer> <!--
operation="delete"-->
      </peer-group>
    </peer-groups>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD g-shut-timer <10-65535>
```

---

## Configure bgp port

The BGP port number of a neighbor

Attribute Name: bgp-port

Attribute Type: uint16

Default Value: 179

Attribute Range: 0-65535

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <bgp-port>0</bgp-port> <!-- operation="delete"-->
    </peer-group>
  </peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

**Command Syntax**

```
neighbor WORD port <0-65535>
```

**Configure enable ext opt param len**

Use this attribute for a specific peer to encode extended optional parameter length.

Attribute Name: enable-ext-opt-param-len

Attribute Type: uint8

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>

```

```

</config>
<address-family-vrfs>
<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
  <peer-groups>
  <peer-group>
    <peer-group-tag>WORD</peer-group-tag>
    <config>
      <peer-group-tag>WORD</peer-group-tag>
    </config>
    </enable-ext-opt-param-len><!-- operation="delete"-->
  </peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD extended-optional-param
```

---

## Configure peer-group additional-paths-mode

Adds additional paths in the BGP table

Attribute Name: additional-paths-mode

Attribute Type: bits (send-receive|receive|send|disable)

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>

```

```

    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
  <peer-groups>
  <peer-group>
    <peer-group-tag>WORD</peer-group-tag>
    <config>
      <peer-group-tag>WORD</peer-group-tag>
    </config>
    <additional-paths-mode>send-receive</additional-paths-mode> <!--
operation="delete"-->
  </peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD additional-paths (send-receive|receive|send|disable)
```

---

## Configure peer-group additional-path-select-all

Attribute to select advertise additional path

Attribute Name: additional-path-select-all

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </peer-groups>
        <peer-group>

```

```

        <peer-group-tag>WORD</peer-group-tag>
    </config>
        <peer-group-tag>WORD</peer-group-tag>
    </config>
    </additional-path-select-all><!-- operation="delete"-->
</peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD advertise additional-paths all
```

---

## Configure peer-group additional-paths-best-select-count

Attribute to select best advertise additional path

Attribute Name: additional-paths-best-select-count

Attribute Type: uint8

Attribute Range: 2-3

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <peer-groups>
            <peer-group>
              <peer-group-tag>WORD</peer-group-tag>
              <config>
                <peer-group-tag>WORD</peer-group-tag>
              </config>
                <additional-paths-best-select-count>2</additional-paths-best-
select-count> <!-- operation="delete"-->

```

```

        </peer-group>
    </peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD advertise additional-paths best <2-3>
```

---

## Configure tcp adjust mss

Use this attribute to set the BGP TCP MSS value of a neighbor.

Attribute Name: tcp-adjust-mss

Attribute Type: uint16

Attribute Range: 40-1440

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <peer-groups>
      <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
          <peer-group-tag>WORD</peer-group-tag>
        </config>
          <tcp-adjust-mss>40</tcp-adjust-mss> <!-- operation="delete"-->
        </peer-group>
      </peer-groups>
    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>
</bgp-instances>

```

---

```
</bgp>
```

## Command Syntax

```
neighbor WORD tcp-mss <40-1440>
```

---

## Configure enable peer bfd

Enable bidirectional forwarding detection (BFD) for the BGP peer

Attribute Name: enable-peer-bfd

Attribute Type: uint8

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <peer-groups>
            <peer-group>
              <peer-group-tag>WORD</peer-group-tag>
              <config>
                <peer-group-tag>WORD</peer-group-tag>
              </config>
                </enable-peer-bfd><!-- operation="delete"-->
              </peer-group>
            </peer-groups>
          </address-family-vrf>
        </address-family-vrfs>
      </bgp-instance>
    </bgp-instances>
  </bgp>
```

## Command Syntax

```
neighbor WORD fall-over bfd
```

---

## Configure enable peer bfd multihop

Enable bidirectional forwarding detection (BFD) for the BGP peer with multihop

Attribute Name: enable-peer-bfd-multihop

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        <peer-groups>
          <peer-group>
            <peer-group-tag>WORD</peer-group-tag>
            <config>
              <peer-group-tag>WORD</peer-group-tag>
            </config>
            </enable-peer-bfd-multihop><!-- operation="delete"-->
          </peer-group>
        </peer-groups>
      </address-family-vrf>
    </address-family-vrfs>
  </bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD fall-over bfd multihop
```

---

## Configure activate

Activate/Deactivate neighbor. This attribute enables or disables the exchange of AF information with a neighboring router.

Attribute Name: activate

Attribute Type: uint8

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <peer-groups>
      <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
          <peer-group-tag>WORD</peer-group-tag>
        </config>
          </activate><!-- operation="delete"-->
        </peer-group>
      </peer-groups>
    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

**Command Syntax**

```
neighbor WORD activate
```

**Configure default peer route map name**

This attribute allows a BGP local router to send the default route 0.0.0.0 to a neighbor for use as a default route for specified address-family.

Attribute Name: default-peer-route-map-name

Attribute Type: uint8

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>

```

```

    <bgp-as>1</bgp-as>
</config>
<address-family-vrfs>
<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
<peer-groups>
<peer-group>
  <peer-group-tag>WORD</peer-group-tag>
  <config>
    <peer-group-tag>WORD</peer-group-tag>
  </config>
  </default-peer-route-map-name><!-- operation="delete"-->
</peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD default-originate
```

---

## Configure peer route map orig name

This attribute configures route map to be used for a BGP local router to send the default route 0.0.0.0 to a neighbor for use as a default route for specified address-family. This attribute can be used with standard or extended access lists.

Attribute Name: peer-route-map-orig-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>

```

```

    <config>
      <vrf-name>WORD</vrf-name>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  <peer-groups>
  <peer-group>
    <peer-group-tag>WORD</peer-group-tag>
    <config>
      <peer-group-tag>WORD</peer-group-tag>
    </config>
    <peer-route-map-orig-name>WORD</peer-route-map-orig-name> <!--
operation="delete"-->
  </peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD default-originate route-map WORD
```

---

## Configure weight

This attribute specifies a weight value, for specified address-family, to all routes learned from a neighbor for specified address-family. The route with the highest weight gets preference when the same prefix is learned from more than one peer. Unlike the local-preference attribute, the weight attribute is relevant only to the local router. When the weight is set for a peer group, all members of the peer group get the same weight. This attribute can also be used to assign a different weight to an individual peer-group member. When an individually-configured weight of a peer-group member is removed, its weight is reset to its peer groups weight.

Attribute Name: weight

Attribute Type: uint16

Default Value: 0

Attribute Range: 0-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>

```

```

    <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
<peer-groups>
<peer-group>
  <peer-group-tag>WORD</peer-group-tag>
  <config>
    <peer-group-tag>WORD</peer-group-tag>
  </config>
  <weight>0</weight> <!-- operation="delete"-->
</peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD weight <0-65535>
```

---

## Configure peer-group weight

This attribute specifies a weight value, for specified address-family, to all routes learned from a neighbor for specified address-family. The route with the highest weight gets preference when the same prefix is learned from more than one peer. Unlike the local-preference attribute, the weight attribute is relevant only to the local router. When the weight is set for a peer group, all members of the peer group get the same weight. This attribute can also be used to assign a different weight to an individual peer-group member. When an individually-configured weight of a peer-group member is removed, its weight is reset to its peer groups weight.

Attribute Name: weight

Attribute Type: uint16

Default Value: 0

Attribute Range: 0-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
<peer-groups>
<peer-group>
  <peer-group-tag>WORD</peer-group-tag>
  <config>
    <peer-group-tag>WORD</peer-group-tag>
  </config>
  <weight>0</weight> <!-- operation="delete"-->
</peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD weight <0-65535>
```

---

## Configure peer route reflector

This attribute configures the router as a BGP route reflector and configure the specified neighbor as its client for specified address-family. Route reflectors are a solution for the explosion of iBGP peering within an autonomous system. By route reflection the number of iBGP peers within an AS is reduced. Use this attribute to configure the local router as the route reflector and specify neighbors as its client. An AS can have more than one route reflector. One route reflector treats the other route reflector as another iBGP speaker.

Attribute Name: peer-route-reflector

Attribute Type: uint8

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>

```

```

        <safi>unicast</safi>
        <afi>ipv4</afi>
    </config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
    <peer-groups>
    <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
            <peer-group-tag>WORD</peer-group-tag>
        </config>
        </peer-route-reflector><!-- operation="delete"-->
    </peer-group>
    </peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD route-reflector-client
```

---

## Configure peer remove private as

This attribute removes the private Autonomous System (AS) number from outbound updates. Private AS numbers are not advertised to the Internet. This attribute is used with external BGP peers only. The router removes the AS numbers only if the update includes private AS numbers. If the update includes both private and public AS numbers, the system treats it as an error.

Attribute Name: peer-remove-private-as

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
    <bgp-instance>
        <bgp-as>1</bgp-as>
        <config>
            <bgp-as>1</bgp-as>
        </config>
        <address-family-vrfs>
        <address-family-vrf>
            <vrf-name>WORD</vrf-name>
            <config>
                <vrf-name>WORD</vrf-name>
                <safi>unicast</safi>
                <afi>ipv4</afi>
            </config>
            <safi>unicast</safi>

```

```

    <afi>ipv4</afi>
  <peer-groups>
  <peer-group>
    <peer-group-tag>WORD</peer-group-tag>
  <config>
    <peer-group-tag>WORD</peer-group-tag>
  </config>
    </peer-remove-private-as><!-- operation="delete"-->
  </peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD remove-private-AS
```

---

## Configure no send community

This attribute specifies if a community attribute should be sent to a BGP neighbor for specified address-family. The community attribute groups destinations in a certain community and applies routing decisions according to those communities. By default, both standard and extended community attributes are sent to a neighbor

Attribute Name: no-send-community

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
    <config>

```

```

        <peer-group-tag>WORD</peer-group-tag>
    </config>
    </no-send-community><!-- operation="delete"-->
</peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
no neighbor WORD send-community
```

---

## Configure no send community type

This attribute specifies the type of community attribute to be sent to a BGP neighbor.

Attribute Name: no-send-community-type

Attribute Type: bits (both|standard|extended|large)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <peer-groups>
      <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
          <peer-group-tag>WORD</peer-group-tag>
        </config>
        <no-send-community-type>both</no-send-community-type> <!--
operation="delete"-->
      </peer-group>
    </peer-groups>
  </address-family-vrf>

```

```

</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
no neighbor WORD send-community (both|standard|extended|large)
```

---

## Configure neighbor attribute unchanged

This attribute advertises unchanged BGP AS path, next hop and med to the specified neighbor.

Attribute Name: neighbor-attribute-unchanged

Attribute Type: bits (as-path|next-hop|med)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <neighbor-attribute-unchanged>14</neighbor-attribute-unchanged> <!--
- operation="delete"-->
    </peer-group>
  </peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD attribute-unchanged
```

---

## Configure peer-group neighbor-attribute-unchanged

This attribute advertises unchanged BGP AS path, next hop and med to the specified neighbor.

Attribute Name: neighbor-attribute-unchanged

Attribute Type: bits (as-path|next-hop|med)

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
          <peer-groups>
            <peer-group>
              <peer-group-tag>WORD</peer-group-tag>
              <config>
                <peer-group-tag>WORD</peer-group-tag>
              </config>
              <neighbor-attribute-unchanged>as-path</neighbor-attribute-
unchanged> <!-- operation="delete"-->
            </peer-group>
          </peer-groups>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD attribute-unchanged {as-path|next-hop|med}
```

---

## Configure orf prefix capability

This attribute enables Outbound Router Filtering (ORF), and advertise the ORF capability to its neighbors. The ORFs send and receive capabilities to lessen the number of updates exchanged between neighbors. By filtering updates, this option minimizes generating and processing of updates. The two routers exchange updates to maintain the ORF for each router.

Attribute Name: orf-prefix-capability

Attribute Type: bits (both|receive|send)

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
          <peer-groups>
            <peer-group>
              <peer-group-tag>WORD</peer-group-tag>
              <config>
                <peer-group-tag>WORD</peer-group-tag>
              </config>
              <orf-prefix-capability>both</orf-prefix-capability> <!--
operation="delete"-->
            </peer-group>
          </peer-groups>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD capability orf prefix-list (both|receive|send)
```

---

## Configure peer allow ebgp vpn

This attribute allows an eBGP neighbor to be a VPN peer. By default, BGP VPN functionality is allowed only for iBGP peers. Using the peer-allow-ebgp-vpn attribute allows the VPN connection to be established to an eBGP peer.

Attribute Name: peer-allow-ebgp-vpn

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        <peer-groups>
          <peer-group>
            <peer-group-tag>WORD</peer-group-tag>
            <config>
              <peer-group-tag>WORD</peer-group-tag>
            </config>
            </peer-allow-ebgp-vpn><!-- operation="delete"-->
          </peer-group>
        </peer-groups>
      </address-family-vrf>
    </address-family-vrfs>
  </bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD allow-ebgp-vpn
```

---

## Configure allow as number

This attribute advertises prefixes (routes) even when the source of the prefixes is from the same Autonomous System (AS) number for specified address-family. Use this attribute in a scenario where two routers at different locations use the same Autonomous System number and are connected via an ISP. Once prefixes arrive from one branch at the ISP, they are tagged with the customers AS number. By default, when the ISP passes the prefixes to the other router, the

prefixes are dropped if the other router uses the same AS number. Use this attribute to advertise the prefixes at the other side. Control the number of times an AS number is advertised by specifying a number. In a hub and spoke configuration in a VPN, a PE (Provider Edge) router advertises all prefixes containing duplicate AS numbers. Use this attribute to configure two VRFs on each PE router to receive and advertise prefixes. One of the VRFs receives prefixes with AS numbers from all PE routers and then advertises them to neighboring PE routers. The other VRF receives prefixes with AS numbers from the CE (Customer Edge) router and advertises them to all PE routers in the hub and spoke configuration.

Attribute Name: allow-as-number

Attribute Type: uint32

Default Value: 3

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <peer-groups>
            <peer-group>
              <peer-group-tag>WORD</peer-group-tag>
              <config>
                <peer-group-tag>WORD</peer-group-tag>
              </config>
                <allow-as-number>1</allow-as-number> <!-- operation="delete"-->
              </peer-group>
            </peer-groups>
          </address-family-vrf>
        </address-family-vrfs>
      </bgp-instance>
    </bgp-instances>
  </bgp>
```

### Command Syntax

```
neighbor WORD allowas-in <1-10>
```

---

## Configure capability graceful restart

This attribute configures the router to advertise the Graceful Restart Capability to the neighbors. This configuration indicates that the BGP speaker has the ability to preserve its forwarding state for the address family when BGP restarts. Use this attribute to advertise to the neighbor routers the capability of graceful restart.

Attribute Name: capability-graceful-restart

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        <peer-groups>
          <peer-group>
            <peer-group-tag>WORD</peer-group-tag>
            <config>
              <peer-group-tag>WORD</peer-group-tag>
            </config>
            </capability-graceful-restart><!-- operation="delete"-->
          </peer-group>
        </peer-groups>
      </address-family-vrf>
    </address-family-vrfs>
  </bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD capability graceful-restart
```

---

## Configure prefix count

This attribute specifies number of prefixes that a BGP router is allowed to receive from a neighbor. When the maximum-prefix-warning attribute is not set and extra prefixes are received, the router ends the peering.

Attribute Name: prefix-count

Attribute Type: uint32

Attribute Range: 1-4294967295

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <maximum-prefixes>
            <maximum-prefix> <!-- operation="delete"-->
              <prefix-count>1</prefix-count>
            <config>
              <prefix-count>1</prefix-count>
            </config>
          </maximum-prefix>
        </maximum-prefixes>
      </peer-group>
    </peer-groups>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295>
```

---

## Configure stop update

Stop installing the routes when limit is exceeded.

Attribute Name: stop-update

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <peer-groups>
            <peer-group>
              <peer-group-tag>WORD</peer-group-tag>
              <config>
                <peer-group-tag>WORD</peer-group-tag>
              </config>
              <maximum-prefixes>
                <maximum-prefix>
                  <prefix-count>1</prefix-count>
                <config>
                  <prefix-count>1</prefix-count>
                </config>
                </stop-update>
              </maximum-prefix>
            </maximum-prefixes>
          </peer-group>
        </peer-groups>
      </address-family-vrf>
    </address-family-vrfs>
  </bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295> stop-update
```

---

## Configure maximum prefix warning

This attribute when enabled only give warning message when limit is exceeded. When it is not set and extra prefixes are received, the router ends the peering.

Attribute Name: maximum-prefix-warning

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <maximum-prefixes>
            <maximum-prefix>
              <prefix-count>1</prefix-count>
              <config>
                <prefix-count>1</prefix-count>
              </config>
            </maximum-prefix-warning>
          </maximum-prefix>
        </maximum-prefixes>
      </peer-group>
    </peer-groups>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295> warning-only
```

---

## Configure threshold percentage

Threshold-value in percen. This attribute controls the number of prefixes that can be received from a neighbor. This attribute allows the configuration of a specified number of prefixes that a BGP router is allowed to receive from a neighbor. When the maximum-prefix-warning attribute is not set and extra prefixes are received, the router ends the peering.

Attribute Name: threshold-percentage

Attribute Type: uint8

Default Value: 75

Attribute Range: 1-100

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <maximum-prefixes>
            <maximum-prefix>
              <prefix-count>1</prefix-count>
              <config>
                <prefix-count>1</prefix-count>
              </config>
            </maximum-prefix>
          </maximum-prefixes>
        </peer-group>
      </address-family-vrf>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

```

    </peer-groups>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295> <1-100>
```

---

## Configure warning only

Throw warning if exceeds threshold-value

Attribute Name: warning-only

Attribute Type: uint8

Attribute Name: threshold-percentage

Attribute Type: uint8

Default Value: 75

Attribute Range: 1-100

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </peer-groups>
        <peer-group>
          <peer-group-tag>WORD</peer-group-tag>
          <config>
            <peer-group-tag>WORD</peer-group-tag>
          </config>
          <maximum-prefixes>
            <maximum-prefix>
              <prefix-count>1</prefix-count>
            </config>

```

```

        <prefix-count>1</prefix-count>
        <threshold-percentage>1</threshold-percentage>
    </config>
    </warning-only>
</maximum-prefix>
</maximum-prefixes>
</peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD maximum-prefix <1-4294967295> <1-100> warning-only
```

---

## Configure unsuppress route map name

unsuppress map name. This attribute is used to selectively leak more-specific routes to a particular neighbor.

Attribute Name: unsuppress-route-map-name

Attribute Type: string

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <peer-groups>
      <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
          <peer-group-tag>WORD</peer-group-tag>
        </config>
        <unsuppress-route-map-name>WORD</unsuppress-route-map-name> <!--
operation="delete"-->

```

```

    </peer-group>
  </peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD unsuppress-map WORD
```

---

## Configure access list identifier

Access List information

Attribute Name: access-list-identifier

Attribute Type: string

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <peer-groups>
            <peer-group>
              <peer-group-tag>WORD</peer-group-tag>
              <config>
                <peer-group-tag>WORD</peer-group-tag>
              </config>
              <distribute-list-filters>
                <distribute-list-filter>
                  <filter-direction>in</filter-direction>
                  <config>
                    <filter-direction>in</filter-direction>
                  </config>
                  <access-list-identifier>WORD</access-list-identifier>
                </distribute-list-filter>

```

```

        </distribute-list-filters>
    </peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD distribute-list WORD (in|out)
```

---

## Configure as access list identifier

Access-list number. This attribute sets a BGP filter. This attribute specifies an access list filter on updates based on the BGP autonomous system paths. Each filter is an access list based on regular expressions

Attribute Name: as-access-list-identifier

Attribute Type: string

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <peer-groups>
            <peer-group>
              <peer-group-tag>WORD</peer-group-tag>
              <config>
                <peer-group-tag>WORD</peer-group-tag>
              </config>
            <as-list-filters>
              <as-list-filter>
                <as-list-direction>in</as-list-direction>
                <config>
                  <as-list-direction>in</as-list-direction>
                </config>
              </as-list-filter>
            </as-list-filters>
          </peer-group>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        <as-access-list-identifier>WORD</as-access-list-identifier>
    </as-list-filter>
</as-list-filters>
</peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD filter-list WORD (in|out)
```

---

## Configure prefix list name

This attribute specifies a prefix list for filtering BGP advertisements for specified address-family. Filtering by prefix list matches the prefixes of routes with those listed in the prefix list. If there is a match, the route is used. An empty prefix list permits all prefixes. If a given prefix does not match any entries of a prefix list, the route is denied access. When multiple entries of a prefix list match a prefix, the entry with the smallest sequence number is considered to be a real match. The router begins the search at the top of the prefix list, with the sequence number 1. Once a match or deny occurs, the router does not need to go through the rest of the prefix list. For efficiency the most common matches or denials are listed at the top.

Attribute Name: prefix-list-name

Attribute Type: string

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </peer-groups>
          <peer-group>
            <peer-group-tag>WORD</peer-group-tag>
            <config>
              <peer-group-tag>WORD</peer-group-tag>
            </config>

```

```

    <prefix-list-filters>
    <prefix-list-filter>
      <prefix-filter-direction>in</prefix-filter-direction>
      <config>
        <prefix-filter-direction>in</prefix-filter-direction>
      </config>
      <prefix-list-name>WORD</prefix-list-name>
    </prefix-list-filter>
  </prefix-list-filters>
</peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor WORD prefix-list WORD (in|out)
```

---

## Configure route map name

Use this attribute to apply a route map to incoming or outgoing routes. This attribute filters updates and modifies attributes. A route map is applied to inbound or outbound updates. Only the routes that pass the route map are sent or accepted in updates.

Attribute Name: route-map-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    <peer-group-tag>WORD</peer-group-tag>
  <config>
    <peer-group-tag>WORD</peer-group-tag>
  </config>
  <route-map-filters>
  <route-map-filter>
    <route-map-direction>in</route-map-direction>
    <config>
      <route-map-direction>in</route-map-direction>
    </config>
    <route-map-name>WORD</route-map-name>
  </route-map-filter>
</route-map-filters>
</peer-group>
</peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor WORD route-map WORD (in|out)
```

---

## Configure peer address

Use this attribute to configure the authentication key to specify if the password is to be encrypted or not.

Attribute Name: auth-key-encrypt

Attribute Type: enum (0|1)

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>

```

```

    <vrf-peer>
      <peer-address>CML_IP_ADDR_T</peer-address>
      <config>
        <peer-address>CML_IP_ADDR_T</peer-address>
      </config>
      <bgp-passwords>
        <bgp-password>
          <password>WORD</password>
          <config>
            <password>WORD</password>
          </config>
          <auth-key-encrypt>1</auth-key-encrypt>
        </bgp-password>
      </bgp-passwords>
    </vrf-peer>
  </vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor authentication-key (0|1) WORD
```

---

## Configure password

Use this attribute to configure the authentication key to specify if the password is to be encrypted or not.

Attribute Name: auth-key-encrypt

Attribute Type: enum (0|1)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </vrf>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    <vrf-peers>
    <vrf-peer>
      <peer-address>CML_IP_ADDR_T</peer-address>
      <config>
        <peer-address>CML_IP_ADDR_T</peer-address>
      </config>
      <bgp-passwords>
      <bgp-password>
        <password>WORD</password>
        <config>
          <password>WORD</password>
        </config>
        <auth-key-encrypt>2</auth-key-encrypt>
      </bgp-password>
    </bgp-passwords>
  </vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor authentication-key WORD
```

---

## Configure vrf-peer neighbor-passive

Use this attribute to set a BGP neighbor as passive.

Attribute Name: neighbor-passive

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
    </address-family-vrf>
    </address-family-vrfs>
  </bgp-instance>
</bgp-instances>
</bgp>

```

```

    <afi>ipv4</afi>
  <vrf-peers>
  <vrf-peer>
    <peer-address>CML_IP_ADDR_T</peer-address>
    <config>
      <peer-address>CML_IP_ADDR_T</peer-address>
    </config>
    </neighbor-passive><!-- operation="delete"-->
  </vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor passive
```

---

## Configure vrf-peer disable-capability-negotiation

Use this attribute to disable capability negotiation. The capability negotiation is performed by default. This attribute is used to allow compatibility with older BGP versions that have no capability parameters used in open messages between peers.

Attribute Name: disable-capability-negotiation

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
          <vrf-peer>
            <peer-address>CML_IP_ADDR_T</peer-address>
          <config>

```

```

        <peer-address>CML_IP_ADDR_T</peer-address>
    </config>
    </disable-capability-negotiation><!-- operation="delete"-->
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor dont-capability-negotiate
```

## Configure vrf-peer enable-dynamic-capability

Use this attribute to enable the dynamic capability for a specific peer. This attribute allows a BGP speaker to advertise or withdraw an address family capability to a peer in a non-disruptive manner.

Attribute Name: enable-dynamic-capability

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
              </enable-dynamic-capability><!-- operation="delete"-->
            </vrf-peer>
          </vrf-peers>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor capability dynamic
```

---

## Configure vrf-peer min-route-advertisement-interval

Minimum route advertisement interval. Sets minimum interval between the sending of BGP routing updates. To reduce the flapping of routes to internet, a minimum advertisement interval is set, so that the BGP routing updates are sent only per interval seconds. BGP dampening can also be used to control the effects of flapping routes.

Attribute Name: min-route-advertisement-interval

Attribute Type: uint32

Attribute Range: 0-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
                <min-route-advertisement-interval>0</min-route-advertisement-
interval> <!-- operation="delete" -->
              </vrf-peer>
            </vrf-peers>
          </address-family-vrf>
        </address-family-vrfs>
      </bgp-instance>
    </bgp-instances>

```

```
</bgp>
```

## Command Syntax

```
neighbor advertisement-interval <0-65535>
```

---

## Configure vrf-peer peer-as-origin-interval

Time interval. This attribute adjust the interval of sending AS origination routing updates. This attribute is used to change the minimum interval between the sending of AS-origination routing updates.

Attribute Name: peer-as-origin-interval

Attribute Type: uint32

Attribute Range: 1-65535

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
              <peer-as-origin-interval>1</peer-as-origin-interval> <!--
operation="delete"-->
            </vrf-peer>
          </vrf-peers>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor as-origination-interval <1-65535>
```

---

## Configure vrf-peer neighbor-as-override

Use this attribute to configure a PE router to override the Autonomous System Number (ASN) of a site with the ASN of a provider. BGP normally ignores the routes from the same AS. However, this attribute is used to override the customer's ASN in BGP, so that the customer CE accepts and installs routes from the same AS. Typically, this attribute is used when Customer Edge (CE) routers have the same ASN in some or all sites. As per BGP requirement, a BGP speaker rejects a route that has the same ASN as itself, in the AS\_PATH attribute. Thus the CE routers having the same ASN do not accept routes from each other. Set neighborAsOverrideAf attribute on the PE router removes the CE neighbors ASN from the AS\_PATH attribute allowing CE routers with the same ASN to accept routes from each other.

Attribute Name: neighbor-as-override

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        <vrf-peers>
          <vrf-peer>
            <peer-address>CML_IP_ADDR_T</peer-address>
            <config>
              <peer-address>CML_IP_ADDR_T</peer-address>
            </config>
            </neighbor-as-override><!-- operation="delete"-->
          </vrf-peer>
        </vrf-peers>
      </address-family-vrf>
    </address-family-vrfs>
  </bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor as-override
```

---

## Configure peer interface name

Interface name. Configures IP address or IPv6 address on interface

Attribute Name: peer-interface-name

Attribute Type: string

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
              <peer-interface-name>WORD</peer-interface-name> <!--
operation="delete"-->
            </vrf-peer>
          </vrf-peers>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) interface WORD
```

---

## Configure vrf-peer peer-description

Use this attribute to associate a description with a neighbor. This attribute helps in identifying a neighbor quickly. It is useful for an ISP that has multiple neighbor relationships.

Attribute Name: peer-description

Attribute Type: string

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
      <address-family-vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <vrf-peers>
      <vrf-peer>
        <peer-address>CML_IP_ADDR_T</peer-address>
        <config>
          <peer-address>CML_IP_ADDR_T</peer-address>
        </config>
        <peer-description>LINE</peer-description> <!-- operation="delete"-->
      </vrf-peer>
      </vrf-peers>
    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor description LINE
```

## Configure vrf-peer peer-restart-time

This attribute sets a different restart-time other than the global restart-time. This attribute takes precedence over the restart-time value specified using the graceful-restart-set attribute. The restart-time value is the maximum time that a graceful-restart neighbor waits to come back up after a restart. The default value is 120 seconds.

Attribute Name: peer-restart-time

Attribute Type: uint32

Attribute Range: 1-3600

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <vrf-peers>
      <vrf-peer>
        <peer-address>CML_IP_ADDR_T</peer-address>
        <config>
          <peer-address>CML_IP_ADDR_T</peer-address>
        </config>
          <peer-restart-time>1</peer-restart-time> <!-- operation="delete"-->
        </vrf-peer>
      </vrf-peers>
    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor restart-time <1-3600>
```

---

## Configure vrf-peer site-origin-identifier

Use this attribute to enable the site-of-origin (SOO) feature. If the customer AS is multi-homed to the ISP, this attribute ensures that the PE does not advertise the routes back to the same AS.

Attribute Name: site-origin-identifier

Attribute Type: string

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>

```

```

    <bgp-as>1</bgp-as>
</config>
<address-family-vrfs>
<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
</vrf-peers>
<vrf-peer>
  <peer-address>CML_IP_ADDR_T</peer-address>
  <config>
    <peer-address>CML_IP_ADDR_T</peer-address>
  </config>
  <site-origin-identifier>AS:nn_or_IP:nn</site-origin-identifier> <!--
- operation="delete"-->
  </vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor soo AS:nn_or_IP:nn
```

---

## Configure vrf-peer graceful-shut

Use this attribute to start a graceful shutdown for the BGP session of the specified BGP neighbor. The BGP session for this neighbor is shut down after the graceful shutdown timer expires. If there is no alternate path available for traffic to flow prior the actual shutdown of the BGP session, this path is made available for 60 seconds or for configured time after which the path is no longer available and traffic is dropped.

Attribute Name: graceful-shut

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
  <address-family-vrfs>
  <address-family-vrf>

```

```

    <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
</vrf-peers>
<vrf-peer>
  <peer-address>CML_IP_ADDR_T</peer-address>
  <config>
    <peer-address>CML_IP_ADDR_T</peer-address>
  </config>
  </graceful-shut><!-- operation="delete"-->
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor g-shut
```

---

## Configure vrf-peer graceful-shut-timer

Use this attribute to configure the value of the graceful shutdown timer. After the timer expires, the BGP session initiated for graceful shutdown is shut down.

Attribute Name: graceful-shut-timer

Attribute Type: uint32

Attribute Range: 10-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    </config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  <vrf-peers>
  <vrf-peer>
    <peer-address>CML_IP_ADDR_T</peer-address>
    <config>
      <peer-address>CML_IP_ADDR_T</peer-address>
    </config>
    <graceful-shut-timer>10</graceful-shut-timer> <!--
operation="delete"-->
  </vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor g-shut-timer <10-65535>
```

---

## Configure vrf-peer bgp-port

The BGP port number of a neighbor

Attribute Name: bgp-port

Attribute Type: uint16

Default Value: 179

Attribute Range: 0-65535

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    <vrf-peer>
      <peer-address>CML_IP_ADDR_T</peer-address>
      <config>
        <peer-address>CML_IP_ADDR_T</peer-address>
      </config>
      <bgp-port>0</bgp-port> <!-- operation="delete"-->
    </vrf-peer>
  </vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor port <0-65535>
```

---

## Configure vrf-peer enable-ext-opt-param-len

Use this attribute for a specific peer to encode extended optional parameter length.

Attribute Name: enable-ext-opt-param-len

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
              </enable-ext-opt-param-len><!-- operation="delete"-->
            </vrf-peer>
          </vrf-peers>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    </vrf-peers>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor extended-optional-param
```

---

## Configure vrf-peer additional-paths-mode

Adds additional paths in the BGP table

Attribute Name: additional-paths-mode

Attribute Type: bits (send-receive|receive|send|disable)

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
              <additional-paths-mode>send-receive</additional-paths-mode> <!--
operation="delete"-->
            </vrf-peer>
          </vrf-peers>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor additional-paths (send-receive|receive|send|disable)
```

## Configure vrf-peer additional-path-select-all

Attribute to select advertise additional path

Attribute Name: additional-path-select-all

Attribute Type: uint8

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
              </additional-path-select-all><!-- operation="delete"-->
            </vrf-peer>
          </vrf-peers>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor advertise additional-paths all
```

## Configure vrf-peer additional-paths-best-select-count

Attribute to select best advertise additional path

Attribute Name: additional-paths-best-select-count

Attribute Type: uint8

Attribute Range: 2-3

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
                <additional-paths-best-select-count>2</additional-paths-best-
select-count> <!-- operation="delete"-->
              </vrf-peer>
            </vrf-peers>
          </address-family-vrf>
        </address-family-vrfs>
      </bgp-instance>
    </bgp-instances>
  </bgp>
```

### Command Syntax

```
neighbor advertise additional-paths best <2-3>
```

## Configure vrf-peer tcp-adjust-mss

Use this attribute to set the BGP TCP MSS value of a neighbor.

Attribute Name: tcp-adjust-mss

Attribute Type: uint16

Attribute Range: 40-1440

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <vrf-peers>
      <vrf-peer>
        <peer-address>CML_IP_ADDR_T</peer-address>
        <config>
          <peer-address>CML_IP_ADDR_T</peer-address>
        </config>
          <tcp-adjust-mss>40</tcp-adjust-mss> <!-- operation="delete"-->
        </vrf-peer>
      </vrf-peers>
    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

**Command Syntax**

```
neighbor tcp-mss <40-1440>
```

**Configure vrf-peer enable-peer-bfd**

Enable bidirectional forwarding detection (BFD) for the BGP peer

Attribute Name: enable-peer-bfd

Attribute Type: uint8

**Netconf edit-config payload**

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>

```

```

</config>
<address-family-vrfs>
<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
  <vrf-peers>
  <vrf-peer>
    <peer-address>CML_IP_ADDR_T</peer-address>
    <config>
      <peer-address>CML_IP_ADDR_T</peer-address>
    </config>
    </enable-peer-bfd><!-- operation="delete"-->
  </vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor fall-over bfd
```

---

## Configure vrf-peer enable-peer-bfd-multihop

Enable bidirectional forwarding detection (BFD) for the BGP peer with multihop

Attribute Name: enable-peer-bfd-multihop

Attribute Type: uint8

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>

```

```

    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
  <vrf-peers>
  <vrf-peer>
    <peer-address>CML_IP_ADDR_T</peer-address>
    <config>
      <peer-address>CML_IP_ADDR_T</peer-address>
    </config>
    </enable-peer-bfd-multihop><!-- operation="delete"-->
  </vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor fall-over bfd multihop
```

---

## Configure vrf-peer activate

Activate/Deactivate neighbor. This attribute enables or disables the exchange of AF information with a neighboring router.

Attribute Name: activate

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </vrf-peers>
        <vrf-peer>

```

```

        <peer-address>CML_IP_ADDR_T</peer-address>
    </config>
    <peer-address>CML_IP_ADDR_T</peer-address>
</config>
    </activate><!-- operation="delete"-->
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor activate
```

---

## Configure de activate

Deactivate neighbor. This attribute disables the exchange of AF information with a neighboring router.

Attribute Name: de-activate

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
              </de-activate><!-- operation="delete"-->
            </vrf-peer>
          </vrf-peers>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor de-activate
```

---

## Configure vrf-peer default-peer-route-map-name

This attribute allows a BGP local router to send the default route 0.0.0.0 to a neighbor for use as a default route for specified address-family.

Attribute Name: default-peer-route-map-name

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
              </default-peer-route-map-name><!-- operation="delete"-->
            </vrf-peer>
          </vrf-peers>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor default-originate
```

---

## Configure vrf-peer peer-route-map-orig-name

This attribute configures route map to be used for a BGP local router to send the default route 0.0.0.0 to a neighbor for use as a default route for specified address-family. This attribute can be used with standard or extended access lists.

Attribute Name: peer-route-map-orig-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
              <peer-route-map-orig-name>WORD</peer-route-map-orig-name> <!--
operation="delete"-->
            </vrf-peer>
          </vrf-peers>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor default-originate route-map WORD
```

---

## Configure vrf-peer weight

This attribute specifies a weight value, for specified address-family, to all routes learned from a neighbor for specified address-family. The route with the highest weight gets preference when the same prefix is learned from more than one peer. Unlike the local-preference attribute, the weight attribute is relevant only to the local router. When the weight is set for a peer group, all members of the peer group get the same weight. This attribute can also be used to assign a different weight to an individual peer-group member. When an individually-configured weight of a peer-group member is removed, its weight is reset to its peer groups weight.

Attribute Name: weight

Attribute Type: uint16

Default Value: 0

Attribute Range: 0-65535

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
              <weight>0</weight> <!-- operation="delete"-->
            </vrf-peer>
          </vrf-peers>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor weight <0-65535>
```

---

## Configure vrf-peer weight

This attribute specifies a weight value, for specified address-family, to all routes learned from a neighbor for specified address-family. The route with the highest weight gets preference when the same prefix is learned from more than one peer. Unlike the local-preference attribute, the weight attribute is relevant only to the local router. When the weight is set for a peer group, all members of the peer group get the same weight. This attribute can also be used to assign a different weight to an individual peer-group member. When an individually-configured weight of a peer-group member is removed, its weight is reset to its peer groups weight.

Attribute Name: weight

Attribute Type: uint16

Default Value: 0

Attribute Range: 0-65535

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
              <weight>0</weight> <!-- operation="delete"-->
            </vrf-peer>
          </vrf-peers>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor weight <0-65535>
```

---

## Configure vrf-peer peer-route-reflector

This attribute configures the router as a BGP route reflector and configure the specified neighbor as its client for specified address-family. Route reflectors are a solution for the explosion of iBGP peering within an autonomous system. By route reflection the number of iBGP peers within an AS is reduced. Use this attribute to configure the local router as the route reflector and specify neighbors as its client. An AS can have more than one route reflector. One route reflector treats the other route reflector as another iBGP speaker.

Attribute Name: peer-route-reflector

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
              </peer-route-reflector><!-- operation="delete"-->
            </vrf-peer>
          </vrf-peers>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor route-reflector-client
```

---

## Configure vrf-peer peer-remove-private-as

This attribute removes the private Autonomous System (AS) number from outbound updates. Private AS numbers are not advertised to the Internet. This attribute is used with external BGP peers only. The router removes the AS numbers only if the update includes private AS numbers. If the update includes both private and public AS numbers, the system treats it as an error.

Attribute Name: peer-remove-private-as

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
              </peer-remove-private-as><!-- operation="delete"-->
            </vrf-peer>
          </vrf-peers>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor remove-private-AS
```

---

## Configure vrf-peer no-send-community

This attribute specifies if a community attribute should be sent to a BGP neighbor for specified address-family. The community attribute groups destinations in a certain community and applies routing decisions according to those communities. By default, both standard and extended community attributes are sent to a neighbor

Attribute Name: no-send-community

Attribute Type: uint8

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
              </no-send-community><!-- operation="delete"-->
            </vrf-peer>
          </vrf-peers>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
no neighbor send-community
```

---

## Configure vrf-peer no-send-community-type

This attribute specifies the type of community attribute to be sent to a BGP neighbor.

Attribute Name: no-send-community-type

Attribute Type: bits (both|standard|extended|large)

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <vrf-peers>
      <vrf-peer>
        <peer-address>CML_IP_ADDR_T</peer-address>
        <config>
          <peer-address>CML_IP_ADDR_T</peer-address>
        </config>
        <no-send-community-type>both</no-send-community-type> <!--
operation="delete"-->
      </vrf-peer>
    </vrf-peers>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
no neighbor send-community (both|standard|extended|large)
```

---

## Configure vrf-peer neighbor-attribute-unchanged

This attribute advertises unchanged BGP AS path, next hop and med to the specified neighbor.

Attribute Name: neighbor-attribute-unchanged

Attribute Type: bits (as-path|next-hop|med)

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
```

```

    <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
</address-family-vrfs>
<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
  <vrf-peers>
  <vrf-peer>
    <peer-address>CML_IP_ADDR_T</peer-address>
    <config>
      <peer-address>CML_IP_ADDR_T</peer-address>
    </config>
    <neighbor-attribute-unchanged>14</neighbor-attribute-unchanged> <!--
- operation="delete"-->
      </vrf-peer>
    </vrf-peers>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor attribute-unchanged
```

---

## Configure vrf-peer neighbor-attribute-unchanged

This attribute advertises unchanged BGP AS path, next hop and med to the specified neighbor.

Attribute Name: neighbor-attribute-unchanged

Attribute Type: bits (as-path|next-hop|med)

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
      <address-family-vrf>

```

```

    <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
<vrf-peers>
<vrf-peer>
  <peer-address>CML_IP_ADDR_T</peer-address>
  <config>
    <peer-address>CML_IP_ADDR_T</peer-address>
  </config>
  <neighbor-attribute-unchanged>as-path</neighbor-attribute-
unchanged> <!-- operation="delete"-->
  </vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor attribute-unchanged {as-path|next-hop|med}
```

---

## Configure vrf-peer orf-prefix-capability

This attribute enables Outbound Router Filtering (ORF), and advertise the ORF capability to its neighbors. The ORFs send and receive capabilities to lessen the number of updates exchanged between neighbors. By filtering updates, this option minimizes generating and processing of updates. The two routers exchange updates to maintain the ORF for each router.

Attribute Name: orf-prefix-capability

Attribute Type: bits (both|receive|send)

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>

```

```

    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
<vrf-peers>
<vrf-peer>
  <peer-address>CML_IP_ADDR_T</peer-address>
  <config>
    <peer-address>CML_IP_ADDR_T</peer-address>
  </config>
  <orf-prefix-capability>both</orf-prefix-capability> <!--
operation="delete"-->
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor capability orf prefix-list (both|receive|send)
```

---

## Configure vrf-peer peer-allow-ebgp-vpn

This attribute allows an eBGP neighbor to be a VPN peer. By default, BGP VPN functionality is allowed only for iBGP peers. Using the peer-allow-ebgp-vpn attribute allows the VPN connection to be established to an eBGP peer.

Attribute Name: peer-allow-ebgp-vpn

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </vrf-peers>

```

```

    <vrf-peer>
      <peer-address>CML_IP_ADDR_T</peer-address>
      <config>
        <peer-address>CML_IP_ADDR_T</peer-address>
      </config>
      </peer-allow-ebgp-vpn><!-- operation="delete"-->
    </vrf-peer>
  </vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor allow-ebgp-vpn
```

---

## Configure vrf-peer allow-as-number

This attribute advertises prefixes (routes) even when the source of the prefixes is from the same Autonomous System (AS) number for specified address-family. Use this attribute in a scenario where two routers at different locations use the same Autonomous System number and are connected via an ISP. Once prefixes arrive from one branch at the ISP, they are tagged with the customers AS number. By default, when the ISP passes the prefixes to the other router, the prefixes are dropped if the other router uses the same AS number. Use this attribute to advertise the prefixes at the other side. Control the number of times an AS number is advertised by specifying a number. In a hub and spoke configuration in a VPN, a PE (Provider Edge) router advertises all prefixes containing duplicate AS numbers. Use this attribute to configure two VRFs on each PE router to receive and advertise prefixes. One of the VRFs receives prefixes with AS numbers from all PE routers and then advertises them to neighboring PE routers. The other VRF receives prefixes with AS numbers from the CE (Customer Edge) router and advertises them to all PE routers in the hub and spoke configuration.

Attribute Name: allow-as-number

Attribute Type: uint32

Default Value: 3

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

</config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
<vrf-peers>
<vrf-peer>
  <peer-address>CML_IP_ADDR_T</peer-address>
  <config>
    <peer-address>CML_IP_ADDR_T</peer-address>
  </config>
  <allow-as-number>1</allow-as-number> <!-- operation="delete"-->
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor allowas-in <1-10>
```

---

## Configure vrf-peer capability-graceful-restart

This attribute configures the router to advertise the Graceful Restart Capability to the neighbors. This configuration indicates that the BGP speaker has the ability to preserve its forwarding state for the address family when BGP restarts. Use this attribute to advertise to the neighbor routers the capability of graceful restart.

Attribute Name: capability-graceful-restart

Attribute Type: uint8

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    <vrf-peers>
    <vrf-peer>

```

```

    <peer-address>CML_IP_ADDR_T</peer-address>
  <config>
    <peer-address>CML_IP_ADDR_T</peer-address>
  </config>
  </capability-graceful-restart><!-- operation="delete"-->
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor capability graceful-restart
```

---

## Configure mapped peer group tag af

BGP peer group name. Adds a neighbor to an existing peer group. Neighbors with the same update policies are grouped into peer groups. This facilitates the updates of various policies, such as distribute and filter lists. The peer group is then configured easily with any of the neighbor attributes. Any changes made to the peer group affect all members.

Attribute Name: mapped-peer-group-tag-af

Attribute Type: string

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </vrf-peers>
        <vrf-peer>
          <peer-address>CML_IP_ADDR_T</peer-address>
          <config>
            <peer-address>CML_IP_ADDR_T</peer-address>
          </config>
        </vrf-peer>
      </address-family-vrf>
    </address-family-vrfs>
  </bgp-instance>
</bgp-instances>
</bgp>

```

```

        <mapped-peer-group-tag-af>WORD</mapped-peer-group-tag-af> <!--
operation="delete"-->
        </vrf-peer>
    </vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor (A.B.C.D|X:X::X:X) peer-group WORD
```

---

## Configure maximum-prefixes prefix-count

This attribute specifies number of prefixes that a BGP router is allowed to receive from a neighbor. When the maximum-prefix-warning attribute is not set and extra prefixes are received, the router ends the peering.

Attribute Name: prefix-count

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </vrf-peers>
    <vrf-peer>
      <peer-address>CML_IP_ADDR_T</peer-address>
      <config>
        <peer-address>CML_IP_ADDR_T</peer-address>
      </config>
      <maximum-prefixes>
      <maximum-prefix> <!-- operation="delete"-->
        <prefix-count>1</prefix-count>
      </config>
    </vrf-peer>
  </bgp-instance>
</bgp-instances>
</bgp>

```

```

        <prefix-count>1</prefix-count>
    </config>
</maximum-prefix>
</maximum-prefixes>
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor maximum-prefix <1-4294967295>
```

---

## Configure maximum-prefix stop-update

Stop installing the routes when limit is exceeded.

Attribute Name: stop-update

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
            <maximum-prefixes>
              <maximum-prefix>
                <prefix-count>1</prefix-count>
              </maximum-prefix>
            </maximum-prefixes>
          </vrf-peer>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        <prefix-count>1</prefix-count>
    </config>
</stop-update>
</maximum-prefix>
</maximum-prefixes>
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor maximum-prefix <1-4294967295> stop-update
```

---

## Configure maximum-prefix maximum-prefix-warning

This attribute when enabled only give warning message when limit is exceeded. When it is not set and extra prefixes are received, the router ends the peering.

Attribute Name: maximum-prefix-warning

Attribute Type: uint8

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <vrf-peers>
            <vrf-peer>
              <peer-address>CML_IP_ADDR_T</peer-address>
              <config>
                <peer-address>CML_IP_ADDR_T</peer-address>
              </config>
            <maximum-prefixes>
            <maximum-prefix>

```

```

        <prefix-count>1</prefix-count>
        <config>
            <prefix-count>1</prefix-count>
        </config>
        </maximum-prefix-warning>
    </maximum-prefix>
</maximum-prefixes>
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor maximum-prefix <1-4294967295> warning-only
```

## Configure maximum-prefix threshold-percentage

Threshold-value in percen. This attribute controls the number of prefixes that can be received from a neighbor. This attribute allows the configuration of a specified number of prefixes that a BGP router is allowed to receive from a neighbor. When the maximum-prefix-warning attribute is not set and extra prefixes are received, the router ends the peering.

Attribute Name: threshold-percentage

Attribute Type: uint8

Default Value: 75

Attribute Range: 1-100

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </vrf-peers>
    <vrf-peer>

```

```

    <peer-address>CML_IP_ADDR_T</peer-address>
  <config>
    <peer-address>CML_IP_ADDR_T</peer-address>
  </config>
  <maximum-prefixes>
  <maximum-prefix>
    <prefix-count>1</prefix-count>
  <config>
    <prefix-count>1</prefix-count>
  </config>
    <threshold-percentage>1</threshold-percentage>
  </maximum-prefix>
</maximum-prefixes>
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor maximum-prefix <1-4294967295> <1-100>
```

---

## Configure maximum-prefix warning-only

Throw warning if exceeds threshold-value

Attribute Name: warning-only

Attribute Type: uint8

Attribute Name: threshold-percentage

Attribute Type: uint8

Default Value: 75

Attribute Range: 1-100

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
          </config>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
  <vrf-peers>
  <vrf-peer>
    <peer-address>CML_IP_ADDR_T</peer-address>
    <config>
      <peer-address>CML_IP_ADDR_T</peer-address>
    </config>
    <maximum-prefixes>
    <maximum-prefix>
      <prefix-count>1</prefix-count>
      <config>
        <prefix-count>1</prefix-count>
        <threshold-percentage>1</threshold-percentage>
      </config>
      </warning-only>
    </maximum-prefix>
  </maximum-prefixes>
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor maximum-prefix <1-4294967295> <1-100> warning-only
```

---

## Configure vrf-peer unsuppress-route-map-name

unsuppress map name. This attribute is used to selectively leak more-specific routes to a particular neighbor.

Attribute Name: unsuppress-route-map-name

Attribute Type: string

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
      <address-family-vrf>
        <vrf-name>WORD</vrf-name>
      </config>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
    </config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
    <vrf-peers>
    <vrf-peer>
        <peer-address>CML_IP_ADDR_T</peer-address>
    <config>
        <peer-address>CML_IP_ADDR_T</peer-address>
    </config>
        <unsuppress-route-map-name>WORD</unsuppress-route-map-name> <!--
operation="delete"-->
    </vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor unsuppress-map WORD
```

---

## Configure filter direction

Access List information

Attribute Name: access-list-identifier

Attribute Type: string

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>

```

```

    <vrf-peers>
    <vrf-peer>
      <peer-address>CML_IP_ADDR_T</peer-address>
      <config>
        <peer-address>CML_IP_ADDR_T</peer-address>
      </config>
      <distribute-list-filters>
      <distribute-list-filter>
        <filter-direction>in</filter-direction>
        <config>
          <filter-direction>in</filter-direction>
        </config>
        <access-list-identifier>WORD</access-list-identifier>
      </distribute-list-filter>
    </distribute-list-filters>
  </vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

### Command Syntax

```
neighbor distribute-list WORD (in|out)
```

---

## Configure as list direction

Access-list number. This attribute sets a BGP filter. This attribute specifies an access list filter on updates based on the BGP autonomous system paths. Each filter is an access list based on regular expressions

Attribute Name: as-access-list-identifier

Attribute Type: string

### Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

```

    <safi>unicast</safi>
    <afi>ipv4</afi>
  <vrf-peers>
  <vrf-peer>
    <peer-address>CML_IP_ADDR_T</peer-address>
    <config>
      <peer-address>CML_IP_ADDR_T</peer-address>
    </config>
    <as-list-filters>
    <as-list-filter>
      <as-list-direction>in</as-list-direction>
      <config>
        <as-list-direction>in</as-list-direction>
      </config>
      <as-access-list-identifier>WORD</as-access-list-identifier>
    </as-list-filter>
  </as-list-filters>
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor filter-list WORD (in|out)
```

---

## Configure prefix filter direction

This attribute specifies a prefix list for filtering BGP advertisements for specified address-family. Filtering by prefix list matches the prefixes of routes with those listed in the prefix list. If there is a match, the route is used. An empty prefix list permits all prefixes. If a given prefix does not match any entries of a prefix list, the route is denied access. When multiple entries of a prefix list match a prefix, the entry with the smallest sequence number is considered to be a real match. The router begins the search at the top of the prefix list, with the sequence number 1. Once a match or deny occurs, the router does not need to go through the rest of the prefix list. For efficiency the most common matches or denies are listed at the top.

Attribute Name: prefix-list-name

Attribute Type: string

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
    <address-family-vrfs>
    <address-family-vrf>

```

```

    <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
</vrf-peers>
<vrf-peer>
  <peer-address>CML_IP_ADDR_T</peer-address>
  <config>
    <peer-address>CML_IP_ADDR_T</peer-address>
  </config>
  <prefix-list-filters>
  <prefix-list-filter>
    <prefix-filter-direction>in</prefix-filter-direction>
    <config>
      <prefix-filter-direction>in</prefix-filter-direction>
    </config>
    <prefix-list-name>WORD</prefix-list-name>
  </prefix-list-filter>
</prefix-list-filters>
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor prefix-list WORD (in|out)
```

---

## Configure route map direction

Use this attribute to apply a route map to incoming or outgoing routes. This attribute filters updates and modifies attributes. A route map is applied to inbound or outbound updates. Only the routes that pass the route map are sent or accepted in updates.

Attribute Name: route-map-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>

```

```

    <bgp-as>1</bgp-as>
  </config>
  <address-family-vrfs>
  <address-family-vrf>
    <vrf-name>WORD</vrf-name>
    <config>
      <vrf-name>WORD</vrf-name>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  <vrf-peers>
  <vrf-peer>
    <peer-address>CML_IP_ADDR_T</peer-address>
    <config>
      <peer-address>CML_IP_ADDR_T</peer-address>
    </config>
    <route-map-filters>
    <route-map-filter>
      <route-map-direction>in</route-map-direction>
      <config>
        <route-map-direction>in</route-map-direction>
      </config>
      <route-map-name>WORD</route-map-name>
    </route-map-filter>
    </route-map-filters>
  </vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor route-map WORD (in|out)
```

---

## Configure identifier

This attribute to specifies a BGP confederation identifier.

Attribute Name: identifier

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>

```

```

    <bgp-as>1</bgp-as>
  <config>
    <bgp-as>1</bgp-as>
  </config>
</address-family-vrfs>
<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
  <confederation>
  <config>
    <identifier>1</identifier> <!-- operation="delete"-->
  </config>
</confederation>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp confederation identifier <1-4294967295>
```

---

## Configure peer as number

Use this attribute to configure the Autonomous Systems (AS) that belong to a confederation. A confederation allows an AS to be divided into several ASs. The AS is given a confederation identifier. External BGP (eBGP) routers view only the whole confederation as one AS. Each AS is fully meshed within itself and is visible internally to the confederation.

Attribute Name: peer-as-number

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
      <address-family-vrf>
        <vrf-name>WORD</vrf-name>
        <config>

```

```

        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
    </config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
    <confederation>
    <config>
        <peer-as-number>1</peer-as-number> <!-- operation="delete"-->
    </config>
    </confederation>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp confederation peers .<1-4294967295>
```

---

## Configure enable dampening

Use this attribute to enable route flap dampening

Attribute Name: enable-dampening

Attribute Type: enum (enable-dampening)

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    <route-flap-dampenings>
    <route-flap-dampening> <!-- operation="delete"-->
      <enable-dampening>enable-dampening</enable-dampening>
    <config>
      <enable-dampening>enable-dampening</enable-dampening>

```

```

        </config>
    </route-flap-dampening>
</route-flap-dampenings>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp dampening
```

---

## Configure reach half life

Use this attribute to configure reachability half-life time for the penalty in minutes for the bgp route dampening. The time for the penalty to decrease to one-half of its current value.

Attribute Name: reach-half-life

Attribute Type: uint32

Default Value: 15

Attribute Range: 1-45

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          <route-flap-dampenings>
            <route-flap-dampening>
              <enable-dampening>enable-dampening</enable-dampening>
              <config>
                <enable-dampening>enable-dampening</enable-dampening>
              </config>
              <reach-half-life>1</reach-half-life> <!-- operation="delete"-->
            </route-flap-dampening>
          </route-flap-dampenings>
        </address-family-vrf>
      </address-family-vrfs>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

    </address-family-vrf>
  </address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp dampening <1-45>
```

---

## Configure max suppress time

Use this attribute to configure the value to start suppressing a route for BGP route dampening. When the penalty for a route exceeds the suppress value, the route is suppressed

Attribute Name: max-suppress-time

Attribute Type: uint32

Attribute Range: 1-255

Attribute Name: reach-half-life

Attribute Type: uint32

Attribute Range: 1-45

Attribute Name: reuse-penalty

Attribute Type: uint32

Attribute Range: 1-20000

Attribute Name: suppress-penalty

Attribute Type: uint32

Attribute Range: 1-20000

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
        <address-family-vrf>
          <vrf-name>WORD</vrf-name>
          <config>
            <vrf-name>WORD</vrf-name>
            <safi>unicast</safi>
            <afi>ipv4</afi>
          </config>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </address-family-vrf>
      </address-family-vrfs>
      <route-flap-dampenings>

```

```

    <route-flap-dampening>
      <enable-dampening>enable-dampening</enable-dampening>
      <config>
        <enable-dampening>enable-dampening</enable-dampening>
        <reach-half-life>1</reach-half-life> <!-- operation="delete"-->
        <reuse-penalty>1</reuse-penalty> <!-- operation="delete"-->
        <suppress-penalty>1</suppress-penalty> <!-- operation="delete"-->
      </config>
      <max-suppress-time>1</max-suppress-time> <!-- operation="delete"-->
    </route-flap-dampening>
  </route-flap-dampenings>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp dampening <1-45> <1-20000> <1-20000> <1-255>
```

---

## Configure unreachable half life

Use this attribute to configure un-reachability half-life time for the penalty in minutes for bgp route dampening. The dampening information is purged from the router once the penalty becomes less than half of the reuse limit.

Attribute Name: unreachable-half-life

Attribute Type: uint32

Attribute Range: 1-45

Attribute Name: reach-half-life

Attribute Type: uint32

Attribute Range: 1-45

Attribute Name: reuse-penalty

Attribute Type: uint32

Attribute Range: 1-20000

Attribute Name: suppress-penalty

Attribute Type: uint32

Attribute Range: 1-20000

Attribute Name: max-suppress-time

Attribute Type: uint32

Attribute Range: 1-255

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>

```

```

<bgp-as>1</bgp-as>
<config>
  <bgp-as>1</bgp-as>
</config>
<address-family-vrfs>
<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
<route-flap-dampenings>
<route-flap-dampening>
  <enable-dampening>enable-dampening</enable-dampening>
  <config>
    <enable-dampening>enable-dampening</enable-dampening>
    <reach-half-life>1</reach-half-life> <!-- operation="delete"-->
    <reuse-penalty>1</reuse-penalty> <!-- operation="delete"-->
    <suppress-penalty>1</suppress-penalty> <!-- operation="delete"-->
    <max-suppress-time>1</max-suppress-time> <!-- operation="delete"-->
  </config>
  <unreach-half-life>1</unreach-half-life> <!-- operation="delete"-->
</route-flap-dampening>
</route-flap-dampenings>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp dampening <1-45> <1-20000> <1-20000> <1-255> <1-45>
```

---

## Configure dampening rmap name

Use this attribute to configure route map to specify criteria for dampening.

Attribute Name: dampening-rmap-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>

```

```

    <bgp-as>1</bgp-as>
  </config>
</address-family-vrfs>
<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
  <route-flap-dampenings>
  <route-flap-dampening>
    <enable-dampening>enable-dampening</enable-dampening>
    <config>
      <enable-dampening>enable-dampening</enable-dampening>
    </config>
    <dampening-rmap-name>WORD</dampening-rmap-name> <!--
operation="delete"-->
  </route-flap-dampening>
</route-flap-dampenings>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
bgp dampening route-map WORD
```

---

## Configure ebgp-multihop enabled

Use this attribute to accept and attempt BGP connections to external peers on indirectly connected networks. Multihop is not established if the only route to the multihop peer is a default route. This avoids loop formation.

Attribute Name: enabled

Attribute Type: empty

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
      <address-family-vrf>
        <vrf-name>WORD</vrf-name>

```

```

    <config>
      <vrf-name>WORD</vrf-name>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </config>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  <vrf-peers>
  <vrf-peer>
    <peer-address>CML_IP_ADDR_T</peer-address>
    <config>
      <peer-address>CML_IP_ADDR_T</peer-address>
    </config>
    <ebgp-multihop>
    <config>
      </enabled>
    </config>
  </ebgp-multihop>
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor ebgp-multihop
```

---

## Configure ebgp-multihop enabled

Use this attribute to accept and attempt BGP connections to external peers on indirectly connected networks. Multihop is not established if the only route to the multihop peer is a default route. This avoids loop formation.

Attribute Name: enabled

Attribute Type: empty

Attribute Name: maximum-hop-count

Attribute Type: uint8

Attribute Range: 1-255

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
    <address-family-vrfs>

```

```

    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    </address-family-vrf>
    <vrf-peers>
      <vrf-peer>
        <peer-address>CML_IP_ADDR_T</peer-address>
        <config>
          <peer-address>CML_IP_ADDR_T</peer-address>
        </config>
        <ebgp-multihop>
          <config>
            <maximum-hop-count>1</maximum-hop-count> <!--
operation="delete"-->
            </enabled><!-- operation="delete"-->
          </config>
        </ebgp-multihop>
      </vrf-peer>
    </vrf-peers>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor ebgp-multihop <1-255>
```

---

## Configure peer local as

Specifies an AS (autonomous system) number to use with BGP neighbor.

Attribute Name: peer-local-as

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```

<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
    </bgp-instance>
  </bgp-instances>
</bgp>

```

```

<address-family-vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
    <safi>unicast</safi>
    <afi>ipv4</afi>
  </config>
  <safi>unicast</safi>
  <afi>ipv4</afi>
<vrf-peers>
<vrf-peer>
  <peer-address>CML_IP_ADDR_T</peer-address>
  <config>
    <peer-address>CML_IP_ADDR_T</peer-address>
  </config>
  <local-as>
  <local-as-list> <!-- operation="delete"-->
    <peer-local-as>1</peer-local-as>
    <config>
      <peer-local-as>1</peer-local-as>
    </config>
  </local-as-list>
  </local-as>
</vrf-peer>
</vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor local-as <1-4294967295>
```

---

## Configure no prepend local as

Specifies an AS (autonomous system) number to use with BGP neighbor.

Attribute Name: peer-local-as

Attribute Type: uint32

Attribute Range: 1-4294967295

Attribute Name: no-prepend-local-as

Attribute Type: empty

Attribute Name: replace-local-as

Attribute Type: empty

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
```

```

<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    <vrf-peers>
    <vrf-peer>
      <peer-address>CML_IP_ADDR_T</peer-address>
      <config>
        <peer-address>CML_IP_ADDR_T</peer-address>
      </config>
      <local-as>
      <local-as-list>
        <peer-local-as>1</peer-local-as>
        <config>
          <peer-local-as>1</peer-local-as>
          </no-prepend-local-as>
          </replace-local-as>
        </config>
      </local-as-list>
      </local-as>
    </vrf-peer>
  </vrf-peers>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>

```

## Command Syntax

```
neighbor local-as <1-4294967295> (no-prepend|) (replace-as|)
```

---

## Configure backdoor

network address with backdoor for address family

Attribute Name: backdoor

Attribute Type: uint8

Attribute Name: network-rmap-name

Attribute Type: string

Default Value: NULL

Attribute Range: 1-63

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
      <address-family-vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <network-lists>
      <network-list>
        <local-network-prefix>A.B.C.D</local-network-prefix>
        <config>
          <local-network-prefix>BGP_IP_NETWORK_T</local-network-prefix>
          <network-rmap-name>WORD</network-rmap-name>
        </config>
        </backdoor>
      </network-list>
    </network-lists>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
network (A.B.C.D | A.B.C.D/M) (route-map WORD|) (backdoor|)
```

---

## Configure local network prefix

network address with backdoor for address family

Attribute Name: backdoor

Attribute Type: uint8

Attribute Name: network-rmap-name

Attribute Type: string

Default Value: NULL

Attribute Range: 1-63

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
      <address-family-vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </address-family-vrf>
      </address-family-vrfs>
      <network-lists>
      <network-list>
        <local-network-prefix>A.B.C.D</local-network-prefix>
        <config>
          <local-network-prefix>BGP_IP_NETWORK_T</local-network-prefix>
          <network-rmap-name>WORD</network-rmap-name>
        </config>
        </backdoor>
      </network-list>
      </network-lists>
    </bgp-instance>
  </bgp-instances>
</bgp>
```

### Command Syntax

```
network (X:X::X:X/M) (route-map WORD|) (backdoor|)
```

---

## Configure local-as peer-local-as

Specifies an AS (autonomous system) number to use with BGP neighbor.

Attribute Name: peer-local-as

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
<bgp-instances>
  <bgp-instance>
    <bgp-as>1</bgp-as>
    <config>
      <bgp-as>1</bgp-as>
    </config>
    <address-family-vrfs>
    <address-family-vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      </config>
      <safi>unicast</safi>
      <afi>ipv4</afi>
    <peer-groups>
    <peer-group>
      <peer-group-tag>WORD</peer-group-tag>
      <config>
        <peer-group-tag>WORD</peer-group-tag>
      </config>
      <local-as>
      <local-as-list> <!-- operation="delete"-->
        <peer-local-as>1</peer-local-as>
        <config>
          <peer-local-as>1</peer-local-as>
        </config>
      </local-as-list>
      </local-as>
    </peer-group>
  </peer-groups>
</address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>
```

## Command Syntax

```
neighbor WORD local-as <1-4294967295>
```

---

## Configure replace local as

Specifies an AS (autonomous system) number to use with BGP neighbor.

Attribute Name: peer-local-as

Attribute Type: uint32

Attribute Range: 1-4294967295

Attribute Name: no-prepend-local-as

Attribute Type: empty

Attribute Name: replace-local-as

Attribute Type: empty

### Netconf edit-config payload

```
<bgp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <bgp-instances>
    <bgp-instance>
      <bgp-as>1</bgp-as>
      <config>
        <bgp-as>1</bgp-as>
      </config>
      <address-family-vrfs>
      <address-family-vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
          <safi>unicast</safi>
          <afi>ipv4</afi>
        </config>
        <safi>unicast</safi>
        <afi>ipv4</afi>
      <peer-groups>
      <peer-group>
        <peer-group-tag>WORD</peer-group-tag>
        <config>
          <peer-group-tag>WORD</peer-group-tag>
        </config>
        <local-as>
        <local-as-list>
          <peer-local-as>1</peer-local-as>
          <config>
            <peer-local-as>1</peer-local-as>
            </no-prepend-local-as>
            </replace-local-as>
          </config>
        </local-as-list>
        </local-as>
      </peer-group>
    </peer-groups>
  </address-family-vrf>
</address-family-vrfs>
</bgp-instance>
</bgp-instances>
</bgp>
```

### Command Syntax

```
neighbor WORD local-as <1-4294967295> (no-prepend|) (replace-as|)
```

---

## clear ip bgp all vrf (VRFNAME|all|default) (description LINE|)

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: peer-reset-description

Attribute Type: string

Attribute Range: 1-255

### Netconf RPC payload

```
<ipi-bgp-address-family-vrf_clear-ip-bgp-all-vrf xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <vrf-name>VRFNAME</vrf-name>
  <peer-reset-description>l</peer-reset-description>
</ipi-bgp-address-family-vrf_clear-ip-bgp-all-vrf>
```

### Command Syntax

```
clear ip bgp all vrf (VRFNAME|all|default) (description LINE|)
```

---

## clear ip bgp vrf WORD (A.B.C.D|X:X::X:X|WORD|WORD) (description LINE|)

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: address

Attribute Type: union

Attribute Name: peer-reset-description

Attribute Type: string

Attribute Range: 1-255

### Netconf RPC payload

```
<ipi-bgp-address-family-vrf_clear-ip-bgp-vrf-peer xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-bgp">
  <vrf-name>WORD</vrf-name>
  <address>BGP_HOSTNAME_T</address>
  <peer-reset-description>l</peer-reset-description>
</ipi-bgp-address-family-vrf_clear-ip-bgp-vrf-peer>
```

### Command Syntax

```
clear ip bgp vrf WORD (A.B.C.D|X:X::X:X|WORD|WORD) (description LINE|)
```

---

## IPI-BGP-VRF

---

### Configure rd string

Use this attribute to assign a route distinguisher (RD) for the VRF. The route distinguisher value must be a unique value on the router. This attribute creates routing and forwarding tables and specifies the default RD for a VPN. The RD is added to the customers IPv4 prefixes, changing them into globally unique VPN-IPv4 prefixes.

Attribute Name: rd-string

Attribute Type: string

Attribute Range: 1-32

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>WORD</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <bgp-vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp-vrf">
        <config>
          <rd-string>ASN:nn_or_IP-address:nn</rd-string> <!--
operation="delete"-->
        </config>
      </bgp-vrf>
    </vrf>
  </network-instance>
</network-instances>
```

### Command Syntax

```
rd ASN:nn_or_IP-address:nn
```

---

### Configure import map

This attribute assigns a route map to the VRF. This map is applied for routing information imported from another PE or VRF. Use this attribute when an application requires finer control over the routes imported into a VRF than provided by the import and export extended communities. You can filter routes that are eligible for import into a VRF through the use of a route map. The route map can deny access to selected routes from a community that is on the import list.

Attribute Name: import-map

Attribute Type: string

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
```

```

<network-instance>
  <instance-name>WORD</instance-name>
  <config>
    <instance-name>WORD</instance-name>
    <instance-type>vrf</instance-type>
  </config>
  <instance-type>vrf</instance-type>
  <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
    <bgp-vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp-vrf">
      <config>
        <import-map>WORD</import-map> <!-- operation="delete"-->
      </config>
    </bgp-vrf>
  </vrf>
</network-instance>
</network-instances>

```

### Command Syntax

```
import map WORD
```

---

## Configure export map

export map name

Attribute Name: export-map

Attribute Type: string

### Netconf edit-config payload

```

<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>WORD</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <bgp-vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp-vrf">
        <config>
          <export-map>WORD</export-map> <!-- operation="delete"-->
        </config>
      </bgp-vrf>
    </vrf>
  </network-instance>
</network-instances>

```

### Command Syntax

```
export map WORD
```

---

## Configure direction

Use this attribute to add a list of import and export route-target extended communities to the VRF. This attribute creates lists of import and export route-target extended communities for the VRF. It specifies a target VPN extended community. All routes with the specific route-target extended community are imported into all VRFs with the same extended community as an import route-target.

Attribute Name: direction

Attribute Type: bits (import|export|both)

### Netconf edit-config payload

```
<network-instances xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-network-
instance">
  <network-instance>
    <instance-name>WORD</instance-name>
    <config>
      <instance-name>WORD</instance-name>
      <instance-type>vrf</instance-type>
    </config>
    <instance-type>vrf</instance-type>
    <vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrf">
      <bgp-vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bgp-vrf">
        <route-targets>
          <route-target>
            <rt-rd-string>BGP_ROUTE_TARGET_TYPE_T</rt-rd-string>
            <config>
              <rt-rd-string>BGP_ROUTE_TARGET_TYPE_T</rt-rd-string>
            </config>
            <direction>import</direction>
          </route-target>
        </route-targets>
      </bgp-vrf>
    </vrf>
  </network-instance>
</network-instances>
```

### Command Syntax

```
route-target (import|export|both) (ASN:nn_or_IP-address:nn|evpn-auto-rt)
```

---

## IPI-BFD

### Configure notification enabled

Use this attribute to enable or disable BFD SNMP notification.

Attribute Name: notification-enabled

Attribute Type: boolean

Default Value: false

---

### Netconf edit-config payload

```
<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
  <global>
  <config>
    <notification-enabled>true</notification-enabled> <!-- operation="delete"-->
  </config>
</global>
</bfd>
```

### Command Syntax

```
bfd notification (disable|enable)
```

---

## Configure echo mode enabled

This leaf exists when echo mode is running between the local and remote system. When it does not exist, solely asynchronous mode is active.

Attribute Name: echo-mode-enabled

Attribute Type: empty

### Netconf edit-config payload

```
<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
  <global>
  <config>
    <echo-mode-enabled><!-- operation="delete"-->
  </config>
</global>
</bfd>
```

### Command Syntax

```
bfd echo
```

---

## Configure slow tx interval

Use this command to set a BFD slow timer interval.

Attribute Name: slow-tx-interval

Attribute Type: uint32

Default Value: 2000

Attribute Range: 1000-30000

### Netconf edit-config payload

```
<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
  <global>
  <config>
    <slow-tx-interval>1000</slow-tx-interval> <!-- operation="delete"-->
  </config>
</global>
</bfd>
```

---

## Command Syntax

```
bfd slow-timer <1000-30000>
```

---

## Configure detection multiplier

The number of packets that must be missed to declare this session as down. The detection interval for the BFD session is calculated by multiplying the value of the negotiated transmission interval by this value.

This command is supported when following feature are enabled BFD-MONO feature enabled

Attribute Name: detection-multiplier

Attribute Type: uint8

Attribute Range: 3-50

## Netconf edit-config payload

```
<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
  <global>
    <intervals>
      <interval> <!-- operation="delete"-->
        <detection-multiplier>3</detection-multiplier>
        <config>
          <detection-multiplier>3</detection-multiplier>
          <required-minimum-rx-interval>3</required-minimum-rx-interval>
          <desired-minimum-tx-interval>3</desired-minimum-tx-interval>
        </config>
        <required-minimum-rx-interval>3</required-minimum-rx-interval>
        <desired-minimum-tx-interval>3</desired-minimum-tx-interval>
      </interval>
    </intervals>
  </global>
</bfd>
```

## Command Syntax

```
bfd interval <3-999> minrx <3-999> multiplier <3-50>
```

---

## Configure remote address

The number of packets that must be missed to declare this session as down. The detection interval for the BFD session is calculated by multiplying the value of the negotiated transmission interval by this value.

This command is supported when following feature are enabled BFD-MONO feature enabled

Attribute Name: detection-multiplier

Attribute Type: uint8

Attribute Range: 3-50

## Netconf edit-config payload

```
<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
  <peers>
    <peer>
```

```

    <remote-address>A.B.C.D</remote-address>
  <config>
    <remote-address>A.B.C.D</remote-address>
  </config>
</intervals>
<interval> <!-- operation="delete"-->
  <detection-multiplier>3</detection-multiplier>
  <config>
    <detection-multiplier>3</detection-multiplier>
    <required-minimum-rx-interval>3</required-minimum-rx-interval>
    <desired-minimum-tx-interval>3</desired-minimum-tx-interval>
  </config>
  <required-minimum-rx-interval>50</required-minimum-rx-interval>
  <desired-minimum-tx-interval>50</desired-minimum-tx-interval>
</interval>
</intervals>
</peer>
</peers>
</bfd>

```

## Command Syntax

```

bfd multihop-peer (A.B.C.D|X:X::X:X) interval <50-999> minrx <50-999> multiplier
<3-50>

```

---

## Configure key string

Use this attribute to specify the key authentication string

Attribute Name: key-string

Attribute Type: string

Attribute Name: key-type

Attribute Type: enum (simple|keyed-sha1|meticulous-keyed-sha1)

Attribute Name: key-id

Attribute Type: uint32

Attribute Range: 0-255

Attribute Name: key-encrypted

Attribute Type: enum (0|1)

## Netconf edit-config payload

```

<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
  <peers>
    <peer>
      <remote-address>A.B.C.D</remote-address>
      <config>
        <remote-address>A.B.C.D</remote-address>
      </config>
    </peer>
  </peers>
  <authentication>

```

```

<config>
  <key-type>simple</key-type> <!-- operation="delete"-->
  <key-id>0</key-id> <!-- operation="delete"-->
  <key-encrypted>0</key-encrypted> <!-- operation="delete"-->
  <key-string>WORD</key-string> <!-- operation="delete"-->
</config>
</authentication>
</peer>
</peers>
</bfd>

```

### Command Syntax

```

bfd multihop-peer (A.B.C.D|X:X::X:X) auth type (simple|keyed-sha1|meticulous-keyed-
sha1) key-id <0-255> (0|1) key WORD

```

---

## Configure options

Use this attribute to debug the oamd process.

Attribute Name: options

Attribute Type: bits (events|packets|ipc-error|ipc-event|session|nsm|all)

### Netconf edit-config payload

```

<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
  <debug>
  <config>
    <options>events</options> <!-- operation="delete"-->
  </config>
</debug>
</bfd>

```

### Command Syntax

```

debug bfd (events|packets|ipc-error|ipc-event|session|nsm|all)

```

---

## snmp restart bfd

### Netconf RPC payload

```

<bfd-snmp-restart xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd"/>

```

### Command Syntax

```

snmp restart bfd

```

---

## debug bfd (events|packets|ipc-error|ipc-event|session|nsm|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (events|packets|ipc-error|ipc-event|session|nsm|all)

**Netconf RPC payload**

```
<bfd-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
<terminal-debug-options>events</terminal-debug-options>
</bfd-terminal-debug-on>
```

**Command Syntax**

```
debug bfd (events|packets|ipc-error|ipc-event|session|nsm|all)
```

**no debug bfd (events|packets|ipc-error|ipc-event|session|nsm|all)**

Attribute Name: terminal-debug-options

Attribute Type: bits (events|packets|ipc-error|ipc-event|session|nsm|all)

**Netconf RPC payload**

```
<bfd-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
<terminal-debug-options>events</terminal-debug-options>
</bfd-terminal-debug-off>
```

**Command Syntax**

```
no debug bfd (events|packets|ipc-error|ipc-event|session|nsm|all)
```

**IPI-BFD-INTERFACE****Configure bfd disabled**

Use this attribute to enable or disable all the BFD sessions on this interface.

Attribute Name: bfd-disabled

Attribute Type: uint8

**Netconf edit-config payload**

```
<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </bfd-disabled><!-- operation="delete"-->
</interface>
</interfaces>
</bfd>
```

**Command Syntax**

```
bfd disable
```

---

## Configure bfd session type

Use this attribute to offload Single HOP BFD sessions to software or hardware.

Attribute Name: bfd-session-type

Attribute Type: enum (hardware|software)

### Netconf edit-config payload

```
<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <bfd-session-type>hardware</bfd-session-type> <!-- operation="delete"-->
    </interface>
  </interfaces>
</bfd>
```

### Command Syntax

```
bfd session (hardware|software)
```

---

## Configure detection multiplier

The number of packets that must be missed to declare this session as down. The detection interval for the BFD session is calculated by multiplying the value of the negotiated transmission interval by this value.

This command is supported when following feature are enabled BFD-MONO feature enabled

Attribute Name: detection-multiplier

Attribute Type: uint8

Attribute Range: 3-50

### Netconf edit-config payload

```
<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <intervals>
        <interval> <!-- operation="delete"-->
          <detection-multiplier>3</detection-multiplier>
        </interval>
      </intervals>
      <config>
        <detection-multiplier>3</detection-multiplier>
        <required-minimum-rx-interval>3</required-minimum-rx-interval>
        <desired-minimum-tx-interval>3</desired-minimum-tx-interval>
      </config>
    </interface>
  </interfaces>
</bfd>
```

```

        <required-minimum-rx-interval>3</required-minimum-rx-interval>
        <desired-minimum-tx-interval>3</desired-minimum-tx-interval>
    </interval>
</intervals>
</interface>
</interfaces>
</bfd>

```

### Command Syntax

```
bfd interval <3-999> minrx <3-999> multiplier <3-50>
```

---

## Configure ipv4 source

Use this attribute to configure BFD echo packet IPv4 source address

Attribute Name: ipv4-source

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
<interfaces>
<interface>
    <name>WORD</name>
    <config>
        <name>WORD</name>
        </config>
        <echo>
        <config>
            <ipv4-source>A.B.C.D</ipv4-source> <!-- operation="delete"-->
        </config>
        </echo>
    </interface>
</interfaces>
</bfd>

```

### Command Syntax

```
echo ipv4 source A.B.C.D
```

---

## Configure name

Use this attribute to configure BFD echo packet IPv4 source address

Attribute Name: ipv4-source

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
<interfaces>
<interface>
    <name>WORD</name>

```

```

    <config>
      <name>WORD</name>
    </config>
  <echo>
    <config>
      <ipv4-source>A.B.C.D</ipv4-source> <!-- operation="delete"-->
    </config>
  </echo>
</interface>
</interfaces>
</bfd>

```

### Command Syntax

```
bfd echo ipv4 source A.B.C.D
```

---

## Configure required minimum tx interval

Use this attribute to configure BFD echo packet transmission interval, in milliseconds

Attribute Name: required-minimum-tx-interval

Attribute Type: uint32

Attribute Range: 50-4294967

### Netconf edit-config payload

```

<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <echo>
        <config>
          <required-minimum-tx-interval>50</required-minimum-tx-interval> <!--
operation="delete"-->
        </config>
      </echo>
    </interface>
  </interfaces>
</bfd>

```

### Command Syntax

```
bfd echo interval <50-4294967>
```

---

## Configure key string

Use this attribute to specify the key authentication string

Attribute Name: key-string

Attribute Type: string

Attribute Name: key-type

Attribute Type: enum (simple|keyed-sha1|meticulous-keyed-sha1)

Attribute Name: key-id

Attribute Type: uint32

Attribute Range: 0-255

Attribute Name: key-encrypted

Attribute Type: enum (0|1)

### Netconf edit-config payload

```
<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <authentication>
        <config>
          <key-type>simple</key-type> <!-- operation="delete"-->
          <key-id>0</key-id> <!-- operation="delete"-->
          <key-encrypted>0</key-encrypted> <!-- operation="delete"-->
          <key-string>WORD</key-string> <!-- operation="delete"-->
        </config>
      </authentication>
    </interface>
  </interfaces>
</bfd>
```

### Command Syntax

```
bfd auth type (simple|keyed-sha1|meticulous-keyed-sha1) key-id <0-255> (0|1) key
WORD
```

---

## Configure session type

BFD session type

Attribute Name: session-type

Attribute Type: enum (singlehop|multihop)

### Netconf edit-config payload

```
<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <sessions>
```

```

<session> <!-- operation="delete"-->
  <session-type>singlehop</session-type>
  <config>
    <session-type>singlehop</session-type>
    <remote-address>A.B.C.D</remote-address>
    <local-address>A.B.C.D</local-address>
  </config>
  <remote-address>A.B.C.D</remote-address>
  <local-address>A.B.C.D</local-address>
</session>
</sessions>
</interface>
</interfaces>
</bfd>

```

## Command Syntax

```
bfd session (A.B.C.D|X:X::X:X) (A.B.C.D|X:X::X:X) (multihop|)
```

---

## Configure administrative down

BFD administrative down session

Attribute Name: administrative-down

Attribute Type: empty

## Netconf edit-config payload

```

<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<sessions>
<session>
  <session-type>singlehop</session-type>
  <config>
    <session-type>singlehop</session-type>
    <remote-address>A.B.C.D</remote-address>
    <local-address>A.B.C.D</local-address>
  </config>
  <remote-address>A.B.C.D</remote-address>
  <local-address>A.B.C.D</local-address>
  </administrative-down><!-- operation="delete"-->
</session>
</sessions>
</interface>
</interfaces>
</bfd>

```

---

## Command Syntax

```
bfd session (A.B.C.D|X:X::X:X) (A.B.C.D|X:X::X:X) (multihop|) admin-down
```

---

## Configure non persistent

BFD non persistent session

Attribute Name: non-persistent

Attribute Type: empty

## Netconf edit-config payload

```
<bfd xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-bfd">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <sessions>
        <session>
          <session-type>singlehop</session-type>
          <config>
            <session-type>singlehop</session-type>
            <remote-address>A.B.C.D</remote-address>
            <local-address>A.B.C.D</local-address>
          </config>
          <remote-address>A.B.C.D</remote-address>
          <local-address>A.B.C.D</local-address>
          </non-persistent><!-- operation="delete"-->
        </session>
      </sessions>
    </interface>
  </interfaces>
</bfd>
```

## Command Syntax

```
bfd session (A.B.C.D|X:X::X:X) (A.B.C.D|X:X::X:X) (multihop|) non-persistent
```

---

## IPI-VRRP

---

### Configure disable virtual router mac address

Use this attribute to enable or disable Virtual MAC (VMAC). This affects all VRRP groups in a router. On a single network segment, multiple VRRP groups can be configured, each using a different VMAC. The use of VMAC addressing allows for faster switchover when a backup router assumes the master role. When this attribute is used to enable a VMAC, the virtual router forwards packets with a special-purpose multicast VMAC address (0:0:5e:0:01:VR\_ID). Otherwise, it forwards with interface physical address. The VMAC address is assigned to a router interface at the time the VRRP group is enabled in the router.

Attribute Name: disable-virtual-router-mac-address

Attribute Type: empty

### Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <global>
  <config>
    </disable-virtual-router-mac-address><!-- operation="delete"-->
  </config>
</global>
</vrrp>
```

### Command Syntax

```
vrrp vmac disable
```

---

## Configure vrrp v2 compatible

Use this attribute to enable or disable backward-compatibility feature. When enabled, both VRRPv3 and VRRPv2 interoperation are supported.

Attribute Name: vrrp-v2-compatible

Attribute Type: empty

### Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <global>
  <config>
    </vrrp-v2-compatible><!-- operation="delete"-->
  </config>
</global>
</vrrp>
```

### Command Syntax

```
vrrp compatible-v2 enable
```

---

## Configure ipv4 exclude pseudo header

This command excludes the pseudo-header in IPv4 VRRPv3 checksum calculation on the VRRP group

Attribute Name: ipv4-exclude-pseudo-header

Attribute Type: empty

### Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <global>
  <config>
    </ipv4-exclude-pseudo-header><!-- operation="delete"-->
  </config>
</global>
```

```
</vrrp>
```

## Command Syntax

```
vrrp ipv4-exclude-pseudo-header enable
```

---

## Configure options

use this attribute to specify debugging options for VRRP

Attribute Name: options

Attribute Type: bits (all|packet|events|packet send|packet recv)

## Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <debug>
    <config>
      <options>14</options> <!-- operation="delete"-->
    </config>
  </debug>
</vrrp>
```

## Command Syntax

```
debug vrrp
```

---

## Configure debug options

use this attribute to specify debugging options for VRRP

Attribute Name: options

Attribute Type: bits (all|packet|events|packet send|packet recv)

## Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <debug>
    <config>
      <options>all</options> <!-- operation="delete"-->
    </config>
  </debug>
</vrrp>
```

## Command Syntax

```
debug vrrp (all|packet|events|packet send|packet recv)
```

---

## Configure interface name

Use this attribute to configure an VRRP routing process for an interface.

Attribute Name: interface-name

Attribute Type: string

**Netconf edit-config payload**

```

<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
<ipv4-instances>
<ipv4-instance>
  <virtual-router-id>1</virtual-router-id>
  <config>
    <virtual-router-id>1</virtual-router-id>
  </config>
</interfaces>
<interface> <!-- operation="delete"-->
  <interface-name>IFNAME</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
</interface>
</interfaces>
</ipv4-instance>
</ipv4-instances>
</vrrp>

```

**Command Syntax**

```
router vrrp <1-255> IFNAME
```

**Configure disable preempt mode**

Use this attribute to configure preempt mode. If set to true, the highest priority backup is always the master when the default master is unavailable. If set to false, a higher priority backup does not preempt a lower priority backup which is acting as master

Attribute Name: disable-preempt-mode

Attribute Type: empty

**Netconf edit-config payload**

```

<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
<ipv4-instances>
<ipv4-instance>
  <virtual-router-id>1</virtual-router-id>
  <config>
    <virtual-router-id>1</virtual-router-id>
  </config>
</interfaces>
<interface>
  <interface-name>IFNAME</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  </disable-preempt-mode><!-- operation="delete"-->
</interface>
</interfaces>
</ipv4-instance>

```

```
</ipv4-instances>
</vrrp>
```

### Command Syntax

```
preempt-mode false
```

---

## Configure disable accept mode

Use this attribute to enable accept mode for the session

Attribute Name: disable-accept-mode

Attribute Type: empty

### Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
<ipv4-instances>
<ipv4-instance>
  <virtual-router-id>1</virtual-router-id>
  <config>
    <virtual-router-id>1</virtual-router-id>
  </config>
</interfaces>
<interface>
  <interface-name>IFNAME</interface-name>
  <config>
    <interface-name>WORD</interface-name>
    </disable-accept-mode><!-- operation="delete"-->
  </config>
</interface>
</interfaces>
</ipv4-instance>
</ipv4-instances>
</vrrp>
```

### Command Syntax

```
accept-mode false
```

---

## Configure virtual router id

Use this attribute to enable or disable the backward-compatibility feature

Attribute Name: vrrp-v2-compatible

Attribute Type: empty

### Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
<ipv4-instances>
<ipv4-instance>
  <virtual-router-id>1</virtual-router-id>
  <config>
```

```

    <virtual-router-id>1</virtual-router-id>
  </config>
</interfaces>
<interface>
  <interface-name>IFNAME</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  </vrrp-v2-compatible><!-- operation="delete"-->
</interface>
</interfaces>
</ipv4-instance>
</ipv4-instances>
</vrrp>

```

### Command Syntax

v2-compatible

---

## Configure interface ipv4-exclude-pseudo-header

Use this attribute to excludes the pseudo-header in IPv4 VRRPv3 checksum calculation

Attribute Name: ipv4-exclude-pseudo-header

Attribute Type: empty

### Netconf edit-config payload

```

<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv4-instances>
    <ipv4-instance>
      <virtual-router-id>1</virtual-router-id>
      <config>
        <virtual-router-id>1</virtual-router-id>
      </config>
    </interface>
  </interfaces>
  <interface>
    <interface-name>IFNAME</interface-name>
    <config>
      <interface-name>WORD</interface-name>
    </config>
    </ipv4-exclude-pseudo-header><!-- operation="delete"-->
  </interface>
</interfaces>
</ipv4-instance>
</ipv4-instances>
</vrrp>

```

### Command Syntax

ipv4-exclude-pseudo-header

---

## Configure authentication data

Use this attribute to include authentication simple text

Attribute Name: authentication-data

Attribute Type: string

### Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv4-instances>
    <ipv4-instance>
      <virtual-router-id>1</virtual-router-id>
      <config>
        <virtual-router-id>1</virtual-router-id>
      </config>
    </ipv4-instance>
  </ipv4-instances>
  <interface>
    <interface-name>IFNAME</interface-name>
    <config>
      <interface-name>WORD</interface-name>
    </config>
    <authentication-data>TEXT-STRING</authentication-data> <!--
operation="delete"-->
  </interface>
</interface>
</vrrp>
```

### Command Syntax

```
authentication text TEXT-STRING
```

---

## Configure primary ip address

Use this attribute to set the operational-ip address for the virtual router

Attribute Name: primary-ip-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv4-instances>
    <ipv4-instance>
      <virtual-router-id>1</virtual-router-id>
      <config>
        <virtual-router-id>1</virtual-router-id>
      </config>
    </ipv4-instance>
  </ipv4-instances>
  <interface>
    <interface-name>IFNAME</interface-name>
```

```

<config>
  <interface-name>WORD</interface-name>
</config>
  <primary-ip-address>A.B.C.D</primary-ip-address> <!-- operation="delete"-->
</interface>
</interfaces>
</ipv4-instance>
</ipv4-instances>
</vrrp>

```

### Command Syntax

```
operational-ip A.B.C.D
```

---

## Configure mlag active standby

Use this attribute to set active-standby mlag mode

Attribute Name: mlag-active-standby

Attribute Type: empty

### Netconf edit-config payload

```

<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv4-instances>
    <ipv4-instance>
      <virtual-router-id>1</virtual-router-id>
      <config>
        <virtual-router-id>1</virtual-router-id>
      </config>
    <interfaces>
      <interface>
        <interface-name>IFNAME</interface-name>
        <config>
          <interface-name>WORD</interface-name>
        </config>
        </mlag-active-standby><!-- operation="delete"-->
      </interface>
    </interfaces>
  </ipv4-instance>
</ipv4-instances>
</vrrp>

```

### Command Syntax

```
mlag active-standby
```

---

## Configure priority

Use this attribute to configure the VRRP router priority within the virtual router. Priority determines the role that each VRRP router plays and what happens if the master virtual router fails. If a VRRP router owns the IP address of the virtual router and the IP address of the physical interface, this router functions as the master virtual router

Attribute Name: priority

Attribute Type: uint8

Attribute Range: 1-254

### Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv4-instances>
    <ipv4-instance>
      <virtual-router-id>1</virtual-router-id>
      <config>
        <virtual-router-id>1</virtual-router-id>
      </config>
    </ipv4-instance>
  </ipv4-instances>
  <interfaces>
    <interface>
      <interface-name>IFNAME</interface-name>
      <config>
        <interface-name>WORD</interface-name>
        <priority>1</priority> <!-- operation="delete"-->
      </config>
    </interface>
  </interfaces>
</vrrp>
```

### Command Syntax

```
priority <1-254>
```

---

## Configure preempt delay

Use this attribute to set a switch-back delay timer for the master VRRP router. This feature prevents the original master VRRP router from transitioning back to the master state after coming back online until the configured delay timer has expired.

Attribute Name: preempt-delay

Attribute Type: uint32

Attribute Range: 1-500000

### Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv4-instances>
    <ipv4-instance>
      <virtual-router-id>1</virtual-router-id>
      <config>
        <virtual-router-id>1</virtual-router-id>
      </config>
    </ipv4-instance>
  </ipv4-instances>
  <interfaces>
    <interface>
      <interface-name>IFNAME</interface-name>
```

```

<config>
  <interface-name>WORD</interface-name>
</config>
  <preempt-delay>1</preempt-delay> <!-- operation="delete"-->
</interface>
</interfaces>
</ipv4-instance>
</ipv4-instances>
</vrrp>

```

## Command Syntax

```
switch-back-delay <1-500000>
```

---

## Configure advertisement interval

Use this attribute to configure the advertisement interval of a virtual router. This is the length of time, in seconds, between each advertisement sent from the master to its backup(s). The master virtual router sends VRRP advertisements to other VRRP routers in the same group. The advertisements communicate the priority and state of the master virtual router. The VRRP advertisements are encapsulated in IP packets and sent to the multicast address assigned to the VRRP group (224.0.0.18). Advertisements are sent every second by default.

Attribute Name: advertisement-interval

Attribute Type: uint16

Default Value: 100

Attribute Range: 5-4095

## Netconf edit-config payload

```

<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv4-instances>
    <ipv4-instance>
      <virtual-router-id>1</virtual-router-id>
      <config>
        <virtual-router-id>1</virtual-router-id>
      </config>
    <interfaces>
      <interface>
        <interface-name>IFNAME</interface-name>
        <config>
          <interface-name>WORD</interface-name>
          </config>
          <advertisement-interval>5</advertisement-interval> <!-- operation="delete"-->
        </interface>
      </interfaces>
    </ipv4-instance>
  </ipv4-instances>
</vrrp>

```

## Command Syntax

```
advertisement-interval <5-4095>
```

---

## Configure enable

Use this attribute to enable a VRRP session on the router (to make it participate in virtual routing). To make any changes to the VRRP configuration, first disable the router from participating in virtual routing using the disable command

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv4-instances>
    <ipv4-instance>
      <virtual-router-id>1</virtual-router-id>
      <config>
        <virtual-router-id>1</virtual-router-id>
      </config>
    </ipv4-instance>
  </ipv4-instances>
  <interfaces>
    <interface>
      <interface-name>IFNAME</interface-name>
      <config>
        <interface-name>WORD</interface-name>
      </config>
      <protocol-enable>
        <config>
          </enable><!-- operation="delete"-->
        </config>
      </protocol-enable>
    </interface>
  </interfaces>
</vrrp>
```

### Command Syntax

```
enable
```

---

## Configure ip address owner

Use this attribute to set the virtual IP address for the VRRP virtual router as VRRP Owner. This is the IP address used by end hosts to address their default gateway.

Attribute Name: ip-address-owner

Attribute Type: boolean

Attribute Name: virtual-ip-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
```

```

<ipv4-instances>
<ipv4-instance>
  <virtual-router-id>1</virtual-router-id>
  <config>
    <virtual-router-id>1</virtual-router-id>
  </config>
</interfaces>
<interface>
  <interface-name>IFNAME</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <virtual-ip>
  <config>
    <virtual-ip-address>A.B.C.D</virtual-ip-address>
    <ip-address-owner>>true</ip-address-owner>
  </config>
</virtual-ip>
</interface>
</interfaces>
</ipv4-instance>
</ipv4-instances>
</vrrp>

```

### Command Syntax

```
virtual-ip A.B.C.D (owner|)
```

---

## Configure interface tracking name

Use this command to enable the VRRP circuit failover feature.

Attribute Name: interface-tracking-name

Attribute Type: string

Attribute Name: priority-decrement

Attribute Type: uint8

Attribute Range: 1-253

### Netconf edit-config payload

```

<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
<ipv4-instances>
<ipv4-instance>
  <virtual-router-id>1</virtual-router-id>
  <config>
    <virtual-router-id>1</virtual-router-id>
  </config>
</interfaces>
<interface>
  <interface-name>IFNAME</interface-name>
  <config>

```

```

    <interface-name>WORD</interface-name>
  </config>
</interfaces-tracking>
<interface-tracking> <!-- operation="delete"-->
  <interface-tracking-name>IFNAME</interface-tracking-name>
  <config>
    <interface-tracking-name>WORD</interface-tracking-name>
    <priority-decrement>1</priority-decrement>
  </config>
</interface-tracking>
</interfaces-tracking>
</interface>
</interfaces>
</ipv4-instance>
</ipv4-instances>
</vrrp>

```

### Command Syntax

```
circuit-failover IFNAME <1-253>
```

---

## Configure tracking id

Use this command to enable the VRRP object tracking feature.

This command is supported when following feature are enabled HAVE\_OBJ\_TRACKING

Attribute Name: tracking-id

Attribute Type: uint16

Attribute Name: decrement

Attribute Type: uint8

Attribute Range: 1-253

### Netconf edit-config payload

```

<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv4-instances>
    <ipv4-instance>
      <virtual-router-id>1</virtual-router-id>
      <config>
        <virtual-router-id>1</virtual-router-id>
      </config>
    </interfaces>
    <interface>
      <interface-name>IFNAME</interface-name>
      <config>
        <interface-name>WORD</interface-name>
      </config>
      <objects-tracking>
        <object-tracking> <!-- operation="delete"-->
          <tracking-id>0</tracking-id>
        </config>
      </objects-tracking>
    </interface>
  </ipv4-instance>
</ipv4-instances>
</vrrp>

```

```

        <tracking-id>1</tracking-id>
        <decrement>1</decrement>
    </config>
</object-tracking>
</objects-tracking>
</interface>
</interfaces>
</ipv4-instance>
</ipv4-instances>
</vrrp>

```

### Command Syntax

```
track <0-65535> decrement <1-253>
```

---

## Configure interfaces interface-name

Use this attribute to configure an VRRP routing process for an interface.

Attribute Name: interface-name

Attribute Type: string

### Netconf edit-config payload

```

<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv6-instances>
    <ipv6-instance>
      <virtual-router-id>1</virtual-router-id>
      <config>
        <virtual-router-id>1</virtual-router-id>
      </config>
    </interfaces>
    <interface> <!-- operation="delete"-->
      <interface-name>IFNAME</interface-name>
      <config>
        <interface-name>WORD</interface-name>
      </config>
    </interface>
  </interfaces>
</ipv6-instance>
</ipv6-instances>
</vrrp>

```

### Command Syntax

```
router ipv6 vrrp <1-255> IFNAME
```

---

## Configure interface disable-preempt-mode

Use this attribute to configure preempt mode. If set to true, the highest priority backup is always the master when the default master is unavailable. If set to false, a higher priority backup does not preempt a lower priority backup which is acting as master

Attribute Name: disable-preempt-mode

Attribute Type: empty

### Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv6-instances>
    <ipv6-instance>
      <virtual-router-id>1</virtual-router-id>
      <config>
        <virtual-router-id>1</virtual-router-id>
      </config>
    </ipv6-instance>
  </ipv6-instances>
  <interfaces>
    <interface>
      <interface-name>IFNAME</interface-name>
      <config>
        <interface-name>WORD</interface-name>
        </disable-preempt-mode><!-- operation="delete"-->
      </config>
    </interface>
  </interfaces>
</vrrp>
```

### Command Syntax

```
preempt-mode false
```

---

## Configure interface disable-accept-mode

Use this attribute to enable accept mode for the session

Attribute Name: disable-accept-mode

Attribute Type: empty

### Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv6-instances>
    <ipv6-instance>
      <virtual-router-id>1</virtual-router-id>
      <config>
        <virtual-router-id>1</virtual-router-id>
      </config>
    </ipv6-instance>
  </ipv6-instances>
  <interfaces>
    <interface>
      <interface-name>IFNAME</interface-name>
      <config>
        <interface-name>WORD</interface-name>
        </disable-accept-mode><!-- operation="delete"-->
      </config>
    </interface>
  </interfaces>
</vrrp>
```

```

</interfaces>
</ipv6-instance>
</ipv6-instances>
</vrrp>

```

### Command Syntax

```
accept-mode false
```

---

## Configure interface primary-ip-address

Use this attribute to set the operational-ip address for the virtual router

Attribute Name: primary-ip-address

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```

<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
<ipv6-instances>
<ipv6-instance>
  <virtual-router-id>1</virtual-router-id>
  <config>
    <virtual-router-id>1</virtual-router-id>
  </config>
</interfaces>
<interface>
  <interface-name>IFNAME</interface-name>
  <config>
    <interface-name>WORD</interface-name>
    <primary-ip-address>X:X::X:X</primary-ip-address> <!-- operation="delete"-->
  </config>
</interface>
</interfaces>
</ipv6-instance>
</ipv6-instances>
</vrrp>

```

### Command Syntax

```
operational-ipv6 X:X::X:X
```

---

## Configure interface priority

Use this attribute to configure the VRRP router priority within the virtual router. Priority determines the role that each VRRP router plays and what happens if the master virtual router fails. If a VRRP router owns the IP address of the virtual router and the IP address of the physical interface, this router functions as the master virtual router

Attribute Name: priority

Attribute Type: uint8

Attribute Range: 1-254

**Netconf edit-config payload**

```

<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
<ipv6-instances>
<ipv6-instance>
  <virtual-router-id>1</virtual-router-id>
  <config>
    <virtual-router-id>1</virtual-router-id>
  </config>
</interfaces>
<interface>
  <interface-name>IFNAME</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <priority>1</priority> <!-- operation="delete"-->
</interface>
</interfaces>
</ipv6-instance>
</ipv6-instances>
</vrrp>

```

**Command Syntax**

```
priority <1-254>
```

**Configure interface preempt-delay**

Use this attribute to set a switch-back delay timer for the master VRRP router. This feature prevents the original master VRRP router from transitioning back to the master state after coming back online until the configured delay timer has expired.

Attribute Name: preempt-delay

Attribute Type: uint32

Attribute Range: 1-500000

**Netconf edit-config payload**

```

<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
<ipv6-instances>
<ipv6-instance>
  <virtual-router-id>1</virtual-router-id>
  <config>
    <virtual-router-id>1</virtual-router-id>
  </config>
</interfaces>
<interface>
  <interface-name>IFNAME</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <preempt-delay>1</preempt-delay> <!-- operation="delete"-->
</interface>

```

```

</interfaces>
</ipv6-instance>
</ipv6-instances>
</vrrp>

```

## Command Syntax

```
switch-back-delay <1-500000>
```

---

## Configure interface advertisement-interval

Use this attribute to configure the advertisement interval of a virtual router. This is the length of time, in seconds, between each advertisement sent from the master to its backup(s). The master virtual router sends VRRP advertisements to other VRRP routers in the same group. The advertisements communicate the priority and state of the master virtual router. The VRRP advertisements are encapsulated in IP packets and sent to the multicast address assigned to the VRRP group (224.0.0.18). Advertisements are sent every second by default.

Attribute Name: advertisement-interval

Attribute Type: uint16

Default Value: 100

Attribute Range: 5-4095

## Netconf edit-config payload

```

<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv6-instances>
    <ipv6-instance>
      <virtual-router-id>1</virtual-router-id>
      <config>
        <virtual-router-id>1</virtual-router-id>
      </config>
    </ipv6-instance>
  </ipv6-instances>
  <interfaces>
    <interface>
      <interface-name>IFNAME</interface-name>
      <config>
        <interface-name>WORD</interface-name>
        <advertisement-interval>5</advertisement-interval> <!-- operation="delete"-->
      </config>
    </interface>
  </interfaces>
</vrrp>

```

## Command Syntax

```
advertisement-interval <5-4095>
```

---

## Configure protocol-enable enable

Use this attribute to enable a VRRP session on the router (to make it participate in virtual routing). To make any changes to the VRRP configuration, first disable the router from participating in virtual routing using the disable command

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv6-instances>
    <ipv6-instance>
      <virtual-router-id>1</virtual-router-id>
      <config>
        <virtual-router-id>1</virtual-router-id>
      </config>
    </ipv6-instance>
  </ipv6-instances>
  <interfaces>
    <interface>
      <interface-name>IFNAME</interface-name>
      <config>
        <interface-name>WORD</interface-name>
        </config>
        <protocol-enable>
          <config>
            </enable><!-- operation="delete"-->
          </config>
        </protocol-enable>
      </config>
    </interface>
  </interfaces>
</vrrp>
```

### Command Syntax

```
enable
```

---

## Configure virtual ip address

VRRP Virtual IPV6 address

This command is supported when following feature are enabled IPV6 feature

Attribute Name: virtual-ip-address

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```
<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv6-instances>
    <ipv6-instance>
      <virtual-router-id>1</virtual-router-id>
```

```

    <config>
      <virtual-router-id>1</virtual-router-id>
    </config>
  </interfaces>
</interface>
  <interface-name>IFNAME</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <virtual-ip-addresses>
  <virtual-ip-address> <!-- operation="delete"-->
    <virtual-ip-address>X:X::X:X</virtual-ip-address>
    <config>
      <virtual-ip-address>X:X::X:X</virtual-ip-address>
    </config>
  </virtual-ip-address>
</virtual-ip-addresses>
</interface>
</interfaces>
</ipv6-instance>
</ipv6-instances>
</vrrp>

```

### Command Syntax

```
virtual-ipv6 X:X::X:X
```

---

## Configure virtual-ip-address ip-address-owner

Use this attribute to set the virtual IP address for the VRRP virtual router as VRRP Owner. This is the IP address used by end hosts to address their default gateway.

This command is supported when following feature are enabled IPV6 feature

Attribute Name: ip-address-owner

Attribute Type: boolean

### Netconf edit-config payload

```

<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv6-instances>
  <ipv6-instance>
    <virtual-router-id>1</virtual-router-id>
    <config>
      <virtual-router-id>1</virtual-router-id>
    </config>
  </interfaces>
  <interface>
    <interface-name>IFNAME</interface-name>
    <config>
      <interface-name>WORD</interface-name>
    </config>
  </virtual-ip-addresses>

```

```

<virtual-ip-address>
  <virtual-ip-address>X:X::X:X</virtual-ip-address>
  <config>
    <virtual-ip-address>X:X::X:X</virtual-ip-address>
  </config>
  <ip-address-owner>true</ip-address-owner> <!-- operation="delete"-->
</virtual-ip-address>
</virtual-ip-addresses>
</interface>
</interfaces>
</ipv6-instance>
</ipv6-instances>
</vrrp>

```

## Command Syntax

```
virtual-ipv6 X:X::X:X (owner|)
```

---

## Configure priority decrement

Use this command to enable the VRRP circuit failover feature.

Attribute Name: interface-tracking-name

Attribute Type: string

Attribute Name: priority-decrement

Attribute Type: uint8

Attribute Range: 1-253

## Netconf edit-config payload

```

<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <ipv6-instances>
    <ipv6-instance>
      <virtual-router-id>1</virtual-router-id>
      <config>
        <virtual-router-id>1</virtual-router-id>
      </config>
    </ipv6-instance>
  </ipv6-instances>
  <interfaces>
    <interface>
      <interface-name>IFNAME</interface-name>
      <config>
        <interface-name>WORD</interface-name>
      </config>
      <interfaces-tracking>
        <interface-tracking> <!-- operation="delete"-->
          <interface-tracking-name>IFNAME</interface-tracking-name>
          <config>
            <interface-tracking-name>WORD</interface-tracking-name>
            <priority-decrement>1</priority-decrement>
          </config>
        </interface-tracking>
      </interfaces-tracking>
    </interface>
  </interfaces>
</vrrp>

```

```

</interfaces-tracking>
</interface>
</interfaces>
</ipv6-instance>
</ipv6-instances>
</vrrp>

```

## Command Syntax

```
circuit-failover IFNAME <1-253>
```

---

## Configure decrement

Use this command to enable the VRRP object tracking feature.

This command is supported when following feature are enabled HAVE\_OBJ\_TRACKING

Attribute Name: tracking-id

Attribute Type: uint16

Attribute Name: decrement

Attribute Type: uint8

Attribute Range: 1-253

## Netconf edit-config payload

```

<vrrp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
<ipv6-instances>
<ipv6-instance>
  <virtual-router-id>1</virtual-router-id>
  <config>
    <virtual-router-id>1</virtual-router-id>
  </config>
</interfaces>
<interface>
  <interface-name>IFNAME</interface-name>
  <config>
    <interface-name>WORD</interface-name>
  </config>
  <objects-tracking>
  <object-tracking> <!-- operation="delete"-->
    <tracking-id>0</tracking-id>
    <config>
      <tracking-id>1</tracking-id>
      <decrement>1</decrement>
    </config>
  </object-tracking>
</objects-tracking>
</interface>
</interfaces>
</ipv6-instance>
</ipv6-instances>
</vrrp>

```

---

## Command Syntax

```
track <0-65535> decrement <1-253>
```

---

## snmp restart vrrp

### Netconf RPC payload

```
<vrrp-snmp-restart xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp"/>
```

### Command Syntax

```
snmp restart vrrp
```

---

## clear vrrp global statistics

### Netconf RPC payload

```
<vrrp-clear-statistics xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp"/>
```

### Command Syntax

```
clear vrrp global statistics
```

---

## clear vrrp ipv4 statistics

### Netconf RPC payload

```
<vrrp-clear-ipv4-statistics xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp"/>
```

### Command Syntax

```
clear vrrp ipv4 statistics
```

---

## clear vrrp ipv6 statistics

### Netconf RPC payload

```
<vrrp-clear-ipv6-statistics xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp"/>
```

### Command Syntax

```
clear vrrp ipv6 statistics
```

---

## clear vrrp ipv4 statistics <1-255> IFNAME

Attribute Name: vrrp-id

Attribute Type: uint8

Attribute Range: 1-255

Attribute Name: interface-name

Attribute Type: string

---

## Netconf RPC payload

```
<vrrp-clear-session-ipv4-statistics xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-vrrp">
  <vrrp-id>1</vrrp-id>
  <interface-name>IFNAME</interface-name>
</vrrp-clear-session-ipv4-statistics>
```

## Command Syntax

```
clear vrrp ipv4 statistics <1-255> IFNAME
```

---

## clear vrrp ipv6 statistics <1-255> IFNAME

Attribute Name: vrrp-id

Attribute Type: uint8

Attribute Range: 1-255

Attribute Name: interface-name

Attribute Type: string

## Netconf RPC payload

```
<vrrp-clear-session-ipv6-statistics xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-vrrp">
  <vrrp-id>1</vrrp-id>
  <interface-name>IFNAME</interface-name>
</vrrp-clear-session-ipv6-statistics>
```

## Command Syntax

```
clear vrrp ipv6 statistics <1-255> IFNAME
```

---

## debug vrrp

### Netconf RPC payload

```
<vrrp-terminal-debug-all-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
vrrp"/>
```

### Command Syntax

```
debug vrrp
```

---

## no debug vrrp

### Netconf RPC payload

```
<vrrp-terminal-debug-all-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
vrrp"/>
```

### Command Syntax

```
no debug vrrp
```

---

## debug vrrp (all|packet|events|packet send|packet recv)

Attribute Name: terminal-debug-options

Attribute Type: bits (all|packet|events|packet send|packet recv)

### Netconf RPC payload

```
<vrrp-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <terminal-debug-options>all</terminal-debug-options>
</vrrp-terminal-debug-on>
```

### Command Syntax

```
debug vrrp (all|packet|events|packet send|packet recv)
```

---

## no debug vrrp (all|packet|events|packet send|packet recv)

Attribute Name: terminal-debug-options

Attribute Type: bits (all|packet|events|packet send|packet recv)

### Netconf RPC payload

```
<vrrp-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vrrp">
  <terminal-debug-options>all</terminal-debug-options>
</vrrp-terminal-debug-off>
```

### Command Syntax

```
no debug vrrp (all|packet|events|packet send|packet recv)
```

---

## IPI-PREFIX-LIST

---

### Configure prefix list name

prefix-list name

Attribute Name: prefix-list-name

Attribute Type: string

### Netconf edit-config payload

```
<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <prefix> <!-- operation="delete"-->
    <prefix-list-type>ip</prefix-list-type>
  </prefix>
  <prefix>
    <config>
      <prefix-list-type>ip</prefix-list-type>
      <prefix-list-name>WORD</prefix-list-name>
    </config>
  </prefix>
</prefixes>
```

---

## Command Syntax

```
ip prefix-list WORD
```

---

## Configure prefix list type

prefix-list name

Attribute Name: prefix-list-name

Attribute Type: string

### Netconf edit-config payload

```
<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
<prefix> <!-- operation="delete"-->
  <prefix-list-type>ipv6</prefix-list-type>
  <config>
    <prefix-list-type>ipv6</prefix-list-type>
    <prefix-list-name>WORD</prefix-list-name>
  </config>
  <prefix-list-name>WORD</prefix-list-name>
</prefix>
</prefixes>
```

## Command Syntax

```
ipv6 prefix-list WORD
```

---

## Configure description

Up to 80 characters describing this prefix-list

Attribute Name: description

Attribute Type: string

Attribute Range: 1-80

### Netconf edit-config payload

```
<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
<prefix>
  <prefix-list-type>ip</prefix-list-type>
  <config>
    <prefix-list-type>ip</prefix-list-type>
    <prefix-list-name>WORD</prefix-list-name>
  </config>
  <prefix-list-name>WORD</prefix-list-name>
  <description>LINE</description> <!-- operation="delete"-->
</prefix>
</prefixes>
```

## Command Syntax

```
description LINE
```

---

## Configure prefix addr

Either IP address mask and length of the prefix list mask or Take all packets of any length. This parameter is the same as using 0.0.0.0/0 le 32 for A.B.C.D/M.

Attribute Name: prefix-addr

Attribute Type: union

### Netconf edit-config payload

```
<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <prefix>
    <prefix-list-type>ip</prefix-list-type>
    <config>
      <prefix-list-type>ip</prefix-list-type>
      <prefix-list-name>WORD</prefix-list-name>
    </config>
    <prefix-list-name>WORD</prefix-list-name>
  </prefix>
  <prefix-entries>
    <prefix-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <entry>
          <prefix-addr>any</prefix-addr>
          <config>
            <prefix-addr>any</prefix-addr>
            <action>deny</action>
          </config>
          <action>deny</action>
        </entry>
      </ipv4>
    </prefix-entry>
  </prefix-entries>
</prefixes>
```

### Command Syntax

```
(seq <1-4294967295>|) (deny|permit) any
```

---

## Configure sequence id

Either IP address mask and length of the prefix list mask or Take all packets of any length. This parameter is the same as using 0.0.0.0/0 le 32 for A.B.C.D/M.

Attribute Name: prefix-addr

Attribute Type: enum (any)

**Netconf edit-config payload**

```

<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <prefix>
    <prefix-list-type>ip</prefix-list-type>
    <config>
      <prefix-list-type>ip</prefix-list-type>
      <prefix-list-name>WORD</prefix-list-name>
    </config>
    <prefix-list-name>WORD</prefix-list-name>
  </prefix-entries>
  <prefix-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv4>
      <entry>
        <prefix-addr>any</prefix-addr>
        <config>
          <prefix-addr>any</prefix-addr>
          <action>deny</action>
        </config>
        <action>deny</action>
      </entry>
    </ipv4>
  </prefix-entry>
</prefix-entries>
</prefix>
</prefixes>

```

**Command Syntax**

```
(seq <1-4294967295>|) (deny|permit)
```

**Configure maximum prefix length match**

Maximum prefix length match

Attribute Name: maximum-prefix-length-match

Attribute Type: uint8

Attribute Range: 0-32

Attribute Name: minimum-prefix-length-match

Attribute Type: uint8

Attribute Range: 0-32

**Netconf edit-config payload**

```

<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <prefix>
    <prefix-list-type>ip</prefix-list-type>

```

```

<config>
  <prefix-list-type>ip</prefix-list-type>
  <prefix-list-name>WORD</prefix-list-name>
</config>
<prefix-list-name>WORD</prefix-list-name>
<prefix-entries>
<prefix-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
  <entry>
    <prefix-addr>any</prefix-addr>
    <config>
      <prefix-addr>any</prefix-addr>
      <action>deny</action>
      <minimum-prefix-length-match>0</minimum-prefix-length-match> <!--
operation="delete"-->
    </config>
      <action>deny</action>
      <maximum-prefix-length-match>0</maximum-prefix-length-match> <!--
operation="delete"-->
    </entry>
  </ipv4>
</prefix-entry>
</prefix-entries>
</prefix>
</prefixes>

```

## Command Syntax

```
(seq <1-4294967295>|) (deny|permit) ge <0-32> le <0-32>
```

---

## Configure minimum prefix length match

Minimum prefix length match

Attribute Name: minimum-prefix-length-match

Attribute Type: uint8

Attribute Range: 0-32

Attribute Name: maximum-prefix-length-match

Attribute Type: uint8

Attribute Range: 0-32

## Netconf edit-config payload

```

<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <prefix>
    <prefix-list-type>ip</prefix-list-type>
    <config>

```

```

    <prefix-list-type>ip</prefix-list-type>
    <prefix-list-name>WORD</prefix-list-name>
  </config>
  <prefix-list-name>WORD</prefix-list-name>
</prefix-entries>
<prefix-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
  <entry>
    <prefix-addr>any</prefix-addr>
    <config>
      <prefix-addr>any</prefix-addr>
      <action>deny</action>
      <maximum-prefix-length-match>0</maximum-prefix-length-match> <!--
operation="delete"-->
    </config>
      <action>deny</action>
      <minimum-prefix-length-match>0</minimum-prefix-length-match> <!--
operation="delete"-->
    </entry>
  </ipv4>
</prefix-entry>
</prefix-entries>
</prefix>
</prefixes>

```

## Command Syntax

```
(seq <1-4294967295>|) (deny|permit) le <0-32> ge <0-32>
```

---

## Configure action

Minimum prefix length match

Attribute Name: minimum-prefix-length-match

Attribute Type: uint8

Attribute Range: 0-32

## Netconf edit-config payload

```

<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <prefix>
    <prefix-list-type>ip</prefix-list-type>
    <config>
      <prefix-list-type>ip</prefix-list-type>
      <prefix-list-name>WORD</prefix-list-name>
    </config>
    <prefix-list-name>WORD</prefix-list-name>
  </prefix-entries>

```

```

<prefix-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
    <entry>
      <prefix-addr>any</prefix-addr>
      <config>
        <prefix-addr>any</prefix-addr>
        <action>deny</action>
      </config>
      <action>deny</action>
      <minimum-prefix-length-match>0</minimum-prefix-length-match> <!--
operation="delete"-->
    </entry>
  </ipv4>
</prefix-entry>
</prefix-entries>
</prefix>
</prefixes>

```

## Command Syntax

```
(seq <1-4294967295>|) (deny|permit) ge <0-32>
```

---

## Configure entry maximum-prefix-length-match

Maximum prefix length match

Attribute Name: maximum-prefix-length-match

Attribute Type: uint8

Attribute Range: 0-32

## Netconf edit-config payload

```

<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <prefix>
    <prefix-list-type>ip</prefix-list-type>
    <config>
      <prefix-list-type>ip</prefix-list-type>
      <prefix-list-name>WORD</prefix-list-name>
    </config>
    <prefix-list-name>WORD</prefix-list-name>
  </prefix-entries>
  <prefix-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
  </prefix-entry>
</prefixes>

```

```

    <prefix-addr>any</prefix-addr>
    <config>
      <prefix-addr>any</prefix-addr>
      <action>deny</action>
    </config>
    <action>deny</action>
    <maximum-prefix-length-match>0</maximum-prefix-length-match> <!--
operation="delete"-->
  </entry>
</ipv4>
</prefix-entry>
</prefix-entries>
</prefix>
</prefixes>

```

## Command Syntax

```
(seq <1-4294967295>|) (deny|permit) le <0-32>
```

---

## Configure exact prefix length match

Exact prefix length match

Attribute Name: exact-prefix-length-match

Attribute Type: uint8

Attribute Range: 0-32

## Netconf edit-config payload

```

<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <prefix>
    <prefix-list-type>ip</prefix-list-type>
    <config>
      <prefix-list-type>ip</prefix-list-type>
      <prefix-list-name>WORD</prefix-list-name>
    </config>
    <prefix-list-name>WORD</prefix-list-name>
  </prefix-entries>
  <prefix-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv4>
      <entry>
        <prefix-addr>any</prefix-addr>
        <config>
          <prefix-addr>any</prefix-addr>
          <action>deny</action>
        </config>
        <action>deny</action>
      </entry>
    </ipv4>
  </prefix-entry>
</prefixes>

```

```

        <exact-prefix-length-match>0</exact-prefix-length-match> <!--
operation="delete"-->
    </entry>
</ipv4>
</prefix-entry>
</prefix-entries>
</prefix>
</prefixes>

```

## Command Syntax

```
(seq <1-4294967295>|) (deny|permit) eq <0-32>
```

---

## Configure ipv6 prefix addr

Either IPv6 address mask and length of the prefix list mask or This is the same as specifying ::/0 for X:X::X:X/M

This command is supported when following feature are enabled ipv6 feature

Attribute Name: ipv6-prefix-addr

Attribute Type: union

## Netconf edit-config payload

```

<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
<prefix>
  <prefix-list-type>ip</prefix-list-type>
  <config>
    <prefix-list-type>ip</prefix-list-type>
    <prefix-list-name>WORD</prefix-list-name>
  </config>
  <prefix-list-name>WORD</prefix-list-name>
</prefix-entries>
<prefix-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv6>
  <entry> <!-- operation="delete"-->
    <ipv6-prefix-addr>any</ipv6-prefix-addr>
    <config>
      <ipv6-prefix-addr>any</ipv6-prefix-addr>
      <action>deny</action>
    </config>
    <action>deny</action>
  </entry>
</ipv6>
</prefix-entry>
</prefix-entries>
</prefix>
</prefixes>

```

## Command Syntax

```
(seq <1-4294967295>|) (deny|permit) any
```

---

## Configure ipv6 ipv6-prefix-addr

Either IPv6 address mask and length of the prefix list mask or This is the same as specifying ::/0 for X:X::X:X/M

This command is supported when following feature are enabled ipv6 feature

Attribute Name: ipv6-prefix-addr

Attribute Type: union

## Netconf edit-config payload

```
<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <prefix>
    <prefix-list-type>ip</prefix-list-type>
    <config>
      <prefix-list-type>ip</prefix-list-type>
      <prefix-list-name>WORD</prefix-list-name>
    </config>
    <prefix-list-name>WORD</prefix-list-name>
  </prefix-entries>
  <prefix-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv6>
      <entry> <!-- operation="delete"-->
        <ipv6-prefix-addr>any</ipv6-prefix-addr>
        <config>
          <ipv6-prefix-addr>any</ipv6-prefix-addr>
          <action>deny</action>
        </config>
        <action>deny</action>
      </entry>
    </ipv6>
  </prefix-entry>
</prefix-entries>
</prefix>
</prefixes>
```

## Command Syntax

```
(seq <1-4294967295>|) (deny|permit) X:X::X:X/M
```

---

## Configure entry maximum-prefix-length-match

Maximum prefix length match

This command is supported when following feature are enabled ipv6 feature

Attribute Name: maximum-prefix-length-match

Attribute Type: uint8

Attribute Range: 0-128

Attribute Name: minimum-prefix-length-match

Attribute Type: uint8

Attribute Range: 0-128

### Netconf edit-config payload

```
<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <prefix>
    <prefix-list-type>ip</prefix-list-type>
    <config>
      <prefix-list-type>ip</prefix-list-type>
      <prefix-list-name>WORD</prefix-list-name>
    </config>
    <prefix-list-name>WORD</prefix-list-name>
  <prefix-entries>
  <prefix-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv6>
    <entry>
      <ipv6-prefix-addr>any</ipv6-prefix-addr>
      <config>
        <ipv6-prefix-addr>any</ipv6-prefix-addr>
        <action>deny</action>
        <minimum-prefix-length-match>0</minimum-prefix-length-match> <!--
operation="delete"-->
        </config>
        <action>deny</action>
        <maximum-prefix-length-match>0</maximum-prefix-length-match> <!--
operation="delete"-->
      </entry>
    </ipv6>
  </prefix-entry>
</prefix-entries>
</prefix>
</prefixes>
```

### Command Syntax

```
(seq <1-4294967295>|) (deny|permit) ge <0-128> le <0-128>
```

## Configure entry minimum-prefix-length-match

Minimum prefix length match

This command is supported when following feature are enabled ipv6 feature

Attribute Name: minimum-prefix-length-match

Attribute Type: uint8

Attribute Range: 0-128

Attribute Name: maximum-prefix-length-match

Attribute Type: uint8

Attribute Range: 0-128

### Netconf edit-config payload

```
<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <prefix>
    <prefix-list-type>ip</prefix-list-type>
    <config>
      <prefix-list-type>ip</prefix-list-type>
      <prefix-list-name>WORD</prefix-list-name>
    </config>
    <prefix-list-name>WORD</prefix-list-name>
  <prefix-entries>
    <prefix-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv6>
        <entry>
          <ipv6-prefix-addr>any</ipv6-prefix-addr>
          <config>
            <ipv6-prefix-addr>any</ipv6-prefix-addr>
            <action>deny</action>
            <maximum-prefix-length-match>0</maximum-prefix-length-match> <!--
operation="delete"-->
          </config>
            <action>deny</action>
            <minimum-prefix-length-match>0</minimum-prefix-length-match> <!--
operation="delete"-->
          </entry>
        </ipv6>
      </prefix-entry>
    </prefix-entries>
  </prefix>
</prefixes>
```

### Command Syntax

```
(seq <1-4294967295>|) (deny|permit) le <0-128> ge <0-128>
```

## Configure entry minimum-prefix-length-match

Minimum prefix length match

This command is supported when following feature are enabled ipv6 feature

Attribute Name: minimum-prefix-length-match

Attribute Type: uint8

Attribute Range: 0-128

### Netconf edit-config payload

```
<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <prefix>
    <prefix-list-type>ip</prefix-list-type>
    <config>
      <prefix-list-type>ip</prefix-list-type>
      <prefix-list-name>WORD</prefix-list-name>
    </config>
    <prefix-list-name>WORD</prefix-list-name>
  </prefix-entries>
  <prefix-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv6>
      <entry>
        <ipv6-prefix-addr>any</ipv6-prefix-addr>
        <config>
          <ipv6-prefix-addr>any</ipv6-prefix-addr>
          <action>deny</action>
        </config>
        <action>deny</action>
        <minimum-prefix-length-match>0</minimum-prefix-length-match> <!--
operation="delete"-->
      </entry>
    </ipv6>
  </prefix-entry>
</prefix-entries>
</prefix>
</prefixes>
```

### Command Syntax

```
(seq <1-4294967295>|) (deny|permit) ge <0-128>
```

## Configure entry maximum-prefix-length-match

Maximum prefix length match

This command is supported when following feature are enabled ipv6 feature

Attribute Name: maximum-prefix-length-match

Attribute Type: uint8

Attribute Range: 0-128

**Netconf edit-config payload**

```

<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <prefix>
    <prefix-list-type>ip</prefix-list-type>
    <config>
      <prefix-list-type>ip</prefix-list-type>
      <prefix-list-name>WORD</prefix-list-name>
    </config>
    <prefix-list-name>WORD</prefix-list-name>
  </prefix-entries>
  <prefix-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv6>
      <entry>
        <ipv6-prefix-addr>any</ipv6-prefix-addr>
        <config>
          <ipv6-prefix-addr>any</ipv6-prefix-addr>
          <action>deny</action>
        </config>
        <action>deny</action>
        <maximum-prefix-length-match>0</maximum-prefix-length-match> <!--
operation="delete"-->
      </entry>
    </ipv6>
  </prefix-entry>
</prefix-entries>
</prefix>
</prefixes>

```

**Command Syntax**

```
(seq <1-4294967295>|) (deny|permit) le <0-128>
```

**Configure disable ipv4 sequence display**

Use this attribute to configure prefix list sequence number. Include and exclude sequence numbers in nonvolatile generation (NVGEN).

Attribute Name: disable-ipv4-sequence-display

Attribute Type: empty

**Netconf edit-config payload**

```

<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <global>
    <config>
      </disable-ipv4-sequence-display><!-- operation="delete"-->
    </config>
  </global>

```

```
</prefixes>
```

## Command Syntax

```
no ip prefix-list sequence-number
```

---

## Configure disable ipv6 sequence display

Use this attribute to configure prefix list sequence number. Include and exclude sequence numbers in nonvolatile generation (NVGEN).

Attribute Name: disable-ipv6-sequence-display

Attribute Type: empty

## Netconf edit-config payload

```
<prefixes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <global>
    <config>
      </disable-ipv6-sequence-display><!-- operation="delete"-->
    </config>
  </global>
</prefixes>
```

## Command Syntax

```
no ipv6 prefix-list sequence-number
```

---

## clear ip prefix-list

### Netconf RPC payload

```
<clear-prefix-list-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list"/>
```

### Command Syntax

```
clear ip prefix-list
```

---

## clear ipv6 prefix-list

### Netconf RPC payload

```
<clear-prefix-list-ipv6-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list"/>
```

### Command Syntax

```
clear ipv6 prefix-list
```

---

## clear ip prefix-list WORD (A.B.C.D/M|)

Attribute Name: prefix-list-name

Attribute Type: string

Attribute Name: prefix

Attribute Type: string

### Netconf RPC payload

```
<clear-ipv4-prefix-list xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <prefix-list-name>WORD</prefix-list-name>
  <prefix>A.B.C.D/M</prefix>
</clear-ipv4-prefix-list>
```

### Command Syntax

```
clear ip prefix-list WORD (A.B.C.D/M|)
```

---

## clear ipv6 prefix-list WORD (X:X::X:X/M|)

Attribute Name: prefix-list-name

Attribute Type: string

Attribute Name: prefix

Attribute Type: string

### Netconf RPC payload

```
<clear-ipv6-prefix-list xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-prefix-list">
  <prefix-list-name>WORD</prefix-list-name>
  <prefix>X:X::X:X/M</prefix>
</clear-ipv6-prefix-list>
```

### Command Syntax

```
clear ipv6 prefix-list WORD (X:X::X:X/M|)
```

---

## IPI-ISIS

---

### Configure vrf name

VRF Name to associate with this instance

Attribute Name: vrf-name

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
</isis>
```

```
    <vrf-name>WORD</vrf-name>
  </isis-instance>
</isis-instances>
</isis>
```

## Command Syntax

```
router isis WORD WORD
```

---

## Configure instance

Use this attribute to initiate an ISIS routing instance. Configure at least one NET to start routing.

Attribute Name: instance

Attribute Type: string

Attribute Name: vrf-name

Attribute Type: string

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance> <!-- operation="delete"-->
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
        <vrf-name>WORD</vrf-name>
      </config>
    </isis-instance>
  </isis-instances>
</isis>
```

## Command Syntax

```
router isis WORD
```

---

## Configure disable gr capability

Use this attribute to enable the GR

Attribute Name: disable-gr-capability

Attribute Type: uint8

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </disable-gr-capability><!-- operation="delete"-->
  </isis-instances>
</isis>
```

```

</isis-instance>
</isis-instances>
</isis>

```

## Command Syntax

```
no capability restart graceful
```

---

## Configure isis-instance disable-gr-capability

Use this attribute to enable the GR

Attribute Name: disable-gr-capability

Attribute Type: uint8

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
  </disable-gr-capability><!-- operation="delete"-->
</isis-instance>
</isis-instances>
</isis>

```

## Command Syntax

```
no capability restart
```

---

## Configure disable adjacency check

Use this attribute to configure the policy of adjacency based on the protocol related TLVs in the ISIS Hello packet. ISIS checks adjacency with protocol related TLVs including Protocols Supported TLV or IP Interface Address TLV by default. The command with no parameter disables this check.

Attribute Name: disable-adjacency-check

Attribute Type: uint8

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
  </disable-adjacency-check><!-- operation="delete"-->
</isis-instance>
</isis-instances>

```

```
</isis>
```

## Command Syntax

```
no adjacency-check
```

---

## Configure authentication send only

Use this attribute to set the send-only option at the instance level. Use this command before configuring the authentication mode and authentication key-chain, so that the implementation of authentication goes smoothly. That is, the routers will have more time for the keys to be configured on each router if authentication is inserted only on the packets being sent, not checked on packets being received. After all routers that must communicate are configured with this command, enable the authentication mode and key chain on each router.

Attribute Name: authentication-send-only

Attribute Type: enum (level-1-only|level-2-only|level-1-2)

Default Value: level-1-2

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
      <authentication-send-only>3</authentication-send-only> <!-- operation="delete"-->
    >
  </isis-instance>
</isis-instances>
</isis>
```

## Command Syntax

```
authentication send-only level-1
```

---

## Configure isis-instance authentication-send-only

Use this attribute to set the send-only option at the instance level. Use this command before configuring the authentication mode and authentication key-chain, so that the implementation of authentication goes smoothly. That is, the routers will have more time for the keys to be configured on each router if authentication is inserted only on the packets being sent, not checked on packets being received. After all routers that must communicate are configured with this command, enable the authentication mode and key chain on each router.

Attribute Name: authentication-send-only

Attribute Type: enum (level-1-only|level-2-only|level-1-2)

Default Value: level-1-2

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
```

```

    <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
  <authentication-send-only>3</authentication-send-only> <!-- operation="delete"-->
>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
authentication send-only level-2
```

---

## Configure distance

Use this attribute to set the administrative distance for all IPv4 routes.

Attribute Name: distance

Attribute Type: uint8

Default Value: 115

Attribute Range: 1-255

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
      <distance>1</distance> <!-- operation="delete"-->
    </isis-instance>
  </isis-instances>
</isis>

```

### Command Syntax

```
distance <1-255>
```

---

## Configure dynamic host name

Use this attribute to configure the hostname to be advertised for an ISIS instance using the dynamic hostname exchange mechanism (RFC 2763) and system-ID-to-hostname translation. This command configures a hostname to be used for the Dynamic Hostname Exchange Mechanism and System-ID to hostname translation. Use the routing area tag as the hostname, not the router's global hostname

Attribute Name: dynamic-host-name

Attribute Type: enum (dynamic-hostname|area-tag)

Default Value: dynamic-hostname

## Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
  <dynamic-host-name>dynamic-hostname</dynamic-host-name> <!-- operation="delete"-
->
</isis-instance>
</isis-instances>
</isis>

```

## Command Syntax

```
dynamic-hostname (area-tag|)
```

---

## Configure ignore lsp errors

Use this attribute to ignore LSPs with checksum errors. By default, ISIS validates checksum for LSP whenever it receives LSPs and if the checksum has an error, the LSP will be dropped. Configuring this command to ignore the LSP checksum error and treat it as if checksum is passed.

Attribute Name: ignore-lsp-errors

Attribute Type: empty

## Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
  </ignore-lsp-errors><!-- operation="delete"-->
</isis-instance>
</isis-instances>
</isis>

```

## Command Syntax

```
ignore-lsp-errors
```

---

## Configure lfa hold timer

LFA terminate-hold-on interval

Attribute Name: lfa-hold-timer

Attribute Type: int32

Default Value: 1000

---

Attribute Range: 100-100000

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
  <lfa-hold-timer>100</lfa-hold-timer> <!-- operation="delete"-->
</isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
fast-reroute terminate-hold-on interval <100-100000>
```

---

## Configure protocol topology

Use this attribute to configure ISIS Protocol Topology Support.

Attribute Name: protocol-topology

Attribute Type: empty

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
  </protocol-topology><!-- operation="delete"-->
</isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
protocol-topology
```

---

## Configure level capability

Use this attribute to set the IS to the specified level of routing. Changing is-type brings down, then brings up a particular level of routing. There is a limitation: Only one ISIS instance can run Level-2 routing (either Level-2 only IS, or Level-1-2 IS)

Attribute Name: level-capability

Attribute Type: enum (level-1|level-2-only|level-1-2)

Default Value: level-1-2

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
  <level-capability>level-1-2</level-capability> <!-- operation="delete"-->
</isis-instance>
</isis-instances>
</isis>
```

## Command Syntax

```
is-type (level-1|level-2-only|level-1-2)
```

## Configure isis-instance authentication-send-only

Use this attribute to set the send-only option at the instance level. Use this command before configuring the authentication mode and authentication key-chain, so that the implementation of authentication goes smoothly. That is, the routers will have more time for the keys to be configured on each router if authentication is inserted only on the packets being sent, not checked on packets being received. After all routers that must communicate are configured with this command, enable the authentication mode and key chain on each router.

Attribute Name: authentication-send-only

Attribute Type: enum (level-1-only|level-2-only|level-1-2)

Default Value: level-1-2

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
  <authentication-send-only>level-1-2</authentication-send-only> <!--
operation="delete"-->
</isis-instance>
</isis-instances>
</isis>
```

## Command Syntax

```
authentication send-only (level-1-only|level-2-only|level-1-2|)
```

## Configure incremental spf levels

Use this attribute to enable incremental SPF for a routing process

Attribute Name: incremental-spf-levels

Attribute Type: enum (level-1|level-2-only|level-1-2)

Default Value: level-1-2

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
      <incremental-spf-levels>level-1-2</incremental-spf-levels> <!--
operation="delete"-->
    </isis-instance>
  </isis-instances>
</isis>
```

### Command Syntax

```
ispf (level-1|level-2-only|level-1-2|)
```

---

## Configure priority tag

Use this attribute to set a high priority tag value

Attribute Name: priority-tag

Attribute Type: uint32

Attribute Range: 1-4294967295

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
      <priority-tag>1</priority-tag> <!-- operation="delete"-->
    </isis-instance>
  </isis-instances>
</isis>
```

### Command Syntax

```
ip route high-priority tag <1-4294967295>
```

---

## Configure enable bfd all interfaces

Use this attribute to enable the Bidirectional Forwarding Detection (BFD) feature on the interfaces enabled with this ISIS instance. This command sets BFD fall-over check for all the neighbors under specified process.

Attribute Name: enable-bfd-all-interfaces

Attribute Type: empty

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
  </enable-bfd-all-interfaces><!-- operation="delete"-->
</isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
bfd all-interfaces
```

---

## Configure maximum area addresses

Use this attribute to set the maximum number of ISIS areas that can be configured on this router with the net command. By default, ISIS permits a maximum of three areas that can be defined on a router.

Attribute Name: maximum-area-addresses

Attribute Type: uint8

Default Value: 3

Attribute Range: 3-254

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
  <maximum-area-addresses>3</maximum-area-addresses> <!-- operation="delete"-->
</isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
max-area-address <3-254>
```

---

## Configure context name

Use this attribute to set the SNMP context name for ISIS instance.

Attribute Name: context-name

Attribute Type: string

Attribute Range: 1-32

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
      <context-name>WORD</context-name> <!-- operation="delete"-->
    </isis-instance>
  </isis-instances>
</isis>
```

### Command Syntax

```
snmp context-name WORD
```

---

## Configure area password

Use this attribute to set the authentication password for the Level-1 area and to set authentication on Level-1 SNP PDUs. This command enables authentication when receiving and sending LSP and SNP PDU in Level-1 areas. Area password must be the same for all the ISIS routers in the same area

Attribute Name: area-password

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <area-authentication>
      <config>
        <area-password>WORD</area-password>
      </config>
    </area-authentication>
  </isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
area-password WORD
```

---

## Configure sequence number packet

Use this attribute to set the authentication password for the Level-1 area and to set authentication on Level-1 SNP PDUs. This command enables authentication when receiving and sending LSP and SNP PDU in Level-1 areas. Area password must be the same for all the ISIS routers in the same area

Attribute Name: sequence-number-packet

Attribute Type: enum (send-only|validate)

Attribute Name: area-password

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <area-authentication>
      <config>
        <area-password>WORD</area-password> <!-- operation="delete"-->
        <sequence-number-packet>send-only</sequence-number-packet> <!--
operation="delete"-->
      </config>
    </area-authentication>
  </isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
area-password WORD authenticate snp (send-only|validate)
```

---

## Configure net

Use this attribute to add a Network Entity Title (NET) for the instance. On a router running ISIS, a NET can be 8 to 20 bytes in length. The last byte is always the n-selector, and must be zero. The n-selector indicates no transport entity, and means that the packet is for the routing software of the system. The six bytes directly preceding the n-selector are the system ID. The system ID length is a fixed size and cannot be changed. The system ID must be unique throughout each area (Level 1) and throughout the backbone (Level 2). The bytes preceding the system ID are the area ID, which can be from 1 - 13 bytes in length. By default, a maximum of three NETs per router are allowed with a different area ID but the system ID should be the same for all NETs. You can increase the number of area IDs per system ID with the max-area-address command.

Attribute Name: net

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
```

```

<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
</network-entity-title>
<config>
  <net>NET</net> <!-- operation="delete"-->
</config>
</network-entity-title>
</isis-instance>
</isis-instances>
</isis>

```

## Command Syntax

```
net NET
```

---

## Configure domain password

Use this attribute to set the authentication password for the Level-2 domain, and optionally, the authentication password on Level-2 SNP PDUs. Configuring this command to enable authentication when receiving and sending LSP and SNP PDU in Level-2 domain. Domain password must be the same in Level-2 domain.

Attribute Name: domain-password

Attribute Type: string

## Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <domain-authentication>
    <config>
      <domain-password>WORD</domain-password>
    </config>
  </domain-authentication>
</isis>

```

## Command Syntax

```
domain password WORD
```

---

## Configure domain snp

Use this attribute to set the authentication password for the Level-2 domain, and optionally, the authentication password on Level-2 SNP PDUs. Configuring this command to enable authentication when receiving and sending LSP and SNP PDU in Level-2 domain. Domain password must be the same in Level-2 domain.

Attribute Name: domain-snp

Attribute Type: enum (send-only|validate)

Attribute Name: domain-password

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <domain-authentication>
      <config>
        <domain-password>WORD</domain-password> <!-- operation="delete"-->
        <domain-snp>send-only</domain-snp> <!-- operation="delete"-->
      </config>
    </domain-authentication>
  </isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
domain password WORD authenticate snp (send-only|validate)
```

---

## Configure style

Use this attribute to configure the ISIS metric style

Attribute Name: style

Attribute Type: enum (narrow|wide|transition|narrow transition|wide transition)

Attribute Name: level-number

Attribute Type: enum (level-1|level-2|level-1-2)

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
</isis>
```

```

<metric>
<config>
  <level-number>level-1-2</level-number> <!-- operation="delete"-->
  <style>1</style> <!-- operation="delete"-->
</config>
</metric>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
metric-style (narrow) level-1-2
```

---

## Configure level number

Use this attribute to configure the ISIS metric style

Attribute Name: style

Attribute Type: enum (narrow|wide|transition|narrow transition|wide transition)

Attribute Name: level-number

Attribute Type: enum (level-1|level-2|level-1-2)

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<metric>
<config>
  <level-number>level-1-2</level-number> <!-- operation="delete"-->
  <style>2</style> <!-- operation="delete"-->
</config>
</metric>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
metric-style (wide) level-1-2
```

---

## Configure metric style

Use this attribute to configure the ISIS metric style

Attribute Name: style

Attribute Type: enum (narrow|wide|transition|narrow transition|wide transition)

Attribute Name: level-number

Attribute Type: enum (level-1|level-2|level-1-2)

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <metric>
    <config>
      <level-number>level-1-2</level-number> <!-- operation="delete"-->
      <style>3</style> <!-- operation="delete"-->
    </config>
  </metric>
</isis>
```

### Command Syntax

```
metric-style (transition) level-1-2
```

---

## Configure metric style

Use this attribute to configure the ISIS metric style

Attribute Name: style

Attribute Type: enum (narrow|wide|transition|narrow transition|wide transition)

Attribute Name: level-number

Attribute Type: enum (level-1|level-2|level-1-2)

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <metric>
    <config>
      <level-number>level-1-2</level-number> <!-- operation="delete"-->
      <style>4</style> <!-- operation="delete"-->
    </config>
  </metric>
</isis>
```

```
</isis>
```

## Command Syntax

```
metric-style (narrow transition) level-1-2
```

---

## Configure metric style

Use this attribute to configure the ISIS metric style

Attribute Name: style

Attribute Type: enum (narrow|wide|transition|narrow transition|wide transition)

Attribute Name: level-number

Attribute Type: enum (level-1|level-2|level-1-2)

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <metric>
    <config>
      <level-number>level-1-2</level-number> <!-- operation="delete"-->
      <style>5</style> <!-- operation="delete"-->
    </config>
  </metric>
</isis>
```

## Command Syntax

```
metric-style (wide transition) level-1-2
```

---

## Configure metric level-number

Use this attribute to configure the ISIS metric style

This command is supported when following feature are enabled wide metric feature

Attribute Name: level-number

Attribute Type: enum (level-1|level-2|level-1-2)

Attribute Name: style

Attribute Type: enum (narrow|wide|transition|narrow transition|wide transition)

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
```

```

<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
</metric>
<config>
  <style>narrow</style> <!-- operation="delete"-->
  <level-number>level-1-2</level-number> <!-- operation="delete"-->
</config>
</metric>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
metric-style (narrow|wide|transition|narrow transition|wide transition) (level-1|level-2|)
```

---

## Configure lsp refresh interval

Use this attribute to set the LSP refresh interval. IP Infusion Inc. recommends making the lsp-refresh-interval smaller than max-lsp-lifetime value.

Attribute Name: lsp-refresh-interval

Attribute Type: uint16

Default Value: 900

Attribute Range: 1-65535

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
</timers>
<config>
  <lsp-refresh-interval>1</lsp-refresh-interval> <!-- operation="delete"-->
</config>
</timers>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
lsp-refresh-interval <1-65535>
```

---

## Configure lsp lifetime interval

Use this attribute to set the maximum LSP lifetime. You must set max-lsp-lifetime greater than lsp-refreshinterval.

Attribute Name: lsp-lifetime-interval

Attribute Type: uint16

Default Value: 1200

Attribute Range: 350-65535

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <timers>
    <config>
      <lsp-lifetime-interval>350</lsp-lifetime-interval> <!-- operation="delete"-->
    </config>
  </timers>
</isis>
```

### Command Syntax

```
max-lsp-lifetime <350-65535>
```

---

## Configure enable

Use this attribute to redistribute reachability information from one level to the other level. If an distribute-list name is given with this command for an access list that does not exist, the routes are still redistributed.

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <address-family-ipv6>
    <level-1-into-2-redistributes>
      <redistribute-level-1-into-2> <!-- operation="delete"-->
    </enable>
  </address-family-ipv6>
</isis>
```

```

    <config>
      </enable>
    </config>
  </redistribute-level-1-into-2>
</level-1-into-2-redistributes>
</address-family-ipv6>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
redistribute isis level-1 into level-2
```

---

## Configure level 1 acl

Use this attribute to redistribute reachability information from one level to the other level. If an distribute-list name is given with this command for an access list that does not exist, the routes are still redistributed.

Attribute Name: level-1-acl

Attribute Type: string

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <address-family-ipv6>
    <level-1-into-2-redistributes>
      <redistribute-level-1-into-2>
        </enable>
      </redistribute-level-1-into-2>
    </level-1-into-2-redistributes>
  </address-family-ipv6>
  </isis-instance>
</isis>

```

### Command Syntax

```
redistribute isis level-1 into level-2 distribute-list WORD
```

---

## Configure level-2-into-1-redistributes enable

Use this attribute to redistribute reachability information from one level to the other level. If an distribute-list name is given with this command for an access list that does not exist, the routes are still redistributed.

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <address-family-ipv6>
      <level-2-into-1-redistributes>
        <redistribute-level-2-into-1> <!-- operation="delete"-->
          </enable>
        <config>
          </enable>
        </config>
      </redistribute-level-2-into-1>
    </level-2-into-1-redistributes>
  </address-family-ipv6>
</isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
redistribute isis level-2 into level-1
```

---

## Configure level 2 acl

Use this attribute to redistribute reachability information from one level to the other level. If an distribute-list name is given with this command for an access list that does not exist, the routes are still redistributed.

Attribute Name: level-2-acl

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <address-family-ipv6>
```

```

<level-2-into-1-redistributes>
<redistribute-level-2-into-1>
  </enable>
  <config>
    </enable><!-- operation="delete"-->
  </config>
  <level-2-acl>WORD</level-2-acl> <!-- operation="delete"-->
</redistribute-level-2-into-1>
</level-2-into-1-redistributes>
</address-family-ipv6>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
redistribute isis level-2 into level-1 distribute-list WORD
```

---

## Configure originate

Use this attribute to set originate reachability information to Default destination into LSP. There is no default information in Level-2 domain by default, while Level-1 router calculates default to L1L2 route during SPF calculation. This command enables to originate default route into Level-2 domain.

Attribute Name: originate

Attribute Type: enum (originate|originate level-1|originate always)

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<address-family-ipv6>
<default-route-informations>
<default-route-information> <!-- operation="delete"-->
  <originate>originate</originate>
  <config>
    <originate>originate</originate>
  </config>
</default-route-information>
</default-route-informations>
</address-family-ipv6>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
default-information (originate|originate level-1|originate always)
```

---

## Configure route map name

Route-map Name

Attribute Name: route-map-name

Attribute Type: string

Default Value: ""

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <address-family-ipv6>
      <default-route-informations>
        <default-route-information>
          <originate>originate</originate>
          <config>
            <originate>originate</originate>
          </config>
          <route-map-name>WORD</route-map-name> <!-- operation="delete"-->
        </default-route-information>
      </default-route-informations>
    </address-family-ipv6>
  </isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
default-information (originate|originate level-1|originate always) route-map WORD
```

---

## Configure afi name

Use this attribute to configure IPv6 routing specific configuration

Attribute Name: afi-name

Attribute Type: enum (ipv6)

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <address-family-ipv6>
```

```
<config>
  <afi-name>1</afi-name>
</config>
</address-family-ipv6>
</isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
address-family ipv6
```

---

## Configure address-family-ipv6 afi-name

Use this attribute to configure IPv6 routing specific configuration

Attribute Name: afi-name

Attribute Type: enum (ipv6)

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <address-family-ipv6>
    <config>
      <afi-name>1</afi-name>
    </config>
  </address-family-ipv6>
</isis>
```

### Command Syntax

```
address-family ipv6 unicast
```

---

## Configure address-family-ipv6 disable-adjacency-check

Use this attribute to configure the policy of adjacency based on the protocol related TLVs in the ISIS Hello packet. ISIS checks adjacency with protocol related TLVs including Protocols Supported TLV or IP Interface Address TLV by default. The command with no parameter disables this check.

Attribute Name: disable-adjacency-check

Attribute Type: uint8

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
```

```

<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<address-family-ipv6>
<config>
  </disable-adjacency-check><!-- operation="delete"-->
</config>
</address-family-ipv6>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
no adjacency-check
```

---

## Configure administrative distance

Use this attribute to set the administrative distance for all IPv6 routes

Attribute Name: administrative-distance

Attribute Type: uint32

Default Value: 115

Attribute Range: 1-255

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<address-family-ipv6>
<config>
  <administrative-distance>1</administrative-distance> <!-- operation="delete"-->
->
</config>
</address-family-ipv6>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
distance <1-255>
```

---

## Configure ipv6 metric value

Use this attributes to redistribute routes from another protocol into the ISIS routing table. With metric, metric-type, level and route-map options.

Attribute Name: ipv6-metric-value

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-16777215

Attribute Name: ipv6-metric-type

Attribute Type: enum (internal|external)

Default Value: internal

Attribute Name: ipv6-level

Attribute Type: enum (level-1|level-2|level-1-2)

Default Value: level-2

Attribute Name: ipv6-route-map

Attribute Type: string

Default Value: ""

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <address-family-ipv6>
      <redistributions>
        <redistribute>
          <ipv6-protocol-type>kernel</ipv6-protocol-type>
          <config>
            <ipv6-protocol-type>kernel</ipv6-protocol-type>
            <ipv6-metric-type>internal</ipv6-metric-type>
            <ipv6-level>level-2</ipv6-level>
            <ipv6-route-map>WORD</ipv6-route-map>
          </config>
          <ipv6-metric-value>0</ipv6-metric-value>
        </redistribute>
      </redistributions>
    </address-family-ipv6>
  </isis-instance>
</isis-instances>
</isis>
```

## Command Syntax

```
redistribute (kernel|connected|static|rip|ospf|bgp) ({ metric-type
  (internal|external)| level-1|level-2|level-1-2| route-map WORD| metric <0-
  16777215> }|)
```

---

## Configure prefix

Use this attribute to configure the summary prefix to summarize IPv6 reachability information.

Attribute Name: prefix

Attribute Type: string

Attribute Name: level

Attribute Type: enum (level-1|level-2|level-1-2)

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 1-63

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <address-family-ipv6>
      <summary-prefixes>
        <summary-prefix> <!-- operation="delete"-->
          <prefix>X:X::X:X/M</prefix>
          <config>
            <prefix>X:X::X:X/M</prefix>
            <level>level-1</level>
            <metric>1</metric>
          </config>
        </summary-prefix>
      </summary-prefixes>
    </address-family-ipv6>
  </isis-instance>
</isis-instances>
</isis>
```

## Command Syntax

```
summary-prefix X:X::X:X/M (level-1|level-2|level-1-2) (metric <1-63>|)
```

---

## Configure level

Use this attribute to configure the ISIS Multi-topology

Attribute Name: level

Attribute Type: enum (level-1|level-2|level-1-2|level-1 transition|level-1-2 transition|level-2 transition)

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <address-family-ipv6>
    <multi-topologies>
    <multi-topology>
      <level>level-1-2</level>
      <config>
        <level>level-1-2</level>
      </config>
    </multi-topology>
    </multi-topologies>
  </address-family-ipv6>
</isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
multi-topology (level-1)
```

---

## Configure multi-topologies level

Use this attribute to configure the ISIS Multi-topology

Attribute Name: level

Attribute Type: enum (level-1|level-2|level-1-2|level-1 transition|level-1-2 transition|level-2 transition)

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <address-family-ipv6>
    <multi-topologies>
    <multi-topology>
      <level>level-1-2</level>
      <config>
        <level>level-1-2</level>
      </config>
    </multi-topology>
    </multi-topologies>
  </address-family-ipv6>
</isis-instance>
</isis-instances>
</isis>
```

```

</multi-topology>
</multi-topologies>
</address-family-ipv6>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
multi-topology (level-2)
```

---

## Configure multi-topologies level

Use this attribute to configure the ISIS Multi-topology

Attribute Name: level

Attribute Type: enum (level-1|level-2|level-1-2|level-1 transition|level-1-2 transition|level-2 transition)

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<address-family-ipv6>
<multi-topologies>
<multi-topology>
  <level>level-1-2</level>
  <config>
    <level>level-1-2</level>
  </config>
</multi-topology>
</multi-topologies>
</address-family-ipv6>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
multi-topology (level-1-2)
```

---

## Configure multi-topologies level

Use this attribute to configure the ISIS Multi-topology

Attribute Name: level

Attribute Type: enum (level-1|level-2|level-1-2|level-1 transition|level-1-2 transition|level-2 transition)

**Netconf edit-config payload**

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<address-family-ipv6>
<multi-topologies>
<multi-topology>
  <level>level-1-2</level>
  <config>
    <level>level-1-2</level>
  </config>
</multi-topology>
</multi-topologies>
</address-family-ipv6>
</isis-instance>
</isis-instances>
</isis>

```

**Command Syntax**

```
multi-topology (level-1 transition)
```

**Configure multi-topologies level**

Use this attribute to configure the ISIS Multi-topology

Attribute Name: level

Attribute Type: enum (level-1|level-2|level-1-2|level-1 transition|level-1-2 transition|level-2 transition)

**Netconf edit-config payload**

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<address-family-ipv6>
<multi-topologies>
<multi-topology>
  <level>level-1-2</level>
  <config>
    <level>level-1-2</level>
  </config>
</multi-topology>
</multi-topologies>
</address-family-ipv6>

```

```

</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
multi-topology (level-1-2 transition)
```

---

## Configure multi-topologies level

Use this attribute to configure the ISIS Multi-topology

Attribute Name: level

Attribute Type: enum (level-1|level-2|level-1-2|level-1 transition|level-1-2 transition|level-2 transition)

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<address-family-ipv6>
<multi-topologies>
<multi-topology>
  <level>level-1-2</level>
  <config>
    <level>level-1-2</level>
  </config>
</multi-topology>
</multi-topologies>
</address-family-ipv6>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
multi-topology (level-2 transition)
```

---

## Configure access list name

Use this attribute to set the administrative distance for specific IPv4 routes.

Attribute Name: access-list-name

Attribute Type: string

Default Value: ""

Attribute Name: value

Attribute Type: uint8

Attribute Range: 1-255

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<distances>
<distance>
  <system-id>WORD</system-id>
  <config>
    <system-id>System-ID</system-id>
    <value>1</value> <!-- operation="delete"-->
  </config>
  <access-list-name>WORD</access-list-name> <!-- operation="delete"-->
</distance>
</distances>
</isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
distance <1-255> System-ID (WORD|)
```

---

## Configure set bit on boot

Overload interval after reboot

Attribute Name: set-bit-on-boot

Attribute Type: union

Attribute Name: enabled

Attribute Type: empty

Attribute Name: suppress-type

Attribute Type: enum (default|external|interlevel|external interlevel)

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<lsp-over-load>
<config>
```

```

    </enabled><!-- operation="delete"-->
    <suppress-type>default</suppress-type> <!-- operation="delete"-->
    <set-bit-on-boot>default</set-bit-on-boot> <!-- operation="delete"-->
</config>
</lsp-over-load>
</isis-instance>
</isis-instances>
</isis>

```

## Command Syntax

```

set-overload-bit { suppress (external|interlevel|external interlevel) | on-startup
  (wait-for-bgp|<5-86400>) }

```

## Configure enabled

Use this attribute to set the overload-bit in self-LSPs. If the overload-bit is set in LSPs, the router is not used as a transit router during SPF calculation. This configuration causes a router to update its own LSP with the overload bit set and causes the other routers not to use this router as a transit or forwarding router. The router continues to receive LSPs when the overload bit is set. If the on-startup option is specified, the router sets the overload bit only at startup, then clears the bit after the specified interval has elapsed. If the on-startup option is specified using the wait-for-bgp option, the overload bit is setup at startup, then the bit is cleared after the BGP router signals it has finished converging or if the router does not signal it has finished converging in 10 minutes. If there is no BGP process running, the overload bit clears immediately.

Attribute Name: enabled

Attribute Type: empty

## Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
</lsp-over-load>
<config>
  </enabled>
</config>
</lsp-over-load>
</isis-instance>
</isis-instances>
</isis>

```

## Command Syntax

```

set-overload-bit

```

---

## Configure level-1-into-2-redistributes enable

Use this attribute to redistribute reachability information from one level to the other level. If an distribute-list name is given with this command for an access list that does not exist, the routes are still redistributed.

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <address-family-ipv4>
      <level-1-into-2-redistributes>
        <redistribute-level-1-into-2> <!-- operation="delete"-->
          </enable>
        <config>
          </enable>
        </config>
      </redistribute-level-1-into-2>
    </level-1-into-2-redistributes>
  </address-family-ipv4>
</isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
redistribute isis level-1 into level-2
```

---

## Configure redistribute-level-1-into-2 level-1-acl

Use this attribute to redistribute reachability information from one level to the other level. If an distribute-list name is given with this command for an access list that does not exist, the routes are still redistributed.

Attribute Name: level-1-acl

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <address-family-ipv4>
```

```

<level-1-into-2-redistributes>
<redistribute-level-1-into-2>
  </enable>
  <config>
    </enable><!-- operation="delete"-->
  </config>
  <level-1-acl>WORD</level-1-acl> <!-- operation="delete"-->
</redistribute-level-1-into-2>
</level-1-into-2-redistributes>
</address-family-ipv4>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
redistribute isis level-1 into level-2 distribute-list WORD
```

---

## Configure level-2-into-1-redistributes enable

Use this attribute to redistribute reachability information from one level to the other level. If an distribute-list name is given with this command for an access list that does not exist, the routes are still redistributed.

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<address-family-ipv4>
<level-2-into-1-redistributes>
<redistribute-level-2-into-1> <!-- operation="delete"-->
  </enable>
  <config>
    </enable>
  </config>
</redistribute-level-2-into-1>
</level-2-into-1-redistributes>
</address-family-ipv4>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
redistribute isis level-2 into level-1
```

---

## Configure redistribute-level-2-into-1 level-2-acl

Use this attribute to redistribute reachability information from one level to the other level. If an distribute-list name is given with this command for an access list that does not exist, the routes are still redistributed.

Attribute Name: level-2-acl

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<address-family-ipv4>
<level-2-into-1-redistributes>
<redistribute-level-2-into-1>
  </enable>
  <config>
    </enable><!-- operation="delete"-->
  </config>
  <level-2-acl>WORD</level-2-acl> <!-- operation="delete"-->
</redistribute-level-2-into-1>
</level-2-into-1-redistributes>
</address-family-ipv4>
</isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
redistribute isis level-2 into level-1 distribute-list WORD
```

---

## Configure default-route-informations originate

Use this attribute to originate reachability information to Default destination into LSP. There is no default information in Level-2 domain by default, while Level-1 router calculates default to L1L2 route during SPF calculation. This command enables to originate default route into Level-2 domain.

Attribute Name: originate

Attribute Type: enum (originate|originate level-1|originate always)

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
```

```

    </config>
<address-family-ipv4>
<default-route-informations>
<default-route-information> <!-- operation="delete"-->
  <originate>originate</originate>
  <config>
    <originate>originate</originate>
  </config>
</default-route-information>
</default-route-informations>
</address-family-ipv4>
</isis-instance>
</isis-instances>
</isis>

```

## Command Syntax

```
default-information (originate|originate level-1|originate always)
```

---

## Configure default-route-information route-map-name

Route Map Name Attribute

Attribute Name: route-map-name

Attribute Type: string

Default Value: ""

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<address-family-ipv4>
<default-route-informations>
<default-route-information>
  <originate>originate</originate>
  <config>
    <originate>originate</originate>
  </config>
  <route-map-name>WORD</route-map-name> <!-- operation="delete"-->
</default-route-information>
</default-route-informations>
</address-family-ipv4>
</isis-instance>
</isis-instances>
</isis>

```

## Command Syntax

```
default-information (originate|originate level-1|originate always) route-map WORD
```

---

## Configure metric value

IS-IS metric

Attribute Name: metric-value

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-16777215

Attribute Name: metric-type

Attribute Type: enum (internal|external)

Default Value: internal

Attribute Name: route-map

Attribute Type: string

Default Value: ""

Attribute Name: level

Attribute Type: enum (level-1|level-2|level-1-2)

Default Value: level-2

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <address-family-ipv4>
    <redistributions>
      <redistribute>
        <protocol-type>kernel</protocol-type>
        <config>
          <protocol-type>kernel</protocol-type>
          <metric-type>internal</metric-type>
          <route-map>WORD</route-map>
          <level>level-2</level>
        </config>
        <metric-value>0</metric-value>
      </redistribute>
    </redistributions>
  </address-family-ipv4>
</isis>
```

## Command Syntax

```
redistribute (kernel|connected|static|rip|ospf|bgp) ({ metric-type
  (internal|external)| route-map WORD| level-1|level-2|level-1-2| metric <0-
  16777215> }|)
```

---

## Configure metric

Use this attribute to Summary Address to summarize IPv4 reachability information.

Attribute Name: prefix

Attribute Type: string

Attribute Name: level

Attribute Type: enum (level-1|level-2|level-1-2)

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 1-63

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <address-family-ipv4>
      <summary-addresses>
        <summary-address> <!-- operation="delete"-->
          <prefix>A.B.C.D/M</prefix>
          <config>
            <prefix>A.B.C.D/M</prefix>
            <level>level-1</level>
            <metric>1</metric>
          </config>
        </summary-address>
      </summary-addresses>
    </address-family-ipv4>
  </isis-instance>
</isis-instances>
</isis>
```

## Command Syntax

```
summary-address A.B.C.D/M (level-1|level-2|level-1-2) (metric <1-63>|)
```

---

## Configure id

Instance ID

Attribute Name: id

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <address-family-ipv4>
    <redistribute-isis-instances>
    <redistribute-isis-instance> <!-- operation="delete"-->
      <id>WORD</id>
      <config>
        <id>WORD</id>
      </config>
    </redistribute-isis-instance>
    </redistribute-isis-instances>
    </address-family-ipv4>
  </isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
redistribute isis WORD
```

---

## Configure metric type

IS-IS metric

Attribute Name: metric-value

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-16777215

Attribute Name: metric-type

Attribute Type: enum (internal|external)

Default Value: internal

Attribute Name: route-map

Attribute Type: string

Default Value: ""

Attribute Name: level

Attribute Type: enum (level-1|level-2|level-1-2)

Default Value: level-2

**Netconf edit-config payload**

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<address-family-ipv4>
<redistribute-isis-instances>
<redistribute-isis-instance>
  <id>WORD</id>
  <config>
    <id>WORD</id>
    <metric-type>internal</metric-type>
    <route-map>WORD</route-map>
    <level>level-2</level>
  </config>
  <metric-value>0</metric-value>
</redistribute-isis-instance>
</redistribute-isis-instances>
</address-family-ipv4>
</isis-instance>
</isis-instances>
</isis>

```

**Command Syntax**

```

redistribute isis WORD { metric-type (internal|external) | route-map WORD | level-
1|level-2|level-1-2 | metric <0-16777215> }

```

**Configure passive interface all**

Use this attribute to set all interfaces as passive.

Attribute Name: passive-interface-all

Attribute Type: empty

**Netconf edit-config payload**

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<passive-interfaces>
<config>
  </passive-interface-all><!-- operation="delete"-->
</config>
</passive-interfaces>

```

```
</isis-instance>  
</isis-instances>  
</isis>
```

## Command Syntax

```
passive-interface
```

---

## Configure name

Use this attribute to set interface as passive.

Attribute Name: name

Attribute Type: string

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">  
<isis-instances>  
<isis-instance>  
  <instance>WORD</instance>  
  <config>  
    <instance>WORD</instance>  
  </config>  
</passive-interfaces>  
<passive-interface> <!-- operation="delete"-->  
  <name>IFNAME</name>  
  <config>  
    <name>WORD</name>  
  </config>  
</passive-interface>  
</passive-interfaces>  
</isis-instance>  
</isis-instances>  
</isis>
```

## Command Syntax

```
passive-interface IFNAME
```

---

## Configure disable-passive-interfaces name

Use this attribute to set interface as passive.

Attribute Name: name

Attribute Type: string

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">  
<isis-instances>  
<isis-instance>  
  <instance>WORD</instance>  
  <config>
```

```

    <instance>WORD</instance>
  </config>
</passive-interfaces>
<disable-passive-interfaces>
<disable-passive-interface> <!-- operation="delete"-->
  <name>IFNAME</name>
  <config>
    <name>WORD</name>
  </config>
</disable-passive-interface>
</disable-passive-interfaces>
</passive-interfaces>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
passive-interface IFNAME disable
```

---

## Configure hold timer

Time that a router waits to acquire a set of LSPs to process together

Attribute Name: hold-timer

Attribute Type: uint8

Attribute Range: 1-60

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <microloop-avoidances>
    <microloop-avoidance>
      <level-type>level-1</level-type>
      <config>
        <level-type>level-1</level-type>
      </config>
      <hold-timer>1</hold-timer> <!-- operation="delete"-->
    </microloop-avoidance>
  </microloop-avoidances>
</isis>

```

### Command Syntax

```
microloop-avoidance hold-timer <1-60> (level-1|level-2)
```

---

## Configure max fib

Maximum time required to update a FIB irrespective of the change

Attribute Name: max-fib

Attribute Type: uint8

Attribute Range: 1-60

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <microloop-avoidances>
    <microloop-avoidance>
      <level-type>level-1</level-type>
      <config>
        <level-type>level-1</level-type>
      </config>
      <max-fib>1</max-fib> <!-- operation="delete" -->
    </microloop-avoidance>
  </microloop-avoidances>
</isis>
```

### Command Syntax

```
microloop-avoidance max-fib <1-60> (level-1|level-2)
```

---

## Configure level type

Microloop avoidance

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <microloop-avoidances>
    <microloop-avoidance>
      <level-type>level-1</level-type>
    </microloop-avoidance>
  </microloop-avoidances>
</isis>
```

```

    <config>
      <level-type>level-1</level-type>
    </config>
    </enable><!-- operation="delete"-->
</microloop-avoidance>
</microloop-avoidances>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
microloop-avoidance (level-1|level-2)
```

---

## Configure algo number

Use this attribute to configure Flexible Algorithm specific configuration

Attribute Name: algo-number

Attribute Type: uint8

Attribute Range: 128-255

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <flexalgos>
    <flexalgo> <!-- operation="delete"-->
      <algo-number>128</algo-number>
      <config>
        <algo-number>128</algo-number>
      </config>
    </flexalgo>
  </flexalgos>
</isis>

```

### Command Syntax

```
flex-algo <128-255>
```

---

## Configure flexalgo metric-type

ISIS Flexible Algorithm metric type

Attribute Name: metric-type

Attribute Type: enum (igp-metric|link-delay|te-metric)

**Netconf edit-config payload**

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
</flexalgos>
<flexalgo>
  <algo-number>128</algo-number>
  <config>
    <algo-number>128</algo-number>
  </config>
  <metric-type>igp-metric</metric-type> <!-- operation="delete"-->
</flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>
</isis>

```

**Command Syntax**

```
metric-type (igp-metric|link-delay|te-metric)
```

---

**Configure calculation type**

ISIS Flexible Algorithm calculation type

Attribute Name: calculation-type

Attribute Type: enum (spf|strict-spf)

**Netconf edit-config payload**

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
</flexalgos>
<flexalgo>
  <algo-number>128</algo-number>
  <config>
    <algo-number>128</algo-number>
  </config>
  <calculation-type>spf</calculation-type> <!-- operation="delete"-->
</flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>

```

```
</isis>
```

## Command Syntax

```
calculation-type (spf|strict-spf)
```

---

## Configure priority

Flexible Algorithm priority Value

Attribute Name: priority

Attribute Type: uint8

Attribute Range: 1-255

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
    <flexalgos>
      <flexalgo>
        <algo-number>128</algo-number>
        <config>
          <algo-number>128</algo-number>
        </config>
        <priority>1</priority> <!-- operation="delete"-->
      </flexalgo>
    </flexalgos>
  </isis-instances>
</isis>
```

## Command Syntax

```
priority <1-255>
```

---

## Configure exclude minimum bandwidth

Minimum bandwidth value constraint for flexible algorithm. The bandwidth input ranges are 1 to 999 Kbps, 1 to 999 Mbps and 1 to 100 Gbps.

Attribute Name: exclude-minimum-bandwidth

Attribute Type: string

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
```

```

    <config>
      <instance>WORD</instance>
    </config>
  </flexalgos>
<flexalgo>
  <algo-number>128</algo-number>
  <config>
    <algo-number>128</algo-number>
  </config>
  <exclude-minimum-bandwidth>BANDWIDTH</exclude-minimum-bandwidth> <!--
operation="delete"-->
</flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>
</isis>

```

## Command Syntax

```
exclude-minimum-bandwidth BANDWIDTH
```

---

## Configure exclude maximum delay

Use this attribute to specify maximum link delay value constraint for flexible algorithm

Attribute Name: exclude-maximum-delay

Attribute Type: uint32

Attribute Range: 1-16777215

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </flexalgos>
    <flexalgo>
      <algo-number>128</algo-number>
      <config>
        <algo-number>128</algo-number>
      </config>
      <exclude-maximum-delay>1</exclude-maximum-delay> <!-- operation="delete"-->
    </flexalgo>
  </flexalgos>
</isis-instance>
</isis-instances>
</isis>

```

---

## Command Syntax

```
exclude-maximum-delay <1-16777215>
```

---

## Configure enable intf group mode bw calc

Enable interface group mode total bandwidth calculation for ISIS Flexible algorithm

Attribute Name: enable-intf-group-mode-bw-calc

Attribute Type: empty

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
    <flexalgos>
      <flexalgo>
        <algo-number>128</algo-number>
        <config>
          <algo-number>128</algo-number>
        </config>
        </enable-intf-group-mode-bw-calc><!-- operation="delete"-->
      </flexalgo>
    </flexalgos>
  </isis-instances>
</isis>
```

## Command Syntax

```
intf-group-mode bandwidth
```

---

## Configure reference bandwidth

Reference bandwidth value constraint for flexible algorithm SPF's automatic metric calculation. The bandwidth input ranges are 1 to 999 Kbps, 1 to 999 Mbps and 1 to 100 Gbps.

Attribute Name: reference-bandwidth

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
</isis>
```

```

<flexalgos>
<flexalgo>
  <algo-number>128</algo-number>
  <config>
    <algo-number>128</algo-number>
  </config>
  <reference-bandwidth>BANDWIDTH</reference-bandwidth> <!-- operation="delete"-
->
</flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
reference-bandwidth BANDWIDTH
```

---

## Configure granularity bandwidth

Granularity bandwidth value constraint for flexible algorithm SPF's automatic metric calculation. The bandwidth input ranges are 1 to 999 Kbps, 1 to 999 Mbps and 1 to 100 Gbps.

Attribute Name: granularity-bandwidth

Attribute Type: string

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<flexalgos>
<flexalgo>
  <algo-number>128</algo-number>
  <config>
    <algo-number>128</algo-number>
  </config>
  <granularity-bandwidth>BANDWIDTH</granularity-bandwidth> <!--
operation="delete"-->
</flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
granularity-bandwidth BANDWIDTH
```

---

## Configure enable advertise definition

Use this attribute to configure the ISIS Flexible Algorithm Advertisement

Attribute Name: enable-advertise-definition

Attribute Type: empty

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <flexalgos>
    <flexalgo>
      <algo-number>128</algo-number>
      <config>
        <algo-number>128</algo-number>
      </config>
    </flexalgo>
  </flexalgos>
  </enable-advertise-definition><!-- operation="delete"-->
</isis>
```

### Command Syntax

```
advertise
```

---

## Configure enable participate

Use this attribute to configure the ISIS Flexible Algorithm Participation

Attribute Name: enable-participate

Attribute Type: empty

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <flexalgos>
    <flexalgo>
      <algo-number>128</algo-number>
      <config>
```

```

        <algo-number>128</algo-number>
    </config>
    </enable-participate><!-- operation="delete"-->
</flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
participate
```

---

## Configure enable fast reroute

Use this attribute to configure the ISIS Flexible Algorithm fast rerouting

Attribute Name: enable-fast-reroute

Attribute Type: empty

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <flexalgos>
    <flexalgo>
      <algo-number>128</algo-number>
      <config>
        <algo-number>128</algo-number>
      </config>
    </enable-fast-reroute><!-- operation="delete"-->
  </flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
fast-reroute
```

---

## Configure enable remote lfa

Use this attribute to configure the ISIS Flexible Algorithm Remote-LFA

Attribute Name: enable-remote-lfa

Attribute Type: empty

**Netconf edit-config payload**

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
</flexalgos>
<flexalgo>
  <algo-number>128</algo-number>
  <config>
    <algo-number>128</algo-number>
  </config>
  </enable-remote-lfa><!-- operation="delete"-->
</flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>
</isis>

```

**Command Syntax**

```
remote-lfa
```

---

**Configure enable ti lfa**

Use this attribute to configure the ISIS Flexible Algorithm TI-LFA

Attribute Name: enable-ti-lfa

Attribute Type: empty

**Netconf edit-config payload**

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
</flexalgos>
<flexalgo>
  <algo-number>128</algo-number>
  <config>
    <algo-number>128</algo-number>
  </config>
  </enable-ti-lfa><!-- operation="delete"-->
</flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>

```

```
</isis>
```

## Command Syntax

```
ti-lfa
```

---

## Configure enable prefix metric flag

Use this attribute to configure the ISIS Flexible Algorithm prefix-metric flag sub-TLV advertisement

Attribute Name: enable-prefix-metric-flag

Attribute Type: empty

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    <flexalgos>
      <flexalgo>
        <algo-number>128</algo-number>
        <config>
          <algo-number>128</algo-number>
        </config>
        </enable-prefix-metric-flag><!-- operation="delete"-->
      </flexalgo>
    </flexalgos>
  </isis-instance>
</isis-instances>
</isis>
```

## Command Syntax

```
prefix-metric-flag
```

---

## Configure fapm metric

Distance Value

Attribute Name: fapm-metric

Attribute Type: uint8

Attribute Range: 1-255

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
```

```

    <config>
      <instance>WORD</instance>
    </config>
  </flexalgos>
</flexalgo>
  <algo-number>128</algo-number>
  <config>
    <algo-number>128</algo-number>
  </config>
  <fapm-metric>1</fapm-metric> <!-- operation="delete"-->
</flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
fapm-metric <1-255>
```

---

## Configure affinity eag exclude any

Flexible Algorithm Exclude Any Affinity-EAG Name

Attribute Name: affinity-eag-exclude-any

Attribute Type: string

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <flexalgos>
    <flexalgo>
      <algo-number>128</algo-number>
      <config>
        <algo-number>128</algo-number>
      </config>
      <affinity-eag-exclude-any>WORD</affinity-eag-exclude-any> <!--
operation="delete"-->
    </flexalgo>
  </flexalgos>
</isis>

```

### Command Syntax

```
affinity-eag-exclude-any WORD
```

---

## Configure affinity eag include any

Flexible Algorithm Include Any Affinity-EAG Name

Attribute Name: affinity-eag-include-any

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <flexalgos>
    <flexalgo>
      <algo-number>128</algo-number>
      <config>
        <algo-number>128</algo-number>
      </config>
      <affinity-eag-include-any>WORD</affinity-eag-include-any> <!--
operation="delete"-->
    </flexalgo>
  </flexalgos>
</isis>
```

### Command Syntax

```
affinity-eag-include-any WORD
```

---

## Configure affinity eag include all

Flexible Algorithm Include All Affinity-EAG Name

Attribute Name: affinity-eag-include-all

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <flexalgos>
    <flexalgo>
      <algo-number>128</algo-number>
```

```

    <config>
      <algo-number>128</algo-number>
    </config>
    <affinity-eag-include-all>WORD</affinity-eag-include-all> <!--
operation="delete"-->
  </flexalgo>
</flexalgorithms>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
affinity-eag-include-all WORD
```

---

## Configure affinity eag reverse exclude any

Flexible Algorithm reverse Exclude Any Affinity-EAG Name

Attribute Name: affinity-eag-reverse-exclude-any

Attribute Type: string

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <flexalgorithms>
    <flexalgo>
      <algo-number>128</algo-number>
      <config>
        <algo-number>128</algo-number>
      </config>
    </flexalgo>
  </flexalgorithms>
  <affinity-eag-reverse-exclude-any>WORD</affinity-eag-reverse-exclude-any> <!--
- operation="delete"-->
</flexalgo>
</flexalgorithms>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
affinity-eag-reverse-exclude-any WORD
```

---

## Configure affinity eag reverse include any

Flexible Algorithm reverse Include Any Affinity-EAG Name

Attribute Name: affinity-eag-reverse-include-any

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <flexalgorithms>
    <flexalgo>
      <algo-number>128</algo-number>
      <config>
        <algo-number>128</algo-number>
      </config>
      <affinity-eag-reverse-include-any>WORD</affinity-eag-reverse-include-any> <!--
- operation="delete"-->
    </flexalgo>
  </flexalgorithms>
</isis>
```

### Command Syntax

```
affinity-eag-reverse-include-any WORD
```

---

## Configure affinity eag reverse include all

Flexible Algorithm reverse Include All Affinity-EAG Name

Attribute Name: affinity-eag-reverse-include-all

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <flexalgorithms>
    <flexalgo>
      <algo-number>128</algo-number>
      <config>
        <algo-number>128</algo-number>
      </config>
      <affinity-eag-reverse-include-all>WORD</affinity-eag-reverse-include-all> <!--
- operation="delete"-->
    </flexalgo>
  </flexalgorithms>
</isis>
```

```

</flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
affinity-eag-reverse-include-all WORD
```

---

## Configure affinity ag exclude any

Flexible Algorithm Exclude Any Affinity-AG Name

Attribute Name: affinity-ag-exclude-any

Attribute Type: string

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <flexalgos>
    <flexalgo>
      <algo-number>128</algo-number>
      <config>
        <algo-number>128</algo-number>
      </config>
      <affinity-ag-exclude-any>WORD</affinity-ag-exclude-any> <!--
operation="delete"-->
    </flexalgo>
  </flexalgos>
</isis>

```

### Command Syntax

```
affinity-ag-exclude-any WORD
```

---

## Configure affinity ag include any

Flexible Algorithm Include Any Affinity-AG Name

Attribute Name: affinity-ag-include-any

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
```

```

<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
</flexalgos>
<flexalgo>
  <algo-number>128</algo-number>
  <config>
    <algo-number>128</algo-number>
  </config>
  <affinity-ag-include-any>WORD</affinity-ag-include-any> <!--
operation="delete"-->
</flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>
</isis>

```

## Command Syntax

```
affinity-ag-include-any WORD
```

---

## Configure affinity ag include all

Flexible Algorithm Include All Affinity-AG Name

Attribute Name: affinity-ag-include-all

Attribute Type: string

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
</flexalgos>
<flexalgo>
  <algo-number>128</algo-number>
  <config>
    <algo-number>128</algo-number>
  </config>
  <affinity-ag-include-all>WORD</affinity-ag-include-all> <!--
operation="delete"-->
</flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>
</isis>

```

## Command Syntax

```
affinity-ag-include-all WORD
```

---

## Configure affinity ag reverse exclude any

Flexible Algorithm reverse Exclude Any Affinity-AG Name

Attribute Name: affinity-ag-reverse-exclude-any

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <flexalgos>
    <flexalgo>
      <algo-number>128</algo-number>
      <config>
        <algo-number>128</algo-number>
      </config>
      <affinity-ag-reverse-exclude-any>WORD</affinity-ag-reverse-exclude-any> <!--
operation="delete"-->
    </flexalgo>
  </flexalgos>
</isis>
```

## Command Syntax

```
affinity-ag-reverse-exclude-any WORD
```

---

## Configure affinity ag reverse include any

Flexible Algorithm reverse Include Any Affinity-AG Name

Attribute Name: affinity-ag-reverse-include-any

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
</isis>
```

```

<flexalgos>
<flexalgo>
  <algo-number>128</algo-number>
  <config>
    <algo-number>128</algo-number>
  </config>
  <affinity-ag-reverse-include-any>WORD</affinity-ag-reverse-include-any> <!--
operation="delete"-->
</flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
affinity-ag-reverse-include-any WORD
```

---

## Configure affinity ag reverse include all

Flexible Algorithm reverse Include All Affinity-AG Name

Attribute Name: affinity-ag-reverse-include-all

Attribute Type: string

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
<flexalgos>
<flexalgo>
  <algo-number>128</algo-number>
  <config>
    <algo-number>128</algo-number>
  </config>
  <affinity-ag-reverse-include-all>WORD</affinity-ag-reverse-include-all> <!--
operation="delete"-->
</flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
affinity-ag-reverse-include-all WORD
```

---

## Configure threshold metric

Link metric value for the bandwidth threshold

Attribute Name: threshold-metric

Attribute Type: uint32

Attribute Range: 1-4261412

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
    </isis-instance>
  </isis-instances>
  <flexalgos>
    <flexalgo>
      <algo-number>128</algo-number>
      <config>
        <algo-number>128</algo-number>
      </config>
      <flexalgo-bandwidth-thresholds>
        <flexalgo-bandwidth-threshold>
          <bandwidth-threshold>BANDWIDTH</bandwidth-threshold>
          <config>
            <bandwidth-threshold>BANDWIDTH</bandwidth-threshold>
          </config>
          <threshold-metric>1</threshold-metric> <!-- operation="delete"-->
        </flexalgo-bandwidth-threshold>
      </flexalgo-bandwidth-thresholds>
    </flexalgo>
  </flexalgos>
</isis>
```

### Command Syntax

```
flex-algo <128-255> bandwidth-threshold BANDWIDTH threshold-metric <1-4261412>
```

---

## Configure flexalgo-microloop-avoidance enable

Microloop avoidance

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
```

```

<isis-instance>
  <instance>WORD</instance>
  <config>
    <instance>WORD</instance>
  </config>
</flexalgos>
<flexalgo>
  <algo-number>128</algo-number>
  <config>
    <algo-number>128</algo-number>
  </config>
  <flexalgo-microloop-avoidances>
  <flexalgo-microloop-avoidance>
    <level-type>level-1</level-type>
    <config>
      <level-type>level-1</level-type>
    </config>
    </enable><!-- operation="delete"-->
  </flexalgo-microloop-avoidance>
</flexalgo-microloop-avoidances>
</flexalgo>
</flexalgos>
</isis-instance>
</isis-instances>
</isis>

```

## Command Syntax

```
microloop-avoidance flex-algo <128-255> (level-1|level-2)
```

---

## Configure options

Debug Configuration Flag

Attribute Name: options

Attribute Type: bits (ifsm|nfsm|pdu|lsp|spf|events|nsm|checksum|authentication|local-updates|protocol-errors|bfd|rib|lfa|ofib|asla|flexalgo|all)

## Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <debug>
  <config>
    <options>ifsm</options> <!-- operation="delete"-->
  </config>
</debug>
</isis>

```

## Command Syntax

```
debug isis (ifsm|nfsm|pdu|lsp|spf|events|nsm|checksum|authentication|local-updates|protocol-errors|bfd|rib|lfa|ofib|asla|flexalgo|all)
```

---

## Configure enable hello

Use this attribute to turn on debugging for ISIS hello.

Attribute Name: enable-hello

Attribute Type: empty

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <debug>
  <config>
    </enable-hello><!-- operation="delete"-->
  </config>
</debug>
</isis>
```

### Command Syntax

```
debug isis hello
```

---

## clear clns is-neighbors System-ID

Attribute Name: system-id

Attribute Type: string

### Netconf RPC payload

```
<isis-clear-is-neighbors xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <system-id>System-ID</system-id>
</isis-clear-is-neighbors>
```

### Command Syntax

```
clear clns is-neighbors System-ID
```

---

## clear clns neighbors

### Netconf RPC payload

```
<isis-clear-clns-neighbors xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis"/>
```

### Command Syntax

```
clear clns neighbors
```

---

## clear ip isis (WORD|) route (redistribution|all)

Attribute Name: instance

Attribute Type: string

Attribute Name: ipv4-route

Attribute Type: enum (redistribution|all)

---

## Netconf RPC payload

```
<isis-clear-ip-route xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <instance>WORD</instance>
  <ipv4-route>redistribution</ipv4-route>
</isis-clear-ip-route>
```

## Command Syntax

```
clear ip isis (WORD|) route (redistribution|all)
```

---

## clear ipv6 isis (WORD|) route (redistribution|all)

Attribute Name: instance

Attribute Type: string

Attribute Name: ipv6-route

Attribute Type: enum (redistribution|all)

## Netconf RPC payload

```
<isis-clear-ipv6-route xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <instance>WORD</instance>
  <ipv6-route>redistribution</ipv6-route>
</isis-clear-ipv6-route>
```

## Command Syntax

```
clear ipv6 isis (WORD|) route (redistribution|all)
```

---

## clear isis (WORD|) process

Attribute Name: instance

Attribute Type: string

## Netconf RPC payload

```
<isis-process-clear xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <instance>WORD</instance>
</isis-process-clear>
```

## Command Syntax

```
clear isis (WORD|) process
```

---

## clear isis counter

## Netconf RPC payload

```
<isis-clear-counters xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis"/>
```

## Command Syntax

```
clear isis counter
```

---

## clear isis adjacency \* (vrf VRFNAME|)

Attribute Name: adjacency-vrf-name

Attribute Type: string

### Netconf RPC payload

```
<isis-clear-adjacency-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <adjacency-vrf-name>VRFNAME</adjacency-vrf-name>
</isis-clear-adjacency-all>
```

### Command Syntax

```
clear isis adjacency * (vrf VRFNAME|)
```

---

## clear isis WORD adjacency \* (vrf VRFNAME|)

Attribute Name: tag-name

Attribute Type: string

Attribute Name: adjacency-vrf-name

Attribute Type: string

### Netconf RPC payload

```
<isis-process-clear-adjacency-all xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-isis">
  <tag-name>WORD</tag-name>
  <adjacency-vrf-name>VRFNAME</adjacency-vrf-name>
</isis-process-clear-adjacency-all>
```

### Command Syntax

```
clear isis WORD adjacency * (vrf VRFNAME|)
```

---

## clear isis WORD adjacency (IFNAME|) (vrf VRFNAME|)

Attribute Name: tag-name

Attribute Type: string

Attribute Name: tag-if-name

Attribute Type: string

Attribute Name: adjacency-vrf-name

Attribute Type: string

### Netconf RPC payload

```
<isis-process-clear-adjacency-interface xmlns="http://www.ipinfusion.com/yang/
ocnos/ipi-isis">
  <tag-name>WORD</tag-name>
  <tag-if-name>IFNAME</tag-if-name>
  <adjacency-vrf-name>VRFNAME</adjacency-vrf-name>
</isis-process-clear-adjacency-interface>
```

---

## Command Syntax

```
clear isis WORD adjacency (IFNAME|) (vrf VRFNAME|)
```

---

### clear isis adjacency (IFNAME|) (vrf VRFNAME|)

Attribute Name: adjacency-if-name

Attribute Type: string

Attribute Name: adjacency-vrf-name

Attribute Type: string

### Netconf RPC payload

```
<isis-clear-adjacency-interface xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <adjacency-if-name>IFNAME</adjacency-if-name>
  <adjacency-vrf-name>VRFNAME</adjacency-vrf-name>
</isis-clear-adjacency-interface>
```

## Command Syntax

```
clear isis adjacency (IFNAME|) (vrf VRFNAME|)
```

---

### clear isis WORD adjacency system-id XXXX.XXXX.XXXX (vrf VRFNAME|)

Attribute Name: tag-name

Attribute Type: string

Attribute Name: tag-system-id

Attribute Type: string

Attribute Name: tag-vrf-name

Attribute Type: string

### Netconf RPC payload

```
<isis-process-clear-adjacency-system-id xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <tag-name>WORD</tag-name>
  <tag-system-id>XXXX.XXXX.XXXX</tag-system-id>
  <tag-vrf-name>VRFNAME</tag-vrf-name>
</isis-process-clear-adjacency-system-id>
```

## Command Syntax

```
clear isis WORD adjacency system-id XXXX.XXXX.XXXX (vrf VRFNAME|)
```

---

### clear isis adjacency system-id XXXX.XXXX.XXXX (vrf VRFNAME|)

Attribute Name: adjacency-system-id

Attribute Type: string

Attribute Name: adjacency-vrf-name

Attribute Type: string

### Netconf RPC payload

```
<isis-clear-adjacency-system-id xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <adjacency-system-id>XXXX.XXXX.XXXX</adjacency-system-id>
  <adjacency-vrf-name>VRFNAME</adjacency-vrf-name>
</isis-clear-adjacency-system-id>
```

### Command Syntax

```
clear isis adjacency system-id XXXX.XXXX.XXXX (vrf VRFNAME|)
```

---

## snmp restart isis

### Netconf RPC payload

```
<isis-restart-snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis"/>
```

### Command Syntax

```
snmp restart isis
```

---

## debug isis (ifsm|nfsm|pdu|lsp|spf|events|nsm|checksum|authentication|local-updates|protocol-errors|bfd|rib|lfa|ofib|asla|flexalgo|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (ifsm|nfsm|pdu|lsp|spf|events|nsm|checksum|authentication|local-updates|protocol-errors|bfd|rib|lfa|ofib|asla|flexalgo|all)

### Netconf RPC payload

```
<isis-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <terminal-debug-options>ifsm</terminal-debug-options>
</isis-terminal-debug-on>
```

### Command Syntax

```
debug isis (ifsm|nfsm|pdu|lsp|spf|events|nsm|checksum|authentication|local-
updates|protocol-errors|bfd|rib|lfa|ofib|asla|flexalgo|all)
```

---

## no debug isis (ifsm|nfsm|pdu|lsp|spf|events|nsm|checksum|authentication|local-updates|protocol-errors|bfd|rib|lfa|ofib|asla|flexalgo|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (ifsm|nfsm|pdu|lsp|spf|events|nsm|checksum|authentication|local-updates|protocol-errors|bfd|rib|lfa|ofib|asla|flexalgo|all)

### Netconf RPC payload

```
<isis-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <terminal-debug-options>ifsm</terminal-debug-options>
```

---

```
</isis-debug-off>
```

### Command Syntax

```
no debug isis (ifsm|nfsn|pdu|lsp|spf|events|nsm|checksum|authentication|local-  
updates|protocol-errors|bfd|rib|lfa|ofib|asla|flexalgo|all)
```

---

## debug isis spf-trace

### Netconf RPC payload

```
<isis-terminal-debug-spf-trace-on xmlns="http://www.ipinfusion.com/yang/ocnos/  
ipi-isis"/>
```

### Command Syntax

```
debug isis spf-trace
```

---

## no debug isis spf-trace

### Netconf RPC payload

```
<isis-terminal-debug-spf-trace-off xmlns="http://www.ipinfusion.com/yang/ocnos/  
ipi-isis"/>
```

### Command Syntax

```
no debug isis spf-trace
```

---

## debug isis hello

### Netconf RPC payload

```
<isis-debug-hello-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis"/>
```

### Command Syntax

```
debug isis hello
```

---

## no debug isis hello

### Netconf RPC payload

```
<isis-debug-hello-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis"/>
```

### Command Syntax

```
no debug isis hello
```

---

## debug isis hello interface IFNAME

Attribute Name: interface

Attribute Type: string

---

### Netconf RPC payload

```
<isis-debug-interface-hello-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interface>IFNAME</interface>
</isis-debug-interface-hello-on>
```

### Command Syntax

```
debug isis hello interface IFNAME
```

---

## no debug isis hello interface IFNAME

Attribute Name: interface

Attribute Type: string

### Netconf RPC payload

```
<isis-debug-interface-hello-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interface>IFNAME</interface>
</isis-debug-interface-hello-off>
```

### Command Syntax

```
no debug isis hello interface IFNAME
```

---

## debug isis hello System-ID

Attribute Name: system-id

Attribute Type: string

### Netconf RPC payload

```
<isis-debug-system-id-hello-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <system-id>System-ID</system-id>
</isis-debug-system-id-hello-on>
```

### Command Syntax

```
debug isis hello System-ID
```

---

## no debug isis hello System-ID

Attribute Name: system-id

Attribute Type: string

### Netconf RPC payload

```
<isis-debug-system-id-hello-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <system-id>System-ID</system-id>
</isis-debug-system-id-hello-off>
```

---

## Command Syntax

```
no debug isis hello System-ID
```

---

## no debug all isis

### Netconf RPC payload

```
<isis-all-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis"/>
```

## Command Syntax

```
no debug all isis
```

---

## IPI-ISIS-LSP

---

### Configure spf max delay

Maximum delay between receiving a change to SPF calculation in milliseconds. The default value is 5000

Attribute Name: spf-max-delay

Attribute Type: uint32

Attribute Range: 0-2147483647

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
      <spf-levels>
        <spf-level>
          <level>level-1-2</level>
          <config>
            <level>level-1-2</level>
          </config>
          <spf-delays>
            <spf-delay <!-- operation="delete"-->
              <spf-max-delay>0</spf-max-delay>
            <config>
              <spf-max-delay>0</spf-max-delay>
              <spf-min-delay>0</spf-min-delay>
            </config>
            <spf-min-delay>0</spf-min-delay>
          </spf-delay>
        </spf-delays>
      </spf-level>
    </isis-instance>
  </isis-instances>
</isis>
```

```

</spf-levels>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
spf-interval-exp ((level-1|level-2) |) <0-2147483647> <0-2147483647>
```

---

## Configure lsp max wait interval

Use this attribute to set minimum interval before regenerating the same LSP. The smaller the interval, the faster the convergence. However, this setting might cause more frequent flooding

Attribute Name: lsp-max-wait-interval

Attribute Type: uint32

Default Value: 5

Attribute Range: 1-120

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
      <levels>
        <level>
          <type>level-1-2</type>
          <config>
            <type>level-1-2</type>
          </config>
          <lsp-max-wait-interval>1</lsp-max-wait-interval> <!--
operation="delete"-->
        </level>
      </levels>
    </isis-instance>
  </isis-instances>
</isis>

```

### Command Syntax

```
lsp-gen-interval ((level-1|level-2) |) <1-120>
```

---

## Configure lsp mtu size

Use this attribute to set minimum interval before regenerating the same LSP

Attribute Name: lsp-mtu-size

Attribute Type: uint16

Default Value: 1492

Attribute Range: 512-4352

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
  <isis-instance>
    <instance>WORD</instance>
    <config>
      <instance>WORD</instance>
    </config>
    <levels>
    <level>
      <type>level-1-2</type>
      <config>
        <type>level-1-2</type>
      </config>
      <lsp-mtu-size>512</lsp-mtu-size> <!-- operation="delete"-->
    </level>
    </levels>
  </isis-instance>
</isis-instances>
</isis>
```

### Command Syntax

```
lsp-mtu ((level-1|level-2)|) <512-4352>
```

---

## Configure wait timer

Number of seconds to delay in waiting state before on state

Attribute Name: wait-timer

Attribute Type: uint16

Attribute Range: 1-65535

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
  <isis-instance>
    <instance>WORD</instance>
    <config>
      <instance>WORD</instance>
    </config>
    <levels>
    <level>
      <type>level-1-2</type>
      <config>
        <type>level-1-2</type>
      </config>
    </level>
  </isis-instance>
</isis-instances>
</isis>
```

```

        <wait-timer>1</wait-timer> <!-- operation="delete"-->
    </level>
</levels>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
isis wait-timer <1-65535> level-1-2
```

---

## Configure restart timer

Use this attribute to restart the ISIS timer

Attribute Name: restart-timer

Attribute Type: uint16

Attribute Range: 5-65535

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
      <levels>
        <level>
          <type>level-1-2</type>
          <config>
            <type>level-1-2</type>
          </config>
          <restart-timer>5</restart-timer> <!-- operation="delete"-->
        </level>
      </levels>
    </isis-instance>
  </isis-instances>
</isis>

```

### Command Syntax

```
restart-timer <5-65535> level-1-2
```

---

## Configure instance

Number of seconds to delay in waiting state before on state

Attribute Name: wait-timer

Attribute Type: uint16

Attribute Range: 1-65535

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
  <isis-instance>
    <instance>WORD</instance>
    <config>
      <instance>WORD</instance>
    </config>
    <levels>
    <level>
      <type>level-1-2</type>
      <config>
        <type>level-1-2</type>
      </config>
      <wait-timer>1</wait-timer> <!-- operation="delete"-->
    </level>
  </levels>
</isis-instance>
</isis-instances>
</isis>
```

## Command Syntax

```
isis wait-timer <1-65535> (level-1|level-2|)
```

---

## Configure type

Use this attribute to restart the ISIS timer

Attribute Name: restart-timer

Attribute Type: uint16

Attribute Range: 5-65535

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
  <isis-instance>
    <instance>WORD</instance>
    <config>
      <instance>WORD</instance>
    </config>
    <levels>
    <level>
      <type>level-1-2</type>
      <config>
        <type>level-1-2</type>
      </config>
      <restart-timer>5</restart-timer> <!-- operation="delete"-->
    </level>
  </levels>
</isis-instances>
</isis>
```

```

</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
restart-timer <5-65535> (level-1|level-2|)
```

---

## Configure mode

Use this attribute to set the authentication mode at the instance level.

Attribute Name: mode

Attribute Type: enum (md5|text)

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
  <isis-instance>
    <instance>WORD</instance>
    <config>
      <instance>WORD</instance>
    </config>
    <levels>
    <level>
      <type>level-1-2</type>
      <config>
        <type>level-1-2</type>
      </config>
      <authentication>
      <config>
        <mode>md5</mode>
      </config>
    </authentication>
    </level>
  </levels>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
authentication mode (md5|text) (level-1|level-2|)
```

---

## Configure key chain

Use this attribute to set the key chain to be used for authentication at the instance level. Authentication mode must be set to md5/text to configure the key chain.

Attribute Name: key-chain

Attribute Type: string

**Netconf edit-config payload**

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
  <isis-instance>
    <instance>WORD</instance>
    <config>
      <instance>WORD</instance>
    </config>
    <levels>
    <level>
      <type>level-1-2</type>
      <config>
        <type>level-1-2</type>
      </config>
      <authentication>
      <config>
        <key-chain>WORD</key-chain> <!-- operation="delete"-->
      </config>
      </authentication>
    </level>
  </levels>
</isis-instance>
</isis-instances>
</isis>

```

**Command Syntax**

```
authentication key-chain WORD (level-1|level-2|)
```

---

**IPI-ISIS-EXTENDED**

---

**Configure name**

Specific prefixex allowed using this route map

Attribute Name: name

Attribute Type: string

**Netconf edit-config payload**

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<isis-instances>
  <isis-instance>
    <instance>WORD</instance>
    <config>
      <instance>WORD</instance>
    </config>
    <fast-reroute-levels>
    <fast-reroute>
      <level-type>level-1</level-type>
    </fast-reroute>
  </fast-reroute-levels>
</isis-instance>
</isis-instances>
</isis>

```

```

<config>
  <level-type>level-1</level-type>
</config>
<route-maps>
<route-map>
  <protocol>ipv4</protocol>
  <config>
    <protocol>ipv4</protocol>
  </config>
  <name>WORD</name> <!-- operation="delete"-->
</route-map>
</route-maps>
</fast-reroute>
</fast-reroute-levels>
</isis-instance>
</isis-instances>
</isis>

```

### Command Syntax

```
fast-reroute per-prefix (level-1|level-2) proto (ipv4) route-map WORD
```

---

## Configure enable all prefixes

Apply on all prefixes

Attribute Name: enable-all-prefixes

Attribute Type: enum (all)

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
      <fast-reroute-levels>
      <fast-reroute>
        <level-type>level-1</level-type>
        <config>
          <level-type>level-1</level-type>
        </config>
        <route-maps>
        <route-map>
          <protocol>ipv4</protocol>
          <config>
            <protocol>ipv4</protocol>
          </config>
          <enable-all-prefixes>all</enable-all-prefixes> <!--
operation="delete"-->

```

```

    </route-map>
  </route-maps>
</fast-reroute>
</fast-reroute-levels>
</isis-instance>
</isis-instances>
</isis>

```

## Command Syntax

```
fast-reroute per-prefix (level-1|level-2) proto (ipv4) (all)
```

---

## Configure preference index

this index indicates which tie-break option to be given preference

This command is supported when following feature are enabled ISIS feature

Attribute Name: preference-index

Attribute Type: uint32

Attribute Range: 1-255

## Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <isis-instances>
    <isis-instance>
      <instance>WORD</instance>
      <config>
        <instance>WORD</instance>
      </config>
      <fast-reroute-levels>
      <fast-reroute>
        <level-type>level-1</level-type>
        <config>
          <level-type>level-1</level-type>
        </config>
        <protocols>
        <protocol>
          <preference-value>primary-path</preference-value>
          <config>
            <preference-value>primary-path</preference-value>
            <lfa-protocol>ipv4</lfa-protocol>
          </config>
            <lfa-protocol>ipv4</lfa-protocol>
            <preference-index>1</preference-index> <!-- operation="delete"-->
          </protocol>
        </protocols>
      </fast-reroute>
    </fast-reroute-levels>
  </isis-instance>
</isis-instances>

```

```
</isis>
```

## Command Syntax

```
fast-reroute tie-break (level-1|level-2) proto (ipv4) (primary-path|node-protecting|interface-disjoint|broadcast-interface-disjoint|downstream-path|secondary-path) index <1-255>
```

---

## Configure grace period

The period within which ISIS should come up

Attribute Name: grace-period

Attribute Type: uint16

Attribute Range: 1-65535

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <graceful-restart>
    <config>
      <grace-period>1</grace-period> <!-- operation="delete"-->
    </config>
  </graceful-restart>
</isis>
```

## Command Syntax

```
isis restart grace-period <1-65535>
```

---

## Configure enable helper only

Attribute to configure helper mode

Attribute Name: enable-helper-only

Attribute Type: empty

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <graceful-restart>
    <config>
      </enable-helper-only><!-- operation="delete"-->
    </config>
  </graceful-restart>
</isis>
```

## Command Syntax

```
isis restart helper
```

---

## Configure suppress adjacency

When set to true, adjacency is not advertised. The SA bit is used by a starting router to request that its neighbor suppress advertisement of the adjacency to the starting router in the neighbor's LSPs.

Attribute Name: suppress-adjacency

Attribute Type: empty

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <graceful-restart>
  <config>
    </suppress-adjacency><!-- operation="delete"-->
  </config>
</graceful-restart>
</isis>
```

### Command Syntax

```
isis restart suppress-adjacency
```

---

## restart isis graceful (grace-period <1-65535>|)

Attribute Name: grace-period

Attribute Type: uint16

Attribute Range: 1-65535

### Netconf RPC payload

```
<ipi-isis-extended_isis-restart-graceful xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <grace-period>1</grace-period>
</ipi-isis-extended_isis-restart-graceful>
```

### Command Syntax

```
restart isis graceful (grace-period <1-65535>|)
```

---

## IPI-ISIS-INTERFACE

---

### Configure minimal

Use this attribute to set the minimal Hello interval in seconds.

Attribute Name: minimal

Attribute Type: enum (level-1-only|level-2-only|level-1-2)

Default Value: level-1-2

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
```

```

<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <minimal>3</minimal> <!-- operation="delete"-->
</interface>
</interfaces>
</isis>

```

### Command Syntax

```
isis hello-interval minimal level-1
```

---

## Configure name

Use this attribute to set the minimal Hello interval in seconds.

Attribute Name: minimal

Attribute Type: enum (level-1-only|level-2-only|level-1-2)

Default Value: level-1-2

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <minimal>3</minimal> <!-- operation="delete"-->
</interface>
</interfaces>
</isis>

```

### Command Syntax

```
isis hello-interval minimal level-2
```

---

## Configure send only

Use this attribute to set the send-only option to the interface-related packets. Use this attribute before configuring the ISIS authentication mode and ISIS authentication key-chain, so that the implementation of authentication goes smoothly. That is, the routers will have more time for the keys to be configured on each router if authentication is inserted only on the packets being sent, not checked on packets being received. After all routers that must communicate are configured with this attribute, enable the authentication mode and key chain on each router.

Attribute Name: send-only

Attribute Type: enum (level-1-only|level-2-only|level-1-2)

Default Value: level-1-2

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <send-only>3</send-only> <!-- operation="delete"-->
</interface>
</interfaces>
</isis>
```

## Command Syntax

```
isis authentication send-only level-1
```

---

## Configure interface send-only

Use this attribute to set the send-only option to the interface-related packets. Use this attribute before configuring the ISIS authentication mode and ISIS authentication key-chain, so that the implementation of authentication goes smoothly. That is, the routers will have more time for the keys to be configured on each router if authentication is inserted only on the packets being sent, not checked on packets being received. After all routers that must communicate are configured with this attribute, enable the authentication mode and key chain on each router.

Attribute Name: send-only

Attribute Type: enum (level-1-only|level-2-only|level-1-2)

Default Value: level-1-2

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <send-only>3</send-only> <!-- operation="delete"-->
</interface>
</interfaces>
</isis>
```

## Command Syntax

```
isis authentication send-only level-2
```

---

## Configure interface minimal

Use this attribute to set the minimal Hello interval in seconds.

Attribute Name: minimal

Attribute Type: enum (level-1-only|level-2-only|level-1-2)

Default Value: level-1-2

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <minimal>level-1-2</minimal> <!-- operation="delete"-->
    </interface>
  </interfaces>
</isis>
```

### Command Syntax

```
isis hello-interval minimal (level-1-only|level-2-only|)
```

---

## Configure interface send-only

Use this attribute to set the send-only option to the interface-related packets. Use this attribute before configuring the ISIS authentication mode and ISIS authentication key-chain, so that the implementation of authentication goes smoothly. That is, the routers will have more time for the keys to be configured on each router if authentication is inserted only on the packets being sent, not checked on packets being received. After all routers that must communicate are configured with this attribute, enable the authentication mode and key chain on each router.

Attribute Name: send-only

Attribute Type: enum (level-1-only|level-2-only|level-1-2)

Default Value: level-1-2

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <send-only>level-1-2</send-only> <!-- operation="delete"-->
    </interface>
  </interfaces>
</isis>
```

### Command Syntax

```
isis authentication send-only (level-1-only|level-2-only|level-1-2|)
```

---

## Configure maximum bandwidth flex algo

Interface ASLA maximum bandwidth value for IGP Flexible Algorithm. The bandwidth input ranges are 1 to 999 Kbps, 1 to 999 Mbps and 1 to 100 Gbps.

Attribute Name: maximum-bandwidth-flex-algo

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <maximum-bandwidth-flex-algo>BANDWIDTH</maximum-bandwidth-flex-algo> <!--
operation="delete"-->
    </interface>
  </interfaces>
</isis>
```

### Command Syntax

```
maximum-bandwidth flex-algo BANDWIDTH
```

---

## Configure disable asla usage flex algo

Use this attribute to disable ASLA Link attributes usage for flexible-algorithm on this Link. The command with no keyword enables the ASLA usage

Attribute Name: disable-asla-usage-flex-algo

Attribute Type: empty

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </disable-asla-usage-flex-algo><!-- operation="delete"-->
    </interface>
  </interfaces>
</isis>
```

### Command Syntax

```
disable asla flex-algo
```

---

## Configure disable padding

Use this attribute to configure/unconfigure the padding of the ISIS Hello packet. ISIS pads the Hello packet by default to notify neighbors of the supported MTU size.

Attribute Name: disable-padding

Attribute Type: uint8

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <config>
          </disable-padding><!-- operation="delete"-->
        </config>
      </interface-parameters>
    </interface>
  </interfaces>
</isis>
```

### Command Syntax

```
no isis hello padding
```

---

## Configure interface-parameters disable-padding

Use this attribute to configure/unconfigure the padding of the ISIS Hello packet. ISIS pads the Hello packet by default to notify neighbors of the supported MTU size.

Attribute Name: disable-padding

Attribute Type: uint8

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <config>
          </disable-padding><!-- operation="delete"-->
        </config>
      </interface-parameters>
    </interface>
  </interfaces>
</isis>
```

### Command Syntax

```
no isis hello padding
```

---

## Configure network type

Use this attribute to change a broadcast interface network type to a point-to-point network type and vice-versa.

Attribute Name: network-type

Attribute Type: enum (broadcast|point-to-point)

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <config>
          <network-type>broadcast</network-type> <!-- operation="delete"-->
        </config>
      </interface-parameters>
    </interface>
  </interfaces>
</isis>
```

### Command Syntax

```
isis network (broadcast|point-to-point)
```

---

## Configure circuit type

Use this attribute to set the circuit type for the interface. If level-1 or level-2-only is specified in this attribute, ISIS sends only the specified level of PDUs. On the point-to-point interface, there is only one type of Hello packet, so in this case ISIS Hello will be sent regardless of circuit-type. If istype is configured as level-1 or level-2 only, routing for this instance is performed for only the specified level. In this manner, only the particular level of PDU is sent on the interface.

Attribute Name: circuit-type

Attribute Type: enum (level-1|level-2-only|level-1-2)

Default Value: level-1-2

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <config>
          <circuit-type>level-1-2</circuit-type> <!-- operation="delete"-->
        </config>
      </interface-parameters>
    </interface>
  </interfaces>
</isis>
```

```

</interface-parameters>
</interface>
</interfaces>
</isis>

```

## Command Syntax

```
isis circuit-type (level-1|level-2-only|level-1-2)
```

---

## Configure ipv4 instance tag

Use this attribute to enable ISIS IPv4 routing on the interface. This attribute is mandatory to ISIS configuration. Match the ISIS instance tag to one of existing instance.s tags, or a new instance with the tag name should be initiated, otherwise routing will not run on this interface. Configuring this attribute, the router sends ISIS Hello with IP address TLV on this interface, and IP reachability information TLV in the LSP will be updated.

Attribute Name: ipv4-instance-tag

Attribute Type: string

## Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <interface-parameters>
  <config>
    <ipv4-instance-tag>WORD</ipv4-instance-tag> <!-- operation="delete"-->
  </config>
</interface-parameters>
</interface>
</interfaces>
</isis>

```

## Command Syntax

```
ip router isis WORD
```

---

## Configure ipv6 instance tag

Use this attribute to enable ISIS IPv6 routing on the interface. This attribute is mandatory to IPv6 ISIS configuration. Match the ISIS instance tag to one of existing instance.s tags, or a new instance with the tag name should be initiated, otherwise routing will not run on this interface. Configuring this attribute, the router sends ISIS Hello with IPv6 address TLV on this interface, and IPv6 reachability information TLV in the LSP will be updated.

Attribute Name: ipv6-instance-tag

Attribute Type: string

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
```

```

<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <interface-parameters>
  <config>
    <ipv6-instance-tag>WORD</ipv6-instance-tag> <!-- operation="delete"-->
  </config>
</interface-parameters>
</interface>
</interfaces>
</isis>

```

### Command Syntax

```
ipv6 router isis WORD
```

---

## Configure lsp interval

Use this attribute to set the Link State Packet (LSP) transmission interval. Configuring this attribute changes the minimum interval between two consecutive LSP transmission. When flooding or some other event triggers LSP to transmit, the LSP is put on the interface queue and scheduled to transmit according to this interval. Two consecutive LSP transmissions are scheduled to have at least this interval.

Attribute Name: lsp-interval

Attribute Type: uint32

Default Value: 33

Attribute Range: 1-4294967295

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <interface-parameters>
  <config>
    <lsp-interval>1</lsp-interval> <!-- operation="delete"-->
  </config>
</interface-parameters>
</interface>
</interfaces>
</isis>

```

### Command Syntax

```
isis lsp-interval <1-4294967295>
```

---

## Configure retransmit interval

Interval between retransmissions of the same LSP in seconds

Attribute Name: retransmit-interval

Attribute Type: uint16

Default Value: 5

Attribute Range: 1-65535

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <config>
          <retransmit-interval>1</retransmit-interval> <!-- operation="delete"-->
        </config>
      </interface-parameters>
    </interface>
  </interfaces>
</isis>
```

### Command Syntax

```
isis retransmit-interval <1-65535>
```

---

## Configure mesh group id

Use this attribute to specify to block LSPs on the current interface. If an interface is configured as mesh group blocked, the standard LSP database synchronization process is applied if the interface receives CSNP or PSNP.

Attribute Name: mesh-group-id

Attribute Type: union

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <config>
          <mesh-group-id>blocked</mesh-group-id> <!-- operation="delete"-->
        </config>
      </interface-parameters>
    </interface>
  </interfaces>
</isis>
```

```

</interface-parameters>
</interface>
</interfaces>
</isis>

```

## Command Syntax

```
isis mesh-group (blocked|<1-4294967295>)
```

---

## Configure enable

Use this attribute to enable the BFD check on interface.

This command is supported when following feature are enabled

Attribute Name: enable

Attribute Type: empty

## Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <bfd>
          <config>
            </enable><!-- operation="delete"-->
          </config>
        </bfd>
      </interface-parameters>
    </interface>
  </interfaces>
</isis>

```

## Command Syntax

```
isis bfd
```

---

## Configure disable

Use this attribute to disable the BFD check on interface.

This command is supported when following feature are enabled

Attribute Name: disable

Attribute Type: empty

## Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>

```

```

<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <interface-parameters>
    <bfd>
      <config>
        </disable><!-- operation="delete"-->
      </config>
    </bfd>
  </interface-parameters>
</interface>
</interfaces>
</isis>

```

### Command Syntax

```
isis bfd disable
```

---

## Configure disable level 1

Use this attribute to disable fr on an interface for level-1.

Attribute Name: disable-level-1

Attribute Type: empty

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <fast-re-route>
          <config>
            </disable-level-1><!-- operation="delete"-->
          </config>
        </fast-re-route>
      </interface-parameters>
    </interface>
  </interfaces>
</isis>

```

### Command Syntax

```
isis fast-reroute per-prefix candidate disable level-1
```

---

## Configure disable level 2

Use this attribute to disable frr on an interface for level-2.

Attribute Name: disable-level-2

Attribute Type: empty

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <fast-re-route>
          <config>
            </disable-level-2><!-- operation="delete"-->
          </config>
        </fast-re-route>
      </interface-parameters>
    </interface>
  </interfaces>
</isis>
```

### Command Syntax

```
isis fast-reroute per-prefix candidate disable level-2
```

---

## Configure hello interval

Use this attribute to set the Hello interval in seconds. The Hello-interval is set with the hello-multiplier. Configuring this attribute changes the time interval between two consecutive Hello transmissions. If a device receives its own LSP with a maximum sequence number, then it suspends ISIS for the hold interval. DIS sends Hello transmissions at three times the rate than non-DIS. If ISIS is elected as DIS on this interface, ISIS sends Hello every 3.3 seconds. If minimal keyword is specified, Holding timer in Hello PDU is set to 1 second and Hello interval is calculated by dividing by the hello-multiplier.

Attribute Name: hello-interval

Attribute Type: uint16

Default Value: 10

Attribute Range: 1-65535

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
</isis>
```

```

</config>
<interface-parameters>
<level-infos>
<level-info>
  <level>level-1-2</level>
  <config>
    <level>level-1-2</level>
  </config>
  <hello-interval>1</hello-interval> <!-- operation="delete"-->
</level-info>
</level-infos>
</interface-parameters>
</interface>
</interfaces>
</isis>

```

## Command Syntax

```
isis hello-interval <1-65535> (level-1|level-2|)
```

---

## Configure hello multiplier

Use this attribute to set multiplier for Hello holding time. Changes Holding Timer in Hello PDU. Holding timer is calculated by .Hello-Interval. multiplied by this value. If minimal keyword is specified with the Hello-Interval, the holding timer is set to 1 second and the hello-interval is calculated by dividing 1 by this value.

Attribute Name: hello-multiplier

Attribute Type: uint8

Default Value: 3

Attribute Range: 2-100

## Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<interface-parameters>
<level-infos>
<level-info>
  <level>level-1-2</level>
  <config>
    <level>level-1-2</level>
  </config>
  <hello-multiplier>2</hello-multiplier> <!-- operation="delete"-->
</level-info>
</level-infos>
</interface-parameters>

```

```

</interface>
</interfaces>
</isis>

```

## Command Syntax

```
isis hello-multiplier <2-100> (level-1|level-2|)
```

---

## Configure csnp interval

Use this attribute to set CSNP (Complete sequence number PDU) interval in seconds. Configuring this attribute changes the interval between two consecutive CSNP transmission. By default, CSNP is sent every 10 seconds only by LAN DIS. This parameter is only valid on broadcast interface, since periodic CSNP is only sent on broadcast interface, while CSNP on Point-to-Point interface is sent only when adjacency is initiated.

Attribute Name: csnp-interval

Attribute Type: uint16

Default Value: 10

Attribute Range: 1-65535

## Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <interface-parameters>
  <level-infos>
  <level-info>
    <level>level-1-2</level>
    <config>
      <level>level-1-2</level>
    </config>
    <csnp-interval>1</csnp-interval> <!-- operation="delete"-->
  </level-info>
</level-infos>
</interface-parameters>
</interface>
</interfaces>
</isis>

```

## Command Syntax

```
isis csnp-interval <1-65535> (level-1|level-2|)
```

---

## Configure priority

Use this attribute to set the priority for LAN DIS election. This attribute changes the priority value in LAN ISIS Hello PDUs. A lower priority value is less preferred in DIS election, and a higher priority value is more preferred

Attribute Name: priority

Attribute Type: uint8

Default Value: 64

Attribute Range: 0-127

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <level-infos>
          <level-info>
            <level>level-1-2</level>
            <config>
              <level>level-1-2</level>
            </config>
            <priority>0</priority> <!-- operation="delete"-->
          </level-info>
        </level-infos>
      </interface-parameters>
    </interface>
  </interfaces>
</isis>
```

### Command Syntax

```
isis priority <0-127> (level-1|level-2|)
```

---

## Configure metric

Use this attribute to set default metric for the interface. The interface default metric is put into IP reachability information TLVs, IS reachability information TLVs and IPv6 reachability TLVs in LSPs. The value is used for SPF calculation, and is applied when the metric-style is configured as `.narrow`.

Attribute Name: metric

Attribute Type: uint8

Default Value: 10

Attribute Range: 1-63

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
```

```

    <name>WORD</name>
  </config>
</interface-parameters>
<level-infos>
<level-info>
  <level>level-1-2</level>
  <config>
    <level>level-1-2</level>
  </config>
  <metric>1</metric> <!-- operation="delete"-->
</level-info>
</level-infos>
</interface-parameters>
</interface>
</interfaces>
</isis>

```

### Command Syntax

```
isis metric <1-63> (level-1|level-2|)
```

---

## Configure password

Use this attribute to set the authentication password of Hello PDU on the interface.

Attribute Name: password

Attribute Type: string

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <interface-parameters>
  <level-infos>
  <level-info>
    <level>level-1-2</level>
    <config>
      <level>level-1-2</level>
    </config>
    <password>WORD</password> <!-- operation="delete"-->
  </level-info>
</level-infos>
</interface-parameters>
</interface>
</interfaces>
</isis>

```

## Command Syntax

```
isis password WORD (level-1|level-2|)
```

---

## Configure tag

Use this attribute to sets the tag for link-state packets (LSPs) sent out advertising routes for networks directly connected to an interface. If you do not specify a parameter, then the tag value is set for level-1-2 boundary

Attribute Name: tag

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <level-infos>
          <level-info>
            <level>level-1-2</level>
            <config>
              <level>level-1-2</level>
            </config>
            <tag>1</tag> <!-- operation="delete"-->
          </level-info>
        </level-infos>
      </interface-parameters>
    </interface>
  </interfaces>
</isis>
```

## Command Syntax

```
isis tag <1-4294967295> (level-1|level-2|)
```

---

## Configure wide metric

Use this attribute to set wide metric for the interface. Interface wide-metric is put into Extended IP reachability TLVs, Extended IS reachability TLVs and IPv6 reachability TLVs in LSPs. The value is used for SPF calculation. This value is applied when metric-style is configured as 'wide'.

Attribute Name: wide-metric

Attribute Type: uint32

Default Value: 10

Attribute Range: 1-16777214

**Netconf edit-config payload**

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <interface-parameters>
  <level-infos>
  <level-info>
    <level>level-1-2</level>
    <config>
      <level>level-1-2</level>
    </config>
    <wide-metric>1</wide-metric> <!-- operation="delete"-->
  </level-info>
</level-infos>
</interface-parameters>
</interface>
</interfaces>
</isis>

```

**Command Syntax**

```
isis wide-metric <1-16777214> (level-1|level-2|)
```

**Configure restart hello interval**

Use this attribute to configure the T1 timer, interval of ISIS Hello packet with restart TLV.

Attribute Name: restart-hello-interval

Attribute Type: uint16

Default Value: 3

Attribute Range: 1-65535

**Netconf edit-config payload**

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <interface-parameters>
  <level-infos>
  <level-info>
    <level>level-1-2</level>
    <config>
      <level>level-1-2</level>
    </config>
  </level-info>
</level-infos>
</interface-parameters>
</interface>
</interfaces>
</isis>

```

```

    </config>
    <restart-hello-interval>1</restart-hello-interval> <!--
operation="delete"-->
    </level-info>
  </level-infos>
</interface-parameters>
</interface>
</interfaces>
</isis>

```

### Command Syntax

```
isis restart-hello-interval <1-65535> (level-1|level-2|)
```

---

## Configure te minimum delay

Interface minimum delay value in microseconds.

Attribute Name: te-minimum-delay

Attribute Type: uint32

Attribute Range: 1-65535

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <level-infos>
          <level-info>
            <level>level-1-2</level>
            <config>
              <level>level-1-2</level>
            </config>
            <te-minimum-delay>1</te-minimum-delay> <!-- operation="delete"-->
          </level-info>
        </level-infos>
      </interface-parameters>
    </interface>
  </interfaces>
</isis>

```

### Command Syntax

```
isis te-minimum-delay <1-65535> (level-1|level-2|)
```

---

## Configure te maximum delay

Interface maximum delay value in microseconds.

Attribute Name: te-maximum-delay

Attribute Type: uint32

Attribute Range: 1-65535

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <level-infos>
          <level-info>
            <level>level-1-2</level>
            <config>
              <level>level-1-2</level>
            </config>
            <te-maximum-delay>1</te-maximum-delay> <!-- operation="delete"-->
          </level-info>
        </level-infos>
      </interface-parameters>
    </interface>
  </interfaces>
</isis>
```

### Command Syntax

```
isis te-maximum-delay <1-65535> (level-1|level-2|)
```

---

## Configure te minimum delay flex algo

Interface minimum delay value for IGP Flexible Algorithm in microseconds.

Attribute Name: te-minimum-delay-flex-algo

Attribute Type: uint32

Attribute Range: 1-65535

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <level-infos>
          <level-info>
```

```

    <level>level-1-2</level>
  <config>
    <level>level-1-2</level>
  </config>
  <te-minimum-delay-flex-algo>1</te-minimum-delay-flex-algo> <!--
operation="delete"-->
</level-info>
</level-infos>
</interface-parameters>
</interface>
</interfaces>
</isis>

```

### Command Syntax

```
isis te-minimum-delay flex-algo <1-65535> (level-1|level-2|)
```

---

## Configure te maximum delay flex algo

Interface maximum delay value for IGP Flexible Algorithm in microseconds.

Attribute Name: te-maximum-delay-flex-algo

Attribute Type: uint32

Attribute Range: 1-65535

### Netconf edit-config payload

```

<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <level-infos>
          <level-info>
            <level>level-1-2</level>
            <config>
              <level>level-1-2</level>
            </config>
            <te-maximum-delay-flex-algo>1</te-maximum-delay-flex-algo> <!--
operation="delete"-->
          </level-info>
        </level-infos>
      </interface-parameters>
    </interface>
  </interfaces>
</isis>

```

### Command Syntax

```
isis te-maximum-delay flex-algo <1-65535> (level-1|level-2|)
```

---

## Configure mode

Use this attribute to set the MD5 authentication mode.

Attribute Name: mode

Attribute Type: enum (md5|text)

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-parameters>
        <level-infos>
          <level-info>
            <level>level-1-2</level>
            <config>
              <level>level-1-2</level>
            </config>
            <authentication>
              <config>
                <mode>md5</mode>
              </config>
            </authentication>
          </level-info>
        </level-infos>
      </interface-parameters>
    </interface>
  </interfaces>
</isis>
```

### Command Syntax

```
isis authentication mode (md5|text) (level-1|level-2|)
```

---

## Configure key chain

Use this attribute to set the key chain to be used for authentication on the interface-related packets. Authentication mode must be set to md5/text to configure the key chain. Only one authentication key-chain is applied to an ISIS interface at a time. Authentication can be specified for an entire instance of ISIS, instead of at the interface level, by setting the authentication key-chain attribute at global level.

Attribute Name: key-chain

Attribute Type: string

### Netconf edit-config payload

```
<isis xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-isis">
  <interfaces>
```

```

<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <interface-parameters>
  <level-infos>
  <level-info>
    <level>level-1-2</level>
    <config>
      <level>level-1-2</level>
    </config>
    <authentication>
    <config>
      <key-chain>WORD</key-chain> <!-- operation="delete"-->
    </config>
    </authentication>
  </level-info>
</level-infos>
</interface-parameters>
</interface>
</interfaces>
</isis>

```

### Command Syntax

```
isis authentication key-chain WORD (level-1|level-2|)
```

---

## clear isis interface counter (IFNAME|)

Attribute Name: name

Attribute Type: string

### Netconf RPC payload

```

<ipi-isis-interface_isis-clear-interface-counters xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-isis">
  <name>IFNAME</name>
</ipi-isis-interface_isis-clear-interface-counters>

```

### Command Syntax

```
clear isis interface counter (IFNAME|)
```

---

## IPI-KEYCHAIN

---

### Configure name

key-chain name

Attribute Name: name

Attribute Type: string

### Netconf edit-config payload

```
<key-chains xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-keychain">
<key-chain> <!-- operation="delete"-->
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</key-chain>
</key-chains>
```

### Command Syntax

```
key chain WORD
```

---

## Configure key id

Use this attribute to manageCOMMA add or delete authentication keys in a key-chain

Attribute Name: key-id

Attribute Type: uint32

Attribute Range: 0-2147483647

### Netconf edit-config payload

```
<key-chains xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-keychain">
<key-chain>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<keys>
<key-list> <!-- operation="delete"-->
  <key-id>0</key-id>
  <config>
    <key-id>0</key-id>
  </config>
</key-list>
</keys>
</key-chain>
</key-chains>
```

### Command Syntax

```
key-id <0-2147483647>
```

---

## Configure key string

Use this attribute to define a password to be used by a key

Attribute Name: key-string

Attribute Type: string

Attribute Range: 1-80

### Netconf edit-config payload

```
<key-chains xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-keychain">
  <key-chain>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  </key-chain>
</key-chains>
```

### Command Syntax

```
key-string WORD
```

---

## Configure encrypted

Use this attribute to pass the key string in hexadecimal string format

Attribute Name: encrypted

Attribute Type: string

Attribute Range: 18-162

### Netconf edit-config payload

```
<key-chains xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-keychain">
  <key-chain>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  </key-chain>
</key-chains>
```

```
</key-chain>
</key-chains>
```

## Command Syntax

```
key-string encrypted WORD
```

---

## Configure start date time for accept

Configure the start date-time of the key for accept-lifetime

Attribute Name: start-date-time-for-accept

Attribute Type: string

Attribute Name: end-date-time-for-accept

Attribute Type: string

Attribute Name: infinite-for-accept

Attribute Type: empty

Attribute Name: duration-for-accept

Attribute Type: uint32

Attribute Range: 1-2147483646

## Netconf edit-config payload

```
<key-chains xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-keychain">
  <key-chain>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  </key-chain>
</key-chains>
<key-list>
  <key-id>0</key-id>
  <config>
    <key-id>0</key-id>
  </config>
</key-list>
<accept-lifetime>
  <config>
    <end-date-time-for-accept>KEYCHAIN_DATE_TIME_T</end-date-time-for-accept>
    </infinite-for-accept>
    <duration-for-accept>1</duration-for-accept>
    <start-date-time-for-accept>KEYCHAIN_DATE_TIME_T</start-date-time-for-accept>
  </config>
</accept-lifetime>
</key-list>
</key-chains>
```

## Command Syntax

```
accept-lifetime HH:MM:SS MONTH <01-31> <1993-2035> HH:MM:SS MONTH <01-31> <1993-2035> infinite duration <1-2147483646>
```

---

## Configure start date time for send

Configure the start date-time of the key for send-lifetime

Attribute Name: start-date-time-for-send

Attribute Type: string

Attribute Name: end-date-time-for-send

Attribute Type: string

Attribute Name: infinite-for-send

Attribute Type: empty

Attribute Name: duration-for-send

Attribute Type: uint32

Attribute Range: 1-2147483646

## Netconf edit-config payload

```
<key-chains xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-keychain">
  <key-chain>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  <keys>
    <key-list>
      <key-id>0</key-id>
      <config>
        <key-id>0</key-id>
        </config>
      <send-lifetime>
        <config>
          <end-date-time-for-send>KEYCHAIN_DATE_TIME_T</end-date-time-for-send>
          </infinite-for-send>
          <duration-for-send>1</duration-for-send>
          <start-date-time-for-send>KEYCHAIN_DATE_TIME_T</start-date-time-for-send>
        </config>
      </send-lifetime>
    </key-list>
  </keys>
</key-chain>
</key-chains>
```

## Command Syntax

```
send-lifetime HH:MM:SS MONTH <01-31> <1993-2035> HH:MM:SS MONTH <01-31> <1993-2035>
infinite duration <1-2147483646>
```

---

## IPI-PIM

---

### Configure bfd

Use this attribute to debug the PIM BFD feature.

This command is supported when following feature are enabled Bidirectional Forwarding Detection (BFD)

Attribute Name: bfd

Attribute Type: empty

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <debug>
    <config>
      </bfd><!-- operation="delete"-->
    </config>
  </debug>
</pim>
```

### Command Syntax

```
debug pim bfd
```

---

## IPI-PIM-IPV4

---

### Configure router id

Use this attribute to configure PIM router-ID to uniquely identify the router. By default, PIM registers for the NSM router-id service. This attribute will override the router-id received from NSM.

Attribute Name: router-id

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </config>
          <router-id>A.B.C.D</router-id> <!-- operation="delete"-->
        </instance>
      </instances>
    </ipv4>
  </pim>
```

---

## Command Syntax

```
ip pim (vrf NAME|) router-id A.B.C.D
```

---

## Configure join prune interval

Use this attribute to set a PIM join/prune timer.

Attribute Name: join-prune-interval

Attribute Type: uint16

Attribute Range: 1-65535

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <join-prune-interval>1</join-prune-interval> <!-- operation="delete"-->
      </instance>
    </instances>
  </ipv4>
</pim>
```

## Command Syntax

```
ip pim (vrf NAME|) jp-timer <1-65535>
```

---

## Configure ecmp bundle

Use this attribute to create an ECMP bundle.

Attribute Name: ecmp-bundle

Attribute Type: string

Attribute Range: 1-50

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <ecmp-bundle>WORD</ecmp-bundle> <!-- operation="delete"-->
      </instance>
    </instances>
  </ipv4>
</pim>
```

```
</ipv4>
</pim>
```

## Command Syntax

```
ip pim (vrf NAME|) ecmp-bundle WORD
```

---

## Configure enable bfd all interfaces

Use this attribute to enable Bidirectional Forwarding Detection (BFD) on all interfaces.

Attribute Name: enable-bfd-all-interfaces

Attribute Type: empty

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        </enable-bfd-all-interfaces><!-- operation="delete"-->
      </instance>
    </instances>
  </ipv4>
</pim>
```

## Command Syntax

```
ip pim (vrf NAME|) bfd all-interfaces
```

---

## Configure register reachability check

Use this attribute to enable the RP reachability check for PIM Registers at the designated router (DR).

This command is supported when following feature are enabled PIM Sparse Mode (SM)

Attribute Name: register-reachability-check

Attribute Type: enum (disable|enable)

Default Value: enable

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
      </instance>
    </instances>
  </ipv4>
</pim>
```

```

    <register-packet>
    <config>
        <register-reachability-check>enable</register-reachability-check> <!--
operation="delete"-->
    </config>
</register-packet>
</instance>
</instances>
</ipv4>
</pim>

```

## Command Syntax

```
ip pim (vrf NAME|) register-rp-reachability (disable|enable)
```

---

## Configure rate limit

Use this attribute to configure the rate of register packets sent by this designated router (DR).

This command is supported when following feature are enabled PIM Sparse Mode (SM)

Attribute Name: rate-limit

Attribute Type: uint16

Attribute Range: 1-65535

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
<ipv4>
<instances>
<instance>
    <vrf-name>NAME</vrf-name>
    <config>
        <vrf-name>NAME</vrf-name>
    </config>
    <register-packet>
    <config>
        <rate-limit>1</rate-limit> <!-- operation="delete"-->
    </config>
</register-packet>
</instance>
</instances>
</ipv4>
</pim>

```

## Command Syntax

```
ip pim (vrf NAME|) register-rate-limit <1-65535>
```

---

## Configure suppress interval

Use this attribute to configure the register suppression time.

This command is supported when following feature are enabled PIM Sparse Mode (SM)

Attribute Name: suppress-interval

Attribute Type: uint16

Default Value: 60

Attribute Range: 11-65535

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </config>
          <register-packet>
            <config>
              <suppress-interval>11</suppress-interval> <!-- operation="delete"-->
            </config>
          </register-packet>
        </instance>
      </instances>
    </ipv4>
  </pim>
```

### Command Syntax

```
ip pim (vrf NAME|) register-suppression <11-65535>
```

---

## Configure keep alive interval

Use this attribute to configure a Keep alive Timer (KAT) value for (S,G) states at RP to monitor PIM register packets.

This command is supported when following feature are enabled PIM Sparse Mode (SM)

Attribute Name: keep-alive-interval

Attribute Type: uint16

Default Value: 185

Attribute Range: 1-65535

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </config>
          <register-packet>
            <config>
```

```

        <keep-alive-interval>1</keep-alive-interval> <!-- operation="delete"-->
    </config>
</register-packet>
</instance>
</instances>
</ipv4>
</pim>

```

### Command Syntax

```
ip pim (vrf NAME|) rp-register-kat <1-65535>
```

---

## Configure source address

Use this attribute to configure the source address of register packets sent by this designated router (DR).

This command is supported when following feature are enabled PIM Sparse Mode (SM)

Attribute Name: source-address

Attribute Type: union

### Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </config>
          <register-packet>
            <config>
              <source-address>PIM_IPV4_REG_SOURCE_T</source-address>
            </config>
          </register-packet>
        </instance>
      </instances>
    </ipv4>
  </pim>

```

### Command Syntax

```
ip pim (vrf NAME|) register-source (A.B.C.D|IFNAME)
```

---

## Configure accept register

Use this attribute to configure the ACL of register packets accepted by this designated router (DR).

This command is supported when following feature are enabled PIM Sparse Mode (SM)

Attribute Name: accept-register

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <register-packet>
          <config>
            <accept-register>WORD</accept-register> <!-- operation="delete"-->
          </config>
        </register-packet>
      </instance>
    </instances>
  </ipv4>
</pim>

```

## Command Syntax

```
ip pim (vrf NAME|) accept-register list WORD
```

---

## Configure ignore rp set priority

Use this attribute to ignore the RP-SET priority value, and use only the hashing mechanism for RP selection. This is used to inter-operate with older Cisco IOS versions.

Attribute Name: ignore-rp-set-priority

Attribute Type: empty

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <interop>
          <config>
            </ignore-rp-set-priority><!-- operation="delete"-->
          </config>
        </interop>
      </instance>
    </instances>
  </ipv4>
</pim>

```

---

## Command Syntax

```
ip pim (vrf NAME|) ignore-rp-set-priority
```

---

## Configure cisco bsr interop enable

Use this attribute to turn on or turn the Candidate-RP debugging timerworking with Cisco BSR.

Attribute Name: cisco-bsr-interop-enable

Attribute Type: empty

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <interop>
          <config>
            </cisco-bsr-interop-enable><!-- operation="delete"-->
          </config>
        </interop>
      </instance>
    </instances>
  </ipv4>
</pim>
```

## Command Syntax

```
ip pim (vrf NAME|) crp-cisco-prefix
```

---

## Configure access control list

Use this attribute to configure the option to calculate the register checksum over the whole packet on multicast groups specified by the access control list.

Attribute Name: access-control-list

Attribute Type: string

Attribute Range: 1-64

Attribute Name: cisco-register-checksum-enable

Attribute Type: empty

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
```

```

    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
    <interop>
    <register-packet>
    <config>
      </cisco-register-checksum-enable><!-- operation="delete"-->
      <access-control-list>WORD</access-control-list> <!-- operation="delete"--
>
      </config>
    </register-packet>
  </interop>
</instance>
</instances>
</ipv4>
</pim>

```

## Command Syntax

```
ip pim (vrf NAME|) cisco-register-checksum group-list WORD
```

---

## Configure cisco register checksum enable

Use this attribute to configure the option to calculate the register checksum over the whole packet. This is used to interoperate with older Cisco IOS versions.

Attribute Name: cisco-register-checksum-enable

Attribute Type: empty

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <interop>
        <register-packet>
        <config>
          </cisco-register-checksum-enable>
        </config>
      </register-packet>
    </interop>
  </instance>
</instances>
</ipv4>
</pim>

```

## Command Syntax

```
ip pim (vrf NAME|) cisco-register-checksum
```

---

## Configure vrf name

Use this attribute to enable the ability of the last-hop PIM router to switch to SPT for multicast group addresses indicated by the given standard access control list.

Attribute Name: access-control-list

Attribute Type: string

Attribute Range: 1-64

Attribute Name: enable

Attribute Type: empty

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <spt-switch>
          <config>
            </enable><!-- operation="delete"-->
            <access-control-list>WORD</access-control-list> <!-- operation="delete"-->
          </config>
        </spt-switch>
      </instance>
    </instances>
  </ipv4>
</pim>
```

## Command Syntax

```
ip pim (vrf NAME|) spt-threshold group-list WORD
```

---

## Configure enable

Use this attribute to enable the ability of the last-hop PIM router to switch to SPT.

Attribute Name: enable

Attribute Type: empty

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
```

```

<instance>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  <spt-switch>
    <config>
      </enable>
    </config>
  </spt-switch>
</instance>
</instances>
</ipv4>
</pim>

```

### Command Syntax

```
ip pim (vrf NAME|) spt-threshold
```

---

## Configure range policy

Use this attribute to set Source Specific Multicast (SSM) and define the range of multicast IP addresses. Ranges can be either the default, which defines the SSM range as 232/8, or indicated by the given standard access control list.

This command is supported when following feature are enabled PIM Source Specific Multicast (SSM)

Attribute Name: range-policy

Attribute Type: union

### Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <ssm>
          <config>
            <range-policy>PIM_IPV4_SSM_RANGE_POLICY_TYPE_T</range-policy>
          </config>
        </ssm>
      </instance>
    </instances>
  </ipv4>
</pim>

```

### Command Syntax

```
ip pim (vrf NAME|) ssm (range WORD|default)
```

---

## Configure member rp address

Destination IP address where register messages are copied and sent. A Member RP is an individual RP member in the anycast RP set.

This command is supported when following feature are enabled PIM Sparse Mode (SM)

Attribute Name: member-rp-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <anycast-rps>
          <anycast-rp> <!-- operation="delete"-->
            <member-rp-address>A.B.C.D</member-rp-address>
            <config>
              <member-rp-address>A.B.C.D</member-rp-address>
              <anycast-rp-address>A.B.C.D</anycast-rp-address>
            </config>
            <anycast-rp-address>A.B.C.D</anycast-rp-address>
          </anycast-rp>
        </anycast-rps>
      </instance>
    </instances>
  </ipv4>
</pim>
```

### Command Syntax

```
ip pim (vrf NAME|) anycast-rp A.B.C.D A.B.C.D
```

---

## Configure rp address

Use this attribute to statically configure Rendezvous Point (RP) address for multicast groups.

Attribute Name: rp-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
```

```

    <vrf-name>NAME</vrf-name>
  </config>
  <rendezvous-point>
  <static-rps>
  <static-rps-default>
  <static-rp-default> <!-- operation="delete"-->
    <rp-address>A.B.C.D</rp-address>
  <config>
    <rp-address>A.B.C.D</rp-address>
  </config>
  </static-rp-default>
</static-rps-default>
</static-rps>
</rendezvous-point>
</instance>
</instances>
</ipv4>
</pim>

```

## Command Syntax

```
ip pim (vrf NAME|) rp-address A.B.C.D
```

---

## Configure override dynamically learned rp

Use this attribute to configure the flag to override dynamically learned RP mappings.

Attribute Name: `override-dynamically-learned-rp`

Attribute Type: empty

Attribute Name: `access-control-list`

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
  <instances>
  <instance>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
    <rendezvous-point>
    <static-rps>
    <static-rps-default>
    <static-rp-default>
      <rp-address>A.B.C.D</rp-address>
    <config>
      <rp-address>A.B.C.D</rp-address>

```

```

    <access-control-list>WORD</access-control-list> <!-- operation="delete"-->
>
    </config>
    </override-dynamically-learned-rp><!-- operation="delete"-->
    </static-rp-default>
</static-rps-default>
</static-rps>
</rendezvous-point>
</instance>
</instances>
</ipv4>
</pim>

```

## Command Syntax

```
ip pim (vrf NAME|) rp-address A.B.C.D WORD override
```

## Configure static-rp-default access-control-list

Use this attribute to configure the name of access control list (ACL).

Attribute Name: access-control-list

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
<ipv4>
<instances>
<instance>
    <vrf-name>NAME</vrf-name>
    <config>
        <vrf-name>NAME</vrf-name>
    </config>
    <rendezvous-point>
    <static-rps>
    <static-rps-default>
    <static-rp-default>
        <rp-address>A.B.C.D</rp-address>
    <config>
        <rp-address>A.B.C.D</rp-address>
    </config>
        <access-control-list>WORD</access-control-list> <!-- operation="delete"-->
>
    </static-rp-default>
</static-rps-default>
</static-rps>
</rendezvous-point>
</instance>
</instances>
</ipv4>

```

---

```
</pim>
```

## Command Syntax

```
ip pim (vrf NAME|) rp-address A.B.C.D WORD
```

---

## Configure static-rp-default override-dynamically-learned-rp

Use this attribute to configure the flag to override dynamically learned RP mappings.

Attribute Name: override-dynamically-learned-rp

Attribute Type: empty

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <rendezvous-point>
          <static-rps>
            <static-rps-default>
              <static-rp-default>
                <rp-address>A.B.C.D</rp-address>
                <config>
                  <rp-address>A.B.C.D</rp-address>
                </config>
              </override-dynamically-learned-rp><!-- operation="delete"-->
            </static-rp-default>
          </static-rps-default>
        </static-rps>
      </rendezvous-point>
    </instance>
  </instances>
</ipv4>
</pim>
```

## Command Syntax

```
ip pim (vrf NAME|) rp-address A.B.C.D override
```

---

## Configure interface name

Use this attribute to configure the interface for the candidate BSR router.

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
<ipv4>
<instances>
<instance>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  <rendezvous-point>
  <bootstrap-router>
  <bsr-candidate>
  <config>
    <interface-name>IFNAME</interface-name> <!-- operation="delete"-->
  </config>
</bsr-candidate>
</bootstrap-router>
</rendezvous-point>
</instance>
</instances>
</ipv4>
</pim>

```

## Command Syntax

```
ip pim (vrf NAME|) bsr-candidate IFNAME
```

---

## Configure hash mask length

Use this attribute to configure the mask length used to calculate the group address for RP.

Attribute Name: hash-mask-length

Attribute Type: uint8

Attribute Range: 0-32

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
<ipv4>
<instances>
<instance>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  <rendezvous-point>
  <bootstrap-router>

```

```

    <bsr-candidate>
    <config>
        <interface-name>IFNAME</interface-name> <!-- operation="delete"-->
        <hash-mask-length>0</hash-mask-length> <!-- operation="delete"-->
    </config>
</bsr-candidate>
</bootstrap-router>
</rendezvous-point>
</instance>
</instances>
</ipv4>
</pim>

```

## Command Syntax

```
ip pim (vrf NAME|) bsr-candidate IFNAME <0-32>
```

---

## Configure priority

Use this attribute to configure the priority value for candidate BSR router.

Attribute Name: priority

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

Attribute Name: hash-mask-length

Attribute Type: uint8

Attribute Range: 0-32

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
<ipv4>
<instances>
<instance>
    <vrf-name>NAME</vrf-name>
    <config>
        <vrf-name>NAME</vrf-name>
    </config>
    <rendezvous-point>
    <bootstrap-router>
    <bsr-candidate>
    <config>
        <interface-name>IFNAME</interface-name> <!-- operation="delete"-->
        <hash-mask-length>0</hash-mask-length> <!-- operation="delete"-->
        <priority>0</priority> <!-- operation="delete"-->
    </config>

```

```

</bsr-candidate>
</bootstrap-router>
</rendezvous-point>
</instance>
</instances>
</ipv4>
</pim>

```

## Command Syntax

```
ip pim (vrf NAME|) bsr-candidate IFNAME <0-32> <0-255>
```

---

## Configure bsr-candidate interface-name

Use this attribute to configure the interface for the candidate BSR router.

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </config>
          <rendezvous-point>
          <bootstrap-router>
          <bsr-candidate>
            <config>
              <interface-name>IFNAME</interface-name> <!-- operation="delete"-->
            </config>
          </bsr-candidate>
          </bootstrap-router>
          </rendezvous-point>
        </instance>
      </instances>
    </ipv4>
  </pim>

```

## Command Syntax

```
ip pim (vrf NAME|) bsr-candidate IFNAME
```

---

## Configure rp-candidates interface-name

Use this attribute to configure the interface name for RP.

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <rendezvous-point>
          <rp-candidates>
            <rp-candidate> <!-- operation="delete"-->
              <interface-name>IFNAME</interface-name>
              <config>
                <interface-name>IFNAME</interface-name>
              </config>
            </rp-candidate>
          </rp-candidates>
        </rendezvous-point>
      </instance>
    </instances>
  </ipv4>
</pim>
```

### Command Syntax

```
ip pim (vrf NAME|) rp-candidate IFNAME
```

---

## Configure advertisement interval

Use this attribute to configure the priority value for RP candidate.

Attribute Name: priority

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: access-control-list

Attribute Type: string

Attribute Range: 1-64

Attribute Name: advertisement-interval

Attribute Type: uint16

Attribute Range: 1-16383

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
```

```

<instances>
<instance>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  <rendezvous-point>
  <rp-candidates>
  <rp-candidate>
    <interface-name>IFNAME</interface-name>
    <config>
      <interface-name>IFNAME</interface-name>
      <access-control-list>WORD</access-control-list> <!-- operation="delete"-->
    >
      <advertisement-interval>1</advertisement-interval> <!--
operation="delete"-->
    </config>
      <priority>0</priority> <!-- operation="delete"-->
    </rp-candidate>
  </rp-candidates>
</rendezvous-point>
</instance>
</instances>
</ipv4>
</pim>

```

## Command Syntax

```

ip pim (vrf NAME|) rp-candidate IFNAME (group-list WORD|) (interval <1-16383>|)
(priority <0-255>|)

```

---

## Configure originator id

Use this attribute to allow a Multicast Source Discovery Protocol (MSDP) speaker that originates a Source-Active (SA) message to use the IP address of an interface as a rendezvous point (RP) address in the SA message.

This command is supported when following feature are enabled HAVE\_PIM\_MSDP

Attribute Name: originator-id

Attribute Type: string

Attribute Range: 1-33

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
<ipv4>
<instances>
<instance>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  <msdp>

```

```

    <config>
      <originator-id>IFNAME</originator-id> <!-- operation="delete"-->
    </config>
  </msdp>
</instance>
</instances>
</ipv4>
</pim>

```

## Command Syntax

```
ip msdp (vrf NAME|) originator-id IFNAME
```

---

## Configure group address

Use this attribute to configure an Multicast Source Discovery Protocol (MSDP) remote group.

This command is supported when following feature are enabled HAVE\_PIM\_MSDP

Attribute Name: group-address

Attribute Type: inet:ipv4-address

Attribute Name: rp-address

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <msdp>
          <source-active-entries>
            <source-active-entry> <!-- operation="delete"-->
              <group-address>A.B.C.D</group-address>
              <config>
                <group-address>A.B.C.D</group-address>
                <source-address>A.B.C.D</source-address>
                <rp-address>A.B.C.D</rp-address>
              </config>
              <source-address>A.B.C.D</source-address>
            </source-active-entry>
          </source-active-entries>
        </msdp>
      </instance>
    </instances>
  </ipv4>
</pim>

```

---

## Command Syntax

```
ip msdp (vrf NAME|) sa s A.B.C.D g A.B.C.D r A.B.C.D
```

---

## Configure address

Use this attribute to configure an Multicast Source Discovery Protocol (MSDP) peer relationship.

This command is supported when following feature are enabled HAVE\_PIM\_MSDP

Attribute Name: address

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <msdp>
          <peers>
            <peer> <!-- operation="delete"-->
              <address>A.B.C.D</address>
              <config>
                <address>A.B.C.D</address>
              </config>
            </peer>
          </peers>
        </msdp>
      </instance>
    </instances>
  </ipv4>
</pim>
```

## Command Syntax

```
ip msdp (vrf NAME|) peer A.B.C.D
```

---

## Configure mesh group

Use this attribute to configure an Multicast Source Discovery Protocol (MSDP) peer relationship.

This command is supported when following feature are enabled HAVE\_PIM\_MSDP

Attribute Name: address

Attribute Type: inet:ipv4-address

Attribute Name: mesh-group

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <msdp>
          <peers>
            <peer>
              <address>A.B.C.D</address>
              <config>
                <address>A.B.C.D</address>
                <mesh-group>WORD</mesh-group> <!-- operation="delete"-->
              </config>
            </peer>
          </peers>
        </msdp>
      </instance>
    </instances>
  </ipv4>
</pim>

```

## Command Syntax

```
ip msdp (vrf NAME|) mesh-group WORD A.B.C.D
```

---

## Configure default peer

Use this attribute to configure an Multicast Source Discovery Protocol (MSDP) peer relationship.

This command is supported when following feature are enabled HAVE\_PIM\_MSDP

Attribute Name: address

Attribute Type: inet:ipv4-address

Attribute Name: default-peer

Attribute Type: empty

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <msdp>
          <peers>

```

```

    <peer>
      <address>A.B.C.D</address>
      <config>
        <address>A.B.C.D</address>
        </default-peer><!-- operation="delete"-->
      </config>
    </peer>
  </peers>
</msdp>
</instance>
</instances>
</ipv4>
</pim>

```

## Command Syntax

```
ip msdp (vrf NAME|) default-peer A.B.C.D
```

---

## Configure prefix list

Use this attribute to set a Multicast Source Discovery Protocol (MSDP) peer from which to accept Source-Active (SA) messages. You can have multiple active default peers: 1. When you enter multiple `ip msdp default-peer` commands with a `prefix-list` keyword, all the default peers are used at the same time for different RP prefixes. This form is typically used in a service provider cloud that connects stub site clouds. 2. When you enter multiple `ip msdp default-peer` commands without a `prefix-list` keyword, a single active peer accepts all SA messages. If that peer fails, the next configured default peer accepts all SA messages. This form is typically used at a stub site.

This command is supported when following feature are enabled `HAVE_PIM_MSDP`

Attribute Name: `prefix-list`

Attribute Type: union

Attribute Name: `default-peer`

Attribute Type: empty

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <msdp>
          <peers>
            <peer>
              <address>A.B.C.D</address>
              <config>
                <address>A.B.C.D</address>
                </default-peer><!-- operation="delete"-->
              </config>
            </peer>
          </peers>
        </msdp>
      </instance>
    </instances>
  </ipv4>
</pim>

```

```

        <prefix-list>PIM_IPV4_MSDP_PEER_ACL_T</prefix-list>
    </peer>
</peers>
</msdp>
</instance>
</instances>
</ipv4>
</pim>

```

## Command Syntax

```
ip msdp (vrf NAME|) default-peer A.B.C.D prefix-list (WORD|<1-99>)
```

---

## Configure peer source-address

Use this attribute to configure an Multicast Source Discovery Protocol (MSDP) peer relationship.

This command is supported when following feature are enabled HAVE\_PIM\_MSDP

Attribute Name: source-address

Attribute Type: union

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <msdp>
          <peers>
            <peer>
              <address>A.B.C.D</address>
              <config>
                <address>A.B.C.D</address>
              </config>
              <source-address>PIM_IPV4_REG_SOURCE_T</source-address>
            </peer>
          </peers>
        </msdp>
      </instance>
    </instances>
  </ipv4>
</pim>

```

## Command Syntax

```
ip msdp (vrf NAME|) peer A.B.C.D connect-source (A.B.C.D|IFNAME)
```

---

## Configure password

Use this command to set an password key used for authenticating a Multicast Source Discovery Protocol (MSDP) peer. By default, no password is enabled.

This command is supported when following feature are enabled HAVE\_PIM\_MSDP

Attribute Name: password

Attribute Type: string

Attribute Range: 1-162

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <msdp>
          <peers>
            <peer>
              <address>A.B.C.D</address>
              <config>
                <address>A.B.C.D</address>
              </config>
              <authentication>
                <config>
                  <password>WORD</password> <!-- operation="delete"-->
                </config>
              </authentication>
            </peer>
          </peers>
        </msdp>
      </instance>
    </instances>
  </ipv4>
</pim>
```

### Command Syntax

```
ip msdp (vrf NAME|) password WORD peer A.B.C.D
```

---

## Configure options

Use this attribute to debug the PIM IPv4 feature.

Attribute Name: options

Attribute Type: bits (all|events|packet|packet in|packet out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer hello nt|timer hello tht|timer joinprune jt|timer joinprune et|timer joinprune ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr bst|timer bsr crp|mib|nsm|nexthop|mtrace|msdp)

**Netconf edit-config payload**

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
<ipv4>
<instances>
<instance>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  <debug>
  <config>
    <options>all</options> <!-- operation="delete"-->
  </config>
</debug>
</instance>
</instances>
</ipv4>
</pim>

```

**Command Syntax**

```

debug ip pim (vrf NAME|) (all|events|packet|packet in|packet
out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer
hello nlt|timer hello tht|timer joinprune jt|timer joinprune et|timer joinprune
ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr
bst|timer bsr crp|mib|nsm|nexthop|mtrace|msdp)

```

**Configure passive enable**

PIM IPv4 passive mode.

Attribute Name: passive-enable

Attribute Type: empty

Attribute Name: pim-mode

Attribute Type: enum (dense-mode|sparse-mode)

**Netconf edit-config payload**

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
<ipv4>
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
    <pim-mode>dense-mode</pim-mode> <!-- operation="delete"-->
  </config>
  </passive-enable><!-- operation="delete"-->
</interface>
</interfaces>
</ipv4>

```

```
</pim>
```

## Command Syntax

```
ip pim (dense-mode|sparse-mode) passive
```

---

## Configure pim mode

PIM IPv4 mode to use when delivering multicast traffic via this interface.

Attribute Name: pim-mode

Attribute Type: enum (dense-mode|sparse-mode)

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <pim-mode>dense-mode</pim-mode> <!-- operation="delete"-->
      </interface>
    </interfaces>
  </ipv4>
</pim>
```

## Command Syntax

```
ip pim (dense-mode|sparse-mode)
```

---

## Configure bsr border

When set to true the device will not send bootstrap router messages over this interface. By default these are transmitted over all PIM IPv4 sparse mode (PIM-SM) enabled interfaces.

Attribute Name: bsr-border

Attribute Type: empty

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        </bsr-border><!-- operation="delete"-->
      </interface>
    </interfaces>
  </ipv4>
</pim>
```

```
</ipv4>
</pim>
```

## Command Syntax

```
ip pim bsr-border
```

---

## Configure dr priority

The designated router priority of this interface. Larger always preferred.

Attribute Name: dr-priority

Attribute Type: uint32

Attribute Range: 0-4294967294

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <dr-priority>0</dr-priority> <!-- operation="delete"-->
      </interface>
    </interfaces>
  </ipv4>
</pim>
```

## Command Syntax

```
ip pim dr-priority <0-4294967294>
```

---

## Configure hello interval

Use this attribute to configure a hello interval value other than the default. When a hello-interval is configured and hello-holdtime is not configured, or when the hello-holdtime value configured is less than the new hello-interval value, the holdtime value is modified to (3.5 \* hello\_interval). Otherwise, the hello-holdtime value is the configured value.

Attribute Name: hello-interval

Attribute Type: uint16

Default Value: 30

Attribute Range: 1-18724

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <interfaces>
      <interface>
        <name>WORD</name>
```

```
<config>
  <name>WORD</name>
</config>
  <hello-interval>1</hello-interval> <!-- operation="delete"-->
</interface>
</interfaces>
</ipv4>
</pim>
```

### Command Syntax

```
ip pim hello-interval <1-18724>
```

---

## Configure hello holdtime

Use this attribute to configure a hello message holdtime other than the default.

Attribute Name: hello-holdtime

Attribute Type: uint16

Default Value: 105

Attribute Range: 1-65535

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <hello-holdtime>1</hello-holdtime> <!-- operation="delete"-->
      </interface>
    </interfaces>
  </ipv4>
</pim>
```

### Command Syntax

```
ip pim hello-holdtime <1-65535>
```

---

## Configure exclude generated id

Exclude Gen-id option from PIM IPv4 Hello packets on this interface.

Attribute Name: exclude-generated-id

Attribute Type: empty

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
```

```

<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </exclude-generated-id><!-- operation="delete"-->
</interface>
</interfaces>
</ipv4>
</pim>

```

### Command Syntax

```
ip pim exclude-genid
```

---

## Configure unicast bootstrap router

Use this attribute to enable support for sending and receiving unicast Bootstrap Messages (BSM) on an interface.

Attribute Name: unicast-bootstrap-router

Attribute Type: empty

### Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
<ipv4>
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </unicast-bootstrap-router><!-- operation="delete"-->
</interface>
</interfaces>
</ipv4>
</pim>

```

### Command Syntax

```
ip pim unicast-bsm
```

---

## Configure neighbor access control list filter

Use this attribute to enable filtering of neighbors on the interface. When configuring a neighbor filter, PIM IPv4 either not establishes adjacency with neighbor or terminates adjacency with existing neighbors, when denied by filtering access list.

Attribute Name: neighbor-access-control-list-filter

Attribute Type: string

Attribute Range: 1-64

**Netconf edit-config payload**

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <neighbor-access-control-list-filter>WORD</neighbor-access-control-list-
filter> <!-- operation="delete"-->
      </interface>
    </interfaces>
  </ipv4>
</pim>

```

**Command Syntax**

```
ip pim neighbor-filter WORD
```

**Configure state refresh origination interval**

Use this attribute to configure a PIM-DM State-Refresh origination interval other than the default value. The origination interval is the number of seconds between PIM-DM State Refresh control messages.

Attribute Name: state-refresh-origination-interval

Attribute Type: uint16

Default Value: 60

Attribute Range: 1-100

**Netconf edit-config payload**

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <state-refresh-origination-interval>1</state-refresh-origination-interval>
      <!-- operation="delete"-->
    </interface>
  </interfaces>
</ipv4>
</pim>

```

**Command Syntax**

```
ip pim state-refresh origination-interval <1-100>
```

---

## Configure name

Use this attribute to configure an ECMP bundle.

Attribute Name: ecmp-bundle

Attribute Type: string

Attribute Range: 1-50

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <ecmp-bundle>WORD</ecmp-bundle> <!-- operation="delete"-->
      </interface>
    </interfaces>
  </ipv4>
</pim>
```

### Command Syntax

```
ip pim bind ecmp-bundle WORD
```

---

## Configure propagation delay

Propagation-delay value.

Attribute Name: propagation-delay

Attribute Type: uint16

Default Value: 1000

Attribute Range: 0-32767

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <propagation-delay>0</propagation-delay> <!-- operation="delete"-->
      </interface>
    </interfaces>
  </ipv4>
</pim>
```

## Command Syntax

```
ip pim propagation-delay <0-32767>
```

---

## Configure enable bfd

Use this attribute to configure Bidirectional Forwarding Detection.

Attribute Name: enable-bfd

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <enable-bfd>enable</enable-bfd> <!-- operation="delete"-->
      </interface>
    </interfaces>
  </ipv4>
</pim>
```

## Command Syntax

```
ip pim bfd (disable|)
```

---

## Configure virtual router id

Use this attribute to set the designated router's priority value.

This command is supported when following feature are enabled HAVE\_PIM\_SM\_VRRP\_AWARE

Attribute Name: dr-priority

Attribute Type: uint32

Attribute Range: 0-4294967294

Attribute Name: virtual-router-id

Attribute Type: uint8

Attribute Range: 1-255

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv4>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
      </interface>
    </interfaces>
  </ipv4>
</pim>
```

```

</config>
<pim-redundancy>
<vrrp>
<config>
  <virtual-router-id>1</virtual-router-id>
  <dr-priority>0</dr-priority>
</config>
</vrrp>
</pim-redundancy>
</interface>
</interfaces>
</ipv4>
</pim>

```

## Command Syntax

```
ip pim redundancy <1-255> vrrp dr-priority <0-4294967294>
```

---

## Configure vrrp virtual-router-id

Use this attribute to set virtual router identifier value.

This command is supported when following feature are enabled HAVE\_PIM\_SM\_VRRP\_AWARE

Attribute Name: virtual-router-id

Attribute Type: uint8

Attribute Range: 1-255

Attribute Name: dr-priority

Attribute Type: uint32

Attribute Range: 0-4294967294

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
<ipv4>
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <pim-redundancy>
  <vrrp>
  <config>
    <dr-priority>0</dr-priority>
    <virtual-router-id>1</virtual-router-id>
  </config>
</vrrp>
</pim-redundancy>
</interface>
</interfaces>

```

```
</ipv4>
</pim>
```

### Command Syntax

```
ip pim redundancy <1-255> vrrp dr-priority <0-4294967294>
```

---

## snmp restart pim

### Netconf RPC payload

```
<ipi-pim-ipv4_pim-snmp-restart xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim"/>
```

### Command Syntax

```
snmp restart pim
```

---

## clear ip pim (vrf NAME|) (sparse-mode) bsr rp-set \*

Attribute Name: vrf-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: pim-mode

Attribute Type: enum (sparse-mode)

### Netconf RPC payload

```
<ipi-pim-ipv4_pim-ipv4-clear-bsr-rendezvous-point xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
  <pim-mode>sparse-mode</pim-mode>
</ipi-pim-ipv4_pim-ipv4-clear-bsr-rendezvous-point>
```

### Command Syntax

```
clear ip pim (vrf NAME|) (sparse-mode) bsr rp-set *
```

---

## clear ip mroute (vrf NAME|) \* pim (dense-mode|sparse-mode)

Attribute Name: vrf-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: pim-mode

Attribute Type: enum (dense-mode|sparse-mode)

### Netconf RPC payload

```
<ipi-pim-ipv4_pim-ipv4-clear-multicast-route xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
  <pim-mode>dense-mode</pim-mode>
```

```
</ipi-pim-ipv4_pim-ipv4-clear-multicast-route>
```

## Command Syntax

```
clear ip mroute (vrf NAME|) * pim (dense-mode|sparse-mode)
```

---

## clear ip mroute (vrf NAME|) A.B.C.D pim sparse-mode

Attribute Name: vrf-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: group-address

Attribute Type: inet:ipv4-address

## Netconf RPC payload

```
<ipi-pim-ipv4_pim-ipv4-clear-multicast-route-source-group xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
  <group-address>A.B.C.D</group-address>
</ipi-pim-ipv4_pim-ipv4-clear-multicast-route-source-group>
```

## Command Syntax

```
clear ip mroute (vrf NAME|) A.B.C.D pim sparse-mode
```

---

## clear ip mroute (vrf NAME|) A.B.C.D A.B.C.D pim (dense-mode|sparse-mode)

Attribute Name: vrf-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: group-address

Attribute Type: inet:ipv4-address

Attribute Name: source-address

Attribute Type: inet:ipv4-address

Attribute Name: pim-mode

Attribute Type: enum (dense-mode|sparse-mode)

## Netconf RPC payload

```
<ipi-pim-ipv4_pim-ipv4-clear-multicast-route-source-group-mode xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
  <group-address>A.B.C.D</group-address>
  <source-address>A.B.C.D</source-address>
  <pim-mode>dense-mode</pim-mode>
</ipi-pim-ipv4_pim-ipv4-clear-multicast-route-source-group-mode>
```

## Command Syntax

```
clear ip mroute (vrf NAME|) A.B.C.D A.B.C.D pim (dense-mode|sparse-mode)
```

---

## clear ip msdp (vrf NAME|) peer (A.B.C.D|)

Attribute Name: vrf-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: address

Attribute Type: inet:ipv4-address

## Netconf RPC payload

```
<ipi-pim-ipv4_pim-ipv4-clear-msdp-peer xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
  <address>A.B.C.D</address>
</ipi-pim-ipv4_pim-ipv4-clear-msdp-peer>
```

## Command Syntax

```
clear ip msdp (vrf NAME|) peer (A.B.C.D|)
```

---

## clear ip msdp (vrf NAME|) sa-cache (A.B.C.D|)

Attribute Name: vrf-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: group-address

Attribute Type: inet:ipv4-address

## Netconf RPC payload

```
<ipi-pim-ipv4_pim-ipv4-clear-msdp-sa-cache xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
  <group-address>A.B.C.D</group-address>
</ipi-pim-ipv4_pim-ipv4-clear-msdp-sa-cache>
```

## Command Syntax

```
clear ip msdp (vrf NAME|) sa-cache (A.B.C.D|)
```

---

**debug ip pim (vrf NAME|) (all|events|packet|packet in|packet out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer hello nlt|timer hello tht|timer joinprune jt|timer joinprune et|timer joinprune**

## **ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr bst|timer bsr crp|mib|nsm|nexthop|mtrace|msdp)**

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: terminal-debug-options

Attribute Type: bits (all|events|packet|packet in|packet out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer hello nlt|timer hello tht|timer joinprune jt|timer joinprune et|timer joinprune ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr bst|timer bsr crp|mib|nsm|nexthop|mtrace|msdp)

### **Netconf RPC payload**

```
<ipi-pim-ipv4-debug_pim-ipv4-terminal-debug-on xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
  <terminal-debug-options>all</terminal-debug-options>
</ipi-pim-ipv4-debug_pim-ipv4-terminal-debug-on>
```

### **Command Syntax**

```
debug ip pim (vrf NAME|) (all|events|packet|packet in|packet
out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer
hello nlt|timer hello tht|timer joinprune jt|timer joinprune et|timer joinprune
ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr
bst|timer bsr crp|mib|nsm|nexthop|mtrace|msdp)
```

---

## **no debug ip pim (vrf NAME|) (all|events|packet|packet in|packet out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer hello nlt|timer hello tht|timer joinprune jt|timer joinprune et|timer joinprune ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr bst|timer bsr crp|mib|nsm|nexthop|mtrace|msdp)**

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: terminal-debug-options

Attribute Type: bits (all|events|packet|packet in|packet out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer hello nlt|timer hello tht|timer joinprune jt|timer joinprune et|timer joinprune ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr bst|timer bsr crp|mib|nsm|nexthop|mtrace|msdp)

### **Netconf RPC payload**

```
<ipi-pim-ipv4-debug_pim-ipv4-terminal-debug-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
  <terminal-debug-options>all</terminal-debug-options>
</ipi-pim-ipv4-debug_pim-ipv4-terminal-debug-off>
```

### **Command Syntax**

```
no debug ip pim (vrf NAME|) (all|events|packet|packet in|packet
out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer
```

```
hello nlt|timer hello tht|timer joinprune jt|timer joinprune et|timer joinprune
ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr
bst|timer bsr crp|mib|nsm|nexthop|mtrace|msdp)
```

---

## debug ip pim (vrf NAME|)

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

### Netconf RPC payload

```
<ipi-pim-ipv4-debug_pim-ipv4-terminal-debug-all-on xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
</ipi-pim-ipv4-debug_pim-ipv4-terminal-debug-all-on>
```

### Command Syntax

```
debug ip pim (vrf NAME|)
```

---

## no debug ip pim (vrf NAME|)

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

### Netconf RPC payload

```
<ipi-pim-ipv4-debug_pim-ipv4-terminal-debug-all-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
</ipi-pim-ipv4-debug_pim-ipv4-terminal-debug-all-off>
```

### Command Syntax

```
no debug ip pim (vrf NAME|)
```

---

## IPI-PIM-IPV6

---

### Configure router id

Use this attribute to configure PIM router-ID to uniquely identify the router. By default, PIM registers for the NSM router-id service. This attribute will override the router-id received from NSM.

Attribute Name: router-id

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
```

```

<instances>
<instance>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  <router-id>A.B.C.D</router-id> <!-- operation="delete"-->
</instance>
</instances>
</ipv6>
</pim>

```

### Command Syntax

```
ipv6 pim (vrf NAME|) router-id A.B.C.D
```

---

## Configure join prune interval

Use this attribute to set a PIM join/prune timer.

Attribute Name: join-prune-interval

Attribute Type: uint16

Attribute Range: 1-65535

### Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
<ipv6>
<instances>
<instance>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  <join-prune-interval>1</join-prune-interval> <!-- operation="delete"-->
</instance>
</instances>
</ipv6>
</pim>

```

### Command Syntax

```
ipv6 pim (vrf NAME|) jp-timer <1-65535>
```

---

## Configure ecmp bundle

Use this attribute to create an ECMP bundle.

Attribute Name: ecmp-bundle

Attribute Type: string

Attribute Range: 1-50

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <ecmp-bundle>WORD</ecmp-bundle> <!-- operation="delete"-->
      </instance>
    </instances>
  </ipv6>
</pim>
```

## Command Syntax

```
ipv6 pim (vrf NAME|) ecmp-bundle WORD
```

---

## Configure enable bfd all interfaces

Use this attribute to enable Bidirectional Forwarding Detection (BFD) on all interfaces.

Attribute Name: enable-bfd-all-interfaces

Attribute Type: empty

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        </enable-bfd-all-interfaces><!-- operation="delete"-->
      </instance>
    </instances>
  </ipv6>
</pim>
```

## Command Syntax

```
ipv6 pim (vrf NAME|) bfd all-interfaces
```

---

## Configure register reachability check

Use this attribute to enable the RP reachability check for PIM Registers at the designated router (DR).

This command is supported when following feature are enabled PIM Sparse Mode (SM)

Attribute Name: register-reachability-check

Attribute Type: enum (disable|enable)

Default Value: enable

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <register-packet>
          <config>
            <register-reachability-check>enable</register-reachability-check> <!--
operation="delete"-->
          </config>
        </register-packet>
      </instance>
    </instances>
  </ipv6>
</pim>
```

### Command Syntax

```
ipv6 pim (vrf NAME|) register-rp-reachability (disable|enable)
```

---

## Configure rate limit

Use this attribute to configure the rate of register packets sent by this designated router (DR).

This command is supported when following feature are enabled PIM Sparse Mode (SM)

Attribute Name: rate-limit

Attribute Type: uint16

Attribute Range: 1-65535

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <register-packet>
          <config>
            <rate-limit>1</rate-limit> <!-- operation="delete"-->
          </config>
        </register-packet>
      </instance>
    </instances>
  </ipv6>
</pim>
```

```
</instance>
</instances>
</ipv6>
</pim>
```

## Command Syntax

```
ipv6 pim (vrf NAME|) register-rate-limit <1-65535>
```

---

## Configure suppress interval

Use this attribute to configure the register suppression time.

This command is supported when following feature are enabled PIM Sparse Mode (SM)

Attribute Name: suppress-interval

Attribute Type: uint16

Default Value: 60

Attribute Range: 11-65535

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </config>
          <register-packet>
            <config>
              <suppress-interval>11</suppress-interval> <!-- operation="delete"-->
            </config>
          </register-packet>
        </instance>
      </instances>
    </ipv6>
  </pim>
```

## Command Syntax

```
ipv6 pim (vrf NAME|) register-suppression <11-65535>
```

---

## Configure keep alive interval

Use this attribute to configure a Keep alive Timer (KAT) value for (S,G) states at RP to monitor PIM register packets.

This command is supported when following feature are enabled PIM Sparse Mode (SM)

Attribute Name: keep-alive-interval

Attribute Type: uint16

Default Value: 185

Attribute Range: 1-65535

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <register-packet>
          <config>
            <keep-alive-interval>1</keep-alive-interval> <!-- operation="delete"-->
          </config>
        </register-packet>
      </instance>
    </instances>
  </ipv6>
</pim>
```

### Command Syntax

```
ipv6 pim (vrf NAME|) rp-register-kat <1-65535>
```

---

## Configure source address

Use this attribute to configure the source address of register packets sent by this designated router (DR).

This command is supported when following feature are enabled PIM Sparse Mode (SM)

Attribute Name: source-address

Attribute Type: union

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <register-packet>
          <config>
            <source-address>PIM_IPV6_REG_SOURCE_T</source-address>
          </config>
        </register-packet>
      </instance>
    </instances>
  </ipv6>
</pim>
```

## Command Syntax

```
ipv6 pim (vrf NAME|) register-source (X:X::X:X|IFNAME)
```

---

## Configure accept register

Use this attribute to configure the ACL of register packets accepted by this designated router (DR).

This command is supported when following feature are enabled PIM Sparse Mode (SM)

Attribute Name: accept-register

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </config>
          <register-packet>
            <config>
              <accept-register>WORD</accept-register> <!-- operation="delete"-->
            </config>
          </register-packet>
        </instance>
      </instances>
    </ipv6>
  </pim>
```

## Command Syntax

```
ipv6 pim (vrf NAME|) accept-register list WORD
```

---

## Configure ignore rp set priority

Use this attribute to ignore the RP-SET priority value, and use only the hashing mechanism for RP selection. This is used to inter-operate with older Cisco IOS versions.

Attribute Name: ignore-rp-set-priority

Attribute Type: empty

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
```

```

        <vrf-name>NAME</vrf-name>
    </config>
</interop>
<config>
    </ignore-rp-set-priority><!-- operation="delete"-->
</config>
</interop>
</instance>
</instances>
</ipv6>
</pim>

```

### Command Syntax

```
ipv6 pim (vrf NAME|) ignore-rp-set-priority
```

---

## Configure cisco bsr interop enable

Use this attribute to turn on or turn the Candidate-RP debugging timerworking with Cisco BSR.

Attribute Name: cisco-bsr-interop-enable

Attribute Type: empty

### Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <interop>
          <config>
            </cisco-bsr-interop-enable><!-- operation="delete"-->
          </config>
        </interop>
      </instance>
    </instances>
  </ipv6>
</pim>

```

### Command Syntax

```
ipv6 pim (vrf NAME|) crp-cisco-prefix
```

---

## Configure access control list

Use this attribute to configure the option to calculate the register checksum over the whole packet on multicast groups specified by the access control list.

Attribute Name: access-control-list

Attribute Type: string

Attribute Range: 1-64

Attribute Name: cisco-register-checksum-enable

Attribute Type: empty

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <interop>
          <register-packet>
            <config>
              </cisco-register-checksum-enable><!-- operation="delete"-->
              <access-control-list>WORD</access-control-list> <!-- operation="delete"-->
            </config>
          </register-packet>
        </interop>
      </instance>
    </instances>
  </ipv6>
</pim>
```

### Command Syntax

```
ipv6 pim (vrf NAME|) cisco-register-checksum group-list WORD
```

---

## Configure cisco register checksum enable

Use this attribute to configure the option to calculate the register checksum over the whole packet. This is used to interoperate with older Cisco IOS versions.

Attribute Name: cisco-register-checksum-enable

Attribute Type: empty

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <interop>
```

```

    <register-packet>
    <config>
        </cisco-register-checksum-enable>
    </config>
</register-packet>
</interop>
</instance>
</instances>
</ipv6>
</pim>

```

### Command Syntax

```
ipv6 pim (vrf NAME|) cisco-register-checksum
```

---

## Configure vrf name

Use this attribute to to enable the ability of the last-hop PIM router to switch to SPT for multicast group addresses indicated by the given standard access control list.

Attribute Name: access-control-list

Attribute Type: string

Attribute Range: 1-64

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <spt-switch>
          <config>
            </enable><!-- operation="delete"-->
            <access-control-list>WORD</access-control-list> <!-- operation="delete"-->
          </config>
        </spt-switch>
      </instance>
    </instances>
  </ipv6>
</pim>

```

### Command Syntax

```
ipv6 pim (vrf NAME|) spt-threshold group-list WORD
```

---

## Configure enable

Use this attribute to enable the ability of the last-hop PIM router to switch to SPT.

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <spt-switch>
          <config>
            </enable>
          </config>
        </spt-switch>
      </instance>
    </instances>
  </ipv6>
</pim>
```

### Command Syntax

```
ipv6 pim (vrf NAME|) spt-threshold
```

---

## Configure range policy

Use this attribute to set Source Specific Multicast (SSM) and define the range of multicast IP addresses. Ranges can be either the default, which defines the SSM range as FF3x::/96, or indicated by the given standard access control list.

This command is supported when following feature are enabled PIM Source Specific Multicast (SSM)

Attribute Name: range-policy

Attribute Type: union

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <ssm>
          <config>
            <range-policy>PIM_IPV6_SSM_RANGE_POLICY_TYPE_T</range-policy>
          </config>
        </ssm>
      </instance>
    </instances>
  </ipv6>
</pim>
```

```

    </config>
  </ssm>
</instance>
</instances>
</ipv6>
</pim>

```

## Command Syntax

```
ipv6 pim (vrf NAME|) ssm (range WORD|default)
```

---

## Configure member rp address

Destination IPv6 address where register messages are copied and sent. A Member RP is an individual RP member in the anycast RP set.

This command is supported when following feature are enabled PIM Sparse Mode (SM)

Attribute Name: member-rp-address

Attribute Type: inet:ipv6-address

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <anycast-rps>
          <anycast-rp> <!-- operation="delete"-->
            <member-rp-address>X:X::X:X</member-rp-address>
            <config>
              <member-rp-address>X:X::X:X</member-rp-address>
              <anycast-rp-address>X:X::X:X</anycast-rp-address>
            </config>
            <anycast-rp-address>X:X::X:X</anycast-rp-address>
          </anycast-rp>
        </anycast-rps>
      </instance>
    </instances>
  </ipv6>
</pim>

```

## Command Syntax

```
ipv6 pim (vrf NAME|) anycast-rp X:X::X:X X:X::X:X
```

---

## Configure embed rp

Use this attribute to embed the PIM Rendezvous Point

Attribute Name: embed-rp

Attribute Type: enum (disable|enable)

Default Value: enable

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </config>
          <rendezvous-point>
            <config>
              <embed-rp>enable</embed-rp> <!-- operation="delete"-->
            </config>
          </rendezvous-point>
        </instance>
      </instances>
    </ipv6>
  </pim>
```

### Command Syntax

```
ipv6 pim (vrf NAME|) rp embedded (disable|enable)
```

---

## Configure rp address

Use this attribute to statically configure Rendezvous Point (RP) address for multicast groups.

Attribute Name: rp-address

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </config>
          <rendezvous-point>
            <static-rps>
              <static-rps-default>
                <static-rp-default> <!-- operation="delete"-->
                  <rp-address>X:X::X:X</rp-address>
                </static-rp-default>
              </static-rps>
            </rendezvous-point>
          </config>
          <rp-address>X:X::X:X</rp-address>
        </instance>
      </instances>
    </ipv6>
  </pim>
```

```

    </config>
  </static-rp-default>
</static-rps-default>
</static-rps>
</rendezvous-point>
</instance>
</instances>
</ipv6>
</pim>

```

## Command Syntax

```
ipv6 pim (vrf NAME|) rp-address X:X::X:X
```

---

## Configure override dynamically learned rp

Use this attribute to configure the flag to override dynamically learned RP mappings.

Attribute Name: override-dynamically-learned-rp

Attribute Type: empty

Attribute Name: access-control-list

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <rendezvous-point>
          <static-rps>
            <static-rps-default>
              <static-rp-default>
                <rp-address>X:X::X:X</rp-address>
              <config>
                <rp-address>X:X::X:X</rp-address>
                <access-control-list>WORD</access-control-list> <!-- operation="delete"-->
              </config>
            </override-dynamically-learned-rp><!-- operation="delete"-->
          </static-rp-default>
        </static-rps-default>
      </static-rps>
    </rendezvous-point>
  </instance>
</instances>

```

```
</ipv6>
</pim>
```

## Command Syntax

```
ipv6 pim (vrf NAME|) rp-address X:X::X:X WORD override
```

---

## Configure static-rp-default access-control-list

Use this attribute to configure the name of access control list (ACL).

Attribute Name: access-control-list

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <rendezvous-point>
          <static-rps>
            <static-rps-default>
              <static-rp-default>
                <rp-address>X:X::X:X</rp-address>
                <config>
                  <rp-address>X:X::X:X</rp-address>
                </config>
                <access-control-list>WORD</access-control-list> <!-- operation="delete"-->
              </static-rp-default>
            </static-rps-default>
          </static-rps>
        </rendezvous-point>
      </instance>
    </instances>
  </ipv6>
</pim>
```

## Command Syntax

```
ipv6 pim (vrf NAME|) rp-address X:X::X:X WORD
```

---

## Configure static-rp-default override-dynamically-learned-rp

Use this attribute do configure the flag to overrides dynamically learned RP mappings.

Attribute Name: override-dynamically-learned-rp

Attribute Type: empty

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <rendezvous-point>
          <static-rps>
            <static-rps-default>
              <static-rp-default>
                <rp-address>X:X::X:X</rp-address>
                <config>
                  <rp-address>X:X::X:X</rp-address>
                </config>
                </override-dynamically-learned-rp><!-- operation="delete"-->
              </static-rp-default>
            </static-rps-default>
          </static-rps>
        </rendezvous-point>
      </instance>
    </instances>
  </ipv6>
</pim>
```

### Command Syntax

```
ipv6 pim (vrf NAME|) rp-address X:X::X:X override
```

---

## Configure interface name

Use this attribute to configure the interface for the candidate BSR router.

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <rendezvous-point>
```

```

    <bootstrap-router>
    <bsr-candidate>
    <config>
        <interface-name>IFNAME</interface-name> <!-- operation="delete"-->
    </config>
</bsr-candidate>
</bootstrap-router>
</rendezvous-point>
</instance>
</instances>
</ipv6>
</pim>

```

## Command Syntax

```
ipv6 pim (vrf NAME|) bsr-candidate IFNAME
```

---

## Configure hash mask length

Use this attribute to configure the mask length used to calculate the group address for RP.

Attribute Name: hash-mask-length

Attribute Type: uint8

Attribute Range: 0-32

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
<ipv6>
<instances>
<instance>
    <vrf-name>NAME</vrf-name>
    <config>
        <vrf-name>NAME</vrf-name>
    </config>
    <rendezvous-point>
    <bootstrap-router>
    <bsr-candidate>
    <config>
        <interface-name>IFNAME</interface-name> <!-- operation="delete"-->
        <hash-mask-length>0</hash-mask-length> <!-- operation="delete"-->
    </config>
</bsr-candidate>
</bootstrap-router>
</rendezvous-point>
</instance>
</instances>
</ipv6>

```

```
</pim>
```

## Command Syntax

```
ipv6 pim (vrf NAME|) bsr-candidate IFNAME <0-32>
```

---

## Configure priority

Use this attribute to configure the priority value for candidate BSR router.

Attribute Name: priority

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

Attribute Name: hash-mask-length

Attribute Type: uint8

Attribute Range: 0-32

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </config>
          <rendezvous-point>
            <bootstrap-router>
              <bsr-candidate>
                <config>
                  <interface-name>IFNAME</interface-name> <!-- operation="delete"-->
                  <hash-mask-length>0</hash-mask-length> <!-- operation="delete"-->
                  <priority>0</priority> <!-- operation="delete"-->
                </config>
              </bsr-candidate>
            </bootstrap-router>
          </rendezvous-point>
        </instance>
      </instances>
    </ipv6>
  </pim>
```

## Command Syntax

```
ipv6 pim (vrf NAME|) bsr-candidate IFNAME <0-32> <0-255>
```

---

## Configure bsr-candidate interface-name

Use this attribute to configure the interface for the candidate BSR router.

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </config>
          <rendezvous-point>
            <bootstrap-router>
              <bsr-candidate>
                <config>
                  <interface-name>IFNAME</interface-name> <!-- operation="delete"-->
                </config>
              </bsr-candidate>
            </bootstrap-router>
          </rendezvous-point>
        </instance>
      </instances>
    </ipv6>
  </pim>
```

### Command Syntax

```
ipv6 pim (vrf NAME|) bsr-candidate IFNAME
```

---

## Configure rp-candidates interface-name

Use this attribute to configure the interface name for RP.

Attribute Name: interface-name

Attribute Type: string

Attribute Range: 1-33

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
```

```

    <vrf-name>NAME</vrf-name>
  </config>
  <rendezvous-point>
  <rp-candidates>
  <rp-candidate> <!-- operation="delete"-->
    <interface-name>IFNAME</interface-name>
    <config>
      <interface-name>IFNAME</interface-name>
    </config>
  </rp-candidate>
</rp-candidates>
</rendezvous-point>
</instance>
</instances>
</ipv6>
</pim>

```

## Command Syntax

```
ipv6 pim (vrf NAME|) rp-candidate IFNAME
```

---

## Configure advertisement interval

Use this attribute to configure the priority value for RP candidate.

Attribute Name: priority

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: access-control-list

Attribute Type: string

Attribute Range: 1-64

Attribute Name: advertisement-interval

Attribute Type: uint16

Attribute Range: 1-16383

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
  <instances>
  <instance>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
    <rendezvous-point>
    <rp-candidates>
    <rp-candidate>
      <interface-name>IFNAME</interface-name>

```

```

    <config>
      <interface-name>IFNAME</interface-name>
      <access-control-list>WORD</access-control-list> <!-- operation="delete"-->
>
      <advertisement-interval>1</advertisement-interval> <!--
operation="delete"-->
    </config>
      <priority>0</priority> <!-- operation="delete"-->
    </rp-candidate>
  </rp-candidates>
</rendezvous-point>
</instance>
</instances>
</ipv6>
</pim>

```

## Command Syntax

```

ipv6 pim (vrf NAME|) rp-candidate IFNAME (group-list WORD|) (interval <1-16383>|)
(priority <0-255>|)

```

## Configure options

Use this attribute to debug the PIM IPv6 feature.

Attribute Name: options

Attribute Type: bits (all|events|packet|packet in|packet out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer hello nt|timer hello th|timer joinprune jt|timer joinprune et|timer joinprune ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr bst|timer bsr crp|mib|nsm|nexthop|mtrace)

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <instances>
      <instance>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </config>
          <debug>
            <config>
              <options>all</options> <!-- operation="delete"-->
            </config>
          </debug>
        </instance>
      </instances>
    </ipv6>
  </pim>

```

## Command Syntax

```

debug ipv6 pim (vrf NAME|) (all|events|packet|packet in|packet
out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer

```

```
hello nlt|timer hello tht|timer joinprune jt|timer joinprune et|timer joinprune
ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr
bst|timer bsr crp|mib|nsm|nexthop|mtrace)
```

---

## Configure passive enable

PIM IPv6 passive mode.

Attribute Name: passive-enable

Attribute Type: empty

Attribute Name: pim-mode

Attribute Type: enum (dense-mode|sparse-mode)

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
          <pim-mode>dense-mode</pim-mode> <!-- operation="delete"-->
        </config>
        </passive-enable><!-- operation="delete"-->
      </interface>
    </interfaces>
  </ipv6>
</pim>
```

### Command Syntax

```
ipv6 pim (dense-mode|sparse-mode) passive
```

---

## Configure pim mode

PIM IPv6 mode to use when delivering multicast traffic via this interface.

Attribute Name: pim-mode

Attribute Type: enum (dense-mode|sparse-mode)

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
          <pim-mode>dense-mode</pim-mode> <!-- operation="delete"-->
        </config>
      </interface>
    </interfaces>
  </ipv6>
</pim>
```

```

</interface>
</interfaces>
</ipv6>
</pim>

```

## Command Syntax

```
ipv6 pim (dense-mode|sparse-mode)
```

---

## Configure bsr border

When set to true the device will not send bootstrap router messages over this interface. By default these are transmitted over all PIM IPv6 sparse mode (PIM-SM) enabled interfaces.

Attribute Name: bsr-border

Attribute Type: empty

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        </bsr-border><!-- operation="delete"-->
      </interface>
    </interfaces>
  </ipv6>
</pim>

```

## Command Syntax

```
ipv6 pim bsr-border
```

---

## Configure dr priority

The designated router priority of this interface. Larger always preferred.

Attribute Name: dr-priority

Attribute Type: uint32

Attribute Range: 0-4294967294

## Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>

```

```

    </config>
      <dr-priority>0</dr-priority> <!-- operation="delete"-->
</interface>
</interfaces>
</ipv6>
</pim>

```

### Command Syntax

```
ipv6 pim dr-priority <0-4294967294>
```

---

## Configure hello interval

Use this attribute to configure a hello interval value other than the default. When a hello-interval is configured and hello-holdtime is not configured, or when the hello-holdtime value configured is less than the new hello-interval value, the holdtime value is modified to (3.5 \* hello\_interval). Otherwise, the hello-holdtime value is the configured value.

Attribute Name: hello-interval

Attribute Type: uint16

Default Value: 30

Attribute Range: 1-18724

### Netconf edit-config payload

```

<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
          </config>
          <hello-interval>1</hello-interval> <!-- operation="delete"-->
        </interface>
      </interfaces>
    </ipv6>
  </pim>

```

### Command Syntax

```
ipv6 pim hello-interval <1-18724>
```

---

## Configure hello holdtime

Use this attribute to configure a hello message holdtime other than the default.

Attribute Name: hello-holdtime

Attribute Type: uint16

Default Value: 105

Attribute Range: 1-65535

---

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <hello-holdtime>1</hello-holdtime> <!-- operation="delete"-->
      </interface>
    </interfaces>
  </ipv6>
</pim>
```

## Command Syntax

```
ipv6 pim hello-holdtime <1-65535>
```

---

## Configure exclude generated id

Exclude Gen-id option from PIM IPv6 Hello packets on this interface.

Attribute Name: exclude-generated-id

Attribute Type: empty

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        </exclude-generated-id><!-- operation="delete"-->
      </interface>
    </interfaces>
  </ipv6>
</pim>
```

## Command Syntax

```
ipv6 pim exclude-genid
```

---

## Configure unicast bootstrap router

Use this attribute to enable support for sending and receiving unicast Bootstrap Messages (BSM) on an interface.

Attribute Name: unicast-bootstrap-router

Attribute Type: empty

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
<ipv6>
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </unicast-bootstrap-router><!-- operation="delete"-->
</interface>
</interfaces>
</ipv6>
</pim>
```

## Command Syntax

```
ipv6 pim unicast-bsm
```

---

## Configure neighbor access control list filter

Use this attribute to enable filtering of neighbors on the interface. When configuring a neighbor filter, PIM IPv6 either not establishes adjacency with neighbor or terminates adjacency with existing neighbors, when denied by filtering access list.

Attribute Name: neighbor-access-control-list-filter

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
<ipv6>
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <neighbor-access-control-list-filter>WORD</neighbor-access-control-list-
filter> <!-- operation="delete"-->
</interface>
</interfaces>
</ipv6>
</pim>
```

## Command Syntax

```
ipv6 pim neighbor-filter WORD
```

---

## Configure state refresh origination interval

Use this attribute to configure a PIM-DM State-Refresh origination interval other than the default value. The origination interval is the number of seconds between PIM-DM State Refresh control messages.

Attribute Name: state-refresh-origination-interval

Attribute Type: uint16

Default Value: 60

Attribute Range: 1-100

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <state-refresh-origination-interval>1</state-refresh-origination-interval>
<!-- operation="delete"-->
      </interface>
    </interfaces>
  </ipv6>
</pim>
```

### Command Syntax

```
ipv6 pim state-refresh origination-interval <1-100>
```

---

## Configure name

Use this attribute to configure an ECMP bundle.

Attribute Name: ecmp-bundle

Attribute Type: string

Attribute Range: 1-50

### Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <ecmp-bundle>WORD</ecmp-bundle> <!-- operation="delete"-->
      </interface>
    </interfaces>
```

```
</ipv6>
</pim>
```

## Command Syntax

```
ipv6 pim bind ecmp-bundle WORD
```

---

## Configure propagation delay

Propagation-delay value.

Attribute Name: propagation-delay

Attribute Type: uint16

Default Value: 1000

Attribute Range: 0-32767

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
          </config>
          <propagation-delay>0</propagation-delay> <!-- operation="delete"-->
        </interface>
      </interfaces>
    </ipv6>
  </pim>
```

## Command Syntax

```
ipv6 pim propagation-delay <0-32767>
```

---

## Configure enable bfd

Use this attribute to configure Bidirectional Forwarding Detection.

Attribute Name: enable-bfd

Attribute Type: enum (disable|enable)

## Netconf edit-config payload

```
<pim xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <ipv6>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
          </config>
        </interface>
      </interfaces>
    </ipv6>
  </pim>
```

```

        <enable-bfd>enable</enable-bfd> <!-- operation="delete"-->
</interface>
</interfaces>
</ipv6>
</pim>

```

### Command Syntax

```
ipv6 pim bfd (disable|)
```

---

## clear ipv6 pim (vrf NAME|) (sparse-mode) bsr rp-set \*

Attribute Name: vrf-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: pim-mode

Attribute Type: enum (sparse-mode)

### Netconf RPC payload

```

<ipi-pim-ipv6_pim-ipv6-clear-bsr-rendezvous-point xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
  <pim-mode>sparse-mode</pim-mode>
</ipi-pim-ipv6_pim-ipv6-clear-bsr-rendezvous-point>

```

### Command Syntax

```
clear ipv6 pim (vrf NAME|) (sparse-mode) bsr rp-set *
```

---

## clear ipv6 mroute (vrf NAME|) \* pim (dense-mode|sparse-mode)

Attribute Name: vrf-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: pim-mode

Attribute Type: enum (dense-mode|sparse-mode)

### Netconf RPC payload

```

<ipi-pim-ipv6_pim-ipv6-clear-multicast-route xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
  <pim-mode>dense-mode</pim-mode>
</ipi-pim-ipv6_pim-ipv6-clear-multicast-route>

```

### Command Syntax

```
clear ipv6 mroute (vrf NAME|) * pim (dense-mode|sparse-mode)
```

---

## clear ipv6 mroute (vrf NAME|) X:X::X:X pim sparse-mode

Attribute Name: vrf-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: group-address

Attribute Type: inet:ipv6-address

### Netconf RPC payload

```
<ipi-pim-ipv6_pim-ipv6-clear-multicast-route-source-group xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
  <group-address>X:X::X:X</group-address>
</ipi-pim-ipv6_pim-ipv6-clear-multicast-route-source-group>
```

### Command Syntax

```
clear ipv6 mroute (vrf NAME|) X:X::X:X pim sparse-mode
```

---

## clear ipv6 mroute (vrf NAME|) X:X::X:X X:X::X:X pim (dense-mode|sparse-mode)

Attribute Name: vrf-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: group-address

Attribute Type: inet:ipv6-address

Attribute Name: source-address

Attribute Type: inet:ipv6-address

Attribute Name: pim-mode

Attribute Type: enum (dense-mode|sparse-mode)

### Netconf RPC payload

```
<ipi-pim-ipv6_pim-ipv6-clear-multicast-route-source-group-mode xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
  <group-address>X:X::X:X</group-address>
  <source-address>X:X::X:X</source-address>
  <pim-mode>dense-mode</pim-mode>
</ipi-pim-ipv6_pim-ipv6-clear-multicast-route-source-group-mode>
```

### Command Syntax

```
clear ipv6 mroute (vrf NAME|) X:X::X:X X:X::X:X pim (dense-mode|sparse-mode)
```

---

## debug pim bfd

### Netconf RPC payload

```
<ipi-pim-debug_pim-terminal-debug-bfd-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim"/>
```

### Command Syntax

```
debug pim bfd
```

---

## no debug pim bfd

### Netconf RPC payload

```
<ipi-pim-debug_pim-terminal-debug-bfd-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim"/>
```

### Command Syntax

```
no debug pim bfd
```

---

## debug ipv6 pim (vrf NAME|) (all|events|packet|packet in|packet out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer hello nlt|timer hello tht|timer joinprune jt|timer joinprune et|timer joinprune ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr bst|timer bsr crp|mib|nsm|nexthop|mtrace)

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: terminal-debug-options

Attribute Type: bits (all|events|packet|packet in|packet out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer hello nlt|timer hello tht|timer joinprune jt|timer joinprune et|timer joinprune ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr bst|timer bsr crp|mib|nsm|nexthop|mtrace)

### Netconf RPC payload

```
<ipi-pim-ipv6-debug_pim-ipv6-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
  <terminal-debug-options>all</terminal-debug-options>
</ipi-pim-ipv6-debug_pim-ipv6-terminal-debug-on>
```

### Command Syntax

```
debug ipv6 pim (vrf NAME|) (all|events|packet|packet in|packet out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer hello nlt|timer hello tht|timer joinprune jt|timer joinprune et|timer joinprune ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr bst|timer bsr crp|mib|nsm|nexthop|mtrace)
```

---

```
no debug ipv6 pim (vrf NAME|) (all|events|packet|packet in|packet
out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer
hello nlt|timer hello tht|timer joinprune jt|timer joinprune et|timer joinprune
ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr
bst|timer bsr crp|mib|nsm|nexthop|mtrace)
```

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: terminal-debug-options

Attribute Type: bits (all|events|packet|packet in|packet out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer hello nlt|timer hello tht|timer joinprune jt|timer joinprune et|timer joinprune ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr bst|timer bsr crp|mib|nsm|nexthop|mtrace)

### Netconf RPC payload

```
<ipi-pim-ipv6-debug_pim-ipv6-terminal-debug-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
  <terminal-debug-options>all</terminal-debug-options>
</ipi-pim-ipv6-debug_pim-ipv6-terminal-debug-off>
```

### Command Syntax

```
no debug ipv6 pim (vrf NAME|) (all|events|packet|packet in|packet
out|state|mfc|timer|timer hello|timer bsr|timer joinprune|timer hello ht|timer
hello nlt|timer hello tht|timer joinprune jt|timer joinprune et|timer joinprune
ppt|timer joinprune kat|timer joinprune ot|timer assert|timer register|timer bsr
bst|timer bsr crp|mib|nsm|nexthop|mtrace)
```

---

## debug ipv6 pim (vrf NAME|)

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

### Netconf RPC payload

```
<ipi-pim-ipv6-debug_pim-ipv6-terminal-debug-all-on xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
</ipi-pim-ipv6-debug_pim-ipv6-terminal-debug-all-on>
```

### Command Syntax

```
debug ipv6 pim (vrf NAME|)
```

---

## no debug ipv6 pim (vrf NAME|)

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

### Netconf RPC payload

```
<ipi-pim-ipv6-debug_pim-ipv6-terminal-debug-all-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-pim">
  <vrf-name>NAME</vrf-name>
</ipi-pim-ipv6-debug_pim-ipv6-terminal-debug-all-off>
```

### Command Syntax

```
no debug ipv6 pim (vrf NAME|)
```

---

## IPI-VXLAN

---

### Configure mac address

Use this attribute to set the mac address with arp-nd refresh-timer

Attribute Name: mac-address

Attribute Type: string

Attribute Name: arp-nd-refresh-timer

Attribute Type: uint32

Attribute Range: 3-190

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <global>
  <config>
    <arp-nd-refresh-timer>3</arp-nd-refresh-timer> <!-- operation="delete"-->
    <mac-address>XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</mac-address>
<!-- operation="delete"-->
  </config>
</global>
</vxlan>
```

### Command Syntax

```
nvo vxlan arp-nd refresh-timer <3-190> mac (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX)
```

---

### Configure enable vxlan

Use this attribute to enable VxLAN module. Without this attribute vxlan functionality can not be achieved

Attribute Name: enable-vxlan

Attribute Type: empty

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
```

```
<global>
<config>
  </enable-vxlan>
</config>
</global>
</vxlan>
```

### Command Syntax

```
nvo vxlan enable
```

---

## Configure vtep ipv4

Use this attribute to set source vtep global ip address. This will be treated at vxlan tunnel source address

Attribute Name: vtep-ipv4

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<global>
<config>
  <vtep-ipv4>A.B.C.D</vtep-ipv4> <!-- operation="delete"-->
</config>
</global>
</vxlan>
```

### Command Syntax

```
nvo vxlan vtep-ip-global A.B.C.D
```

---

## Configure mac ageing timer

Use this attribute to set the time till a learned mac address will persist after last update

Attribute Name: mac-ageing-timer

Attribute Type: uint32

Default Value: 300

Attribute Range: 10-572

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<global>
<config>
  <mac-ageing-timer>10</mac-ageing-timer> <!-- operation="delete"-->
</config>
</global>
</vxlan>
```

### Command Syntax

```
nvo vxlan mac-ageing-time <10-572>
```

---

## Configure arp nd refresh timer

Use this attribute to configure aging out the arp-cache and nd-cache entries for given time multiplied by 3 in secs.

Attribute Name: arp-nd-refresh-timer

Attribute Type: uint32

Attribute Range: 3-190

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <global>
    <config>
      <arp-nd-refresh-timer>3</arp-nd-refresh-timer> <!-- operation="delete"-->
    </config>
  </global>
</vxlan>
```

### Command Syntax

```
nvo vxlan arp-nd refresh-timer <3-190>
```

---

## Configure maximum cache disable count

Use this command to configure the maximum number of ARP and ND cache disables on access ports configured with the port+VLAN options. This command does not limit the ARP and ND cache disables on access ports created with only the port option.

Attribute Name: maximum-cache-disable-count

Attribute Type: uint16

Attribute Range: 1-2500

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <global>
    <config>
      <maximum-cache-disable-count>1</maximum-cache-disable-count> <!--
operation="delete"-->
    </config>
  </global>
</vxlan>
```

### Command Syntax

```
nvo vxlan max-cache-disable <1-2500>
```

---

## Configure disable arp storm control for cpu

Use this attribute to set the vxlan disable arp storm control for cpu

Attribute Name: disable-arp-storm-control-for-cpu

Attribute Type: empty

## Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <global>
    <config>
      </disable-arp-storm-control-for-cpu><!-- operation="delete"-->
    </config>
  </global>
</vxlan>
```

## Command Syntax

```
nvo vxlan disable-arp-storm-control-for-cpu
```

---

## Configure traffic direction

Use this attribute to set global direction(ingress/egress) for VxLAN. Ingress means traffic coming to network side and egress means traffic going out from network side

This command is supported when following feature are enabled QOS feature

Attribute Name: traffic-direction

Attribute Type: enum (ingress|egress)

Attribute Name: profile-name

Attribute Type: string

## Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <qos-tunnel-mappings>
    <qos-tunnel-mapping> <!-- operation="delete"-->
      <traffic-direction>ingress</traffic-direction>
    </qos-tunnel-mapping>
  </qos-tunnel-mappings>
  <config>
    <traffic-direction>ingress</traffic-direction>
    <qos-map-mode>cos-dscp</qos-map-mode>
    <profile-name>NAME</profile-name>
  </config>
  <qos-map-mode>cos-dscp</qos-map-mode>
</vxlan>
```

## Command Syntax

```
nvo vxlan tunnel qos-map-mode (cos-dscp) (ingress|egress) NAME
```

---

## Configure tenant type

Use this attribute to create tenant with multicast tunnel

Attribute Name: tenant-type

Attribute Type: enum (default|multicast|ingress-replication|ingress-replication inner-vid-disabled)

Attribute Name: etree-leaf

Attribute Type: uint8

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <vxlan-tenants>
  <vxlan-tenant>
    <vxlan-identifier>1</vxlan-identifier>
    <config>
      <vxlan-identifier>1</vxlan-identifier>
      </etree-leaf>
    </config>
    <tenant-type>default</tenant-type>
  </vxlan-tenant>
</vxlan-tenants>
</vxlan>
```

### Command Syntax

```
nvo vxlan id <1-16777215> ((default|multicast|ingress-replication|ingress-
  replication inner-vid-disabled)|) (etree-leaf|)
```

---

## Configure bridge vlan id

Use this attribute to create tenant with ingress-replication bridge-vlan tunnel

Attribute Name: bridge-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: tenant-type-bridge

Attribute Type: enum (default|multicast|ingress-replication)

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <vxlan-tenants>
  <vxlan-tenant>
    <vxlan-identifier>1</vxlan-identifier>
    <config>
      <vxlan-identifier>1</vxlan-identifier>
      <tenant-type-bridge>default</tenant-type-bridge>
    </config>
    <bridge-vlan-id>1</bridge-vlan-id>
  </vxlan-tenant>
</vxlan-tenants>
</vxlan>
```

### Command Syntax

```
nvo vxlan id <1-16777215> (default|multicast|ingress-replication) (bridge-vlan <1-
  4094>|)
```

---

## Configure vrf name

Use this attribute to map VRF to carry EVPN routes. This defines BGP as the mechanism for host reachability advertisement.

Attribute Name: vrf-name

Attribute Type: string

Attribute Range: 1-32

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <vxlan-tenants>
    <vxlan-tenant>
      <vxlan-identifier>1</vxlan-identifier>
      <config>
        <vxlan-identifier>1</vxlan-identifier>
      </config>
      <vrf-name>NAME</vrf-name> <!-- operation="delete"-->
    </vxlan-tenant>
  </vxlan-tenants>
</vxlan>
```

### Command Syntax

```
vxlan host-reachability-protocol evpn-bgp NAME
```

---

## Configure map network

Use this attribute to map a tunnel to the tenant

Attribute Name: map-network

Attribute Type: string

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <vxlan-tenants>
    <vxlan-tenant>
      <vxlan-identifier>1</vxlan-identifier>
      <config>
        <vxlan-identifier>1</vxlan-identifier>
      </config>
      <map-network>NAME</map-network> <!-- operation="delete"-->
    </vxlan-tenant>
  </vxlan-tenants>
</vxlan>
```

### Command Syntax

```
vxlan map-network tunnel NAME
```

---

## Configure mac hold timer

Use this attribute to set the time a host mac entry will persist after unconfiguring. Hold time range -1 to 300 in seconds. -1(never expire)

Attribute Name: mac-hold-timer

Attribute Type: int32

Default Value: 0

Attribute Range: -1-300

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <vxlan-tenants>
    <vxlan-tenant>
      <vxlan-identifier>1</vxlan-identifier>
      <config>
        <vxlan-identifier>1</vxlan-identifier>
      </config>
      <mac-hold-timer>-1</mac-hold-timer> <!-- operation="delete"-->
    </vxlan-tenant>
  </vxlan-tenants>
</vxlan>
```

### Command Syntax

```
mac-holdtime <-1-300>
```

---

## Configure tenant description

Use this attribute to set VxLAN identifier name

Attribute Name: tenant-description

Attribute Type: string

Attribute Range: 1-10

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <vxlan-tenants>
    <vxlan-tenant>
      <vxlan-identifier>1</vxlan-identifier>
      <config>
        <vxlan-identifier>1</vxlan-identifier>
      </config>
      <tenant-description>WORD</tenant-description> <!-- operation="delete"-->
    </vxlan-tenant>
  </vxlan-tenants>
</vxlan>
```

### Command Syntax

```
vni-name WORD
```

---

## Configure irb name

Use this attribute to to configure default gateway behavior on a VTEP for particular VNID.

Attribute Name: irb-name

Attribute Type: string

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <vxlan-tenants>
    <vxlan-tenant>
      <vxlan-identifier>1</vxlan-identifier>
      <config>
        <vxlan-identifier>1</vxlan-identifier>
      </config>
      <irb-name>NAME</irb-name> <!-- operation="delete"-->
    </vxlan-tenant>
  </vxlan-tenants>
</vxlan>
```

### Command Syntax

```
evpn NAME
```

---

## Configure irb advertise host route

Use this attribute to set advertise host to route

Attribute Name: irb-advertise-host-route

Attribute Type: empty

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <vxlan-tenants>
    <vxlan-tenant>
      <vxlan-identifier>1</vxlan-identifier>
      <config>
        <vxlan-identifier>1</vxlan-identifier>
      </config>
      <irb>
        <config>
          </irb-advertise-host-route><!-- operation="delete"-->
        </config>
      </irb>
    </vxlan-tenant>
  </vxlan-tenants>
</vxlan>
```

### Command Syntax

```
evpn irb-advertise-host-route
```

---

## Configure vxlan identifier

Use this attribute to know MAC address of the host.create a static route to reach a destination MAC in the VXLAN forwarding table. This command helps to supports different tenants so that they can have the same MAC/IP, but different VNIDs.This command is required for unicast tunnels to map the remote VTEP

Attribute Name: mac-address

Attribute Type: string

Attribute Name: remote-vtep-ipv4

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <vxlan-tenants>
  <vxlan-tenant>
    <vxlan-identifier>1</vxlan-identifier>
    <config>
      <vxlan-identifier>1</vxlan-identifier>
    </config>
  <static-tenants>
  <static-tenant> <!-- operation="delete"-->
    <mac-address>XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</mac-address>
    <config>
      <mac-address>CML_MAC_ADDR_T</mac-address>
      <remote-vtep-ipv4>A.B.C.D</remote-vtep-ipv4>
    </config>
  </static-tenant>
</static-tenants>
</vxlan-tenant>
</vxlan-tenants>
</vxlan>
```

### Command Syntax

```
vxlan static-entry host-mac (XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX)
remote-vtep-ip A.B.C.D
```

---

## Configure untagged interface name

Use this attribute to map a physical interface to identify the tenant traffic and to enter NVO access interface mode

Attribute Name: untagged-interface-name

Attribute Type: string

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <untagged-access-interfaces>
  <untagged-access-interface> <!-- operation="delete"-->
    <untagged-interface-name>WORD</untagged-interface-name>
  </untagged-access-interface>
</untagged-access-interfaces>
</vxlan>
```

```

    <untagged-interface-name>WORD</untagged-interface-name>
  </config>
</untagged-access-interface>
</untagged-access-interfaces>
</vxlan>

```

### Command Syntax

```
nvo vxlan access-if port IFNAME
```

---

## Configure default access interface

Use this attribute to create default access interface

Attribute Name: default-access-interface

Attribute Type: empty

### Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <untagged-access-interfaces>
    <untagged-access-interface>
      <untagged-interface-name>WORD</untagged-interface-name>
      <config>
        <untagged-interface-name>WORD</untagged-interface-name>
      </config>
    </default-access-interface>
  </untagged-access-interface>
</untagged-access-interfaces>
</vxlan>

```

### Command Syntax

```
nvo vxlan access-if port IFNAME default
```

---

## Configure admin shutdown

Use this attribute to shutdown vxlan access interface

This command is supported when following feature are disabled DNX feature

Attribute Name: admin-shutdown

Attribute Type: empty

### Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <untagged-access-interfaces>
    <untagged-access-interface>
      <untagged-interface-name>WORD</untagged-interface-name>
      <config>
        <untagged-interface-name>WORD</untagged-interface-name>
      </config>
    </admin-shutdown><!-- operation="delete"-->
  </untagged-access-interfaces>
</vxlan>

```

```

</untagged-access-interface>
</untagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
shutdown
```

---

## Configure description

Use this attribute to set description of access interface

This command is supported when following feature are disabled DNX feature

Attribute Name: description

Attribute Type: string

Attribute Range: 1-32

## Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<untagged-access-interfaces>
<untagged-access-interface>
  <untagged-interface-name>WORD</untagged-interface-name>
  <config>
    <untagged-interface-name>WORD</untagged-interface-name>
  </config>
  <description>LINE</description> <!-- operation="delete"-->
</untagged-access-interface>
</untagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
description LINE
```

---

## Configure dynamic learning disable

Use this attribute to disable dynamic learning of MACs at the access port. This command also disables dynamic learning of MAC/IP from ARP/ND messages received on this access port.

This command is supported when following feature are disabled DNX feature

Attribute Name: dynamic-learning-disable

Attribute Type: empty

## Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<untagged-access-interfaces>
<untagged-access-interface>
  <untagged-interface-name>WORD</untagged-interface-name>
  <config>
    <untagged-interface-name>WORD</untagged-interface-name>
  </config>
</untagged-access-interfaces>
</vxlan>

```

```

    </dynamic-learning-disable><!-- operation="delete"-->
</untagged-access-interface>
</untagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
dynamic-learning disable
```

---

## Configure access mac hold time

Use this attribute to set the time a host mac entry will persist after unconfiguring. The feature holds the MAC in hardware until BGP has withdrawn from the neighbors. This helps to reduce flooding to other access ports. This setting applies when the access port is shut down, the physical port on which the access port is down, or the access port is removed from the VNID using the no form of the map vnid command. When the MAC hold time is configured as -1, then the MAC is not removed from the hardware and is also not withdrawn from EVPN BGP

This command is supported when following feature are disabled DNX feature

Attribute Name: access-mac-hold-time

Attribute Type: int32

Attribute Range: -1-300

## Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<untagged-access-interfaces>
<untagged-access-interface>
    <untagged-interface-name>WORD</untagged-interface-name>
    <config>
        <untagged-interface-name>WORD</untagged-interface-name>
    </config>
    <access-mac-hold-time>-1</access-mac-hold-time> <!-- operation="delete"-->
</untagged-access-interface>
</untagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
mac-holdtime <-1-300>
```

---

## Configure arp nd flood suppress

Use this attribute to restrict the flood of ARP/ND packets towards remote VTEPs or other access ports. This command applies only when the ARP cache and ND cache are enabled. When the ARP cache is disabled, ARP flooding is not suppressed even if this command is given. When the ND cache is disabled, ND flooding is not disabled, even if this command is given

This command is supported when following feature are disabled DNX feature

Attribute Name: arp-nd-flood-suppress

Attribute Type: empty

---

## Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<untagged-access-interfaces>
<untagged-access-interface>
  <untagged-interface-name>WORD</untagged-interface-name>
  <config>
    <untagged-interface-name>WORD</untagged-interface-name>
  </config>
  </arp-nd-flood-suppress><!-- operation="delete"-->
</untagged-access-interface>
</untagged-access-interfaces>
</vxlan>
```

## Command Syntax

```
arp-nd flood-suppress
```

---

## Configure garp gna enable

Use this attribute to allow garp-gna packets advertisement

This command is supported when following feature are disabled DNX feature

Attribute Name: garp-gna-enable

Attribute Type: empty

## Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<untagged-access-interfaces>
<untagged-access-interface>
  <untagged-interface-name>WORD</untagged-interface-name>
  <config>
    <untagged-interface-name>WORD</untagged-interface-name>
  </config>
  </garp-gna-enable><!-- operation="delete"-->
</untagged-access-interface>
</untagged-access-interfaces>
</vxlan>
```

## Command Syntax

```
garp-gna enable
```

---

## Configure untagged-access-interface mac-address

Use this attribute to set the static mac address of host

This command is supported when following feature are disabled DNX feature

Attribute Name: mac-address

Attribute Type: string

## Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <untagged-access-interfaces>
    <untagged-access-interface>
      <untagged-interface-name>WORD</untagged-interface-name>
      <config>
        <untagged-interface-name>WORD</untagged-interface-name>
      </config>
      <mac-address>XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</mac-address>
<!-- operation="delete"-->
    </untagged-access-interface>
  </untagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
mac (XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX)
```

## Configure arp cache disable

Use this attribute to disable the ARP cache for MAC/IP. When the ARP cache is disabled on a VxLAN access port, ZebOS-XP does not reply to any ARP arriving on this port from the cache. ZebOS-XP withdraws all MAC/IPs configured/learned on this access port and removes the MAC/IP entry for this access port from the local ARP cache. ZebOS-XP also makes sure that on withdrawing the MAC/IP route, the MAC does not become unknown. If all routes for this MAC are being withdrawn because of this command, then ZebOS-XP advertises a MAC-only route. This is done so that the MAC does not become unknown and only the cache functionality becomes disabled. See also `nvo vxlan max-cache-disable`. Use the `no` form of this command to enable ARP cache for MAC/IP. Note: On enabling the cache, an IP will be in conflict, then the cache enable will fail. The conflict has to be manually removed and then the cache enabled.

This command is supported when following feature are disabled DNX feature

Attribute Name: arp-cache-disable

Attribute Type: empty

## Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <untagged-access-interfaces>
    <untagged-access-interface>
      <untagged-interface-name>WORD</untagged-interface-name>
      <config>
        <untagged-interface-name>WORD</untagged-interface-name>
      </config>
      <cache>
      <config>
        </arp-cache-disable><!-- operation="delete"-->
      </config>
      </cache>
    </untagged-access-interface>
  </untagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
arp-cache disable
```

---

## Configure nd cache disable

Use this attribute to disable ND cache for MAC/IPv6. When the ARP cache is disabled on a VxLAN access port, ZebOS-XP does not reply to any ARP arriving on this port from the cache. ZebOS-XP withdraws all MAC/IPs configured/learned on this access port and removes the MAC/IP entry for this access port from the local ARP cache. ZebOS-XP also makes sure that on withdrawing the MAC/IP route, the MAC does not become unknown. If all routes for this MAC are being withdrawn because of this command, then ZebOS-XP advertises a MAC-only route. This is done so that the MAC does not become unknown and only the cache functionality becomes disabled. Use the no form of this command to enable ND cache for MAC/IPv6. Note: On enabling the cache, an IP will be in conflict, then the cache enable will fail. The conflict has to be manually removed and then the cache enabled.

This command is supported when following feature are disabled DNX feature

Attribute Name: nd-cache-disable

Attribute Type: empty

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <untagged-access-interfaces>
    <untagged-access-interface>
      <untagged-interface-name>WORD</untagged-interface-name>
      <config>
        <untagged-interface-name>WORD</untagged-interface-name>
      </config>
    </untagged-access-interface>
  </untagged-access-interfaces>
  <cache>
    <config>
      </nd-cache-disable><!-- operation="delete"-->
    </config>
  </cache>
</vxlan>
```

## Command Syntax

```
nd-cache disable
```

---

## Configure map vxlan-identifier

Use this attribute to map a tenant to an access-port

This command is supported when following feature are disabled DNX feature

Attribute Name: vxlan-identifier

Attribute Type: uint32

Attribute Range: 1-16777215

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
```

```

<untagged-access-interfaces>
<untagged-access-interface>
  <untagged-interface-name>WORD</untagged-interface-name>
  <config>
    <untagged-interface-name>WORD</untagged-interface-name>
  </config>
</map>
<config>
  <vxlan-identifier>1</vxlan-identifier> <!-- operation="delete"-->
</config>
</map>
</untagged-access-interface>
</untagged-access-interfaces>
</vxlan>

```

### Command Syntax

```
map vnid <1-16777215>
```

---

## Configure map tenant-description

Use this attribute to map VXLAN Identifier Name

This command is supported when following feature are disabled DNX feature

Attribute Name: tenant-description

Attribute Type: string

Attribute Range: 1-10

### Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<untagged-access-interfaces>
<untagged-access-interface>
  <untagged-interface-name>WORD</untagged-interface-name>
  <config>
    <untagged-interface-name>WORD</untagged-interface-name>
  </config>
</map>
<config>
  <tenant-description>WORD</tenant-description> <!-- operation="delete"-->
</config>
</map>
</untagged-access-interface>
</untagged-access-interfaces>
</vxlan>

```

### Command Syntax

```
map vni-name WORD
```

---

## Configure ipv4 address

Use this attribute to know MAC address of the host

Attribute Name: mac-address

Attribute Type: string

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <untagged-access-interfaces>
    <untagged-access-interface>
      <untagged-interface-name>WORD</untagged-interface-name>
      <config>
        <untagged-interface-name>WORD</untagged-interface-name>
      </config>
    </untagged-access-interface>
  </untagged-access-interfaces>
  <host-macs-ipv4>
    <host-mac-ipv4> <!-- operation="delete"-->
      <ipv4-address>A.B.C.D</ipv4-address>
      <config>
        <ipv4-address>A.B.C.D</ipv4-address>
        <mac-address>CML_MAC_ADDR_T</mac-address>
      </config>
      <mac-address>CML_MAC_ADDR_T</mac-address>
    </host-mac-ipv4>
  </host-macs-ipv4>
</vxlan>
```

### Command Syntax

```
mac (XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) ip IP-ADDRESS
```

---

## Configure ipv6 address

Use this attribute to know MAC address of the host

Attribute Name: mac-address

Attribute Type: string

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <untagged-access-interfaces>
    <untagged-access-interface>
      <untagged-interface-name>WORD</untagged-interface-name>
      <config>
        <untagged-interface-name>WORD</untagged-interface-name>
      </config>
    </untagged-access-interface>
  </untagged-access-interfaces>
  <host-macs-ipv6>
    <host-mac-ipv6> <!-- operation="delete"-->
      <ipv6-address>X:X::X:X</ipv6-address>
    </host-mac-ipv6>
  </host-macs-ipv6>
</vxlan>
```

```

<config>
  <ipv6-address>IP-ADDRESS</ipv6-address>
  <mac-address>XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</mac-address>
</config>
  <mac-address>CML_MAC_ADDR_T</mac-address>
</host-mac-ipv6>
</host-macs-ipv6>
</untagged-access-interface>
</untagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
mac (XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) ipv6 IP-ADDRESS
```

---

## Configure profile map type

Use this attribute to map the profile type for which qos profile is already created globally to access port

This command is supported when following feature are enabled QOS feature and following feature are disabled DNX feature

Attribute Name: profile-map-type

Attribute Type: enum (cos-to-queue|queue-color-to-cos)

Attribute Name: profile-name

Attribute Type: string

## Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <untagged-access-interfaces>
  <untagged-access-interface>
    <untagged-interface-name>WORD</untagged-interface-name>
  <config>
    <untagged-interface-name>WORD</untagged-interface-name>
  </config>
  <access-interface-qos-type-mappings>
  <access-interface-qos-type-mapping> <!-- operation="delete"-->
    <profile-map-type>cos-to-queue</profile-map-type>
  <config>
    <profile-map-type>cos-to-queue</profile-map-type>
    <profile-name>NAME</profile-name>
  </config>
  </access-interface-qos-type-mapping>
  </access-interface-qos-type-mappings>
  </untagged-access-interface>
  </untagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
map qos-profile (cos-to-queue|queue-color-to-cos) NAME
```

---

## Configure vlan identifier

Use this attribute to map a VLAN on physical interface to identify the tenant traffic and to enter NVO access interface mode

This command is supported when following feature are disabled DNX feature

Attribute Name: vlan-identifier

Attribute Type: string

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <tagged-access-interfaces>
    <tagged-access-interface> <!-- operation="delete"-->
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <config>
        <vlan-identifier>VLAN_RANGE</vlan-identifier>
        <interface-name>WORD</interface-name>
      </config>
    </tagged-access-interface>
  </tagged-access-interfaces>
</vxlan>
```

### Command Syntax

```
nvo vxlan access-if port-vlan IFNAME VLAN_RANGE
```

---

## Configure tag protocol identifier

Use this attribute to set the Tpid for the outer vlan. Ox88A8: IEEE 802.1ad Provider Bridging and Ox9100: IEEE 802.1Q VLAN-tagged frame with double tagging

This command is supported when following feature are disabled DNX feature

Attribute Name: tag-protocol-identifier

Attribute Type: string

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <tagged-access-interfaces>
    <tagged-access-interface>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <config>
        <vlan-identifier>VLAN_RANGE</vlan-identifier>
        <interface-name>WORD</interface-name>
      </config>
    </tagged-access-interface>
  </tagged-access-interfaces>
  <tag-protocol-identifier>TPID</tag-protocol-identifier> <!-- operation="delete"-->
->
</vxlan>
```

## Command Syntax

```
encapsulation TPID
```

---

## Configure interface name

Use this attribute to shutdown vxlan access interface

This command is supported when following feature are disabled DNX feature

Attribute Name: admin-shutdown

Attribute Type: empty

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <tagged-access-interfaces>
    <tagged-access-interface>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <config>
        <vlan-identifier>VLAN_RANGE</vlan-identifier>
        <interface-name>WORD</interface-name>
      </config>
      <interface-name>WORD</interface-name>
      </admin-shutdown><!-- operation="delete"-->
    </tagged-access-interface>
  </tagged-access-interfaces>
</vxlan>
```

## Command Syntax

```
shutdown
```

---

## Configure tagged-access-interface description

Use this attribute to set description of access interface

This command is supported when following feature are disabled DNX feature

Attribute Name: description

Attribute Type: string

Attribute Range: 1-32

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <tagged-access-interfaces>
    <tagged-access-interface>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <config>
        <vlan-identifier>VLAN_RANGE</vlan-identifier>
        <interface-name>WORD</interface-name>
      </config>
      <interface-name>WORD</interface-name>
    </tagged-access-interface>
  </tagged-access-interfaces>
</vxlan>
```

```

    <description>LINE</description> <!-- operation="delete"-->
  </tagged-access-interface>
</tagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
description LINE
```

---

## Configure tagged-access-interface dynamic-learning-disable

Use this attribute to disable dynamic learning of MACs at the access port. This command also disables dynamic learning of MAC/IP from ARP/ND messages received on this access port.

This command is supported when following feature are disabled DNX feature

Attribute Name: dynamic-learning-disable

Attribute Type: empty

## Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <tagged-access-interfaces>
    <tagged-access-interface>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <config>
        <vlan-identifier>VLAN_RANGE</vlan-identifier>
        <interface-name>WORD</interface-name>
      </config>
      <interface-name>WORD</interface-name>
      </dynamic-learning-disable><!-- operation="delete"-->
    </tagged-access-interface>
  </tagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
dynamic-learning disable
```

---

## Configure tagged-access-interface access-mac-hold-time

Use this attribute to set the time a host mac entry will persist after unconfiguring. The feature holds the MAC in hardware until BGP has withdrawn from the neighbors. This helps to reduce flooding to other access ports. This setting applies when the access port is shut down, the physical port on which the access port is down, or the access port is removed from the VNID using the no form of the map vnid command. When the MAC hold time is configured as -1, then the MAC is not removed from the hardware and is also not withdrawn from EVPN BGP

This command is supported when following feature are disabled DNX feature

Attribute Name: access-mac-hold-time

Attribute Type: int32

Attribute Range: -1-300

**Netconf edit-config payload**

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<tagged-access-interfaces>
<tagged-access-interface>
  <vlan-identifier>VLAN_RANGE</vlan-identifier>
  <config>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
  </config>
  <interface-name>WORD</interface-name>
  <access-mac-hold-time>-1</access-mac-hold-time> <!-- operation="delete"-->
</tagged-access-interface>
</tagged-access-interfaces>
</vxlan>

```

**Command Syntax**

```
mac-holdtime <-1-300>
```

**Configure tagged-access-interface arp-nd-flood-suppress**

Use this attribute to restrict the flood of ARP/ND packets towards remote VTEPs or other access ports. This command applies only when the ARP cache and ND cache are enabled. When the ARP cache is disabled, ARP flooding is not suppressed even if this command is given. When the ND cache is disabled, ND flooding is not disabled, even if this command is given

This command is supported when following feature are disabled DNX feature

Attribute Name: arp-nd-flood-suppress

Attribute Type: empty

**Netconf edit-config payload**

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<tagged-access-interfaces>
<tagged-access-interface>
  <vlan-identifier>VLAN_RANGE</vlan-identifier>
  <config>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
  </config>
  <interface-name>WORD</interface-name>
  </arp-nd-flood-suppress><!-- operation="delete"-->
</tagged-access-interface>
</tagged-access-interfaces>
</vxlan>

```

**Command Syntax**

```
arp-nd flood-suppress
```

---

## Configure tagged-access-interface garp-gna-enable

Use this attribute to allow garp-gna packets advertisement

This command is supported when following feature are disabled DNX feature

Attribute Name: garp-gna-enable

Attribute Type: empty

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <tagged-access-interfaces>
    <tagged-access-interface>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <config>
        <vlan-identifier>VLAN_RANGE</vlan-identifier>
        <interface-name>WORD</interface-name>
      </config>
      <interface-name>WORD</interface-name>
      </garp-gna-enable><!-- operation="delete"-->
    </tagged-access-interface>
  </tagged-access-interfaces>
</vxlan>
```

### Command Syntax

```
garp-gna enable
```

---

## Configure tagged-access-interface mac-address

Use this attribute to set the static mac address of host

This command is supported when following feature are disabled DNX feature

Attribute Name: mac-address

Attribute Type: string

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <tagged-access-interfaces>
    <tagged-access-interface>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <config>
        <vlan-identifier>VLAN_RANGE</vlan-identifier>
        <interface-name>WORD</interface-name>
      </config>
      <interface-name>WORD</interface-name>
      <mac-address>XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</mac-address>
      <!-- operation="delete"-->
    </tagged-access-interface>
  </tagged-access-interfaces>
</vxlan>
```

## Command Syntax

```
mac (XX-XX-XX-XX-XX-XX | XX:XX:XX:XX:XX:XX | XXXX.XXXX.XXXX)
```

---

## Configure cache arp-cache-disable

Use this attribute to disable the ARP cache for MAC/IP. When the ARP cache is disabled on a VxLAN access port, ZebOS-XP does not reply to any ARP arriving on this port from the cache. ZebOS-XP withdraws all MAC/IPs configured/learned on this access port and removes the MAC/IP entry for this access port from the local ARP cache. ZebOS-XP also makes sure that on withdrawing the MAC/IP route, the MAC does not become unknown. If all routes for this MAC are being withdrawn because of this command, then ZebOS-XP advertises a MAC-only route. This is done so that the MAC does not become unknown and only the cache functionality becomes disabled. See also `nvo vxlan max-cache-disable`. Use the `no` form of this command to enable ARP cache for MAC/IP. Note: On enabling the cache, an IP will be in conflict, then the cache enable will fail. The conflict has to be manually removed and then the cache enabled.

This command is supported when following feature are disabled DNX feature

Attribute Name: `arp-cache-disable`

Attribute Type: empty

## Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <tagged-access-interfaces>
    <tagged-access-interface>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <config>
        <vlan-identifier>VLAN_RANGE</vlan-identifier>
        <interface-name>WORD</interface-name>
      </config>
      <interface-name>WORD</interface-name>
    </tagged-access-interface>
  </tagged-access-interfaces>
  <cache>
    <config>
      </arp-cache-disable><!-- operation="delete"-->
    </config>
  </cache>
</vxlan>
```

## Command Syntax

```
arp-cache disable
```

---

## Configure cache nd-cache-disable

Use this attribute to disable ND cache for MAC/IPv6. When the ARP cache is disabled on a VxLAN access port, ZebOS-XP does not reply to any ARP arriving on this port from the cache. ZebOS-XP withdraws all MAC/IPs configured/learned on this access port and removes the MAC/IP entry for this access port from the local ARP cache. ZebOS-XP also makes sure that on withdrawing the MAC/IP route, the MAC does not become unknown. If all routes for this MAC are being withdrawn because of this command, then ZebOS-XP advertises a MAC-only route. This is done so that the MAC does not become unknown and only the cache functionality becomes disabled. Use the `no` form

of this command to enable ND cache for MAC/IPv6. Note: On enabling the cache, an IP will be in conflict, then the cache enable will fail. The conflict has to be manually removed and then the cache enabled.

This command is supported when following feature are disabled DNX feature

Attribute Name: nd-cache-disable

Attribute Type: empty

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <tagged-access-interfaces>
    <tagged-access-interface>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <config>
        <vlan-identifier>VLAN_RANGE</vlan-identifier>
        <interface-name>WORD</interface-name>
      </config>
      <interface-name>WORD</interface-name>
    </tagged-access-interface>
  </tagged-access-interfaces>
  <cache>
    <config>
      </nd-cache-disable><!-- operation="delete"-->
    </config>
  </cache>
</vxlan>
```

### Command Syntax

```
nd-cache disable
```

---

## Configure map vxlan-identifier

Use this attribute to map a tenant to an access-port

This command is supported when following feature are disabled DNX feature

Attribute Name: vxlan-identifier

Attribute Type: uint32

Attribute Range: 1-16777215

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <tagged-access-interfaces>
    <tagged-access-interface>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <config>
        <vlan-identifier>VLAN_RANGE</vlan-identifier>
        <interface-name>WORD</interface-name>
      </config>
      <interface-name>WORD</interface-name>
    </tagged-access-interface>
  </tagged-access-interfaces>
  <map>
```

```

<config>
  <vxlan-identifier>1</vxlan-identifier> <!-- operation="delete"-->
</config>
</map>
</tagged-access-interface>
</tagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
map vnid <1-16777215>
```

---

## Configure map tenant-description

Use this attribute to map VXLAN Identifier Name

This command is supported when following feature are disabled DNX feature

Attribute Name: tenant-description

Attribute Type: string

Attribute Range: 1-10

## Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<tagged-access-interfaces>
<tagged-access-interface>
  <vlan-identifier>VLAN_RANGE</vlan-identifier>
  <config>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
  </config>
  <interface-name>WORD</interface-name>
</map>
<config>
  <tenant-description>WORD</tenant-description> <!-- operation="delete"-->
</config>
</map>
</tagged-access-interface>
</tagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
map vni-name WORD
```

---

## Configure host-macs-ipv4 mac-address

Use this attribute to know MAC address of the host

Attribute Name: mac-address

Attribute Type: string

**Netconf edit-config payload**

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<tagged-access-interfaces>
<tagged-access-interface>
  <vlan-identifier>VLAN_RANGE</vlan-identifier>
  <config>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
  </config>
  <interface-name>WORD</interface-name>
</tagged-access-interface>
</tagged-access-interfaces>
</vxlan>

```

**Command Syntax**

```
mac (XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) ip IP-ADDRESS
```

**Configure host-macs-ipv6 mac-address**

Use this attribute to know MAC address of the host

Attribute Name: mac-address

Attribute Type: string

**Netconf edit-config payload**

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<tagged-access-interfaces>
<tagged-access-interface>
  <vlan-identifier>VLAN_RANGE</vlan-identifier>
  <config>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
  </config>
  <interface-name>WORD</interface-name>
</tagged-access-interface>
</tagged-access-interfaces>
</vxlan>

```

```

    </config>
      <mac-address>CML_MAC_ADDR_T</mac-address>
</host-mac-ipv6>
</host-macs-ipv6>
</tagged-access-interface>
</tagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
mac (XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) ipv6 IP-ADDRESS
```

---

## Configure profile name

Use this attribute to map the profile type for which qos profile is already created globally to access port

This command is supported when following feature are enabled QOS feature and following feature are disabled DNX feature

Attribute Name: profile-map-type

Attribute Type: enum (cos-to-queue|queue-color-to-cos)

Attribute Name: profile-name

Attribute Type: string

## Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <tagged-access-interfaces>
    <tagged-access-interface>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <config>
        <vlan-identifier>VLAN_RANGE</vlan-identifier>
        <interface-name>WORD</interface-name>
      </config>
      <interface-name>WORD</interface-name>
    </tagged-access-interface>
  </tagged-access-interfaces>
  <access-interface-qos-type-mappings>
    <access-interface-qos-type-mapping> <!-- operation="delete"-->
      <profile-map-type>cos-to-queue</profile-map-type>
    </access-interface-qos-type-mapping>
    <config>
      <profile-map-type>cos-to-queue</profile-map-type>
      <profile-name>NAME</profile-name>
    </config>
  </access-interface-qos-type-mapping>
</access-interface-qos-type-mappings>
</tagged-access-interface>
</tagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
map qos-profile (cos-to-queue|queue-color-to-cos) NAME
```

---

## Configure inner vlan identifier

Use this attribute to map VLAN'S on an interface to identify the tenant traffic and to enter NVO access interface mode

This command is supported when following feature are disabled DNX feature

Attribute Name: inner-vlan-identifier

Attribute Type: uint32

Attribute Range: 2-4094

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<double-tagged-access-interfaces>
<double-tagged-access-interface> <!-- operation="delete"-->
  <inner-vlan-identifier>2</inner-vlan-identifier>
  <config>
    <inner-vlan-identifier>2</inner-vlan-identifier>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
  </config>
  <vlan-identifier>VLAN_RANGE</vlan-identifier>
  <interface-name>WORD</interface-name>
</double-tagged-access-interface>
</double-tagged-access-interfaces>
</vxlan>
```

### Command Syntax

```
nvo vxlan access-if port-vlan IFNAME VLAN_RANGE inner-vlan <2-4094>
```

---

## Configure double-tagged-access-interface tag-protocol-identifier

Use this attribute to set the Tpid for the outer vlan. Ox88A8: IEEE 802.1ad Provider Bridging and Ox9100: IEEE 802.1Q VLAN-tagged frame with double tagging

This command is supported when following feature are disabled DNX feature

Attribute Name: tag-protocol-identifier

Attribute Type: string

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<double-tagged-access-interfaces>
<double-tagged-access-interface>
  <inner-vlan-identifier>2</inner-vlan-identifier>
  <config>
    <inner-vlan-identifier>2</inner-vlan-identifier>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
  </config>
  <vlan-identifier>VLAN_RANGE</vlan-identifier>
  <interface-name>WORD</interface-name>
```

```

->     <tag-protocol-identifier>TPID</tag-protocol-identifier> <!-- operation="delete"-->
    </double-tagged-access-interface>
    </double-tagged-access-interfaces>
    </vxlan>

```

### Command Syntax

```
encapsulation TPID
```

---

## Configure double-tagged-access-interface admin-shutdown

Use this attribute to shutdown vxlan access interface

This command is supported when following feature are disabled DNX feature

Attribute Name: admin-shutdown

Attribute Type: empty

### Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <double-tagged-access-interfaces>
    <double-tagged-access-interface>
      <inner-vlan-identifier>2</inner-vlan-identifier>
      <config>
        <inner-vlan-identifier>2</inner-vlan-identifier>
        <vlan-identifier>VLAN_RANGE</vlan-identifier>
        <interface-name>WORD</interface-name>
      </config>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <interface-name>WORD</interface-name>
      </admin-shutdown><!-- operation="delete"-->
    </double-tagged-access-interface>
  </double-tagged-access-interfaces>
</vxlan>

```

### Command Syntax

```
shutdown
```

---

## Configure double-tagged-access-interface description

Use this attribute to set description of access interface

This command is supported when following feature are disabled DNX feature

Attribute Name: description

Attribute Type: string

Attribute Range: 1-32

### Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <double-tagged-access-interfaces>

```

```

<double-tagged-access-interface>
  <inner-vlan-identifier>2</inner-vlan-identifier>
  <config>
    <inner-vlan-identifier>2</inner-vlan-identifier>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
  </config>
  <vlan-identifier>VLAN_RANGE</vlan-identifier>
  <interface-name>WORD</interface-name>
  <description>LINE</description> <!-- operation="delete"-->
</double-tagged-access-interface>
</double-tagged-access-interfaces>
</vxlan>

```

### Command Syntax

```
description LINE
```

---

## Configure double-tagged-access-interface dynamic-learning-disable

Use this attribute to disable dynamic learning of MACs at the access port. This command also disables dynamic learning of MAC/IP from ARP/ND messages received on this access port.

This command is supported when following feature are disabled DNX feature

Attribute Name: dynamic-learning-disable

Attribute Type: empty

### Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <double-tagged-access-interfaces>
  <double-tagged-access-interface>
    <inner-vlan-identifier>2</inner-vlan-identifier>
    <config>
      <inner-vlan-identifier>2</inner-vlan-identifier>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <interface-name>WORD</interface-name>
    </config>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
    </dynamic-learning-disable><!-- operation="delete"-->
  </double-tagged-access-interface>
  </double-tagged-access-interfaces>
</vxlan>

```

### Command Syntax

```
dynamic-learning disable
```

---

## Configure double-tagged-access-interface access-mac-hold-time

Use this attribute to set the time a host mac entry will persist after unconfiguring. The feature holds the MAC in hardware until BGP has withdrawn from the neighbors. This helps to reduce flooding to other access ports. This setting applies when the access port is shut down, the physical port on which the access port is down, or the access port is removed from the VNID using the no form of the map vnid command. When the MAC hold time is configured as -1, then the MAC is not removed from the hardware and is also not withdrawn from EVPN BGP

This command is supported when following feature are disabled DNX feature

Attribute Name: access-mac-hold-time

Attribute Type: int32

Attribute Range: -1-300

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <double-tagged-access-interfaces>
    <double-tagged-access-interface>
      <inner-vlan-identifier>2</inner-vlan-identifier>
      <config>
        <inner-vlan-identifier>2</inner-vlan-identifier>
        <vlan-identifier>VLAN_RANGE</vlan-identifier>
        <interface-name>WORD</interface-name>
      </config>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <interface-name>WORD</interface-name>
      <access-mac-hold-time>-1</access-mac-hold-time> <!-- operation="delete"-->
    </double-tagged-access-interface>
  </double-tagged-access-interfaces>
</vxlan>
```

### Command Syntax

```
mac-holdtime <-1-300>
```

---

## Configure double-tagged-access-interface arp-nd-flood-suppress

Use this attribute to restrict the flood of ARP/ND packets towards remote VTEPs or other access ports. This command applies only when the ARP cache and ND cache are enabled. When the ARP cache is disabled, ARP flooding is not suppressed even if this command is given. When the ND cache is disabled, ND flooding is not disabled, even if this command is given

This command is supported when following feature are disabled DNX feature

Attribute Name: arp-nd-flood-suppress

Attribute Type: empty

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <double-tagged-access-interfaces>
    <double-tagged-access-interface>
      <inner-vlan-identifier>2</inner-vlan-identifier>
```

```

<config>
  <inner-vlan-identifier>2</inner-vlan-identifier>
  <vlan-identifier>VLAN_RANGE</vlan-identifier>
  <interface-name>WORD</interface-name>
</config>
<vlan-identifier>VLAN_RANGE</vlan-identifier>
<interface-name>WORD</interface-name>
</arp-nd-flood-suppress><!-- operation="delete"-->
</double-tagged-access-interface>
</double-tagged-access-interfaces>
</vxlan>

```

### Command Syntax

```
arp-nd flood-suppress
```

---

## Configure double-tagged-access-interface garp-gna-enable

Use this attribute to allow garp-gna packets advertisement

This command is supported when following feature are disabled DNX feature

Attribute Name: garp-gna-enable

Attribute Type: empty

### Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <double-tagged-access-interfaces>
  <double-tagged-access-interface>
    <inner-vlan-identifier>2</inner-vlan-identifier>
    <config>
      <inner-vlan-identifier>2</inner-vlan-identifier>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <interface-name>WORD</interface-name>
    </config>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
    </garp-gna-enable><!-- operation="delete"-->
  </double-tagged-access-interface>
</double-tagged-access-interfaces>
</vxlan>

```

### Command Syntax

```
garp-gna enable
```

---

## Configure double-tagged-access-interface mac-address

Use this attribute to set the static mac address of host

This command is supported when following feature are disabled DNX feature

Attribute Name: mac-address

Attribute Type: string

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <double-tagged-access-interfaces>
  <double-tagged-access-interface>
    <inner-vlan-identifier>2</inner-vlan-identifier>
    <config>
      <inner-vlan-identifier>2</inner-vlan-identifier>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <interface-name>WORD</interface-name>
    </config>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
    <mac-address>XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</mac-address>
  <!-- operation="delete"-->
  </double-tagged-access-interface>
</double-tagged-access-interfaces>
</vxlan>
```

### Command Syntax

```
mac (XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX)
```

---

## Configure map vxlan-identifier

Use this attribute to map a tenant to an access-port

This command is supported when following feature are disabled DNX feature

Attribute Name: vxlan-identifier

Attribute Type: uint32

Attribute Range: 1-16777215

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <double-tagged-access-interfaces>
  <double-tagged-access-interface>
    <inner-vlan-identifier>2</inner-vlan-identifier>
    <config>
      <inner-vlan-identifier>2</inner-vlan-identifier>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <interface-name>WORD</interface-name>
    </config>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
  <map>
  <config>
    <vxlan-identifier>1</vxlan-identifier> <!-- operation="delete"-->
  </config>
</map>
```

```

</double-tagged-access-interface>
</double-tagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
map vnid <1-16777215>
```

---

## Configure map tenant-description

Use this attribute to map VXLAN Identifier Name

This command is supported when following feature are disabled DNX feature

Attribute Name: tenant-description

Attribute Type: string

Attribute Range: 1-10

## Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<double-tagged-access-interfaces>
<double-tagged-access-interface>
  <inner-vlan-identifier>2</inner-vlan-identifier>
  <config>
    <inner-vlan-identifier>2</inner-vlan-identifier>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
  </config>
  <vlan-identifier>VLAN_RANGE</vlan-identifier>
  <interface-name>WORD</interface-name>
</map>
<config>
  <tenant-description>WORD</tenant-description> <!-- operation="delete"-->
</config>
</map>
</double-tagged-access-interface>
</double-tagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
map vni-name WORD
```

---

## Configure cache arp-cache-disable

Use this attribute to disable the ARP cache for MAC/IP. When the ARP cache is disabled on a VxLAN access port, ZebOS-XP does not reply to any ARP arriving on this port from the cache. ZebOS-XP withdraws all MAC/IPs configured/learned on this access port and removes the MAC/IP entry for this access port from the local ARP cache. ZebOS-XP also makes sure that on withdrawing the MAC/IP route, the MAC does not become unknown. If all routes for this MAC are being withdrawn because of this command, then ZebOS-XP advertises a MAC-only route. This is done so that the MAC does not become unknown and only the cache functionality becomes disabled. See also `nvo vxlan max-cache-disable`. Use the `no` form of this command to enable ARP cache for MAC/IP. Note: On enabling the

cache, an IP will be in conflict, then the cache enable will fail. The conflict has to be manually removed and then the cache enabled.

This command is supported when following feature are disabled DNX feature

Attribute Name: arp-cache-disable

Attribute Type: empty

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <double-tagged-access-interfaces>
  <double-tagged-access-interface>
    <inner-vlan-identifier>2</inner-vlan-identifier>
    <config>
      <inner-vlan-identifier>2</inner-vlan-identifier>
      <vlan-identifier>VLAN_RANGE</vlan-identifier>
      <interface-name>WORD</interface-name>
    </config>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
  </double-tagged-access-interface>
</double-tagged-access-interfaces>
  <cache>
  <config>
    </arp-cache-disable><!-- operation="delete"-->
  </config>
</cache>
</vxlan>
```

### Command Syntax

```
arp-cache disable
```

---

## Configure cache nd-cache-disable

Use this attribute to disable ND cache for MAC/IPv6. When the ARP cache is disabled on a VxLAN access port, ZebOS-XP does not reply to any ARP arriving on this port from the cache. ZebOS-XP withdraws all MAC/IPs configured/learned on this access port and removes the MAC/IP entry for this access port from the local ARP cache. ZebOS-XP also makes sure that on withdrawing the MAC/IP route, the MAC does not become unknown. If all routes for this MAC are being withdrawn because of this command, then ZebOS-XP advertises a MAC-only route. This is done so that the MAC does not become unknown and only the cache functionality becomes disabled. Use the no form of this command to enable ND cache for MAC/IPv6. Note: On enabling the cache, an IP will be in conflict, then the cache enable will fail. The conflict has to be manually removed and then the cache enabled.

This command is supported when following feature are disabled DNX feature

Attribute Name: nd-cache-disable

Attribute Type: empty

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <double-tagged-access-interfaces>
  <double-tagged-access-interface>
```

```

<inner-vlan-identifier>2</inner-vlan-identifier>
<config>
  <inner-vlan-identifier>2</inner-vlan-identifier>
  <vlan-identifier>VLAN_RANGE</vlan-identifier>
  <interface-name>WORD</interface-name>
</config>
<vlan-identifier>VLAN_RANGE</vlan-identifier>
<interface-name>WORD</interface-name>
<cache>
<config>
  </nd-cache-disable><!-- operation="delete"-->
</config>
</cache>
</double-tagged-access-interface>
</double-tagged-access-interfaces>
</vxlan>

```

## Command Syntax

```
nd-cache disable
```

---

## Configure host-macs-ipv4 mac-address

Use this attribute to know MAC address of the host

Attribute Name: mac-address

Attribute Type: string

### Netconf edit-config payload

```

<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<double-tagged-access-interfaces>
<double-tagged-access-interface>
  <inner-vlan-identifier>2</inner-vlan-identifier>
  <config>
    <inner-vlan-identifier>2</inner-vlan-identifier>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
  </config>
  <vlan-identifier>VLAN_RANGE</vlan-identifier>
  <interface-name>WORD</interface-name>
</double-tagged-access-interface>
</double-tagged-access-interfaces>
<host-macs-ipv4>
<host-mac-ipv4> <!-- operation="delete"-->
  <ipv4-address>A.B.C.D</ipv4-address>
  <config>
    <ipv4-address>A.B.C.D</ipv4-address>
    <mac-address>CML_MAC_ADDR_T</mac-address>
  </config>
  <mac-address>CML_MAC_ADDR_T</mac-address>
</host-mac-ipv4>
</host-macs-ipv4>
</double-tagged-access-interface>

```

```
</double-tagged-access-interfaces>
</vxlan>
```

## Command Syntax

```
mac (XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) ip IP-ADDRESS
```

---

## Configure host-macs-ipv6 mac-address

Use this attribute to know MAC address of the host

Attribute Name: mac-address

Attribute Type: string

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<double-tagged-access-interfaces>
<double-tagged-access-interface>
  <inner-vlan-identifier>2</inner-vlan-identifier>
  <config>
    <inner-vlan-identifier>2</inner-vlan-identifier>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
  </config>
  <vlan-identifier>VLAN_RANGE</vlan-identifier>
  <interface-name>WORD</interface-name>
</double-tagged-access-interface>
</double-tagged-access-interfaces>
</vxlan>
```

```
<host-macs-ipv6>
<host-mac-ipv6> <!-- operation="delete"-->
  <ipv6-address>X:X::X:X</ipv6-address>
  <config>
    <ipv6-address>IP-ADDRESS</ipv6-address>
    <mac-address>XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</mac-address>
  </config>
  <mac-address>CML_MAC_ADDR_T</mac-address>
</host-mac-ipv6>
</host-macs-ipv6>
```

## Command Syntax

```
mac (XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) ipv6 IP-ADDRESS
```

---

## Configure access-interface-qos-type-mappings profile-map-type

Use this attribute to map the profile type for which qos profile is already created globally to access port

This command is supported when following feature are enabled QOS feature and following feature are disabled DNX feature

Attribute Name: profile-map-type

Attribute Type: enum (cos-to-queue|queue-color-to-cos)

Attribute Name: profile-name

Attribute Type: string

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<double-tagged-access-interfaces>
<double-tagged-access-interface>
  <inner-vlan-identifier>2</inner-vlan-identifier>
  <config>
    <inner-vlan-identifier>2</inner-vlan-identifier>
    <vlan-identifier>VLAN_RANGE</vlan-identifier>
    <interface-name>WORD</interface-name>
  </config>
  <vlan-identifier>VLAN_RANGE</vlan-identifier>
  <interface-name>WORD</interface-name>
</double-tagged-access-interface>
</double-tagged-access-interfaces>
<access-interface-qos-type-mappings>
<access-interface-qos-type-mapping> <!-- operation="delete"-->
  <profile-map-type>cos-to-queue</profile-map-type>
  <config>
    <profile-map-type>cos-to-queue</profile-map-type>
    <profile-name>NAME</profile-name>
  </config>
</access-interface-qos-type-mapping>
</access-interface-qos-type-mappings>
</double-tagged-access-interface>
</double-tagged-access-interfaces>
</vxlan>
```

### Command Syntax

```
map qos-profile (cos-to-queue|queue-color-to-cos) NAME
```

---

## Configure access if

VXLAN logical access port per physical interface

This command is supported when following feature are enabled XGS feature and following feature are disabled DUNE feature

Attribute Name: access-if

Attribute Type: empty

### Netconf edit-config payload

```
<vxlan xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</access-if><!-- operation="delete"-->
```

```

</interface>
</interfaces>
</vxlan>

```

### Command Syntax

```
access-if-vxlan
```

---

## clear mac address-table dynamic vxlan

### Netconf RPC payload

```
<clear-nvo-vxlan-dynamic-mac-address-table xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-vxlan"/>
```

### Command Syntax

```
clear mac address-table dynamic vxlan
```

---

## clear mac address-table dynamic vxlan vnid <1-16777215> (address MACADDR|)

Attribute Name: vxlan-identifier

Attribute Type: uint32

Attribute Range: 1-16777215

Attribute Name: mac-address

Attribute Type: string

### Netconf RPC payload

```

<clear-nvo-vxlan-dynamic-mac-address-table-vnid xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <vxlan-identifier>1</vxlan-identifier>
  <mac-address>MACADDR</mac-address>
</clear-nvo-vxlan-dynamic-mac-address-table-vnid>

```

### Command Syntax

```
clear mac address-table dynamic vxlan vnid <1-16777215> (address MACADDR|)
```

---

## clear nvo vxlan tunnels

### Netconf RPC payload

```
<clear-nvo-vxlan-tunnels xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-vxlan"/>
```

### Command Syntax

```
clear nvo vxlan tunnels
```

---

## clear nvo vxlan tunnels dst-ip A.B.C.D

Attribute Name: destination-vtep-ip

Attribute Type: inet:ipv4-address

### Netconf RPC payload

```
<clear-nvo-id-vxlan-tunnels-destip xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-vxlan">
  <destination-vtep-ip>A.B.C.D</destination-vtep-ip>
</clear-nvo-id-vxlan-tunnels-destip>
```

### Command Syntax

```
clear nvo vxlan tunnels dst-ip A.B.C.D
```

---

## clear nvo vxlan mac-stale-entries (vnid <1-16777215>|)

Attribute Name: vxlan-identifier

Attribute Type: uint32

Attribute Range: 1-16777215

### Netconf RPC payload

```
<clear-nvo-vxlan-mac-stale-entries xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-vxlan">
  <vxlan-identifier>1</vxlan-identifier>
</clear-nvo-vxlan-mac-stale-entries>
```

### Command Syntax

```
clear nvo vxlan mac-stale-entries (vnid <1-16777215>|)
```

---

## clear nvo vxlan counters access-port port IFNAME

Attribute Name: interface-name

Attribute Type: string

### Netconf RPC payload

```
<clear-vxlan-untagged-access-port-counters xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-vxlan">
  <interface-name>IFNAME</interface-name>
</clear-vxlan-untagged-access-port-counters>
```

### Command Syntax

```
clear nvo vxlan counters access-port port IFNAME
```

---

## clear nvo vxlan counters access-port port-vlan IFNAME VLAN\_RANGE

Attribute Name: interface-name

Attribute Type: string

Attribute Name: vlan-identifier

Attribute Type: string

### Netconf RPC payload

```
<clear-vxlan-single-tagged-access-port-counters xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <interface-name>IFNAME</interface-name>
  <vlan-identifier>VLAN_RANGE</vlan-identifier>
</clear-vxlan-single-tagged-access-port-counters>
```

### Command Syntax

```
clear nvo vxlan counters access-port port-vlan IFNAME VLAN_RANGE
```

---

## clear nvo vxlan counters access-port port-vlan IFNAME outer-vlan <2-4094> inner-vlan <2-4094>

Attribute Name: interface-name

Attribute Type: string

Attribute Name: outer-vlan-identifier

Attribute Type: uint32

Attribute Range: 2-4094

Attribute Name: inner-vlan-identifier

Attribute Type: uint32

Attribute Range: 2-4094

### Netconf RPC payload

```
<clear-vxlan-double-tagged-access-port-counters xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-vxlan">
  <interface-name>IFNAME</interface-name>
  <outer-vlan-identifier>outer-vlan</outer-vlan-identifier>
  <inner-vlan-identifier>inner-vlan</inner-vlan-identifier>
</clear-vxlan-double-tagged-access-port-counters>
```

### Command Syntax

```
clear nvo vxlan counters access-port port-vlan IFNAME outer-vlan <2-4094> inner-
vlan <2-4094>
```

---

## clear nvo vxlan counters access-port all

### Netconf RPC payload

```
<clear-vxlan-access-port-counters-all xmlns="http://www.ipinfusion.com/yang/
ocnos/ipi-vxlan"/>
```

### Command Syntax

```
clear nvo vxlan counters access-port all
```

---

## clear nvo vxlan counters network-port dst A.B.C.D

Attribute Name: destination-vtep-ip

Attribute Type: inet:ipv4-address

### Netconf RPC payload

```
<clear-vxlan-network-port-counters xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-vxlan">
  <destination-vtep-ip>A.B.C.D</destination-vtep-ip>
</clear-vxlan-network-port-counters>
```

### Command Syntax

```
clear nvo vxlan counters network-port dst A.B.C.D
```

---

## clear nvo vxlan counters network-port all

### Netconf RPC payload

```
<clear-vxlan-network-port-counters-all xmlns="http://www.ipinfusion.com/yang/
ocnos/ipi-vxlan"/>
```

### Command Syntax

```
clear nvo vxlan counters network-port all
```

---

## IPI-ETHERNET-VPN

---

### Configure esi hold time

Use this attribute to set time before ESI can be made up on enabling evpn

Attribute Name: esi-hold-time

Attribute Type: uint32

Attribute Range: 10-300

### Netconf edit-config payload

```
<evpn xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ethernet-vpn">
  <multi-homing>
    <config>
      <esi-hold-time>10</esi-hold-time> <!-- operation="delete"-->
    </config>
  </multi-homing>
</evpn>
```

### Command Syntax

```
evpn esi hold-time <10-300>
```

---

## Configure enable vxlan multihoming

Use this attribute to enable multihoming module on vxlan. Without this attribute multihomig functionality can not be achieved

Attribute Name: enable-vxlan-multihoming

Attribute Type: uint8

### Netconf edit-config payload

```
<evpn xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ethernet-vpn">
  <global>
    <config>
      </enable-vxlan-multihoming><!-- operation="delete"-->
    </config>
  </global>
</evpn>
```

### Command Syntax

```
evpn multihoming enable
```

---

## Configure global enable-vxlan-multihoming

Use this attribute to enable multihoming module on vxlan. Without this attribute multihomig functionality can not be achieved

Attribute Name: enable-vxlan-multihoming

Attribute Type: empty

### Netconf edit-config payload

```
<evpn xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ethernet-vpn">
  <global>
    <config>
      </enable-vxlan-multihoming><!-- operation="delete"-->
    </config>
  </global>
</evpn>
```

### Command Syntax

```
evpn vxlan multihoming enable
```

---

## Configure enable irb

Use this attribute to enable integrated routing and bridging module. Without this attribute IRB functionality can not be achieved

Attribute Name: enable-irb

Attribute Type: empty

### Netconf edit-config payload

```
<evpn xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ethernet-vpn">
```

```

<global>
<config>
  </enable-irb><!-- operation="delete"-->
</config>
</global>
</evpn>

```

### Command Syntax

```
nvo vxlan irb
```

---

## Configure enable evpn etree

Use this attribute to enable evpn etree module on evpn mpls or vxlan.

Attribute Name: enable-evpn-etree

Attribute Type: empty

### Netconf edit-config payload

```

<evpn xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ethernet-vpn">
<global>
<config>
  </enable-evpn-etree><!-- operation="delete"-->
</config>
</global>
</evpn>

```

### Command Syntax

```
evpn etree enable
```

---

## Configure mac address

Use this attribute to configure common anycast mac-address for all IRB interfaces

Attribute Name: mac-address

Attribute Type: string

### Netconf edit-config payload

```

<evpn xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ethernet-vpn">
<irb-forwarding>
<config>
  <mac-address>XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</mac-address>
<!-- operation="delete"-->
</config>
</irb-forwarding>
</evpn>

```

### Command Syntax

```
evpn irb-forwarding anycast-gateway-mac (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX)
```

---

## Configure gateway mac

Use this attribute to configure anycast mac-address for an IRB interface

Attribute Name: gateway-mac

Attribute Type: empty

### Netconf edit-config payload

```
<evpn xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ethernet-vpn">
  <irb-forwarding>
  <irb-interfaces>
  <irb-interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
    </gateway-mac><!-- operation="delete"-->
  </irb-interface>
</irb-interfaces>
</irb-forwarding>
</evpn>
```

### Command Syntax

```
evpn irb-if-forwarding anycast-gateway-mac
```

---

## Configure name

Reference to interface name

Attribute Name: name

Attribute Type: string

Attribute Name: evpn-segment-id

Attribute Type: string

### Netconf edit-config payload

```
<evpn xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ethernet-vpn">
  <interfaces>
  <interface> <!-- operation="delete"-->
    <name>WORD</name>
    <config>
      <name>WORD</name>
      <evpn-segment-id>XX:XX:XX:XX:XX:XX:XX:XX:XX</evpn-segment-id>
    </config>
  </interface>
</interfaces>
</evpn>
```

### Command Syntax

```
evpn multi-homed esi XX:XX:XX:XX:XX:XX:XX:XX:XX
```

---

## Configure system mac

Reference to interface name

Attribute Name: name

Attribute Type: string

Attribute Name: system-mac

Attribute Type: string

### Netconf edit-config payload

```
<evpn xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ethernet-vpn">
  <interfaces>
    <interface> <!-- operation="delete"-->
      <name>WORD</name>
      <config>
        <name>WORD</name>
        <system-mac>XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</system-mac>
      </config>
    </interface>
  </interfaces>
</evpn>
```

### Command Syntax

```
evpn multi-homed system-mac (XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX)
```

---

## Configure service type

Use this attribute to configure Vlan-Based EVPN-Service Type

Attribute Name: service-type

Attribute Type: enum (vlan-based|vlan-aware-bundle)

### Netconf edit-config payload

```
<evpn xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ethernet-vpn">
  <vrfs>
    <vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
      </config>
      <service-type>vlan-based</service-type> <!-- operation="delete"-->
    </vrf>
  </vrfs>
</evpn>
```

### Command Syntax

```
evpn-vlan-service (vlan-based|vlan-aware-bundle)
```

---

## IPI-TFO

---

### Configure admin status

Use this attribute to enable or disable trigger failover (TFO). TFO can be enabled only if the bridge mode is STP or RSTP.

Attribute Name: admin-status

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<trigger-failover xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tfo">
  <config>
    <admin-status>disable</admin-status> <!-- operation="delete"-->
  </config>
</trigger-failover>
```

### Command Syntax

```
tfo (disable|enable)
```

---

## Configure link type

Use this attribute to make a port an uplink or downlink.

Attribute Name: link-type

Attribute Type: enum (uplink|downlink)

### Netconf edit-config payload

```
<trigger-failover xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tfo">
  <interfaces>
    <interface>
      <name>IFNAME</name>
      <config>
        <name>WORD</name>
      </config>
      <link-type>uplink</link-type> <!-- operation="delete"-->
    </interface>
  </interfaces>
</trigger-failover>
```

### Command Syntax

```
link-type (uplink|downlink)
```

---

## Configure fog id

Use this attribute to Create or delete a failover group (FOG) on interface.

Attribute Name: fog-id

Attribute Type: uint32

Attribute Range: 1-64

Attribute Name: group-type

Attribute Type: enum (mpg|cpg)

### Netconf edit-config payload

```
<trigger-failover xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tfo">
  <interfaces>
    <interface>
      <name>IFNAME</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
  <tfo-groups>
    <tfo-group <!-- operation="delete"-->
      <fog-id>1</fog-id>
      <config>
        <fog-id>1</fog-id>
        <group-type>mpg</group-type>
      </config>
    </tfo-group>
  </tfo-groups>
</trigger-failover>
```

### Command Syntax

```
fog <1-64> type (mpg|cpg)
```

---

## Configure group id

Use this attribute to Create or delete a failover group (FOG).

Attribute Name: group-id

Attribute Type: uint32

Attribute Range: 1-64

Attribute Name: admin-status

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<trigger-failover xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tfo">
  <failover-groups>
    <failover-group <!-- operation="delete"-->
      <group-id>1</group-id>
      <config>
        <group-id>1</group-id>
        <admin-status>disable</admin-status>
      </config>
    </failover-group>
  </failover-groups>
</trigger-failover>
```

```
</failover-group>  
</failover-groups>  
</trigger-failover>
```

## Command Syntax

```
fog <1-64> (disable|enable)
```

---

## Configure failover trigger count

Use this attribute to set the number of links to trigger failover for a Monitor Port Groups (MPG).

Attribute Name: failover-trigger-count

Attribute Type: uint32

Attribute Range: 0-63

## Netconf edit-config payload

```
<trigger-failover xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tfo">  
  <failover-groups>  
    <failover-group>  
      <group-id>1</group-id>  
      <config>  
        <group-id>1</group-id>  
      </config>  
      <failover-trigger-count>0</failover-trigger-count> <!-- operation="delete"-->  
    </failover-group>  
  </failover-groups>  
</trigger-failover>
```

## Command Syntax

```
fog <1-64> tfc <0-63>
```

---

## clear tfo counter

## Netconf RPC payload

```
<tfo-clear-counters-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tfo"/>
```

## Command Syntax

```
clear tfo counter
```

---

## clear tfo counter fog <1-64>

Attribute Name: group-id

Attribute Type: uint32

Attribute Range: 1-64

## Netconf RPC payload

```
<tfo-clear-fog-counters xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tfo">
```

```
<group-id>1</group-id>
</tfo-clear-fog-counters>
```

### Command Syntax

```
clear tfo counter fog <1-64>
```

---

## IPI-LOGGING

---

### Configure severity level

Use this attribute to set the severity level that a message for a specific module must reach before the messages is logged. Default value is 2-critical.

Attribute Name: severity-level

Attribute Type: enum (0|1|2|3|4|5|6|7)

### Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
  <logging-modules>
    <module-logging>
      <module-name>auth</module-name>
      <config>
        <module-name>auth</module-name>
      </config>
      <severity-level>2</severity-level>
    </module-logging>
  </logging-modules>
</logging>
```

### Command Syntax

```
logging level
  (auth|bgp|cmm|hostp|hsl|isis|lag|l2mrib|mstp|mrib|nsm|onm|oam|ospf|ospf6|rip|pim
  |rib|vrrp|sflow|pserv|cml|ndd|ripng|vlog|all|udld) ((0|1|2|3|4|5|6|7) |)
```

---

### Configure enable logging

Use this attribute to set severity level of logging monitor. Default value is 7-debug-details.

Attribute Name: severity-level

Attribute Type: enum (0|1|2|3|4|5|6|7)

Default Value: 7

Attribute Name: enable-logging

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
  <monitor-logging>
```

```

<config>
  <enable-logging>enable</enable-logging> <!-- operation="delete"-->
  <severity-level>7</severity-level> <!-- operation="delete"-->
</config>
</monitor-logging>
</logging>

```

### Command Syntax

```
logging monitor ((disable)|) ((0|1|2|3|4|5|6|7)|)
```

---

## Configure console-logging severity-level

Use this attribute to set severity level of logging console. Default value is 2-critical.

Attribute Name: severity-level

Attribute Type: enum (0|1|2|3|4|5|6|7)

Default Value: 2

Attribute Name: enable-logging

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```

<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
  <console-logging>
    <config>
      <enable-logging>enable</enable-logging> <!-- operation="delete"-->
      <severity-level>2</severity-level> <!-- operation="delete"-->
    </config>
  </console-logging>
</logging>

```

### Command Syntax

```
logging console ((disable)|) ((0|1|2|3|4|5|6|7)|)
```

---

## Configure max file size

Set size of the log file in bytes. Default value is 419430400 bytes.

Attribute Name: max-file-size

Attribute Type: uint32

Attribute Range: 4096-419430400

Attribute Name: file-name

Attribute Type: string

Attribute Name: severity-level

Attribute Type: enum (0|1|2|3|4|5|6|7)

### Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
```

```
<logfile>
<config>
  <file-name>LOGFILENAME</file-name> <!-- operation="delete"-->
  <severity-level>6</severity-level> <!-- operation="delete"-->
  <max-file-size>4096</max-file-size> <!-- operation="delete"-->
</config>
</logfile>
</logging>
```

## Command Syntax

```
logging logfile LOGFILENAME (0|1|2|3|4|5|6|7) size <4096-419430400>
```

---

## Configure file name

Use this attribute to set name of the logging file.

Attribute Name: file-name

Attribute Type: string

Attribute Name: severity-level

Attribute Type: enum (0|1|2|3|4|5|6|7)

## Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
<logfile>
<config>
  <severity-level>6</severity-level>
  <file-name>LOGFILENAME</file-name>
</config>
</logfile>
</logging>
```

## Command Syntax

```
logging logfile LOGFILENAME (0|1|2|3|4|5|6|7)
```

---

## Configure debug-logfile max-file-size

Set size of the debug log file in bytes. The default value is 4194304 bytes.

Attribute Name: max-file-size

Attribute Type: uint32

Attribute Range: 4096-4194304

Attribute Name: file-name

Attribute Type: string

## Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
<debug-logfile>
<config>
```

```
<file-name>LOGFILE</file-name>
<max-file-size>4096</max-file-size>
</config>
</debug-logfile>
</logging>
```

### Command Syntax

```
debug logfile LOGFILE size <4096-4194304>
```

---

## Configure enable syslog

Use this attribute to begin logging of information to the system log and set the level to debug.

This command is supported when following feature are enabled syslog feature

Attribute Name: enable-syslog

Attribute Type: empty

### Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
<syslog>
<config>
  </enable-syslog><!-- operation="delete"-->
</config>
</syslog>
</logging>
```

### Command Syntax

```
log syslog
```

---

## Configure timestamp granularity

Use this attribute to set the logging timestamp granularity.

This command is supported when following feature are enabled syslog feature

Attribute Name: timestamp-granularity

Attribute Type: enum (none|microseconds|milliseconds|seconds)

Default Value: milliseconds

### Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
<syslog>
<config>
  <timestamp-granularity>milliseconds</timestamp-granularity> <!--
operation="delete"-->
</config>
</syslog>
</logging>
```

---

## Command Syntax

```
logging timestamp (none|microseconds|milliseconds|seconds|)
```

---

## Configure cli timestamp

Use this attribute to display execution timestamp in show output

This command is supported when following feature are enabled syslog feature

Attribute Name: cli-timestamp

Attribute Type: empty

### Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
  <syslog>
  <config>
    </cli-timestamp><!-- operation="delete"-->
  </config>
</syslog>
</logging>
```

## Command Syntax

```
cli timestamp
```

---

## Configure disable all modules debug

Use this attribute to unset debug globally

Attribute Name: disable-all-modules-debug

Attribute Type: empty

### Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
  <global>
  <config>
    </disable-all-modules-debug><!-- operation="delete"-->
  </config>
</global>
</logging>
```

## Command Syntax

```
no debug all
```

---

## no debug all

### Netconf RPC payload

```
<terminal-debug-all-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging"/>
```

---

## Command Syntax

```
no debug all
```

---

## clear debug logfile

### Netconf RPC payload

```
<logging-clear-debug-logfile xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging"/>
```

### Command Syntax

```
clear debug logfile
```

---

## clear logging logfile

### Netconf RPC payload

```
<logging-clear-logging-logfile xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging"/>
```

### Command Syntax

```
clear logging logfile
```

---

## remove file (techsupport) (all|FILENAME)

Attribute Name: file\_type

Attribute Type: enum (techsupport)

Attribute Name: filename

Attribute Type: union

### Netconf RPC payload

```
<remove-file xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">  
<file_type>techsupport</file_type>  
<filename>FILE_TYPE_T</filename>  
</remove-file>
```

### Command Syntax

```
remove file (techsupport) (all|FILENAME)
```

---

## IPI-LOGGING-REMOTE

---

### Configure enable

This attribute enables/disables the logging host debug.

Attribute Name: enable

Attribute Type: empty

---

### Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
  <debug>
  <config>
    </enable><!-- operation="delete"-->
  </config>
</debug>
</logging>
```

### Command Syntax

```
debug logging host
```

---

## Configure enable rsyslog

Enable/disable the rsyslog feature

Attribute Name: enable-rsyslog

Attribute Type: empty

### Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
  <remote-logging>
  <config>
    </enable-rsyslog><!-- operation="delete"-->
  </config>
</remote-logging>
</logging>
```

### Command Syntax

```
feature rsyslog
```

---

## Configure port

Use this attribute to configure the syslog server UDP port. Default value is 514

This command is supported when following feature are enabled Virtual routing and forwarding

Attribute Name: port

Attribute Type: uint16

Attribute Range: 1024-65535

Attribute Name: severity

Attribute Type: enum (0|1|2|3|4|5|6|7)

### Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
  <remote-logging>
  <remote-servers>
  <remote-server>
    <vrf>NAME</vrf>
  </remote-server>
</remote-servers>
</remote-logging>
```

```

<config>
  <vrf>NAME</vrf>
</config>
<servers>
<server>
  <address>A.B.C.D</address>
  <config>
    <address>1</address>
    <severity>7</severity> <!-- operation="delete"-->
  </config>
  <port>1024</port> <!-- operation="delete"-->
</server>
</servers>
</remote-server>
</remote-servers>
</remote-logging>
</logging>

```

## Command Syntax

```

logging remote server (A.B.C.D|X:X:X:X|HOSTNAME) ((0|1|2|3|4|5|6|7)|) port <1024-
65535> (vrf (NAME|management)|)

```

---

## Configure severity

This attribute is used to specify the kind of messages by severity level. The default value is debug-detail. The possible values for levels are as follows: [Operator] 0-emerg; 1-alert; 2-critical; 3-error; 4-notify; 5-info [Debug] 3-error; 4-warning; 5-notif; 6-debug-info; 7-debug-detail

This command is supported when following feature are enabled Virtual routing and forwarding

Attribute Name: severity

Attribute Type: enum (0|1|2|3|4|5|6|7)

## Netconf edit-config payload

```

<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
<remote-logging>
<remote-servers>
<remote-server>
  <vrf>NAME</vrf>
  <config>
    <vrf>NAME</vrf>
  </config>
  <servers>
  <server>
    <address>A.B.C.D</address>
    <config>
      <address>1</address>
    </config>
    <severity>7</severity>
  </server>
</servers>
</remote-servers>
</remote-logging>
</logging>

```

```

</remote-server>
</remote-servers>
</remote-logging>
</logging>

```

## Command Syntax

```

logging remote server (A.B.C.D|X:X::X:X|HOSTNAME) ((0|1|2|3|4|5|6|7)|) (vrf
(NAME|management)|)

```

---

## Configure disable default instance

Use this attribute to prevent default rsyslog config from being enabled at start up

Attribute Name: disable-default-instance

Attribute Type: empty

### Netconf edit-config payload

```

<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
<remote-logging>
<default-instance>
<config>
    </disable-default-instance><!-- operation="delete"-->
</config>
</default-instance>
</remote-logging>
</logging>

```

## Command Syntax

```

logging remote disable-default

```

---

## Configure remote server facility

This attribute is used to specify the facility level used by syslog messages. The default value is local7. The possible values are local0, local1, local2, local3, local4, local5, local6, local7 and user.

Attribute Name: remote-server-facility

Attribute Type: enum (local0|local1|local2|local3|local4|local5|local6|local7|user)

Default Value: local7

### Netconf edit-config payload

```

<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
<global>
<config>
    <remote-server-facility>local7</remote-server-facility> <!--
operation="delete"-->
</config>
</global>
</logging>

```

---

## Command Syntax

```
logging remote facility
(local0|local1|local2|local3|local4|local5|local6|local7|user)
```

---

## Configure remote authpriv facility

Enable/disable logging authpriv facility for remote syslog server.

Attribute Name: remote-authpriv-facility

Attribute Type: empty

### Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
  <global>
    <config>
      </remote-authpriv-facility><!-- operation="delete"-->
    </config>
  </global>
</logging>
```

## Command Syntax

```
logging remote authpriv
```

---

## IPI-LOGGING-CLI

---

### Configure enable logging

Use this attribute to enable/disable CLI history logs. By default CLI history is enabled.

Attribute Name: enable-logging

Attribute Type: empty

### Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
  <cli-logging>
    <config>
      </enable-logging><!-- operation="delete"-->
    </config>
  </cli-logging>
</logging>
```

## Command Syntax

```
logging cli
```

---

### Configure max session limit

Use this attribute to set maximum session limit for vty.

Attribute Name: max-session-limit

Attribute Type: uint8

Attribute Range: 1-40

### Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
  <cli-logging>
  <max-session-limit>
  <config>
    <max-session-limit>1</max-session-limit> <!-- operation="delete"-->
  </config>
</max-session-limit>
</cli-logging>
</logging>
```

### Command Syntax

```
max-session <1-40>
```

---

## IPI-EVENT-MANAGER

---

### Configure feature

Enable Event Manager

Attribute Name: feature

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<event-manager xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-event-manager">
  <config>
    <feature>disable</feature> <!-- operation="delete"-->
  </config>
</event-manager>
```

### Command Syntax

```
event-manager (disable|enable)
```

---

### Configure event pattern

Pattern to match

Attribute Name: event-pattern

Attribute Type: string

Attribute Name: event-type

Attribute Type: enum (syslog)

Attribute Name: event-id

Attribute Type: string

Attribute Range: 4-128

Attribute Name: severity

Attribute Type: enum (0|1|2|3|4|5|all)

Default Value: all

### Netconf edit-config payload

```
<event-manager xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-event-manager">
  <event-entries>
    <event-entry>
      <event-name>NAME</event-name>
      <config>
        <event-name>WORD</event-name>
        <event-type>syslog</event-type>
        <event-id>EVENT-ID</event-id>
        <severity>all</severity>
      </config>
      <event-pattern>PATTERN</event-pattern>
    </event-entry>
  </event-entries>
</event-manager>
```

### Command Syntax

```
event-manager event NAME type (syslog) EVENT-ID ({ severity (0|1|2|3|4|5|all) |
  pattern PATTERN })
```

---

## Configure action script

Name of script

Attribute Name: action-script

Attribute Type: string

Attribute Range: 4-64

Attribute Name: action-type

Attribute Type: enum (script)

### Netconf edit-config payload

```
<event-manager xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-event-manager">
  <action-entries>
    <action-entry>
      <action-name>NAME</action-name>
      <config>
        <action-name>WORD</action-name>
        <action-type>script</action-type>
      </config>
      <action-script>SCRIPT</action-script>
    </action-entry>
  </action-entries>
</event-manager>
```

```
</action-entries>
</event-manager>
```

## Command Syntax

```
event-manager action NAME type (script) SCRIPT
```

---

## Configure action name

Name of action

Attribute Name: action-name

Attribute Type: string

Attribute Range: 2-32

Attribute Name: event-name

Attribute Type: string

Attribute Range: 2-32

## Netconf edit-config payload

```
<event-manager xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-event-manager">
<policies>
<policy>
  <policy-name>NAME</policy-name>
  <config>
    <policy-name>NAME</policy-name>
    <event-name>NAME</event-name>
  </config>
  <action-name>NAME</action-name>
</policy>
</policies>
</event-manager>
```

## Command Syntax

```
event-manager policy NAME event NAME action NAME
```

---

## clear event-manager statistics all

### Netconf RPC payload

```
<event-manager-clear-statistics-all xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-event-manager"/>
```

### Command Syntax

```
clear event-manager statistics all
```

---

## clear event-manager statistics policy NAME

Attribute Name: policy-name

Attribute Type: string

---

## Netconf RPC payload

```
<event-manager-clear-statistics-on-policy xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-event-manager">
  <policy-name>NAME</policy-name>
</event-manager-clear-statistics-on-policy>
```

## Command Syntax

```
clear event-manager statistics policy NAME
```

---

# IPI-LOGGING-FAULT-MANAGEMENT

---

## Configure enable fault management

Enable Fault Management System

Attribute Name: enable-fault-management

Attribute Type: uint8

## Netconf edit-config payload

```
<logging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
  <fault-management>
  <config>
    </enable-fault-management><!-- operation="delete"-->
  </config>
</fault-management>
</logging>
```

## Command Syntax

```
fault-management enable
```

---

## fault-management flush-db

## Netconf RPC payload

```
<ipi-logging-fault-management_logging-fms-flush-db xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging"/>
```

## Command Syntax

```
fault-management flush-db
```

---

## fault-management shelve ALARM-TYPE

Attribute Name: alarm-type

Attribute Type: string

## Netconf RPC payload

```
<ipi-logging-fault-management_logging-fms-shelve xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-logging">
```

```
<alarm-type>ALARM-TYPE</alarm-type>
</ipi-logging-fault-management_logging-fms-shelve>
```

### Command Syntax

```
fault-management shelve ALARM-TYPE
```

---

## fault-management close ACTIVE-ALARM-ID

Attribute Name: active-alarm-id

Attribute Type: string

### Netconf RPC payload

```
<ipi-logging-fault-management_logging-fms-close xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-logging">
  <active-alarm-id>ACTIVE-ALARM-ID</active-alarm-id>
</ipi-logging-fault-management_logging-fms-close>
```

### Command Syntax

```
fault-management close ACTIVE-ALARM-ID
```

---

## IPI-DHCP

---

### Configure disable dhcp feature

Disable the DHCP client and DHCP relay on the device.

Attribute Name: disable-dhcp-feature

Attribute Type: uint8

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <global>
    <config>
      </disable-dhcp-feature><!-- operation="delete"-->
    </config>
  </global>
</dhcp>
```

### Command Syntax

```
no feature dhcp
```

---

## IPI-RADIUS

---

### Configure vrf name

VRF Name associated with this instance

This command is supported when following feature are enabled aaa feature

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: key-type

Attribute Type: enum (0|7)

Attribute Name: secret-key-string

Attribute Type: string

### Netconf edit-config payload

```
<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
        <key-type>0</key-type> <!-- operation="delete"-->
        <secret-key-string>WORD</secret-key-string> <!-- operation="delete"-->
      </config>
    </vrf>
  </vrfs>
</radius>
```

### Command Syntax

```
radius-server login key (0|7) WORD (vrf management|)
```

---

### Configure timeout

VRF Name associated with this instance

This command is supported when following feature are enabled aaa feature

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: timeout

Attribute Type: uint8

Attribute Range: 1-60

### Netconf edit-config payload

```
<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
```

```

<vrf>
  <vrf-name>management</vrf-name>
  <config>
    <vrf-name>management</vrf-name>
    <timeout>1</timeout> <!-- operation="delete"-->
  </config>
</vrf>
</vrfs>
</radius>

```

### Command Syntax

```
radius-server login timeout <1-60> (vrf management|)
```

---

## Configure sequence number

Use this attribute to set the sequence-number/priority index for the RADIUS server

This command is supported when following feature are enabled aaa feature

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

### Netconf edit-config payload

```

<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        </config>
      <sequence-number>1</sequence-number>
    </server>
  </remote-servers>
</radius>

```

### Command Syntax

```
radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8>
```

---

## Configure secret key string

Shared key used between the authentication-server and the device

This command is supported when following feature are enabled aaa feature

Attribute Name: secret-key-string

Attribute Type: string

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: key-type

Attribute Type: enum (0|7)

### Netconf edit-config payload

```
<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number> <!-- operation="delete"-->
        <key-type>0</key-type> <!-- operation="delete"-->
      </config>
      <secret-key-string>WORD</secret-key-string> <!-- operation="delete"-->
    </server>
  </remote-servers>
</radius>
```

### Command Syntax

```
radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8> key (0|7) WORD
```

---

## Configure accounting port

Use this attribute to configure a RADIUS server and specify a UDP port to use for RADIUS accounting messages

This command is supported when following feature are enabled aaa feature

Attribute Name: accounting-port

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: key-type

Attribute Type: enum (0|7)

Attribute Name: secret-key-string

Attribute Type: string

### Netconf edit-config payload

```
<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number> <!-- operation="delete"-->
        <key-type>0</key-type> <!-- operation="delete"-->
        <secret-key-string>WORD</secret-key-string> <!-- operation="delete"-->
      </config>
      <accounting-port>0</accounting-port> <!-- operation="delete"-->
    </server>
  </remote-servers>
</radius>
```

### Command Syntax

```
radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8> key (0|7) WORD acct-port <0-65535>
```

---

## Configure host address

To represent the timeout configured by the user

This command is supported when following feature are enabled aaa feature

Attribute Name: timeout

Attribute Type: uint8

Default Value: 5

Attribute Range: 1-60

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: key-type

Attribute Type: enum (0|7)

Attribute Name: secret-key-string

Attribute Type: string

Attribute Name: accounting-port

Attribute Type: uint16

Attribute Range: 0-65535

### Netconf edit-config payload

```
<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number> <!-- operation="delete"-->
        <key-type>0</key-type> <!-- operation="delete"-->
        <secret-key-string>WORD</secret-key-string> <!-- operation="delete"-->
        <accounting-port>0</accounting-port> <!-- operation="delete"-->
      </config>
      <timeout>1</timeout> <!-- operation="delete"-->
    </server>
  </remote-servers>
</radius>
```

### Command Syntax

```
radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8> key (0|7) WORD acct-port <0-65535> timeout <1-60>
```

## Configure authentication port

Use this attribute to configure a RADIUS server and specify a UDP port to use for RADIUS authentication messages

This command is supported when following feature are enabled aaa feature

Attribute Name: authentication-port

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: key-type

Attribute Type: enum (0|7)

Attribute Name: secret-key-string

Attribute Type: string

### Netconf edit-config payload

```
<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number> <!-- operation="delete"-->
        <key-type>0</key-type> <!-- operation="delete"-->
        <secret-key-string>WORD</secret-key-string> <!-- operation="delete"-->
      </config>
      <authentication-port>0</authentication-port> <!-- operation="delete"-->
    </server>
  </remote-servers>
</radius>
```

### Command Syntax

```
radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8> key (0|7) WORD auth-port <0-65535>
```

---

## Configure key type

Use this attribute to configure a RADIUS server and specify a UDP port to use for RADIUS accounting messages

This command is supported when following feature are enabled aaa feature

Attribute Name: accounting-port

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: key-type

Attribute Type: enum (0|7)

Attribute Name: secret-key-string

Attribute Type: string

Attribute Name: authentication-port

Attribute Type: uint16

Attribute Range: 0-65535

### Netconf edit-config payload

```
<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    <remote-servers>
      <server>
        <host-address>A.B.C.D</host-address>
        <config>
          <host-address>A.B.C.D</host-address>
          <sequence-number>1</sequence-number> <!-- operation="delete"-->
          <key-type>0</key-type> <!-- operation="delete"-->
          <secret-key-string>WORD</secret-key-string> <!-- operation="delete"-->
          <authentication-port>0</authentication-port> <!-- operation="delete"-->
        </config>
        <accounting-port>0</accounting-port> <!-- operation="delete"-->
      </server>
    </remote-servers>
  </vrf>
</vrfs>
</radius>
```

### Command Syntax

```
radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8> key (0|7) WORD auth-port <0-65535> acct-port <0-65535>
```

---

## Configure server timeout

To represent the timeout configured by the user

This command is supported when following feature are enabled aaa feature

Attribute Name: timeout

Attribute Type: uint8

Default Value: 5

Attribute Range: 1-60

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: key-type

Attribute Type: enum (0|7)

Attribute Name: secret-key-string

Attribute Type: string

Attribute Name: authentication-port

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: accounting-port

Attribute Type: uint16

Attribute Range: 0-65535

### Netconf edit-config payload

```

<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number> <!-- operation="delete"-->
        <key-type>0</key-type> <!-- operation="delete"-->
        <secret-key-string>WORD</secret-key-string> <!-- operation="delete"-->
        <authentication-port>0</authentication-port> <!-- operation="delete"-->
        <accounting-port>0</accounting-port> <!-- operation="delete"-->
      </config>
      <timeout>1</timeout> <!-- operation="delete"-->
    </server>
  </remote-servers>
</radius>

```

## Command Syntax

```
radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8> key (0|7) WORD auth-port <0-65535> acct-port <0-65535> timeout <1-60>
```

---

## Configure server timeout

To represent the timeout configured by the user

This command is supported when following feature are enabled aaa feature

Attribute Name: timeout

Attribute Type: uint8

Default Value: 5

Attribute Range: 1-60

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: key-type

Attribute Type: enum (0|7)

Attribute Name: secret-key-string

Attribute Type: string

Attribute Name: authentication-port

Attribute Type: uint16

Attribute Range: 0-65535

## Netconf edit-config payload

```
<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number> <!-- operation="delete"-->
        <key-type>0</key-type> <!-- operation="delete"-->
        <secret-key-string>WORD</secret-key-string> <!-- operation="delete"-->
        <authentication-port>0</authentication-port> <!-- operation="delete"-->
      </config>
      <timeout>1</timeout> <!-- operation="delete"-->
    </server>
  </remote-servers>
```

```

</vrf>
</vrfs>
</radius>

```

## Command Syntax

```

radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8> key (0|7) WORD auth-port <0-65535> timeout <1-60>

```

---

## Configure server timeout

To represent the timeout configured by the user

This command is supported when following feature are enabled aaa feature

Attribute Name: timeout

Attribute Type: uint8

Default Value: 5

Attribute Range: 1-60

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: key-type

Attribute Type: enum (0|7)

Attribute Name: secret-key-string

Attribute Type: string

## Netconf edit-config payload

```

<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number> <!-- operation="delete"-->
        <key-type>0</key-type> <!-- operation="delete"-->
        <secret-key-string>WORD</secret-key-string> <!-- operation="delete"-->
      </config>
      <timeout>1</timeout> <!-- operation="delete"-->
    </server>
  </remote-servers>
</radius>

```

```
</vrfs>
</radius>
```

## Command Syntax

```
radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8> key (0|7) WORD timeout <1-60>
```

---

## Configure server authentication-port

Use this attribute to configure a RADIUS server and specify a UDP port to use for RADIUS authentication messages

This command is supported when following feature are enabled aaa feature

Attribute Name: authentication-port

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

## Netconf edit-config payload

```
<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number> <!-- operation="delete"-->
      </config>
      <authentication-port>0</authentication-port> <!-- operation="delete"-->
    </server>
  </remote-servers>
</radius>
```

## Command Syntax

```
radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8> auth-port <0-65535>
```

---

## Configure server accounting-port

Use this attribute to configure a RADIUS server and specify a UDP port to use for RADIUS accounting messages

This command is supported when following feature are enabled aaa feature

Attribute Name: accounting-port

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: authentication-port

Attribute Type: uint16

Attribute Range: 0-65535

### Netconf edit-config payload

```
<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number> <!-- operation="delete"-->
        <authentication-port>0</authentication-port> <!-- operation="delete"-->
      </config>
      <accounting-port>0</accounting-port> <!-- operation="delete"-->
    </server>
  </remote-servers>
</radius>
```

### Command Syntax

```
radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8>
auth-port <0-65535> acct-port <0-65535>
```

---

## Configure server timeout

To represent the timeout configured by the user

This command is supported when following feature are enabled aaa feature

Attribute Name: timeout

Attribute Type: uint8

Default Value: 5

Attribute Range: 1-60

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: authentication-port

Attribute Type: uint16

Attribute Range: 0-65535

### Netconf edit-config payload

```
<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number> <!-- operation="delete"-->
        <authentication-port>0</authentication-port> <!-- operation="delete"-->
      </config>
      <timeout>1</timeout> <!-- operation="delete"-->
    </server>
  </remote-servers>
</radius>
```

### Command Syntax

```
radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8>
auth-port <0-65535> timeout <1-60>
```

---

## Configure server timeout

To represent the timeout configured by the user

This command is supported when following feature are enabled aaa feature

Attribute Name: timeout

Attribute Type: uint8

Default Value: 5

Attribute Range: 1-60

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: authentication-port

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: accounting-port

Attribute Type: uint16

Attribute Range: 0-65535

### Netconf edit-config payload

```
<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number> <!-- operation="delete"-->
        <authentication-port>0</authentication-port> <!-- operation="delete"-->
        <accounting-port>0</accounting-port> <!-- operation="delete"-->
      </config>
      <timeout>1</timeout> <!-- operation="delete"-->
    </server>
  </remote-servers>
</radius>
```

### Command Syntax

```
radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8>
auth-port <0-65535> acct-port <0-65535> timeout <1-60>
```

---

## Configure server accounting-port

Use this attribute to configure a RADIUS server and specify a UDP port to use for RADIUS accounting messages

This command is supported when following feature are enabled aaa feature

Attribute Name: accounting-port

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

### Netconf edit-config payload

```
<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number> <!-- operation="delete"-->
      </config>
      <accounting-port>0</accounting-port> <!-- operation="delete"-->
    </server>
  </remote-servers>
</radius>
```

### Command Syntax

```
radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8> acct-port <0-65535>
```

---

## Configure server timeout

To represent the timeout configured by the user

This command is supported when following feature are enabled aaa feature

Attribute Name: timeout

Attribute Type: uint8

Default Value: 5

Attribute Range: 1-60

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: accounting-port

Attribute Type: uint16

Attribute Range: 0-65535

### Netconf edit-config payload

```
<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
```

```

<vrf>
  <vrf-name>management</vrf-name>
  <config>
    <vrf-name>management</vrf-name>
  </config>
</remote-servers>
<server>
  <host-address>A.B.C.D</host-address>
  <config>
    <host-address>A.B.C.D</host-address>
    <sequence-number>1</sequence-number> <!-- operation="delete"-->
    <accounting-port>0</accounting-port> <!-- operation="delete"-->
  </config>
  <timeout>1</timeout> <!-- operation="delete"-->
</server>
</remote-servers>
</vrf>
</vrfs>
</radius>

```

## Command Syntax

```
radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8> acct-port <0-65535> timeout <1-60>
```

---

## Configure server timeout

To represent the timeout configured by the user

This command is supported when following feature are enabled aaa feature

Attribute Name: timeout

Attribute Type: uint8

Default Value: 5

Attribute Range: 1-60

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

## Netconf edit-config payload

```

<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </remote-servers>
  </server>
  <host-address>A.B.C.D</host-address>

```

```

<config>
  <host-address>A.B.C.D</host-address>
  <sequence-number>1</sequence-number> <!-- operation="delete"-->
</config>
  <timeout>1</timeout> <!-- operation="delete"-->
</server>
</remote-servers>
</vrf>
</vrfs>
</radius>

```

### Command Syntax

```
radius-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf management|) seq-num <1-8> timeout <1-60>
```

---

## Configure enable

This attribute is to enable/disable RADIUS debug logging

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```

<radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <debug>
    <config>
      </enable><!-- operation="delete"-->
    </config>
  </debug>
</radius>

```

### Command Syntax

```
debug radius
```

---

## clear radius-server counters (vrf management|)

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```

<radius-clear-all-server-counters xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <vrf-name>management</vrf-name>
</radius-clear-all-server-counters>

```

### Command Syntax

```
clear radius-server counters (vrf management|)
```

---

## clear radius-server host (A.B.C.D|X:X::X:X|HOSTNAME) counters (vrf (management|all)|)

Attribute Name: hostname

Attribute Type: union

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<radius-clear-server-counters xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius">
  <hostname>A.B.C.D</hostname>
  <vrf-name>management</vrf-name>
</radius-clear-server-counters>
```

### Command Syntax

```
clear radius-server host (A.B.C.D|X:X::X:X|HOSTNAME) counters (vrf
(management|all)|)
```

---

## debug radius

### Netconf RPC payload

```
<radius-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius"/>
```

### Command Syntax

```
debug radius
```

---

## no debug radius

### Netconf RPC payload

```
<radius-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-radius"/>
```

### Command Syntax

```
no debug radius
```

---

## IPI-USER-MANAGEMENT

---

### Configure enable

Use this attribute to enable user management debugging information.

Attribute Name: enable

Attribute Type: empty

---

## Netconf edit-config payload

```
<user-management xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-management">
  <debug>
  <config>
    </enable><!-- operation="delete"-->
  </config>
  </debug>
</user-management>
```

## Command Syntax

```
debug user-mgmt
```

---

## Configure disable default user

Use this attribute to prevent default user from being enabled at start up

Attribute Name: disable-default-user

Attribute Type: empty

## Netconf edit-config payload

```
<user-management xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-management">
  <global>
  <config>
    </disable-default-user><!-- operation="delete"-->
  </config>
  </global>
</user-management>
```

## Command Syntax

```
username disable-default
```

---

## Configure username

Login name of the user

Attribute Name: username

Attribute Type: string

Attribute Range: 2-32

## Netconf edit-config payload

```
<user-management xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-management">
  <users>
  <user> <!-- operation="delete"-->
    <username>USERNAME</username>
  <config>
    <username>USERNAME</username>
  </config>
  </user>
</users>
```

---

```
</user-management>
```

## Command Syntax

```
username USERNAME
```

---

## Configure role

Use this attribute to set the user role. Operations that an user is allowed to perform are determined based on the role

Attribute Name: role

Attribute Type: enum (network-admin|network-engineer|network-operator|network-user)

## Netconf edit-config payload

```
<user-management xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-management">
  <users>
    <user>
      <username>USERNAME</username>
      <config>
        <username>USERNAME</username>
      </config>
      <role>network-admin</role> <!-- operation="delete"-->
    </user>
  </users>
</user-management>
```

## Command Syntax

```
username USERNAME role (network-admin|network-engineer|network-operator|network-user)
```

---

## Configure password

Use this attribute to add a user or to change a user password.

Attribute Name: password

Attribute Type: string

Attribute Range: 8-32

Attribute Name: role

Attribute Type: enum (network-admin|network-engineer|network-operator|network-user)

## Netconf edit-config payload

```
<user-management xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-management">
  <users>
    <user>
      <username>USERNAME</username>
      <config>
        <username>USERNAME</username>
        <role>network-admin</role> <!-- operation="delete"-->
      </config>
      <password>PASSWORD</password> <!-- operation="delete"-->
    </user>
  </users>
</user-management>
```

```

</user>
</users>
</user-management>

```

## Command Syntax

```

username USERNAME role (network-admin|network-engineer|network-operator|network-
user) password PASSWORD

```

---

## Configure password hashed

Use this attribute to specify user password in encrypted form. This option is provided for reconfiguring a user password using an earlier encrypted password that was available in running configuration display or get-config payload. Users are advised not to use this option for entering passwords generated in any other method

Attribute Name: password-hashed

Attribute Type: string

Attribute Range: 26-106

Attribute Name: role

Attribute Type: enum (network-admin|network-engineer|network-operator|network-user)

## Netconf edit-config payload

```

<user-management xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-management">
  <users>
    <user>
      <username>USERNAME</username>
      <config>
        <username>USERNAME</username>
        <role>network-admin</role> <!-- operation="delete"-->
      </config>
      <password-hashed>PASSWORD</password-hashed> <!-- operation="delete"-->
    </user>
  </users>
</user-management>

```

## Command Syntax

```

username USERNAME role (network-admin|network-engineer|network-operator|network-
user) password encrypted PASSWORD

```

---

## Configure rbac role

Use this attribute to set the user role. Operations that an user is allowed to perform are determined based on the role

Attribute Name: rbac-role

Attribute Type: string

## Netconf edit-config payload

```

<user-management xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-management">
  <users>
    <user>

```

```

    <username>USERNAME</username>
  </config>
  <username>USERNAME</username>
</config>
<rbac-role>ROLE-NAME</rbac-role> <!-- operation="delete"-->
</user>
</users>
</user-management>

```

### Command Syntax

```
username USERNAME role ROLE-NAME
```

---

## Configure user password

Use this attribute to add a user or to change a user password.

Attribute Name: password

Attribute Type: string

Attribute Range: 8-32

Attribute Name: rbac-role

Attribute Type: string

### Netconf edit-config payload

```

<user-management xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-management">
  <users>
    <user>
      <username>USERNAME</username>
      <config>
        <username>USERNAME</username>
        <rbac-role>ROLE-NAME</rbac-role> <!-- operation="delete"-->
      </config>
      <password>PASSWORD</password> <!-- operation="delete"-->
    </user>
  </users>
</user-management>

```

### Command Syntax

```
username USERNAME role ROLE-NAME password PASSWORD
```

---

## Configure user password-hashed

Use this attribute to specify user password in encrypted form. This option is provided for reconfiguring a user password using an earlier encrypted password that was available in running configuration display or get-config payload. Users are advised not to use this option for entering passwords generated in any other method

Attribute Name: password-hashed

Attribute Type: string

Attribute Range: 26-106

Attribute Name: rbac-role

Attribute Type: string

### Netconf edit-config payload

```
<user-management xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-management">
  <users>
    <user>
      <username>USERNAME</username>
      <config>
        <username>USERNAME</username>
        <rbac-role>ROLE-NAME</rbac-role> <!-- operation="delete"-->
      </config>
      <password-hashed>PASSWORD</password-hashed> <!-- operation="delete"-->
    </user>
  </users>
</user-management>
```

### Command Syntax

```
username USERNAME role ROLE-NAME password encrypted PASSWORD
```

---

## Configure user password

Use this attribute to add a user or to change a user password.

Attribute Name: password

Attribute Type: string

Attribute Range: 8-32

### Netconf edit-config payload

```
<user-management xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-management">
  <users>
    <user>
      <username>USERNAME</username>
      <config>
        <username>USERNAME</username>
      </config>
      <password>PASSWORD</password> <!-- operation="delete"-->
    </user>
  </users>
</user-management>
```

### Command Syntax

```
username USERNAME password PASSWORD
```

---

## Configure user password-hashed

Use this attribute to specify user password in encrypted form. This option is provided for reconfiguring a user password using an earlier encrypted password that was available in running configuration display or get-config payload. Users are advised not to use this option for entering passwords generated in any other method

Attribute Name: password-hashed

Attribute Type: string

Attribute Range: 26-106

### Netconf edit-config payload

```
<user-management xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-management">
  <users>
    <user>
      <username>USERNAME</username>
      <config>
        <username>USERNAME</username>
      </config>
      <password-hashed>PASSWORD</password-hashed> <!-- operation="delete"-->
    </user>
  </users>
</user-management>
```

### Command Syntax

```
username USERNAME password encrypted PASSWORD
```

---

## debug user-mgmt

### Netconf RPC payload

```
<user-management-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-user-management"/>
```

### Command Syntax

```
debug user-mgmt
```

---

## no debug user-mgmt

### Netconf RPC payload

```
<user-management-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-user-management"/>
```

### Command Syntax

```
no debug user-mgmt
```

---

## IPI-SSH

---

### Configure enable

Use this attribute to enable ssh debugging configurations

Attribute Name: enable

Attribute Type: empty

---

## Netconf edit-config payload

```
<ssh-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <debug>
  <config>
    </enable><!-- operation="delete"-->
  </config>
</debug>
</ssh-server>
```

## Command Syntax

```
debug ssh server
```

---

## Configure vrf name

Use this attribute to enable the SSH server.

Attribute Name: enable

Attribute Type: boolean

## Netconf edit-config payload

```
<ssh-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <vrfs>
  <vrf>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
    <enable>true</enable> <!-- operation="delete"-->
  </vrf>
</vrfs>
</ssh-server>
```

## Command Syntax

```
feature ssh (vrf (NAME|management) |)
```

---

## Configure vrf enable

Use this attribute to enable the SSH server.

Attribute Name: enable

Attribute Type: boolean

## Netconf edit-config payload

```
<ssh-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <vrfs>
  <vrf>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
  </vrf>
</vrfs>
```

```

    <enable>true</enable> <!-- operation="delete"-->
  </vrf>
</vrfs>
</ssh-server>

```

## Command Syntax

```
no feature ssh (vrf (NAME|management)|)
```

---

## Configure port

VRF Name associated with this instance

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: port

Attribute Type: uint32

Attribute Range: 1024-65535

## Netconf edit-config payload

```

<ssh-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
        <port>1024</port> <!-- operation="delete"-->
      </config>
    </vrf>
  </vrfs>
</ssh-server>

```

## Command Syntax

```
ssh server port <1024-65535> (vrf (NAME|management)|)
```

---

## Configure max login attempts

VRF Name associated with this instance

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: max-login-attempts

Attribute Type: uint8

Default Value: 3

Attribute Range: 1-3

## Netconf edit-config payload

```
<ssh-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
```

```

<vrfs>
<vrf>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
    <max-login-attempts>1</max-login-attempts> <!-- operation="delete"-->
  </config>
</vrf>
</vrfs>
</ssh-server>

```

### Command Syntax

```
ssh login-attempts <1-3> (vrf (NAME|management) |)
```

---

## Configure session limit

VRF Name associated with this instance

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: session-limit

Attribute Type: uint8

Attribute Range: 1-40

### Netconf edit-config payload

```

<ssh-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
<vrfs>
<vrf>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
    <session-limit>1</session-limit> <!-- operation="delete"-->
  </config>
</vrf>
</vrfs>
</ssh-server>

```

### Command Syntax

```
ssh server session-limit <1-40> (vrf (NAME|management) |)
```

---

## Configure default algorithm

VRF Name associated with this instance

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: default-algorithm

Attribute Type: empty

## Netconf edit-config payload

```
<ssh-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
        </default-algorithm><!-- operation="delete"-->
      </config>
    </vrf>
  </vrfs>
</ssh-server>
```

## Command Syntax

```
ssh server default algorithm (vrf (NAME|management)|)
```

---

## Configure chacha20 poly1305

Use this attribute to set the ChaCha20-Poly1305 Cipher

This command is supported when following feature are enabled ssh server feature

Attribute Name: chacha20-poly1305

Attribute Type: empty

Attribute Name: aes128-ctr

Attribute Type: empty

Attribute Name: aes192-ctr

Attribute Type: empty

Attribute Name: aes256-ctr

Attribute Type: empty

Attribute Name: aes128-cbc

Attribute Type: empty

Attribute Name: aes192-cbc

Attribute Type: empty

Attribute Name: aes256-cbc

Attribute Type: empty

Attribute Name: triple-des-cbc

Attribute Type: empty

Attribute Name: rijndael-cbc

Attribute Type: empty

Attribute Name: aes128-gcm

Attribute Type: empty

Attribute Name: aes256-gcm

Attribute Type: empty

### Netconf edit-config payload

```
<ssh-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <encryption-algorithms>
    <config>
      </aes128-ctr><!-- operation="delete"-->
      </aes192-ctr><!-- operation="delete"-->
      </aes256-ctr><!-- operation="delete"-->
      </aes128-cbc><!-- operation="delete"-->
      </aes192-cbc><!-- operation="delete"-->
      </aes256-cbc><!-- operation="delete"-->
      </triple-des-cbc><!-- operation="delete"-->
      </rijndael-cbc><!-- operation="delete"-->
      </aes128-gcm><!-- operation="delete"-->
      </aes256-gcm><!-- operation="delete"-->
      </chacha20-poly1305><!-- operation="delete"-->
    </config>
  </encryption-algorithms>
</ssh-server>
```

### Command Syntax

```
ssh server algorithm encryption { aes128-ctr| aes192-ctr| aes256-ctr| aes128-cbc|
  aes192-cbc| aes256-cbc| 3des-cbc| rijndael-cbc| aes128-gcm| aes256-gcm| chacha20-
  poly1305 } (vrf (NAME|management)|)
```

---

## Configure curve25519 sha256 libssh org

Use this attribute to set the Curve25519 SHA256 @libssh.org algorithm

This command is supported when following feature are enabled ssh server feature

Attribute Name: curve25519-sha256-libssh-org

Attribute Type: empty

Attribute Name: diffie-hellman-group1-sha1

Attribute Type: empty

Attribute Name: diffie-hellman-group14-sha1

Attribute Type: empty

Attribute Name: diffie-hellman-group14-sha256

Attribute Type: empty

Attribute Name: diffie-hellman-group16-sha512

Attribute Type: empty

Attribute Name: diffie-hellman-group18-sha512

Attribute Type: empty

Attribute Name: diffie-hellman-group-exchange-sha1

Attribute Type: empty

Attribute Name: diffie-hellman-group-exchange-sha256

Attribute Type: empty

Attribute Name: ecdh-sha2-nistp256

Attribute Type: empty

Attribute Name: ecdh-sha2-nistp384

Attribute Type: empty

Attribute Name: ecdh-sha2-nistp521

Attribute Type: empty

Attribute Name: curve25519-sha256

Attribute Type: empty

### Netconf edit-config payload

```
<ssh-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <kex-algorithms>
    <config>
      </diffie-hellman-group1-sha1><!-- operation="delete"-->
      </diffie-hellman-group14-sha1><!-- operation="delete"-->
      </diffie-hellman-group14-sha256><!-- operation="delete"-->
      </diffie-hellman-group16-sha512><!-- operation="delete"-->
      </diffie-hellman-group18-sha512><!-- operation="delete"-->
      </diffie-hellman-group-exchange-sha1><!-- operation="delete"-->
      </diffie-hellman-group-exchange-sha256><!-- operation="delete"-->
      </ecdh-sha2-nistp256><!-- operation="delete"-->
      </ecdh-sha2-nistp384><!-- operation="delete"-->
      </ecdh-sha2-nistp521><!-- operation="delete"-->
      </curve25519-sha256><!-- operation="delete"-->
      </curve25519-sha256-libssh-org><!-- operation="delete"-->
    </config>
  </kex-algorithms>
</ssh-server>
```

---

## Command Syntax

```
ssh server algorithm kex { diffie-hellman-group1-sha1| diffie-hellman-group14-sha1|
diffie-hellman-group14-sha256| diffie-hellman-group16-sha512| diffie-hellman-
group18-sha512| diffie-hellman-group-exchange-sha1| diffie-hellman-group-
exchange-sha256| ecdh-sha2-nistp256| ecdh-sha2-nistp384| ecdh-sha2-nistp521|
curve25519-sha256| curve25519-sha256-libssh-org } (vrf (NAME|management)|)
```

---

## Configure umac 128 etm

Use this attribute to set the UMAC-128-ETM @openssh.com MAC

This command is supported when following feature are enabled ssh server feature

Attribute Name: umac-128-etm

Attribute Type: empty

Attribute Name: hmac-sha1

Attribute Type: empty

Attribute Name: hmac-sha1-96

Attribute Type: empty

Attribute Name: hmac-sha2-256

Attribute Type: empty

Attribute Name: hmac-sha2-512

Attribute Type: empty

Attribute Name: hmac-md5

Attribute Type: empty

Attribute Name: hmac-md5-96

Attribute Type: empty

Attribute Name: umac-64

Attribute Type: empty

Attribute Name: umac-128

Attribute Type: empty

Attribute Name: hmac-sha1-etm

Attribute Type: empty

Attribute Name: hmac-sha1-96-etm

Attribute Type: empty

Attribute Name: hmac-sha2-256-etm

Attribute Type: empty

Attribute Name: hmac-sha2-512-etm

Attribute Type: empty

Attribute Name: hmac-md5-etm

Attribute Type: empty

Attribute Name: hmac-md5-96-etm

Attribute Type: empty

Attribute Name: umac-64-etm

Attribute Type: empty

### Netconf edit-config payload

```
<ssh-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <mac-algorithms>
    <config>
      </hmac-sha1><!-- operation="delete"-->
      </hmac-sha1-96><!-- operation="delete"-->
      </hmac-sha2-256><!-- operation="delete"-->
      </hmac-sha2-512><!-- operation="delete"-->
      </hmac-md5><!-- operation="delete"-->
      </hmac-md5-96><!-- operation="delete"-->
      </umac-64><!-- operation="delete"-->
      </umac-128><!-- operation="delete"-->
      </hmac-sha1-etm><!-- operation="delete"-->
      </hmac-sha1-96-etm><!-- operation="delete"-->
      </hmac-sha2-256-etm><!-- operation="delete"-->
      </hmac-sha2-512-etm><!-- operation="delete"-->
      </hmac-md5-etm><!-- operation="delete"-->
      </hmac-md5-96-etm><!-- operation="delete"-->
      </umac-64-etm><!-- operation="delete"-->
      </umac-128-etm><!-- operation="delete"-->
    </config>
  </mac-algorithms>
</ssh-server>
```

### Command Syntax

```
ssh server algorithm mac { hmac-sha1| hmac-sha1-96| hmac-sha2-256| hmac-sha2-512|
  hmac-md5| hmac-md5-96| umac-64| umac-128| hmac-sha1-etm| hmac-sha1-96-etm| hmac-
  sha2-256-etm| hmac-sha2-512-etm| hmac-md5-etm| hmac-md5-96-etm| umac-64-etm|
  umac-128-etm } (vrf (NAME|management)|)
```

## Configure public key

Use this attribute to set the ssh public-key

Attribute Name: public-key

Attribute Type: string

---

## Netconf edit-config payload

```
<user-management xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-management">
  <users>
    <user>
      <username>USERNAME</username>
      <config>
        <username>USERNAME</username>
      </config>
      <ssh-keys xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
        <config>
          <public-key>LINE</public-key> <!-- operation="delete"-->
        </config>
      </ssh-keys>
    </user>
  </users>
</user-management>
```

## Command Syntax

```
username USERNAME sshkey LINE
```

---

## debug ssh server

### Netconf RPC payload

```
<ssh-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh"/>
```

### Command Syntax

```
debug ssh server
```

---

## no debug ssh server

### Netconf RPC payload

```
<ssh-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh"/>
```

### Command Syntax

```
no debug ssh server
```

---

## clear ssh hosts

### Netconf RPC payload

```
<ssh-clear-hosts xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh"/>
```

### Command Syntax

```
clear ssh hosts
```

---

## ssh keygen host dsa (vrf (NAME|management)) (force|)

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: force

Attribute Type: boolean

Default Value: false

### Netconf RPC payload

```
<ssh-generate-server-dsa-key xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <vrf-name>NAME</vrf-name>
  <force>true</force/>
</ssh-generate-server-dsa-key>
```

### Command Syntax

```
ssh keygen host dsa (vrf (NAME|management)) (force|)
```

---

## ssh keygen host rsa (length <1024-4096>|) (vrf (NAME|management)) (force|)

Attribute Name: length

Attribute Type: uint32

Default Value: 2048

Attribute Range: 1024-4096

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: force

Attribute Type: boolean

Default Value: false

### Netconf RPC payload

```
<ssh-generate-server-rsa-key xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <length>1024</length>
  <vrf-name>NAME</vrf-name>
  <force>true</force/>
</ssh-generate-server-rsa-key>
```

### Command Syntax

```
ssh keygen host rsa (length <1024-4096>|) (vrf (NAME|management)) (force|)
```

---

## ssh keygen host ecdsa (length (256|384|521)|) (vrf (NAME|management|)) (force|)

Attribute Name: length

Attribute Type: enum (256|384|521)

Default Value: 521

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: force

Attribute Type: boolean

Default Value: false

### Netconf RPC payload

```
<ssh-generate-server-ecdsa-key xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <length>521</length>
  <vrf-name>NAME</vrf-name>
  <force>true</force/>
</ssh-generate-server-ecdsa-key>
```

### Command Syntax

```
ssh keygen host ecdsa (length (256|384|521)|) (vrf (NAME|management|)) (force|)
```

---

## ssh keygen host ed25519 (vrf (NAME|management|)) (force|)

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: force

Attribute Type: boolean

Default Value: false

### Netconf RPC payload

```
<ssh-generate-server-ed25519-key xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <vrf-name>NAME</vrf-name>
  <force>true</force/>
</ssh-generate-server-ed25519-key>
```

### Command Syntax

```
ssh keygen host ed25519 (vrf (NAME|management|)) (force|)
```

---

## **clear ssh host-key ((dsa|rsa|ecdsa|ed25519)) (vrf (NAME|management))**

Attribute Name: type

Attribute Type: enum (all-keys|dsa|rsa|ecdsa|ed25519)

Default Value: all-keys

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

### **Netconf RPC payload**

```
<ssh-clear-server-keys xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <type>all-keys</type>
  <vrf-name>NAME</vrf-name>
</ssh-clear-server-keys>
```

### **Command Syntax**

```
clear ssh host-key ((dsa|rsa|ecdsa|ed25519)) (vrf (NAME|management))
```

---

## **username USERNAME keypair rsa (length <1024-4096>|) (force|)**

Attribute Name: user-name

Attribute Type: string

Attribute Name: length

Attribute Type: uint32

Default Value: 4096

Attribute Range: 1024-4096

Attribute Name: force

Attribute Type: boolean

Default Value: false

### **Netconf RPC payload**

```
<ssh-generate-user-rsa-key xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <user-name>USERNAME</user-name>
  <length>1024</length>
  <force>true</force/>
</ssh-generate-user-rsa-key>
```

### **Command Syntax**

```
username USERNAME keypair rsa (length <1024-4096>|) (force|)
```

---

## **username USERNAME keypair dsa (force|)**

Attribute Name: user-name

Attribute Type: string

Attribute Name: force

Attribute Type: boolean

Default Value: false

### Netconf RPC payload

```
<ssh-generate-user-dsa-key xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <user-name>USERNAME</user-name>
  <force>true</force/>
</ssh-generate-user-dsa-key>
```

### Command Syntax

```
username USERNAME keypair dsa (force|)
```

---

## clear ssh keypair user USERNAME

Attribute Name: user-name

Attribute Type: string

### Netconf RPC payload

```
<ssh-clear-user-keys xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ssh">
  <user-name>USERNAME</user-name>
</ssh-clear-user-keys>
```

### Command Syntax

```
clear ssh keypair user USERNAME
```

---

## IPI-TELNET

---

### Configure enable

Use this attribute to enable telnet debugging configurations

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```
<telnet-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-telnet">
  <debug>
  <config>
    </enable><!-- operation="delete"-->
  </config>
</debug>
</telnet-server>
```

### Command Syntax

```
debug telnet server
```

---

## Configure vrf name

Use this attribute to enable the Telnet server.

Attribute Name: enable

Attribute Type: boolean

### Netconf edit-config payload

```
<telnet-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-telnet">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <enable>true</enable> <!-- operation="delete"-->
    </vrf>
  </vrfs>
</telnet-server>
```

### Command Syntax

```
feature telnet (vrf (NAME|management) |)
```

---

## Configure vrf enable

Use this attribute to enable the Telnet server.

Attribute Name: enable

Attribute Type: boolean

### Netconf edit-config payload

```
<telnet-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-telnet">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <enable>true</enable> <!-- operation="delete"-->
    </vrf>
  </vrfs>
</telnet-server>
```

### Command Syntax

```
no feature telnet (vrf (NAME|management) |)
```

---

## Configure port

VRF Name associated with this instance

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: port

Attribute Type: uint32

Attribute Range: 1024-65535

### Netconf edit-config payload

```
<telnet-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-telnet">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
        <port>1024</port> <!-- operation="delete"-->
      </config>
    </vrf>
  </vrfs>
</telnet-server>
```

### Command Syntax

```
telnet server port <1024-65535> (vrf (NAME|management) |)
```

---

## Configure session limit

VRF Name associated with this instance

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: session-limit

Attribute Type: uint8

Attribute Range: 1-40

### Netconf edit-config payload

```
<telnet-server xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-telnet">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
        <session-limit>1</session-limit> <!-- operation="delete"-->
      </config>
    </vrf>
  </vrfs>
</telnet-server>
```

### Command Syntax

```
telnet server session-limit <1-40> (vrf (NAME|management) |)
```

---

## debug telnet server

### Netconf RPC payload

```
<telnet-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-telnet"/>
```

### Command Syntax

```
debug telnet server
```

---

## no debug telnet server

### Netconf RPC payload

```
<telnet-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-telnet"/>
```

### Command Syntax

```
no debug telnet server
```

---

## IPI-NTP

---

### Configure feature enable

Use this attribute to enable or disable NTP feature.

Attribute Name: feature-enable

Attribute Type: boolean

### Netconf edit-config payload

```
<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
      <feature-enable>true</feature-enable> <!-- operation="delete"-->
    </vrf>
  </vrfs>
</ntp>
```

### Command Syntax

```
feature ntp (vrf (management|NAME) |)
```

---

### Configure vrf name

Use this attribute to enable or disable NTP feature.

Attribute Name: feature-enable

Attribute Type: boolean

### Netconf edit-config payload

```
<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
      <feature-enable>true</feature-enable> <!-- operation="delete"-->
    </vrf>
  </vrfs>
</ntp>
```

### Command Syntax

```
no feature ntp (vrf (management|NAME)|)
```

---

## Configure enable ntp

Use this attribute to enable or disable NTP server

Attribute Name: enable-ntp

Attribute Type: boolean

### Netconf edit-config payload

```
<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
      <enable-ntp>true</enable-ntp> <!-- operation="delete"-->
    </vrf>
  </vrfs>
</ntp>
```

### Command Syntax

```
ntp enable (vrf (management|NAME)|)
```

---

## Configure vrf enable-ntp

Use this attribute to enable or disable NTP server

Attribute Name: enable-ntp

Attribute Type: boolean

---

## Netconf edit-config payload

```
<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
      <enable-ntp>true</enable-ntp> <!-- operation="delete"-->
    </vrf>
  </vrfs>
</ntp>
```

## Command Syntax

```
no ntp enable (vrf (management|NAME) |)
```

---

## Configure enable logging

Use this attribute to specify the vrf for which ntp feature is enabled

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: enable-logging

Attribute Type: empty

## Netconf edit-config payload

```
<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
        </enable-logging><!-- operation="delete"-->
      </config>
    </vrf>
  </vrfs>
</ntp>
```

## Command Syntax

```
ntp logging (vrf (management|NAME) |)
```

---

## Configure enable local master

Use this attribute to configure the device as an NTP server.

Attribute Name: enable-local-master

Attribute Type: empty

**Netconf edit-config payload**

```

<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <ref-clock-master>
    <config>
      </enable-local-master>
    </config>
  </ref-clock-master>
</ntp>

```

**Command Syntax**

```
ntp master (vrf (management|NAME) |)
```

**Configure local stratum**

Use this attribute to configure stratum level for a NTP server.

Attribute Name: local-stratum

Attribute Type: uint8

Attribute Range: 1-15

**Netconf edit-config payload**

```

<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <ref-clock-master>
    <config>
      <local-stratum>1</local-stratum> <!-- operation="delete"-->
    </config>
  </ref-clock-master>
</ntp>

```

**Command Syntax**

```
ntp master stratum <1-15> (vrf (management|NAME) |)
```

---

## Configure enable ntp auth

Use this attribute to enable NTP authentication.

Attribute Name: enable-ntp-auth

Attribute Type: empty

### Netconf edit-config payload

```
<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    <authentication>
      <config>
        </enable-ntp-auth><!-- operation="delete"-->
      </config>
    </authentication>
  </vrf>
</vrfs>
</ntp>
```

### Command Syntax

```
ntp authenticate (vrf (management|NAME) |)
```

---

## Configure ntp trusted keys

Use this attribute to configure one or more trusted authentication keys. If a key is trusted, the device will synchronize with a system that specifies this key in its NTP packets

Attribute Name: ntp-trusted-keys

Attribute Type: uint32

Attribute Range: 1-65535

### Netconf edit-config payload

```
<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    <authentication>
      <config>
        <ntp-trusted-keys>1</ntp-trusted-keys> <!-- operation="delete"-->
      </config>
    </authentication>
  </vrf>
```

```
</vrf>
</ntp>
```

## Command Syntax

```
ntp trusted-key <1-65535> (vrf (management|NAME) |)
```

---

## Configure ntp request key

Use this to attribute to configure request key which shall be used as password for ntpdc utility.

Attribute Name: ntp-request-key

Attribute Type: uint32

Attribute Range: 1-65534

## Netconf edit-config payload

```
<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <vrf>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrf>
  <authentication>
    <config>
      <ntp-request-key>1</ntp-request-key> <!-- operation="delete"-->
    </config>
  </authentication>
</ntp>
```

## Command Syntax

```
ntp request-key <1-65534> (vrf (management|NAME) |)
```

---

## Configure key id

Use this attribute to set an NTP authentication key.

Attribute Name: key-id

Attribute Type: uint32

Attribute Range: 1-65535

Attribute Name: key-value

Attribute Type: string

Attribute Name: key-type

Attribute Type: enum (0|7)

## Netconf edit-config payload

```
<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
```

```

<vrfs>
<vrf>
  <vrf-name>management</vrf-name>
  <config>
    <vrf-name>management</vrf-name>
  </config>
<authentication>
<ntp-keys>
<ntp-key> <!-- operation="delete"-->
  <key-id>1</key-id>
  <config>
    <key-id>1</key-id>
    <key-value>WORD</key-value>
    <key-type>1</key-type>
  </config>
</ntp-key>
</ntp-keys>
</authentication>
</vrf>
</vrfs>
</ntp>

```

## Command Syntax

```
ntp authentication-key <1-65535> md5 WORD 7 (vrf (management|NAME) |)
```

---

## Configure key value

Use this attribute to set an NTP authentication key.

Attribute Name: key-id

Attribute Type: uint32

Attribute Range: 1-65535

Attribute Name: key-value

Attribute Type: string

Attribute Name: key-type

Attribute Type: enum (0|7)

## Netconf edit-config payload

```

<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
<vrfs>
<vrf>
  <vrf-name>management</vrf-name>
  <config>
    <vrf-name>management</vrf-name>
  </config>
<authentication>
<ntp-keys>
<ntp-key> <!-- operation="delete"-->

```

```

    <key-id>1</key-id>
  <config>
    <key-id>1</key-id>
    <key-value>WORD</key-value>
    <key-type>0</key-type>
  </config>
</ntp-key>
</ntp-keys>
</authentication>
</vrf>
</vrfs>
</ntp>

```

## Command Syntax

```
ntp authentication-key <1-65535> md5 WORD (vrf (management|NAME) |)
```

---

## Configure prefer

preferred NTP server/peer

Attribute Name: prefer

Attribute Type: empty

Attribute Name: auth-key

Attribute Type: uint32

Default Value: 65535

Attribute Range: 1-65535

Attribute Name: minpoll

Attribute Type: uint16

Default Value: 4

Attribute Range: 4-16

Attribute Name: maxpoll

Attribute Type: uint16

Default Value: 6

Attribute Range: 4-16

## Netconf edit-config payload

```

<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <servers>
    <server>

```

```

<server-address>A.B.C.D</server-address>
<config>
  <server-address>A.B.C.D</server-address>
  <auth-key>1</auth-key> <!-- operation="delete"-->
  <minpoll>4</minpoll> <!-- operation="delete"-->
  <maxpoll>4</maxpoll> <!-- operation="delete"-->
</config>
  </prefer><!-- operation="delete"-->
</server>
</servers>
</vrf>
</vrfs>
</ntp>

```

## Command Syntax

```

ntp server (A.B.C.D|X:X::X:X|HOSTNAME) { key <1-65535>| minpoll <4-16>| maxpoll <4-16>| prefer } (vrf (management|NAME)|)

```

---

## Configure server address

Use this attribute to set the NTP server IP address or hostname

Attribute Name: server-address

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```

<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <servers>
    <server>
      <server-address>A.B.C.D</server-address>
      <config>
        <server-address>A.B.C.D</server-address>
      </config>
    </server>
  </servers>
</ntp>

```

## Command Syntax

```

ntp server (A.B.C.D|X:X::X:X|HOSTNAME) (vrf (management|NAME)|)

```

---

## Configure peer address

preferred NTP server/peer

Attribute Name: prefer

Attribute Type: empty

Attribute Name: auth-key

Attribute Type: uint32

Default Value: 65535

Attribute Range: 1-65535

Attribute Name: minpoll

Attribute Type: uint16

Default Value: 4

Attribute Range: 4-16

Attribute Name: maxpoll

Attribute Type: uint16

Default Value: 6

Attribute Range: 4-16

### Netconf edit-config payload

```
<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <peers>
    <peer>
      <peer-address>A.B.C.D</peer-address>
      <config>
        <peer-address>A.B.C.D</peer-address>
        <auth-key>1</auth-key> <!-- operation="delete"-->
        <minpoll>4</minpoll> <!-- operation="delete"-->
        <maxpoll>4</maxpoll> <!-- operation="delete"-->
      </config>
    </peer>
  </peers>
</ntp>
```

### Command Syntax

```
ntp peer (A.B.C.D|X:X::X:X|HOSTNAME) { key <1-65535>| minpoll <4-16>| maxpoll <4-16>| prefer } (vrf (management|NAME)|)
```

---

## Configure peer peer-address

Use this attribute to set the NTP peer IP address or hostname

Attribute Name: peer-address

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```
<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <peers>
    <peer>
      <peer-address>A.B.C.D</peer-address>
      <config>
        <peer-address>A.B.C.D</peer-address>
      </config>
    </peer>
  </peers>
</ntp>
```

### Command Syntax

```
ntp peer (A.B.C.D|X:X::X:X|HOSTNAME) (vrf (management|NAME) |)
```

---

## Configure minimum pkt spacing

Use this attribute to specify the minimum packet spacing to be permitted

Attribute Name: minimum-pkt-spacing

Attribute Type: uint16

Attribute Range: 1-65535

### Netconf edit-config payload

```
<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <rate-limiting>
    <config>

```

```

        <minimum-pkt-spacing>1</minimum-pkt-spacing> <!-- operation="delete"-->
</config>
</rate-limiting>
</vrf>
</vrfs>
</ntp>

```

## Command Syntax

```
ntp discard { minimum <1-65535> } (vrf (management|NAME)|)
```

---

## Configure netmask

use this attribute to specify the allowed NTP client IP network mask

Attribute Name: netmask

Attribute Type: union

## Netconf edit-config payload

```

<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
<vrfs>
<vrf>
  <vrf-name>management</vrf-name>
  <config>
    <vrf-name>management</vrf-name>
  </config>
<access-control-entries>
<access-control-entry>
  <client-ip-address>CML_IP_ADDR_T</client-ip-address>
  <config>
    <client-ip-address>CML_IP_ADDR_T</client-ip-address>
  </config>
  <netmask>NTP_CLIENT_IP_NET_MASK_T</netmask>
</access-control-entry>
</access-control-entries>
</vrf>
</vrfs>
</ntp>

```

## Command Syntax

```
ntp allow (A.B.C.D|X:X::X:X) mask (A.B.C.D|<1-128>) (vrf (management|NAME)|)
```

---

## Configure access options

use this attribute to specify the allowed access options for NTP client

Attribute Name: access-options

Attribute Type: bits (kod|nopeer|noserve|noquery|nomodify|notrap|limited)

## Netconf edit-config payload

```
<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
```

```

<vrfs>
<vrf>
  <vrf-name>management</vrf-name>
  <config>
    <vrf-name>management</vrf-name>
  </config>
<access-control-entries>
<access-control-entry>
  <client-ip-address>CML_IP_ADDR_T</client-ip-address>
  <config>
    <client-ip-address>CML_IP_ADDR_T</client-ip-address>
  </config>
  <access-options>kod</access-options> <!-- operation="delete"-->
</access-control-entry>
</access-control-entries>
</vrf>
</vrfs>
</ntp>

```

## Command Syntax

```

ntp allow {kod|nopeer|noserve|noquery|nomodify|notrap|limited} (vrf
(management|NAME) |)

```

---

## Configure client ip address

use this attribute to specify the allowed access options for NTP client

Attribute Name: access-options

Attribute Type: bits (kod|nopeer|noserve|noquery|nomodify|notrap|limited)

Attribute Name: netmask

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```

<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
<vrfs>
<vrf>
  <vrf-name>management</vrf-name>
  <config>
    <vrf-name>management</vrf-name>
  </config>
<access-control-entries>
<access-control-entry>
  <client-ip-address>CML_IP_ADDR_T</client-ip-address>
  <config>
    <client-ip-address>CML_IP_ADDR_T</client-ip-address>
    <netmask>NTP_CLIENT_IP_NET_MASK_T</netmask>
  </config>
  <access-options>kod</access-options> <!-- operation="delete"-->
</access-control-entry>

```

```

</access-control-entries>
</vrf>
</vrfs>
</ntp>

```

## Command Syntax

```

ntp allow mask {kod|nopeer|noserve|noquery|nomodify|notrap|limited} (vrf
(management|NAME) |)

```

---

## Configure access-control-entry client-ip-address

use this attribute to specify the allowed NTP client IP address

Attribute Name: client-ip-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
<vrfs>
<vrf>
  <vrf-name>management</vrf-name>
  <config>
    <vrf-name>management</vrf-name>
  </config>
<access-control-entries>
<access-control-entry>
  <client-ip-address>CML_IP_ADDR_T</client-ip-address>
  <config>
    <client-ip-address>CML_IP_ADDR_T</client-ip-address>
  </config>
</access-control-entry>
</access-control-entries>
</vrf>
</vrfs>
</ntp>

```

## Command Syntax

```

ntp allow (vrf (management|NAME) |)

```

---

## Configure enable

Use this attribute to enable NTP debug logs

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```

<ntp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
<debug>
<config>

```

```
</enable><!-- operation="delete"-->
</config>
</debug>
</ntp>
```

## Command Syntax

```
debug ntp
```

---

## clear ntp statistics (all-peers|io|local|memory)

Attribute Name: statistics-type

Attribute Type: enum (all-peers|io|local|memory)

### Netconf RPC payload

```
<ntp-clear-statistics xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp">
  <statistics-type>all-peers</statistics-type>
</ntp-clear-statistics>
```

## Command Syntax

```
clear ntp statistics (all-peers|io|local|memory)
```

---

## ntp sync-retry (vrf (management|NAME)|)

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<ntp-retry-server-synchronization xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-ntp">
  <vrf-name>management</vrf-name>
</ntp-retry-server-synchronization>
```

## Command Syntax

```
ntp sync-retry (vrf (management|NAME)|)
```

---

## debug ntp

### Netconf RPC payload

```
<ntp-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp"/>
```

## Command Syntax

```
debug ntp
```

---

## no debug ntp

### Netconf RPC payload

```
<ntp-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ntp"/>
```

## Command Syntax

```
no debug ntp
```

---

## IPI-AAA

---

### Configure authentication method rule

Use this attribute to set AAA methods for authentication

Attribute Name: authentication-method-rule

Attribute Type: string

#### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
      <authentication-method-rule>LINE</authentication-method-rule> <!--
operation="delete"-->
    </vrf>
  </vrfs>
</aaa>
```

## Command Syntax

```
aaa authentication login default (vrf (management|NAME)|) group LINE
```

---

### Configure vrf name

Use this attribute to set AAA methods for authentication

Attribute Name: authentication-method-rule

Attribute Type: string

#### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
      <authentication-method-rule>LINE</authentication-method-rule> <!--
operation="delete"-->
    </vrf>
  </vrfs>
</aaa>
```

```
</aaa>
```

## Command Syntax

```
aaa authentication login default (vrf (management|NAME)|) local
```

---

## Configure vrf authentication-method-rule

Use this attribute to set AAA methods for authentication

Attribute Name: authentication-method-rule

Attribute Type: string

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
      <authentication-method-rule>LINE</authentication-method-rule> <!--
operation="delete"-->
    </vrf>
  </vrfs>
</aaa>
```

## Command Syntax

```
aaa authentication login default (vrf (management|NAME)|) none
```

---

## Configure vrf authentication-method-rule

Use this attribute to set AAA methods for authentication

Attribute Name: authentication-method-rule

Attribute Type: string

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
      <authentication-method-rule>LINE</authentication-method-rule> <!--
operation="delete"-->
    </vrf>
  </vrfs>
</aaa>
```

---

## Command Syntax

```
aaa authentication login default (vrf (management|NAME)|) local none
```

---

## Configure accounting method rule

Use this attribute to set AAA methods for accounting

Attribute Name: accounting-method-rule

Attribute Type: string

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
      <accounting-method-rule>LINE</accounting-method-rule> <!-- operation="delete"-->
    </vrf>
  </vrfs>
</aaa>
```

## Command Syntax

```
aaa accounting default (vrf (management|NAME)|) group LINE
```

---

## Configure vrf accounting-method-rule

Use this attribute to set AAA methods for accounting

Attribute Name: accounting-method-rule

Attribute Type: string

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
      <accounting-method-rule>LINE</accounting-method-rule> <!-- operation="delete"-->
    </vrf>
  </vrfs>
</aaa>
```

## Command Syntax

```
aaa accounting default (vrf (management|NAME)|) local
```

---

## Configure authorization method rule

Use this attribute to set AAA methods for authorization

Attribute Name: authorization-method-rule

Attribute Type: string

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
      <authorization-method-rule>LINE</authorization-method-rule> <!--
operation="delete"-->
    </vrf>
  </vrfs>
</aaa>
```

### Command Syntax

```
aaa authorization default (vrf (management|NAME)|) group LINE
```

---

## Configure vrf authorization-method-rule

Use this attribute to set AAA methods for authorization

Attribute Name: authorization-method-rule

Attribute Type: string

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
      <authorization-method-rule>LINE</authorization-method-rule> <!--
operation="delete"-->
    </vrf>
  </vrfs>
</aaa>
```

### Command Syntax

```
aaa authorization default (vrf (management|NAME)|) local
```

---

## Configure error enable

This is to enable error message on login failures

Attribute Name: error-enable

Attribute Type: uint8

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
      </error-enable><!-- operation="delete"-->
    </vrf>
  </vrfs>
</aaa>
```

### Command Syntax

```
aaa authentication login error-enable (vrf (management|NAME) |)
```

---

## Configure enable fallback

VRF Name associated with this instance

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: enable-fallback

Attribute Type: empty

Attribute Name: non-existent

Attribute Type: boolean

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
        </enable-fallback>
        <non-existent>true</non-existent>
      </config>
    </vrf>
  </vrfs>
</aaa>
```

## Command Syntax

```
aaa authentication login default fallback error local (non-existent-user|) (vrf
(management|NAME) |)
```

---

## Configure group type

This is to create server group type

Attribute Name: group-type

Attribute Type: enum (tacacs+|radius)

## Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
<vrfs>
<vrf>
  <vrf-name>management</vrf-name>
  <config>
    <vrf-name>management</vrf-name>
  </config>
</server-groups>
<server-group> <!-- operation="delete"-->
  <group-name>WORD</group-name>
  <config>
    <group-name>WORD</group-name>
    <group-type>tacacs+</group-type>
  </config>
  <group-type>tacacs+</group-type>
</server-group>
</server-groups>
</vrf>
</vrfs>
</aaa>
```

## Command Syntax

```
aaa group server (tacacs+|radius) WORD (vrf (management|NAME) |)
```

---

## Configure host address

Use this attribute to add a host address to a server group

Attribute Name: host-address

Attribute Type: union

## Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
<vrfs>
<vrf>
  <vrf-name>management</vrf-name>
  <config>
    <vrf-name>management</vrf-name>
```

```

    </config>
  <server-groups>
  <server-group>
    <group-name>WORD</group-name>
    <config>
      <group-name>WORD</group-name>
      <group-type>tacacs+</group-type>
    </config>
    <group-type>tacacs+</group-type>
  <server-addresses>
  <server-address> <!-- operation="delete"-->
    <host-address>CML_HOSTNAME_T</host-address>
    <config>
      <host-address>CML_HOSTNAME_T</host-address>
    </config>
  </server-address>
</server-addresses>
</server-group>
</server-groups>
</vrf>
</vrf>
</aaa>

```

## Command Syntax

```
server (A.B.C.D|X:X::X:X|WORD)
```

---

## Configure group name

Use this attribute to add a host address to a server group

Attribute Name: host-address

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```

<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <vrf>
  <vrf>
    <vrf-name>management</vrf-name>
    <config>
      <vrf-name>management</vrf-name>
    </config>
  <server-groups>
  <server-group>
    <group-name>WORD</group-name>
    <config>
      <group-name>WORD</group-name>
      <group-type>tacacs+</group-type>
    </config>
    <group-type>tacacs+</group-type>
  <server-addresses>

```

```

    <server-address>
      <host-address>CML_HOSTNAME_T</host-address>
      <config>
        <host-address>CML_HOSTNAME_T</host-address>
      </config>
    </server-address>
  </server-addresses>
</server-group>
</server-groups>
</vrf>
</vrfs>
</aaa>

```

### Command Syntax

```
server server
```

---

## Configure aaa-authentication-console authentication-method-rule

Use this attribute to set AAA methods for authentication

Attribute Name: authentication-method-rule

Attribute Type: string

### Netconf edit-config payload

```

<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-authentication-console>
    <config>
      <authentication-method-rule>LINE</authentication-method-rule> <!--
operation="delete"-->
    </config>
  </aaa-authentication-console>
</aaa>

```

### Command Syntax

```
aaa authentication login console group LINE
```

---

## Configure aaa-authentication-console authentication-method-rule

Use this attribute to set AAA methods for authentication

Attribute Name: authentication-method-rule

Attribute Type: string

### Netconf edit-config payload

```

<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-authentication-console>
    <config>
      <authentication-method-rule>LINE</authentication-method-rule> <!--
operation="delete"-->
    </config>

```

```
</aaa-authentication-console>  
</aaa>
```

### Command Syntax

```
aaa authentication login console local
```

---

## Configure aaa-authentication-console authentication-method-rule

Use this attribute to set AAA methods for authentication

Attribute Name: authentication-method-rule

Attribute Type: string

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">  
<aaa-authentication-console>  
<config>  
  <authentication-method-rule>LINE</authentication-method-rule> <!--  
operation="delete"-->  
</config>  
</aaa-authentication-console>  
</aaa>
```

### Command Syntax

```
aaa authentication login console none
```

---

## Configure aaa-authentication-console authentication-method-rule

Use this attribute to set AAA methods for authentication

Attribute Name: authentication-method-rule

Attribute Type: string

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">  
<aaa-authentication-console>  
<config>  
  <authentication-method-rule>LINE</authentication-method-rule> <!--  
operation="delete"-->  
</config>  
</aaa-authentication-console>  
</aaa>
```

### Command Syntax

```
aaa authentication login console local none
```

---

## Configure aaa-authentication-console authorization-method-rule

Use this attribute to set AAA methods for console authorization

Attribute Name: authorization-method-rule

Attribute Type: string

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-authentication-console>
    <config>
      <authorization-method-rule>LINE</authorization-method-rule> <!--
operation="delete"-->
    </config>
  </aaa-authentication-console>
</aaa>
```

### Command Syntax

```
aaa authorization console group LINE
```

---

## Configure aaa-authentication-console authorization-method-rule

Use this attribute to set AAA methods for console authorization

Attribute Name: authorization-method-rule

Attribute Type: string

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-authentication-console>
    <config>
      <authorization-method-rule>LINE</authorization-method-rule> <!--
operation="delete"-->
    </config>
  </aaa-authentication-console>
</aaa>
```

### Command Syntax

```
aaa authorization console local
```

---

## Configure aaa-authentication-console accounting-method-rule

Use this attribute to set AAA methods for console accounting

Attribute Name: accounting-method-rule

Attribute Type: string

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-authentication-console>
    <config>
      <accounting-method-rule>LINE</accounting-method-rule> <!-- operation="delete"-->
    </config>
  </aaa-authentication-console>
</aaa>
```

---

## Command Syntax

```
aaa accounting console group LINE
```

---

## Configure aaa-authentication-console accounting-method-rule

Use this attribute to set AAA methods for console accounting

Attribute Name: accounting-method-rule

Attribute Type: string

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-authentication-console>
    <config>
      <accounting-method-rule>LINE</accounting-method-rule> <!-- operation="delete"-->
    </config>
  </aaa-authentication-console>
</aaa>
```

## Command Syntax

```
aaa accounting console local
```

---

## Configure user non existent

This is to enable fallback to local authentication if remote authentication is configured and all AAA servers are unreachable

Attribute Name: enable-fallback

Attribute Type: boolean

Attribute Name: user-non-existent

Attribute Type: boolean

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-authentication-console>
    <config>
      <user-non-existent>true</user-non-existent> <!-- operation="delete"-->
      <enable-fallback>true</enable-fallback> <!-- operation="delete"-->
    </config>
  </aaa-authentication-console>
</aaa>
```

## Command Syntax

```
aaa authentication login console fallback error local (non-existent-user|)
```

---

## Configure authentication max failure attempts

Use this attribute to set the number of unsuccessful authentication attempts before a user is locked out

Attribute Name: authentication-max-failure-attempts

Attribute Type: uint8

Attribute Range: 1-25

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-user>
    <config>
      <authentication-max-failure-attempts>1</authentication-max-failure-attempts> <!--
- operation="delete"-->
    </config>
  </aaa-user>
</aaa>
```

### Command Syntax

```
aaa local authentication attempts max-fail <1-25>
```

---

## Configure local user unlock timeout

Use this attribute to set unlock timeout after local user/s locked out

Attribute Name: local-user-unlock-timeout

Attribute Type: uint16

Attribute Range: 1-3600

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-user>
    <config>
      <local-user-unlock-timeout>1</local-user-unlock-timeout> <!--
operation="delete"-->
    </config>
  </aaa-user>
</aaa>
```

### Command Syntax

```
aaa local authentication unlock-timeout <1-3600>
```

---

## Configure enable

Enable feature of applying policy to update password

Attribute Name: enable

Attribute Type: uint8

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-user>
    <password-policy>
```

```
<config>
  </enable><!-- operation="delete"-->
</config>
</password-policy>
</aaa-user>
</aaa>
```

## Command Syntax

```
aaa local authentication password-policy
```

---

## Configure numeric count

The minimum number of digits

Attribute Name: numeric-count

Attribute Type: uint8

Attribute Range: 1-32

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-user>
  <password-policy>
  <config>
    <numeric-count>1</numeric-count> <!-- operation="delete"-->
  </config>
</password-policy>
</aaa-user>
</aaa>
```

## Command Syntax

```
aaa local authentication password-policy numeric-count <1-32>
```

---

## Configure uppercase count

The minimum number of upper letters

Attribute Name: uppercase-count

Attribute Type: uint8

Attribute Range: 1-32

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-user>
  <password-policy>
  <config>
    <uppercase-count>1</uppercase-count> <!-- operation="delete"-->
  </config>
</password-policy>
</aaa-user>
```

```
</aaa>
```

## Command Syntax

```
aaa local authentication password-policy uppercase-count <1-32>
```

---

## Configure lowercase count

The minimum number of lower letters

Attribute Name: lowercase-count

Attribute Type: uint8

Attribute Range: 1-32

## Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-user>
    <password-policy>
      <config>
        <lowercase-count>1</lowercase-count> <!-- operation="delete"-->
      </config>
    </password-policy>
  </aaa-user>
</aaa>
```

## Command Syntax

```
aaa local authentication password-policy lowercase-count <1-32>
```

---

## Configure special count

The minimum number of special characters

Attribute Name: special-count

Attribute Type: uint8

Attribute Range: 1-32

## Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-user>
    <password-policy>
      <config>
        <special-count>1</special-count> <!-- operation="delete"-->
      </config>
    </password-policy>
  </aaa-user>
</aaa>
```

## Command Syntax

```
aaa local authentication password-policy special-count <1-32>
```

---

## Configure history

history

Attribute Name: history

Attribute Type: uint16

Attribute Range: 1-400

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-user>
    <password-policy>
      <config>
        <history>1</history> <!-- operation="delete"-->
      </config>
    </password-policy>
  </aaa-user>
</aaa>
```

### Command Syntax

```
aaa local authentication password-policy history <1-400>
```

---

## Configure maxsequence

The maximum number of monotonic character sequences to be accepted.

Attribute Name: maxsequence

Attribute Type: uint8

Attribute Range: 1-32

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-user>
    <password-policy>
      <config>
        <maxsequence>1</maxsequence> <!-- operation="delete"-->
      </config>
    </password-policy>
  </aaa-user>
</aaa>
```

### Command Syntax

```
aaa local authentication password-policy maxsequence <1-32>
```

---

## Configure disable usercheck

Disable the check if password contains username

Attribute Name: disable-usercheck

Attribute Type: empty

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-user>
    <password-policy>
      <config>
        </disable-usercheck><!-- operation="delete"-->
      </config>
    </password-policy>
  </aaa-user>
</aaa>
```

### Command Syntax

```
aaa local authentication password-policy disable-usercheck
```

---

## Configure maxrepeat

The maximum number of same consecutive characters to be accepted

Attribute Name: maxrepeat

Attribute Type: uint8

Attribute Range: 1-32

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-user>
    <password-policy>
      <config>
        <maxrepeat>1</maxrepeat> <!-- operation="delete"-->
      </config>
    </password-policy>
  </aaa-user>
</aaa>
```

### Command Syntax

```
aaa local authentication password-policy maxrepeat <1-32>
```

---

## Configure min length

Minimum password length

Attribute Name: min-length

Attribute Type: uint8

Attribute Range: 8-32

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-user>
```

```

<password-policy>
<config>
  <min-length>8</min-length> <!-- operation="delete"-->
</config>
</password-policy>
</aaa-user>
</aaa>

```

### Command Syntax

```
aaa local authentication password-policy min-length <8-32>
```

---

## Configure role

use this attribute to set the role for password expiry

Attribute Name: role

Attribute Type: enum (network-admin|network-engineer|network-operator|network-user)

Attribute Name: expire

Attribute Type: uint16

Attribute Range: 0-1000

### Netconf edit-config payload

```

<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
<aaa-user>
<password-policy>
<role-expdays>
<role-expday>
  <role>network-admin</role>
  <config>
    <role>network-admin</role>
    <expire>0</expire> <!-- operation="delete"-->
  </config>
</role-expday>
</role-expdays>
</password-policy>
</aaa-user>
</aaa>

```

### Command Syntax

```
aaa local authentication password expire <0-1000> role (network-admin|network-
engineer|network-operator|network-user)
```

---

## Configure user

use this attribute to set the username for password expiry

Attribute Name: user

Attribute Type: string

Attribute Name: expire

Attribute Type: uint16

Attribute Range: 0-1000

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <aaa-user>
    <password-policy>
    <user-expdays>
    <user-expday>
      <user>WORD</user>
      <config>
        <user>WORD</user>
        <expire>0</expire> <!-- operation="delete"-->
      </config>
    </user-expday>
  </user-expdays>
</password-policy>
</aaa-user>
</aaa>
```

### Command Syntax

```
aaa local authentication password expire <0-1000> user WORD
```

---

## Configure debug enable

Use this attribute to display AAA debugging information.

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```
<aaa xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <debug>
    <config>
      </enable><!-- operation="delete"-->
    </config>
  </debug>
</aaa>
```

### Command Syntax

```
debug aaa
```

---

## debug aaa

### Netconf RPC payload

```
<aaa-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa"/>
```

---

## Command Syntax

```
debug aaa
```

---

## no debug aaa

### Netconf RPC payload

```
<aaa-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa"/>
```

## Command Syntax

```
no debug aaa
```

---

## clear aaa local user lockout username USERNAME

Attribute Name: username

Attribute Type: string

Attribute Range: 2-32

### Netconf RPC payload

```
<aaa-clear-local-user-lockout xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-aaa">
  <username>USERNAME</username>
</aaa-clear-local-user-lockout>
```

## Command Syntax

```
clear aaa local user lockout username USERNAME
```

---

## IPI-DHCP-RELAY

---

### Configure disable dhcpv4 relay

Use this attribute to disable the DHCP relay global config

Attribute Name: disable-dhcpv4-relay

Attribute Type: uint8

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <global>
      <config>
        </disable-dhcpv4-relay><!-- operation="delete"-->
      </config>
    </global>
  </relay>
</dhcp>
```

---

## Command Syntax

```
no ip dhcp relay
```

---

## Configure disable dhcpv6 relay

Use this attribute to disable the DHCP relay global config

Attribute Name: disable-dhcpv6-relay

Attribute Type: uint8

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <global>
      <config>
        </disable-dhcpv6-relay><!-- operation="delete"-->
      </config>
    </global>
  </relay>
</dhcp>
```

## Command Syntax

```
no ipv6 dhcp relay
```

---

## Configure ipv4 relay interface

Enable relay on Client facing interface

Attribute Name: ipv4-relay-interface

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
      </ipv4-relay-interface><!-- operation="delete"-->
    </interface>
  </interfaces>
</relay>
</dhcp>
```

## Command Syntax

```
ip dhcp relay
```

---

## Configure ipv4 uplink interface

Specify the interface as an uplink interface(Server facing)

Attribute Name: ipv4-uplink-interface

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        </ipv4-uplink-interface><!-- operation="delete"-->
      </interface>
    </interfaces>
  </relay>
</dhcp>
```

### Command Syntax

```
ip dhcp relay uplink
```

---

## Configure ipv4 group name

Correlate specified interface to a specified DHCP server group.

Attribute Name: ipv4-group-name

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
          <ipv4-group-name>GROUP-NAME</ipv4-group-name> <!-- operation="delete"-->
        </config>
      </interface>
    </interfaces>
  </relay>
</dhcp>
```

### Command Syntax

```
ip dhcp relay server-select GROUP-NAME
```

---

## Configure ipv6 relay interface

Enable IPv6 relay on Client facing interface

Attribute Name: ipv6-relay-interface

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
      </ipv6-relay-interface><!-- operation="delete"-->
    </interface>
  </interfaces>
</relay>
</dhcp>
```

### Command Syntax

```
ipv6 dhcp relay
```

---

## Configure ipv6 uplink interface

Specify the interface as an uplink interface(Server facing)

Attribute Name: ipv6-uplink-interface

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
      </ipv6-uplink-interface><!-- operation="delete"-->
    </interface>
  </interfaces>
</relay>
</dhcp>
```

### Command Syntax

```
ipv6 dhcp relay uplink
```

---

## Configure ipv6 group name

Correlate specified interface to a specified DHCPv6 server group.

Attribute Name: ipv6-group-name

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
          </config>
          <ipv6-group-name>GROUP-NAME</ipv6-group-name> <!-- operation="delete"-->
        </interface>
      </interfaces>
    </relay>
  </dhcp>
```

### Command Syntax

```
ipv6 dhcp relay server-select GROUP-NAME
```

---

## Configure interface type

DHCP relay vpn interface type

Attribute Name: interface-type

Attribute Type: enum (l3vpn|evpn)

Attribute Name: interface-direction

Attribute Type: enum (uplink|downlink)

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </config>
          <ipv4-vpn-links>
            <ipv4-vpn-link> <!-- operation="delete"-->
              <interface-type>l3vpn</interface-type>
              <config>
                <interface-type>l3vpn</interface-type>
              </config>
            </ipv4-vpn-link>
          </ipv4-vpn-links>
        </vrf>
      </vrfs>
    </relay>
  </dhcp>
```

```

        <interface-direction>uplink</interface-direction>
    </config>
</ipv4-vpn-link>
</ipv4-vpn-links>
</vrf>
</vrfs>
</relay>
</dhcp>

```

### Command Syntax

```
ip dhcp relay (uplink|downlink) (l3vpn|evpn)
```

---

## Configure interface type v6

DHCPv6 relay vpn interface type

Attribute Name: interface-type-v6

Attribute Type: enum (l3vpn|evpn)

Attribute Name: interface-direction-v6

Attribute Type: enum (uplink|downlink)

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
      <ipv6-vpn-links>
        <ipv6-vpn-link> <!-- operation="delete"-->
          <interface-type-v6>l3vpn</interface-type-v6>
          <config>
            <interface-type-v6>l3vpn</interface-type-v6>
            <interface-direction-v6>uplink</interface-direction-v6>
          </config>
        </ipv6-vpn-link>
      </ipv6-vpn-links>
    </vrf>
  </vrfs>
</relay>
</dhcp>

```

### Command Syntax

```
ipv6 dhcp relay (uplink|downlink) (l3vpn|evpn)
```

---

## Configure link selection source ip

Enable link selection sub-option (5) in the option-82 in DHCP packet

Attribute Name: link-selection-source-ip

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <link-selection-source-ip>A.B.C.D</link-selection-source-ip> <!--
operation="delete"-->
      </vrf>
    </vrfs>
  </relay>
</dhcp>
```

### Command Syntax

```
ip dhcp relay information source-ip A.B.C.D
```

---

## Configure enable option82

Enable the device to insert and remove option-82 information on DHCP packets forwarded by the DHCP relay agent.

Attribute Name: enable-option82

Attribute Type: uint8

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        </enable-option82><!-- operation="delete"-->
      </vrf>
    </vrfs>
  </relay>
</dhcp>
```

### Command Syntax

```
ip dhcp relay information option
```

---

## Configure ip address

IPv4 address of the DHCP server

Attribute Name: ip-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <ipv4-dhcp-servers>
          <ipv4-dhcp-server> <!-- operation="delete"-->
            <ip-address>A.B.C.D</ip-address>
            <config>
              <ip-address>A.B.C.D</ip-address>
            </config>
          </ipv4-dhcp-server>
        </ipv4-dhcp-servers>
      </vrf>
    </vrfs>
  </relay>
</dhcp>
```

### Command Syntax

```
ip dhcp relay address A.B.C.D
```

---

## Configure dhcpv4 server global vrf

This attributes defines the VRF in which the DHCPv4 relay server is present

Attribute Name: dhcpv4-server-global-vrf

Attribute Type: string

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <ipv4-dhcp-servers>
          <ipv4-dhcp-server>
```

```

    <ip-address>A.B.C.D</ip-address>
    <config>
      <ip-address>A.B.C.D</ip-address>
    </config>
    <dhcpv4-server-global-vrf>VRF-NAME</dhcpv4-server-global-vrf> <!--
operation="delete"-->
  </ipv4-dhcp-server>
</ipv4-dhcp-servers>
</vrf>
</vrfs>
</relay>
</dhcp>

```

### Command Syntax

```
ip dhcp relay address A.B.C.D global (VRF-NAME|)
```

---

## Configure vrf name

This attributes defines the VRF in which the DHCPv4 relay server is present

Attribute Name: dhcpv4-server-global-vrf

Attribute Type: string

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
      <ipv4-dhcp-servers>
        <ipv4-dhcp-server>
          <ip-address>A.B.C.D</ip-address>
          <config>
            <ip-address>A.B.C.D</ip-address>
          </config>
          <dhcpv4-server-global-vrf>VRF-NAME</dhcpv4-server-global-vrf> <!--
operation="delete"-->
        </ipv4-dhcp-server>
      </ipv4-dhcp-servers>
    </vrfs>
  </relay>
</dhcp>

```

### Command Syntax

```
ip dhcp relay address A.B.C.D global (VRF-NAME|)
```

---

## Configure ipv6 address

IPv6 address of the DHCP server

Attribute Name: ipv6-address

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <ipv6-dhcp-servers>
          <ipv6-dhcp-server> <!-- operation="delete"-->
            <ipv6-address>X:X::X:X</ipv6-address>
            <config>
              <ipv6-address>X:X::X:X</ipv6-address>
            </config>
          </ipv6-dhcp-server>
        </ipv6-dhcp-servers>
      </vrf>
    </vrfs>
  </relay>
</dhcp>
```

### Command Syntax

```
ipv6 dhcp relay address X:X::X:X
```

---

## Configure dhcpv6 server global vrf

This attributes defines the VRF in which the DHCPv6 relay server is present

Attribute Name: dhcpv6-server-global-vrf

Attribute Type: string

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <ipv6-dhcp-servers>
          <ipv6-dhcp-server>
```

```

    <ipv6-address>X:X::X:X</ipv6-address>
    <config>
      <ipv6-address>X:X::X:X</ipv6-address>
    </config>
    <dhcpv6-server-global-vrf>VRF-NAME</dhcpv6-server-global-vrf> <!--
operation="delete"-->
  </ipv6-dhcp-server>
</ipv6-dhcp-servers>
</vrf>
</vrfs>
</relay>
</dhcp>

```

### Command Syntax

```
ipv6 dhcp relay address X:X::X:X global (VRF-NAME|)
```

## Configure ipv6-dhcp-server dhcpv6-server-global-vrf

This attribute defines the VRF in which the DHCPv6 relay server is present

Attribute Name: dhcpv6-server-global-vrf

Attribute Type: string

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
      <ipv6-dhcp-servers>
        <ipv6-dhcp-server>
          <ipv6-address>X:X::X:X</ipv6-address>
          <config>
            <ipv6-address>X:X::X:X</ipv6-address>
          </config>
          <dhcpv6-server-global-vrf>VRF-NAME</dhcpv6-server-global-vrf> <!--
operation="delete"-->
        </ipv6-dhcp-server>
      </ipv6-dhcp-servers>
    </vrfs>
  </relay>
</dhcp>

```

### Command Syntax

```
ipv6 dhcp relay address X:X::X:X global (VRF-NAME|)
```

---

## Configure enable dhcpv6 pd route injection

Enable the route installation from the prefixes learned through prefix delegation.

Attribute Name: enable-dhcpv6-pd-route-injection

Attribute Type: uint8

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        </enable-dhcpv6-pd-route-injection><!-- operation="delete"-->
      </vrf>
    </vrfs>
  </relay>
</dhcp>
```

### Command Syntax

```
ipv6 dhcp relay pd-route-injection
```

---

## Configure remote id

Remote host identifier. Use option 82 to provide the DHCP server information about the DHCP client

Attribute Name: remote-id

Attribute Type: union

Attribute Name: enable-option82

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </enable-option82><!-- operation="delete"-->
        </config>
        <remote-id>WORD</remote-id> <!-- operation="delete"-->
      </vrf>
    </vrfs>
  </relay>
</dhcp>
```

---

## Command Syntax

```
ip dhcp relay information option remote-id WORD
```

---

## Configure vrf remote-id

Remote host identifier. Use option 82 to provide the DHCP server information about the DHCP client

Attribute Name: remote-id

Attribute Type: union

Attribute Name: enable-option82

Attribute Type: empty

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </enable-option82><!-- operation="delete"-->
        </config>
        <remote-id>0</remote-id> <!-- operation="delete"-->
      </vrf>
    </vrfs>
  </relay>
</dhcp>
```

## Command Syntax

```
ip dhcp relay information option remote-id hostname
```

---

## Configure vrf remote-id

Remote host identifier. Use option 82 to provide the DHCP server information about the DHCP client

Attribute Name: remote-id

Attribute Type: union

Attribute Name: enable-option82

Attribute Type: empty

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
      </vrf>
    </vrfs>
  </relay>
</dhcp>
```

```

    </enable-option82><!-- operation="delete"-->
  </config>
  <remote-id>WORD</remote-id> <!-- operation="delete"-->
</vrf>
</vrfs>
</relay>
</dhcp>

```

## Command Syntax

```
ip dhcp relay information option remote-id WORD
```

---

## Configure vrf remote-id

Remote host identifier. Use option 82 to provide the DHCP server information about the DHCP client

Attribute Name: remote-id

Attribute Type: union

Attribute Name: enable-option82

Attribute Type: empty

## Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
  <vrfs>
  <vrf>
    <vrf-name>WORD</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
      </enable-option82><!-- operation="delete"-->
    </config>
    <remote-id>0</remote-id> <!-- operation="delete"-->
  </vrf>
</vrfs>
</relay>
</dhcp>

```

## Command Syntax

```
ip dhcp relay information option remote-id hostname
```

---

## Configure enable option82 always on

Keep option-82 information on DHCP packets forwarded by the DHCP relay agent.

Attribute Name: enable-option82-always-on

Attribute Type: uint8

Attribute Name: enable-option82

Attribute Type: empty

**Netconf edit-config payload**

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </enable-option82><!-- operation="delete"-->
        </config>
        </enable-option82-always-on><!-- operation="delete"-->
      </vrf>
    </vrfs>
  </relay>
</dhcp>

```

**Command Syntax**

```
ip dhcp relay information option always-on
```

**Configure vrf enable-option82-always-on**

Keep option-82 information on DHCP packets forwarded by the DHCP relay agent.

Attribute Name: enable-option82-always-on

Attribute Type: uint8

Attribute Name: enable-option82

Attribute Type: empty

**Netconf edit-config payload**

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
          </enable-option82><!-- operation="delete"-->
        </config>
        </enable-option82-always-on><!-- operation="delete"-->
      </vrf>
    </vrfs>
  </relay>
</dhcp>

```

**Command Syntax**

```
ip dhcp relay information option always-on
```

---

## Configure subscriber id

Subscriber identifier. Use this option to allows the service provider to assign/activate subscriber-specific actions

Attribute Name: subscriber-id

Attribute Type: string

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <subscriber-id>WORD</subscriber-id> <!-- operation="delete"-->
      </vrf>
    </vrfs>
  </relay>
</dhcp>
```

### Command Syntax

```
ipv6 dhcp relay information option subscriber-id WORD
```

---

## Configure group6 name

IPv6 DHCP Relay group name

Attribute Name: group6-name

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
      <dhcpv6-groups>
        <dhcpv6-group> <!-- operation="delete"-->
          <group6-name>GROUP-NAME</group6-name>
          <config>
            <group6-name>WORD</group6-name>
          </config>
        </dhcpv6-group>
      </dhcpv6-groups>
    </vrfs>
  </relay>
</dhcp>
```

```
</vrf>  
</vrfs>  
</relay>  
</dhcp>
```

## Command Syntax

```
ipv6 dhcp relay server-group GROUP-NAME
```

---

## Configure group name

IPv4 DHCP Relay group name

Attribute Name: group-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">  
  <relay>  
    <vrfs>  
      <vrf>  
        <vrf-name>WORD</vrf-name>  
        <config>  
          <vrf-name>NAME</vrf-name>  
        </config>  
      <dhcp-groups>  
        <dhcp-group> <!-- operation="delete"-->  
          <group-name>GROUP-NAME</group-name>  
          <config>  
            <group-name>WORD</group-name>  
          </config>  
        </dhcp-group>  
      </dhcp-groups>  
    </vrf>  
  </vrfs>  
</relay>  
</dhcp>
```

## Command Syntax

```
ip dhcp relay server-group GROUP-NAME
```

---

## Configure vrf link-selection-source-ip

Enable link selection sub-option (5) in the option-82 in DHCP packet

Attribute Name: link-selection-source-ip

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <link-selection-source-ip>A.B.C.D</link-selection-source-ip> <!--
operation="delete"-->
      </vrf>
    </vrfs>
  </relay>
</dhcp>

```

## Command Syntax

```
ip dhcp relay information source-ip A.B.C.D
```

---

## Configure vrf enable-option82

Enable the device to insert and remove option-82 information on DHCP packets forwarded by the DHCP relay agent.

Attribute Name: enable-option82

Attribute Type: empty

## Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        </enable-option82><!-- operation="delete"-->
      </vrf>
    </vrfs>
  </relay>
</dhcp>

```

## Command Syntax

```
ip dhcp relay information option
```

---

## Configure vrf enable-dhcpv6-pd-route-injection

Enable the route installation from the prefixes learned through prefix delegation.

Attribute Name: enable-dhcpv6-pd-route-injection

Attribute Type: empty

---

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        </enable-dhcpv6-pd-route-injection><!-- operation="delete"-->
      </vrf>
    </vrfs>
  </relay>
</dhcp>
```

## Command Syntax

```
ipv6 dhcp relay pd-route-injection
```

---

## Configure enable dhcpv6 duplicate clients

Specify that the DHCPv6 relay agent uses the clients incoming interfaces to differentiate between the duplicate DUIDs.

Attribute Name: enable-dhcpv6-duplicate-clients

Attribute Type: empty

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        </enable-dhcpv6-duplicate-clients><!-- operation="delete"-->
      </vrf>
    </vrfs>
  </relay>
</dhcp>
```

## Command Syntax

```
ipv6 dhcp relay duplicate-clients
```

---

## Configure vrf subscriber-id

Subscriber identifier. Use this option to allows the service provider to assign/activate subscriber-specific actions

Attribute Name: subscriber-id

Attribute Type: string

**Netconf edit-config payload**

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <subscriber-id>WORD</subscriber-id> <!-- operation="delete"-->
      </vrf>
    </vrfs>
  </relay>
</dhcp>

```

**Command Syntax**

```
ipv6 dhcp relay information option subscriber-id WORD
```

**Configure interface direction**

DHCP relay vpn interface type

Attribute Name: interface-type

Attribute Type: enum (l3vpn|evpn)

Attribute Name: interface-direction

Attribute Type: enum (uplink|downlink)

**Netconf edit-config payload**

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <ipv4-vpn-links>
          <ipv4-vpn-link>
            <interface-type>l3vpn</interface-type>
            <config>
              <interface-type>l3vpn</interface-type>
              <interface-direction>uplink</interface-direction>
            </config>
          </ipv4-vpn-link>
        </ipv4-vpn-links>
      </vrf>
    </vrfs>
  </relay>
</dhcp>

```

## Command Syntax

```
ip dhcp relay (uplink|downlink) (l3vpn|evpn)
```

---

## Configure interface direction v6

DHCPv6 relay vpn interface type

This command is supported when following feature are enabled IPV6 feature

Attribute Name: interface-type-v6

Attribute Type: enum (l3vpn|evpn)

Attribute Name: interface-direction-v6

Attribute Type: enum (uplink|downlink)

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <ipv6-vpn-links>
          <ipv6-vpn-link>
            <interface-type-v6>l3vpn</interface-type-v6>
            <config>
              <interface-type-v6>l3vpn</interface-type-v6>
              <interface-direction-v6>uplink</interface-direction-v6>
            </config>
          </ipv6-vpn-link>
        </ipv6-vpn-links>
      </vrf>
    </vrfs>
  </relay>
</dhcp>
```

## Command Syntax

```
ipv6 dhcp relay (uplink|downlink) (l3vpn|evpn)
```

---

## Configure ipv4-dhcp-servers ip-address

IPv4 address of the DHCP server

Attribute Name: ip-address

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
```

```

<relay>
<vrfs>
<vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  <ipv4-dhcp-servers>
  <ipv4-dhcp-server> <!-- operation="delete"-->
    <ip-address>A.B.C.D</ip-address>
    <config>
      <ip-address>A.B.C.D</ip-address>
    </config>
  </ipv4-dhcp-server>
</ipv4-dhcp-servers>
</vrf>
</vrfs>
</relay>
</dhcp>

```

## Command Syntax

```
ip dhcp relay address A.B.C.D
```

---

## Configure ipv4-dhcp-server ip-address

IPv4 address of the DHCP server

Attribute Name: ip-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
<relay>
<vrfs>
<vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  <ipv4-dhcp-servers>
  <ipv4-dhcp-server>
    <ip-address>A.B.C.D</ip-address>
    <config>
      <ip-address>A.B.C.D</ip-address>
    </config>
  </ipv4-dhcp-server>
</ipv4-dhcp-servers>
</vrf>
</vrfs>
</relay>

```

---

```
</dhcp>
```

### Command Syntax

```
ip dhcp relay address A.B.C.D ip dhcp relay address A.B.C.D
```

---

## Configure ipv6-dhcp-servers ipv6-address

IPv6 address of the DHCP server

This command is supported when following feature are enabled IPV6 feature

Attribute Name: ipv6-address

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
        <ipv6-dhcp-servers>
          <ipv6-dhcp-server> <!-- operation="delete"-->
            <ipv6-address>X:X::X:X</ipv6-address>
            <config>
              <ipv6-address>X:X::X:X</ipv6-address>
            </config>
          </ipv6-dhcp-server>
        </ipv6-dhcp-servers>
      </vrf>
    </vrfs>
  </relay>
</dhcp>
```

### Command Syntax

```
ipv6 dhcp relay address X:X::X:X
```

---

## Configure ipv6-dhcp-server ipv6-address

IPv6 address of the DHCP server

This command is supported when following feature are enabled IPV6 feature

Attribute Name: ipv6-address

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
```

```

<vrfs>
<vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  <ipv6-dhcp-servers>
  <ipv6-dhcp-server>
    <ipv6-address>X:X::X:X</ipv6-address>
    <config>
      <ipv6-address>X:X::X:X</ipv6-address>
    </config>
  </ipv6-dhcp-server>
</ipv6-dhcp-servers>
</vrf>
</vrfs>
</relay>
</dhcp>

```

### Command Syntax

```
ipv6 dhcp relay address X:X::X:X ipv6 dhcp relay address X:X::X:X
```

---

## Configure dhcp-groups group-name

IPv4 DHCP Relay group name

Attribute Name: group-name

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
    <vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    <dhcp-groups>
    <dhcp-group> <!-- operation="delete"-->
      <group-name>GROUP-NAME</group-name>
      <config>
        <group-name>WORD</group-name>
      </config>
    </dhcp-group>
  </dhcp-groups>
</vrf>
</vrfs>
</relay>

```

```
</dhcp>
```

## Command Syntax

```
ip dhcp relay server-group GROUP-NAME
```

---

## Configure server

IPv4 DHCP Relay Group server details

Attribute Name: server

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <relay>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>NAME</vrf-name>
        </config>
      <dhcp-groups>
        <dhcp-group>
          <group-name>GROUP-NAME</group-name>
          <config>
            <group-name>WORD</group-name>
          </config>
          <server>A.B.C.D</server> <!-- operation="delete"-->
        </dhcp-group>
      </dhcp-groups>
    </vrf>
  </vrfs>
</relay>
</dhcp>
```

## Command Syntax

```
server A.B.C.D
```

---

## Configure dhcpv6-groups group6-name

IPv6 DHCP Relay group name

This command is supported when following feature are enabled IPV6 feature

Attribute Name: group6-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
```

```

<relay>
<vrfs>
<vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  <dhcpv6-groups>
  <dhcpv6-group> <!-- operation="delete"-->
    <group6-name>GROUP-NAME</group6-name>
    <config>
      <group6-name>WORD</group6-name>
    </config>
  </dhcpv6-group>
</dhcpv6-groups>
</vrf>
</vrfs>
</relay>
</dhcp>

```

## Command Syntax

```
ipv6 dhcp relay server-group GROUP-NAME
```

---

## Configure dhcpv6-group server

IPv6 DHCP Relay Group server details

This command is supported when following feature are enabled IPV6 feature

Attribute Name: server

Attribute Type: inet:ipv6-address

## Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
<relay>
<vrfs>
<vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  <dhcpv6-groups>
  <dhcpv6-group>
    <group6-name>GROUP-NAME</group6-name>
    <config>
      <group6-name>WORD</group6-name>
    </config>
    <server>X:X::X:X</server> <!-- operation="delete"-->
  </dhcpv6-group>
</dhcpv6-groups>
</vrf>

```

```
</vrfs>  
</relay>  
</dhcp>
```

### Command Syntax

```
server X:X::X:X
```

---

## clear ip dhcp relay statistics

### Netconf RPC payload

```
<ipi-dhcp-relay_clear-relay-stats xmlns="http://www.ipinfusion.com/yang/ocnos/  
ipi-dhcp"/>
```

### Command Syntax

```
clear ip dhcp relay statistics
```

---

## clear ip dhcp relay option statistics

### Netconf RPC payload

```
<ipi-dhcp-relay_clear-relay-option-stats xmlns="http://www.ipinfusion.com/yang/  
ocnos/ipi-dhcp"/>
```

### Command Syntax

```
clear ip dhcp relay option statistics
```

---

## clear ipv6 dhcp pd-route (vrf NAME|)

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<ipi-dhcp-relay_clear-dhcpv6-pd-route xmlns="http://www.ipinfusion.com/yang/  
ocnos/ipi-dhcp">  
  <vrf-name>NAME</vrf-name>  
</ipi-dhcp-relay_clear-dhcpv6-pd-route>
```

### Command Syntax

```
clear ipv6 dhcp pd-route (vrf NAME|)
```

---

## IPI-DNS-RELAY

---

### Configure enable dns feature

Use this attribute to enable the DNS relay agent feature.

Attribute Name: enable-dns-feature

Attribute Type: boolean

### Netconf edit-config payload

```
<dns-relay xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-relay">
  <config>
    <enable-dns-feature>true</enable-dns-feature> <!-- operation="delete"-->
  </config>
</dns-relay>
```

### Command Syntax

```
feature dns relay
```

---

## Configure dns-relay enable-dns-feature

Use this attribute to enable the DNS relay agent feature.

Attribute Name: enable-dns-feature

Attribute Type: boolean

### Netconf edit-config payload

```
<dns-relay xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-relay">
  <config>
    <enable-dns-feature>true</enable-dns-feature> <!-- operation="delete"-->
  </config>
</dns-relay>
```

### Command Syntax

```
no feature dns relay
```

---

## Configure enable dnsv4 relay

Use this attribute to enable the IPv4 DNS relay agent.

Attribute Name: enable-dnsv4-relay

Attribute Type: boolean

### Netconf edit-config payload

```
<dns-relay xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-relay">
  <config>
    <enable-dnsv4-relay>true</enable-dnsv4-relay> <!-- operation="delete"-->
  </config>
</dns-relay>
```

### Command Syntax

```
ip dns relay
```

---

## Configure dns-relay enable-dnsv4-relay

Use this attribute to enable the IPv4 DNS relay agent.

Attribute Name: enable-dnsv4-relay

Attribute Type: boolean

### Netconf edit-config payload

```
<dns-relay xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-relay">
  <config>
    <enable-dnsv4-relay>true</enable-dnsv4-relay> <!-- operation="delete"-->
  </config>
</dns-relay>
```

### Command Syntax

```
no ip dns relay
```

---

## Configure enable dnsv6 relay

Use this attribute to enable the IPv6 DNS relay agent.

Attribute Name: enable-dnsv6-relay

Attribute Type: boolean

### Netconf edit-config payload

```
<dns-relay xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-relay">
  <config>
    <enable-dnsv6-relay>true</enable-dnsv6-relay> <!-- operation="delete"-->
  </config>
</dns-relay>
```

### Command Syntax

```
ipv6 dns relay
```

---

## Configure dns-relay enable-dnsv6-relay

Use this attribute to enable the IPv6 DNS relay agent.

Attribute Name: enable-dnsv6-relay

Attribute Type: boolean

### Netconf edit-config payload

```
<dns-relay xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-relay">
  <config>
    <enable-dnsv6-relay>true</enable-dnsv6-relay> <!-- operation="delete"-->
  </config>
</dns-relay>
```

### Command Syntax

```
no ipv6 dns relay
```

---

## Configure dns server v4 addr

Use this attribute to set the IPv4 address

Attribute Name: dns-server-v4-addr

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<dns-relay xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-relay">
  <config>
    <dns-server-v4-addr>A.B.C.D</dns-server-v4-addr> <!-- operation="delete"-->
  </config>
</dns-relay>
```

### Command Syntax

```
ip dns relay address A.B.C.D
```

---

## Configure dns server v6 addr

Use this attribute to set the IPv6 address

Attribute Name: dns-server-v6-addr

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```
<dns-relay xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-relay">
  <config>
    <dns-server-v6-addr>X:X::X:X</dns-server-v6-addr> <!-- operation="delete"-->
  </config>
</dns-relay>
```

### Command Syntax

```
ipv6 dns relay address X:X::X:X
```

---

## Configure name

Use this attribute to enable the IPv4 DNS relay agent.

Attribute Name: enable-dnsv4-relay

Attribute Type: empty

### Netconf edit-config payload

```
<dns-relay xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-relay">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </enable-dnsv4-relay><!-- operation="delete"-->
  </interfaces>
</dns-relay>
```

```
</interface>  
</interfaces>  
</dns-relay>
```

## Command Syntax

```
ip dns relay
```

---

## Configure interface enable-dnsv6-relay

Use this attribute to enable the IPv6 DNS relay agent.

Attribute Name: enable-dnsv6-relay

Attribute Type: empty

## Netconf edit-config payload

```
<dns-relay xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-relay">  
<interfaces>  
<interface>  
  <name>WORD</name>  
  <config>  
    <name>WORD</name>  
  </config>  
  </enable-dnsv6-relay><!-- operation="delete"-->  
</interface>  
</interfaces>  
</dns-relay>
```

## Command Syntax

```
ipv6 dns relay
```

---

## Configure dns relay uplink

Use this attribute to set the uplink IPv4 DNS relay agent.

Attribute Name: dns-relay-uplink

Attribute Type: empty

## Netconf edit-config payload

```
<dns-relay xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-relay">  
<interfaces>  
<interface>  
  <name>WORD</name>  
  <config>  
    <name>WORD</name>  
  </config>  
  </dns-relay-uplink><!-- operation="delete"-->  
</interface>  
</interfaces>  
</dns-relay>
```

---

## Command Syntax

```
ip dns relay uplink
```

---

## Configure dns relay v6 uplink

Use this attribute to set the uplink IPv6 DNS relay agent.

Attribute Name: dns-relay-v6-uplink

Attribute Type: empty

### Netconf edit-config payload

```
<dns-relay xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-relay">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </dns-relay-v6-uplink><!-- operation="delete"-->
    </interface>
  </interfaces>
</dns-relay>
```

## Command Syntax

```
ipv6 dns relay uplink
```

---

## Configure vrf name

Use this attribute to set the IPv4 address

This command is supported when following feature are enabled Virtual routing and forwarding

Attribute Name: dns-server-v4-addr

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<dns-relay xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-relay">
  <vrfs>
    <vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
      </config>
      <dns-server-v4-addr>A.B.C.D</dns-server-v4-addr> <!-- operation="delete"-->
    </vrf>
  </vrfs>
</dns-relay>
```

## Command Syntax

```
ip dns relay address A.B.C.D
```

---

## Configure vrf dns-server-v6-addr

Use this attribute to set the IPv4 address

This command is supported when following feature are enabled Virtual routing and forwarding

Attribute Name: dns-server-v6-addr

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```
<dns-relay xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-relay">
  <vrfs>
    <vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
      </config>
      <dns-server-v6-addr>X:X::X:X</dns-server-v6-addr> <!-- operation="delete"-->
    </vrf>
  </vrfs>
</dns-relay>
```

### Command Syntax

```
ipv6 dns relay address X:X::X:X
```

---

## IPI-DNS-CLIENT

---

### Configure default domain name

Default domain name used to complete unqualified host names (names without a dotted-decimal domain name).

Attribute Name: default-domain-name

Attribute Type: inet:domain-name

### Netconf edit-config payload

```
<dns xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-client">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <default-domain-name>DOMAIN-NAME</default-domain-name> <!-- operation="delete"-->
    </vrf>
  </vrfs>
</dns>
```

---

## Command Syntax

```
ip domain-name (vrf (NAME|management)|) DOMAIN-NAME
```

---

## Configure lookup enabled

Enable DNS translation.

Attribute Name: lookup-enabled

Attribute Type: boolean

## Netconf edit-config payload

```
<dns xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-client">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <lookup-enabled>true</lookup-enabled> <!-- operation="delete"-->
    </vrf>
  </vrfs>
</dns>
```

## Command Syntax

```
ip domain-lookup (vrf (NAME|management)|)
```

---

## Configure vrf name

Enable DNS translation.

Attribute Name: lookup-enabled

Attribute Type: boolean

## Netconf edit-config payload

```
<dns xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-client">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <lookup-enabled>true</lookup-enabled> <!-- operation="delete"-->
    </vrf>
  </vrfs>
</dns>
```

## Command Syntax

```
no ip domain-lookup (vrf (NAME|management)|)
```

---

## Configure address

Name server address used for name resolution.

Attribute Name: address

Attribute Type: inet:ip-address

### Netconf edit-config payload

```
<dns xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-client">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <servers>
    <server> <!-- operation="delete"-->
      <address>CML_IP_ADDR_T</address>
      <config>
        <address>CML_IP_ADDR_T</address>
      </config>
    </server>
  </servers>
</dns>
```

### Command Syntax

```
ip name-server (vrf (NAME|management)|) (A.B.C.D|X:X::X:X)
```

---

## Configure domain name

Use this attribute to define a list of default domain names used to complete unqualified host names. Each domain in the list is to be tried in turn. The ip domain-list command is similar to the ip domain-name command, except that with the ip domain-list command you can define a list of domains, each to be tried in turn. If there is no domain list, the default domain name specified with the ip domain-name command is used. If there is a domain list, the default domain name is not used.

Attribute Name: domain-name

Attribute Type: inet:domain-name

### Netconf edit-config payload

```
<dns xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-client">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <search-domains>
```

```

<search-domain> <!-- operation="delete"-->
  <domain-name>DOMAIN-NAME</domain-name>
  <config>
    <domain-name>CML_DOMAIN_NAME_T</domain-name>
  </config>
</search-domain>
</search-domains>
</vrf>
</vrfs>
</dns>

```

### Command Syntax

```
ip domain-list (vrf (NAME|management)|) DOMAIN-NAME
```

---

## Configure ipv6 address

Configure a static hostname-to-address IPv6 mapping in DNS.

Attribute Name: ipv6-address

Attribute Type: inet:ipv6-address

Attribute Name: ipv4-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<dns xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-client">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <host-entries>
    <host-entry>
      <hostname>HOSTNAME</hostname>
      <config>
        <hostname>1</hostname>
        <ipv4-address>A.B.C.D</ipv4-address> <!-- operation="delete"-->
      </config>
        <ipv6-address>X:X::X:X</ipv6-address> <!-- operation="delete"-->
      </host-entry>
    </host-entries>
  </dns>

```

### Command Syntax

```
ip host (vrf (NAME|management)|) HOSTNAME A.B.C.D X:X::X:X
```

---

## Configure ipv4 address

Configure a static hostname-to-address IPv4 mapping in DNS.

Attribute Name: ipv4-address

Attribute Type: inet:ipv4-address

Attribute Name: ipv6-address

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```
<dns xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-client">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    <host-entries>
      <host-entry>
        <hostname>HOSTNAME</hostname>
        <config>
          <hostname>1</hostname>
          <ipv6-address>X:X::X:X</ipv6-address> <!-- operation="delete"-->
        </config>
          <ipv4-address>A.B.C.D</ipv4-address> <!-- operation="delete"-->
        </host-entry>
      </host-entries>
    </vrf>
  </vrfs>
</dns>
```

### Command Syntax

```
ip host (vrf (NAME|management)|) HOSTNAME X:X::X:X A.B.C.D
```

---

## Configure hostname

Configure a static hostname-to-address IPv4 mapping in DNS.

Attribute Name: ipv4-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<dns xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-client">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    </vrf>
  </vrfs>
</dns>
```

```

<host-entries>
<host-entry>
  <hostname>HOSTNAME</hostname>
  <config>
    <hostname>1</hostname>
  </config>
  <ipv4-address>A.B.C.D</ipv4-address> <!-- operation="delete"-->
</host-entry>
</host-entries>
</vrf>
</vrfs>
</dns>

```

### Command Syntax

```
ip host (vrf (NAME|management)|) HOSTNAME A.B.C.D
```

---

## Configure host-entry ipv6-address

Configure a static hostname-to-address IPv6 mapping in DNS.

Attribute Name: ipv6-address

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```

<dns xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-client">
<vrfs>
<vrf>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
<host-entries>
<host-entry>
  <hostname>HOSTNAME</hostname>
  <config>
    <hostname>1</hostname>
  </config>
  <ipv6-address>X:X::X:X</ipv6-address> <!-- operation="delete"-->
</host-entry>
</host-entries>
</vrf>
</vrfs>
</dns>

```

### Command Syntax

```
ip host (vrf (NAME|management)|) HOSTNAME X:X::X:X
```

---

## Configure enable

DNS client debug.

Attribute Name: enable

Attribute Type: uint8

### Netconf edit-config payload

```
<dns xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dns-client">
  <debug>
  <config>
    </enable><!-- operation="delete"-->
  </config>
</debug>
</dns>
```

### Command Syntax

```
debug dns client
```

---

## debug dns client

### Netconf RPC payload

```
<dns-client-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
dns-client"/>
```

### Command Syntax

```
debug dns client
```

---

## no debug dns client

### Netconf RPC payload

```
<dns-client-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
dns-client"/>
```

### Command Syntax

```
no debug dns client
```

---

## IPI-DHCP-CLIENT

---

### Configure request ipv4 dns

Use this attribute to to add an option to a DHCP request.

Attribute Name: request-ipv4-dns

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <client>
  <interfaces>
```

```

<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </request-ipv4-dns><!-- operation="delete"-->
</interface>
</interfaces>
</client>
</dhcp>

```

### Command Syntax

```
ip dhcp client request dns-nameserver
```

---

## Configure request log server

Use this attribute to to add an option to a DHCP request.

Attribute Name: request-log-server

Attribute Type: empty

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <client>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        </request-log-server><!-- operation="delete"-->
      </interface>
    </interfaces>
  </client>
</dhcp>

```

### Command Syntax

```
ip dhcp client request log-server
```

---

## Configure request host name

Use this attribute to to add an option to a DHCP request.

Attribute Name: request-host-name

Attribute Type: empty

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <client>
    <interfaces>

```

```
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </request-host-name><!-- operation="delete"-->
</interface>
</interfaces>
</client>
</dhcp>
```

### Command Syntax

```
ip dhcp client request host-name
```

---

## Configure request ntp server

Use this attribute to to add an option to a DHCP request.

Attribute Name: request-ntp-server

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <client>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        </request-ntp-server><!-- operation="delete"-->
      </interface>
    </interfaces>
  </client>
</dhcp>
```

### Command Syntax

```
ip dhcp client request ntp-server
```

---

## Configure request ipv6 dns

Use this attribute to to add an option to a DHCP request.

Attribute Name: request-ipv6-dns

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <client>
    <interfaces>
```

```
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </request-ipv6-dns><!-- operation="delete"-->
</interface>
</interfaces>
</client>
</dhcp>
```

### Command Syntax

```
ipv6 dhcp client request dns-nameserver
```

---

## Configure request ipv6 domain list

Use this attribute to specifies a search list of Domain Names to be used by the client to locate not-fully-qualified domain names.

Attribute Name: request-ipv6-domain-list

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <client>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        </request-ipv6-domain-list><!-- operation="delete"-->
      </interface>
    </interfaces>
  </client>
</dhcp>
```

### Command Syntax

```
ipv6 dhcp client request domain-search
```

---

## Configure request ipv6 ntp server

Use this attribute to specifies a list of local NTP servers available for the client to synchronize their clocks.

Attribute Name: request-ipv6-ntp-server

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <client>
```

```

<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </request-ipv6-ntp-server><!-- operation="delete"-->
</interface>
</interfaces>
</client>
</dhcp>

```

### Command Syntax

```
ipv6 dhcp client request ntp-server
```

---

## Configure request ipv6 rapid commit

Use this attribute to indicate the clients to enter into rapid-commit with the server.

Attribute Name: request-ipv6-rapid-commit

Attribute Type: empty

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
<client>
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </request-ipv6-rapid-commit><!-- operation="delete"-->
</interface>
</interfaces>
</client>
</dhcp>

```

### Command Syntax

```
ipv6 dhcp client request rapid-commit
```

---

## Configure request ipv6 vendor opts

Use this attribute to specify a 32-bit Enterprise-ID number.

Attribute Name: request-ipv6-vendor-opts

Attribute Type: empty

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
<client>

```

```
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </request-ipv6-vendor-opts><!-- operation="delete"-->
</interface>
</interfaces>
</client>
</dhcp>
```

### Command Syntax

```
ipv6 dhcp client request vendor-specific-information
```

---

## Configure ipv6 information request

Use this attribute to get only stateless configuration parameters (i.e., without address).

Attribute Name: ipv6-information-request

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
<client>
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </ipv6-information-request><!-- operation="delete"-->
</interface>
</interfaces>
</client>
</dhcp>
```

### Command Syntax

```
ipv6 dhcp client information-request
```

---

## Configure ipv6 dad wait time

Use this attribute to Specify maximum time (in seconds) that the client should wait for the duplicate address detection (DAD) to complete on an interface.

Attribute Name: ipv6-dad-wait-time

Attribute Type: uint16

Attribute Range: 1-600

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <client>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <ipv6-dad-wait-time>1</ipv6-dad-wait-time> <!-- operation="delete"-->
      </interface>
    </interfaces>
  </client>
</dhcp>
```

## Command Syntax

```
ipv6 dhcp client dad-wait-time <1-600>
```

---

## Configure ipv6 client duid type

Use this attribute to configure duid type(II or IIt).

Attribute Name: ipv6-client-duid-type

Attribute Type: enum (II|IIt)

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <client>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <ipv6-client-duid-type>II</ipv6-client-duid-type> <!-- operation="delete"-->
      </interface>
    </interfaces>
  </client>
</dhcp>
```

## Command Syntax

```
ipv6 dhcp client duid (II|IIt)
```

---

## Configure ipv6 max delegated prefix

Use this attribute to configure the maximum number of simultaneous prefixes delegated to a single client

Attribute Name: ipv6-max-delegated-prefix

Attribute Type: uint16

Attribute Range: 1-64

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <client>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <ipv6-max-delegated-prefix>1</ipv6-max-delegated-prefix> <!--
operation="delete"-->
      </interface>
    </interfaces>
  </client>
</dhcp>
```

### Command Syntax

```
ipv6 dhcp client max-delegated-prefixes <1-64>
```

---

## Configure request ipv6 prefix

Use this attribute to add an option to a DHCP request.

Attribute Name: request-ipv6-prefix

Attribute Type: string

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <client>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <request-ipv6-prefix>PREFIX-NAME</request-ipv6-prefix> <!--
operation="delete"-->
      </interface>
    </interfaces>
  </client>
</dhcp>
```

### Command Syntax

```
ipv6 dhcp prefix-delegation PREFIX-NAME
```

---

## Configure suffix ipv6 addr

This attribute points to IPv6 address

This command is supported when following feature are enabled IPV6 feature

Attribute Name: suffix-ipv6-addr

Attribute Type: string

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <client>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <prefix-ipv6-addresses>
          <prefix-ipv6-address> <!-- operation="delete"-->
            <suffix-ipv6-addr>X:X::X:X/M</suffix-ipv6-addr>
            <config>
              <suffix-ipv6-addr>X:X::X:X/M</suffix-ipv6-addr>
              <prefix-name>PREFIX-NAME</prefix-name>
            </config>
            <prefix-name>PREFIX-NAME</prefix-name>
          </prefix-ipv6-address>
        </prefix-ipv6-addresses>
      </interface>
    </interfaces>
  </client>
</dhcp>
```

### Command Syntax

```
ipv6 address PREFIX-NAME X:X::X:X/M
```

---

## IPI-DHCP-SERVER

---

### Configure enable ipv4 server

Interface on which IPv4 DHCP Server has to be run

Attribute Name: enable-ipv4-server

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
```

```

    <name>WORD</name>
  </config>
  </enable-ipv4-server><!-- operation="delete"-->
</interface>
</interfaces>
</server>
</dhcp>

```

### Command Syntax

```
ip dhcp server
```

---

## Configure enable ipv6 server

Interface on which IPv6 DHCP Server has to be run

Attribute Name: enable-ipv6-server

Attribute Type: empty

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        </enable-ipv6-server><!-- operation="delete"-->
      </interface>
    </interfaces>
  </server>
</dhcp>

```

### Command Syntax

```
ipv6 dhcp server
```

---

## Configure pool6 name

IPv6 DHCP Server address pool name

Attribute Name: pool6-name

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>

```

```

    <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
  </config>
  <dhcp6-pools>
  <dhcp6-pool> <!-- operation="delete"-->
    <pool6-name>NAME</pool6-name>
    <config>
      <pool6-name>WORD</pool6-name>
    </config>
  </dhcp6-pool>
</dhcp6-pools>
</vrf>
</vrfs>
</server>
</dhcp>

```

## Command Syntax

```
ipv6 dhcp server pool NAME
```

---

## Configure pool name

IPv4 DHCP Server address pool name

Attribute Name: pool-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
    <vrf>
      <vrf-name>WORD</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
      </config>
    <dhcp-pools>
    <dhcp-pool> <!-- operation="delete"-->
      <pool-name>NAME</pool-name>
      <config>
        <pool-name>WORD</pool-name>
      </config>
    </dhcp-pool>
  </dhcp-pools>
</vrf>
</vrfs>
</server>
</dhcp>

```

---

## Command Syntax

```
ip dhcp server pool NAME
```

---

## Configure max lease time

Maximum length in seconds that will be assigned to a lease. If not defined, the default maximum lease time is 86400.

Attribute Name: max-lease-time

Attribute Type: int32

Default Value: 86400

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <max-lease-time>SECONDS</max-lease-time> <!-- operation="delete"-->
      </vrf>
    </vrfs>
  </server>
</dhcp>
```

## Command Syntax

```
ip dhcp server max-lease-time SECONDS
```

---

## Configure default lease time

Length in seconds that will be assigned to a lease if the client requesting the lease does not ask for a specific expiration time. The default is 86400

Attribute Name: default-lease-time

Attribute Type: int32

Default Value: 86400

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <default-lease-time>SECONDS</default-lease-time> <!-- operation="delete"-->
      </vrf>
    </vrfs>
  </server>
</dhcp>
```

```

</vrfs>
</server>
</dhcp>

```

## Command Syntax

```
ip dhcp server default-lease-time SECONDS
```

---

## Configure rapid commit

Option enables the DHCP Client to obtain configuration parameters from the server through a rapid two message exchange (solicit and reply).

Attribute Name: rapid-commit

Attribute Type: empty

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        </rapid-commit><!-- operation="delete"-->
      </vrf>
    </vrfs>
  </server>
</dhcp>

```

## Command Syntax

```
ipv6 dhcp server rapid-commit
```

---

## Configure preference

Use this to configure preference option in dhcp server.

Attribute Name: preference

Attribute Type: empty

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        </preference><!-- operation="delete"-->
      </vrf>
    </vrfs>
  </server>
</dhcp>

```

```
</vrf>  
</vrfs>  
</server>  
</dhcp>
```

## Command Syntax

```
ipv6 dhcp server preference
```

---

## Configure vrf name

Option enables the DHCP Client to obtain configuration parameters from the server through a rapid two message exchange (solicit and reply).

Attribute Name: rapid-commit

Attribute Type: empty

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">  
  <server>  
    <vrfs>  
      <vrf>  
        <vrf-name>WORD</vrf-name>  
        <config>  
          <vrf-name>WORD</vrf-name>  
        </config>  
        </rapid-commit><!-- operation="delete"-->  
      </vrf>  
    </vrfs>  
  </server>  
</dhcp>
```

## Command Syntax

```
ipv6 dhcp server rapid-commit
```

---

## Configure vrf preference

Use this to configure preference option in dhcp server.

Attribute Name: preference

Attribute Type: empty

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">  
  <server>  
    <vrfs>  
      <vrf>  
        <vrf-name>WORD</vrf-name>  
        <config>  
          <vrf-name>WORD</vrf-name>  
        </config>  
      </vrf>  
    </vrfs>  
  </server>  
</dhcp>
```

```

        </preference><!-- operation="delete"-->
</vrf>
</vrfs>
</server>
</dhcp>

```

### Command Syntax

```
ipv6 dhcp server preference
```

---

## Configure vrf max-lease-time

Maximum length in seconds that will be assigned to a lease. If not defined, the default maximum lease time is 86400.

Attribute Name: max-lease-time

Attribute Type: int32

Default Value: 86400

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <max-lease-time>SECONDS</max-lease-time> <!-- operation="delete"-->
      </vrf>
    </vrfs>
  </server>
</dhcp>

```

### Command Syntax

```
ip dhcp server max-lease-time SECONDS
```

---

## Configure vrf default-lease-time

Length in seconds that will be assigned to a lease if the client requesting the lease does not ask for a specific expiration time. The default is 86400

Attribute Name: default-lease-time

Attribute Type: int32

Default Value: 86400

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>

```

```

    <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
  </config>
    <default-lease-time>SECONDS</default-lease-time> <!-- operation="delete"-->
</vrf>
</vrfs>
</server>
</dhcp>

```

### Command Syntax

```
ip dhcp server default-lease-time SECONDS
```

---

## Configure dhcp-pools pool-name

IPv4 DHCP Server address pool name

Attribute Name: pool-name

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
      <dhcp-pools>
        <dhcp-pool> <!-- operation="delete"-->
          <pool-name>NAME</pool-name>
          <config>
            <pool-name>WORD</pool-name>
          </config>
        </dhcp-pool>
      </dhcp-pools>
    </vrf>
  </vrfs>
</server>
</dhcp>

```

### Command Syntax

```
ip dhcp server pool NAME
```

---

## Configure host name

IPv4 DHCP Server option to provide hostname details to a DHCP client

Attribute Name: host-name

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <dhcp-pools>
          <dhcp-pool>
            <pool-name>NAME</pool-name>
            <config>
              <pool-name>WORD</pool-name>
            </config>
            <host-name>NAME</host-name> <!-- operation="delete"-->
          </dhcp-pool>
        </dhcp-pools>
      </vrf>
    </vrfs>
  </server>
</dhcp>
```

### Command Syntax

```
host-name NAME
```

---

## Configure routers

IPv4 DHCP Server option to provide routers details to a DHCP client

Attribute Name: routers

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <dhcp-pools>
          <dhcp-pool>
            <pool-name>NAME</pool-name>
```

```

    <config>
      <pool-name>WORD</pool-name>
    </config>
    <!-- operation="delete"-->
  </dhcp-pool>
</dhcp-pools>
</vrf>
</vrfs>
</server>
</dhcp>

```

### Command Syntax

```

routers A.B.C.D

```

---

## Configure ntp server

IPv4 DHCP Server option to provide ntp-server details to a DHCP client

Attribute Name: ntp-server

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
      <dhcp-pools>
        <dhcp-pool>
          <pool-name>NAME</pool-name>
          <config>
            <pool-name>WORD</pool-name>
          </config>
          <ntp-server>A.B.C.D</ntp-server> <!-- operation="delete"-->
        </dhcp-pool>
      </dhcp-pools>
    </vrf>
  </vrfs>
</server>
</dhcp>

```

### Command Syntax

```

ntp-server A.B.C.D

```

---

## Configure boot file

IPv4 DHCP Server option to provide boot-file details to a DHCP client

Attribute Name: boot-file

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <dhcp-pools>
          <dhcp-pool>
            <pool-name>NAME</pool-name>
            <config>
              <pool-name>WORD</pool-name>
            </config>
            <boot-file>BOOTFILE</boot-file> <!-- operation="delete"-->
          </dhcp-pool>
        </dhcp-pools>
      </vrf>
    </vrfs>
  </server>
</dhcp>
```

### Command Syntax

```
boot-file BOOTFILE
```

---

## Configure tftp server

IPv4 DHCP Server option to provide tftp-server details to a DHCP client

Attribute Name: tftp-server

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <dhcp-pools>
          <dhcp-pool>
            <pool-name>NAME</pool-name>
```

```

    <config>
      <pool-name>WORD</pool-name>
    </config>
    <tftp-server>A.B.C.D</tftp-server> <!-- operation="delete"-->
  </dhcp-pool>
</dhcp-pools>
</vrf>
</vrfs>
</server>
</dhcp>

```

### Command Syntax

```
tftp-server A.B.C.D
```

---

## Configure log server

IPv4 DHCP Server option to provide log-server details to a DHCP client

Attribute Name: log-server

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
      <dhcp-pools>
        <dhcp-pool>
          <pool-name>NAME</pool-name>
          <config>
            <pool-name>WORD</pool-name>
          </config>
          <log-server>A.B.C.D</log-server> <!-- operation="delete"-->
        </dhcp-pool>
      </dhcp-pools>
    </vrf>
  </vrfs>
</server>
</dhcp>

```

### Command Syntax

```
log-server A.B.C.D
```

---

## Configure dns server

IPv4 DHCP Server option to provide dns name-server details to a DHCP client

Attribute Name: dns-server

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <dhcp-pools>
          <dhcp-pool>
            <pool-name>NAME</pool-name>
            <config>
              <pool-name>WORD</pool-name>
            </config>
            <dns-server>A.B.C.D</dns-server> <!-- operation="delete"-->
          </dhcp-pool>
        </dhcp-pools>
      </vrf>
    </vrfs>
  </server>
</dhcp>
```

### Command Syntax

```
dns-server A.B.C.D
```

---

## Configure netmask

Mask part of the subnet that will be used to assign IPv4 addresses to hosts

Attribute Name: netmask

Attribute Type: inet:ipv4-address

Attribute Name: network

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <dhcp-pools>
          <dhcp-pool>
```

```

    <pool-name>NAME</pool-name>
  <config>
    <pool-name>WORD</pool-name>
    <network>A.B.C.D</network> <!-- operation="delete"-->
  </config>
    <netmask>A.B.C.D</netmask> <!-- operation="delete"-->
  </dhcp-pool>
</dhcp-pools>
</vrf>
</vrfs>
</server>
</dhcp>

```

## Command Syntax

```
network A.B.C.D netmask A.B.C.D
```

---

## Configure high address in range

Specifies the high range of the IPv4 addresses that the DHCP server should assign to DHCP clients.

Attribute Name: high-address-in-range

Attribute Type: inet:ipv4-address

Attribute Name: low-address-in-range

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
      <dhcp-pools>
        <dhcp-pool>
          <pool-name>NAME</pool-name>
          <config>
            <pool-name>WORD</pool-name>
            <low-address-in-range>A.B.C.D</low-address-in-range> <!--
operation="delete"-->
          </config>
            <high-address-in-range>A.B.C.D</high-address-in-range> <!--
operation="delete"-->
          </dhcp-pool>
        </dhcp-pools>
      </vrf>
    </vrfs>
  </server>
</dhcp>

```

---

## Command Syntax

```
address range low-address A.B.C.D (high-address A.B.C.D|)
```

---

## Configure dhcp6-pools pool6-name

IPv6 DHCP Server address pool name

This command is supported when following feature are enabled IPV6 feature

Attribute Name: pool6-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
      <dhcp6-pools>
        <dhcp6-pool> <!-- operation="delete"-->
          <pool6-name>NAME</pool6-name>
          <config>
            <pool6-name>WORD</pool6-name>
          </config>
        </dhcp6-pool>
      </dhcp6-pools>
    </vrf>
  </vrfs>
</server>
</dhcp>
```

## Command Syntax

```
ipv6 dhcp server pool NAME
```

---

## Configure domain name

IPv6 DHCP Server option to provide domain-name details to a DHCP client

This command is supported when following feature are enabled IPV6 feature

Attribute Name: domain-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
```

```

<server>
<vrfs>
<vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
  </config>
  <dhcp6-pools>
  <dhcp6-pool>
    <pool6-name>NAME</pool6-name>
    <config>
      <pool6-name>WORD</pool6-name>
    </config>
    <domain-name>NAME</domain-name> <!-- operation="delete"-->
  </dhcp6-pool>
</dhcp6-pools>
</vrf>
</vrfs>
</server>
</dhcp>

```

## Command Syntax

domain-name NAME

---

## Configure vendor options

IPv6 DHCP Server option to provide vendor details to a DHCP client

This command is supported when following feature are enabled IPV6 feature

Attribute Name: vendor-options

Attribute Type: string

## Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
<server>
<vrfs>
<vrf>
  <vrf-name>WORD</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
  </config>
  <dhcp6-pools>
  <dhcp6-pool>
    <pool6-name>NAME</pool6-name>
    <config>
      <pool6-name>WORD</pool6-name>
    </config>
    <vendor-options>VENDOR-OPTS</vendor-options> <!-- operation="delete"-->
  </dhcp6-pool>
</dhcp6-pools>
</server>
</dhcp>

```

```

</vrf>
</vrfs>
</server>
</dhcp>

```

## Command Syntax

```
vendor-options VENDOR-OPTS
```

---

## Configure dhcp6-pool ntp-server

IPv6 DHCP Server option to provide ntp-server details to a DHCP client

This command is supported when following feature are enabled IPV6 feature

Attribute Name: ntp-server

Attribute Type: inet:ipv6-address

## Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <dhcp6-pools>
          <dhcp6-pool>
            <pool6-name>NAME</pool6-name>
            <config>
              <pool6-name>WORD</pool6-name>
            </config>
            <ntp-server>X:X::X:X</ntp-server> <!-- operation="delete"-->
          </dhcp6-pool>
        </dhcp6-pools>
      </vrf>
    </vrfs>
  </server>
</dhcp>

```

## Command Syntax

```
ntp-server X:X::X:X
```

---

## Configure dhcp6-pool dns-server

IPv6 DHCP Server option to provide dns name-server details to a DHCP client

This command is supported when following feature are enabled IPV6 feature

Attribute Name: dns-server

Attribute Type: inet:ipv6-address

**Netconf edit-config payload**

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <dhcp6-pools>
          <dhcp6-pool>
            <pool6-name>NAME</pool6-name>
            <config>
              <pool6-name>WORD</pool6-name>
            </config>
            <dns-server>X:X::X:X</dns-server> <!-- operation="delete"-->
          </dhcp6-pool>
        </dhcp6-pools>
      </vrf>
    </vrfs>
  </server>
</dhcp>

```

**Command Syntax**

```
dns-server X:X::X:X
```

---

**Configure ipv6 netmask**

Mask part of the subnet that will be used to assign IPv6 addresses to hosts

This command is supported when following feature are enabled IPV6 feature

Attribute Name: ipv6-netmask

Attribute Type: uint8

Attribute Range: 1-128

Attribute Name: ipv6-network

Attribute Type: inet:ipv6-address

**Netconf edit-config payload**

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
      <dhcp6-pools>
        <dhcp6-pool>

```

```

    <pool6-name>NAME</pool6-name>
    <config>
      <pool6-name>WORD</pool6-name>
      <ipv6-network>X:X::X:X</ipv6-network> <!-- operation="delete"-->
    </config>
    <ipv6-netmask>1</ipv6-netmask> <!-- operation="delete"-->
  </dhcp6-pool>
</dhcp6-pools>
</vrf>
</vrfs>
</server>
</dhcp>

```

## Command Syntax

```
network X:X::X:X netmask <1-128>
```

---

## Configure low address in range

Specifies the high range of the IPv6 addresses that the DHCP server should assign to DHCP clients.

This command is supported when following feature are enabled IPV6 feature

Attribute Name: high-address-in-range

Attribute Type: inet:ipv6-address

Attribute Name: low-address-in-range

Attribute Type: inet:ipv6-address

## Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <dhcp6-pools>
          <dhcp6-pool>
            <pool6-name>NAME</pool6-name>
            <config>
              <pool6-name>WORD</pool6-name>
              <low-address-in-range>X:X::X:X</low-address-in-range> <!--
operation="delete"-->
            </config>
              <high-address-in-range>X:X::X:X</high-address-in-range> <!--
operation="delete"-->
            </dhcp6-pool>
          </dhcp6-pools>
        </vrf>
      </vrfs>

```

```
</server>
</dhcp>
```

## Command Syntax

```
address range low-address X:X::X:X (high-address X:X::X:X|)
```

---

## Configure temporary address

Specifies the temporary IPv6 address that the DHCP server should assign to DHCP clients.

This command is supported when following feature are enabled IPV6 feature

Attribute Name: temporary-address

Attribute Type: inet:ipv6-address

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <dhcp6-pools>
          <dhcp6-pool>
            <pool6-name>NAME</pool6-name>
            <config>
              <pool6-name>WORD</pool6-name>
            </config>
            <temporary-address>X:X::X:X</temporary-address> <!-- operation="delete"-->
          >
        </dhcp6-pool>
      </dhcp6-pools>
    </vrf>
  </vrfs>
</server>
</dhcp>
```

## Command Syntax

```
temporary address X:X::X:X
```

---

## Configure ipv6 prefix netmask

Mask part of the ipv6 Prefix used for Prefix delegation

This command is supported when following feature are enabled IPV6 feature

Attribute Name: ipv6-prefix-netmask

Attribute Type: uint8

Attribute Range: 1-128

Attribute Name: ipv6-prefix-high-address

Attribute Type: inet:ipv6-address

Attribute Name: ipv6-prefix-low-address

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <server>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <dhcp6-pools>
          <dhcp6-pool>
            <pool6-name>NAME</pool6-name>
            <config>
              <pool6-name>WORD</pool6-name>
              <ipv6-prefix-high-address>X:X::X:X</ipv6-prefix-high-address> <!--
operation="delete"-->
              <ipv6-prefix-low-address>X:X::X:X</ipv6-prefix-low-address> <!--
operation="delete"-->
            </config>
            <ipv6-prefix-netmask>1</ipv6-prefix-netmask> <!-- operation="delete"-->
          </dhcp6-pool>
        </dhcp6-pools>
      </vrf>
    </vrfs>
  </server>
</dhcp>
```

### Command Syntax

```
prefix high-range X:X::X:X low-range X:X::X:X netmask <1-128>
```

---

## IPI-SFLOW

---

### Configure enabled

Use this attribute to enable or disable Sampled Flow (sFlow) feature globally.

Attribute Name: enabled

Attribute Type: empty

### Netconf edit-config payload

```
<sampling xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow">
  <sflow>
```

```
<config>
  </enabled>
</config>
</sflow>
</sampling>
```

## Command Syntax

```
feature sflow
```

---

## Configure source address

The IP address associated with this agent. In the case of a multi-homed agent, this should be the loopback address of the agent. The sFlowAgent address must provide SNMP connectivity to the agent. The address should be an invariant that does not change as interfaces are reconfigured, enabled, disabled, added or removed. A manager should be able to use the sFlowAgentAddress as a unique key that will identify this agent over extended periods of time so that a history can be maintained.

Attribute Name: source-address

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```
<sampling xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow">
  <sflow>
    <config>
      <source-address>A.B.C.D</source-address> <!-- operation="delete"-->
    </config>
  </sflow>
</sampling>
```

## Command Syntax

```
sflow agent-ip A.B.C.D
```

---

## Configure cpu rate limit

CPU rate in packets per second

Attribute Name: cpu-rate-limit

Attribute Type: uint32

Attribute Range: 2000-100000

## Netconf edit-config payload

```
<sampling xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow">
  <sflow>
    <config>
      <cpu-rate-limit>2000</cpu-rate-limit> <!-- operation="delete"-->
    </config>
  </sflow>
</sampling>
```

## Command Syntax

```
sflow rate-limit <2000-100000>
```

---

## Configure vrf name

The VRF name from which this collector is reachable.

Attribute Name: vrf-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: receiver-timeout

Attribute Type: uint32

Attribute Range: 0-2147483647

Attribute Name: max-datagram-size

Attribute Type: uint16

Attribute Range: 200-9000

## Netconf edit-config payload

```
<sampling xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow">
  <sflow>
    <collectors>
      <collector>
        <collector-id>1</collector-id>
        <config>
          <collector-id>1</collector-id>
          <port>1024</port>
          <address>A.B.C.D</address>
          <receiver-timeout>0</receiver-timeout> <!-- operation="delete"-->
          <max-datagram-size>200</max-datagram-size> <!-- operation="delete"-->
        </config>
      </collector>
    </collectors>
  </sflow>
</sampling>
```

## Command Syntax

```
sflow (collector-id <1-5>|) collector A.B.C.D port <1024-65535> receiver-time-out
<0-2147483647> max-datagram-size <200-9000> (vrf WORD|)
```

---

## Configure max entries

Specifies the maximum number of log entries that are cached, default is 1000 entries

This command is supported when following feature are enabled custom1 access-list options

Attribute Name: max-entries

Attribute Type: uint16

Default Value: 1000

Attribute Range: 1000-10000

### Netconf edit-config payload

```
<sampling xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow">
  <sflow>
    <logging>
      <config>
        <max-entries>1000</max-entries> <!-- operation="delete"-->
      </config>
    </logging>
  </sflow>
</sampling>
```

### Command Syntax

```
access-list logging cache-size <1000-10000>
```

---

## Configure rate limit

Configures rate limits in packets per second, Default is 200 packets/sec

This command is supported when following feature are enabled custom1 access-list options

Attribute Name: rate-limit

Attribute Type: uint16

Default Value: 200

Attribute Range: 0-1000

### Netconf edit-config payload

```
<sampling xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow">
  <sflow>
    <logging>
      <config>
        <rate-limit>0</rate-limit> <!-- operation="delete"-->
      </config>
    </logging>
  </sflow>
</sampling>
```

### Command Syntax

```
access-list logging rate-limit <0-1000>
```

---

## Configure options

Set sFlow debug in config mode

Attribute Name: options

---

Attribute Type: bits (agent|sampling|polling|all)

### Netconf edit-config payload

```
<sampling xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow">
  <sflow>
    <debug>
      <config>
        <options>agent</options> <!-- operation="delete"-->
      </config>
    </debug>
  </sflow>
</sampling>
```

### Command Syntax

```
debug sflow (agent|sampling|polling|all)
```

---

## clear access-list log-cache

### Netconf RPC payload

```
<sflow-clear-access-list-log-cache xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-sflow"/>
```

### Command Syntax

```
clear access-list log-cache
```

---

## debug sflow (agent|sampling|polling|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (agent|sampling|polling|all)

### Netconf RPC payload

```
<sflow-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow">
  <terminal-debug-options>agent</terminal-debug-options>
</sflow-terminal-debug-on>
```

### Command Syntax

```
debug sflow (agent|sampling|polling|all)
```

---

## no debug sflow (agent|sampling|polling|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (agent|sampling|polling|all)

### Netconf RPC payload

```
<sflow-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
sflow">
  <terminal-debug-options>agent</terminal-debug-options>
</sflow-terminal-debug-off>
```

## Command Syntax

```
no debug sflow (agent|sampling|polling|all)
```

# IPI-SFLOW-INTERFACE

## Configure enabled

To enable or disable sampling on an interface after giving the sflow sampling-rate command on the same interface

Attribute Name: enabled

Attribute Type: empty

## Netconf edit-config payload

```
<sampling xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow">
  <sflow>
    <interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow-interface">
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        </enabled><!-- operation="delete"-->
      </interface>
    </interfaces>
  </sflow>
</sampling>
```

## Command Syntax

```
sflow enable
```

## Configure polling interval

The maximum number of seconds between successive samples of the counters associated with this data source. A sampling interval of 0 disables counter sampling. The agent is permitted to have minimum and maximum allowable values for the counter polling interval. A minimum interval lets the agent designer set an upper bound on the overhead associated with polling, and a maximum interval may be the result of implementation restrictions (such as counter size). In addition, not all values between the maximum and minimum may be realizable as the sampling interval (again because of implementation considerations). When the sampling rate is set, the agent is free to adjust the value so that it lies between the maximum and minimum values and has the closest achievable value. When read, the agent must return the actual sampling interval it will be using (after the adjustments previously described). The sampling algorithm must converge so that over time the number of packets sampled approaches 1/Nth of the total number of packets in the monitored flows.

Attribute Name: polling-interval

Attribute Type: uint8

Attribute Range: 5-60

## Netconf edit-config payload

```
<sampling xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow">
<sflow>
  <interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow-interface">
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <polling-interval>5</polling-interval> <!-- operation="delete"-->
    </interface>
  </interfaces>
</sflow>
</sampling>
```

## Command Syntax

```
sflow poll-interval <5-60>
```

---

## Configure collector id

Add a collector id to the interface so that it can be used by sflow to send the data.

Attribute Name: collector-id

Attribute Type: uint8

Default Value: 1

Attribute Range: 1-5

## Netconf edit-config payload

```
<sampling xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow">
<sflow>
  <interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow-interface">
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <collector-id>1</collector-id> <!-- operation="delete"-->
    </interface>
  </interfaces>
</sflow>
</sampling>
```

## Command Syntax

```
sflow collector-id <1-5>
```

---

## Configure sample size

The maximum number of bytes that should be copied from a sampled packet. The agent may have an internal maximum and minimum permissible sizes. If an attempt is made to set this value outside the permissible range then the agent should adjust the value to the closest permissible value.

Attribute Name: sample-size

Attribute Type: uint16

Attribute Range: 16-256

Attribute Name: sampling-rate

Attribute Type: uint32

Attribute Range: 1024-16777215

## Netconf edit-config payload

```
<sampling xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow">
  <sflow>
    <interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow-interface">
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
          </config>
          <ingress>
            <config>
              <sampling-rate>1024</sampling-rate>
              <sample-size>16</sample-size>
            </config>
          </ingress>
        </interface>
      </interfaces>
    </sflow>
  </sampling>
```

## Command Syntax

```
sflow sampling-rate <1024-16777215> direction ingress max-header-size <16-256>
```

---

## Configure name

The maximum number of bytes that should be copied from a sampled packet. The agent may have an internal maximum and minimum permissible sizes. If an attempt is made to set this value outside the permissible range then the agent should adjust the value to the closest permissible value.

Attribute Name: sample-size

Attribute Type: uint16

Attribute Range: 16-256

Attribute Name: sampling-rate

Attribute Type: uint32

Attribute Range: 1024-16777215

### Netconf edit-config payload

```
<sampling xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow">
  <sflow>
    <interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow-interface">
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <egress>
          <config>
            <sampling-rate>1024</sampling-rate>
            <sample-size>16</sample-size>
          </config>
        </egress>
      </interface>
    </interfaces>
  </sflow>
</sampling>
```

### Command Syntax

```
sflow sampling-rate <1024-16777215> direction egress max-header-size <16-256>
```

---

## clear sflow statistics (interface IFNAME|)

Attribute Name: interface

Attribute Type: string

### Netconf RPC payload

```
<sflow-clear-statistics xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sflow-
interface">
  <interface>IFNAME</interface>
</sflow-clear-statistics>
```

### Command Syntax

```
clear sflow statistics (interface IFNAME|)
```

---

## IPI-WATCHDOG

---

### Configure watchdog disabled

Disable software watchdog functionality for all modules. This feature is enabled by default.

Attribute Name: watchdog-disabled

Attribute Type: uint8

---

### Netconf edit-config payload

```
<watchdog xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-watchdog">
<config>
  </watchdog-disabled><!-- operation="delete"-->
</config>
</watchdog>
```

### Command Syntax

```
no feature software-watchdog
```

---

## Configure keepalive interval

Software watchdog keep-alive time interval in seconds. Default value is 60 seconds.

This command is supported when following feature are enabled Watchdog feature

Attribute Name: keepalive-interval

Attribute Type: uint16

Default Value: 60

Attribute Range: 30-1800

### Netconf edit-config payload

```
<watchdog xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-watchdog">
<config>
  <keepalive-interval>30</keepalive-interval> <!-- operation="delete"-->
</config>
</watchdog>
```

### Command Syntax

```
software-watchdog keep-alive-time <30-1800>
```

---

## Configure module watchdog status disabled

Enable software watchdog functionality for a particular software module.

Attribute Name: module-watchdog-status-disabled

Attribute Type: uint8

### Netconf edit-config payload

```
<watchdog xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-watchdog">
<software-modules>
<software-module>
  <name>nsm</name>
  <config>
    <name>nsm</name>
  </config>
  </module-watchdog-status-disabled><!-- operation="delete"-->
</software-module>
</software-modules>
```

---

```
</watchdog>
```

## Command Syntax

```
no software-watchdog
  (nsm|ripd|ripngd|ospfd|ospf6d|isisd|hostpd|mribd|pimd|authd|mstpd|imi|onmd|hsl|o
  amd|vlogd|vrrpd|nnd|ribd|bgpd|l2mribd|lagd|sflow|udld|cmlld|cmmd)
```

---

## clear cores (WORD|)

Attribute Name: core-dump

Attribute Type: string

### Netconf RPC payload

```
<clear-core-dump xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-watchdog">
  <core-dump>WORD</core-dump>
</clear-core-dump>
```

## Command Syntax

```
clear cores (WORD|)
```

---

## sys-update un-install

### Netconf RPC payload

```
<sys-update-uninstall xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sys-
update"/>
```

## Command Syntax

```
sys-update un-install
```

---

## sys-container (raon) (install|update) file FILENAME

Attribute Name: type

Attribute Type: enum (raon)

Attribute Name: upgrade-type

Attribute Type: enum (install|update)

Attribute Name: file

Attribute Type: string

### Netconf RPC payload

```
<sys-container-install xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sys-
update">
  <type>raon</type>
  <upgrade-type>install</upgrade-type>
  <file>FILENAME</file>
</sys-container-install>
```

---

## Command Syntax

```
sys-container (raon) (install|update) file FILENAME
```

---

## sys-container (raon) un-install

Attribute Name: type

Attribute Type: enum (raon)

Attribute Name: un-install

Attribute Type: boolean

Default Value: false

## Netconf RPC payload

```
<sys-container-uninstall xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sys-
update">
  <type>raon</type>
  <un-install>true</un-install/>
</sys-container-uninstall>
```

## Command Syntax

```
sys-container (raon) un-install
```

---

## sys-container (raon) (start|stop|restart)

Attribute Name: type

Attribute Type: enum (raon)

Attribute Name: boot-type

Attribute Type: enum (start|stop|restart)

## Netconf RPC payload

```
<sys-container-boot xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sys-update">
  <type>raon</type>
  <boot-type>start</boot-type>
</sys-container-boot>
```

## Command Syntax

```
sys-container (raon) (start|stop|restart)
```

---

## sys-container (raon) get URL (source-interface IFNAME|)

Attribute Name: type

Attribute Type: enum (raon)

Attribute Name: url

Attribute Type: string

Attribute Name: source-interface

Attribute Type: string

### Netconf RPC payload

```
<sys-container-get xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sys-update">
  <type>raon</type>
  <url>URL</url>
  <source-interface>IFNAME</source-interface>
</sys-container-get>
```

### Command Syntax

```
sys-container (raon) get URL (source-interface IFNAME|)
```

---

## sys-container (raon) remove file FILENAME

Attribute Name: type

Attribute Type: enum (raon)

Attribute Name: file

Attribute Type: string

### Netconf RPC payload

```
<sys-container-remove xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sys-
update">
  <type>raon</type>
  <file>FILENAME</file>
</sys-container-remove>
```

### Command Syntax

```
sys-container (raon) remove file FILENAME
```

---

## sys-container (raon) verify image FILEPATH signature FILEPATH

Attribute Name: type

Attribute Type: enum (raon)

Attribute Name: image

Attribute Type: string

Attribute Name: signature

Attribute Type: string

### Netconf RPC payload

```
<sys-container-verify xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sys-
update">
  <type>raon</type>
  <image>FILEPATH</image>
  <signature>FILEPATH</signature>
</sys-container-verify>
```

## Command Syntax

```
sys-container (raon) verify image FILEPATH signature FILEPATH
```

---

## sys-container cancel download

### Netconf RPC payload

```
<sys-container-cancel-download xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-sys-update"/>
```

### Command Syntax

```
sys-container cancel download
```

---

## IPI-MRIB-IPV4

---

### Configure options

Use this attribute to specify debug options

Attribute Name: options

Attribute Type: bits (all|event|vif|mrt|stats|fib-msg|register-msg|nsm-msg|mrrib-msg|mtrace|mtrace-detail)

### Netconf edit-config payload

```
<mrrib xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mrrib">
  <ipv4>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <debug>
          <config>
            <options>all</options> <!-- operation="delete"-->
          </config>
        </debug>
      </vrf>
    </vrfs>
  </ipv4>
</mrrib>
```

### Command Syntax

```
debug ip mrrib (vrf WORD|) (all|event|vif|mrt|stats|fib-msg|register-msg|nsm-
msg|mrrib-msg|mtrace|mtrace-detail)
```

---

## Configure multicast routing enable

Use this attribute to turn on/off multicast routing on the router when turned off, the multicast protocol daemon remains present, but does not perform multicast functions. When multicast routing is enabled, the MRIB re-creates tunnels, and starts processing any VIF addition/deletion requests, MRT addition/deletion requests, and any multicast forwarding events.

Attribute Name: multicast-routing-enable

Attribute Type: uint8

### Netconf edit-config payload

```
<mrib xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mrib">
  <ipv4>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        </multicast-routing-enable><!-- operation="delete"-->
      </vrf>
    </vrfs>
  </ipv4>
</mrib>
```

### Command Syntax

```
ip multicast-routing (vrf WORD|)
```

---

## Configure maximum routes

Use this attribute to limit the number of multicast routes that can be added to a multicast routing table. It generates an error message when the limit is exceeded.

Attribute Name: maximum-routes

Attribute Type: uint32

Attribute Range: 1-2147483647

### Netconf edit-config payload

```
<mrib xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mrib">
  <ipv4>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
          </config>
          <route-limit>
            <config>
              <maximum-routes>1</maximum-routes> <!-- operation="delete"-->
            </config>
          </route-limit>
        </config>
      </vrf>
    </vrfs>
  </ipv4>
</mrib>
```

```

</route-limit>
</vrf>
</vrfs>
</ipv4>
</mrib>

```

## Command Syntax

```
ip multicast (vrf WORD|) route-limit <1-2147483647>
```

---

## Configure warning threshold

Use this attribute to limit the number of multicast routes that can be added to a multicast routing table. It generates an error message when the limit is exceeded. If the threshold parameter is set, a threshold warning message is generated when this threshold is exceeded and the message continues to occur until the number of mroutes reaches the limit set by the limit argument.

Attribute Name: warning-threshold

Attribute Type: uint32

Attribute Range: 1-2147483647

Attribute Name: maximum-routes

Attribute Type: uint32

Attribute Range: 1-2147483647

## Netconf edit-config payload

```

<mrib xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mrib">
  <ipv4>
    <vrfs>
      <vrf>
        <vrf-name>WORD</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
          </config>
          <route-limit>
            <config>
              <maximum-routes>1</maximum-routes> <!-- operation="delete"-->
              <warning-threshold>1</warning-threshold> <!-- operation="delete"-->
            </config>
          </route-limit>
        </vrf>
      </vrfs>
    </ipv4>
  </mrib>

```

## Command Syntax

```
ip multicast (vrf WORD|) route-limit <1-2147483647> <1-2147483647>
```

---

## Configure ttl threshold

Use this attribute to configure the time-to-live (TTL) threshold of packets being forwarded out of an interface. Only multicast packets with a TTL value greater than the threshold are forwarded out of the interface.

Attribute Name: ttl-threshold

Attribute Type: uint8

Attribute Range: 1-255

### Netconf edit-config payload

```
<mrib xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mrib">
  <ipv4>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <ttl-threshold>1</ttl-threshold> <!-- operation="delete"-->
      </interface>
    </interfaces>
  </ipv4>
</mrib>
```

### Command Syntax

```
ip multicast ttl-threshold <1-255>
```

---

## debug ip mrib (vrf WORD|) (all|event|vif|mrt|stats|fib-msg|register-msg|nsm-msg|mrib-msg|mtrace|mtrace-detail)

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: terminal-debug-options

Attribute Type: bits (all|event|vif|mrt|stats|fib-msg|register-msg|nsm-msg|mrib-msg|mtrace|mtrace-detail)

### Netconf RPC payload

```
<ipi-mrib-ipv4_mrib-ipv4-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mrib">
  <vrf-name>WORD</vrf-name>
  <terminal-debug-options>all</terminal-debug-options>
</ipi-mrib-ipv4_mrib-ipv4-terminal-debug-on>
```

### Command Syntax

```
debug ip mrib (vrf WORD|) (all|event|vif|mrt|stats|fib-msg|register-msg|nsm-msg|mrib-msg|mtrace|mtrace-detail)
```

---

## no debug ip mrib (vrf WORD|) (all|event|vif|mrt|stats|fib-msg|register-msg|nsm-msg|mrib-msg|mtrace|mtrace-detail)

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: terminal-debug-options

Attribute Type: bits (all|event|vif|mrt|stats|fib-msg|register-msg|nsm-msg|mrib-msg|mtrace|mtrace-detail)

### Netconf RPC payload

```
<ipi-mrib-ipv4_mrib-ipv4-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mrib">
  <vrf-name>WORD</vrf-name>
  <terminal-debug-options>all</terminal-debug-options>
</ipi-mrib-ipv4_mrib-ipv4-terminal-debug-off>
```

### Command Syntax

```
no debug ip mrib (vrf WORD|) (all|event|vif|mrt|stats|fib-msg|register-msg|nsm-
msg|mrib-msg|mtrace|mtrace-detail)
```

---

## clear ip mroute (vrf NAME|) \*

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: all-routes

Attribute Type: empty

### Netconf RPC payload

```
<ipi-mrib-ipv4_mrib-ipv4-clear-mroute-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mrib">
  <vrf-name>NAME</vrf-name>
  <all-routes>CML_EMPTY_T</all-routes>
</ipi-mrib-ipv4_mrib-ipv4-clear-mroute-all>
```

### Command Syntax

```
clear ip mroute (vrf NAME|) *
```

---

## clear ip mroute (vrf NAME|) A.B.C.D

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: group-address

Attribute Type: inet:ipv4-address

### Netconf RPC payload

```
<ipi-mrib-ipv4_mrib-ipv4-clear-mroute-group xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mrib">
```

```
<vrf-name>NAME</vrf-name>
<group-address>A.B.C.D</group-address>
</ipi-mrib-ipv4_mrib-ipv4-clear-mroute-group>
```

## Command Syntax

```
clear ip mroute (vrf NAME|) A.B.C.D
```

---

## clear ip mroute (vrf NAME|) A.B.C.D A.B.C.D

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: group-address

Attribute Type: inet:ipv4-address

Attribute Name: source-address

Attribute Type: inet:ipv4-address

## Netconf RPC payload

```
<ipi-mrib-ipv4_mrib-ipv4-clear-mroute-source-group xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-mrib">
  <vrf-name>NAME</vrf-name>
  <group-address>A.B.C.D</group-address>
  <source-address>A.B.C.D</source-address>
</ipi-mrib-ipv4_mrib-ipv4-clear-mroute-source-group>
```

## Command Syntax

```
clear ip mroute (vrf NAME|) A.B.C.D A.B.C.D
```

---

## clear ip mroute (vrf NAME|) statistics \*

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: all-routes

Attribute Type: empty

## Netconf RPC payload

```
<ipi-mrib-ipv4_mrib-ipv4-clear-mroute-statistics-all xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-mrib">
  <vrf-name>NAME</vrf-name>
  <all-routes>CML_EMPTY_T</all-routes>
</ipi-mrib-ipv4_mrib-ipv4-clear-mroute-statistics-all>
```

## Command Syntax

```
clear ip mroute (vrf NAME|) statistics *
```

---

## clear ip mroute (vrf NAME|) statistics A.B.C.D

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: group-address

Attribute Type: inet:ipv4-address

### Netconf RPC payload

```
<ipi-mrib-ipv4_mrib-ipv4-clear-mroute-statistics-group xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-mrib">
  <vrf-name>NAME</vrf-name>
  <group-address>A.B.C.D</group-address>
</ipi-mrib-ipv4_mrib-ipv4-clear-mroute-statistics-group>
```

### Command Syntax

```
clear ip mroute (vrf NAME|) statistics A.B.C.D
```

---

## clear ip mroute (vrf NAME|) statistics A.B.C.D A.B.C.D

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: group-address

Attribute Type: inet:ipv4-address

Attribute Name: source-address

Attribute Type: inet:ipv4-address

### Netconf RPC payload

```
<ipi-mrib-ipv4_mrib-ipv4-clear-mroute-statistics-source-group xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-mrib">
  <vrf-name>NAME</vrf-name>
  <group-address>A.B.C.D</group-address>
  <source-address>A.B.C.D</source-address>
</ipi-mrib-ipv4_mrib-ipv4-clear-mroute-statistics-source-group>
```

### Command Syntax

```
clear ip mroute (vrf NAME|) statistics A.B.C.D A.B.C.D
```

---

## snmp restart mrib

### Netconf RPC payload

```
<ipi-mrib-ipv4_mrib-ipv4-snmp-restart xmlns="http://www.ipinfusion.com/yang/
ocnos/ipi-mrib"/>
```

### Command Syntax

```
snmp restart mrib
```

---

## IPI-MRIB-IPV6

---

### Configure options

Use this attribute to specify debug options

Attribute Name: options

Attribute Type: bits (all|event|vif|mrt|stats|fib-msg|register-msg|nsm-msg|mrrib-msg|mtrace|mtrace-detail)

### Netconf edit-config payload

```
<mrrib xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mrrib">
  <ipv6>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <debug>
          <config>
            <options>all</options> <!-- operation="delete"-->
          </config>
        </debug>
      </vrf>
    </vrfs>
  </ipv6>
</mrrib>
```

### Command Syntax

```
debug ipv6 mrrib (vrf NAME|) (all|event|vif|mrt|stats|fib-msg|register-msg|nsm-
msg|mrrib-msg|mtrace|mtrace-detail)
```

---

## Configure multicast routing enable

Use this attribute to turn on/off multicast routing on the router when turned off, the multicast protocol daemon remains present, but does not perform multicast functions. When multicast routing is enabled, the MRIB re-creates tunnels, and starts processing any VIF addition/deletion requests, MRT addition/deletion requests, and any multicast forwarding events.

Attribute Name: multicast-routing-enable

Attribute Type: uint8

### Netconf edit-config payload

```
<mrrib xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mrrib">
  <ipv6>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
```

```

<config>
  <vrf-name>WORD</vrf-name>
</config>
  </multicast-routing-enable><!-- operation="delete"-->
</vrf>
</vrfs>
</ipv6>
</mrib>

```

## Command Syntax

```
ipv6 multicast-routing (vrf NAME|)
```

---

## Configure maximum routes

Use this attribute to limit the number of multicast routes that can be added to a multicast routing table. It generates an error message when the limit is exceeded.

Attribute Name: maximum-routes

Attribute Type: uint32

Attribute Range: 1-2147483647

## Netconf edit-config payload

```

<mrib xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mrib">
<ipv6>
<vrfs>
<vrf>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
  </config>
  <route-limit>
    <config>
      <maximum-routes>1</maximum-routes> <!-- operation="delete"-->
    </config>
  </route-limit>
</vrf>
</vrfs>
</ipv6>
</mrib>

```

## Command Syntax

```
ipv6 multicast (vrf NAME|) route-limit <1-2147483647>
```

---

## Configure warning threshold

Use this attribute to limit the number of multicast routes that can be added to a multicast routing table. It generates an error message when the limit is exceeded. If the threshold parameter is set, a threshold warning message is generated when this threshold is exceeded and the message continues to occur until the number of mroutes reaches the limit set by the limit argument.

Attribute Name: warning-threshold

Attribute Type: uint32

Attribute Range: 1-2147483647

Attribute Name: maximum-routes

Attribute Type: uint32

Attribute Range: 1-2147483647

### Netconf edit-config payload

```
<mrib xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mrib">
  <ipv6>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <route-limit>
          <config>
            <maximum-routes>1</maximum-routes> <!-- operation="delete"-->
            <warning-threshold>1</warning-threshold> <!-- operation="delete"-->
          </config>
        </route-limit>
      </vrf>
    </vrfs>
  </ipv6>
</mrib>
```

### Command Syntax

```
ipv6 multicast (vrf NAME|) route-limit <1-2147483647> <1-2147483647>
```

## debug ipv6 mrib (vrf WORD|) (all|event|vif|mrt|stats|fib-msg|register-msg|nsm-msg|mrib-msg|mtrace|mtrace-detail)

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: terminal-debug-options

Attribute Type: bits (all|event|vif|mrt|stats|fib-msg|register-msg|nsm-msg|mrib-msg|mtrace|mtrace-detail)

### Netconf RPC payload

```
<ipi-mrib-ipv6_mrib-ipv6-terminal-debug-on xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-mrib">
  <vrf-name>WORD</vrf-name>
  <terminal-debug-options>all</terminal-debug-options>
</ipi-mrib-ipv6_mrib-ipv6-terminal-debug-on>
```

---

## Command Syntax

```
debug ipv6 mrib (vrf WORD|) (all|event|vif|mrt|stats|fib-msg|register-msg|nsm-
msg|mrib-msg|mtrace|mtrace-detail)
```

---

## no debug ipv6 mrib (vrf WORD|) (all|event|vif|mrt|stats|fib-msg|register- msg|nsm-msg|mrib-msg|mtrace|mtrace-detail)

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: terminal-debug-options

Attribute Type: bits (all|event|vif|mrt|stats|fib-msg|register-msg|nsm-msg|mrib-msg|mtrace|mtrace-detail)

## Netconf RPC payload

```
<ipi-mrib-ipv6_mrib-ipv6-terminal-debug-off xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-mrib">
  <vrf-name>WORD</vrf-name>
  <terminal-debug-options>all</terminal-debug-options>
</ipi-mrib-ipv6_mrib-ipv6-terminal-debug-off>
```

## Command Syntax

```
no debug ipv6 mrib (vrf WORD|) (all|event|vif|mrt|stats|fib-msg|register-msg|nsm-
msg|mrib-msg|mtrace|mtrace-detail)
```

---

## clear ipv6 mroute (vrf NAME|) \*

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: all-routes

Attribute Type: empty

## Netconf RPC payload

```
<ipi-mrib-ipv6_mrib-ipv6-clear-mroute-all xmlns="http://www.ipinfusion.com/yang/
ocnos/ipi-mrib">
  <vrf-name>NAME</vrf-name>
  <all-routes>CML_EMPTY_T</all-routes>
</ipi-mrib-ipv6_mrib-ipv6-clear-mroute-all>
```

## Command Syntax

```
clear ipv6 mroute (vrf NAME|) *
```

---

## clear ipv6 mroute (vrf NAME|) X:X::X:X

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: group-address

Attribute Type: inet:ipv6-address

**Netconf RPC payload**

```
<ipi-mrib-ipv6_mrib-ipv6-clear-mroute-group xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-mrib">
  <vrf-name>NAME</vrf-name>
  <group-address>X:X::X:X</group-address>
</ipi-mrib-ipv6_mrib-ipv6-clear-mroute-group>
```

**Command Syntax**

```
clear ipv6 mroute (vrf NAME|) X:X::X:X
```

**clear ipv6 mroute (vrf NAME|) X:X::X:X X:X::X:X**

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: group-address

Attribute Type: inet:ipv6-address

Attribute Name: source-address

Attribute Type: inet:ipv6-address

**Netconf RPC payload**

```
<ipi-mrib-ipv6_mrib-ipv6-clear-mroute-source-group xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-mrib">
  <vrf-name>NAME</vrf-name>
  <group-address>X:X::X:X</group-address>
  <source-address>X:X::X:X</source-address>
</ipi-mrib-ipv6_mrib-ipv6-clear-mroute-source-group>
```

**Command Syntax**

```
clear ipv6 mroute (vrf NAME|) X:X::X:X X:X::X:X
```

**clear ipv6 mroute (vrf NAME|) statistics \***

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: all-routes

Attribute Type: empty

**Netconf RPC payload**

```
<ipi-mrib-ipv6_mrib-ipv6-clear-mroute-statistics-all xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-mrib">
  <vrf-name>NAME</vrf-name>
  <all-routes>CML_EMPTY_T</all-routes>
</ipi-mrib-ipv6_mrib-ipv6-clear-mroute-statistics-all>
```

**Command Syntax**

```
clear ipv6 mroute (vrf NAME|) statistics *
```

---

## clear ipv6 mroute (vrf NAME|) statistics X:X::X:X

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: group-address

Attribute Type: inet:ipv6-address

### Netconf RPC payload

```
<ipi-mrib-ipv6_mrib-ipv6-clear-mroute-statistics-group xmlns="http://
www.ipinfusion.com/yāng/ocnos/ipi-mrib">
  <vrf-name>NAME</vrf-name>
  <group-address>X:X::X:X</group-address>
</ipi-mrib-ipv6_mrib-ipv6-clear-mroute-statistics-group>
```

### Command Syntax

```
clear ipv6 mroute (vrf NAME|) statistics X:X::X:X
```

---

## clear ipv6 mroute (vrf NAME|) statistics X:X::X:X X:X::X:X

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: group-address

Attribute Type: inet:ipv6-address

Attribute Name: source-address

Attribute Type: inet:ipv6-address

### Netconf RPC payload

```
<ipi-mrib-ipv6_mrib-ipv6-clear-mroute-statistics-source-group xmlns="http://
www.ipinfusion.com/yāng/ocnos/ipi-mrib">
  <vrf-name>NAME</vrf-name>
  <group-address>X:X::X:X</group-address>
  <source-address>X:X::X:X</source-address>
</ipi-mrib-ipv6_mrib-ipv6-clear-mroute-statistics-source-group>
```

### Command Syntax

```
clear ipv6 mroute (vrf NAME|) statistics X:X::X:X X:X::X:X
```

---

## IPI-IGMP

---

### Configure disable ssm map

Use this attribute to enable the IGMP operation on an interface. This command enables IGMP operation in standalone mode, and can be used to learn local-membership information prior to enabling a multicast routing protocol on the interface. This command will have no effect on interfaces configured for IGMP proxy.

Attribute Name: disable-ssm-map

Attribute Type: empty

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    </disable-ssm-map><!-- operation="delete"-->
  </vrf>
</vrfs>
</igmp>
```

### Command Syntax

```
no ip igmp (vrf NAME|) ssm-map enable
```

---

## Configure disable tos check

Use this attribute to disable TOS check for Internetnetwork Control

Attribute Name: disable-tos-check

Attribute Type: empty

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    </disable-tos-check><!-- operation="delete"-->
  </vrf>
</vrfs>
</igmp>
```

### Command Syntax

```
no ip igmp (vrf NAME|) tos-check
```

---

## Configure limit exception acl

Use this attribute to set the maximum number of group membership states, at either the router level or at the interface level. Once the specified number of group memberships is reached, all further local-memberships are ignored.

Optionally, an exception access-list can be configured to specify the group-address(es) to be excluded from being subject to the limit. This command applies to interfaces configured for IGMP Layer-3 multicast protocols and IGMP Proxy. The limit applies, individually, to each of its constituent interfaces.

Attribute Name: limit-exception-acl

Attribute Type: string

Attribute Name: member-limit

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-2097152

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    <group-membership-control>
      <config>
        <member-limit>1</member-limit> <!-- operation="delete"-->
        <limit-exception-acl>WORD</limit-exception-acl> <!-- operation="delete"-->
      </config>
    </group-membership-control>
  </vrf>
</vrfs>
</igmp>
```

### Command Syntax

```
ip igmp (vrf NAME|) limit <1-2097152> (except WORD|)
```

---

## Configure member limit

Use this attribute to set the maximum number of group membership states, at either the router level or at the interface level. Once the specified number of group memberships is reached, all further local-memberships are ignored. Optionally, an exception access-list can be configured to specify the group-address(es) to be excluded from being subject to the limit. This command applies to interfaces configured for IGMP Layer-3 multicast protocols and IGMP Proxy. The limit applies, individually, to each of its constituent interfaces.

Attribute Name: member-limit

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-2097152

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    </vrf>
  </vrfs>
</igmp>
```

```

    </config>
  <group-membership-control>
    <config>
      <member-limit>1</member-limit> <!-- operation="delete"-->
    </config>
  </group-membership-control>
</vrf>
</vrf>
</igmp>

```

## Command Syntax

```
ip igmp (vrf NAME|) limit <1-2097152>
```

---

## Configure source

Use this attribute to specify the static mode of defining SSM mapping. SSM mapping statically assigns sources to IGMPv1 and IGMPv2 groups to translate such (star G) groups memberships to (S,G) memberships for use with PIMSSM. This attribute applies to interfaces configured for IGMP Layer-3 multicast protocols and IGMP Proxy.

Attribute Name: source

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```

<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <vrf>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    </vrf>
  </vrf>
  <ssm>
    <static-mappings>
      <static-mapping> <!-- operation="delete"-->
        <source>A.B.C.D</source>
        <config>
          <source>A.B.C.D</source>
          <group-ranges-acl>WORD</group-ranges-acl>
        </config>
        <group-ranges-acl>WORD</group-ranges-acl>
      </static-mapping>
    </static-mappings>
  </ssm>
</igmp>

```

## Command Syntax

```
ip igmp (vrf NAME|) ssm-map static WORD A.B.C.D
```

---

## Configure options

Use this attribute to enable igmp debugging configurations

Attribute Name: options

Attribute Type: bits (all|decode|encode|events|fsm|tib)

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <debug>
    <config>
      <options>all</options> <!-- operation="delete"-->
    </config>
  </debug>
</igmp>
```

### Command Syntax

```
debug ip igmp (vrf NAME|) (all|decode|encode|events|fsm|tib)
```

---

## debug ip igmp (vrf NAME|) (all|decode|encode|events|fsm|tib)

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: terminal-debug-options

Attribute Type: bits (all|decode|encode|events|fsm|tib)

### Netconf RPC payload

```
<igmp-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <vrf-name>NAME</vrf-name>
  <terminal-debug-options>all</terminal-debug-options>
</igmp-terminal-debug-on>
```

### Command Syntax

```
debug ip igmp (vrf NAME|) (all|decode|encode|events|fsm|tib)
```

---

## no debug ip igmp (vrf NAME|) (all|decode|encode|events|fsm|tib)

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: terminal-debug-options

Attribute Type: bits (all|decode|encode|events|fsm|tib)

### Netconf RPC payload

```
<igmp-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <vrf-name>NAME</vrf-name>
  <terminal-debug-options>all</terminal-debug-options>
</igmp-terminal-debug-off>
```

### Command Syntax

```
no debug ip igmp (vrf NAME|) (all|decode|encode|events|fsm|tib)
```

---

## clear ip igmp (vrf NAME|)

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

### Netconf RPC payload

```
<igmp-clear-all-groups-for-vrf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <vrf-name>NAME</vrf-name>
</igmp-clear-all-groups-for-vrf>
```

### Command Syntax

```
clear ip igmp (vrf NAME|)
```

---

## clear ip igmp (vrf NAME|) group \*

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: clear-all

Attribute Type: empty

### Netconf RPC payload

```
<igmp-clear-all-groups xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <vrf-name>NAME</vrf-name>
  <clear-all>CML_EMPTY_T</clear-all>
</igmp-clear-all-groups>
```

### Command Syntax

```
clear ip igmp (vrf NAME|) group *
```

---

## clear ip igmp (vrf NAME|) group A.B.C.D IFNAME

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: group-address

Attribute Type: inet:ipv4-address

Attribute Name: if-name

Attribute Type: string

### Netconf RPC payload

```
<igmp-clear-group-on-interface xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <vrf-name>NAME</vrf-name>
  <group-address>A.B.C.D</group-address>
  <if-name>IFNAME</if-name>
</igmp-clear-group-on-interface>
```

### Command Syntax

```
clear ip igmp (vrf NAME|) group A.B.C.D IFNAME
```

---

## clear ip igmp (vrf NAME|) interface IFNAME

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: if-name

Attribute Type: string

### Netconf RPC payload

```
<igmp-clear-all-groups-on-interface xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <vrf-name>NAME</vrf-name>
  <if-name>IFNAME</if-name>
</igmp-clear-all-groups-on-interface>
```

### Command Syntax

```
clear ip igmp (vrf NAME|) interface IFNAME
```

---

## clear ip igmp (vrf NAME|) group A.B.C.D

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: group-address

Attribute Type: inet:ipv4-address

### Netconf RPC payload

```
<igmp-clear-group xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <vrf-name>NAME</vrf-name>
  <group-address>A.B.C.D</group-address>
</igmp-clear-group>
```

### Command Syntax

```
clear ip igmp (vrf NAME|) group A.B.C.D
```

---

## IPI-IGMP-INTERFACE

---

### Configure enabled

Use this attribute to enable the IGMP operation on an interface. This attribute enables IGMP operation in standalone mode, and can be used to learn local-membership information prior to enabling a multicast routing protocol on the interface. This attribute will have no effect on interfaces configured for IGMP proxy

Attribute Name: enabled

Attribute Type: empty

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </enabled><!-- operation="delete"-->
    </interface>
  </interfaces>
</igmp>
```

### Command Syntax

```
ip igmp
```

---

### Configure last member query count

Use this attribute to set the last-member query-count value. This attribute applies to interfaces configured for IGMP Layer-3 multicast protocols and IGMP Proxy.

Attribute Name: last-member-query-count

Attribute Type: uint8

Default Value: 2

Attribute Range: 2-7

## Netconf edit-config payload

```

<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
        </config>
        <last-member-query-count>2</last-member-query-count> <!-- operation="delete"-
->
      </interface>
    </interfaces>
  </igmp>

```

## Command Syntax

```
ip igmp last-member-query-count <2-7>
```

---

## Configure last member query interval

Use this attribute to configure the frequency at which the router sends IGMP group-specific host query messages. This attribute applies to interfaces configured for IGMP Layer-3 multicast protocols and IGMP Proxy.

Attribute Name: last-member-query-interval

Attribute Type: uint16

Default Value: 1000

Attribute Range: 1000-25500

## Netconf edit-config payload

```

<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
        </config>
        <last-member-query-interval>1000</last-member-query-interval> <!--
operation="delete"-->
      </interface>
    </interfaces>
  </igmp>

```

## Command Syntax

```
ip igmp last-member-query-interval <1000-25500>
```

---

## Configure querier timeout

Use this attribute to set the timeout period before the router takes over as the querier for the interface after the previous querier has stopped querying. This attribute applies to interfaces configured for IGMP Layer-3 multicast protocols and IGMP Proxy.

Attribute Name: querier-timeout

Attribute Type: uint16

Default Value: 255

Attribute Range: 60-300

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <querier-timeout>60</querier-timeout> <!-- operation="delete"-->
    </interface>
  </interfaces>
</igmp>
```

### Command Syntax

```
ip igmp querier-timeout <60-300>
```

---

## Configure query interval

Use this attribute to set the frequency of sending IGMP host query messages. This attribute applies to interfaces configured for IGMP Layer-3 multicast protocols and IGMP Proxy.

Attribute Name: query-interval

Attribute Type: uint16

Default Value: 125

Attribute Range: 1-18000

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <query-interval>1</query-interval> <!-- operation="delete"-->
    </interface>
  </interfaces>
</igmp>
```

### Command Syntax

```
ip igmp query-interval <1-18000>
```

---

## Configure query max response time

Use this attribute to set the maximum response time advertised in IGMP queries. This attribute applies to interfaces configured for IGMP Layer-3 multicast protocols and IGMP Proxy.

Attribute Name: query-max-response-time

Attribute Type: uint8

Default Value: 10

Attribute Range: 1-240

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
        <query-max-response-time>1</query-max-response-time> <!-- operation="delete"-
->
      </interface>
    </interfaces>
  </igmp>
```

### Command Syntax

```
ip igmp query-max-response-time <1-240>
```

---

## Configure startup query interval

Use this attribute to set a query interval value for IGMP

Attribute Name: startup-query-interval

Attribute Type: uint16

Default Value: 31

Attribute Range: 1-18000

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
        <startup-query-interval>1</startup-query-interval> <!-- operation="delete"-->
      </interface>
    </interfaces>
  </igmp>
```

## Command Syntax

```
ip igmp startup-query-interval <1-18000>
```

---

## Configure startup query count

Use this attribute to set a startup query count for IGMP

Attribute Name: startup-query-count

Attribute Type: uint8

Default Value: 2

Attribute Range: 2-10

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
        </config>
        <startup-query-count>2</startup-query-count> <!-- operation="delete"-->
      </interface>
    </interfaces>
  </igmp>
```

## Command Syntax

```
ip igmp startup-query-count <2-10>
```

---

## Configure robustness variable

Use this attribute to set the robustness variable value on an interface. This attribute applies to interfaces configured for IGMP Layer-3 multicast protocols and IGMP Proxy.

Attribute Name: robustness-variable

Attribute Type: uint8

Default Value: 2

Attribute Range: 2-7

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
        </config>
        <robustness-variable>2</robustness-variable> <!-- operation="delete"-->
      </interface>
    </interfaces>
  </igmp>
```

```
</interfaces>  
</igmp>
```

## Command Syntax

```
ip igmp robustness-variable <2-7>
```

---

## Configure version

Use this attribute to set the current IGMP protocol version on an interface. This attribute applies to interfaces configured for IGMP Layer-3 multicast protocols and IGMP Proxy.

Attribute Name: version

Attribute Type: uint8

Default Value: 3

Attribute Range: 1-3

## Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">  
<interfaces>  
<interface>  
  <name>WORD</name>  
  <config>  
    <name>WORD</name>  
  </config>  
  <version>1</version> <!-- operation="delete"-->  
</interface>  
</interfaces>  
</igmp>
```

## Command Syntax

```
ip igmp version <1-3>
```

---

## Configure require router alert option

Use this attribute to configure strict Router Advertisement validation for IGMP.

Attribute Name: require-router-alert-option

Attribute Type: empty

## Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">  
<interfaces>  
<interface>  
  <name>WORD</name>  
  <config>  
    <name>WORD</name>  
  </config>  
  </require-router-alert-option><!-- operation="delete"-->  
</interface>
```

```
</interfaces>
</igmp>
```

## Command Syntax

```
ip igmp ra-option
```

---

## Configure allow offlink host

Use this attribute to configure off-link for IGMP.

Attribute Name: allow-offlink-host

Attribute Type: empty

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </allow-offlink-host><!-- operation="delete"-->
</interface>
</interfaces>
</igmp>
```

## Command Syntax

```
ip igmp offlink
```

---

## Configure enable proxy service

Use this attribute to designate an interface to be the IGMP proxy-service (upstream host-side) interface, thus enabling IGMP host-side protocol operation on this interface. All associated downstream router-side interfaces will have their memberships consolidated on this interface, according to IGMP host-side functionality

Attribute Name: enable-proxy-service

Attribute Type: empty

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <proxy>
  <config>
    </enable-proxy-service><!-- operation="delete"-->
  </config>
</interface>
</interfaces>
</igmp>
```

```

</proxy>
</interface>
</interfaces>
</igmp>

```

## Command Syntax

```
ip igmp proxy-service
```

---

## Configure mroute proxy interface

Use this attribute to specify the IGMP Proxy service interface with which to be associated. IGMP router-side protocol operation is enabled only when the specified upstream proxy-service interface is functional.

Attribute Name: mroute-proxy-interface

Attribute Type: string

Default Value: NULL

## Netconf edit-config payload

```

<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <proxy>
        <config>
          <mroute-proxy-interface>IFNAME</mroute-proxy-interface> <!--
operation="delete"-->
        </config>
      </proxy>
    </interface>
  </interfaces>
</igmp>

```

## Command Syntax

```
ip igmp mroute-proxy IFNAME
```

---

## Configure unsolicited report interval

Use this attribute to set an unsolicited report interval for an interface designated as an IGMP proxy

Attribute Name: unsolicited-report-interval

Attribute Type: uint16

Default Value: 1000

Attribute Range: 1000-25500

## Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
```

```

<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <proxy>
  <config>
    <unsolicited-report-interval>1000</unsolicited-report-interval> <!--
operation="delete"-->
  </config>
</proxy>
</interface>
</interfaces>
</igmp>

```

### Command Syntax

```
ip igmp proxy unsolicited-report-interval <1000-25500>
```

---

## Configure limit exception acl

Use this attribute to set the maximum number of group membership states, at either the router level or at the interface level. Once the specified number of group memberships is reached, all further local-memberships are ignored. Optionally, an exception access-list can be configured to specify the group-address to be excluded from being subject to the limit.

Attribute Name: limit-exception-acl

Attribute Type: string

Attribute Name: member-limit

Attribute Type: uint32

Attribute Range: 1-2097152

### Netconf edit-config payload

```

<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <group-membership-control>
  <config>
    <member-limit>1</member-limit> <!-- operation="delete"-->
    <limit-exception-acl>WORD</limit-exception-acl> <!-- operation="delete"--
>
  </config>
</group-membership-control>
</interface>
</interfaces>
</igmp>

```

## Command Syntax

```
ip igmp limit <1-2097152> (except WORD|)
```

---

## Configure member limit

Use this attribute to set the maximum number of group membership states, at either the router level or at the interface level. Once the specified number of group memberships is reached, all further local-memberships are ignored. Optionally, an exception access-list can be configured to specify the group-address to be excluded from being subject to the limit.

Attribute Name: member-limit

Attribute Type: uint32

Attribute Range: 1-2097152

## Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <group-membership-control>
        <config>
          <member-limit>1</member-limit> <!-- operation="delete"-->
        </config>
      </group-membership-control>
    </interface>
  </interfaces>
</igmp>
```

## Command Syntax

```
ip igmp limit <1-2097152>
```

---

## Configure access group name

Use this attribute to control the multicast local-membership groups learned on an interface. This attribute applies to interfaces configured for IGMP Layer-3 multicast protocols, IGMP proxy.

Attribute Name: access-group-name

Attribute Type: string

Default Value: NULL

## Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
```

```

    <name>WORD</name>
  </config>
</group-membership-control>
</config>
  <access-group-name>WORD</access-group-name> <!-- operation="delete"-->
</config>
</group-membership-control>
</interface>
</interfaces>
</igmp>

```

### Command Syntax

```
ip igmp access-group WORD
```

---

## Configure immediate leave groups list

In IGMP version 2, use this attribute to minimize the leave latency of IGMP memberships. This attribute is used when only one receiver host is connected to each interface. This command applies to interfaces configured for IGMP Layer-3 multicast protocols, IGMP Proxy.

Attribute Name: immediate-leave-groups-list

Attribute Type: string

Default Value: NULL

### Netconf edit-config payload

```

<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <group-membership-control>
        <config>
          <immediate-leave-groups-list>WORD</immediate-leave-groups-list> <!--
operation="delete"-->
        </config>
      </group-membership-control>
    </interface>
  </interfaces>
</igmp>

```

### Command Syntax

```
ip igmp immediate-leave group-list WORD
```

---

## Configure group address

Use this attribute to statically configure group membership entries on an interface. To statically add only a group membership, do not specify any parameters. This attribute applies to IGMP operation on a specific interface to statically add group and/or source records on a VLAN interface to statically add group and/or source records.

Attribute Name: group-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <asm-static-groups>
  <asm-static-group <!-- operation="delete"-->
    <group-address>A.B.C.D</group-address>
    <config>
      <group-address>A.B.C.D</group-address>
    </config>
  </asm-static-group>
</asm-static-groups>
</interface>
</interfaces>
</igmp>
```

### Command Syntax

```
ip igmp static-group A.B.C.D
```

---

## Configure source

Use this attribute to statically configure the group to be joined.

Attribute Name: source

Attribute Type: union

### Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <ssm-static-groups>
  <ssm-static-group <!-- operation="delete"-->
    <source>ssm-map</source>
    <config>
      <source>ssm-map</source>
      <group-address>A.B.C.D</group-address>
    </config>
    <group-address>A.B.C.D</group-address>
  </ssm-static-group>
</interfaces>
```

```
</ssm-static-groups>
</interface>
</interfaces>
</igmp>
```

## Command Syntax

```
ip igmp static-group A.B.C.D source (ssm-map|A.B.C.D)
```

---

## Configure name

Use this attribute to configure a join multicast group.

Attribute Name: group-address

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <asm-join-groups>
  <asm-join-group> <!-- operation="delete"-->
    <group-address>A.B.C.D</group-address>
    <config>
      <group-address>A.B.C.D</group-address>
    </config>
  </asm-join-group>
</asm-join-groups>
</interface>
</interfaces>
</igmp>
```

## Command Syntax

```
ip igmp join-group A.B.C.D
```

---

## Configure ssm-join-groups source

Use this attribute to statically configure the group to be joined.

Attribute Name: source

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```
<igmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp">
<interfaces>
<interface>
  <name>WORD</name>
```

```

<config>
  <name>WORD</name>
</config>
<ssm-join-groups>
<ssm-join-group> <!-- operation="delete"-->
  <source>A.B.C.D</source>
  <config>
    <source>A.B.C.D</source>
    <group-address>A.B.C.D</group-address>
  </config>
  <group-address>A.B.C.D</group-address>
</ssm-join-group>
</ssm-join-groups>
</interface>
</interfaces>
</igmp>

```

### Command Syntax

```
ip igmp join-group A.B.C.D source A.B.C.D
```

---

## IPI-IGMP-SNOOPING

---

### Configure disable igmp snooping

Use this attribute to disable IGMP Snooping. When this attribute is given in the Configure mode, IGMP snooping is enabled at switch level on all the vlans in switch. When this attribute is given at the VLAN interface level, IGMP Snooping is enabled for that VLAN.

Attribute Name: disable-igmp-snooping

Attribute Type: uint8

### Netconf edit-config payload

```

<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
<global>
<config>
  </disable-igmp-snooping><!-- operation="delete"-->
</config>
</global>
</igmp-snooping>

```

### Command Syntax

```
no igmp snooping
```

---

### Configure disable report suppression

Use this attribute to disable report suppression for IGMP version 1, 2 and 3 reports. By default report suppression is enabled.

Attribute Name: disable-report-suppression

Attribute Type: uint8

### Netconf edit-config payload

```
<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <global>
    <config>
      </disable-report-suppression><!-- operation="delete"-->
    </config>
  </global>
</igmp-snooping>
```

### Command Syntax

```
no igmp snooping report-suppression
```

---

## Configure unknown multicast action

Use this attribute to set the action to be taken on receiving I2 unknown multicast packets.

Attribute Name: unknown-multicast-action

Attribute Type: enum (flood|discard)

Default Value: flood

### Netconf edit-config payload

```
<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <global>
    <config>
      <unknown-multicast-action>flood</unknown-multicast-action> <!--
operation="delete"-->
    </config>
  </global>
</igmp-snooping>
```

### Command Syntax

```
l2 unknown mcast (flood|discard)
```

---

## Configure options

Enable IGMP snooping debug

Attribute Name: options

Attribute Type: bits (decode|encode|events|fsm|tib|all)

### Netconf edit-config payload

```
<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <debug>
    <config>
      <options>decode</options> <!-- operation="delete"-->
    </config>
  </debug>
</igmp-snooping>
```

---

## Command Syntax

```
debug igmp snooping (decode|encode|events|fsm|tib|all)
```

---

## Configure igmp snooping

Use this attribute to enable or disable IGMP Snooping. When this command is given at the VLAN interface level, IGMP Snooping is enabled for that VLAN.

Attribute Name: igmp-snooping

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <igmp-snooping>disable</igmp-snooping> <!-- operation="delete"-->
    </interface>
  </interfaces>
</igmp-snooping>
```

## Command Syntax

```
no ip igmp snooping
```

---

## Configure report suppression

Use this attribute to enable or disable report suppression for IGMP version 1, 2 and 3 reports. By default report suppression is enabled.

Attribute Name: report-suppression

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <report-suppression>disable</report-suppression> <!-- operation="delete"-->
    </interface>
  </interfaces>
</igmp-snooping>
```

## Command Syntax

```
no ip igmp snooping report-suppression
```

---

## Configure enable fast leave

Use this attribute to enable IGMP Snooping fast-leave processing. Fast-leave processing is analogous to immediateleave processing the IGMP group-membership is removed, as soon as an IGMP leave group message is received without sending out a group-specific query

Attribute Name: enable-fast-leave

Attribute Type: uint8

### Netconf edit-config payload

```
<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </enable-fast-leave><!-- operation="delete"-->
    </interface>
  </interfaces>
</igmp-snooping>
```

### Command Syntax

```
ip igmp snooping fast-leave
```

---

## Configure mrouter interface name

Use this attribute to statically configure the specified VLAN constituent interface as a multicast router interface for IGMP Snooping in that VLAN.

Attribute Name: mrouter-interface-name

Attribute Type: string

### Netconf edit-config payload

```
<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <mrouter-interface-name>IFNAME</mrouter-interface-name> <!-- operation="delete"-->
    </interface>
  </interfaces>
</igmp-snooping>
```

### Command Syntax

```
ip igmp snooping mrouter interface IFNAME
```

---

## Configure enable querier

Use this attribute to enable IGMP snooping querier functionality on a VLAN when IGMP is not enabled on the particular VLAN. When enabled, the IGMP Snooping querier sends out periodic IGMP queries for all interfaces on that VLAN. The IGMP Snooping querier uses the 0.0.0.0 source IP address, because it only masquerades as a proxy IGMP querier for faster network convergence. It does not start, or automatically cease, the IGMP Querier operation if it detects query message(s) from a multicast router. It restarts as the IGMP Snooping querier if no queries are seen within the other querier interval.

Attribute Name: enable-querier

Attribute Type: uint8

### Netconf edit-config payload

```
<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </enable-querier><!-- operation="delete"-->
    </interface>
  </interfaces>
</igmp-snooping>
```

### Command Syntax

```
ip igmp snooping querier
```

---

## Configure name

Use this attribute to enable or disable IGMP Snooping. When this command is given at the VLAN interface level, IGMP Snooping is enabled for that VLAN.

Attribute Name: igmp-snooping

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <igmp-snooping>disable</igmp-snooping> <!-- operation="delete"-->
    </interface>
  </interfaces>
</igmp-snooping>
```

---

## Command Syntax

```
igmp snooping (disable|enable)
```

---

## Configure interface enable-fast-leave

Use this attribute to enable IGMP Snooping fast-leave processing. Fast-leave processing is analogous to immediateleave processing the IGMP group-membership is removed, as soon as an IGMP leave group message is received without sending out a group-specific query

Attribute Name: enable-fast-leave

Attribute Type: empty

### Netconf edit-config payload

```
<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </enable-fast-leave><!-- operation="delete"-->
    </interface>
  </interfaces>
</igmp-snooping>
```

## Command Syntax

```
igmp snooping fast-leave
```

---

## Configure interface report-suppression

Use this attribute to enable or disable report suppression for IGMP version 1, 2 and 3 reports. By default report suppression is enabled.

Attribute Name: report-suppression

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <report-suppression>disable</report-suppression> <!-- operation="delete"-->
    </interface>
  </interfaces>
</igmp-snooping>
```

## Command Syntax

```
igmp snooping report-suppression (disable|enable)
```

---

## Configure interface mrouter-interface-name

Use this attribute to statically configure the specified VLAN constituent interface as a multicast router interface for IGMP Snooping in that VLAN.

Attribute Name: mrouter-interface-name

Attribute Type: string

### Netconf edit-config payload

```
<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <mrouter-interface-name>IFNAME</mrouter-interface-name> <!-- operation="delete"-->
->
    </interface>
  </interfaces>
</igmp-snooping>
```

## Command Syntax

```
igmp snooping mrouter interface IFNAME
```

---

## Configure interface enable-querier

Use this attribute to enable IGMP snooping querier functionality on a VLAN when IGMP is not enabled on the particular VLAN. When enabled, the IGMP Snooping querier sends out periodic IGMP queries for all interfaces on that VLAN. The IGMP Snooping querier uses the 0.0.0.0 source IP address, because it only masquerades as a proxy IGMP querier for faster network convergence. It does not start, or automatically cease, the IGMP Querier operation if it detects query message(s) from a multicast router. It restarts as the IGMP Snooping querier if no queries are seen within the other querier interval.

Attribute Name: enable-querier

Attribute Type: empty

### Netconf edit-config payload

```
<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </enable-querier><!-- operation="delete"-->
    </interface>
```

```
</interfaces>  
</igmp-snooping>
```

## Command Syntax

```
igmp snooping querier
```

---

## Configure source address

Use this attribute to set the Source Address to be joined

Attribute Name: source-address

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```
<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">  
<interfaces>  
<interface>  
  <name>WORD</name>  
  <config>  
    <name>WORD</name>  
  </config>  
<static-groups>  
<ssm-groups>  
<ssm-group>  
  <interface-name>IFNAME</interface-name>  
  <config>  
    <interface-name>IFNAME</interface-name>  
    <source-address>A.B.C.D</source-address>  
    <group-address>A.B.C.D</group-address>  
  </config>  
  <source-address>A.B.C.D</source-address>  
  <group-address>A.B.C.D</group-address>  
</ssm-group>  
</ssm-groups>  
</static-groups>  
</interface>  
</interfaces>  
</igmp-snooping>
```

## Command Syntax

```
igmp snooping static-group A.B.C.D source A.B.C.D interface IFNAME
```

---

## Configure group address

Use this attribute to set the static group-address to be joined

Attribute Name: group-address

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```

<igmp-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</static-groups>
</ssm-groups>
<ssm-group>
  <interface-name>IFNAME</interface-name>
  <config>
    <interface-name>IFNAME</interface-name>
    <source-address>A.B.C.D</source-address>
    <group-address>A.B.C.D</group-address>
  </config>
  <source-address>A.B.C.D</source-address>
  <group-address>A.B.C.D</group-address>
</ssm-group>
</ssm-groups>
</static-groups>
</interface>
</interfaces>
</igmp-snooping>

```

## Command Syntax

```
igmp snooping static-group A.B.C.D interface IFNAME
```

---

## clear igmp snooping group A.B.C.D IFNAME

Attribute Name: group-address

Attribute Type: inet:ipv4-address

Attribute Name: interface-name

Attribute Type: string

## Netconf RPC payload

```

<igmp-snooping-clear-group-interface xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <group-address>A.B.C.D</group-address>
  <interface-name>IFNAME</interface-name>
</igmp-snooping-clear-group-interface>

```

## Command Syntax

```
clear igmp snooping group A.B.C.D IFNAME
```

---

## clear igmp snooping interface IFNAME

Attribute Name: interface-name

Attribute Type: string

### Netconf RPC payload

```
<igmp-snooping-clear-interface xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <interface-name>IFNAME</interface-name>
</igmp-snooping-clear-interface>
```

### Command Syntax

```
clear igmp snooping interface IFNAME
```

---

## clear igmp snooping group \*

### Netconf RPC payload

```
<igmp-snooping-clear-group-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping"/>
```

### Command Syntax

```
clear igmp snooping group *
```

---

## clear igmp snooping

### Netconf RPC payload

```
<igmp-snooping-clear-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping"/>
```

### Command Syntax

```
clear igmp snooping
```

---

## clear igmp snooping group A.B.C.D

Attribute Name: group-address

Attribute Type: inet:ipv4-address

### Netconf RPC payload

```
<igmp-snooping-clear-group xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-igmp-snooping">
  <group-address>A.B.C.D</group-address>
</igmp-snooping-clear-group>
```

### Command Syntax

```
clear igmp snooping group A.B.C.D
```

---

## debug igmp snooping (decode|encode|events|fsm|tib|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (decode|encode|events|fsm|tib|all)

### Netconf RPC payload

```
<igmp-snooping-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-igmp-snooping">
  <terminal-debug-options>decode</terminal-debug-options>
</igmp-snooping-terminal-debug-on>
```

### Command Syntax

```
debug igmp snooping (decode|encode|events|fsm|tib|all)
```

---

## no debug igmp snooping (decode|encode|events|fsm|tib|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (decode|encode|events|fsm|tib|all)

### Netconf RPC payload

```
<igmp-snooping-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-igmp-snooping">
  <terminal-debug-options>decode</terminal-debug-options>
</igmp-snooping-terminal-debug-off>
```

### Command Syntax

```
no debug igmp snooping (decode|encode|events|fsm|tib|all)
```

---

## IPI-MLD-SNOOPING

---

### Configure disable mld snooping

Use this attribute to enable MLD Snooping. When this command is given in the Configure mode, MLD Snooping is enabled at the switch level. When this attribute is given at the VLAN interface level, 5MLD Snooping is enabled for that VLAN.

Attribute Name: disable-mld-snooping

Attribute Type: uint8

### Netconf edit-config payload

```
<mld-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld-snooping">
  <global>
    <config>
      </disable-mld-snooping><!-- operation="delete"-->
    </config>
  </global>
</mld-snooping>
```

---

## Command Syntax

```
no mld snooping
```

---

## Configure disable report suppression

Use this attribute to enable report suppression for MLD version 1.

Attribute Name: disable-report-suppression

Attribute Type: uint8

### Netconf edit-config payload

```
<mld-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld-snooping">
  <global>
    <config>
      </disable-report-suppression><!-- operation="delete"-->
    </config>
  </global>
</mld-snooping>
```

## Command Syntax

```
no mld snooping report-suppression
```

---

## Configure options

Use this attribute to enable mld snooping debugging configurations

Attribute Name: options

Attribute Type: bits (decode|encode|events|fsm|tib|all)

### Netconf edit-config payload

```
<mld-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld-snooping">
  <debug>
    <config>
      <options>decode</options> <!-- operation="delete"-->
    </config>
  </debug>
</mld-snooping>
```

## Command Syntax

```
debug mld snooping (decode|encode|events|fsm|tib|all)
```

---

## Configure report suppression

Use this attribute to enable or disable report suppression for MLD version 1, and 2 reports. By default report suppression is enabled.

Attribute Name: report-suppression

Attribute Type: enum (disable|enable)

---

### Netconf edit-config payload

```
<mld-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld-snooping">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <report-suppression>disable</report-suppression> <!-- operation="delete"-->
</interface>
</interfaces>
</mld-snooping>
```

### Command Syntax

```
no mld snooping report-suppression
```

---

## Configure mld snooping

Use this attribute to enable MLD Snooping. When this attribute is given at the VLAN interface level, MLD Snooping is enabled for that VLAN.

Attribute Name: mld-snooping

Attribute Type: enum (disable|enable)

Default Value: enable

### Netconf edit-config payload

```
<mld-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld-snooping">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <mld-snooping>enable</mld-snooping> <!-- operation="delete"-->
</interface>
</interfaces>
</mld-snooping>
```

### Command Syntax

```
mld snooping (disable|enable)
```

---

## Configure enable fast leave

Use this attribute to enable MLD Snooping fast-leave processing. Fast-leave processing is analogous to immediateleave processing the MLD group-membership is removed, as soon as an MLD leave group message is received without sending out a group-specific query.

Attribute Name: enable-fast-leave

Attribute Type: empty

**Netconf edit-config payload**

```
<mld-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld-snooping">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </enable-fast-leave><!-- operation="delete"-->
</interface>
</interfaces>
</mld-snooping>
```

**Command Syntax**

```
mld snooping fast-leave
```

---

**Configure name**

Use this attribute to enable or disable report suppression for MLD version 1, and 2 reports. By default report suppression is enabled.

Attribute Name: report-suppression

Attribute Type: enum (disable|enable)

**Netconf edit-config payload**

```
<mld-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld-snooping">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
    <report-suppression>disable</report-suppression> <!-- operation="delete"-->
  </config>
</interface>
</interfaces>
</mld-snooping>
```

**Command Syntax**

```
mld snooping report-suppression (disable|enable)
```

---

**Configure mrouter interface name**

Use this attribute to statically configure the specified VLAN constituent interface as a multicast router interface for MLD Snooping in that VLAN

Attribute Name: mrouter-interface-name

Attribute Type: string

**Netconf edit-config payload**

```
<mld-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld-snooping">
```

```

<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <mrouter-interface-name>IFNAME</mrouter-interface-name> <!-- operation="delete"-
->
</interface>
</interfaces>
</mld-snooping>

```

### Command Syntax

```
mld snooping mrouter interface IFNAME
```

---

## Configure enable querier

Use this attribute to enable MLD querier operation on a subnet (VLAN) when no multicast routing protocol is configured in the subnet VLAN. When enabled, the MLD Snooping querier sends out periodic MLD queries for all interfaces on that VLAN. The MLD Snooping querier uses the 0.0.0.0 source IP address, because it masquerades as a proxy MLD querier for faster network convergence. It does not start or automatically cease the MLD querier operation if it detects a query message from a multicast router. It restarts as MLD snooping querier if no queries are seen within another querier interval

Attribute Name: enable-querier

Attribute Type: empty

### Netconf edit-config payload

```

<mld-snooping xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld-snooping">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </enable-querier><!-- operation="delete"-->
</interface>
</interfaces>
</mld-snooping>

```

### Command Syntax

```
mld snooping querier
```

---

## debug mld snooping (decode|encode|events|fsm|tib|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (decode|encode|events|fsm|tib|all)

---

**Netconf RPC payload**

```
<mld-snooping-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
mld-snooping">
  <terminal-debug-options>decode</terminal-debug-options>
</mld-snooping-terminal-debug-on>
```

**Command Syntax**

```
debug mld snooping (decode|encode|events|fsm|tib|all)
```

---

**no debug mld snooping (decode|encode|events|fsm|tib|all)**

Attribute Name: terminal-debug-options

Attribute Type: bits (decode|encode|events|fsm|tib|all)

**Netconf RPC payload**

```
<mld-snooping-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-mld-snooping">
  <terminal-debug-options>decode</terminal-debug-options>
</mld-snooping-terminal-debug-off>
```

**Command Syntax**

```
no debug mld snooping (decode|encode|events|fsm|tib|all)
```

---

**clear mld snooping group X:X::X:X IFNAME**

Attribute Name: group-address

Attribute Type: string

Attribute Name: interface-name

Attribute Type: string

**Netconf RPC payload**

```
<mld-snooping-clear-group-on-interface xmlns="http://www.ipinfusion.com/yang/
ocnos/ipi-mld-snooping">
  <group-address>X:X::X:X</group-address>
  <interface-name>IFNAME</interface-name>
</mld-snooping-clear-group-on-interface>
```

**Command Syntax**

```
clear mld snooping group X:X::X:X IFNAME
```

---

**clear mld snooping interface IFNAME**

Attribute Name: interface-name

Attribute Type: string

**Netconf RPC payload**

```
<mld-snooping-clear-all-groups-on-interface xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-mld-snooping">
```

```
<interface-name>IFNAME</interface-name>  
</mld-snooping-clear-all-groups-on-interface>
```

### Command Syntax

```
clear mld snooping interface IFNAME
```

---

## clear mld snooping group X:X::X:X

Attribute Name: group-address

Attribute Type: string

### Netconf RPC payload

```
<mld-snooping-clear-group xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld-snooping">  
  <group-address>X:X::X:X</group-address>  
</mld-snooping-clear-group>
```

### Command Syntax

```
clear mld snooping group X:X::X:X
```

---

## clear mld snooping group \*

### Netconf RPC payload

```
<mld-snooping-clear-all-groups xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld-snooping"/>
```

### Command Syntax

```
clear mld snooping group *
```

---

## clear mld snooping

### Netconf RPC payload

```
<mld-snooping-clear-all-groups-alias xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld-snooping"/>
```

### Command Syntax

```
clear mld snooping
```

---

## IPI-MLD

---

### Configure disable ssm map

Use this attribute to enable/disable SSM mapping on the router

Attribute Name: disable-ssm-map

Attribute Type: empty

## Netconf edit-config payload

```

<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
<vrfs>
<vrf>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  </disable-ssm-map><!-- operation="delete"-->
</vrf>
</vrfs>
</mld>

```

## Command Syntax

```
no ipv6 mld (vrf NAME|) ssm-map enable
```

---

## Configure limit exception acl

Use this attribute to set the maximum number of group membership states at the router level. Once the specified number of group memberships is reached, all further local-memberships are ignored. Optionally, an exception access-list can be configured to specify the group-address(es) to be excluded from being subject to the limit. This command applies to interfaces configured for MLD Layer-3 multicast protocols and MLD Proxy. The limit applies, individually, to each of its constituent interfaces.

Attribute Name: limit-exception-acl

Attribute Type: string

Attribute Name: member-limit

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-2097152

## Netconf edit-config payload

```

<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
<vrfs>
<vrf>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
<group-membership-control>
<config>
  <member-limit>1</member-limit> <!-- operation="delete"-->
  <limit-exception-acl>WORD</limit-exception-acl> <!-- operation="delete"-->
</config>
</group-membership-control>
</vrf>
</vrfs>
</mld>

```

## Command Syntax

```
ipv6 mld (vrf NAME|) limit <1-2097152> (except WORD|)
```

---

## Configure member limit

Use this attribute to set the maximum number of group membership states at the router level. Once the specified number of group memberships is reached, all further local-memberships are ignored. Optionally, an exception access-list can be configured to specify the group-address(es) to be excluded from being subject to the limit. This command applies to interfaces configured for MLD Layer-3 multicast protocols and MLD Proxy. The limit applies, individually, to each of its constituent interfaces.

Attribute Name: member-limit

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-2097152

## Netconf edit-config payload

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <group-membership-control>
    <config>
      <member-limit>1</member-limit> <!-- operation="delete"-->
    </config>
  </group-membership-control>
</mld>
```

## Command Syntax

```
ipv6 mld (vrf NAME|) limit <1-2097152>
```

---

## Configure source

Use this attribute to specify the static mcast source for SSM mapping. SSM mapping statically assigns sources to MLDv1 groups to translate such (star G) groups memberships to (S,G) memberships for use with PIM-SSM. This attribute applies to interfaces configured for MLD Layer-3 multicast protocols and MLD Proxy.

Attribute Name: source

Attribute Type: inet:ipv6-address

## Netconf edit-config payload

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <vrfs>
    <vrf>
```

```

    <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
</ssm>
<static-mappings>
<static-mapping> <!-- operation="delete"-->
  <source>X:X::X:X</source>
  <config>
    <source>X:X::X:X</source>
    <group-ranges-acl>WORD</group-ranges-acl>
  </config>
  <group-ranges-acl>WORD</group-ranges-acl>
</static-mapping>
</static-mappings>
</ssm>
</vrf>
</vrfs>
</mld>

```

### Command Syntax

```
ipv6 mld (vrf NAME|) ssm-map static WORD X:X::X:X
```

---

## Configure debug options

Use this attribute to enable mld debugging configurations

Attribute Name: debug-options

Attribute Type: bits (all|decode|encode|events|fsm|tib)

### Netconf edit-config payload

```

<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <vrfs>
  <vrf>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
  <debug>
  <config>
    <debug-options>all</debug-options> <!-- operation="delete"-->
  </config>
</debug>
</vrf>
</vrfs>
</mld>

```

### Command Syntax

```
debug ipv6 mld (vrf NAME|) (all|decode|encode|events|fsm|tib)
```

---

## **debug ipv6 mld (vrf NAME|) (all|decode|encode|events|fsm|tib)**

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: term-debug-options

Attribute Type: bits (all|decode|encode|events|fsm|tib)

### **Netconf RPC payload**

```
<mld-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
<vrf-name>NAME</vrf-name>
<term-debug-options>all</term-debug-options>
</mld-terminal-debug-on>
```

### **Command Syntax**

```
debug ipv6 mld (vrf NAME|) (all|decode|encode|events|fsm|tib)
```

---

## **no debug ipv6 mld (vrf NAME|) (all|decode|encode|events|fsm|tib)**

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: term-debug-options

Attribute Type: bits (all|decode|encode|events|fsm|tib)

### **Netconf RPC payload**

```
<mld-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
<vrf-name>NAME</vrf-name>
<term-debug-options>all</term-debug-options>
</mld-terminal-debug-off>
```

### **Command Syntax**

```
no debug ipv6 mld (vrf NAME|) (all|decode|encode|events|fsm|tib)
```

---

## **clear ipv6 mld (vrf NAME|)**

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

### **Netconf RPC payload**

```
<mld-clear-all-groups-alias xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
mld">
<vrf-name>NAME</vrf-name>
</mld-clear-all-groups-alias>
```

## Command Syntax

```
clear ipv6 mld (vrf NAME|)
```

---

## clear ipv6 mld (vrf NAME|) group \*

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: clear-all

Attribute Type: empty

## Netconf RPC payload

```
<mld-clear-all-groups xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
<vrf-name>NAME</vrf-name>
<clear-all>CML_EMPTY_T</clear-all>
</mld-clear-all-groups>
```

## Command Syntax

```
clear ipv6 mld (vrf NAME|) group *
```

---

## clear ipv6 mld (vrf NAME|) group X:X::X:X IFNAME

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: group-address

Attribute Type: inet:ipv6-address

Attribute Name: if-name

Attribute Type: string

## Netconf RPC payload

```
<mld-clear-group-on-interface xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
mld">
<vrf-name>NAME</vrf-name>
<group-address>X:X::X:X</group-address>
<if-name>IFNAME</if-name>
</mld-clear-group-on-interface>
```

## Command Syntax

```
clear ipv6 mld (vrf NAME|) group X:X::X:X IFNAME
```

---

## clear ipv6 mld (vrf NAME|) interface IFNAME

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: if-name

Attribute Type: string

### Netconf RPC payload

```
<mld-clear-all-groups-on-interface xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-mld">
  <vrf-name>NAME</vrf-name>
  <if-name>IFNAME</if-name>
</mld-clear-all-groups-on-interface>
```

### Command Syntax

```
clear ipv6 mld (vrf NAME|) interface IFNAME
```

---

## clear ipv6 mld (vrf NAME|) group X:X::X:X

Attribute Name: vrf-name

Attribute Type: string

Default Value: default

Attribute Name: group-address

Attribute Type: inet:ipv6-address

### Netconf RPC payload

```
<mld-clear-group xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <vrf-name>NAME</vrf-name>
  <group-address>X:X::X:X</group-address>
</mld-clear-group>
```

### Command Syntax

```
clear ipv6 mld (vrf NAME|) group X:X::X:X
```

---

## IPI-MLD-INTERFACE

---

### Configure enabled

Use this attribute to enable the MLD protocol operation on an interface. This attribute enables MLD protocol operation in stand-alone mode, and can be used to learn local-membership information prior to enabling a multicast routing protocol on the interface. This attribute will have no effect on interfaces configured for MLD Proxy.

Attribute Name: enabled

Attribute Type: empty

### Netconf edit-config payload

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <interfaces>
  <interface>
```

```

    <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </enabled><!-- operation="delete"-->
</interface>
</interfaces>
</mld>

```

### Command Syntax

```
ipv6 mld
```

---

## Configure last member query count

Use this attribute to set the last-member query-count value. This attribute applies to interfaces configured for MLD Layer-3 multicast protocols, MLD Snooping, or MLD Proxy.

Attribute Name: last-member-query-count

Attribute Type: uint8

Default Value: 2

Attribute Range: 2-7

### Netconf edit-config payload

```

<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <last-member-query-count>2</last-member-query-count> <!-- operation="delete"-
->
    </interface>
  </interfaces>
</mld>

```

### Command Syntax

```
ipv6 mld last-member-query-count <2-7>
```

---

## Configure last member query interval

Use this attribute to set the frequency at which the router sends MLD group-specific host query messages. This attribute applies to interfaces configured for MLD Layer-3 multicast protocols, MLD Snooping, or MLD Proxy

Attribute Name: last-member-query-interval

Attribute Type: uint16

Default Value: 1000

Attribute Range: 1000-25500

## Netconf edit-config payload

```

<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <last-member-query-interval>1000</last-member-query-interval> <!--
operation="delete"-->
    </interface>
  </interfaces>
</mld>

```

## Command Syntax

```
ipv6 mld last-member-query-interval <1000-25500>
```

---

## Configure querier timeout

Use this attribute to configure the timeout period before the router takes over as the querier for the interface after the previous querier has stopped querying. This attribute applies to interfaces configured for MLD Layer-3 multicast protocols, MLD Snooping, or MLD Proxy.

Attribute Name: querier-timeout

Attribute Type: uint16

Default Value: 250

Attribute Range: 60-300

## Netconf edit-config payload

```

<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <querier-timeout>60</querier-timeout> <!-- operation="delete"-->
    </interface>
  </interfaces>
</mld>

```

## Command Syntax

```
ipv6 mld querier-timeout <60-300>
```

---

## Configure query interval

Use this attribute to set the frequency of sending MLD host query messages. This attribute applies to interfaces configured for MLD Layer-3 multicast protocols, MLD Snooping, or MLD Proxy.

Attribute Name: query-interval

Attribute Type: uint16

Default Value: 125

Attribute Range: 1-18000

### Netconf edit-config payload

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <query-interval>1</query-interval> <!-- operation="delete"-->
    </interface>
  </interfaces>
</mld>
```

### Command Syntax

```
ipv6 mld query-interval <1-18000>
```

---

## Configure query max response time

Use this attribute to set the maximum response time advertised in MLD queries. This attribute applies to interfaces configured for MLD Layer-3 multicast protocols, MLD Snooping, or MLD Proxy.

Attribute Name: query-max-response-time

Attribute Type: uint8

Default Value: 10

Attribute Range: 1-240

### Netconf edit-config payload

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <query-max-response-time>1</query-max-response-time> <!-- operation="delete"-
->
    </interface>
  </interfaces>
</mld>
```

### Command Syntax

```
ipv6 mld query-max-response-time <1-240>
```

---

## Configure startup query interval

Use this attribute to set a startup query interval value for MLD

Attribute Name: startup-query-interval

Attribute Type: uint16

Default Value: 31

Attribute Range: 1-18000

### Netconf edit-config payload

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mlld">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <startup-query-interval>1</startup-query-interval> <!-- operation="delete"-->
    </interface>
  </interfaces>
</mld>
```

### Command Syntax

```
ipv6 mld startup-query-interval <1-18000>
```

---

## Configure startup query count

Use this attribute to set a startup query count for MLD

Attribute Name: startup-query-count

Attribute Type: uint8

Default Value: 2

Attribute Range: 2-10

### Netconf edit-config payload

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mlld">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <startup-query-count>2</startup-query-count> <!-- operation="delete"-->
    </interface>
  </interfaces>
</mld>
```

## Command Syntax

```
ipv6 mld startup-query-count <2-10>
```

---

## Configure robustness variable

Use this attribute to set the robustness variable value on an interface. This attribute applies to interfaces configured for MLD Layer-3 multicast protocols, MLD Snooping, or MLD Proxy.

Attribute Name: robustness-variable

Attribute Type: uint8

Default Value: 2

Attribute Range: 2-7

## Netconf edit-config payload

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <robustness-variable>2</robustness-variable> <!-- operation="delete"-->
    </interface>
  </interfaces>
</mld>
```

## Command Syntax

```
ipv6 mld robustness-variable <2-7>
```

---

## Configure version

Use this attribute to set the current MLD protocol version on an interface. This attribute applies to interfaces configured for MLD Layer-3 multicast protocols, MLD Snooping, or MLD Proxy.

Attribute Name: version

Attribute Type: uint8

Attribute Range: 1-2

## Netconf edit-config payload

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <version>1</version> <!-- operation="delete"-->
    </interface>
  </interfaces>
```

```
</mld>
```

## Command Syntax

```
ipv6 mld version <1-2>
```

---

## Configure enable proxy service

Use this attribute to designate an interface to be the MLD proxy-service upstream host-side interface, thus enabling MLD host-side protocol operation on this interface. All associated downstream router-side interfaces will have their memberships consolidated on this interface, according to MLD host-side functionality. This attribute should not be used when configuring interfaces enabled for MLD in association with a multicast-routing protocol, otherwise the behavior will be undefined.

Attribute Name: enable-proxy-service

Attribute Type: empty

## Netconf edit-config payload

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
        </config>
        <proxy>
          <config>
            </enable-proxy-service><!-- operation="delete"-->
          </config>
        </proxy>
      </interface>
    </interfaces>
  </mld>
```

## Command Syntax

```
ipv6 mld proxy-service
```

---

## Configure mroute proxy interface

Use this attribute to specify the MLD Proxy service (upstream host-side) interface with which to be associated. MLD router-side protocol operation is enabled only when the specified upstream proxy-service interface is functional. This attribute should not be configured on interfaces enabled for MLD in association with a multicast routing protocol otherwise, the behavior will be undefined.

Attribute Name: mroute-proxy-interface

Attribute Type: string

Default Value: NULL

## Netconf edit-config payload

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <interfaces>
```

```

<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <proxy>
  <config>
    <mroute-proxy-interface>IFNAME</mroute-proxy-interface> <!--
operation="delete"-->
  </config>
</proxy>
</interface>
</interfaces>
</mld>

```

### Command Syntax

```
ipv6 mld mroute-proxy IFNAME
```

---

## Configure unsolicited report interval

Use this attribute to set an unsolicited report interval for an interface designated as an MLD proxy

Attribute Name: unsolicited-report-interval

Attribute Type: uint16

Default Value: 1000

Attribute Range: 1000-25500

### Netconf edit-config payload

```

<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <interfaces>
  <interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
    <proxy>
    <config>
      <unsolicited-report-interval>1000</unsolicited-report-interval> <!--
operation="delete"-->
    </config>
  </proxy>
  </interface>
</interfaces>
</mld>

```

### Command Syntax

```
ipv6 mld proxy unsolicited-report-interval <1000-25500>
```

---

## Configure limit exception acl

Use this attribute to set the maximum number of group membership states, at either the router level or at the interface level. Once the specified number of group memberships is reached, all further local-memberships are ignored. Optionally, an exception access-list can be configured to specify the group-address to be excluded from being subject to the limit.

Attribute Name: limit-exception-acl

Attribute Type: string

Default Value: NULL

Attribute Name: member-limit

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-2097152

## Netconf edit-config payload

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <group-membership-control>
        <config>
          <member-limit>1</member-limit> <!-- operation="delete"-->
          <limit-exception-acl>WORD</limit-exception-acl> <!-- operation="delete"-->
        </config>
      </group-membership-control>
    </interface>
  </interfaces>
</mld>
```

## Command Syntax

```
ipv6 mld limit <1-2097152> (except WORD|)
```

---

## Configure member limit

Use this attribute to set the limit on the maximum number of group membership states at either the router level, or for the specified interface. Once the specified number of group memberships is reached, all further local-memberships will be ignored. Optionally, an exception access-list can be configured to specify the group-address(es) to be excluded from being subject to the limit.

Attribute Name: member-limit

Attribute Type: uint32

Default Value: 1

Attribute Range: 1-2097152

**Netconf edit-config payload**

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <group-membership-control>
  <config>
    <member-limit>1</member-limit> <!-- operation="delete"-->
  </config>
</group-membership-control>
</interface>
</interfaces>
</mld>
```

**Command Syntax**

```
ipv6 mld limit <1-2097152>
```

**Configure access group name**

Use this attribute to control the multicast local-membership groups learned on an interface. This attribute applies to interfaces configured for MLD Layer-3 multicast protocols, MLD proxy.

Attribute Name: access-group-name

Attribute Type: string

Default Value: NULL

**Netconf edit-config payload**

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <group-membership-control>
  <config>
    <access-group-name>WORD</access-group-name> <!-- operation="delete"-->
  </config>
</group-membership-control>
</interface>
</interfaces>
</mld>
```

**Command Syntax**

```
ipv6 mld access-group WORD
```

---

## Configure immediate leave groups list

In MLD version 2, use this attribute to minimize the leave latency of MLD memberships. This attribute is used when only one receiver host is connected to each interface. This command applies to interfaces configured for MLD Layer-3 multicast protocols, MLD Proxy.

Attribute Name: immediate-leave-groups-list

Attribute Type: string

Default Value: NULL

### Netconf edit-config payload

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mlld">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <group-membership-control>
        <config>
          <immediate-leave-groups-list>WORD</immediate-leave-groups-list> <!--
operation="delete"-->
        </config>
      </group-membership-control>
    </interface>
  </interfaces>
</mld>
```

### Command Syntax

```
ipv6 mld immediate-leave group-list WORD
```

---

## Configure group address

Use this attribute to statically configure IPv6 group membership entries on an interface. To statically add only a group membership, do not specify any parameters. This attribute applies to MLD operation on a specific interface to statically add group and/or source records or to MLD Snooping on a VLAN interface to statically add group and/or source records.

Attribute Name: group-address

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```
<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mlld">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <asm-static-groups>
```

```

    <asm-static-group> <!-- operation="delete"-->
      <group-address>X:X::X:X</group-address>
      <config>
        <group-address>X:X::X:X</group-address>
      </config>
    </asm-static-group>
  </asm-static-groups>
</interface>
</interfaces>
</mld>

```

### Command Syntax

```
ipv6 mld static-group X:X::X:X
```

---

## Configure source

Use this attribute to statically configure the multicast source for group to be joined.

Attribute Name: source

Attribute Type: union

### Netconf edit-config payload

```

<mld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mld">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <ssm-static-groups>
        <ssm-static-group> <!-- operation="delete"-->
          <source>ssm-map</source>
          <config>
            <source>ssm-map</source>
            <group-address>X:X::X:X</group-address>
          </config>
          <group-address>X:X::X:X</group-address>
        </ssm-static-group>
      </ssm-static-groups>
    </interface>
  </interfaces>
</mld>

```

### Command Syntax

```
ipv6 mld static-group X:X::X:X source (ssm-map|X:X::X:X)
```

---

## IPI-ROTEMAP

---

### Configure action

Use this attribute to enter the route-map mode and to permit or deny match/set operations. If deny is specified, and the match criteria are met, the route is not redistributed, and any other route maps with the same map tag are not examined. If permit is specified, and the match criteria are met, the route is redistributed as specified by the set actions. If the match criteria are not met, the next route map with the same tag is tested.

Attribute Name: action

Attribute Type: enum (permit|deny)

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
    <action>permit</action>
  </routemap>
</routemaps>
```

### Command Syntax

```
route-map WORD ((permit|deny)|) (<1-65535>|)
```

---

### Configure continue to next sequence

The continue clause provides the capability to execute additional entries in a route map after an entry is executed with a successful match and set clauses. Example: the continue command allows multiple entries to be evaluated within a single route-map.

Attribute Name: continue-to-next-sequence

Attribute Type: empty

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
    <continue-on-match>
  </config>
```

```

        </continue-to-next-sequence><!-- operation="delete"-->
</config>
</continue-on-match>
</routemap>
</routemaps>

```

## Command Syntax

```
continue
```

---

## Configure next sequence number

Continue commands can be assigned optional sequence numbers that indicate the order in which clauses are to be evaluated.

Attribute Name: next-sequence-number

Attribute Type: uint32

Attribute Range: 2-65535

### Netconf edit-config payload

```

<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
</continue-on-match>
<config>
  <next-sequence-number>2</next-sequence-number> <!-- operation="delete"-->
</config>
</continue-on-match>
</routemap>
</routemaps>

```

## Command Syntax

```
continue <2-65535>
```

---

## Configure interface name

Use this attribute to define the interface match criterion. This command specifies the next-hop interface name of a route to be matched

Attribute Name: interface-name

Attribute Type: string

### Netconf edit-config payload

```

<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>

```

```

<config>
  <sequence-id>1</sequence-id>
  <routemap-name>WORD</routemap-name>
</config>
<routemap-name>WORD</routemap-name>
<match-condition>
<config>
  <interface-name>IFNAME</interface-name> <!-- operation="delete"-->
</config>
</match-condition>
</routemap>
</routemaps>

```

### Command Syntax

```
match interface IFNAME
```

---

## Configure metric

Use this attribute to match a metric of a route. The route specified by the policies might not be the same as specified by the routing protocols. Setting policies enable packets to take different routes depending on their length or content. Packet forwarding based on configured policies overrides packet forwarding specified in routing tables.

Attribute Name: metric

Attribute Type: uint32

Attribute Range: 1-4294967295

### Netconf edit-config payload

```

<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<match-condition>
<config>
  <metric>1</metric> <!-- operation="delete"-->
</config>
</match-condition>
</routemap>
</routemaps>

```

### Command Syntax

```
match metric <1-4294967295>
```

---

## Configure tag

Use this command to set a tag value. The parameter is the route tag that is labeled by another routing protocol (BGP or other IGP when redistributing), because AS-external-LSA has a route-tag field in its LSAs. In addition, when using

route-map, OcNOS can tag the LSAs with the appropriate tag value. Sometimes the tag matches with using route-map and sometimes, the value may be used by another application.

Attribute Name: tag

Attribute Type: uint32

Attribute Range: 1-4294967295

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<match-condition>
<config>
  <tag>1</tag> <!-- operation="delete"-->
</config>
</match-condition>
</routemap>
</routemaps>
```

### Command Syntax

```
match tag <1-4294967295>
```

---

## Configure route type

Use this attribute to match an external route type. AS-external LSA is either Type-1 or Type-2. External type-1 matches only Type 1 external routes and external type-2 matches only Type 2 external routes.

Attribute Name: route-type

Attribute Type: enum (type-1|type-2)

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<match-condition>
<config>
  <route-type>type-1</route-type> <!-- operation="delete"-->
</config>
</match-condition>
</routemap>
```

```
</routemaps>
```

## Command Syntax

```
match route-type external (type-1|type-2)
```

---

## Configure as path name

Use this command to match an autonomous system path access list. This command specifies the autonomous system path to be matched. If there is a match for the specified AS path, and permit is specified, the route is redistributed or controlled, as specified by the set action. If the match criteria are met, and deny is specified, the route is not redistributed or controlled. If the match criteria are not met then the route is neither accepted nor forwarded, irrespective of permit or deny specifications. The route specified by the policies might not be the same as specified by the routing protocols. Setting policies enable packets to take different routes, depending on their length or content. Packet forwarding based on configured policies overrides packet forwarding specified in routing tables.

Attribute Name: as-path-name

Attribute Type: string

## Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  <match-condition>
    <config>
      <as-path-name>WORD</as-path-name> <!-- operation="delete"-->
    </config>
  </match-condition>
</routemap>
</routemaps>
```

## Command Syntax

```
match as-path WORD
```

---

## Configure route origin

Use this attribute to match origin code. The origin attribute defines the origin of the path information. The egp parameter is indicated as an e in the routing table, and it indicates that the origin of the information is learned via EGP (Exterior Gateway Protocol). The igp parameter is indicated as an i in the routing table, and it indicates the origin of the path information is interior to the originating AS. The incomplete parameter is indicated as a ? in the routing table, and indicates that the origin of the path information is unknown or learned through other means. If a static route is redistributed into BGP, the origin of the route is incomplete. This command specifies the origin to be matched. If there is a match for the specified origin, and permit is specified when you created the route-map, the route is redistributed or controlled as specified by the set action. If the match criteria are met, and deny is specified, the route is not redistributed or controlled. If the match criteria are not met, the route is neither accepted nor forwarded, irrespective of permit or deny specifications. The route specified by the policies might not be the same as specified by the routing

protocols. Setting policies enable packets to take different routes depending on their length or content. Packet forwarding based on configured policies overrides packet forwarding specified in routing tables

Attribute Name: route-origin

Attribute Type: enum (egp|igp|incomplete)

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<match-condition>
<config>
  <route-origin>egp</route-origin> <!-- operation="delete"-->
</config>
</match-condition>
</routemap>
</routemaps>
```

### Command Syntax

```
match origin (egp|igp|incomplete)
```

---

## Configure community identifier

Use this attribute to specify the community to be matched. Communities are used to group and filter routes. They are designed to provide the ability to apply policies to large numbers of routes by using match and set commands. Community lists are used to identify and filter routes by their common attributes. This command allows the matching based on community lists. The values set by the match community command overrides the global values. The route that does not match at least one match clause is ignored.

Attribute Name: community-identifier

Attribute Type: union

Attribute Name: match-type

Attribute Type: enum (no-exact-match|exact-match)

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<match-condition>
<communities>
```

```

<community> <!-- operation="delete"-->
  <community-identifier>RMAP_COMMUNITY_STRING_T</community-identifier>
  <config>
    <community-identifier>RMAP_COMMUNITY_STRING_T</community-identifier>
    <match-type>no-exact-match</match-type>
  </config>
</community>
</communities>
</match-condition>
</routemap>
</routemaps>

```

## Command Syntax

```
match community (WORD|<1-99>|<100-500>) ((exact-match)|)
```

---

## Configure extended community identifier

Use this attribute to match BGP external community list. Communities are used to group and filter routes. They are designed to provide the ability to apply policies to large numbers of routes by using match and set commands. Community lists are used to identify and filter routes by their common attributes. This command allows the matching based on community lists. The values set by this command overrides the global values. The route that does not match at least one match clause is ignored

Attribute Name: extended-community-identifier

Attribute Type: union

Attribute Name: match-type

Attribute Type: enum (no-exact-match|exact-match)

## Netconf edit-config payload

```

<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  <match-condition>
    <extended-communities>
      <extended-community> <!-- operation="delete"-->
        <extended-community-identifier>RMAP_EXTCOMMUNITY_STRING_T</extended-community-identifier>
        <config>
          <extended-community-identifier>RMAP_EXTCOMMUNITY_STRING_T</extended-community-identifier>
          <match-type>no-exact-match</match-type>
        </config>
      </extended-community>
    </extended-communities>
  </match-condition>

```

```
</routemap>
</routemaps>
```

## Command Syntax

```
match extcommunity (WORD|<1-99>|<100-500>) ((exact-match)|)
```

---

## Configure match type

Do exact matching of communities

Attribute Name: match-type

Attribute Type: enum (no-exact-match|exact-match)

## Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<match-condition>
<extended-communities>
<extended-community>
  <extended-community-identifier>RMAP_EXTCOMMUNITY_STRING_T</extended-community-
identifier>
  <config>
    <extended-community-identifier>RMAP_EXTCOMMUNITY_STRING_T</extended-
community-identifier>
  </config>
  <match-type>0</match-type> <!-- operation="delete"-->
</extended-community>
</extended-communities>
</match-condition>
</routemap>
</routemaps>
```

## Command Syntax

```
no match extcommunity exact-match
```

---

## Configure ip access list name

Use this attribute to specify the match address of route. If there is a match for the specified IP address, and permit is specified, the route is redistributed or controlled, as specified by the set action. If the match criteria are met, and deny is specified then the route is not redistributed or controlled. If the match criteria are not met, the route is neither accepted nor forwarded, irrespective of permit or deny specifications. The route specified by the policies might not be the same as specified by the routing protocols. Setting policies enable packets to take different routes, depending on their length or content. Packet forwarding based on configured policies overrides packet forwarding specified in routing tables.

Attribute Name: ip-access-list-name

Attribute Type: string

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<match-condition>
<ipv4>
<config>
  <ip-access-list-name>WORD</ip-access-list-name> <!-- operation="delete"-->
</config>
</ipv4>
</match-condition>
</routemap>
</routemaps>
```

### Command Syntax

```
match ip address WORD
```

---

## Configure ip prefix list name

Use this attribute to match entries of a prefix-list. The route specified by the policies might not be the same as specified by the routing protocols. Setting policies enable packets to take different routes depending on their length or content. Packet forwarding based on configured policies overrides packet forwarding specified in routing tables.

Attribute Name: ip-prefix-list-name

Attribute Type: string

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<match-condition>
<ipv4>
<config>
  <ip-prefix-list-name>WORD</ip-prefix-list-name> <!-- operation="delete"-->
</config>
</ipv4>
</match-condition>
```

```
</routemap>
</routemaps>
```

## Command Syntax

```
match ip address prefix-list WORD
```

---

## Configure peer access list name

Use this attribute to specify the match peer IPv4 address of a route.

Attribute Name: peer-access-list-name

Attribute Type: string

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<match-condition>
<ipv4>
<config>
  <peer-access-list-name>WORD</peer-access-list-name> <!-- operation="delete"-->
>
</config>
</ipv4>
</match-condition>
</routemap>
</routemaps>
```

## Command Syntax

```
match ip peer WORD
```

---

## Configure next hop prefix list name

Use this attribute to specify the next-hop IP address match criterion using the prefix-list. This command matches the next-hop IP address of a route.

Attribute Name: next-hop-prefix-list-name

Attribute Type: string

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
```

```

        <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
<match-condition>
<ipv4>
<config>
        <next-hop-prefix-list-name>WORD</next-hop-prefix-list-name> <!--
operation="delete"-->
    </config>
</ipv4>
</match-condition>
</routemap>
</routemaps>

```

### Command Syntax

```
match ip next-hop prefix-list WORD
```

---

## Configure next hop access list name

Use this attribute to specify a next-hop address to be matched in a route-map. The route specified by the policies might not be the same as specified by the routing protocols. Setting policies enable packets to take different routes depending on their length or content. Packet forwarding based on configured policies overrides packet forwarding specified in routing tables.

Attribute Name: next-hop-access-list-name

Attribute Type: string

### Netconf edit-config payload

```

<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
    <sequence-id>1</sequence-id>
    <config>
        <sequence-id>1</sequence-id>
        <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
<match-condition>
<ipv4>
<config>
        <next-hop-access-list-name>WORD</next-hop-access-list-name> <!--
operation="delete"-->
    </config>
</ipv4>
</match-condition>
</routemap>
</routemaps>

```

### Command Syntax

```
match ip next-hop WORD
```

---

## Configure ipv6 address access list name

Use this attribute to specify the match address of route. The route specified by the policies might not be the same as specified by the routing protocols. Setting policies enable packets to take different routes depending on their length or content. Packet forwarding based on configured policies overrides packet forwarding specified in routing tables

This command is supported when following feature are enabled IPV6 feature

Attribute Name: ipv6-address-access-list-name

Attribute Type: string

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  <match-condition>
    <ipv6>
      <config>
        <ipv6-address-access-list-name>WORD</ipv6-address-access-list-name> <!--
operation="delete"-->
      </config>
    </ipv6>
  </match-condition>
</routemap>
</routemaps>
```

### Command Syntax

```
match ipv6 address WORD
```

---

## Configure ipv6 prefix list name

Use this attribute to match entries of a prefix-list. The route specified by the policies might not be the same as specified by the routing protocols. Setting policies enable packets to take different routes, depending on their length or content. Packet forwarding based on configured policies overrides packet forwarding specified in routing tables.

This command is supported when following feature are enabled IPV6 feature

Attribute Name: ipv6-prefix-list-name

Attribute Type: string

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
  </routemap>
</routemaps>
```

```

    </config>
    <routermap-name>WORD</routermap-name>
<match-condition>
<ipv6>
<config>
    <ipv6-prefix-list-name>WORD</ipv6-prefix-list-name> <!-- operation="delete"--
>
</config>
</ipv6>
</match-condition>
</routermap>
</routermaps>

```

### Command Syntax

```
match ipv6 address prefix-list WORD
```

---

## Configure routermap name

Use this attribute to specify the match peer IPv6 address of a route.

This command is supported when following feature are enabled IPV6 feature

Attribute Name: peer-access-list-name

Attribute Type: string

### Netconf edit-config payload

```

<routermaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routermap">
<routermap>
    <sequence-id>1</sequence-id>
    <config>
        <sequence-id>1</sequence-id>
        <routermap-name>WORD</routermap-name>
    </config>
    <routermap-name>WORD</routermap-name>
<match-condition>
<ipv6>
<config>
    <peer-access-list-name>WORD</peer-access-list-name> <!-- operation="delete"--
>
</config>
</ipv6>
</match-condition>
</routermap>
</routermaps>

```

### Command Syntax

```
match ipv6 peer WORD
```

---

## Configure sequence id

Use this attribute to match entries of a prefix-list. The route specified by the policies might not be the same as specified by the routing protocols. Setting policies enable packets to take different routes depending on their length or content. Packet forwarding based on configured policies overrides packet forwarding specified in routing tables.

This command is supported when following feature are enabled IPV6 feature

Attribute Name: next-hop-prefix-list-name

Attribute Type: string

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  <match-condition>
    <ipv6>
      <config>
        <next-hop-prefix-list-name>WORD</next-hop-prefix-list-name> <!--
operation="delete"-->
      </config>
    </ipv6>
  </match-condition>
</routemap>
</routemaps>
```

### Command Syntax

```
match ipv6 next-hop prefix-list WORD
```

---

## Configure next hop match string

Use this attribute to specify the next-hop address to be matched. The route specified by the policies might not be the same as specified by the routing protocols. Setting policies enable packets to take different routes depending on their length or content. Packet forwarding based on configured policies overrides packet forwarding specified in routing tables.

This command is supported when following feature are enabled IPV6 feature

Attribute Name: next-hop-match-string

Attribute Type: union

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
```

```

    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<match-condition>
<ipv6>
<config>
    <next-hop-match-string>RMAP_IPV6_NEXTHOP_T</next-hop-match-string>
</config>
</ipv6>
</match-condition>
</routemap>
</routemaps>

```

### Command Syntax

```
match ipv6 next-hop (WORD|X:X::X:X)
```

---

## Configure large community number match

Use this attributes to set the communities attribute. and group destinations in a certain community, as well as apply routing decisions according to those communities.

Attribute Name: large-community-number-match

Attribute Type: string

### Netconf edit-config payload

```

<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  <match-condition>
  <large-match-community>
  <config>
    <large-community-number-match>XXX:YYYY:ZZZ</large-community-number-match> <!--
- operation="delete"-->
  </config>
  </large-match-community>
  </match-condition>
</routemap>
</routemaps>

```

### Command Syntax

```
match large-community [XXX:YYYY:ZZZ]
```

---

## Configure metric value

Use this command to set a metric value for a route and influence external neighbors about the preferred path into an Autonomous System (AS). The preferred path is the one with a lower metric value. A router compares metrics for paths from neighbors in the same ASs. To compare metrics from neighbors coming from different ASs, use the `bgp always-compare-med` command. To use this command, you must first have a match clause. Match and set commands set the conditions for redistributing routes from one routing protocol to another. The match command specifies the match criteria under which redistribution is allowed for the current route-map. The set command specifies the set redistribution actions to be performed, if the match criteria are met. If the packets do not match any of the defined criteria, they are routed through the normal routing process.

Attribute Name: metric-value

Attribute Type: string

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  <set-action>
    <config>
      <metric-value>WORD</metric-value> <!-- operation="delete"-->
    </config>
  </set-action>
</routemap>
</routemaps>
```

### Command Syntax

```
set metric WORD
```

---

## Configure forward interface type

Use this attributes to discard routes based on policy/rules configured for a route map. Route maps can be applied to BGP neighbors. When this command is given for a route map and that route map is applied to a BGP neighbor, the discard route entries are added by BGP for the prefix permitted by the route map.

Attribute Name: forward-interface-type

Attribute Type: enum (null|tunnel-te)

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
```

```

    <routemap-name>WORD</routemap-name>
  <set-action>
  <config>
    <forward-interface-type>null0</forward-interface-type> <!--
operation="delete"-->
  </config>
</set-action>
</routemap>
</routemaps>

```

## Command Syntax

```
set interface (null0|tunnel-te)
```

---

## Configure route tag

Use this attribute to set a tag value. The parameter is the route tag that is labeled by another routing protocol (BGP or other IGP when redistributing), because AS-external-LSA has a route-tag field in its LSAs. In addition, when using route-map, OcNOS can tag the LSAs with the appropriate tag value. Sometimes the tag matches with using route-map, and sometimes, the value may be used by another application.

Attribute Name: route-tag

Attribute Type: uint32

Attribute Range: 1-4294967295

## Netconf edit-config payload

```

<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  <set-action>
  <config>
    <route-tag>1</route-tag> <!-- operation="delete"-->
  </config>
</set-action>
</routemap>
</routemaps>

```

## Command Syntax

```
set tag <1-4294967295>
```

---

## Configure weight

Use this attribute to set weights for the routing table. The weight value is used to assist in best path selection. It is assigned locally to a router. When there are several routes with a common destination, the routes with a higher weight value are preferred. To use this command, you must first have a match clause. Match and set commands set the conditions for redistributing routes from one routing protocol to another. The match command specifies the match

criteria under which redistribution is allowed for the current route-map. The set command specifies the set redistribution actions to be performed, if the match criteria are met.

Attribute Name: weight

Attribute Type: uint32

Attribute Range: 0-65535

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<config>
  <weight>0</weight> <!-- operation="delete"-->
</config>
</set-action>
</routemap>
</routemaps>
```

### Command Syntax

```
set weight <0-65535>
```

---

## Configure local preference

Use this attribute to set the BGP local preference path attribute

Attribute Name: local-preference

Attribute Type: uint32

Attribute Range: 0-4294967295

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<config>
  <local-preference>0</local-preference> <!-- operation="delete"-->
</config>
</set-action>
</routemap>
```

```
</routemaps>
```

## Command Syntax

```
set local-preference <0-4294967295>
```

---

## Configure route origin type

Use this command to set the BGP origin code. The origin attribute defines the origin of the path information. To use this command, you must first have a match clause. Match and set commands set the conditions for redistributing routes from one routing protocol to another. The match command specifies the match criteria under which redistribution is allowed for the current route-map. The set command specifies the set redistribution actions to be performed, if the match criteria are met. If the packets do not match any of the defined criteria, they are routed through the normal routing process.

Attribute Name: route-origin-type

Attribute Type: enum (egp|igp|incomplete)

## Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  <set-action>
    <config>
      <route-origin-type>egp</route-origin-type> <!-- operation="delete"-->
    </config>
  </set-action>
</routemap>
</routemaps>
```

## Command Syntax

```
set origin (egp|igp|incomplete)
```

---

## Configure metric type

Use this command to set the metric type for the destination routing protocol. Select a type to be either Type-1 or Type-2 in the AS-external-LSA when the route-map matches the condition.

Attribute Name: metric-type

Attribute Type: enum (type-1|type-2|internal|external)

## Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
```

```

    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<config>
    <metric-type>type-1</metric-type> <!-- operation="delete"-->
</config>
</set-action>
</routemap>
</routemaps>

```

### Command Syntax

```
set metric-type (type-1|type-2|internal|external)
```

---

## Configure aigp metric

Use this command to set the AIGP metric for BGP protocol routes.

Attribute Name: aigp-metric

Attribute Type: union

### Netconf edit-config payload

```

<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  <set-action>
  <config>
    <aigp-metric>igp-metric</aigp-metric> <!-- operation="delete"-->
  </config>
  </set-action>
</routemap>
</routemaps>

```

### Command Syntax

```
set aigp-metric (igp-metric|<1-4294967295>)
```

---

## Configure level type

Use this attribute to set the IS-IS level to export a route.

Attribute Name: level-type

Attribute Type: enum (level-1|level-2|level-1-2)

## Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<config>
  <level-type>level-1</level-type> <!-- operation="delete"-->
</config>
</set-action>
</routemap>
</routemaps>
```

## Command Syntax

```
set level (level-1|level-2|level-1-2)
```

---

## Configure enable as path tag

Use this command to modify an autonomous system path for a route. By specifying the length of the AS-Path, the router influences the best path selection by a neighbor

Attribute Name: enable-as-path-tag

Attribute Type: empty

## Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<config>
  </enable-as-path-tag><!-- operation="delete"-->
</config>
</set-action>
</routemap>
</routemaps>
```

## Command Syntax

```
set as-path tag
```

---

## Configure atomic aggregate

Use this attribute to set an atomic aggregate attribute. To use this command, you must first have a match clause. Match and set commands set the conditions for redistributing routes from one routing protocol to another. The match command specifies the match criteria under which redistribution is allowed for the current route-map. The set command specifies the set redistribution actions to be performed, if the match criteria are met. If the packets do not match any of the defined criteria, they are routed through the normal routing process.

Attribute Name: atomic-aggregate

Attribute Type: empty

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<config>
  </atomic-aggregate><!-- operation="delete"-->
</config>
</set-action>
</routemap>
</routemaps>
```

### Command Syntax

```
set atomic-aggregate
```

---

## Configure delete community value

Use this attribute to delete the matched communities from the community attribute of an inbound or outbound update when applying route-map.

Attribute Name: delete-community-value

Attribute Type: union

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<config>
```

```

        <delete-community-value>RMAP_COMMUNITY_STRING_T</delete-community-value>
</config>
</set-action>
</routemap>
</routemaps>

```

### Command Syntax

```
set comm-list (WORD|<1-99>|<100-500>) delete
```

---

## Configure bgp originator id

Use this command to set the originator ID attribute. To use this command, you must first have a match clause. Match and set commands set the conditions for redistributing routes from one routing protocol to another. The match command specifies the match criteria under which redistribution is allowed for the current route-map. The set command specifies the set redistribution actions to be performed, if the match criteria are met. If the packets do not match any of the defined criteria, they are routed through the normal routing process.

Attribute Name: bgp-originator-id

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<config>
  <bgp-originator-id>A.B.C.D</bgp-originator-id> <!-- operation="delete"-->
</config>
</set-action>
</routemap>
</routemaps>

```

### Command Syntax

```
set originator-id A.B.C.D
```

---

## Configure as path prepend

Use this attributes to modify an autonomous system path for a route. By specifying the length of the AS-Path, the router influences the best path selection by a neighbor. Use this command to prepend an AS path string to routes increasing the AS path length. To use this command, you must first give the match and set commands configure the conditions for redistributing routes from one routing protocol to another: 1. The match command specifies the match criteria under which redistribution is allowed for the current route-map. 2. The set command specifies the set redistribution actions to be performed if the match criteria are met. If the packets do not match any of the defined criteria, they are routed through the normal routing process.

Attribute Name: as-path-prepend

Attribute Type: string

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<config>
  <as-path-prepend>1</as-path-prepend> <!-- operation="delete"-->
</config>
</set-action>
</routemap>
</routemaps>
```

### Command Syntax

```
set as-path prepend .<1-4294967295>
```

---

## Configure ext community site of origin

Use this attribute to set an extended community attribute as Site-of-origin extended community.

Attribute Name: ext-community-site-of-origin

Attribute Type: string

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<config>
  <ext-community-site-of-origin>AA:NN</ext-community-site-of-origin> <!--
operation="delete"-->
</config>
</set-action>
</routemap>
</routemaps>
```

### Command Syntax

```
set extcommunity soo .AA:NN
```

---

## Configure ext community color

Use this attribute to set an extended community attribute color value

Attribute Name: ext-community-color

Attribute Type: uint32

Attribute Range: 1-4294967295

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<config>
  <ext-community-color>1</ext-community-color> <!-- operation="delete"-->
</config>
</set-action>
</routemap>
</routemaps>
```

### Command Syntax

```
set extcommunity color <1-4294967295>
```

---

## Configure ip nexthop address

Use this attribute to set the specified next-hop value.

Attribute Name: ip-nexthop-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<ipv4>
<config>
  <ip-nexthop-address>A.B.C.D</ip-nexthop-address> <!-- operation="delete"-->
</config>
</ipv4>
```

```

</set-action>
</routemap>
</routemaps>

```

## Command Syntax

```
set ip next-hop A.B.C.D
```

---

## Configure use peer address

Use this attribute to set the next hop value as BGP peer-address

Attribute Name: use-peer-address

Attribute Type: empty

## Netconf edit-config payload

```

<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  <set-action>
    <ipv4>
    <config>
      </use-peer-address><!-- operation="delete"-->
    </config>
    </ipv4>
  </set-action>
</routemap>
</routemaps>

```

## Command Syntax

```
set ip next-hop peer-address
```

---

## Configure vpnv4 nexthop address

Use this command to set a VPNv4 next-hop address. To use this command, you must first have a match clause. Match and set commands set the conditions for redistributing routes from one routing protocol to another. The match command specifies the match criteria under which redistribution is allowed for the current route-map. The set command specifies the set redistribution actions to be performed, if the match criteria are met. If the packets do not match any of the defined criteria, they are routed through the normal routing process.

Attribute Name: vpnv4-nexthop-address

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```

<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>

```

```

    <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<ipv4>
<config>
  <vpn4-nexthop-address>A.B.C.D</vpn4-nexthop-address> <!--
operation="delete"-->
</config>
</ipv4>
</set-action>
</routemap>
</routemaps>

```

### Command Syntax

```
set vpn4 next-hop A.B.C.D
```

---

## Configure ipv6 nexthop address

Use this attribute to set a next hop-address.

Attribute Name: ipv6-nexthop-address

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```

<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<ipv6>
<config>
  <ipv6-nexthop-address>X:X::X:X</ipv6-nexthop-address> <!--
operation="delete"-->
</config>
</ipv6>
</set-action>
</routemap>
</routemaps>

```

### Command Syntax

```
set ipv6 next-hop X:X::X:X
```

---

## Configure local ipv6 nexthop address

Use this attribute to set Local IPv6 address as next hop-address

Attribute Name: local-ipv6-nexthop-address

Attribute Type: inet:ipv6-address

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<ipv6>
<config>
  <local-ipv6-nexthop-address>X:X::X:X</local-ipv6-nexthop-address> <!--
operation="delete"-->
</config>
</ipv6>
</set-action>
</routemap>
</routemaps>
```

### Command Syntax

```
set ipv6 next-hop local X:X::X:X
```

---

## Configure aggregator ip address

IP address of aggregator.

Attribute Name: aggregator-ip-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
<routemap>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
    <routemap-name>WORD</routemap-name>
  </config>
  <routemap-name>WORD</routemap-name>
<set-action>
<bgp-aggregator-attributes>
<bgp-aggregator-attribute> <!-- operation="delete"-->
  <aggregator-ip-address>A.B.C.D</aggregator-ip-address>
```

```

<config>
  <aggregator-ip-address>A.B.C.D</aggregator-ip-address>
  <as-number>1</as-number>
</config>
  <as-number>1</as-number>
</bgp-aggregator-attribute>
</bgp-aggregator-attributes>
</set-action>
</routemap>
</routemaps>

```

## Command Syntax

```
set aggregator as <1-4294967295> A.B.C.D
```

---

## Configure ext community rt

use this attribute to set an Route target extended community

Attribute Name: ext-community-rt

Attribute Type: string

Attribute Range: 1-255

Attribute Name: additive-type

Attribute Type: enum (no-additive|additive)

## Netconf edit-config payload

```

<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  </set-action>
  <extended-community>
  <route-targets>
  <route-target> <!-- operation="delete"-->
    <ext-community-rt>AA:NN</ext-community-rt>
    <config>
      <ext-community-rt>AA:NN</ext-community-rt>
      <additive-type>no-additive</additive-type>
    </config>
  </route-target>
</route-targets>
</extended-community>
</set-action>
</routemap>
</routemaps>

```

---

## Command Syntax

```
set extcommunity rt .AA:NN ((additive|))
```

---

## Configure cost value

use this attribute to set Extended community cost value

Attribute Name: cost-value

Attribute Type: uint32

Attribute Range: 0-4294967295

## Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  <set-action>
    <extended-community>
      <costs>
        <cost> <!-- operation="delete"-->
          <cost-value>0</cost-value>
          <config>
            <cost-value>0</cost-value>
            <community-id>0</community-id>
            <comparison-type>no-comparision</comparison-type>
          </config>
          <community-id>0</community-id>
          <comparison-type>no-comparision</comparison-type>
        </cost>
      </costs>
    </extended-community>
  </set-action>
</routemap>
</routemaps>
```

## Command Syntax

```
set extcommunity cost (igp|pre-bestpath|) <0-255> <0-4294967295>
```

---

## Configure max suppress time limit

Maximum duration to suppress a stable route in minutes.

Attribute Name: max-suppress-time-limit

Attribute Type: uint8

Default Value: 60

Attribute Range: 1-255

Attribute Name: enable-dampening

Attribute Type: empty

Attribute Name: reachability-half-life-time

Attribute Type: uint8

Default Value: 15

Attribute Range: 1-45

Attribute Name: reuse-time-limit

Attribute Type: uint16

Default Value: 750

Attribute Range: 1-20000

Attribute Name: suppress-time-limit

Attribute Type: uint16

Default Value: 2000

Attribute Range: 1-20000

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  <set-action>
    <dampening>
      <config>
        </enable-dampening><!-- operation="delete"-->
        <reachability-half-life-time>1</reachability-half-life-time> <!--
operation="delete"-->
        <reuse-time-limit>1</reuse-time-limit> <!-- operation="delete"-->
        <suppress-time-limit>1</suppress-time-limit> <!-- operation="delete"-->
        <max-suppress-time-limit>1</max-suppress-time-limit> <!-- operation="delete"-
-->
      </config>
    </dampening>
  </set-action>
</routemap>
</routemaps>
```

### Command Syntax

```
set dampening <1-45> <1-20000> <1-20000> <1-255>
```

---

## Configure unreachability half life time

Un-reachability half-life time for the penalty in minutes.

Attribute Name: unreachability-half-life-time

Attribute Type: uint8

Default Value: 15

Attribute Range: 1-45

Attribute Name: enable-dampening

Attribute Type: empty

Attribute Name: reachability-half-life-time

Attribute Type: uint8

Default Value: 15

Attribute Range: 1-45

Attribute Name: reuse-time-limit

Attribute Type: uint16

Default Value: 750

Attribute Range: 1-20000

Attribute Name: suppress-time-limit

Attribute Type: uint16

Default Value: 2000

Attribute Range: 1-20000

Attribute Name: max-suppress-time-limit

Attribute Type: uint8

Default Value: 60

Attribute Range: 1-255

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  <set-action>
    <dampening>
      <config>
        </enable-dampening><!-- operation="delete"-->
        <reachability-half-life-time>1</reachability-half-life-time> <!--
operation="delete"-->
        <reuse-time-limit>1</reuse-time-limit> <!-- operation="delete"-->
      </config>
    </dampening>
  </set-action>
</routemap>
</routemaps>
```

```

        <suppress-time-limit>1</suppress-time-limit> <!-- operation="delete"-->
        <max-suppress-time-limit>1</max-suppress-time-limit> <!-- operation="delete"-->
->
        <unreachability-half-life-time>1</unreachability-half-life-time> <!--
operation="delete"-->
    </config>
</dampening>
</set-action>
</routemap>
</routemaps>

```

## Command Syntax

```
set dampening <1-45> <1-20000> <1-20000> <1-255> <1-45>
```

---

## Configure enable dampening

Use this attribute to enable route dampening and set various parameters. Route dampening minimizes the instability caused by route flapping. A penalty is added for every flap in a flapping route. As soon as the total penalty reaches the suppress limit the advertisement of the route is suppressed. This penalty is decayed according to the configured half time value. Once the penalty is lower than the reuse limit, the route advertisement is unsuppressed. The dampening information is purged from the router once the penalty becomes less than half of the reuse limit. Reachability half-life time for the penalty in minutes. The time for the penalty to decrease to one-half of its current value.

Attribute Name: enable-dampening

Attribute Type: empty

## Netconf edit-config payload

```

<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  <set-action>
    <dampening>
      <config>
        </enable-dampening>
      </config>
    </dampening>
  </set-action>
</routemap>
</routemaps>

```

## Command Syntax

```
set dampening
```

---

## Configure community with as number

Autonomous system (AS) number and network number entered in the 4-byte new community format. This value is configured with two 2-byte numbers separated by a colon. A number from 1 to 65535 can be entered as each 2-byte number. A single community can be entered or multiple communities can be entered, each separated by a space.

Attribute Name: community-with-as-number

Attribute Type: string

Attribute Name: additive-set

Attribute Type: empty

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
      <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
  <set-action>
    <communities>
      <config>
        </additive-set><!-- operation="delete"-->
        <community-with-as-number>AA:NN</community-with-as-number> <!--
operation="delete"-->
      </config>
    </communities>
  </set-action>
</routemap>
</routemaps>
```

### Command Syntax

```
set community-additive .AA:NN
```

---

## Configure large community number set

Use this attributes to set the communities attribute. and group destinations in a certain community, as well as apply routing decisions according to those communities.

Attribute Name: large-community-number-set

Attribute Type: string

Attribute Range: 1-32

### Netconf edit-config payload

```
<routemaps xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-routemap">
  <routemap>
    <sequence-id>1</sequence-id>
    <config>
```

```

        <sequence-id>1</sequence-id>
        <routemap-name>WORD</routemap-name>
    </config>
    <routemap-name>WORD</routemap-name>
<set-action>
<large-community>
<config>
    <large-community-number-set>XXX:YYYY:ZZZ</large-community-number-set> <!--
operation="delete"-->
</config>
</large-community>
</set-action>
</routemap>
</routemaps>

```

### Command Syntax

```
set large-community XXX:YYYY:ZZZ
```

---

## IPI-DCB

---

### Configure dcb enabled

Enable Data-Center-Bridging

Attribute Name: dcb-enabled

Attribute Type: boolean

#### Netconf edit-config payload

```

<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
<bridges>
<bridge>
    <bridge-id>1</bridge-id>
    <config>
        <bridge-id>1</bridge-id>
    </config>
    <dcb-enabled>true</dcb-enabled> <!-- operation="delete"-->
</bridge>
</bridges>
</dcb>

```

### Command Syntax

```
data-center-bridging enable bridge <1-32>
```

---

### Configure bridge id

Enable Data-Center-Bridging

Attribute Name: dcb-enabled

Attribute Type: boolean

### Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
  <bridges>
    <bridge>
      <bridge-id>1</bridge-id>
      <config>
        <bridge-id>1</bridge-id>
      </config>
      <dcb-enabled>true</dcb-enabled> <!-- operation="delete"-->
    </bridge>
  </bridges>
</dcb>
```

### Command Syntax

```
data-center-bridging disable bridge <1-32>
```

---

## Configure enable ets

Enhanced-Transmission-Selection

Attribute Name: enable-ets

Attribute Type: uint8

### Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
  <bridges>
    <bridge>
      <bridge-id>1</bridge-id>
      <config>
        <bridge-id>1</bridge-id>
      </config>
      </enable-ets><!-- operation="delete"-->
    </bridge>
  </bridges>
</dcb>
```

### Command Syntax

```
enhanced-transmission-selection enable bridge <1-32>
```

---

## Configure enable application priority

enable Application-Priority

Attribute Name: enable-application-priority

Attribute Type: uint8

### Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
```

```

<bridges>
<bridge>
  <bridge-id>1</bridge-id>
  <config>
    <bridge-id>1</bridge-id>
  </config>
  </enable-application-priority><!-- operation="delete"-->
</bridge>
</bridges>
</dcb>

```

### Command Syntax

```
application-priority enable bridge <1-32>
```

---

## Configure enable pfc

enable Priority-Flow-Control

This command is supported when following feature are enabled DCB feature

Attribute Name: enable-pfc

Attribute Type: empty

### Netconf edit-config payload

```

<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
<bridges>
<bridge>
  <bridge-id>1</bridge-id>
  <config>
    <bridge-id>1</bridge-id>
  </config>
  </enable-pfc><!-- operation="delete"-->
</bridge>
</bridges>
</dcb>

```

### Command Syntax

```
priority-flow-control enable bridge <1-32>
```

---

## Configure enabled

Use this attribute to enable QCN for a bridge

Attribute Name: enabled

Attribute Type: uint8

Attribute Name: cnm-transmit-priority

Attribute Type: uint8

Default Value: 6

Attribute Range: 0-7

**Netconf edit-config payload**

```

<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
<bridges>
<bridge>
  <bridge-id>1</bridge-id>
  <config>
    <bridge-id>1</bridge-id>
  </config>
</bridge>
</bridges>
</dcb>

```

**Command Syntax**

```
qcn enable bridge <1-32> (cnm-transmit-priority <0-7>|)
```

**Configure priority value**

Use this attribute to configure cnpv defense priority value

Attribute Name: priority-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: qcn-mode

Attribute Type: enum (admin|auto|component)

**Netconf edit-config payload**

```

<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
<bridges>
<bridge>
  <bridge-id>1</bridge-id>
  <config>
    <bridge-id>1</bridge-id>
  </config>
</bridge>
</bridges>
</dcb>

```

```

</qcn>
</bridge>
</bridges>
</dcb>

```

## Command Syntax

```
defense-mode cnpv <0-7> (auto)
```

---

## Configure qcn mode

Use this attribute to configure cnpv defense priority value

Attribute Name: priority-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: qcn-mode

Attribute Type: enum (admin|auto|component)

Attribute Name: admin-defense-mode

Attribute Type: enum (disabled|interior|interior-ready|edge)

Attribute Name: alternate-priority

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```

<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
  <bridges>
    <bridge>
      <bridge-id>1</bridge-id>
      <config>
        <bridge-id>1</bridge-id>
      </config>
    </bridge>
  </bridges>
  <qcn>
    <cnpv-defenses>
      <cnpv-defense <!-- operation="delete"-->
        <priority-value>0</priority-value>
        <config>
          <priority-value>0</priority-value>
          <qcn-mode>admin</qcn-mode>
          <admin-defense-mode>disabled</admin-defense-mode>
          <alternate-priority>0</alternate-priority>
        </config>
      </cnpv-defense>
    </cnpv-defenses>
  </qcn>
</dcb>

```

---

## Command Syntax

```
defense-mode cnpv <0-7> (admin) (disabled|interior|interior-ready|edge) alternate-
priority <0-7>
```

---

## Configure enable

This attribute enables debugging for DCB

Attribute Name: enable

Attribute Type: uint8

## Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
<debug>
<config>
  </enable><!-- operation="delete"-->
</config>
</debug>
</dcb>
```

## Command Syntax

```
debug dcb on
```

---

# IPI-DCB-INTERFACE

---

## Configure pfc mode

Enable Data-Center-Bridging

This command is supported when following feature are enabled DCB feature

Attribute Name: pfc-mode

Attribute Type: enum (on|auto)

## Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <pfc-mode>on</pfc-mode> <!-- operation="delete"-->
</interface>
</interfaces>
</dcb>
```

---

## Command Syntax

```
priority-flow-control mode (on|auto)
```

---

## Configure ets mode

Use this attribute to set Enhanced Transmission Selection mode

This command is supported when following feature are enabled DCB feature

Attribute Name: ets-mode

Attribute Type: enum (on|auto)

### Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <ets-mode>on</ets-mode> <!-- operation="delete"-->
    </interface>
  </interfaces>
</dcb>
```

## Command Syntax

```
enhanced-transmission-selection mode (on|auto)
```

---

## Configure priority value

Use this attribute to configure cnpv defense priority value

Attribute Name: priority-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: qcn-mode

Attribute Type: enum (admin|auto|component)

### Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <qcn>
        <cnpv-defenses>
          <cnpv-defense> <!-- operation="delete"-->
        </cnpv-defenses>
      </qcn>
    </interface>
  </interfaces>
</dcb>
```

```

    <priority-value>0</priority-value>
  <config>
    <priority-value>0</priority-value>
    <qcn-mode>admin</qcn-mode>
  </config>
</cnpv-defense>
</cnpv-defenses>
</qcn>
</interface>
</interfaces>
</dcb>

```

## Command Syntax

```
defense-mode cnpv <0-7> (auto|component)
```

---

## Configure name

Use this attribute to configure cnpv defense priority value

Attribute Name: priority-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: qcn-mode

Attribute Type: enum (admin|auto|component)

Attribute Name: admin-defense-mode

Attribute Type: enum (disabled|interior|interior-ready|edge)

Attribute Name: alternate-priority

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```

<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
  <cnpv-defenses>
    <cnpv-defense <!-- operation="delete"-->
      <priority-value>0</priority-value>
      <config>
        <priority-value>0</priority-value>
        <qcn-mode>admin</qcn-mode>
        <admin-defense-mode>disabled</admin-defense-mode>
        <alternate-priority>0</alternate-priority>
      </config>
    </cnpv-defense>
  </cnpv-defenses>
</dcb>

```

```

    </config>
  </cnpv-defense>
</cnpv-defenses>
</qcn>
</interface>
</interfaces>
</dcb>

```

## Command Syntax

```

defense-mode cnpv <0-7> (admin) (disabled|interior|interior-ready|edge) alternate-
priority <0-7>

```

---

## Configure cnpv value

Use this attribute to configure cnpv value

Attribute Name: cnpv-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: sample-base

Attribute Type: uint32

Attribute Range: 1024-10240

Attribute Name: weight

Attribute Type: int8

## Netconf edit-config payload

```

<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <qcn>
  <congestion-points>
  <congestion-point> <!-- operation="delete"-->
    <cnpv-value>0</cnpv-value>
    <config>
      <cnpv-value>0</cnpv-value>
      <sample-base>1024</sample-base>
      <weight>WEIGHT</weight>
    </config>
  </congestion-point>
</congestion-points>
</qcn>
</interface>
</interfaces>
</dcb>

```

## Command Syntax

```
cp enable cnpv <0-7> (sample-base <1024-10240>|) (weight WEIGHT|)
```

---

## Configure weight

Use this attribute to configure weight

This command is supported when following feature are enabled DCB feature

Attribute Name: weight

Attribute Type: int8

Attribute Name: sample-base

Attribute Type: uint32

Attribute Range: 1024-10240

## Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <qcn>
  <congestion-points>
  <congestion-point>
    <cnpv-value>0</cnpv-value>
    <config>
      <cnpv-value>0</cnpv-value>
      <sample-base>1024</sample-base> <!-- operation="delete"-->
    </config>
    <weight>WEIGHT</weight> <!-- operation="delete"-->
  </congestion-point>
</congestion-points>
</qcn>
</interface>
</interfaces>
</dcb>
```

## Command Syntax

```
cp enable cnpv <0-7> (sample-base <1024-10240>|) (weight WEIGHT|)
```

---

## Configure accept peer config

Use this attribute to accept peer configuration

This command is supported when following feature are enabled DCB feature

Attribute Name: accept-peer-config

Attribute Type: empty

## Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <priority-flow-control>
  <config>
    </accept-peer-config><!-- operation="delete"-->
  </config>
</priority-flow-control>
</interface>
</interfaces>
</dcb>
```

## Command Syntax

```
priority-flow-control accept-peer-config
```

---

## Configure advertise local config

Use this attribute to advertise local configuration to peer

This command is supported when following feature are enabled DCB feature

Attribute Name: advertise-local-config

Attribute Type: empty

## Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <priority-flow-control>
  <config>
    </advertise-local-config><!-- operation="delete"-->
  </config>
</priority-flow-control>
</interface>
</interfaces>
</dcb>
```

## Command Syntax

```
priority-flow-control advertise-local-config
```

---

## Configure cap

Use this attribute to set cap value

This command is supported when following feature are enabled DCB feature

Attribute Name: cap

Attribute Type: uint8

Attribute Range: 0-8

### Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <priority-flow-control>
        <config>
          <cap>0</cap> <!-- operation="delete"-->
        </config>
      </priority-flow-control>
    </interface>
  </interfaces>
</dcb>
```

### Command Syntax

```
priority-flow-control cap <0-8>
```

---

## Configure link delay allowance

Use this attribute to set link delay allowance

This command is supported when following feature are enabled DCB feature

Attribute Name: link-delay-allowance

Attribute Type: uint32

Attribute Range: 0-65535

### Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <priority-flow-control>
        <config>
```

```

        <link-delay-allowance>0</link-delay-allowance> <!-- operation="delete"-->
    </config>
</priority-flow-control>
</interface>
</interfaces>
</dcb>

```

### Command Syntax

```
priority-flow-control link-delay-allowance <0-65535>
```

---

## Configure enhanced-transmission-selection advertise-local-config

Use this attribute to advertise local configuration to peer

This command is supported when following feature are enabled DCB feature

Attribute Name: advertise-local-config

Attribute Type: empty

### Netconf edit-config payload

```

<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <enhanced-transmission-selection>
        <config>
          </advertise-local-config><!-- operation="delete"-->
        </config>
      </enhanced-transmission-selection>
    </interface>
  </interfaces>
</dcb>

```

### Command Syntax

```
enhanced-transmission-selection advertise-local-config
```

---

## Configure enhanced-transmission-selection accept-peer-config

Use this attribute to accept peer configuration

This command is supported when following feature are enabled DCB feature

Attribute Name: accept-peer-config

Attribute Type: empty

### Netconf edit-config payload

```

<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
  <interfaces>

```

```

<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <enhanced-transmission-selection>
  <config>
    </accept-peer-config><!-- operation="delete"-->
  </config>
</enhanced-transmission-selection>
</interface>
</interfaces>
</dcb>

```

### Command Syntax

```
enhanced-transmission-selection accept-peer-config
```

---

## Configure max traffic class groups

Use this attribute to set maximum traffic class groups

This command is supported when following feature are enabled DCB feature

Attribute Name: max-traffic-class-groups

Attribute Type: uint8

Attribute Range: 0-2

### Netconf edit-config payload

```

<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
  <interfaces>
  <interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
    <enhanced-transmission-selection>
    <config>
      <max-traffic-class-groups>0</max-traffic-class-groups> <!--
operation="delete"-->
    </config>
  </enhanced-transmission-selection>
  </interface>
</interfaces>
</dcb>

```

### Command Syntax

```
max-traffic-class-group <0-2>
```

---

## Configure bandwidth percentage

Use this attribute to set bandwidth percentage

Attribute Name: bandwidth-percentage

Attribute Type: uint8

Attribute Range: 0-100

### Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <enhanced-transmission-selection>
        <traffic-class-groups>
          <traffic-class-group>
            <group-index>0</group-index>
            <config>
              <group-index>0</group-index>
            </config>
            <bandwidth-percentage>0</bandwidth-percentage> <!-- operation="delete"-->
          </traffic-class-group>
        </traffic-class-groups>
      </enhanced-transmission-selection>
    </interface>
  </interfaces>
</dcb>
```

### Command Syntax

```
bandwidth-percentage <0-1> <0-100>
```

---

## Configure enabled

Use this attribute to enable application priority

This command is supported when following feature are enabled DCB feature

Attribute Name: enabled

Attribute Type: empty

### Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
</dcb>
```

```

    </config>
  <application-priority>
    <config>
      </enabled><!-- operation="delete"-->
    </config>
  </application-priority>
</interface>
</interfaces>
</dcb>

```

### Command Syntax

```
application-priority enable
```

---

## Configure application-priority advertise-local-config

Use this attribute to advertise local configuration to peer

This command is supported when following feature are enabled DCB feature

Attribute Name: advertise-local-config

Attribute Type: empty

### Netconf edit-config payload

```

<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
        </config>
        <application-priority>
          <config>
            </advertise-local-config><!-- operation="delete"-->
          </config>
        </application-priority>
      </interface>
    </interfaces>
  </dcb>

```

### Command Syntax

```
application-priority advertise-local-config
```

---

## Configure protocol type

Use this attribute to set priority value

This command is supported when following feature are enabled DCB feature

Attribute Name: priority-value

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <application-priority>
  <port-mappings>
  <port-mapping> <!-- operation="delete"-->
    <priority-value>0</priority-value>
    <config>
      <priority-value>0</priority-value>
      <port-number>1</port-number>
      <protocol-type>tcp</protocol-type>
    </config>
    <port-number>1</port-number>
    <protocol-type>tcp</protocol-type>
  </port-mapping>
</port-mappings>
</application-priority>
</interface>
</interfaces>
</dcb>
```

## Command Syntax

```
(tcp|udp|both-tcp-udp) port-no <1-1023> priority <0-7>
```

---

## Configure service name

Use this attribute to set priority value of service map

This command is supported when following feature are enabled DCB feature

Attribute Name: priority-value

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <application-priority>
  <service-mappings>
  <service-mapping> <!-- operation="delete"-->
```

```

    <priority-value>0</priority-value>
  <config>
    <priority-value>0</priority-value>
    <service-name>PROTOSERV</service-name>
    <protocol-type>tcp</protocol-type>
  </config>
  <service-name>PROTOSERV</service-name>
  <protocol-type>tcp</protocol-type>
</service-mapping>
</service-mappings>
</application-priority>
</interface>
</interfaces>
</dcb>

```

## Command Syntax

```
(tcp|udp|both-tcp-udp) service-name PROTOSERV priority <0-7>
```

---

## Configure ether name

Use this attribute to configure priority

This command is supported when following feature are enabled DCB feature

Attribute Name: priority-value

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```

<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <application-priority>
  <ethertype-name-mappings>
  <ethertype-name-mapping> <!-- operation="delete"-->
    <priority-value>0</priority-value>
    <config>
      <priority-value>0</priority-value>
      <ether-name>ETHERNAME</ether-name>
    </config>
    <ether-name>ip</ether-name>
  </ethertype-name-mapping>
</ethertype-name-mappings>
</application-priority>
</interface>
</interfaces>

```

---

```
</dcb>
```

## Command Syntax

```
ethertype name
(ip|x25|arp|g8bpqx25|ieeepup|ieeeeaddrtrans|dec|decnadumpload|decdnaremoteconsol
e|decdnarouting|declat|decdiagnostics|rarp|atalkddp|atalkaarp|ipx|ipv6|atmmulti|
pppdiscovery|pppsession|atmtransport|ETHERNAME) priority <0-7>
```

---

## Configure ether value

Use this attribute to configure priority

This command is supported when following feature are enabled DCB feature

Attribute Name: priority-value

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```
<dcb xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dcb">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <application-priority>
  <ethertype-value-mappings>
  <ethertype-value-mapping> <!-- operation="delete"-->
    <priority-value>0</priority-value>
    <config>
      <priority-value>0</priority-value>
      <ether-value>ETHERTYPE</ether-value>
    </config>
    <ether-value>ETHERTYPE</ether-value>
  </ethertype-value-mapping>
</ethertype-value-mappings>
</application-priority>
</interface>
</interfaces>
</dcb>
```

## Command Syntax

```
ethertype value ETHERTYPE priority <0-7>
```

---

## IPI-RIP

---

### Configure options

This attribute enables debugging for RIP

Attribute Name: options

Attribute Type: bits (all|events|packet send|packet rcv|packet|packet detail|nsm|rib|bfd)

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <debug>
  <config>
    <options>all</options> <!-- operation="delete"-->
  </config>
</debug>
</rip>
```

### Command Syntax

```
debug rip (all|events|packet send|packet rcv|packet|packet detail|nsm|rib|bfd)
```

---

### Configure split horizon

Use this attribute to controls RIP split-horizon processing on the specified interface.

Attribute Name: split-horizon

Attribute Type: boolean

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <interfaces>
  <interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
    <split-horizon>true</split-horizon> <!-- operation="delete"-->
  </interface>
</interfaces>
</rip>
```

### Command Syntax

```
ip rip split-horizon
```

---

### Configure name

Use this attribute to controls RIP split-horizon processing on the specified interface.

Attribute Name: split-horizon

Attribute Type: boolean

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <split-horizon>true</split-horizon> <!-- operation="delete"-->
    </interface>
  </interfaces>
</rip>
```

### Command Syntax

```
no ip rip split-horizon
```

---

## Configure disable receive packet

Use this attribute to configure the interface to enable/disable the reception of RIP packets

Attribute Name: disable-receive-packet

Attribute Type: uint8

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </disable-receive-packet><!-- operation="delete"-->
    </interface>
  </interfaces>
</rip>
```

### Command Syntax

```
no ip rip receive-packet
```

---

## Configure disable send packet

Use this attribute to enable/disable sending RIP packets through current interface

Attribute Name: disable-send-packet

Attribute Type: uint8

**Netconf edit-config payload**

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </disable-send-packet><!-- operation="delete"-->
</interface>
</interfaces>
</rip>
```

**Command Syntax**

```
no ip rip send-packet
```

---

**Configure receive version**

Use this attribute to receive specified version of RIP packets on an interface

Attribute Name: receive-version

Attribute Type: enum (1|2|1 2|1-compatible)

**Netconf edit-config payload**

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <receive-version>1</receive-version> <!-- operation="delete"-->
</interface>
</interfaces>
</rip>
```

**Command Syntax**

```
ip rip receive version (1|2|1 2)
```

---

**Configure send version**

Use this attribute to set the version of RIP packets which can be sent from an interface

Attribute Name: send-version

Attribute Type: enum (1|2|1 2|1-compatible)

**Netconf edit-config payload**

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
<interfaces>
<interface>
```

```
<name>WORD</name>
<config>
  <name>WORD</name>
</config>
<send-version>1</send-version> <!-- operation="delete"-->
</interface>
</interfaces>
</rip>
```

### Command Syntax

```
ip rip send version (1|2|1 2|1-compatible)
```

---

## Configure auth mode

Use this attribute to set the type of authentication mode used for RIP packets

Attribute Name: auth-mode

Attribute Type: enum (text|md5)

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <auth-mode>text</auth-mode> <!-- operation="delete"-->
</interface>
</interfaces>
</rip>
```

### Command Syntax

```
ip rip authentication mode (text|md5)
```

---

## Configure auth string

Use this attribute to set the authentication string or password used by a key

Attribute Name: auth-string

Attribute Type: string

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</interfaces>
</rip>
```

```
    <auth-string>LINE</auth-string> <!-- operation="delete"-->
</interface>
</interfaces>
</rip>
```

### Command Syntax

```
ip rip authentication string LINE
```

---

## Configure auth keychain

Use this attribute to enable RIP authentication on an interface and specify the name of the key chain to be used

Attribute Name: auth-keychain

Attribute Type: string

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
<interfaces>
<interface>
    <name>WORD</name>
    <config>
        <name>WORD</name>
    </config>
    <auth-keychain>LINE</auth-keychain> <!-- operation="delete"-->
</interface>
</interfaces>
</rip>
```

### Command Syntax

```
ip rip authentication key-chain LINE
```

---

## Configure rip enabled

Use this attribute enable a RIP routing process

Attribute Name: rip-enabled

Attribute Type: uint8

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
<instance>
<config>
    </rip-enabled>
</config>
</instance>
</rip>
```

### Command Syntax

```
router rip
```

---

## Configure bfd enable

This feature indicates that the RIP implementation on the system supports BFD

Attribute Name: bfd-enable

Attribute Type: empty

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <config>
      </bfd-enable><!-- operation="delete"-->
    </config>
  </instance>
</rip>
```

### Command Syntax

```
bfd all-interfaces
```

---

## Configure receive buffer size

Use this attribute to set the RIP UDP receive-buffer size.

Attribute Name: receive-buffer-size

Attribute Type: uint32

Default Value: 32768

Attribute Range: 8192-2147483647

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <config>
      <receive-buffer-size>8192</receive-buffer-size> <!-- operation="delete"-->
    </config>
  </instance>
</rip>
```

### Command Syntax

```
recv-buffer-size <8192-2147483647>
```

---

## Configure passive interfaces

Disables sending of RIP packets on the specified interface

Attribute Name: passive-interfaces

Attribute Type: string

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
```

```
<instance>
<config>
  <passive-interfaces>IFNAME</passive-interfaces> <!-- operation="delete"-->
</config>
</instance>
</rip>
```

### Command Syntax

```
passive-interface IFNAME
```

---

## Configure static routes

Use this attribute to set static RIP routes

Attribute Name: static-routes

Attribute Type: string

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
<instance>
<config>
  <static-routes>A.B.C.D/M</static-routes> <!-- operation="delete"-->
</config>
</instance>
</rip>
```

### Command Syntax

```
route A.B.C.D/M
```

---

## Configure neighbors

Specifies the RIP neighbors

Attribute Name: neighbors

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
<instance>
<config>
  <neighbors>A.B.C.D</neighbors> <!-- operation="delete"-->
</config>
</instance>
</rip>
```

### Command Syntax

```
neighbor A.B.C.D
```

---

## Configure neighbor fall over bfd

Specified the BFD neighbors

Attribute Name: neighbor-fall-over-bfd

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <config>
      <neighbor-fall-over-bfd>A.B.C.D</neighbor-fall-over-bfd> <!--
operation="delete"-->
    </config>
  </instance>
</rip>
```

### Command Syntax

```
neighbor A.B.C.D fall-over bfd
```

---

## Configure enable cisco metric behavior

Use this attribute to set metric updation behavior as Cisco

Attribute Name: enable-cisco-metric-behavior

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <config>
      <enable-cisco-metric-behavior>disable</enable-cisco-metric-behavior> <!--
operation="delete"-->
    </config>
  </instance>
</rip>
```

### Command Syntax

```
cisco-metric-behavior (disable|enable)
```

---

## Configure default metric

Set the default metric

Attribute Name: default-metric

Attribute Type: uint8

Default Value: 1

Attribute Range: 1-15

---

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <config>
      <default-metric>1</default-metric> <!-- operation="delete"-->
    </config>
  </instance>
</rip>
```

### Command Syntax

```
default-metric <1-15>
```

---

## Configure version

Use this attribute to set version of routing protocol

Attribute Name: version

Attribute Type: uint8

Default Value: 2

Attribute Range: 1-2

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <config>
      <version>1</version> <!-- operation="delete"-->
    </config>
  </instance>
</rip>
```

### Command Syntax

```
version <1-2>
```

---

## Configure distance

Use this attribute to set administrative distance of the RIP for the current RIP instance

Attribute Name: distance

Attribute Type: uint8

Default Value: 120

Attribute Range: 1-255

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <config>
      <distance>1</distance> <!-- operation="delete"-->
    </config>
  </instance>
</rip>
```

```
</instance>  
</rip>
```

### Command Syntax

```
distance <1-255>
```

---

## Configure network interfaces

Use this attribute to enable routing on an interface

Attribute Name: network-interfaces

Attribute Type: string

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">  
  <instance>  
    <config>  
      <network-interfaces>IFNAME</network-interfaces> <!-- operation="delete"-->  
    </config>  
  </instance>  
</rip>
```

### Command Syntax

```
network IFNAME
```

---

## Configure network routes

Use this attribute to enable routing on an IP network

Attribute Name: network-routes

Attribute Type: string

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">  
  <instance>  
    <config>  
      <network-routes>A.B.C.D/M</network-routes> <!-- operation="delete"-->  
    </config>  
  </instance>  
</rip>
```

### Command Syntax

```
network A.B.C.D/M
```

---

## Configure access list name

Use this attribute to set the access list name

Attribute Name: access-list-name

Attribute Type: string

Attribute Name: distance

Attribute Type: uint8

Attribute Range: 1-255

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <distances>
      <distance>
        <source-prefix>A.B.C.D/M</source-prefix>
        <config>
          <source-prefix>A.B.C.D/M</source-prefix>
          <distance>1</distance>
        </config>
        <access-list-name>WORD</access-list-name>
      </distance>
    </distances>
  </instance>
</rip>
```

### Command Syntax

```
distance <1-255> A.B.C.D/M (WORD|)
```

---

## Configure route table update interval

Interval at which RIP updates are sent

Attribute Name: route-table-update-interval

Attribute Type: uint32

Attribute Range: 5-2147483647

Attribute Name: route-info-timeout-interval

Attribute Type: uint32

Attribute Range: 5-2147483647

Attribute Name: garbage-collection-interval

Attribute Type: uint32

Attribute Range: 5-2147483647

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <timers>
      <config>
        <route-info-timeout-interval>5</route-info-timeout-interval>
        <garbage-collection-interval>5</garbage-collection-interval>
        <route-table-update-interval>5</route-table-update-interval>
      </config>
    </timers>
  </instance>
</rip>
```

```

</instance>
</rip>

```

### Command Syntax

```
timers basic <5-2147483647> <5-2147483647> <5-2147483647>
```

---

## Configure warning threshold percentage

Use this attribute to set the percentage of maximum routes to generate a warning

Attribute Name: warning-threshold-percentage

Attribute Type: uint32

Attribute Range: 1-100

Attribute Name: max-routes

Attribute Type: uint32

Attribute Range: 1-65535

### Netconf edit-config payload

```

<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <maximum-prefix>
      <config>
        <max-routes>1</max-routes> <!-- operation="delete"-->
        <warning-threshold-percentage>1</warning-threshold-percentage> <!--
operation="delete"-->
      </config>
    </maximum-prefix>
  </instance>
</rip>

```

### Command Syntax

```
maximum-prefix <1-65535> (<1-100>|)
```

---

## Configure route type

Use this attribute to redistributes only specified route-type routes matching the specified route type into the RIP routing instance

Attribute Name: route-type

Attribute Type: enum (kernel|connected|static|ospf|isis|bgp)

### Netconf edit-config payload

```

<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <redistribute-policies>
      <redistribute-policy> <!-- operation="delete"-->
        <route-type>kernel</route-type>
      </redistribute-policy>
    </redistribute-policies>
  </instance>
</rip>

```

```

    </config>
  </redistribute-policy>
</redistribute-policies>
</instance>
</rip>

```

### Command Syntax

```
redistribute (kernel|connected|static|ospf|isis|bgp)
```

---

## Configure route map

Use this attribute to set th route-map

Attribute Name: route-map

Attribute Type: string

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

### Netconf edit-config payload

```

<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <redistribute-policies>
      <redistribute-policy>
        <route-type>kernel</route-type>
        <config>
          <route-type>kernel</route-type>
          <metric>0</metric> <!-- operation="delete"-->
        </config>
        <route-map>WORD</route-map> <!-- operation="delete"-->
      </redistribute-policy>
    </redistribute-policies>
  </instance>
</rip>

```

### Command Syntax

```
redistribute (kernel|connected|static|ospf|isis|bgp) metric <0-16> route-map WORD
```

---

## Configure metric

Metric used for the redistributed route

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
```

```

<instance>
<redistribute-policies>
<redistribute-policy>
  <route-type>kernel</route-type>
  <config>
    <route-type>kernel</route-type>
  </config>
  <metric>0</metric> <!-- operation="delete"-->
</redistribute-policy>
</redistribute-policies>
</instance>
</rip>

```

### Command Syntax

```
redistribute (kernel|connected|static|ospf|isis|bgp) metric <0-16>
```

---

## Configure redistribute-policy route-map

Use this attribute to set th route-map

Attribute Name: route-map

Attribute Type: string

### Netconf edit-config payload

```

<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
<instance>
<redistribute-policies>
<redistribute-policy>
  <route-type>kernel</route-type>
  <config>
    <route-type>kernel</route-type>
  </config>
  <route-map>WORD</route-map> <!-- operation="delete"-->
</redistribute-policy>
</redistribute-policies>
</instance>
</rip>

```

### Command Syntax

```
redistribute (kernel|connected|static|ospf|isis|bgp) route-map WORD
```

---

## Configure originate

Use this attribute to apply conditions of the route policy to the default route

Attribute Name: route-map

Attribute Type: string

Attribute Name: originate

Attribute Type: empty

Attribute Name: always-advertise

Attribute Type: empty

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <default-information>
      <config>
        </originate><!-- operation="delete"-->
        </always-advertise><!-- operation="delete"-->
        <route-map>WORD</route-map> <!-- operation="delete"-->
      </config>
    </default-information>
  </instance>
</rip>
```

### Command Syntax

```
default-information originate (always|) (route-map WORD|)
```

---

## Configure direction

Use this attribute to set the metric value of routing protocol

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

Attribute Name: access-list-name

Attribute Type: string

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <offset-lists>
      <offset-list>
        <direction>in</direction>
        <config>
          <direction>in</direction>
          <access-list-name>WORD</access-list-name>
        </config>
        <metric>0</metric>
      </offset-list>
    </offset-lists>
  </instance>
</rip>
```

### Command Syntax

```
offset-list WORD (in|out) <0-16>
```

---

## Configure distribute-filter-list direction

Use this attribute to set direction of the routing updates

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: access-list-name

Attribute Type: string

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <distribute-filter-lists>
      <distribute-filter-list>
        <direction>in</direction>
        <config>
          <direction>in</direction>
          <access-list-name>WORD</access-list-name>
        </config>
      </distribute-filter-list>
    </distribute-filter-lists>
  </instance>
</rip>
```

### Command Syntax

```
distribute-list WORD (in|out)
```

---

## Configure distribute-prefix-list direction

Use this attribute to set direction of the routing updates

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: access-list-name

Attribute Type: string

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <distribute-prefix-lists>
      <distribute-prefix-list>
        <direction>in</direction>
        <config>
          <direction>in</direction>
          <access-list-name>WORD</access-list-name>
        </config>
      </distribute-prefix-list>
    </distribute-prefix-lists>
  </instance>
</rip>
```

```
</instance>  
</rip>
```

## Command Syntax

```
distribute-list prefix WORD (in|out)
```

---

## Configure offset-list metric

Use this attribute to set the metric value of routing protocol

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

Attribute Name: access-list-name

Attribute Type: string

## Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">  
  <instance>  
    <interfaces>  
      <interface>  
        <name>IFNAME</name>  
        <config>  
          <name>IFNAME</name>  
          </config>  
        <offset-lists>  
          <offset-list>  
            <direction>in</direction>  
            <config>  
              <direction>in</direction>  
              <access-list-name>WORD</access-list-name>  
            </config>  
            <metric>0</metric>  
          </offset-list>  
        </offset-lists>  
      </interface>  
    </interfaces>  
  </instance>  
</rip>
```

## Command Syntax

```
offset-list WORD (in|out) <0-16> IFNAME
```

---

## Configure distribute-filter-list direction

Use this attribute to set direction of the routing updates

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: access-list-name

Attribute Type: string

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <interfaces>
      <interface>
        <name>IFNAME</name>
        <config>
          <name>IFNAME</name>
        </config>
        <distribute-filter-lists>
          <distribute-filter-list>
            <direction>in</direction>
            <config>
              <direction>in</direction>
              <access-list-name>WORD</access-list-name>
            </config>
          </distribute-filter-list>
        </distribute-filter-lists>
      </interface>
    </interfaces>
  </instance>
</rip>
```

### Command Syntax

```
distribute-list WORD (in|out) IFNAME
```

---

## Configure distribute-prefix-list direction

Use this attribute to set direction of the routing updates

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: access-list-name

Attribute Type: string

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <interfaces>
      <interface>
        <name>IFNAME</name>
        <config>
          <name>IFNAME</name>
        </config>
        <distribute-prefix-lists>
          <distribute-prefix-list>
```

```
<direction>in</direction>
<config>
  <direction>in</direction>
  <access-list-name>WORD</access-list-name>
</config>
</distribute-prefix-list>
</distribute-prefix-lists>
</interface>
</interfaces>
</instance>
</rip>
```

### Command Syntax

```
distribute-list prefix WORD (in|out) IFNAME
```

---

## clear ip rip route (kernel|connected|static|ospf|isis|bgp|rip|all)

Attribute Name: route-type

Attribute Type: enum (kernel|connected|static|ospf|isis|bgp|rip|all)

### Netconf RPC payload

```
<rip-clear-route xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <route-type>kernel</route-type>
</rip-clear-route>
```

### Command Syntax

```
clear ip rip route (kernel|connected|static|ospf|isis|bgp|rip|all)
```

---

## clear ip rip route A.B.C.D/M

Attribute Name: prefix-address

Attribute Type: string

### Netconf RPC payload

```
<rip-clear-route-prefix xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <prefix-address>A.B.C.D/M</prefix-address>
</rip-clear-route-prefix>
```

### Command Syntax

```
clear ip rip route A.B.C.D/M
```

---

## clear ip rip statistics (IFNAME)

Attribute Name: name

Attribute Type: string

Default Value: NULL

---

## Netconf RPC payload

```
<rip-clear-statistics xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <name>IFNAME</name>
</rip-clear-statistics>
```

## Command Syntax

```
clear ip rip statistics (IFNAME|)
```

---

## snmp restart rip

### Netconf RPC payload

```
<rip-snmp-restart xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip"/>
```

### Command Syntax

```
snmp restart rip
```

---

## debug rip (all|events|packet send|packet rcv|packet|packet detail|nsm|rib|bfd)

Attribute Name: terminal-debug-options

Attribute Type: bits (all|events|packet send|packet rcv|packet|packet detail|nsm|rib|bfd)

### Netconf RPC payload

```
<rip-terminal-debugging-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <terminal-debug-options>all</terminal-debug-options>
</rip-terminal-debugging-on>
```

### Command Syntax

```
debug rip (all|events|packet send|packet rcv|packet|packet detail|nsm|rib|bfd)
```

---

## no debug rip (all|events|packet send|packet rcv|packet|packet detail|nsm|rib|bfd)

Attribute Name: terminal-debug-options

Attribute Type: bits (all|events|packet send|packet rcv|packet|packet detail|nsm|rib|bfd)

### Netconf RPC payload

```
rip">
  <rip-terminal-debugging-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
  <terminal-debug-options>all</terminal-debug-options>
  </rip-terminal-debugging-off>
```

### Command Syntax

```
no debug rip (all|events|packet send|packet rcv|packet|packet detail|nsm|rib|bfd)
```

---

## IPI-RIP-VRF

---

### Configure vrf name

VRF name

Attribute Name: vrf-name

Attribute Type: string

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf> <!-- operation="delete"-->
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
      </vrf>
    </vrfs>
  </instance>
</rip>
```

### Command Syntax

```
address-family ipv4 vrf NAME
```

---

### Configure enable cisco metric behavior

Use this attribute to set metric updation behavior as Cisco

Attribute Name: enable-cisco-metric-behavior

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <enable-cisco-metric-behavior>disable</enable-cisco-metric-behavior> <!--
operation="delete"-->
      </vrf>
    </vrfs>
  </instance>
</rip>
```

---

## Command Syntax

```
cisco-metric-behavior (disable|enable)
```

---

## Configure default metric

Set the default metric

Attribute Name: default-metric

Attribute Type: uint8

Default Value: 1

Attribute Range: 1-15

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <default-metric>1</default-metric> <!-- operation="delete"-->
      </vrf>
    </vrfs>
  </instance>
</rip>
```

## Command Syntax

```
default-metric <1-15>
```

---

## Configure version

Use this attribute to set version of routing protocol

Attribute Name: version

Attribute Type: uint8

Default Value: 2

Attribute Range: 1-2

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
      </vrf>
    </vrfs>
  </instance>
</rip>
```

```

        <version>1</version> <!-- operation="delete"-->
    </vrf>
</vrfs>
</instance>
</rip>

```

### Command Syntax

```
version <1-2>
```

---

## Configure distance

Use this attribute to set administrative distance of the RIP for the current RIP instance

Attribute Name: distance

Attribute Type: uint8

Default Value: 120

Attribute Range: 1-255

### Netconf edit-config payload

```

<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <distance>1</distance> <!-- operation="delete"-->
      </vrf>
    </vrfs>
  </instance>
</rip>

```

### Command Syntax

```
distance <1-255>
```

---

## Configure network interfaces

Use this attribute to enable routing on an interface

Attribute Name: network-interfaces

Attribute Type: string

### Netconf edit-config payload

```

<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>

```

```

    <config>
      <vrf-name>WORD</vrf-name>
    </config>
    <network-interfaces>IFNAME</network-interfaces> <!-- operation="delete"-->
  >
    </vrf>
  </vrf>
</instance>
</rip>

```

### Command Syntax

```
network IFNAME
```

---

## Configure network routes

Use this attribute to enable routing on an IP network

Attribute Name: network-routes

Attribute Type: string

### Netconf edit-config payload

```

<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
      </config>
      <network-routes>A.B.C.D/M</network-routes> <!-- operation="delete"-->
    </vrf>
  </instance>
</rip>

```

### Command Syntax

```
network A.B.C.D/M
```

---

## Configure access list name

Use this attribute to set the access list name

Attribute Name: access-list-name

Attribute Type: string

Attribute Name: distance

Attribute Type: uint8

Attribute Range: 1-255

## Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <distances>
          <distance>
            <source-prefix>A.B.C.D/M</source-prefix>
            <config>
              <source-prefix>A.B.C.D/M</source-prefix>
              <distance>1</distance>
            </config>
            <access-list-name>WORD</access-list-name>
          </distance>
        </distances>
      </vrf>
    </vrfs>
  </instance>
</rip>
```

## Command Syntax

```
distance <1-255> A.B.C.D/M (WORD|)
```

---

## Configure route type

Use this attribute to redistributes only specified route-type routes matching the specified route type into the RIP routing instance

Attribute Name: route-type

Attribute Type: enum (connected|static|ospf|bgp)

## Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <redistribute-policies>
          <redistribute-policy> <!-- operation="delete"-->
            <route-type>connected</route-type>
            <config>
              <route-type>connected</route-type>
            </config>
          </redistribute-policy>
        </redistribute-policies>
      </vrf>
    </vrfs>
  </instance>
</rip>
```

```

    </redistribute-policy>
  </redistribute-policies>
</vrf>
</vrfs>
</instance>
</rip>

```

## Command Syntax

```
redistribute (connected|static|ospf|bgp)
```

---

## Configure route map

Use this attribute to set the name of the route-map

Attribute Name: route-map

Attribute Type: string

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

## Netconf edit-config payload

```

<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <redistribute-policies>
          <redistribute-policy>
            <route-type>connected</route-type>
            <config>
              <route-type>connected</route-type>
              <metric>0</metric> <!-- operation="delete"-->
            </config>
            <route-map>WORD</route-map> <!-- operation="delete"-->
          </redistribute-policy>
        </redistribute-policies>
      </vrf>
    </vrfs>
  </instance>
</rip>

```

## Command Syntax

```
redistribute (connected|static|ospf|bgp) metric <0-16> route-map WORD
```

---

## Configure metric

Use this attribute to set the metric used for the redistributed route

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <redistribute-policies>
          <redistribute-policy>
            <route-type>connected</route-type>
            <config>
              <route-type>connected</route-type>
            </config>
            <metric>0</metric> <!-- operation="delete"-->
          </redistribute-policy>
        </redistribute-policies>
      </vrf>
    </vrfs>
  </instance>
</rip>
```

### Command Syntax

```
redistribute (connected|static|ospf|bgp) metric <0-16>
```

---

## Configure redistribute-policy route-map

Use this attribute to set the name of the route-map

Attribute Name: route-map

Attribute Type: string

### Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
      </vrf>
    </vrfs>
  </instance>
</rip>
```

```

    <redistribute-policies>
    <redistribute-policy>
      <route-type>connected</route-type>
      <config>
        <route-type>connected</route-type>
      </config>
      <route-map>WORD</route-map> <!-- operation="delete"-->
    </redistribute-policy>
  </redistribute-policies>
</vrf>
</vrfs>
</instance>
</rip>

```

### Command Syntax

```
redistribute (connected|static|ospf|bgp) route-map WORD
```

---

## Configure originate

Use this attribute to apply conditions of the route policy to the default route

Attribute Name: route-map

Attribute Type: string

Attribute Name: originate

Attribute Type: empty

Attribute Name: always-advertise

Attribute Type: empty

### Netconf edit-config payload

```

<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <default-information>
          <config>
            </originate><!-- operation="delete"-->
            </always-advertise><!-- operation="delete"-->
            <route-map>WORD</route-map> <!-- operation="delete"-->
          </config>
        </default-information>
      </vrf>
    </vrfs>
  </instance>
</rip>

```

## Command Syntax

```
default-information originate (always|) (route-map WORD|)
```

---

## Configure direction

Use this attribute to set the metric value of routing protocol

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

Attribute Name: access-list-name

Attribute Type: string

## Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <offset-lists>
          <offset-list>
            <direction>in</direction>
            <config>
              <direction>in</direction>
              <access-list-name>WORD</access-list-name>
            </config>
            <metric>0</metric>
          </offset-list>
        </offset-lists>
      </vrf>
    </vrfs>
  </instance>
</rip>
```

## Command Syntax

```
offset-list WORD (in|out) <0-16>
```

---

## Configure distribute-filter-list direction

Use this attribute to set direction of the routing updates

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: access-list-name

Attribute Type: string

**Netconf edit-config payload**

```

<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <distribute-filter-lists>
          <distribute-filter-list>
            <direction>in</direction>
            <config>
              <direction>in</direction>
              <access-list-name>WORD</access-list-name>
            </config>
          </distribute-filter-list>
        </distribute-filter-lists>
      </vrf>
    </vrfs>
  </instance>
</rip>

```

**Command Syntax**

```
distribute-list WORD (in|out)
```

**Configure distribute-prefix-list direction**

Use this attribute to set direction of the routing updates

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: access-list-name

Attribute Type: string

**Netconf edit-config payload**

```

<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <distribute-prefix-lists>
          <distribute-prefix-list>
            <direction>in</direction>
            <config>
              <direction>in</direction>
            </config>
          </distribute-prefix-list>
        </distribute-prefix-lists>
      </vrf>
    </vrfs>
  </instance>
</rip>

```

```

        <access-list-name>WORD</access-list-name>
    </config>
</distribute-prefix-list>
</distribute-prefix-lists>
</vrf>
</vrfs>
</instance>
</rip>

```

## Command Syntax

```
distribute-list prefix WORD (in|out)
```

---

## Configure name

Use this attribute to set the metric value of routing protocol

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

Attribute Name: access-list-name

Attribute Type: string

## Netconf edit-config payload

```

<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <interfaces>
          <interface>
            <name>IFNAME</name>
            <config>
              <name>IFNAME</name>
              </config>
              <offset-lists>
                <offset-list>
                  <direction>in</direction>
                  <config>
                    <direction>in</direction>
                    <access-list-name>WORD</access-list-name>
                  </config>
                  <metric>0</metric>
                </offset-list>
              </offset-lists>
            </interface>
          </interfaces>

```

```

</vrf>
</vrfs>
</instance>
</rip>

```

## Command Syntax

```
offset-list WORD (in|out) <0-16> IFNAME
```

---

## Configure distribute-filter-list direction

Use this attribute to set direction of the routing updates

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: access-list-name

Attribute Type: string

## Netconf edit-config payload

```

<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <interfaces>
          <interface>
            <name>IFNAME</name>
            <config>
              <name>IFNAME</name>
              <distribute-filter-lists>
                <distribute-filter-list>
                  <direction>in</direction>
                  <config>
                    <direction>in</direction>
                    <access-list-name>WORD</access-list-name>
                  </config>
                </distribute-filter-list>
              </distribute-filter-lists>
            </interface>
          </interfaces>
        </vrf>
      </vrfs>
    </instance>
  </rip>

```

## Command Syntax

```
distribute-list WORD (in|out) IFNAME
```

## Configure distribute-prefix-list direction

Use this attribute to set direction of the routing updates

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: access-list-name

Attribute Type: string

## Netconf edit-config payload

```
<rip xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-rip">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <interfaces>
          <interface>
            <name>IFNAME</name>
            <config>
              <name>IFNAME</name>
              <direction>in</direction>
            </config>
            <distribute-prefix-lists>
              <distribute-prefix-list>
                <direction>in</direction>
                <config>
                  <direction>in</direction>
                  <access-list-name>WORD</access-list-name>
                </config>
              </distribute-prefix-list>
            </distribute-prefix-lists>
          </interface>
        </interfaces>
      </vrf>
    </vrfs>
  </instance>
</rip>
```

## Command Syntax

```
distribute-list prefix WORD (in|out) IFNAME
```

## clear ip rip route vrf NAME A.B.C.D/M

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: prefix

Attribute Type: string

### Netconf RPC payload

```
<ipi-rip-vrf_rip-vrf-clear-route xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-rip">
  <vrf-name>NAME</vrf-name>
  <prefix>A.B.C.D/M</prefix>
</ipi-rip-vrf_rip-vrf-clear-route>
```

### Command Syntax

```
clear ip rip route vrf NAME A.B.C.D/M
```

---

## clear ip rip route vrf NAME \*

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<ipi-rip-vrf_rip-vrf-clear-route-all xmlns="http://www.ipinfusion.com/yang/
ocnos/ipi-rip">
  <vrf-name>NAME</vrf-name>
</ipi-rip-vrf_rip-vrf-clear-route-all>
```

### Command Syntax

```
clear ip rip route vrf NAME *
```

---

## IPI-SNMP

---

### Configure enable link down trap

Use this attribute to enable or disable SNMP linkdown traps.

Attribute Name: enable-link-down-trap

Attribute Type: boolean

Attribute Name: enable-link-up-trap

Attribute Type: boolean

### Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snm">
  <server-traps>
  <config>
    <enable-link-up-trap>true</enable-link-up-trap> <!-- operation="delete"-->
    <enable-link-down-trap>true</enable-link-down-trap> <!-- operation="delete"-->
  </config>
```

```
</server-traps>  
</snmp>
```

## Command Syntax

```
snmp-server enable traps link
```

---

## Configure enable link up trap

Use this attribute to enable or disable SNMP linkdown traps.

Attribute Name: enable-link-down-trap

Attribute Type: boolean

Attribute Name: enable-link-up-trap

Attribute Type: boolean

## Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">  
<server-traps>  
<config>  
  <enable-link-up-trap>true</enable-link-up-trap> <!-- operation="delete"-->  
  <enable-link-down-trap>true</enable-link-down-trap> <!-- operation="delete"-->  
</config>  
</server-traps>  
</snmp>
```

## Command Syntax

```
no snmp-server enable traps link
```

---

## Configure include interface name

Use this attribute to include ifname with SNMP linkdown traps.

Attribute Name: include-interface-name

Attribute Type: uint8

## Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">  
<server-traps>  
<config>  
  </include-interface-name><!-- operation="delete"-->  
</config>  
</server-traps>  
</snmp>
```

## Command Syntax

```
snmp-server enable traps link include-interface-name
```

---

## Configure server-traps enable-link-down-trap

Use this attribute to enable or disable SNMP linkdown traps.

Attribute Name: enable-link-down-trap

Attribute Type: boolean

### Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <server-traps>
    <config>
      <enable-link-down-trap>true</enable-link-down-trap> <!-- operation="delete"-->
    </config>
  </server-traps>
</snmp>
```

### Command Syntax

```
snmp-server enable traps link linkDown
```

---

## Configure server-traps enable-link-down-trap

Use this attribute to enable or disable SNMP linkdown traps.

Attribute Name: enable-link-down-trap

Attribute Type: boolean

### Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <server-traps>
    <config>
      <enable-link-down-trap>true</enable-link-down-trap> <!-- operation="delete"-->
    </config>
  </server-traps>
</snmp>
```

### Command Syntax

```
no snmp-server enable traps link linkDown
```

---

## Configure server-traps enable-link-up-trap

Use this attribute to enable or disable SNMP linkup traps.

Attribute Name: enable-link-up-trap

Attribute Type: boolean

### Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <server-traps>
    <config>
      <enable-link-up-trap>true</enable-link-up-trap> <!-- operation="delete"-->
    </config>
  </server-traps>
</snmp>
```

```

</config>
</server-traps>
</snmp>

```

## Command Syntax

```
snmp-server enable traps link linkUp
```

---

## Configure server-traps enable-link-up-trap

Use this attribute to enable or disable SNMP linkup traps.

Attribute Name: enable-link-up-trap

Attribute Type: boolean

### Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <server-traps>
    <config>
      <enable-link-up-trap>true</enable-link-up-trap> <!-- operation="delete"-->
    </config>
  </server-traps>
</snmp>

```

## Command Syntax

```
no snmp-server enable traps link linkUp
```

---

## Configure enable traps

Use this attribute to enable or disable SNMP traps and inform requests.

This command is supported when following feature are enabled SNMP-AGENT feature

Attribute Name: enable-traps

Attribute Type: bits (snmp authentication|mpls|pw|pwdelete|rsvp|ospf|bgp|isis|vrrp|vxlan|ospf6|mpls3vpn|rib|pim)

### Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <server-traps>
    <config>
      <enable-traps>snmp authentication</enable-traps> <!-- operation="delete"-->
    </config>
  </server-traps>
</snmp>

```

## Command Syntax

```
snmp-server enable traps (snmp
authentication|mpls|pw|pwdelete|rsvp|ospf|bgp|isis|vrrp|vxlan|ospf6|mpls3vpn|ri
b|pim)
```

---

## Configure enable trap cache

Enables trap caching

This command is supported when following feature are enabled SNMP-AGENT feature

Attribute Name: enable-trap-cache

Attribute Type: empty

### Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <server-traps>
    <trap-cache>
      <config>
        </enable-trap-cache>
      </config>
    </trap-cache>
  </server-traps>
</snmp>
```

### Command Syntax

```
snmp-server trap-cache
```

---

## Configure timeout

Sets timeout before sending traps

This command is supported when following feature are enabled SNMP-AGENT feature

Attribute Name: timeout

Attribute Type: int8

Default Value: 10

Attribute Range: 1-20

### Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <server-traps>
    <trap-cache>
      <config>
        <timeout>1</timeout> <!-- operation="delete"-->
      </config>
    </trap-cache>
  </server-traps>
</snmp>
```

### Command Syntax

```
timeout <1-20>
```

---

## Configure disable ping

Disables pings to check host reachability

This command is supported when following feature are enabled SNMP-AGENT feature

Attribute Name: disable-ping

Attribute Type: empty

### Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <server-traps>
    <trap-cache>
      <config>
        </disable-ping><!-- operation="delete"-->
      </config>
    </trap-cache>
  </server-traps>
</snmp>
```

### Command Syntax

```
disable-ping
```

---

## Configure max count

Sets the maximum number of traps that can be cached

This command is supported when following feature are enabled SNMP-AGENT feature

Attribute Name: max-count

Attribute Type: int16

Default Value: 200

Attribute Range: 1-500

### Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <server-traps>
    <trap-cache>
      <config>
        <max-count>1</max-count> <!-- operation="delete"-->
      </config>
    </trap-cache>
  </server-traps>
</snmp>
```

### Command Syntax

```
max-count <1-500>
```

---

## **debug (snmp send|snmp receive|snmp process|snmp xdump|snmp error-string|snmp detail|snmp|snmp all)**

Attribute Name: debug

Attribute Type: bits (snmp send|snmp receive|snmp process|snmp xdump|snmp error-string|snmp detail|snmp|snmp all)

### **Netconf RPC payload**

```
<snmp-agentx-enable-terminal-debugging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <debug>snmp send</debug>
</snmp-agentx-enable-terminal-debugging>
```

### **Command Syntax**

```
debug (snmp send|snmp receive|snmp process|snmp xdump|snmp error-string|snmp
detail|snmp|snmp all)
```

---

## **no debug (snmp send|snmp receive|snmp process|snmp xdump|snmp error-string|snmp detail|snmp|snmp all)**

Attribute Name: debug

Attribute Type: bits (snmp send|snmp receive|snmp process|snmp xdump|snmp error-string|snmp detail|snmp|snmp all)

### **Netconf RPC payload**

```
<snmp-agentx-disable-terminal-debugging xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <debug>snmp send</debug>
</snmp-agentx-disable-terminal-debugging>
```

### **Command Syntax**

```
no debug (snmp send|snmp receive|snmp process|snmp xdump|snmp error-string|snmp
detail|snmp|snmp all)
```

---

## **IPI-SNMP-SERVER**

---

### **Configure vrf name**

VRF name associated with this instance.

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: enabled

Attribute Type: empty

---

## Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
<server>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
    </enabled>
  </config>
</server>
</servers>
</snmp>
```

## Command Syntax

```
snmp-server enable snmp (vrf (NAME|management)|)
```

---

## Configure system contact

Use this attribute to set the system contact information for the device (sysContact object)

Attribute Name: system-contact

Attribute Type: string

## Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
<server>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
    </config>
  <global>
    <config>
      <system-contact>LINE</system-contact> <!-- operation="delete"-->
    </config>
  </global>
</server>
</servers>
</snmp>
```

## Command Syntax

```
snmp-server contact (vrf (NAME|management)|) LINE
```

---

## Configure system location

Use this attribute to set the physical location information of the device (sysLocation object)

Attribute Name: system-location

Attribute Type: string

## Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
<server>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
</global>
<config>
  <system-location>LINE</system-location> <!-- operation="delete"-->
</config>
</global>
</server>
</servers>
</snmp>

```

## Command Syntax

```
snmp-server location (vrf (NAME|management) |) LINE
```

---

## Configure tcp session enabled

Use this attribute to start the SNMP agent daemon over TCP

Attribute Name: tcp-session-enabled

Attribute Type: empty

## Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
<server>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
</global>
<config>
  </tcp-session-enabled><!-- operation="delete"-->
</config>
</global>
</server>
</servers>
</snmp>

```

## Command Syntax

```
snmp-server tcp-session (vrf (NAME|management) |)
```

---

## Configure disable default instance

Use this attribute to prevent default snmp instance from being enabled at start up

Attribute Name: disable-default-instance

Attribute Type: empty

### Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <default-instance>
      <config>
        </disable-default-instance><!-- operation="delete"-->
      </config>
    </default-instance>
  </servers>
</snmp>
```

### Command Syntax

```
snmp-server disable-default
```

---

## Configure ent ipi iftable

Use this attribute to enable separate logical/physical interface tables

Attribute Name: ent-ipi-iftable

Attribute Type: empty

### Netconf edit-config payload

```
<custom xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
  <config>
    </ent-ipi-iftable><!-- operation="delete"-->
  </config>
</custom>
```

### Command Syntax

```
snmp ent-ipi-iftable
```

---

## IPI-SNMP-SERVER-EXTENDED

---

### Configure include directive

Use this attribute to create and include extension directory for snmp-dir

Attribute Name: include-directive

Attribute Type: empty

**Netconf edit-config payload**

```
<snmp-dir xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
<config>
  </include-directive><!-- operation="delete"-->
</config>
</snmp-dir>
```

**Command Syntax**

```
snmp-server include-directive
```

---

**Configure enable**

Use this attribute to enable/disable SNMP server debugging

Attribute Name: enable

Attribute Type: empty

**Netconf edit-config payload**

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
  <debug xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
    <config>
      </enable><!-- operation="delete"-->
    </config>
  </debug>
</servers>
</snmp>
```

**Command Syntax**

```
debug snmp-server
```

---

**Configure filter type**

Use this attribute to update oid tree filter type for a view entry.

This command is supported when following feature are enabled SNMP-AGENT feature

Attribute Name: filter-type

Attribute Type: enum (included|excluded)

**Netconf edit-config payload**

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
  <server>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
  <snmp-views xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
```

```

<snmp-view>
  <view-name>VIEW-NAME</view-name>
  <config>
    <view-name>VIEW-NAME</view-name>
  </config>
  <oid-trees>
  <oid-tree>
    <oid>OID-TREE</oid>
    <config>
      <oid>OID-TREE</oid>
    </config>
    <filter-type>included</filter-type> <!-- operation="delete"-->
  </oid-tree>
</oid-trees>
</snmp-view>
</snmp-views>
</server>
</servers>
</snmp>

```

### Command Syntax

```
snmp-server view VIEW-NAME OID-TREE (included|excluded) (vrf (NAME|management)|)
```

---

## Configure engine id

Use this attribute to configure SNMPv3 engine ID.

This command is supported when following feature are enabled snmp version v3

Attribute Name: engine-id

Attribute Type: string

Attribute Range: 1-24

### Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <engine-id xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
  <config>
    <engine-id>ENGINE_ID_STR</engine-id> <!-- operation="delete"-->
  </config>
  </engine-id>
</snmp>

```

### Command Syntax

```
snmp-server engineID ENGINE_ID_STR
```

---

## Configure smux port enable

Use this attribute to enable smux-port.

Attribute Name: smux-port-enable

Attribute Type: empty

### Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <smux-port xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
        <config>
          </smux-port-enable><!-- operation="delete"-->
        </config>
      </smux-port>
    </server>
  </servers>
</snmp>
```

### Command Syntax

```
snmp-server smux-port-enable (vrf (NAME|management) |)
```

---

## Configure host name

Use this attribute to configure an SNMP trap host. An SNMP trap host is usually a network management station (NMS) or an SNMP manager.

Attribute Name: host-name

Attribute Type: string

Attribute Range: 1-63

Attribute Name: notification-type

Attribute Type: enum (traps|informs)

Attribute Name: snmp-version

Attribute Type: enum (1|2c|3)

Attribute Name: community

Attribute Type: string

Attribute Name: udp-port

Attribute Type: uint32

Attribute Range: 1-65535

### Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
```

```

<config>
  <vrf-name>NAME</vrf-name>
</config>
<hosts xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
<host>
  <host-name>A.B.C.D</host-name>
  <config>
    <host-name>A.B.C.D</host-name>
    <notification-type>traps</notification-type>
    <snmp-version>1</snmp-version>
    <community>WORD</community>
    <udp-port>1</udp-port>
  </config>
</host>
</hosts>
</server>
</servers>
</snmp>

```

## Command Syntax

```
snmp-server host (A.B.C.D|X:X::X:X|HOSTNAME) (traps) version (1|2c) WORD (udp-port
<1-65535>|) (vrf (NAME|management)|)
```

---

## Configure notification type

Use this attribute to configure an SNMP trap host. An SNMP trap host is usually a network management station (NMS) or an SNMP manager.

Attribute Name: host-name

Attribute Type: string

Attribute Range: 1-63

Attribute Name: notification-type

Attribute Type: enum (traps|informs)

Attribute Name: snmp-version

Attribute Type: enum (1|2c|3)

Attribute Name: snmpv3-auth-type

Attribute Type: enum (noauth|auth|priv)

Attribute Name: snmpv3-user

Attribute Type: string

Attribute Name: udp-port

Attribute Type: uint32

Attribute Range: 1-65535

## Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">

```

```

<server>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  <hosts xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
  <host>
    <host-name>A.B.C.D</host-name>
    <config>
      <host-name>A.B.C.D</host-name>
      <notification-type>traps</notification-type>
      <snmp-version>1</snmp-version>
      <snmpv3-auth-type>noauth</snmpv3-auth-type>
      <snmpv3-user>WORD</snmpv3-user>
      <udp-port>1</udp-port>
    </config>
  </host>
</hosts>
</server>
</servers>
</snmp>

```

## Command Syntax

```
snmp-server host (A.B.C.D|X:X::X:X|HOSTNAME) (traps) version (3) (noauth|auth|priv)
WORD (udp-port <1-65535>|) (vrf (NAME|management)|)
```

---

## Configure snmp version

Use this attribute to configure an SNMP trap host. An SNMP trap host is usually a network management station (NMS) or an SNMP manager.

Attribute Name: host-name

Attribute Type: string

Attribute Range: 1-63

Attribute Name: notification-type

Attribute Type: enum (traps|informs)

Attribute Name: snmp-version

Attribute Type: enum (1|2c|3)

Attribute Name: community

Attribute Type: string

Attribute Name: udp-port

Attribute Type: uint32

Attribute Range: 1-65535

## Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
```

```

<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
  <server>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
    <hosts xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
      <host>
        <host-name>A.B.C.D</host-name>
        <config>
          <host-name>A.B.C.D</host-name>
          <notification-type>traps</notification-type>
          <snmp-version>1</snmp-version>
          <community>WORD</community>
          <udp-port>1</udp-port>
        </config>
      </host>
    </hosts>
  </server>
</servers>
</snmp>

```

## Command Syntax

```

snmp-server host (A.B.C.D|X:X::X:X|HOSTNAME) (informs) version (2c) WORD (udp-port
<1-65535>|) (vrf (NAME|management)|)

```

---

## Configure snmpv3 auth type

Use this attribute to configure an SNMP trap host. An SNMP trap host is usually a network management station (NMS) or an SNMP manager.

Attribute Name: host-name

Attribute Type: string

Attribute Range: 1-63

Attribute Name: notification-type

Attribute Type: enum (traps|informs)

Attribute Name: snmp-version

Attribute Type: enum (1|2c|3)

Attribute Name: snmpv3-auth-type

Attribute Type: enum (noauth|auth|priv)

Attribute Name: snmpv3-user

Attribute Type: string

Attribute Name: udp-port

Attribute Type: uint32

Attribute Range: 1-65535

## Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
  <server>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
    <hosts xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
    <host>
      <host-name>A.B.C.D</host-name>
      <config>
        <host-name>A.B.C.D</host-name>
        <notification-type>traps</notification-type>
        <snmp-version>1</snmp-version>
        <snmpv3-auth-type>noauth</snmpv3-auth-type>
        <snmpv3-user>WORD</snmpv3-user>
        <udp-port>1</udp-port>
      </config>
    </host>
  </hosts>
</server>
</servers>
</snmp>
```

## Command Syntax

```
snmp-server host (A.B.C.D|X:X::X:X|HOSTNAME) (informs) version (3)
(noauth|auth|priv) WORD (udp-port <1-65535>|) (vrf (NAME|management)|)
```

---

## Configure community

Use this attribute to configure an SNMP trap host. An SNMP trap host is usually a network management station (NMS) or an SNMP manager.

Attribute Name: host-name

Attribute Type: string

Attribute Range: 1-63

Attribute Name: snmp-version

Attribute Type: enum (1|2c|3)

Attribute Name: community

Attribute Type: string

Attribute Name: udp-port

Attribute Type: uint32

Attribute Range: 1-65535

## Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
```

```

<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
  <server>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
    <hosts xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
      <host>
        <host-name>A.B.C.D</host-name>
        <config>
          <host-name>A.B.C.D</host-name>
          <snmp-version>1</snmp-version>
          <community>WORD</community>
          <udp-port>1</udp-port>
        </config>
      </host>
    </hosts>
  </server>
</servers>
</snmp>

```

## Command Syntax

```
snmp-server host (A.B.C.D|X:X::X:X|HOSTNAME) version (1|2c) WORD (udp-port <1-65535>|) (vrf (NAME|management)|)
```

---

## Configure snmpv3 user

Use this attribute to configure an SNMP trap host. An SNMP trap host is usually a network management station (NMS) or an SNMP manager.

Attribute Name: host-name

Attribute Type: string

Attribute Range: 1-63

Attribute Name: snmp-version

Attribute Type: enum (1|2c|3)

Attribute Name: snmpv3-auth-type

Attribute Type: enum (noauth|auth|priv)

Attribute Name: snmpv3-user

Attribute Type: string

Attribute Name: udp-port

Attribute Type: uint32

Attribute Range: 1-65535

## Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">

```

```

<server>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>NAME</vrf-name>
  </config>
  <hosts xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
  <host>
    <host-name>A.B.C.D</host-name>
    <config>
      <host-name>A.B.C.D</host-name>
      <snmp-version>1</snmp-version>
      <snmpv3-auth-type>noauth</snmpv3-auth-type>
      <snmpv3-user>WORD</snmpv3-user>
      <udp-port>1</udp-port>
    </config>
  </host>
</hosts>
</server>
</servers>
</snmp>

```

## Command Syntax

```
snmp-server host (A.B.C.D|X:X::X:X|HOSTNAME) version (3) (noauth|auth|priv) WORD
(udp-port <1-65535>|) (vrf (NAME|management)|)
```

## Configure udp port

Use this attribute to specify the port to be used when SNMP sends packets to host. The default is 162.

This command is supported when following feature are enabled SNMP-AGENT feature

Attribute Name: udp-port

Attribute Type: uint32

Attribute Range: 1-65535

Attribute Name: host-user

Attribute Type: string

## Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <hosts xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
      <host>
        <host-name>A.B.C.D</host-name>
        <config>
          <host-name>A.B.C.D</host-name>

```

```

        <host-user>WORD</host-user> <!-- operation="delete"-->
    </config>
    <udp-port>1</udp-port> <!-- operation="delete"-->
</host>
</hosts>
</server>
</servers>
</snmp>

```

## Command Syntax

```
snmp-server host (A.B.C.D|X:X::X:X|HOSTNAME) WORD (udp-port <1-65535>|) (vrf
(NAME|management) |)
```

---

## Configure user name

Use this attribute to create an SNMP server user.

Attribute Name: user-name

Attribute Type: string

Attribute Range: 5-32

Attribute Name: authentication-type

Attribute Type: enum (md5|sha)

Attribute Name: encryption-type

Attribute Type: enum (plain|encrypt)

Attribute Name: authentication-password

Attribute Type: string

## Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
  <server>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
    <users xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
      <user> <!-- operation="delete"-->
        <user-name>WORD</user-name>
        <config>
          <user-name>WORD</user-name>
          <authentication-type>md5</authentication-type>
          <encryption-type>1</encryption-type>
          <authentication-password>AUTH-PASSWORD</authentication-password>
        </config>
      </user>
    </users>
  </server>

```

```
</servers>
</snmp>
```

## Command Syntax

```
snmp-server user WORD auth (md5|sha) encrypt AUTH-PASSWORD (vrf (NAME|management) |)
```

---

## Configure authentication type

Use this attribute to create an SNMP server user.

Attribute Name: user-name

Attribute Type: string

Attribute Range: 5-32

Attribute Name: authentication-type

Attribute Type: enum (md5|sha)

Attribute Name: encryption-type

Attribute Type: enum (plain|encrypt)

Attribute Name: authentication-password

Attribute Type: string

## Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snm">
<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snm-server">
  <server>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
    <users xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snm-server-extended">
      <user <!-- operation="delete"-->
        <user-name>WORD</user-name>
        <config>
          <user-name>WORD</user-name>
          <authentication-type>md5</authentication-type>
          <encryption-type>0</encryption-type>
          <authentication-password>AUTH-PASSWORD</authentication-password>
        </config>
      </user>
    </users>
  </server>
</servers>
</snmp>
```

## Command Syntax

```
snmp-server user WORD auth (md5|sha) AUTH-PASSWORD (vrf (NAME|management) |)
```

---

## Configure user type

Use this attribute to create an SNMP server user.

Attribute Name: user-name

Attribute Type: string

Attribute Range: 5-32

Attribute Name: user-type

Attribute Type: union

Attribute Name: authentication-type

Attribute Type: enum (md5|sha)

Attribute Name: encryption-type

Attribute Type: enum (plain|encrypt)

Attribute Name: authentication-password

Attribute Type: string

## Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmplib">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmplib-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <users xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmplib-server-extended">
        <user> <!-- operation="delete"-->
          <user-name>WORD</user-name>
          <config>
            <user-name>WORD</user-name>
            <user-type>network-operator</user-type>
            <authentication-type>md5</authentication-type>
            <encryption-type>1</encryption-type>
            <authentication-password>AUTH-PASSWORD</authentication-password>
          </config>
        </user>
      </users>
    </server>
  </servers>
</snmp>
```

## Command Syntax

```
snmp-server user WORD (network-operator|network-admin|WORD) auth (md5|sha) encrypt
AUTH-PASSWORD (vrf (NAME|management) |)
```

---

## Configure encryption type

Use this attribute to create an SNMP server user.

Attribute Name: user-name

Attribute Type: string

Attribute Range: 5-32

Attribute Name: user-type

Attribute Type: union

Attribute Name: authentication-type

Attribute Type: enum (md5|sha)

Attribute Name: encryption-type

Attribute Type: enum (plain|encrypt)

Attribute Name: authentication-password

Attribute Type: string

### Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snm">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snm-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <users xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snm-server-extended">
        <user> <!-- operation="delete"-->
          <user-name>WORD</user-name>
          <config>
            <user-name>WORD</user-name>
            <user-type>network-operator</user-type>
            <authentication-type>md5</authentication-type>
            <encryption-type>0</encryption-type>
            <authentication-password>AUTH-PASSWORD</authentication-password>
          </config>
        </user>
      </users>
    </server>
  </servers>
</snmp>
```

### Command Syntax

```
snmp-server user WORD (network-operator|network-admin|WORD) auth (md5|sha) AUTH-
  PASSWORD (vrf (NAME|management)|)
```

---

## Configure authentication password

Use this attribute to create an SNMP server user.

Attribute Name: user-name

Attribute Type: string

Attribute Range: 5-32

Attribute Name: authentication-type

Attribute Type: enum (md5|sha)

Attribute Name: encryption-type

Attribute Type: enum (plain|encrypt)

Attribute Name: authentication-password

Attribute Type: string

Attribute Name: privilege-type

Attribute Type: enum (des|aes)

Attribute Name: privilege-password

Attribute Type: string

### Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <users xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
        <user <!-- operation="delete"-->
          <user-name>WORD</user-name>
          <config>
            <user-name>WORD</user-name>
            <authentication-type>md5</authentication-type>
            <encryption-type>l</encryption-type>
            <authentication-password>AUTH-PASSWORD</authentication-password>
            <privilege-type>des</privilege-type>
            <privilege-password>PRIV-PASSWORD</privilege-password>
          </config>
        </user>
      </users>
    </server>
  </servers>
</snmp>
```

### Command Syntax

```
snmp-server user WORD auth (md5|sha) encrypt AUTH-PASSWORD priv (des|aes) PRIV-
PASSWORD (vrf (NAME|management)|)
```

---

## Configure privilege type

Use this attribute to create an SNMP server user.

Attribute Name: user-name

Attribute Type: string

Attribute Range: 5-32

Attribute Name: authentication-type

Attribute Type: enum (md5|sha)

Attribute Name: encryption-type

Attribute Type: enum (plain|encrypt)

Attribute Name: authentication-password

Attribute Type: string

Attribute Name: privilege-type

Attribute Type: enum (des|aes)

Attribute Name: privilege-password

Attribute Type: string

## Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <users xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
        <user <!-- operation="delete"-->
          <user-name>WORD</user-name>
          <config>
            <user-name>WORD</user-name>
            <authentication-type>md5</authentication-type>
            <encryption-type>0</encryption-type>
            <authentication-password>AUTH-PASSWORD</authentication-password>
            <privilege-type>des</privilege-type>
            <privilege-password>PRIV-PASSWORD</privilege-password>
          </config>
        </user>
      </users>
    </server>
  </servers>
</snmp>
```

## Command Syntax

```
snmp-server user WORD auth (md5|sha) AUTH-PASSWORD priv (des|aes) PRIV-PASSWORD
(vrf (NAME|management) |)
```

---

## Configure privilege password

Use this attribute to create an SNMP server user.

Attribute Name: user-name

Attribute Type: string

Attribute Range: 5-32

Attribute Name: user-type

Attribute Type: union

Attribute Name: authentication-type

Attribute Type: enum (md5|sha)

Attribute Name: encryption-type

Attribute Type: enum (plain|encrypt)

Attribute Name: authentication-password

Attribute Type: string

Attribute Name: privilege-type

Attribute Type: enum (des|aes)

Attribute Name: privilege-password

Attribute Type: string

## Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <users xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
        <user> <!-- operation="delete"-->
          <user-name>WORD</user-name>
          <config>
            <user-name>WORD</user-name>
            <user-type>network-operator</user-type>
            <authentication-type>md5</authentication-type>
            <encryption-type>1</encryption-type>
            <authentication-password>AUTH-PASSWORD</authentication-password>
            <privilege-type>des</privilege-type>
            <privilege-password>PRIV-PASSWORD</privilege-password>
          </config>
        </user>
      </users>
    </server>
  </servers>
</snmp>
```

## Command Syntax

```
snmp-server user WORD (network-operator|network-admin|WORD) auth (md5|sha) encrypt
AUTH-PASSWORD priv (des|aes) PRIV-PASSWORD (vrf (NAME|management) |)
```

---

## Configure vrf name

Use this attribute to create an SNMP server user.

Attribute Name: user-name

Attribute Type: string

Attribute Range: 5-32

Attribute Name: user-type

Attribute Type: union

Attribute Name: authentication-type

Attribute Type: enum (md5|sha)

Attribute Name: encryption-type

Attribute Type: enum (plain|encrypt)

Attribute Name: authentication-password

Attribute Type: string

Attribute Name: privilege-type

Attribute Type: enum (des|aes)

Attribute Name: privilege-password

Attribute Type: string

## Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <users xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
        <user> <!-- operation="delete"-->
          <user-name>WORD</user-name>
          <config>
            <user-name>WORD</user-name>
            <user-type>network-operator</user-type>
            <authentication-type>md5</authentication-type>
            <encryption-type>0</encryption-type>
            <authentication-password>AUTH-PASSWORD</authentication-password>
            <privilege-type>des</privilege-type>
            <privilege-password>PRIV-PASSWORD</privilege-password>
          </config>
        </user>
      </users>
    </server>
  </servers>
</snmp>
```

```

    </users>
  </server>
</servers>
</snmp>

```

## Command Syntax

```
snmp-server user WORD (network-operator|network-admin|WORD) auth (md5|sha) AUTH-
PASSWORD priv (des|aes) PRIV-PASSWORD (vrf (NAME|management)|)
```

---

## Configure user user-name

Use this attribute to create an SNMP server user.

This command is supported when following feature are enabled SNMP-AGENT feature,snmp version v3

Attribute Name: user-name

Attribute Type: string

Attribute Range: 5-32

## Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <users xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
        <user>
          <user-name>WORD</user-name>
          <config>
            <user-name>WORD</user-name>
          </config>
        </user>
      </users>
    </server>
  </servers>
</snmp>

```

## Command Syntax

```
snmp-server user WORD (vrf (NAME|management)|)
```

---

## Configure user user-type

Use this attribute to create an SNMP server user of specified type.

This command is supported when following feature are enabled SNMP-AGENT feature,snmp version v3

Attribute Name: user-type

Attribute Type: union

## Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
  <server>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
    <users xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
    <user>
      <user-name>WORD</user-name>
      <config>
        <user-name>WORD</user-name>
      </config>
      <user-type>network-operator</user-type> <!-- operation="delete"-->
    </user>
  </users>
</server>
</servers>
</snmp>

```

## Command Syntax

```
snmp-server user WORD (network-operator|network-admin|WORD) (vrf
(NAME|management) |)
```

---

## Configure context name

Use this attribute to create an SNMP server context

Attribute Name: context-name

Attribute Type: string

Attribute Range: 1-32

## Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
  <server>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
    <contexts xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-
extended">
    <context>
      <context-name>WORD</context-name>
      <config>
        <context-name>WORD</context-name>
      </config>
    </context>
  </contexts>

```

```

</server>
</servers>
</snmp>

```

## Command Syntax

```
snmp-server context WORD (vrf (NAME|management) |)
```

---

## Configure acl name

Use this attribute to create an SNMP community string and user-acl.

This command is supported when following feature are enabled SNMP-AGENT feature

Attribute Name: acl-name

Attribute Type: string

## Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <communities xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
        <community>
          <community-name>WORD</community-name>
          <config>
            <community-name>WORD</community-name>
          </config>
          <acl-name>WORD</acl-name> <!-- operation="delete"-->
        </community>
      </communities>
    </server>
  </servers>
</snmp>

```

## Command Syntax

```
snmp-server community WORD use-acl WORD (vrf (NAME|management) |)
```

---

## Configure community name

Use this attribute to create an SNMP community string and access privileges.

This command is supported when following feature are enabled SNMP-AGENT feature

Attribute Name: community-name

Attribute Type: string

Attribute Range: 1-32

**Netconf edit-config payload**

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <communities xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
        <community>
          <community-name>WORD</community-name>
          <config>
            <community-name>WORD</community-name>
          </config>
        </community>
      </communities>
    </server>
  </servers>
</snmp>

```

**Command Syntax**

```
snmp-server community WORD (vrf (NAME|management) |)
```

**Configure snmp group**

Use this attribute to create an SNMP community string with group.

This command is supported when following feature are enabled SNMP-AGENT feature

Attribute Name: snmp-group

Attribute Type: enum (network-operator|network-admin)

**Netconf edit-config payload**

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <communities xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
        <community>
          <community-name>WORD</community-name>
          <config>
            <community-name>WORD</community-name>
            <snmp-group>network-operator</snmp-group> <!-- operation="delete" -->
          </config>
        </community>
      </communities>
    </server>
  </servers>
</snmp>

```

```

</server>
</servers>
</snmp>

```

## Command Syntax

```
snmp-server community WORD group (network-operator|network-admin) (vrf
(NAME|management) |)
```

---

## Configure access privileges

Use this attribute to create an SNMP community string and access privileges.

This command is supported when following feature are enabled SNMP-AGENT feature

Attribute Name: access-privileges

Attribute Type: enum (ro)

## Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <communities xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-
extended">
        <community>
          <community-name>WORD</community-name>
          <config>
            <community-name>WORD</community-name>
          </config>
          <access-privileges>ro</access-privileges> <!-- operation="delete"-->
        </community>
      </communities>
    </server>
  </servers>
</snmp>

```

## Command Syntax

```
snmp-server community WORD (ro) (vrf (NAME|management) |)
```

---

## Configure access

Use this attribute to set access privileges to this community view.

This command is supported when following feature are enabled SNMP-AGENT feature

Attribute Name: access

Attribute Type: enum (ro)

Attribute Name: community-view-name

Attribute Type: string

Attribute Name: version

Attribute Type: enum (v1|v2c)

### Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <communities xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
        <community>
          <community-name>WORD</community-name>
          <config>
            <community-name>WORD</community-name>
            <community-view-name>VIEW-NAME</community-view-name> <!--
operation="delete"-->
            <version>v1</version> <!-- operation="delete"-->
          </config>
          <access>ro</access> <!-- operation="delete"-->
        </community>
      </communities>
    </server>
  </servers>
</snmp>
```

### Command Syntax

```
snmp-server community WORD view VIEW-NAME version (v1|v2c) (ro) (vrf
(NAME|management) |)
```

---

## Configure community context

Use this attribute to create an SNMP community string and access privileges.

Attribute Name: community-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: community-context

Attribute Type: string

Attribute Range: 1-32

Attribute Name: community-user

Attribute Type: string

## Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
  <server>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>
    <communities xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
      <community>
        <community-name>WORD</community-name>
        <config>
          <community-name>WORD</community-name>
        </config>
        <community-context-mapping>
          <config>
            <community-context>WORD</community-context>
            <community-user>WORD</community-user>
          </config>
        </community-context-mapping>
      </community>
    </communities>
  </server>
</servers>
</snmp>

```

## Command Syntax

```
snmp-server community-map WORD context WORD user WORD (vrf (NAME|management)|)
```

---

## Configure group name

Use this attribute to create an SNMP group string.

Attribute Name: group-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: group-version

Attribute Type: enum (1|2c|3)

## Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
<servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
  <server>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>NAME</vrf-name>
    </config>

```

```

    <server-groups xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
      <server-group>
        <group-name>WORD</group-name>
        <config>
          <group-name>WORD</group-name>
          <group-version>1</group-version>
        </config>
      </server-group>
    </server-groups>
  </server>
</servers>
</snmp>

```

## Command Syntax

```
snmp-server group WORD version (1|2c) (vrf (NAME|management) |)
```

---

## Configure group version

Use this attribute to create an SNMP group string.

Attribute Name: group-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: group-version

Attribute Type: enum (1|2c|3)

Attribute Name: snmpv3-group-auth-type

Attribute Type: enum (auth|priv|noauth)

## Netconf edit-config payload

```

<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
    <server-groups xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
      <server-group>
        <group-name>WORD</group-name>
        <config>
          <group-name>WORD</group-name>
          <group-version>1</group-version>
          <snmpv3-group-auth-type>auth</snmpv3-group-auth-type>
        </config>
      </server-group>
    </server-groups>
  </server>

```

```
</servers>
</snmp>
```

## Command Syntax

```
snmp-server group WORD version (3) (auth|priv|noauth) (vrf (NAME|management)|)
```

---

## Configure context

Use this attribute to create an SNMP group string.

Attribute Name: group-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: group-version

Attribute Type: enum (1|2c|3)

Attribute Name: context

Attribute Type: union

Attribute Range: 1-32

## Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <server-groups xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
        <server-group>
          <group-name>WORD</group-name>
          <config>
            <group-name>WORD</group-name>
            <group-version>1</group-version>
            <context>1</context>
          </config>
        </server-group>
      </server-groups>
    </server>
  </servers>
</snmp>
```

## Command Syntax

```
snmp-server group WORD version (1|2c) context (all|WORD) (vrf (NAME|management)|)
```

---

## Configure snmpv3 group auth type

Use this attribute to create an SNMP group string.

Attribute Name: group-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: group-version

Attribute Type: enum (1|2|3)

Attribute Name: snmpv3-group-auth-type

Attribute Type: enum (auth|priv|noauth)

Attribute Name: context

Attribute Type: enum (all)

Attribute Range: 1-32

### Netconf edit-config payload

```
<snmp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp">
  <servers xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server">
    <server>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>NAME</vrf-name>
      </config>
      <server-groups xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmp-server-extended">
        <server-group>
          <group-name>WORD</group-name>
          <config>
            <group-name>WORD</group-name>
            <group-version>1</group-version>
            <snmpv3-group-auth-type>auth</snmpv3-group-auth-type>
            <context>1</context>
          </config>
        </server-group>
      </server-groups>
    </server>
  </servers>
</snmp>
```

### Command Syntax

```
snmp-server group WORD version (3) (auth|priv|noauth) context <1-32> (all) (vrf
(NAME|management) |)
```

---

## debug snmp-server

### Netconf RPC payload

```
<snmp-server-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
snmp-server-extended"/>
```

---

## Command Syntax

```
debug snmp-server
```

---

## no debug snmp-server

### Netconf RPC payload

```
<snmp-server-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-snmpp-server-extended"/>
```

## Command Syntax

```
no debug snmp-server
```

---

# IPI-QOS

---

## Configure enable qos

Use this attribute to globally enable or disable QoS

Attribute Name: enable-qos

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <config>
      <enable-qos>disable</enable-qos> <!-- operation="delete"-->
    </config>
  </global>
</qos>
```

## Command Syntax

```
qos (disable|enable)
```

---

## Configure name

Use this attribute to set a name to CoS to Traffic-Class profile

This command is supported when following feature are enabled QoS Mapping Profile feature

Attribute Name: name

Attribute Type: string

Attribute Range: 1-31

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <map-profile>
```

```

<cos-to-queue-profiles>
<cos-to-queue-profile> <!-- operation="delete"-->
  <name>NAME</name>
  <config>
    <name>WORD</name>
  </config>
</cos-to-queue-profile>
</cos-to-queue-profiles>
</map-profile>
</global>
</qos>

```

## Command Syntax

```
qos profile cos-to-queue (NAME|default)
```

---

## Configure color

Use this attribute to select the color CoS DEI is mapped to.

This command is supported when following feature are enabled QoS Mapping Profile feature and following feature are disabled QoS custom options2

Attribute Name: color

Attribute Type: enum (green|yellow|red)

Attribute Name: queue-id

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<map-profile>
<cos-to-queue-profiles>
<cos-to-queue-profile>
  <name>NAME</name>
  <config>
    <name>WORD</name>
  </config>
<cos-dei-to-queues>
<cos-dei-to-queue>
  <dei-value>all</dei-value>
  <config>
    <dei-value>all</dei-value>
    <cos-value>0</cos-value>
    <queue-id>0</queue-id> <!-- operation="delete"-->
  </config>
    <cos-value>0</cos-value>
    <color>green</color> <!-- operation="delete"-->
</cos-dei-to-queue>
</cos-dei-to-queues>

```

```

</cos-to-queue-profile>
</cos-to-queue-profiles>
</map-profile>
</global>
</qos>

```

### Command Syntax

```
cos <0-7> (dei (0|1|all)|) queue <0-7> (color (green|yellow|red)|)
```

---

## Configure dscp-to-queue-profiles name

Use this attribute to set a name to DSCP to Traffic-Class profile

This command is supported when following feature are enabled QoS Mapping Profile feature

Attribute Name: name

Attribute Type: string

Attribute Range: 1-31

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<map-profile>
<dscp-to-queue-profiles>
<dscp-to-queue-profile> <!-- operation="delete"-->
  <name>NAME</name>
  <config>
    <name>WORD</name>
  </config>
</dscp-to-queue-profile>
</dscp-to-queue-profiles>
</map-profile>
</global>
</qos>

```

### Command Syntax

```
qos profile dscp-to-queue (NAME|default)
```

---

## Configure dscp value

Use this attribute to select the color to map.

This command is supported when following feature are enabled QoS Mapping Profile feature

Attribute Name: color

Attribute Type: enum (green|yellow|red)

Attribute Name: queue-id

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<map-profile>
<dscp-to-queue-profiles>
<dscp-to-queue-profile>
  <name>NAME</name>
  <config>
    <name>WORD</name>
  </config>
</dscp-to-queue-profiles>
<dscp-to-queues>
<dscp-to-queue>
  <dscp-value>0</dscp-value>
  <config>
    <dscp-value>0</dscp-value>
    <queue-id>0</queue-id> <!-- operation="delete"-->
  </config>
  <color>green</color> <!-- operation="delete"-->
</dscp-to-queue>
</dscp-to-queues>
</dscp-to-queue-profile>
</dscp-to-queue-profiles>
</map-profile>
</global>
</qos>

```

## Command Syntax

```
dscp <0-63> queue <0-7> color (green|yellow|red)
```

---

## Configure queue id

Use this attribute to select the Traffic-Class DSCP is mapped to

This command is supported when following feature are enabled QoS Mapping Profile feature

Attribute Name: queue-id

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<map-profile>
<dscp-to-queue-profiles>
<dscp-to-queue-profile>
  <name>NAME</name>
  <config>
    <name>WORD</name>
  </config>
</dscp-to-queue-profiles>

```

```

<dscp-to-queue>
  <dscp-value>0</dscp-value>
  <config>
    <dscp-value>0</dscp-value>
  </config>
  <queue-id>0</queue-id> <!-- operation="delete"-->
</dscp-to-queue>
</dscp-to-queues>
</dscp-to-queue-profile>
</dscp-to-queue-profiles>
</map-profile>
</global>
</qos>

```

### Command Syntax

```
dscp <0-63> queue <0-7>
```

---

## Configure queue-color-to-cos-profiles name

Use this attribute to select the Traffic-Class color to CoS profile name

This command is supported when following feature are enabled QoS Mapping Profile feature

Attribute Name: name

Attribute Type: string

Attribute Range: 1-31

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <map-profile>
      <queue-color-to-cos-profiles>
        <queue-color-to-cos-profile> <!-- operation="delete"-->
          <name>NAME</name>
        <config>
          <name>WORD</name>
        </config>
      </queue-color-to-cos-profile>
    </queue-color-to-cos-profiles>
  </map-profile>
</global>
</qos>

```

### Command Syntax

```
qos profile queue-color-to-cos (NAME|default)
```

---

## Configure cos value

Use this attribute to select the color to map. Default value is 3.

This command is supported when following feature are enabled QoS Mapping Profile feature

Attribute Name: color

Attribute Type: enum (green|yellow|red|all)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <map-profile>
      <queue-color-to-cos-profiles>
        <queue-color-to-cos-profile>
          <name>NAME</name>
          <config>
            <name>WORD</name>
          </config>
        <queue-color-to-coses>
          <queue-color-to-cos> <!-- operation="delete"-->
            <color>all</color>
            <config>
              <color>all</color>
              <queue-id>0</queue-id>
              <cos-value>0</cos-value>
            </config>
            <queue-id>0</queue-id>
          </queue-color-to-cos>
        </queue-color-to-coses>
      </queue-color-to-cos-profile>
    </queue-color-to-cos-profiles>
  </map-profile>
</global>
</qos>
```

### Command Syntax

```
queue <0-7> (color (green|yellow|red|all)|) cos <0-7>
```

---

## Configure queue-to-precedence-profiles name

Use this attribute to select the Traffic-Class to Precedence profile name

This command is supported when following feature are enabled QoS Mapping Profile feature

Attribute Name: name

Attribute Type: string

Attribute Range: 1-31

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
```

```

<map-profile>
<queue-to-precedence-profiles>
<queue-to-precedence-profile> <!-- operation="delete"-->
  <name>NAME</name>
  <config>
    <name>WORD</name>
  </config>
</queue-to-precedence-profile>
</queue-to-precedence-profiles>
</map-profile>
</global>
</qos>

```

## Command Syntax

```
qos profile queue-to-precedence NAME
```

---

## Configure precedence value

Use this attribute to select the Traffic-Class to map

This command is supported when following feature are enabled QoS Mapping Profile feature

Attribute Name: queue-id

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: precedence-value

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<map-profile>
<queue-to-precedence-profiles>
<queue-to-precedence-profile>
  <name>NAME</name>
  <config>
    <name>WORD</name>
  </config>
<queue-to-precedences>
<queue-to-precedence> <!-- operation="delete"-->
  <queue-id>0</queue-id>
  <config>
    <queue-id>0</queue-id>
    <precedence-value>0</precedence-value>
  </config>
</queue-to-precedence>
</queue-to-precedences>
</queue-to-precedence-profile>

```

```
</queue-to-precedence-profiles>  
</map-profile>  
</global>  
</qos>
```

## Command Syntax

```
queue <0-7> precedence <0-7>
```

---

## Configure precedence-to-queue-profiles name

Use this attribute to set a name to Precedence to Traffic-Class profile

This command is supported when following feature are enabled QoS Mapping Profile feature

Attribute Name: name

Attribute Type: string

Attribute Range: 1-31

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">  
<global>  
<map-profile>  
<precedence-to-queue-profiles>  
<precedence-to-queue-profile> <!-- operation="delete"-->  
  <name>NAME</name>  
  <config>  
    <name>WORD</name>  
  </config>  
</precedence-to-queue-profile>  
</precedence-to-queue-profiles>  
</map-profile>  
</global>  
</qos>
```

## Command Syntax

```
qos profile precedence-to-queue NAME
```

---

## Configure precedence-to-queue queue-id

Use this attribute to select the Traffic-Class IP Precedence is mapped to

This command is supported when following feature are enabled QoS Mapping Profile feature

Attribute Name: queue-id

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">  
<global>
```

```

<map-profile>
<precedence-to-queue-profiles>
<precedence-to-queue-profile>
  <name>NAME</name>
  <config>
    <name>WORD</name>
  </config>
</precedence-to-queue-profiles>
<precedence-to-queue>
  <precedence-value>0</precedence-value>
  <config>
    <precedence-value>0</precedence-value>
  </config>
  <queue-id>0</queue-id> <!-- operation="delete"-->
</precedence-to-queue>
</precedence-to-queue-profiles>
</precedence-to-queue-profile>
</map-profile>
</global>
</qos>

```

### Command Syntax

```
precedence <0-7> queue <0-7>
```

---

## Configure queue-color-to-dscp-profiles name

Use this attribute to select the Traffic-Class color to DSCP profile name

This command is supported when following feature are enabled QoS Mapping Profile feature

Attribute Name: name

Attribute Type: string

Attribute Range: 1-31

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<map-profile>
<queue-color-to-dscp-profiles>
<queue-color-to-dscp-profile> <!-- operation="delete"-->
  <name>NAME</name>
  <config>
    <name>WORD</name>
  </config>
</queue-color-to-dscp-profile>
</queue-color-to-dscp-profiles>
</map-profile>
</global>
</qos>

```

## Command Syntax

```
qos profile queue-color-to-dscp (NAME|default)
```

---

## Configure queue-color-to-dscps color

Use this attribute to select the color to map. Default value is 3.

This command is supported when following feature are enabled QoS Mapping Profile feature

Attribute Name: color

Attribute Type: enum (green|yellow|red|all)

Attribute Name: dscp-value

Attribute Type: uint8

Attribute Range: 0-63

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <map-profile>
      <queue-color-to-dscp-profiles>
        <queue-color-to-dscp-profile>
          <name>NAME</name>
          <config>
            <name>WORD</name>
          </config>
        <queue-color-to-dscps>
          <queue-color-to-dscp> <!-- operation="delete"-->
            <color>all</color>
            <config>
              <color>all</color>
              <queue-id>0</queue-id>
              <dscp-value>0</dscp-value>
            </config>
            <queue-id>0</queue-id>
          </queue-color-to-dscp>
        </queue-color-to-dscps>
      </queue-color-to-dscp-profile>
    </queue-color-to-dscp-profiles>
  </map-profile>
</global>
</qos>
```

## Command Syntax

```
queue <0-7> (color (green|yellow|red|all) |) dscp <0-63>
```

---

## Configure cos

Use this command to enable remarking of CoS set by the egress map

Attribute Name: cos

Attribute Type: empty

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <remark>
      <config>
        </cos><!-- operation="delete"-->
      </config>
    </remark>
  </global>
</qos>
```

### Command Syntax

```
qos remark cos
```

---

## Configure dei

Use this command to enable remarking of DEI set by the egress map

Attribute Name: dei

Attribute Type: empty

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <remark>
      <config>
        </dei><!-- operation="delete"-->
      </config>
    </remark>
  </global>
</qos>
```

### Command Syntax

```
qos remark dei
```

---

## Configure dscp

Use this command to enable remarking of DSCP set by the egress map

Attribute Name: dscp

Attribute Type: empty

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <remark>
```

```
<config>
  </dscp><!-- operation="delete"-->
</config>
</remark>
</global>
</qos>
```

### Command Syntax

```
qos remark dscp
```

---

## Configure type

Use this attribute to set the class-map name

Attribute Name: name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing-default|vlan-queuing)

Attribute Name: match-criteria

Attribute Type: enum (match-all|match-any)

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<class-maps>
<class-map <!-- operation="delete"-->
  <name>NAME</name>
  <config>
    <name>NAME</name>
    <type>1</type>
    <match-criteria>1</match-criteria>
  </config>
</class-map>
</class-maps>
</global>
</qos>
```

### Command Syntax

```
class-map NAME
```

---

## Configure match criteria

Use this attribute to set the class-map name

Attribute Name: name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing-default|vlan-queuing)

Attribute Name: match-criteria

Attribute Type: enum (match-all|match-any)

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map <!-- operation="delete"-->
        <name>NAME</name>
        <config>
          <name>NAME</name>
          <type>qos</type>
          <match-criteria>1</match-criteria>
        </config>
      </class-map>
    </class-maps>
  </global>
</qos>
```

### Command Syntax

```
class-map type (qos) NAME
```

---

## Configure class-maps name

Use this attribute to set the class-map name

Attribute Name: name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing-default|vlan-queuing)

Attribute Name: match-criteria

Attribute Type: enum (match-all|match-any)

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map <!-- operation="delete"-->
        <name>NAME</name>
        <config>
          <name>NAME</name>
          <type>qos</type>
          <match-criteria>match-all</match-criteria>
        </config>
      </class-map>
    </class-maps>
  </global>
</qos>
```

```
</class-map>  
</class-maps>  
</global>  
</qos>
```

## Command Syntax

```
class-map type (qos) (match-all) NAME
```

---

## Configure class-maps name

Use this attribute to set the class-map name

Attribute Name: name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing-default|vlan-queuing)

Attribute Name: match-criteria

Attribute Type: enum (match-all|match-any)

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">  
<global>  
<class-maps>  
<class-map <!-- operation="delete"-->  
  <name>NAME</name>  
  <config>  
    <name>NAME</name>  
    <type>qos</type>  
    <match-criteria>match-all</match-criteria>  
  </config>  
</class-map>  
</class-maps>  
</global>  
</qos>
```

## Command Syntax

```
class-map type (qos) (match-any) NAME
```

---

## Configure class-maps name

Use this attribute to set the class-map name

Attribute Name: name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing-default|vlan-queuing)

Attribute Name: match-criteria

Attribute Type: enum (match-all|match-any)

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <class-maps>
  <class-map <!-- operation="delete"-->
    <name>NAME</name>
    <config>
      <name>NAME</name>
      <type>1</type>
      <match-criteria>match-all</match-criteria>
    </config>
  </class-map>
</class-maps>
</global>
</qos>
```

### Command Syntax

```
class-map (match-any) NAME
```

---

## Configure class-maps name

Use this attribute to set the class-map name

Attribute Name: name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing-default|vlan-queuing)

Attribute Name: match-criteria

Attribute Type: enum (match-all|match-any)

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <class-maps>
  <class-map <!-- operation="delete"-->
    <name>NAME</name>
    <config>
      <name>NAME</name>
      <type>1</type>
      <match-criteria>match-all</match-criteria>
    </config>
  </class-map>
```

```
</class-maps>  
</global>  
</qos>
```

## Command Syntax

```
class-map (match-all) NAME
```

---

## Configure reference description

This attribute configures reference description message on class-map profile for QoS type.

Attribute Name: reference-description

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">  
<global>  
<class-maps>  
<class-map>  
  <name>NAME</name>  
  <config>  
    <name>NAME</name>  
  </config>  
  <reference-description>LINE</reference-description> <!-- operation="delete"-->  
</class-map>  
</class-maps>  
</global>  
</qos>
```

## Command Syntax

```
reference-description LINE
```

---

## Configure access control list name

Use this attribute to classify traffic based on the Access Control List (ACL)

Attribute Name: access-control-list-name

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">  
<global>  
<class-maps>  
<class-map>  
  <name>NAME</name>  
  <config>  
    <name>NAME</name>
```

```

    </config>
  <match-any-conditions>
    <config>
      <access-control-list-name>NAME</access-control-list-name> <!--
operation="delete"-->
    </config>
  </match-any-conditions>
</class-map>
</class-maps>
</global>
</qos>

```

### Command Syntax

```
match access-group NAME
```

---

## Configure ethertype

Use this attribute to classify traffic based on the EtherType value(s)

Attribute Name: ethertype

Attribute Type: string

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
      <match-any-conditions>
        <config>
          <ethertype>WORD</ethertype> <!-- operation="delete"-->
        </config>
      </match-any-conditions>
    </class-map>
  </class-maps>
</global>
</qos>

```

### Command Syntax

```
match ethertype WORD
```

---

## Configure traffic type

Use this attribute to classify traffic based on the traffic type value

Attribute Name: traffic-type

Attribute Type: enum (I2-uc|I2-uc-unknown|default)

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <class-maps>
  <class-map>
    <name>NAME</name>
    <config>
      <name>NAME</name>
    </config>
  <match-any-conditions>
  <config>
    <traffic-type>l2-uc</traffic-type> <!-- operation="delete"-->
  </config>
</match-any-conditions>
</class-map>
</class-maps>
</global>
</qos>

```

## Command Syntax

```
match traffic-type (l2-uc|l2-uc-unknown|default)
```

---

## Configure match-any-conditions cos

Use this attribute to classify traffic based on the Class of Service (CoS) value

Attribute Name: cos

Attribute Type: string

Attribute Range: 0-7

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <class-maps>
  <class-map>
    <name>NAME</name>
    <config>
      <name>NAME</name>
    </config>
  <match-any-conditions>
  <config>
    <cos>WORD</cos> <!-- operation="delete"-->
  </config>
</match-any-conditions>
</class-map>
</class-maps>
</global>
</qos>

```

---

## Command Syntax

```
match cos WORD
```

---

## Configure inner cos

Use this attribute to classify traffic based on inner Class of Service (CoS) value

Attribute Name: inner-cos

Attribute Type: string

Attribute Range: 0-7

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
      <match-any-conditions>
        <config>
          <inner-cos>WORD</inner-cos> <!-- operation="delete"-->
        </config>
      </match-any-conditions>
    </class-map>
  </class-maps>
</global>
</qos>
```

## Command Syntax

```
match cos inner WORD
```

---

## Configure vlan

Use this attribute to classify traffic based on VLAN ID. Enter VLAN ID 1-4094 or range of VLAN ID's.

Attribute Name: vlan

Attribute Type: string

Attribute Range: 1-4094

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
      </class-map>
    </class-maps>
  </global>
</qos>
```

```

    </config>
  <match-any-conditions>
  <config>
    <vlan>WORD</vlan> <!-- operation="delete"-->
  </config>
</match-any-conditions>
</class-map>
</class-maps>
</global>
</qos>

```

### Command Syntax

```
match vlan WORD
```

---

## Configure vlan id

Use this attribute to classify traffic based on VLAN ID. Enter VLAN ID 1-4094.

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <class-maps>
  <class-map>
    <name>NAME</name>
    <config>
      <name>NAME</name>
    </config>
  <match-any-conditions>
  <config>
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
  </config>
</match-any-conditions>
</class-map>
</class-maps>
</global>
</qos>

```

### Command Syntax

```
match vlan <1-4094>
```

---

## Configure inner vlan

Use this attribute to classify traffic based on inner VLAN ID. Enter VLAN ID 1-4094 or range of VLAN ID's.

Attribute Name: inner-vlan

Attribute Type: string

Attribute Range: 1-4094

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
      <match-any-conditions>
        <config>
          <inner-vlan>WORD</inner-vlan> <!-- operation="delete"-->
        </config>
      </match-any-conditions>
    </class-map>
  </class-maps>
</global>
</qos>
```

### Command Syntax

```
match vlan inner WORD
```

---

## Configure inner vlan id

Use this attribute to classify traffic based on inner VLAN ID. Enter VLAN ID 1-4094.

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
      <match-any-conditions>
        <config>
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        </config>
      </match-any-conditions>
    </class-map>
  </class-maps>
</global>
</qos>
```

---

## Command Syntax

```
match vlan inner <1-4094>
```

---

## Configure rtp

Use this attribute to classify traffic based on the Real-time Transport Protocol (RTP). The rtp value 2000-65535 or range of rtp values.

Attribute Name: rtp

Attribute Type: string

Attribute Range: 2000-65535

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
      <match-any-conditions>
        <config>
          <rtp>WORD</rtp> <!-- operation="delete" -->
        </config>
      </match-any-conditions>
    </class-map>
  </class-maps>
</global>
</qos>
```

## Command Syntax

```
match ip rtp WORD
```

---

## Configure match-any-conditions dscp

Use this attribute to classify traffic based on the Differentiated Services Control Protocol (DSCP) value. Warning: In CLI show running, DSCP values with well-known names (ex.: af11, cs0) will be displayed as such. On Netconf, DSCP values will always be numeric.

Attribute Name: dscp

Attribute Type: string

Attribute Range: 0-63

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
```

```

    <name>NAME</name>
  <config>
    <name>NAME</name>
  </config>
</match-any-conditions>
<config>
  <dscp>WORD</dscp> <!-- operation="delete"-->
</config>
</match-any-conditions>
</class-map>
</class-maps>
</global>
</qos>

```

### Command Syntax

```
match dscp WORD
```

---

## Configure precedence

Use this attribute to classify traffic based on the precedence value. Warning: In CLI show running, precedence values with well-known names (ex.: priority, immediate) will be displayed as such. On Netconf, precedence values will always be numeric.

Attribute Name: precedence

Attribute Type: string

Attribute Range: 0-7

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <class-maps>
  <class-map>
    <name>NAME</name>
    <config>
      <name>NAME</name>
    </config>
  </class-map>
  </class-maps>
  <match-any-conditions>
  <config>
    <precedence>WORD</precedence> <!-- operation="delete"-->
  </config>
  </match-any-conditions>
  </class-map>
  </class-maps>
  </global>
</qos>

```

### Command Syntax

```
match precedence WORD
```

---

## Configure packet protocol

Use this attribute to classify traffic based on the protocol

Attribute Name: packet-protocol

Attribute Type: enum (arp|bridging|cdp|clns|clns-es|clns-is|dhcp|isis|ldp|netbios)

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
      <match-any-conditions>
        <config>
          <packet-protocol>arp</packet-protocol> <!-- operation="delete"-->
        </config>
      </match-any-conditions>
    </class-map>
  </class-maps>
</global>
</qos>
```

### Command Syntax

```
match protocol (arp|bridging|cdp|clns|clns-es|clns-is|dhcp|isis|ldp|netbios)
```

---

## Configure source mac

Use this attribute to classify traffic based on the source MAC address. The MAC address value allow up to 17 characters.

Attribute Name: source-mac

Attribute Type: string

Attribute Range: 1-17

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
      <match-any-conditions>
        <config>
          <source-mac>MAC_ADDR</source-mac> <!-- operation="delete"-->
        </config>
      </match-any-conditions>
    </class-map>
  </class-maps>
</global>
</qos>
```

```
</config>
</match-any-conditions>
</class-map>
</class-maps>
</global>
</qos>
```

## Command Syntax

```
match mac src MAC_ADDR
```

---

## Configure destination mac

Use this attribute to classify traffic based on the destination MAC address. The MAC address value allow up to 17 characters.

Attribute Name: destination-mac

Attribute Type: string

Attribute Range: 1-17

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
      <match-any-conditions>
        <config>
          <destination-mac>MAC_ADDR</destination-mac> <!-- operation="delete"-->
        </config>
      </match-any-conditions>
    </class-map>
  </class-maps>
</global>
</qos>
```

## Command Syntax

```
match mac dest MAC_ADDR
```

---

## Configure port type

Use this attribute to classify traffic based on layer 4 source port or destination port

Attribute Name: port-type

Attribute Type: enum (source-port|destination-port)

Attribute Name: port

Attribute Type: string

Attribute Range: 1-65535

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <class-maps>
  <class-map>
    <name>NAME</name>
    <config>
      <name>NAME</name>
    </config>
  <match-any-conditions>
  <ipv4>
  <layer4-match> <!-- operation="delete"-->
    <port-type>source-port</port-type>
    <config>
      <port-type>source-port</port-type>
      <protocol>any</protocol>
      <port>WORD</port>
    </config>
    <protocol>any</protocol>
  </layer4-match>
  </ipv4>
  </match-any-conditions>
  </class-map>
  </class-maps>
  </global>
</qos>
```

### Command Syntax

```
match layer4 (any|tcp|udp) (source-port|destination-port) WORD
```

---

## Configure ethertype all

Use this attribute to classify traffic based on the EtherType value

Attribute Name: ethertype-all

Attribute Type: string

Attribute Range: 5-6

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <class-maps>
  <class-map>
    <name>NAME</name>
    <config>
      <name>NAME</name>
    </config>
  <match-all-conditions>
```

```

<config>
  <ethertype-all>WORD</ethertype-all> <!-- operation="delete"-->
</config>
</match-all-conditions>
</class-map>
</class-maps>
</global>
</qos>

```

### Command Syntax

```
match ethertype WORD
```

---

## Configure traffic type all

Use this attribute to classify traffic based on the traffic type

Attribute Name: traffic-type-all

Attribute Type: enum (l2-uc|l2-uc-unknown|default)

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<class-maps>
<class-map>
  <name>NAME</name>
  <config>
    <name>NAME</name>
  </config>
<match-all-conditions>
<config>
  <traffic-type-all>l2-uc</traffic-type-all> <!-- operation="delete"-->
</config>
</match-all-conditions>
</class-map>
</class-maps>
</global>
</qos>

```

### Command Syntax

```
match traffic-type (l2-uc|l2-uc-unknown|default)
```

---

## Configure cos all

Use this attribute to classify traffic based on the Class of Service (CoS) value

Attribute Name: cos-all

Attribute Type: uint8

Attribute Range: 0-7

**Netconf edit-config payload**

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <class-maps>
  <class-map>
    <name>NAME</name>
    <config>
      <name>NAME</name>
    </config>
  <match-all-conditions>
  <config>
    <cos-all>0</cos-all> <!-- operation="delete"-->
  </config>
</match-all-conditions>
</class-map>
</class-maps>
</global>
</qos>

```

**Command Syntax**

```
match cos <0-7>
```

**Configure inner cos all**

Use this attribute to classify traffic based on the inner Class of Service (CoS) value

Attribute Name: inner-cos-all

Attribute Type: uint8

Attribute Range: 0-7

**Netconf edit-config payload**

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <class-maps>
  <class-map>
    <name>NAME</name>
    <config>
      <name>NAME</name>
    </config>
  <match-all-conditions>
  <config>
    <inner-cos-all>0</inner-cos-all> <!-- operation="delete"-->
  </config>
</match-all-conditions>
</class-map>
</class-maps>
</global>
</qos>

```

---

## Command Syntax

```
match cos inner <0-7>
```

---

## Configure vlan all

Use this attribute to classify traffic based on the VLAN ID

Attribute Name: vlan-all

Attribute Type: uint16

Attribute Range: 1-4094

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
      <match-all-conditions>
        <config>
          <vlan-all>1</vlan-all> <!-- operation="delete" -->
        </config>
      </match-all-conditions>
    </class-map>
  </class-maps>
</global>
</qos>
```

## Command Syntax

```
match vlan <1-4094>
```

---

## Configure inner vlan all

Use this attribute to classify traffic based on the inner VLAN ID

Attribute Name: inner-vlan-all

Attribute Type: uint16

Attribute Range: 1-4094

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
      </class-map>
    </class-maps>
  </global>
</qos>
```

```

    </config>
  <match-all-conditions>
  <config>
    <inner-vlan-all>1</inner-vlan-all> <!-- operation="delete"-->
  </config>
</match-all-conditions>
</class-map>
</class-maps>
</global>
</qos>

```

### Command Syntax

```
match vlan inner <1-4094>
```

---

## Configure rtp all

Use this attribute to classify traffic based on the Real-time Transport Protocol (RTP)

Attribute Name: rtp-all

Attribute Type: uint32

Attribute Range: 2000-65535

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <class-maps>
  <class-map>
    <name>NAME</name>
    <config>
      <name>NAME</name>
    </config>
  <match-all-conditions>
  <config>
    <rtp-all>2000</rtp-all> <!-- operation="delete"-->
  </config>
</match-all-conditions>
</class-map>
</class-maps>
</global>
</qos>

```

### Command Syntax

```
match ip rtp <2000-65535>
```

---

## Configure dscp all

Use this attribute to classify traffic based on the Differentiated Services Control Protocol (DSCP) value. The DSCP value range is 0-63. Warning: In CLI show running, DSCP values with well-known names (ex.: af11, cs0) will be displayed as such. On Netconf, DSCP values will always be numeric. The string type allow up to 8 characters on well-known name.

Attribute Name: dscp-all

Attribute Type: string

Attribute Range: 1-8

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
      <match-all-conditions>
        <config>
          <dscp-all>WORD</dscp-all> <!-- operation="delete"-->
        </config>
      </match-all-conditions>
    </class-map>
  </class-maps>
</global>
</qos>
```

### Command Syntax

```
match dscp WORD
```

---

## Configure precedence all

Use this attribute to classify traffic based on the precedence value. The precedence value range is 0-7. Warning: In CLI show running, precedence values with well-known names (ex.: priority, immediate) will be displayed as such. On Netconf, precedence values will always be numeric. The string type allow up to 13 characters on well-known name.

Attribute Name: precedence-all

Attribute Type: string

Attribute Range: 1-13

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
      <match-all-conditions>
        <config>
          <precedence-all>WORD</precedence-all> <!-- operation="delete"-->
        </config>
      </match-all-conditions>
    </class-map>
  </class-maps>
</global>
</qos>
```

```

</match-all-conditions>
</class-map>
</class-maps>
</global>
</qos>

```

## Command Syntax

```
match precedence WORD
```

---

## Configure packet protocol all

Use this attribute to classify traffic based on the protocol

Attribute Name: packet-protocol-all

Attribute Type: enum (arp|bridging|cdp|clns|clns-es|clns-is|dhcp|isis|ldp|netbios)

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
        <name>NAME</name>
        <config>
          <name>NAME</name>
        </config>
      <match-all-conditions>
        <config>
          <packet-protocol-all>arp</packet-protocol-all> <!-- operation="delete"-->
        </config>
      </match-all-conditions>
    </class-map>
  </class-maps>
</global>
</qos>

```

## Command Syntax

```
match protocol (arp|bridging|cdp|clns|clns-es|clns-is|dhcp|isis|ldp|netbios)
```

---

## Configure source mac all

Use this attribute to classify traffic based on the source MAC address. The MAC address value allow up to 17 characters.

Attribute Name: source-mac-all

Attribute Type: string

Attribute Range: 1-17

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>

```

```

<class-maps>
<class-map>
  <name>NAME</name>
  <config>
    <name>NAME</name>
  </config>
<match-all-conditions>
<config>
  <source-mac-all>MAC_ADDR</source-mac-all> <!-- operation="delete"-->
</config>
</match-all-conditions>
</class-map>
</class-maps>
</global>
</qos>

```

### Command Syntax

```
match mac src MAC_ADDR
```

---

## Configure destination mac all

Use this attribute to classify traffic based on the destination MAC address. The MAC address value allow up to 17 characters.

Attribute Name: destination-mac-all

Attribute Type: string

Attribute Range: 1-17

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<class-maps>
<class-map>
  <name>NAME</name>
  <config>
    <name>NAME</name>
  </config>
<match-all-conditions>
<config>
  <destination-mac-all>MAC_ADDR</destination-mac-all> <!-- operation="delete"--
>
</config>
</match-all-conditions>
</class-map>
</class-maps>
</global>
</qos>

```

### Command Syntax

```
match mac dest MAC_ADDR
```

---

## Configure port all

Use this attribute to classify traffic based on the port

Attribute Name: port-all

Attribute Type: uint16

Attribute Range: 1-65535

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps>
      <class-map>
        <name>NAME</name>
        <config>
          <name>NAME</name>
          </config>
        <match-all-conditions>
          <layer4-matches-ipv4>
            <layer4-match-ipv4> <!-- operation="delete"-->
              <port-all>1</port-all>
              <config>
                <port-all>1</port-all>
                <port-type-all>source-port</port-type-all>
                <protocol-all>any</protocol-all>
              </config>
              <port-type-all>source-port</port-type-all>
              <protocol-all>any</protocol-all>
            </layer4-match-ipv4>
          </layer4-matches-ipv4>
        </match-all-conditions>
      </class-map>
    </class-maps>
  </global>
</qos>
```

### Command Syntax

```
match layer4 (any|tcp|udp) (source-port|destination-port) <1-65535>
```

---

## Configure class-maps name

Use this attribute to set the class-map name

Attribute Name: name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing-default|vlan-queuing)

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <class-maps>
  <class-map> <!-- operation="delete"-->
    <name>NAME</name>
    <config>
      <name>NAME</name>
      <type>qos</type>
    </config>
  </class-map>
</class-maps>
</global>
</qos>
```

## Command Syntax

```
class-map type (queuing|vlan-queuing) NAME
```

---

## Configure class-map-queuing reference-description

This attribute configures reference description message on class-map profile for queuing.

Attribute Name: reference-description

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <class-maps-queuing>
  <class-map-queuing>
    <name>WORD</name>
    <config>
      <name>NAME</name>
    </config>
    <reference-description>LINE</reference-description> <!-- operation="delete"-->
  </class-map-queuing>
</class-maps-queuing>
</global>
</qos>
```

## Command Syntax

```
reference-description LINE
```

---

## Configure qos group

Use this attribute to classify traffic QoS group

Attribute Name: qos-group

Attribute Type: uint32

Attribute Range: 1-2000

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps-queuing>
      <class-map-queuing>
        <name>WORD</name>
        <config>
          <name>NAME</name>
        </config>
      </class-map-queuing>
    </class-maps-queuing>
  </global>
</qos>
```

### Command Syntax

```
match qos-group <1-2000>
```

---

## Configure vlan queue

Use this attribute to classify traffic based on the VLAN ID

Attribute Name: vlan-queue

Attribute Type: uint16

Attribute Range: 1-4094

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps-queuing>
      <class-map-queuing>
        <name>WORD</name>
        <config>
          <name>NAME</name>
        </config>
      </class-map-queuing>
    </class-maps-queuing>
  </global>
</qos>
```

```
</global>
</qos>
```

## Command Syntax

```
match vlan <1-4094>
```

---

## Configure match-conditions cos

Use this attribute to classify traffic based on the Class of Service (CoS) value

Attribute Name: cos

Attribute Type: string

Attribute Range: 0-7

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <class-maps-queuing>
      <class-map-queuing>
        <name>WORD</name>
        <config>
          <name>NAME</name>
        </config>
      <match-conditions>
        <config>
          <cos>WORD</cos> <!-- operation="delete"-->
        </config>
      </match-conditions>
    </class-map-queuing>
  </class-maps-queuing>
</global>
</qos>
```

## Command Syntax

```
match cos WORD
```

---

## Configure policy map name

Use this attribute to set the policy-map name

Attribute Name: policy-map-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing default|vlan-queuing|hybrid-queuing)

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
```

```

<global>
<policy-maps>
<policy-map> <!-- operation="delete"-->
  <policy-map-name>NAME</policy-map-name>
  <config>
    <policy-map-name>NAME</policy-map-name>
    <type>1</type>
  </config>
</policy-map>
</policy-maps>
</global>
</qos>

```

### Command Syntax

```
policy-map NAME
```

---

## Configure policy-maps policy-map-name

Use this attribute to set the policy-map name

Attribute Name: policy-map-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing default|vlan-queuing|hybrid-queuing)

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<policy-maps>
<policy-map> <!-- operation="delete"-->
  <policy-map-name>NAME</policy-map-name>
  <config>
    <policy-map-name>NAME</policy-map-name>
    <type>qos</type>
  </config>
</policy-map>
</policy-maps>
</global>
</qos>

```

### Command Syntax

```
policy-map type (qos) NAME
```

---

## Configure policy-maps policy-map-name

Use this attribute to set the policy-map name

Attribute Name: policy-map-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing default|vlan-queuing|hybrid-queuing)

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <policy-maps>
  <policy-map> <!-- operation="delete"-->
    <policy-map-name>NAME</policy-map-name>
    <config>
      <policy-map-name>NAME</policy-map-name>
      <type>qos</type>
    </config>
  </policy-map>
</policy-maps>
</global>
</qos>
```

### Command Syntax

```
policy-map type (queuing) NAME
```

---

## Configure policy-maps policy-map-name

Use this attribute to set the policy-map name

Attribute Name: policy-map-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing default|vlan-queuing|hybrid-queuing)

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <policy-maps>
  <policy-map> <!-- operation="delete"-->
    <policy-map-name>NAME</policy-map-name>
    <config>
      <policy-map-name>NAME</policy-map-name>
      <type>qos</type>
    </config>
  </policy-map>
</policy-maps>
</global>
</qos>
```

## Command Syntax

```
policy-map type (queuing default) NAME
```

---

## Configure policy-maps policy-map-name

Use this attribute to set the policy-map name

Attribute Name: policy-map-name

Attribute Type: string

Attribute Range: 1-32

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing default|vlan-queuing|hybrid-queuing)

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <policy-maps>
      <policy-map> <!-- operation="delete"-->
        <policy-map-name>NAME</policy-map-name>
        <config>
          <policy-map-name>NAME</policy-map-name>
          <type>qos</type>
        </config>
      </policy-map>
    </policy-maps>
  </global>
</qos>
```

## Command Syntax

```
policy-map type (vlan-queuing|hybrid-queuing) NAME
```

---

## Configure policy-map reference-description

This attribute configures reference description message on policy-map profile

Attribute Name: reference-description

Attribute Type: string

Attribute Range: 1-64

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <policy-maps>
      <policy-map>
        <policy-map-name>NAME</policy-map-name>
        <config>
          <policy-map-name>NAME</policy-map-name>
        </config>
      </policy-map>
    </policy-maps>
  </global>
</qos>
```

```

    <reference-description>LINE</reference-description> <!-- operation="delete"-->
</policy-map>
</policy-maps>
</global>
</qos>

```

### Command Syntax

```
reference-description LINE
```

---

## Configure class map name

Use this attribute to attach a class-map of type qos or queue to the policy-map

Attribute Name: class-map-name

Attribute Type: union

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing default|vlan-queuing|hybrid-queuing)

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<policy-maps>
<policy-map>
    <policy-map-name>NAME</policy-map-name>
    <config>
        <policy-map-name>NAME</policy-map-name>
    </config>
<classes>
<class> <!-- operation="delete"-->
    <class-map-name>NAME</class-map-name>
    <config>
        <class-map-name>NAME</class-map-name>
        <type>qos</type>
    </config>
</class>
</classes>
</policy-map>
</policy-maps>
</global>
</qos>

```

### Command Syntax

```
class (type (qos)|) NAME
```

---

## Configure classes class-map-name

Use this attribute to attach a class-map of type qos or queue to the policy-map

Attribute Name: class-map-name

Attribute Type: union

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing default|vlan-queuing|hybrid-queuing)

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <policy-maps>
  <policy-map>
    <policy-map-name>NAME</policy-map-name>
    <config>
      <policy-map-name>NAME</policy-map-name>
    </config>
  </policy-map>
  </policy-maps>
  <classes>
  <class> <!-- operation="delete"-->
    <class-map-name>NAME</class-map-name>
    <config>
      <class-map-name>NAME</class-map-name>
      <type>qos</type>
    </config>
  </class>
  </classes>
</policy-map>
</policy-maps>
</global>
</qos>
```

### Command Syntax

```
class (type (qos)|) class-default
```

---

## Configure classes class-map-name

Use this attribute to attach a class-map of type qos or queue to the policy-map

Attribute Name: class-map-name

Attribute Type: union

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing default|vlan-queuing|hybrid-queuing)

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <policy-maps>
  <policy-map>
    <policy-map-name>NAME</policy-map-name>
    <config>
      <policy-map-name>NAME</policy-map-name>
    </config>
  </policy-map>
  </policy-maps>
</global>
</qos>
```

```

<classes>
<class> <!-- operation="delete"-->
  <class-map-name>NAME</class-map-name>
  <config>
    <class-map-name>NAME</class-map-name>
    <type>queuing</type>
  </config>
</class>
</classes>
</policy-map>
</policy-maps>
</global>
</qos>

```

### Command Syntax

```
class (type (queuing)|) class-default-q
```

---

## Configure classes class-map-name

Use this attribute to attach a class-map of type qos or queue to the policy-map

Attribute Name: class-map-name

Attribute Type: string

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing default|vlan-queuing|hybrid-queuing)

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<policy-maps>
<policy-map>
  <policy-map-name>NAME</policy-map-name>
  <config>
    <policy-map-name>NAME</policy-map-name>
  </config>
<classes>
<class> <!-- operation="delete"-->
  <class-map-name>NAME</class-map-name>
  <config>
    <class-map-name>NAME</class-map-name>
    <type>queuing</type>
  </config>
</class>
</classes>
</policy-map>
</policy-maps>
</global>
</qos>

```

---

## Command Syntax

```
class (type (queuing)|) NAME
```

---

## Configure classes class-map-name

Use this attribute to attach a class-map of type qos or queue to the policy-map

Attribute Name: class-map-name

Attribute Type: string

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing default|vlan-queuing|hybrid-queuing)

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <policy-maps>
      <policy-map>
        <policy-map-name>NAME</policy-map-name>
        <config>
          <policy-map-name>NAME</policy-map-name>
        </config>
      </policy-map>
    </policy-maps>
    <classes>
      <class> <!-- operation="delete"-->
        <class-map-name>NAME</class-map-name>
        <config>
          <class-map-name>NAME</class-map-name>
          <type>queuing</type>
        </config>
      </class>
    </classes>
  </global>
</qos>
```

## Command Syntax

```
class (type (queuing|vlan-queuing)|) NAME
```

---

## Configure classes class-map-name

Use this attribute to attach a class-map of type qos or queue to the policy-map

Attribute Name: class-map-name

Attribute Type: union

Attribute Name: type

Attribute Type: enum (qos|queuing|queuing default|vlan-queuing|hybrid-queuing)

**Netconf edit-config payload**

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<policy-maps>
<policy-map>
  <policy-map-name>NAME</policy-map-name>
  <config>
    <policy-map-name>NAME</policy-map-name>
  </config>
</policy-map>
</policy-maps>
</global>
</qos>

```

**Command Syntax**

```
class type (queuing default) (q0|q1|q2|q3|q4|q5|q6|q7)
```

**Configure child service policy name**

Use this attribute to attach a child service-policy to the policy-map

Attribute Name: child-service-policy-name

Attribute Type: string

**Netconf edit-config payload**

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<policy-maps>
<policy-map>
  <policy-map-name>NAME</policy-map-name>
  <config>
    <policy-map-name>NAME</policy-map-name>
  </config>
</policy-map>
</policy-maps>
</global>
</qos>

```

```

</class>
</classes>
</policy-map>
</policy-maps>
</global>
</qos>

```

## Command Syntax

```
service-policy NAME
```

---

## Configure class reference-description

This attribute configures reference description message on the association between policy-map profile and class-map profile.

Attribute Name: reference-description

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<policy-maps>
<policy-map>
  <policy-map-name>NAME</policy-map-name>
  <config>
    <policy-map-name>NAME</policy-map-name>
  </config>
</policy-map>
</policy-maps>
</global>
</qos>

```

## Command Syntax

```
reference-description LINE
```

---

## Configure lossless

Use this attribute to set the lossless setting for queue.

Attribute Name: lossless

Attribute Type: empty

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <policy-maps>
  <policy-map>
    <policy-map-name>NAME</policy-map-name>
    <config>
      <policy-map-name>NAME</policy-map-name>
    </config>
  <classes>
  <class>
    <class-map-name>NAME</class-map-name>
    <config>
      <class-map-name>NAME</class-map-name>
    </config>
    <queue-mode>
    <config>
      </lossless><!-- operation="delete"-->
    </config>
  </queue-mode>
</class>
</classes>
</policy-map>
</policy-maps>
</global>
</qos>
```

### Command Syntax

```
lossless
```

---

## Configure weighted round robin queue weight

Use this attribute to set the weight for Weighted Round Robin queue scheduling algorithm

Attribute Name: weighted-round-robin-queue-weight

Attribute Type: uint8

Attribute Range: 1-127

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <policy-maps>
  <policy-map>
    <policy-map-name>NAME</policy-map-name>
    <config>
      <policy-map-name>NAME</policy-map-name>
```

```

    </config>
<classes>
<class>
  <class-map-name>NAME</class-map-name>
  <config>
    <class-map-name>NAME</class-map-name>
  </config>
  <queue-mode>
  <config>
    <weighted-round-robin-queue-weight>1</weighted-round-robin-queue-weight>
<!-- operation="delete"-->
  </config>
</queue-mode>
</class>
</classes>
</policy-map>
</policy-maps>
</global>
</qos>

```

## Command Syntax

```
wrr-queue weight <1-127>
```

---

## Configure strict priority enabled

Use this attribute to set Strict Priority as queue scheduling algorithm

Attribute Name: strict-priority-enabled

Attribute Type: empty

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<policy-maps>
<policy-map>
  <policy-map-name>NAME</policy-map-name>
  <config>
    <policy-map-name>NAME</policy-map-name>
  </config>
<classes>
<class>
  <class-map-name>NAME</class-map-name>
  <config>
    <class-map-name>NAME</class-map-name>
  </config>
  <queue-mode>
  <config>
    </strict-priority-enabled><!-- operation="delete"-->
  </config>
</queue-mode>

```

```

</class>
</classes>
</policy-map>
</policy-maps>
</global>
</qos>

```

## Command Syntax

```
priority
```

---

## Configure weight

Use this attribute to set weight for Weighted Random Early Detection

Attribute Name: weight

Attribute Type: uint8

Attribute Range: 0-15

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<policy-maps>
<policy-map>
  <policy-map-name>NAME</policy-map-name>
  <config>
    <policy-map-name>NAME</policy-map-name>
  </config>
</policy-map>
</policy-maps>
</global>
</qos>

```

## Command Syntax

```
random-detect weight <0-15>
```

---

## Configure min threshold

Use this attribute to set Weighted Random Early Detection minimum threshold

Attribute Name: min-threshold

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: max-threshold

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: threshold-unit

Attribute Type: enum (packets|bytes|kbytes)

Attribute Name: drop-probability

Attribute Type: uint8

Attribute Range: 1-100

Attribute Name: explicit-congestion-notification

Attribute Type: empty

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <policy-maps>
      <policy-map>
        <policy-map-name>NAME</policy-map-name>
        <config>
          <policy-map-name>NAME</policy-map-name>
        </config>
      <classes>
        <class>
          <class-map-name>NAME</class-map-name>
          <config>
            <class-map-name>NAME</class-map-name>
          </config>
          <queue-mode>
            <red>
              <wred>
                <config>
                  <max-threshold>1</max-threshold> <!-- operation="delete"-->
                  <threshold-unit>packets</threshold-unit> <!-- operation="delete"-->
                  <drop-probability>1</drop-probability> <!-- operation="delete"-->
                  </explicit-congestion-notification><!-- operation="delete"-->
                  <min-threshold>1</min-threshold> <!-- operation="delete"-->
                </config>
              </wred>
            </red>
          </queue-mode>
        </class>
      </classes>
    </policy-map>
  </policy-maps>
</global>
</qos>
```

```
</class>  
</classes>  
</policy-map>  
</policy-maps>  
</global>  
</qos>
```

## Command Syntax

```
random-detect <1-524288> <1-524288> (packets|bytes|kbytes) (drop-probability <1-100>|) (ecn|)
```

---

## Configure max threshold

Use this attribute to set Weighted Random Early Detection minimum threshold

Attribute Name: min-threshold

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: max-threshold

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: drop-probability

Attribute Type: uint8

Attribute Range: 1-100

Attribute Name: min-threshold-yellow

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: max-threshold-yellow

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: drop-probability-yellow

Attribute Type: uint8

Attribute Range: 1-100

Attribute Name: min-threshold-red

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: max-threshold-red

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: drop-probability-red

Attribute Type: uint8

Attribute Range: 1-100

Attribute Name: threshold-unit

Attribute Type: enum (packets|bytes|kbytes)

Attribute Name: explicit-congestion-notification

Attribute Type: empty

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <policy-maps>
  <policy-map>
    <policy-map-name>NAME</policy-map-name>
    <config>
      <policy-map-name>NAME</policy-map-name>
    </config>
  <classes>
  <class>
    <class-map-name>NAME</class-map-name>
    <config>
      <class-map-name>NAME</class-map-name>
    </config>
    <queue-mode>
    <red>
    <wred>
    <config>
      <max-threshold>1</max-threshold> <!-- operation="delete"-->
      <drop-probability>1</drop-probability> <!-- operation="delete"-->
      <min-threshold-yellow>1</min-threshold-yellow> <!-- operation="delete"-->
      <max-threshold-yellow>1</max-threshold-yellow> <!-- operation="delete"-->
      <drop-probability-yellow>1</drop-probability-yellow> <!--
operation="delete"-->
      <min-threshold-red>1</min-threshold-red> <!-- operation="delete"-->
      <max-threshold-red>1</max-threshold-red> <!-- operation="delete"-->
      <drop-probability-red>1</drop-probability-red> <!-- operation="delete"-->
      <threshold-unit>packets</threshold-unit> <!-- operation="delete"-->
      </explicit-congestion-notification><!-- operation="delete"-->
      <min-threshold>1</min-threshold> <!-- operation="delete"-->
    </config>
  </wred>
</red>
</queue-mode>
</class>
</classes>
</policy-map>
</policy-maps>
</global>
</qos>
```

## Command Syntax

```
random-detect green <1-524288> <1-524288> (drop-probability <1-100>|) yellow <1-524288> <1-524288> (drop-probability <1-100>|) red <1-524288> <1-524288> (drop-probability <1-100>|) (packets|bytes|kbytes) (ecn|)
```

---

## Configure threshold unit

Use this attribute to set Weighted Random Early Detection minimum threshold

Attribute Name: min-threshold

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: max-threshold

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: threshold-unit

Attribute Type: enum (packets|bytes|kbytes)

Attribute Name: drop-probability

Attribute Type: uint8

Attribute Range: 1-100

Attribute Name: explicit-congestion-notification

Attribute Type: empty

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <policy-maps>
      <policy-map>
        <policy-map-name>NAME</policy-map-name>
        <config>
          <policy-map-name>NAME</policy-map-name>
        </config>
      </policy-map>
    </policy-maps>
    <classes>
      <class>
        <class-map-name>NAME</class-map-name>
        <config>
          <class-map-name>NAME</class-map-name>
        </config>
        <queue-mode>
          <red>
            <wred>
              <config>
                <max-threshold>1</max-threshold> <!-- operation="delete"-->
                <threshold-unit>packets</threshold-unit> <!-- operation="delete"-->
                <drop-probability>1</drop-probability> <!-- operation="delete"-->
              </explicit-congestion-notification><!-- operation="delete"-->
            </wred>
          </red>
        </queue-mode>
      </class>
    </classes>
  </global>
</qos>
```

```
        <min-threshold>1</min-threshold> <!-- operation="delete"-->
    </config>
</wred>
</red>
</queue-mode>
</class>
</classes>
</policy-map>
</policy-maps>
</global>
</qos>
```

## Command Syntax

```
random-detect min-threshold <1-524288> max-threshold <1-524288>
(packet|bytes|kbytes) (drop-probability <1-100>|) (ecn|)
```

---

## Configure drop probability

Use this attribute to set Weighted Random Early Detection minimum threshold

Attribute Name: min-threshold

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: max-threshold

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: drop-probability

Attribute Type: uint8

Attribute Range: 1-100

Attribute Name: min-threshold-yellow

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: max-threshold-yellow

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: drop-probability-yellow

Attribute Type: uint8

Attribute Range: 1-100

Attribute Name: min-threshold-red

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: max-threshold-red

Attribute Type: uint32

Attribute Range: 1-524288

Attribute Name: drop-probability-red

Attribute Type: uint8

Attribute Range: 1-100

Attribute Name: threshold-unit

Attribute Type: enum (packets|bytes|kbytes)

Attribute Name: explicit-congestion-notification

Attribute Type: empty

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <policy-maps>
      <policy-map>
        <policy-map-name>NAME</policy-map-name>
        <config>
          <policy-map-name>NAME</policy-map-name>
        </config>
      <classes>
        <class>
          <class-map-name>NAME</class-map-name>
          <config>
            <class-map-name>NAME</class-map-name>
            <queue-mode>
              <red>
                <wred>
                  <config>
                    <max-threshold>1</max-threshold> <!-- operation="delete"-->
                    <drop-probability>1</drop-probability> <!-- operation="delete"-->
                    <min-threshold-yellow>1</min-threshold-yellow> <!-- operation="delete"-->
                    <max-threshold-yellow>1</max-threshold-yellow> <!-- operation="delete"-->
                    <drop-probability-yellow>1</drop-probability-yellow> <!--
operation="delete"-->
                    <min-threshold-red>1</min-threshold-red> <!-- operation="delete"-->
                    <max-threshold-red>1</max-threshold-red> <!-- operation="delete"-->
                    <drop-probability-red>1</drop-probability-red> <!-- operation="delete"-->
                    <threshold-unit>packets</threshold-unit> <!-- operation="delete"-->
                    </explicit-congestion-notification><!-- operation="delete"-->
                    <min-threshold>1</min-threshold> <!-- operation="delete"-->
                  </config>
                </wred>
              </red>
            </queue-mode>
          </class>
        </classes>
      </policy-map>
    </policy-maps>
  </global>
</qos>
```

```

</policy-map>
</policy-maps>
</global>
</qos>

```

## Command Syntax

```

random-detect green min-threshold <1-524288> max-threshold <1-524288> (drop-
probability <1-100>|) yellow min-threshold <1-524288> max-threshold <1-524288>
(drop-probability <1-100>|) red min-threshold <1-524288> max-threshold <1-524288>
(drop-probability <1-100>|) (packets|bytes|kbytes) (ecn|)

```

---

## Configure max threshold type

Use this attribute to set tail drop limits on egress queue

Attribute Name: max-threshold-type

Attribute Type: enum (packets|bytes|kbytes)

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<policy-maps>
<policy-map>
  <policy-map-name>NAME</policy-map-name>
  <config>
    <policy-map-name>NAME</policy-map-name>
  </config>
</classes>
<class>
  <class-map-name>NAME</class-map-name>
  <config>
    <class-map-name>NAME</class-map-name>
  </config>
  <queue-mode>
  <tail-drops>
  <tail-drop> <!-- operation="delete"-->
    <max-threshold-type>packets</max-threshold-type>
    <config>
      <max-threshold-type>packets</max-threshold-type>
      <max-threshold>1</max-threshold>
    </config>
    <max-threshold>1</max-threshold>
  </tail-drop>
</tail-drops>
</queue-mode>
</class>
</classes>
</policy-map>
</policy-maps>
</global>

```

---

```
</qos>
```

## Command Syntax

```
queue-limit <1-524288> (packets|bytes|kbytes)
```

---

## Configure rate value

Use this attribute to set a minimum bandwidth rate on the egress queue

Attribute Name: rate-value

Attribute Type: uint32

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <policy-maps>
      <policy-map>
        <policy-map-name>NAME</policy-map-name>
        <config>
          <policy-map-name>NAME</policy-map-name>
        </config>
      </policy-map>
    </policy-maps>
    <classes>
      <class>
        <class-map-name>NAME</class-map-name>
        <config>
          <class-map-name>NAME</class-map-name>
          <queue-mode>
            <bandwidths>
              <bandwidth> <!-- operation="delete"-->
                <rate-type>kbps</rate-type>
                <config>
                  <rate-type>kbps</rate-type>
                  <rate-value>0</rate-value>
                </config>
                <rate-value>0</rate-value>
              </bandwidth>
            </bandwidths>
          </queue-mode>
        </config>
      </class>
    </classes>
  </policy-map>
</policy-maps>
</global>
</qos>
```

## Command Syntax

```
bandwidth <1-1000000000> (kbps|mbps|gbps)
```

---

## Configure rate type

Use this attribute to set a minimum bandwidth rate on the egress queue

Attribute Name: rate-value

Attribute Type: uint32

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <policy-maps>
      <policy-map>
        <policy-map-name>NAME</policy-map-name>
        <config>
          <policy-map-name>NAME</policy-map-name>
        </config>
      </policy-map>
    </policy-maps>
    <classes>
      <class>
        <class-map-name>NAME</class-map-name>
        <config>
          <class-map-name>NAME</class-map-name>
          <queue-mode>
            <bandwidths>
              <bandwidth> <!-- operation="delete"-->
                <rate-type>kbps</rate-type>
                <config>
                  <rate-type>kbps</rate-type>
                  <rate-value>0</rate-value>
                </config>
                <rate-value>0</rate-value>
              </bandwidth>
            </bandwidths>
          </queue-mode>
        </config>
      </class>
    </classes>
  </policy-map>
</policy-maps>
</global>
</qos>
```

### Command Syntax

```
bandwidth (percent) <1-100>
```

---

## Configure rate unit

Use this attribute to set a maximum shaping rate on the egress queue

Attribute Name: rate-value

Attribute Type: uint32

**Netconf edit-config payload**

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <policy-maps>
  <policy-map>
    <policy-map-name>NAME</policy-map-name>
    <config>
      <policy-map-name>NAME</policy-map-name>
    </config>
  </policy-map>
  </policy-maps>
  </global>
</qos>

```

**Command Syntax**

```
shape <1-1000000000> (kbps|mbps|gbps)
```

**Configure shapes rate-value**

Use this attribute to set a maximum shaping rate on the egress queue

Attribute Name: rate-value

Attribute Type: uint32

**Netconf edit-config payload**

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <policy-maps>
  <policy-map>
    <policy-map-name>NAME</policy-map-name>

```

```

    <config>
      <policy-map-name>NAME</policy-map-name>
    </config>
  </classes>
<class>
  <class-map-name>NAME</class-map-name>
  <config>
    <class-map-name>NAME</class-map-name>
  </config>
  <queue-mode>
  <shapes>
    <shape> <!-- operation="delete"-->
      <rate-unit>kbps</rate-unit>
      <config>
        <rate-unit>kbps</rate-unit>
        <rate-value>0</rate-value>
      </config>
      <rate-value>0</rate-value>
    </shape>
  </shapes>
</queue-mode>
</class>
</classes>
</policy-map>
</policy-maps>
</global>
</qos>

```

## Command Syntax

```
shape (percent) <1-100>
```

---

## Configure priority

Use this attribute to set the user priority for the class attached to this policy-map

Attribute Name: priority

Attribute Type: uint16

Attribute Range: 1-1000

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <policy-maps>
      <policy-map>
        <policy-map-name>NAME</policy-map-name>
        <config>
          <policy-map-name>NAME</policy-map-name>
        </config>
      </policy-map>
    </policy-maps>
  </global>
</qos>

```

```

    <class-map-name>NAME</class-map-name>
  <config>
    <class-map-name>NAME</class-map-name>
  </config>
  <qos-mode>
  <config>
    <priority>1</priority> <!-- operation="delete"-->
  </config>
</qos-mode>
</class>
</classes>
</policy-map>
</policy-maps>
</global>
</qos>

```

## Command Syntax

```
priority <1-1000>
```

---

## Configure precedence remark

Use this attribute to match traffic classes set action as change precedence in the egress packet to the defined value. The precedence value range is 0-7. Warning: In CLI show running, precedence values with well-known names (ex.: priority, immediate) will be displayed as such. On Netconf, precedence values will always be numeric. The string type allow up to 13 characters on well-known name.

Attribute Name: precedence-remark

Attribute Type: string

Attribute Range: 1-13

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
  <policy-maps>
  <policy-map>
    <policy-map-name>NAME</policy-map-name>
    <config>
      <policy-map-name>NAME</policy-map-name>
    </config>
  </policy-map>
  </policy-maps>
  </global>
  </qos>

```

```

</class>
</classes>
</policy-map>
</policy-maps>
</global>
</qos>

```

## Command Syntax

```
set precedence WORD
```

---

## Configure qos-mode cos-value

Use this attribute to match traffic classes set action as change CoS in the egress packet to the defined value

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<policy-maps>
<policy-map>
  <policy-map-name>NAME</policy-map-name>
  <config>
    <policy-map-name>NAME</policy-map-name>
  </config>
</policy-map>
</policy-maps>
</global>
</qos>

```

## Command Syntax

```
set cos <0-7>
```

---

## Configure cos remark only bridged

Use this attribute to enable remarking only bridged packets

Attribute Name: cos-remark-only-bridged

Attribute Type: uint8

Attribute Range: 0-7

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <policy-maps>
      <policy-map>
        <policy-map-name>NAME</policy-map-name>
        <config>
          <policy-map-name>NAME</policy-map-name>
        </config>
      </policy-map>
    </policy-maps>
    <classes>
      <class>
        <class-map-name>NAME</class-map-name>
        <config>
          <class-map-name>NAME</class-map-name>
        </config>
        <qos-mode>
          <config>
            <cos-remark-only-bridged>0</cos-remark-only-bridged> <!--
operation="delete"-->
          </config>
        </qos-mode>
      </class>
    </classes>
  </policy-map>
</policy-maps>
</global>
</qos>
```

### Command Syntax

```
set bridge cos <0-7>
```

---

## Configure dscp value remark

Use this attribute to match traffic classes set action as change DSCP in the egress packet to the defined value. The DSCP value range is 0-63. Warning: In CLI show running, DSCP values with well-known names (ex.: af11, cs0) will be displayed as such. On Netconf, DSCP values will always be numeric. The string type allow up to 8 characters on well-known name.

Attribute Name: dscp-value-remark

Attribute Type: string

Attribute Range: 1-8

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<policy-maps>
<policy-map>
  <policy-map-name>NAME</policy-map-name>
  <config>
    <policy-map-name>NAME</policy-map-name>
  </config>
</policy-map>
</policy-maps>
<classes>
<class>
  <class-map-name>NAME</class-map-name>
  <config>
    <class-map-name>NAME</class-map-name>
  </config>
  <qos-mode>
  <config>
    <dscp-value-remark>WORD</dscp-value-remark> <!-- operation="delete"-->
  </config>
</qos-mode>
</class>
</classes>
</policy-map>
</policy-maps>
</global>
</qos>

```

## Command Syntax

```
set dscp WORD
```

---

## Configure dscp remark only bridged

Use this attribute to enable remarking only bridged packets. The DSCP value range is 0-63. Warning: In CLI show running, DSCP values with well-known names (ex.: af11, cs0) will be displayed as such. On Netconf, DSCP values will always be numeric. The string type allow up to 8 characters on well-known name.

Attribute Name: dscp-remark-only-bridged

Attribute Type: string

Attribute Range: 1-8

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<policy-maps>
<policy-map>
  <policy-map-name>NAME</policy-map-name>
  <config>
    <policy-map-name>NAME</policy-map-name>
  </config>
</policy-map>
</policy-maps>
</global>
</qos>

```

```

<class>
  <class-map-name>NAME</class-map-name>
  <config>
    <class-map-name>NAME</class-map-name>
  </config>
  <qos-mode>
  <config>
    <dscp-remark-only-bridged>WORD</dscp-remark-only-bridged> <!--
operation="delete"-->
  </config>
</qos-mode>
</class>
</classes>
</policy-map>
</policy-maps>
</global>
</qos>

```

## Command Syntax

```
set bridge dscp WORD
```

---

## Configure qos-mode queue-id

Use this attribute to match traffic classes set action as change queue in the egress packet to the defined value

Attribute Name: queue-id

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<policy-maps>
<policy-map>
  <policy-map-name>NAME</policy-map-name>
  <config>
    <policy-map-name>NAME</policy-map-name>
  </config>
</policy-map>
</policy-maps>
</global>
</qos>

```

```

</classes>
</policy-map>
</policy-maps>
</global>
</qos>

```

## Command Syntax

```
set queue <0-7>
```

---

## Configure queue remark only bridged

Use this attribute to enable remarking only bridged packets

Attribute Name: queue-remark-only-bridged

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <policy-maps>
      <policy-map>
        <policy-map-name>NAME</policy-map-name>
        <config>
          <policy-map-name>NAME</policy-map-name>
        </config>
      </policy-map>
    </policy-maps>
    <classes>
      <class>
        <class-map-name>NAME</class-map-name>
        <config>
          <class-map-name>NAME</class-map-name>
        </config>
        <qos-mode>
          <config>
            <queue-remark-only-bridged>0</queue-remark-only-bridged> <!--
operation="delete"-->
          </config>
        </qos-mode>
      </class>
    </classes>
  </policy-map>
</policy-maps>
</global>
</qos>

```

## Command Syntax

```
set bridge queue <0-7>
```

---

## Configure qos-mode qos-group

Use this attribute to set action as change QoS group in the egress packet to the defined value

Attribute Name: qos-group

Attribute Type: uint16

Attribute Range: 1-2000

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <policy-maps>
      <policy-map>
        <policy-map-name>NAME</policy-map-name>
        <config>
          <policy-map-name>NAME</policy-map-name>
        </config>
      </policy-map>
    </policy-maps>
    <classes>
      <class>
        <class-map-name>NAME</class-map-name>
        <config>
          <class-map-name>NAME</class-map-name>
        </config>
        <qos-mode>
          <config>
            <qos-group>1</qos-group> <!-- operation="delete"-->
          </config>
        </qos-mode>
      </class>
    </classes>
  </policy-map>
</policy-maps>
</global>
</qos>
```

### Command Syntax

```
set qos-group <1-2000>
```

---

## Configure non unicast queue weight

Use this attribute to set action as change qos wrr weight for non-uc queue in the egress to the defined value for matched packets

Attribute Name: non-unicast-queue-weight

Attribute Type: uint8

Attribute Range: 1-127

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
```

```
<global>
<scheduler-mode>
<weighted-round-robins>
<weighted-round-robin> <!-- operation="delete"-->
  <non-unicast-queue-weight>1</non-unicast-queue-weight>
  <config>
    <non-unicast-queue-weight>1</non-unicast-queue-weight>
    <unicast-queue-weight>1</unicast-queue-weight>
  </config>
  <unicast-queue-weight>1</unicast-queue-weight>
</weighted-round-robin>
</weighted-round-robins>
</scheduler-mode>
</global>
</qos>
```

### Command Syntax

```
set qos wrr uc <1-127> non-uc <1-127>
```

---

## Configure enabled

Use this attribute to set strict-priority for scheduler mode of L1 node to WRR

Attribute Name: enabled

Attribute Type: empty

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<global>
<scheduler-mode>
<strict-priority>
<config>
  </enabled><!-- operation="delete"-->
</config>
</strict-priority>
</scheduler-mode>
</global>
</qos>
```

### Command Syntax

```
set qos sp
```

---

## Configure statistics enabled

Use this attribute to enable QoS statistics

Attribute Name: enabled

Attribute Type: empty

---

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <statistics>
      <config>
        </enabled><!-- operation="delete"-->
      </config>
    </statistics>
  </global>
</qos>
```

### Command Syntax

```
qos statistics
```

---

## Configure block size

Use this attribute to configure block-size for vlan-queuing

Attribute Name: block-size

Attribute Type: uint8

Default Value: 1

Attribute Range: 1-8

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <global>
    <vlan-queuing>
      <config>
        <block-size>1</block-size> <!-- operation="delete"-->
      </config>
    </vlan-queuing>
  </global>
</qos>
```

### Command Syntax

```
qos vlan-queuing block-size <1-8>
```

---

## clear qos statistics (interface IFNAME|) ((type qos|type qos input|type qos output|type queuing|type all|))

Attribute Name: interface-name

Attribute Type: string

Default Value: NULL

Attribute Name: type

Attribute Type: enum (type qos|type qos input|type qos output|type queuing|type all)

Default Value: type all

## Netconf RPC payload

```
<qos-clear-statistics xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <interface-name>IFNAME</interface-name>
  <type>type all</type>
</qos-clear-statistics>
```

## Command Syntax

```
clear qos statistics (interface IFNAME|) ((type qos|type qos input|type qos
  output|type queuing|type all)|)
```

---

# IPI-QOS-IF

---

## Configure untagged priority

Use this attribute to set internal priority for untagged traffic on L2 interface

Attribute Name: untagged-priority

Attribute Type: uint8

Attribute Range: 0-7

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <untagged-priority>0</untagged-priority> <!-- operation="delete"-->
    </interface>
  </interfaces>
</qos>
```

## Command Syntax

```
qos untagged-priority <0-7>
```

---

## Configure trust dscp

Use this command to classify the ingress traffic based on DSCP map on L2 interface

Attribute Name: trust-dscp

Attribute Type: empty

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
    <interface>
```

```
<name>WORD</name>
<config>
  <name>WORD</name>
</config>
  </trust-dscp><!-- operation="delete"-->
</interface>
</interfaces>
</qos>
```

## Command Syntax

```
trust dscp
```

---

## Configure cos

Use this command to enable/disable remarking of CoS set by the egress map

Attribute Name: cos

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <remark>
    <config>
      <cos>disable</cos> <!-- operation="delete"-->
    </config>
  </remark>
</interface>
</interfaces>
</qos>
```

## Command Syntax

```
qos remark cos (disable|enable)
```

---

## Configure dei

Use this command to enable/disable remarking of DEI set by the egress map

Attribute Name: dei

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
<interface>
```

```

    <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <remark>
  <config>
    <dei>disable</dei> <!-- operation="delete"-->
  </config>
</remark>
</interface>
</interfaces>
</qos>

```

### Command Syntax

```
qos remark dei (disable|enable)
```

---

## Configure dscp

Use this command to enable/disable remarking of DSCP set by the egress map

Attribute Name: dscp

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
  <interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <remark>
      <config>
        <dscp>disable</dscp> <!-- operation="delete"-->
      </config>
    </remark>
  </interface>
</interfaces>
</qos>

```

### Command Syntax

```
qos remark dscp (disable|enable)
```

---

## Configure name

Interface name for which QoS is being configured

Attribute Name: name

Attribute Type: string

Attribute Name: rate

Attribute Type: uint64

Attribute Name: rate-unit

Attribute Type: enum (kbps|mbps|gbps)

Attribute Name: burst-rate

Attribute Type: uint64

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
<interface> <!-- operation="delete"-->
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <traffic-shape>
  <config>
    <rate>1</rate>
    <rate-unit>kbps</rate-unit>
    <burst-rate>1</burst-rate>
  </config>
  </traffic-shape>
</interface>
</interfaces>
</qos>
```

### Command Syntax

```
shape rate <1-1000000000> (kbps|mbps|gbps) burst <2-1000000>
```

---

## Configure rate

Interface name for which QoS is being configured

Attribute Name: name

Attribute Type: string

Attribute Name: rate

Attribute Type: uint64

Attribute Name: rate-unit

Attribute Type: enum (kbps|mbps|gbps)

Attribute Name: burst-rate

Attribute Type: uint64

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
<interface> <!-- operation="delete"-->
  <name>WORD</name>
```

```

<config>
  <name>WORD</name>
</config>
<traffic-shape>
<config>
  <rate>1</rate>
    <rate-unit>kbps</rate-unit>
      <burst-rate>1</burst-rate>
    </config>
  </traffic-shape>
</interface>
</interfaces>
</qos>

```

### Command Syntax

```
shape rate <1-1000000000> (kbps|mbps|gbps) burst <2-1000000>
```

---

## Configure cos to queue

Use this attribute to attach a CoS to Traffic-Class profile to the interface

This command is supported when following feature are enabled QoS Mapping profile

Attribute Name: cos-to-queue

Attribute Type: string

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <map-profile>
  <config>
    <cos-to-queue>NAME</cos-to-queue> <!-- operation="delete"-->
  </config>
</map-profile>
</interface>
</interfaces>
</qos>

```

### Command Syntax

```
qos map-profile cos-to-queue NAME
```

---

## Configure dscp to queue

Use this attribute to attach a DSCP to Traffic-Class profile to the interface

This command is supported when following feature are enabled QoS Mapping profile

Attribute Name: dscp-to-queue

Attribute Type: string

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <map-profile>
  <config>
    <dscp-to-queue>NAME</dscp-to-queue> <!-- operation="delete"-->
  </config>
</map-profile>
</interface>
</interfaces>
</qos>
```

### Command Syntax

```
qos map-profile dscp-to-queue NAME
```

---

## Configure precedence to queue

Use this attribute to attach a Precedence to Traffic-Class profile to the interface

This command is supported when following feature are enabled QoS Mapping profile

Attribute Name: precedence-to-queue

Attribute Type: string

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <map-profile>
  <config>
    <precedence-to-queue>NAME</precedence-to-queue> <!-- operation="delete"-->
  </config>
</map-profile>
</interface>
</interfaces>
</qos>
```

---

## Command Syntax

```
qos map-profile precedence-to-queue NAME
```

---

## Configure queue color to cos

Use this attribute to attach a Traffic-Class color to CoS profile to the interface

This command is supported when following feature are enabled QoS Mapping profile

Attribute Name: queue-color-to-cos

Attribute Type: string

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <map-profile>
  <config>
    <queue-color-to-cos>NAME</queue-color-to-cos> <!-- operation="delete"-->
  </config>
</map-profile>
</interface>
</interfaces>
</qos>
```

## Command Syntax

```
qos map-profile queue-color-to-cos NAME
```

---

## Configure queue color to dscp

Use this attribute to attach a Traffic-Class color to DSCP profile to the interface

This command is supported when following feature are enabled QoS Mapping profile

Attribute Name: queue-color-to-dscp

Attribute Type: string

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <map-profile>
  <config>
```

```

    <queue-color-to-dscp>NAME</queue-color-to-dscp> <!-- operation="delete"-->
>
    </config>
</map-profile>
</interface>
</interfaces>
</qos>

```

## Command Syntax

```
qos map-profile queue-color-to-dscp NAME
```

---

## Configure queue to precedence

Use this attribute to attach a queue color to Precedence profile to the interface

This command is supported when following feature are enabled QoS Mapping profile

Attribute Name: queue-to-precedence

Attribute Type: string

### Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
<interface>
    <name>WORD</name>
    <config>
        <name>WORD</name>
    </config>
    <map-profile>
    <config>
        <queue-to-precedence>NAME</queue-to-precedence> <!-- operation="delete"-->
>
    </config>
</map-profile>
</interface>
</interfaces>
</qos>

```

## Command Syntax

```
qos map-profile queue-to-precedence NAME
```

---

## Configure type qos policy map name

Use this attribute to attach a service-policy of type qos to the interface

Attribute Name: type-qos-policy-map-name

Attribute Type: string

Attribute Range: 1-32

### Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
```

```

<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <service-policy>
  <ingress>
  <config>
    <type-qos-policy-map-name>NAME</type-qos-policy-map-name> <!--
operation="delete"-->
  </config>
</ingress>
</service-policy>
</interface>
</interfaces>
</qos>

```

## Command Syntax

```
service-policy type qos input NAME
```

---

## Configure egress type-qos-policy-map-name

Use this attribute to attach a service-policy of type qos to the interface

Attribute Name: type-qos-policy-map-name

Attribute Type: string

Attribute Range: 1-32

## Netconf edit-config payload

```

<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <service-policy>
  <egress>
  <config>
    <type-qos-policy-map-name>NAME</type-qos-policy-map-name> <!--
operation="delete"-->
  </config>
</egress>
</service-policy>
</interface>
</interfaces>
</qos>

```

## Command Syntax

```
service-policy type qos output NAME
```

## Configure type queuing policy map name

Use this attribute to attach a service-policy of type queue to the interface

Attribute Name: type-queuing-policy-map-name

Attribute Type: string

Attribute Range: 1-32

## Netconf edit-config payload

```
<qos xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos">
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-qos-if">
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <service-policy>
  <egress>
  <config>
    <type-queuing-policy-map-name>NAME</type-queuing-policy-map-name> <!--
operation="delete"-->
  </config>
</egress>
</service-policy>
</interface>
</interfaces>
</qos>
```

## Command Syntax

```
service-policy type queuing output NAME
```

# IPI-MCEC

## Configure options

Use this attribute to debug the mlag feature.

Attribute Name: options

Attribute Type: bits (hello|info|timer|event|cli|mac-sync|stp|all)

## Netconf edit-config payload

```
<mcec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mcec">
<debug>
<config>
  <options>hello</options> <!-- operation="delete"-->
```

```
</config>  
</debug>  
</mcec>
```

## Command Syntax

```
debug mcec (hello|info|timer|event|cli|mac-sync|stp|all)
```

---

## Configure system number

Use this attribute to configure domain system number, which uniquely identifies domain system in MCEC domain

Attribute Name: system-number

Attribute Type: uint8

Attribute Range: 1-2

## Netconf edit-config payload

```
<mcec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mcec">  
<domain>  
<config>  
  <system-number>1</system-number> <!-- operation="delete"-->  
</config>  
</domain>  
</mcec>
```

## Command Syntax

```
domain-system-number <1-2>
```

---

## Configure address

Use this attribute configure domain address, which helps to identify the MCEC domain

Attribute Name: address

Attribute Type: string

## Netconf edit-config payload

```
<mcec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mcec">  
<domain>  
<config>  
  <address>MAC</address> <!-- operation="delete"-->  
</config>  
</domain>  
</mcec>
```

## Command Syntax

```
domain-address MAC
```

---

## Configure priority

Use this attribute to specify the priority value associated with MCEC domain

Attribute Name: priority

Attribute Type: uint16

Default Value: 32768

Attribute Range: 1-65535

### Netconf edit-config payload

```
<mcec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mcec">
  <domain>
    <config>
      <priority>1</priority> <!-- operation="delete"-->
    </config>
  </domain>
</mcec>
```

### Command Syntax

```
domain-priority <1-65535>
```

---

## Configure hello timeout

Use this attribute to specify the domain hello-timeout value

Attribute Name: hello-timeout

Attribute Type: enum (long|short)

Default Value: long

### Netconf edit-config payload

```
<mcec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mcec">
  <domain>
    <config>
      <hello-timeout>long</hello-timeout> <!-- operation="delete"-->
    </config>
  </domain>
</mcec>
```

### Command Syntax

```
domain-hello-timeout (long|short)
```

---

## Configure interface

Use this attribute to map an interface as intra domain link that connects the domain system with its neighbour in a mcec domain

Attribute Name: interface

Attribute Type: string

### Netconf edit-config payload

```
<mcec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mcec">
  <intra-domain>
```

```
<peer-link>
<config>
  <interface>IFNAME</interface> <!-- operation="delete"-->
</config>
</peer-link>
</intra-domain>
</mcec>
```

### Command Syntax

```
intra-domain-link IFNAME
```

---

## Configure higig

Turn on/off higig on inter domain link

Attribute Name: higig

Attribute Type: empty

### Netconf edit-config payload

```
<mcec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mcec">
<intra-domain>
<peer-link>
<config>
  </higig><!-- operation="delete"-->
</config>
</peer-link>
</intra-domain>
</mcec>
```

### Command Syntax

```
idl-higig
```

---

## Configure vrf

vrf of the peer DSN node

Attribute Name: vrf

Attribute Type: string

Attribute Name: peer-address

Attribute Type: inet:ipv4-address

Attribute Name: local-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<mcec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mcec">
<intra-domain>
<peer-address>
<config>
```

```

    <peer-address>A.B.C.D</peer-address>
    <local-address>A.B.C.D</local-address>
    <vrf>VRF_NAME</vrf>
</config>
</peer-address>
</intra-domain>
</mcec>

```

## Command Syntax

```
intra-domain-peer A.B.C.D source-address A.B.C.D (vrf VRF_NAME|)
```

---

## Configure interface mode

Use this attribute to set the MC-LAG mode. active-standby: The interface is ready to transition from active to standby state should a failure occur in the other node.

Attribute Name: interface-mode

Attribute Type: enum (active-standby|active-active)

Default Value: active-active

## Netconf edit-config payload

```

<mcec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mcec">
  <mlag-interfaces>
    <mlag-interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <interface-mode>active-active</interface-mode> <!-- operation="delete"-->
    </mlag-interface>
  </mlag-interfaces>
</mcec>

```

## Command Syntax

```
mode (active-standby|active-active)
```

---

## Configure revertive timer

Use this attribute to set the timer for MC-LAG switchover revertive type. After Revertive timer expires Slave will handover the control to Master Node. If a failure happens that triggers a switchover, after failure recovery the initially-active node becomes active again. Default switchover type is revertive 10s.

Attribute Name: revertive-timer

Attribute Type: uint8

Default Value: 10

Attribute Range: 1-255

## Netconf edit-config payload

```
<mcec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mcec">
```

```

<mlog-interfices>
<mlog-interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<switchover-type>
<config>
  <revertive-timer>1</revertive-timer> <!-- operation="delete"-->
</config>
</switchover-type>
</mlog-interface>
</mlog-interfices>
</mcec>

```

### Command Syntax

```
switchover type revertive <1-255>
```

---

## Configure enable non revertive

Use this attribute to set the MC-LAG switchover to non-revertive type. Do not switch back to the initially-active node after failure recovery. Default switchover type is revertive 10s.

Attribute Name: enable-non-revertive

Attribute Type: empty

### Netconf edit-config payload

```

<mcec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mcec">
<mlog-interfices>
<mlog-interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<switchover-type>
<config>
  </enable-non-revertive><!-- operation="delete"-->
</config>
</switchover-type>
</mlog-interface>
</mlog-interfices>
</mcec>

```

### Command Syntax

```
switchover type non-revertive
```

---

## debug mcec (hello|info|timer|event|cli|mac-sync|stp|all)

Attribute Name: terminal-debug-options

---

Attribute Type: bits (hello|info|timer|event|cli|mac-sync|stp|all)

### Netconf RPC payload

```
<mcec-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mcec">  
<terminal-debug-options>hello</terminal-debug-options>  
</mcec-terminal-debug-on>
```

### Command Syntax

```
debug mcec (hello|info|timer|event|cli|mac-sync|stp|all)
```

---

## no debug mcec (hello|info|timer|event|cli|mac-sync|stp|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (hello|info|timer|event|cli|mac-sync|stp|all)

### Netconf RPC payload

```
<mcec-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mcec">  
<terminal-debug-options>hello</terminal-debug-options>  
</mcec-terminal-debug-off>
```

### Command Syntax

```
no debug mcec (hello|info|timer|event|cli|mac-sync|stp|all)
```

---

## clear mcec statistics

### Netconf RPC payload

```
<clear-mcec-statistics xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mcec"/>
```

### Command Syntax

```
clear mcec statistics
```

---

## reload-trigger-mcec-notification

### Netconf RPC payload

```
<trigger-reload xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mcec"/>
```

### Command Syntax

```
reload-trigger-mcec-notification
```

---

## IPI-MLAG

---

### Configure mlag id

MLAG group number

Attribute Name: mlag-id

Attribute Type: uint16

Attribute Range: 1-255

### Netconf edit-config payload

```
<interfaces xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-interface">
  <interface>
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
    </config>
    <mlag-aggregation xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mlag">
      <config>
        <mlag-id>1</mlag-id>
      </config>
    </mlag-aggregation>
  </interface>
</interfaces>
```

### Command Syntax

```
mlag <1-255>
```

---

## reload-trigger-save-mlag-info

### Netconf RPC payload

```
<trigger-save-mlag-info xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-mlag"/>
```

### Command Syntax

```
reload-trigger-save-mlag-info
```

---

## IPI-PLATFORM

---

### Configure enable cmm

Use this attribute to turn on debugging for chassis monitoring

Attribute Name: enable-cmm

Attribute Type: empty

### Netconf edit-config payload

```
<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <debug>
    <config>
      </enable-cmm><!-- operation="delete"-->
    </config>
  </debug>
</components>
```

---

## Command Syntax

```
debug cmm
```

---

## Configure enable ddm

Use this attribute to turn on debugging for digital diagnostic monitoring

Attribute Name: enable-ddm

Attribute Type: empty

## Netconf edit-config payload

```
<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <debug>
    <config>
      </enable-ddm><!-- operation="delete"-->
    </config>
  </debug>
</components>
```

## Command Syntax

```
debug ddm
```

---

## Configure warning repeat

To enable cmm warning level logs to repeat.

Attribute Name: warning-repeat

Attribute Type: empty

## Netconf edit-config payload

```
<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <global>
    <config>
      </warning-repeat><!-- operation="delete"-->
    </config>
  </global>
</components>
```

## Command Syntax

```
cmm warning repeat
```

---

## Configure locator led enable

To set the locator-led on or off.

Attribute Name: locator-led-enable

Attribute Type: empty

---

### Netconf edit-config payload

```
<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <global>
  <config>
    </locator-led-enable><!-- operation="delete"-->
  </config>
</global>
</components>
```

### Command Syntax

```
locator-led on
```

---

## Configure ddm monitor time interval

To set DDM Monitor interval time.

Attribute Name: ddm-monitor-time-interval

Attribute Type: uint16

Attribute Range: 60-3600

### Netconf edit-config payload

```
<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <global>
  <config>
    <ddm-monitor-time-interval>60</ddm-monitor-time-interval> <!--
operation="delete"-->
  </config>
</global>
</components>
```

### Command Syntax

```
ddm monitor interval <60-3600>
```

---

## Configure service unsupported transceiver

To enable DDM Monitor for unsupported transceivers at user risk.

Attribute Name: service-unsupported-transceiver

Attribute Type: empty

### Netconf edit-config payload

```
<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <global>
  <config>
    </service-unsupported-transceiver><!-- operation="delete"-->
  </config>
</global>
</components>
```

---

## Command Syntax

```
service unsupported-transceiver
```

---

## Configure enable ddm monitor

To enable DDM monitor for all transceivers.

Attribute Name: enable-ddm-monitor

Attribute Type: empty

### Netconf edit-config payload

```
<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <global>
    <config>
      </enable-ddm-monitor><!-- operation="delete"-->
    </config>
  </global>
</components>
```

## Command Syntax

```
ddm monitor all
```

---

## Configure system 15min load avg alarm

System 15min average load for alarm

Attribute Name: system-15min-load-avg-alarm

Attribute Type: uint8

Attribute Range: 51-100

### Netconf edit-config payload

```
<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <global>
    <system-load-average-thresholds>
      <system-load-average-threshold> <!-- operation="delete"-->
        <system-15min-load-avg-alarm>51</system-15min-load-avg-alarm>
      </config>
        <system-15min-load-avg-alarm>51</system-15min-load-avg-alarm>
        <system-5min-load-avg-alarm>51</system-5min-load-avg-alarm>
        <system-1min-load-avg-alarm>51</system-1min-load-avg-alarm>
        <system-1min-load-avg-warning-threshold>41</system-1min-load-avg-warning-
threshold>
      </config>
        <system-5min-load-avg-alarm>51</system-5min-load-avg-alarm>
        <system-1min-load-avg-alarm>51</system-1min-load-avg-alarm>
        <system-1min-load-avg-warning-threshold>41</system-1min-load-avg-warning-
threshold>
      </system-load-average-threshold>
    </system-load-average-thresholds>
  </global>
```

```
</components>
```

## Command Syntax

```
system-load-average 1min warning <41-100> alarm <51-100> 5min alarm <51-100> 15min
alarm <51-100>
```

---

## Configure alarm threshold

Cpu threshold for alarm

Attribute Name: alarm-threshold

Attribute Type: uint8

Attribute Range: 91-100

### Netconf edit-config payload

```
<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <global>
    <cpu-core-usage-thresholds>
      <cpu-core-usage-threshold <!-- operation="delete"-->
        <alarm-threshold>91</alarm-threshold>
      <config>
        <alarm-threshold>91</alarm-threshold>
        <warning-threshold>51</warning-threshold>
      </config>
      <warning-threshold>51</warning-threshold>
    </cpu-core-usage-threshold>
  </cpu-core-usage-thresholds>
</global>
</components>
```

## Command Syntax

```
cpu-core-usage warning <51-100> alarm <91-100>
```

---

## Configure monitor port

To enable DDM monitor for current transceiver.

This command is supported when following feature are disabled Tibit MicroPlug OLT feature

Attribute Name: monitor-port

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <interfaces>
    <interface>
      <interface-name>WORD</interface-name>
      <config>
        <interface-name>WORD</interface-name>
      </config>
    </interface>
  </interfaces>
</components>
```

```

    <monitor-port>disable</monitor-port> <!-- operation="delete"-->
  </interface>
</interfaces>
</components>

```

## Command Syntax

```
ddm monitor (disable|enable)
```

---

## Configure poe enable

To enable PoE for current interface.

This command is supported when following feature are disabled Tibit MicroPlug OLT feature

Attribute Name: poe-enable

Attribute Type: empty

## Netconf edit-config payload

```

<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <interfaces>
    <interface>
      <interface-name>WORD</interface-name>
      <config>
        <interface-name>WORD</interface-name>
      </config>
      </poe-enable><!-- operation="delete"-->
    </interface>
  </interfaces>
</components>

```

## Command Syntax

```
poe-enable
```

---

## Configure transceiver code

To set transceiver code for current transceiver.

This command is supported when following feature are disabled Tibit MicroPlug OLT feature

Attribute Name: transceiver-code

Attribute Type: enum (1000base-sx|1000base-lx|1000base-ex|1000base-cx|10gbase-sr|10gbase-lr|10gbase-er|10gbase-cr|25gbase-sr|25gbase-lr|25gbase-er|25gbase-cr|40gbase-sr4|40gbase-lr4|40gbase-er4|40gbase-cr4|100gbase-sr4|100gbase-lr4|100gbase-er4|100gbase-cr4)

## Netconf edit-config payload

```

<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <interfaces>
    <interface>
      <interface-name>WORD</interface-name>
      <config>
        <interface-name>WORD</interface-name>

```

```

    </config>
    <transceiver-code>1000base-sx</transceiver-code> <!-- operation="delete"-->
</interface>
</interfaces>
</components>

```

### Command Syntax

```

transceiver (1000base-sx|1000base-lx|1000base-ex|1000base-cx|10gbase-sr|10gbase-
lr|10gbase-er|10gbase-cr|25gbase-sr|25gbase-lr|25gbase-er|25gbase-cr|40gbase-
sr4|40gbase-lr4|40gbase-er4|40gbase-cr4|100gbase-sr4|100gbase-lr4|100gbase-
er4|100gbase-cr4)

```

---

## Configure wavelength

wavelength

This command is supported when following feature are disabled Tibit MicroPlug OLT feature

Attribute Name: wavelength

Attribute Type: union

### Netconf edit-config payload

```

<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<interfaces>
<interface>
    <interface-name>WORD</interface-name>
    <config>
        <interface-name>WORD</interface-name>
    </config>
    <wavelength>CML_WAVELENGTH_T</wavelength>
</interface>
</interfaces>
</components>

```

### Command Syntax

```

wavelength (channel-number <1-96>|update <1528773-1566723>)

```

---

## Configure tx disable

To disable laser tx for current transceiver.

This command is supported when following feature are disabled Tibit MicroPlug OLT feature

Attribute Name: tx-disable

Attribute Type: empty

### Netconf edit-config payload

```

<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<interfaces>
<interface>
    <interface-name>WORD</interface-name>

```

```

    <config>
      <interface-name>WORD</interface-name>
    </config>
  </tx-disable><!-- operation="delete"-->
</interface>
</interfaces>
</components>

```

## Command Syntax

```
tx-disable
```

---

## Configure edfa operating mode

To set the EDFA operating mode

This command is supported when following feature are disabled Tibit MicroPlug OLT feature

Attribute Name: edfa-operating-mode

Attribute Type: enum (agc|apc)

### Netconf edit-config payload

```

<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <interfaces>
    <interface>
      <interface-name>WORD</interface-name>
      <config>
        <interface-name>WORD</interface-name>
      </config>
      <edfa-operating-mode>agc</edfa-operating-mode> <!-- operation="delete"-->
    </interface>
  </interfaces>
</components>

```

## Command Syntax

```
edfa operating-mode (agc|apc)
```

---

## Configure edfa target output power

To configure the target output power value in dBm

This command is supported when following feature are disabled Tibit MicroPlug OLT feature

Attribute Name: edfa-target-output-power

Attribute Type: decimal64

### Netconf edit-config payload

```

<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <interfaces>
    <interface>
      <interface-name>WORD</interface-name>
      <config>

```

```

        <interface-name>WORD</interface-name>
    </config>
    <edfa-target-output-power>VALUE</edfa-target-output-power> <!--
operation="delete"-->
</interface>
</interfaces>
</components>

```

### Command Syntax

```
edfa target-outpwr VALUE
```

---

## Configure edfa target gain

To set the target-gain

This command is supported when following feature are disabled Tibit MicroPlug OLT feature

Attribute Name: edfa-target-gain

Attribute Type: decimal64

### Netconf edit-config payload

```

<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<interfaces>
<interface>
    <interface-name>WORD</interface-name>
    <config>
        <interface-name>WORD</interface-name>
    </config>
    <edfa-target-gain>VALUE</edfa-target-gain> <!-- operation="delete"-->
</interface>
</interfaces>
</components>

```

### Command Syntax

```
edfa target-gain VALUE
```

---

## Configure tx cdr bypass

Bypass the TX CDR control

This command is supported when following feature are disabled Tibit MicroPlug OLT feature

Attribute Name: tx-cdr-bypass

Attribute Type: empty

### Netconf edit-config payload

```

<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<interfaces>
<interface>
    <interface-name>WORD</interface-name>
    <config>

```

```

    <interface-name>WORD</interface-name>
  </config>
  </tx-cdr-bypass><!-- operation="delete"-->
</interface>
</interfaces>
</components>

```

### Command Syntax

```
tx cdr-bypass
```

---

## Configure rx cdr bypass

Bypass the CDR control

This command is supported when following feature are disabled Tibit MicroPlug OLT feature

Attribute Name: rx-cdr-bypass

Attribute Type: empty

### Netconf edit-config payload

```

<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <interfaces>
    <interface>
      <interface-name>WORD</interface-name>
      <config>
        <interface-name>WORD</interface-name>
      </config>
      </rx-cdr-bypass><!-- operation="delete"-->
    </interface>
  </interfaces>
</components>

```

### Command Syntax

```
rx cdr-bypass
```

---

## Configure interval

To set disk activity sampling window interval time.

Attribute Name: interval

Attribute Type: uint16

Attribute Range: 30-1200

### Netconf edit-config payload

```

<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <disk-activity-monitoring>
    <config>
      <interval>30</interval> <!-- operation="delete"-->
    </config>
  </disk-activity-monitoring>

```

---

```
</components>
```

## Command Syntax

```
disk-activity-monitoring interval <30-1200>
```

---

## Configure read threshold

To set disk read activity alarm threshold.

Attribute Name: read-threshold

Attribute Type: uint32

Attribute Range: 1-20000

## Netconf edit-config payload

```
<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <disk-activity-monitoring>
    <config>
      <read-threshold>1</read-threshold> <!-- operation="delete"-->
    </config>
  </disk-activity-monitoring>
</components>
```

## Command Syntax

```
disk-activity-monitoring threshold read <1-20000>
```

---

## Configure write threshold

To set disk write activity alarm threshold.

Attribute Name: write-threshold

Attribute Type: uint32

Attribute Range: 1-20000

## Netconf edit-config payload

```
<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <disk-activity-monitoring>
    <config>
      <write-threshold>1</write-threshold> <!-- operation="delete"-->
    </config>
  </disk-activity-monitoring>
</components>
```

## Command Syntax

```
disk-activity-monitoring threshold write <1-20000>
```

---

## Configure temperature policy

Set temperature policy

Attribute Name: temperature-policy

Attribute Type: enum (sys-halt|sys-reboot|none)

### Netconf edit-config payload

```
<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <temperature>
    <config>
      <temperature-policy>sys-halt</temperature-policy> <!-- operation="delete"-->
    </config>
  </temperature>
</components>
```

### Command Syntax

```
temperature policy (sys-halt|sys-reboot|none)
```

---

## Configure sensor id

Sensor ID

Attribute Name: sensor-id

Attribute Type: uint8

Attribute Range: 1-15

### Netconf edit-config payload

```
<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <temperature>
    <thresholds>
      <threshold> <!-- operation="delete"-->
        <sensor-id>1</sensor-id>
      <config>
        <sensor-id>1</sensor-id>
      </config>
    </threshold>
  </thresholds>
</temperature>
</components>
```

### Command Syntax

```
temperature threshold <1-15>
```

---

## Configure value

Value to over-write temperature sensor threshold

Attribute Name: value

Attribute Type: int16

Attribute Range: -50-150

## Netconf edit-config payload

```
<components xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <temperature>
    <thresholds>
      <threshold>
        <sensor-id>1</sensor-id>
        <config>
          <sensor-id>1</sensor-id>
        </config>
      </threshold>
    </thresholds>
  </temperature>
</components>
```

## Command Syntax

```
(emer-max|alrt-max|crit-max|crit-min|alrt-min|emer-min) <-50-150>
```

---

## clear ddm transceiver alarm all

### Netconf RPC payload

```
<ddm-clear-transceiver-alarm-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform"/>
```

### Command Syntax

```
clear ddm transceiver alarm all
```

---

## clear ddm transceiver alarm

Attribute Name: name

Attribute Type: string

### Netconf RPC payload

```
<ddm-clear-transceiver-alarm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <name>WORD</name>
</ddm-clear-transceiver-alarm>
```

### Command Syntax

```
clear ddm transceiver alarm
```

---

## debug ddm

### Netconf RPC payload

```
<cmm-terminal-debug-ddm-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-  
platform"/>
```

### Command Syntax

```
debug ddm
```

---

## no debug ddm

### Netconf RPC payload

```
<cmm-terminal-debug-ddm-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-  
platform"/>
```

### Command Syntax

```
no debug ddm
```

---

## debug cmm

### Netconf RPC payload

```
<cmm-terminal-debug-cmm-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-  
platform"/>
```

### Command Syntax

```
debug cmm
```

---

## no debug cmm

### Netconf RPC payload

```
<cmm-terminal-debug-cmm-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-  
platform"/>
```

### Command Syntax

```
no debug cmm
```

---

## IPI-PLATFORM-PROFILE

---

### Configure route mode

This Object is to check forwarding profile limit

This command is supported when following feature are enabled bcm uft feature and following feature are disabled dune feature

Attribute Name: route-mode

Attribute Type: enum (narrow|wide)

Default Value: wide

### Netconf edit-config payload

```
<forwarding-profile-route-modes xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
platform">
  <config>
    <route-mode>wide</route-mode> <!-- operation="delete"-->
  </config>
</forwarding-profile-route-modes>
```

### Command Syntax

```
forwarding-profile route-mode (narrow|wide)
```

---

## Configure egress ipv6

Use this attribute to enable or disable Egress IPv6 filter groups. Disabling filter groups increases the configurable filter entries.

This command is supported when following feature are enabled broadcom feature

Attribute Name: egress-ipv6

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<profiles xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <hardware-profile>
    <filters>
      <config>
        <egress-ipv6>disable</egress-ipv6> <!-- operation="delete"-->
      </config>
    </filters>
  </hardware-profile>
</profiles>
```

### Command Syntax

```
hardware-profile filter egress-ipv6 (disable|enable)
```

---

## Configure ingress ipv6 acl

Use this attribute to enable or disable Ingress IPv6 filter groups. Disabling filter groups increases the configurable filter entries.

This command is supported when following feature are enabled broadcom feature

Attribute Name: ingress-ipv6-acl

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<profiles xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <hardware-profile>
```

```

<filters>
<config>
  <ingress-ipv6-acl>disable</ingress-ipv6-acl> <!-- operation="delete"-->
</config>
</filters>
</hardware-profile>
</profiles>

```

### Command Syntax

```
hardware-profile filter ingress-ipv6 (disable|enable)
```

---

## Configure ingress ipv4 custom0

Use this attribute to enable or disable Ingress IPv4 filter groups. Disabling filter groups increases the configurable filter entries.

This command is supported when following feature are enabled broadcom feature

Attribute Name: ingress-ipv4-custom0

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```

<profiles xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<hardware-profile>
<filters>
<config>
  <ingress-ipv4-custom0>disable</ingress-ipv4-custom0> <!-- operation="delete"-->
</config>
</filters>
</hardware-profile>
</profiles>

```

### Command Syntax

```
hardware-profile filter ingress-ipv4 (disable|enable)
```

---

## Configure ingress arp

Use this attribute to enable or disable Ingress ARP filter groups.

This command is supported when following feature are enabled broadcom feature

Attribute Name: ingress-arp

Attribute Type: empty

### Netconf edit-config payload

```

<profiles xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<hardware-profile>
<filters>
<config>
  </ingress-arp><!-- operation="delete"-->
</config>

```

```
</filters>  
</hardware-profile>  
</profiles>
```

## Command Syntax

```
hardware-profile filter ingress-arp enable
```

---

## Configure ingress mirror

Use this attribute to enable or disable Ingress Mirror filter groups. Disabling filter groups increases the configurable filter entries.

This command is supported when following feature are enabled broadcom feature

Attribute Name: ingress-mirror

Attribute Type: empty

## Netconf edit-config payload

```
<profiles xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">  
<hardware-profile>  
<filters>  
<config>  
  </ingress-mirror><!-- operation="delete"-->  
</config>  
</filters>  
</hardware-profile>  
</profiles>
```

## Command Syntax

```
hardware-profile filter ingress-mirror enable
```

---

## Configure ingress bfd

Use this attribute to enable or disable Ingress BFD filter groups. Disabling filter groups increases the configurable filter entries.

This command is supported when following feature are enabled broadcom feature

Attribute Name: ingress-bfd

Attribute Type: enum (disable|enable)

## Netconf edit-config payload

```
<profiles xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">  
<hardware-profile>  
<filters>  
<config>  
  <ingress-bfd>disable</ingress-bfd> <!-- operation="delete"-->  
</config>  
</filters>  
</hardware-profile>  
</profiles>
```

---

## Command Syntax

```
hardware-profile filter bfd-group (disable|enable)
```

---

## Configure ipsg ipv6

Use this attribute to enable or disable IP Source Guard(IPSG) ipv6 filter groups. Disabling filter groups increases the configurable filter entries.

This command is supported when following feature are enabled broadcom feature

Attribute Name: ipsg-ipv6

Attribute Type: empty

### Netconf edit-config payload

```
<profiles xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <hardware-profile>
    <filters>
      <config>
        </ipsg-ipv6><!-- operation="delete"-->
      </config>
    </filters>
  </hardware-profile>
</profiles>
```

## Command Syntax

```
hardware-profile filter ipsg-ipv6 enable
```

---

## Configure isolation

Use this attribute to enable or disable port isolation. Disabling filter groups increases the configurable filter entries.

This command is supported when following feature are enabled broadcom feature

Attribute Name: isolation

Attribute Type: enum (disable|enable)

### Netconf edit-config payload

```
<profiles xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <hardware-profile>
    <filters>
      <config>
        <isolation>disable</isolation> <!-- operation="delete"-->
      </config>
    </filters>
  </hardware-profile>
</profiles>
```

## Command Syntax

```
hardware-profile filter port-isolation (disable|enable)
```

---

## Configure profile

This Object is to check forwarding profile limit

This command is supported when following feature are enabled bcm uft feature and following feature are disabled dune feature

Attribute Name: profile

Attribute Type: enum (l2-profile-one|l2-profile-two|l2-profile-three|l3-profile|l3-128bit-profile|lpm-profile|lpm-128bit-profile|custom-profile)

Default Value: l2-profile-three

### Netconf edit-config payload

```
<profiles xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <forwarding-profiles>
    <config>
      <profile>l2-profile-three</profile> <!-- operation="delete"-->
    </config>
  </forwarding-profiles>
</profiles>
```

### Command Syntax

```
forwarding profile (l2-profile-one|l2-profile-two|l2-profile-three|l3-profile|l3-
128bit-profile|lpm-profile)
```

---

## Configure forwarding-profiles profile

This Object is to check forwarding profile limit

This command is supported when following feature are enabled bcm uft feature and following feature are disabled dune feature

Attribute Name: profile

Attribute Type: enum (l2-profile-one|l2-profile-two|l2-profile-three|l3-profile|l3-128bit-profile|lpm-profile|lpm-128bit-profile|custom-profile)

Default Value: l2-profile-three

### Netconf edit-config payload

```
<profiles xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <forwarding-profiles>
    <config>
      <profile>l2-profile-three</profile> <!-- operation="delete"-->
    </config>
  </forwarding-profiles>
</profiles>
```

### Command Syntax

```
forwarding profile (l2-profile-one|l2-profile-two|l2-profile-three|l3-profile|l3-
128bit-profile|lpm-profile|lpm-128bit-profile|custom-profile)
```

---

## Configure forwarding-profiles profile

This Object is to check forwarding profile limit

This command is supported when following feature are enabled bcm uft feature and following feature are disabled dune feature

Attribute Name: profile

Attribute Type: enum (l2-profile-one|l2-profile-two|l2-profile-three|l3-profile|l3-128bit-profile|lpm-profile|lpm-128bit-profile|custom-profile)

Default Value: l2-profile-three

### Netconf edit-config payload

```
<profiles xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <forwarding-profiles>
    <config>
      <profile>l2-profile-three</profile> <!-- operation="delete"-->
    </config>
  </forwarding-profiles>
</profiles>
```

### Command Syntax

```
forwarding profile (lpm-profile|lpm-128bit-profile)
```

---

## Configure forwarding-profiles profile

This Object is to check forwarding profile limit

This command is supported when following feature are enabled bcm uft feature and following feature are disabled dune feature

Attribute Name: profile

Attribute Type: enum (l2-profile-one|l2-profile-two|l2-profile-three|l3-profile|l3-128bit-profile|lpm-profile|lpm-128bit-profile|custom-profile)

Default Value: l2-profile-three

### Netconf edit-config payload

```
<profiles xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <forwarding-profiles>
    <config>
      <profile>l2-profile-three</profile> <!-- operation="delete"-->
    </config>
  </forwarding-profiles>
</profiles>
```

### Command Syntax

```
forwarding profile (l2-profile-three|lpm-profile|lpm-128bit-profile)
```

---

## Configure forwarding-profiles profile

This Object is to check forwarding profile limit

This command is supported when following feature are enabled bcm uft feature and following feature are disabled dune feature

Attribute Name: profile

Attribute Type: enum (l2-profile-one|l2-profile-two|l2-profile-three|l3-profile|l3-128bit-profile|lpm-profile|lpm-128bit-profile|custom-profile)

Default Value: l2-profile-three

### Netconf edit-config payload

```
<profiles xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <forwarding-profiles>
    <config>
      <profile>l2-profile-three</profile> <!-- operation="delete"-->
    </config>
  </forwarding-profiles>
</profiles>
```

### Command Syntax

```
forwarding profile (l2-profile-one|l2-profile-two|l2-profile-three|l3-profile|l3-
128bit-profile|custom-profile)
```

---

## Configure mpls ip payload

This Object is set for load balancing based on MPLS IP payload

This command is supported when following feature are enabled broadcom feature

Attribute Name: mpls-ip-payload

Attribute Type: empty

Attribute Name: mpls-label-based

Attribute Type: empty

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
    <config>
      </mpls-label-based><!-- operation="delete"-->
      </mpls-ip-payload><!-- operation="delete"-->
    </config>
  </load-balance>
</hardware>
```

### Command Syntax

```
load-balance rtag7 mpls labels ip-payload
```

---

## Configure mpls label based

This Object is set for load balancing based on mpls labels

This command is supported when following feature are enabled broadcom feature

Attribute Name: mpls-label-based

Attribute Type: empty

Attribute Name: mpls-ip-payload

Attribute Type: empty

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
    <config>
      </mpls-ip-payload><!-- operation="delete"-->
      </mpls-label-based><!-- operation="delete"-->
    </config>
  </load-balance>
</hardware>
```

### Command Syntax

```
load-balance rtag7 mpls ip-payload labels
```

---

## Configure enable

This Object is set loadBalance

This command is supported when following feature are enabled broadcom feature

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
    <config>
      </enable>
    </config>
  </load-balance>
</hardware>
```

### Command Syntax

```
load-balance rtag7
```

---

## Configure load-balance mpls-label-based

This Object is set for load balancing based on mpls labels

This command is supported when following feature are enabled broadcom feature

Attribute Name: mpls-label-based

Attribute Type: empty

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
  <config>
    </mpls-label-based><!-- operation="delete"-->
  </config>
</load-balance>
</hardware>
```

### Command Syntax

```
load-balance rtag7 mpls labels
```

---

## Configure load-balance mpls-ip-payload

This Object is set for load balancing based on MPLS IP payload

This command is supported when following feature are enabled broadcom feature

Attribute Name: mpls-ip-payload

Attribute Type: empty

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
  <config>
    </mpls-ip-payload><!-- operation="delete"-->
  </config>
</load-balance>
</hardware>
```

### Command Syntax

```
load-balance rtag7 mpls ip-payload
```

---

## Configure hash

This Object is used to set (hash values)CRC

This command is supported when following feature are enabled broadcom feature

Attribute Name: hash

Attribute Type: enum (crc16-bisync|crc16-ccitt|crc32-lo|crc32-hi)

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
  <config>
    <hash>crc16-bisync</hash> <!-- operation="delete"-->
  </config>
```

```
</load-balance>
</hardware>
```

## Command Syntax

```
load-balance rtag7 hash (crc16-bisync|crc16-ccitt|crc32-lo|crc32-hi)
```

---

## Configure macro flow based

macro-flow based dynamic hash selection

This command is supported when following feature are enabled broadcom feature

Attribute Name: macro-flow-based

Attribute Type: empty

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
    <config>
      </macro-flow-based><!-- operation="delete"-->
    </config>
  </load-balance>
</hardware>
```

## Command Syntax

```
load-balance rtag7 macro-flow
```

---

## Configure vlan based

This Object is set for Vlan based load balancing

This command is supported when following feature are enabled L2 feature,broadcom feature

Attribute Name: vlan-based

Attribute Type: empty

Attribute Name: dest-mac-based

Attribute Type: empty

Attribute Name: src-mac-based

Attribute Type: empty

Attribute Name: ether-type-based

Attribute Type: empty

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
    <l2>
      <config>
        </dest-mac-based><!-- operation="delete"-->
        </src-mac-based><!-- operation="delete"-->
      </config>
    </l2>
  </load-balance>
</hardware>
```

```

    </ether-type-based><!-- operation="delete"-->
    </vlan-based><!-- operation="delete"-->
</config>
</l2>
</load-balance>
</hardware>

```

## Command Syntax

```
load-balance rtag7 l2 { dest-mac| src-mac| ether-type| vlan }
```

---

## Configure symmetric

Symmetric load balancing

This command is supported when following feature are enabled L3 feature,broadcom feature

Attribute Name: symmetric

Attribute Type: empty

Attribute Name: src-ipv4-address-based

Attribute Type: empty

Attribute Name: dest-ipv4-address-based

Attribute Type: empty

Attribute Name: src-l4-port-based

Attribute Type: empty

Attribute Name: dest-l4-port-based

Attribute Type: empty

Attribute Name: protocol-id-based

Attribute Type: empty

## Netconf edit-config payload

```

<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
    <ipv4>
      <config>
        </src-ipv4-address-based><!-- operation="delete"-->
        </dest-ipv4-address-based><!-- operation="delete"-->
        </src-l4-port-based><!-- operation="delete"-->
        </dest-l4-port-based><!-- operation="delete"-->
        </protocol-id-based><!-- operation="delete"-->
        </symmetric><!-- operation="delete"-->
      </config>
    </ipv4>
  </load-balance>
</hardware>

```

## Command Syntax

```
load-balance rtag7 ipv4 { src-ipv4| dest-ipv4| srcl4-port| destl4-port| protocol-
id| symmetric }
```

---

## Configure src ipv6 address based

Symmetric load balancing

This command is supported when following feature are enabled L3 feature,broadcom feature

Attribute Name: symmetric

Attribute Type: empty

Attribute Name: src-ipv6-address-based

Attribute Type: empty

Attribute Name: dest-ipv6-address-based

Attribute Type: empty

Attribute Name: src-l4-port-based

Attribute Type: empty

Attribute Name: dest-l4-port-based

Attribute Type: empty

Attribute Name: next-header-based

Attribute Type: empty

## Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
    <ipv6>
      <config>
        </src-ipv6-address-based><!-- operation="delete"-->
        </dest-ipv6-address-based><!-- operation="delete"-->
        </src-l4-port-based><!-- operation="delete"-->
        </dest-l4-port-based><!-- operation="delete"-->
        </next-header-based><!-- operation="delete"-->
        </symmetric><!-- operation="delete"-->
      </config>
    </ipv6>
  </load-balance>
</hardware>
```

## Command Syntax

```
load-balance rtag7 ipv6 { src-ipv6| dest-ipv6| srcl4-port| destl4-port| next-hdr|
symmetric }
```

---

## Configure queue name

This attribute specifies CPU queue name for rate limiting config

Attribute Name: queue-name

Attribute Type: enum (best-effort|ipmc-miss|l3-miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)

Attribute Name: rate

Attribute Type: int32

Attribute Range: 0-100000

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-queue>
    <rate-limits>
      <rate-limit>
        <queue-name>best-effort</queue-name>
        <config>
          <queue-name>best-effort</queue-name>
          <rate>0</rate>
        </config>
      </rate-limit>
    </rate-limits>
  </cpu-queue>
</hardware>
```

### Command Syntax

```
cpu-queue (best-effort|ipmc-miss|l3-
  miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)
rate <0-100000>
```

---

## Configure monitor

This attribute specifies CPU queue name for rate limiting config

Attribute Name: queue-name

Attribute Type: enum (best-effort|ipmc-miss|l3-miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)

Attribute Name: monitor

Attribute Type: enum (no-monitor|monitor)

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-queue>
    <rate-limits>
      <rate-limit>
        <queue-name>best-effort</queue-name>
        <config>
          <queue-name>best-effort</queue-name>
          <monitor>no-monitor</monitor>
        </config>
      </rate-limit>
    </rate-limits>
  </cpu-queue>
</hardware>
```

```

</rate-limits>
</cpu-queue>
</hardware>

```

## Command Syntax

```

cpu-queue (best-effort|ipmc-miss|l3-
miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)
(no-monitor|monitor)

```

---

## Configure lossy

This attribute specifies CPU queue name for rate limiting config

Attribute Name: queue-name

Attribute Type: enum (best-effort|ipmc-miss|l3-miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)

Attribute Name: lossy

Attribute Type: enum (lossless|lossy)

## Netconf edit-config payload

```

<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-queue>
    <rate-limits>
      <rate-limit>
        <queue-name>best-effort</queue-name>
        <config>
          <queue-name>best-effort</queue-name>
          <lossy>lossless</lossy>
        </config>
      </rate-limit>
    </rate-limits>
  </cpu-queue>
</hardware>

```

## Command Syntax

```

cpu-queue (best-effort|ipmc-miss|l3-
miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)
(lossless|lossy)

```

---

## Configure rate

This attribute specifies CPU queue name for rate limiting config

Attribute Name: queue-name

Attribute Type: enum (best-effort|ipmc-miss|l3-miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)

Attribute Name: rate

Attribute Type: int32

Attribute Range: 0-100000

Attribute Name: monitor

Attribute Type: enum (no-monitor|monitor)

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-queue>
    <rate-limits>
      <rate-limit>
        <queue-name>best-effort</queue-name>
        <config>
          <queue-name>best-effort</queue-name>
          <rate>0</rate>
          <monitor>no-monitor</monitor>
        </config>
      </rate-limit>
    </rate-limits>
  </cpu-queue>
</hardware>
```

### Command Syntax

```
cpu-queue (best-effort|ipmc-miss|l3-
  miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)
rate <0-100000> (no-monitor|monitor)
```

---

## Configure rate-limits queue-name

This attribute specifies CPU queue name for rate limiting config

Attribute Name: queue-name

Attribute Type: enum (best-effort|ipmc-miss|l3-miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)

Attribute Name: rate

Attribute Type: int32

Attribute Range: 0-100000

Attribute Name: lossy

Attribute Type: enum (lossless|lossy)

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-queue>
    <rate-limits>
      <rate-limit>
        <queue-name>best-effort</queue-name>
        <config>
          <queue-name>best-effort</queue-name>
          <rate>0</rate>
          <lossy>lossless</lossy>
        </config>
      </rate-limit>
    </rate-limits>
  </cpu-queue>
</hardware>
```

```

    </config>
  </rate-limit>
</rate-limits>
</cpu-queue>
</hardware>

```

## Command Syntax

```

cpu-queue (best-effort|ipmc-miss|l3-
  miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)
rate <0-100000> (lossless|lossy)

```

---

## Configure rate-limits queue-name

This attribute specifies CPU queue name for rate limiting config

Attribute Name: queue-name

Attribute Type: enum (best-effort|ipmc-miss|l3-  
miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)

Attribute Name: monitor

Attribute Type: enum (no-monitor|monitor)

Attribute Name: rate

Attribute Type: int32

Attribute Range: 0-100000

## Netconf edit-config payload

```

<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-queue>
    <rate-limits>
      <rate-limit>
        <queue-name>best-effort</queue-name>
        <config>
          <queue-name>best-effort</queue-name>
          <monitor>no-monitor</monitor>
          <rate>0</rate>
        </config>
      </rate-limit>
    </rate-limits>
  </cpu-queue>
</hardware>

```

## Command Syntax

```

cpu-queue (best-effort|ipmc-miss|l3-
  miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)
(no-monitor|monitor) rate <0-100000>

```

---

## Configure rate-limits queue-name

This attribute specifies CPU queue name for rate limiting config

Attribute Name: queue-name

Attribute Type: enum (best-effort|ipmc-miss|l3-miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)

Attribute Name: monitor

Attribute Type: enum (no-monitor|monitor)

Attribute Name: lossy

Attribute Type: enum (lossless|lossy)

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-queue>
    <rate-limits>
      <rate-limit>
        <queue-name>best-effort</queue-name>
        <config>
          <queue-name>best-effort</queue-name>
          <monitor>no-monitor</monitor>
          <lossy>lossless</lossy>
        </config>
      </rate-limit>
    </rate-limits>
  </cpu-queue>
</hardware>
```

### Command Syntax

```
cpu-queue (best-effort|ipmc-miss|l3-
  miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)
  (no-monitor|monitor) (lossless|lossy)
```

---

## Configure rate-limits queue-name

This attribute specifies CPU queue name for rate limiting config

Attribute Name: queue-name

Attribute Type: enum (best-effort|ipmc-miss|l3-miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)

Attribute Name: lossy

Attribute Type: enum (lossless|lossy)

Attribute Name: rate

Attribute Type: int32

Attribute Range: 0-100000

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-queue>
    <rate-limits>
```

```

<rate-limit>
  <queue-name>best-effort</queue-name>
  <config>
    <queue-name>best-effort</queue-name>
    <lossy>lossless</lossy>
    <rate>0</rate>
  </config>
</rate-limit>
</rate-limits>
</cpu-queue>
</hardware>

```

### Command Syntax

```

cpu-queue (best-effort|ipmc-miss|l3-
  miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)
(lossless|lossy) rate <0-100000>

```

---

## Configure rate-limits queue-name

This attribute specifies CPU queue name for rate limiting config

Attribute Name: queue-name

Attribute Type: enum (best-effort|ipmc-miss|l3-miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)

Attribute Name: lossy

Attribute Type: enum (lossless|lossy)

Attribute Name: monitor

Attribute Type: enum (no-monitor|monitor)

### Netconf edit-config payload

```

<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-queue>
    <rate-limits>
      <rate-limit>
        <queue-name>best-effort</queue-name>
        <config>
          <queue-name>best-effort</queue-name>
          <lossy>lossless</lossy>
          <monitor>no-monitor</monitor>
        </config>
      </rate-limit>
    </rate-limits>
  </cpu-queue>
</hardware>

```

### Command Syntax

```

cpu-queue (best-effort|ipmc-miss|l3-
  miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)
(lossless|lossy) (no-monitor|monitor)

```

---

## Configure rate-limits queue-name

This attribute specifies CPU queue name for rate limiting config

Attribute Name: queue-name

Attribute Type: enum (best-effort|ipmc-miss|l3-miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)

Attribute Name: rate

Attribute Type: int32

Attribute Range: 0-100000

Attribute Name: monitor

Attribute Type: enum (no-monitor|monitor)

Attribute Name: lossy

Attribute Type: enum (lossless|lossy)

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-queue>
    <rate-limits>
      <rate-limit>
        <queue-name>best-effort</queue-name>
        <config>
          <queue-name>best-effort</queue-name>
          <rate>0</rate>
          <monitor>no-monitor</monitor>
          <lossy>lossless</lossy>
        </config>
      </rate-limit>
    </rate-limits>
  </cpu-queue>
</hardware>
```

### Command Syntax

```
cpu-queue (best-effort|ipmc-miss|l3-
  miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)
rate <0-100000> (no-monitor|monitor) (lossless|lossy)
```

---

## Configure rate-limits queue-name

This attribute specifies CPU queue name for rate limiting config

Attribute Name: queue-name

Attribute Type: enum (best-effort|ipmc-miss|l3-miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)

Attribute Name: rate

Attribute Type: int32

Attribute Range: 0-100000

Attribute Name: lossy

Attribute Type: enum (lossless|lossy)

Attribute Name: monitor

Attribute Type: enum (no-monitor|monitor)

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-queue>
    <rate-limits>
      <rate-limit>
        <queue-name>best-effort</queue-name>
        <config>
          <queue-name>best-effort</queue-name>
          <rate>0</rate>
          <lossy>lossless</lossy>
          <monitor>no-monitor</monitor>
        </config>
      </rate-limit>
    </rate-limits>
  </cpu-queue>
</hardware>
```

### Command Syntax

```
cpu-queue (best-effort|ipmc-miss|l3-
  miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)
  rate <0-100000> (lossless|lossy) (no-monitor|monitor)
```

---

## Configure rate-limits queue-name

This attribute specifies CPU queue name for rate limiting config

Attribute Name: queue-name

Attribute Type: enum (best-effort|ipmc-miss|l3-miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)

Attribute Name: monitor

Attribute Type: enum (no-monitor|monitor)

Attribute Name: rate

Attribute Type: int32

Attribute Range: 0-100000

Attribute Name: lossy

Attribute Type: enum (lossless|lossy)

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-queue>
    <rate-limits>
```

```

<rate-limit>
  <queue-name>best-effort</queue-name>
  <config>
    <queue-name>best-effort</queue-name>
    <monitor>no-monitor</monitor>
    <rate>0</rate>
    <lossy>lossless</lossy>
  </config>
</rate-limit>
</rate-limits>
</cpu-queue>
</hardware>

```

## Command Syntax

```

cpu-queue (best-effort|ipmc-miss|l3-
  miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)
  (no-monitor|monitor) rate <0-100000> (lossless|lossy)

```

---

## Configure rate-limits queue-name

This attribute specifies CPU queue name for rate limiting config

Attribute Name: queue-name

Attribute Type: enum (best-effort|ipmc-miss|l3-miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)

Attribute Name: monitor

Attribute Type: enum (no-monitor|monitor)

Attribute Name: lossy

Attribute Type: enum (lossless|lossy)

Attribute Name: rate

Attribute Type: int32

Attribute Range: 0-100000

## Netconf edit-config payload

```

<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-queue>
    <rate-limits>
      <rate-limit>
        <queue-name>best-effort</queue-name>
        <config>
          <queue-name>best-effort</queue-name>
          <monitor>no-monitor</monitor>
          <lossy>lossless</lossy>
          <rate>0</rate>
        </config>
      </rate-limit>
    </rate-limits>
  </cpu-queue>

```

---

```
</hardware>
```

## Command Syntax

```
cpu-queue (best-effort|ipmc-miss|l3-
  miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)
  (no-monitor|monitor) (lossless|lossy) rate <0-100000>
```

---

## Configure rate-limits queue-name

This attribute specifies CPU queue name for rate limiting config

Attribute Name: queue-name

Attribute Type: enum (best-effort|ipmc-miss|l3-miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)

Attribute Name: lossy

Attribute Type: enum (lossless|lossy)

Attribute Name: rate

Attribute Type: int32

Attribute Range: 0-100000

Attribute Name: monitor

Attribute Type: enum (no-monitor|monitor)

## Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-queue>
    <rate-limits>
      <rate-limit>
        <queue-name>best-effort</queue-name>
        <config>
          <queue-name>best-effort</queue-name>
          <lossy>lossless</lossy>
          <rate>0</rate>
          <monitor>no-monitor</monitor>
        </config>
      </rate-limit>
    </rate-limits>
  </cpu-queue>
</hardware>
```

## Command Syntax

```
cpu-queue (best-effort|ipmc-miss|l3-
  miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)
  (lossless|lossy) rate <0-100000> (no-monitor|monitor)
```

---

## Configure rate-limits queue-name

This attribute specifies CPU queue name for rate limiting config

---

Attribute Name: queue-name

Attribute Type: enum (best-effort|ipmc-miss|l3-miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)

Attribute Name: lossy

Attribute Type: enum (lossless|lossy)

Attribute Name: monitor

Attribute Type: enum (no-monitor|monitor)

Attribute Name: rate

Attribute Type: int32

Attribute Range: 0-100000

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-queue>
    <rate-limits>
      <rate-limit>
        <queue-name>best-effort</queue-name>
        <config>
          <queue-name>best-effort</queue-name>
          <lossy>lossless</lossy>
          <monitor>no-monitor</monitor>
          <rate>0</rate>
        </config>
      </rate-limit>
    </rate-limits>
  </cpu-queue>
</hardware>
```

### Command Syntax

```
cpu-queue (best-effort|ipmc-miss|l3-
  miss|sflow|bgp|vrrp|rip|ospf|dhcp|nd|pim|arp|igmp|bpdu|ccm|bfd|isis|acl|vxlan)
  (lossless|lossy) (no-monitor|monitor) rate <0-100000>
```

---

### cpu-q-default rate <0-100000>

Attribute Name: rate

Attribute Type: uint32

Attribute Range: 0-100000

### Netconf RPC payload

```
<ipi-platform-profile_platform-profile-cpu-q-rate-set xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-platform">
  <rate>0</rate>
</ipi-platform-profile_platform-profile-cpu-q-rate-set>
```

---

## Command Syntax

```
cpu-q-default rate <0-100000>
```

---

## no cpu-q-default rate

Attribute Name: rate

Attribute Type: empty

## Netconf RPC payload

```
<ipi-platform-profile_platform-profile-cpu-q-rate-unset xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <rate>CML_EMPTY_T</rate>
</ipi-platform-profile_platform-profile-cpu-q-rate-unset>
```

## Command Syntax

```
no cpu-q-default rate
```

---

# IPI-PLATFORM-PROFILE-EXTENDED

---

## Configure enable mac ageing timer

Use this command to enable or disable the MAC ageing timer calculation in control plane

This command is supported when following feature are disabled marvell feature

Attribute Name: enable-mac-ageing-timer

Attribute Type: empty

## Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <mac-ageing>
    <config>
      </enable-mac-ageing-timer><!-- operation="delete"-->
    </config>
  </mac-ageing>
</hardware>
```

## Command Syntax

```
mac-ageing-display
```

---

## Configure soc

Attribute to indicate the SoC running on this platform. This attribute cannot be configured.

This command is supported when following feature are disabled marvell feature

Attribute Name: soc

Attribute Type: enum

(qax|qux|qmx|dnx|tomahawk|tomahawk2|tomahawk3|tomahawkplus|trident2|trident2plus|trident3|helix4|saber2|maverick2|hurricane4|trident4|tomahawk4|unknown)

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <platform>
    <config>
      <soc>qax</soc> <!-- operation="delete"-->
    </config>
  </platform>
</hardware>
```

### Command Syntax

```
platform-extended-soc
  (qax|qux|qmx|dnx|tomahawk|tomahawk2|tomahawk3|tomahawkplus|trident2|trident2plus
  |trident3|helix4|saber2|maverick2|hurricane4|trident4|tomahawk4|unknown)
```

---

## Configure lpm banks

Use this attribute to set Sets memory allocation profile - Use 'show forwarding profile limit' to check size

This command is supported when following feature are enabled bcm uft feature and following feature are disabled dune feature,marvell feature

Attribute Name: lpm-banks

Attribute Type: enum (2)

Attribute Name: l2-banks

Attribute Type: uint8

Attribute Range: 1-24

Attribute Name: l3-banks

Attribute Type: uint8

Attribute Range: 1-23

### Netconf edit-config payload

```
<profiles xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <forwarding-profiles>
    <custom-profile>
      <config>
        <l2-banks>1</l2-banks> <!-- operation="delete"-->
        <l3-banks>1</l3-banks> <!-- operation="delete"-->
        <lpm-banks>2</lpm-banks> <!-- operation="delete"-->
      </config>
    </custom-profile>
  </forwarding-profiles>
</profiles>
```

### Command Syntax

```
forwarding custom-profile { l2-banks <1-24>| l3-banks <1-23>| lpm-banks (2) }
```

---

## Configure ep vlan xlate banks

Use this attribute to set Sets memory allocation profile - Use 'show forwarding profile limit' to check size

This command is supported when following feature are enabled bcm uft feature and following feature are disabled dune feature,marvell feature

Attribute Name: ep-vlan-xlate-banks

Attribute Type: uint8

Attribute Range: 1-23

Attribute Name: l2-banks

Attribute Type: uint8

Attribute Range: 1-24

Attribute Name: l3-banks

Attribute Type: uint8

Attribute Range: 1-23

Attribute Name: vlan-xlate-banks

Attribute Type: uint8

Attribute Range: 1-23

### Netconf edit-config payload

```
<profiles xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <forwarding-profiles>
    <custom-profile>
      <config>
        <l2-banks>1</l2-banks> <!-- operation="delete"-->
        <l3-banks>1</l3-banks> <!-- operation="delete"-->
        <vlan-xlate-banks>1</vlan-xlate-banks> <!-- operation="delete"-->
        <ep-vlan-xlate-banks>1</ep-vlan-xlate-banks> <!-- operation="delete"-->
      </config>
    </custom-profile>
  </forwarding-profiles>
</profiles>
```

### Command Syntax

```
forwarding custom-profile { l2-banks <1-24>| l3-banks <1-23>| vlan-xlate-banks <1-23>| ep-vlan-xlate-banks <1-23> }
```

---

## Configure outer l3 header

Used to set Load balance tunneled packets based on outer header

This command is supported when following feature are enabled L3 feature and following feature are disabled dune feature,marvell feature

Attribute Name: outer-l3-header

Attribute Type: empty

## Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
    <tunnel>
      <config>
        </outer-l3-header><!-- operation="delete"-->
      </config>
    </tunnel>
  </load-balance>
</hardware>
```

## Command Syntax

```
load-balance rtag7 tunnel outer-l3-header
```

---

## Configure dest mac based

VXLAN Destination MAC address based load balancing

This command is supported when following feature are enabled vxlan feature and following feature are disabled dune feature,marvell feature

Attribute Name: dest-mac-based

Attribute Type: empty

Attribute Name: src-mac-based

Attribute Type: empty

## Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
    <vxlan>
      <inner-l2>
        <config>
          </src-mac-based><!-- operation="delete"-->
          </dest-mac-based><!-- operation="delete"-->
        </config>
      </inner-l2>
    </vxlan>
  </load-balance>
</hardware>
```

## Command Syntax

```
load-balance rtag7 vxlan inner-l2 { dest-mac| src-mac }
```

---

## Configure src ip based

VXLAN Source IP

This command is supported when following feature are enabled vxlan feature and following feature are disabled dune feature,marvell feature

Attribute Name: src-ip-based

Attribute Type: empty

Attribute Name: dest-ip-based

Attribute Type: empty

Attribute Name: src-l4-port-based

Attribute Type: empty

Attribute Name: dest-l4-port-based

Attribute Type: empty

Attribute Name: protocol-id-based

Attribute Type: empty

### Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
    <vxlan>
      <inner-l3>
        <config>
          </dest-ip-based><!-- operation="delete"-->
          </src-l4-port-based><!-- operation="delete"-->
          </dest-l4-port-based><!-- operation="delete"-->
          </protocol-id-based><!-- operation="delete"-->
          </src-ip-based><!-- operation="delete"-->
        </config>
      </inner-l3>
    </vxlan>
  </load-balance>
</hardware>
```

### Command Syntax

```
load-balance rtag7 vxlan inner-l3 { src-ip| dest-ip| srcl4-port| destl4-port|
  protocol-id }
```

---

## Configure src mac based

mpls destination Mac address based load balancing

This command is supported when following feature are disabled dune feature,marvell feature

Attribute Name: dest-mac-based

Attribute Type: empty

Attribute Name: src-mac-based

Attribute Type: empty

Attribute Name: ether-type-based

Attribute Type: empty

Attribute Name: vlan-based

Attribute Type: empty

## Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
    <mpls-ler>
      <inner-l2>
        <config>
          </src-mac-based><!-- operation="delete"-->
          </ether-type-based><!-- operation="delete"-->
          </vlan-based><!-- operation="delete"-->
          </dest-mac-based><!-- operation="delete"-->
        </config>
      </inner-l2>
    </mpls-ler>
  </load-balance>
</hardware>
```

## Command Syntax

```
load-balance rtag7 mpls-ler inner-l2 { dest-mac | src-mac | ether-type | vlan }
```

---

## Configure src ip address based

### Source IP

This command is supported when following feature are disabled dune feature,marvell feature

Attribute Name: src-ip-address-based

Attribute Type: empty

Attribute Name: dest-ip-address-based

Attribute Type: empty

Attribute Name: src-l4-port-based

Attribute Type: empty

Attribute Name: dest-l4-port-based

Attribute Type: empty

Attribute Name: protocol-id-based

Attribute Type: empty

## Netconf edit-config payload

```
<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
    <mpls-ler>
      <inner-l3>
        <config>
          </dest-ip-address-based><!-- operation="delete"-->
          </src-l4-port-based><!-- operation="delete"-->
          </dest-l4-port-based><!-- operation="delete"-->
          </protocol-id-based><!-- operation="delete"-->
          </src-ip-address-based><!-- operation="delete"-->
        </config>
      </inner-l3>
    </mpls-ler>
  </load-balance>
</hardware>
```

```

    </config>
  </inner-l3>
</mpls-ler>
</load-balance>
</hardware>

```

### Command Syntax

```

load-balance rtag7 mpls-ler inner-l3 { src-ip| dest-ip| srcl4-port| destl4-port|
  protocol-id }

```

---

## Configure disable vxlan

This Object is to disable the control packets to CPU

This command is supported when following feature are enabled vxlan feature and following feature are disabled dune feature,marvell feature

Attribute Name: disable-vxlan

Attribute Type: empty

### Netconf edit-config payload

```

<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <cpu-control>
    <packets>
      <config>
        </disable-vxlan><!-- operation="delete"-->
      </config>
    </packets>
  </cpu-control>
</hardware>

```

### Command Syntax

```

l3-protocols-cpu-disable vxlan

```

---

## Configure type

This Object is used to set LACP port-channel load-balancing and set port selection criteria (PSC) on an interface

This command is supported when following feature are enabled lacp feature and following feature are disabled dune feature,marvell feature

Attribute Name: type

Attribute Type: enum (dst-mac|src-mac|src-dst-mac|src-ip|dst-ip|src-dst-ip|rtag7)

### Netconf edit-config payload

```

<hardware xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <load-balance>
    <port-channel>
      <interfaces>
        <interface>
          <name>WORD</name>

```

```

    <config>
      <name>WORD</name>
    </config>
    <type>dst-mac</type> <!-- operation="delete"-->
  </interface>
</interfaces>
</port-channel>
</load-balance>
</hardware>

```

### Command Syntax

```
port-channel load-balance (dst-mac|src-mac|src-dst-mac|src-ip|dst-ip|src-dst-
ip|rtag7)
```

---

## IPI-PLATFORM-CMIS

---

### Configure fp port

Front port panel number

Attribute Name: fp-port

Attribute Type: uint8

#### Netconf edit-config payload

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd> <!-- operation="delete"-->
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  </qsfp-dd>
</qsfp-dds>

```

### Command Syntax

```
qsfp-dd <0-255>
```

---

### Configure application

Application configuration

Attribute Name: application

Attribute Type: uint8

Attribute Range: 2-15

#### Netconf edit-config payload

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>

```

```
<config>
  <fp-port>0</fp-port>
</config>
<application>2</application> <!-- operation="delete"-->
</qsfp-dd>
</qsfp-dds>
```

### Command Syntax

```
application <2-15>
```

---

## Configure service disable

To disable the service for a particular port

Attribute Name: service-disable

Attribute Type: empty

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</service-disable><!-- operation="delete"-->
</qsfp-dd>
</qsfp-dds>
```

### Command Syntax

```
service-disable
```

---

## Configure custom app host id

Configuration of custom application host ID

Attribute Name: custom-app-host-id

Attribute Type: uint8

Attribute Range: 1-32

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
<custom-app-host-id>1</custom-app-host-id> <!-- operation="delete"-->
</qsfp-dd>
</qsfp-dds>
```

---

## Command Syntax

```
custom-app-host-id <1-32>
```

---

## Configure custom app media id

Configuration of custom application media ID

Attribute Name: custom-app-media-id

Attribute Type: uint8

Attribute Range: 1-32

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
    <custom-app-media-id>1</custom-app-media-id> <!-- operation="delete"-->
  </qsfp-dd>
</qsfp-dds>
```

## Command Syntax

```
custom-app-media-id <1-32>
```

---

## Configure type

PRBS pattern type for generator/checker

Attribute Name: type

Attribute Type: enum (31q|31|23q|23|15q|15|13q|13|9q|9|7q|7|ssprq)

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  <host>
    <prbs>
      <generator>
        <config>
          <type>31q</type> <!-- operation="delete"-->
        </config>
      </generator>
    </prbs>
  </host>
</qsfp-dd>
```

```
</qsfp-dds>
```

## Command Syntax

```
prbs generator type (31q|31|23q|23|15q|15|13q|13|9q|9|7q|7|ssprq) host
```

---

## Configure location

PRBS pattern generator/checker location

Attribute Name: location

Attribute Type: enum (pre-fec|post-fec)

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</host>
</prbs>
</generator>
</config>
  <location>pre-fec</location> <!-- operation="delete"-->
</config>
</generator>
</prbs>
</host>
</qsfp-dd>
</qsfp-dds>
```

## Command Syntax

```
prbs generator (pre-fec|post-fec) host
```

---

## Configure checker type

PRBS pattern type for generator/checker

Attribute Name: type

Attribute Type: enum (31q|31|23q|23|15q|15|13q|13|9q|9|7q|7|ssprq)

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</host>
</prbs>
```

```

<checker>
<config>
  <type>31q</type> <!-- operation="delete"-->
</config>
</checker>
</prbs>
</host>
</qsfp-dd>
</qsfp-dds>

```

### Command Syntax

```
prbs checker type (31q|31|23q|23|15q|15|13q|13|9q|9|7q|7|ssprq) host
```

---

## Configure checker location

PRBS pattern generator/checker location

Attribute Name: location

Attribute Type: enum (pre-fec|post-fec)

### Netconf edit-config payload

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</host>
</prbs>
<checker>
<config>
  <location>pre-fec</location> <!-- operation="delete"-->
</config>
</checker>
</prbs>
</host>
</qsfp-dd>
</qsfp-dds>

```

### Command Syntax

```
prbs checker (pre-fec|post-fec) host
```

---

## Configure loopback type

Loopback type

Attribute Name: type

Attribute Type: enum (in|out|both)

**Netconf edit-config payload**

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</host>
<loopback>
<config>
  <type>in</type> <!-- operation="delete"-->
</config>
</loopback>
</host>
</qsfp-dd>
</qsfp-dds>

```

**Command Syntax**

```
loopback (in|out|both) host
```

**Configure lane number**

Host lane number

Attribute Name: lane-number

Attribute Type: uint8

**Netconf edit-config payload**

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</host>
<lanes>
<lane> <!-- operation="delete"-->
  <lane-number>1</lane-number>
  <config>
    <lane-number>1</lane-number>
  </config>
</lane>
</lanes>
</host>
</qsfp-dd>
</qsfp-dds>

```

**Command Syntax**

```
host-lane <1-32>
```

---

## Configure id

Threshold ID

Attribute Name: id

Attribute Type: enum (tx-fdd|tx-fed)

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  </qsfp-dd>
  <host>
  <lanes>
  <lane>
    <lane-number>1</lane-number>
    <config>
      <lane-number>1</lane-number>
    </config>
    <thresholds>
    <threshold> <!-- operation="delete"-->
      <id>tx-fdd</id>
      <config>
        <id>tx-fdd</id>
      </config>
    </threshold>
  </thresholds>
</lane>
</lanes>
</host>
</qsfp-dd>
</qsfp-dds>
```

### Command Syntax

```
threshold (tx-fdd|tx-fed)
```

---

## Configure high alarm

High alarm threshold

Attribute Name: high-alarm

Attribute Type: decimal64

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
```

```

        <fp-port>0</fp-port>
    </config>
</host>
</lanes>
</lane>
    <lane-number>1</lane-number>
    <config>
        <lane-number>1</lane-number>
    </config>
    <thresholds>
    <threshold>
        <id>tx-fdd</id>
        <config>
            <id>tx-fdd</id>
        </config>
        <high-alarm>VALUE</high-alarm> <!-- operation="delete"-->
    </threshold>
</thresholds>
</lane>
</lanes>
</host>
</qsfp-dd>
</qsfp-dds>

```

## Command Syntax

```
ha VALUE
```

---

## Configure low alarm

Low alarm threshold

Attribute Name: low-alarm

Attribute Type: decimal64

### Netconf edit-config payload

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  </qsfp-dd>
</qsfp-dds>
</host>
</lanes>
</lane>
    <lane-number>1</lane-number>
    <config>
        <lane-number>1</lane-number>
    </config>
    <thresholds>
    <threshold>

```

```

    <id>tx-fdd</id>
    <config>
      <id>tx-fdd</id>
    </config>
    <low-alarm>VALUE</low-alarm> <!-- operation="delete"-->
  </threshold>
</thresholds>
</lane>
</lanes>
</host>
</qsfp-dd>
</qsfp-dds>

```

## Command Syntax

```
la VALUE
```

---

## Configure high warning

High warn threshold

Attribute Name: high-warning

Attribute Type: decimal64

### Netconf edit-config payload

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  </qsfp-dd>
</qsfp-dds>
<host>
<lanes>
<lane>
  <lane-number>1</lane-number>
  <config>
    <lane-number>1</lane-number>
  </config>
  <thresholds>
  <threshold>
    <id>tx-fdd</id>
    <config>
      <id>tx-fdd</id>
    </config>
    <high-warning>VALUE</high-warning> <!-- operation="delete"-->
  </threshold>
</thresholds>
</lane>
</lanes>
</host>
</qsfp-dd>

```

---

```
</qsfp-dds>
```

## Command Syntax

```
hw VALUE
```

---

## Configure low warning

Low warn threshold

Attribute Name: low-warning

Attribute Type: decimal64

## Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</host>
<lanes>
<lane>
  <lane-number>1</lane-number>
  <config>
    <lane-number>1</lane-number>
  </config>
  <thresholds>
  <threshold>
    <id>tx-fdd</id>
    <config>
      <id>tx-fdd</id>
    </config>
    <low-warning>VALUE</low-warning> <!-- operation="delete"-->
  </threshold>
</thresholds>
</lane>
</lanes>
</host>
</qsfp-dd>
</qsfp-dds>
```

## Command Syntax

```
lw VALUE
```

---

## Configure tx input equalizer target

Tx input equalizer target value code

Attribute Name: tx-input-equalizer-target

Attribute Type: uint8

Attribute Range: 1-15

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</host>
<lanes>
<lane>
  <lane-number>1</lane-number>
  <config>
    <lane-number>1</lane-number>
  </config>
  <signal-integrity>
  <config>
    <tx-input-equalizer-target>1</tx-input-equalizer-target> <!--
operation="delete"-->
  </config>
</signal-integrity>
</lane>
</lanes>
</host>
</qsfp-dd>
</qsfp-dds>
```

### Command Syntax

```
tx-input eq-target <1-15>
```

---

## Configure rx output equalizer pre cursor target

Rx output equalizer pre-cursor target value code

Attribute Name: rx-output-equalizer-pre-cursor-target

Attribute Type: uint8

Attribute Range: 1-15

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</host>
<lanes>
<lane>
  <lane-number>1</lane-number>
```

```

    <config>
      <lane-number>1</lane-number>
    </config>
  </signal-integrity>
</config>
  <rx-output-equalizer-pre-cursor-target>1</rx-output-equalizer-pre-cursor-
target> <!-- operation="delete"-->
  </config>
</signal-integrity>
</lane>
</lanes>
</host>
</qsfp-dd>
</qsfp-dds>

```

### Command Syntax

```
rx-output eq-pre-cursor-target <1-15>
```

---

## Configure rx output equalizer post cursor target

Rx output equalizer post-cursor target value code

Attribute Name: rx-output-equalizer-post-cursor-target

Attribute Type: uint8

Attribute Range: 1-15

### Netconf edit-config payload

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  </qsfp-dd>
  <host>
    <lanes>
      <lane>
        <lane-number>1</lane-number>
        <config>
          <lane-number>1</lane-number>
        </config>
        <signal-integrity>
          <config>
            <rx-output-equalizer-post-cursor-target>1</rx-output-equalizer-post-
cursor-target> <!-- operation="delete"-->
          </config>
        </signal-integrity>
      </lane>
    </lanes>
  </host>
</qsfp-dd>

```

```
</qsfp-dds>
```

## Command Syntax

```
rx-output eq-post-cursor-target <1-15>
```

---

## Configure rx output amplitude target

Rx output equalizer amplitude target value code

Attribute Name: rx-output-amplitude-target

Attribute Type: uint8

Attribute Range: 0-15

## Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  <host>
    <lanes>
      <lane>
        <lane-number>1</lane-number>
        <config>
          <lane-number>1</lane-number>
        </config>
        <signal-integrity>
          <config>
            <rx-output-amplitude-target>0</rx-output-amplitude-target> <!--
operation="delete"-->
          </config>
        </signal-integrity>
      </lane>
    </lanes>
  </host>
</qsfp-dd>
</qsfp-dds>
```

## Command Syntax

```
rx-output amp-target <0-15>
```

---

## Configure tx cdr bypass

Bypass the TX CDR control

Attribute Name: tx-cdr-bypass

Attribute Type: empty

**Netconf edit-config payload**

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</host>
</lanes>
<lane>
  <lane-number>1</lane-number>
  <config>
    <lane-number>1</lane-number>
  </config>
  <signal-integrity>
  <config>
    </tx-cdr-bypass><!-- operation="delete"-->
  </config>
</signal-integrity>
</lane>
</lanes>
</host>
</qsfp-dd>
</qsfp-dds>

```

**Command Syntax**

```
tx cdr-bypass
```

---

**Configure rx cdr bypass**

Bypass the CDR control

Attribute Name: rx-cdr-bypass

Attribute Type: empty

**Netconf edit-config payload**

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</host>
</lanes>
<lane>
  <lane-number>1</lane-number>
  <config>
    <lane-number>1</lane-number>
  </config>
  <signal-integrity>

```

```

    <config>
      </rx-cdr-bypass><!-- operation="delete"-->
    </config>
  </signal-integrity>
</lane>
</lanes>
</host>
</qsfp-dd>
</qsfp-dds>

```

### Command Syntax

```
rx cdr-bypass
```

---

## Configure generator type

PRBS pattern type for generator/checker

Attribute Name: type

Attribute Type: enum (31q|31|23q|23|15q|15|13q|13|9q|9|7q|7|ssprq)

### Netconf edit-config payload

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  <media>
    <prbs>
      <generator>
        <config>
          <type>31q</type> <!-- operation="delete"-->
        </config>
      </generator>
    </prbs>
  </media>
</qsfp-dd>
</qsfp-dds>

```

### Command Syntax

```
prbs generator type (31q|31|23q|23|15q|15|13q|13|9q|9|7q|7|ssprq) media
```

---

## Configure generator location

PRBS pattern generator/checker location

Attribute Name: location

Attribute Type: enum (pre-fec|post-fec)

## Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</media>
</prbs>
</generator>
</config>
  <location>pre-fec</location> <!-- operation="delete"-->
</config>
</generator>
</prbs>
</media>
</qsfp-dd>
</qsfp-dds>
```

## Command Syntax

```
prbs generator (pre-fec|post-fec) media
```

---

## Configure checker type

PRBS pattern type for generator/checker

Attribute Name: type

Attribute Type: enum (31q|31|23q|23|15q|15|13q|13|9q|9|7q|7|ssprq)

## Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</media>
</prbs>
<checker>
</config>
  <type>31q</type> <!-- operation="delete"-->
</config>
</checker>
</prbs>
</media>
</qsfp-dd>
</qsfp-dds>
```

## Command Syntax

```
prbs checker type (31q|31|23q|23|15q|15|13q|13|9q|9|7q|7|ssprq) media
```

---

## Configure checker location

PRBS pattern generator/checker location

Attribute Name: location

Attribute Type: enum (pre-fec|post-fec)

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  </qsfp-dd>
  <media>
    <prbs>
      <checker>
        <config>
          <location>pre-fec</location> <!-- operation="delete"-->
        </config>
      </checker>
    </prbs>
  </media>
</qsfp-dd>
</qsfp-dds>
```

### Command Syntax

```
prbs checker (pre-fec|post-fec) media
```

---

## Configure loopback type

Loopback type

Attribute Name: type

Attribute Type: enum (in|out|both)

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  </qsfp-dd>
  <media>
    <loopback>
      <config>
        <type>in</type> <!-- operation="delete"-->
      </config>
    </loopback>
  </media>
</qsfp-dds>
```

```
</qsfp-dd>  
</qsfp-dds>
```

## Command Syntax

```
loopback (in|out|both) media
```

---

## Configure lanes lane-number

Media lane number

Attribute Name: lane-number

Attribute Type: uint8

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">  
<qsfp-dd>  
  <fp-port>0</fp-port>  
  <config>  
    <fp-port>0</fp-port>  
  </config>  
</media>  
<lanes>  
<lane> <!-- operation="delete"-->  
  <lane-number>1</lane-number>  
  <config>  
    <lane-number>1</lane-number>  
  </config>  
</lane>  
</lanes>  
</media>  
</qsfp-dd>  
</qsfp-dds>
```

## Command Syntax

```
media-lane <1-32>
```

---

## Configure channel

Channel number

Attribute Name: channel

Attribute Type: int16

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">  
<qsfp-dd>  
  <fp-port>0</fp-port>  
  <config>  
    <fp-port>0</fp-port>  
  </config>
```

```

<media>
<lanes>
<lane>
  <lane-number>1</lane-number>
  <config>
    <lane-number>1</lane-number>
  </config>
  <laser>
  <config>
    <channel>0</channel>
  </config>
</laser>
</lane>
</lanes>
</media>
</qsfp-dd>
</qsfp-dds>

```

### Command Syntax

```
laser channel <-32768-32767>
```

---

## Configure grid

Grid spacing

Attribute Name: grid

Attribute Type: enum (3p125|6p25|12p5|25|33|50|75|100)

### Netconf edit-config payload

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
<media>
<lanes>
<lane>
  <lane-number>1</lane-number>
  <config>
    <lane-number>1</lane-number>
  </config>
  <laser>
  <config>
    <grid>3p125</grid> <!-- operation="delete"-->
  </config>
</laser>
</lane>
</lanes>
</media>

```

```
</qsfp-dd>
</qsfp-dds>
```

## Command Syntax

```
laser grid (3p125|6p25|12p5|25|33|50|75|100)
```

---

## Configure fine tune freq

Fine tune frequency offset

Attribute Name: fine-tune-freq

Attribute Type: decimal64

## Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</media>
<lanes>
<lane>
  <lane-number>1</lane-number>
  <config>
    <lane-number>1</lane-number>
  </config>
  <laser>
  <config>
    <fine-tune-freq>VALUE</fine-tune-freq> <!-- operation="delete"-->
  </config>
</laser>
</lane>
</lanes>
</media>
</qsfp-dd>
</qsfp-dds>
```

## Command Syntax

```
laser fine-tune-freq VALUE
```

---

## Configure output power

Targeted output power

Attribute Name: output-power

Attribute Type: decimal64

## Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
```

```

<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
<media>
<lanes>
<lane>
  <lane-number>1</lane-number>
  <config>
    <lane-number>1</lane-number>
  </config>
  <laser>
  <config>
    <output-power>VALUE</output-power> <!-- operation="delete"-->
  </config>
</laser>
</lane>
</lanes>
</media>
</qsfp-dd>
</qsfp-dds>

```

## Command Syntax

```
laser output-power VALUE
```

---

## Configure thresholds id

Threshold ID

Attribute Name: id

Attribute Type: enum (rx-fdd|rx-fed|rx-total-power|rx-signal-power)

### Netconf edit-config payload

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  <media>
  <lanes>
  <lane>
    <lane-number>1</lane-number>
    <config>
      <lane-number>1</lane-number>
    </config>
    <thresholds>
    <threshold> <!-- operation="delete"-->
      <id>rx-fdd</id>

```

```

    <config>
      <id>rx-fdd</id>
    </config>
  </threshold>
</thresholds>
</lane>
</lanes>
</media>
</qsfp-dd>
</qsfp-dds>

```

## Command Syntax

```
threshold (rx-fdd|rx-fed|rx-total-power|rx-signal-power)
```

---

## Configure threshold high-alarm

High alarm threshold

Attribute Name: high-alarm

Attribute Type: decimal64

### Netconf edit-config payload

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  <media>
  <lanes>
  <lane>
    <lane-number>1</lane-number>
    <config>
      <lane-number>1</lane-number>
    </config>
    <thresholds>
    <threshold>
      <id>rx-fdd</id>
      <config>
        <id>rx-fdd</id>
      </config>
      <high-alarm>VALUE</high-alarm> <!-- operation="delete"-->
    </threshold>
  </thresholds>
</lane>
</lanes>
</media>
</qsfp-dd>
</qsfp-dds>

```

---

## Command Syntax

ha VALUE

---

## Configure threshold low-alarm

Low alarm threshold

Attribute Name: low-alarm

Attribute Type: decimal64

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  </qsfp-dd>
  <media>
    <lanes>
      <lane>
        <lane-number>1</lane-number>
        <config>
          <lane-number>1</lane-number>
        </config>
        <thresholds>
          <threshold>
            <id>rx-fdd</id>
            <config>
              <id>rx-fdd</id>
              <low-alarm>VALUE</low-alarm> <!-- operation="delete"-->
            </config>
          </threshold>
        </thresholds>
      </lane>
    </lanes>
  </media>
</qsfp-dd>
</qsfp-dds>
```

## Command Syntax

la VALUE

---

## Configure threshold high-warning

High warn threshold

Attribute Name: high-warning

Attribute Type: decimal64

**Netconf edit-config payload**

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</media>
</lanes>
<lane>
  <lane-number>1</lane-number>
  <config>
    <lane-number>1</lane-number>
  </config>
  <thresholds>
  <threshold>
    <id>rx-fdd</id>
    <config>
      <id>rx-fdd</id>
    </config>
    <high-warning>VALUE</high-warning> <!-- operation="delete"-->
  </threshold>
</thresholds>
</lane>
</lanes>
</media>
</qsfp-dd>
</qsfp-dds>

```

**Command Syntax**

```
hw VALUE
```

**Configure threshold low-warning**

Low warn threshold

Attribute Name: low-warning

Attribute Type: decimal64

**Netconf edit-config payload**

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</media>
</lanes>
<lane>
  <lane-number>1</lane-number>

```

```

<config>
  <lane-number>1</lane-number>
</config>
<thresholds>
<threshold>
  <id>rx-fdd</id>
  <config>
    <id>rx-fdd</id>
  </config>
  <low-warning>VALUE</low-warning> <!-- operation="delete"-->
</threshold>
</thresholds>
</lane>
</lanes>
</media>
</qsfp-dd>
</qsfp-dds>

```

### Command Syntax

```
lw VALUE
```

---

## Configure laser channel

Channel number

Attribute Name: channel

Attribute Type: int16

### Netconf edit-config payload

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
</qsfp-dd>
</qsfp-dds>

```

### Command Syntax

```
laser channel <-32768-32767>
```

---

## Configure laser grid

Grid spacing

Attribute Name: grid

Attribute Type: enum (3p125|6p25|12p5|25|33|50|75|100)

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  </qsfp-dd>
  <config>
    <grid>3p125</grid> <!-- operation="delete"-->
  </config>
</qsfp-dds>
```

### Command Syntax

```
laser grid (3p125|6p25|12p5|25|33|50|75|100)
```

---

## Configure laser fine-tune-freq

Fine tune frequency offset

Attribute Name: fine-tune-freq

Attribute Type: decimal64

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  </qsfp-dd>
  <config>
    <fine-tune-freq>VALUE</fine-tune-freq> <!-- operation="delete"-->
  </config>
</qsfp-dds>
```

### Command Syntax

```
laser fine-tune-freq VALUE
```

---

## Configure laser output-power

Targeted output power

Attribute Name: output-power

Attribute Type: decimal64

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  </qsfp-dd>
  <config>
    <output-power>VALUE</output-power> <!-- operation="delete"-->
  </config>
</qsfp-dds>
```

### Command Syntax

```
laser output-power VALUE
```

---

## Configure thresholds id

Threshold ID

Attribute Name: id

Attribute Type: enum (rx-fdd|rx-fed|rx-total-power|rx-signal-power|tx-fdd|tx-fed)

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  <thresholds>
    <threshold> <!-- operation="delete"-->
      <id>rx-fdd</id>
      <config>
        <id>rx-fdd</id>
      </config>
    </threshold>
  </thresholds>
</qsfp-dds>
```

### Command Syntax

```
threshold (rx-fdd|rx-fed|rx-total-power|rx-signal-power|tx-fdd|tx-fed)
```

---

## Configure threshold high-alarm

High alarm threshold

Attribute Name: high-alarm

Attribute Type: decimal64

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  </qsfp-dd>
  <thresholds>
  <threshold>
    <id>rx-fdd</id>
    <config>
      <id>rx-fdd</id>
      <high-alarm>VALUE</high-alarm> <!-- operation="delete"-->
    </config>
  </threshold>
</thresholds>
</qsfp-dds>
```

### Command Syntax

```
ha VALUE
```

---

## Configure threshold low-alarm

Low alarm threshold

Attribute Name: low-alarm

Attribute Type: decimal64

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  </qsfp-dd>
  <thresholds>
  <threshold>
    <id>rx-fdd</id>
    <config>
      <id>rx-fdd</id>
      <low-alarm>VALUE</low-alarm> <!-- operation="delete"-->
    </config>
  </threshold>
</thresholds>
</qsfp-dds>
```

```
</threshold>  
</thresholds>  
</qsfp-dd>  
</qsfp-dds>
```

## Command Syntax

```
la VALUE
```

---

## Configure threshold high-warning

High warn threshold

Attribute Name: high-warning

Attribute Type: decimal64

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">  
<qsfp-dd>  
  <fp-port>0</fp-port>  
  <config>  
    <fp-port>0</fp-port>  
  </config>  
</thresholds>  
<threshold>  
  <id>rx-fdd</id>  
  <config>  
    <id>rx-fdd</id>  
    <high-warning>VALUE</high-warning> <!-- operation="delete"-->  
</threshold>  
</thresholds>  
</qsfp-dd>  
</qsfp-dds>
```

## Command Syntax

```
hw VALUE
```

---

## Configure threshold low-warning

Low warn threshold

Attribute Name: low-warning

Attribute Type: decimal64

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">  
<qsfp-dd>  
  <fp-port>0</fp-port>  
  <config>  
    <fp-port>0</fp-port>
```

```

    </config>
  <thresholds>
  <threshold>
    <id>rx-fdd</id>
    <config>
      <id>rx-fdd</id>
    </config>
    <low-warning>VALUE</low-warning> <!-- operation="delete"-->
  </threshold>
</thresholds>
</qsfp-dd>
</qsfp-dds>

```

### Command Syntax

```
lw VALUE
```

---

## Configure signal-integrity tx-input-equalizer-target

Tx input equalizer target value code

Attribute Name: tx-input-equalizer-target

Attribute Type: uint8

Attribute Range: 1-15

### Netconf edit-config payload

```

<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  <signal-integrity>
    <config>
      <tx-input-equalizer-target>1</tx-input-equalizer-target> <!--
operation="delete"-->
    </config>
  </signal-integrity>
</qsfp-dd>
</qsfp-dds>

```

### Command Syntax

```
tx-input eq-target <1-15>
```

---

## Configure signal-integrity rx-output-equalizer-pre-cursor-target

Rx output equalizer pre-cursor target value code

Attribute Name: rx-output-equalizer-pre-cursor-target

Attribute Type: uint8

Attribute Range: 1-15

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
<signal-integrity>
<config>
  <rx-output-equalizer-pre-cursor-target>1</rx-output-equalizer-pre-cursor-
target> <!-- operation="delete"-->
</config>
</signal-integrity>
</qsfp-dd>
</qsfp-dds>
```

### Command Syntax

```
rx-output eq-pre-cursor-target <1-15>
```

---

## Configure signal-integrity rx-output-equalizer-post-cursor-target

Rx output equalizer post-cursor target value code

Attribute Name: rx-output-equalizer-post-cursor-target

Attribute Type: uint8

Attribute Range: 1-15

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
<qsfp-dd>
  <fp-port>0</fp-port>
  <config>
    <fp-port>0</fp-port>
  </config>
<signal-integrity>
<config>
  <rx-output-equalizer-post-cursor-target>1</rx-output-equalizer-post-cursor-
target> <!-- operation="delete"-->
</config>
</signal-integrity>
</qsfp-dd>
</qsfp-dds>
```

### Command Syntax

```
rx-output eq-post-cursor-target <1-15>
```

---

## Configure signal-integrity rx-output-amplitude-target

Rx output equalizer amplitude target value code

Attribute Name: rx-output-amplitude-target

Attribute Type: uint8

Attribute Range: 0-15

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  <signal-integrity>
    <config>
      <rx-output-amplitude-target>0</rx-output-amplitude-target> <!--
operation="delete"-->
    </config>
  </signal-integrity>
</qsfp-dd>
</qsfp-dds>
```

### Command Syntax

```
rx-output amp-target <0-15>
```

---

## Configure signal-integrity tx-cdr-bypass

Bypass the TX CDR control

Attribute Name: tx-cdr-bypass

Attribute Type: empty

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  <signal-integrity>
    <config>
      </tx-cdr-bypass><!-- operation="delete"-->
    </config>
  </signal-integrity>
</qsfp-dd>
</qsfp-dds>
```

## Command Syntax

```
tx cdr-bypass
```

---

## Configure signal-integrity rx-cdr-bypass

Bypass the CDR control

Attribute Name: rx-cdr-bypass

Attribute Type: empty

### Netconf edit-config payload

```
<qsfp-dds xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <qsfp-dd>
    <fp-port>0</fp-port>
    <config>
      <fp-port>0</fp-port>
    </config>
  </qsfp-dd>
  <signal-integrity>
    <config>
      </rx-cdr-bypass><!-- operation="delete"-->
    </config>
  </signal-integrity>
</qsfp-dds>
```

## Command Syntax

```
rx cdr-bypass
```

---

## tibit-olt-microplug set interface IFNAME management-vlan-tpid (0x8100|0x88a8)

Attribute Name: interface-name

Attribute Type: string

Attribute Name: vlan-tpid

Attribute Type: string

### Netconf RPC payload

```
<ipi-platform-transceiver-tibit_tibit-olt-microplug-set-management-vlan-tpid
xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <interface-name>IFNAME</interface-name>
  <vlan-tpid>0x8100</vlan-tpid>
</ipi-platform-transceiver-tibit_tibit-olt-microplug-set-management-vlan-tpid>
```

## Command Syntax

```
tibit-olt-microplug set interface IFNAME management-vlan-tpid (0x8100|0x88a8)
```

---

## **tibit-olt-microplug set interface IFNAME management-vlan-id <1-4094>**

Attribute Name: interface-name

Attribute Type: string

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

### **Netconf RPC payload**

```
<ipi-platform-transceiver-tibit_tibit-olt-microplug-set-management-vlan-id
xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <interface-name>IFNAME</interface-name>
  <vlan-id>1</vlan-id>
</ipi-platform-transceiver-tibit_tibit-olt-microplug-set-management-vlan-id>
```

### **Command Syntax**

```
tibit-olt-microplug set interface IFNAME management-vlan-id <1-4094>
```

---

## **tibit-olt-microplug set interface IFNAME ethernet-mac-address XX:XX:XX:XX:XX:XX**

Attribute Name: interface-name

Attribute Type: string

Attribute Name: mac-address

Attribute Type: yang:mac-address

### **Netconf RPC payload**

```
<ipi-platform-transceiver-tibit_tibit-olt-microplug-set-ethernet-mac-address
xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
  <interface-name>IFNAME</interface-name>
  <mac-address>XX:XX:XX:XX:XX:XX</mac-address>
</ipi-platform-transceiver-tibit_tibit-olt-microplug-set-ethernet-mac-address>
```

### **Command Syntax**

```
tibit-olt-microplug set interface IFNAME ethernet-mac-address XX:XX:XX:XX:XX:XX
```

---

## **tibit-olt-microplug set interface IFNAME next-active-firmware-bank-id <0-3>**

Attribute Name: interface-name

Attribute Type: string

Attribute Name: bank-id

Attribute Type: uint8

Attribute Range: 0-3

## Netconf RPC payload

```

    <ipi-platform-transceiver-tibit_tibit-olt-microplug-set-next-active-firmware-
bank xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform">
    <interface-name>IFNAME</interface-name>
    <bank-id>0</bank-id>
    </ipi-platform-transceiver-tibit_tibit-olt-microplug-set-next-active-firmware-
bank>

```

## Command Syntax

```
tibit-olt-microplug set interface IFNAME next-active-firmware-bank-id <0-3>
```

---

## tibit-olt-microplug reboot interface IFNAME

Attribute Name: interface-name

Attribute Type: string

## Netconf RPC payload

```

    <ipi-platform-transceiver-tibit_tibit-olt-microplug-reboot xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-platform">
    <interface-name>IFNAME</interface-name>
    </ipi-platform-transceiver-tibit_tibit-olt-microplug-reboot>

```

## Command Syntax

```
tibit-olt-microplug reboot interface IFNAME
```

---

## IPI-PLATFORM-TRANSCEIVER-SMART-SFP

### Configure xcvr loopback remote

Use this attribute to set TX/RX loopback for remote

Attribute Name: xcvr-loopback-remote

Attribute Type: enum (in|out)

## Netconf edit-config payload

```

    <smart-sfp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-platform-transceiver-
smart-sfp">
    <interfaces>
    <interface>
        <interface-name>IFNAME</interface-name>
        <config>
            <interface-name>WORD</interface-name>
        </config>
        <xcvr-loopback-remote>in</xcvr-loopback-remote> <!-- operation="delete"-->
    </interface>
    </interfaces>
    </smart-sfp>

```

---

## Command Syntax

```
xcvr loopback (in|out) remote
```

---

## xcvr IFNAME tx-disable <1-256> remote

Attribute Name: if-name

Attribute Type: string

Attribute Name: xcvr-tx-disable-duration

Attribute Type: uint16

Attribute Range: 1-256

## Netconf RPC payload

```
<smart-sfp-xcvr-txdisable-duration xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-platform-transceiver-smart-sfp">
  <if-name>IFNAME</if-name>
  <xcvr-tx-disable-duration>1</xcvr-tx-disable-duration>
</smart-sfp-xcvr-txdisable-duration>
```

## Command Syntax

```
xcvr IFNAME tx-disable <1-256> remote
```

---

## xcvr IFNAME reset remote

Attribute Name: if-name

Attribute Type: string

## Netconf RPC payload

```
<smart-sfp-xcvr-reset-remote xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
platform-transceiver-smart-sfp">
  <if-name>IFNAME</if-name>
</smart-sfp-xcvr-reset-remote>
```

## Command Syntax

```
xcvr IFNAME reset remote
```

---

# IPI-AUTHENTICATION

---

## Configure mac authentication

Use this attribute to enable MAC authentication globally. If MAC authentication is not enabled, other MAC authentication related commands throw an error when issued.

This command is supported when following feature are enabled HAVE\_AUTHD feature

Attribute Name: mac-authentication

Attribute Type: empty

---

### Netconf edit-config payload

```
<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
  <global>
  <config>
    </mac-authentication><!-- operation="delete"-->
  </config>
</global>
</authentication>
```

### Command Syntax

```
auth-mac system-auth-ctrl
```

---

## Configure dot1x authentication

Use this attribute to enable globally authentication.

This command is supported when following feature are enabled HAVE\_AUTHD feature

Attribute Name: dot1x-authentication

Attribute Type: empty

### Netconf edit-config payload

```
<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
  <global>
  <config>
    </dot1x-authentication><!-- operation="delete"-->
  </config>
</global>
</authentication>
```

### Command Syntax

```
dot1x system-auth-ctrl
```

---

## Configure dot1x control

Use this attribute to enable or disable the 802.1X authentication control on an interface.

This command is supported when following feature are enabled HAVE\_AUTHD feature

Attribute Name: dot1x-control

Attribute Type: enum (force-unauthorized|force-authorized|auto)

### Netconf edit-config payload

```
<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
  <dot1x-interfaces>
  <dot1x-interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  <dot1x-control>force-authorized</dot1x-control>
```

```

</dot1x-interface>
</dot1x-interfaces>
</authentication>

```

## Command Syntax

```
dot1x port-control (force-unauthorized|force-authorized|auto)
```

---

## Configure protocol version

Use this attribute to set the protocol version of dot1x to 1 or 2. The protocol version must be synchronized with the Xsupplicant being used in that interface.

This command is supported when following feature are enabled HAVE\_AUTHD feature

Attribute Name: protocol-version

Attribute Type: enum (1|2)

## Netconf edit-config payload

```

<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
  <dot1x-interfaces>
    <dot1x-interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <protocol-version>2</protocol-version> <!-- operation="delete"-->
    </dot1x-interface>
  </dot1x-interfaces>
</authentication>

```

## Command Syntax

```
dot1x protocol-version (1|2)
```

---

## Configure quiet period

Use this attribute to set the quiet-period time interval. When a switch cannot authenticate a client, the switch remains idle for a quiet-period interval of time, then tries again. By administratively changing the quiet-period interval, by entering a lower number than the default, a faster response time can be provided

This command is supported when following feature are enabled HAVE\_AUTHD feature

Attribute Name: quiet-period

Attribute Type: uint16

Attribute Range: 1-65535

## Netconf edit-config payload

```

<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
  <dot1x-interfaces>
    <dot1x-interface>
      <name>WORD</name>
      <config>

```

```

        <name>WORD</name>
    </config>
<authenticator-pae>
<config>
    <quiet-period>1</quiet-period> <!-- operation="delete"-->
</config>
</authenticator-pae>
</dot1x-interface>
</dot1x-interfaces>
</authentication>

```

### Command Syntax

```
dot1x quiet-period <1-65535>
```

---

## Configure max reauth value

Use this attribute to set the maximum reauthentication value, which sets the maximum number of reauthentication attempts after which the port will be unauthorized.

This command is supported when following feature are enabled HAVE\_AUTHD feature

Attribute Name: max-reauth-value

Attribute Type: uint8

Attribute Range: 1-10

### Netconf edit-config payload

```

<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
<dot1x-interfaces>
<dot1x-interface>
    <name>WORD</name>
    <config>
        <name>WORD</name>
    </config>
<authenticator-pae>
<config>
    <max-reauth-value>1</max-reauth-value> <!-- operation="delete"-->
</config>
</authenticator-pae>
</dot1x-interface>
</dot1x-interfaces>
</authentication>

```

### Command Syntax

```
dot1x reauthMax <1-10>
```

---

## Configure interval period

Use this attribute to set the interval between successive attempts to request an ID.

This command is supported when following feature are enabled HAVE\_AUTHD feature

Attribute Name: interval-period

Attribute Type: uint16

Attribute Range: 1-65535

### Netconf edit-config payload

```
<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
  <dot1x-interfaces>
    <dot1x-interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <authenticator-pae>
      <config>
        <interval-period>1</interval-period> <!-- operation="delete"-->
      </config>
    </authenticator-pae>
  </dot1x-interface>
</dot1x-interfaces>
</authentication>
```

### Command Syntax

```
dot1x timeout tx-period <1-65535>
```

---

## Configure reauthentication period

Use this attribute to set the interval between reauthorization attempts.

This command is supported when following feature are enabled HAVE\_AUTHD feature

Attribute Name: reauthentication-period

Attribute Type: uint32

Attribute Range: 1-4294967295

### Netconf edit-config payload

```
<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
  <dot1x-interfaces>
    <dot1x-interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <reauthentication-timer>
      <config>
        <reauthentication-period>1</reauthentication-period> <!-- operation="delete"-
->
      </config>
    </reauthentication-timer>
  </dot1x-interface>
</dot1x-interfaces>
```

```
</authentication>
```

## Command Syntax

```
dot1x timeout re-authperiod <1-4294967295>
```

---

## Configure enable reauthentication

Use this attribute to enable reauthentication on a port.

This command is supported when following feature are enabled HAVE\_AUTHD feature

Attribute Name: enable-reauthentication

Attribute Type: empty

## Netconf edit-config payload

```
<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
  <dot1x-interfaces>
    <dot1x-interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <reauthentication-timer>
        <config>
          </enable-reauthentication><!-- operation="delete"-->
        </config>
      </reauthentication-timer>
    </dot1x-interface>
  </dot1x-interfaces>
</authentication>
```

## Command Syntax

```
dot1x reauthentication
```

---

## Configure enable mac auth bypass

Use this attribute to enable/disable mac-auth-bypass on a port.

This command is supported when following feature are enabled HAVE\_AUTHD feature

Attribute Name: enable-mac-auth-bypass

Attribute Type: enum (enable|disable)

## Netconf edit-config payload

```
<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
  <dot1x-interfaces>
    <dot1x-interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </dot1x-interface>
  </dot1x-interfaces>
</authentication>
```

```

    <reauthentication-timer>
    <config>
        <enable-mac-auth-bypass>enable</enable-mac-auth-bypass> <!--
operation="delete"-->
    </config>
</reauthentication-timer>
</dot1x-interface>
</dot1x-interfaces>
</authentication>

```

## Command Syntax

```
dot1x mac-auth-bypass (enable|disable)
```

---

## Configure supplicant timeout

Use this attribute to set the interval for a supplicant to respond.

This command is supported when following feature are enabled HAVE\_AUTHD feature

Attribute Name: supplicant-timeout

Attribute Type: uint16

Attribute Range: 1-65535

## Netconf edit-config payload

```

<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
<dot1x-interfaces>
<dot1x-interface>
    <name>WORD</name>
    <config>
        <name>WORD</name>
    </config>
<authenticator-be>
<config>
    <supplicant-timeout>1</supplicant-timeout> <!-- operation="delete"-->
</config>
</authenticator-be>
</dot1x-interface>
</dot1x-interfaces>
</authentication>

```

## Command Syntax

```
dot1x timeout supp-timeout <1-65535>
```

---

## Configure server timeout

Use this attribute to set the authentication server response timeout.

This command is supported when following feature are enabled HAVE\_AUTHD feature

Attribute Name: server-timeout

Attribute Type: uint16

Attribute Range: 1-65535

### Netconf edit-config payload

```
<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
  <dot1x-interfaces>
  <dot1x-interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  <authenticator-be>
  <config>
    <server-timeout>1</server-timeout> <!-- operation="delete"-->
  </config>
</authenticator-be>
</dot1x-interface>
</dot1x-interfaces>
</authentication>
```

### Command Syntax

```
dot1x timeout server-timeout <1-65535>
```

---

## Configure mac control

Use this attribute to enable or disable the MAC authentication control on an interface.

This command is supported when following feature are enabled MAC\_AUTH feature,HAVE\_AUTHD feature

Attribute Name: mac-control

Attribute Type: empty

### Netconf edit-config payload

```
<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
  <mac-interfaces>
  <mac-interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  </mac-control>
</mac-interface>
</mac-interfaces>
</authentication>
```

### Command Syntax

```
auth-mac
```

---

## Configure mac mode

Use this attribute to enable or disable the MAC authentication mode on an interface.

---

This command is supported when following feature are enabled MAC\_AUTH feature,HAVE\_AUTHD feature

Attribute Name: mac-mode

Attribute Type: enum (filter|shutdown)

### Netconf edit-config payload

```
<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
  <mac-interfaces>
    <mac-interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <mac-mode>shutdown</mac-mode> <!-- operation="delete"-->
    </mac-interface>
  </mac-interfaces>
</authentication>
```

### Command Syntax

```
auth-mac mode (filter|shutdown)
```

---

## Configure dynamic vlan creation

Use this attribute to enable or disable dynamic VLAN creation after successful MAC authentication.

This command is supported when following feature are enabled MAC\_AUTH feature,HAVE\_AUTHD feature

Attribute Name: dynamic-vlan-creation

Attribute Type: empty

### Netconf edit-config payload

```
<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
  <mac-interfaces>
    <mac-interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </dynamic-vlan-creation><!-- operation="delete"-->
    </mac-interface>
  </mac-interfaces>
</authentication>
```

### Command Syntax

```
auth-mac dynamic-vlan-creation
```

---

## Configure mac address aging

Use this attribute to either enable or disable MAC aging. When enabled, a MAC entry is added to the forwarding database, with aging time equal to the bridge aging time. Otherwise, the MAC entry will not be aged out. If MAC aging is disabled, the MAC entry will not be aged out

---

This command is supported when following feature are enabled MAC\_AUTH feature,HAVE\_AUTHD feature

Attribute Name: mac-address-aging

Attribute Type: empty

### Netconf edit-config payload

```
<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
  <mac-interfaces>
    <mac-interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </mac-address-aging><!-- operation="delete"-->
    </mac-interface>
  </mac-interfaces>
</authentication>
```

### Command Syntax

```
auth-mac mac-aging
```

---

## Configure options

Use this attribute to turn on or turn off 802.1x debugging at various levels.

This command is supported when following feature are enabled HAVE\_AUTHD feature

Attribute Name: options

Attribute Type: bits (event|timer|packet|nsm|all)

### Netconf edit-config payload

```
<authentication xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-authentication">
  <debug>
    <config>
      <options>event</options> <!-- operation="delete"-->
    </config>
  </debug>
</authentication>
```

### Command Syntax

```
debug dot1x (event|timer|packet|nsm|all)
```

---

## dot1x initialize interface IFNAME

Attribute Name: name

Attribute Type: string

Attribute Range: 1-33

---

## Netconf RPC payload

```
<dot1x-authentication-initialize-interface xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-authentication">
  <name>IFNAME</name>
</dot1x-authentication-initialize-interface>
```

## Command Syntax

```
dot1x initialize interface IFNAME
```

---

## snmp restart auth

### Netconf RPC payload

```
<dot1x-authentication-snmp-restart xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-authentication"/>
```

### Command Syntax

```
snmp restart auth
```

---

## debug dot1x (event|timer|packet|nsm|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (event|timer|packet|nsm|all)

### Netconf RPC payload

```
<dot1x-authentication-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/
ocnos/ipi-authentication">
  <terminal-debug-options>event</terminal-debug-options>
</dot1x-authentication-terminal-debug-on>
```

### Command Syntax

```
debug dot1x (event|timer|packet|nsm|all)
```

---

## no debug dot1x (event|timer|packet|nsm|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (event|timer|packet|nsm|all)

### Netconf RPC payload

```
<dot1x-authentication-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/
ocnos/ipi-authentication">
  <terminal-debug-options>event</terminal-debug-options>
</dot1x-authentication-terminal-debug-off>
```

### Command Syntax

```
no debug dot1x (event|timer|packet|nsm|all)
```

---

# IPI-AUTHENTICATION-RADIUS

---

## Configure port

Specify the radius client port number. The default port number is 1812.

This command is supported when following feature are enabled OpenSSL crypto library available

Attribute Name: port

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: source-address

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```
<authentication-radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
authentication-radius">
  <global>
  <config>
    <source-address>A.B.C.D</source-address> <!-- operation="delete"-->
    <port>0</port> <!-- operation="delete"-->
  </config>
</global>
</authentication-radius>
```

## Command Syntax

```
ip radius source-interface A.B.C.D <0-65535>
```

---

## Configure timeout

Use this attribute to set the global timeout which is how long the device waits for a response from a RADIUS server before declaring a timeout failure.

This command is supported when following feature are enabled OpenSSL crypto library available

Attribute Name: timeout

Attribute Type: uint8

Attribute Range: 1-60

## Netconf edit-config payload

```
<authentication-radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
authentication-radius">
  <global>
  <config>
    <timeout>1</timeout> <!-- operation="delete"-->
  </config>
</global>
</authentication-radius>
```

---

## Command Syntax

```
radius-server dot1x timeout <1-60>
```

---

## Configure retransmit max retries

Use this attribute to specify the number of times the router transmits each radius request to the server before giving up

This command is supported when following feature are enabled OpenSSL crypto library available

Attribute Name: retransmit-max-retries

Attribute Type: uint8

Attribute Range: 1-100

## Netconf edit-config payload

```
<authentication-radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
authentication-radius">
  <global>
    <config>
      <retransmit-max-retries>1</retransmit-max-retries> <!-- operation="delete"-->
    </config>
  </global>
</authentication-radius>
```

## Command Syntax

```
radius-server dot1x retransmit <1-100>
```

---

## Configure key string

Use this attribute to set a global preshared key (shared secret) which is a text string shared between the device and RADIUS servers

This command is supported when following feature are enabled OpenSSL crypto library available

Attribute Name: key-string

Attribute Type: string

Attribute Range: 1-64

## Netconf edit-config payload

```
<authentication-radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
authentication-radius">
  <global>
    <config>
      <key-string>WORD</key-string> <!-- operation="delete"-->
    </config>
  </global>
</authentication-radius>
```

## Command Syntax

```
radius-server dot1x key-string WORD
```

---

## Configure encryption key

Use this attribute to set a global preshared key (shared secret) which is a text string shared between the device and RADIUS servers

This command is supported when following feature are enabled OpenSSL crypto library available

Attribute Name: encryption-key

Attribute Type: string

Attribute Range: 18-130

### Netconf edit-config payload

```
<authentication-radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
authentication-radius">
  <global>
    <config>
      <encryption-key>WORD</encryption-key> <!-- operation="delete"-->
    </config>
  </global>
</authentication-radius>
```

### Command Syntax

```
radius-server dot1x key-string encrypted WORD
```

---

## Configure host address

The host-address to configure the radius host.

This command is supported when following feature are enabled OpenSSL crypto library available

Attribute Name: host-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```
<authentication-radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
authentication-radius">
  <hosts>
    <host> <!-- operation="delete"-->
      <host-address>A.B.C.D</host-address>
    <config>
      <host-address>A.B.C.D</host-address>
    </config>
  </host>
</hosts>
</authentication-radius>
```

### Command Syntax

```
radius-server dot1x host A.B.C.D
```

---

## Configure host port

Specify the radius client port number. The default port number is 1812.

This command is supported when following feature are enabled OpenSSL crypto library available

Attribute Name: host-port

Attribute Type: uint16

Attribute Range: 0-65535

### Netconf edit-config payload

```
<authentication-radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
authentication-radius">
  <hosts>
    <host>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
      </config>
      <host-port>0</host-port> <!-- operation="delete"-->
    </host>
  </hosts>
</authentication-radius>
```

### Command Syntax

```
auth-port <0-65535>
```

---

## Configure host timeout

Use this attribute to set the timeout which is how long the device waits for a response from a RADIUS server before declaring a timeout failure.

This command is supported when following feature are enabled OpenSSL crypto library available

Attribute Name: host-timeout

Attribute Type: uint8

Attribute Range: 0-60

### Netconf edit-config payload

```
<authentication-radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
authentication-radius">
  <hosts>
    <host>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
      </config>
      <host-timeout>0</host-timeout> <!-- operation="delete"-->
    </host>
  </hosts>
</authentication-radius>
```

## Command Syntax

```
timeout <0-60>
```

---

## Configure host retransmit max retries

Use this attribute to specify the number of times the router transmits each radius request to the server before giving up.

This command is supported when following feature are enabled OpenSSL crypto library available

Attribute Name: host-retransmit-max-retries

Attribute Type: uint8

Attribute Range: 0-100

### Netconf edit-config payload

```
<authentication-radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
authentication-radius">
  <hosts>
    <host>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
      </config>
      <host-retransmit-max-retries>0</host-retransmit-max-retries> <!--
operation="delete"-->
    </host>
  </hosts>
</authentication-radius>
```

## Command Syntax

```
retransmit <0-100>
```

---

## Configure host key-string

Use this attribute to set a key (shared secret) which is a text string shared between the device and RADIUS servers

This command is supported when following feature are enabled OpenSSL crypto library available

Attribute Name: key-string

Attribute Type: string

Attribute Range: 1-64

### Netconf edit-config payload

```
<authentication-radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
authentication-radius">
  <hosts>
    <host>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
      </config>
      <key-string>WORD</key-string> <!-- operation="delete"-->
    </host>
  </hosts>
</authentication-radius>
```

```
</host>  
</hosts>  
</authentication-radius>
```

## Command Syntax

```
key-string WORD
```

---

## Configure host encryption-key

Use this attribute to set a key (shared secret) which is a text string shared between the device and RADIUS servers

This command is supported when following feature are enabled OpenSSL crypto library available

Attribute Name: encryption-key

Attribute Type: string

Attribute Range: 18-130

## Netconf edit-config payload

```
<authentication-radius xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-  
authentication-radius">  
  <hosts>  
    <host>  
      <host-address>A.B.C.D</host-address>  
      <config>  
        <host-address>A.B.C.D</host-address>  
      </config>  
      <encryption-key>WORD</encryption-key> <!-- operation="delete"-->  
    </host>  
  </hosts>  
</authentication-radius>
```

## Command Syntax

```
key-string encrypted WORD
```

---

## IPI-ACL

---

### Configure type

Type indicates the fields allowed in the ACL entries belonging to the ACL set (e.g., ip, ipv6, etc.)

Attribute Name: type

Attribute Type: enum (mac|ip|ipv6|arp)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">  
  <acl-sets>  
    <acl-set> <!-- operation="delete"-->  
      <type>ip</type>
```

```
<config>
  <type>ip</type>
  <name>WORD</name>
</config>
<name>NAME</name>
</acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
ip access-list NAME
```

---

## Configure name

Type indicates the fields allowed in the ACL entries belonging to the ACL set (e.g., ip, ipv6, etc.)

Attribute Name: type

Attribute Type: enum (mac|ip|ipv6|arp)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
  <acl-set> <!-- operation="delete"-->
    <type>ipv6</type>
    <config>
      <type>ipv6</type>
      <name>WORD</name>
    </config>
    <name>NAME</name>
  </acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
ipv6 access-list NAME
```

---

## Configure acl-sets type

Type indicates the fields allowed in the ACL entries belonging to the ACL set (e.g., ip, ipv6, etc.)

Attribute Name: type

Attribute Type: enum (mac|ip|ipv6|arp)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
  <acl-set> <!-- operation="delete"-->
    <type>mac</type>
    <config>
      <type>mac</type>
    </config>
  </acl-set>
</acl-sets>
</acl>
```

```
    <name>WORD</name>
  </config>
  <name>NAME</name>
</acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
mac access-list NAME
```

---

## Configure acl-sets type

Type indicates the fields allowed in the ACL entries belonging to the ACL set (e.g., ip, ipv6, etc.)

Attribute Name: type

Attribute Type: enum (mac|ip|ipv6|arp)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set> <!-- operation="delete"-->
      <type>arp</type>
      <config>
        <type>arp</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
</acl>
```

### Command Syntax

```
arp access-list NAME
```

---

## Configure description

Description, or comment, for the ACL set

Attribute Name: description

Attribute Type: string

Attribute Range: 1-100

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>

```

```

    <name>WORD</name>
  </config>
  <name>NAME</name>
  <description>LINE</description> <!-- operation="delete"-->
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```
remark LINE
```

---

## Configure ipv6 disable default icmpv6 rule

Use this attribute to inform that the default icmpv6 rule is disable for the IPv6 ACL.

Attribute Name: ipv6-disable-default-icmpv6-rule

Attribute Type: uint8

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
  <acl-set>
    <type>mac</type>
    <config>
      <type>mac</type>
      <name>WORD</name>
    </config>
    <name>NAME</name>
    </ipv6-disable-default-icmpv6-rule><!-- operation="delete"-->
  </acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```
no 268435453 permit icmpv6 any any
```

---

## Configure acl-set ipv6-disable-default-icmpv6-rule

Use this attribute to inform that the default icmpv6 rule is disable for the IPv6 ACL.

Attribute Name: ipv6-disable-default-icmpv6-rule

Attribute Type: uint8

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
  <acl-set>
    <type>mac</type>
    <config>
      <type>mac</type>

```

```

    <name>WORD</name>
  </config>
  <name>NAME</name>
  </ipv6-disable-default-icmpv6-rule><!-- operation="delete"-->
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```
no 268435453
```

---

## Configure starting sequence number

Use this attribute to set starting sequence number for resequencing

Attribute Name: starting-sequence-number

Attribute Type: uint32

Attribute Range: 1-268435453

Attribute Name: increment-steps

Attribute Type: uint32

Attribute Range: 1-268435453

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
  <acl-set>
    <type>mac</type>
    <config>
      <type>mac</type>
      <name>WORD</name>
    </config>
    <name>NAME</name>
  </acl-set>
  <re-sequence>
  <config>
    <increment-steps>1</increment-steps> <!-- operation="delete"-->
    <starting-sequence-number>1</starting-sequence-number> <!--
operation="delete"-->
  </config>
  </re-sequence>
</acl-sets>
</acl>

```

## Command Syntax

```
resequence <1-268435453> <1-268435453>
```

---

## Configure forwarding action default

Use this attribute to set default forwarding action

Attribute Name: forwarding-action-default

Attribute Type: enum (deny-all|permit-all)

Attribute Name: monitor-action-default

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
  <acl-set>
    <type>mac</type>
    <config>
      <type>mac</type>
      <name>WORD</name>
    </config>
    <name>NAME</name>
  <default-actions>
  <config>
    <monitor-action-default>log</monitor-action-default> <!-- operation="delete"-
->
      <forwarding-action-default>deny-all</forwarding-action-default> <!--
operation="delete"-->
    </config>
  </default-actions>
</acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
default (deny-all|permit-all) ((log|sample)|)
```

---

## Configure redirect interface name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: union

Attribute Name: destination-address

Attribute Type: union

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>
```

## Command Syntax

```
(<1-268435453>|) (deny|permit) tcp (any|host A.B.C.D|A.B.C.D/M|A.B.C.D A.B.C.D)
  (any|host A.B.C.D|A.B.C.D/M|A.B.C.D A.B.C.D)
  ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
  ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure sequence id

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: union

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
    </acl-set>
  </acl-sets>
</acl>
```

```

    <name>NAME</name>
  <acl-entries>
  <acl-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv4>
    <config>
      <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
      </protocol-tcp><!-- operation="delete"-->
      <source-address>any</source-address> <!-- operation="delete"-->
      <destination-address>any</destination-address> <!-- operation="delete"-->
      <dscp>default</dscp> <!-- operation="delete"-->
      <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
      <vlan-id>1</vlan-id> <!-- operation="delete"-->
      <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
      <monitor-action>log</monitor-action> <!-- operation="delete"-->
      <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
  </ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (any) dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7|<0-63>) ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-
4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure forwarding action

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: precedence

Attribute Type: union

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <precedence>routine</precedence> <!-- operation="delete"-->
          <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
```

```

</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (any) precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network|<0-7>)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure protocol tcp

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
<acl-set>
  <type>mac</type>
</config>

```

```

        <type>mac</type>
        <name>WORD</name>
    </config>
    <name>NAME</name>
<acl-entries>
<acl-entry>
    <sequence-id>1</sequence-id>
    <config>
        <sequence-id>1</sequence-id>
    </config>
    <ipv4>
    <config>
        <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
        </protocol-tcp><!-- operation="delete"-->
        <source-address>any</source-address> <!-- operation="delete"-->
        <destination-address>any</destination-address> <!-- operation="delete"-->
        </fragments><!-- operation="delete"-->
        <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (any) fragments
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure source address

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          </fragments><!-- operation="delete"-->
          <dscp>default</dscp> <!-- operation="delete"-->
          <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (any) fragments dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|)
(inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure destination address

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
  <acl-set>
    <type>mac</type>
    <config>
      <type>mac</type>
      <name>WORD</name>
    </config>
    <name>NAME</name>
  </acl-sets>
  <acl-entries>
  <acl-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv4>
    <config>
      <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
      </protocol-tcp><!-- operation="delete"-->
      <source-address>any</source-address> <!-- operation="delete"-->
      <destination-address>any</destination-address> <!-- operation="delete"-->
      </fragments><!-- operation="delete"-->
      <precedence>routine</precedence> <!-- operation="delete"-->
      <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
      <vlan-id>1</vlan-id> <!-- operation="delete"-->
      <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
      <monitor-action>log</monitor-action> <!-- operation="delete"-->
      <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
  </ipv4>
  </acl-entry>
  </acl-entries>
  </acl-set>
  </acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) tcp (any) (any) fragments precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)
```

## Configure destination port operator

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-destination-port

Attribute Type: union

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
    </acl-entry>
  </acl-entries>
</acl>
```

```

    <ipv4>
    <config>
        <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
        </protocol-tcp><!-- operation="delete"-->
        <source-address>any</source-address> <!-- operation="delete"-->
        <destination-address>any</destination-address> <!-- operation="delete"-->
        <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
        <tcp-destination-port>echo</tcp-destination-port> <!--
operation="delete"-->
        <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (any) (eq|neq|lt|gt)
(echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls|<0-
65535>) ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure tcp destination port

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-destination-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: dscp

Attribute Type: enum  
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
          <tcp-destination-port>echo</tcp-destination-port> <!--
operation="delete"-->
          <dscp>default</dscp> <!-- operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

    <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (any) (eq|neq|lt|gt)
(echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls) dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|)
(inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure precedence

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-destination-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-  
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|p  
im-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
          <tcp-destination-port>echo</tcp-destination-port> <!--
operation="delete"-->
          <precedence>routine</precedence> <!-- operation="delete"-->
          <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
```

```

</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (any) (eq|neq|lt|gt)
(echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure lower destination port in range

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
          <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
          <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) tcp (any) (any) range <0-65535> <0-65535>
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure upper destination port in range

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
    </acl-set>
  </acl-sets>
</acl>
```

```

        <type>mac</type>
        <name>WORD</name>
    </config>
    <name>NAME</name>
<acl-entries>
<acl-entry>
    <sequence-id>1</sequence-id>
    <config>
        <sequence-id>1</sequence-id>
    </config>
    <ipv4>
    <config>
        <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
        </protocol-tcp><!-- operation="delete"-->
        <source-address>any</source-address> <!-- operation="delete"-->
        <destination-address>any</destination-address> <!-- operation="delete"-->
        <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
        <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
        <dscp>default</dscp> <!-- operation="delete"-->
        <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (any) range <0-65535> <0-65535> dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|)
(inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure tcp flags

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
      </config>
    </acl-entry>
  </acl-entries>
</acl>
```

```

    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </protocol-tcp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
    <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
    <precedence>routine</precedence> <!-- operation="delete"-->
    <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (any) range <0-65535> <0-65535> precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure source port operator

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-source-port

Attribute Type: union

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-destination-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

        <destination-address>any</destination-address> <!-- operation="delete"-->
        <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
        <tcp-destination-port>echo</tcp-destination-port> <!--
operation="delete"-->
        <dscp>default</dscp> <!-- operation="delete"-->
        <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (eq|neq|lt|gt)
(echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls|<0-
65535>) (any) (eq|neq|lt|gt) (echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls) dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|)
(inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure tcp source port

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-source-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-destination-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

>
    <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
    <tcp-source-port>echo</tcp-source-port> <!-- operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
    <tcp-destination-port>echo</tcp-destination-port> <!--
operation="delete"-->
    <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (eq|neq|lt|gt)
(echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
(any) (eq|neq|lt|gt) (echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure vlan id

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-source-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-destination-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
```

```

    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </protocol-tcp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <source-port-operator>eq</source-port-operator> <!-- operation="delete"--
>
    <tcp-source-port>echo</tcp-source-port> <!-- operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
    <tcp-destination-port>echo</tcp-destination-port> <!--
operation="delete"-->
    <precedence>routine</precedence> <!-- operation="delete"-->
    <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (eq|neq|lt|gt)
(echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
(any) (eq|neq|lt|gt) (echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure inner vlan id

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-source-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entry>
    <sequence-id>1</sequence-id>
```

```

<config>
  <sequence-id>1</sequence-id>
</config>
<ipv4>
<config>
  <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
  </protocol-tcp><!-- operation="delete"-->
  <source-address>any</source-address> <!-- operation="delete"-->
  <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
>
  <tcp-source-port>echo</tcp-source-port> <!-- operation="delete"-->
  <destination-address>any</destination-address> <!-- operation="delete"-->
  <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
  <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
  <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
  <vlan-id>1</vlan-id> <!-- operation="delete"-->
  <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
  <monitor-action>log</monitor-action> <!-- operation="delete"-->
  <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (eq|neq|lt|gt)
(echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
(any) range <0-65535> <0-65535> ({ack|established|fin|psh|rst|syn|urg}|) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure dscp

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-source-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    <acl-entries>
      <acl-entry>
```

```

<sequence-id>1</sequence-id>
<config>
  <sequence-id>1</sequence-id>
</config>
<ipv4>
<config>
  <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
  </protocol-tcp><!-- operation="delete"-->
  <source-address>any</source-address> <!-- operation="delete"-->
  <source-port-operator>eq</source-port-operator> <!-- operation="delete"--
>
  <tcp-source-port>echo</tcp-source-port> <!-- operation="delete"-->
  <destination-address>any</destination-address> <!-- operation="delete"-->
  <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
  <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
  <dscp>default</dscp> <!-- operation="delete"-->
  <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
  <vlan-id>1</vlan-id> <!-- operation="delete"-->
  <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
  <monitor-action>log</monitor-action> <!-- operation="delete"-->
  <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (eq|neq|lt|gt)
(echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
(any) range <0-65535> <0-65535> dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) ({ack|established|fin|psh|rst|syn|urg|}) (vlan <1-4094>|)
(inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure monitor action

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-source-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
    </acl-set>
  </acl-sets>
</acl>
```

```

    <name>NAME</name>
  <acl-entries>
  <acl-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv4>
    <config>
      <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
      </protocol-tcp><!-- operation="delete"-->
      <source-address>any</source-address> <!-- operation="delete"-->
      <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
    >
      <tcp-source-port>echo</tcp-source-port> <!-- operation="delete"-->
      <destination-address>any</destination-address> <!-- operation="delete"-->
      <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
      <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
      <precedence>routine</precedence> <!-- operation="delete"-->
      <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
      <vlan-id>1</vlan-id> <!-- operation="delete"-->
      <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
      <monitor-action>log</monitor-action> <!-- operation="delete"-->
      <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
  </ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (eq|neq|lt|gt)
(echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
(any) range <0-65535> <0-65535> precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-source-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
    </acl-entry>
  </acl-entries>
</ipv4>
```

```

<config>
  <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
  </protocol-tcp><!-- operation="delete"-->
  <source-address>any</source-address> <!-- operation="delete"-->
  <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
>
  <tcp-source-port>echo</tcp-source-port> <!-- operation="delete"-->
  <destination-address>any</destination-address> <!-- operation="delete"-->
  <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
  <vlan-id>1</vlan-id> <!-- operation="delete"-->
  <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
  <monitor-action>log</monitor-action> <!-- operation="delete"-->
  <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (eq|neq|lt|gt)
(echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
(any) ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-source-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum  
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
        </config>
      </ipv4>
      <tcp-source-port>echo</tcp-source-port> <!-- operation="delete"-->
      <destination-address>any</destination-address> <!-- operation="delete"-->
      <dscp>default</dscp> <!-- operation="delete"-->
    </acl-entry>
  </acl-entries>
</acl>
```

```

    <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (eq|neq|lt|gt)
(echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
(any) dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|)
(inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-source-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-  
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|p  
im-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv4>
          <config>
            <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
            </protocol-tcp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
          </config>
          <tcp-source-port>echo</tcp-source-port> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <precedence>routine</precedence> <!-- operation="delete"-->
          <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-sets>
</acl>
```

```

</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (eq|neq|lt|gt)
  (echo|discard|daytime|chargen|ftp-
  data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
  2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
  rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
  (any) precedence
  (routine|priority|immediate|flash|flashoverride|critical|internet|network)
  ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
  ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure lower source port in range

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-destination-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-  
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|p  
im-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-sets>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv4>
          <config>
            <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
            </protocol-tcp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
            <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
            <destination-address>any</destination-address> <!-- operation="delete"-->
            <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
            <tcp-destination-port>echo</tcp-destination-port> <!--
operation="delete"-->
            <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv4>
      </acl-entry>
    </acl-entries>
  </acl>
```

```

</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) range <0-65535> <0-65535> (any)
  (eq|neq|lt|gt) (echo|discard|daytime|chargen|ftp-
  data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
  2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
  rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
  ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
  ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure upper source port in range

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-destination-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-  
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|p  
im-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: dscp

Attribute Type: enum  
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
          <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
          <tcp-destination-port>echo</tcp-destination-port> <!--
operation="delete"-->
          <dscp>default</dscp> <!-- operation="delete"-->
          <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) range <0-65535> <0-65535> (any)
(eq|neq|lt|gt) (echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls) dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|)
(inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-destination-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
          <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
          <tcp-destination-port>echo</tcp-destination-port> <!--
operation="delete"-->
          <precedence>routine</precedence> <!-- operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

    <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) range <0-65535> <0-65535> (any)
  (eq|neq|lt|gt) (echo|discard|daytime|chargen|ftp-
  data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
  2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
  rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
  precedence
  (routine|priority|immediate|flash|flashoverride|critical|internet|network)
  ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
  ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
          <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

        <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
        <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) range <0-65535> <0-65535> (any) range <0-
65535> <0-65535> ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|)
(inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
          <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

        <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
        <dscp>default</dscp> <!-- operation="delete"-->
        <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) range <0-65535> <0-65535> (any) range <0-
65535> <0-65535> dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|)
(inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
          <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

        <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
        <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
        <precedence>routine</precedence> <!-- operation="delete"-->
        <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) range <0-65535> <0-65535> (any) range <0-
65535> <0-65535> precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
          <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <dscp>default</dscp> <!-- operation="delete"-->
          <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

    </config>
  </ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) range <0-65535> <0-65535> (any) dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7) ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|)
  (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
  <acl-set>
    <type>mac</type>
    <config>
      <type>mac</type>
      <name>WORD</name>
    </config>
    <name>NAME</name>
  <acl-entries>
  <acl-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv4>
    <config>
      <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
      </protocol-tcp><!-- operation="delete"-->
      <source-address>any</source-address> <!-- operation="delete"-->
      <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
      <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
      <destination-address>any</destination-address> <!-- operation="delete"-->
      <precedence>routine</precedence> <!-- operation="delete"-->
      <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
      <vlan-id>1</vlan-id> <!-- operation="delete"-->
      <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
      <monitor-action>log</monitor-action> <!-- operation="delete"-->
      <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
  </ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
<1-268435453>|) (deny|permit) tcp (any) range <0-65535> <0-65535> (any) precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network)
```

```
{ack|established|fin|psh|rst|syn|urg|}) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample|)) (redirect-to-port IFNAME|)
```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
```

```

    <name>WORD</name>
  </config>
  <name>NAME</name>
<acl-entries>
<acl-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
  <config>
    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </protocol-tcp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
    <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) range <0-65535> <0-65535> (any)
  ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
  ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure protocol udp

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-udp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>
```

## Command Syntax

```
(<1-268435453>|) (deny|permit) udp (any) (any) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entry>
    <sequence-id>1</sequence-id>
```

```

<config>
  <sequence-id>1</sequence-id>
</config>
<ipv4>
<config>
  <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
  </protocol-udp><!-- operation="delete"-->
  <source-address>any</source-address> <!-- operation="delete"-->
  <destination-address>any</destination-address> <!-- operation="delete"-->
  <dscp>default</dscp> <!-- operation="delete"-->
  <vlan-id>1</vlan-id> <!-- operation="delete"-->
  <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
  <monitor-action>log</monitor-action> <!-- operation="delete"-->
  <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (any) dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
  (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-udp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <precedence>routine</precedence> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>
```

## Command Syntax

```
(<1-268435453>|) (deny|permit) udp (any) (any) precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure fragments

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
```

```

    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </protocol-udp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    </fragments><!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (any) fragments (vlan <1-4094>|) (inner-
vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv4>
          <config>
            <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
            </protocol-udp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <destination-address>any</destination-address> <!-- operation="delete"-->
            </fragments><!-- operation="delete"-->
            <dscp>default</dscp> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv4>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) udp (any) (any) fragments dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
(redirect-to-port IFNAME|)
```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
    </acl-entry>
  </acl-entries>
</acl>
```

```

<ipv4>
<config>
  <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
  </protocol-udp><!-- operation="delete"-->
  <source-address>any</source-address> <!-- operation="delete"-->
  <destination-address>any</destination-address> <!-- operation="delete"-->
  </fragments><!-- operation="delete"-->
  <precedence>routine</precedence> <!-- operation="delete"-->
  <vlan-id>1</vlan-id> <!-- operation="delete"-->
  <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
  <monitor-action>log</monitor-action> <!-- operation="delete"-->
  <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (any) fragments precedence
  (routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
  <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure udp destination port

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-destination-port

Attribute Type: union

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-sets>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv4>
          <config>
            <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
            </protocol-udp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <destination-address>any</destination-address> <!-- operation="delete"-->
            <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
            <udp-destination-port>echo</udp-destination-port> <!--
operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv4>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

## Command Syntax

```
(<1-268435453>|) (deny|permit) udp (any) (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp|<0-65535>) (vlan <1-4094>|)
(inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-destination-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
<acl-set>
```

```

    <type>mac</type>
  <config>
    <type>mac</type>
    <name>WORD</name>
  </config>
  <name>NAME</name>
<acl-entries>
<acl-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
  <config>
    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </protocol-udp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
    <udp-destination-port>echo</udp-destination-port> <!--
operation="delete"-->
    <dscp>default</dscp> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
(redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-destination-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
```

```

    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </protocol-udp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
    <udp-destination-port>echo</udp-destination-port> <!--
operation="delete"-->
    <precedence>routine</precedence> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv4>
          <config>
            <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
            </protocol-udp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <destination-address>any</destination-address> <!-- operation="delete"-->
            <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
            <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv4>
      </acl-entry>
    </acl-entries>
  </acl-sets>
</acl>
```

```

</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (any) range <0-65535> <0-65535> (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
  <acl-set>
    <type>mac</type>
    <config>
      <type>mac</type>
      <name>WORD</name>
    </config>
    <name>NAME</name>
  </acl-set>
  <acl-entries>
  <acl-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv4>
    <config>
      <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
      </protocol-udp><!-- operation="delete"-->
      <source-address>any</source-address> <!-- operation="delete"-->
      <destination-address>any</destination-address> <!-- operation="delete"-->
      <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
      <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
      <dscp>default</dscp> <!-- operation="delete"-->
      <vlan-id>1</vlan-id> <!-- operation="delete"-->
      <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
      <monitor-action>log</monitor-action> <!-- operation="delete"-->
      <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
  </ipv4>
  </acl-entry>
  </acl-entries>
  </acl-set>
  </acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (any) range <0-65535> <0-65535> dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
(redirect-to-port IFNAME|)

```

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string  
Attribute Name: forwarding-action  
Attribute Type: enum (deny|permit)  
Attribute Name: protocol-udp  
Attribute Type: empty  
Attribute Name: source-address  
Attribute Type: enum (any)  
Attribute Name: destination-address  
Attribute Type: enum (any)  
Attribute Name: lower-destination-port-in-range  
Attribute Type: uint16  
Attribute Range: 0-65535  
Attribute Name: upper-destination-port-in-range  
Attribute Type: uint16  
Attribute Range: 0-65535  
Attribute Name: precedence  
Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)  
Attribute Name: vlan-id  
Attribute Type: uint16  
Attribute Range: 1-4094  
Attribute Name: inner-vlan-id  
Attribute Type: uint16  
Attribute Range: 1-4094  
Attribute Name: monitor-action  
Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
    </acl-entry>
  </acl-entries>
</acl>
```

```

</config>
<ipv4>
<config>
  <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
  </protocol-udp><!-- operation="delete"-->
  <source-address>any</source-address> <!-- operation="delete"-->
  <destination-address>any</destination-address> <!-- operation="delete"-->
  <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
  <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
  <precedence>routine</precedence> <!-- operation="delete"-->
  <vlan-id>1</vlan-id> <!-- operation="delete"-->
  <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
  <monitor-action>log</monitor-action> <!-- operation="delete"-->
  <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
</config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (any) range <0-65535> <0-65535> precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure udp source port

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-source-port

Attribute Type: union

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-destination-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv4>
          <config>
            <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
            </protocol-udp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
          </config>
          <udp-source-port>echo</udp-source-port> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
          <udp-destination-port>echo</udp-destination-port> <!--
operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        </config>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

```

        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp|<0-65535>) (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) (vlan <1-4094>|) (inner-vlan
<1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-source-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-destination-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-udp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
        </config>
      </ipv4>
      <udp>
        <config>
          <udp-source-port>echo</udp-source-port> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
          <udp-destination-port>echo</udp-destination-port> <!--
operation="delete"-->
          <dscp>default</dscp> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </udp>
    </acl-entry>
  </acl-entries>
</acl>
```

```

</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
(redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-source-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-destination-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv4>
          <config>
            <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
            </protocol-udp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
          >
            <udp-source-port>echo</udp-source-port> <!-- operation="delete"-->
            <destination-address>any</destination-address> <!-- operation="delete"-->
            <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
            <udp-destination-port>echo</udp-destination-port> <!--
operation="delete"-->
            <precedence>routine</precedence> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv4>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

```

</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-source-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-udp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
        >
          <udp-source-port>echo</udp-source-port> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
          <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```
(<1-268435453>|) (deny|permit) udp (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) (any) range <0-65535> <0-65535>
(vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port
IFNAME|)
```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-source-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv4>
          <config>
            <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
            </protocol-udp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
          >
            <udp-source-port>echo</udp-source-port> <!-- operation="delete"-->
            <destination-address>any</destination-address> <!-- operation="delete"-->
            <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
            <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
            <dscp>default</dscp> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv4>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) udp (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio)
```

```
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) (any) range <0-65535> <0-65535>
dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
(redirect-to-port IFNAME|)
```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-source-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
  <acl-set>
    <type>mac</type>
    <config>
      <type>mac</type>
      <name>WORD</name>
    </config>
    <name>NAME</name>
  <acl-entries>
  <acl-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv4>
    <config>
      <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
      </protocol-udp><!-- operation="delete"-->
      <source-address>any</source-address> <!-- operation="delete"-->
      <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
    >
      <udp-source-port>echo</udp-source-port> <!-- operation="delete"-->
      <destination-address>any</destination-address> <!-- operation="delete"-->
      <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
      <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
      <precedence>routine</precedence> <!-- operation="delete"-->
      <vlan-id>1</vlan-id> <!-- operation="delete"-->
      <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
      <monitor-action>log</monitor-action> <!-- operation="delete"-->
      <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
  </ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) udp (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) (any) range <0-65535> <0-65535>
```

```
precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-source-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
```

```

<acl-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
    <config>
      <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
      </protocol-udp><!-- operation="delete"-->
      <source-address>any</source-address> <!-- operation="delete"-->
      <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
    >
      <udp-source-port>echo</udp-source-port> <!-- operation="delete"-->
      <destination-address>any</destination-address> <!-- operation="delete"-->
      <vlan-id>1</vlan-id> <!-- operation="delete"-->
      <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
      <monitor-action>log</monitor-action> <!-- operation="delete"-->
      <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
  </ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) (any) (vlan <1-4094>|) (inner-
vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-source-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum  
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-udp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
        </config>
        <udp-source-port>echo</udp-source-port> <!-- operation="delete"-->
        <destination-address>any</destination-address> <!-- operation="delete"-->
        <dscp>default</dscp> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
      </config>
    </acl-entry>
  </acl-entries>
</acl>
```

```

        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) (any) dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
(redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-source-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
  <acl-set>
    <type>mac</type>
    <config>
      <type>mac</type>
      <name>WORD</name>
    </config>
    <name>NAME</name>
  <acl-entries>
  <acl-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv4>
    <config>
      <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
      </protocol-udp><!-- operation="delete"-->
      <source-address>any</source-address> <!-- operation="delete"-->
      <source-port-operator>eq</source-port-operator> <!-- operation="delete"-->
    >
      <udp-source-port>echo</udp-source-port> <!-- operation="delete"-->
      <destination-address>any</destination-address> <!-- operation="delete"-->
      <precedence>routine</precedence> <!-- operation="delete"-->
      <vlan-id>1</vlan-id> <!-- operation="delete"-->
      <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
      <monitor-action>log</monitor-action> <!-- operation="delete"-->
      <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
  </ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) udp (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) (any) precedence
```

```
(routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-destination-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
```

```

<acl-set>
  <type>mac</type>
  <config>
    <type>mac</type>
    <name>WORD</name>
  </config>
  <name>NAME</name>
<acl-entries>
<acl-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
  <config>
    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </protocol-udp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
    <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
    <udp-destination-port>echo</udp-destination-port> <!--
operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) range <0-65535> <0-65535> (any)
(eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) (vlan <1-4094>|) (inner-vlan
<1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-destination-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
    </acl-set>
  </acl-sets>
</acl>
```

```

        <type>mac</type>
        <name>WORD</name>
    </config>
    <name>NAME</name>
<acl-entries>
<acl-entry>
    <sequence-id>1</sequence-id>
    <config>
        <sequence-id>1</sequence-id>
    </config>
    <ipv4>
    <config>
        <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
        </protocol-udp><!-- operation="delete"-->
        <source-address>any</source-address> <!-- operation="delete"-->
        <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
        <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
        <destination-address>any</destination-address> <!-- operation="delete"-->
        <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
        <udp-destination-port>echo</udp-destination-port> <!--
operation="delete"-->
        <dscp>default</dscp> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) range <0-65535> <0-65535> (any)
(eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
(redirect-to-port IFNAME|)

```

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-destination-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
      </config>
    </acl-set>
  </acl-sets>
</acl>
```

```

    <name>WORD</name>
  </config>
  <name>NAME</name>
<acl-entries>
<acl-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
  <config>
    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </protocol-udp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
    <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
    <udp-destination-port>echo</udp-destination-port> <!--
operation="delete"-->
    <precedence>routine</precedence> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) range <0-65535> <0-65535> (any)
(eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action  
Attribute Type: enum (deny|permit)  
Attribute Name: protocol-udp  
Attribute Type: empty  
Attribute Name: source-address  
Attribute Type: enum (any)  
Attribute Name: lower-source-port-in-range  
Attribute Type: uint16  
Attribute Range: 0-65535  
Attribute Name: upper-source-port-in-range  
Attribute Type: uint16  
Attribute Range: 0-65535  
Attribute Name: destination-address  
Attribute Type: enum (any)  
Attribute Name: lower-destination-port-in-range  
Attribute Type: uint16  
Attribute Range: 0-65535  
Attribute Name: upper-destination-port-in-range  
Attribute Type: uint16  
Attribute Range: 0-65535  
Attribute Name: vlan-id  
Attribute Type: uint16  
Attribute Range: 1-4094  
Attribute Name: inner-vlan-id  
Attribute Type: uint16  
Attribute Range: 1-4094  
Attribute Name: monitor-action  
Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
</acl>
```

```

<acl-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
    <config>
      <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
      </protocol-udp><!-- operation="delete"-->
      <source-address>any</source-address> <!-- operation="delete"-->
      <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
      <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
      <destination-address>any</destination-address> <!-- operation="delete"-->
      <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
      <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
      <vlan-id>1</vlan-id> <!-- operation="delete"-->
      <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
      <monitor-action>log</monitor-action> <!-- operation="delete"-->
      <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
  </ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) range <0-65535> <0-65535> (any) range <0-
65535> <0-65535> (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
(redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
    </acl-entry>
  </acl-entries>
</acl>
```

```

</config>
<ipv4>
<config>
  <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
  </protocol-udp><!-- operation="delete"-->
  <source-address>any</source-address> <!-- operation="delete"-->
  <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
  <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
  <destination-address>any</destination-address> <!-- operation="delete"-->
  <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
  <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
  <dscp>default</dscp> <!-- operation="delete"-->
  <vlan-id>1</vlan-id> <!-- operation="delete"-->
  <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
  <monitor-action>log</monitor-action> <!-- operation="delete"-->
  <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) range <0-65535> <0-65535> (any) range <0-
65535> <0-65535> dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
(redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
      </config>
    </acl-entry>
  </acl-entries>
</acl>
```

```

        <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
        </protocol-udp><!-- operation="delete"-->
        <source-address>any</source-address> <!-- operation="delete"-->
        <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
        <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
        <destination-address>any</destination-address> <!-- operation="delete"-->
        <lower-destination-port-in-range>0</lower-destination-port-in-range> <!--
operation="delete"-->
        <upper-destination-port-in-range>0</upper-destination-port-in-range> <!--
operation="delete"-->
        <precedence>routine</precedence> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) range <0-65535> <0-65535> (any) range <0-
65535> <0-65535> precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-udp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
          <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) range <0-65535> <0-65535> (any) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
<acl-set>
  <type>mac</type>
  <config>
    <type>mac</type>
    <name>WORD</name>
  </config>
  <name>NAME</name>
</acl-sets>
<acl-entries>
<acl-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
  <config>
    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </protocol-udp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
    <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <dscp>default</dscp> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
  </ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) range <0-65535> <0-65535> (any) dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
(redirect-to-port IFNAME|)

```

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string  
Attribute Name: forwarding-action  
Attribute Type: enum (deny|permit)  
Attribute Name: protocol-udp  
Attribute Type: empty  
Attribute Name: source-address  
Attribute Type: enum (any)  
Attribute Name: lower-source-port-in-range  
Attribute Type: uint16  
Attribute Range: 0-65535  
Attribute Name: upper-source-port-in-range  
Attribute Type: uint16  
Attribute Range: 0-65535  
Attribute Name: destination-address  
Attribute Type: enum (any)  
Attribute Name: precedence  
Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)  
Attribute Name: vlan-id  
Attribute Type: uint16  
Attribute Range: 1-4094  
Attribute Name: inner-vlan-id  
Attribute Type: uint16  
Attribute Range: 1-4094  
Attribute Name: monitor-action  
Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
    </acl-entry>
  </acl-entries>
</acl>
```

```

</config>
<ipv4>
<config>
    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </protocol-udp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
    <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <precedence>routine</precedence> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

<1-268435453>|) (deny|permit) udp (any) range <0-65535> <0-65535> (any) precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure protocol icmp

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-message

Attribute Type: enum (administratively-prohibited|alternate-address|conversion-error|dod-host-prohibited|dod-net-prohibited|echo|echo-reply|general-parameter-problem|host-isolated|host-precedence-unreachable|host-redirect|host-

tos-redirect|host-tos-unreachable|host-unknown|host-unreachable|information-reply|information-request|mask-reply|mask-request|mobile-redirect|net-redirect|net-tos-redirect|net-tos-unreachable|net-unreachable|network-unknown|no-room-for-option|option-missing|packet-too-big|parameter-problem|port-unreachable|precedence-unreachable|protocol-unreachable|reassembly-timeout|redirect|router-advertisement|router-solicitation|source-quench|source-route-failed|time-exceeded|timestamp-reply|timestamp-request|traceroute|ttl-exceeded|unreachable)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-icmp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <icmp-message>administratively-prohibited</icmp-message> <!--
operation="delete"-->
          </fragments><!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmp (any) (any) ((administratively-
  prohibited|alternate-address|conversion-error|dod-host-prohibited|dod-net-
  prohibited|echo|echo-reply|general-parameter-problem|host-isolated|host-
  precedence-unreachable|host-redirect|host-tos-redirect|host-tos-
  unreachable|host-unknown|host-unreachable|information-reply|information-
  request|mask-reply|mask-request|mobile-redirect|net-redirect|net-tos-
  redirect|net-tos-unreachable|net-unreachable|network-unknown|no-room-for-
  option|option-missing|packet-too-big|parameter-problem|port-
  unreachable|precedence-unreachable|protocol-unreachable|reassembly-
  timeout|redirect|router-advertisement|router-solicitation|source-quench|source-
  route-failed|time-exceeded|timestamp-reply|timestamp-request|traceroute|ttl-
  exceeded|unreachable)|) fragments (vlan <1-4094>|) (inner-vlan <1-4094>|)
  ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure icmp message

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-message

Attribute Type: enum (administratively-prohibited|alternate-address|conversion-error|dod-host-prohibited|dod-net-prohibited|echo|echo-reply|general-parameter-problem|host-isolated|host-precedence-unreachable|host-redirect|host-tos-redirect|host-tos-unreachable|host-unknown|host-unreachable|information-reply|information-request|mask-reply|mask-request|mobile-redirect|net-redirect|net-tos-redirect|net-tos-unreachable|net-unreachable|network-unknown|no-room-for-option|option-missing|packet-too-big|parameter-problem|port-unreachable|precedence-unreachable|protocol-unreachable|reassembly-timeout|redirect|router-advertisement|router-solicitation|source-quench|source-route-failed|time-exceeded|timestamp-reply|timestamp-request|traceroute|ttl-exceeded|unreachable)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-sets>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv4>
          <config>
            <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
            </protocol-icmp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <destination-address>any</destination-address> <!-- operation="delete"-->
            <icmp-message>administratively-prohibited</icmp-message> <!--
operation="delete"-->
            </fragments><!-- operation="delete"-->
            <dscp>default</dscp> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv4>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
```

---

```
</acl>
```

## Command Syntax

```
(<1-268435453>|) (deny|permit) icmp (any) (any) ((administratively-
  prohibited|alternate-address|conversion-error|dod-host-prohibited|dod-net-
  prohibited|echo|echo-reply|general-parameter-problem|host-isolated|host-
  precedence-unreachable|host-redirect|host-tos-redirect|host-tos-
  unreachable|host-unknown|host-unreachable|information-reply|information-
  request|mask-reply|mask-request|mobile-redirect|net-redirect|net-tos-
  redirect|net-tos-unreachable|net-unreachable|network-unknown|no-room-for-
  option|option-missing|packet-too-big|parameter-problem|port-
  unreachable|precedence-unreachable|protocol-unreachable|reassembly-
  timeout|redirect|router-advertisement|router-solicitation|source-quench|source-
  route-failed|time-exceeded|timestamp-reply|timestamp-request|traceroute|ttl-
  exceeded|unreachable)|) fragments dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
  (redirect-to-port IFNAME|)
```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-message

Attribute Type: enum (administratively-prohibited|alternate-address|conversion-error|dod-host-prohibited|dod-net-prohibited|echo|echo-reply|general-parameter-problem|host-isolated|host-precedence-unreachable|host-redirect|host-tos-redirect|host-tos-unreachable|host-unknown|host-unreachable|information-reply|information-request|mask-reply|mask-request|mobile-redirect|net-redirect|net-tos-redirect|net-tos-unreachable|net-unreachable|network-unknown|no-room-for-option|option-missing|packet-too-big|parameter-problem|port-unreachable|precedence-unreachable|protocol-unreachable|reassembly-timeout|redirect|router-advertisement|router-solicitation|source-quench|source-route-failed|time-exceeded|timestamp-reply|timestamp-request|traceroute|ttl-exceeded|unreachable)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv4>
          <config>
            <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
            </protocol-icmp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <destination-address>any</destination-address> <!-- operation="delete"-->
            <icmp-message>administratively-prohibited</icmp-message> <!--
operation="delete"-->
            </fragments><!-- operation="delete"-->
            <precedence>routine</precedence> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv4>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

## Command Syntax

```
<1-268435453>|) (deny|permit) icmp (any) (any) ((administratively-
  prohibited|alternate-address|conversion-error|dod-host-prohibited|dod-net-
  prohibited|echo|echo-reply|general-parameter-problem|host-isolated|host-
  precedence-unreachable|host-redirect|host-tos-redirect|host-tos-
  unreachable|host-unknown|host-unreachable|information-reply|information-
  request|mask-reply|mask-request|mobile-redirect|net-redirect|net-tos-
  redirect|net-tos-unreachable|net-unreachable|network-unknown|no-room-for-
  option|option-missing|packet-too-big|parameter-problem|port-
  unreachable|precedence-unreachable|protocol-unreachable|reassembly-
  timeout|redirect|router-advertisement|router-solicitation|source-quench|source-
  route-failed|time-exceeded|timestamp-reply|timestamp-request|traceroute|ttl-
  exceeded|unreachable)|) fragments precedence
  (routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
  <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-message

Attribute Type: enum (administratively-prohibited|alternate-address|conversion-error|dod-host-prohibited|dod-net-prohibited|echo|echo-reply|general-parameter-problem|host-isolated|host-precedence-unreachable|host-redirect|host-tos-redirect|host-tos-unreachable|host-unknown|host-unreachable|information-reply|information-request|mask-reply|mask-request|mobile-redirect|net-redirect|net-tos-redirect|net-tos-unreachable|net-unreachable|network-unknown|no-room-for-option|option-missing|packet-too-big|parameter-problem|port-unreachable|precedence-unreachable|protocol-unreachable|reassembly-timeout|redirect|router-advertisement|router-solicitation|source-quench|source-route-failed|time-exceeded|timestamp-reply|timestamp-request|traceroute|ttl-exceeded|unreachable)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
<acl-set>
  <type>mac</type>
  <config>
    <type>mac</type>
    <name>WORD</name>
  </config>
  <name>NAME</name>
<acl-entries>
<acl-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
  <config>
    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </protocol-icmp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <icmp-message>administratively-prohibited</icmp-message> <!--
operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
  </ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) icmp (any) (any) ((administratively-
prohibited|alternate-address|conversion-error|dod-host-prohibited|dod-net-
prohibited|echo|echo-reply|general-parameter-problem|host-isolated|host-
precedence-unreachable|host-redirect|host-tos-redirect|host-tos-
unreachable|host-unknown|host-unreachable|information-reply|information-
request|mask-reply|mask-request|mobile-redirect|net-redirect|net-tos-
redirect|net-tos-unreachable|net-unreachable|network-unknown|no-room-for-
option|option-missing|packet-too-big|parameter-problem|port-
unreachable|precedence-unreachable|protocol-unreachable|reassembly-
timeout|redirect|router-advertisement|router-solicitation|source-quench|source-
route-failed|time-exceeded|timestamp-reply|timestamp-request|traceroute|ttl-
```

```
exceeded|unreachable)|) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
(redirect-to-port IFNAME|)
```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-message

Attribute Type: enum (administratively-prohibited|alternate-address|conversion-error|dod-host-prohibited|dod-net-prohibited|echo|echo-reply|general-parameter-problem|host-isolated|host-precedence-unreachable|host-redirect|host-tos-redirect|host-tos-unreachable|host-unknown|host-unreachable|information-reply|information-request|mask-reply|mask-request|mobile-redirect|net-redirect|net-tos-redirect|net-tos-unreachable|net-unreachable|network-unknown|no-room-for-option|option-missing|packet-too-big|parameter-problem|port-unreachable|precedence-unreachable|protocol-unreachable|reassembly-timeout|redirect|router-advertisement|router-solicitation|source-quench|source-route-failed|time-exceeded|timestamp-reply|timestamp-request|traceroute|ttl-exceeded|unreachable)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
    </acl-set>
  </acl-sets>
</acl>
```

```

        <type>mac</type>
        <name>WORD</name>
    </config>
    <name>NAME</name>
<acl-entries>
<acl-entry>
    <sequence-id>1</sequence-id>
    <config>
        <sequence-id>1</sequence-id>
    </config>
    <ipv4>
    <config>
        <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
        </protocol-icmp><!-- operation="delete"-->
        <source-address>any</source-address> <!-- operation="delete"-->
        <destination-address>any</destination-address> <!-- operation="delete"-->
        <icmp-message>administratively-prohibited</icmp-message> <!--
operation="delete"-->
        <dscp>default</dscp> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmp (any) (any) ((administratively-
prohibited|alternate-address|conversion-error|dod-host-prohibited|dod-net-
prohibited|echo|echo-reply|general-parameter-problem|host-isolated|host-
precedence-unreachable|host-redirect|host-tos-redirect|host-tos-
unreachable|host-unknown|host-unreachable|information-reply|information-
request|mask-reply|mask-request|mobile-redirect|net-redirect|net-tos-
redirect|net-tos-unreachable|net-unreachable|network-unknown|no-room-for-
option|option-missing|packet-too-big|parameter-problem|port-
unreachable|precedence-unreachable|protocol-unreachable|reassembly-
timeout|redirect|router-advertisement|router-solicitation|source-quench|source-
route-failed|time-exceeded|timestamp-reply|timestamp-request|traceroute|ttl-
exceeded|unreachable)|) dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
(redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-message

Attribute Type: enum (administratively-prohibited|alternate-address|conversion-error|dod-host-prohibited|dod-net-prohibited|echo|echo-reply|general-parameter-problem|host-isolated|host-precedence-unreachable|host-redirect|host-tos-redirect|host-tos-unreachable|host-unknown|host-unreachable|information-reply|information-request|mask-reply|mask-request|mobile-redirect|net-redirect|net-tos-redirect|net-tos-unreachable|net-unreachable|network-unknown|no-room-for-option|option-missing|packet-too-big|parameter-problem|port-unreachable|precedence-unreachable|protocol-unreachable|reassembly-timeout|redirect|router-advertisement|router-solicitation|source-quench|source-route-failed|time-exceeded|timestamp-reply|timestamp-request|traceroute|ttl-exceeded|unreachable)

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
  <acl-set>
    <type>mac</type>
    <config>
      <type>mac</type>
      <name>WORD</name>
    </config>
    <name>NAME</name>
```

```

<acl-entries>
<acl-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
  <config>
    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </protocol-icmp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <icmp-message>administratively-prohibited</icmp-message> <!--
operation="delete"-->
    <precedence>routine</precedence> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmp (any) (any) ((administratively-
prohibited|alternate-address|conversion-error|dod-host-prohibited|dod-net-
prohibited|echo|echo-reply|general-parameter-problem|host-isolated|host-
precedence-unreachable|host-redirect|host-tos-redirect|host-tos-
unreachable|host-unknown|host-unreachable|information-reply|information-
request|mask-reply|mask-request|mobile-redirect|net-redirect|net-tos-
redirect|net-tos-unreachable|net-unreachable|network-unknown|no-room-for-
option|option-missing|packet-too-big|parameter-problem|port-
unreachable|precedence-unreachable|protocol-unreachable|reassembly-
timeout|redirect|router-advertisement|router-solicitation|source-quench|source-
route-failed|time-exceeded|timestamp-reply|timestamp-request|traceroute|ttl-
exceeded|unreachable)|) precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure icmp type

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-type

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: icmp-code

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: fragments

Attribute Type: empty

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
      </config>
    </acl-entry>
  </acl-entries>
</acl>
```

```

    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </protocol-icmp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <icmp-type>0</icmp-type> <!-- operation="delete"-->
    <icmp-code>0</icmp-code> <!-- operation="delete"-->
    </fragments><!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmp (any) (any) <0-255> <0-255> fragments (vlan <1-
4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure icmp code

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-type

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: icmp-code

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: fragments

Attribute Type: empty

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-icmp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <icmp-type>0</icmp-type> <!-- operation="delete"-->
          <icmp-code>0</icmp-code> <!-- operation="delete"-->
          </fragments><!-- operation="delete"-->
          <dscp>default</dscp> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>

```

```

</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmp (any) (any) <0-255> <0-255> fragments dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
  (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-type

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: icmp-code

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: fragments

Attribute Type: empty

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
  <acl-set>
    <type>mac</type>
    <config>
      <type>mac</type>
      <name>WORD</name>
    </config>
    <name>NAME</name>
  <acl-entries>
  <acl-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv4>
    <config>
      <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
      </protocol-icmp><!-- operation="delete"-->
      <source-address>any</source-address> <!-- operation="delete"-->
      <destination-address>any</destination-address> <!-- operation="delete"-->
      <icmp-type>0</icmp-type> <!-- operation="delete"-->
      <icmp-code>0</icmp-code> <!-- operation="delete"-->
      </fragments><!-- operation="delete"-->
      <precedence>routine</precedence> <!-- operation="delete"-->
      <vlan-id>1</vlan-id> <!-- operation="delete"-->
      <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
      <monitor-action>log</monitor-action> <!-- operation="delete"-->
      <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
  </ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) icmp (any) (any) <0-255> <0-255> fragments
precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-type

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: icmp-code

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
```

```

<config>
  <sequence-id>1</sequence-id>
</config>
<ipv4>
<config>
  <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
  </protocol-icmp><!-- operation="delete"-->
  <source-address>any</source-address> <!-- operation="delete"-->
  <destination-address>any</destination-address> <!-- operation="delete"-->
  <icmp-type>0</icmp-type> <!-- operation="delete"-->
  <icmp-code>0</icmp-code> <!-- operation="delete"-->
  <vlan-id>1</vlan-id> <!-- operation="delete"-->
  <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
  <monitor-action>log</monitor-action> <!-- operation="delete"-->
  <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmp (any) (any) <0-255> <0-255> (vlan <1-4094>|)
(inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-type

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: icmp-code

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-icmp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <icmp-type>0</icmp-type> <!-- operation="delete"-->
          <icmp-code>0</icmp-code> <!-- operation="delete"-->
          <dscp>default</dscp> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmp (any) (any) <0-255> <0-255> dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
  (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-type

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: icmp-code

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-icmp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <icmp-type>0</icmp-type> <!-- operation="delete"-->
          <icmp-code>0</icmp-code> <!-- operation="delete"-->
          <precedence>routine</precedence> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) icmp (any) (any) <0-255> <0-255> precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string  
 Attribute Name: forwarding-action  
 Attribute Type: enum (deny|permit)  
 Attribute Name: protocol-icmp  
 Attribute Type: empty  
 Attribute Name: source-address  
 Attribute Type: enum (any)  
 Attribute Name: destination-address  
 Attribute Type: enum (any)  
 Attribute Name: icmp-type  
 Attribute Type: uint8  
 Attribute Range: 0-255  
 Attribute Name: fragments  
 Attribute Type: empty  
 Attribute Name: vlan-id  
 Attribute Type: uint16  
 Attribute Range: 1-4094  
 Attribute Name: inner-vlan-id  
 Attribute Type: uint16  
 Attribute Range: 1-4094  
 Attribute Name: monitor-action  
 Attribute Type: enum (log|sample)

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
  
```

```

    </protocol-icmp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <icmp-type>0</icmp-type> <!-- operation="delete"-->
    </fragments><!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmp (any) (any) <0-255> fragments (vlan <1-4094>|)
(inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-type

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: fragments

Attribute Type: empty

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-icmp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <icmp-type>0</icmp-type> <!-- operation="delete"-->
          </fragments><!-- operation="delete"-->
          <dscp>default</dscp> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>
```

## Command Syntax

```
(<1-268435453>|) (deny|permit) icmp (any) (any) <0-255> fragments dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
  (redirect-to-port IFNAME|)
```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-type

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: fragments

Attribute Type: empty

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
```

```

<config>
  <type>mac</type>
  <name>WORD</name>
</config>
<name>NAME</name>
<acl-entries>
<acl-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
  <config>
    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </protocol-icmp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <icmp-type>0</icmp-type> <!-- operation="delete"-->
    </fragments><!-- operation="delete"-->
    <precedence>routine</precedence> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmp (any) (any) <0-255> fragments precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-type

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-icmp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <icmp-type>0</icmp-type> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```
</acl-entry>  
</acl-entries>  
</acl-set>  
</acl-sets>  
</acl>
```

## Command Syntax

```
(<1-268435453>|) (deny|permit) icmp (any) (any) <0-255> (vlan <1-4094>|) (inner-  
vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-type

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">  
<acl-sets>
```

```

<acl-set>
  <type>mac</type>
  <config>
    <type>mac</type>
    <name>WORD</name>
  </config>
  <name>NAME</name>
<acl-entries>
<acl-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
  <config>
    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </protocol-icmp><!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <icmp-type>0</icmp-type> <!-- operation="delete"-->
    <dscp>default</dscp> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmp (any) (any) <0-255> dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
  (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-type

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          </protocol-icmp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <icmp-type>0</icmp-type> <!-- operation="delete"-->
          <precedence>routine</precedence> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmp (any) (any) <0-255> precedence
(routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure protocol name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-name

Attribute Type: union

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">

```

```

<acl-sets>
<acl-set>
  <type>mac</type>
  <config>
    <type>mac</type>
    <name>WORD</name>
  </config>
  <name>NAME</name>
<acl-entries>
<acl-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
  <config>
    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    <protocol-name>igmp</protocol-name> <!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    </fragments><!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit)
  (igmp|ipip|ipv6ip|rsvp|gre|esp|ahp|eigrp|ospf|pim|ipcomp|vrrp|any|<0-255>) (any)
  (any) fragments (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
  (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-name

Attribute Type: enum (igmp|ipip|ipv6ip|rsvp|gre|esp|ahp|eigrp|ospf|pim|ipcomp|vrrp|any)

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          <protocol-name>igmp</protocol-name> <!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          </fragments><!-- operation="delete"-->
          <dscp>default</dscp> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit)
  (igmp|ipip|ipv6ip|rsvp|gre|esp|ahp|eigrp|ospf|pim|ipcomp|vrrp|any) (any) (any)
  fragments dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
  (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-name

Attribute Type: enum (igmp|ipip|ipv6ip|rsvp|gre|esp|ahp|eigrp|ospf|pim|ipcomp|vrrp|any)

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
  <acl-set>
    <type>mac</type>
    <config>
      <type>mac</type>
      <name>WORD</name>
    </config>
    <name>NAME</name>
  <acl-entries>
  <acl-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv4>
    <config>
      <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
      <protocol-name>igmp</protocol-name> <!-- operation="delete"-->
      <source-address>any</source-address> <!-- operation="delete"-->
      <destination-address>any</destination-address> <!-- operation="delete"-->
      </fragments><!-- operation="delete"-->
      <precedence>routine</precedence> <!-- operation="delete"-->
      <vlan-id>1</vlan-id> <!-- operation="delete"-->
      <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
      <monitor-action>log</monitor-action> <!-- operation="delete"-->
      <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
  </ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
<(1-268435453>|) (deny|permit)
  (igmp|ipip|ipv6ip|rsvp|gre|esp|ahp|eigrp|ospf|pim|ipcomp|vrrp|any) (any) (any)
  fragments precedence
  (routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
  <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-name

Attribute Type: enum (igmp|ipip|ipv6ip|rsvp|gre|esp|ahp|eigrp|ospf|pim|ipcomp|vrrp|any)

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          <protocol-name>igmp</protocol-name> <!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit)
  (igmp|ipip|ipv6ip|rsvp|gre|esp|ahp|eigrp|ospf|pim|ipcomp|vrrp|any) (any) (any)
  (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port
IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-name

Attribute Type: enum (igmp|ipip|ipv6ip|rsvp|gre|esp|ahp|eigrp|ospf|pim|ipcomp|vrrp|any)

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">

```

```

<acl-sets>
<acl-set>
  <type>mac</type>
  <config>
    <type>mac</type>
    <name>WORD</name>
  </config>
  <name>NAME</name>
<acl-entries>
<acl-entry>
  <sequence-id>1</sequence-id>
  <config>
    <sequence-id>1</sequence-id>
  </config>
  <ipv4>
  <config>
    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    <protocol-name>igmp</protocol-name> <!-- operation="delete"-->
    <source-address>any</source-address> <!-- operation="delete"-->
    <destination-address>any</destination-address> <!-- operation="delete"-->
    <dscp>default</dscp> <!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
  </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit)
  (igmp|ipip|ipv6ip|rsvp|gre|esp|ahp|eigrp|ospf|pim|ipcomp|vrrp|any) (any) (any)
  dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
  (redirect-to-port IFNAME|)

```

---

## Configure ipv4 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-name

Attribute Type: enum (igmp|ipip|ipv6ip|rsvp|gre|esp|ahp|eigrp|ospf|pim|ipcomp|vrrp|any)

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: precedence

Attribute Type: enum (routine|priority|immediate|flash|flashoverride|critical|internet|network)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <type>mac</type>
      <config>
        <type>mac</type>
        <name>WORD</name>
      </config>
      <name>NAME</name>
    </acl-set>
  </acl-sets>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv4>
        <config>
          <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
          <protocol-name>igmp</protocol-name> <!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!-- operation="delete"-->
          <precedence>routine</precedence> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv4>
    </acl-entry>
  </acl-entries>
</acl>
```

```

    </config>
</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit)
  (igmp|ipip|ipv6ip|rsvp|gre|esp|ahp|eigrp|ospf|pim|ipcomp|vrrp|any) (any) (any)
  precedence
  (routine|priority|immediate|flash|flashoverride|critical|internet|network) (vlan
  <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure fragment monitor action

Use this attribute to enable logging or sampling of the packets on which the match occurred (in-direction only).

This command is supported when following feature are enabled CUSTOM1 ACL feature

Attribute Name: fragment-monitor-action

Attribute Type: enum (log|sample)

Attribute Name: fragment-forwarding-action

Attribute Type: enum (deny-all|permit-all)

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
  <acl-set>
    <type>mac</type>
    <config>
      <type>mac</type>
      <name>WORD</name>
    </config>
    <name>NAME</name>
  </acl-sets>
  <acl-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv4>
    <fragment-actions>
    <config>
      <fragment-forwarding-action>deny-all</fragment-forwarding-action> <!--
operation="delete"-->
      <fragment-monitor-action>log</fragment-monitor-action> <!--
operation="delete"-->
    </config>
  </fragment-actions>

```

```

</ipv4>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

### Command Syntax

```
(<1-268435453>|) fragments (deny-all|permit-all) ((log|sample)|)
```

---

## Configure standard-acl-sets type

Type indicates the fields allowed in the ACL entries belonging to the standard ACL set (ip, ipv6)

Attribute Name: type

Attribute Type: enum (standard\_ip|standard\_ipv6)

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<standard-acl-sets>
<standard-acl-set>
  <type>standard_ip</type>
  <config>
    <type>standard_ip</type>
    <name>WORD</name>
  </config>
  <name>NAME</name>
</standard-acl-set>
</standard-acl-sets>
</acl>

```

### Command Syntax

```
ip access-list standard NAME
```

---

## Configure standard-acl-sets type

Type indicates the fields allowed in the ACL entries belonging to the standard ACL set (ip, ipv6)

Attribute Name: type

Attribute Type: enum (standard\_ip|standard\_ipv6)

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<standard-acl-sets>
<standard-acl-set>
  <type>standard_ipv6</type>
  <config>
    <type>standard_ipv6</type>
    <name>WORD</name>
  </config>

```

```

    <name>NAME</name>
  </standard-acl-set>
</standard-acl-sets>
</acl>

```

## Command Syntax

```
ipv6 access-list standard NAME
```

---

## Configure ipv4-acl-entry source-address

Source IPv4 address prefix.

Attribute Name: source-address

Attribute Type: union

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <standard-acl-sets>
  <standard-acl-set>
    <type>standard_ip</type>
    <config>
      <type>standard_ip</type>
      <name>WORD</name>
    </config>
    <name>NAME</name>
  </standard-acl-set>
  <ipv4-acl-entries>
  <ipv4-acl-entry>
    <source-address>any</source-address>
    <config>
      <source-address>any</source-address>
      <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
    </config>
  </ipv4-acl-entry>
</ipv4-acl-entries>
</standard-acl-set>
</standard-acl-sets>
</acl>

```

## Command Syntax

```
(deny|permit) (any|host A.B.C.D|A.B.C.D/M|A.B.C.D A.B.C.D)
```

---

## IPI-ACL-IPV6

---

### Configure redirect interface name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: union

Attribute Name: destination-address

Attribute Type: union

Attribute Name: dscp

Attribute Type: union

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
```

```

        <name>WORD</name>
        <type>mac</type>
    </config>
    <type>mac</type>
    <acl-entries>
        <acl-entry>
            <sequence-id>1</sequence-id>
            <config>
                <sequence-id>1</sequence-id>
            </config>
            <ipv6>
                <config>
                    <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
                    </protocol-tcp><!-- operation="delete"-->
                    <source-address>any</source-address> <!-- operation="delete"-->
operation="delete"-->
                    <destination-address>any</destination-address> <!--
                    <dscp>default</dscp> <!-- operation="delete"-->
                    <flow-label>0</flow-label> <!-- operation="delete"-->
                    <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
                    <vlan-id>1</vlan-id> <!-- operation="delete"-->
                    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
                    <monitor-action>log</monitor-action> <!-- operation="delete"-->
operation="delete"-->
                    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
                </config>
            </ipv6>
        </acl-entry>
    </acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any|X:X::X:X/M|X:X::X:X X:X::X:X)
  (any|X:X::X:X/M|X:X::X:X X:X::X:X) (dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7|<0-63>|)) (flow-label <0-1048575>|)
  ({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
  ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)  
 Attribute Name: protocol-tcp  
 Attribute Type: empty  
 Attribute Name: source-address  
 Attribute Type: enum (any)  
 Attribute Name: destination-address  
 Attribute Type: enum (any)  
 Attribute Name: destination-port-operator  
 Attribute Type: enum (eq|neq|lt|gt)  
 Attribute Name: tcp-destination-port  
 Attribute Type: union  
 Attribute Name: dscp  
 Attribute Type: enum  
 (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)  
 Attribute Name: flow-label  
 Attribute Type: uint32  
 Attribute Range: 0-1048575  
 Attribute Name: tcp-flags  
 Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)  
 Attribute Name: vlan-id  
 Attribute Type: uint16  
 Attribute Range: 1-4094  
 Attribute Name: inner-vlan-id  
 Attribute Type: uint16  
 Attribute Range: 1-4094  
 Attribute Name: monitor-action  
 Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
```

```

    <config>
      <sequence-id>1</sequence-id>
    </config>
  <ipv6>
    <config>
      <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
      </protocol-tcp><!-- operation="delete"-->
      <source-address>any</source-address> <!-- operation="delete"-->
      <destination-address>any</destination-address> <!--
operation="delete"-->
      <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
      <tcp-destination-port>echo</tcp-destination-port> <!--
operation="delete"-->
      <dscp>default</dscp> <!-- operation="delete"-->
      <flow-label>0</flow-label> <!-- operation="delete"-->
      <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
      <vlan-id>1</vlan-id> <!-- operation="delete"-->
      <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
      <monitor-action>log</monitor-action> <!-- operation="delete"-->
      <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
  </ipv6>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (any) (eq|neq|lt|gt)
(echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls|<0-
65535>) (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure type

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)  
 Attribute Name: protocol-tcp  
 Attribute Type: empty  
 Attribute Name: source-address  
 Attribute Type: enum (any)  
 Attribute Name: destination-address  
 Attribute Type: enum (any)  
 Attribute Name: lower-destination-port-in-range  
 Attribute Type: uint16  
 Attribute Range: 0-65535  
 Attribute Name: upper-destination-port-in-range  
 Attribute Type: uint16  
 Attribute Range: 0-65535  
 Attribute Name: dscp  
 Attribute Type: enum  
 (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)  
 Attribute Name: flow-label  
 Attribute Type: uint32  
 Attribute Range: 0-1048575  
 Attribute Name: tcp-flags  
 Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)  
 Attribute Name: vlan-id  
 Attribute Type: uint16  
 Attribute Range: 1-4094  
 Attribute Name: inner-vlan-id  
 Attribute Type: uint16  
 Attribute Range: 1-4094  
 Attribute Name: monitor-action  
 Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    </acl-set>
  </acl-sets>
</acl>
```

```

    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv6>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            </protocol-tcp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <destination-address>any</destination-address> <!--
operation="delete"-->
            <lower-destination-port-in-range>0</lower-destination-port-in-
range> <!-- operation="delete"-->
            <upper-destination-port-in-range>0</upper-destination-port-in-
range> <!-- operation="delete"-->
            <dscp>default</dscp> <!-- operation="delete"-->
            <flow-label>0</flow-label> <!-- operation="delete"-->
            <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv6>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (any) range <0-65535> <0-65535> (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure sequence id

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
      <ipv6>

```

```

        <config>
          <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          </protocol-tcp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!--
operation="delete"-->
          </fragments><!-- operation="delete"-->
          <dscp>default</dscp> <!-- operation="delete"-->
          <flow-label>0</flow-label> <!-- operation="delete"-->
          <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv6>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (any) fragments (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure forwarding action

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-source-port

Attribute Type: union

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv6>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            </protocol-tcp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <source-port-operator>eq</source-port-operator> <!--
operation="delete"-->
```

```

operation="delete"--> <tcp-source-port>echo</tcp-source-port> <!--
operation="delete"--> <destination-address>any</destination-address> <!--
                        <dscp>default</dscp> <!-- operation="delete"-->
                        <flow-label>0</flow-label> <!-- operation="delete"-->
                        <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
                        <vlan-id>1</vlan-id> <!-- operation="delete"-->
                        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
                        <monitor-action>log</monitor-action> <!-- operation="delete"-->
operation="delete"--> <redirect-interface-name>IFNAME</redirect-interface-name> <!--
                        </config>
                        </ipv6>
                        </acl-entry>
                        </acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (eq|neq|lt|gt)
(echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls|<0-
65535>) (any) (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure protocol tcp

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-source-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-destination-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: dscp

Attribute Type: enum (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

```

        </config>
        <ipv6>
        <config>
operation="delete"-->    <forwarding-action>deny</forwarding-action> <!--
        </protocol-tcp><!-- operation="delete"-->
        <source-address>any</source-address> <!-- operation="delete"-->
operation="delete"-->    <source-port-operator>eq</source-port-operator> <!--
operation="delete"-->    <tcp-source-port>echo</tcp-source-port> <!--
operation="delete"-->    <destination-address>any</destination-address> <!--
operation="delete"-->    <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->    <tcp-destination-port>echo</tcp-destination-port> <!--
operation="delete"-->    <dscp>default</dscp> <!-- operation="delete"-->
        <flow-label>0</flow-label> <!-- operation="delete"-->
        <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
operation="delete"-->    <redirect-interface-name>IFNAME</redirect-interface-name> <!--
        </config>
        </ipv6>
        </acl-entry>
    </acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) (eq|neq|lt|gt)
(echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
(any) (eq|neq|lt|gt) (echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
(dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure source address

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

---

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-source-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv6>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            </protocol-tcp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <source-port-operator>eq</source-port-operator> <!--
operation="delete"-->
            <tcp-source-port>echo</tcp-source-port> <!--
operation="delete"-->
            <destination-address>any</destination-address> <!--
operation="delete"-->
            <lower-destination-port-in-range>0</lower-destination-port-in-
range> <!-- operation="delete"-->
            <upper-destination-port-in-range>0</upper-destination-port-in-
range> <!-- operation="delete"-->
            <dscp>default</dscp> <!-- operation="delete"-->
            <flow-label>0</flow-label> <!-- operation="delete"-->
            <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv6>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```
(<1-268435453>|) (deny|permit) tcp (any) (eq|neq|lt|gt)
(echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
(any) range <0-65535> <0-65535> (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)
```

## Configure lower source port in range

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
            </config>
            <ipv6>
              <config>
                <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
                </protocol-tcp><!-- operation="delete"-->
                <source-address>any</source-address> <!-- operation="delete"-->
                <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
                <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
                <destination-address>any</destination-address> <!--
operation="delete"-->
                <dscp>default</dscp> <!-- operation="delete"-->
                <flow-label>0</flow-label> <!-- operation="delete"-->
                <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
                <vlan-id>1</vlan-id> <!-- operation="delete"-->
                <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
                <monitor-action>log</monitor-action> <!-- operation="delete"-->
                <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
              </config>
            </ipv6>
          </acl-entry>
        </acl-entries>
      </acl-set>
```

```
</acl-sets>
</acl>
```

## Command Syntax

```
(<1-268435453>|) (deny|permit) tcp (any) range <0-65535> <0-65535> (any) (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure upper source port in range

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: tcp-destination-port

Attribute Type: enum (echo|discard|daytime|chargen|ftp-  
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop2|pop3|sunrpc|ident|nntp|bgp|irc|p  
im-auto-rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv6>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            </protocol-tcp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
            <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
            <destination-address>any</destination-address> <!--
operation="delete"-->
            <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
            <tcp-destination-port>echo</tcp-destination-port> <!--
operation="delete"-->
            <dscp>default</dscp> <!-- operation="delete"-->
            <flow-label>0</flow-label> <!-- operation="delete"-->
            <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
          </config>
        </ipv6>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

```

        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv6>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) range <0-65535> <0-65535> (any)
(eq|neq|lt|gt) (echo|discard|daytime|chargen|ftp-
data|ftp|ssh|telnet|smtp|time|whois|tacacs|domain|gopher|finger|www|hostname|pop
2|pop3|sunrpc|ident|nntp|bgp|irc|pim-auto-
rp|exec|login|cmd|lpd|talk|uucp|klogin|kshell|netconf-ssh|drip|netconf-tls)
(dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure destination address

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-tcp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: tcp-flags

Attribute Type: bits (ack|established|fin|psh|rst|syn|urg)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv6>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
```

```

        </protocol-tcp><!-- operation="delete"-->
        <source-address>any</source-address> <!-- operation="delete"-->
        <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
        <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
        <destination-address>any</destination-address> <!--
operation="delete"-->
        <lower-destination-port-in-range>0</lower-destination-port-in-
range> <!-- operation="delete"-->
        <upper-destination-port-in-range>0</upper-destination-port-in-
range> <!-- operation="delete"-->
        <dscp>default</dscp> <!-- operation="delete"-->
        <flow-label>0</flow-label> <!-- operation="delete"-->
        <tcp-flags>ack</tcp-flags> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
</ipv6>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) tcp (any) range <0-65535> <0-65535> (any) range <0-
65535> <0-65535> (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|)
({ack|established|fin|psh|rst|syn|urg}|) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure protocol udp

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
        <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <ipv6>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              </protocol-udp><!-- operation="delete"-->
              <source-address>any</source-address> <!-- operation="delete"-->
              <destination-address>any</destination-address> <!--
operation="delete"-->
              <dscp>default</dscp> <!-- operation="delete"-->
              <flow-label>0</flow-label> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
```

```

        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
    </ipv6>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (any) (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure destination port operator

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-destination-port

Attribute Type: union

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <ipv6>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              </protocol-udp><!-- operation="delete"-->
              <source-address>any</source-address> <!-- operation="delete"-->
              <destination-address>any</destination-address> <!--
operation="delete"-->
              <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
              <udp-destination-port>echo</udp-destination-port> <!--
operation="delete"-->
              <dscp>default</dscp> <!-- operation="delete"-->
              <flow-label>0</flow-label> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
            </config>
          </ipv6>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
```

---

```
</acl>
```

## Command Syntax

```
(<1-268435453>|) (deny|permit) udp (any) (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp|<0-65535>) (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure lower destination port in range

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <ipv6>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              </protocol-udp><!-- operation="delete"-->
              <source-address>any</source-address> <!-- operation="delete"-->
              <destination-address>any</destination-address> <!--
operation="delete"-->
              <lower-destination-port-in-range>0</lower-destination-port-in-
range> <!-- operation="delete"-->
              <upper-destination-port-in-range>0</upper-destination-port-in-
range> <!-- operation="delete"-->
              <dscp>default</dscp> <!-- operation="delete"-->
              <flow-label>0</flow-label> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
            </config>
          </ipv6>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>
```

## Command Syntax

```
(<1-268435453>|) (deny|permit) udp (any) (any) range <0-65535> <0-65535> (dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
  4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure fragments

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
```

```

<acl-set>
  <name>NAME</name>
  <config>
    <name>WORD</name>
    <type>mac</type>
  </config>
  <type>mac</type>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv6>
        <config>
          <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          </protocol-udp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!--
operation="delete"-->
          </fragments><!-- operation="delete"-->
          <dscp>default</dscp> <!-- operation="delete"-->
          <flow-label>0</flow-label> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv6>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (any) fragments (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure source port operator

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-source-port

Attribute Type: union

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
```

```

        <sequence-id>1</sequence-id>
    </config>
    <ipv6>
    <config>
        <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
        </protocol-udp><!-- operation="delete"-->
        <source-address>any</source-address> <!-- operation="delete"-->
        <source-port-operator>eq</source-port-operator> <!--
operation="delete"-->
        <udp-source-port>echo</udp-source-port> <!--
operation="delete"-->
        <destination-address>any</destination-address> <!--
operation="delete"-->
        <dscp>default</dscp> <!-- operation="delete"-->
        <flow-label>0</flow-label> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
    </ipv6>
    </acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp|<0-65535>) (any) (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure udp source port

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-source-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-destination-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
```

```

    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv6>
    <config>
      <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
      </protocol-udp><!-- operation="delete"-->
      <source-address>any</source-address> <!-- operation="delete"-->
operation="delete"-->
      <source-port-operator>eq</source-port-operator> <!--
operation="delete"-->
      <udp-source-port>echo</udp-source-port> <!--
operation="delete"-->
      <destination-address>any</destination-address> <!--
operation="delete"-->
      <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
      <udp-destination-port>echo</udp-destination-port> <!--
operation="delete"-->
      <dscp>default</dscp> <!-- operation="delete"-->
      <flow-label>0</flow-label> <!-- operation="delete"-->
      <vlan-id>1</vlan-id> <!-- operation="delete"-->
      <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
      <monitor-action>log</monitor-action> <!-- operation="delete"-->
      <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
    </config>
  </ipv6>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure upper destination port in range

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-source-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
```

```

<acl-sets>
  <acl-set>
    <name>NAME</name>
    <config>
      <name>WORD</name>
      <type>mac</type>
    </config>
    <type>mac</type>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv6>
        <config>
          <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          </protocol-udp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <source-port-operator>eq</source-port-operator> <!--
operation="delete"-->
          <udp-source-port>echo</udp-source-port> <!--
operation="delete"-->
          <destination-address>any</destination-address> <!--
operation="delete"-->
          <lower-destination-port-in-range>0</lower-destination-port-in-
range> <!-- operation="delete"-->
          <upper-destination-port-in-range>0</upper-destination-port-in-
range> <!-- operation="delete"-->
          <dscp>default</dscp> <!-- operation="delete"-->
          <flow-label>0</flow-label> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv6>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) (eq|neq|lt|gt)
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbio
s-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-
rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) (any) range <0-65535> <0-65535>
(dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|

```

---

```
af43|cs5|ef|cs6|cs7)) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure dscp

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

**Netconf edit-config payload**

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <ipv6>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              </protocol-udp><!-- operation="delete"-->
              <source-address>any</source-address> <!-- operation="delete"-->
              <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
              <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
              <destination-address>any</destination-address> <!--
operation="delete"-->
              <dscp>default</dscp> <!-- operation="delete"-->
              <flow-label>0</flow-label> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
            </config>
          </ipv6>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>

```

**Command Syntax**

```

(<1-268435453>|) (deny|permit) udp (any) range <0-65535> <0-65535> (any) (dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
  4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure udp destination port

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: udp-destination-port

Attribute Type: enum (echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|ftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
  <acl-set>
    <name>NAME</name>
    <config>
      <name>WORD</name>
      <type>mac</type>
    </config>
    <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv6>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            </protocol-udp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
operation="delete"-->
            <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
            <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
            <destination-address>any</destination-address> <!--
operation="delete"-->
            <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
            <udp-destination-port>echo</udp-destination-port> <!--
operation="delete"-->
            <dscp>default</dscp> <!-- operation="delete"-->
            <flow-label>0</flow-label> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv6>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
<1-268435453>|) (deny|permit) udp (any) range <0-65535> <0-65535> (any)
(eq|neq|lt|gt)
```

```
(echo|discard|time|nameserver|tacacs|domain|bootps|bootpc|tftp|sunrpc|ntp|netbios-ns|netbios-dgm|netbios-ss|snmp|snmptrap|xdmcp|dnsix|mobile-ip|pim-auto-rp|isakmp|biff|who|syslog|talk|rip|non500-isakmp) (dscp (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure flow label

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-udp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <ipv6>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              </protocol-udp><!-- operation="delete"-->
              <source-address>any</source-address> <!-- operation="delete"-->
              <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
              <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
              <destination-address>any</destination-address> <!--
operation="delete"-->
              <lower-destination-port-in-range>0</lower-destination-port-in-
range> <!-- operation="delete"-->
              <upper-destination-port-in-range>0</upper-destination-port-in-
range> <!-- operation="delete"-->
              <dscp>default</dscp> <!-- operation="delete"-->
              <flow-label>0</flow-label> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
            </config>
          </acl-entry>
        </acl-entries>
      </acl-set>
    </acl-sets>
  </acl>

```

```

    </ipv6>
  </acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) udp (any) range <0-65535> <0-65535> (any) range <0-
65535> <0-65535> (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure protocol icmp

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <ipv6>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              </protocol-icmp><!-- operation="delete"-->
              <source-address>any</source-address> <!-- operation="delete"-->
              <destination-address>any</destination-address> <!--
operation="delete"-->
              <dscp>default</dscp> <!-- operation="delete"-->
              <flow-label>0</flow-label> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
            </config>
          </ipv6>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>

```

### Command Syntax

```

(<1-268435453>|) (deny|permit) icmpv6 (any) (any) (dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
  4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure icmp message

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-message

Attribute Type: enum (beyond-scope|destination-unreachable|echo-reply|echo-request|header|hop-limit|mld-query|mld-reduction|mld-report|nd-na|nd-ns|next-header|no-admin|no-route|packet-too-big|parameter-option|parameter-problem|port-unreachable|reassembly-timeout|redirect|renum-command|renum-result|renum-seq-number|router-advertisement|router-renumbering|router-solicitation|time-exceeded|unreachable)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    </acl-set>
  </acl-sets>
</acl>
```

```

    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv6>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            </protocol-icmp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
operation="delete"-->
            <destination-address>any</destination-address> <!--
operation="delete"-->
            <icmp-message>beyond-scope</icmp-message> <!--
operation="delete"-->
            <dscp>default</dscp> <!-- operation="delete"-->
            <flow-label>0</flow-label> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv6>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmpv6 (any) (any) (beyond-scope|destination-
unreachable|echo-reply|echo-request|header|hop-limit|mld-query|mld-
reduction|mld-report|nd-na|nd-ns|next-header|no-admin|no-route|packet-too-
big|parameter-option|parameter-problem|port-unreachable|reassembly-
timeout|redirect|renum-command|renum-result|renum-seq-number|router-
advertisement|router-renumbering|router-solicitation|time-exceeded|unreachable)
(dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure icmp type

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-type

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
      <ipv6>
```

```

        <config>
          <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          </protocol-icmp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!--
operation="delete"-->
          <icmp-type>0</icmp-type> <!-- operation="delete"-->
          <dscp>default</dscp> <!-- operation="delete"-->
          <flow-label>0</flow-label> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv6>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmpv6 (any) (any) <0-255> (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure icmp code

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-type

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: icmp-code

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv6>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          </protocol-icmp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!--
operation="delete"-->
          <icmp-type>0</icmp-type> <!-- operation="delete"-->
          <icmp-code>0</icmp-code> <!-- operation="delete"-->
```

```

        <dscp>default</dscp> <!-- operation="delete"-->
        <flow-label>0</flow-label> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
    </ipv6>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmpv6 (any) (any) <0-255> <0-255> (dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
  4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure vlan id

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: fragments

Attribute Type: empty

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <ipv6>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              </protocol-icmp><!-- operation="delete"-->
              <source-address>any</source-address> <!-- operation="delete"-->
              <destination-address>any</destination-address> <!--
operation="delete"-->
              <dscp>default</dscp> <!-- operation="delete"-->
              <flow-label>0</flow-label> <!-- operation="delete"-->
              </fragments><!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
            </config>
          </ipv6>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>

```

## Command Syntax

```
(<1-268435453>|) (deny|permit) icmpv6 (any) (any) (dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) fragments (vlan <1-4094>|)
  (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure inner vlan id

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-message

Attribute Type: enum (beyond-scope|destination-unreachable|echo-reply|echo-request|header|hop-limit|mld-query|mld-reduction|mld-report|nd-na|nd-ns|next-header|no-admin|no-route|packet-too-big|parameter-option|parameter-problem|port-unreachable|reassembly-timeout|redirect|renum-command|renum-result|renum-seq-number|router-advertisement|router-renumbering|router-solicitation|time-exceeded|unreachable)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
  <acl-set>
    <name>NAME</name>
    <config>
      <name>WORD</name>
      <type>mac</type>
    </config>
    <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv6>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            </protocol-icmp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
operation="delete"-->
            <destination-address>any</destination-address> <!--
operation="delete"-->
            <icmp-message>beyond-scope</icmp-message> <!--
operation="delete"-->
            </fragments><!-- operation="delete"-->
            <dscp>default</dscp> <!-- operation="delete"-->
            <flow-label>0</flow-label> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv6>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) icmpv6 (any) (any) (beyond-scope|destination-
unreachable|echo-reply|echo-request|header|hop-limit|mld-query|mld-
reduction|mld-report|nd-na|nd-ns|next-header|no-admin|no-route|packet-too-
big|parameter-option|parameter-problem|port-unreachable|reassembly-
timeout|redirect|renum-command|renum-result|renum-seq-number|router-
advertisement|router-renumbering|router-solicitation|time-exceeded|unreachable)
fragments (dscp
```

```
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure monitor action

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-type

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: fragments

Attribute Type: empty

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <ipv6>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              </protocol-icmp><!-- operation="delete"-->
              <source-address>any</source-address> <!-- operation="delete"-->
              <destination-address>any</destination-address> <!--
operation="delete"-->
              <icmp-type>0</icmp-type> <!-- operation="delete"-->
              </fragments><!-- operation="delete"-->
              <dscp>default</dscp> <!-- operation="delete"-->
              <flow-label>0</flow-label> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
            </config>
          </ipv6>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmpv6 (any) (any) <0-255> fragments (dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
  4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure ipv6 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

---

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-icmp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: icmp-type

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: icmp-code

Attribute Type: uint8

Attribute Range: 0-255

Attribute Name: fragments

Attribute Type: empty

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
```

```

<name>NAME</name>
<config>
  <name>WORD</name>
  <type>mac</type>
</config>
  <type>mac</type>
<acl-entries>
  <acl-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv6>
      <config>
        <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
        </protocol-icmp><!-- operation="delete"-->
        <source-address>any</source-address> <!-- operation="delete"-->
        <destination-address>any</destination-address> <!--
operation="delete"-->
        <icmp-type>0</icmp-type> <!-- operation="delete"-->
        <icmp-code>0</icmp-code> <!-- operation="delete"-->
        </fragments><!-- operation="delete"-->
        <dscp>default</dscp> <!-- operation="delete"-->
        <flow-label>0</flow-label> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
      </config>
    </ipv6>
  </acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) icmpv6 (any) (any) <0-255> <0-255> fragments (dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
  4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure protocol sctp

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-sctp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv6>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
```

```

        </protocol-sctp><!-- operation="delete"-->
        <source-address>any</source-address> <!-- operation="delete"-->
        <destination-address>any</destination-address> <!--
operation="delete"-->
        <dscp>default</dscp> <!-- operation="delete"-->
        <flow-label>0</flow-label> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
    </ipv6>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) sctp (any) (any) (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure ipv6 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-sctp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv6>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            </protocol-sctp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <destination-address>any</destination-address> <!--
operation="delete"-->
            </fragments><!-- operation="delete"-->
            <dscp>default</dscp> <!-- operation="delete"-->
            <flow-label>0</flow-label> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv6>
      </acl-entry>
    </acl-entries>
  </acl-sets>
</acl>
```

```

</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) sctp (any) (any) fragments (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure sctp destination port

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-sctp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: sctp-destination-port

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <ipv6>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              </protocol-sctp><!-- operation="delete"-->
              <source-address>any</source-address> <!-- operation="delete"-->
              <destination-address>any</destination-address> <!--
operation="delete"-->
              <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
              <sctp-destination-port>0</sctp-destination-port> <!--
operation="delete"-->
              <dscp>default</dscp> <!-- operation="delete"-->
              <flow-label>0</flow-label> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
            </config>
          </ipv6>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) sctp (any) (any) (eq|neq|lt|gt) <0-65535> (dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
```

---

```
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure ipv6 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-sctp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

**Netconf edit-config payload**

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
  <acl-set>
    <name>NAME</name>
    <config>
      <name>WORD</name>
      <type>mac</type>
    </config>
    <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv6>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            </protocol-sctp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
            <destination-address>any</destination-address> <!--
operation="delete"-->
            <lower-destination-port-in-range>0</lower-destination-port-in-
range> <!-- operation="delete"-->
            <upper-destination-port-in-range>0</upper-destination-port-in-
range> <!-- operation="delete"-->
            <dscp>default</dscp> <!-- operation="delete"-->
            <flow-label>0</flow-label> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv6>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>

```

**Command Syntax**

```

(<1-268435453>|) (deny|permit) sctp (any) (any) range <0-65535> <0-65535> (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure sctp source port

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-sctp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: sctp-source-port

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
```

```

<config>
  <name>WORD</name>
  <type>mac</type>
</config>
  <type>mac</type>
<acl-entries>
  <acl-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <ipv6>
      <config>
        <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          </protocol-sctp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
          <source-port-operator>eq</source-port-operator> <!--
operation="delete"-->
            <sctp-source-port>0</sctp-source-port> <!-- operation="delete"-->
->
          <destination-address>any</destination-address> <!--
operation="delete"-->
            <dscp>default</dscp> <!-- operation="delete"-->
            <flow-label>0</flow-label> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv6>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) sctp (any) (eq|neq|lt|gt) <0-65535> (any) (dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
  4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure ipv6 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

---

Attribute Name: forwarding-action  
Attribute Type: enum (deny|permit)  
Attribute Name: protocol-sctp  
Attribute Type: empty  
Attribute Name: source-address  
Attribute Type: enum (any)  
Attribute Name: source-port-operator  
Attribute Type: enum (eq|neq|lt|gt)  
Attribute Name: sctp-source-port  
Attribute Type: uint16  
Attribute Range: 0-65535  
Attribute Name: destination-address  
Attribute Type: enum (any)  
Attribute Name: destination-port-operator  
Attribute Type: enum (eq|neq|lt|gt)  
Attribute Name: sctp-destination-port  
Attribute Type: uint16  
Attribute Range: 0-65535  
Attribute Name: dscp  
Attribute Type: enum  
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)  
Attribute Name: flow-label  
Attribute Type: uint32  
Attribute Range: 0-1048575  
Attribute Name: vlan-id  
Attribute Type: uint16  
Attribute Range: 1-4094  
Attribute Name: inner-vlan-id  
Attribute Type: uint16  
Attribute Range: 1-4094  
Attribute Name: monitor-action  
Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
```

```

        <name>WORD</name>
        <type>mac</type>
    </config>
    <type>mac</type>
<acl-entries>
    <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
            <sequence-id>1</sequence-id>
        </config>
        <ipv6>
            <config>
                <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
                </protocol-sctp><!-- operation="delete"-->
                <source-address>any</source-address> <!-- operation="delete"-->
operation="delete"-->
                <source-port-operator>eq</source-port-operator> <!--
->
                <sctp-source-port>0</sctp-source-port> <!-- operation="delete"-
operation="delete"-->
                <destination-address>any</destination-address> <!--
operation="delete"-->
                <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
                <sctp-destination-port>0</sctp-destination-port> <!--
operation="delete"-->
                <dscp>default</dscp> <!-- operation="delete"-->
                <flow-label>0</flow-label> <!-- operation="delete"-->
                <vlan-id>1</vlan-id> <!-- operation="delete"-->
                <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
                <monitor-action>log</monitor-action> <!-- operation="delete"-->
                <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
            </config>
        </ipv6>
    </acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) sctp (any) (eq|neq|lt|gt) <0-65535> (any)
(eq|neq|lt|gt) <0-65535> (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure ipv6 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

---

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-sctp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: source-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: sctp-source-port

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

**Netconf edit-config payload**

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
  <acl-set>
    <name>NAME</name>
    <config>
      <name>WORD</name>
      <type>mac</type>
    </config>
    <type>mac</type>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv6>
        <config>
          <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          </protocol-sctp><!-- operation="delete"-->
          <source-address>any</source-address> <!-- operation="delete"-->
operation="delete"-->
          <source-port-operator>eq</source-port-operator> <!--
->
          <sctp-source-port>0</sctp-source-port> <!-- operation="delete"-
operation="delete"-->
          <destination-address>any</destination-address> <!--
range> <!-- operation="delete"-->
          <lower-destination-port-in-range>0</lower-destination-port-in-
range> <!-- operation="delete"-->
          <upper-destination-port-in-range>0</upper-destination-port-in-
range> <!-- operation="delete"-->
          <dscp>default</dscp> <!-- operation="delete"-->
          <flow-label>0</flow-label> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
          </config>
        </ipv6>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>

```

**Command Syntax**

```

(<1-268435453>|) (deny|permit) sctp (any) (eq|neq|lt|gt) <0-65535> (any) range <0-
65535> <0-65535> (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|

```

---

```
af43|cs5|ef|cs6|cs7)) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure ipv6 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-sctp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

**Netconf edit-config payload**

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
  <acl-set>
    <name>NAME</name>
    <config>
      <name>WORD</name>
      <type>mac</type>
    </config>
    <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv6>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            </protocol-sctp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
operation="delete"-->
            <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
            <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
            <destination-address>any</destination-address> <!--
operation="delete"-->
            <dscp>default</dscp> <!-- operation="delete"-->
            <flow-label>0</flow-label> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv6>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>

```

**Command Syntax**

```

(<1-268435453>|) (deny|permit) sctp (any) range <0-65535> <0-65535> (any) (dscp
  (default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
  af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
  4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure ipv6 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-sctp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: destination-port-operator

Attribute Type: enum (eq|neq|lt|gt)

Attribute Name: sctp-destination-port

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv6>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            </protocol-sctp><!-- operation="delete"-->
            <source-address>any</source-address> <!-- operation="delete"-->
operation="delete"-->
            <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
            <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
            <destination-address>any</destination-address> <!--
operation="delete"-->
            <destination-port-operator>eq</destination-port-operator> <!--
operation="delete"-->
            <sctp-destination-port>0</sctp-destination-port> <!--
operation="delete"-->
            <dscp>default</dscp> <!-- operation="delete"-->
            <flow-label>0</flow-label> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
          </config>
        </ipv6>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```
(<1-268435453>|) (deny|permit) sctp (any) range <0-65535> <0-65535> (any)
(eq|neq|lt|gt) <0-65535> (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure ipv6 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-sctp

Attribute Type: empty

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: lower-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-source-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: lower-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: upper-destination-port-in-range

Attribute Type: uint16

Attribute Range: 0-65535

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <ipv6>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              </protocol-sctp><!-- operation="delete"-->
              <source-address>any</source-address> <!-- operation="delete"-->
              <lower-source-port-in-range>0</lower-source-port-in-range> <!--
operation="delete"-->
              <upper-source-port-in-range>0</upper-source-port-in-range> <!--
operation="delete"-->
              <destination-address>any</destination-address> <!--
operation="delete"-->
              <lower-destination-port-in-range>0</lower-destination-port-in-
range> <!-- operation="delete"-->
              <upper-destination-port-in-range>0</upper-destination-port-in-
range> <!-- operation="delete"-->
              <dscp>default</dscp> <!-- operation="delete"-->
              <flow-label>0</flow-label> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
            </config>
          </acl-entry>
        </acl-entries>
      </acl-set>
    </acl-sets>
  </acl>

```

```

    </ipv6>
  </acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) sctp (any) range <0-65535> <0-65535> (any) range <0-
65535> <0-65535> (dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

---

## Configure protocol name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-name

Attribute Type: union

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
  <acl-set>
    <name>NAME</name>
    <config>
      <name>WORD</name>
      <type>mac</type>
    </config>
    <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <ipv6>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            <protocol-name>ipipv6</protocol-name> <!-- operation="delete"--
>
            <source-address>any</source-address> <!-- operation="delete"-->
            <destination-address>any</destination-address> <!--
operation="delete"-->
            <dscp>default</dscp> <!-- operation="delete"-->
            <flow-label>0</flow-label> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
          </config>
        </ipv6>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit)
(ipipv6|ip6ip6|rsvp|gre|esp|ahp|ospf|pim|ipcomp|vrrp|any|<0-255>) (any) (any)
(dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)
```

---

## Configure ipv6 redirect-interface-name

Use this attribute to set the interface name on which packet to be redirected (in-direction only)

This command is supported when following feature are enabled IPV6 feature

Attribute Name: redirect-interface-name

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: protocol-name

Attribute Type: enum (ipipv6|ipv6ipv6|rsvp|gre|esp|ahp|ospf|pim|ipcomp|vrrp|any)

Attribute Name: source-address

Attribute Type: enum (any)

Attribute Name: destination-address

Attribute Type: enum (any)

Attribute Name: fragments

Attribute Type: empty

Attribute Name: dscp

Attribute Type: enum

(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|af43|cs5|ef|cs6|cs7)

Attribute Name: flow-label

Attribute Type: uint32

Attribute Range: 0-1048575

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
    </acl-set>
  </acl-sets>
</acl>
```

```

    <type>mac</type>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv6>
        <config>
          <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          <protocol-name>ipipv6</protocol-name> <!-- operation="delete"--
>
          <source-address>any</source-address> <!-- operation="delete"-->
          <destination-address>any</destination-address> <!--
operation="delete"-->
          </fragments><!-- operation="delete"-->
          <dscp>default</dscp> <!-- operation="delete"-->
          <flow-label>0</flow-label> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <redirect-interface-name>IFNAME</redirect-interface-name> <!--
operation="delete"-->
        </config>
      </ipv6>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit)
(ipipv6|ip6ip6|rsvp|gre|esp|ahp|ospf|pim|ipcomp|vrrp|any) (any) (any) fragments
(dscp
(default|cs1|af11|af12|af13|cs2|af21|af22|af23|cs3|af31|af32|af33|cs4|af41|af42|
af43|cs5|ef|cs6|cs7)|) (flow-label <0-1048575>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|) (redirect-to-port IFNAME|)

```

## Configure fragment monitor action

Use this attribute to enable logging or sampling of the packets on which the match occurred (in-direction only).

This command is supported when following feature are enabled CUSTOM1 ACL feature, IPV6 feature

Attribute Name: fragment-monitor-action

Attribute Type: enum (log|sample)

Attribute Name: fragment-forwarding-action

Attribute Type: enum (deny-all|permit-all)

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
  <acl-set>
    <name>NAME</name>
    <config>
      <name>WORD</name>
      <type>mac</type>
    </config>
    <type>mac</type>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <ipv6>
        <fragment-actions>
          <config>
            <fragment-forwarding-action>deny-all</fragment-forwarding-
action> <!-- operation="delete"-->
            <fragment-monitor-action>log</fragment-monitor-action> <!--
operation="delete"-->
          </config>
        </fragment-actions>
      </ipv6>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```
(<1-268435453>|) fragments (deny-all|permit-all) ((log|sample)|)
```

---

## Configure ipv6-acl-entry source-address

Source IPv6 address prefix.

This command is supported when following feature are enabled IPV6 feature

Attribute Name: source-address

Attribute Type: union

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<standard-acl-sets>
  <standard-acl-set>

```

```

<name>NAME</name>
<config>
  <name>WORD</name>
  <type>standard_ip</type>
</config>
  <type>standard_ip</type>
<ipv6-acl-entries>
<ipv6-acl-entry>
  <source-address>any</source-address>
  <config>
    <source-address>any</source-address>
    <forwarding-action>deny</forwarding-action> <!-- operation="delete"-->
  </config>
</ipv6-acl-entry>
</ipv6-acl-entries>
</standard-acl-set>
</standard-acl-sets>
</acl>

```

### Command Syntax

```
(deny|permit) (any|X:X::X:X/M|X:X::X:X X:X::X:X)
```

---

## IPI-ACL-ARP

---

### Configure source mac any

Use this attribute to indicate any source address.

Attribute Name: source-mac-any

Attribute Type: empty

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: source-ip-address

Attribute Type: union

Attribute Name: destination-ip-address

Attribute Type: union

Attribute Name: destination-mac-any

Attribute Type: empty

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
            </config>
            <arp>
              <config>
                <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
                <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
                <source-ip-address>any</source-ip-address> <!--
operation="delete"-->
                <destination-ip-address>any</destination-ip-address> <!--
operation="delete"-->
                </destination-mac-any><!-- operation="delete"-->
                <vlan-id>1</vlan-id> <!-- operation="delete"-->
                <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
                <monitor-action>log</monitor-action> <!-- operation="delete"-->
                </source-mac-any><!-- operation="delete"-->
              </config>
            </arp>
          </acl-entry>
        </acl-entries>
      </acl-set>
    </acl-sets>
  </acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) response ip (any|host A.B.C.D|A.B.C.D/M|A.B.C.D
A.B.C.D) (any|host A.B.C.D|A.B.C.D/M|A.B.C.D A.B.C.D) mac any any (vlan <1-
4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
```

---

## Configure name

Use this attribute to indicate any source address.

Attribute Name: source-mac-any

Attribute Type: empty

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: source-ip-address

Attribute Type: enum (any)

Attribute Name: destination-ip-address

Attribute Type: enum (any)

Attribute Name: destination-mac-host

Attribute Type: string

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <arp>
          <config>
```

```

operation="delete"--> <forwarding-action>deny</forwarding-action> <!--
operation="delete"--> <arp-packet-type>none</arp-packet-type> <!--
operation="delete"--> <source-ip-address>any</source-ip-address> <!--
operation="delete"--> <destination-ip-address>any</destination-ip-address> <!--
operation="delete"--> <destination-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-host> <!-- operation="delete"-->
<vlan-id>1</vlan-id> <!-- operation="delete"-->
<inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
<monitor-action>log</monitor-action> <!-- operation="delete"-->
</source-mac-any><!-- operation="delete"-->
    </config>
  </arp>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) response ip (any) (any) mac any host (XX-XX-XX-XX-
XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|)

```

---

## Configure type

Use this attribute to indicate any source address.

Attribute Name: source-mac-any

Attribute Type: empty

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: source-ip-address

Attribute Type: enum (any)

Attribute Name: destination-ip-address

Attribute Type: enum (any)

Attribute Name: destination-mac-address

Attribute Type: string

Attribute Name: destination-mac-mask

Attribute Type: string

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
            </config>
            <arp>
              <config>
                <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
                <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
                <source-ip-address>any</source-ip-address> <!--
operation="delete"-->
                <destination-ip-address>any</destination-ip-address> <!--
operation="delete"-->
                <destination-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-address> <!-- operation="delete"--
>
                <destination-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-mask> <!-- operation="delete"-->
                <vlan-id>1</vlan-id> <!-- operation="delete"-->
                <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
                <monitor-action>log</monitor-action> <!-- operation="delete"-->
                </source-mac-any><!-- operation="delete"-->
              </config>
            </arp>
          </acl-entry>
        </acl-entries>
      </acl-set>
    </acl-sets>
  </acl>
```

## Command Syntax

```
(<1-268435453>|) (deny|permit) response ip (any) (any) mac any (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|)
```

---

## Configure source mac host

Use this attribute to set Host source address.

Attribute Name: source-mac-host

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: source-ip-address

Attribute Type: enum (any)

Attribute Name: destination-ip-address

Attribute Type: enum (any)

Attribute Name: destination-mac-any

Attribute Type: empty

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
```

```

        <sequence-id>1</sequence-id>
    </config>
    <sequence-id>1</sequence-id>
</config>
<arp>
<config>
    <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
    <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
    <source-ip-address>any</source-ip-address> <!--
operation="delete"-->
    <destination-ip-address>any</destination-ip-address> <!--
operation="delete"-->
    </destination-mac-any><!-- operation="delete"-->
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
    <monitor-action>log</monitor-action> <!-- operation="delete"-->
    <source-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-host> <!-- operation="delete"-->
    </config>
</arp>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) response ip (any) (any) mac host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) any (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|)

```

---

## Configure sequence id

Use this attribute to set Host source address.

Attribute Name: source-mac-host

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: source-ip-address

Attribute Type: enum (any)

Attribute Name: destination-ip-address

Attribute Type: enum (any)

Attribute Name: destination-mac-host

Attribute Type: string

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
            </config>
            <arp>
              <config>
                <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
                <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
                <source-ip-address>any</source-ip-address> <!--
operation="delete"-->
                <destination-ip-address>any</destination-ip-address> <!--
operation="delete"-->
                <destination-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-host> <!-- operation="delete"-->
                <vlan-id>1</vlan-id> <!-- operation="delete"-->
                <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
                <monitor-action>log</monitor-action> <!-- operation="delete"-->
                <source-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-host> <!-- operation="delete"-->
              </config>
            </arp>
          </acl-entry>
        </acl-entries>
      </acl-set>
    </acl-sets>
```

---

```
</acl>
```

## Command Syntax

```
(<1-268435453>|) (deny|permit) response ip (any) (any) mac host (XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) host (XX-XX-XX-XX-XX-XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
```

---

## Configure forwarding action

Use this attribute to set Host source address.

Attribute Name: source-mac-host

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: source-ip-address

Attribute Type: enum (any)

Attribute Name: destination-ip-address

Attribute Type: enum (any)

Attribute Name: destination-mac-address

Attribute Type: string

Attribute Name: destination-mac-mask

Attribute Type: string

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
```

```

</config>
  <type>mac</type>
<acl-entries>
  <acl-entry>
    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <arp>
      <config>
        <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
        <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
        <source-ip-address>any</source-ip-address> <!--
operation="delete"-->
        <destination-ip-address>any</destination-ip-address> <!--
operation="delete"-->
        <destination-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-address> <!-- operation="delete"--
>
        <destination-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-mask> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <source-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-host> <!-- operation="delete"-->
      </config>
    </arp>
  </acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) response ip (any) (any) mac host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|)

```

---

## Configure source mac address

Use this attribute to set source mac-address.

Attribute Name: source-mac-address

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: arp-packet-type  
 Attribute Type: enum (none|request|response)

Attribute Name: source-ip-address  
 Attribute Type: enum (any)

Attribute Name: destination-ip-address  
 Attribute Type: enum (any)

Attribute Name: source-mac-mask  
 Attribute Type: string

Attribute Name: destination-mac-any  
 Attribute Type: empty

Attribute Name: vlan-id  
 Attribute Type: uint16  
 Attribute Range: 1-4094

Attribute Name: inner-vlan-id  
 Attribute Type: uint16  
 Attribute Range: 1-4094

Attribute Name: monitor-action  
 Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <arp>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
            <source-ip-address>any</source-ip-address> <!--
operation="delete"-->
            <destination-ip-address>any</destination-ip-address> <!--
operation="delete"-->
```

```

        <source-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-mask> <!-- operation="delete"-->
        </destination-mac-any><!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <source-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-address> <!-- operation="delete"-->
    </config>
</arp>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) response ip (any) (any) mac (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) any (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|)

```

---

## Configure arp packet type

Use this attribute to set source mac-address.

Attribute Name: source-mac-address

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: source-ip-address

Attribute Type: enum (any)

Attribute Name: destination-ip-address

Attribute Type: enum (any)

Attribute Name: source-mac-mask

Attribute Type: string

Attribute Name: destination-mac-host

Attribute Type: string

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <arp>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
              <source-ip-address>any</source-ip-address> <!--
operation="delete"-->
              <destination-ip-address>any</destination-ip-address> <!--
operation="delete"-->
              <source-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-mask> <!-- operation="delete"-->
              <destination-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-host> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              <source-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-address> <!-- operation="delete"-->
            </config>
          </arp>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) response ip (any) (any) mac (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
```

```
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|)
```

---

## Configure source ip address

Use this attribute to set source mac-address.

Attribute Name: source-mac-address

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: source-ip-address

Attribute Type: enum (any)

Attribute Name: destination-ip-address

Attribute Type: enum (any)

Attribute Name: source-mac-mask

Attribute Type: string

Attribute Name: destination-mac-address

Attribute Type: string

Attribute Name: destination-mac-mask

Attribute Type: string

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
    </acl-set>
  </acl-sets>
</acl>
```

```

    <type>mac</type>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <arp>
      <config>
        <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
        <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
        <source-ip-address>any</source-ip-address> <!--
operation="delete"-->
        <destination-ip-address>any</destination-ip-address> <!--
operation="delete"-->
        <source-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-mask> <!-- operation="delete"-->
        <destination-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-address> <!-- operation="delete"--
>
        <destination-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-mask> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <source-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-address> <!-- operation="delete"-->
      </config>
    </arp>
  </acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) response ip (any) (any) mac (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|)

```

## Configure vlan id

Use this attribute to indicate any source address.

Attribute Name: source-mac-any

Attribute Type: empty

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: source-ip-address

Attribute Type: enum (any)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <arp>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
              <source-ip-address>any</source-ip-address> <!--
operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              </source-mac-any><!-- operation="delete"-->
            </config>
          </arp>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>
```

```

</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) ((request)|) ip (any) mac any (vlan <1-4094>|)
(inner-vlan <1-4094>|) ((log|sample)|)

```

---

## Configure inner vlan id

Use this attribute to set Host source address.

Attribute Name: source-mac-host

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: source-ip-address

Attribute Type: enum (any)

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>

```

```

        <arp>
        <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
            <source-ip-address>any</source-ip-address> <!--
operation="delete"-->
                <vlan-id>1</vlan-id> <!-- operation="delete"-->
                <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
                <monitor-action>log</monitor-action> <!-- operation="delete"-->
                <source-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-host> <!-- operation="delete"-->
            </config>
        </arp>
    </acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) ((request)|) ip (any) mac host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|)

```

---

## Configure source mac mask

Use this attribute to set source mac-address.

Attribute Name: source-mac-address

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: source-ip-address

Attribute Type: enum (any)

Attribute Name: source-mac-mask

Attribute Type: string

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <arp>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
              <source-ip-address>any</source-ip-address> <!--
operation="delete"-->
              <source-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-mask> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              <source-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-address> <!-- operation="delete"-->
            </config>
          </arp>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) ((request)|) ip (any) mac (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (vlan <1-4094>|) (inner-vlan <1-4094>|)
((log|sample)|)
```

---

## IPI-ACL-MAC

---

### Configure source mac any

Use this attribute to indicate any source address.

Attribute Name: source-mac-any

Attribute Type: empty

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: destination-mac-any

Attribute Type: empty

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

```

        <mac>
        <config>
        <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
        </destination-mac-any><!-- operation="delete"-->
        <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
        <cos-value>0</cos-value> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        </source-mac-any><!-- operation="delete"-->
        </config>
    </mac>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) any any arp (request|response) (cos <0-7>|) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)

```

---

## Configure name

Use this attribute to indicate any source address.

Attribute Name: source-mac-any

Attribute Type: empty

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: destination-mac-host

Attribute Type: string

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
  <acl-set>
    <name>NAME</name>
    <config>
      <name>WORD</name>
      <type>mac</type>
    </config>
    <type>mac</type>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <mac>
        <config>
          <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          <destination-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-host> <!-- operation="delete"-->
          <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
          <cos-value>0</cos-value> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          </source-mac-any><!-- operation="delete"-->
        </config>
      </mac>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) any host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) arp (request|response) (cos <0-7>|) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
```

## Configure type

Use this attribute to indicate any source address.

Attribute Name: source-mac-any

Attribute Type: empty

Attribute Name: forwarding-action  
 Attribute Type: enum (deny|permit)  
 Attribute Name: destination-mac-address  
 Attribute Type: string  
 Attribute Name: destination-mac-mask  
 Attribute Type: string  
 Attribute Name: arp-packet-type  
 Attribute Type: enum (none|request|response)  
 Attribute Name: cos-value  
 Attribute Type: uint8  
 Attribute Range: 0-7  
 Attribute Name: vlan-id  
 Attribute Type: uint16  
 Attribute Range: 1-4094  
 Attribute Name: inner-vlan-id  
 Attribute Type: uint16  
 Attribute Range: 1-4094  
 Attribute Name: monitor-action  
 Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <mac>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          <destination-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-address> <!-- operation="delete"--
>
```

```

        <destination-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-mask> <!-- operation="delete"-->
        <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
        <cos-value>0</cos-value> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        </source-mac-any><!-- operation="delete"-->
    </config>
</mac>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) any (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) arp (request|response) (cos <0-7>|) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)

```

---

## Configure source mac host

Use this attribute to set Host source address.

Attribute Name: source-mac-host

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: destination-mac-any

Attribute Type: empty

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
  <acl-set>
    <name>NAME</name>
    <config>
      <name>WORD</name>
      <type>mac</type>
    </config>
    <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <mac>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            </destination-mac-any><!-- operation="delete"-->
            <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
            <cos-value>0</cos-value> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <source-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-host> <!-- operation="delete"-->
          </config>
        </mac>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) any arp (request|response) (cos <0-7>|)
(vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
```

## Configure sequence id

Use this attribute to set Host source address.

Attribute Name: source-mac-host

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)  
 Attribute Name: destination-mac-host  
 Attribute Type: string  
 Attribute Name: arp-packet-type  
 Attribute Type: enum (none|request|response)  
 Attribute Name: cos-value  
 Attribute Type: uint8  
 Attribute Range: 0-7  
 Attribute Name: vlan-id  
 Attribute Type: uint16  
 Attribute Range: 1-4094  
 Attribute Name: inner-vlan-id  
 Attribute Type: uint16  
 Attribute Range: 1-4094  
 Attribute Name: monitor-action  
 Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <mac>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            <destination-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-host> <!-- operation="delete"-->
            <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
            <cos-value>0</cos-value> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
```

```

        <source-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-host> <!-- operation="delete"-->
    </config>
    </mac>
    </acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) arp (request|response) (cos <0-7>|) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)

```

---

## Configure forwarding action

Use this attribute to set Host source address.

Attribute Name: source-mac-host

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: destination-mac-address

Attribute Type: string

Attribute Name: destination-mac-mask

Attribute Type: string

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
  <acl-set>
    <name>NAME</name>
    <config>
      <name>WORD</name>
      <type>mac</type>
    </config>
    <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <mac>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            <destination-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-address> <!-- operation="delete"--
>
            <destination-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-mask> <!-- operation="delete"-->
            <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
            <cos-value>0</cos-value> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <source-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-host> <!-- operation="delete"-->
          </config>
        </mac>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) arp (request|response) (cos <0-7>|) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)

```

## Configure source mac address

Use this attribute to set source mac-address.

Attribute Name: source-mac-address

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: source-mac-mask

Attribute Type: string

Attribute Name: destination-mac-any

Attribute Type: empty

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <mac>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
```

```

        <source-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-mask> <!-- operation="delete"-->
        </destination-mac-any><!-- operation="delete"-->
        <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
        <cos-value>0</cos-value> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <source-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-address> <!-- operation="delete"-->
    </config>
    </mac>
    </acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) any arp (request|response) (cos <0-7>|)
(vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)

```

---

## Configure source mac mask

Use this attribute to set source mac-address.

Attribute Name: source-mac-address

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: source-mac-mask

Attribute Type: string

Attribute Name: destination-mac-host

Attribute Type: string

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <mac>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              <source-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-mask> <!-- operation="delete"-->
              <destination-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-host> <!-- operation="delete"-->
              <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
              <cos-value>0</cos-value> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              <source-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-address> <!-- operation="delete"-->
            </config>
          </mac>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>
```

## Command Syntax

```
(<1-268435453>|) (deny|permit) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) host (XX-XX-XX-XX-XX-
```

```
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) arp (request|response) (cos <0-7>|) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)
```

---

## Configure destination mac address

Use this attribute to set source mac-address.

Attribute Name: source-mac-address

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: source-mac-mask

Attribute Type: string

Attribute Name: destination-mac-address

Attribute Type: string

Attribute Name: destination-mac-mask

Attribute Type: string

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    </acl-set>
  </acl-sets>
</acl>
```

```

    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <mac>
        <config>
          <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          <source-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-mask> <!-- operation="delete"-->
          <destination-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-address> <!-- operation="delete"--
>
          <destination-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-mask> <!-- operation="delete"-->
          <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
          <cos-value>0</cos-value> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
          <source-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-address> <!-- operation="delete"-->
        </config>
      </mac>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) arp (request|response) (cos <0-7>|) (vlan
<1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)

```

---

## Configure destination mac any

Use this attribute to indicate any source address.

Attribute Name: source-mac-any

Attribute Type: empty

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: destination-mac-any

Attribute Type: empty

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <mac>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              </destination-mac-any><!-- operation="delete"-->
              <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
              <cos-value>0</cos-value> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              </source-mac-any><!-- operation="delete"-->
            </config>
          </mac>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>
```

```

</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) any any arp (cos <0-7>|) (vlan <1-4094>|) (inner-
vlan <1-4094>|) ((log|sample)|)

```

---

## Configure destination mac host

Use this attribute to indicate any source address.

Attribute Name: source-mac-any

Attribute Type: empty

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: destination-mac-host

Attribute Type: string

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>

```

```

    <sequence-id>1</sequence-id>
    <config>
      <sequence-id>1</sequence-id>
    </config>
    <mac>
    <config>
      <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
      <destination-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-host> <!-- operation="delete"-->
      <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
      <cos-value>0</cos-value> <!-- operation="delete"-->
      <vlan-id>1</vlan-id> <!-- operation="delete"-->
      <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
      <monitor-action>log</monitor-action> <!-- operation="delete"-->
      </source-mac-any><!-- operation="delete"-->
    </config>
  </mac>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) any host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) arp (cos <0-7>|) (vlan <1-4094>|) (inner-
vlan <1-4094>|) ((log|sample)|)

```

---

## Configure destination mac mask

Use this attribute to indicate any source address.

Attribute Name: source-mac-any

Attribute Type: empty

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: destination-mac-address

Attribute Type: string

Attribute Name: destination-mac-mask

Attribute Type: string

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <mac>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              <destination-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-address> <!-- operation="delete"--
>
              <destination-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-mask> <!-- operation="delete"-->
              <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
              <cos-value>0</cos-value> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              </source-mac-any><!-- operation="delete"-->
            </config>
          </mac>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>
```

## Command Syntax

```
(<1-268435453>|) (deny|permit) any (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) arp (cos <0-7>|) (vlan <1-4094>|) (inner-
vlan <1-4094>|) ((log|sample)|)
```

---

## Configure arp packet type

Use this attribute to set Host source address.

Attribute Name: source-mac-host

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: destination-mac-any

Attribute Type: empty

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
  <acl-set>
    <name>NAME</name>
    <config>
      <name>WORD</name>
      <type>mac</type>
    </config>
    <type>mac</type>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
```

```

    <config>
      <sequence-id>1</sequence-id>
    </config>
  <mac>
    <config>
      <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
      </destination-mac-any><!-- operation="delete"-->
      <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
      <cos-value>0</cos-value> <!-- operation="delete"-->
      <vlan-id>1</vlan-id> <!-- operation="delete"-->
      <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
      <monitor-action>log</monitor-action> <!-- operation="delete"-->
      <source-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-host> <!-- operation="delete"-->
    </config>
  </mac>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) any arp (cos <0-7>|) (vlan <1-4094>|)
(inner-vlan <1-4094>|) ((log|sample)|)

```

---

## Configure cos value

Use this attribute to set Host source address.

Attribute Name: source-mac-host

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: destination-mac-host

Attribute Type: string

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <mac>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              <destination-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-host> <!-- operation="delete"-->
              <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
              <cos-value>0</cos-value> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              <source-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-host> <!-- operation="delete"-->
            </config>
          </mac>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) host (XX-XX-XX-XX-XX-
```

```
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) arp (cos <0-7>|) (vlan <1-4094>|) (inner-
vlan <1-4094>|) ((log|sample)|)
```

---

## Configure vlan id

Use this attribute to set Host source address.

Attribute Name: source-mac-host

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: destination-mac-address

Attribute Type: string

Attribute Name: destination-mac-mask

Attribute Type: string

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
```

```

        <sequence-id>1</sequence-id>
    </config>
    <mac>
    <config>
        <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
        <destination-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-address> <!-- operation="delete"--
>
        <destination-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-mask> <!-- operation="delete"-->
        <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
        <cos-value>0</cos-value> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
        <source-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-host> <!-- operation="delete"-->
    </config>
    </mac>
    </acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) arp (cos <0-7>|) (vlan <1-4094>|) (inner-
vlan <1-4094>|) ((log|sample)|)

```

---

## Configure inner vlan id

Use this attribute to set source mac-address.

Attribute Name: source-mac-address

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: source-mac-mask

Attribute Type: string

Attribute Name: destination-mac-any

Attribute Type: empty

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <mac>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              <source-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-mask> <!-- operation="delete"-->
              </destination-mac-any><!-- operation="delete"-->
              <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
              <cos-value>0</cos-value> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
              <source-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-address> <!-- operation="delete"-->
            </config>
          </mac>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>
```

```

</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) any arp (cos <0-7>|) (vlan <1-4094>|)
(inner-vlan <1-4094>|) ((log|sample)|)

```

---

## Configure monitor action

Use this attribute to set source mac-address.

Attribute Name: source-mac-address

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: source-mac-mask

Attribute Type: string

Attribute Name: destination-mac-host

Attribute Type: string

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
  <acl-set>
    <name>NAME</name>
    <config>
      <name>WORD</name>

```

```

    <type>mac</type>
  </config>
  <type>mac</type>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
        </config>
        <mac>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            <source-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-mask> <!-- operation="delete"-->
            <destination-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-host> <!-- operation="delete"-->
            <arp-packet-type>none</arp-packet-type> <!--
operation="delete"-->
            <cos-value>0</cos-value> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
            <source-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-address> <!-- operation="delete"-->
          </config>
        </mac>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) arp (cos <0-7>|) (vlan <1-4094>|) (inner-
vlan <1-4094>|) ((log|sample)|)

```

---

## Configure mac source-mac-address

Use this attribute to set source mac-address.

Attribute Name: source-mac-address

Attribute Type: string

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: source-mac-mask

Attribute Type: string

Attribute Name: destination-mac-address

Attribute Type: string

Attribute Name: destination-mac-mask

Attribute Type: string

Attribute Name: arp-packet-type

Attribute Type: enum (none|request|response)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <mac>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          <source-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-mask> <!-- operation="delete"-->
          <destination-mac-address>XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-address> <!-- operation="delete"--
>
          <destination-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-mask> <!-- operation="delete"-->
```

```

operation="delete"--> <arp-packet-type>none</arp-packet-type> <!--
<cos-value>0</cos-value> <!-- operation="delete"-->
<vlan-id>1</vlan-id> <!-- operation="delete"-->
<inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
<monitor-action>log</monitor-action> <!-- operation="delete"-->
<source-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-address> <!-- operation="delete"-->
</config>
</mac>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) arp (cos <0-7>|) (vlan <1-4094>|) (inner-
vlan <1-4094>|) ((log|sample)|)

```

## Configure ethertype

Use this attribute to enable logging or sampling of the packets on which the match occurred (in-direction only).

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: source-mac-any

Attribute Type: empty

Attribute Name: destination-mac-any

Attribute Type: empty

Attribute Name: ethertype

Attribute Type: union

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <mac>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            </source-mac-any><!-- operation="delete"-->
            </destination-mac-any><!-- operation="delete"-->
            <ethertype>ipv4</ethertype> <!-- operation="delete"-->
            <cos-value>0</cos-value> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
          </config>
        </mac>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) any any ((ipv4|vines-echo|etype-6000|mop-dump|mop-
console|decnet-iv|lat|diagnostic|lavc-sca|etype-
8042|appletalk|aarp|ipv6|mpls|ETHTYPE)|) (cos <0-7>|) (vlan <1-4094>|) (inner-
vlan <1-4094>|) ((log|sample)|)
```

---

## Configure mac monitor-action

Use this attribute to enable logging or sampling of the packets on which the match occurred (in-direction only).

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: source-mac-any

Attribute Type: empty

Attribute Name: destination-mac-host

Attribute Type: string

Attribute Name: ethertype

Attribute Type: enum (ipv4|vines-echo|etype-6000|mop-dump|mop-console|decnet-iv|lat|diagnostic|lavc-sca|etype-8042|appletalk|arp|ipv6|mpls)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <mac>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          </source-mac-any><!-- operation="delete"-->
          <destination-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-host> <!-- operation="delete"-->
          <ethertype>ipv4</ethertype> <!-- operation="delete"-->
          <cos-value>0</cos-value> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->

```

```

        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
    </config>
</mac>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) any host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) ((ipv4|vines-echo|etype-6000|mop-dump|mop-
console|decnet-iv|lat|diagnostic|lavc-sca|etype-8042|appletalk|arp|ipv6|mpls)|)
(cos <0-7>|) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)

```

---

## Configure mac monitor-action

Use this attribute to enable logging or sampling of the packets on which the match occurred (in-direction only).

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: source-mac-any

Attribute Type: empty

Attribute Name: destination-mac-address

Attribute Type: string

Attribute Name: destination-mac-mask

Attribute Type: string

Attribute Name: ethertype

Attribute Type: enum (ipv4|vines-echo|etype-6000|mop-dump|mop-console|decnet-iv|lat|diagnostic|lavc-sca|etype-8042|appletalk|arp|ipv6|mpls)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <mac>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              </source-mac-any><!-- operation="delete"-->
              <destination-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-address> <!-- operation="delete"--
>
              <destination-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-mask> <!-- operation="delete"-->
              <ethertype>ipv4</ethertype> <!-- operation="delete"-->
              <cos-value>0</cos-value> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
            </config>
          </mac>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) any (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) ((ipv4|vines-echo|etype-6000|mop-dump|mop-
console|decnet-iv|lat|diagnostic|lavc-sca|etype-8042|appletalk|aarp|ipv6|mpls)|)
(cos <0-7>|) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)

```

## Configure mac monitor-action

Use this attribute to enable logging or sampling of the packets on which the match occurred (in-direction only).

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: source-mac-host

Attribute Type: string

Attribute Name: destination-mac-any

Attribute Type: empty

Attribute Name: ethertype

Attribute Type: enum (ipv4|vines-echo|etype-6000|mop-dump|mop-console|decnet-iv|lat|diagnostic|lavc-sca|etype-8042|appletalk|arp|ipv6|mpls)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <mac>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          <source-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-host> <!-- operation="delete"-->
          </destination-mac-any><!-- operation="delete"-->
          <ethertype>ipv4</ethertype> <!-- operation="delete"-->
        </config>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

```

        <cos-value>0</cos-value> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
    </config>
</mac>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) any ((ipv4|vines-echo|etype-6000|mop-
dump|mop-console|decnet-iv|lat|diagnostic|lavc-sca|etype-
8042|appletalk|arp|ipv6|mpls)|) (cos <0-7>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|)

```

---

## Configure mac monitor-action

Use this attribute to enable logging or sampling of the packets on which the match occurred (in-direction only).

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: source-mac-host

Attribute Type: string

Attribute Name: destination-mac-host

Attribute Type: string

Attribute Name: ethertype

Attribute Type: enum (ipv4|vines-echo|etype-6000|mop-dump|mop-console|decnet-iv|lat|diagnostic|lavc-sca|etype-8042|appletalk|arp|ipv6|mpls)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<acl-sets>
  <acl-set>
    <name>NAME</name>
    <config>
      <name>WORD</name>
      <type>mac</type>
    </config>
    <type>mac</type>
  <acl-entries>
    <acl-entry>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <mac>
        <config>
          <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          <source-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-host> <!-- operation="delete"-->
          <destination-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-host> <!-- operation="delete"-->
          <ethertype>ipv4</ethertype> <!-- operation="delete"-->
          <cos-value>0</cos-value> <!-- operation="delete"-->
          <vlan-id>1</vlan-id> <!-- operation="delete"-->
          <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
          <monitor-action>log</monitor-action> <!-- operation="delete"-->
        </config>
      </mac>
    </acl-entry>
  </acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) ((ipv4|vines-echo|etype-6000|mop-dump|mop-
console|decnet-iv|lat|diagnostic|lavc-sca|etype-8042|appletalk|arp|ipv6|mpls)|)
(cos <0-7>|) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)

```

## Configure mac monitor-action

Use this attribute to enable logging or sampling of the packets on which the match occurred (in-direction only).

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: source-mac-host

Attribute Type: string

Attribute Name: destination-mac-address

Attribute Type: string

Attribute Name: destination-mac-mask

Attribute Type: string

Attribute Name: ethertype

Attribute Type: enum (ipv4|vines-echo|etype-6000|mop-dump|mop-console|decnet-iv|lat|diagnostic|lavc-sca|etype-8042|appletalk|arp|ipv6|mpls)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
        <mac>
          <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
          <source-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-host> <!-- operation="delete"-->
          <destination-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-address> <!-- operation="delete"--
>
```

```

        <destination-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-mask> <!-- operation="delete"-->
        <ethertype>ipv4</ethertype> <!-- operation="delete"-->
        <cos-value>0</cos-value> <!-- operation="delete"-->
        <vlan-id>1</vlan-id> <!-- operation="delete"-->
        <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
        <monitor-action>log</monitor-action> <!-- operation="delete"-->
    </config>
</mac>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) ((ipv4|vines-echo|etype-6000|mop-dump|mop-
console|decnet-iv|lat|diagnostic|lavc-sca|etype-8042|appletalk|arp|ipv6|mpls)|)
(cos <0-7>|) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)

```

---

## Configure mac monitor-action

Use this attribute to enable logging or sampling of the packets on which the match occurred (in-direction only).

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: source-mac-address

Attribute Type: string

Attribute Name: source-mac-mask

Attribute Type: string

Attribute Name: destination-mac-any

Attribute Type: empty

Attribute Name: ethertype

Attribute Type: enum (ipv4|vines-echo|etype-6000|mop-dump|mop-console|decnet-iv|lat|diagnostic|lavc-sca|etype-8042|appletalk|arp|ipv6|mpls)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
            </config>
            <mac>
              <config>
                <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
                <source-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-address> <!-- operation="delete"-->
                <source-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-mask> <!-- operation="delete"-->
                </destination-mac-any><!-- operation="delete"-->
                <ethertype>ipv4</ethertype> <!-- operation="delete"-->
                <cos-value>0</cos-value> <!-- operation="delete"-->
                <vlan-id>1</vlan-id> <!-- operation="delete"-->
                <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
                <monitor-action>log</monitor-action> <!-- operation="delete"-->
              </config>
            </mac>
          </acl-entry>
        </acl-entries>
      </acl-set>
    </acl-sets>
  </acl>
```

### Command Syntax

```
(<1-268435453>|) (deny|permit) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) any ((ipv4|vines-echo|etype-6000|mop-
dump|mop-console|decnet-iv|lat|diagnostic|lavc-sca|etype-
8042|appletalk|aarp|ipv6|mpls)|) (cos <0-7>|) (vlan <1-4094>|) (inner-vlan <1-
4094>|) ((log|sample)|)
```

---

## Configure mac monitor-action

Use this attribute to enable logging or sampling of the packets on which the match occurred (in-direction only).

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: source-mac-address

Attribute Type: string

Attribute Name: source-mac-mask

Attribute Type: string

Attribute Name: destination-mac-host

Attribute Type: string

Attribute Name: ethertype

Attribute Type: enum (ipv4|vines-echo|etype-6000|mop-dump|mop-console|decnet-iv|lat|diagnostic|lavc-sca|etype-8042|appletalk|aarp|ipv6|mpls)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
    <acl-entries>
      <acl-entry>
        <sequence-id>1</sequence-id>
        <config>
          <sequence-id>1</sequence-id>
        </config>
      </acl-entry>
    </acl-entries>
  </acl-set>
</acl-sets>
</acl>
```

```

        <mac>
        <config>
            <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
            <source-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-address> <!-- operation="delete"-->
            <source-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-mask> <!-- operation="delete"-->
            <destination-mac-host>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-host> <!-- operation="delete"-->
            <ethertype>ipv4</ethertype> <!-- operation="delete"-->
            <cos-value>0</cos-value> <!-- operation="delete"-->
            <vlan-id>1</vlan-id> <!-- operation="delete"-->
            <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
            <monitor-action>log</monitor-action> <!-- operation="delete"-->
        </config>
    </mac>
</acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) host (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) ((ipv4|vines-echo|etype-6000|mop-dump|mop-
console|decnet-iv|lat|diagnostic|lavc-sca|etype-8042|appletalk|arp|ipv6|mpls)|)
(cos <0-7>|) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)

```

## Configure mac monitor-action

Use this attribute to enable logging or sampling of the packets on which the match occurred (in-direction only).

Attribute Name: monitor-action

Attribute Type: enum (log|sample)

Attribute Name: forwarding-action

Attribute Type: enum (deny|permit)

Attribute Name: source-mac-address

Attribute Type: string

Attribute Name: source-mac-mask

Attribute Type: string

Attribute Name: destination-mac-address

Attribute Type: string

Attribute Name: destination-mac-mask

Attribute Type: string

Attribute Name: ethertype

Attribute Type: enum (ipv4|vines-echo|etype-6000|mop-dump|mop-console|decnet-iv|lat|diagnostic|lavc-sca|etype-8042|appletalk|arp|ipv6|mpls)

Attribute Name: cos-value

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <acl-sets>
    <acl-set>
      <name>NAME</name>
      <config>
        <name>WORD</name>
        <type>mac</type>
      </config>
      <type>mac</type>
      <acl-entries>
        <acl-entry>
          <sequence-id>1</sequence-id>
          <config>
            <sequence-id>1</sequence-id>
          </config>
          <mac>
            <config>
              <forwarding-action>deny</forwarding-action> <!--
operation="delete"-->
              <source-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-address> <!-- operation="delete"-->
              <source-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</source-mac-mask> <!-- operation="delete"-->
              <destination-mac-address>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-address> <!-- operation="delete"--
>
              <destination-mac-mask>XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX</destination-mac-mask> <!-- operation="delete"-->
              <ethertype>ipv4</ethertype> <!-- operation="delete"-->
              <cos-value>0</cos-value> <!-- operation="delete"-->
              <vlan-id>1</vlan-id> <!-- operation="delete"-->
              <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
              <monitor-action>log</monitor-action> <!-- operation="delete"-->
            </config>
          </mac>
        </acl-entry>
      </acl-entries>
    </acl-set>
  </acl-sets>
</acl>
```

```

    </mac>
  </acl-entry>
</acl-entries>
</acl-set>
</acl-sets>
</acl>

```

## Command Syntax

```

(<1-268435453>|) (deny|permit) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) (XX-XX-XX-XX-XX-
XX|XX:XX:XX:XX:XX:XX|XXXX.XXXX.XXXX) ( (ipv4|vines-echo|etype-6000|mop-dump|mop-
console|decnet-iv|lat|diagnostic|lavc-sca|etype-8042|appletalk|arp|ipv6|mpls) | )
(cos <0-7>|) (vlan <1-4094>|) (inner-vlan <1-4094>|) ((log|sample)|)

```

---

## IPI-ACL-PORTS

---

### Configure acl name

The name of the access-list set applied on the interface

Attribute Name: acl-name

Attribute Type: string

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <ingress-acl-sets>
  <ingress-acl-set>
    <acl-type>ip</acl-type>
    <config>
      <acl-type>ip</acl-type>
    </config>
    <access-groups>
    <access-group> <!-- operation="delete"-->
      <acl-name>WORD</acl-name>
      <config>
        <acl-name>WORD</acl-name>
      </config>
    </access-group>
    </access-groups>
  </ingress-acl-set>
</ingress-acl-sets>

```

```

</interface>
</interfaces>
</acl>

```

## Command Syntax

```
ip access-group NAME in
```

---

## Configure name

The name of the access-list set applied on the interface

Attribute Name: acl-name

Attribute Type: string

Attribute Name: time-range

Attribute Type: string

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <ingress-acl-sets>
  <ingress-acl-set>
    <acl-type>mac</acl-type>
    <config>
      <acl-type>mac</acl-type>
    </config>
    <access-groups>
    <access-group>
      <acl-name>WORD</acl-name>
      <config>
        <acl-name>WORD</acl-name>
        <time-range>WORD</time-range>
      </config>
    </access-group>
  </access-groups>
</ingress-acl-set>
</ingress-acl-sets>
</interface>
</interfaces>
</acl>

```

## Command Syntax

```
ip access-group NAME in time-range WORD
```

---

## Configure acl type

Reference to the base interface name

Attribute Name: name

Attribute Type: string

Attribute Name: acl-type

Attribute Type: enum (mac|ip|ipv6|arp)

Attribute Name: acl-name

Attribute Type: string

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <interfaces>
    <interface> <!-- operation="delete"-->
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <ingress-acl-sets>
        <ingress-acl-set>
          <acl-type>ipv6</acl-type>
          <access-groups>
            <access-group>
              <acl-name>WORD</acl-name>
            </access-group>
          </access-groups>
        </ingress-acl-set>
      </ingress-acl-sets>
    </interface>
  </interfaces>
</acl>
```

### Command Syntax

```
ipv6 access-group NAME in
```

---

## Configure time range

The time-range associated with this access-group

Attribute Name: time-range

Attribute Type: string

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <interfaces>
    <interface>
      <name>WORD</name>
```

```

<config>
  <name>WORD</name>
</config>
<ingress-acl-sets>
<ingress-acl-set>
  <acl-type>mac</acl-type>
  <config>
    <acl-type>mac</acl-type>
  </config>
  <access-groups>
  <access-group>
    <acl-name>WORD</acl-name>
    <config>
      <acl-name>WORD</acl-name>
    </config>
    <time-range>WORD</time-range> <!-- operation="delete"-->
  </access-group>
</access-groups>
</ingress-acl-set>
</ingress-acl-sets>
</interface>
</interfaces>
</acl>

```

### Command Syntax

```
ipv6 access-group NAME in time-range WORD
```

---

## Configure interfaces name

Reference to the base interface name

Attribute Name: name

Attribute Type: string

Attribute Name: acl-type

Attribute Type: enum (mac|ip|ipv6|arp)

Attribute Name: acl-name

Attribute Type: string

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <interfaces>
  <interface> <!-- operation="delete"-->
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  <ingress-acl-sets>
  <ingress-acl-set>
    <acl-type>arp</acl-type>

```

```

    <access-groups>
    <access-group>
        <acl-name>WORD</acl-name>
    </access-group>
</access-groups>
</ingress-acl-set>
</ingress-acl-sets>
</interface>
</interfaces>
</acl>

```

## Command Syntax

```
arp access-group NAME in
```

---

## Configure interfaces name

Reference to the base interface name

Attribute Name: name

Attribute Type: string

Attribute Name: acl-type

Attribute Type: enum (mac|ip|ipv6|arp)

Attribute Name: acl-name

Attribute Type: string

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<interfaces>
<interface> <!-- operation="delete"-->
    <name>WORD</name>
    <config>
        <name>WORD</name>
    </config>
    <ingress-acl-sets>
    <ingress-acl-set>
        <acl-type>mac</acl-type>
        <access-groups>
        <access-group>
            <acl-name>WORD</acl-name>
        </access-group>
        </access-groups>
    </ingress-acl-set>
</ingress-acl-sets>
</interface>
</interfaces>
</acl>

```

---

## Command Syntax

```
mac access-group NAME in
```

---

## Configure access-group time-range

The time-range associated with this access-group

Attribute Name: time-range

Attribute Type: string

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <ingress-acl-sets>
        <ingress-acl-set>
          <acl-type>mac</acl-type>
          <config>
            <acl-type>mac</acl-type>
          </config>
          <access-groups>
            <access-group>
              <acl-name>WORD</acl-name>
              <config>
                <acl-name>WORD</acl-name>
                </config>
                <time-range>WORD</time-range> <!-- operation="delete"-->
              </access-group>
            </access-groups>
          </ingress-acl-set>
        </ingress-acl-sets>
      </interface>
    </interfaces>
  </acl>
```

## Command Syntax

```
mac access-group NAME in time-range WORD
```

---

## Configure interfaces name

Reference to the base interface name

Attribute Name: name

Attribute Type: string

Attribute Name: acl-type

Attribute Type: enum (mac|ip|ipv6|arp)

Attribute Name: acl-name

Attribute Type: string

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <interfaces>
    <interface> <!-- operation="delete"-->
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <egress-acl-sets>
        <egress-acl-set>
          <acl-type>ip</acl-type>
          <access-groups>
            <access-group>
              <acl-name>WORD</acl-name>
            </access-group>
          </access-groups>
        </egress-acl-set>
      </egress-acl-sets>
    </interface>
  </interfaces>
</acl>
```

### Command Syntax

```
ip access-group NAME out
```

---

## Configure access-group time-range

The time-range associated with this access-group

Attribute Name: time-range

Attribute Type: string

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <egress-acl-sets>
        <egress-acl-set>
          <acl-type>mac</acl-type>
          <config>
            <acl-type>mac</acl-type>
          </config>
        </egress-acl-set>
      </egress-acl-sets>
    </interface>
  </interfaces>
</acl>
```

```

    </config>
    <access-groups>
    <access-group>
        <acl-name>WORD</acl-name>
        <config>
            <acl-name>WORD</acl-name>
        </config>
        <time-range>WORD</time-range> <!-- operation="delete"-->
    </access-group>
    </access-groups>
</egress-acl-set>
</egress-acl-sets>
</interface>
</interfaces>
</acl>

```

## Command Syntax

```
ip access-group NAME out time-range WORD
```

---

## Configure interfaces name

Reference to the base interface name

Attribute Name: name

Attribute Type: string

Attribute Name: acl-type

Attribute Type: enum (mac|ip|ipv6|arp)

Attribute Name: acl-name

Attribute Type: string

## Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<interfaces>
<interface> <!-- operation="delete"-->
    <name>WORD</name>
    <config>
        <name>WORD</name>
    </config>
    <egress-acl-sets>
    <egress-acl-set>
        <acl-type>ipv6</acl-type>
        <access-groups>
        <access-group>
            <acl-name>WORD</acl-name>
        </access-group>
        </access-groups>
    </egress-acl-set>
</egress-acl-sets>
</interface>

```

```
</interfaces>
</acl>
```

## Command Syntax

```
ipv6 access-group NAME out
```

---

## Configure access-group time-range

The time-range associated with this access-group

Attribute Name: time-range

Attribute Type: string

## Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <egress-acl-sets>
  <egress-acl-set>
    <acl-type>mac</acl-type>
    <config>
      <acl-type>mac</acl-type>
    </config>
    <access-groups>
    <access-group>
      <acl-name>WORD</acl-name>
      <config>
        <acl-name>WORD</acl-name>
        </config>
        <time-range>WORD</time-range> <!-- operation="delete"-->
      </access-group>
    </access-groups>
  </egress-acl-set>
</egress-acl-sets>
</interface>
</interfaces>
</acl>
```

## Command Syntax

```
ipv6 access-group NAME out time-range WORD
```

---

## Configure interfaces name

Reference to the base interface name

Attribute Name: name

Attribute Type: string

Attribute Name: acl-type

Attribute Type: enum (mac|ip|ipv6|arp)

Attribute Name: acl-name

Attribute Type: string

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <interfaces>
    <interface> <!-- operation="delete"-->
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <egress-acl-sets>
        <egress-acl-set>
          <acl-type>mac</acl-type>
          <access-groups>
            <access-group>
              <acl-name>WORD</acl-name>
            </access-group>
          </access-groups>
        </egress-acl-set>
      </egress-acl-sets>
    </interface>
  </interfaces>
</acl>
```

### Command Syntax

```
mac access-group NAME out
```

---

## Configure access-group time-range

The time-range associated with this access-group

Attribute Name: time-range

Attribute Type: string

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <ingress-acl-sets>
        <ingress-acl-set>
```

```

    <acl-type>mac</acl-type>
  </config>
  <acl-type>mac</acl-type>
</config>
<access-groups>
<access-group>
  <acl-name>WORD</acl-name>
  <config>
    <acl-name>WORD</acl-name>
  </config>
  <time-range>WORD</time-range> <!-- operation="delete"-->
</access-group>
</access-groups>
</ingress-acl-set>
</ingress-acl-sets>
</interface>
</interfaces>
</acl>

```

### Command Syntax

```
mac access-group NAME out (time-range WORD|)
```

---

## Configure ingress-acl-set acl-name

The name of the access-list set applied on vty line

Attribute Name: acl-name

Attribute Type: string

### Netconf edit-config payload

```

<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <vty-line>
    <ingress-acl-sets>
      <ingress-acl-set>
        <acl-type>ip</acl-type>
        <config>
          <acl-type>ip</acl-type>
        </config>
        <acl-name>NAME</acl-name> <!-- operation="delete"-->
      </ingress-acl-set>
    </ingress-acl-sets>
  </vty-line>
</acl>

```

### Command Syntax

```
ip access-group NAME in
```

---

## Configure ingress-acl-set acl-name

The name of the access-list set applied on vty line

Attribute Name: acl-name

Attribute Type: string

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <vty-line>
    <ingress-acl-sets>
      <ingress-acl-set>
        <acl-type>ip</acl-type>
        <config>
          <acl-type>ip</acl-type>
        </config>
        <acl-name>NAME</acl-name> <!-- operation="delete"-->
      </ingress-acl-set>
    </ingress-acl-sets>
  </vty-line>
</acl>
```

### Command Syntax

```
ipv6 access-group NAME in
```

---

## Configure egress-acl-set acl-name

The name of the access-list set applied on vty line

Attribute Name: acl-name

Attribute Type: string

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <vty-line>
    <egress-acl-sets>
      <egress-acl-set>
        <acl-type>ip</acl-type>
        <config>
          <acl-type>ip</acl-type>
        </config>
        <acl-name>NAME</acl-name> <!-- operation="delete"-->
      </egress-acl-set>
    </egress-acl-sets>
  </vty-line>
</acl>
```

### Command Syntax

```
ip access-group NAME out
```

---

## Configure egress-acl-set acl-name

The name of the access-list set applied on vty line

Attribute Name: acl-name

Attribute Type: string

### Netconf edit-config payload

```
<acl xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">
  <vty-line>
    <egress-acl-sets>
      <egress-acl-set>
        <acl-type>ip</acl-type>
        <config>
          <acl-type>ip</acl-type>
        </config>
        <acl-name>NAME</acl-name> <!-- operation="delete"-->
      </egress-acl-set>
    </egress-acl-sets>
  </vty-line>
</acl>
```

### Command Syntax

```
ipv6 access-group NAME out
```

---

## clear access-list counters

### Netconf RPC payload

```
<ipi-acl-ports_clear-access-list-counters-all xmlns="http://www.ipinfusion.com/
yang/ocnos/ipi-acl"/>
```

### Command Syntax

```
clear access-list counters
```

---

## clear access-list NAME counters

Attribute Name: name

Attribute Type: string

### Netconf RPC payload

```
<ipi-acl-ports_clear-access-list-counters xmlns="http://www.ipinfusion.com/yang/
ocnos/ipi-acl">
  <name>NAME</name>
</ipi-acl-ports_clear-access-list-counters>
```

### Command Syntax

```
clear access-list NAME counters
```

---

## clear ip access-list counters

### Netconf RPC payload

```
<ipi-acl-ports_clear-ip-access-list-counters-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl"/>
```

### Command Syntax

```
clear ip access-list counters
```

---

## clear ip access-list NAME counters

Attribute Name: name

Attribute Type: string

### Netconf RPC payload

```
<ipi-acl-ports_clear-ip-access-list-counters xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">  
  <name>NAME</name>  
</ipi-acl-ports_clear-ip-access-list-counters>
```

### Command Syntax

```
clear ip access-list NAME counters
```

---

## clear ipv6 access-list counters

### Netconf RPC payload

```
<ipi-acl-ports_clear-ipv6-access-list-counters-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl"/>
```

### Command Syntax

```
clear ipv6 access-list counters
```

---

## clear ipv6 access-list NAME counters

Attribute Name: name

Attribute Type: string

### Netconf RPC payload

```
<ipi-acl-ports_clear-ipv6-access-list-counters xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">  
  <name>NAME</name>  
</ipi-acl-ports_clear-ipv6-access-list-counters>
```

### Command Syntax

```
clear ipv6 access-list NAME counters
```

---

## clear mac access-list counters

### Netconf RPC payload

```
<ipi-acl-ports_clear-mac-access-list-counters-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl"/>
```

### Command Syntax

```
clear mac access-list counters
```

---

## clear mac access-list NAME counters

Attribute Name: name

Attribute Type: string

### Netconf RPC payload

```
<ipi-acl-ports_clear-mac-access-list-counters xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">  
  <name>NAME</name>  
</ipi-acl-ports_clear-mac-access-list-counters>
```

### Command Syntax

```
clear mac access-list NAME counters
```

---

## clear arp access-list counters

### Netconf RPC payload

```
<ipi-acl-ports_clear-arp-access-list-counters-all xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl"/>
```

### Command Syntax

```
clear arp access-list counters
```

---

## clear arp access-list NAME counters

Attribute Name: name

Attribute Type: string

### Netconf RPC payload

```
<ipi-acl-ports_clear-arp-access-list-counters xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-acl">  
  <name>NAME</name>  
</ipi-acl-ports_clear-arp-access-list-counters>
```

### Command Syntax

```
clear arp access-list NAME counters
```

---

# IPI-DHCP-SNOOPING

---

## Configure options

Use this attribute to debug the DHCP snooping feature.

Attribute Name: options

Attribute Type: bits (event|rx|tx|packet|all)

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <snooping>
    <debug>
      <config>
        <options>event</options> <!-- operation="delete"-->
      </config>
    </debug>
  </snooping>
</dhcp>
```

### Command Syntax

```
debug ip dhcp snooping (event|rx|tx|packet|all)
```

---

## Configure snooping enable

Enable DHCP snooping feature

Attribute Name: snooping-enable

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <snooping>
    <snooping-bridges>
      <snooping-bridge>
        <bridge-id>1</bridge-id>
        <config>
          <bridge-id>1</bridge-id>
        </config>
      </snooping-bridge>
    </snooping-bridges>
  </snooping>
</dhcp>
```

### Command Syntax

```
ip dhcp snooping bridge <1-32>
```

---

## Configure verify mac address

Use this command to enable MAC address verification.

Attribute Name: verify-mac-address

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <snooping>
    <snooping-bridges>
      <snooping-bridge>
        <bridge-id>1</bridge-id>
        <config>
          <bridge-id>1</bridge-id>
        </config>
        </verify-mac-address><!-- operation="delete"-->
      </snooping-bridge>
    </snooping-bridges>
  </snooping>
</dhcp>
```

### Command Syntax

```
ip dhcp snooping verify mac-address bridge <1-32>
```

---

## Configure option 82 enable

Use this command to insert interface and VLAN name in the option 82 field in DHCP packets.

Attribute Name: option-82-enable

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <snooping>
    <snooping-bridges>
      <snooping-bridge>
        <bridge-id>1</bridge-id>
        <config>
          <bridge-id>1</bridge-id>
          </option-82-enable><!-- operation="delete"-->
        </config>
      </snooping-bridge>
    </snooping-bridges>
  </snooping>
</dhcp>
```

### Command Syntax

```
ip dhcp snooping information option bridge <1-32>
```

---

## Configure write delay

Configure DHCP snooping database write delay in multiples of 10 seconds

Attribute Name: write-delay

Attribute Type: uint32

Default Value: 300

Attribute Range: 20-86400

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <snooping>
    <snooping-bridges>
      <snooping-bridge>
        <bridge-id>1</bridge-id>
        <config>
          <bridge-id>1</bridge-id>
        </config>
        <write-delay>20</write-delay> <!-- operation="delete"-->
      </snooping-bridge>
    </snooping-bridges>
  </snooping>
</dhcp>
```

### Command Syntax

```
ip dhcp snooping database write-delay <20-86400> bridge <1-32>
```

---

## Configure strict validation

Use this command to enable strict validation of DHCP packets.

Attribute Name: strict-validation

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <snooping>
    <snooping-bridges>
      <snooping-bridge>
        <bridge-id>1</bridge-id>
        <config>
          <bridge-id>1</bridge-id>
        </config>
        </strict-validation><!-- operation="delete"-->
      </snooping-bridge>
    </snooping-bridges>
  </snooping>
</dhcp>
```

---

## Command Syntax

```
ip dhcp packet strict-validation bridge <1-32>
```

---

## Configure vlan range

Use this command to enable DHCP snooping for the given VLAN.

Attribute Name: vlan-range

Attribute Type: string

Attribute Range: 2-4094

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <snooping>
    <snooping-bridges>
      <snooping-bridge>
        <bridge-id>1</bridge-id>
        <config>
          <bridge-id>1</bridge-id>
        </config>
        <vlan-range>VLAN_RANGE</vlan-range> <!-- operation="delete"-->
      </snooping-bridge>
    </snooping-bridges>
  </snooping>
</dhcp>
```

## Command Syntax

```
ip dhcp snooping vlan VLAN_RANGE bridge <1-32>
```

---

## Configure enable

Use this command to enable/disable arp-inspection on the bridge.

Attribute Name: enable

Attribute Type: empty

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <snooping>
    <snooping-bridges>
      <snooping-bridge>
        <bridge-id>1</bridge-id>
        <config>
          <bridge-id>1</bridge-id>
          <arp-inspection>
            <config>
              </enable>
            </config>
          </arp-inspection>
        </config>
      </snooping-bridge>
    </snooping-bridges>
  </snooping>
</dhcp>
```

```

</arp-inspection>
</snooping-bridge>
</snooping-bridges>
</snooping>
</dhcp>

```

### Command Syntax

```
ip dhcp snooping arp-inspection bridge <1-32>
```

---

## Configure validate

Use this command to enable validation of the source-mac, destination-mac, or IP address field in the ARP packet payload.

Attribute Name: validate

Attribute Type: enum (src-mac|dst-mac|ip)

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <snooping>
    <snooping-bridges>
      <snooping-bridge>
        <bridge-id>1</bridge-id>
        <config>
          <bridge-id>1</bridge-id>
        </config>
        <arp-inspection>
          <config>
            <validate>src-mac</validate> <!-- operation="delete"-->
          </config>
        </arp-inspection>
      </snooping-bridge>
    </snooping-bridges>
  </snooping>
</dhcp>

```

### Command Syntax

```
ip dhcp snooping arp-inspection validate (src-mac|dst-mac|ip) bridge <1-32>
```

---

## Configure bridge id

Use this command to enable ARP inspection on the VLAN in a bridge.

Attribute Name: vlan-range

Attribute Type: string

Attribute Range: 2-4094

### Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <snooping>

```

```

<snooping-bridges>
<snooping-bridge>
  <bridge-id>1</bridge-id>
  <config>
    <bridge-id>1</bridge-id>
  </config>
  <arp-inspection>
  <config>
    <vlan-range>VLAN_RANGE</vlan-range> <!-- operation="delete"-->
  </config>
</arp-inspection>
</snooping-bridge>
</snooping-bridges>
</snooping>
</dhcp>

```

## Command Syntax

```
ip dhcp snooping arp-inspection vlan VLAN_RANGE bridge <1-32>
```

---

## Configure if name

Use this attribute to set the interface name

Attribute Name: if-name

Attribute Type: string

Attribute Name: ipv4-address

Attribute Type: inet:ipv4-address

## Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
<snooping>
<snooping-bridges>
<snooping-bridge>
  <bridge-id>1</bridge-id>
  <config>
    <bridge-id>1</bridge-id>
  </config>
<vlans>
<vlan>
  <vlan-id>1</vlan-id>
  <config>
    <vlan-id>1</vlan-id>
  </config>
  <mac-addresses-ipv4>
  <mac-address-ipv4>
    <mac-address>XXXX.XXXX.XXXX</mac-address>
  <config>
    <mac-address>XXXX.XXXX.XXXX</mac-address>
    <ipv4-address>A.B.C.D</ipv4-address>
  </config>
  </mac-address-ipv4>
  </mac-addresses-ipv4>
</vlan>
</vlans>
</snooping-bridge>
</snooping-bridges>
</snooping>
</dhcp>

```

```

    </config>
      <if-name>IFNAME</if-name>
    </mac-address-ipv4>
  </mac-addresses-ipv4>
</vlan>
</vlans>
</snooping-bridge>
</snooping-bridges>
</snooping>
</dhcp>

```

## Command Syntax

```
ip dhcp snooping binding bridge <1-32> XXXX.XXXX.XXXX <1-4094> ipv4 A.B.C.D IFNAME
```

---

## Configure mac address

Use this attribute to set the interface name

This command is supported when following feature are enabled HAVE\_IPV6 feature enabled

Attribute Name: if-name

Attribute Type: string

Attribute Name: ipv6-address

Attribute Type: inet:ipv6-address

## Netconf edit-config payload

```

<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <snooping>
    <snooping-bridges>
      <snooping-bridge>
        <bridge-id>1</bridge-id>
        <config>
          <bridge-id>1</bridge-id>
        </config>
      </snooping-bridge>
    </snooping-bridges>
  </snooping>
  <vlans>
    <vlan>
      <vlan-id>1</vlan-id>
      <config>
        <vlan-id>1</vlan-id>
      </config>
      <mac-addresses-ipv6>
        <mac-address-ipv6>
          <mac-address>XXXX.XXXX.XXXX</mac-address>
          <config>
            <mac-address>XXXX.XXXX.XXXX</mac-address>
            <ipv6-address>X:X::X:X</ipv6-address>
          </config>
          <if-name>IFNAME</if-name>
        </mac-address-ipv6>
      </mac-addresses-ipv6>
    </vlan>
  </vlans>
</dhcp>

```

```
</vlan>
</vlans>
</snoothing-bridge>
</snoothing-bridges>
</snoothing>
</dhcp>
```

## Command Syntax

```
ip dhcp snooping binding bridge <1-32> XXXX.XXXX.XXXX <1-4094> ipv6 X:X::X:X IFNAME
```

---

## ip dhcp snooping database bridge WORD

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```
<ipi-dhcp-snooping_dhcp-snooping-write-database xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <bridge-id>WORD</bridge-id>
</ipi-dhcp-snooping_dhcp-snooping-write-database>
```

## Command Syntax

```
ip dhcp snooping database bridge WORD
```

---

## renew ip dhcp snooping binding database bridge WORD

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```
<ipi-dhcp-snooping_dhcp-snooping-renew-database xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <bridge-id>WORD</bridge-id>
</ipi-dhcp-snooping_dhcp-snooping-renew-database>
```

## Command Syntax

```
renew ip dhcp snooping binding database bridge WORD
```

---

## ip dhcp snooping source database bridge WORD

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```
<ipi-dhcp-snooping_dhcp-snooping-write-source-binding-database xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <bridge-id>WORD</bridge-id>
</ipi-dhcp-snooping_dhcp-snooping-write-source-binding-database>
```

---

## Command Syntax

```
ip dhcp snooping source database bridge WORD
```

---

## renew ip dhcp snooping source binding database bridge WORD

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```
<ip-dhcp-snooping_dhcp-snooping-renew-source-database xmlns="http://  
www.ipinfusion.com/yang/ocnos/ipi-dhcp">  
  <bridge-id>WORD</bridge-id>  
</ip-dhcp-snooping_dhcp-snooping-renew-source-database>
```

## Command Syntax

```
renew ip dhcp snooping source binding database bridge WORD
```

---

## clear ip dhcp snooping source binding bridge WORD

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```
<ip-dhcp-snooping_dhcp-snooping-clear-source-binding-database xmlns="http://  
www.ipinfusion.com/yang/ocnos/ipi-dhcp">  
  <bridge-id>WORD</bridge-id>  
</ip-dhcp-snooping_dhcp-snooping-clear-source-binding-database>
```

## Command Syntax

```
clear ip dhcp snooping source binding bridge WORD
```

---

## clear ip dhcp snooping binding bridge WORD

Attribute Name: bridge-id

Attribute Type: string

### Netconf RPC payload

```
<ip-dhcp-snooping_dhcp-snooping-clear-database xmlns="http://  
www.ipinfusion.com/yang/ocnos/ipi-dhcp">  
  <bridge-id>WORD</bridge-id>  
</ip-dhcp-snooping_dhcp-snooping-clear-database>
```

## Command Syntax

```
clear ip dhcp snooping binding bridge WORD
```

---

## debug ip dhcp snooping (event|rx|tx|packet|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (event|rx|tx|packet|all)

### Netconf RPC payload

```
<ipi-dhcp-snooping_dhcp-snooping-terminal-debug-on xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <terminal-debug-options>event</terminal-debug-options>
</ipi-dhcp-snooping_dhcp-snooping-terminal-debug-on>
```

### Command Syntax

```
debug ip dhcp snooping (event|rx|tx|packet|all)
```

---

## no debug ip dhcp snooping (event|rx|tx|packet|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (event|rx|tx|packet|all)

### Netconf RPC payload

```
<ipi-dhcp-snooping_dhcp-snooping-terminal-debug-off xmlns="http://
www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <terminal-debug-options>event</terminal-debug-options>
</ipi-dhcp-snooping_dhcp-snooping-terminal-debug-off>
```

### Command Syntax

```
no debug ip dhcp snooping (event|rx|tx|packet|all)
```

---

## IPI-DHCP-SNOOPING-INTERFACE

---

### Configure snooping trust

Use this command to enable the snooping trust on the interface level.

Attribute Name: snooping-trust

Attribute Type: empty

### Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">
  <snooping>
    <interfaces>
      <interface>
        <name>WORD</name>
        <config>
          <name>WORD</name>
        </config>
        <trust>
          <config>
            </snooping-trust><!-- operation="delete"-->
          </config>
        </trust>
      </interface>
    </interfaces>
  </snooping>
</dhcp>
```

```
</interface>  
</interfaces>  
</snoothing>  
</dhcp>
```

## Command Syntax

```
ip dhcp snoothing trust
```

---

## Configure verify snoothing vlan

Use this command to enable the IPSG feature at the interface level.

Attribute Name: verify-snooping-vlan

Attribute Type: empty

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">  
<snoothing>  
  <interfaces>  
    <interface>  
      <name>WORD</name>  
      <config>  
        <name>WORD</name>  
      </config>  
      <verify>  
        <config>  
          </verify-snooping-vlan>  
        </config>  
      </verify>  
    </interface>  
  </interfaces>  
</snoothing>  
</dhcp>
```

## Command Syntax

```
ip verify source dhcp-snooping-vlan
```

---

## Configure verify access group mode

Use this command to enable the snooping access-group on the interface level.

Attribute Name: verify-access-group-mode

Attribute Type: empty

## Netconf edit-config payload

```
<dhcp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-dhcp">  
<snoothing>  
  <interfaces>  
    <interface>  
      <name>WORD</name>
```

```

    <config>
      <name>WORD</name>
    </config>
  <verify>
    <config>
      </verify-access-group-mode><!-- operation="delete"-->
    </config>
  </verify>
</interface>
</interfaces>
</snooping>
</dhcp>

```

### Command Syntax

```
ip verify source access-group mode merge
```

---

## clear hsl ipc-stat VALUE VALUE

Attribute Name: start-value

Attribute Type: uint16

Attribute Name: end-value

Attribute Type: uint16

### Netconf RPC payload

```

<platform-clear-hsl-ipc-stat-values xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-ras">
  <start-value>VALUE</start-value>
  <end-value>VALUE</end-value>
</platform-clear-hsl-ipc-stat-values>

```

### Command Syntax

```
clear hsl ipc-stat VALUE VALUE
```

---

## clear hsl ipc-stat

### Netconf RPC payload

```

<platform-clear-hsl-ipc-stat xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
ras"/>

```

### Command Syntax

```
clear hsl ipc-stat
```

---

## clear hsl mlag mac-sync-count

### Netconf RPC payload

```

<platform-clear-hsl-mlag-mac-sync xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-ras"/>

```

---

## Command Syntax

```
clear hsl mlag mac-sync-count
```

---

## clear hardware-discard-counters

### Netconf RPC payload

```
<platform-clear-hardware-discard-counters xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ras"/>
```

### Command Syntax

```
clear hardware-discard-counters
```

---

## clear hsl fdb debug-counters

### Netconf RPC payload

```
<platform-clear-hsl-fdb-debug-counters xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ras"/>
```

### Command Syntax

```
clear hsl fdb debug-counters
```

---

## clear hsl system-cpu-stats

### Netconf RPC payload

```
<platform-clear-hsl-system-cpu-stats xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ras"/>
```

### Command Syntax

```
clear hsl system-cpu-stats
```

---

## IPI-UNICAST-RPF

---

### Configure enable route lookup

Use this attribute to enable uRPF globally on the system

This command is supported when following feature are enabled Unicast Reverse Path Forwarding feature

Attribute Name: enable-route-lookup

Attribute Type: empty

### Netconf edit-config payload

```
<unicast-rpf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-unicast-rpf">
  <global>
    <config>
      </enable-route-lookup><!-- operation="delete"-->
```

```

</config>
</global>
</unicast-rpf>

```

### Command Syntax

```
ip urpf enable
```

---

## Configure source reachability mode

Use this attribute to enable uRPF for an interface with specified reachability mode

Attribute Name: source-reachability-mode

Attribute Type: enum (any|rx|any allow-default)

### Netconf edit-config payload

```

<unicast-rpf xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-unicast-rpf">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <source-reachability-mode>any</source-reachability-mode> <!--
operation="delete"-->
    </interface>
  </interfaces>
</unicast-rpf>

```

### Command Syntax

```
ip verify unicast source reachable-via (any|rx|any allow-default)
```

---

## IPI-OSPF-INTERFACE-TRACKING

---

### Configure event name

Attribute used to specify the event-name for OSPF interface tracking.

Attribute Name: event-name

Attribute Type: string

Attribute Name: event-match-criteria

Attribute Type: enum (all|any)

### Netconf edit-config payload

```

<ospf-interfaces-events-tracking xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
ospf-interface-tracking">
  <ospf-interface-events-tracking> <!-- operation="delete"-->
    <event-name>NAME</event-name>
  </config>

```

```

    <event-name>NAME</event-name>
    <event-match-criteria>all</event-match-criteria>
  </config>
</ospf-interface-events-tracking>
</ospf-interfaces-events-tracking>

```

### Command Syntax

```
if-event-track ospf event NAME match (all|any)
```

---

## Configure event neighbor ip address

Attribute used to specify the event neighbor IP address for OSPF interface tracking event.

Attribute Name: event-neighbor-ip-address

Attribute Type: inet:ipv4-address

### Netconf edit-config payload

```

<ospf-interfaces-events-tracking xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
ospf-interface-tracking">
  <ospf-interface-events-tracking>
    <event-name>NAME</event-name>
    <config>
      <event-name>NAME</event-name>
    </config>
    <event-neighbor-ip-address>A.B.C.D</event-neighbor-ip-address> <!--
operation="delete"-->
  </ospf-interface-events-tracking>
</ospf-interfaces-events-tracking>

```

### Command Syntax

```
event nbr A.B.C.D down
```

---

## Configure name

Attribute used to specify the interface name for OSPF interface tracking event action.

Attribute Name: name

Attribute Type: string

Attribute Name: cost

Attribute Type: uint32

Attribute Range: 1-65535

### Netconf edit-config payload

```

<ospf-interfaces-events-tracking xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
ospf-interface-tracking">
  <ospf-interface-events-tracking>
    <event-name>NAME</event-name>
    <config>
      <event-name>NAME</event-name>

```

```

    </config>
  <actions>
  <interfaces>
  <interface> <!-- operation="delete"-->
    <name>IFNAME</name>
    <config>
      <name>IFNAME</name>
      <cost>1</cost>
    </config>
  </interface>
  </interfaces>
  </actions>
</ospf-interface-events-tracking>
</ospf-interfaces-events-tracking>

```

### Command Syntax

```
action interface IFNAME cost <1-65535>
```

---

## IPI-PORT-MIRROR

---

### Configure id

Port mirror session index

Attribute Name: id

Attribute Type: uint32

Attribute Range: 1-18

Attribute Name: type

Attribute Type: enum (local|remote)

### Netconf edit-config payload

```

<port-mirror xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-mirror">
  <sessions>
  <session> <!-- operation="delete"-->
    <id>1</id>
    <config>
      <id>1</id>
      <type>local</type>
    </config>
  </session>
  </sessions>
</port-mirror>

```

### Command Syntax

```
monitor session <1-18> (type (local|remote)|)
```

---

## Configure enabled

Use this attribute to shut/unshut a port-mirror session

Attribute Name: enabled

Attribute Type: uint8

### Netconf edit-config payload

```
<port-mirror xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-mirror">
  <sessions>
    <session>
      <id>1</id>
      <config>
        <id>1</id>
      </config>
      </enabled><!-- operation="delete"-->
    </session>
  </sessions>
</port-mirror>
```

### Command Syntax

```
no shut
```

---

## Configure session enabled

Use this attribute to shut/unshut a port-mirror session

Attribute Name: enabled

Attribute Type: uint8

### Netconf edit-config payload

```
<port-mirror xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-mirror">
  <sessions>
    <session>
      <id>1</id>
      <config>
        <id>1</id>
      </config>
      </enabled><!-- operation="delete"-->
    </session>
  </sessions>
</port-mirror>
```

### Command Syntax

```
no monitor session <1-18> shut
```

---

## Configure description

Use this attribute to add a description to port-mirror session

---

This command is supported when following feature are enabled advance mirror feature

Attribute Name: description

Attribute Type: string

Attribute Range: 1-32

### Netconf edit-config payload

```
<port-mirror xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-mirror">
  <sessions>
    <session>
      <id>1</id>
      <config>
        <id>1</id>
      </config>
      <description>LINE</description> <!-- operation="delete"-->
    </session>
  </sessions>
</port-mirror>
```

### Command Syntax

```
description LINE
```

---

## Configure source vlan

use this attribute to configure source-vlan

This command is supported when following feature are enabled advance mirror feature

Attribute Name: source-vlan

Attribute Type: string

Attribute Range: 2-4094

### Netconf edit-config payload

```
<port-mirror xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-mirror">
  <sessions>
    <session>
      <id>1</id>
      <config>
        <id>1</id>
      </config>
      <source-vlan>VLAN_RANGE</source-vlan> <!-- operation="delete"-->
    </session>
  </sessions>
</port-mirror>
```

### Command Syntax

```
source vlan VLAN_RANGE
```

---

## Configure interface name

Use this attribute to configure port mirror local interface

This command is supported when following feature are enabled advance mirror feature

Attribute Name: interface-name

Attribute Type: string

### Netconf edit-config payload

```
<port-mirror xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-mirror">
  <sessions>
    <session>
      <id>1</id>
      <config>
        <id>1</id>
      </config>
    <destination>
      <local>
        <config>
          <interface-name>IFNAME</interface-name> <!-- operation="delete"-->
        </config>
      </local>
    </destination>
  </session>
</sessions>
</port-mirror>
```

### Command Syntax

```
destination interface IFNAME
```

---

## Configure reflector interface name

Use this attribute to configure port mirror remote reflector interface

This command is supported when following feature are enabled advance mirror feature

Attribute Name: reflector-interface-name

Attribute Type: string

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 2-4094

### Netconf edit-config payload

```
<port-mirror xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-mirror">
  <sessions>
    <session>
      <id>1</id>
      <config>
        <id>1</id>
      </config>
    </session>
  </sessions>
</port-mirror>
```

```

    </config>
  <destination>
    <remote>
      <config>
        <vlan-id>2</vlan-id>
        <reflector-interface-name>IFNAME</reflector-interface-name>
      </config>
    </remote>
  </destination>
</session>
</sessions>
</port-mirror>

```

### Command Syntax

```
destination remote vlan <2-4094> reflector-port IFNAME
```

---

## Configure direction

Source interface direction

This command is supported when following feature are enabled advance mirror feature

Attribute Name: direction

Attribute Type: bits (rx|tx|both)

### Netconf edit-config payload

```

<port-mirror xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-mirror">
  <sessions>
    <session>
      <id>1</id>
      <config>
        <id>1</id>
        </config>
      <source-interfaces>
        <source-interface>
          <name>IFNAME</name>
          <config>
            <name>IFNAME</name>
          </config>
          <direction>rx</direction>
        </source-interface>
      </source-interfaces>
    </session>
  </sessions>
</port-mirror>

```

### Command Syntax

```
source interface IFNAME ((rx|tx|both)|)
```

---

## IPI-RIPNG

---

### Configure options

This attribute enables debugging for RIPng

Attribute Name: options

Attribute Type: bits (all|events|packet send|packet rcv|packet|packet detail|nsm|rib)

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <debug>
  <config>
    <options>all</options> <!-- operation="delete"-->
  </config>
</debug>
</ripng>
```

### Command Syntax

```
debug ipv6 rip (all|events|packet send|packet rcv|packet|packet detail|nsm|rib|)
```

---

### Configure split horizon

Use this attribute to perform the split-horizon action on the interface. Deleting this attribute would set the split-horizon to poisoned reverse which is the default value.

Attribute Name: split-horizon

Attribute Type: boolean

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <interfaces>
  <interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
    <split-horizon>true</split-horizon> <!-- operation="delete"-->
  </interface>
</interfaces>
</ripng>
```

### Command Syntax

```
ipv6 rip split-horizon
```

---

## Configure name

Use this attribute to perform the split-horizon action on the interface. Deleting this attribute would set the split-horizon to poisoned reverse which is the default value.

Attribute Name: split-horizon

Attribute Type: boolean

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <split-horizon>true</split-horizon> <!-- operation="delete"-->
    </interface>
  </interfaces>
</ripng>
```

### Command Syntax

```
no ipv6 rip split-horizon
```

---

## Configure enabled

Use this attribute to perform the router rip action on the interface

Attribute Name: enabled

Attribute Type: empty

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </enabled><!-- operation="delete"-->
    </interface>
  </interfaces>
</ripng>
```

### Command Syntax

```
ipv6 router rip
```

---

## Configure metric offset

Use this attribute to perform the metric-offset action on the interface

Attribute Name: metric-offset

Attribute Type: uint8

Attribute Range: 1-16

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <metric-offset>1</metric-offset> <!-- operation="delete"-->
    </interface>
  </interfaces>
</ripng>
```

### Command Syntax

```
ipv6 rip metric-offset <1-16>
```

---

## Configure ripng enabled

Use this attribute to enable the router instance

Attribute Name: ripng-enabled

Attribute Type: uint8

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <config>
      </ripng-enabled>
    </config>
  </instance>
</ripng>
```

### Command Syntax

```
router ipv6 rip
```

---

## Configure enable cisco metric behavior

Use this attribute to enable the metric update consistent with Cisco

Attribute Name: enable-cisco-metric-behavior

Attribute Type: boolean

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
```

```
<config>
  <enable-cisco-metric-behavior>true</enable-cisco-metric-behavior> <!--
operation="delete"-->
</config>
</instance>
</ripng>
```

## Command Syntax

```
cisco-metric-behavior enable
```

---

## Configure instance enable-cisco-metric-behavior

Use this attribute to enable the metric update consistent with Cisco

Attribute Name: enable-cisco-metric-behavior

Attribute Type: boolean

## Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <config>
      <enable-cisco-metric-behavior>true</enable-cisco-metric-behavior> <!--
operation="delete"-->
    </config>
  </instance>
</ripng>
```

## Command Syntax

```
cisco-metric-behavior disable
```

---

## Configure passive interfaces

Use this attribute to block RIP broadcast on the interface

Attribute Name: passive-interfaces

Attribute Type: string

## Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <config>
      <passive-interfaces>IFNAME</passive-interfaces> <!-- operation="delete"-->
    </config>
  </instance>
</ripng>
```

## Command Syntax

```
passive-interface IFNAME
```

---

## Configure distance

Use this attribute to set the administrative distance. The administrative distance is a feature used by the routers to select the path when there are two or more different routes to the same destination from two different routing protocols. A smaller administrative distance indicating a more reliable protocol

Attribute Name: distance

Attribute Type: uint8

Default Value: 120

Attribute Range: 1-255

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <config>
      <distance>1</distance> <!-- operation="delete"-->
    </config>
  </instance>
</ripng>
```

### Command Syntax

```
distance <1-255>
```

---

## Configure static routes

Use this attribute to configure static RIP routes

Attribute Name: static-routes

Attribute Type: string

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <config>
      <static-routes>X:X::X:X/M</static-routes> <!-- operation="delete"-->
    </config>
  </instance>
</ripng>
```

### Command Syntax

```
route X:X::X:X/M
```

---

## Configure aggregate prefixes

Use this attribute to configure aggregate prefixes

Attribute Name: aggregate-prefixes

Attribute Type: string

---

## Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <config>
      <aggregate-prefixes>X:X::X:X/M</aggregate-prefixes> <!-- operation="delete"-->
    </config>
  </instance>
</ripng>
```

## Command Syntax

```
aggregate-address X:X::X:X/M
```

---

## Configure default metric

Use this attribute to specify the metrics to be assigned to redistributed routers

Attribute Name: default-metric

Attribute Type: uint8

Default Value: 1

Attribute Range: 1-15

## Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <config>
      <default-metric>1</default-metric> <!-- operation="delete"-->
    </config>
  </instance>
</ripng>
```

## Command Syntax

```
default-metric <1-15>
```

---

## Configure originate default route

Use this attribute to add default routes to the RIP updates

Attribute Name: originate-default-route

Attribute Type: empty

## Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <config>
      </originate-default-route><!-- operation="delete"-->
    </config>
  </instance>
</ripng>
```

---

## Command Syntax

```
default-information originate
```

---

## Configure receive buffer size

Use this attribute to run-time configure the RIP UDP receive-buffer size

Attribute Name: receive-buffer-size

Attribute Type: uint32

Default Value: 8192

Attribute Range: 8192-2147483647

## Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <config>
      <receive-buffer-size>8192</receive-buffer-size> <!-- operation="delete"-->
    </config>
  </instance>
</ripng>
```

## Command Syntax

```
recv-buffer-size <8192-2147483647>
```

---

## Configure route type

Use this attribute to redistribute information from other routing protocols

Attribute Name: route-type

Attribute Type: enum (kernel|connected|static|ospf6|isis|bgp)

## Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <redistribute-policies>
      <redistribute-policy> <!-- operation="delete"-->
        <route-type>kernel</route-type>
      </redistribute-policy>
    </redistribute-policies>
  </instance>
</ripng>
```

## Command Syntax

```
redistribute (kernel|connected|static|ospf6|isis|bgp)
```

---

## Configure route map

Use this attribute to redistribute route-map from other routing protocols

Attribute Name: route-map

Attribute Type: string

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <redistribute-policies>
      <redistribute-policy>
        <route-type>kernel</route-type>
        <config>
          <route-type>kernel</route-type>
          <metric>0</metric>
        </config>
        <route-map>WORD</route-map>
      </redistribute-policy>
    </redistribute-policies>
  </instance>
</ripng>
```

### Command Syntax

```
redistribute (kernel|connected|static|ospf6|isis|bgp) metric <0-16> route-map WORD
```

---

## Configure metric

Use this attribute to redistribute metric information from other routing protocols

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <redistribute-policies>
      <redistribute-policy>
        <route-type>kernel</route-type>
        <config>
          <route-type>kernel</route-type>
          <metric>0</metric>
        </config>
      </redistribute-policy>
    </redistribute-policies>
  </instance>
</ripng>
```

```

</redistribute-policies>
</instance>
</ripng>

```

## Command Syntax

```
redistribute (kernel|connected|static|ospf6|isis|bgp) metric <0-16>
```

---

## Configure redistribute-policy route-map

Use this attribute to redistribute route-map from other routing protocols

Attribute Name: route-map

Attribute Type: string

### Netconf edit-config payload

```

<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <redistribute-policies>
      <redistribute-policy>
        <route-type>kernel</route-type>
        <config>
          <route-type>kernel</route-type>
        </config>
        <route-map>WORD</route-map>
      </redistribute-policy>
    </redistribute-policies>
  </instance>
</ripng>

```

## Command Syntax

```
redistribute (kernel|connected|static|ospf6|isis|bgp) route-map WORD
```

---

## Configure route table update interval

Use this attribute to adjust basic routing protocol update timer interval

Attribute Name: route-table-update-interval

Attribute Type: uint32

Attribute Range: 5-2147483647

Attribute Name: route-info-timeout-interval

Attribute Type: uint32

Attribute Range: 5-2147483647

Attribute Name: garbage-collection-interval

Attribute Type: uint32

Attribute Range: 5-2147483647

## Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <timers>
      <config>
        <route-info-timeout-interval>5</route-info-timeout-interval>
        <garbage-collection-interval>5</garbage-collection-interval>
        <route-table-update-interval>5</route-table-update-interval>
      </config>
    </timers>
  </instance>
</ripng>
```

## Command Syntax

```
timers basic <5-2147483647> <5-2147483647> <5-2147483647>
```

---

## Configure address

Use this attribute to specify a link local address of neighbor router. It is used for each connected point-to-point link. This command exchanges non-broadcast routing information. It can be used multiple times for additional neighbors

Attribute Name: address

Attribute Type: inet:ipv6-address

Attribute Name: if-name

Attribute Type: string

## Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <neighbors>
      <neighbor> <!-- operation="delete"-->
        <address>X:X::X:X</address>
        <config>
          <address>X:X::X:X</address>
          <if-name>IFNAME</if-name>
        </config>
      </neighbor>
    </neighbors>
  </instance>
</ripng>
```

## Command Syntax

```
neighbor X:X::X:X IFNAME
```

---

## Configure type

Use this attribute to decide the type of packets to which the filtering is applied

Attribute Name: type

Attribute Type: enum (in|out)

Attribute Name: route-map-name

Attribute Type: string

Attribute Range: 1-63

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <interfaces>
      <interface>
        <name>IFNAME</name>
        <config>
          <name>WORD</name>
        </config>
      <filtering-route-maps>
      <filtering-route-map>
        <type>in</type>
        <config>
          <type>in</type>
          <route-map-name>WORD</route-map-name>
        </config>
      </filtering-route-map>
      </filtering-route-maps>
    </interface>
  </interfaces>
</instance>
</ripng>
```

### Command Syntax

```
route-map WORD (in|out) IFNAME
```

---

## Configure access list name

This attribute describes the metric used for offset list

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

Attribute Name: access-list-name

Attribute Type: string

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <interfaces>
      <interface>
        <name>IFNAME</name>
        <config>
```

```

        <name>WORD</name>
    </config>
</offset-lists>
<offset-list>
    <direction>in</direction>
    <config>
        <direction>in</direction>
        <access-list-name>WORD</access-list-name>
    </config>
    <metric>0</metric>
</offset-list>
</offset-lists>
</interface>
</interfaces>
</instance>
</ripng>

```

## Command Syntax

```
offset-list WORD (in|out) <0-16> IFNAME
```

---

## Configure direction

Use this attribute to decide the type of packets to which the distribute list is applied

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: access-list-name

Attribute Type: string

## Netconf edit-config payload

```

<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <interfaces>
      <interface>
        <name>IFNAME</name>
        <config>
          <name>WORD</name>
        </config>
      <distributed-lists>
      <distributed-list>
        <direction>in</direction>
        <config>
          <direction>in</direction>
          <access-list-name>WORD</access-list-name>
        </config>
      </distributed-list>
    </distributed-lists>
  </interface>
</interfaces>

```

```
</instance>  
</ripng>
```

## Command Syntax

```
distribute-list WORD (in|out) IFNAME
```

---

## Configure list name

Use this attribute to decide the type of packets to which the distribute list prefix is applied

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: list-name

Attribute Type: string

## Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">  
  <instance>  
    <interfaces>  
      <interface>  
        <name>IFNAME</name>  
        <config>  
          <name>WORD</name>  
        </config>  
      <distributed-prefix-lists>  
      <distributed-prefix-list>  
        <direction>in</direction>  
        <config>  
          <direction>in</direction>  
          <list-name>WORD</list-name>  
        </config>  
      </distributed-prefix-list>  
    </distributed-prefix-lists>  
  </interface>  
</interfaces>  
</instance>  
</ripng>
```

## Command Syntax

```
distribute-list prefix WORD (in|out) IFNAME
```

---

## Configure offset-list metric

This attribute describes the metric used for offset list

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

Attribute Name: access-list-name

Attribute Type: string

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <offset-lists>
      <offset-list>
        <direction>in</direction>
        <config>
          <direction>in</direction>
          <access-list-name>WORD</access-list-name>
        </config>
        <metric>0</metric>
      </offset-list>
    </offset-lists>
  </instance>
</ripng>
```

### Command Syntax

```
offset-list WORD (in|out) <0-16>
```

---

## Configure distribute-list direction

Use this attribute to decide the type of packets to which the distribute list is applied

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: access-list-name

Attribute Type: string

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <distribute-lists>
      <distribute-list>
        <direction>in</direction>
        <config>
          <direction>in</direction>
          <access-list-name>WORD</access-list-name>
        </config>
      </distribute-list>
    </distribute-lists>
  </instance>
</ripng>
```

### Command Syntax

```
distribute-list WORD (in|out)
```

---

## Configure distribute-prefix-list direction

Use this attribute to decide the type of packets to which the distribute list prefix is applied

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: list-name

Attribute Type: string

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <distribute-prefix-lists>
      <distribute-prefix-list>
        <direction>in</direction>
        <config>
          <direction>in</direction>
          <list-name>WORD</list-name>
        </config>
      </distribute-prefix-list>
    </distribute-prefix-lists>
  </instance>
</ripng>
```

### Command Syntax

```
distribute-list prefix WORD (in|out)
```

---

## debug ipv6 rip (all|events|packet send|packet rcv|packet|packet detail|nsm|rib)

Attribute Name: terminal-debug-options

Attribute Type: bits (all|events|packet send|packet rcv|packet|packet detail|nsm|rib)

### Netconf RPC payload

```
<ripng-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <terminal-debug-options>all</terminal-debug-options>
</ripng-terminal-debug-on>
```

### Command Syntax

```
debug ipv6 rip (all|events|packet send|packet rcv|packet|packet detail|nsm|rib)
```

---

## no debug ipv6 rip (all|events|packet send|packet rcv|packet|packet detail|nsm|rib)

Attribute Name: terminal-debug-options

Attribute Type: bits (all|events|packet send|packet rcv|packet|packet detail|nsm|rib)

---

## Netconf RPC payload

```
<ripng-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <terminal-debug-options>all</terminal-debug-options>
</ripng-terminal-debug-off>
```

## Command Syntax

```
no debug ipv6 rip (all|events|packet send|packet recv|packet|packet detail|nsm|rib)
```

---

## clear ipv6 rip route (kernel|connected|static|isis|ospf6|bgp|rip|all)

Attribute Name: type

Attribute Type: enum (kernel|connected|static|isis|ospf6|bgp|rip|all)

## Netconf RPC payload

```
<ripng-clear-route xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <type>kernel</type>
</ripng-clear-route>
```

## Command Syntax

```
clear ipv6 rip route (kernel|connected|static|isis|ospf6|bgp|rip|all)
```

---

## clear ipv6 rip route X:X::X:X/M

Attribute Name: prefix

Attribute Type: string

## Netconf RPC payload

```
<ripng-clear-route-prefix xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <prefix>X:X::X:X/M</prefix>
</ripng-clear-route-prefix>
```

## Command Syntax

```
clear ipv6 rip route X:X::X:X/M
```

---

# IPI-RIPNG-VRF

---

## Configure vrf name

VRF Name

Attribute Name: vrf-name

Attribute Type: string

## Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
```

```

<instance>
  <vrfs>
    <vrf> <!-- operation="delete"-->
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
      </config>
    </vrf>
  </vrfs>
</instance>
</ripng>

```

### Command Syntax

```
address-family ipv6 vrf NAME
```

---

## Configure enable cisco metric behavior

Use this attribute to enable the metric update consistent with Cisco

Attribute Name: enable-cisco-metric-behavior

Attribute Type: boolean

### Netconf edit-config payload

```

<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <enable-cisco-metric-behavior>true</enable-cisco-metric-behavior> <!--
operation="delete"-->
      </vrf>
    </vrfs>
  </instance>
</ripng>

```

### Command Syntax

```
cisco-metric-behavior enable
```

---

## Configure vrf enable-cisco-metric-behavior

Use this attribute to enable the metric update consistent with Cisco

Attribute Name: enable-cisco-metric-behavior

Attribute Type: boolean

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
```

```

<instance>
  <vrfs>
    <vrf>
      <vrf-name>NAME</vrf-name>
      <config>
        <vrf-name>WORD</vrf-name>
      </config>
      <enable-cisco-metric-behavior>true</enable-cisco-metric-behavior> <!--
operation="delete"-->
    </vrf>
  </vrfs>
</instance>
</ripng>

```

### Command Syntax

```
cisco-metric-behavior disable
```

---

## Configure passive interfaces

Use this attribute to block RIP broadcast on the interface

Attribute Name: passive-interfaces

Attribute Type: string

### Netconf edit-config payload

```

<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <passive-interfaces>IFNAME</passive-interfaces> <!-- operation="delete"--
>
      </vrf>
    </vrfs>
  </instance>
</ripng>

```

### Command Syntax

```
passive-interface IFNAME
```

---

## Configure distance

Use this attribute to set the administrative distance. The administrative distance is a feature used by the routers to select the path when there are two or more different routes to the same destination from two different routing protocols. A smaller administrative distance indicating a more reliable protocol

Attribute Name: distance

Attribute Type: uint8

Default Value: 120

Attribute Range: 1-255

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <distance>1</distance> <!-- operation="delete"-->
      </vrf>
    </vrfs>
  </instance>
</ripng>
```

### Command Syntax

```
distance <1-255>
```

---

## Configure static routes

Use this attribute to configure static RIP routes

Attribute Name: static-routes

Attribute Type: string

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <static-routes>X:X::X:X/M</static-routes> <!-- operation="delete"-->
      </vrf>
    </vrfs>
  </instance>
</ripng>
```

### Command Syntax

```
route X:X::X:X/M
```

---

## Configure aggregate prefixes

Use this attribute to configure aggregate prefixes

Attribute Name: aggregate-prefixes

Attribute Type: string

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <aggregate-prefixes>X:X::X:X/M</aggregate-prefixes> <!--
operation="delete"-->
      </vrf>
    </vrfs>
  </instance>
</ripng>
```

### Command Syntax

```
aggregate-address X:X::X:X/M
```

---

## Configure default metric

Use this attribute to specify the metrics to be assigned to redistributed routers

Attribute Name: default-metric

Attribute Type: uint8

Default Value: 1

Attribute Range: 1-15

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
          <default-metric>1</default-metric> <!-- operation="delete"-->
        </config>
      </vrf>
    </vrfs>
  </instance>
</ripng>
```

### Command Syntax

```
default-metric <1-15>
```

---

## Configure originate default route

Use this attribute to add default routes to the RIP updates

Attribute Name: originate-default-route

Attribute Type: empty

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        </originate-default-route><!-- operation="delete"-->
      </vrf>
    </vrfs>
  </instance>
</ripng>
```

### Command Syntax

```
default-information originate
```

---

## Configure receive buffer size

Use this attribute to run-time configure the RIP UDP receive-buffer size

Attribute Name: receive-buffer-size

Attribute Type: uint32

Default Value: 8192

Attribute Range: 8192-2147483647

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <receive-buffer-size>8192</receive-buffer-size> <!-- operation="delete"-->
      </vrf>
    </vrfs>
  </instance>
</ripng>
```

---

## Command Syntax

```
recv-buffer-size <8192-2147483647>
```

---

## Configure route type

Use this attribute to redistribute information from other routing protocols

Attribute Name: route-type

Attribute Type: enum (connected|static|ospf6|bgp)

## Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <redistribute-policies>
          <redistribute-policy> <!-- operation="delete"-->
            <route-type>connected</route-type>
            <config>
              <route-type>connected</route-type>
            </config>
          </redistribute-policy>
        </redistribute-policies>
      </vrf>
    </vrfs>
  </instance>
</ripng>
```

## Command Syntax

```
redistribute (connected|static|ospf6|bgp)
```

---

## Configure route map

Use this attribute to redistribute route-map from other routing protocols

Attribute Name: route-map

Attribute Type: string

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

## Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
```

```

<vrfs>
<vrf>
  <vrf-name>NAME</vrf-name>
  <config>
    <vrf-name>WORD</vrf-name>
  </config>
  <redistribute-policies>
  <redistribute-policy>
    <route-type>connected</route-type>
    <config>
      <route-type>connected</route-type>
      <metric>0</metric>
    </config>
    <route-map>WORD</route-map>
  </redistribute-policy>
</redistribute-policies>
</vrf>
</vrfs>
</instance>
</ripng>

```

## Command Syntax

```
redistribute (connected|static|ospf6|bgp) metric <0-16> route-map WORD
```

---

## Configure metric

Use this attribute to redistribute metric information from other routing protocols

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

## Netconf edit-config payload

```

<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
<instance>
  <vrfs>
  <vrf>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>WORD</vrf-name>
    </config>
    <redistribute-policies>
    <redistribute-policy>
      <route-type>connected</route-type>
      <config>
        <route-type>connected</route-type>
      </config>
      <metric>0</metric>
    </redistribute-policy>
  </redistribute-policies>

```

```

</vrf>
</vrfs>
</instance>
</ripng>

```

## Command Syntax

```
redistribute (connected|static|ospf6|bgp) metric <0-16>
```

---

## Configure redistribute-policy route-map

Use this attribute to redistribute route-map from other routing protocols

Attribute Name: route-map

Attribute Type: string

### Netconf edit-config payload

```

<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <redistribute-policies>
          <redistribute-policy>
            <route-type>connected</route-type>
            <config>
              <route-type>connected</route-type>
            </config>
            <route-map>WORD</route-map>
          </redistribute-policy>
        </redistribute-policies>
      </vrf>
    </vrfs>
  </instance>
</ripng>

```

## Command Syntax

```
redistribute (connected|static|ospf6|bgp) route-map WORD
```

---

## Configure route table update interval

Use this attribute to adjust basic routing protocol update timer interval

Attribute Name: route-table-update-interval

Attribute Type: uint32

Attribute Range: 5-2147483647

Attribute Name: route-info-timeout-interval

Attribute Type: uint32

Attribute Range: 5-2147483647

Attribute Name: garbage-collection-interval

Attribute Type: uint32

Attribute Range: 5-2147483647

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <timers>
          <config>
            <route-info-timeout-interval>5</route-info-timeout-interval>
            <garbage-collection-interval>5</garbage-collection-interval>
            <route-table-update-interval>5</route-table-update-interval>
          </config>
        </timers>
      </vrf>
    </vrfs>
  </instance>
</ripng>
```

### Command Syntax

```
timers basic <5-2147483647> <5-2147483647> <5-2147483647>
```

---

## Configure address

Use this attribute to specify a link local address of neighbor router. It is used for each connected point-to-point link. This command exchanges non-broadcast routing information. It can be used multiple times for additional neighbors

Attribute Name: address

Attribute Type: inet:ipv6-address

Attribute Name: if-name

Attribute Type: string

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
      </vrf>
    </vrfs>
  </instance>
</ripng>
```

```

    </config>
  <neighbors>
    <neighbor> <!-- operation="delete"-->
      <address>X:X::X:X</address>
      <config>
        <address>X:X::X:X</address>
        <if-name>IFNAME</if-name>
      </config>
    </neighbor>
  </neighbors>
</vrf>
</vrfs>
</instance>
</ripng>

```

## Command Syntax

```
neighbor X:X::X:X IFNAME
```

---

## Configure type

Use this attribute to decide the type of packets to which the filtering is applied

Attribute Name: type

Attribute Type: enum (in|out)

Attribute Name: route-map-name

Attribute Type: string

Attribute Range: 1-63

## Netconf edit-config payload

```

<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
      </vrf>
    </vrfs>
    <interfaces>
      <interface>
        <name>IFNAME</name>
        <config>
          <name>WORD</name>
        </config>
        <filtering-route-maps>
          <filtering-route-map>
            <type>in</type>
            <config>
              <type>in</type>
              <route-map-name>WORD</route-map-name>
            </config>
          </filtering-route-map>
        </filtering-route-maps>
      </interface>
    </interfaces>
  </instance>
</ripng>

```

```

        </config>
    </filtering-route-map>
</filtering-route-maps>
</interface>
</interfaces>
</vrf>
</vrfs>
</instance>
</ripng>

```

## Command Syntax

```
route-map WORD (in|out) IFNAME
```

---

## Configure access list name

This attribute describes the metric used for offset list

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

Attribute Name: access-list-name

Attribute Type: string

## Netconf edit-config payload

```

<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <interfaces>
          <interface>
            <name>IFNAME</name>
            <config>
              <name>WORD</name>
            </config>
            <offset-lists>
              <offset-list>
                <direction>in</direction>
                <config>
                  <direction>in</direction>
                  <access-list-name>WORD</access-list-name>
                </config>
                <metric>0</metric>
              </offset-list>
            </offset-lists>
          </interface>

```

```

</interfaces>
</vrf>
</vrfs>
</instance>
</ripng>

```

## Command Syntax

```
offset-list WORD (in|out) <0-16> IFNAME
```

---

## Configure direction

Use this attribute to decide the type of packets to which the distribute list is applied

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: access-list-name

Attribute Type: string

## Netconf edit-config payload

```

<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <interfaces>
          <interface>
            <name>IFNAME</name>
            <config>
              <name>WORD</name>
            </config>
            <distribute-lists>
              <distribute-list>
                <direction>in</direction>
                <config>
                  <direction>in</direction>
                  <access-list-name>WORD</access-list-name>
                </config>
              </distribute-list>
            </distribute-lists>
          </interface>
        </interfaces>
      </vrf>
    </vrfs>
  </instance>
</ripng>

```

---

## Command Syntax

```
distribute-list WORD (in|out) IFNAME
```

---

## Configure list name

Use this attribute to decide the type of packets to which the distribute list prefix is applied

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: list-name

Attribute Type: string

## Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <interfaces>
          <interface>
            <name>IFNAME</name>
            <config>
              <name>WORD</name>
            </config>
            <distribute-prefix-lists>
              <distribute-prefix-list>
                <direction>in</direction>
                <config>
                  <direction>in</direction>
                  <list-name>WORD</list-name>
                </config>
              </distribute-prefix-list>
            </distribute-prefix-lists>
          </interface>
        </interfaces>
      </vrf>
    </vrfs>
  </instance>
</ripng>
```

## Command Syntax

```
distribute-list prefix WORD (in|out) IFNAME
```

---

## Configure offset-list metric

This attribute describes the metric used for offset list

Attribute Name: metric

Attribute Type: uint8

Attribute Range: 0-16

Attribute Name: access-list-name

Attribute Type: string

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
        <config>
          <vrf-name>WORD</vrf-name>
        </config>
        <offset-lists>
          <offset-list>
            <direction>in</direction>
            <config>
              <direction>in</direction>
              <access-list-name>WORD</access-list-name>
            </config>
            <metric>0</metric>
          </offset-list>
        </offset-lists>
      </vrf>
    </vrfs>
  </instance>
</ripng>
```

### Command Syntax

```
offset-list WORD (in|out) <0-16>
```

---

## Configure distribute-list direction

Use this attribute to decide the type of packets to which the distribute list is applied

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: access-list-name

Attribute Type: string

### Netconf edit-config payload

```
<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
  <instance>
    <vrfs>
      <vrf>
        <vrf-name>NAME</vrf-name>
```

```

<config>
  <vrf-name>WORD</vrf-name>
</config>
<distribute-lists>
<distribute-list>
  <direction>in</direction>
  <config>
    <direction>in</direction>
    <access-list-name>WORD</access-list-name>
  </config>
</distribute-list>
</distribute-lists>
</vrf>
</vrfs>
</instance>
</ripng>

```

## Command Syntax

```
distribute-list WORD (in|out)
```

---

## Configure distribute-prefix-list direction

Use this attribute to decide the type of packets to which the distribute list prefix is applied

Attribute Name: direction

Attribute Type: enum (in|out)

Attribute Name: list-name

Attribute Type: string

## Netconf edit-config payload

```

<ripng xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ripng">
<instance>
  <vrfs>
  <vrf>
    <vrf-name>NAME</vrf-name>
    <config>
      <vrf-name>WORD</vrf-name>
    </config>
    <distribute-prefix-lists>
    <distribute-prefix-list>
      <direction>in</direction>
      <config>
        <direction>in</direction>
        <list-name>WORD</list-name>
      </config>
    </distribute-prefix-list>
  </distribute-prefix-lists>
  </vrf>
</vrfs>

```

```
</instance>  
</ripng>
```

## Command Syntax

```
distribute-list prefix WORD (in|out)
```

---

# IPI-ARP

---

## Configure ip address

Use this attribute to create a static ARP entry

Attribute Name: ip-address

Attribute Type: inet:ipv4-address

Attribute Name: mac-address

Attribute Type: string

## Netconf edit-config payload

```
<arp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-arp">  
  <entries>  
    <entry> <!-- operation="delete"-->  
      <ip-address>A.B.C.D</ip-address>  
      <config>  
        <ip-address>A.B.C.D</ip-address>  
        <vrf-name>NAME</vrf-name>  
        <mac-address>XXXX.XXXX.XXXX</mac-address>  
      </config>  
    </entry>  
  </entries>  
</arp>
```

## Command Syntax

```
ip arp (vrf NAME|) A.B.C.D XXXX.XXXX.XXXX
```

---

## Configure respond to arp request

Use this attribute to set the response to ARP requests for the IP address

Attribute Name: respond-to-arp-request

Attribute Type: empty

Attribute Name: mac-address

Attribute Type: string

## Netconf edit-config payload

```
<arp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-arp">
```

```

<entries>
<entry>
  <ip-address>A.B.C.D</ip-address>
  <config>
    <ip-address>A.B.C.D</ip-address>
    <vrf-name>NAME</vrf-name>
    <mac-address>XXXX.XXXX.XXXX</mac-address>
  </config>
  <vrf-name>NAME</vrf-name>
  </respond-to-arp-request>
</entry>
</entries>
</arp>

```

### Command Syntax

```
ip arp (vrf NAME|) A.B.C.D XXXX.XXXX.XXXX alias
```

---

## Configure enable

Enable/Disable arp event debug

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```

<arp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-arp">
<debug>
<config>
  </enable><!-- operation="delete"-->
</config>
</debug>
</arp>

```

### Command Syntax

```
debug ip arp event
```

---

## Configure enable proxy arp

Use this attribute to enable the proxy ARP feature

Attribute Name: enable-proxy-arp

Attribute Type: empty

### Netconf edit-config payload

```

<arp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-arp">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>

```

```
    </config>
  </enable-proxy-arp><!-- operation="delete"-->
</interface>
</interfaces>
</arp>
```

### Command Syntax

```
ip proxy-arp
```

---

## Configure enable local proxy arp

Use this attribute to enable the local proxy ARP feature

Attribute Name: enable-local-proxy-arp

Attribute Type: empty

### Netconf edit-config payload

```
<arp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-arp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </enable-local-proxy-arp><!-- operation="delete"-->
    </interface>
  </interfaces>
</arp>
```

### Command Syntax

```
ip local-proxy-arp
```

---

## Configure enable ip redirects

Use this attribute to enable ICMP redirects in kernel

Attribute Name: enable-ip-redirects

Attribute Type: empty

### Netconf edit-config payload

```
<arp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-arp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </enable-ip-redirects><!-- operation="delete"-->
    </interface>
  </interfaces>
```

```
</arp>
```

## Command Syntax

```
ip redirects
```

---

## Configure arp ageing timeout

Use this attribute to set the ARP aging timeout. The bridge aging time affects the ARP entries which are dependent upon the MAC addresses in hardware. If a MAC address ages out, it causes the corresponding ARP entry to refresh.

Attribute Name: arp-ageing-timeout

Attribute Type: uint16

Default Value: 1500

Attribute Range: 60-36000

## Netconf edit-config payload

```
<arp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-arp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <arp-ageing-timeout>60</arp-ageing-timeout> <!-- operation="delete"-->
    </interface>
  </interfaces>
</arp>
```

## Command Syntax

```
arp-ageing-timeout <60-36000>
```

---

## Configure arp reachable time

Use this attribute to set the ARP reachable time.

Attribute Name: arp-reachable-time

Attribute Type: uint16

Default Value: 60

Attribute Range: 10-36000

## Netconf edit-config payload

```
<arp xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-arp">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
</arp>
```

```
<arp-reachable-time>10</arp-reachable-time> <!-- operation="delete"-->
</interface>
</interfaces>
</arp>
```

### Command Syntax

```
arp-reachable-time <10-36000>
```

---

## debug ip arp event

### Netconf RPC payload

```
<arp-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-arp"/>
```

### Command Syntax

```
debug ip arp event
```

---

## no debug ip arp event

### Netconf RPC payload

```
<arp-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-arp"/>
```

### Command Syntax

```
no debug ip arp event
```

---

## clear arp (A.B.C.D|) (vrf (all|VRFNAME|default|))

Attribute Name: ip-address

Attribute Type: inet:ipv4-address

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<clear-arp-entry xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-arp">
<ip-address>A.B.C.D</ip-address>
<vrf-name>all</vrf-name>
</clear-arp-entry>
```

### Command Syntax

```
clear arp (A.B.C.D|) (vrf (all|VRFNAME|default|))
```

---

## clear arp IFNAME (vrf (all|VRFNAME|default|))

Attribute Name: if-name

Attribute Type: string

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<clear-arp-entry-per-interface xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
arp">
  <if-name>IFNAME</if-name>
  <vrf-name>all</vrf-name>
</clear-arp-entry-per-interface>
```

### Command Syntax

```
clear arp IFNAME (vrf (all|VRFNAME|default)|)
```

---

## IPI-NEIGHBOR-DISCOVERY

---

### Configure interface name

Use this attribute to add a static neighbor entry of the interface name

Attribute Name: interface-name

Attribute Type: string

Attribute Name: mac-address

Attribute Type: string

### Netconf edit-config payload

```
<neighbor-discovery xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-neighbor-
discovery">
  <entries>
    <entry> <!-- operation="delete"-->
      <interface-name>IFNAME</interface-name>
      <config>
        <interface-name>IFNAME</interface-name>
        <ipv6-address>X:X::X:X</ipv6-address>
        <mac-address>XXXX.XXXX.XXXX</mac-address>
      </config>
      <ipv6-address>X:X::X:X</ipv6-address>
    </entry>
  </entries>
</neighbor-discovery>
```

### Command Syntax

```
ipv6 neighbor X:X::X:X IFNAME XXXX.XXXX.XXXX
```

---

### Configure ipv6 address

Use this attribute to add a static neighbor entry of the interface name

Attribute Name: interface-name

Attribute Type: string

---

## Netconf edit-config payload

```
<neighbor-discovery xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-neighbor-
discovery">
  <entries>
    <entry>
      <interface-name>IFNAME</interface-name>
      <config>
        <interface-name>IFNAME</interface-name>
        <ipv6-address>X:X::X:X</ipv6-address>
      </config>
      <ipv6-address>X:X::X:X</ipv6-address>
    </entry>
  </entries>
</neighbor-discovery>
```

## Command Syntax

```
ipv6 neighbor X:X::X:X IFNAME IFNAME
```

---

## Configure enable

Use this attribute to enable debugging for neighbor events.

Attribute Name: enable

Attribute Type: empty

## Netconf edit-config payload

```
<neighbor-discovery xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-neighbor-
discovery">
  <debug>
    <config>
      </enable><!-- operation="delete"-->
    </config>
  </debug>
</neighbor-discovery>
```

## Command Syntax

```
debug ipv6 nd event
```

---

## Configure nd ageing timeout

Use this attribute to set the neighbor ageing timeout value.

Attribute Name: nd-ageing-timeout

Attribute Type: uint16

Default Value: 1500

Attribute Range: 60-36000

## Netconf edit-config payload

```
<neighbor-discovery xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-neighbor-
discovery">
```

```

<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <nd-ageing-timeout>60</nd-ageing-timeout> <!-- operation="delete"-->
</interface>
</interfaces>
</neighbor-discovery>

```

### Command Syntax

```
nd-ageing-timeout <60-36000>
```

---

## Configure nd reachable time

Use this attribute to set neighbor reachable time value.

Attribute Name: nd-reachable-time

Attribute Type: uint32

Default Value: 60

Attribute Range: 10-36000

### Netconf edit-config payload

```

<neighbor-discovery xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-neighbor-
discovery">
  <interfaces>
  <interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
    <nd-reachable-time>10</nd-reachable-time> <!-- operation="delete"-->
  </interface>
</interfaces>
</neighbor-discovery>

```

### Command Syntax

```
nd-reachable-time <10-36000>
```

---

## Configure no ip unreachable

Use this attribute to set ip unreachable.

Attribute Name: no-ip-unreachable

Attribute Type: empty

### Netconf edit-config payload

```

<neighbor-discovery xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-neighbor-
discovery">

```

```
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </no-ip-unreachable><!-- operation="delete"-->
</interface>
</interfaces>
</neighbor-discovery>
```

### Command Syntax

```
no ip unreachable
```

---

## Configure no ipv6 unreachable

Use this attribute to set ipv6 unreachable.

Attribute Name: no-ipv6-unreachable

Attribute Type: empty

### Netconf edit-config payload

```
<neighbor-discovery xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-neighbor-
discovery">
  <interfaces>
  <interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
    </no-ipv6-unreachable><!-- operation="delete"-->
  </interface>
</interfaces>
</neighbor-discovery>
```

### Command Syntax

```
no ipv6 unreachable
```

---

## debug ipv6 nd event

### Netconf RPC payload

```
<nd-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-neighbor-
discovery"/>
```

### Command Syntax

```
debug ipv6 nd event
```

---

## no debug ipv6 nd event

### Netconf RPC payload

```
<nd-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-neighbor-discovery"/>
```

### Command Syntax

```
no debug ipv6 nd event
```

---

## clear ipv6 neighbors (X:X::X:X/M|) (vrf (all|VRFNAME|default|))

Attribute Name: ipv6-address

Attribute Type: string

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<clear-ipv6-nd-entry xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-neighbor-discovery">  
  <ipv6-address>X:X::X:X/M</ipv6-address>  
  <vrf-name>all</vrf-name>  
</clear-ipv6-nd-entry>
```

### Command Syntax

```
clear ipv6 neighbors (X:X::X:X/M|) (vrf (all|VRFNAME|default|))
```

---

## clear ipv6 neighbors IFNAME (vrf (all|VRFNAME|default|))

Attribute Name: if-name

Attribute Type: string

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<clear-ipv6-nd-entry-per-interface xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-neighbor-discovery">  
  <if-name>IFNAME</if-name>  
  <vrf-name>all</vrf-name>  
</clear-ipv6-nd-entry-per-interface>
```

### Command Syntax

```
clear ipv6 neighbors IFNAME (vrf (all|VRFNAME|default|))
```

---

## IPI-USER-SESSION-MANAGEMENT

---

### Configure console id

Attribute used to set line console identification.

Attribute Name: console-id

Attribute Type: enum (0)

### Netconf edit-config payload

```
<user-session xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-session-
management">
  <line-console>
    <console> <!-- operation="delete"-->
      <console-id>0</console-id>
    <config>
      <console-id>0</console-id>
    </config>
  </console>
</line-console>
</user-session>
```

### Command Syntax

```
line console <0-0>
```

---

### Configure privilege level

Attribute used to set line privilege level.

Attribute Name: privilege-level

Attribute Type: uint8

Attribute Range: 1-16

### Netconf edit-config payload

```
<user-session xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-session-
management">
  <line-console>
    <console>
      <console-id>0</console-id>
    <config>
      <console-id>0</console-id>
    </config>
    <privilege-level>1</privilege-level> <!-- operation="delete"-->
  </console>
</line-console>
</user-session>
```

---

## Command Syntax

```
privilege level <1-16>
```

---

## Configure command history max limit

Attribute used to set line maximum limit to history commands.

Attribute Name: command-history-max-limit

Attribute Type: uint32

Attribute Range: 0-2147483647

### Netconf edit-config payload

```
<user-session xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-session-
management">
  <line-console>
    <console>
      <console-id>0</console-id>
      <config>
        <console-id>0</console-id>
      </config>
      <command-history-max-limit>0</command-history-max-limit> <!--
operation="delete"-->
    </console>
  </line-console>
</user-session>
```

## Command Syntax

```
history max <0-2147483647>
```

---

## Configure seconds

Attribute used to set line timeout in seconds. The default is 0.

Attribute Name: seconds

Attribute Type: uint32

Attribute Range: 0-2147483

Attribute Name: minutes

Attribute Type: uint32

Attribute Range: 0-35791

### Netconf edit-config payload

```
<user-session xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-session-
management">
  <line-console>
    <console>
      <console-id>0</console-id>
      <config>
        <console-id>0</console-id>
      </config>
    </console>
  </line-console>
</user-session>
```

```
    </config>
  <timeout>
  <config>
    <minutes>0</minutes> <!-- operation="delete"-->
    <seconds>0</seconds> <!-- operation="delete"-->
  </config>
</timeout>
</console>
</line-console>
</user-session>
```

### Command Syntax

```
exec-timeout <0-35791> <0-2147483>
```

---

## Configure minutes

Attribute used to set line timeout in minutes. The default is 10 minutes.

Attribute Name: minutes

Attribute Type: uint32

Attribute Range: 0-35791

### Netconf edit-config payload

```
<user-session xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-session-
management">
  <line-console>
  <console>
    <console-id>0</console-id>
    <config>
      <console-id>0</console-id>
    </config>
  <timeout>
  <config>
    <minutes>0</minutes>
  </config>
</timeout>
</console>
</line-console>
</user-session>
```

### Command Syntax

```
exec-timeout <0-35791>
```

---

## Configure vty id

Attribute used to set line privilege level.

Attribute Name: privilege-level

Attribute Type: uint8

---

Attribute Range: 1-16

### Netconf edit-config payload

```
<user-session xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-session-
management">
  <line-vty>
    <vty>
      <vty-id>0</vty-id>
      <config>
        <vty-id>0</vty-id>
      </config>
      <privilege-level>1</privilege-level> <!-- operation="delete"-->
    </vty>
  </line-vty>
</user-session>
```

### Command Syntax

```
privilege level <1-16>
```

---

## Configure vty command-history-max-limit

Attribute used to set line maximum limit to history commands.

Attribute Name: command-history-max-limit

Attribute Type: uint32

Attribute Range: 0-2147483647

### Netconf edit-config payload

```
<user-session xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-session-
management">
  <line-vty>
    <vty>
      <vty-id>0</vty-id>
      <config>
        <vty-id>0</vty-id>
      </config>
      <command-history-max-limit>0</command-history-max-limit> <!--
operation="delete"-->
    </vty>
  </line-vty>
</user-session>
```

### Command Syntax

```
history max <0-2147483647>
```

---

## Configure timeout seconds

Attribute used to set line timeout in seconds. The default is 0.

Attribute Name: seconds

Attribute Type: uint32

Attribute Range: 0-2147483

Attribute Name: minutes

Attribute Type: uint32

Attribute Range: 0-35791

### Netconf edit-config payload

```
<user-session xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-session-
management">
  <line-vty>
    <vty>
      <vty-id>0</vty-id>
      <config>
        <vty-id>0</vty-id>
        </config>
      <timeout>
        <config>
          <minutes>0</minutes> <!-- operation="delete"-->
          <seconds>0</seconds> <!-- operation="delete"-->
        </config>
      </timeout>
    </vty>
  </line-vty>
</user-session>
```

### Command Syntax

```
exec-timeout <0-35791> <0-2147483>
```

---

## Configure timeout minutes

Attribute used to set line timeout in minutes. The default is 10 minutes.

Attribute Name: minutes

Attribute Type: uint32

Attribute Range: 0-35791

### Netconf edit-config payload

```
<user-session xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-session-
management">
  <line-vty>
    <vty>
      <vty-id>0</vty-id>
      <config>
        <vty-id>0</vty-id>
        </config>
      <timeout>
        <config>
          <minutes>0</minutes>
        </config>
      </timeout>
    </vty>
  </line-vty>
</user-session>
```

```
</timeout>  
</vty>  
</line-vty>  
</user-session>
```

### Command Syntax

```
exec-timeout <0-35791>
```

---

## clear line WORD

Attribute Name: line-name

Attribute Type: string

Attribute Range: 1-64

### Netconf RPC payload

```
<clear-line xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-session-  
management">  
  <line-name>WORD</line-name>  
</clear-line>
```

### Command Syntax

```
clear line WORD
```

---

## mem-info imi monitor-start

Attribute Name: mem-info-imi

Attribute Type: boolean

### Netconf RPC payload

```
<mem-info-monitor-start xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-  
session-management">  
  <mem-info-imi>true</mem-info-imi/>  
</mem-info-monitor-start>
```

### Command Syntax

```
mem-info imi monitor-start
```

---

## mem-info imi monitor-stop

Attribute Name: mem-info-imi

Attribute Type: boolean

### Netconf RPC payload

```
<mem-info-monitor-stop xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-user-  
session-management">  
  <mem-info-imi>true</mem-info-imi/>  
</mem-info-monitor-stop>
```

---

## Command Syntax

```
mem-info imi monitor-stop
```

---

# IPI-IPV6-ROUTER-ADV

---

## Configure suppress-ra

Use this attribute to suppress IPv6 Router Advertisements

Attribute Name: suppress-ra

Attribute Type: uint8

### Netconf edit-config payload

```
<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </suppress-ra><!-- operation="delete"-->
    </interface>
  </interfaces>
</router-advertisement>
```

## Command Syntax

```
ipv6 nd suppress-ra
```

---

## Configure suppress-ra mtu

Use this attribute to disable sending MTU in Router Advertisement messages

Attribute Name: suppress-ra-mtu

Attribute Type: uint8

### Netconf edit-config payload

```
<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </suppress-ra-mtu><!-- operation="delete"-->
    </interface>
  </interfaces>
```

```
</router-advertisement>
```

## Command Syntax

```
ipv6 nd suppress-ra mtu
```

---

## Configure managed flag

Use this attribute to use DHCP for address config by host

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: managed-flag

Attribute Type: empty

## Netconf edit-config payload

```
<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </managed-flag><!-- operation="delete"-->
    </interface>
  </interfaces>
</router-advertisement>
```

## Command Syntax

```
ipv6 nd managed-config-flag
```

---

## Configure other config flag

Use this attribute to use DHCP for non-address config by host

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: other-config-flag

Attribute Type: empty

## Netconf edit-config payload

```
<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </other-config-flag><!-- operation="delete"-->
    </interface>
  </interfaces>
```

```
</router-advertisement>
```

## Command Syntax

```
ipv6 nd other-config-flag
```

---

## Configure current hop limit

Use this attribute to set advertised current hop limit

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: current-hop-limit

Attribute Type: uint8

Default Value: 64

Attribute Range: 0-255

## Netconf edit-config payload

```
<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <current-hop-limit>0</current-hop-limit> <!-- operation="delete"-->
    </interface>
  </interfaces>
</router-advertisement>
```

## Command Syntax

```
ipv6 nd current-hoplimit <0-255>
```

---

## Configure link mtu

Use this attribute to set advertised link-mtu option

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: link-mtu

Attribute Type: uint32

Default Value: 1500

Attribute Range: 1280-65535

## Netconf edit-config payload

```
<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
    <interface>
      <name>WORD</name>
```

```

    <config>
      <name>WORD</name>
    </config>
    <link-mtu>1280</link-mtu> <!-- operation="delete"-->
  </interface>
</interfaces>
</router-advertisement>

```

### Command Syntax

```
ipv6 nd link-mtu <1280-65535>
```

---

## Configure dad attempts

Use this attribute to set number of attempts for duplicate address detection

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: dad-attempts

Attribute Type: uint16

Default Value: 1

Attribute Range: 0-600

### Netconf edit-config payload

```

<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-
adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <dad-attempts>0</dad-attempts> <!-- operation="delete"-->
    </interface>
  </interfaces>
</router-advertisement>

```

### Command Syntax

```
ipv6 nd dad attempts <0-600>
```

---

## Configure off link

The IPV6 Router Advertisement prefix off-link flag

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: off-link

Attribute Type: empty

### Netconf edit-config payload

```

<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-
adv">

```

```

<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
</interface>
</interfaces>
<router-advertisement>
  <ipv6-prefixes>
<config>
  </off-link><!-- operation="delete"-->
</config>
</ipv6-prefixes>
</router-advertisement>

```

### Command Syntax

```
ipv6 nd prefix offlink
```

---

## Configure no auto configuration

The IPV6 Router Advertisement prefix no auto-configuration flag

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: no-auto-configuration

Attribute Type: empty

### Netconf edit-config payload

```

<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
  <interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  </interface>
  </interfaces>
  <router-advertisement>
    <ipv6-prefixes>
<config>
  </no-auto-configuration><!-- operation="delete"-->
</config>
</ipv6-prefixes>
</router-advertisement>

```

### Command Syntax

```
ipv6 nd prefix no-autoconf
```

---

## Configure valid lifetime

The IPV6 Router Advertisement prefix valid lifetime

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: valid-lifetime

Attribute Type: uint32

Default Value: 2592000

Attribute Range: 0-4294967295

### Netconf edit-config payload

```
<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <ipv6-prefixes>
      <config>
        <valid-lifetime>0</valid-lifetime> <!-- operation="delete"-->
      </config>
    </ipv6-prefixes>
  </interface>
</interfaces>
</router-advertisement>
```

### Command Syntax

```
ipv6 nd prefix valid-lifetime <0-4294967295>
```

---

## Configure preferred lifetime

The IPV6 Router Advertisement prefix preferred lifetime

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: preferred-lifetime

Attribute Type: uint32

Default Value: 604800

Attribute Range: 0-4294967295

### Netconf edit-config payload

```
<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <ipv6-prefixes>
      <config>
```

```

        <preferred-lifetime>0</preferred-lifetime> <!-- operation="delete"-->
</config>
</ipv6-prefixes>
</interface>
</interfaces>
</router-advertisement>

```

### Command Syntax

```
ipv6 nd prefix preferred-lifetime <0-4294967295>
```

---

## Configure ipv6 address

The IPV6 Router Advertisement prefix address

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: ipv6-address

Attribute Type: string

### Netconf edit-config payload

```

<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-
adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
  <ipv6-prefixes>
    <ipv6-prefix> <!-- operation="delete"-->
      <ipv6-address>X:X::X:X/M</ipv6-address>
      <config>
        <ipv6-address>X:X::X:X/M</ipv6-address>
      </config>
    </ipv6-prefix>
  </ipv6-prefixes>
</router-advertisement>

```

### Command Syntax

```
ipv6 nd prefix X:X::X:X/M
```

---

## Configure name

The IPV6 Router Advertisement prefix address preferred lifetime

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: preferred-lifetime

Attribute Type: uint32

Default Value: 604800

Attribute Range: 0-4294967295

Attribute Name: valid-lifetime

Attribute Type: uint32

Default Value: 2592000

Attribute Range: 0-4294967295

### Netconf edit-config payload

```
<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <ipv6-prefixes>
    <ipv6-prefix>
      <ipv6-address>X:X::X:X/M</ipv6-address>
      <config>
        <ipv6-address>X:X::X:X/M</ipv6-address>
        <valid-lifetime>0</valid-lifetime>
      </config>
      <preferred-lifetime>0</preferred-lifetime>
    </ipv6-prefix>
  </ipv6-prefixes>
</interface>
</interfaces>
</router-advertisement>
```

### Command Syntax

```
ipv6 nd prefix X:X::X:X/M <0-4294967295> <0-4294967295>
```

---

## Configure ipv6-prefix off-link

The IPV6 Router Advertisement prefix off-link flag

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: off-link

Attribute Type: empty

Attribute Name: valid-lifetime

Attribute Type: uint32

Default Value: 2592000

Attribute Range: 0-4294967295

Attribute Name: preferred-lifetime

Attribute Type: uint32

Default Value: 604800

Attribute Range: 0-4294967295

### Netconf edit-config payload

```
<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <ipv6-prefixes>
    <ipv6-prefix>
      <ipv6-address>X:X::X:X/M</ipv6-address>
      <config>
        <ipv6-address>X:X::X:X/M</ipv6-address>
        <valid-lifetime>0</valid-lifetime>
        <preferred-lifetime>0</preferred-lifetime>
      </config>
    </off-link>
    </ipv6-prefix>
  </ipv6-prefixes>
</interface>
</interfaces>
</router-advertisement>
```

### Command Syntax

```
ipv6 nd prefix X:X::X:X/M <0-4294967295> <0-4294967295> off-link
```

---

## Configure ipv6-prefix no-auto-configuration

The IPV6 Router Advertisement prefix no auto-configuration flag

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: no-auto-configuration

Attribute Type: empty

Attribute Name: valid-lifetime

Attribute Type: uint32

Default Value: 2592000

Attribute Range: 0-4294967295

Attribute Name: preferred-lifetime

Attribute Type: uint32

Default Value: 604800

Attribute Range: 0-4294967295

**Netconf edit-config payload**

```

<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <ipv6-prefixes>
      <ipv6-prefix>
        <ipv6-address>X:X::X:X/M</ipv6-address>
        <config>
          <ipv6-address>X:X::X:X/M</ipv6-address>
          <valid-lifetime>0</valid-lifetime>
          <preferred-lifetime>0</preferred-lifetime>
        </config>
      </no-auto-configuration>
    </ipv6-prefix>
  </ipv6-prefixes>
</interface>
</interfaces>
</router-advertisement>

```

**Command Syntax**

```
ipv6 nd prefix X:X::X:X/M <0-4294967295> <0-4294967295> no-autoconfig
```

**Configure ipv6-prefix no-auto-configuration**

The IPV6 Router Advertisement prefix no auto-configuration flag

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: no-auto-configuration

Attribute Type: empty

Attribute Name: valid-lifetime

Attribute Type: uint32

Default Value: 2592000

Attribute Range: 0-4294967295

Attribute Name: preferred-lifetime

Attribute Type: uint32

Default Value: 604800

Attribute Range: 0-4294967295

Attribute Name: off-link

Attribute Type: empty

## Netconf edit-config payload

```

<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <ipv6-prefixes>
    <ipv6-prefix>
      <ipv6-address>X:X::X:X/M</ipv6-address>
      <config>
        <ipv6-address>X:X::X:X/M</ipv6-address>
        <valid-lifetime>0</valid-lifetime>
        <preferred-lifetime>0</preferred-lifetime>
        </off-link>
      </config>
      </no-auto-configuration>
    </ipv6-prefix>
  </ipv6-prefixes>
</interface>
</interfaces>
</router-advertisement>

```

## Command Syntax

```
ipv6 nd prefix X:X::X:X/M <0-4294967295> <0-4294967295> off-link no-autoconfig
```

---

## Configure reachable time

Use this attribute to set advertised reachability time

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: reachable-time

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-3600000

## Netconf edit-config payload

```

<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    <timers>
  </config>

```

```

        <reachable-time>0</reachable-time> <!-- operation="delete"-->
</config>
</timers>
</interface>
</interfaces>
</router-advertisement>

```

## Command Syntax

```
ipv6 nd reachable-time <0-3600000>
```

---

## Configure retransmission time

Use this attribute to set advertised retransmission timer

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: retransmission-time

Attribute Type: uint32

Default Value: 0

Attribute Range: 0-4294967295

## Netconf edit-config payload

```

<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-
adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
  <timers>
    <config>
      <retransmission-time>0</retransmission-time> <!-- operation="delete"-->
    </config>
  </timers>
</router-advertisement>

```

## Command Syntax

```
ipv6 nd retransmission-time <0-4294967295>
```

---

## Configure router lifetime

Use this attribute to set IPv6 router advertisement lifetime

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: router-lifetime

Attribute Type: uint16

Default Value: 1800

Attribute Range: 0-9000

### Netconf edit-config payload

```
<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
  <timers>
    <config>
      <router-lifetime>0</router-lifetime> <!-- operation="delete"-->
    </config>
  </timers>
</router-advertisement>
```

### Command Syntax

```
ipv6 nd ra-lifetime <0-9000>
```

---

## Configure max ra interval

Use this attribute to set maximum IPv6 router advertisement interval (min-ra-interval must be no greater than 0.75\*max-ra-interval)

This command is supported when following feature are enabled IPv6 Router Advertisement

Attribute Name: max-ra-interval

Attribute Type: uint32

Attribute Range: 4-1800

Attribute Name: min-ra-interval

Attribute Type: uint32

Attribute Range: 3-1350

### Netconf edit-config payload

```
<router-advertisement xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipv6-router-adv">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
    </interface>
  </interfaces>
  <ra-interval>
```

```

<config>
  <min-ra-interval>3</min-ra-interval>
  <max-ra-interval>4</max-ra-interval>
</config>
</ra-interval>
</timers>
</interface>
</interfaces>
</router-advertisement>

```

### Command Syntax

```
ipv6 nd ra-interval <4-1800> (<3-1350>|)
```

---

## IPI-ERPSV2

---

### Configure ring name

G.8032 ring name. This attribute uniquely identifies a ring on the network device.

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: ring-name

Attribute Type: string

Attribute Range: 1-255

### Netconf edit-config payload

```

<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <rings>
    <ring> <!-- operation="delete"-->
      <ring-name>RINGNAME</ring-name>
    <config>
      <ring-name>RINGNAME</ring-name>
    </config>
  </ring>
</rings>
</erpsv2>

```

### Command Syntax

```
g8032 ring RINGNAME
```

---

### Configure east interface

East port associated to the protection ring

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: east-interface

Attribute Type: string

Attribute Range: 1-33

## Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
<rings>
<ring>
  <ring-name>RINGNAME</ring-name>
  <config>
    <ring-name>RINGNAME</ring-name>
  </config>
  <east-interface>IFNAME</east-interface> <!-- operation="delete"-->
</ring>
</rings>
</erpsv2>
```

## Command Syntax

```
east-interface IFNAME
```

---

## Configure west interface

West port associated to the protection ring

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: west-interface

Attribute Type: string

Attribute Range: 1-33

## Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
<rings>
<ring>
  <ring-name>RINGNAME</ring-name>
  <config>
    <ring-name>RINGNAME</ring-name>
  </config>
  <west-interface>IFNAME</west-interface> <!-- operation="delete"-->
</ring>
</rings>
</erpsv2>
```

## Command Syntax

```
west-interface IFNAME
```

---

## Configure description

Textual description of the ring.

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: description

Attribute Type: string

Attribute Range: 1-255

### Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <rings>
    <ring>
      <ring-name>RINGNAME</ring-name>
      <config>
        <ring-name>RINGNAME</ring-name>
      </config>
      <description>1</description> <!-- operation="delete"-->
    </ring>
  </rings>
</erpsv2>
```

### Command Syntax

```
description LINE
```

---

## Configure profile name

G.8032 ring profile name

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: profile-name

Attribute Type: string

Attribute Range: 1-32

### Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <profiles>
    <profile> <!-- operation="delete"-->
      <profile-name>PROFILENAME</profile-name>
      <config>
        <profile-name>PROFILENAME</profile-name>
      </config>
    </profile>
  </profiles>
</erpsv2>
```

### Command Syntax

```
g8032 profile PROFILENAME
```

---

## Configure wait to restore timer

In revertive mode the 'wait to restore' (WTR) timer is used to prevent frequent operation of the protection switching due to intermittent signal failure defects. When recovering from a Signal fail, the delay timer must be long enough to allow the recovering network to become stable. WTR timer is activated on RPL owner node. When WTR timer is expired RPL owner node initiates the reversion process by transmitting an R-APS (NR, RB) message.

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: wait-to-restore-timer

Attribute Type: uint8

Default Value: 5

Attribute Range: 1-12

### Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <profiles>
    <profile>
      <profile-name>PROFILENAME</profile-name>
      <config>
        <profile-name>PROFILENAME</profile-name>
      </config>
      <wait-to-restore-timer>1</wait-to-restore-timer> <!-- operation="delete"-->
    </profile>
  </profiles>
</erpsv2>
```

### Command Syntax

```
timer wait-to-restore <1-12>
```

---

## Configure hold off timer

The hold-off timer is used to coordinate the timing of protection switches. When a new defect or more severe defect occurs (new SF), this event is not to be reported immediately to protection switching if the provisioned hold-off timer value is non-zero. Instead, the hold-off timer is started. When the hold-off timer expires, the trail that started the timer is checked as to whether a defect still exists. If one does exist, that defect is reported to protection switching. Hold off timer values SHOULD be specified in multiple of 100.

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: hold-off-timer

Attribute Type: uint16

Default Value: 0

Attribute Range: 0-10000

### Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <profiles>
    <profile>
      <profile-name>PROFILENAME</profile-name>
      <config>
        <profile-name>PROFILENAME</profile-name>
      </config>
      <hold-off-timer>0</hold-off-timer> <!-- operation="delete"-->
    </profile>
  </profiles>
</erpsv2>
```

---

## Command Syntax

```
timer hold-off <0-10000>
```

---

## Configure guard time

The guard time is used to prevent Ethernet ring nodes from acting upon outdated R-APS messages and prevents the possibility of forming a closed loop. This timer period SHOULD be greater than the maximum expected forwarding delay in which an R-APS message traverses the entire ring. The period of the guard timer MAY be configured by the operator in 10 ms steps between 10 ms and 2 seconds.

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: guard-time

Attribute Type: uint16

Default Value: 500

Attribute Range: 10-2000

## Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <profiles>
    <profile>
      <profile-name>PROFILENAME</profile-name>
      <config>
        <profile-name>PROFILENAME</profile-name>
      </config>
      <guard-time>10</guard-time> <!-- operation="delete"-->
    </profile>
  </profiles>
</erpsv2>
```

## Command Syntax

```
timer guard-time <10-2000>
```

---

## Configure protection mode

This leaf defines G.8032 ring protection mode. A ring may operate in revertive or non-revertive mode. In revertive operation, after the condition(s) causing a switch has cleared, the traffic channel is restored to the working transport entity, i.e., blocked on the RPL. In non-revertive operation, the traffic channel continues to use the RPL, if it has not failed, after a switch condition has cleared.

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: protection-mode

Attribute Type: enum (revertive|non-revertive)

Default Value: revertive

## Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <profiles>
    <profile>
```

```

    <profile-name>PROFILENAME</profile-name>
  <config>
    <profile-name>PROFILENAME</profile-name>
  </config>
  <protection-mode>revertive</protection-mode> <!-- operation="delete"-->
</profile>
</profiles>
</erpsv2>

```

### Command Syntax

```
switching mode (revertive|non-revertive)
```

---

## Configure name

ERPS instance identifier

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: name

Attribute Type: string

Attribute Range: 1-255

### Netconf edit-config payload

```

<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
    <erp-instance> <!-- operation="delete"-->
      <name>INSTANCENAME</name>
      <config>
        <name>INSTANCENAME</name>
      </config>
    </erp-instance>
  </erp-instances>
</erpsv2>

```

### Command Syntax

```
g8032 erp-instance INSTANCENAME
```

---

## Configure erp-instance ring-name

This parameter specifies the ring instance to associated with the ERPS instance

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: ring-name

Attribute Type: string

Attribute Range: 1-255

### Netconf edit-config payload

```

<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>

```

```

<erp-instance>
  <name>INSTANCENAME</name>
  <config>
    <name>INSTANCENAME</name>
  </config>
  <ring-name>RINGNAME</ring-name> <!-- operation="delete"-->
</erp-instance>
</erp-instances>
</erpsv2>

```

### Command Syntax

```
ring RINGNAME
```

---

## Configure mapped profile name

G.8032 ring profile name. If this profile exists in the profile configuration list, profile parameters will be imported from it, default values will be used otherwise.

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: mapped-profile-name

Attribute Type: string

Attribute Range: 1-32

### Netconf edit-config payload

```

<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
    <erp-instance>
      <name>INSTANCENAME</name>
      <config>
        <name>INSTANCENAME</name>
      </config>
      <mapped-profile-name>PROFILENAME</mapped-profile-name> <!-- operation="delete"-->
    </erp-instance>
  </erp-instances>
</erpsv2>

```

### Command Syntax

```
g8032-profile PROFILENAME
```

---

## Configure ring type

Defines type of a ethernet ring. A ring can be configured as major ring where ring nodes are connected in closed loop or as a sub-ring when a ring may not have a complete closed loop

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: ring-type

Attribute Type: enum (major-ring|sub-ring|sub-ring-vc)

Default Value: major-ring

## Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
  <erp-instance>
    <name>INSTANCENAME</name>
    <config>
      <name>INSTANCENAME</name>
    </config>
    <ring-type>major-ring</ring-type> <!-- operation="delete"-->
  </erp-instance>
</erp-instances>
</erpsv2>
```

## Command Syntax

```
ring-type (major-ring|sub-ring|sub-ring-vc)
```

---

## Configure enable tcn propagation

Allows topology change notification (TCN) propagation to the ERPS ring if it is enabled

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: enable-tcn-propagation

Attribute Type: empty

## Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
  <erp-instance>
    <name>INSTANCENAME</name>
    <config>
      <name>INSTANCENAME</name>
    </config>
    </enable-tcn-propagation><!-- operation="delete"-->
  </erp-instance>
</erp-instances>
</erpsv2>
```

## Command Syntax

```
enable-tcn-propagation
```

---

## Configure tcn to instances

List of Instance that are to be notified when TCN occurs for this instance if topology change notification (TCN) propagation is enabled

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: tcn-to-instances

Attribute Type: string

Attribute Range: 1-255

## Netconf edit-config payload

```

<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
    <erp-instance>
      <name>INSTANCENAME</name>
      <config>
        <name>INSTANCENAME</name>
      </config>
      <tcn-to-instances>INSTANCENAME</tcn-to-instances> <!-- operation="delete"-->
    </erp-instance>
  </erp-instances>
</erpsv2>

```

## Command Syntax

```
tcn-to-instance INSTANCENAME
```

---

## Configure non virtual channel

Creates a non-virtual channel

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: non-virtual-channel

Attribute Type: empty

## Netconf edit-config payload

```

<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
    <erp-instance>
      <name>INSTANCENAME</name>
      <config>
        <name>INSTANCENAME</name>
      </config>
      </non-virtual-channel><!-- operation="delete"-->
    </erp-instance>
  </erp-instances>
</erpsv2>

```

## Command Syntax

```
non-virtual-channel
```

---

## Configure ring id

G.8032 ring instance identifier (Ring ID).

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: ring-id

Attribute Type: uint8

Attribute Range: 1-239

---

**Netconf edit-config payload**

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
    <erp-instance>
      <name>INSTANCENAME</name>
      <config>
        <name>INSTANCENAME</name>
      </config>
      <ring-id>1</ring-id> <!-- operation="delete"-->
    </erp-instance>
  </erp-instances>
</erpsv2>
```

**Command Syntax**

```
ring-id <1-239>
```

---

**Configure erp-instance description**

Textual description of the erps-instance.

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: description

Attribute Type: string

Attribute Range: 1-255

**Netconf edit-config payload**

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
    <erp-instance>
      <name>INSTANCENAME</name>
      <config>
        <name>INSTANCENAME</name>
      </config>
      <description>1</description> <!-- operation="delete"-->
    </erp-instance>
  </erp-instances>
</erpsv2>
```

**Command Syntax**

```
description LINE
```

---

**Configure associate ring name**

G.8032 ring name to be associate with.

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: associate-ring-name

Attribute Type: string

Attribute Range: 1-255

### Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
    <erp-instance>
      <name>INSTANCENAME</name>
      <config>
        <name>INSTANCENAME</name>
      </config>
    <associate-rings>
    <associate-ring> <!-- operation="delete"-->
      <associate-ring-name>RINGNAME</associate-ring-name>
      <config>
        <associate-ring-name>RINGNAME</associate-ring-name>
      </config>
    </associate-ring>
  </associate-rings>
</erp-instance>
</erp-instances>
</erpsv2>
```

### Command Syntax

```
associate-ring RINGNAME
```

---

## Configure owner port id

This identifies the ring port for which role is configured

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: owner-port-id

Attribute Type: enum (east-interface|west-interface)

### Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
    <erp-instance>
      <name>INSTANCENAME</name>
      <config>
        <name>INSTANCENAME</name>
      </config>
    <instance-role>
    <config>
      <owner-port-id>east-interface</owner-port-id> <!-- operation="delete"-->
    </config>
  </instance-role>
</erp-instance>
</erp-instances>
</erpsv2>
```

---

## Command Syntax

```
rpl role owner (east-interface|west-interface)
```

---

## Configure neighbor port id

This identifies the ring port for which role is configured

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: neighbor-port-id

Attribute Type: enum (east-interface|west-interface)

## Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
    <erp-instance>
      <name>INSTANCENAME</name>
      <config>
        <name>INSTANCENAME</name>
      </config>
    <instance-role>
      <config>
        <neighbor-port-id>east-interface</neighbor-port-id> <!-- operation="delete"-->
      </config>
    </instance-role>
  </erp-instance>
</erp-instances>
</erpsv2>
```

## Command Syntax

```
rpl role neighbor (east-interface|west-interface)
```

---

## Configure next neighbor port id

This identifies the ring port for which role is configured

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: next-neighbor-port-id

Attribute Type: enum (east-interface|west-interface)

## Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
    <erp-instance>
      <name>INSTANCENAME</name>
      <config>
        <name>INSTANCENAME</name>
      </config>
    <instance-role>
```

```

    <config>
      <next-neighbor-port-id>east-interface</next-neighbor-port-id> <!--
operation="delete"-->
    </config>
  </instance-role>
</erp-instance>
</erp-instances>
</erpsv2>

```

### Command Syntax

```
rpl role next-neighbor (east-interface|west-interface)
```

---

## Configure non owner

This identifies the ring port for which role is configured

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: non-owner

Attribute Type: empty

### Netconf edit-config payload

```

<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
    <erp-instance>
      <name>INSTANCENAME</name>
      <config>
        <name>INSTANCENAME</name>
      </config>
    <instance-role>
      <config>
        </non-owner><!-- operation="delete"-->
      </config>
    </instance-role>
  </erp-instance>
</erp-instances>
</erpsv2>

```

### Command Syntax

```
rpl role non-owner
```

---

## Configure level

Maintenance Endpoint Level (MEL) at which R-APS PDU is transmitted. All nodes in the ring must be configured with same APS level value.

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: level

Attribute Type: uint8

Attribute Range: 0-7

**Netconf edit-config payload**

```

<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
    <erp-instance>
      <name>INSTANCENAME</name>
      <config>
        <name>INSTANCENAME</name>
      </config>
    <aps-channel>
      <config>
        <level>0</level> <!-- operation="delete"-->
      </config>
    </aps-channel>
  </erp-instance>
</erp-instances>
</erpsv2>

```

**Command Syntax**

```
aps-channel level <0-7>
```

**Configure vlan id**

ERPS instance identifier

Attribute Name: name

Attribute Type: string

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 2-4094

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 2-4094

**Netconf edit-config payload**

```

<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
    <erp-instance> <!-- operation="delete"-->
      <name>INSTANCENAME</name>
      <config>
        <name>INSTANCENAME</name>
      </config>
    <aps-channel-vlans>
      <aps-channel-vlan>
        <vlan-id>2</vlan-id>
        <config>
          <inner-vlan-id>2</inner-vlan-id>
        </config>
      </aps-channel-vlan>

```

```

</aps-channel-vlans>
</erp-instance>
</erp-instances>
</erpsv2>

```

## Command Syntax

```
aps-channel vlan <2-4094> (inner-vlan <2-4094>|)
```

---

## Configure data vlan

List of VLAN-IDs, protected by ring instance. For example '2, 3-7, 9, 10-100' VLAN-IDs MUST not overlap with VLAN-IDs of any other instance of the same ring.

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: data-vlan

Attribute Type: string

Attribute Range: 2-4094

## Netconf edit-config payload

```

<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
    <erp-instance>
      <name>INSTANCENAME</name>
      <config>
        <name>INSTANCENAME</name>
      </config>
    </erp-instance>
  </erp-instances>
  <data>
    <config>
      <data-vlan>VLAN_RANGE</data-vlan> <!-- operation="delete"-->
    </config>
  </data>
</erpsv2>

```

## Command Syntax

```
data vlan VLAN_RANGE
```

---

## Configure attached instance

This parameter specifies the ERPS instance on major ring which allows the RAPS messages of Sub-ring, so RAPS message will be sent to other nodes in the sub-ring

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: attached-instance

Attribute Type: string

Attribute Range: 1-31

Attribute Name: channel-id

Attribute Type: uint16

Attribute Range: 2-4094

### Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <erp-instances>
    <erp-instance>
      <name>INSTANCENAME</name>
      <config>
        <name>INSTANCENAME</name>
      </config>
    <virtual-channel>
      <config>
        <channel-id>2</channel-id>
        <attached-instance>INSTANCENAME</attached-instance>
      </config>
    </virtual-channel>
  </erp-instance>
</erp-instances>
</erpsv2>
```

### Command Syntax

```
virtual-channel (<2-4094>|) attached-to-instance INSTANCENAME
```

---

## Configure options

Supported debug options for G.8032

This command is supported when following feature are enabled ERPS V2 feature

Attribute Name: options

Attribute Type: bits (all|tx|rx|fsm|timers|events|external|hal)

### Netconf edit-config payload

```
<erpsv2 xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <debug>
    <config>
      <options>all</options> <!-- operation="delete"-->
    </config>
  </debug>
</erpsv2>
```

### Command Syntax

```
debug g8032 (all|tx|rx|fsm|timers|events|external|hal)
```

---

## g8032 erp-instance (INSTANCENAME|all) (force-switch|manual-switch) (east-interface|west-interface)

Attribute Name: instance-name

Attribute Type: string

Attribute Range: 1-255

Attribute Name: operation

Attribute Type: enum (force-switch|manual-switch)

Attribute Name: port-id

Attribute Type: enum (east-interface|west-interface)

### Netconf RPC payload

```
<erpsv2-switch-erp-instance xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <instance-name>INSTANCENAME</instance-name>
  <operation>force-switch</operation>
  <port-id>east-interface</port-id>
</erpsv2-switch-erp-instance>
```

### Command Syntax

```
g8032 erp-instance (INSTANCENAME|all) (force-switch|manual-switch) (east-
interface|west-interface)
```

---

## clear g8032 erp-instance (INSTANCENAME|all)

Attribute Name: instance-name

Attribute Type: string

Attribute Range: 1-255

### Netconf RPC payload

```
<erpsv2-clear-ring-erp-instance xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <instance-name>INSTANCENAME</instance-name>
</erpsv2-clear-ring-erp-instance>
```

### Command Syntax

```
clear g8032 erp-instance (INSTANCENAME|all)
```

---

## clear g8032 aps-statistics INSTANCENAME

Attribute Name: instance-name

Attribute Type: string

Attribute Range: 1-255

### Netconf RPC payload

```
<erpsv2-clear-aps-statistics xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <instance-name>INSTANCENAME</instance-name>
</erpsv2-clear-aps-statistics>
```

---

## Command Syntax

```
clear g8032 aps-statistics INSTANCENAME
```

---

## debug g8032 (all|tx|rx|fsm|timers|events|external|hal)

Attribute Name: terminal-debug-options

Attribute Type: bits (all|tx|rx|fsm|timers|events|external|hal)

### Netconf RPC payload

```
<erpsv2-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <terminal-debug-options>all</terminal-debug-options>
</erpsv2-terminal-debug-on>
```

## Command Syntax

```
debug g8032 (all|tx|rx|fsm|timers|events|external|hal)
```

---

## no debug g8032 (all|tx|rx|fsm|timers|events|external|hal)

Attribute Name: terminal-debug-options

Attribute Type: bits (all|tx|rx|fsm|timers|events|external|hal)

### Netconf RPC payload

```
<erpsv2-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-erpsv2">
  <terminal-debug-options>all</terminal-debug-options>
</erpsv2-terminal-debug-off>
```

## Command Syntax

```
no debug g8032 (all|tx|rx|fsm|timers|events|external|hal)
```

---

# IPI-CFM

---

## Configure cache enable

This attribute specifies the cache enable

Attribute Name: cache-enable

Attribute Type: uint8

### Netconf edit-config payload

```
<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <global>
    <linktrace>
      <cache>
        <config>
          </cache-enable>
```

```
</config>
</cache>
</linktrace>
</global>
</cfm>
```

## Command Syntax

```
ethernet cfm traceroute cache
```

---

## Configure cache size

This attribute specifies the cache size

Attribute Name: cache-size

Attribute Type: uint16

Default Value: 100

Attribute Range: 1-4095

Attribute Name: cache-enable

Attribute Type: empty

## Netconf edit-config payload

```
<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <global>
    <linktrace>
      <cache>
        <config>
          </cache-enable><!-- operation="delete"-->
          <cache-size>1</cache-size> <!-- operation="delete"-->
        </config>
      </cache>
    </linktrace>
  </global>
</cfm>
```

## Command Syntax

```
ethernet cfm traceroute cache size <1-4095>
```

---

## Configure options

This attribute enables debugging for CFM

This command is supported when following feature are enabled CFM feature

Attribute Name: options

Attribute Type: bits (events|rx|tx|loopback|traceroute|all)

## Netconf edit-config payload

```
<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <debug>
```

```

<config>
  <options>events</options> <!-- operation="delete"-->
</config>
</debug>
</cfm>

```

### Command Syntax

```
debug ethernet cfm (events|rx|tx|loopback|traceroute|all)
```

---

## Configure type

Type discriminator for the value union described in the 'md-name' leaf

Attribute Name: type

Attribute Type: enum (no-name|character-string)

Attribute Name: level

Attribute Type: uint8

Attribute Range: 0-7

Attribute Name: mip-creation

Attribute Type: enum (none|default|explicit)

### Netconf edit-config payload

```

<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <maintenance-domains>
    <maintenance-domain>
      <md-name>DOMAIN_NAME</md-name>
      <config>
        <md-name>DOMAIN_NAME</md-name>
        <level>0</level>
        <mip-creation>none</mip-creation>
      </config>
      <type>no-name</type>
    </maintenance-domain>
  </maintenance-domains>
</cfm>

```

### Command Syntax

```
ethernet cfm domain-type (no-name|character-string) domain-name DOMAIN_NAME level
<0-7> (mip-creation (none|default|explicit)|)
```

---

## Configure ma name

The value union for the Maintenance Association Name.

Attribute Name: ma-name

Attribute Type: string

Attribute Range: 1-43

Attribute Name: type

Attribute Type: enum (string|integer|itu-t)

### Netconf edit-config payload

```
<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
<maintenance-domains>
<maintenance-domain>
  <md-name>DOMAIN_NAME</md-name>
  <config>
    <md-name>DOMAIN_NAME</md-name>
  </config>
</maintenance-domain>
</maintenance-domains>
<maintenance-associations>
<maintenance-association> <!-- operation="delete"-->
  <ma-name>MA_NAME</ma-name>
  <config>
    <ma-name>MA_NAME</ma-name>
    <type>string</type>
  </config>
</maintenance-association>
</maintenance-associations>
</cfm>
```

### Command Syntax

```
service ma-type (string|integer|itu-t) ma-name MA_NAME
```

---

## Configure bridge id

This parameter indicates which bridge this maintenance association will be augmented to.

This command is supported when following feature are enabled CFM feature

Attribute Name: bridge-id

Attribute Type: string

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

### Netconf edit-config payload

```
<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
<maintenance-domains>
<maintenance-domain>
  <md-name>DOMAIN_NAME</md-name>
  <config>
    <md-name>DOMAIN_NAME</md-name>
  </config>
</maintenance-domain>
</maintenance-domains>
<maintenance-associations>
<maintenance-association>
```

```

    <ma-name>MA_NAME</ma-name>
  <config>
    <ma-name>MA_NAME</ma-name>
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
  </config>
    <bridge-id>1</bridge-id> <!-- operation="delete"-->
</maintenance-association>
</maintenance-associations>
</maintenance-domain>
</maintenance-domains>
</cfm>

```

### Command Syntax

```
vlan <1-4094> (bridge <1-32>|)
```

---

## Configure md name

This parameter indicates which bridge this maintenance association will be augmented to.

This command is supported when following feature are enabled CFM feature

Attribute Name: bridge-id

Attribute Type: string

Attribute Name: link-level-ma

Attribute Type: empty

### Netconf edit-config payload

```

<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <maintenance-domains>
  <maintenance-domain>
    <md-name>DOMAIN_NAME</md-name>
    <config>
      <md-name>DOMAIN_NAME</md-name>
    </config>
  <maintenance-associations>
  <maintenance-association>
    <ma-name>MA_NAME</ma-name>
    <config>
      <ma-name>MA_NAME</ma-name>
      </link-level-ma><!-- operation="delete"-->
    </config>
      <bridge-id>1</bridge-id> <!-- operation="delete"-->
  </maintenance-association>
</maintenance-associations>
</maintenance-domain>
</maintenance-domains>
</cfm>

```

### Command Syntax

```
link-level (bridge <1-32>|)
```

---

## Configure mip creation

This parameter indicates whether the management entity can create MIPs for this MA

This command is supported when following feature are enabled CFM feature

Attribute Name: mip-creation

Attribute Type: enum (none|default|explicit|defer)

### Netconf edit-config payload

```
<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <maintenance-domains>
    <maintenance-domain>
      <md-name>DOMAIN_NAME</md-name>
      <config>
        <md-name>DOMAIN_NAME</md-name>
      </config>
    </maintenance-domain>
  </maintenance-domains>
  <maintenance-associations>
    <maintenance-association>
      <ma-name>MA_NAME</ma-name>
      <config>
        <ma-name>MA_NAME</ma-name>
        <mip-creation>none</mip-creation> <!-- operation="delete"-->
      </config>
    </maintenance-association>
  </maintenance-associations>
</maintenance-domain>
</maintenance-domains>
</cfm>
```

### Command Syntax

```
(mip-creation (none|default|explicit|defer) |)
```

---

## Configure inner vlan id

The inner VLAN ID monitored by this MA

This command is supported when following feature are enabled CFM feature

Attribute Name: inner-vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

Attribute Name: vlan-id

Attribute Type: uint16

Attribute Range: 1-4094

### Netconf edit-config payload

```
<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <maintenance-domains>
    <maintenance-domain>
```

```

    <md-name>DOMAIN_NAME</md-name>
  <config>
    <md-name>DOMAIN_NAME</md-name>
  </config>
<maintenance-associations>
<maintenance-association>
  <ma-name>MA_NAME</ma-name>
  <config>
    <ma-name>MA_NAME</ma-name>
    <vlan-id>1</vlan-id> <!-- operation="delete"-->
  </config>
    <inner-vlan-id>1</inner-vlan-id> <!-- operation="delete"-->
</maintenance-association>
</maintenance-associations>
</maintenance-domain>
</maintenance-domains>
</cfm>

```

## Command Syntax

```
vlan <1-4094> (inner-vlan <1-4094>|)
```

---

## Configure link level ma

Use this attribute to set the Service as Link Level MA

This command is supported when following feature are enabled CFM feature

Attribute Name: link-level-ma

Attribute Type: empty

## Netconf edit-config payload

```

<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <maintenance-domains>
  <maintenance-domain>
    <md-name>DOMAIN_NAME</md-name>
    <config>
      <md-name>DOMAIN_NAME</md-name>
    </config>
  <maintenance-associations>
  <maintenance-association>
    <ma-name>MA_NAME</ma-name>
    <config>
      <ma-name>MA_NAME</ma-name>
    </config>
    </link-level-ma><!-- operation="delete"-->
  </maintenance-association>
</maintenance-associations>
</maintenance-domain>
</maintenance-domains>
</cfm>

```

## Command Syntax

link-level

---

## Configure mip interface name

A list of static MIPs configured on the specified interfaces

This command is supported when following feature are enabled CFM feature

Attribute Name: mip-interface-name

Attribute Type: string

### Netconf edit-config payload

```

<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <maintenance-domains>
    <maintenance-domain>
      <md-name>DOMAIN_NAME</md-name>
      <config>
        <md-name>DOMAIN_NAME</md-name>
      </config>
    </maintenance-domain>
  </maintenance-domains>
  <maintenance-associations>
    <maintenance-association>
      <ma-name>MA_NAME</ma-name>
      <config>
        <ma-name>MA_NAME</ma-name>
        <mip-interface-name>IFNAME</mip-interface-name> <!-- operation="delete"-->
      </config>
    </maintenance-association>
  </maintenance-associations>
</cfm>

```

## Command Syntax

ethernet cfm mip interface IFNAME

---

## Configure evpn id

Use this attribute to set the Service as EVPN MA

This command is supported when following feature are enabled CFM feature

Attribute Name: evpn-id

Attribute Type: uint32

Attribute Range: 1-16777215

### Netconf edit-config payload

```

<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <maintenance-domains>
    <maintenance-domain>

```

```

    <md-name>DOMAIN_NAME</md-name>
  <config>
    <md-name>DOMAIN_NAME</md-name>
  </config>
<maintenance-associations>
<maintenance-association>
  <ma-name>MA_NAME</ma-name>
  <config>
    <ma-name>MA_NAME</ma-name>
  </config>
  <evpn-id>1</evpn-id> <!-- operation="delete"-->
</maintenance-association>
</maintenance-associations>
</maintenance-domain>
</maintenance-domains>
</cfm>

```

## Command Syntax

```
evpn <1-16777215>
```

---

## Configure ccm interval

The interval between CCM transmissions to be used by all MEPs in the MA

This command is supported when following feature are enabled CFM feature

Attribute Name: ccm-interval

Attribute Type: enum (10ms|100ms|1s|10s|1min|10min)

## Netconf edit-config payload

```

<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <maintenance-domains>
  <maintenance-domain>
    <md-name>DOMAIN_NAME</md-name>
    <config>
      <md-name>DOMAIN_NAME</md-name>
    </config>
  <maintenance-associations>
  <maintenance-association>
    <ma-name>MA_NAME</ma-name>
    <config>
      <ma-name>MA_NAME</ma-name>
    </config>
    <ccm-interval>10ms</ccm-interval> <!-- operation="delete"-->
  </maintenance-association>
</maintenance-associations>
</maintenance-domain>
</maintenance-domains>
</cfm>

```

## Command Syntax

```
cc interval (10ms|100ms|1s|10s|1min|10min)
```

---

## Configure static rmep identifiers

A list of static remote MEPs in a specified MA.

This command is supported when following feature are enabled CFM feature

Attribute Name: static-rmep-identifiers

Attribute Type: uint16

Attribute Range: 1-8191

## Netconf edit-config payload

```
<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
<maintenance-domains>
<maintenance-domain>
  <md-name>DOMAIN_NAME</md-name>
  <config>
    <md-name>DOMAIN_NAME</md-name>
  </config>
</maintenance-domain>
<maintenance-associations>
<maintenance-association>
  <ma-name>MA_NAME</ma-name>
  <config>
    <ma-name>MA_NAME</ma-name>
  </config>
  <static-rmep-identifiers>1</static-rmep-identifiers> <!-- operation="delete"-
->
</maintenance-association>
</maintenance-associations>
</maintenance-domain>
</maintenance-domains>
</cfm>
```

## Command Syntax

```
mep crosscheck mpid <1-8191>
```

---

## Configure mep id

Integer that is unique among all the MEPs in the same MA. Other definition is: a small integer, unique over a given Maintenance Association, identifying a specific Maintenance association End Point

Attribute Name: mep-id

Attribute Type: uint16

Attribute Range: 1-8191

Attribute Name: direction

Attribute Type: enum (down|up)

Attribute Name: administrative-state

Attribute Type: enum (false|true)

Attribute Name: interface-name

Attribute Type: string

### Netconf edit-config payload

```
<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
<maintenance-domains>
<maintenance-domain>
  <md-name>DOMAIN_NAME</md-name>
  <config>
    <md-name>DOMAIN_NAME</md-name>
  </config>
</maintenance-domain>
</maintenance-domains>
<maintenance-associations>
<maintenance-association>
  <ma-name>MA_NAME</ma-name>
  <config>
    <ma-name>MA_NAME</ma-name>
  </config>
</maintenance-association>
</maintenance-associations>
<maintenance-end-points>
<maintenance-end-point> <!-- operation="delete"-->
  <mep-id>1</mep-id>
  <config>
    <mep-id>1</mep-id>
    <direction>down</direction>
    <administrative-state>>false</administrative-state>
    <interface-name>IFNAME</interface-name>
  </config>
</maintenance-end-point>
</maintenance-end-points>
</maintenance-association>
</maintenance-associations>
</maintenance-domain>
</maintenance-domains>
</cfm>
```

### Command Syntax

```
ethernet cfm mep (down|up) mpid <1-8191> active (false|true) IFNAME
```

### Configure direction

Integer that is unique among all the MEPs in the same MA. Other definition is: a small integer, unique over a given Maintenance Association, identifying a specific Maintenance association End Point

Attribute Name: mep-id

Attribute Type: uint16

Attribute Range: 1-8191

Attribute Name: direction

Attribute Type: enum (down|up)

Attribute Name: administrative-state

Attribute Type: enum (false|true)

Attribute Name: remote-evpn-id

Attribute Type: uint32

Attribute Range: 1-16777215

### Netconf edit-config payload

```
<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
<maintenance-domains>
<maintenance-domain>
  <md-name>DOMAIN_NAME</md-name>
  <config>
    <md-name>DOMAIN_NAME</md-name>
  </config>
</maintenance-domain>
</maintenance-domains>
<maintenance-associations>
<maintenance-association>
  <ma-name>MA_NAME</ma-name>
  <config>
    <ma-name>MA_NAME</ma-name>
  </config>
</maintenance-association>
</maintenance-associations>
<maintenance-end-points>
<maintenance-end-point> <!-- operation="delete"-->
  <mep-id>1</mep-id>
  <config>
    <mep-id>1</mep-id>
    <direction>down</direction>
    <administrative-state>>false</administrative-state>
    <remote-evpn-id>1</remote-evpn-id>
  </config>
</maintenance-end-point>
</maintenance-end-points>
</maintenance-association>
</maintenance-associations>
</maintenance-domain>
</maintenance-domains>
</cfm>
```

### Command Syntax

```
ethernet cfm mep (down|up) mpid <1-8191> active (false|true) evpn <1-16777215>
```

## Configure bw mapped interface

This attribute specifies interface where the bandwidth shapers are to be applied

This command is supported when following feature are enabled CFM feature

Attribute Name: bw-mapped-interface

Attribute Type: string

**Netconf edit-config payload**

```

<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
<maintenance-domains>
<maintenance-domain>
  <md-name>DOMAIN_NAME</md-name>
  <config>
    <md-name>DOMAIN_NAME</md-name>
  </config>
</maintenance-domain>
</maintenance-domains>
<maintenance-associations>
<maintenance-association>
  <ma-name>MA_NAME</ma-name>
  <config>
    <ma-name>MA_NAME</ma-name>
  </config>
</maintenance-association>
</maintenance-associations>
<maintenance-end-points>
<maintenance-end-point>
  <mep-id>1</mep-id>
  <config>
    <mep-id>1</mep-id>
  </config>
  <bw-mapped-interface>IFNAME</bw-mapped-interface> <!--
operation="delete"-->
</maintenance-end-point>
</maintenance-end-points>
</maintenance-association>
</maintenance-associations>
</maintenance-domain>
</maintenance-domains>
</cfm>

```

**Command Syntax**

```
bw-mapped-interface IFNAME
```

**Configure enable cc multicast**

Integer that is unique among all the MEPs in the same MA. Other definition is: a small integer, unique over a given Maintenance Association, identifying a specific Maintenance association End Point

Attribute Name: mep-id

Attribute Type: uint16

Attribute Name: enable-cc-multicast

Attribute Type: empty

**Netconf edit-config payload**

```

<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
<maintenance-domains>
<maintenance-domain>
  <md-name>DOMAIN_NAME</md-name>
  <config>

```

```

    <md-name>DOMAIN_NAME</md-name>
  </config>
<maintenance-associations>
<maintenance-association>
  <ma-name>MA_NAME</ma-name>
  <config>
    <ma-name>MA_NAME</ma-name>
  </config>
  <maintenance-end-points>
  <maintenance-end-point>
    <mep-id>1</mep-id>
    <config>
      <mep-id>1</mep-id>
    </config>
    <continuity-check>
    <config>
      </enable-cc-multicast>
    </config>
  </continuity-check>
</maintenance-end-point>
</maintenance-end-points>
</maintenance-association>
</maintenance-associations>
</maintenance-domain>
</maintenance-domains>
</cfm>

```

## Command Syntax

```
cc multicast state enable
```

---

## Configure lowest fault priority defect

The lowest priority defect that is allowed to generate a Fault Alarm. The non-existence of this leaf means that no defects are to be reported

This command is supported when following feature are enabled CFM feature

Attribute Name: lowest-fault-priority-defect

Attribute Type: enum (defRDICCM|defMACstatus|defRemoteCCM|defErrorCCM|defXconCCM)

Default Value: defMACstatus

## Netconf edit-config payload

```

<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <maintenance-domains>
  <maintenance-domain>
    <md-name>DOMAIN_NAME</md-name>
    <config>
      <md-name>DOMAIN_NAME</md-name>
    </config>
  </maintenance-domain>
  </maintenance-domains>
  <maintenance-associations>

```

```

<maintenance-association>
  <ma-name>MA_NAME</ma-name>
  <config>
    <ma-name>MA_NAME</ma-name>
  </config>
  <maintenance-end-points>
  <maintenance-end-point>
    <mep-id>1</mep-id>
    <config>
      <mep-id>1</mep-id>
    </config>
    <continuity-check>
    <config>
      <lowest-fault-priority-defect>defMACstatus</lowest-fault-priority-
defect> <!-- operation="delete"-->
    </config>
    </continuity-check>
  </maintenance-end-point>
</maintenance-end-points>
</maintenance-association>
</maintenance-associations>
</maintenance-domain>
</maintenance-domains>
</cfm>

```

### Command Syntax

```

mep lowest-priority-defect
  (defRDICCM|defMACstatus|defRemoteCCM|defErrorCCM|defXconCCM)

```

---

## clear ethernet cfm maintenance-points remote domain DOMAIN\_NAME

Attribute Name: domain-name

Attribute Type: string

### Netconf RPC payload

```

<cfm-l2-clear-ethernet-remote-meps xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-cfm">
  <domain-name>DOMAIN_NAME</domain-name>
</cfm-l2-clear-ethernet-remote-meps>

```

### Command Syntax

```

clear ethernet cfm maintenance-points remote domain DOMAIN_NAME

```

---

## clear ethernet cfm statistics

### Netconf RPC payload

```

<cfm-clear-all-mep-stats xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm"/>

```

---

**Command Syntax**

```
clear ethernet cfm statistics
```

---

**clear ethernet cfm statistics mep <1-8191> domain DOMAIN\_NAME ma MA\_NAME**

Attribute Name: mep-id

Attribute Type: uint16

Attribute Range: 1-8191

Attribute Name: domain-name

Attribute Type: string

Attribute Name: ma-name

Attribute Type: string

Attribute Range: 1-6

**Netconf RPC payload**

```
<cfm-l2-clear-mep-stats xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <mep-id>1</mep-id>
  <domain-name>DOMAIN_NAME</domain-name>
  <ma-name>MA_NAME</ma-name>
</cfm-l2-clear-mep-stats>
```

**Command Syntax**

```
clear ethernet cfm statistics mep <1-8191> domain DOMAIN_NAME ma MA_NAME
```

---

**cfm snmp restart****Netconf RPC payload**

```
<cfm-snmp-restart xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm"/>
```

**Command Syntax**

```
cfm snmp restart
```

---

**debug ethernet cfm (events|rx|tx|loopback|traceroute|all)**

Attribute Name: terminal-debug-options

Attribute Type: bits (events|rx|tx|loopback|traceroute|all)

**Netconf RPC payload**

```
<cfm-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <terminal-debug-options>events</terminal-debug-options>
</cfm-terminal-debug-on>
```

**Command Syntax**

```
debug ethernet cfm (events|rx|tx|loopback|traceroute|all)
```

---

## no debug ethernet cfm (events|rx|tx|loopback|traceroute|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (events|rx|tx|loopback|traceroute|all)

### Netconf RPC payload

```
<cfm-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <terminal-debug-options>events</terminal-debug-options>
</cfm-terminal-debug-off>
```

### Command Syntax

```
no debug ethernet cfm (events|rx|tx|loopback|traceroute|all)
```

---

## clear ethernet cfm traceroute-cache

### Netconf RPC payload

```
<cfm-l2-clear-linktrace-cache xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm"/>
```

### Command Syntax

```
clear ethernet cfm traceroute-cache
```

---

## IPI-CFM-Y1731

---

### Configure enable status

This attribute specifies whether ETH-AIS transmission is enabled

Attribute Name: enable-status

Attribute Type: uint8

Attribute Name: client-md-level

Attribute Type: uint8

Attribute Range: 0-7

### Netconf edit-config payload

```
<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <maintenance-domains>
    <maintenance-domain>
      <md-name>DOMAIN_NAME</md-name>
      <config>
        <md-name>DOMAIN_NAME</md-name>
      </config>
    <maintenance-associations>
      <maintenance-association>
        <ma-name>MA_NAME</ma-name>
      <config>
```

```

        <ma-name>MA_NAME</ma-name>
    </config>
    <maintenance-end-points>
        <maintenance-end-point>
            <mep-id>1</mep-id>
            <config>
                <mep-id>1</mep-id>
            </config>
            <ethernet-alarm-indication-signal>
            <config>
                <client-md-level>0</client-md-level>
                </enable-status>
            </config>
        </ethernet-alarm-indication-signal>
    </maintenance-end-point>
</maintenance-end-points>
</maintenance-association>
</maintenance-associations>
</maintenance-domain>
</maintenance-domains>
</cfm>

```

## Command Syntax

```
ais status enable level <0-7>
```

---

## Configure interval

This attribute specifies the ETH-AIS transmission period

This command is supported when following feature are enabled CFM Y1731 feature

Attribute Name: interval

Attribute Type: enum (1s|1min)

Default Value: 1s

## Netconf edit-config payload

```

<cfm xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-cfm">
  <maintenance-domains>
    <maintenance-domain>
      <md-name>DOMAIN_NAME</md-name>
      <config>
        <md-name>DOMAIN_NAME</md-name>
      </config>
      <maintenance-associations>
        <maintenance-association>
          <ma-name>MA_NAME</ma-name>
          <config>
            <ma-name>MA_NAME</ma-name>
          </config>
        </maintenance-association>
      </maintenance-associations>
    </maintenance-domain>
  </maintenance-domains>
</cfm>

```

```

    <maintenance-end-point>
      <mep-id>1</mep-id>
      <config>
        <mep-id>1</mep-id>
      </config>
      <ethernet-alarm-indication-signal>
      <config>
        <interval>1s</interval> <!-- operation="delete"-->
      </config>
    </ethernet-alarm-indication-signal>
  </maintenance-end-point>
</maintenance-end-points>
</maintenance-association>
</maintenance-associations>
</maintenance-domain>
</maintenance-domains>
</cfm>

```

### Command Syntax

```
ais interval (1s|1min)
```

---

## IPI-UDLD

---

### Configure enable

Use this attribute to enable UDLD

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```

<udld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-udld">
  <global>
  <config>
    </enable><!-- operation="delete"-->
  </config>
</global>
</udld>

```

### Command Syntax

```
udld enable
```

---

### Configure message time

Use this attribute to set UDLD message interval value

Attribute Name: message-time

Attribute Type: uint8

---

Attribute Range: 7-90

### Netconf edit-config payload

```
<udld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-udld">
  <global>
  <config>
    <message-time>7</message-time> <!-- operation="delete"-->
  </config>
</global>
</udld>
```

### Command Syntax

```
udld message-time <7-90>
```

---

## Configure options

Use this attribute to enable or disable UDLD debugging at various levels

Attribute Name: options

Attribute Type: bits (event|packet|timer|nsm|hal|all)

### Netconf edit-config payload

```
<udld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-udld">
  <debug>
  <config>
    <options>event</options> <!-- operation="delete"-->
  </config>
</debug>
</udld>
```

### Command Syntax

```
debug udld (event|packet|timer|nsm|hal|all)
```

---

## Configure mode

Use this attribute to configure UDLD mode for an interface

Attribute Name: mode

Attribute Type: enum (normal|aggressive)

### Netconf edit-config payload

```
<udld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-udld">
  <interfaces>
  <interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
    <mode>normal</mode> <!-- operation="delete"-->
  </interface>
```

```
</interfaces>
</udld>
```

## Command Syntax

```
udld mode (normal|aggressive)
```

---

## Configure administrative state

Use this attribute configure UDLD administrative state for an interface

Attribute Name: administrative-state

Attribute Type: enum (disable|enable)

## Netconf edit-config payload

```
<udld xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-udld">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <administrative-state>disable</administrative-state> <!-- operation="delete"-->
</interface>
</interfaces>
</udld>
```

## Command Syntax

```
udld state (disable|enable)
```

---

## debug udld (event|packet|timer|nsm|hal|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (event|packet|timer|nsm|hal|all)

## Netconf RPC payload

```
<udld-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-udld">
<terminal-debug-options>event</terminal-debug-options>
</udld-terminal-debug-on>
```

## Command Syntax

```
debug udld (event|packet|timer|nsm|hal|all)
```

---

## no debug udld (event|packet|timer|nsm|hal|all)

Attribute Name: terminal-debug-options

Attribute Type: bits (event|packet|timer|nsm|hal|all)

---

## Netconf RPC payload

```
<udld-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-udld">
  <terminal-debug-options>event</terminal-debug-options>
</udld-terminal-debug-off>
```

## Command Syntax

```
no debug udld (event|packet|timer|nsm|hal|all)
```

---

# IPI-EFM

---

## Configure link monitor off

Ethernet OAM link monitoring on the interface

Attribute Name: link-monitor-off

Attribute Type: uint8

## Netconf edit-config payload

```
<ethernet-oam xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
  <interfaces>
  <interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
    </link-monitor-off><!-- operation="delete"-->
  </interface>
</interfaces>
</ethernet-oam>
```

## Command Syntax

```
no ethernet oam link-monitor on
```

---

## Configure remote loopback start

Ethernet OAM remote loopback trigger on interface

Attribute Name: remote-loopback-start

Attribute Type: uint8

## Netconf edit-config payload

```
<ethernet-oam xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
  <interfaces>
  <interface>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  </interface>
</interfaces>
</ethernet-oam>
```

```
    </remote-loopback-start><!-- operation="delete"-->
</interface>
</interfaces>
</ethernet-oam>
```

## Command Syntax

```
ethernet oam remote-loopback start
```

---

## Configure enable

Enable Ethernet OAM on the interface

Attribute Name: enable

Attribute Type: empty

## Netconf edit-config payload

```
<ethernet-oam xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </enable><!-- operation="delete"-->
</interface>
</interfaces>
</ethernet-oam>
```

## Command Syntax

```
ethernet oam enable
```

---

## Configure mode

Ethernet OAM mode on the interface

Attribute Name: mode

Attribute Type: enum (active|passive)

## Netconf edit-config payload

```
<ethernet-oam xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <mode>active</mode> <!-- operation="delete"-->
</interface>
</interfaces>
</ethernet-oam>
```

---

## Command Syntax

```
ethernet oam mode (active|passive)
```

---

## Configure link lost timeout

Ethernet OAM link lost timer related configs

Attribute Name: link-lost-timeout

Attribute Type: uint8

Attribute Range: 2-30

### Netconf edit-config payload

```
<ethernet-oam xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <link-lost-timeout>2</link-lost-timeout> <!-- operation="delete"-->
    </interface>
  </interfaces>
</ethernet-oam>
```

## Command Syntax

```
ethernet oam timeout <2-30>
```

---

## Configure pdu min rate

OAMPDU minimum rate per second

Attribute Name: pdu-min-rate

Attribute Type: uint8

Attribute Range: 1-10

### Netconf edit-config payload

```
<ethernet-oam xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <pdu-min-rate>1</pdu-min-rate> <!-- operation="delete"-->
    </interface>
  </interfaces>
</ethernet-oam>
```

---

## Command Syntax

```
ethernet oam min-rate <1-10>
```

---

## Configure pdu max rate

OAMPDU maximum rate per second

Attribute Name: pdu-max-rate

Attribute Type: uint8

Attribute Range: 1-10

## Netconf edit-config payload

```
<ethernet-oam xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <pdu-max-rate>1</pdu-max-rate> <!-- operation="delete"-->
    </interface>
  </interfaces>
</ethernet-oam>
```

## Command Syntax

```
ethernet oam max-rate <1-10>
```

---

## Configure unidirectional link support

Ethernet OAM unidirectional link support on the interface

Attribute Name: unidirectional-link-support

Attribute Type: empty

## Netconf edit-config payload

```
<ethernet-oam xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <unidirectional-link-support><!-- operation="delete"-->
    </interface>
  </interfaces>
</ethernet-oam>
```

## Command Syntax

```
ethernet oam unidirectional-link supported
```

---

## Configure remote loopback support

Ethernet OAM remote loopback support on the interface

Attribute Name: remote-loopback-support

Attribute Type: empty

### Netconf edit-config payload

```
<ethernet-oam xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  </remote-loopback-support><!-- operation="delete"-->
</interface>
</interfaces>
</ethernet-oam>
```

### Command Syntax

```
ethernet oam remote-loopback supported
```

---

## Configure remote loopback timeout

Ethernet OAM remote loopback timeout on the interface

Attribute Name: remote-loopback-timeout

Attribute Type: uint8

Attribute Range: 1-10

### Netconf edit-config payload

```
<ethernet-oam xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <remote-loopback-timeout>1</remote-loopback-timeout> <!-- operation="delete"-->
</interface>
</interfaces>
</ethernet-oam>
```

### Command Syntax

```
ethernet oam remote-loopback timeout <1-10>
```

---

## Configure link monitor support

Ethernet OAM link monitor support on the interface

Attribute Name: link-monitor-support

Attribute Type: empty

### Netconf edit-config payload

```
<ethernet-oam xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      </link-monitor-support><!-- operation="delete"-->
    </interface>
  </interfaces>
</ethernet-oam>
```

### Command Syntax

```
ethernet oam link-monitor supported
```

---

## Configure link monitor event log size

Ethernet OAM maximum event log entries on interface

Attribute Name: link-monitor-event-log-size

Attribute Type: uint8

Attribute Range: 1-100

### Netconf edit-config payload

```
<ethernet-oam xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <link-monitor-event-log-size>1</link-monitor-event-log-size> <!--
operation="delete"-->
    </interface>
  </interfaces>
</ethernet-oam>
```

### Command Syntax

```
ethernet oam link-monitor event-log-size <1-100>
```

---

## Configure disable port on remote failure events

Ethernet OAM remote failure action on interface

Attribute Name: disable-port-on-remote-failure-events

Attribute Type: bits (dying-gasp|link-fault|critical-event)

### Netconf edit-config payload

```
<ethernet-oam xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <disable-port-on-remote-failure-events>dying-gasp</disable-port-on-remote-
failure-events> <!-- operation="delete"-->
    </interface>
  </interfaces>
</ethernet-oam>
```

### Command Syntax

```
ethernet oam remote-failure {dying-gasp|link-fault|critical-event} action error-
  disable-interface
```

---

## Configure options

Debugging enable configuration for Ethernet OAM

Attribute Name: options

Attribute Type: bits (event|rx|tx|all)

### Netconf edit-config payload

```
<ethernet-oam xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
  <debug>
    <config>
      <options>event</options> <!-- operation="delete"-->
    </config>
  </debug>
</ethernet-oam>
```

### Command Syntax

```
debug ethernet oam (event|rx|tx|all)
```

---

## debug ethernet oam (event|rx|tx|all)

Attribute Name: terminal-debug-status

Attribute Type: bits (event|rx|tx|all)

---

## Netconf RPC payload

```
<efm-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
  <terminal-debug-status>event</terminal-debug-status>
</efm-terminal-debug-on>
```

## Command Syntax

```
debug ethernet oam (event|rx|tx|all)
```

---

## no debug ethernet oam (event|rx|tx|all)

Attribute Name: terminal-debug-status

Attribute Type: bits (event|rx|tx|all)

## Netconf RPC payload

```
<efm-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
  <terminal-debug-status>event</terminal-debug-status>
</efm-terminal-debug-off>
```

## Command Syntax

```
no debug ethernet oam (event|rx|tx|all)
```

---

## clear ethernet oam statistics interface IFNAME

Attribute Name: name

Attribute Type: string

## Netconf RPC payload

```
<clear-interface-oam-counters xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-efm">
  <name>IFNAME</name>
</clear-interface-oam-counters>
```

## Command Syntax

```
clear ethernet oam statistics interface IFNAME
```

---

# IPI-ROLE-BASED-ACCESS-CONTROL

---

## Configure policy name

Use this attribute to create a TACACS+ Role-Based Authorization (RBAC) policy and enter RBAC policy mode.

Attribute Name: policy-name

Attribute Type: string

Attribute Range: 2-16

## Netconf edit-config payload

```

<role-based-access-control xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-role-
based-access-control">
  <policies>
  <policy> <!-- operation="delete"-->
    <policy-name>POLICY-NAME</policy-name>
    <config>
      <policy-name>POLICY-NAME</policy-name>
    </config>
  </policy>
</policies>
</role-based-access-control>

```

## Command Syntax

```
policy POLICY-NAME
```

---

## Configure command mode

Attribute to specify the mode in which CLI should be allowed/denied. Command prompt string such as 'config-router' or 'config-if', deny/Permit access to the command only in this mode.

Attribute Name: command-mode

Attribute Type: string

Attribute Name: rule-type

Attribute Type: enum (deny|permit)

## Netconf edit-config payload

```

<role-based-access-control xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-role-
based-access-control">
  <policies>
  <policy>
    <policy-name>POLICY-NAME</policy-name>
    <config>
      <policy-name>POLICY-NAME</policy-name>
    </config>
  </policy>
  <rules>
  <rule>
    <rule-name>RULE-STRING</rule-name>
    <config>
      <rule-name>RULE-STRING</rule-name>
      <rule-type>deny</rule-type> <!-- operation="delete"-->
    </config>
    <command-mode>MODE-NAME</command-mode> <!-- operation="delete"-->
  </rule>
</rules>
</policy>
</policies>
</role-based-access-control>

```

## Command Syntax

```
(deny|permit) RULE-STRING mode MODE-NAME
```

---

## Configure rule name

This attribute specifies rule string configured as regex-expression for cli authorization

Attribute Name: rule-name

Attribute Type: string

Attribute Range: 3-255

Attribute Name: rule-type

Attribute Type: enum (deny|permit)

## Netconf edit-config payload

```
<role-based-access-control xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-role-
based-access-control">
  <policies>
    <policy>
      <policy-name>POLICY-NAME</policy-name>
      <config>
        <policy-name>POLICY-NAME</policy-name>
      </config>
    </rules>
    <rule>
      <rule-name>RULE-STRING</rule-name>
      <config>
        <rule-name>RULE-STRING</rule-name>
        <rule-type>deny</rule-type>
      </config>
    </rule>
  </rules>
</policy>
</policies>
</role-based-access-control>
```

## Command Syntax

```
(deny|permit) RULE-STRING
```

---

## Configure rule type

Attribute to specify the mode in which CLI should be allowed/denied. Command prompt string such as 'config-router' or 'config-if', deny/Permit access to the command only in this mode.

Attribute Name: command-mode

Attribute Type: string

Attribute Name: rule-type

Attribute Type: enum (deny|permit)

## Netconf edit-config payload

```

<role-based-access-control xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-role-
based-access-control">
  <policies>
  <policy>
    <policy-name>POLICY-NAME</policy-name>
    <config>
      <policy-name>POLICY-NAME</policy-name>
    </config>
  </policy>
  </rules>
  <rule>
    <rule-name>RULE-STRING</rule-name>
    <config>
      <rule-name>RULE-STRING</rule-name>
      <rule-type>deny</rule-type>
    </config>
    <command-mode>MODE-NAME</command-mode>
  </rule>
  </rules>
  </policies>
</role-based-access-control>

```

## Command Syntax

```
(deny|permit) RULE-STRING mode MODE-NAME
```

---

## Configure role name

Use this attribute to create a TACACS+ Role-Based Authorization (RBAC) role and to switch to RBAC role mode. End-user cannot specify one of these roles already defined in OcNOS: network-admin network-user network-operator network-engineer For more about these built-in roles, see 'username' CLI configuration

Attribute Name: role-name

Attribute Type: string

Attribute Range: 2-16

## Netconf edit-config payload

```

<role-based-access-control xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-role-
based-access-control">
  <roles>
  <role> <!-- operation="delete"-->
    <role-name>ROLE-NAME</role-name>
    <config>
      <role-name>ROLE-NAME</role-name>
    </config>
  </role>
  </roles>
</role-based-access-control>

```

---

## Command Syntax

```
role ROLE-NAME
```

---

## Configure default policy

Use this attribute to set the default rule for a TACACS+ Role-Based Access Control (RBAC) role.

Attribute Name: default-policy

Attribute Type: enum (deny-all|permit-all)

Default Value: deny-all

### Netconf edit-config payload

```
<role-based-access-control xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-role-based-access-control">
  <roles>
    <role>
      <role-name>ROLE-NAME</role-name>
      <config>
        <role-name>ROLE-NAME</role-name>
      </config>
      <default-policy>deny-all</default-policy> <!-- operation="delete"-->
    </role>
  </roles>
</role-based-access-control>
```

## Command Syntax

```
default (deny-all|permit-all)
```

---

## Configure policies policy-name

Use this attribute to add a policy to a TACACS+ Role-based Access Control (RBAC) role

Attribute Name: policy-name

Attribute Type: string

Attribute Range: 2-16

### Netconf edit-config payload

```
<role-based-access-control xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-role-based-access-control">
  <roles>
    <role>
      <role-name>ROLE-NAME</role-name>
      <config>
        <role-name>ROLE-NAME</role-name>
      </config>
    <polices>
      <policy> <!-- operation="delete"-->
        <policy-name>POLICY-NAME</policy-name>
      </config>
    </polices>
  </role>
</roles>
</role-based-access-control>
```

```

        <policy-name>POLICY-NAME</policy-name>
    </config>
</policy>
</policies>
</role>
</roles>
</role-based-access-control>

```

### Command Syntax

```
add policy POLICY-NAME
```

---

## Configure enable

Enable or disable the TACAS+ Role-Based Access Control of RBAC feature

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```

<role-based-access-control xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-role-
based-access-control">
  <config>
    </enable><!-- operation="delete"-->
  </config>
</role-based-access-control>

```

### Command Syntax

```
feature dynamic-rbac
```

---

## IPI-PORT-BREAKOUT

---

### Configure interface

Name of the interface to breakout

Attribute Name: interface

Attribute Type: string

Attribute Name: mode

Attribute Type: enum

(4X10g|4X25g|2X50g|4X100g|8X50g|8X25g|8X10g|2X200g|3X100g|2X100g|1X100g|1X200g|4X50g|1X40g)

### Netconf edit-config payload

```

<port-breakout xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-breakout">
  <breakouts>
    <breakout> <!-- operation="delete"-->
      <interface>IFNAME</interface>
    </breakout>
  </breakouts>
  <config>
    <interface>WORD</interface>
  </config>
</port-breakout>

```

```

    <mode>4X10g</mode>
  </config>
</breakout>
</breakouts>
</port-breakout>

```

## Command Syntax

```

port IFNAME breakout
(4X10g|4X25g|2X50g|4X100g|8X50g|8X25g|8X10g|2X200g|3X100g|1X200g|4X50g)

```

---

## Configure mode

Name of the interface to breakout

Attribute Name: interface

Attribute Type: string

Attribute Name: mode

Attribute Type: enum

(4X10g|4X25g|2X50g|4X100g|8X50g|8X25g|8X10g|2X200g|3X100g|2X100g|1X100g|1X200g|4X50g|1X40g)

Attribute Name: serdes

Attribute Type: enum (25g)

## Netconf edit-config payload

```

<port-breakout xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-breakout">
  <breakouts>
    <breakout> <!-- operation="delete"-->
      <interface>IFNAME</interface>
      <config>
        <interface>WORD</interface>
        <mode>4X10g</mode>
        <serdes>25g</serdes>
      </config>
    </breakout>
  </breakouts>
</port-breakout>

```

## Command Syntax

```

port IFNAME breakout (2X100g|1X100g) (serdes (25g)|)

```

---

## Configure breakouts interface

Name of the interface to breakout

Attribute Name: interface

Attribute Type: string

Attribute Name: mode

Attribute Type: enum

(4X10g|4X25g|2X50g|4X100g|8X50g|8X25g|8X10g|2X200g|3X100g|2X100g|1X100g|1X200g|4X50g|1X40g)

**Netconf edit-config payload**

```
<port-breakout xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-breakout">
<breakouts>
<breakout> <!-- operation="delete"-->
  <interface>IFNAME</interface>
  <config>
    <interface>WORD</interface>
    <mode>4X10g</mode>
  </config>
</breakout>
</breakouts>
</port-breakout>
```

**Command Syntax**

```
port IFNAME breakout (4X10g|4X25g|2X50g|4X100g|2X200g|3X100g|1X200g|4X50g)
```

---

**Configure breakouts interface**

Name of the interface to breakout

Attribute Name: interface

Attribute Type: string

Attribute Name: mode

Attribute Type: enum

(4X10g|4X25g|2X50g|4X100g|8X50g|8X25g|8X10g|2X200g|3X100g|2X100g|1X100g|1X200g|4X50g|1X40g)

**Netconf edit-config payload**

```
<port-breakout xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-breakout">
<breakouts>
<breakout> <!-- operation="delete"-->
  <interface>IFNAME</interface>
  <config>
    <interface>WORD</interface>
    <mode>4X10g</mode>
  </config>
</breakout>
</breakouts>
</port-breakout>
```

**Command Syntax**

```
port IFNAME breakout (4X10g|4X25g|2X50g)
```

---

**Configure breakouts interface**

Name of the interface to breakout

Attribute Name: interface

Attribute Type: string

Attribute Name: mode

Attribute Type: enum

(4X10g|4X25g|2X50g|4X100g|8X50g|8X25g|8X10g|2X200g|3X100g|2X100g|1X100g|1X200g|4X50g|1X40g)

### Netconf edit-config payload

```
<port-breakout xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-breakout">
  <breakouts>
    <breakout> <!-- operation="delete"-->
      <interface>IFNAME</interface>
      <config>
        <interface>WORD</interface>
        <mode>4X10g</mode>
      </config>
    </breakout>
  </breakouts>
</port-breakout>
```

### Command Syntax

```
port IFNAME breakout (1X40g)
```

---

## Configure breakouts interface

Name of the interface to breakout

Attribute Name: interface

Attribute Type: string

Attribute Name: mode

Attribute Type: enum

(4X10g|4X25g|2X50g|4X100g|8X50g|8X25g|8X10g|2X200g|3X100g|2X100g|1X100g|1X200g|4X50g|1X40g)

### Netconf edit-config payload

```
<port-breakout xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-breakout">
  <breakouts>
    <breakout> <!-- operation="delete"-->
      <interface>IFNAME</interface>
      <config>
        <interface>WORD</interface>
        <mode>4X10g</mode>
      </config>
    </breakout>
  </breakouts>
</port-breakout>
```

### Command Syntax

```
port <1-128> breakout (4X10g|4X25g|2X50g)
```

---

## Configure port group

Use this attribute to set the port group associated with this instance

This command is supported when following feature are disabled DUNE feature

Attribute Name: port-group

Attribute Type: uint8

Attribute Range: 1-64

Attribute Name: speed

Attribute Type: enum (10g)

### Netconf edit-config payload

```
<port-breakout xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-breakout">
  <groups-speed>
    <group-speed> <!-- operation="delete"-->
      <port-group>1</port-group>
      <config>
        <port-group>0</port-group>
        <speed>10g</speed>
      </config>
    </group-speed>
  </groups-speed>
</port-breakout>
```

### Command Syntax

```
port-group <1-64> speed (10g)
```

---

## Configure name

Use this attribute to configure Port-breakout mode for an interface

Attribute Name: mode

Attribute Type: enum (4X10g|4X25g|2X50g)

### Netconf edit-config payload

```
<port-breakout xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-port-breakout">
  <interfaces>
    <interface>
      <name>WORD</name>
      <config>
        <name>WORD</name>
      </config>
      <mode>4X10g</mode> <!-- operation="delete"-->
    </interface>
  </interfaces>
</port-breakout>
```

### Command Syntax

```
port breakout enable (4X10g|4X25g|2X50g)
```

---

## IPI-SOURCE-INTERFACE

---

### Configure vrf name

VRF to apply the source-interface.

This command is supported when following feature are enabled hostp feature

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: port-number

Attribute Type: union

### Netconf edit-config payload

```
<source-interface xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-source-
interface">
  <address-family-ipv4>
    <source-nat-mappings>
      <source-nat-mapping>
        <vrf-name>VRF_NAME</vrf-name>
        <config>
          <vrf-name>VRF_NAME</vrf-name>
          <protocol-type>tacacs+</protocol-type>
          <interface-name>WORD</interface-name>
          <port-number>0</port-number> <!-- operation="delete"-->
        </config>
        <protocol-type>tacacs+</protocol-type>
        <interface-name>IFNAME</interface-name>
      </source-nat-mapping>
    </source-nat-mappings>
  </address-family-ipv4>
</source-interface>
```

### Command Syntax

```
ip source-interface IFNAME (tacacs+|ntp|snmp|syslog|radius) (port (0|<1025-
65535>)|) (vrf VRF_NAME|)
```

---

### Configure interface name

VRF to apply the source-interface.

This command is supported when following feature are enabled IPV6 feature,hostp feature

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: port-number

Attribute Type: union

## Netconf edit-config payload

```

<source-interface xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-source-
interface">
  <address-family-ipv6>
  <source-nat-mappings>
  <source-nat-mapping>
    <vrf-name>VRF_NAME</vrf-name>
    <config>
      <vrf-name>VRF_NAME</vrf-name>
      <protocol-type>tacacs+</protocol-type>
      <interface-name>WORD</interface-name>
      <port-number>0</port-number> <!-- operation="delete"-->
    </config>
    <protocol-type>tacacs+</protocol-type>
    <interface-name>IFNAME</interface-name>
  </source-nat-mapping>
</source-nat-mappings>
</address-family-ipv6>
</source-interface>

```

## Command Syntax

```

ipv6 source-interface IFNAME (tacacs+|ntp|snmp|syslog|radius) (port (0|<1025-
65535>)|) (vrf VRF_NAME|)

```

---

# IPI-TACACS

---

## Configure feature enable

Use this attribute to enable the TACACS+ feature

Attribute Name: feature-enable

Attribute Type: empty

## Netconf edit-config payload

```

<tacacs xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tacacs">
  <vrfs>
  <vrf>
    <vrf-name>management</vrf-name>
    <config>
      <vrf-name>management</vrf-name>
    </config>
    </feature-enable>
  </vrf>
</vrfs>
</tacacs>

```

## Command Syntax

```

feature tacacs+ (vrf (management|NAME)|)

```

---

## Configure vrf name

VRF Name associated with this instance

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: key-type

Attribute Type: enum (0|7)

Attribute Name: secret-key-string

Attribute Type: string

### Netconf edit-config payload

```
<tacacs xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tacacs">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
        <key-type>0</key-type>
        <secret-key-string>WORD</secret-key-string>
      </config>
    </vrf>
  </vrfs>
</tacacs>
```

### Command Syntax

```
tacacs-server login key (0|7) WORD (vrf (management|NAME) |)
```

---

## Configure key type

VRF Name associated with this instance

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: key-type

Attribute Type: enum (0|7)

Attribute Name: secret-key-string

Attribute Type: string

### Netconf edit-config payload

```
<tacacs xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tacacs">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
        <key-type>0</key-type>
      </config>
    </vrf>
  </vrfs>
</tacacs>
```

```

        <secret-key-string>WORD</secret-key-string>
    </config>
</vrf>
</vrfs>
</tacacs>

```

### Command Syntax

```
tacacs-server login key (0|7) WORD (vrf (management|NAME)|)
```

---

## Configure timeout

VRF Name associated with this instance

This command is supported when following feature are enabled hostp feature,aaa feature,tacacs-client feature

Attribute Name: vrf-name

Attribute Type: string

Attribute Name: timeout

Attribute Type: uint8

Default Value: 5

Attribute Range: 1-60

### Netconf edit-config payload

```

<tacacs xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tacacs">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
        <timeout>1</timeout> <!-- operation="delete"-->
      </config>
    </vrf>
  </vrfs>
</tacacs>

```

### Command Syntax

```
tacacs-server login timeout <1-60> (vrf (management|NAME)|)
```

---

## Configure host address

Use this attribute to set the TACACS+ server host name or IP address

Attribute Name: host-address

Attribute Type: union

Attribute Range: 1-63

Attribute Name: sequence-number

Attribute Type: uint8

---

Attribute Range: 1-8

### Netconf edit-config payload

```
<tacacs xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tacacs">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server> <!-- operation="delete"-->
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number>
      </config>
    </server>
  </remote-servers>
</tacacs>
```

### Command Syntax

```
tacacs-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf (management|NAME)|) seq-
num <1-8>
```

---

## Configure secret key string

Shared key used between the authentication-server and the device

Attribute Name: secret-key-string

Attribute Type: string

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: key-type

Attribute Type: enum (0|7)

### Netconf edit-config payload

```
<tacacs xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tacacs">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
</tacacs>
```

```

<server>
  <host-address>A.B.C.D</host-address>
  <config>
    <host-address>A.B.C.D</host-address>
    <sequence-number>1</sequence-number> <!-- operation="delete"-->
    <key-type>0</key-type> <!-- operation="delete"-->
  </config>
  <secret-key-string>WORD</secret-key-string> <!-- operation="delete"-->
</server>
</remote-servers>
</vrf>
</vrfs>
</tacacs>

```

## Command Syntax

```

tacacs-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf (management|NAME)|) seq-
num <1-8> key (0|7) WORD

```

---

## Configure port

Port number used for TACACS+ Server Connection

Attribute Name: port

Attribute Type: uint32

Attribute Range: 1025-65535

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

## Netconf edit-config payload

```

<tacacs xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tacacs">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number> <!-- operation="delete"-->
      </config>
      <port>1025</port> <!-- operation="delete"-->
    </server>
  </remote-servers>
</tacacs>

```

---

```
</tacacs>
```

## Command Syntax

```
tacacs-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf (management|NAME)|) seq-
  num <1-8> port <1025-65535>
```

---

## Configure sequence number

To represent the timeout configured by the user

Attribute Name: timeout

Attribute Type: uint32

Default Value: 5

Attribute Range: 1-60

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

## Netconf edit-config payload

```
<tacacs xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tacacs">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number> <!-- operation="delete"-->
      </config>
      <timeout>1</timeout> <!-- operation="delete"-->
    </server>
  </remote-servers>
</tacacs>
```

## Command Syntax

```
tacacs-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf (management|NAME)|) seq-
  num <1-8> timeout <1-60>
```

---

## Configure server timeout

To represent the timeout configured by the user

Attribute Name: timeout

---

Attribute Type: uint32

Default Value: 5

Attribute Range: 1-60

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: port

Attribute Type: uint32

Attribute Range: 1025-65535

### Netconf edit-config payload

```
<tacacs xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tacacs">
  <vrfs>
    <vrf>
      <vrf-name>management</vrf-name>
      <config>
        <vrf-name>management</vrf-name>
      </config>
    </vrf>
  </vrfs>
  <remote-servers>
    <server>
      <host-address>A.B.C.D</host-address>
      <config>
        <host-address>A.B.C.D</host-address>
        <sequence-number>1</sequence-number> <!-- operation="delete"-->
        <port>1025</port> <!-- operation="delete"-->
      </config>
      <timeout>1</timeout> <!-- operation="delete"-->
    </server>
  </remote-servers>
</tacacs>
```

### Command Syntax

```
tacacs-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf (management|NAME)|) seq-
num <1-8> port <1025-65535> timeout <1-60>
```

---

## Configure server port

Port number used for TACACS+ Server Connection

Attribute Name: port

Attribute Type: uint32

Attribute Range: 1025-65535

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: key-type

Attribute Type: enum (0|7)

Attribute Name: secret-key-string

Attribute Type: string

### Netconf edit-config payload

```
<tacacs xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tacacs">
<vrfs>
<vrf>
  <vrf-name>management</vrf-name>
  <config>
    <vrf-name>management</vrf-name>
  </config>
<remote-servers>
<server>
  <host-address>A.B.C.D</host-address>
  <config>
    <host-address>A.B.C.D</host-address>
    <sequence-number>1</sequence-number> <!-- operation="delete"-->
    <key-type>0</key-type> <!-- operation="delete"-->
    <secret-key-string>WORD</secret-key-string> <!-- operation="delete"-->
  </config>
  <port>1025</port> <!-- operation="delete"-->
</server>
</remote-servers>
</vrf>
</vrfs>
</tacacs>
```

### Command Syntax

```
tacacs-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf (management|NAME)|) seq-
num <1-8> key (0|7) WORD port <1025-65535>
```

---

## Configure server timeout

To represent the timeout configured by the user

Attribute Name: timeout

Attribute Type: uint32

Default Value: 5

Attribute Range: 1-60

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: key-type

Attribute Type: enum (0|7)

Attribute Name: secret-key-string

Attribute Type: string

### Netconf edit-config payload

```
<tacacs xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tacacs">
<vrfs>
<vrf>
  <vrf-name>management</vrf-name>
  <config>
    <vrf-name>management</vrf-name>
  </config>
<remote-servers>
<server>
  <host-address>A.B.C.D</host-address>
  <config>
    <host-address>A.B.C.D</host-address>
    <sequence-number>1</sequence-number> <!-- operation="delete"-->
    <key-type>0</key-type> <!-- operation="delete"-->
    <secret-key-string>WORD</secret-key-string> <!-- operation="delete"-->
  </config>
  <timeout>1</timeout> <!-- operation="delete"-->
</server>
</remote-servers>
</vrf>
</vrfs>
</tacacs>
```

### Command Syntax

```
tacacs-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf (management|NAME)|) seq-
num <1-8> key (0|7) WORD timeout <1-60>
```

---

## Configure server timeout

To represent the timeout configured by the user

Attribute Name: timeout

Attribute Type: uint32

Default Value: 5

Attribute Range: 1-60

Attribute Name: sequence-number

Attribute Type: uint8

Attribute Range: 1-8

Attribute Name: key-type

Attribute Type: enum (0|7)

Attribute Name: secret-key-string

Attribute Type: string

Attribute Name: port

Attribute Type: uint32

Attribute Range: 1025-65535

### Netconf edit-config payload

```
<tacacs xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tacacs">
<vrfs>
<vrf>
  <vrf-name>management</vrf-name>
  <config>
    <vrf-name>management</vrf-name>
  </config>
</remote-servers>
<server>
  <host-address>A.B.C.D</host-address>
  <config>
    <host-address>A.B.C.D</host-address>
    <sequence-number>1</sequence-number> <!-- operation="delete"-->
    <key-type>0</key-type> <!-- operation="delete"-->
    <secret-key-string>WORD</secret-key-string> <!-- operation="delete"-->
    <port>1025</port> <!-- operation="delete"-->
  </config>
  <timeout>1</timeout> <!-- operation="delete"-->
</server>
</remote-servers>
</vrf>
</vrfs>
</tacacs>
```

### Command Syntax

```
tacacs-server login host (A.B.C.D|X:X::X:X|HOSTNAME) (vrf (management|NAME)|) seq-
num <1-8> key (0|7) WORD port <1025-65535> timeout <1-60>
```

---

## Configure enable

This attribute is to enable/disable TACACS+ debug logging

Attribute Name: enable

Attribute Type: empty

### Netconf edit-config payload

```
<tacacs xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tacacs">
<debug>
<config>
  </enable><!-- operation="delete"-->
</config>
</debug>
</tacacs>
```

---

## Command Syntax

```
debug tacacs+
```

---

## clear tacacs-server counters (vrf (management|NAME|all))

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<clear-all-tacacs-server-counters xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-tacacs">
  <vrf-name>management</vrf-name>
</clear-all-tacacs-server-counters>
```

## Command Syntax

```
clear tacacs-server counters (vrf (management|NAME|all) |)
```

---

## clear tacacs-server (A.B.C.D|X:X::X:X|HOSTNAME) counters (vrf (management|NAME|all))

Attribute Name: hostname

Attribute Type: union

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<clear-tacacs-server-host-counters xmlns="http://www.ipinfusion.com/yang/ocnos/
ipi-tacacs">
  <hostname>A.B.C.D</hostname>
  <vrf-name>management</vrf-name>
</clear-tacacs-server-host-counters>
```

## Command Syntax

```
clear tacacs-server (A.B.C.D|X:X::X:X|HOSTNAME) counters (vrf
(management|NAME|all) |)
```

---

## debug tacacs+

### Netconf RPC payload

```
<tacacs-terminal-debug-on xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
tacacs"/>
```

## Command Syntax

```
debug tacacs+
```

---

## no debug tacacs+

### Netconf RPC payload

```
<tacacs-terminal-debug-off xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-tacacs"/>
```

### Command Syntax

```
no debug tacacs+
```

---

## IPI-TIME-RANGE

---

### Configure name

Time range name to be configured

Attribute Name: name

Attribute Type: string

Attribute Range: 1-60

### Netconf edit-config payload

```
<time-ranges xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-time-range">
  <time-range> <!-- operation="delete"-->
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  </time-range>
</time-ranges>
```

### Command Syntax

```
time-range WORD
```

---

## Configure absolute start time

Start time hour and minute

Attribute Name: absolute-start-time

Attribute Type: string

### Netconf edit-config payload

```
<time-ranges xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-time-range">
  <time-range>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  <start-time-options>
```

```
<config>
  <absolute-start-time>TIME_RANGE_DATE_TIME_T</absolute-start-time>
</config>
</start-time-options>
</time-range>
</time-ranges>
```

### Command Syntax

```
start-time HH:MM:SS <01-31> MONTH <1995-2035>
```

---

## Configure relative start time

Configure the start-time of the time-range to be now or after sometime

Attribute Name: relative-start-time

Attribute Type: union

### Netconf edit-config payload

```
<time-ranges xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-time-range">
  <time-range>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  <start-time-options>
  <config>
    <relative-start-time>TIME_RANGE_RELATIVE_TIME_T</relative-start-time>
  </config>
</start-time-options>
</time-range>
</time-ranges>
```

### Command Syntax

```
start-time (after (<1-129600>) | now)
```

---

## Configure absolute end time

End time hour and minute

Attribute Name: absolute-end-time

Attribute Type: string

### Netconf edit-config payload

```
<time-ranges xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-time-range">
  <time-range>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  <end-time-options>
```

```

<config>
  <absolute-end-time>TIME_RANGE_DATE_TIME_T</absolute-end-time>
</config>
</end-time-options>
</time-range>
</time-ranges>

```

### Command Syntax

```
end-time HH:MM:SS <01-31> MONTH <1995-2035>
```

---

## Configure relative end time

Relative time in minutes

Attribute Name: relative-end-time

Attribute Type: string

### Netconf edit-config payload

```

<time-ranges xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-time-range">
  <time-range>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  <end-time-options>
  <config>
    <relative-end-time>1</relative-end-time> <!-- operation="delete"-->
  </config>
</end-time-options>
</time-range>
</time-ranges>

```

### Command Syntax

```
end-time after <1-129600>
```

---

## Configure frequency

Frequency (hourly, daily, weekly)

Attribute Name: frequency

Attribute Type: union

### Netconf edit-config payload

```

<time-ranges xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-time-range">
  <time-range>
    <name>WORD</name>
    <config>
      <name>WORD</name>
    </config>
  <frequency-options>

```

```

<config>
  <frequency>daily</frequency> <!-- operation="delete"-->
</config>
</frequency-options>
</time-range>
</time-ranges>

```

### Command Syntax

```
frequency (daily|hourly|weekly|days WORD)
```

---

## crypto pki generate rsa common-name ipv4 IPv4ADDR

Attribute Name: ipv4-addr

Attribute Type: inet:ipv4-address

### Netconf RPC payload

```

<crypto-rsa-key-gen xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-crypto">
  <ipv4-addr>IPv4ADDR</ipv4-addr>
</crypto-rsa-key-gen>

```

### Command Syntax

```
crypto pki generate rsa common-name ipv4 IPv4ADDR
```

---

## IPI-IP-SLA

---

### Configure identifier

Use this attribute to set the IPSLA.

Attribute Name: identifier

Attribute Type: uint16

Attribute Range: 1-65535

### Netconf edit-config payload

```

<ip-sla xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ip-sla">
  <processes>
  <process> <!-- operation="delete"-->
    <identifier>1</identifier>
    <config>
      <identifier>1</identifier>
    </config>
  </process>
</processes>
</ip-sla>

```

### Command Syntax

```
ip sla <1-65535>
```

---

## Configure host

Use this attribute to set the ICMP Echo host name or IP address.

Attribute Name: host

Attribute Type: union

Attribute Name: source-interface

Attribute Type: string

### Netconf edit-config payload

```
<ip-sla xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ip-sla">
  <processes>
    <process>
      <identifier>1</identifier>
      <config>
        <identifier>1</identifier>
      </config>
    <icmp-echo-processes>
    <icmp-echo-process> <!-- operation="delete"-->
      <host>IP_SLA_HOSTNAME_T</host>
      <config>
        <host>IP_SLA_HOSTNAME_T</host>
        <source-interface>IFNAME</source-interface>
      </config>
    </icmp-echo-process>
    </icmp-echo-processes>
  </process>
</processes>
</ip-sla>
```

### Command Syntax

```
icmp-echo (ipv4 A.B.C.D|ipv6 X:X::X:X|HOSTNAME) (source-interface IFNAME|)
```

---

## Configure frequency

The frequency (interval) correlates to how often the ICMP packet is sent. The unit of this parameter is in seconds.

Attribute Name: frequency

Attribute Type: uint8

Attribute Range: 1-60

### Netconf edit-config payload

```
<ip-sla xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ip-sla">
  <processes>
    <process>
      <identifier>1</identifier>
      <config>
        <identifier>1</identifier>
      </config>
    </process>
  </processes>
</ip-sla>
```

```

<icmp-echo-processes>
<icmp-echo-process>
  <host>IP_SLA_HOSTNAME_T</host>
  <config>
    <host>IP_SLA_HOSTNAME_T</host>
  </config>
  <frequency>1</frequency> <!-- operation="delete"-->
</icmp-echo-process>
</icmp-echo-processes>
</process>
</processes>
</ip-sla>

```

### Command Syntax

```
frequency <1-60>
```

---

## Configure timeout

The timeout value correlates to how long the Ping application will wait for the response after sending packets ICMP Echo packets.

Attribute Name: timeout

Attribute Type: uint16

Attribute Range: 1000-60000

### Netconf edit-config payload

```

<ip-sla xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ip-sla">
<processes>
<process>
  <identifier>1</identifier>
  <config>
    <identifier>1</identifier>
  </config>
<icmp-echo-processes>
<icmp-echo-process>
  <host>IP_SLA_HOSTNAME_T</host>
  <config>
    <host>IP_SLA_HOSTNAME_T</host>
  </config>
  <timeout>1000</timeout> <!-- operation="delete"-->
</icmp-echo-process>
</icmp-echo-processes>
</process>
</processes>
</ip-sla>

```

### Command Syntax

```
timeout <1000-60000>
```

---

## Configure threshold

The threshold value correlates to the limit the administrator sets as what would be a successful test. Threshold can be configured in milli-seconds.

Attribute Name: threshold

Attribute Type: uint16

Attribute Range: 1000-60000

### Netconf edit-config payload

```
<ip-sla xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ip-sla">
  <processes>
    <process>
      <identifier>1</identifier>
      <config>
        <identifier>1</identifier>
      </config>
    <icmp-echo-processes>
    <icmp-echo-process>
      <host>IP_SLA_HOSTNAME_T</host>
      <config>
        <host>IP_SLA_HOSTNAME_T</host>
        </config>
        <threshold>1000</threshold> <!-- operation="delete"-->
      </icmp-echo-process>
    </icmp-echo-processes>
  </process>
</processes>
</ip-sla>
```

### Command Syntax

```
threshold <1000-60000>
```

---

## Configure vrf name

VRF name

Attribute Name: vrf-name

Attribute Type: string

### Netconf edit-config payload

```
<ip-sla xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ip-sla">
  <scheduled-processes>
    <scheduled-process>
      <time-range-name>WORD</time-range-name>
      <config>
        <time-range-name>WORD</time-range-name>
        <scheduled-pid>1</scheduled-pid>
      </config>
    <scheduled-pid>1</scheduled-pid>
```

```

    <vrf-name>NAME</vrf-name>
  </scheduled-process>
</scheduled-processes>
</ip-sla>

```

### Command Syntax

```
ip sla schedule <1-65535> time-range WORD (vrf NAME|)
```

---

## clear ip sla statistics (<1-65535>|)

Attribute Name: identifier

Attribute Type: uint16

Attribute Range: 1-65535

### Netconf RPC payload

```

<ip-sla-clear-statistics xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ip-
sla">
  <identifier>1</identifier>
</ip-sla-clear-statistics>

```

### Command Syntax

```
clear ip sla statistics (<1-65535>|)
```

---

## IPI-OBJECT-TRACKING

---

### Configure tracker id

Use this attribute for Object Tracking id.

Attribute Name: tracker-id

Attribute Type: uint16

Attribute Name: delay-up

Attribute Type: uint16

Attribute Range: 1-9999

### Netconf edit-config payload

```

<object-tracking xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-object-tracking">
  <trackers>
    <tracker>
      <tracker-id>1</tracker-id>
      <config>
        <tracker-id>1</tracker-id>
        <delay-up>1</delay-up>
      </config>
    </tracker>
  </trackers>

```

```
</object-tracking>
```

## Command Syntax

```
delay up <1-9999>
```

---

## Configure delay down

Use this attribute for Object Tracking id.

Attribute Name: tracker-id

Attribute Type: uint16

Attribute Name: delay-down

Attribute Type: uint16

Attribute Range: 1-9999

## Netconf edit-config payload

```
<object-tracking xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-object-tracking">
  <trackers>
    <tracker>
      <tracker-id>1</tracker-id>
      <config>
        <tracker-id>1</tracker-id>
        <delay-down>1</delay-down>
      </config>
    </tracker>
  </trackers>
</object-tracking>
```

## Command Syntax

```
delay down <1-9999>
```

---

## Configure delay up

Use this attribute for Object Tracking id.

Attribute Name: tracker-id

Attribute Type: uint16

Attribute Name: delay-up

Attribute Type: uint16

Attribute Range: 1-9999

Attribute Name: delay-down

Attribute Type: uint16

Attribute Range: 1-9999

## Netconf edit-config payload

```
<object-tracking xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-object-tracking">
```

```

<trackers>
<tracker>
  <tracker-id>1</tracker-id>
  <config>
    <tracker-id>1</tracker-id>
    <delay-up>1</delay-up>
    <delay-down>1</delay-down>
  </config>
</tracker>
</trackers>
</object-tracking>

```

### Command Syntax

```
delay up <1-9999> down <1-9999>
```

---

## Configure select option

object tracking options

Attribute Name: select-option

Attribute Type: enum (all|any)

### Netconf edit-config payload

```

<object-tracking xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-object-tracking">
<interfaces>
<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
  <select-option>all</select-option> <!-- operation="delete"-->
</interface>
</interfaces>
</object-tracking>

```

### Command Syntax

```
object-tracking (all|any)
```

---

## Configure track id

Use this attribute for Object Tracking id.

Attribute Name: track-id

Attribute Type: uint32

Attribute Range: 1-500

### Netconf edit-config payload

```

<object-tracking xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-object-tracking">
<interfaces>

```

```

<interface>
  <name>WORD</name>
  <config>
    <name>WORD</name>
  </config>
<track-interfaces>
<track-interface> <!-- operation="delete"-->
  <track-id>1</track-id>
  <config>
    <track-id>1</track-id>
  </config>
</track-interface>
</track-interfaces>
</interface>
</interfaces>
</object-tracking>

```

### Command Syntax

```
object-tracking <1-500>
```

---

## IPI-ELK

---

### Configure password

Use this to configure ELK server password

Attribute Name: password

Attribute Type: string

Attribute Name: username

Attribute Type: string

### Netconf edit-config payload

```

<elk xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-elk">
  <metricbeats>
  <metricbeat>
    <ip>A.B.C.D</ip>
    <config>
      <ip>A.B.C.D</ip>
      <username>USERNAME</username> <!-- operation="delete"-->
    </config>
    <password>PASSWORD</password> <!-- operation="delete"-->
  </metricbeat>
</metricbeats>
</elk>

```

### Command Syntax

```
elk server metricbeat A.B.C.D username USERNAME password PASSWORD
```

---

## Configure certificate path

Used to configure Filebeat server path to certificate file

Attribute Name: certificate-path

Attribute Type: string

### Netconf edit-config payload

```
<elk xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-elk">
  <filebeats>
    <filebeat>
      <ip>A.B.C.D</ip>
      <config>
        <ip>A.B.C.D</ip>
      </config>
      <certificate-path>FILE-PATH</certificate-path> <!-- operation="delete"-->
    </filebeat>
  </filebeats>
</elk>
```

### Command Syntax

```
elk server filebeat A.B.C.D FILE-PATH
```

---

## service enable metricbeat (vrf management|)

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<elk-metricbeat-service-enable xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
elk">
  <vrf-name>management</vrf-name>
</elk-metricbeat-service-enable>
```

### Command Syntax

```
service enable metricbeat (vrf management|)
```

---

## service enable filebeat (vrf management|)

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<elk-filebeat-service-enable xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-
elk">
  <vrf-name>management</vrf-name>
</elk-filebeat-service-enable>
```

---

## Command Syntax

```
service enable filebeat (vrf management|)
```

---

## service disable metricbeat (vrf management|)

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<elk-metricbeat-service-disable xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-  
elk">  
  <vrf-name>management</vrf-name>  
</elk-metricbeat-service-disable>
```

## Command Syntax

```
service disable metricbeat (vrf management|)
```

---

## service disable filebeat (vrf management|)

Attribute Name: vrf-name

Attribute Type: string

### Netconf RPC payload

```
<elk-filebeat-service-disable xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-  
elk">  
  <vrf-name>management</vrf-name>  
</elk-filebeat-service-disable>
```

## Command Syntax

```
service disable filebeat (vrf management|)
```

---

# IPI-IPSEC

---

## Configure transform set name

IPsec transform-set name

This command is supported when following feature are enabled IPsec feature

Attribute Name: transform-set-name

Attribute Type: string

Attribute Range: 1-127

### Netconf edit-config payload

```
<ipsec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipsec">  
  <transform-sets>  
    <transform-set> <!-- operation="delete"-->
```

```

    <transform-set-name>NAME</transform-set-name>
  <config>
    <transform-set-name>NAME</transform-set-name>
  </config>
</transform-set>
</transform-sets>
</ipsec>

```

### Command Syntax

```
crypto ipsec transform-set NAME
```

---

## Configure transform set mode

This attribute is used to configure mode for a transform-set.

This command is supported when following feature are enabled IPsec feature

Attribute Name: transform-set-mode

Attribute Type: enum (transport)

Default Value: transport

### Netconf edit-config payload

```

<ipsec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipsec">
  <transform-sets>
    <transform-set>
      <transform-set-name>NAME</transform-set-name>
      <config>
        <transform-set-name>NAME</transform-set-name>
      </config>
      <transform-set-mode>transport</transform-set-mode> <!-- operation="delete"-->
    </transform-set>
  </transform-sets>
</ipsec>

```

### Command Syntax

```
crypto ipsec transform-set NAME mode (transport)
```

---

## Configure ah authentication

This attribute configures IPsec AH authentication type.

This command is supported when following feature are enabled IPsec feature

Attribute Name: ah-authentication

Attribute Type: enum (none|ah-md5|ah-sha1|ah-sha256|ah-sha384|ah-sha512)

### Netconf edit-config payload

```

<ipsec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipsec">
  <transform-sets>
    <transform-set>
      <transform-set-name>NAME</transform-set-name>

```

```

    <config>
      <transform-set-name>NAME</transform-set-name>
    </config>
  <ah-auth>
    <config>
      <ah-authentication>none</ah-authentication> <!-- operation="delete"-->
    </config>
  </ah-auth>
</transform-set>
</transform-sets>
</ipsec>

```

### Command Syntax

```
crypto ipsec transform-set NAME ah (none|ah-md5|ah-sha1|ah-sha256|ah-sha384|ah-sha512)
```

---

## Configure ah-auth ah-authentication

This attribute configures IPsec AH authentication type.

This command is supported when following feature are enabled IPsec feature

Attribute Name: ah-authentication

Attribute Type: enum (none|ah-md5|ah-sha1|ah-sha256|ah-sha384|ah-sha512)

### Netconf edit-config payload

```

<ipsec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipsec">
  <transform-sets>
    <transform-set>
      <transform-set-name>NAME</transform-set-name>
      <config>
        <transform-set-name>NAME</transform-set-name>
      </config>
    <ah-auth>
      <config>
        <ah-authentication>none</ah-authentication> <!-- operation="delete"-->
      </config>
    </ah-auth>
  </transform-set>
</transform-sets>
</ipsec>

```

### Command Syntax

```
crypto ipsec transform-set NAME ah (none|ah-md5|ah-sha1|ah-sha256|ah-sha384|ah-sha512)
```

---

## Configure esp encryption

This attribute configures IPsec ESP encryption type.

This command is supported when following feature are enabled IPsec feature

Attribute Name: esp-encryption

Attribute Type: enum (esp-null|esp-3des|esp-cast|esp-blf|esp-blf192|esp-blf256|esp-aes|esp-aes192|esp-aes256)

Attribute Name: esp-authentication

Attribute Type: enum (none|esp-md5|esp-sha1|esp-sha256|esp-sha384|esp-sha512)

### Netconf edit-config payload

```
<ipsec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipsec">
  <transform-sets>
  <transform-set>
    <transform-set-name>NAME</transform-set-name>
    <config>
      <transform-set-name>NAME</transform-set-name>
    </config>
  <esp-auth>
  <config>
    <esp-authentication>none</esp-authentication>
    <esp-encryption>esp-null</esp-encryption>
  </config>
</esp-auth>
</transform-set>
</transform-sets>
</ipsec>
```

### Command Syntax

```
crypto ipsec transform-set NAME esp-auth (none|esp-md5|esp-sha1|esp-sha256|esp-
sha384|esp-sha512) esp-enc (esp-null|esp-3des|esp-cast|esp-blf|esp-blf192|esp-
blf256|esp-aes|esp-aes192|esp-aes256)
```

---

## Configure esp authentication

This attribute configures IPsec ESP authentication type.

This command is supported when following feature are enabled IPsec feature

Attribute Name: esp-authentication

Attribute Type: enum (none|esp-md5|esp-sha1|esp-sha256|esp-sha384|esp-sha512)

Attribute Name: esp-encryption

Attribute Type: enum (esp-null|esp-3des|esp-cast|esp-blf|esp-blf192|esp-blf256|esp-aes|esp-aes192|esp-aes256)

### Netconf edit-config payload

```
<ipsec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipsec">
  <transform-sets>
  <transform-set>
    <transform-set-name>NAME</transform-set-name>
    <config>
      <transform-set-name>NAME</transform-set-name>
    </config>
  <esp-auth>
  <config>
```

```

    <esp-encryption>esp-null</esp-encryption>
    <esp-authentication>none</esp-authentication>
</config>
</esp-auth>
</transform-set>
</transform-sets>
</ipsec>

```

## Command Syntax

```

crypto ipsec transform-set NAME esp-auth (none|esp-md5|esp-sha1|esp-sha256|esp-
sha384|esp-sha512) esp-enc (esp-null|esp-3des|esp-cast|esp-blf|esp-blf192|esp-
blf256|esp-aes|esp-aes192|esp-aes256)

```

---

## Configure name

IPsec Crypto Map name

This command is supported when following feature are enabled IPsec feature

Attribute Name: name

Attribute Type: string

Attribute Range: 1-127

Attribute Name: sa-type

Attribute Type: enum (ipsec-manual)

## Netconf edit-config payload

```

<ipsec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipsec">
  <crypto-maps>
    <crypto-map> <!-- operation="delete"-->
      <name>MAP-NAME</name>
      <config>
        <name>WORD</name>
        <sa-type>ipsec-manual</sa-type>
      </config>
    </crypto-map>
  </crypto-maps>
</ipsec>

```

## Command Syntax

```

crypto map MAP-NAME (ipsec-manual)

```

---

## Configure sequence id

Map sequence-id

This command is supported when following feature are enabled IPsec feature

Attribute Name: sequence-id

Attribute Type: uint16

Attribute Range: 1-65535

**Netconf edit-config payload**

```

<ipsec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipsec">
  <crypto-maps>
    <crypto-map>
      <name>MAP-NAME</name>
      <config>
        <name>WORD</name>
      </config>
    </crypto-map>
  </crypto-maps>
  <sessions>
    <session> <!-- operation="delete"-->
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
    </session>
  </sessions>
</ipsec>

```

**Command Syntax**

```
sequence <1-65535>
```

**Configure transform-sets transform-set-name**

Map session transform-set name

This command is supported when following feature are enabled IPsec feature

Attribute Name: transform-set-name

Attribute Type: string

Attribute Range: 1-127

**Netconf edit-config payload**

```

<ipsec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipsec">
  <crypto-maps>
    <crypto-map>
      <name>MAP-NAME</name>
      <config>
        <name>WORD</name>
      </config>
    </crypto-map>
  </crypto-maps>
  <sessions>
    <session>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <transform-sets>
        <transform-set> <!-- operation="delete"-->
          <transform-set-name>NAME</transform-set-name>
        </transform-set>
      </transform-sets>
    </session>
  </sessions>
</ipsec>

```

```

    <config>
      <transform-set-name>WORD</transform-set-name>
    </config>
  </transform-set>
</transform-sets>
</session>
</sessions>
</crypto-map>
</crypto-maps>
</ipsec>

```

## Command Syntax

```
set transform-set NAME
```

---

## Configure peer

Map session peer IP address

This command is supported when following feature are enabled IPsec feature

Attribute Name: peer

Attribute Type: inet:ip-address

Attribute Name: spi

Attribute Type: uint16

## Netconf edit-config payload

```

<ipsec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipsec">
  <crypto-maps>
    <crypto-map>
      <name>MAP-NAME</name>
      <config>
        <name>WORD</name>
      </config>
    </sessions>
    <session>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <peer-addresses>
        <peer-address> <!-- operation="delete"-->
          <peer>A.B.C.D</peer>
          <config>
            <peer>CML_IP_ADDR_T</peer>
            <spi>0</spi>
          </config>
        </peer-address>
      </peer-addresses>
    </session>
  </sessions>

```

```

</crypto-map>
</crypto-maps>
</ipsec>

```

## Command Syntax

```
set peer (A.B.C.D|X:X::X:X) (spi <0-4096>|)
```

---

## Configure security parameter index

Crypto Map session key security parameter index (SPI)

This command is supported when following feature are enabled IPsec feature

Attribute Name: security-parameter-index

Attribute Type: uint16

Attribute Range: 0-4096

Attribute Name: cipher

Attribute Type: string

Attribute Range: 1-128

Attribute Name: authentication-key

Attribute Type: string

Attribute Range: 1-32

## Netconf edit-config payload

```

<ipsec xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-ipsec">
  <crypto-maps>
    <crypto-map>
      <name>MAP-NAME</name>
      <config>
        <name>WORD</name>
      </config>
    </crypto-map>
  </crypto-maps>
  <sessions>
    <session>
      <sequence-id>1</sequence-id>
      <config>
        <sequence-id>1</sequence-id>
      </config>
      <session-keys>
        <session-key> <!-- operation="delete"-->
          <security-parameter-index>0</security-parameter-index>
          <config>
            <security-parameter-index>0</security-parameter-index>
            <protocol>esp</protocol>
            <direction>inbound</direction>
            <cipher>HEX-KEY-DATA</cipher>
            <authentication-key>HEX-KEY-DATA</authentication-key>
          </config>
          <protocol>esp</protocol>
        </session-key>
      </session-keys>
    </session>
  </sessions>
</ipsec>

```

```

        <direction>inbound</direction>
    </session-key>
</session-keys>
</session>
</sessions>
</crypto-map>
</crypto-maps>
</ipsec>

```

### Command Syntax

```

set session-key (inbound|outbound) (esp) <0-4096> cipher HEX-KEY-DATA authenticator
HEX-KEY-DATA

```

---

## IPI-HOST

---

### Configure disable service advanced vty

Use this attribute to enable advanced mode vty interface.

Attribute Name: disable-service-advanced-vty

Attribute Type: uint8

#### Netconf edit-config payload

```

<system-host xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-host">
  <config>
    </disable-service-advanced-vty><!-- operation="delete"-->
  </config>
</system-host>

```

### Command Syntax

```

no service advanced-vty

```

---

### Configure service passwd encryption

Use this attribute to enable password encryption.

Attribute Name: service-passwd-encryption

Attribute Type: boolean

Default Value: true

#### Netconf edit-config payload

```

<system-host xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-host">
  <config>
    <service-passwd-encryption>true</service-passwd-encryption> <!--
operation="delete"-->
  </config>
</system-host>

```

---

## Command Syntax

```
service password-encryption
```

---

## Configure system-host service-passwd-encryption

Use this attribute to enable password encryption.

Attribute Name: service-passwd-encryption

Attribute Type: boolean

Default Value: true

### Netconf edit-config payload

```
<system-host xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-host">
  <config>
    <service-passwd-encryption>true</service-passwd-encryption> <!--
operation="delete"-->
  </config>
</system-host>
```

## Command Syntax

```
no service password-encryption
```

---

## Configure passwd encrypted

Use this attribute to provide encrypted password.

Attribute Name: passwd-encrypted

Attribute Type: uint8

Attribute Name: system-enable-passwd

Attribute Type: string

### Netconf edit-config payload

```
<system-host xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-host">
  <config>
    <system-enable-passwd>LINE</system-enable-passwd> <!-- operation="delete"-->
    </passwd-encrypted><!-- operation="delete"-->
  </config>
</system-host>
```

## Command Syntax

```
enable password (8|) LINE
```

---

## Configure banner motd

Use this attribute to set the login banner for the OcNOS device.

This command is supported when following feature are enabled IMI feature

Attribute Name: banner-motd

Attribute Type: union

### Netconf edit-config payload

```
<system-host xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-host">
  <config>
    <banner-motd>CML_BANNER_T</banner-motd>
  </config>
</system-host>
```

### Command Syntax

```
banner motd (LINE|default)
```

---

## Configure banner motd file

Use this attribute to set the filename containing the banner message

This command is supported when following feature are enabled IMI feature

Attribute Name: banner-motd-file

Attribute Type: string

### Netconf edit-config payload

```
<system-host xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-host">
  <config>
    <banner-motd-file>FILENAME</banner-motd-file> <!-- operation="delete"-->
  </config>
</system-host>
```

### Command Syntax

```
banner motd file FILENAME
```

---

## Configure service term length

Use this attribute to set system wide terminal length.

This command is supported when following feature are enabled IMI feature

Attribute Name: service-term-length

Attribute Type: uint16

Attribute Range: 0-512

### Netconf edit-config payload

```
<system-host xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-host">
  <config>
    <service-term-length>0</service-term-length> <!-- operation="delete"-->
  </config>
</system-host>
```

### Command Syntax

```
service terminal-length <0-512>
```

## Configure disable default autoenable

Use this attribute to disable auto enable feature based on the user role which is happening by default for remote authentication.

This command is supported when following feature are enabled IMI feature

Attribute Name: disable-default-autoenable

Attribute Type: empty

### Netconf edit-config payload

```
<system-host xmlns="http://www.ipinfusion.com/yang/ocnos/ipi-host">
  <config>
    </disable-default-autoenable><!-- operation="delete"-->
  </config>
</system-host>
```

### Command Syntax

```
disable default auto-enable
```



---

## CHAPTER 2 PYANG Tree

---

### module: ipi-aaa

```

+--rw aaa
  +--rw vrfs
    | +--rw vrf* [vrf-name]
    |   +--rw vrf-name    -> ../config/vrf-name
    |   +--rw config
    |     | +--rw vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
    |     | +--rw authentication-method-rule?  cml-data-types:cml_line_t
    |     | +--rw accounting-method-rule?     cml-data-types:cml_line_t
    |     | +--rw authorization-method-rule?  cml-data-types:cml_line_t
    |     | +--rw enable-fallback?           empty
    |     | +--rw non-existent?              boolean
    |     | +--rw error-enable?              empty
    |     +--ro state
    |     | +--ro vrf-name?                  -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
    |     | +--ro authentication-method-rule? cml-data-types:cml_line_t
    |     | +--ro accounting-method-rule?     cml-data-types:cml_line_t
    |     | +--ro authorization-method-rule?  cml-data-types:cml_line_t
    |     | +--ro enable-fallback?           empty
    |     | +--ro non-existent?              boolean
    |     | +--ro error-enable?              empty
    |     +--rw server-groups
    |       +--rw server-group* [group-type group-name]
    |         +--rw group-type    -> ../config/group-type
    |         +--rw group-name    -> ../config/group-name
    |         +--rw config
    |           | +--rw group-type? ipi-aaa-types:aaa_server_grp_type_t
    |           | +--rw group-name? string
    |           +--ro state
    |           | +--ro group-type? ipi-aaa-types:aaa_server_grp_type_t
    |           | +--ro group-name? string

```

---

```
|     +--rw server-addresses
|     +--rw server-address* [host-address]
|     +--rw host-address  -> ../config/host-address
|     +--rw config
|         | +--rw host-address?  cml-data-types:cml_hostname_t
|         +--ro state
|             +--ro host-address?  cml-data-types:cml_hostname_t
+--rw aaa-authentication-console
| +--rw config
| | +--rw authentication-method-rule?  cml-data-types:cml_line_t
| | +--rw enable-fallback?            boolean
| | +--rw authorization-method-rule?  cml-data-types:cml_line_t
| | +--rw accounting-method-rule?    cml-data-types:cml_line_t
| | +--rw user-non-existent?         boolean
| +--ro state
|     +--ro authentication-method-rule?  cml-data-types:cml_line_t
|     +--ro enable-fallback?            boolean
|     +--ro authorization-method-rule?  cml-data-types:cml_line_t
|     +--ro accounting-method-rule?    cml-data-types:cml_line_t
|     +--ro user-non-existent?         boolean
+--rw aaa-user
| +--rw config
| | +--rw authentication-max-failure-attempts?  uint8
| | +--rw local-user-unlock-timeout?           uint16
| +--ro state
| | +--ro authentication-max-failure-attempts?  uint8
| | +--ro local-user-unlock-timeout?           uint16
| +--rw password-policy
|     +--rw config
|         | +--rw enable?            empty
|         | +--rw numeric-count?    uint8
|         | +--rw uppercase-count?  uint8
|         | +--rw lowercase-count?  uint8
|         | +--rw special-count?    uint8
|         | +--rw history?          uint16
|         | +--rw maxsequence?     uint8
```

---

```
| | +--rw disable-usercheck? empty
| | +--rw maxrepeat?      uint8
| | +--rw min-length?    uint8
| +--ro state
| | +--ro enable?        empty
| | +--ro numeric-count? uint8
| | +--ro uppercase-count? uint8
| | +--ro lowercase-count? uint8
| | +--ro special-count? uint8
| | +--ro history?       uint16
| | +--ro maxsequence?   uint8
| | +--ro disable-usercheck? empty
| | +--ro maxrepeat?     uint8
| | +--ro min-length?    uint8
| +--rw role-expdays
| | +--rw role-expday* [role]
| |   +--rw role  -> ../config/role
| |   +--rw config
| |     | +--rw expire? uint16
| |     | +--rw role?   ipi-user-management-types:user_mgmt_role_types_t
| |     | +--rw user?   string
| |     +--ro state
| |       +--ro expire? uint16
| |       +--ro role?   ipi-user-management-types:user_mgmt_role_types_t
| |       +--ro user?   string
| +--rw user-expdays
|   +--rw user-expday* [user]
|     +--rw user  -> ../config/user
|     +--rw config
|       | +--rw expire? uint16
|       | +--rw role?   ipi-user-management-types:user_mgmt_role_types_t
|       | +--rw user?   string
|       +--ro state
|         +--ro expire? uint16
|         +--ro role?   ipi-user-management-types:user_mgmt_role_types_t
|         +--ro user?   string
```

```

+--rw debug
  +--rw config
  | +--rw enable?  empty
  +--ro state
    +--ro enable?          empty
    +--ro terminal-debug-status?  cml-data-types:cml_on_off_t

```

rpcs:

```

+---x aaa-terminal-debug-on {feature-list:HAVE_HOSTPD,feature-list:HAVE_AAA}?
+---x aaa-terminal-debug-off {feature-list:HAVE_HOSTPD,feature-list:HAVE_AAA}?
+---x aaa-clear-local-user-lockout {feature-list:HAVE_AAA}?
  +---w input
    +---w username  string

```

---

## module: ipi-acl

```

+--rw acl
  +--rw acl-sets
  | +--rw acl-set* [name type]
  |   +--rw name      -> ../config/name
  |   +--rw type      -> ../config/type
  |   +--rw config
  |   | +--rw name?          string
  |   | +--rw type?         ipi-acl-types:acl_types_t
  |   | +--rw description?   cml-data-types:cml_line_t
  |   | +--rw ipv6-disable-default-icmpv6-rule?  empty
  |   +--ro state
  |   | +--ro name?         string
  |   | +--ro type?        ipi-acl-types:acl_types_t
  |   | +--ro description?  cml-data-types:cml_line_t

```

---

```

| | +-ro ipv6-disable-default-icmpv6-rule? empty
| +-rw default-actions
| | +-rw config
| | | +-rw forwarding-action-default? ipi-acl-types:acl_default_forwarding_action_t
| | | +-rw monitor-action-default? ipi-acl-types:acl_monitor_action_t {feature-list:HAVE_SFLOW,feature-
list:HAVE_CUSTOM1_ACL}?
| | +-ro state
| | +-ro counters
| | | +-ro matched-packets? yang:counter64
| | +-ro forwarding-action-default? ipi-acl-types:acl_default_forwarding_action_t
| | +-ro monitor-action-default? ipi-acl-types:acl_monitor_action_t {feature-list:HAVE_SFLOW,feature-
list:HAVE_CUSTOM1_ACL}?
| +-rw acl-entries
| | +-rw acl-entry* [sequence-id]
| | +-rw sequence-id -> ../config/sequence-id
| | +-rw config
| | | +-rw sequence-id? uint32
| | +-ro state
| | | +-ro sequence-id? uint32
| | +-rw ipv4
| | | +-rw config
| | | | +-rw forwarding-action? ipi-acl-types:acl_forwarding_action_t
| | | | +-rw vlan-id? uint16
| | | | +-rw monitor-action? ipi-acl-types:acl_monitor_action_t {feature-list:HAVE_SFLOW,feature-
list:HAVE_CUSTOM1_ACL}?
| | | | +-rw source-address? ipi-acl-types:acl_any_ipv4_src_addr_t
| | | | +-rw destination-address? ipi-acl-types:acl_any_ipv4_dest_addr_t
| | | | +-rw dscp? ipi-acl-types:acl_dscp_t
| | | | +-rw precedence? ipi-acl-types:acl_precedence_t
| | | | +-rw inner-vlan-id? uint16
| | | | +-rw (protocol)?
| | | | | +-:(tcp)
| | | | | +-rw protocol-tcp? empty
| | | | | +-rw tcp-source-port? ipi-acl-types:acl_tcp_src_port_t
| | | | | +-rw tcp-destination-port? ipi-acl-types:acl_tcp_dest_port_t
| | | | | +-rw tcp-flags? ipi-acl-types:acl_tcp_flags_t
| | | | +-:(udp)

```

---

---

	+--rw protocol-udp?	empty
	+--rw udp-source-port?	ipi-acl-types:acl_udp_src_port_t
	+--rw udp-destination-port?	ipi-acl-types:acl_udp_dest_port_t
	+--:(icmp)	
	+--rw protocol-icmp?	empty
	+--rw icmp-message?	ipi-acl-types:acl_icmp_options_t {feature-list:HAVE_CUSTOM1_ACL}?
	+--rw icmp-type?	uint8 {feature-list:HAVE_CUSTOM1_ACL}?
	+--rw icmp-code?	uint8 {feature-list:HAVE_CUSTOM1_ACL}?
	+--:(other-protocols)	
	+--rw protocol-name?	ipi-acl-types:acl_ip_protocols_t
	+--rw source-port-operator?	ipi-acl-types:acl_src_port_operations_t
	+--rw lower-source-port-in-range?	uint16
	+--rw upper-source-port-in-range?	uint16
	+--rw destination-port-operator?	ipi-acl-types:acl_dest_port_operations_t
	+--rw lower-destination-port-in-range?	uint16
	+--rw upper-destination-port-in-range?	uint16
	+--rw redirect-interface-name?	string {feature-list:HAVE_CUSTOM1_ACL}?
	+--rw fragments?	empty {feature-list:HAVE_CUSTOM1_ACL}?
	+--ro state	
	+--ro counters	
	+--ro matched-packets?	yang:counter64
	+--ro forwarding-action?	ipi-acl-types:acl_forwarding_action_t
	+--ro vlan-id?	uint16
	+--ro monitor-action?	ipi-acl-types:acl_monitor_action_t {feature-list:HAVE_SFLOW,feature-list:HAVE_CUSTOM1_ACL}?
	+--ro source-address?	ipi-acl-types:acl_any_ipv4_src_addr_t
	+--ro destination-address?	ipi-acl-types:acl_any_ipv4_dest_addr_t
	+--ro dscp?	ipi-acl-types:acl_dscp_t
	+--ro precedence?	ipi-acl-types:acl_precedence_t
	+--ro inner-vlan-id?	uint16
	+--ro (protocol)?	
	+--:(tcp)	
	+--ro protocol-tcp?	empty
	+--ro tcp-source-port?	ipi-acl-types:acl_tcp_src_port_t
	+--ro tcp-destination-port?	ipi-acl-types:acl_tcp_dest_port_t
	+--ro tcp-flags?	ipi-acl-types:acl_tcp_flags_t
	+--:(udp)	

---

---

```

| | | | | +--ro protocol-udp?          empty
| | | | | +--ro udp-source-port?      ipi-acl-types:acl_udp_src_port_t
| | | | | +--ro udp-destination-port?  ipi-acl-types:acl_udp_dest_port_t
| | | | | +--:(icmp)
| | | | | +--ro protocol-icmp?        empty
| | | | | +--ro icmp-message?         ipi-acl-types:acl_icmp_options_t {feature-list:HAVE_CUSTOM1_ACL}?
| | | | | +--ro icmp-type?            uint8 {feature-list:HAVE_CUSTOM1_ACL}?
| | | | | +--ro icmp-code?            uint8 {feature-list:HAVE_CUSTOM1_ACL}?
| | | | | +--:(other-protocols)
| | | | | +--ro protocol-name?         ipi-acl-types:acl_ip_protocols_t
| | | | | +--ro source-port-operator?  ipi-acl-types:acl_src_port_operations_t
| | | | | +--ro lower-source-port-in-range?  uint16
| | | | | +--ro upper-source-port-in-range?  uint16
| | | | | +--ro destination-port-operator?  ipi-acl-types:acl_dest_port_operations_t
| | | | | +--ro lower-destination-port-in-range?  uint16
| | | | | +--ro upper-destination-port-in-range?  uint16
| | | | | +--ro redirect-interface-name?    string {feature-list:HAVE_CUSTOM1_ACL}?
| | | | | +--ro fragments?                empty {feature-list:HAVE_CUSTOM1_ACL}?
| | | | +--rw fragment-actions {feature-list:HAVE_CUSTOM1_ACL}?
| | | |   +--rw config
| | | | | +--rw fragment-forwarding-action? ipi-acl-types:acl_fragment_forwarding_action_t {feature-
list:HAVE_CUSTOM1_ACL}?
| | | | | +--rw fragment-monitor-action?   ipi-acl-types:acl_monitor_action_t {feature-
list:HAVE_SFLOW,feature-list:HAVE_CUSTOM1_ACL}?
| | | |   +--ro state
| | | |   +--ro fragment-forwarding-action? ipi-acl-types:acl_fragment_forwarding_action_t {feature-
list:HAVE_CUSTOM1_ACL}?
| | | |   +--ro fragment-monitor-action?   ipi-acl-types:acl_monitor_action_t {feature-
list:HAVE_SFLOW,feature-list:HAVE_CUSTOM1_ACL}?
| | | +--rw ipv6 {feature-list:HAVE_IPV6}?
| | | | +--rw config
| | | | | +--rw forwarding-action?        ipi-acl-types:acl_forwarding_action_t
| | | | | +--rw vlan-id?                  uint16
| | | | | +--rw monitor-action?          ipi-acl-types:acl_monitor_action_t {feature-list:HAVE_SFLOW,feature-
list:HAVE_CUSTOM1_ACL}?
| | | | | +--rw source-address?          ipi-acl-types:acl_any_ipv6_src_addr_t
| | | | | +--rw destination-address?     ipi-acl-types:acl_any_ipv6_dest_addr_t
| | | | | +--rw dscp?                    ipi-acl-types:acl_dscp_t

```

---

---

```

| | | | +--rw inner-vlan-id?          uint16 {feature-list:HAVE_CUSTOM1_ACL}?
| | | | +--rw flow-label?            uint32 {feature-list:HAVE_CUSTOM1_ACL}?
| | | | +--rw (protocol)?
| | | | | +--:(tcp)
| | | | | | +--rw protocol-tcp?      empty
| | | | | | +--rw tcp-source-port?   ipi-acl-types:acl_tcp_src_port_t
| | | | | | +--rw tcp-destination-port? ipi-acl-types:acl_tcp_dest_port_t
| | | | | | +--rw tcp-flags?        ipi-acl-types:acl_tcp_flags_t {feature-list:HAVE_CUSTOM1_ACL}?
| | | | | | +--:(udp)
| | | | | | +--rw protocol-udp?      empty
| | | | | | +--rw udp-source-port?   ipi-acl-types:acl_udp_src_port_t
| | | | | | +--rw udp-destination-port? ipi-acl-types:acl_udp_dest_port_t
| | | | | | +--:(icmp)
| | | | | | +--rw protocol-icmp?     empty
| | | | | | +--rw icmp-message?      ipi-acl-types:acl_icmpv6_options_t {feature-
list:HAVE_CUSTOM1_ACL}?
| | | | | | +--rw icmp-type?        uint8 {feature-list:HAVE_CUSTOM1_ACL}?
| | | | | | +--rw icmp-code?        uint8 {feature-list:HAVE_CUSTOM1_ACL}?
| | | | | | +--:(sctp)
| | | | | | +--rw protocol-sctp?     empty
| | | | | | +--rw sctp-source-port?  uint16
| | | | | | +--rw sctp-destination-port? uint16
| | | | | | +--:(other-protocols)
| | | | | | +--rw protocol-name?     ipi-acl-types:acl_ipv6_protocols_t
| | | | | +--rw source-port-operator? ipi-acl-types:acl_src_port_operations_t
| | | | | +--rw lower-source-port-in-range? uint16
| | | | | +--rw upper-source-port-in-range? uint16
| | | | | +--rw destination-port-operator? ipi-acl-types:acl_dest_port_operations_t
| | | | | +--rw lower-destination-port-in-range? uint16
| | | | | +--rw upper-destination-port-in-range? uint16
| | | | | +--rw redirect-interface-name? string {feature-list:HAVE_CUSTOM1_ACL}?
| | | | | +--rw fragments?          empty {feature-list:HAVE_CUSTOM1_ACL}?
| | | | +--ro state
| | | | +--ro counters
| | | | | +--ro matched-packets? yang:counter64
| | | | | +--ro forwarding-action?   ipi-acl-types:acl_forwarding_action_t
| | | | +--ro vlan-id?              uint16

```

---

---

```

| | | | +--ro monitor-action?      ipi-acl-types:acl_monitor_action_t {feature-list:HAVE_SFLOW,feature-
list:HAVE_CUSTOM1_ACL}?
| | | | +--ro source-address?      ipi-acl-types:acl_any_ipv6_src_addr_t
| | | | +--ro destination-address?  ipi-acl-types:acl_any_ipv6_dest_addr_t
| | | | +--ro dscp?                 ipi-acl-types:acl_dscp_t
| | | | +--ro inner-vlan-id?        uint16 {feature-list:HAVE_CUSTOM1_ACL}?
| | | | +--ro flow-label?           uint32 {feature-list:HAVE_CUSTOM1_ACL}?
| | | | +--ro (protocol)?
| | | | | +--:(tcp)
| | | | | | +--ro protocol-tcp?     empty
| | | | | | +--ro tcp-source-port?  ipi-acl-types:acl_tcp_src_port_t
| | | | | | +--ro tcp-destination-port? ipi-acl-types:acl_tcp_dest_port_t
| | | | | | +--ro tcp-flags?        ipi-acl-types:acl_tcp_flags_t {feature-list:HAVE_CUSTOM1_ACL}?
| | | | | | +--:(udp)
| | | | | | +--ro protocol-udp?     empty
| | | | | | +--ro udp-source-port?  ipi-acl-types:acl_udp_src_port_t
| | | | | | +--ro udp-destination-port? ipi-acl-types:acl_udp_dest_port_t
| | | | | | +--:(icmp)
| | | | | | +--ro protocol-icmp?    empty
| | | | | | +--ro icmp-message?     ipi-acl-types:acl_icmpv6_options_t {feature-
list:HAVE_CUSTOM1_ACL}?
| | | | | | +--ro icmp-type?        uint8 {feature-list:HAVE_CUSTOM1_ACL}?
| | | | | | +--ro icmp-code?        uint8 {feature-list:HAVE_CUSTOM1_ACL}?
| | | | | | +--:(sctp)
| | | | | | +--ro protocol-sctp?    empty
| | | | | | +--ro sctp-source-port?  uint16
| | | | | | +--ro sctp-destination-port? uint16
| | | | | | +--:(other-protocols)
| | | | | | +--ro protocol-name?    ipi-acl-types:acl_ipv6_protocols_t
| | | | +--ro source-port-operator?  ipi-acl-types:acl_src_port_operations_t
| | | | +--ro lower-source-port-in-range? uint16
| | | | +--ro upper-source-port-in-range? uint16
| | | | +--ro destination-port-operator? ipi-acl-types:acl_dest_port_operations_t
| | | | +--ro lower-destination-port-in-range? uint16
| | | | +--ro upper-destination-port-in-range? uint16
| | | | +--ro redirect-interface-name? string {feature-list:HAVE_CUSTOM1_ACL}?
| | | | +--ro fragments?            empty {feature-list:HAVE_CUSTOM1_ACL}?

```

---

---

```

| | | +--rw fragment-actions {feature-list:HAVE_CUSTOM1_ACL}?
| | |   +--rw config
| | | | +--rw fragment-forwarding-action? ipi-acl-types:acl_fragment_forwarding_action_t {feature-
list:HAVE_CUSTOM1_ACL}?
| | | | +--rw fragment-monitor-action? ipi-acl-types:acl_monitor_action_t {feature-
list:HAVE_SFLOW,feature-list:HAVE_CUSTOM1_ACL}?
| | |   +--ro state
| | |   +--ro fragment-forwarding-action? ipi-acl-types:acl_fragment_forwarding_action_t {feature-
list:HAVE_CUSTOM1_ACL}?
| | |   +--ro fragment-monitor-action? ipi-acl-types:acl_monitor_action_t {feature-
list:HAVE_SFLOW,feature-list:HAVE_CUSTOM1_ACL}?
| |   +--rw arp
| |   +--rw config
| |   | +--rw forwarding-action? ipi-acl-types:acl_forwarding_action_t
| |   | +--rw vlan-id? uint16
| |   | +--rw monitor-action? ipi-acl-types:acl_monitor_action_t {feature-list:HAVE_SFLOW,feature-
list:HAVE_CUSTOM1_ACL}?
| |   | +--rw inner-vlan-id? uint16
| |   | +--rw (source-mac-options)?
| |   | | +--:(any-mac)
| |   | | | +--rw source-mac-any? empty
| |   | | | +--:(host-mac)
| |   | | | +--rw source-mac-host? ipi-acl-types:acl_mac_addr_t
| |   | | | +--:(mac-with-mask)
| |   | | | +--rw source-mac-address? ipi-acl-types:acl_mac_addr_t
| |   | | | +--rw source-mac-mask? ipi-acl-types:acl_mac_addr_t
| |   | | +--rw arp-packet-type? ipi-acl-types:acl_arp_type_t
| |   | | +--rw source-ip-address? ipi-acl-types:acl_any_ipv4_src_addr_t
| |   | | +--rw destination-ip-address? ipi-acl-types:acl_any_ipv4_dest_addr_t
| |   | | +--rw (destination-mac-options)?
| |   | | +--:(any-mac)
| |   | | | +--rw destination-mac-any? empty
| |   | | | +--:(host-mac)
| |   | | | +--rw destination-mac-host? ipi-acl-types:acl_mac_addr_t
| |   | | | +--:(mac-with-mask)
| |   | | | +--rw destination-mac-address? ipi-acl-types:acl_mac_addr_t
| |   | | | +--rw destination-mac-mask? ipi-acl-types:acl_mac_addr_t
| |   | +--ro state

```

---

---

```

| | | +--ro counters
| | | | +--ro matched-packets? yang:counter64
| | | +--ro forwarding-action?      ipi-acl-types:acl_forwarding_action_t
| | | +--ro vlan-id?                uint16
| | | +--ro monitor-action?         ipi-acl-types:acl_monitor_action_t {feature-list:HAVE_SFLOW,feature-
list:HAVE_CUSTOM1_ACL}?
| | | +--ro inner-vlan-id?          uint16
| | | +--ro (source-mac-options)?
| | | | +--:(any-mac)
| | | | | +--ro source-mac-any?      empty
| | | | | +--:(host-mac)
| | | | | +--ro source-mac-host?     ipi-acl-types:acl_mac_addr_t
| | | | | +--:(mac-with-mask)
| | | | | +--ro source-mac-address?  ipi-acl-types:acl_mac_addr_t
| | | | | +--ro source-mac-mask?     ipi-acl-types:acl_mac_addr_t
| | | +--ro arp-packet-type?        ipi-acl-types:acl_arp_type_t
| | | +--ro source-ip-address?       ipi-acl-types:acl_any_ipv4_src_addr_t
| | | +--ro destination-ip-address?  ipi-acl-types:acl_any_ipv4_dest_addr_t
| | | +--ro (destination-mac-options)?
| | | | +--:(any-mac)
| | | | | +--ro destination-mac-any?  empty
| | | | | +--:(host-mac)
| | | | | +--ro destination-mac-host? ipi-acl-types:acl_mac_addr_t
| | | | | +--:(mac-with-mask)
| | | | | +--ro destination-mac-address? ipi-acl-types:acl_mac_addr_t
| | | | | +--ro destination-mac-mask?  ipi-acl-types:acl_mac_addr_t
| | +--rw mac
| | +--rw config
| | | +--rw forwarding-action?       ipi-acl-types:acl_forwarding_action_t
| | | +--rw vlan-id?                uint16
| | | +--rw monitor-action?         ipi-acl-types:acl_monitor_action_t {feature-list:HAVE_SFLOW,feature-
list:HAVE_CUSTOM1_ACL}?
| | | +--rw inner-vlan-id?          uint16
| | | +--rw (source-mac-options)?
| | | | +--:(any-mac)
| | | | | +--rw source-mac-any?      empty
| | | | | +--:(host-mac)

```

---

```

| | | | +--rw source-mac-host?      ipi-acl-types:acl_mac_addr_t
| | | | +--:(mac-with-mask)
| | | | +--rw source-mac-address?   ipi-acl-types:acl_mac_addr_t
| | | | +--rw source-mac-mask?     ipi-acl-types:acl_mac_addr_t
| | | | +--rw ethertype?           ipi-acl-types:acl_ether_type_t
| | | | +--rw arp-packet-type?     ipi-acl-types:acl_arp_packet_type_t
| | | | +--rw cos-value?           uint8
| | | | +--rw (destination-mac-options)?
| | | |   +--:(any-mac)
| | | | | +--rw destination-mac-any?  empty
| | | | | +--:(host-mac)
| | | | | +--rw destination-mac-host? ipi-acl-types:acl_mac_addr_t
| | | | | +--:(mac-with-mask)
| | | | |   +--rw destination-mac-address? ipi-acl-types:acl_mac_addr_t
| | | | |   +--rw destination-mac-mask?  ipi-acl-types:acl_mac_addr_t
| | | +--ro state
| | |   +--ro counters
| | |     | +--ro matched-packets? yang:counter64
| | |     +--ro forwarding-action?   ipi-acl-types:acl_forwarding_action_t
| | |     +--ro vlan-id?             uint16
| | |     +--ro monitor-action?     ipi-acl-types:acl_monitor_action_t {feature-list:HAVE_SFLOW,feature-
list:HAVE_CUSTOM1_ACL}?
| | |     +--ro inner-vlan-id?       uint16
| | |     +--ro (source-mac-options)?
| | |       | +--:(any-mac)
| | |       | | +--ro source-mac-any?  empty
| | |       | | +--:(host-mac)
| | |       | | +--ro source-mac-host? ipi-acl-types:acl_mac_addr_t
| | |       | | +--:(mac-with-mask)
| | |       |   +--ro source-mac-address? ipi-acl-types:acl_mac_addr_t
| | |       |   +--ro source-mac-mask?  ipi-acl-types:acl_mac_addr_t
| | |       +--ro ethertype?         ipi-acl-types:acl_ether_type_t
| | |       +--ro arp-packet-type?   ipi-acl-types:acl_arp_packet_type_t
| | |       +--ro cos-value?         uint8
| | |       +--ro (destination-mac-options)?
| | |         +--:(any-mac)
| | |         | +--ro destination-mac-any?  empty

```

---

```

| |      +--:(host-mac)
| |      | +--ro destination-mac-host?   ipi-acl-types:acl_mac_addr_t
| |      +--:(mac-with-mask)
| |      +--ro destination-mac-address? ipi-acl-types:acl_mac_addr_t
| |      +--ro destination-mac-mask?   ipi-acl-types:acl_mac_addr_t
| +--ro summary-info
|   +--ro state
|     +--ro counters
|       | +--ro total-acl-entries?  yang:counter32
|       | +--ro statistics-enabled? empty
|     +--ro interfaces
|       +--ro interface* [interface-name]
|         +--ro interface-name  -> ../state/interface-name
|         +--ro state
|           +--ro interface-name?  -> /ipi-interface:interfaces/interface/name
|           +--ro filter-direction? ipi-acl-types:acl_filter_direction_t
|           +--ro interface-type?   ipi-acl-types:acl_interface_type_t
|           +--ro interface-status? ipi-acl-types:acl_interface_status_t
|     +--ro vty-line
|       +--ro state
|         +--ro filter-direction? ipi-acl-types:acl_filter_direction_t
+--rw standard-acl-sets
| +--rw standard-acl-set* [name type]
|   +--rw name          -> ../config/name
|   +--rw type          -> ../config/type
|   +--rw config
|     | +--rw name?  string
|     | +--rw type? ipi-acl-types:acl_standard_types_t
|     +--ro state
|       | +--ro name?  string
|       | +--ro type? ipi-acl-types:acl_standard_types_t
|     +--rw ipv4-acl-entries
|       | +--rw ipv4-acl-entry* [source-address]
|       |   +--rw source-address  -> ../config/source-address
|       |   +--rw config
|       | | +--rw source-address? ipi-acl-types:acl_any_ipv4_src_addr_t

```

---

```
| | | +--rw forwarding-action ipi-acl-types:acl_forwarding_action_t
| | +--ro state
| | +--ro source-address? ipi-acl-types:acl_any_ipv4_src_addr_t
| | +--ro forwarding-action ipi-acl-types:acl_forwarding_action_t
| +--rw ipv6-acl-entries {feature-list:HAVE_IPV6}?
|   +--rw ipv6-acl-entry* [source-address]
|     +--rw source-address -> ../config/source-address
|     +--rw config
|       | +--rw source-address? ipi-acl-types:acl_any_ipv6_src_addr_t
|       | +--rw forwarding-action ipi-acl-types:acl_forwarding_action_t
|       +--ro state
|         +--ro source-address? ipi-acl-types:acl_any_ipv6_src_addr_t
|         +--ro forwarding-action ipi-acl-types:acl_forwarding_action_t
+--rw interfaces
| +--rw interface* [name]
|   +--rw name -> ../config/name
|   +--rw config
|     | +--rw name? -> /ipi-interface:interfaces/interface/name
|     +--ro state
|     | +--ro name? -> /ipi-interface:interfaces/interface/name
|     +--rw ingress-acl-sets
|       | +--rw ingress-acl-set* [acl-type]
|       |   +--rw acl-type -> ../config/acl-type
|       |   +--rw config
|       |     | +--rw acl-type? ipi-acl-types:acl_types_t
|       |     +--ro state
|       |     | +--ro acl-type? ipi-acl-types:acl_types_t
|       |     +--rw access-groups
|       |       +--rw access-group* [acl-name]
|       |         +--rw acl-name -> ../config/acl-name
|       |         +--rw config
|       |           | +--rw acl-name? string
|       |           | +--rw time-range? string
|       |           +--ro state
|       |             +--ro acl-name? string
|       |             +--ro time-range? string
```

```
| +--rw egress-acl-sets
|   +--rw egress-acl-set* [acl-type]
|     +--rw acl-type    -> ../config/acl-type
|     +--rw config
|       | +--rw acl-type? ipi-acl-types:acl_types_t
|       +--ro state
|         | +--ro acl-type? ipi-acl-types:acl_types_t
|         +--rw access-groups
|           +--rw access-group* [acl-name]
|             +--rw acl-name  -> ../config/acl-name
|             +--rw config
|               | +--rw acl-name?  string
|               | +--rw time-range? string
|               +--ro state
|                 +--ro acl-name?  string
|                 +--ro time-range? string
+--rw vty-line
  +--rw ingress-acl-sets
  | +--rw ingress-acl-set* [acl-type]
  | +--rw acl-type  -> ../config/acl-type
  | +--rw config
  | | +--rw acl-type? ipi-acl-types:acl_vty_types_t
  | | +--rw acl-name? string
  | +--ro state
  | +--ro acl-type? ipi-acl-types:acl_vty_types_t
  | +--ro acl-name? string
+--rw egress-acl-sets
  +--rw egress-acl-set* [acl-type]
  +--rw acl-type  -> ../config/acl-type
  +--rw config
  | +--rw acl-type? ipi-acl-types:acl_vty_types_t
  | +--rw acl-name? string
  +--ro state
  +--ro acl-type? ipi-acl-types:acl_vty_types_t
  +--ro acl-name? string
```

rpcs:

```
+---x clear-access-list-counters-all {feature-list:HAVE_ACL}?
+---x clear-access-list-counters {feature-list:HAVE_ACL}?
| +---w input
|   +---w name   string
+---x clear-ip-access-list-counters-all {feature-list:HAVE_ACL}?
+---x clear-ip-access-list-counters {feature-list:HAVE_ACL}?
| +---w input
|   +---w name   string
+---x clear-ipv6-access-list-counters-all {feature-list:HAVE_IPV6}?
+---x clear-ipv6-access-list-counters {feature-list:HAVE_IPV6}?
| +---w input
|   +---w name   string
+---x clear-mac-access-list-counters-all {feature-list:HAVE_ACL}?
+---x clear-mac-access-list-counters {feature-list:HAVE_ACL}?
| +---w input
|   +---w name   string
+---x clear-arp-access-list-counters-all {feature-list:HAVE_ACL}?
+---x clear-arp-access-list-counters {feature-list:HAVE_ACL}?
    +---w input
        +---w name   string
```

---

## module: ipi-alarms

```
+--rw alarms
+--ro alarm* [id]
  +--ro id    -> ../state/id
  +--ro state
    +--ro id?          string
    +--ro resource?   string
    +--ro text?       string
    +--ro time-created? uint64
    +--ro alarm-reported-timestamp? ipi-alarms-types:alarm_date_time_t
    +--ro alarm-severity? ipi-alarms-types:alarm_severity_t
    +--ro type-id?     ipi-alarms-types:alarm_type_id_t
```

augment /ipi-platform:components/ipi-platform:component/ipi-platform:state:

```
+--ro component-alarm {feature-list:HAVE_CMMD}?
  +--ro equipment-failure?  boolean
```

notifications:

```
+---n alarm
  +--ro severity?           cml-data-types:cml_notif_severity_t
  +--ro eventClass?        cml-data-types:cml_notif_class_t
  +--ro id?                 string
  +--ro resource?          string
  +--ro text?              string
  +--ro time-created?      uint64
  +--ro alarm-reported-timestamp? ipi-alarms-types:alarm_date_time_t
  +--ro alarm-severity?    ipi-alarms-types:alarm_severity_t
  +--ro type-id?           ipi-alarms-types:alarm_type_id_t
  +--ro is-clear?         boolean
```

---

## module: ipi-arp

```
+--rw arp
  +--rw entries
  | +--rw entry* [vrf-name ip-address]
  |   +--rw vrf-name   -> ../config/vrf-name
  |   +--rw ip-address -> ../config/ip-address
  |   +--rw config
  |   | +--rw vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
  |   | +--rw ip-address?    inet:ipv4-address
  |   | +--rw mac-address    cml-data-types:cml_mac_addr_t
  |   | +--rw respond-to-arp-request? empty
  |   +--ro state
  |     +--ro vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
  |     +--ro ip-address?    inet:ipv4-address
```

---

```
|   +--ro mac-address          cml-data-types:cml_mac_addr_t
|   +--ro respond-to-arp-request?  empty
|   +--ro arp-age?             string
|   +--ro interface-name?       string
|   +--ro physical-interface-name? string
|   +--ro arp-state?           ipi-arp-types:ndd_arp_state_t
|   +--ro interface-state?      ipi-arp-types:ndd_arp_if_type_t
+--rw debug
| +--rw config
| | +--rw enable?  empty
| +--ro state
|   +--ro enable?          empty
|   +--ro terminal-debug-status? cml-data-types:cml_on_off_t
+--rw interfaces
| +--rw interface* [name]
|   +--rw name    -> ../config/name
|   +--rw config
|   | +--rw name?          -> /ipi-interface:interfaces/interface/name
|   | +--rw enable-proxy-arp?  empty
|   | +--rw enable-local-proxy-arp? empty
|   | +--rw enable-ip-redirects? empty
|   | +--rw arp-ageing-timeout? uint16
|   | +--rw arp-reachable-time? uint16
|   +--ro state
|     +--ro name?          -> /ipi-interface:interfaces/interface/name
|     +--ro enable-proxy-arp?  empty
|     +--ro enable-local-proxy-arp? empty
|     +--ro enable-ip-redirects? empty
|     +--ro arp-ageing-timeout? uint16
|     +--ro arp-reachable-time? uint16
+--ro dynamic-arp* [vrf-name]
  +--ro vrf-name      string
  +--ro entry* [ipv4-address]
  | +--ro ipv4-address      inet:ipv4-address
  | +--ro mac-address?     cml-data-types:cml_mac_addr_t
  | +--ro arp-age?        string
```

```

| +--ro interface-name?      string
| +--ro physical-interface-name? string
| +--ro arp-state?          ipi-arp-types:ndd_arp_state_t
| +--ro interface-state?    ipi-arp-types:ndd_arp_if_type_t
+--ro adjacency-summary
  +--ro resolved-arp?      uint32
  +--ro incomplete-arp?    uint32
  +--ro unknown-arp?      uint32
  +--ro total-arp?        uint32

```

rpcs:

```

+---x arp-terminal-debug-on {feature-list:HAVE_L3,feature-list:HAVE_NDD}?
+---x arp-terminal-debug-off {feature-list:HAVE_L3,feature-list:HAVE_NDD}?
+---x clear-arp-entry {feature-list:HAVE_L3,feature-list:HAVE_NDD}?
| +---w input
|   +---w ip-address?  inet:ipv4-address
|   +---w vrf-name?   string
+---x clear-arp-entry-per-interface {feature-list:HAVE_L3,feature-list:HAVE_NDD}?
  +---w input
    +---w if-name   string
    +---w vrf-name? string

```

---

## module: ipi-authentication-radius

```

+--rw authentication-radius {feature-list:HAVE_ENCRYPT_CLEARTEXT}?
  +--rw global
  | +--rw config
  | | +--rw source-address?      inet:ipv4-address
  | | +--rw port?                uint16
  | | +--rw timeout?             uint8
  | | +--rw retransmit-max-retries? uint8
  | | +--rw (key-type)?
  | |   +--:(key-string)
  | |   | +--rw key-string?      string

```

---

```

| | +--:(encrypted)
| |   +--rw encryption-key?  string
| +--ro state
|   +--ro source-address?    inet:ipv4-address
|   +--ro port?              uint16
|   +--ro timeout?          uint8
|   +--ro retransmit-max-retries? uint8
|   +--ro (key-type)?
|     +--:(key-string)
|     | +--ro key-string?    string
|     | +--:(encrypted)
|     |   +--ro encryption-key?  string
+--rw hosts
+--rw host* [host-address]
+--rw host-address -> ../config/host-address
+--rw config
| +--rw host-address?      inet:ipv4-address
| +--rw host-port?        uint16
| +--rw host-timeout?     uint8
| +--rw host-retransmit-max-retries? uint8
| +--rw (host-key-type)?
|   +--:(key-string)
|   | +--rw key-string?    string
|   | +--:(encrypted)
|   |   +--rw encryption-key?  string
+--ro state
+--ro host-address?      inet:ipv4-address
+--ro host-port?        uint16
+--ro host-timeout?     uint8
+--ro host-retransmit-max-retries? uint8
+--ro (host-key-type)?
| +--:(key-string)
| | +--ro key-string?    string
| | +--:(encrypted)
| |   +--ro encryption-key?  string
+--ro next-radius-message-id?  uint8

```

```

+--ro encryption-key-operational?      string
+--ro host-port-operational?           uint16
+--ro host-timeout-operational?       uint8
+--ro host-retransmit-max-retries-operational? uint8

```

---

## module: ipi-authentication

```

+--rw authentication {feature-list:HAVE_AUTHD}?
  +--rw global
    | +--rw config
    | | +--rw mac-authentication?  empty {feature-list:HAVE_MAC_AUTH}?
    | | +--rw dot1x-authentication? empty
    | +--ro state
    | +--ro mac-authentication?  empty {feature-list:HAVE_MAC_AUTH}?
    | +--ro dot1x-authentication? empty
  +--rw dot1x-interfaces
    | +--rw dot1x-interface* [name]
    | +--rw name                  -> ../config/name
    | +--rw config
    | | +--rw name?              -> /ipi-interface:interfaces/interface/name
    | | +--rw dot1x-control      ipi-authentication-types:auth_dot1x_control_t
    | | +--rw protocol-version?  ipi-authentication-types:auth_dot1x_eapol_version_t
    | +--ro state
    | | +--ro name?              -> /ipi-interface:interfaces/interface/name
    | | +--ro dot1x-control      ipi-authentication-types:auth_dot1x_control_t
    | | +--ro protocol-version?  ipi-authentication-types:auth_dot1x_eapol_version_t
    | +--ro auth-dot1x-interface-operational
    | | +--ro state
    | | +--ro dot1x-control-operational? ipi-authentication-types:auth_dot1x_control_t
    | | +--ro supplicant-name?      string
    | | +--ro supplicant-mac-address? ipi-authentication-types:auth_dot1x_mac_address_t
    | | +--ro port-enabled?         boolean
    | | +--ro authentication-abort?  boolean
    | | +--ro authentication-fail?   boolean
    | | +--ro authentication-start?  boolean

```

---

```
| | +--ro authentication-timeout?   boolean
| | +--ro authentication-success?   boolean
| | +--ro key-available?            boolean
| | +--ro key-tx-enabled?           boolean
| +--ro authentication-control-dir-operational
| | +--ro state
| | +--ro admin-controlled-directions? ipi-authentication-types:auth_dot1x_control_dir_t
| | +--ro oper-controlled-directions? ipi-authentication-types:auth_dot1x_control_dir_t
| | +--ro bridge-detected?         boolean
| +--ro authentication-key-received-operational
| | +--ro state
| | +--ro rx-key?                  boolean
| +--rw authenticator-pae
| | +--rw config
| | | +--rw quiet-period?          uint16
| | | +--rw max-reauth-value?      uint8
| | | +--rw interval-period?       uint16
| | +--ro state
| | +--ro quiet-period?            uint16
| | +--ro max-reauth-value?        uint8
| | +--ro interval-period?         uint16
| +--ro auth-authenticator-pae-operational
| | +--ro state
| | +--ro quiet-period-operational? uint16
| | +--ro max-reauth-value-operational? uint8
| | +--ro interval-period-operational? uint16
| | +--ro port-status?             ipi-authentication-types:auth_dot1x_port_status_t
| | +--ro pae-state?               ipi-authentication-types:auth_dot1x_pae_state_t
| | +--ro port-mode?               ipi-authentication-types:auth_dot1x_port_ctrl_t
| | +--ro reauth-count?            uint32
| | +--ro rx-response-id?          uint32
| +--rw reauthentication-timer
| | +--rw config
| | | +--rw reauthentication-period? uint32
| | | +--rw enable-reauthentication? empty
| | | +--rw enable-mac-auth-bypass? ipi-authentication-types:auth_dot1x_mac_auth_bypass_t {feature-
list:HAVE_MAC_AUTH}?
```

---

```

| | +--ro state
| |   +--ro reauthentication-period? uint32
| |   +--ro enable-reauthentication? empty
| |   +--ro enable-mac-auth-bypass? ipi-authentication-types:auth_dot1x_mac_auth_bypass_t {feature-
list:HAVE_MAC_AUTH}?
| |   +--ro reauthentication-timer-operational
| |   +--ro state
| |     +--ro reauthentication-period-operational? uint32
| |     +--ro enable-reauthentication-operational? empty
| |     +--ro dot1x-timer? ipi-authentication-types:auth_mac_dot1x_timer_status_t {feature-
list:HAVE_MAC_AUTH}?
| |     +--ro mac-status? ipi-authentication-types:auth_mac_status_t {feature-
list:HAVE_MAC_AUTH}?
| |     +--ro last-rejected-mac? ipi-authentication-types:auth_dot1x_mac_address_t {feature-
list:HAVE_MAC_AUTH}?
| |   +--rw authenticator-be
| |     +--rw config
| |       +--rw supplicant-timeout? uint16
| |       +--rw server-timeout? uint16
| |     +--ro state
| |       +--ro supplicant-timeout? uint16
| |       +--ro server-timeout? uint16
| |     +--ro authenticator-be-operational
| |     +--ro state
| |       +--ro supplicant-timeout-operational? uint16
| |       +--ro server-timeout-operational? uint16
| |     +--ro current-id? uint8
| |     +--ro be-state? ipi-authentication-types:auth_be_state_t
| |     +--ro req-count? uint8
| |     +--ro id-from-server? uint8
+--rw mac-interfaces {feature-list:HAVE_MAC_AUTH}?
| +--rw mac-interface* [name]
|   +--rw name -> ../config/name
|   +--rw config
| |   +--rw name? -> /ipi-interface:interfaces/interface/name
| |   +--rw mac-control empty
| |   +--rw mac-mode? ipi-authentication-types:auth_mac_mode_t
| |   +--rw dynamic-vlan-creation? empty

```

```

| | +--rw mac-address-aging?    empty
| +--ro state
|   +--ro name?                -> /ipi-interface:interfaces/interface/name
|   +--ro mac-control          empty
|   +--ro mac-mode?            ipi-authentication-types:auth_mac_mode_t
|   +--ro dynamic-vlan-creation? empty
|   +--ro mac-address-aging?    empty
+--rw debug
  +--rw config
  | +--rw options? ipi-authentication-types:auth_dot1x_debug_t
  +--ro state
    +--ro options?          ipi-authentication-types:auth_dot1x_debug_t
    +--ro terminal-debug-status? ipi-authentication-types:auth_dot1x_debug_t

```

rpcs:

```

+---x dot1x-authentication-initialize-interface {feature-list:HAVE_MAC_AUTH}?
| +---w input
|   +---w name    string
+---x dot1x-authentication-snmp-restart {feature-list:HAVE_SNMP}?
+---x dot1x-authentication-terminal-debug-on {feature-list:HAVE_AUTHD}?
| +---w input
|   +---w terminal-debug-options ipi-authentication-types:auth_dot1x_debug_t
+---x dot1x-authentication-terminal-debug-off {feature-list:HAVE_AUTHD}?
  +---w input
    +---w terminal-debug-options ipi-authentication-types:auth_dot1x_debug_t

```

---

## module: ipi-bfd

```

+--rw bfd
  +--rw global
  | +--rw config
  | | +--rw notification-enabled? boolean {feature-list:HAVE_BFD_MONO}?

```

```

| | +--rw echo-mode-enabled?    empty {feature-list:HAVE_BFD_MONO}?
| | +--rw slow-tx-interval?     uint32 {feature-list:HAVE_BFD_MONO}?
| +--ro state
| | +--ro notification-enabled?  boolean {feature-list:HAVE_BFD_MONO}?
| | +--ro echo-mode-enabled?     empty {feature-list:HAVE_BFD_MONO}?
| | +--ro slow-tx-interval?      uint32 {feature-list:HAVE_BFD_MONO}?
| | +--ro start-time?           yang:timeticks {feature-list:HAVE_BFD_MONO}?
| | +--ro administrative-state?   ipi-bfd-types:oambfd_admin_state_t {feature-list:HAVE_BFD_MONO}?
| | +--ro image-type?           ipi-bfd-types:oambfd_image_type_t {feature-list:HAVE_BFD_MONO}?
| | +--ro next-session-discriminator? string {feature-list:HAVE_BFD_MONO}?
| | +--ro counters
| |   +--ro total-sessions? yang:counter32
| +--rw intervals
|   +--rw interval* [desired-minimum-tx-interval required-minimum-rx-interval detection-multiplier] {feature-
list:HAVE_BFD_MONO}?
|     +--rw desired-minimum-tx-interval  -> ../config/desired-minimum-tx-interval
|     +--rw required-minimum-rx-interval -> ../config/required-minimum-rx-interval
|     +--rw detection-multiplier        -> ../config/detection-multiplier
|     +--rw config
|       | +--rw desired-minimum-tx-interval?  uint32
|       | +--rw required-minimum-rx-interval? uint32
|       | +--rw detection-multiplier?        uint8
|       +--ro state
|         +--ro desired-minimum-tx-interval?  uint32
|         +--ro required-minimum-rx-interval? uint32
|         +--ro detection-multiplier?        uint8
+--rw peers
| +--rw peer* [remote-address]
|   +--rw remote-address  -> ../config/remote-address
|   +--rw config
|     | +--rw remote-address?  inet:ip-address
|     +--ro state
|     | +--ro remote-address?  inet:ip-address
|     +--rw intervals
|       | +--rw interval* [desired-minimum-tx-interval | required-minimum-rx-interval detection-multiplier] {feature-
list:HAVE_BFD_MONO}?
|       | +--rw desired-minimum-tx-interval  -> ../config/desired-minimum-tx-interval

```

---

```

| | +--rw required-minimum-rx-interval -> ../config/required-minimum-rx-interval
| | +--rw detection-multiplier        -> ../config/detection-multiplier
| | +--rw config
| | | +--rw desired-minimum-tx-interval? uint32
| | | +--rw required-minimum-rx-interval? uint32
| | | +--rw detection-multiplier?      uint8
| | +--ro state
| |   +--ro desired-minimum-tx-interval? uint32
| |   +--ro required-minimum-rx-interval? uint32
| |   +--ro detection-multiplier?      uint8
| +--rw authentication
|   +--rw config
|     +--rw key-type?          ipi-bfd-types:bfd_multihop_auth_type_t
|     +--rw (key-option)?
|     | +--:(key-id)
|     | | +--rw key-id?       uint32
|     | | +--rw key-encrypted? ipi-bfd-types:oambfd_encrypt_key_t
|     | | +--rw key-string?   string
|     | +--:(key-chain)
|     +--ro state
|     | +--ro key-type?       ipi-bfd-types:bfd_multihop_auth_type_t
|     | +--ro (key-option)?
|     | | +--:(key-id)
|     | | | +--ro key-id?     uint32
|     | | | +--ro key-encrypted? ipi-bfd-types:oambfd_encrypt_key_t
|     | | | +--ro key-string? string
|     | | +--:(key-chain)
+--rw debug
| +--rw config
| | +--rw options? ipi-bfd-types:bfd_debug_t
| +--ro state
|   +--ro options?          ipi-bfd-types:bfd_debug_t
|   +--ro terminal-debug-status? ipi-bfd-types:bfd_debug_t
+--rw interfaces
| +--rw interface* [name]
|   +--rw name              -> ../config/name

```

---

```

| +--rw config
| | +--rw name?          -> /ipi-interface:interfaces/interface/name
| | +--rw bfd-disabled?  empty
| | +--rw bfd-session-type? ipi-bfd-types:oambfd_session_type_t {feature-list:HAVE_BFD_HW_OFFLOAD}?
| +--ro state
| | +--ro name?          -> /ipi-interface:interfaces/interface/name
| | +--ro bfd-disabled?  empty
| | +--ro bfd-session-type? ipi-bfd-types:oambfd_session_type_t {feature-list:HAVE_BFD_HW_OFFLOAD}?
| | +--ro interface-index? uint32
| | +--ro interface-state? ipi-bfd-types:oambfd_if_state_t
| +--rw intervals
| | +--rw interval* [desired-minimum-tx-interval required-minimum-rx-interval detection-multiplier] {feature-
list:HAVE_BFD_MONO}?
| | | +--rw desired-minimum-tx-interval -> ../config/desired-minimum-tx-interval
| | | +--rw required-minimum-rx-interval -> ../config/required-minimum-rx-interval
| | | +--rw detection-multiplier       -> ../config/detection-multiplier
| | | +--rw config
| | | | +--rw desired-minimum-tx-interval? uint32
| | | | +--rw required-minimum-rx-interval? uint32
| | | | +--rw detection-multiplier?      uint8
| | | +--ro state
| | | | +--ro desired-minimum-tx-interval? uint32
| | | | +--ro required-minimum-rx-interval? uint32
| | | | +--ro detection-multiplier?      uint8
| +--rw echo
| | +--rw config
| | | +--rw ipv4-source?          inet:ipv4-address
| | | +--rw required-minimum-tx-interval? uint32
| | +--ro state
| | | +--ro ipv4-source?          inet:ipv4-address
| | | +--ro required-minimum-tx-interval? uint32
| +--rw authentication
| | +--rw config
| | | +--rw key-type?            ipi-bfd-types:bfd_multihop_auth_type_t
| | | +--rw (key-option)?
| | | | +--:(key-id)
| | | | | +--rw key-id?         uint32

```

```

| | | | +--rw key-encrypted? ipi-bfd-types:oambfd_encrypt_key_t
| | | | +--rw key-string?   string
| | |   +--:(key-chain)
| | +--ro state
| |   +--ro key-type?       ipi-bfd-types:bfd_multihop_auth_type_t
| |   +--ro (key-option)?
| |     +--:(key-id)
| |       | +--ro key-id?    uint32
| |       | +--ro key-encrypted? ipi-bfd-types:oambfd_encrypt_key_t
| |       | +--ro key-string?  string
| |       +--:(key-chain)
| +--rw sessions
|   +--rw session* [local-address remote-address session-type]
|     +--rw local-address  -> ../config/local-address
|     +--rw remote-address -> ../config/remote-address
|     +--rw session-type   -> ../config/session-type
|     +--rw config
|       | +--rw local-address?   inet:ip-address
|       | +--rw remote-address?  inet:ip-address
|       | +--rw session-type?    ipi-bfd-types:bfd_session_type_t
|       | +--rw administrative-down? empty
|       | +--rw non-persistent?  empty
|       +--ro state
|         +--ro local-address?   inet:ip-address
|         +--ro remote-address?  inet:ip-address
|         +--ro session-type?    ipi-bfd-types:bfd_session_type_t
|         +--ro administrative-down? empty
|         +--ro non-persistent?  empty
+--ro sessions
  +--ro session* [local-discriminator vrf-name]
    +--ro local-discriminator -> ../state/local-discriminator
    +--ro vrf-name            -> ../state/vrf-name
    +--ro state
      | +--ro counters
      | | +--ro packets
      | | +--ro ipv4

```

---

```
| | | +--ro received?      yang:counter64
| | | +--ro transmitted?   yang:counter64
| | | +--ro echo-transmitted? yang:counter64
| | +--ro ipv6 {feature-list:HAVE_IPV6}?
| |   +--ro received?      yang:counter64
| |   +--ro transmitted?   yang:counter64
| |   +--ro echo-transmitted? yang:counter64
| +--ro up-transitions?   yang:counter32
| +--ro lower-layer-type? ipi-bfd-types:oambfd_sess_lower_layer_t
| +--ro uptime?          yang:timeticks
| +--ro version?         uint32
| +--ro local-port?      inet:port-number
| +--ro remote-port?     inet:port-number
| +--ro negotiated-detection-multiplier? uint8
| +--ro forward-hello-timer-hits?   uint32
| +--ro remote-heard?     empty
| +--ro fate-shared?      empty
| +--ro remote-administrative-down?  empty
| +--ro remote-demand-mode-enabled?  empty
| +--ro remote-echo-enabled?  empty
| +--ro poll-bit?        empty
| +--ro storage-type?    ipi-bfd-types:bfd_storage_type_t
| +--ro downtime?       yang:timeticks
| +--ro discontinuity-time? yang:timeticks
| +--ro authentication-key-id?   uint32
| +--ro last-up-time?    yang:timeticks
| +--ro hold-down-timer?  uint32
| +--ro hold-down-timer-hits?  uint32
| +--ro session-type-status? ipi-bfd-types:oambfd_session_type_status_t
| +--ro remote-address?  inet:ip-address
| +--ro local-address?   inet:ip-address
| +--ro vrf-name?        string
| +--ro interface-index? uint32
| +--ro interface-name?  string
| +--ro remote-discriminator?  string
| +--ro local-discriminator?  string
```

---

```

| +--ro session-state?          ipi-bfd-types:oambfd_session_state_t
| +--ro session-type?          ipi-bfd-types:bfd_session_type_state_t
| +--ro session-diagnostics?   ipi-bfd-types:oambfd_perform_diag_t
| +--ro negotiated-tx-interval? uint32
| +--ro negotiated-rx-interval? uint32
+--ro micro-bfd-sessions {feature-list:HAVE_BFD_HW_OFFLOAD}?
| +--ro interface* [member-interface] {feature-list:HAVE_BFD_HW_OFFLOAD}?
|   +--ro member-interface -> ../state/member-interface
|   +--ro state
|     +--ro member-interface? -> /ipi-interface:interfaces/interface/name
|     +--ro remote-session-state? ipi-bfd-types:oambfd_session_state_t
|     +--ro remote-session-diagnostics? ipi-bfd-types:oambfd_perform_diag_t
|     +--ro interface-index?      uint32
|     +--ro interface-name?       string
|     +--ro remote-discriminator? string
|     +--ro local-discriminator?  string
|     +--ro session-state?        ipi-bfd-types:oambfd_session_state_t
|     +--ro session-type?        ipi-bfd-types:bfd_session_type_state_t
|     +--ro session-diagnostics? ipi-bfd-types:oambfd_perform_diag_t
|     +--ro negotiated-tx-interval? uint32
|     +--ro negotiated-rx-interval? uint32
+--ro echo
| +--ro state
|   +--ro local-echo-port?        inet:port-number
|   +--ro echo-desired-minimum-tx-interval? uint32
|   +--ro echo-required-minimum-rx-interval? uint32
|   +--ro negotiated-interval?    uint32
+--ro packet
+--ro clients
  +--ro client* [index]
  +--ro index -> ../state/index
  +--ro state
  +--ro index? uint32
  +--ro flags? ipi-bfd-types:oambfd_client_flags_t

```

rpcs:

---

```
+---x bfd-snmp-restart {feature-list:HAVE_SNMP}?
+---x bfd-terminal-debug-on {feature-list:HAVE_BFD}?
| +---w input
|   +---w terminal-debug-options  ipi-bfd-types:bfd_debug_t
+---x bfd-terminal-debug-off {feature-list:HAVE_BFD}?
  +---w input
    +---w terminal-debug-options  ipi-bfd-types:bfd_debug_t
```

notifications:

```
+---n bfd-session-state-change
  +--ro severity?          cml-data-types:cml_notif_severity_t
  +--ro eventClass?       cml-data-types:cml_notif_class_t
  +--ro local-discriminator? string
  +--ro vrf-name?         string
  +--ro session-state?    ipi-bfd-types:oambfd_session_state_t
  +--ro session-diagnostics? ipi-bfd-types:oambfd_perform_diag_t
```

---

## module: ipi-bgp-vrf

augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance/ipi-vrf:vrf:

```
+--rw bgp-vrf
  +--rw config
    | +--rw import-map? string
```

---

```
| +--rw export-map? string
| +--rw rd-string?  string
+--ro state
| +--ro counters
| | +--ro neighbor-rx-tx-stat
| | | +--ro messages-sent?      uint32
| | | +--ro messages-received?  uint32
| | | +--ro bytes-sent?         uint32
| | | +--ro bytes-received?     uint32
| | | +--ro opens-sent?        uint32
| | | +--ro opens-received?     uint32
| | | +--ro updates-sent?      uint32
| | | +--ro updates-received?  uint32
| | | +--ro keepalive-sent?    uint32
| | | +--ro keepalive-received? uint32
| | | +--ro notification-sent?  uint32
| | | +--ro notification-received? uint32
| | | +--ro route-refresh-sent?  uint32
| | | +--ro route-refresh-received? uint32
| | | +--ro capabilities-sent?   uint32
| | | +--ro capabilities-received? uint32
| | +--ro local-input-output
| | | +--ro active-open?        uint16
| | | +--ro passive-open?      uint16
| | | +--ro open-loops?        uint16
| | | +--ro open-calls?        uint16
| | | +--ro open-received-calls? uint16
| | | +--ro send-calls?        uint16
| | | +--ro received-calls?    uint16
| | | +--ro write-calls?       uint16
| | | +--ro write-loops?       uint16
| | | +--ro write-loops-yield?  uint16
| | | +--ro read-calls?        uint16
| | | +--ro read-loops?        uint16
| | | +--ro read-loop-yield?   uint16
| | | +--ro process-nlri-yields? uint16
```

---

```
| | | +--ro process-withdraw-yields?      uint16
| | | +--ro read-time-exceed?            uint16
| | | +--ro update-send-pending?         uint16
| | | +--ro update-buffer-not-available?  uint16
| | | +--ro update-walk-suspend?         uint16
| | | +--ro yield-in-update?             uint16
| | | +--ro yield-in-pack?               uint16
| | | +--ro no-send-buffer-peer?         uint16
| | | +--ro no-withdraw-buffer-peer?     uint16
| | | +--ro yields-in-update-peer-loop?   uint16
| | | +--ro no-updates-pending-or-no-buffers? uint16
| | | +--ro no-data-to-write?            uint16
| | | +--ro message-queue-received-error? uint16
| | +--ro sockets
| |   +--ro created?      uint32
| |   +--ro accepted?    uint32
| |   +--ro closed?      uint32
| |   +--ro create-retries? uint32
| |   +--ro create-failures? uint32
| |   +--ro fd-close-session? uint32
| +--ro import-map?  string
| +--ro export-map?  string
| +--ro rd-string?   string
+--ro next-hop-tracking
| +--ro state
|   +--ro bgp-as?      uint32
|   +--ro router-id?   inet:ipv4-address
|   +--ro configured?  boolean
|   +--ro delay-time?  uint32
|   +--ro received-message-count? cml-data-types:cml_line_t
|   +--ro ipv4-count?  int32
|   +--ro ipv6-count?  int32
|   +--ro delay-time-remaining? int32
+--rw route-targets
| +--rw route-target* [rt-rd-string]
|   +--rw rt-rd-string  -> ../config/rt-rd-string
```

```

|  +--rw config
|  |  +--rw rt-rd-string?  ipi-bgp-types:bgp_route_target_type_t
|  |  +--rw direction      ipi-bgp-types:bgp_target_route_type_t
|  +--ro state
|  +--ro rt-rd-string?  ipi-bgp-types:bgp_route_target_type_t
|  +--ro direction      ipi-bgp-types:bgp_target_route_type_t
+--ro bgp-rd
  +--ro bgp-rd-as
  |  +--ro state
  |  +--ro brd-as?        int32
  |  +--ro brd-as-number? int32
  +--ro bgp-rd-as4
  |  +--ro state
  |  +--ro brd-as4?       int32
  |  +--ro brd-as-num4?   int32
  +--ro bgp-rd-ip
  +--ro state
  +--ro brd-ip?           int32
  +--ro brd-ip-number?   int32

```

---

## module: ipi-bgp

```

+--rw bgp
  +--rw global
  |  +--rw config
  |  |  +--rw enable-aggregate-nexthop?  empty
  |  |  +--rw enable-path-select?        empty
  |  |  +--rw disable-adj-out?            empty
  |  |  +--rw disable-rfc7606-error-handling? empty
  |  |  +--rw enable-bogon-filtering?     empty
  |  |  +--rw enable-extended-asn-capability? empty {feature-list:HAVE_EXT_CAP_ASN}?
  |  |  +--rw enable-nexthop-tracking?    empty
  |  |  +--rw nexthop-tracking-delay?     uint8
  |  |  +--rw enable-rfc-1771-strict-origin? empty
  |  +--ro state
  |  |  +--ro enable-aggregate-nexthop?  empty

```

---

```

| | +--ro enable-path-select?      empty
| | +--ro disable-adj-out?        empty
| | +--ro disable-rfc7606-error-handling?  empty
| | +--ro enable-bogon-filtering?   empty
| | +--ro enable-extended-asn-capability?  empty {feature-list:HAVE_EXT_CAP_ASN}?
| | +--ro enable-nexthop-tracking?   empty
| | +--ro nexthop-tracking-delay?   uint8
| | +--ro enable-rfc-1771-strict-origin?  empty
| +--rw community-lists
| | +--rw numbered-lists
| | | +--rw numbered-list* [standard-number]
| | |   +--rw standard-number   -> ../config/standard-number
| | |   +--rw config
| | |     | +--rw standard-number?  uint32
| | |     +--ro state
| | |     | +--ro standard-number?  uint32
| | |     +--rw action-for-any
| | |     | +--rw config!
| | |     | | +--rw action-name   ipi-bgp-types:bgp_community_list_action_t
| | |     | +--ro state
| | |     |   +--ro action-name   ipi-bgp-types:bgp_community_list_action_t
| | |     +--rw action-list-values
| | |       +--rw action-list-value* [action-standard-number standard-number-value]
| | |         +--rw action-standard-number   -> ../config/action-standard-number
| | |         +--rw standard-number-value   -> ../config/standard-number-value
| | |         +--rw config
| | |           | +--rw action-standard-number?  ipi-bgp-types:bgp_community_list_action_t
| | |           | +--rw standard-number-value?  string
| | |           +--ro state
| | |             +--ro action-standard-number?  ipi-bgp-types:bgp_community_list_action_t
| | |             +--ro standard-number-value?  string
| | +--rw standards
| | | +--rw standard* [list-type name]
| | |   +--rw list-type   -> ../config/list-type
| | |   +--rw name       -> ../config/name
| | |   +--rw config

```

---

---

```
| | | | +--rw list-type? ipi-bgp-types:bgp_community_list_type_t
| | | | +--rw name? string
| | | +--ro state
| | | | +--ro list-type? ipi-bgp-types:bgp_community_list_type_t
| | | | +--ro name? string
| | | +--rw action-for-any
| | | | +--rw config!
| | | | | +--rw action-name ipi-bgp-types:bgp_community_list_action_t
| | | | | +--ro state
| | | | | +--ro action-name ipi-bgp-types:bgp_community_list_action_t
| | | +--rw action-values
| | |   +--rw action-value* [action-name-standard community-value-standard]
| | |     +--rw action-name-standard -> ../config/action-name-standard
| | |     +--rw community-value-standard -> ../config/community-value-standard
| | |     +--rw config
| | |     | +--rw action-name-standard? ipi-bgp-types:bgp_community_list_action_t
| | |     | +--rw community-value-standard? string
| | |     +--ro state
| | |     +--ro action-name-standard? ipi-bgp-types:bgp_community_list_action_t
| | |     +--ro community-value-standard? string
| | +--rw expanded-lists
| | | +--rw expanded-list* [list-type expanded-type]
| | |   +--rw list-type -> ../config/list-type
| | |   +--rw expanded-type -> ../config/expanded-type
| | |   +--rw config
| | |     | +--rw list-type? ipi-bgp-types:bgp_expanded_list_t
| | |     | +--rw expanded-type? ipi-bgp-types:bgp_expanded_list_type_t
| | |     +--ro state
| | |     | +--ro list-type? ipi-bgp-types:bgp_expanded_list_t
| | |     | +--ro expanded-type? ipi-bgp-types:bgp_expanded_list_type_t
| | |     +--rw action-values
| | |       +--rw action-value* [action-expanded regular-expression-list]
| | |         +--rw action-expanded -> ../config/action-expanded
| | |         +--rw regular-expression-list -> ../config/regular-expression-list
| | |         +--rw config
| | |         | +--rw action-expanded? ipi-bgp-types:bgp_community_list_action_t
```

---

```

| | | | +-rw regular-expression-list? cml-data-types:cml_line_t
| | | +-ro state
| | | +-ro action-expanded? ipi-bgp-types:bgp_community_list_action_t
| | | +-ro regular-expression-list? cml-data-types:cml_line_t
| | +-rw extended-community
| | +-rw numbered-lists
| | | +-rw numbered-list* [standard-number]
| | | +-rw standard-number -> ../config/standard-number
| | | +-rw config
| | | | +-rw standard-number? uint32
| | | +-ro state
| | | | +-ro standard-number? uint32
| | | +-rw action-values
| | | +-rw action-value* [extended-action-number extended-value]
| | | +-rw extended-action-number -> ../config/extended-action-number
| | | +-rw extended-value -> ../config/extended-value
| | | +-rw config
| | | | +-rw extended-action-number? ipi-bgp-types:bgp_community_list_action_t
| | | | +-rw extended-value? cml-data-types:cml_line_t
| | | +-ro state
| | | +-ro extended-action-number? ipi-bgp-types:bgp_community_list_action_t
| | | +-ro extended-value? cml-data-types:cml_line_t
| | +-rw standards
| | | +-rw standard* [name]
| | | +-rw name -> ../config/name
| | | +-rw config
| | | | +-rw name? string
| | | +-ro state
| | | | +-ro name? string
| | | +-rw action-values
| | | +-rw action-value* [extended-action route-target-soo value]
| | | +-rw extended-action -> ../config/extended-action
| | | +-rw route-target-soo -> ../config/route-target-soo
| | | +-rw value -> ../config/value
| | | +-rw config
| | | | +-rw extended-action? ipi-bgp-types:bgp_community_list_action_t

```

```

| | | | +--rw route-target-soo? ipi-bgp-types:bgp_route_target_t
| | | | +--rw value?          string
| | | | +--ro state
| | | | +--ro extended-action? ipi-bgp-types:bgp_community_list_action_t
| | | | +--ro route-target-soo? ipi-bgp-types:bgp_route_target_t
| | | | +--ro value?          string
| | +--rw expanded-lists
| |   +--rw expanded-list* [list-type expanded-type]
| |     +--rw list-type    -> ../config/list-type
| |     +--rw expanded-type -> ../config/expanded-type
| |     +--rw config
| |     | +--rw list-type?   ipi-bgp-types:bgp_expanded_list_t
| |     | +--rw expanded-type? ipi-bgp-types:bgp_expanded_list_type_t
| |     | +--ro state
| |     | | +--ro list-type?   ipi-bgp-types:bgp_expanded_list_t
| |     | | +--ro expanded-type? ipi-bgp-types:bgp_expanded_list_type_t
| |     | +--rw action-values
| |     |   +--rw action-value* [action value]
| |     |   +--rw action    -> ../config/action
| |     |   +--rw value     -> ../config/value
| |     |   +--rw config
| |     | | +--rw action?   ipi-bgp-types:bgp_community_list_action_t
| |     | | +--rw value?   cml-data-types:cml_line_t
| |     | +--ro state
| |     |   +--ro action? ipi-bgp-types:bgp_community_list_action_t
| |     |   +--ro value?  cml-data-types:cml_line_t
| | +--rw as-path-access-lists
| | +--rw as-path-access-list* [access-list-name access-list-action access-list-regular-expression]
| |   +--rw access-list-name      -> ../config/access-list-name
| |   +--rw access-list-action    -> ../config/access-list-action
| |   +--rw access-list-regular-expression -> ../config/access-list-regular-expression
| |   +--rw config
| |     | +--rw access-list-name?      string
| |     | +--rw access-list-action?   ipi-bgp-types:bgp_community_list_action_t
| |     | +--rw access-list-regular-expression? cml-data-types:cml_line_t
| |     +--ro state

```

---

```

| |   +--ro access-list-name?      string
| |   +--ro access-list-action?    ipi-bgp-types:bgp_community_list_action_t
| |   +--ro access-list-regular-expression?  cml-data-types:cml_line_t
| +--rw mpls-l3vpn-label-modes
| +--rw debug
|   +--rw config
|     | +--rw options? ipi-bgp-types:bgp_debug_t
|     +--ro state
|       +--ro terminal-debug-status
|         | +--ro terminal-debug-status? ipi-bgp-types:bgp_debug_t
|         +--ro options? ipi-bgp-types:bgp_debug_t
+--rw bgp-instances
  +--rw bgp-instance* [bgp-as]
    +--rw bgp-as      -> ../config/bgp-as
    +--rw config
      | +--rw bgp-as?      uint32
      | +--rw router-id?   inet:ipv4-address
      | +--rw cluster-id?  ipi-bgp-types:bgp_cluster_id_t
      | +--rw local-preference?  uint32
      | +--rw graceful-shutdown-capable?  empty
      | +--rw graceful-shutdown?  empty
      | +--rw graceful-shutdown-local-preference?  uint32
      | +--rw inbound-route-filter-disable?  empty {feature-list:HAVE_VRF}?
      | +--rw external-route-leak-disable?  empty {feature-list:HAVE_VRF}?
      | +--rw log-neighbor-changes?  empty
      | +--rw scan-interval?  uint32
      | +--rw best-path-dont-compare-originator?  empty
      | +--rw no-best-path-tie-break?  empty
      | +--rw enable-deterministic-med?  empty
      | +--rw enforce-first-as-for-ebgp?  empty
      | +--rw no-external-fail-over?  empty
      | +--rw local-as-count?  uint8
      | +--rw no-client-route-reflection?  empty
      | +--rw med-type?  ipi-bgp-types:bgp_med_type_t
      | +--rw multi-path-relax?  empty
      | +--rw ignore-aigp-for-bestpath?  empty {feature-list:HAVE_BGP_AIGP}?

```

---

```
+--rw confederation
| +--rw config
| | +--rw identifier?   uint32
| | +--rw peer-as-number* uint32
| +--ro state
|   +--ro identifier?   uint32
|   +--ro peer-as-number* uint32
+--rw view-lists
| +--rw view-list* [view-name]
|   +--rw view-name  -> ../config/view-name
|   +--rw config
|     | +--rw view-name? string
|     +--ro state
|       +--ro view-name? string
+--ro state
| +--ro version?          ipi-bgp-types:bgp_version_t
| +--ro table-version?    int32
| +--ro total-prefixes?   int32
| +--ro router-run-time-ip-address? inet:ipv4-address
| +--ro scan-remain-time? uint32
| +--ro bgp-as?           uint32
| +--ro router-id?        inet:ipv4-address
| +--ro cluster-id?       ipi-bgp-types:bgp_cluster_id_t
| +--ro local-preference? uint32
| +--ro graceful-shutdown-capable? empty
| +--ro graceful-shutdown? empty
| +--ro graceful-shutdown-local-preference? uint32
| +--ro inbound-route-filter-disable? empty {feature-list:HAVE_VRF}?
| +--ro external-route-leak-disable? empty {feature-list:HAVE_VRF}?
| +--ro log-neighbor-changes? empty
| +--ro scan-interval?    uint32
| +--ro best-path-dont-compare-originator? empty
| +--ro no-best-path-tie-break? empty
| +--ro enable-deterministic-med? empty
| +--ro enforce-first-as-for-ebgp? empty
| +--ro no-external-fail-over? empty
```

---

```
| +--ro local-as-count?          uint8
| +--ro no-client-route-reflection?  empty
| +--ro med-type?                ipi-bgp-types:bgp_med_type_t
| +--ro multi-path-relax?         empty
| +--ro ignore-aigp-for-bestpath?   empty {feature-list:HAVE_BGP_AIGP}?
+--rw graceful-restart
| +--rw config
| | +--rw enable-graceful-restart?  empty {feature-list:HAVE_RESTART}?
| | +--rw restart-time?            uint32 {feature-list:HAVE_RESTART}?
| | +--rw stale-path-max-retention-time?  uint32 {feature-list:HAVE_RESTART}?
| | +--rw route-selection-max-defer-time?  uint32 {feature-list:HAVE_RESTART}?
| | +--rw graceful-reset?          empty
| +--ro state
|   +--ro enable-graceful-restart?  empty {feature-list:HAVE_RESTART}?
|   +--ro restart-time?            uint32 {feature-list:HAVE_RESTART}?
|   +--ro stale-path-max-retention-time?  uint32 {feature-list:HAVE_RESTART}?
|   +--ro route-selection-max-defer-time?  uint32 {feature-list:HAVE_RESTART}?
|   +--ro graceful-reset?          empty
+--rw timers
| +--rw config!
| | +--rw keep-alive  uint16
| | +--rw hold-time  uint16
| +--ro state
|   +--ro keep-alive  uint16
|   +--ro hold-time  uint16
+--rw route-selection
| +--rw config
| | +--rw always-compare-med?      empty
| | +--rw ignore-as-path-length?   empty
| | +--rw best-path-compare-confed?  empty
| | +--rw external-compare-router-id?  empty
| +--ro state
|   +--ro always-compare-med?      empty
|   +--ro ignore-as-path-length?   empty
|   +--ro best-path-compare-confed?  empty
|   +--ro external-compare-router-id?  empty
```

```

+--rw administrative-distances
| +--rw administrative-distance* [source-ip-prefix]
|   +--rw source-ip-prefix  -> ../config/source-ip-prefix
|   +--rw config
|     | +--rw source-ip-prefix?  cml-data-types:cml_ipv4_prefix_t
|     | +--rw distance          uint8
|     | +--rw access-list-name? string
|     +--ro state
|       +--ro source-ip-prefix?  cml-data-types:cml_ipv4_prefix_t
|       +--ro distance          uint8
|       +--ro access-list-name? string
+--ro rib
| +--ro address-family* [afi safi]
|   +--ro afi          -> ../state/afi
|   +--ro safi         -> ../state/safi
|   +--ro state
|     | +--ro afi?   ipi-bgp-types:bgp_afi_type_t
|     | +--ro safi? ipi-bgp-types:bgp_safi_type_t
|     +--ro routes
|       | +--ro route* [network-address route-distinguisher]
|       |   +--ro network-address  -> ../state/network-address
|       |   +--ro route-distinguisher -> ../state/route-distinguisher
|       |   +--ro next-hop* [next-hop-address]
|       |     | +--ro next-hop-address -> ../state/next-hop-address
|       |     | +--ro state
|       |     |   +--ro next-hop-address?      ipi-bgp-types:bgp_hostname_t
|       |     |   +--ro peer-network-weight?   uint32
|       |     |   +--ro flap-time-reuse-list?  string
|       |     |   +--ro flap-record-duration?  string
|       |     |   +--ro damp-time-to-reuse?    string
|       |     |   +--ro bgp-med-value?         uint32
|       |     |   +--ro bgp-as-path-string*    cml-data-types:cml_line_t
|       |     |   +--ro bgp-as-path-4-byte-string* string
|       |     |   +--ro bgp-as-path-4-byte-origin? ipi-bgp-types:bgp_origin_t
|       |     |   +--ro ibgp-metric-route?    int32
|       |     |   +--ro aggregate-as-route?   int32

```

---

```
| | | +--ro aggregator-address-route?   ipi-bgp-types:bgp_hostname_t
| | | +--ro network-remote-address-route? ipi-bgp-types:bgp_hostname_t
| | | +--ro originator-id-route?       ipi-bgp-types:bgp_hostname_t
| | | +--ro route-peer-address?        ipi-bgp-types:bgp_hostname_t
| | | +--ro route-local-preference?    uint32
| | | +--ro route-prefix-label?       uint32
| | | +--ro route-community-string?   string
| | | +--ro cluster-list-route*       ipi-bgp-types:bgp_hostname_t
| | | +--ro route-penalty?            int32
| | | +--ro route-flap-count?         int32
| | | +--ro last-update-route?        yang:date-and-time
| | | +--ro reflector-client-route?   boolean
| | | +--ro route-dampening-active?   boolean
| | | +--ro history-route?            boolean
| | | +--ro nexthop-valid-route?      boolean
| | | +--ro med-flag-type-route?      boolean
| | | +--ro valid-route?              boolean
| | | +--ro stale-route?              boolean
| | | +--ro route-type?               ipi-bgp-types:bgp_ri_type_t
| | | +--ro ecmp-multi-candidate-route? boolean
| | | +--ro multi-installed-route?    boolean
| | | +--ro route-synchronized-flag-route? boolean
| | | +--ro atomic-aggregate-route?   boolean
| | | +--ro selected-route?           boolean
| | | +--ro bgp-tx-path-id?           int16 {feature-list:HAVE_BGP_ADD_PATH}?
| | | +--ro bgp-rx-path-id?           int16 {feature-list:HAVE_BGP_ADD_PATH}?
| | | +--ro ipv4-multicast-capability? string
| | | +--ro vpnv4-unicast-capability? string
| | | +--ro rtfiler-unicast-capability? string
| | | +--ro l2vpn-evpn-capability?    string
| | | +--ro ipv6-unicast-capability?  string
| | | +--ro ipv6-multicast-capability? string
| | | +--ro ipv6-label-unicast-capability? string
| | +--ro state
| |   +--ro network-address?   ipi-bgp-types:bgp_ip_network_t
| |   +--ro route-distinguisher? string
```

---

```
|  +--ro evpn-routes
|  +--ro evpn-route* [route-distinguisher]
|  +--ro route-distinguisher      -> ../state/route-distinguisher
|  +--ro state
|  |  +--ro route-distinguisher?  string
|  |  +--ro vrf-name?            string
|  +--ro mac-ip-route* [host-mac-address host-ip-address ethernet-tag-identifier next-hop-address]
|  |  +--ro host-mac-address      -> ../state/host-mac-address
|  |  +--ro host-ip-address      -> ../state/host-ip-address
|  |  +--ro ethernet-tag-identifier -> ../state/ethernet-tag-identifier
|  |  +--ro next-hop-address     -> ../state/next-hop-address
|  |  +--ro state
|  |  |  +--ro host-mac-address?    cml-data-types:cml_mac_addr_t
|  |  |  +--ro host-ip-address?    inet:ip-address
|  |  |  +--ro ethernet-tag-identifier? uint32
|  |  |  +--ro next-hop-address?   inet:ipv4-address
|  |  |  +--ro encapsulation-type?  string
|  |  |  +--ro ethernet-segment-identifier? string
|  |  |  +--ro l2-label?           uint32
|  |  |  +--ro l3-label?           uint32
|  +--ro inclusive-multicast-route* [ethernet-tag-identifier originating-router-ip-address]
|  |  +--ro ethernet-tag-identifier -> ../state/ethernet-tag-identifier
|  |  +--ro originating-router-ip-address -> ../state/originating-router-ip-address
|  |  +--ro state
|  |  |  +--ro ethernet-tag-identifier?  uint32
|  |  |  +--ro originating-router-ip-address? inet:ipv4-address
|  |  |  +--ro next-hop-address?        inet:ipv4-address
|  |  |  +--ro encapsulation-type?      string
|  +--ro ethernet-segment-route* [ethernet-segment-identifier originating-router-ip-address]
|  |  +--ro ethernet-segment-identifier -> ../state/ethernet-segment-identifier
|  |  +--ro originating-router-ip-address -> ../state/originating-router-ip-address
|  |  +--ro state
|  |  |  +--ro ethernet-segment-identifier?  string
|  |  |  +--ro originating-router-ip-address? inet:ipv4-address
|  |  |  +--ro next-hop-address?            inet:ipv4-address
|  |  |  +--ro encapsulation-type?         string
```

```

|   +--ro ethernet-auto-discovery-route* [ethernet-segment-identifier ethernet-tag-identifier next-hop-address]
|   |   +--ro ethernet-segment-identifier  -> ../state/ethernet-segment-identifier
|   |   +--ro ethernet-tag-identifier      -> ../state/ethernet-tag-identifier
|   |   +--ro next-hop-address             -> ../state/next-hop-address
|   |   +--ro state
|   |       +--ro ethernet-segment-identifier?  string
|   |       +--ro ethernet-tag-identifier?      uint32
|   |       +--ro next-hop-address?             inet:ipv4-address
|   |       +--ro encapsulation-type?          string
|   |       +--ro label?                       uint32
|   +--ro ip-prefix-route* [ethernet-segment-identifier ethernet-tag-identifier originating-router-ip-address]
|   |   +--ro ethernet-segment-identifier  -> ../state/ethernet-segment-identifier
|   |   +--ro ethernet-tag-identifier      -> ../state/ethernet-tag-identifier
|   |   +--ro originating-router-ip-address -> ../state/originating-router-ip-address
|   |   +--ro state
|   |       +--ro ethernet-segment-identifier?  string
|   |       +--ro ethernet-tag-identifier?      uint32
|   |       +--ro originating-router-ip-address? inet:ipv4-address
|   |       +--ro next-hop-address?             inet:ipv4-address
|   |       +--ro encapsulation-type?          string
|   |       +--ro l3-label?                   uint32
+--rw address-families
| +--rw address-family* [afi safi]
|   +--rw afi          -> ../config/afi
|   +--rw safi         -> ../config/safi
|   +--rw config
|   |   +--rw enable-auto-summary?          empty
|   |   +--rw enable-network-igp-sync?     empty
|   |   +--rw enable-igp-sync?             empty
|   |   +--rw enable-bgp-implicit-null?    empty
|   |   +--rw afi?                          ipi-bgp-types:bgp_afi_type_t
|   |   +--rw safi?                          ipi-bgp-types:bgp_safi_type_t
|   |   +--rw additional-paths-mode?        ipi-bgp-types:bgp_additional_path_type_t {feature-
list:HAVE_BGP_ADD_PATH}?
|   |   +--rw additional-path-select-all?  empty {feature-list:HAVE_BGP_ADD_PATH}?
|   |   +--rw additional-paths-best-select-count? uint8 {feature-list:HAVE_BGP_ADD_PATH}?
|   |   +--rw no-client-route-reflection?   empty

```

```

|   +--ro state
|   |   +--ro enable-auto-summary?          empty
|   |   +--ro enable-network-igp-sync?      empty
|   |   +--ro enable-igp-sync?              empty
|   |   +--ro enable-bgp-implicit-null?     empty
|   |   +--ro afi?                           ipi-bgp-types:bgp_afi_type_t
|   |   +--ro safi?                           ipi-bgp-types:bgp_safi_type_t
|   |   +--ro additional-paths-mode?         ipi-bgp-types:bgp_additional_path_type_t {feature-
list:HAVE_BGP_ADD_PATH}?
|   |   +--ro additional-path-select-all?    empty {feature-list:HAVE_BGP_ADD_PATH}?
|   |   +--ro additional-paths-best-select-count? uint8 {feature-list:HAVE_BGP_ADD_PATH}?
|   |   +--ro no-client-route-reflection?    empty
|   +--rw network-lists
|   |   +--rw network-list* [local-network-prefix]
|   |   |   +--rw local-network-prefix  -> ../config/local-network-prefix
|   |   |   +--rw config
|   |   |   |   +--rw local-network-prefix? ipi-bgp-types:bgp_ip_network_t
|   |   |   |   +--rw network-rmap-name?  string
|   |   |   |   +--rw backdoor?          empty
|   |   +--ro state
|   |   |   +--ro network-path-route-count?    int32
|   |   |   +--ro no-advertise-route?          string
|   |   |   +--ro no-export-route?             boolean
|   |   |   +--ro local-as-route?              boolean
|   |   |   +--ro suppress-route?              boolean
|   |   |   +--ro network-best-path-route-count? int32
|   |   |   +--ro ip-routing-table?            string
|   |   |   +--ro advertised-non-peer-group-address* ipi-bgp-types:bgp_hostname_t
|   |   |   +--ro advertised-peer-group-name-route* string
|   |   |   +--ro advertised-any-peer?         boolean
|   |   |   +--ro local-network-prefix?        ipi-bgp-types:bgp_ip_network_t
|   |   |   +--ro network-rmap-name?          string
|   |   |   +--ro backdoor?                    empty
|   +--rw aggregate-address-lists
|   |   +--rw aggregate-address-list* [aggregate-address]
|   |   |   +--rw aggregate-address  -> ../config/aggregate-address
|   |   |   +--rw config

```

```
| | | +-rw aggregate-address? cml-data-types:cml_ip_prefix_t
| | | +-rw aggregate-type? ipi-bgp-types:bgp_aggregate_type_t
| | +-ro state
| | +-ro aggregate-address? cml-data-types:cml_ip_prefix_t
| | +-ro aggregate-type? ipi-bgp-types:bgp_aggregate_type_t
| +-rw distances
| | +-rw distance* [ebgp ibgp local]
| | +-rw ebgp -> ../config/ebgp
| | +-rw ibgp -> ../config/ibgp
| | +-rw local -> ../config/local
| | +-rw config
| | | +-rw ebgp? uint8
| | | +-rw ibgp? uint8
| | | +-rw local? uint8
| | +-ro state
| | +-ro ebgp? uint8
| | +-ro ibgp? uint8
| | +-ro local? uint8
| +-rw maximum-paths
| | +-rw config
| | | +-rw ebgp-max-path? int32
| | | +-rw ibgp-max-path? int32
| | | +-rw eibgp-max-path? int32
| | +-ro state
| | +-ro ebgp-max-path? int32
| | +-ro ibgp-max-path? int32
| | +-ro eibgp-max-path? int32
| +-rw table-map {feature-list:HAVE_BGP_TABLE_MAP}?
| | +-rw config!
| | | +-rw map-name string {feature-list:HAVE_BGP_TABLE_MAP}?
| | | +-rw table-map-filter? boolean {feature-list:HAVE_BGP_TABLE_MAP}?
| | +-ro state
| | +-ro map-name string {feature-list:HAVE_BGP_TABLE_MAP}?
| | +-ro table-map-filter? boolean {feature-list:HAVE_BGP_TABLE_MAP}?
| +-rw route-flap-dampenings
| | +-rw route-flap-dampening* [enable-dampening]
```

---

```
| | +--rw enable-dampening -> ../config/enable-dampening
| | +--rw config
| | | +--rw enable-dampening? ipi-bgp-types:bgp_dampening_t
| | | +--rw reach-half-life? uint32
| | | +--rw reuse-penalty? uint32
| | | +--rw suppress-penalty? uint32
| | | +--rw max-suppress-time? uint32
| | | +--rw unreach-half-life? uint32
| | | +--rw dampening-rmap-name? string
| | +--ro state
| | | +--ro enable-dampening? ipi-bgp-types:bgp_dampening_t
| | | +--ro reach-half-life? uint32
| | | +--ro reuse-penalty? uint32
| | | +--ro suppress-penalty? uint32
| | | +--ro max-suppress-time? uint32
| | | +--ro unreach-half-life? uint32
| | | +--ro dampening-rmap-name? string
| | | +--ro maximum-penalty-ceil? int32
| | | +--ro minimum-penalty-ceil? int32
| +--rw route-redistribute-lists
| | +--rw route-redistribute-list* [protocol-type]
| | | +--rw protocol-type -> ../config/protocol-type
| | | +--rw config
| | | | +--rw protocol-type? ipi-bgp-types:bgp_redistribute_type_t
| | | | +--rw redist-route-map-name? string
| | | +--ro state
| | | | +--ro protocol-type? ipi-bgp-types:bgp_redistribute_type_t
| | | | +--ro redist-route-map-name? string
| +--rw bgp-redistributes-ospf
| | +--rw bgp-redistribute-ospf* [ospf-instance-number]
| | | +--rw ospf-instance-number -> ../config/ospf-instance-number
| | | +--rw config
| | | | +--rw ospf-instance-number? ipi-bgp-types:cml_ospf_area_id_t
| | | | +--rw redistribute-ospf-route-map? string
| | | +--ro state
| | | | +--ro ospf-instance-number? ipi-bgp-types:cml_ospf_area_id_t
```

---

```

|       +--ro redistribute-ospf-route-map? string
+--rw peer-groups
| +--rw peer-group* [peer-group-tag]
|   +--rw peer-group-tag   -> ../config/peer-group-tag
|   +--rw config
|     | +--rw peer-group-tag?          string
|     | +--rw peer-group-range         ipi-bgp-types:bgp_peer_group_type_t
|     | +--rw group-limit?            uint8
|     | +--rw peer-as?                uint32
|     | +--rw graceful-shut?          empty
|     | +--rw enable-peer-bfd?        empty {feature-list:HAVE_BFD}?
|     | +--rw enable-peer-bfd-multihop? empty {feature-list:HAVE_BFD}?
|     | +--rw graceful-shutdown-timer? uint32
|     | +--rw peer-restart-time?      uint32 {feature-list:HAVE_RESTART}?
|     | +--rw peer-description?      cml-data-types:cml_line_t
|     | +--rw peer-connect-interval?  uint32
|     | +--rw peer-as-origin-interval? uint32
|     | +--rw min-route-advertisement-interval? uint32
|     | +--rw enable-dynamic-capability? empty
|     | +--rw collide-established?    empty
|     | +--rw source-identifier?      string
|     | +--rw enforce-multi-hop?     empty
|     | +--rw neighbor-override-capability? empty
|     | +--rw neighbor-strict-capability-match? empty
|     | +--rw disallow-infinite-hold-time? empty
|     | +--rw disable-capability-negotiation? empty
|     | +--rw neighbor-passive?      empty
|     | +--rw peer-shutdown?         empty
|     | +--rw peer-shutdown-description? cml-data-types:cml_line_t
|     | +--rw peer-port?             uint16
|     | +--rw bgp-version?           uint8
|     | +--rw enable-ext-opt-param-len? empty
|     | +--rw tcp-adjust-mss?        uint16
|   +--ro state
|     | +--ro peer-group-tag?        string
|     | +--ro peer-group-range       ipi-bgp-types:bgp_peer_group_type_t

```

---

---

```

| | +--ro group-limit?          uint8
| | +--ro peer-type?           ipi-bgp-types:bgp_peer_type_t
| | +--ro peer-as?            uint32
| | +--ro graceful-shut?      empty
| | +--ro enable-peer-bfd?    empty {feature-list:HAVE_BFD}?
| | +--ro enable-peer-bfd-multihop?  empty {feature-list:HAVE_BFD}?
| | +--ro graceful-shutdown-timer?  uint32
| | +--ro peer-restart-time?  uint32 {feature-list:HAVE_RESTART}?
| | +--ro peer-description?   cml-data-types:cml_line_t
| | +--ro peer-connect-interval?  uint32
| | +--ro peer-as-origin-interval?  uint32
| | +--ro min-route-advertisement-interval?  uint32
| | +--ro enable-dynamic-capability?  empty
| | +--ro collide-established?  empty
| | +--ro source-identifier?  string
| | +--ro enforce-multi-hop?    empty
| | +--ro neighbor-override-capability?  empty
| | +--ro neighbor-strict-capability-match?  empty
| | +--ro disallow-infinite-hold-time?  empty
| | +--ro disable-capability-negotiation?  empty
| | +--ro neighbor-passive?    empty
| | +--ro peer-shutdown?      empty
| | +--ro peer-shutdown-description?  cml-data-types:cml_line_t
| | +--ro peer-port?          uint16
| | +--ro bgp-version?        uint8
| | +--ro enable-ext-opt-param-len?  empty
| | +--ro tcp-adjust-mss?     uint16
| +--rw timers
| | +--rw config!
| | | +--rw keep-alive  uint16
| | | +--rw hold-time  uint16
| | +--ro state
| |   +--ro keep-alive  uint16
| |   +--ro hold-time  uint16
| +--rw ebgp-multihop
| | +--rw config!

```

---

```
| | | +--rw maximum-hop-count? uint8
| | | +--rw enabled          empty
| | +--ro state
| |   +--ro maximum-hop-count? uint8
| |   +--ro enabled          empty
| +--rw bgp-passwords
| | +--rw bgp-password* [password]
| |   +--rw password  -> ../config/password
| |   +--rw config
| |     | +--rw password?      ipi-bgp-types:bgp_md5_password_t {feature-list:HAVE_TCP_MD5SIG}?
| |     | +--rw auth-key-encrypt ipi-bgp-types:bgp_md5_t
| |     +--ro state
| |       +--ro password?      ipi-bgp-types:bgp_md5_password_t {feature-list:HAVE_TCP_MD5SIG}?
| |       +--ro auth-key-encrypt ipi-bgp-types:bgp_md5_t
| +--rw optional-as-lists
| | +--rw optional-as-list* [optional-as]
| |   +--rw optional-as  -> ../config/optional-as
| |   +--rw config
| |     | +--rw optional-as?  uint32
| |     +--ro state
| |       +--ro optional-as?  uint32
| +--rw local-as
| | +--rw local-as-list* [peer-local-as]
| |   +--rw peer-local-as  -> ../config/peer-local-as
| |   +--rw config
| |     | +--rw peer-local-as?  uint32
| |     | +--rw no-prepend-local-as? empty
| |     | +--rw replace-local-as? empty
| |     +--ro state
| |       +--ro peer-local-as?  uint32
| |       +--ro no-prepend-local-as? empty
| |       +--ro replace-local-as? empty
| +--rw address-families
|   +--rw address-family* [afi safi]
|     +--rw afi          -> ../config/afi
|     +--rw safi         -> ../config/safi
```

```

|   +--rw config
|   |   +--rw bgp-port?                uint16
|   |   +--rw activate?                empty
|   |   +--rw default-peer-route-map-name?    empty
|   |   +--rw peer-route-map-orig-name?    string
|   |   +--rw weight?                  uint16
|   |   +--rw peer-route-reflector?       empty
|   |   +--rw peer-remove-private-as?     empty
|   |   +--rw no-send-community?         empty
|   |   +--rw no-send-community-type?     ipi-bgp-types:bgp_send_commu_type_t
|   |   +--rw neighbor-attribute-unchanged? ipi-bgp-types:bgp_attribute_unchanged_type_t
|   |   +--rw orf-prefix-capability?     ipi-bgp-types:bgp_orf_prefix_type_t
|   |   +--rw peer-allow-ebgp-vpn?       empty {feature-list:HAVE_VRF}?
|   |   +--rw allow-as-number?           uint32
|   |   +--rw capability-graceful-restart? empty
|   |   +--rw unsuppress-route-map-name?   string
|   |   +--rw afi?                      ipi-bgp-types:bgp_afi_type_t
|   |   +--rw safi?                      ipi-bgp-types:bgp_safi_type_t
|   |   +--rw additional-paths-mode?     ipi-bgp-types:bgp_peer_additional_path_type_t {feature-
list:HAVE_BGP_ADD_PATH}?
|   |   +--rw additional-path-select-all? empty {feature-list:HAVE_BGP_ADD_PATH}?
|   |   +--rw additional-paths-best-select-count? uint8 {feature-list:HAVE_BGP_ADD_PATH}?
|   |   +--rw route-server-client?       empty
|   |   +--rw next-hop-self?             empty
|   +--ro state
|   |   +--ro bgp-port?                uint16
|   |   +--ro activate?                empty
|   |   +--ro default-peer-route-map-name?    empty
|   |   +--ro peer-route-map-orig-name?    string
|   |   +--ro weight?                  uint16
|   |   +--ro peer-route-reflector?       empty
|   |   +--ro peer-remove-private-as?     empty
|   |   +--ro no-send-community?         empty
|   |   +--ro no-send-community-type?     ipi-bgp-types:bgp_send_commu_type_t
|   |   +--ro neighbor-attribute-unchanged? ipi-bgp-types:bgp_attribute_unchanged_type_t
|   |   +--ro orf-prefix-capability?     ipi-bgp-types:bgp_orf_prefix_type_t
|   |   +--ro peer-allow-ebgp-vpn?       empty {feature-list:HAVE_VRF}?

```

---

```

|   | +-ro allow-as-number?          uint32
|   | +-ro capability-graceful-restart?  empty
|   | +-ro unsuppress-route-map-name?    string
|   | +-ro afi?                        ipi-bgp-types:bgp_afi_type_t
|   | +-ro safi?                        ipi-bgp-types:bgp_safi_type_t
|   | +-ro additional-paths-mode?       ipi-bgp-types:bgp_peer_additional_path_type_t {feature-
list:HAVE_BGP_ADD_PATH}?
|   | +-ro additional-path-select-all?  empty {feature-list:HAVE_BGP_ADD_PATH}?
|   | +-ro additional-paths-best-select-count? uint8 {feature-list:HAVE_BGP_ADD_PATH}?
|   | +-ro route-server-client?         empty
|   | +-ro next-hop-self?               empty
|   +-rw maximum-prefixes
|   | +-rw maximum-prefix* [prefix-count]
|   | +-rw prefix-count  -> ../config/prefix-count
|   | +-rw config
|   | | +-rw prefix-count?            uint32
|   | | +-rw stop-update?             empty
|   | | +-rw maximum-prefix-warning?  empty
|   | | +-rw threshold-percentage?    uint8
|   | | +-rw warning-only?           empty
|   | +-ro state
|   | +-ro prefix-count?              uint32
|   | +-ro stop-update?               empty
|   | +-ro maximum-prefix-warning?    empty
|   | +-ro threshold-percentage?      uint8
|   | +-ro warning-only?              empty
|   +-rw distribute-list-filters
|   | +-rw distribute-list-filter* [filter-direction]
|   | +-rw filter-direction  -> ../config/filter-direction
|   | +-rw config
|   | | +-rw access-list-identifier  string
|   | | +-rw filter-direction?      ipi-bgp-types:bgp_distribute_list_direction_t
|   | +-ro state
|   | +-ro access-list-identifier  string
|   | +-ro filter-direction?      ipi-bgp-types:bgp_distribute_list_direction_t
|   +-rw as-list-filters
|   | +-rw as-list-filter* [as-list-direction]

```

---

```

|   |   |--rw as-list-direction  -> ../config/as-list-direction
|   |   |--rw config
|   |   |   |--rw as-access-list-identifier  string
|   |   |   |--rw as-list-direction?       ipi-bgp-types:bgp_distribute_list_direction_t
|   |   |--ro state
|   |       |--ro as-access-list-identifier  string
|   |       |--ro as-list-direction?       ipi-bgp-types:bgp_distribute_list_direction_t
|--rw prefix-list-filters
|   |--rw prefix-list-filter* [prefix-filter-direction]
|   |--rw prefix-filter-direction  -> ../config/prefix-filter-direction
|   |--rw config
|   |   |--rw prefix-list-name        string
|   |   |--rw prefix-filter-direction? ipi-bgp-types:bgp_distribute_list_direction_t
|   |--ro state
|   |   |--ro prefix-list-name        string
|   |   |--ro prefix-filter-direction? ipi-bgp-types:bgp_distribute_list_direction_t
|--rw route-map-filters
|   |--rw route-map-filter* [route-map-direction]
|   |--rw route-map-direction  -> ../config/route-map-direction
|   |--rw config
|   |   |--rw route-map-name        string
|   |   |--rw route-map-direction? ipi-bgp-types:bgp_distribute_list_direction_t
|   |--ro state
|   |   |--ro route-map-name        string
|   |   |--ro route-map-direction? ipi-bgp-types:bgp_distribute_list_direction_t
|--rw aigp {feature-list:HAVE_BGP_AIGP}?
|   |--rw config
|   |   |--rw admin-status?  cml-data-types:cml_enable_disable_t {feature-list:HAVE_BGP_AIGP}?
|   |   |--rw aigp-send-med?  empty
|   |--ro state
|   |   |--ro admin-status?  cml-data-types:cml_enable_disable_t {feature-list:HAVE_BGP_AIGP}?
|   |   |--ro aigp-send-med?  empty
|--rw cost-community {feature-list:HAVE_BGP_AIGP}?
|   |--rw config!
|   |   |--rw send-cost-community-id  uint8 {feature-list:HAVE_BGP_AIGP}?
|   |   |--rw point-of-insertion     ipi-bgp-types:bgp_aigp_metric_cost_community_poi_t {feature-
list:HAVE_BGP_AIGP}?

```

---

```

|         | +--rw enable-transitive?    empty {feature-list:HAVE_BGP_AIGP}?
|         +--ro state
|         +--ro send-cost-community-id  uint8 {feature-list:HAVE_BGP_AIGP}?
|         +--ro point-of-insertion      ipi-bgp-types:bgp_aigp_metric_cost_community_poi_t {feature-
list:HAVE_BGP_AIGP}?
|         +--ro enable-transitive?      empty {feature-list:HAVE_BGP_AIGP}?
+--rw peers
| +--rw peer* [peer-address]
|   +--rw peer-address    -> ../config/peer-address
|   +--rw config
|     | +--rw peer-address?          ipi-bgp-types:bgp_ip_addr_t
|     | +--rw peer-as?              ipi-bgp-types:bgp_as_type_t
|     | +--rw graceful-shut?        empty
|     | +--rw enable-peer-bfd?      empty {feature-list:HAVE_BFD}?
|     | +--rw enable-peer-bfd-multihop?  empty {feature-list:HAVE_BFD}?
|     | +--rw graceful-shutdown-timer?  uint32
|     | +--rw peer-restart-time?      uint32 {feature-list:HAVE_RESTART}?
|     | +--rw peer-description?      cml-data-types:cml_line_t
|     | +--rw peer-connect-interval?   uint32
|     | +--rw peer-as-origin-interval?  uint32
|     | +--rw min-route-advertisement-interval?  uint32
|     | +--rw enable-dynamic-capability?  empty
|     | +--rw collide-established?      empty
|     | +--rw source-identifier?        string
|     | +--rw enforce-multi-hop?        empty
|     | +--rw neighbor-override-capability?  empty
|     | +--rw neighbor-strict-capability-match?  empty
|     | +--rw disallow-infinite-hold-time?  empty
|     | +--rw disable-capability-negotiation?  empty
|     | +--rw neighbor-passive?         empty
|     | +--rw peer-shutdown?            empty
|     | +--rw peer-shutdown-description?  cml-data-types:cml_line_t
|     | +--rw peer-port?                uint16
|     | +--rw bgp-version?              uint8
|     | +--rw interface-name?          string
|     | +--rw mapped-peer-group-tag?    string
|     | +--rw enable-ext-opt-param-len?  empty

```

---

---

```

| | +--rw tcp-adjust-mss?          uint16
| | +--ro state
| | +--ro counters
| | | +--ro notification-in?      int32
| | | +--ro notification-out?    int32
| | | +--ro update-message-in?   int32
| | | +--ro update-message-out?  int32
| | +--ro peer-address?          ipi-bgp-types:bgp_ip_addr_t
| | +--ro peer-as?               ipi-bgp-types:bgp_as_type_t
| | +--ro graceful-shut?         empty
| | +--ro enable-peer-bfd?       empty {feature-list:HAVE_BFD}?
| | +--ro enable-peer-bfd-multihop? empty {feature-list:HAVE_BFD}?
| | +--ro graceful-shutdown-timer? uint32
| | +--ro peer-restart-time?     uint32 {feature-list:HAVE_RESTART}?
| | +--ro peer-description?      cml-data-types:cml_line_t
| | +--ro peer-connect-interval? uint32
| | +--ro peer-as-origin-interval? uint32
| | +--ro min-route-advertisement-interval? uint32
| | +--ro enable-dynamic-capability? empty
| | +--ro collide-established?    empty
| | +--ro source-identifier?      string
| | +--ro enforce-multi-hop?     empty
| | +--ro neighbor-override-capability? empty
| | +--ro neighbor-strict-capability-match? empty
| | +--ro disallow-infinite-hold-time? empty
| | +--ro disable-capability-negotiation? empty
| | +--ro neighbor-passive?      empty
| | +--ro peer-shutdown?         empty
| | +--ro peer-shutdown-description? cml-data-types:cml_line_t
| | +--ro peer-port?             uint16
| | +--ro bgp-version?           uint8
| | +--ro interface-name?        string
| | +--ro mapped-peer-group-tag?  string
| | +--ro enable-ext-opt-param-len? empty
| | +--ro tcp-adjust-mss?        uint16
| | +--ro peer-type?             ipi-bgp-types:bgp_peer_type_t

```

---

---

```

| | +--ro dynamically-configured?      boolean
| | +--ro connection-established-count? int32
| | +--ro error-notify-sent?          boolean
| | +--ro notify-code-string?         cml-data-types:cml_line_t
| | +--ro bgp-peer-state?             ipi-bgp-types:bgp_peer_status_t
| +--rw timers
| | +--rw config!
| | | +--rw keep-alive  uint16
| | | +--rw hold-time   uint16
| | +--ro state
| |   +--ro keep-alive  uint16
| |   +--ro hold-time   uint16
| +--rw ebgp-multihop
| | +--rw config!
| | | +--rw maximum-hop-count? uint8
| | | +--rw enabled            empty
| | +--ro state
| |   +--ro maximum-hop-count? uint8
| |   +--ro enabled            empty
| +--rw local-as
| | +--rw local-as-list* [peer-local-as]
| |   +--rw peer-local-as  -> ../config/peer-local-as
| |   +--rw config
| |     | +--rw peer-local-as?    uint32
| |     | +--rw no-prepend-local-as? empty
| |     | +--rw replace-local-as? empty
| |     +--ro state
| |       +--ro peer-local-as?    uint32
| |       +--ro no-prepend-local-as? empty
| |       +--ro replace-local-as? empty
| +--rw bgp-passwords
| | +--rw bgp-password* [password]
| |   +--rw password  -> ../config/password
| |   +--rw config
| |     | +--rw password?        ipi-bgp-types:bgp_md5_password_t {feature-list:HAVE_TCP_MD5SIG}?
| |     | +--rw auth-key-encrypt ipi-bgp-types:bgp_md5_t

```

---

```

| | +--ro state
| |   +--ro password?      ipi-bgp-types:bgp_md5_password_t {feature-list:HAVE_TCP_MD5SIG}?
| |   +--ro auth-key-encrypt ipi-bgp-types:bgp_md5_t
| +--rw address-families
|   +--rw address-family* [afi safi]
|     +--rw afi            -> ../config/afi
|     +--rw safi          -> ../config/safi
|     +--ro peer-adj-out-route* [network-address]
|       | +--ro network-address -> ../state/network-address
|       | +--ro next-hop* [next-hop-address]
|       | | +--ro next-hop-address -> ../state/next-hop-address
|       | | +--ro state
|       | |   +--ro next-hop-address?      ipi-bgp-types:bgp_hostname_t
|       | |   +--ro peer-network-weight?   uint32
|       | |   +--ro flap-time-reuse-list?  string
|       | |   +--ro flap-record-duration?  string
|       | |   +--ro damp-time-to-reuse?    string
|       | |   +--ro bgp-med-value?         uint32
|       | |   +--ro bgp-as-path-string*    cml-data-types:cml_line_t
|       | |   +--ro bgp-as-path-4-byte-string* string
|       | |   +--ro bgp-as-path-4-byte-origin? ipi-bgp-types:bgp_origin_t
|       | |   +--ro ibgp-metric-route?     int32
|       | |   +--ro aggregate-as-route?    int32
|       | |   +--ro aggregator-address-route? ipi-bgp-types:bgp_hostname_t
|       | |   +--ro network-remote-address-route? ipi-bgp-types:bgp_hostname_t
|       | |   +--ro originator-id-route?   ipi-bgp-types:bgp_hostname_t
|       | |   +--ro route-peer-address?    ipi-bgp-types:bgp_hostname_t
|       | |   +--ro route-local-preference? uint32
|       | |   +--ro route-prefix-label?    uint32
|       | |   +--ro route-community-string? string
|       | |   +--ro cluster-list-route*    ipi-bgp-types:bgp_hostname_t
|       | |   +--ro route-penalty?        int32
|       | |   +--ro route-flap-count?     int32
|       | |   +--ro last-update-route?     yang:date-and-time
|       | |   +--ro reflector-client-route? boolean
|       | |   +--ro route-dampening-active? boolean

```

---

```

|   | | +--ro history-route?          boolean
|   | | +--ro nexthop-valid-route?    boolean
|   | | +--ro med-flag-type-route?    boolean
|   | | +--ro valid-route?            boolean
|   | | +--ro stale-route?            boolean
|   | | +--ro route-type?              ipi-bgp-types:bgp_ri_type_t
|   | | +--ro ecmp-multi-candidate-route?  boolean
|   | | +--ro multi-installed-route?    boolean
|   | | +--ro route-synchronized-flag-route?  boolean
|   | | +--ro atomic-aggregate-route?    boolean
|   | | +--ro selected-route?           boolean
|   | | +--ro bgp-tx-path-id?           int16 {feature-list:HAVE_BGP_ADD_PATH}
|   | | +--ro bgp-rx-path-id?           int16 {feature-list:HAVE_BGP_ADD_PATH}
|   | | +--ro ipv4-multicast-capability?  string
|   | | +--ro vpv4-unicast-capability?   string
|   | | +--ro rfilter-unicast-capability? string
|   | | +--ro l2vpn-evpn-capability?     string
|   | | +--ro ipv6-unicast-capability?   string
|   | | +--ro ipv6-multicast-capability?  string
|   | | +--ro ipv6-label-unicast-capability? string
|   | | +--ro state
|   | | +--ro network-address? ipi-bgp-types:bgp_ip_network_t
|   | +--ro peer-adj-in-route* [network-address]
|   | | +--ro network-address -> ../state/network-address
|   | | +--ro next-hop* [next-hop-address]
|   | | | +--ro next-hop-address -> ../state/next-hop-address
|   | | | +--ro state
|   | | | +--ro next-hop-address? ipi-bgp-types:bgp_hostname_t
|   | | | +--ro peer-network-weight? uint32
|   | | | +--ro flap-time-reuse-list? string
|   | | | +--ro flap-record-duration? string
|   | | | +--ro damp-time-to-reuse? string
|   | | | +--ro bgp-med-value? uint32
|   | | | +--ro bgp-as-path-string* cml-data-types:cml_line_t
|   | | | +--ro bgp-as-path-4-byte-string* string
|   | | | +--ro bgp-as-path-4-byte-origin? ipi-bgp-types:bgp_origin_t

```

---

---

```
| | | +--ro ibgp-metric-route?      int32
| | | +--ro aggregate-as-route?    int32
| | | +--ro aggregator-address-route?  ipi-bgp-types:bgp_hostname_t
| | | +--ro network-remote-address-route? ipi-bgp-types:bgp_hostname_t
| | | +--ro originator-id-route?    ipi-bgp-types:bgp_hostname_t
| | | +--ro route-peer-address?    ipi-bgp-types:bgp_hostname_t
| | | +--ro route-local-preference? uint32
| | | +--ro route-prefix-label?    uint32
| | | +--ro route-community-string? string
| | | +--ro cluster-list-route*    ipi-bgp-types:bgp_hostname_t
| | | +--ro route-penalty?        int32
| | | +--ro route-flap-count?     int32
| | | +--ro last-update-route?     yang:date-and-time
| | | +--ro reflector-client-route? boolean
| | | +--ro route-dampening-active? boolean
| | | +--ro history-route?        boolean
| | | +--ro nexthop-valid-route?   boolean
| | | +--ro med-flag-type-route?   boolean
| | | +--ro valid-route?          boolean
| | | +--ro stale-route?          boolean
| | | +--ro route-type?           ipi-bgp-types:bgp_ri_type_t
| | | +--ro ecmp-multi-candidate-route? boolean
| | | +--ro multi-installed-route? boolean
| | | +--ro route-synchronized-flag-route? boolean
| | | +--ro atomic-aggregate-route? boolean
| | | +--ro selected-route?       boolean
| | | +--ro bgp-tx-path-id?       int16 {feature-list:HAVE_BGP_ADD_PATH}?
| | | +--ro bgp-rx-path-id?       int16 {feature-list:HAVE_BGP_ADD_PATH}?
| | | +--ro ipv4-multicast-capability? string
| | | +--ro vpv4-unicast-capability? string
| | | +--ro rfilter-unicast-capability? string
| | | +--ro l2vpn-evpn-capability? string
| | | +--ro ipv6-unicast-capability? string
| | | +--ro ipv6-multicast-capability? string
| | | +--ro ipv6-label-unicast-capability? string
| | +--ro state
```

---

---

```

|   |   |--ro network-address?  ipi-bgp-types:bgp_ip_network_t
|   |--rw config
|   |   |--rw afi?              ipi-bgp-types:bgp_afi_type_t
|   |   |--rw safi?            ipi-bgp-types:bgp_safi_type_t
|   |   |--rw additional-paths-mode?  ipi-bgp-types:bgp_peer_additional_path_type_t {feature-
list:HAVE_BGP_ADD_PATH}?
|   |   |--rw additional-path-select-all?  empty {feature-list:HAVE_BGP_ADD_PATH}?
|   |   |--rw additional-paths-best-select-count?  uint8 {feature-list:HAVE_BGP_ADD_PATH}?
|   |   |--rw route-server-client?        empty
|   |   |--rw next-hop-self?              empty
|   |   |--rw bgp-port?                   uint16
|   |   |--rw activate?                   empty
|   |   |--rw de-activate?                empty
|   |   |--rw default-peer-route-map-name?  empty
|   |   |--rw peer-route-map-orig-name?    string
|   |   |--rw soft-reconfig?              ipi-bgp-types:bgp_update_clear_t
|   |   |--rw weight?                     uint16
|   |   |--rw peer-route-reflector?       empty
|   |   |--rw peer-remove-private-as?     empty
|   |   |--rw no-send-community?         empty
|   |   |--rw no-send-community-type?    ipi-bgp-types:bgp_send_commu_type_t
|   |   |--rw neighbor-attribute-unchanged?  ipi-bgp-types:bgp_attribute_unchanged_type_t
|   |   |--rw orf-prefix-capability?     ipi-bgp-types:bgp_orf_prefix_type_t
|   |   |--rw peer-allow-ebgp-vpn?       empty {feature-list:HAVE_VRF}?
|   |   |--rw allow-as-number?           uint32
|   |   |--rw capability-graceful-restart?  empty
|   |   |--rw extended-nexthop-encode?    empty
|   |   |--rw mapped-peer-group-tag-af?   string
|   |   |--rw unsuppress-route-map-name?  string
|   |--ro state
|   |--ro counters
|   |   |--ro keepalive-in-messages?     int32
|   |   |--ro keepalive-out-messages?    int32
|   |   |--ro open-messages-in?         int32
|   |   |--ro open-messages-out?       int32
|   |   |--ro as-path-count?           int32
|   |   |--ro as-path-extended-count?   int32

```

---

---

```

| | | +--ro received-packet-count?      int32
| | | +--ro packet-in-queue?           int32
| | | +--ro packet-out-queue?         int32
| | | +--ro sent-packet-count?        int32
| | | +--ro refresh-received-packet-count? int32
| | | +--ro refresh-sent-packet-count?  int32
| | | +--ro afi?                      ipi-bgp-types:bgp_afi_type_t
| | | +--ro safi?                     ipi-bgp-types:bgp_safi_type_t
| | | +--ro additional-paths-mode?     ipi-bgp-types:bgp_peer_additional_path_type_t {feature-
list:HAVE_BGP_ADD_PATH}?
| | | +--ro additional-path-select-all? empty {feature-list:HAVE_BGP_ADD_PATH}?
| | | +--ro additional-paths-best-select-count? uint8 {feature-list:HAVE_BGP_ADD_PATH}?
| | | +--ro route-server-client?      empty
| | | +--ro next-hop-self?            empty
| | | +--ro bgp-port?                 uint16
| | | +--ro activate?                 empty
| | | +--ro de-activate?              empty
| | | +--ro default-peer-route-map-name? empty
| | | +--ro peer-route-map-orig-name?  string
| | | +--ro soft-reconfig?            ipi-bgp-types:bgp_update_clear_t
| | | +--ro weight?                   uint16
| | | +--ro peer-route-reflector?     empty
| | | +--ro peer-remove-private-as?   empty
| | | +--ro no-send-community?        empty
| | | +--ro no-send-community-type?   ipi-bgp-types:bgp_send_commu_type_t
| | | +--ro neighbor-attribute-unchanged? ipi-bgp-types:bgp_attribute_unchanged_type_t
| | | +--ro orf-prefix-capability?    ipi-bgp-types:bgp_orf_prefix_type_t
| | | +--ro peer-allow-ebgp-vpn?      empty {feature-list:HAVE_VRF}?
| | | +--ro allow-as-number?          uint32
| | | +--ro capability-graceful-restart? empty
| | | +--ro extended-nexthop-encode?  empty
| | | +--ro mapped-peer-group-tag-af?  string
| | | +--ro unsuppress-route-map-name? string
| | | +--ro max-paths-ibgp?           int16
| | | +--ro configured-max-paths-ebgp? int16
| | | +--ro max-paths-ebgp?           int16
| | | +--ro configured-max-paths-ibgp? int16

```

---

---

		++ro max-paths-eibgp?	int16
		++ro configured-max-paths-eibgp?	int16
		++ro community-count?	int32
		++ro confederation-id-check?	boolean
		++ro peer-and-extended-asn-capability?	ipi-bgp-types:bgp_adv_rcv_type_t
		++ro address-family-capability?	ipi-bgp-types:bgp_adv_rcv_type_t
		++ro ipv6-next-hop-global?	inet:ipv6-address
		++ro ipv6-next-hop-local?	inet:ipv6-address
		++ro remote-port?	int32
		++ro remote-address?	ipi-bgp-types:bgp_hostname_t
		++ro local-host?	ipi-bgp-types:bgp_hostname_t
		++ro ipv4-next-hop?	inet:ipv4-address
		++ro local-port?	int32
		++ro default-information-originate?	boolean
		++ro inbound-path-policy?	boolean
		++ro outbound-path-policy?	boolean
		++ro default-originate-information-sent?	cml-data-types:cml_line_t
		++ro graceful-restart?	ipi-bgp-types:bgp_adv_rcv_type_t
		++ro address-family-dependent-capability?	boolean
		++ro peer-address-family-table-version?	int32
		++ro address-family-table-version?	int32
		++ro forward-status-preserve?	string
		++ro orf-type-prefix?	cml-data-types:cml_line_t
		++ro orf-type-prefix-send-mode?	ipi-bgp-types:bgp_adv_rcv_type_t
		++ro orf-type-prefix-receive-mode?	ipi-bgp-types:bgp_adv_rcv_type_t
		++ro orf-type-prefix-old?	cml-data-types:cml_line_t
		++ro orf-type-prefix-send-mode-old?	ipi-bgp-types:bgp_adv_rcv_type_t
		++ro orf-type-prefix-receive-mode-old?	ipi-bgp-types:bgp_adv_rcv_type_t
		++ro prefix-count?	int32
		++ro send-prefix-count?	int32
		++ro flag-shut-down?	ipi-bgp-types:bgp_peerflag_shutdown_t
		++ro count?	int32
		++ro notify-info?	boolean
		++ro notify-last-reset-time?	string
		++ro connection-type?	ipi-bgp-types:bgp_connection_type_t
		++ro next-connection-timer?	int32

---

---

```

|   | +--ro connection-dropped-count?      int32
|   | +--ro graceful-restart-status?       string
|   | +--ro graceful-restart-time?        int32
|   | +--ro bgp-established-up-time?      string
|   | +--ro last-read-time?               string
|   | +--ro link-type?                    ipi-bgp-types:bgp_link_type_t
|   | +--ro ebgp-hop-away-count?          int32
|   | +--ro router-id?                    inet:ipv4-address
|   | +--ro advertisement-interval?       int32
|   | +--ro calculated-hold-time?         int32
|   | +--ro calculated-keepalive?        int32
|   | +--ro dynamic-capability?          cml-data-types:cml_line_t
|   | +--ro route-refresh-capability?     ipi-bgp-types:bgp_route_refresh_cap_type_t
|   | +--ro no-interface-binding?        boolean
|   | +--ro additional-path-receive-capability? string {feature-list:HAVE_BGP_ADD_PATH}?
|   | +--ro additional-path-send-capability? string {feature-list:HAVE_BGP_ADD_PATH}?
|   | +--ro capability-ipv4-unicast?      ipi-bgp-types:bgp_capability_type_t
|   | +--ro capability-ipv4-multicast?    ipi-bgp-types:bgp_capability_type_t
|   | +--ro capability-vpnv4-unicast?     ipi-bgp-types:bgp_capability_type_t
|   | +--ro capability-vpnv6-unicast?     ipi-bgp-types:bgp_capability_type_t
|   | +--ro capability-rtfilter-unicast?  ipi-bgp-types:bgp_capability_type_t
|   | +--ro capability-l2vpn-evpn?        ipi-bgp-types:bgp_capability_type_t
|   | +--ro capability-ipv6-unicast?      ipi-bgp-types:bgp_capability_type_t
|   | +--ro capability-ipv6-multicast?    ipi-bgp-types:bgp_capability_type_t
|   | +--ro capability-ipv6-label-unicast? ipi-bgp-types:bgp_capability_type_t
|   | +--ro evpn-ad-route-count?          uint32 {feature-list:HAVE_BGP_EVPN}?
|   | +--ro evpn-mac-ip-route-count?      uint32 {feature-list:HAVE_BGP_EVPN}?
|   | +--ro evpn-inclusive-multicast-route-count? uint32 {feature-list:HAVE_BGP_EVPN}?
|   | +--ro evpn-segment-route-count?     uint32 {feature-list:HAVE_BGP_EVPN}?
|   | +--ro evpn-ip-prefix-route-count?   uint32 {feature-list:HAVE_BGP_EVPN}?
|   +--rw maximum-prefixes
|   | +--rw maximum-prefix* [prefix-count]
|   |   +--rw prefix-count  -> ../config/prefix-count
|   |   +--rw config
|   |     | +--rw prefix-count?          uint32
|   |     | +--rw stop-update?          empty

```

---

---

```
| | | +--rw maximum-prefix-warning? empty
| | | +--rw threshold-percentage? uint8
| | | +--rw warning-only? empty
| | +--ro state
| |   +--ro prefix-count? uint32
| |   +--ro stop-update? empty
| |   +--ro maximum-prefix-warning? empty
| |   +--ro threshold-percentage? uint8
| |   +--ro warning-only? empty
| +--rw distribute-list-filters
| | +--rw distribute-list-filter* [filter-direction]
| |   +--rw filter-direction -> ../config/filter-direction
| |   +--rw config
| |     | +--rw access-list-identifier string
| |     | +--rw filter-direction? ipi-bgp-types:bgp_distribute_list_direction_t
| |     +--ro state
| |       +--ro access-list-identifier string
| |       +--ro filter-direction? ipi-bgp-types:bgp_distribute_list_direction_t
| +--rw as-list-filters
| | +--rw as-list-filter* [as-list-direction]
| |   +--rw as-list-direction -> ../config/as-list-direction
| |   +--rw config
| |     | +--rw as-access-list-identifier string
| |     | +--rw as-list-direction? ipi-bgp-types:bgp_distribute_list_direction_t
| |     +--ro state
| |       +--ro as-access-list-identifier string
| |       +--ro as-list-direction? ipi-bgp-types:bgp_distribute_list_direction_t
| +--rw prefix-list-filters
| | +--rw prefix-list-filter* [prefix-filter-direction]
| |   +--rw prefix-filter-direction -> ../config/prefix-filter-direction
| |   +--rw config
| |     | +--rw prefix-list-name string
| |     | +--rw prefix-filter-direction? ipi-bgp-types:bgp_distribute_list_direction_t
| |     +--ro state
| |       +--ro prefix-list-name string
| |       +--ro prefix-filter-direction? ipi-bgp-types:bgp_distribute_list_direction_t
```

```

|   +--rw route-map-filters
|   |   +--rw route-map-filter* [route-map-direction]
|   |   |   +--rw route-map-direction  -> ../config/route-map-direction
|   |   |   +--rw config
|   |   |   |   +--rw route-map-name      string
|   |   |   |   +--rw route-map-direction? ipi-bgp-types:bgp_distribute_list_direction_t
|   |   |   +--ro state
|   |   |   |   +--ro route-map-name      string
|   |   |   |   +--ro route-map-direction? ipi-bgp-types:bgp_distribute_list_direction_t
|   +--ro outbound-route-filter
|   |   +--ro state
|   |   |   +--ro orf-prefix-string?  boolean
|   |   |   +--ro orf-prefix-send?   string
|   |   |   +--ro orf-prefix-count?  string
|   |   |   +--ro orf-wait-refresh?  boolean
|   +--ro peer-prefix
|   |   +--ro state
|   |   |   +--ro entry-sequence?   int32
|   |   |   +--ro entry-type?       ipi-bgp-types:bgp_prefix_entry_type_t
|   |   |   +--ro entry-max-length? int32
|   |   |   +--ro entry-min-length? int32
|   |   |   +--ro prefix-length?   int32
|   +--ro peer-index
|   |   +--ro state
|   |   |   +--ro peer-index?  int32
|   |   |   +--ro offset?     int32
|   |   |   +--ro mask?      string
|   +--rw aigp {feature-list:HAVE_BGP_AIGP}?
|   |   +--rw config
|   |   |   +--rw admin-status?  cml-data-types:cml_enable_disable_t {feature-list:HAVE_BGP_AIGP}?
|   |   |   +--rw aigp-send-med? empty
|   |   +--ro state
|   |   |   +--ro admin-status?  cml-data-types:cml_enable_disable_t {feature-list:HAVE_BGP_AIGP}?
|   |   |   +--ro aigp-send-med? empty
|   +--rw cost-community {feature-list:HAVE_BGP_AIGP}?
|   |   +--rw config!

```

```

|          | +--rw send-cost-community-id  uint8 {feature-list:HAVE_BGP_AIGP}?
|          | +--rw point-of-insertion      ipi-bgp-types:bgp_aigp_metric_cost_community_poi_t {feature-
list:HAVE_BGP_AIGP}?
|          | +--rw enable-transitive?      empty {feature-list:HAVE_BGP_AIGP}?
|          +--ro state
|          +--ro send-cost-community-id    uint8 {feature-list:HAVE_BGP_AIGP}?
|          +--ro point-of-insertion        ipi-bgp-types:bgp_aigp_metric_cost_community_poi_t {feature-
list:HAVE_BGP_AIGP}?
|          +--ro enable-transitive?        empty {feature-list:HAVE_BGP_AIGP}?
+--rw address-family-vrfs
+--rw address-family-vrf* [afi safi vrf-name]
+--rw afi                -> ../config/afi
+--rw safi                -> ../config/safi
+--rw vrf-name            -> ../config/vrf-name
+--rw config
| +--rw enable-auto-summary?          empty
| +--rw enable-network-igp-sync?      empty
| +--rw enable-igp-sync?              empty
| +--rw enable-bgp-implicit-null?     empty
| +--rw afi?                          ipi-bgp-types:bgp_vrf_afi_type_t
| +--rw safi?                          ipi-bgp-types:bgp_vrf_safi_type_t
| +--rw vrf-name?                      string
| +--rw multipath-relax?               empty
| +--rw graceful-shutdown?            empty
| +--rw graceful-shutdown-capable?     empty
| +--rw graceful-shutdown-local-preference?  uint32
| +--rw additional-paths-mode?         ipi-bgp-types:bgp_additional_path_type_t {feature-
list:HAVE_BGP_ADD_PATH}?
| +--rw additional-path-select-all?    empty {feature-list:HAVE_BGP_ADD_PATH}?
| +--rw additional-paths-best-select-count?  uint8 {feature-list:HAVE_BGP_ADD_PATH}?
+--ro state
| +--ro enable-auto-summary?          empty
| +--ro enable-network-igp-sync?      empty
| +--ro enable-igp-sync?              empty
| +--ro enable-bgp-implicit-null?     empty
| +--ro afi?                          ipi-bgp-types:bgp_vrf_afi_type_t
| +--ro safi?                          ipi-bgp-types:bgp_vrf_safi_type_t

```

```

| +--ro vrf-name?          string
| +--ro multipath-relax?   empty
| +--ro graceful-shutdown? empty
| +--ro graceful-shutdown-capable? empty
| +--ro graceful-shutdown-local-preference? uint32
| +--ro additional-paths-mode? ipi-bgp-types:bgp_additional_path_type_t {feature-
list:HAVE_BGP_ADD_PATH}?
| +--ro additional-path-select-all? empty {feature-list:HAVE_BGP_ADD_PATH}?
| +--ro additional-paths-best-select-count? uint8 {feature-list:HAVE_BGP_ADD_PATH}?
+--rw confederation
| +--rw config
| | +--rw identifier?    uint32
| | +--rw peer-as-number* uint32
| +--ro state
|   +--ro identifier?    uint32
|   +--ro peer-as-number* uint32
+--rw distances
| +--rw distance* [ebgp ibgp local]
|   +--rw ebgp  -> ../config/ebgp
|   +--rw ibgp  -> ../config/ibgp
|   +--rw local -> ../config/local
|   +--rw config
|     | +--rw ebgp?  uint8
|     | +--rw ibgp?  uint8
|     | +--rw local? uint8
|     +--ro state
|       +--ro ebgp?  uint8
|       +--ro ibgp?  uint8
|       +--ro local? uint8
+--rw maximum-paths
| +--rw config
| | +--rw ebgp-max-path? int32
| | +--rw ibgp-max-path? int32
| | +--rw eibgp-max-path? int32
| +--ro state
|   +--ro ebgp-max-path? int32
|   +--ro ibgp-max-path? int32

```

---

```
|  +--ro eibgp-max-path?  int32
+--rw table-map {feature-list:HAVE_BGP_TABLE_MAP}?
| +--rw config!
| | +--rw map-name      string {feature-list:HAVE_BGP_TABLE_MAP}?
| | +--rw table-map-filter?  boolean {feature-list:HAVE_BGP_TABLE_MAP}?
| +--ro state
|   +--ro map-name      string {feature-list:HAVE_BGP_TABLE_MAP}?
|   +--ro table-map-filter?  boolean {feature-list:HAVE_BGP_TABLE_MAP}?
+--rw route-flap-dampenings
| +--rw route-flap-dampening* [enable-dampening]
|   +--rw enable-dampening  -> ../config/enable-dampening
|   +--rw config
|   | +--rw enable-dampening?  ipi-bgp-types:bgp_dampening_t
|   | +--rw reach-half-life?   uint32
|   | +--rw reuse-penalty?    uint32
|   | +--rw suppress-penalty?  uint32
|   | +--rw max-suppress-time? uint32
|   | +--rw unreach-half-life? uint32
|   | +--rw dampening-rmap-name? string
|   +--ro state
|     +--ro enable-dampening?  ipi-bgp-types:bgp_dampening_t
|     +--ro reach-half-life?   uint32
|     +--ro reuse-penalty?    uint32
|     +--ro suppress-penalty?  uint32
|     +--ro max-suppress-time? uint32
|     +--ro unreach-half-life? uint32
|     +--ro dampening-rmap-name? string
+--rw route-redistribute-lists
| +--rw route-redistribute-list* [protocol-type]
|   +--rw protocol-type  -> ../config/protocol-type
|   +--rw config
|   | +--rw protocol-type?      ipi-bgp-types:bgp_redistribute_type_t
|   | +--rw redist-route-map-name? string
|   +--ro state
|     +--ro protocol-type?      ipi-bgp-types:bgp_redistribute_type_t
|     +--ro redist-route-map-name? string
```

```
+--rw bgp-redistribute-ospfs
| +--rw bgp-redistribute-ospf* [ospf-instance-number]
|   +--rw ospf-instance-number -> ../config/ospf-instance-number
|   +--rw config
|     | +--rw ospf-instance-number?      ipi-bgp-types:cml_ospf_area_id_t
|     | +--rw redistribute-ospf-route-map? string
|     +--ro state
|       +--ro ospf-instance-number?      ipi-bgp-types:cml_ospf_area_id_t
|       +--ro redistribute-ospf-route-map? string
+--rw vrf-peers
| +--rw vrf-peer* [peer-address]
|   +--rw peer-address          -> ../config/peer-address
|   +--ro peer-adj-out-route* [network-address]
|     | +--ro network-address -> ../state/network-address
|     | +--ro next-hop* [next-hop-address]
|     | | +--ro next-hop-address -> ../state/next-hop-address
|     | | +--ro state
|     | | | +--ro next-hop-address?      ipi-bgp-types:bgp_hostname_t
|     | | | +--ro peer-network-weight?   uint32
|     | | | +--ro flap-time-reuse-list?  string
|     | | | +--ro flap-record-duration?  string
|     | | | +--ro damp-time-to-reuse?    string
|     | | | +--ro bgp-med-value?         uint32
|     | | | +--ro bgp-as-path-string*    cml-data-types:cml_line_t
|     | | | +--ro bgp-as-path-4-byte-string* string
|     | | | +--ro bgp-as-path-4-byte-origin? ipi-bgp-types:bgp_origin_t
|     | | | +--ro ibgp-metric-route?     int32
|     | | | +--ro aggregate-as-route?    int32
|     | | | +--ro aggregator-address-route? ipi-bgp-types:bgp_hostname_t
|     | | | +--ro network-remote-address-route? ipi-bgp-types:bgp_hostname_t
|     | | | +--ro originator-id-route?   ipi-bgp-types:bgp_hostname_t
|     | | | +--ro route-peer-address?    ipi-bgp-types:bgp_hostname_t
|     | | | +--ro route-local-preference? uint32
|     | | | +--ro route-prefix-label?    uint32
|     | | | +--ro route-community-string? string
|     | | | +--ro cluster-list-route*    ipi-bgp-types:bgp_hostname_t
```

---

```

| | | +--ro route-penalty?          int32
| | | +--ro route-flap-count?       int32
| | | +--ro last-update-route?      yang:date-and-time
| | | +--ro reflector-client-route?  boolean
| | | +--ro route-dampening-active?  boolean
| | | +--ro history-route?          boolean
| | | +--ro nexthop-valid-route?     boolean
| | | +--ro med-flag-type-route?     boolean
| | | +--ro valid-route?            boolean
| | | +--ro stale-route?            boolean
| | | +--ro route-type?             ipi-bgp-types:bgp_ri_type_t
| | | +--ro ecmp-multi-candidate-route?  boolean
| | | +--ro multi-installed-route?    boolean
| | | +--ro route-synchronized-flag-route?  boolean
| | | +--ro atomic-aggregate-route?    boolean
| | | +--ro selected-route?          boolean
| | | +--ro bgp-tx-path-id?          int16 {feature-list:HAVE_BGP_ADD_PATH}?
| | | +--ro bgp-rx-path-id?          int16 {feature-list:HAVE_BGP_ADD_PATH}?
| | | +--ro ipv4-multicast-capability?  string
| | | +--ro vpv4-unicast-capability?   string
| | | +--ro rfilter-unicast-capability? string
| | | +--ro l2vpn-evpn-capability?     string
| | | +--ro ipv6-unicast-capability?   string
| | | +--ro ipv6-multicast-capability?  string
| | | +--ro ipv6-label-unicast-capability? string
| | +--ro state
| |   +--ro network-address? ipi-bgp-types:bgp_ip_network_t
| |   +--ro peer-adj-in-route* [network-address]
| |     +--ro network-address  -> ../state/network-address
| |     +--ro next-hop* [next-hop-address]
| |       +--ro next-hop-address  -> ../state/next-hop-address
| |       +--ro state
| |         +--ro next-hop-address? ipi-bgp-types:bgp_hostname_t
| |         +--ro peer-network-weight? uint32
| |         +--ro flap-time-reuse-list? string
| |         +--ro flap-record-duration? string

```

---

---

		+--ro damp-time-to-reuse?	string
		+--ro bgp-med-value?	uint32
		+--ro bgp-as-path-string*	cml-data-types:cml_line_t
		+--ro bgp-as-path-4-byte-string*	string
		+--ro bgp-as-path-4-byte-origin?	ipi-bgp-types:bgp_origin_t
		+--ro ibgp-metric-route?	int32
		+--ro aggregate-as-route?	int32
		+--ro aggregator-address-route?	ipi-bgp-types:bgp_hostname_t
		+--ro network-remote-address-route?	ipi-bgp-types:bgp_hostname_t
		+--ro originator-id-route?	ipi-bgp-types:bgp_hostname_t
		+--ro route-peer-address?	ipi-bgp-types:bgp_hostname_t
		+--ro route-local-preference?	uint32
		+--ro route-prefix-label?	uint32
		+--ro route-community-string?	string
		+--ro cluster-list-route*	ipi-bgp-types:bgp_hostname_t
		+--ro route-penalty?	int32
		+--ro route-flap-count?	int32
		+--ro last-update-route?	yang:date-and-time
		+--ro reflector-client-route?	boolean
		+--ro route-dampening-active?	boolean
		+--ro history-route?	boolean
		+--ro nexthop-valid-route?	boolean
		+--ro med-flag-type-route?	boolean
		+--ro valid-route?	boolean
		+--ro stale-route?	boolean
		+--ro route-type?	ipi-bgp-types:bgp_ri_type_t
		+--ro ecmp-multi-candidate-route?	boolean
		+--ro multi-installed-route?	boolean
		+--ro route-synchronized-flag-route?	boolean
		+--ro atomic-aggregate-route?	boolean
		+--ro selected-route?	boolean
		+--ro bgp-tx-path-id?	int16 {feature-list:HAVE_BGP_ADD_PATH}?
		+--ro bgp-rx-path-id?	int16 {feature-list:HAVE_BGP_ADD_PATH}?
		+--ro ipv4-multicast-capability?	string
		+--ro vpv4-unicast-capability?	string
		+--ro rfilter-unicast-capability?	string

---

---

```

| | | +--ro l2vpn-evpn-capability?    string
| | | +--ro ipv6-unicast-capability?  string
| | | +--ro ipv6-multicast-capability? string
| | | +--ro ipv6-label-unicast-capability? string
| | +--ro state
| | +--ro network-address? ipi-bgp-types:bgp_ip_network_t
| +--rw config
| | +--rw peer-address?              inet:ip-address
| | +--rw peer-as?                  uint32
| | +--rw source-identifier?        string
| | +--rw bgp-version?              uint8
| | +--rw peer-connection-interval? uint32
| | +--rw enforce-multihop?         empty
| | +--rw peer-shutdown?            empty
| | +--rw peer-shutdown-description? cml-data-types:cml_line_t
| | +--rw neighbor-passive?         empty
| | +--rw disable-capability-negotiation? empty
| | +--rw enable-dynamic-capability? empty
| | +--rw min-route-advertisement-interval? uint32
| | +--rw peer-as-origin-interval?  uint32
| | +--rw neighbor-as-override?     empty
| | +--rw peer-interface-name?      string {feature-list:HAVE_VRF}?
| | +--rw peer-description?         cml-data-types:cml_line_t
| | +--rw peer-restart-time?        uint32 {feature-list:HAVE_RESTART,feature-list:HAVE_VRF}?
| | +--rw graceful-shut?            empty
| | +--rw graceful-shut-timer?      uint32
| | +--rw enable-peer-bfd?          empty {feature-list:HAVE_BFD}?
| | +--rw enable-peer-bfd-multihop? empty {feature-list:HAVE_BFD}?
| | +--rw bgp-port?                 uint16
| | +--rw activate?                 empty
| | +--rw de-activate?              empty
| | +--rw default-peer-route-map-name? empty
| | +--rw peer-route-map-orig-name?  string
| | +--rw weight?                   uint16
| | +--rw peer-route-reflector?     empty
| | +--rw peer-remove-private-as?   empty

```

---

---

```

| | +-rw no-send-community?          empty
| | +-rw no-send-community-type?     ipi-bgp-types:bgp_send_commu_type_t
| | +-rw neighbor-attribute-unchanged? ipi-bgp-types:bgp_attribute_unchanged_type_t
| | +-rw orf-prefix-capability?      ipi-bgp-types:bgp_orf_prefix_type_t
| | +-rw peer-allow-ebgp-vpn?        empty {feature-list:HAVE_VRF}?
| | +-rw allow-as-number?            uint32
| | +-rw capability-graceful-restart? empty
| | +-rw mapped-peer-group-tag-af?   string
| | +-rw unsuppress-route-map-name?  string
| | +-rw enable-ext-opt-param-len?   empty
| | +-rw additional-paths-mode?      ipi-bgp-types:bgp_peer_additional_path_type_t {feature-
list:HAVE_BGP_ADD_PATH}?
| | +-rw additional-path-select-all? empty {feature-list:HAVE_BGP_ADD_PATH}?
| | +-rw additional-paths-best-select-count? uint8 {feature-list:HAVE_BGP_ADD_PATH}?
| | +-rw tcp-adjust-mss?             uint16
| | +-rw site-origin-identifier?     string {feature-list:HAVE_VRF}?
| +-ro state
| | +-ro counters
| | | +-ro keepalive-in-messages?    int32
| | | +-ro keepalive-out-messages?   int32
| | | +-ro open-messages-in?         int32
| | | +-ro open-messages-out?        int32
| | | +-ro as-path-count?            int32
| | | +-ro as-path-extended-count?   int32
| | | +-ro received-packet-count?    int32
| | | +-ro packet-in-queue?          int32
| | | +-ro packet-out-queue?         int32
| | | +-ro sent-packet-count?        int32
| | | +-ro refresh-received-packet-count? int32
| | | +-ro refresh-sent-packet-count? int32
| | | +-ro notification-in?          int32
| | | +-ro notification-out?         int32
| | | +-ro update-message-in?        int32
| | | +-ro update-message-out?       int32
| | +-ro peer-address?               inet:ip-address
| | +-ro peer-as?                    uint32
| | +-ro source-identifier?          string

```

---

---

		++ro bgp-version?	uint8
		++ro peer-connection-interval?	uint32
		++ro enforce-multihop?	empty
		++ro peer-shutdown?	empty
		++ro peer-shutdown-description?	cml-data-types:cml_line_t
		++ro neighbor-passive?	empty
		++ro disable-capability-negotiation?	empty
		++ro enable-dynamic-capability?	empty
		++ro min-route-advertisement-interval?	uint32
		++ro peer-as-origin-interval?	uint32
		++ro neighbor-as-override?	empty
		++ro peer-interface-name?	string {feature-list:HAVE_VRF}?
		++ro peer-description?	cml-data-types:cml_line_t
		++ro peer-restart-time?	uint32 {feature-list:HAVE_RESTART,feature-list:HAVE_VRF}?
		++ro graceful-shut?	empty
		++ro graceful-shut-timer?	uint32
		++ro enable-peer-bfd?	empty {feature-list:HAVE_BFD}?
		++ro enable-peer-bfd-multihop?	empty {feature-list:HAVE_BFD}?
		++ro bgp-port?	uint16
		++ro activate?	empty
		++ro de-activate?	empty
		++ro default-peer-route-map-name?	empty
		++ro peer-route-map-orig-name?	string
		++ro weight?	uint16
		++ro peer-route-reflector?	empty
		++ro peer-remove-private-as?	empty
		++ro no-send-community?	empty
		++ro no-send-community-type?	ipi-bgp-types:bgp_send_commu_type_t
		++ro neighbor-attribute-unchanged?	ipi-bgp-types:bgp_attribute_unchanged_type_t
		++ro orf-prefix-capability?	ipi-bgp-types:bgp_orf_prefix_type_t
		++ro peer-allow-ebgp-vpn?	empty {feature-list:HAVE_VRF}?
		++ro allow-as-number?	uint32
		++ro capability-graceful-restart?	empty
		++ro mapped-peer-group-tag-af?	string
		++ro unsuppress-route-map-name?	string
		++ro enable-ext-opt-param-len?	empty

---

---

```

| | +-ro additional-paths-mode?      ipi-bgp-types:bgp_peer_additional_path_type_t {feature-
list:HAVE_BGP_ADD_PATH}?
| | +-ro additional-path-select-all?  empty {feature-list:HAVE_BGP_ADD_PATH}?
| | +-ro additional-paths-best-select-count?  uint8 {feature-list:HAVE_BGP_ADD_PATH}?
| | +-ro tcp-adjust-mss?              uint16
| | +-ro site-origin-identifier?      string {feature-list:HAVE_VRF}?
| | +-ro connection-established-count?    int32
| | +-ro error-notify-sent?           boolean
| | +-ro notify-code-string?          cml-data-types:cml_line_t
| | +-ro bgp-peer-state?              ipi-bgp-types:bgp_peer_status_t
| | +-ro max-paths-ibgp?              int16
| | +-ro configured-max-paths-ebgp?    int16
| | +-ro max-paths-ebgp?              int16
| | +-ro configured-max-paths-ibgp?    int16
| | +-ro max-paths-eibgp?             int16
| | +-ro configured-max-paths-eibgp?   int16
| | +-ro community-count?             int32
| | +-ro confederation-id-check?      boolean
| | +-ro peer-and-extended-asn-capability?  ipi-bgp-types:bgp_adv_rcv_type_t
| | +-ro address-family-capability?     ipi-bgp-types:bgp_adv_rcv_type_t
| | +-ro ipv6-next-hop-global?         inet:ipv6-address
| | +-ro ipv6-next-hop-local?         inet:ipv6-address
| | +-ro remote-port?                 int32
| | +-ro remote-address?              ipi-bgp-types:bgp_hostname_t
| | +-ro local-host?                  ipi-bgp-types:bgp_hostname_t
| | +-ro ipv4-next-hop?                inet:ipv4-address
| | +-ro local-port?                  int32
| | +-ro default-information-originate?  boolean
| | +-ro inbound-path-policy?          boolean
| | +-ro outbound-path-policy?         boolean
| | +-ro default-originate-information-sent?  cml-data-types:cml_line_t
| | +-ro graceful-restart?            ipi-bgp-types:bgp_adv_rcv_type_t
| | +-ro address-family-dependent-capability?  boolean
| | +-ro peer-address-family-table-version?  int32
| | +-ro address-family-table-version?    int32
| | +-ro forward-status-preserve?      string
| | +-ro orf-type-prefix?              cml-data-types:cml_line_t

```

---

---

		++ro orf-type-prefix-send-mode?	ipi-bgp-types:bgp_adv_rcv_type_t
		++ro orf-type-prefix-receive-mode?	ipi-bgp-types:bgp_adv_rcv_type_t
		++ro orf-type-prefix-old?	cml-data-types:cml_line_t
		++ro orf-type-prefix-send-mode-old?	ipi-bgp-types:bgp_adv_rcv_type_t
		++ro orf-type-prefix-receive-mode-old?	ipi-bgp-types:bgp_adv_rcv_type_t
		++ro prefix-count?	int32
		++ro send-prefix-count?	int32
		++ro flag-shut-down?	ipi-bgp-types:bgp_peerflag_shutdown_t
		++ro count?	int32
		++ro notify-info?	boolean
		++ro notify-last-reset-time?	string
		++ro connection-type?	ipi-bgp-types:bgp_connection_type_t
		++ro next-connection-timer?	int32
		++ro connection-dropped-count?	int32
		++ro graceful-restart-status?	string
		++ro graceful-restart-time?	int32
		++ro bgp-established-up-time?	string
		++ro last-read-time?	string
		++ro link-type?	ipi-bgp-types:bgp_link_type_t
		++ro ebgp-hop-away-count?	int32
		++ro router-id?	inet:ipv4-address
		++ro advertisement-interval?	int32
		++ro calculated-hold-time?	int32
		++ro calculated-keepalive?	int32
		++ro dynamic-capability?	cml-data-types:cml_line_t
		++ro route-refresh-capability?	ipi-bgp-types:bgp_route_refresh_cap_type_t
		++ro no-interface-binding?	boolean
		++ro additional-path-receive-capability?	string {feature-list:HAVE_BGP_ADD_PATH}?
		++ro additional-path-send-capability?	string {feature-list:HAVE_BGP_ADD_PATH}?
		++ro capability-ipv4-unicast?	ipi-bgp-types:bgp_capability_type_t
		++ro capability-ipv4-multicast?	ipi-bgp-types:bgp_capability_type_t
		++ro capability-vpnv4-unicast?	ipi-bgp-types:bgp_capability_type_t
		++ro capability-vpnv6-unicast?	ipi-bgp-types:bgp_capability_type_t
		++ro capability-rtfilter-unicast?	ipi-bgp-types:bgp_capability_type_t
		++ro capability-l2vpn-evpn?	ipi-bgp-types:bgp_capability_type_t
		++ro capability-ipv6-unicast?	ipi-bgp-types:bgp_capability_type_t

---

---

```

| | +-ro capability-ipv6-multicast?      ipi-bgp-types:bgp_capability_type_t
| | +-ro capability-ipv6-label-unicast?  ipi-bgp-types:bgp_capability_type_t
| | +-ro evpn-ad-route-count?           uint32 {feature-list:HAVE_BGP_EVPN}?
| | +-ro evpn-mac-ip-route-count?       uint32 {feature-list:HAVE_BGP_EVPN}?
| | +-ro evpn-inclusive-multicast-route-count?  uint32 {feature-list:HAVE_BGP_EVPN}?
| | +-ro evpn-segment-route-count?      uint32 {feature-list:HAVE_BGP_EVPN}?
| | +-ro evpn-ip-prefix-route-count?    uint32 {feature-list:HAVE_BGP_EVPN}?
| +-rw timers
| | +-rw config!
| | | +-rw keep-alive  uint16
| | | +-rw hold-time   uint16
| | +-ro state
| | | +-ro keep-alive  uint16
| | | +-ro hold-time   uint16
| +-rw ebgp-multihop
| | +-rw config!
| | | +-rw maximum-hop-count?  uint8
| | | +-rw enabled             empty
| | +-ro state
| | | +-ro maximum-hop-count?  uint8
| | | +-ro enabled             empty
| +-rw maximum-prefixes
| | +-rw maximum-prefix* [prefix-count]
| | +-rw prefix-count  -> ../config/prefix-count
| | +-rw config
| | | +-rw prefix-count?      uint32
| | | +-rw stop-update?      empty
| | | +-rw maximum-prefix-warning?  empty
| | | +-rw threshold-percentage?  uint8
| | | +-rw warning-only?       empty
| | +-ro state
| | | +-ro prefix-count?      uint32
| | | +-ro stop-update?      empty
| | | +-ro maximum-prefix-warning?  empty
| | | +-ro threshold-percentage?  uint8
| | | +-ro warning-only?       empty

```

```
| +--rw bgp-passwords
| | +--rw bgp-password* [password]
| |   +--rw password -> ../config/password
| |   +--rw config
| |     | +--rw password?      ipi-bgp-types:bgp_md5_password_t {feature-list:HAVE_TCP_MD5SIG}?
| |     | +--rw auth-key-encrypt ipi-bgp-types:bgp_md5_t
| |     +--ro state
| |       +--ro password?      ipi-bgp-types:bgp_md5_password_t {feature-list:HAVE_TCP_MD5SIG}?
| |       +--ro auth-key-encrypt ipi-bgp-types:bgp_md5_t
| +--rw distribute-list-filters
| | +--rw distribute-list-filter* [filter-direction]
| |   +--rw filter-direction -> ../config/filter-direction
| |   +--rw config
| |     | +--rw access-list-identifier string
| |     | +--rw filter-direction?    ipi-bgp-types:bgp_distribute_list_direction_t
| |     +--ro state
| |       +--ro access-list-identifier string
| |       +--ro filter-direction?    ipi-bgp-types:bgp_distribute_list_direction_t
| +--rw as-list-filters
| | +--rw as-list-filter* [as-list-direction]
| |   +--rw as-list-direction -> ../config/as-list-direction
| |   +--rw config
| |     | +--rw as-access-list-identifier string
| |     | +--rw as-list-direction?    ipi-bgp-types:bgp_distribute_list_direction_t
| |     +--ro state
| |       +--ro as-access-list-identifier string
| |       +--ro as-list-direction?    ipi-bgp-types:bgp_distribute_list_direction_t
| +--rw prefix-list-filters
| | +--rw prefix-list-filter* [prefix-filter-direction]
| |   +--rw prefix-filter-direction -> ../config/prefix-filter-direction
| |   +--rw config
| |     | +--rw prefix-list-name      string
| |     | +--rw prefix-filter-direction? ipi-bgp-types:bgp_distribute_list_direction_t
| |     +--ro state
| |       +--ro prefix-list-name      string
| |       +--ro prefix-filter-direction? ipi-bgp-types:bgp_distribute_list_direction_t
```

---

```
| +--rw route-map-filters
| | +--rw route-map-filter* [route-map-direction]
| |   +--rw route-map-direction -> ../config/route-map-direction
| |   +--rw config
| |     | +--rw route-map-name      string
| |     | +--rw route-map-direction? ipi-bgp-types:bgp_distribute_list_direction_t
| |     +--ro state
| |       +--ro route-map-name      string
| |       +--ro route-map-direction? ipi-bgp-types:bgp_distribute_list_direction_t
| +--rw local-as
| | +--rw local-as-list* [peer-local-as]
| |   +--rw peer-local-as -> ../config/peer-local-as
| |   +--rw config
| |     | +--rw peer-local-as?      uint32
| |     | +--rw no-prepend-local-as? empty
| |     | +--rw replace-local-as?  empty
| |     +--ro state
| |       +--ro peer-local-as?      uint32
| |       +--ro no-prepend-local-as? empty
| |       +--ro replace-local-as?  empty
| +--ro outbound-route-filter
| | +--ro state
| |   +--ro orf-prefix-string?  boolean
| |   +--ro orf-prefix-send?    string
| |   +--ro orf-prefix-count?   string
| |   +--ro orf-wait-refresh?   boolean
| +--ro peer-prefix
| | +--ro state
| |   +--ro entry-sequence?     int32
| |   +--ro entry-type?        ipi-bgp-types:bgp_prefix_entry_type_t
| |   +--ro entry-max-length?  int32
| |   +--ro entry-min-length?  int32
| |   +--ro prefix-length?     int32
| +--ro peer-index
| | +--ro state
| |   +--ro peer-index?        int32
```

```
|     +--ro offset?    int32
|     +--ro mask?     string
+--rw network-lists
| +--rw network-list* [local-network-prefix]
|   +--rw local-network-prefix  -> ../config/local-network-prefix
|   +--rw config
|   | +--rw local-network-prefix? ipi-bgp-types:bgp_ip_network_t
|   | +--rw network-rmap-name?   string
|   | +--rw backdoor?           empty
|   +--ro state
|     +--ro local-network-prefix?      ipi-bgp-types:bgp_ip_network_t
|     +--ro network-rmap-name?        string
|     +--ro backdoor?                 empty
|     +--ro network-path-route-count?  int32
|     +--ro no-advertise-route?       string
|     +--ro no-export-route?          boolean
|     +--ro local-as-route?           boolean
|     +--ro suppress-route?          boolean
|     +--ro network-best-path-route-count?  int32
|     +--ro ip-routing-table?         string
|     +--ro advertised-non-peer-group-address* ipi-bgp-types:bgp_hostname_t
|     +--ro advertised-peer-group-name-route* string
|     +--ro advertised-any-peer?      boolean
+--rw peer-groups
  +--rw peer-group* [peer-group-tag]
    +--rw peer-group-tag      -> ../config/peer-group-tag
    +--rw config
    | +--rw bgp-port?          uint16
    | +--rw activate?         empty
    | +--rw default-peer-route-map-name?  empty
    | +--rw peer-route-map-orig-name?     string
    | +--rw weight?           uint16
    | +--rw peer-route-reflector?        empty
    | +--rw peer-remove-private-as?     empty
    | +--rw no-send-community?          empty
    | +--rw no-send-community-type?     ipi-bgp-types:bgp_send_commu_type_t
```

```

| +-rw neighbor-attribute-unchanged?    ipi-bgp-types:bgp_attribute_unchanged_type_t
| +-rw orf-prefix-capability?           ipi-bgp-types:bgp_orf_prefix_type_t
| +-rw peer-allow-ebgp-vpn?             empty {feature-list:HAVE_VRF}?
| +-rw allow-as-number?                 uint32
| +-rw capability-graceful-restart?     empty
| +-rw unsuppress-route-map-name?      string
| +-rw additional-paths-mode?           ipi-bgp-types:bgp_peer_additional_path_type_t {feature-
list:HAVE_BGP_ADD_PATH}?
| +-rw additional-path-select-all?     empty {feature-list:HAVE_BGP_ADD_PATH}?
| +-rw additional-paths-best-select-count? uint8 {feature-list:HAVE_BGP_ADD_PATH}?
| +-rw site-origin-identifier?         string {feature-list:HAVE_VRF}?
| +-rw peer-group-range                ipi-bgp-types:bgp_peer_group_type_t
| +-rw group-limit?                    uint8
| +-rw peer-group-tag?                 string
| +-rw peer-as?                        uint32
| +-rw source-identifier?              string
| +-rw bgp-version?                   uint8
| +-rw peer-connection-interval?       uint32
| +-rw enforce-multihop?               empty
| +-rw peer-shutdown?                 empty
| +-rw peer-shutdown-description?      cml-data-types:cml_line_t
| +-rw neighbor-passive?               empty
| +-rw disable-capability-negotiation? empty
| +-rw connection-retry-interval?      int32
| +-rw enable-dynamic-capability?     empty
| +-rw min-route-advertisement-interval? uint32
| +-rw peer-as-origin-interval?        uint32
| +-rw neighbor-as-override?           empty
| +-rw peer-description?               cml-data-types:cml_line_t
| +-rw peer-restart-time?              uint32 {feature-list:HAVE_RESTART,feature-list:HAVE_VRF}?
| +-rw graceful-shut?                  empty
| +-rw graceful-shut-timer?            uint32
| +-rw enable-peer-bfd?                 empty {feature-list:HAVE_BFD}?
| +-rw enable-peer-bfd-multihop?       empty {feature-list:HAVE_BFD}?
| +-rw enable-ext-opt-param-len?       empty
| +-rw tcp-adjust-mss?                  uint16
+--ro state

```

---

	++ro bgp-port?	uint16
	++ro activate?	empty
	++ro default-peer-route-map-name?	empty
	++ro peer-route-map-orig-name?	string
	++ro weight?	uint16
	++ro peer-route-reflector?	empty
	++ro peer-remove-private-as?	empty
	++ro no-send-community?	empty
	++ro no-send-community-type?	ipi-bgp-types:bgp_send_commu_type_t
	++ro neighbor-attribute-unchanged?	ipi-bgp-types:bgp_attribute_unchanged_type_t
	++ro orf-prefix-capability?	ipi-bgp-types:bgp_orf_prefix_type_t
	++ro peer-allow-ebgp-vpn?	empty {feature-list:HAVE_VRF}?
	++ro allow-as-number?	uint32
	++ro capability-graceful-restart?	empty
	++ro unsuppress-route-map-name?	string
	++ro additional-paths-mode?	ipi-bgp-types:bgp_peer_additional_path_type_t {feature-list:HAVE_BGP_ADD_PATH}?
	++ro additional-path-select-all?	empty {feature-list:HAVE_BGP_ADD_PATH}?
	++ro additional-paths-best-select-count?	uint8 {feature-list:HAVE_BGP_ADD_PATH}?
	++ro site-origin-identifier?	string {feature-list:HAVE_VRF}?
	++ro peer-group-range	ipi-bgp-types:bgp_peer_group_type_t
	++ro group-limit?	uint8
	++ro peer-group-tag?	string
	++ro peer-as?	uint32
	++ro source-identifier?	string
	++ro bgp-version?	uint8
	++ro peer-connection-interval?	uint32
	++ro enforce-multihop?	empty
	++ro peer-shutdown?	empty
	++ro peer-shutdown-description?	cml-data-types:cml_line_t
	++ro neighbor-passive?	empty
	++ro disable-capability-negotiation?	empty
	++ro connection-retry-interval?	int32
	++ro enable-dynamic-capability?	empty
	++ro min-route-advertisement-interval?	uint32
	++ro peer-as-origin-interval?	uint32
	++ro neighbor-as-override?	empty

---

---

```

| +-ro peer-description?          cml-data-types:cml_line_t
| +-ro peer-restart-time?        uint32 {feature-list:HAVE_RESTART,feature-list:HAVE_VRF}?
| +-ro graceful-shut?           empty
| +-ro graceful-shut-timer?      uint32
| +-ro enable-peer-bfd?         empty {feature-list:HAVE_BFD}?
| +-ro enable-peer-bfd-multihop? empty {feature-list:HAVE_BFD}?
| +-ro enable-ext-opt-param-len? empty
| +-ro tcp-adjust-mss?          uint16
+--rw optional-as-lists
| +-rw optional-as-list* [optional-as]
|   +-rw optional-as  -> ../config/optional-as
|   +-rw config
|     | +-rw optional-as?  uint32
|     +-ro state
|       +-ro optional-as?  uint32
+--rw bgp-passwords
| +-rw bgp-password* [password]
|   +-rw password  -> ../config/password
|   +-rw config
|     | +-rw password?      ipi-bgp-types:bgp_md5_password_t {feature-list:HAVE_TCP_MD5SIG}?
|     | +-rw auth-key-encrypt ipi-bgp-types:bgp_md5_t
|     +-ro state
|       +-ro password?      ipi-bgp-types:bgp_md5_password_t {feature-list:HAVE_TCP_MD5SIG}?
|       +-ro auth-key-encrypt ipi-bgp-types:bgp_md5_t
+--rw timers
| +-rw config!
| | +-rw keep-alive  uint16
| | +-rw hold-time   uint16
| +-ro state
|   +-ro keep-alive  uint16
|   +-ro hold-time   uint16
+--rw local-as
| +-rw local-as-list* [peer-local-as]
|   +-rw peer-local-as  -> ../config/peer-local-as
|   +-rw config
|     | +-rw peer-local-as?  uint32

```

---

---

```
| | +--rw no-prepend-local-as? empty
| | +--rw replace-local-as? empty
| +--ro state
|   +--ro peer-local-as? uint32
|   +--ro no-prepend-local-as? empty
|   +--ro replace-local-as? empty
+--rw ebgp-multihop
| +--rw config!
| | +--rw maximum-hop-count? uint8
| | +--rw enabled empty
| +--ro state
|   +--ro maximum-hop-count? uint8
|   +--ro enabled empty
+--rw maximum-prefixes
| +--rw maximum-prefix* [prefix-count]
|   +--rw prefix-count -> ../config/prefix-count
|   +--rw config
|     | +--rw prefix-count? uint32
|     | +--rw stop-update? empty
|     | +--rw maximum-prefix-warning? empty
|     | +--rw threshold-percentage? uint8
|     | +--rw warning-only? empty
|     +--ro state
|       +--ro prefix-count? uint32
|       +--ro stop-update? empty
|       +--ro maximum-prefix-warning? empty
|       +--ro threshold-percentage? uint8
|       +--ro warning-only? empty
+--rw distribute-list-filters
| +--rw distribute-list-filter* [filter-direction]
|   +--rw filter-direction -> ../config/filter-direction
|   +--rw config
|     | +--rw access-list-identifier string
|     | +--rw filter-direction? ipi-bgp-types:bgp_distribute_list_direction_t
|     +--ro state
|       +--ro access-list-identifier string
```

```

|   +--ro filter-direction?      ipi-bgp-types:bgp_distribute_list_direction_t
+--rw as-list-filters
| +--rw as-list-filter* [as-list-direction]
|   +--rw as-list-direction   -> ../config/as-list-direction
|   +--rw config
|   | +--rw as-access-list-identifier  string
|   | +--rw as-list-direction?      ipi-bgp-types:bgp_distribute_list_direction_t
|   +--ro state
|     +--ro as-access-list-identifier  string
|     +--ro as-list-direction?      ipi-bgp-types:bgp_distribute_list_direction_t
+--rw prefix-list-filters
| +--rw prefix-list-filter* [prefix-filter-direction]
|   +--rw prefix-filter-direction -> ../config/prefix-filter-direction
|   +--rw config
|   | +--rw prefix-list-name      string
|   | +--rw prefix-filter-direction? ipi-bgp-types:bgp_distribute_list_direction_t
|   +--ro state
|     +--ro prefix-list-name      string
|     +--ro prefix-filter-direction? ipi-bgp-types:bgp_distribute_list_direction_t
+--rw route-map-filters
+--rw route-map-filter* [route-map-direction]
  +--rw route-map-direction -> ../config/route-map-direction
  +--rw config
  | +--rw route-map-name      string
  | +--rw route-map-direction? ipi-bgp-types:bgp_distribute_list_direction_t
  +--ro state
    +--ro route-map-name      string
    +--ro route-map-direction? ipi-bgp-types:bgp_distribute_list_direction_t

```

rpcs:

```

+---x clear-ip-bgp-peer {feature-list:HAVE_BGPD}?
| +---w input
|   +---w arg          ipi-bgp-types:bgp_hostname_t
|   +---w peer-reset-description?  cml-data-types:cml_line_t
+---x clear-peer-group-l2vpn-evpn-soft-all {feature-list:HAVE_BGP_EVPN}?
| +---w input

```

---

```
| +---w peer-group-tag  string
| +---w soft-reconfig  ipi-bgp-types:bgp_update_clear_t
+---x clear-ip-bgp-all-peer {feature-list:HAVE_BGPD}?
| +---w input
| +---w peer-reset-description?  cml-data-types:cml_line_t
+---x clear-bgp-l2vpn-evpn-soft-all {feature-list:HAVE_BGP_EVPN}?
| +---w input
| +---w soft-reconfig  ipi-bgp-types:bgp_update_clear_t
+---x clear-bgp-remote-as-l2vpn-evpn-soft-all {feature-list:HAVE_BGP_EVPN}?
| +---w input
| +---w peer-as        uint32
| +---w soft-reconfig  ipi-bgp-types:bgp_update_clear_t
+---x clear-bgp-peer-address-l2vpn-evpn-soft {feature-list:HAVE_BGP_EVPN}?
| +---w input
| +---w peer-address   ipi-bgp-types:bgp_ip_addr_t
| +---w soft-reconfig  ipi-bgp-types:bgp_update_clear_t
+---x clear-ip-bgp-all-vrf {feature-list:HAVE_BGPD}?
| +---w input
| +---w vrf-name       string
| +---w peer-reset-description?  cml-data-types:cml_line_t
+---x clear-ip-bgp-vrf-peer {feature-list:HAVE_BGPD}?
| +---w input
| +---w vrf-name       string
| +---w address        ipi-bgp-types:bgp_hostname_t
| +---w peer-reset-description?  cml-data-types:cml_line_t
+---x bgp-graceful-restart {feature-list:HAVE_RESTART}?
+---x clear-bgp-statistics {feature-list:HAVE_BGPD}?
+---x bgp-snmp-restart {feature-list:HAVE_BGPD}?
+---x bgp-debug-on {feature-list:HAVE_BGPD}?
| +---w input
| +---w terminal-debug-options  ipi-bgp-types:bgp_debug_t
+---x bgp-debug-off {feature-list:HAVE_BGPD}?
| +---w input
| +---w terminal-debug-options  ipi-bgp-types:bgp_debug_t
+---x bgp-all-debug-off {feature-list:HAVE_BGPD}?
```

notifications:

```
+---n bgp-established-notification
| +--ro severity?    cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro peer-address? ipi-bgp-types:bgp_ip_addr_t
| +--ro bgp-as?      uint32
| +--ro peer-state?  ipi-bgp-types:bgp_peer_status_t
+---n bgp-backward-transition-notification
  +--ro severity?    cml-data-types:cml_notif_severity_t
  +--ro eventClass?  cml-data-types:cml_notif_class_t
  +--ro peer-address? ipi-bgp-types:bgp_ip_addr_t
  +--ro bgp-as?      uint32
  +--ro peer-state?  ipi-bgp-types:bgp_peer_status_t
```

---

## module: ipi-bridge-domain

augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance:

```
+--rw bridge-domain {feature-list:HAVE_SUBINTERFACE,feature-list:NOT_HAVE_SWFWDR}?
  +--rw config
  | +--rw domain-id?    -> /ipi-network-instance:network-instances/network-instance/instance-name
  | +--rw description?  cml-data-types:cml_line_t
  | +--rw route-interface? -> /ipi-interface:interfaces/interface/name
  +--rw bridge-instance
  | +--rw config!
  | | +--rw instance-id  uint8
  | | +--rw bridge-id    string
  | +--ro state
  |   +--ro instance-id  uint8
  |   +--ro bridge-id    string
  +--ro state
  | +--ro domain-id?    -> /ipi-network-instance:network-instances/network-instance/instance-name
  | +--ro description?  cml-data-types:cml_line_t
  | +--ro route-interface? -> /ipi-interface:interfaces/interface/name
  +--rw member-interfaces
    +--rw member-interface* [name]
```

```

+--rw name    -> ../config/name
+--rw config
| +--rw name? -> /ipi-interface:interfaces/interface/name
+--ro state
  +--ro name? -> /ipi-interface:interfaces/interface/name

```

---

## module: ipi-bridge

```

+--rw global-bridge-vlan-check
  +--rw global
    +--rw config
      | +--rw enable?  empty
    +--ro state
      +--ro enable?  empty

```

augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance:

```

+--rw bridge
  +--rw config!
    | +--rw protocol          ipi-bridge-types:bridge_protocol_t
    | +--rw disable-dynamic-learning?  empty
    | +--rw l2-protocol-destination-mac? cml-data-types:cml_mac_addr_t {feature-list:HAVE_PROVIDER_BRIDGE}?
    +--ro state
      | +--ro protocol          ipi-bridge-types:bridge_protocol_t
      | +--ro disable-dynamic-learning?  empty
      | +--ro l2-protocol-destination-mac? cml-data-types:cml_mac_addr_t {feature-list:HAVE_PROVIDER_BRIDGE}?
    +--rw bridge-ports
      | +--rw interface* [name]
      |   +--rw name    -> ../config/name
      |   +--rw config
      |     | +--rw name?          -> /ipi-interface:interfaces/interface/name
      |     | +--rw spanning-tree-protocol-status? ipi-bridge-types:bridge_spanningtree_enable_disable_t
      |     +--ro state
      |       +--ro name?          -> /ipi-interface:interfaces/interface/name
      |       +--ro spanning-tree-protocol-status? ipi-bridge-types:bridge_spanningtree_enable_disable_t
      |       +--ro switchport-mode?          ipi-port-vlan-types:port_vlan_switch_port_mode_t

```

```

+--rw fdb
  +--rw interfaces
    | +--rw interface* [interface-name]
    |   +--rw interface-name  -> ../config/interface-name
    |   +--rw config
    |     | +--rw interface-name?    -> /ipi-interface:interfaces/interface/name
    |     | +--rw disable-mac-learning  empty
    |     +--ro state
    |       +--ro interface-name?    -> /ipi-interface:interfaces/interface/name
    |       +--ro disable-mac-learning  empty
  +--rw static-mac-table
    | +--rw entry* [mac-address]
    |   +--rw mac-address  -> ../config/mac-address
    |   +--rw config
    |     | +--rw interface-name  -> /ipi-interface:interfaces/interface/name
    |     | +--rw mac-address?    cml-data-types:cml_mac_addr_t
    |     | +--rw action          ipi-bridge-types:bridge_discardforward_t
    |     +--ro state
    |       +--ro interface-name  -> /ipi-interface:interfaces/interface/name
    |       +--ro mac-address?    cml-data-types:cml_mac_addr_t
    |       +--ro action          ipi-bridge-types:bridge_discardforward_t
  +--rw dynamic-mac-table
    +--ro entry* [mac-address vlan-id] {feature-list:HAVE_HAL}?
      +--ro mac-address  -> ../state/mac-address
      +--ro vlan-id     -> ../state/vlan-id
      +--ro state {feature-list:HAVE_HAL}?
        +--ro mac-address?  cml-data-types:cml_mac_addr_t
        +--ro vlan-id?     uint16
        +--ro svlan-id?    uint16 {feature-list:HAVE_PROVIDER_BRIDGE}?
        +--ro interface-name? -> /ipi-interface:interfaces/interface/name
        +--ro action?      ipi-bridge-types:bridge_discardforward_t
        +--ro entry-time-out? uint32

```

rpcs:

```

+---x bridge-clear-provider-edge-mac-address-table {feature-list:HAVE_L2}?
| +---w input

```

---

```
| +---w mac-type    ipi-bridge-types:bridge_mac_type_t
| +---w cvlan-id   uint16
| +---w svlan-id   uint16
| +---w bridge-id  string
+---x bridge-clear-mac-address-table {feature-list:HAVE_L2}?
| +---w input
| +---w mac-type    ipi-bridge-types:bridge_mac_type_t
| +---w bridge-id   string
| +---w interface-name? string
| +---w mac-address? cml-data-types:cml_mac_addr_t
| +---w vlan-id?    uint16
+---x bridge-clear-provider-edge-dynamic-mac-address-table {feature-list:HAVE_L2}?
| +---w input
| +---w cvlan-id   uint16
| +---w svlan-id   uint16
| +---w bridge-id  string
+---x bridge-clear-dynamic-mac-address-table {feature-list:HAVE_L2}?
| +---w input
| +---w bridge-id   string
| +---w mac-address? cml-data-types:cml_mac_addr_t
| +---w interface-name? string
| +---w vlan-id?    uint16
+---x bridge-clear-allowed-ethertype-stats {feature-list:HAVE_ALLOWED_ETHERTYPE}?
| +---w input
| +---w interface-name? string
+---x bridge-clear-mstp-port-dynamic-mac-address-table {feature-list:HAVE_L2}?
+---w input
+---w interface-name string
+---w instance-id   uint32
+---w bridge-id     string
```

---

## module: ipi-cfm

```
+--rw cfm {feature-list:HAVE_CFM}?
  +--rw global
    | +--ro loopback
    | | +--ro state
    | |   +--ro counters
    | |     +--ro messages-transmitted?      yang:zero-based-counter32
    | |     +--ro replies-received?         yang:zero-based-counter32
    | |     +--ro out-of-order-replies-received? yang:zero-based-counter32
    | |     +--ro bad-msdu?                  yang:zero-based-counter32
    | +--rw linktrace
    |   +--rw cache
    |     | +--rw config!
    |     | | +--rw cache-enable  empty
    |     | | +--rw cache-size?  uint16
    |     | | +--ro state
    |     | |   +--ro cache-enable  empty
    |     | |   +--ro cache-size?  uint16
    |     | +--ro state
    |     |   +--ro counters
    |     |     +--ro messages-transmitted?      yang:zero-based-counter32
    |     |     +--ro replies-transmitted?      yang:zero-based-counter32
    |     |     +--ro valid-replies-received?   yang:zero-based-counter32
    |     |     +--ro unexpected-replies-received? yang:zero-based-counter32
  +--rw debug
    | +--rw config
    | | +--rw options? ipi-cfm-data-types:cfm_debug_t
    | +--ro state
    |   +--ro options?          ipi-cfm-data-types:cfm_debug_t
    |   +--ro terminal-debug-status? ipi-cfm-data-types:cfm_debug_t
  +--rw maintenance-domains
    +--rw maintenance-domain* [md-name]
      +--rw md-name          -> ../config/md-name
      +--rw config
      | +--rw md-name?      string
```

---

```

| +--rw type      ipi-cfm-data-types:cfm_md_type_t
| +--rw level     uint8
| +--rw mip-creation? ipi-cfm-data-types:cfm_mip_creation_mode_t {feature-list:HAVE_PROVIDER_BRIDGE}?
+--ro state
| +--ro md-name?   string
| +--ro type      ipi-cfm-data-types:cfm_md_type_t
| +--ro level     uint8
| +--ro mip-creation? ipi-cfm-data-types:cfm_mip_creation_mode_t {feature-list:HAVE_PROVIDER_BRIDGE}?
+--rw maintenance-associations
  +--rw maintenance-association* [ma-name]
    +--rw ma-name      -> ../config/ma-name
    +--rw config
      | +--rw ma-name?      string
      | +--rw type          ipi-cfm-data-types:cfm_ma_type_t
      | +--rw ccm-interval? ipi-cfm-data-types:cfm_msg_interval_t
      | +--rw static-rmep-identifiers* uint16
      | +--rw mip-creation? ipi-cfm-data-types:cfm_ma_mip_creation_mode_t
      | +--rw vlan-id?     uint16
      | +--rw inner-vlan-id? uint16
      | +--rw bridge-id?   -> /ipi-network-instance:network-instances/network-instance/instance-name
      | +--rw link-level-ma? empty
      | +--rw mip-interface-name* -> /ipi-interface:interfaces/interface/name {feature-
list:HAVE_PROVIDER_BRIDGE}?
      | +--rw evpn-id?      uint32 {feature-list:HAVE_BGP_EVPN,feature-
list:NOT_HAVE_CUSTOM1_MPLS_OR_HAVE_NVO3_OAM}?
    +--ro state
      | +--ro ma-name?      string
      | +--ro type          ipi-cfm-data-types:cfm_ma_type_t
      | +--ro ccm-interval? ipi-cfm-data-types:cfm_msg_interval_t
      | +--ro static-rmep-identifiers* uint16
      | +--ro mip-creation? ipi-cfm-data-types:cfm_ma_mip_creation_mode_t
      | +--ro vlan-id?     uint16
      | +--ro inner-vlan-id? uint16
      | +--ro bridge-id?   -> /ipi-network-instance:network-instances/network-instance/instance-name
      | +--ro link-level-ma? empty
      | +--ro mip-interface-name* -> /ipi-interface:interfaces/interface/name {feature-
list:HAVE_PROVIDER_BRIDGE}?

```

---

---

```

| +--ro evpn-id?          uint32 {feature-list:HAVE_BGP_EVPN,feature-
list:NOT_HAVE_CUSTOM1_MPLS_OR_HAVE_NVO3_OAM}?
+--rw maintenance-end-points
| +--rw maintenance-end-point* [mep-id]
|   +--rw mep-id          -> ../config/mep-id
|   +--rw config
|     | +--rw mep-id?      uint16
|     | +--rw direction   ipi-cfm-data-types:cfm_mep_direction_t
|     | +--rw administrative-state ipi-cfm-data-types:cfm_mep_state_t
|     | +--rw mep-outer-vlan? uint16
|     | +--rw mep-inner-vlan? uint16
|     | +--rw bw-mapped-interface? -> /ipi-interface:interfaces/interface/name
|     | +--rw interface-name?     -> /ipi-interface:interfaces/interface/name
|     | +--rw remote-vpws-vc-name? string
|     | +--rw remote-evpn-id?     uint32
|     +--ro state
|       | +--ro mep-id?          uint16
|       | +--ro direction       ipi-cfm-data-types:cfm_mep_direction_t
|       | +--ro administrative-state ipi-cfm-data-types:cfm_mep_state_t
|       | +--ro mep-outer-vlan?  uint16
|       | +--ro mep-inner-vlan?  uint16
|       | +--ro interface-name?  -> /ipi-interface:interfaces/interface/name
|       | +--ro remote-vpws-vc-name? string
|       | +--ro remote-evpn-id?  uint32
|       | +--ro mac-address?     cml-data-types:cml_mac_addr_t
|       | +--ro ma-status?       ipi-cfm-data-types:cfm_ma_status_t
|       | +--ro mep-connectivity-status? ipi-cfm-data-types:cfm_mep_connectivity_status_t
|       | +--ro bw-mapped-interface? -> /ipi-interface:interfaces/interface/name
|     +--rw continuity-check
|       | +--rw config
|         | | +--rw enable-cc-multicast?      empty
|         | | +--rw lowest-fault-priority-defect? ipi-cfm-data-types:cfm_mep_lowest_fault_priority_t
|         +--ro state
|           | | +--ro enable-cc-multicast?      empty
|           | | +--ro lowest-fault-priority-defect? ipi-cfm-data-types:cfm_mep_lowest_fault_priority_t
|           | | +--ro highest-priority-defect-found? ipi-cfm-data-types:cfm_mep_highest_fault_defect_t
|           | | +--ro cc-received-defect?       ipi-cfm-data-types:cfm_received_ccm_defect_t

```

---

---

```
| | | +--ro cc-messages-received?      yang:zero-based-counter32
| | | +--ro cc-messages-sent?          yang:zero-based-counter32
| | | +--ro remote-mep-database
| | |   +--ro remote-mep* [rmep-id]
| | |     +--ro rmep-id  -> ../state/rmep-id
| | |     +--ro state
| | |       +--ro rmep-id?   uint16
| | |       +--ro mac-address? cml-data-types:cml_mac_addr_t
| | |       +--ro rdi?      empty
| | +--ro loopback
| | | +--ro last-test-result
| | | +--ro state
| | |   +--ro target-mac-address? ipi-cfm-data-types:cfm_rmep_mac_addr_t
| | |   +--ro messages-transmitted? yang:zero-based-counter32
| | |   +--ro replies-received?   yang:zero-based-counter32
| | +--ro linktrace-database
| | | +--ro linktrace-entry* [transaction-id]
| | |   +--ro transaction-id  -> ../state/transaction-id
| | |   +--ro state
| | |     | +--ro transaction-id?   uint32
| | |     | +--ro target-mac-address? ipi-cfm-data-types:cfm_rmep_mac_addr_t
| | |     +--ro replies
| | |       +--ro reply* [index]
| | |         +--ro index  -> ../state/index
| | |         +--ro state
| | |           +--ro index?        uint8
| | |           +--ro hops?         uint8
| | |           +--ro destination-mac-address? ipi-cfm-data-types:cfm_rmep_mac_addr_t
| | |           +--ro relay-action?   ipi-cfm-data-types:cfm_relay_action_t
| | +--rw ethernet-alarm-indication-signal {feature-list:HAVE_CFM_Y1731}?
| | | +--rw config!
| | | | +--rw enable-status  empty
| | | | +--rw client-md-level uint8
| | | | +--rw interval?     ipi-cfm-data-types:cfm_y1731_tx_interval_t
| | | +--ro state
| | |   +--ro enable-status  empty
```

```

| | +--ro client-md-level      uint8
| | +--ro interval?           ipi-cfm-data-types:cfm_y1731_tx_interval_t
| | +--ro is-ais-frame-received? boolean
| +--rw y1731-responders {feature-list:HAVE_CFM_Y1731}?
|   +--rw config
|   +--ro state
+--ro default-mips
  +--ro default-mip* [interface-name]
    +--ro interface-name  -> ../state/interface-name
    +--ro state
      +--ro interface-name? string
      +--ro vlan-id?      uint16
      +--ro mac-address?  cml-data-types:cml_mac_addr_t

```

## rpcs:

```

+---x cfm-l2-clear-ethernet-remote-meps {feature-list:HAVE_CFM,feature-list:HAVE_ONMD}?
| +---w input
|   +---w domain-name  string
+---x cfm-clear-all-mep-stats {feature-list:HAVE_CFM}?
+---x cfm-l2-clear-mep-stats {feature-list:HAVE_CFM}?
| +---w input
|   +---w domain-name  string
|   +---w mep-id       uint16
|   +---w ma-name      string
+---x cfm-snmp-restart {feature-list:HAVE_CFM,feature-list:HAVE_ONMD}?
+---x cfm-terminal-debug-on {feature-list:HAVE_CFM,feature-list:HAVE_ONMD}?
| +---w input
|   +---w terminal-debug-options  ipi-cfm-data-types:cfm_debug_t
+---x cfm-terminal-debug-off {feature-list:HAVE_CFM,feature-list:HAVE_ONMD}?
| +---w input
|   +---w terminal-debug-options  ipi-cfm-data-types:cfm_debug_t
+---x cfm-l2-test-loopback {feature-list:HAVE_CFM,feature-list:HAVE_ONMD}?
| +---w input
|   +---w md-name      string
|   +---w ma-name      string
|   +---w mep-id       uint16

```

---

```

| +---w mac-address  ipi-cfm-data-types:cfm_lb_mac_addr_t
+---x cfm-l2-test-linktrace {feature-list:HAVE_CFM,feature-list:HAVE_ONMD}?
| +---w input
| | +---w md-name      string
| | +---w ma-name      string
| | +---w mep-id       uint16
| | +---w mac-address  ipi-cfm-data-types:cfm_lb_mac_addr_t
| +--ro output
|   +--ro transaction-id  uint32
+---x cfm-l2-clear-linktrace-cache {feature-list:HAVE_CFM,feature-list:HAVE_ONMD}?

```

notifications:

```

+---n cfm-l2-mep-ccm-highest-fault-info {feature-list:HAVE_CFM}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro mep-id?           uint16
| +--ro ma-name?          string
| +--ro md-name?          string
| +--ro highest-priority-defect-found? ipi-cfm-data-types:cfm_mep_highest_fault_defect_t
+---n cfm-l2-ethernet-loopback-test-completed {feature-list:HAVE_CFM}?
| +--ro severity?         cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro mep-id?           uint16
| +--ro ma-name?          string
| +--ro md-name?          string
| +--ro target-mac-address? ipi-cfm-data-types:cfm_rmep_mac_addr_t
+---n cfm-l2-ethernet-linktrace-test-completed {feature-list:HAVE_CFM}?
  +--ro severity?         cml-data-types:cml_notif_severity_t
  +--ro eventClass?       cml-data-types:cml_notif_class_t
  +--ro transaction-id?   uint32
  +--ro mep-id?           uint16
  +--ro ma-name?          string
  +--ro md-name?          string
  +--ro target-mac-address? ipi-cfm-data-types:cfm_rmep_mac_addr_t

```

---

## module: ipi-cross-connect

augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance:

```

+--rw cross-connect
  +--rw config
    | +--rw xc-name?      -> /ipi-network-instance:network-instances/network-instance/instance-name
    | +--rw description?  cml-data-types:cml_line_t
    | +--rw admin-disable? empty
    +--ro state
    | +--ro xc-name?      -> /ipi-network-instance:network-instances/network-instance/instance-name
    | +--ro description?  cml-data-types:cml_line_t
    | +--ro admin-disable? empty
    | +--ro operational-state? ipi-cross-connect-types:xc_oper_status_t
    +--rw cross-connect-interfaces
      +--rw cross-connect-interface* [endpoint-if]
        +--rw endpoint-if -> ../config/endpoint-if
        +--rw config
          | +--rw endpoint-if?   -> /ipi-interface:interfaces/interface/name
          | +--rw endpoint-if-bkp? string {feature-list:HAVE_DUNE}?
          | +--rw evc-name?      string {feature-list:HAVE_DUNE}?
        +--ro state
          +--ro endpoint-if?     -> /ipi-interface:interfaces/interface/name
          +--ro endpoint-if-bkp? string {feature-list:HAVE_DUNE}?
          +--ro evc-name?       string {feature-list:HAVE_DUNE}?

```

---

## module: ipi-crypto

rpcs:

```

+---x crypto-rsa-key-gen {feature-list:HAVE_HOSTPD}?
  +---w input
    +---w ipv4-addr  inet:ipv4-address

```

---

## module: ipi-customstats

notifications:

```
+---n platform-cpu-queue-full
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro queue-id?     uint8
| +--ro queue-name?   string
| +--ro rate-percent? int8
| +--ro tx-pkt-rate?  yang:counter32
| +--ro last-increment-count? yang:counter64
| +--ro last-increment-time? yang:date-and-time
+---n platform-cpu-queue-high
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro queue-id?     uint8
| +--ro queue-name?   string
| +--ro rate-percent? int8
| +--ro tx-pkt-rate?  yang:counter32
+---n platform-cpu-queue-recovery
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro queue-id?     uint8
| +--ro queue-name?   string
| +--ro rate-percent? int8
+---n platform-cpu-crc-error-packets
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro bad-crc?      yang:counter64
+---n platform-cpu-undersize-error-packets
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro undersize-pkts? yang:counter64
+---n platform-cpu-oversize-error-packets
| +--ro severity?     cml-data-types:cml_notif_severity_t
```

---

```
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro mtu-exceed?  yang:counter64
+---n platform-cpu-fragment-error-packets
| +--ro severity?    cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro fragments-pkts? yang:counter64
+---n platform-cpu-jabber-error-packets
| +--ro severity?    cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro jabber-pkts? yang:counter64
+---n platform-interface-crc-error-packets
| +--ro severity?    cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?        string
| +--ro bad-crc?     yang:counter64
+---n platform-interface-undersize-error-packets
| +--ro severity?    cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?        string
| +--ro undersize-pkts? yang:counter64
+---n platform-interface-oversize-error-packets
| +--ro severity?    cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?        string
| +--ro mtu-exceed?  yang:counter64
+---n platform-interface-fragment-error-packets
| +--ro severity?    cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?        string
| +--ro fragments-pkts? yang:counter64
+---n platform-interface-jabber-error-packets
  +--ro severity?    cml-data-types:cml_notif_severity_t
  +--ro eventClass?  cml-data-types:cml_notif_class_t
  +--ro name?        string
  +--ro jabber-pkts? yang:counter64
```

---

## module: ipi-dcb

```

+--rw dcb {feature-list:HAVE_DCB}?
  +--rw bridges
    | +--rw bridge* [bridge-id]
    |   +--rw bridge-id  -> ../config/bridge-id
    |   +--rw config
    |     | +--rw bridge-id?          -> /ipi-network-instance:network-instances/network-instance/instance-name
    |     | +--rw dcb-enabled          boolean
    |     | +--rw enable-ets?          empty
    |     | +--rw enable-pfc?          empty
    |     | +--rw enable-application-priority? empty
    |     +--ro state
    |       | +--ro bridge-id?          -> /ipi-network-instance:network-instances/network-instance/instance-name
    |       | +--ro dcb-enabled          boolean
    |       | +--ro enable-ets?          empty
    |       | +--ro enable-pfc?          empty
    |       | +--ro enable-application-priority? empty
    |       +--rw qcn
    |         +--rw config!
    |           | +--rw enabled          empty
    |           | +--rw cnm-transmit-priority? uint8
    |           | +--rw cnpv-priorities*  uint8
    |           +--ro state
    |             | +--ro enabled          empty
    |             | +--ro cnm-transmit-priority? uint8
    |             | +--ro cnpv-priorities*  uint8
    |             +--rw cnpv-defenses
    |               +--rw cnpv-defense* [priority-value]
    |                 +--rw priority-value  -> ../config/priority-value
    |                 +--rw config
    |                   | +--rw priority-value?  -> /dcb/bridges/bridge/qcn/config/cnpv-priorities
    |                   | +--rw qcn-mode          ipi-dcb-types:dcb_qcn_mode_t

```

---

```

|      | +--rw admin-defense-mode? ipi-dcb-types:dcb_qcn_admin_defense_mode_t
|      | +--rw alternate-priority? uint8
|      +--ro state
|          +--ro priority-value?    -> /dcb/bridges/bridge/qcn/config/cnpv-priorities
|          +--ro qcn-mode            ipi-dcb-types:dcb_qcn_mode_t
|          +--ro admin-defense-mode? ipi-dcb-types:dcb_qcn_admin_defense_mode_t
|          +--ro alternate-priority? uint8
+--rw debug
| +--rw config
| | +--rw enable? empty
| +--ro state
| +--ro enable? empty
+--rw interfaces
+--rw interface* [name] {feature-list:HAVE_DCB}?
+--rw name          -> ../config/name
+--rw config
| +--rw name?      -> /ipi-interface:interfaces/interface/name
| +--rw pfc-mode? ipi-dcb-types:dcb_pfc_mode_t
| +--rw ets-mode? ipi-dcb-types:dcb_ets_mode_t
+--ro state
| +--ro name?     -> /ipi-interface:interfaces/interface/name
| +--ro pfc-mode? ipi-dcb-types:dcb_pfc_mode_t
| +--ro ets-mode? ipi-dcb-types:dcb_ets_mode_t
+--rw qcn
| +--rw cnpv-defenses
| | +--rw cnpv-defense* [priority-value]
| | +--rw priority-value -> ../config/priority-value
| | +--rw config
| | | +--rw priority-value? -> /dcb/bridges/bridge/qcn/config/cnpv-priorities
| | | +--rw qcn-mode        ipi-dcb-types:dcb_qcn_mode_t
| | | +--rw admin-defense-mode? ipi-dcb-types:dcb_qcn_admin_defense_mode_t
| | | +--rw alternate-priority? uint8
| | +--ro state
| | +--ro priority-value?    -> /dcb/bridges/bridge/qcn/config/cnpv-priorities
| | +--ro qcn-mode          ipi-dcb-types:dcb_qcn_mode_t
| | +--ro admin-defense-mode? ipi-dcb-types:dcb_qcn_admin_defense_mode_t

```

---

---

```
| |   +--ro alternate-priority?  uint8
| +--rw congestion-points
|   +--rw congestion-point* [cnpv-value]
|     +--rw cnpv-value   -> ../config/cnpv-value
|     +--rw config
|       | +--rw cnpv-value?   -> /dcb/bridges/bridge/qcn/config/cnpv-priorities
|       | +--rw sample-base? uint32
|       | +--rw weight?      int8
|       +--ro state
|         +--ro cnpv-value?   -> /dcb/bridges/bridge/qcn/config/cnpv-priorities
|         +--ro sample-base? uint32
|         +--ro weight?      int8
+--rw priority-flow-control
| +--rw config
| | +--rw accept-peer-config?   empty
| | +--rw advertise-local-config? empty
| | +--rw enabled-priorities*   uint8
| | +--rw cap?                  uint8
| | +--rw link-delay-allowance? uint32
| +--ro state
|   +--ro accept-peer-config?   empty
|   +--ro advertise-local-config? empty
|   +--ro enabled-priorities*   uint8
|   +--ro cap?                  uint8
|   +--ro link-delay-allowance? uint32
+--rw enhanced-transmission-selection
| +--rw config
| | +--rw advertise-local-config? empty
| | +--rw accept-peer-config?   empty
| | +--rw max-traffic-class-groups? uint8
| +--ro state
| | +--ro advertise-local-config? empty
| | +--ro accept-peer-config?   empty
| | +--ro max-traffic-class-groups? uint8
+--rw traffic-class-groups
|   +--rw traffic-class-group* [group-index]
```

---

```
|   +--rw group-index  -> ../config/group-index
|   +--rw config
|   |   +--rw group-index?      uint8
|   |   +--rw mapped-priorities*  uint8
|   |   +--rw bandwidth-percentage?  uint8
|   +--ro state
|   |   +--ro group-index?      uint8
|   |   +--ro mapped-priorities*  uint8
|   |   +--ro bandwidth-percentage?  uint8
+--rw application-priority
  +--rw config
  |   +--rw enabled?          empty
  |   +--rw advertise-local-config?  empty
  +--ro state
  |   +--ro enabled?          empty
  |   +--ro advertise-local-config?  empty
  +--rw port-mappings
  |   +--rw port-mapping* [protocol-type port-number priority-value]
  |   |   +--rw protocol-type  -> ../config/protocol-type
  |   |   +--rw port-number    -> ../config/port-number
  |   |   +--rw priority-value -> ../config/priority-value
  |   |   +--rw config
  |   |   |   +--rw protocol-type?  ipi-dcb-types:dcb_app_prio_protocol_t
  |   |   |   +--rw port-number?    uint16
  |   |   |   +--rw priority-value?  uint8
  |   |   +--ro state
  |   |   |   +--ro protocol-type?  ipi-dcb-types:dcb_app_prio_protocol_t
  |   |   |   +--ro port-number?    uint16
  |   |   |   +--ro priority-value?  uint8
  +--rw service-mappings
  |   +--rw service-mapping* [protocol-type service-name priority-value]
  |   |   +--rw protocol-type  -> ../config/protocol-type
  |   |   +--rw service-name    -> ../config/service-name
  |   |   +--rw priority-value -> ../config/priority-value
  |   |   +--rw config
  |   |   |   +--rw protocol-type?  ipi-dcb-types:dcb_app_prio_protocol_t
```

```

| | +--rw service-name?  string
| | +--rw priority-value? uint8
| +--ro state
|   +--ro protocol-type?  ipi-dcb-types:dcb_app_prio_protocol_t
|   +--ro service-name?  string
|   +--ro priority-value? uint8
+--rw ethertype-name-mappings
| +--rw ethertype-name-mapping* [ether-name priority-value]
|   +--rw ether-name      -> ../config/ether-name
|   +--rw priority-value  -> ../config/priority-value
|   +--rw config
|     | +--rw ether-name?  ipi-dcb-types:dcb_app_ether_name_t
|     | +--rw priority-value? uint8
|     +--ro state
|       +--ro ether-name?  ipi-dcb-types:dcb_app_ether_name_t
|       +--ro priority-value? uint8
+--rw ethertype-value-mappings
  +--rw ethertype-value-mapping* [ether-value priority-value]
    +--rw ether-value      -> ../config/ether-value
    +--rw priority-value  -> ../config/priority-value
    +--rw config
      | +--rw ether-value?  ipi-dcb-types:dcb_app_ether_value_t
      | +--rw priority-value? uint8
      +--ro state
        +--ro ether-value?  ipi-dcb-types:dcb_app_ether_value_t
        +--ro priority-value? uint8

```

---

## module: ipi-delay-profile

```

+--rw delay-profiles
  +--rw delay-profile* [profile-type]
    | +--rw profile-type      -> ../config/profile-type
    | +--rw config
    | | +--rw profile-type?  ipi-delay-profile-types:delay_profile_type_t
    | +--ro state

```

---

```
| | +--ro profile-type? ipi-delay-profile-types:delay_profile_type_t
| +--rw profile-parameters
| | +--rw config
| | | +--rw burst-interval? uint16
| | | +--rw burst-count?   uint8
| | | +--rw interval?      uint16
| | | +--rw mode?          ipi-delay-profile-types:delay_profile_measurement_mode_t
| | | +--rw sender-port?   uint16
| | +--ro state
| |   +--ro burst-interval? uint16
| |   +--ro burst-count?   uint8
| |   +--ro interval?      uint16
| |   +--ro mode?          ipi-delay-profile-types:delay_profile_measurement_mode_t
| |   +--ro sender-port?   uint16
| +--rw periodic-advertisement
| | +--rw config
| | | +--rw disable?       empty
| | | +--rw threshold?    uint8
| | | +--rw minimum-change? uint16
| | +--ro state
| |   +--ro disable?       empty
| |   +--ro threshold?    uint8
| |   +--ro minimum-change? uint16
| +--rw accelerated-advertisement
| | +--rw config!
| | | +--rw enable         empty
| | | +--rw threshold?    uint8
| | | +--rw minimum-change? uint16
| | +--ro state
| |   +--ro enable         empty
| |   +--ro threshold?    uint8
| |   +--ro minimum-change? uint16
+--rw delay-profile-clients
  +--rw config!
  | +--rw delay-profile-enable empty
  | +--rw burst-interval?   uint16
```

---

---

```
| +--rw burst-count?      uint8
+--ro state
  +--ro delay-profile-enable  empty
  +--ro burst-interval?     uint16
  +--ro burst-count?       uint8
```

---

## module: ipi-dhcp

```
+--rw dhcp
  +--rw global
    | +--rw config
    | | +--rw disable-dhcp-feature?  empty
    | +--ro state
    | +--ro disable-dhcp-feature?  empty
  +--rw relay
    | +--rw global
    | | +--rw config
    | | | +--rw disable-dhcpv4-relay?  empty
    | | | +--rw disable-dhcpv6-relay?  empty
    | | +--ro state
    | | +--ro disable-dhcpv4-relay?  empty
    | | +--ro disable-dhcpv6-relay?  empty
    | +--rw interfaces
    | | +--rw interface* [name]
    | | +--rw name      -> ../config/name
    | | +--rw config
    | | | +--rw name?          -> /ipi-interface:interfaces/interface/name
    | | | +--rw ipv4-relay-interface?  empty
    | | | +--rw ipv4-uplink-interface?  empty
```

```

| | | +--rw ipv4-group-name?    string
| | | +--rw ipv6-relay-interface? empty {feature-list:HAVE_IPV6}?
| | | +--rw ipv6-uplink-interface? empty {feature-list:HAVE_IPV6}?
| | | +--rw ipv6-group-name?    string
| | +--ro state
| |   +--ro name?                -> /ipi-interface:interfaces/interface/name
| |   +--ro ipv4-relay-interface? empty
| |   +--ro ipv4-uplink-interface? empty
| |   +--ro ipv4-group-name?    string
| |   +--ro ipv6-relay-interface? empty {feature-list:HAVE_IPV6}?
| |   +--ro ipv6-uplink-interface? empty {feature-list:HAVE_IPV6}?
| |   +--ro ipv6-group-name?    string
| +--rw vrfs
|   +--rw vrf* [vrf-name]
|     +--rw vrf-name            -> ../config/vrf-name
|     +--rw config
|       | +--rw vrf-name?        -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/
vrf-name
|       | +--rw link-selection-source-ip?    inet:ipv4-address
|       | +--rw enable-option82?            empty
|       | +--rw enable-option82-always-on?  empty
|       | +--rw enable-dhcpv6-pd-route-injection? empty {feature-list:HAVE_IPV6}?
|       | +--rw enable-dhcpv6-duplicate-clients? empty {feature-list:HAVE_IPV6}?
|       | +--rw remote-id?                  ipi-dhcp-relay-types:dhcp_remote_id_t
|       | +--rw subscriber-id?              string
|       +--ro state
|       | +--ro vrf-name?                  -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/
vrf-name
|       | +--ro link-selection-source-ip?    inet:ipv4-address
|       | +--ro enable-option82?            empty
|       | +--ro enable-option82-always-on?  empty
|       | +--ro enable-dhcpv6-pd-route-injection? empty {feature-list:HAVE_IPV6}?
|       | +--ro enable-dhcpv6-duplicate-clients? empty {feature-list:HAVE_IPV6}?
|       | +--ro remote-id?                  ipi-dhcp-relay-types:dhcp_remote_id_t
|       | +--ro subscriber-id?              string
|       | +--ro bogus-giaddr-drops?         uint32
|       | +--ro client-packets-relayed?     uint32

```

```

| | +--ro server-packet-errors?      uint32
| | +--ro server-packets-relayed?    uint32
| | +--ro client-packet-errors?      uint32
| | +--ro agent-option-errors?       uint32
| | +--ro corrupt-agent-options?     uint32
| | +--ro missing-agent-option?      uint32
| | +--ro bad-circuit-id?            uint32
| | +--ro missing-circuit-id?        uint32
| | +--ro circuit-id?                string
| +--rw ipv4-vpn-links
| | +--rw ipv4-vpn-link* [interface-type]
| | | +--rw interface-type  -> ../config/interface-type
| | | +--rw config
| | | | +--rw interface-type?    ipi-dhcp-relay-types:dhcp_vpn_interface_type_t
| | | | +--rw interface-direction ipi-dhcp-relay-types:dhcp_vpn_interface_direction_t
| | | | +--ro state
| | | |   +--ro interface-type?    ipi-dhcp-relay-types:dhcp_vpn_interface_type_t
| | | |   +--ro interface-direction ipi-dhcp-relay-types:dhcp_vpn_interface_direction_t
| +--rw ipv6-vpn-links
| | +--rw ipv6-vpn-link* [interface-type-v6] {feature-list:HAVE_IPV6}?
| | | +--rw interface-type-v6  -> ../config/interface-type-v6
| | | +--rw config
| | | | +--rw interface-type-v6?    ipi-dhcp-relay-types:dhcp_vpn_interface_type_t
| | | | +--rw interface-direction-v6 ipi-dhcp-relay-types:dhcp_vpn_interface_direction_t
| | | | +--ro state
| | | |   +--ro interface-type-v6?    ipi-dhcp-relay-types:dhcp_vpn_interface_type_t
| | | |   +--ro interface-direction-v6 ipi-dhcp-relay-types:dhcp_vpn_interface_direction_t
| +--ro dhcpv6-delegated-prefixes* [interface-name] {feature-list:HAVE_IPV6}?
| | +--ro interface-name  -> ../state/interface-name
| | +--ro state
| | | +--ro interface-name?    string
| | | +--ro next-hop?          inet:ipv6-address
| | | +--ro prefix?           cml-data-types:cml_ipv6_prefix_t
| | | +--ro preferred-lifetime? uint32
| | | +--ro maximum-lifetime?  uint32
| | | +--ro prefix-start-time?  yang:date-and-time

```

```

|   |   +--ro prefix-expiry-time? yang:date-and-time
|   |   +--ro state?             ipi-dhcp-relay-types:dhcp6_pd_route_state_t
|   +--rw ipv4-dhcp-servers
|   |   +--rw ipv4-dhcp-server* [ip-address]
|   |   +--rw ip-address  -> ../config/ip-address
|   |   +--rw config
|   |   |   +--rw ip-address?      inet:ipv4-address
|   |   |   +--rw dhcpv4-server-global-vrf? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/
config/vrf-name
|   |   +--ro state
|   |   +--ro ip-address?      inet:ipv4-address
|   |   +--ro dhcpv4-server-global-vrf? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/
config/vrf-name
|   +--rw ipv6-dhcp-servers {feature-list:HAVE_IPV6}?
|   |   +--rw ipv6-dhcp-server* [ipv6-address]
|   |   +--rw ipv6-address  -> ../config/ipv6-address
|   |   +--rw config
|   |   |   +--rw ipv6-address?      inet:ipv6-address {feature-list:HAVE_IPV6}?
|   |   |   +--rw dhcpv6-server-global-vrf? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/
config/vrf-name
|   |   +--ro state
|   |   +--ro ipv6-address?      inet:ipv6-address {feature-list:HAVE_IPV6}?
|   |   +--ro dhcpv6-server-global-vrf? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/
config/vrf-name
|   +--rw dhcp-groups
|   |   +--rw dhcp-group* [group-name]
|   |   +--rw group-name  -> ../config/group-name
|   |   +--rw config
|   |   |   +--rw group-name?  string
|   |   |   +--rw server*     inet:ipv4-address
|   |   +--ro state
|   |   +--ro group-name?  string
|   |   +--ro server*     inet:ipv4-address
|   +--rw dhcpv6-groups {feature-list:HAVE_IPV6}?
|   +--rw dhcpv6-group* [group6-name]
|   +--rw group6-name  -> ../config/group6-name
|   +--rw config
|   |   +--rw group6-name?  string

```

```

|         | +--rw server*      inet:ipv6-address
|         +--ro state
|           +--ro group6-name? string
|           +--ro server*      inet:ipv6-address
+--rw client
| +--rw interfaces
|   +--rw interface* [name]
|     +--rw name                -> ../config/name
|     +--rw config
|       | +--rw name?           -> /ipi-interface:interfaces/interface/name
|       | +--rw request-ipv4-dns?    empty
|       | +--rw request-log-server?  empty {feature-list:HAVE_SYSLOG}?
|       | +--rw request-host-name?   empty
|       | +--rw request-ntp-server?  empty {feature-list:HAVE_HOSTP_NTP}?
|       | +--rw request-ipv6-dns?    empty {feature-list:HAVE_IPV6}?
|       | +--rw request-ipv6-domain-list?  empty {feature-list:HAVE_IPV6}?
|       | +--rw request-ipv6-ntp-server?  empty {feature-list:HAVE_IPV6}?
|       | +--rw request-ipv6-rapid-commit?  empty {feature-list:HAVE_IPV6}?
|       | +--rw request-ipv6-vendor-opts?  empty {feature-list:HAVE_IPV6}?
|       | +--rw ipv6-information-request?  empty {feature-list:HAVE_IPV6}?
|       | +--rw ipv6-dad-wait-time?    uint16 {feature-list:HAVE_IPV6}?
|       | +--rw ipv6-client-duid-type?  cml-data-types:dhcp6_duid_type_t {feature-list:HAVE_IPV6}?
|       | +--rw ipv6-max-delegated-prefix? uint16 {feature-list:HAVE_IPV6}?
|       | +--rw request-ipv6-prefix?    string {feature-list:HAVE_IPV6}?
|     +--ro state
|       | +--ro name?           -> /ipi-interface:interfaces/interface/name
|       | +--ro request-ipv4-dns?    empty
|       | +--ro request-log-server?  empty {feature-list:HAVE_SYSLOG}?
|       | +--ro request-host-name?   empty
|       | +--ro request-ntp-server?  empty {feature-list:HAVE_HOSTP_NTP}?
|       | +--ro request-ipv6-dns?    empty {feature-list:HAVE_IPV6}?
|       | +--ro request-ipv6-domain-list?  empty {feature-list:HAVE_IPV6}?
|       | +--ro request-ipv6-ntp-server?  empty {feature-list:HAVE_IPV6}?
|       | +--ro request-ipv6-rapid-commit?  empty {feature-list:HAVE_IPV6}?
|       | +--ro request-ipv6-vendor-opts?  empty {feature-list:HAVE_IPV6}?
|       | +--ro ipv6-information-request?  empty {feature-list:HAVE_IPV6}?

```

```

| | +--ro ipv6-dad-wait-time?      uint16 {feature-list:HAVE_IPV6}?
| | +--ro ipv6-client-duid-type?  cml-data-types:dhcp6_duid_type_t {feature-list:HAVE_IPV6}?
| | +--ro ipv6-max-delegated-prefix? uint16 {feature-list:HAVE_IPV6}?
| | +--ro request-ipv6-prefix?    string {feature-list:HAVE_IPV6}?
| +--rw prefix-ipv6-addresses {feature-list:HAVE_IPV6}?
| | +--rw prefix-ipv6-address* [prefix-name suffix-ipv6-addr]
| | | +--rw prefix-name      -> ../config/prefix-name
| | | +--rw suffix-ipv6-addr -> ../config/suffix-ipv6-addr
| | | +--rw config
| | | | +--rw prefix-name?    string
| | | | +--rw suffix-ipv6-addr? string
| | | +--ro state
| | | | +--ro prefix-name?    string
| | | | +--ro suffix-ipv6-addr? string
| +--ro learned-prefixes* [learnt-prefix] {feature-list:HAVE_IPV6}?
| | +--ro learnt-prefix  cml-data-types:cml_ipv6_prefix_t
| | +--ro state
| | | +--ro learnt-prefix?  cml-data-types:cml_ipv6_prefix_t
| | | +--ro max-lifetime?   uint32
| | | +--ro preferred-lifetime? uint32
+--rw server
| +--rw interfaces
| | +--rw interface* [name]
| | | +--rw name      -> ../config/name
| | | +--rw config
| | | | +--rw name?          -> /ipi-interface:interfaces/interface/name
| | | | +--rw enable-ipv4-server? empty
| | | | +--rw enable-ipv6-server? empty {feature-list:HAVE_IPV6}?
| | | +--ro state
| | | | +--ro name?          -> /ipi-interface:interfaces/interface/name
| | | | +--ro enable-ipv4-server? empty
| | | | +--ro enable-ipv6-server? empty {feature-list:HAVE_IPV6}?
+--rw vrfs
| +--rw vrf* [vrf-name]
| | +--rw vrf-name      -> ../config/vrf-name
| | +--rw config

```

```

| | +--rw max-lease-time?   int32
| | +--rw default-lease-time? int32
| | +--rw rapid-commit?    empty
| | +--rw preference?      empty
| | +--rw vrf-name?        -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
| +--ro state
| | +--ro max-lease-time?   int32
| | +--ro default-lease-time? int32
| | +--ro rapid-commit?    empty
| | +--ro preference?      empty
| | +--ro vrf-name?        -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
| +--rw dhcp-pools
| | +--rw dhcp-pool* [pool-name]
| | | +--rw pool-name -> ../config/pool-name
| | | +--rw config
| | | | +--rw pool-name?    string
| | | | +--rw host-name?   string
| | | | +--rw routers?     inet:ipv4-address
| | | | +--rw ntp-server*   inet:ipv4-address
| | | | +--rw boot-file?    string
| | | | +--rw tftp-server?  inet:ipv4-address
| | | | +--rw log-server*   inet:ipv4-address
| | | | +--rw dns-server*   inet:ipv4-address
| | | | +--rw network?     inet:ipv4-address
| | | | +--rw netmask?     inet:ipv4-address
| | | | +--rw low-address-in-range? inet:ipv4-address
| | | | +--rw high-address-in-range? inet:ipv4-address
| | | +--ro state
| | | | +--ro pool-name?    string
| | | | +--ro host-name?   string
| | | | +--ro routers?     inet:ipv4-address
| | | | +--ro ntp-server*   inet:ipv4-address
| | | | +--ro boot-file?    string
| | | | +--ro tftp-server?  inet:ipv4-address
| | | | +--ro log-server*   inet:ipv4-address
| | | | +--ro dns-server*   inet:ipv4-address

```

---

```
| | +--ro network?          inet:ipv4-address
| | +--ro netmask?         inet:ipv4-address
| | +--ro low-address-in-range?  inet:ipv4-address
| | +--ro high-address-in-range? inet:ipv4-address
| +--rw dhcp6-pools {feature-list:HAVE_IPV6}?
|   +--rw dhcp6-pool* [pool6-name]
|     +--rw pool6-name  -> ../config/pool6-name
|     +--rw config
|       | +--rw pool6-name?      string
|       | +--rw domain-name?     string
|       | +--rw vendor-options?  cml-data-types:cml_line_t
|       | +--rw ntp-server*      inet:ipv6-address
|       | +--rw dns-server*      inet:ipv6-address
|       | +--rw ipv6-network?    inet:ipv6-address
|       | +--rw ipv6-netmask?    uint8
|       | +--rw low-address-in-range?  inet:ipv6-address
|       | +--rw high-address-in-range? inet:ipv6-address
|       | +--rw temporary-address?  inet:ipv6-address
|       | +--rw ipv6-prefix-high-address? inet:ipv6-address
|       | +--rw ipv6-prefix-low-address? inet:ipv6-address
|       | +--rw ipv6-prefix-netmask?  uint8
|     +--ro state
|       +--ro pool6-name?      string
|       +--ro domain-name?     string
|       +--ro vendor-options?  cml-data-types:cml_line_t
|       +--ro ntp-server*      inet:ipv6-address
|       +--ro dns-server*      inet:ipv6-address
|       +--ro ipv6-network?    inet:ipv6-address
|       +--ro ipv6-netmask?    uint8
|       +--ro low-address-in-range?  inet:ipv6-address
|       +--ro high-address-in-range? inet:ipv6-address
|       +--ro temporary-address?  inet:ipv6-address
|       +--ro ipv6-prefix-high-address? inet:ipv6-address
|       +--ro ipv6-prefix-low-address? inet:ipv6-address
|       +--ro ipv6-prefix-netmask?  uint8
+--rw snooping
```

---

```
+--rw debug
| +--rw config
| | +--rw options? ipi-dhcp-snooping-types:dhcp_snooping_debug_t
| +--ro state
|   +--ro options?          ipi-dhcp-snooping-types:dhcp_snooping_debug_t
|   +--ro terminal-debug-status? ipi-dhcp-snooping-types:dhcp_snooping_debug_t
+--rw snooping-bridges
| +--rw snooping-bridge* [bridge-id]
|   +--rw bridge-id      -> ../config/bridge-id
|   +--rw config!
|     +--rw snooping-enable    empty
|     +--rw bridge-id?        -> /ipi-network-instance:network-instances/network-instance/instance-name
|     +--rw verify-mac-address? empty
|     +--rw option-82-enable?  empty
|     +--rw write-delay?      uint32
|     +--rw strict-validation? empty
|     +--rw vlan-range?       cml-data-types:cml_range_t
|   +--ro state
|     +--ro snooping-enable    empty
|     +--ro bridge-id?        -> /ipi-network-instance:network-instances/network-instance/instance-name
|     +--ro verify-mac-address? empty
|     +--ro option-82-enable?  empty
|     +--ro write-delay?      uint32
|     +--ro strict-validation? empty
|     +--ro vlan-range?       cml-data-types:cml_range_t
|   +--rw arp-inspection
|     +--rw config!
|       +--rw enable          empty
|       +--rw validate?      ipi-dhcp-snooping-types:dhcp_snooping_validation_t
|       +--rw vlan-range?    cml-data-types:cml_range_t
|     +--ro state
|       +--ro enable          empty
|       +--ro validate?      ipi-dhcp-snooping-types:dhcp_snooping_validation_t
|       +--ro vlan-range?    cml-data-types:cml_range_t
|       +--ro counters
|         +--ro forwarded?    yang:counter32
```

```

| |   +--ro dropped?   yang:counter32
| +--rw vlans
|   +--rw vlan* [vlan-id]
|     +--rw vlan-id      -> ../config/vlan-id
|     +--rw config
|       | +--rw vlan-id?  uint16
|       +--ro state
|         | +--ro vlan-id?  uint16
|         | +--ro statistics
|         |   +--ro static-entries-ipv4?  yang:counter32
|         |   +--ro dynamic-entries-ipv4?  yang:counter32
|         |   +--ro static-entries-ipv6?  yang:counter32 {feature-list:HAVE_IPV6}?
|         |   +--ro dynamic-entries-ipv6?  yang:counter32 {feature-list:HAVE_IPV6}?
|         +--rw mac-addresses-ipv4
|           | +--rw mac-address-ipv4* [mac-address]
|           |   +--rw mac-address  -> ../config/mac-address
|           |   +--rw config
|           |     | +--rw if-name      -> /ipi-interface:interfaces/interface/name
|           |     | +--rw ipv4-address  inet:ipv4-address
|           |     | +--rw mac-address?  cml-data-types:cml_mac_addr_t
|           |     +--ro state
|           |       +--ro if-name      -> /ipi-interface:interfaces/interface/name
|           |       +--ro ipv4-address  inet:ipv4-address
|           |       +--ro mac-address?  cml-data-types:cml_mac_addr_t
|           +--rw mac-addresses-ipv6 {feature-list:HAVE_IPV6}?
|             | +--rw mac-address-ipv6* [mac-address]
|             |   +--rw mac-address  -> ../config/mac-address
|             |   +--rw config
|             |     | +--rw if-name      -> /ipi-interface:interfaces/interface/name
|             |     | +--rw ipv6-address  inet:ipv6-address
|             |     | +--rw mac-address?  cml-data-types:cml_mac_addr_t
|             |     +--ro state
|             |       +--ro if-name      -> /ipi-interface:interfaces/interface/name
|             |       +--ro ipv6-address  inet:ipv6-address
|             |       +--ro mac-address?  cml-data-types:cml_mac_addr_t
|             +--ro snooping-binding-info

```

---

```

|     +--ro ipv4* [mac-address ip-address]
|     | +--ro mac-address  -> ../state/mac-address
|     | +--ro ip-address   -> ../state/ip-address
|     | +--ro state
|     |   +--ro mac-address?  cml-data-types:cml_mac_addr_t
|     |   +--ro lease-time?   uint32
|     |   +--ro type?         ipi-dhcp-snooping-types:dhcp_snooping_binding_type_t
|     |   +--ro if-name?      string
|     |   +--ro ip-address?   inet:ipv4-address
|     +--ro ipv6* [mac-address ip-address] {feature-list:HAVE_IPV6}?
|     | +--ro mac-address  -> ../state/mac-address
|     | +--ro ip-address   -> ../state/ip-address
|     | +--ro state
|     |   +--ro mac-address?  cml-data-types:cml_mac_addr_t
|     |   +--ro lease-time?   uint32
|     |   +--ro type?         ipi-dhcp-snooping-types:dhcp_snooping_binding_type_t
|     |   +--ro if-name?      string
|     |   +--ro ip-address?   inet:ipv6-address
+--rw interfaces
+--rw interface* [name]
+--rw name          -> ../config/name
+--rw config
| +--rw name?      -> /ipi-interface:interfaces/interface/name
+--ro state
| +--ro name?      -> /ipi-interface:interfaces/interface/name
+--rw trust
| +--rw config
| | +--rw snooping-trust?  empty
| | +--ro state
| | +--ro snooping-trust?  empty
+--rw verify
| +--rw config!
| | +--rw verify-snooping-vlan    empty
| | +--rw verify-access-group-mode?  empty
| | +--ro state
| | +--ro verify-snooping-vlan    empty

```

---

---

```
|  +--ro verify-access-group-mode?  empty
+--ro snooping-binding-info
|  +--ro ipv4-entries
|  |  +--ro ipv4-entry* [ip-address]
|  |  |  +--ro ip-address  -> ../state/ip-address
|  |  |  +--ro state
|  |  |  |  +--ro interface?  string
|  |  |  |  +--ro filter-type?  ipi-dhcp-snooping-types:dhcp_snooping_filter_type_t
|  |  |  |  +--ro vlan-id?    uint16
|  |  |  |  +--ro mac-address?  cml-data-types:cml_mac_addr_t
|  |  |  |  +--ro ip-address?  inet:ipv4-address
|  +--ro ipv6-entries {feature-list:HAVE_IPV6}?
|  |  +--ro ipv6-entry* [ip-address]
|  |  |  +--ro ip-address  -> ../state/ip-address
|  |  |  +--ro state
|  |  |  |  +--ro interface?  string
|  |  |  |  +--ro filter-type?  ipi-dhcp-snooping-types:dhcp_snooping_filter_type_t
|  |  |  |  +--ro vlan-id?    uint16
|  |  |  |  +--ro mac-address?  cml-data-types:cml_mac_addr_t
|  |  |  |  +--ro ip-address?  inet:ipv6-address
+--ro source-binding-info
  +--ro ipv4-entries
  |  +--ro ipv4-entry* [ip-address]
  |  |  +--ro ip-address  -> ../state/ip-address
  |  |  +--ro state
  |  |  |  +--ro interface?  string
  |  |  |  +--ro filter-type?  ipi-dhcp-snooping-types:dhcp_snooping_filter_type_t
  |  |  |  +--ro vlan-id?    uint16
  |  |  |  +--ro mac-address?  cml-data-types:cml_mac_addr_t
  |  |  |  +--ro ip-address?  inet:ipv4-address
  +--ro ipv6-entries {feature-list:HAVE_IPV6}?
  |  +--ro ipv6-entry* [ip-address]
  |  |  +--ro ip-address  -> ../state/ip-address
  |  |  +--ro state
  |  |  |  +--ro interface?  string
  |  |  |  +--ro filter-type?  ipi-dhcp-snooping-types:dhcp_snooping_filter_type_t
```

---

```
+--ro vlan-id?    uint16
+--ro mac-address?  cml-data-types:cml_mac_addr_t
+--ro ip-address?   inet:ipv6-address
```

```
rpcs:
```

```
+---x clear-relay-stats {feature-list:HAVE_HOSTPD,feature-list:HAVE_HOSTP_DHCP_RELAY,feature-
list:HAVE_DHCP_CLIENT_OR_HAVE_HOSTPD_OR_HAVE_DHCP_SNOOP}?
+---x clear-relay-option-stats {feature-list:HAVE_HOSTPD,feature-list:HAVE_HOSTP_DHCP_RELAY,feature-
list:HAVE_DHCP_CLIENT_OR_HAVE_HOSTPD_OR_HAVE_DHCP_SNOOP}?
+---x clear-dhcpv6-pd-route {feature-list:HAVE_HOSTPD,feature-list:HAVE_HOSTP_DHCP_RELAY,feature-
list:HAVE_DHCP_CLIENT_OR_HAVE_HOSTPD_OR_HAVE_DHCP_SNOOP}?
| +---w input
|   +---w vrf-name  string
+---x dhcp-snooping-write-database {feature-list:HAVE_DHCP_SNOOP,feature-list:HAVE_L2,feature-
list:HAVE_DHCP_CLIENT_OR_HAVE_HOSTPD_OR_HAVE_DHCP_SNOOP}?
| +---w input
|   +---w bridge-id  string
+---x dhcp-snooping-renew-database {feature-list:HAVE_DHCP_SNOOP,feature-list:HAVE_L2,feature-
list:HAVE_DHCP_CLIENT_OR_HAVE_HOSTPD_OR_HAVE_DHCP_SNOOP}?
| +---w input
|   +---w bridge-id  string
+---x dhcp-snooping-write-source-binding-database {feature-list:HAVE_DHCP_SNOOP,feature-
list:HAVE_L2,feature-list:HAVE_DHCP_CLIENT_OR_HAVE_HOSTPD_OR_HAVE_DHCP_SNOOP}?
| +---w input
|   +---w bridge-id  string
+---x dhcp-snooping-renew-source-database {feature-list:HAVE_DHCP_SNOOP,feature-list:HAVE_L2,feature-
list:HAVE_DHCP_CLIENT_OR_HAVE_HOSTPD_OR_HAVE_DHCP_SNOOP}?
| +---w input
|   +---w bridge-id  string
+---x dhcp-snooping-clear-source-binding-database {feature-list:HAVE_DHCP_SNOOP,feature-
list:HAVE_L2,feature-list:HAVE_DHCP_CLIENT_OR_HAVE_HOSTPD_OR_HAVE_DHCP_SNOOP}?
| +---w input
|   +---w bridge-id  string
+---x dhcp-snooping-clear-database {feature-list:HAVE_DHCP_SNOOP,feature-list:HAVE_L2,feature-
list:HAVE_DHCP_CLIENT_OR_HAVE_HOSTPD_OR_HAVE_DHCP_SNOOP}?
| +---w input
|   +---w bridge-id  string
+---x dhcp-snooping-terminal-debug-on {feature-list:HAVE_DHCP_SNOOP,feature-list:HAVE_L2,feature-
list:HAVE_DHCP_CLIENT_OR_HAVE_HOSTPD_OR_HAVE_DHCP_SNOOP}?
| +---w input
```

```

| +---w terminal-debug-options ipi-dhcp-snooping-types:dhcp_snooping_debug_t
+---x dhcp-snooping-terminal-debug-off {feature-list:HAVE_DHCP_SNOOP,feature-list:HAVE_L2,feature-
list:HAVE_DHCP_CLIENT_OR_HAVE_HOSTPD_OR_HAVE_DHCP_SNOOP}?
+---w input
+---w terminal-debug-options ipi-dhcp-snooping-types:dhcp_snooping_debug_t

```

notifications:

```

+---n dhcpv6-relay-pd-route
+--ro severity? cml-data-types:cml_notif_severity_t
+--ro eventClass? cml-data-types:cml_notif_class_t
+--ro vrf-name? string
+--ro interface-name? string
+--ro state? ipi-dhcp-relay-types:dhcp6_pd_route_state_t
+--ro prefix? cml-data-types:cml_ipv6_prefix_t
+--ro next-hop? inet:ipv6-address

```

---

## module: ipi-dns-client

```

+--rw dns
+--rw vrfs
| +--rw vrf* [vrf-name]
| +--rw vrf-name -> ../config/vrf-name
| +--rw config
| | +--rw vrf-name? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
| | {feature-list:HAVE_VRF}?
| | +--rw lookup-enabled? boolean
| | +--rw default-domain-name? inet:domain-name
| +--ro state
| | +--ro vrf-name? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
| | {feature-list:HAVE_VRF}?
| | +--ro lookup-enabled? boolean
| | +--ro default-domain-name? inet:domain-name
| +--rw servers
| | +--rw server* [address]
| | +--rw address -> ../config/address
| | +--rw config
| | | +--rw address? inet:ip-address

```

```

| | +--ro state
| |   +--ro address? inet:ip-address
| +--rw search-domains
| | +--rw search-domain* [domain-name]
| |   +--rw domain-name -> ../config/domain-name
| |   +--rw config
| |     | +--rw domain-name? inet:domain-name
| |     +--ro state
| |       +--ro domain-name? inet:domain-name
| +--rw host-entries
|   +--rw host-entry* [hostname]
|     +--rw hostname -> ../config/hostname
|     +--rw config
|       | +--rw hostname? cml-data-types:cml_host_string_t
|       | +--rw ipv4-address? inet:ipv4-address
|       | +--rw ipv6-address? inet:ipv6-address {feature-list:HAVE_IPV6}?
|       +--ro state
|         +--ro hostname? cml-data-types:cml_host_string_t
|         +--ro ipv4-address? inet:ipv4-address
|         +--ro ipv6-address? inet:ipv6-address {feature-list:HAVE_IPV6}?
+--rw debug
  +--rw config
  | +--rw enable? empty
  +--ro state
    +--ro enable? empty
    +--ro terminal-debug-status? cml-data-types:cml_on_off_t

```

rpcs:

```

+---x dns-client-terminal-debug-on {feature-list:HAVE_DNS_CLIENT}?
+---x dns-client-terminal-debug-off {feature-list:HAVE_DNS_CLIENT}?

```

---

## module: ipi-dns-relay

```

+--rw dns-relay
  +--rw config
  | +--rw enable-dns-feature? boolean

```

---

```
| +--rw enable-dnsv4-relay?  boolean
| +--rw enable-dnsv6-relay?  boolean {feature-list:HAVE_IPV6}?
| +--rw dns-server-v4-addr*  inet:ipv4-address
| +--rw dns-server-v6-addr*  inet:ipv6-address {feature-list:HAVE_IPV6}?
+--ro state
| +--ro enable-dns-feature?  boolean
| +--ro enable-dnsv4-relay?  boolean
| +--ro enable-dnsv6-relay?  boolean {feature-list:HAVE_IPV6}?
| +--ro dns-server-v4-addr*  inet:ipv4-address
| +--ro dns-server-v6-addr*  inet:ipv6-address {feature-list:HAVE_IPV6}?
+--rw interfaces
| +--rw interface* [name]
|   +--rw name      -> ../config/name
|   +--rw config
|     | +--rw name?          -> /ipi-interface:interfaces/interface/name
|     | +--rw enable-dnsv4-relay?  empty
|     | +--rw enable-dnsv6-relay?  empty {feature-list:HAVE_IPV6}?
|     | +--rw dns-relay-uplink?    empty
|     | +--rw dns-relay-v6-uplink? empty {feature-list:HAVE_IPV6}?
|     +--ro state
|       +--ro name?          -> /ipi-interface:interfaces/interface/name
|       +--ro enable-dnsv4-relay?  empty
|       +--ro enable-dnsv6-relay?  empty {feature-list:HAVE_IPV6}?
|       +--ro dns-relay-uplink?    empty
|       +--ro dns-relay-v6-uplink? empty {feature-list:HAVE_IPV6}?
+--rw vrfs {feature-list:HAVE_VRF}?
  +--rw vrf* [vrf-name]
    +--rw vrf-name  -> ../config/vrf-name
    +--rw config
    | +--rw vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:config/vrf-name
    | +--rw dns-server-v4-addr*  inet:ipv4-address
    | +--rw dns-server-v6-addr*  inet:ipv6-address {feature-list:HAVE_IPV6}?
    +--ro state
      +--ro vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:config/vrf-name
      +--ro dns-server-v4-addr*  inet:ipv4-address
      +--ro dns-server-v6-addr*  inet:ipv6-address {feature-list:HAVE_IPV6}?
```

---

## module: ipi-efm

```

+--rw ethernet-oam
  +--rw interfaces
    | +--rw interface* [name]
    |   +--rw name    -> ../config/name
    |   +--rw config
    |     | +--rw name?                -> /ipi-interface:interfaces/interface/name
    |     | +--rw enable?              empty
    |     | +--rw mode?                ipi-efm-types:ethernet_oam_mode_t
    |     | +--rw link-lost-timeout?   uint8
    |     | +--rw pdu-min-rate?       uint8
    |     | +--rw pdu-max-rate?       uint8
    |     | +--rw unidirectional-link-support?  empty
    |     | +--rw remote-loopback-support?  empty
    |     | +--rw remote-loopback-timeout?  uint8
    |     | +--rw link-monitor-support?  empty
    |     | +--rw link-monitor-off?      empty
    |     | +--rw link-monitor-event-log-size?  uint8
    |     | +--rw disable-port-on-remote-failure-events? ipi-efm-types:ethernet_oam_remote_failure_events_t
    |     | +--rw remote-loopback-start?  empty
    |   +--ro state
    |     +--ro name?                -> /ipi-interface:interfaces/interface/name
    |     +--ro enable?              empty
    |     +--ro mode?                ipi-efm-types:ethernet_oam_mode_t
    |     +--ro link-lost-timeout?   uint8
    |     +--ro pdu-min-rate?       uint8
    |     +--ro pdu-max-rate?       uint8
    |     +--ro unidirectional-link-support?  empty
    |     +--ro remote-loopback-support?  empty
    |     +--ro remote-loopback-timeout?  uint8
    |     +--ro link-monitor-support?  empty
    |     +--ro link-monitor-off?      empty
    |     +--ro link-monitor-event-log-size?  uint8

```

---

```

|   +--ro disable-port-on-remote-failure-events? ipi-efm-types:ethernet_oam_remote_failure_events_t
|   +--ro remote-loopback-start?                empty
|   +--ro if-index?                             uint32
|   +--ro interface-state?                      ipi-efm-types:ethernet_oam_oper_status_t
+--rw debug
  +--rw config
  | +--rw options? ipi-efm-types:ethernet_oam_debug_t
  +--ro state
    +--ro options?          ipi-efm-types:ethernet_oam_debug_t
    +--ro terminal-debug-status? ipi-efm-types:ethernet_oam_debug_t

```

rpcs:

```

+---x efm-terminal-debug-on {feature-list:HAVE_EFM,feature-list:HAVE_ONMD}?
| +---w input
|   +---w terminal-debug-status ipi-efm-types:ethernet_oam_debug_t
+---x efm-terminal-debug-off {feature-list:HAVE_EFM,feature-list:HAVE_ONMD}?
| +---w input
|   +---w terminal-debug-status ipi-efm-types:ethernet_oam_debug_t
+---x clear-interface-oam-counters {feature-list:HAVE_EFM,feature-list:HAVE_ONMD}?
  +---w input
    +---w name string

```

---

## module: ipi-elk

```

+--rw elk
  +--rw metricbeats
  | +--rw metricbeat* [ip]
  |   +--rw ip    -> ../config/ip
  |   +--rw config
  |     | +--rw ip?      inet:ipv4-address
  |     | +--rw username string
  |     | +--rw password string
  |     +--ro state
  |       +--ro ip?      inet:ipv4-address
  |       +--ro username string
  |       +--ro password string

```

```
+--rw filebeats
  +--rw filebeat* [ip]
    +--rw ip    -> ../config/ip
    +--rw config
      | +--rw ip?          inet:ipv4-address
      | +--rw certificate-path? string
    +--ro state
      +--ro ip?          inet:ipv4-address
      +--ro certificate-path? string
```

rpcs:

```
+---x elk-metricbeat-service-enable {feature-list:HAVE_HOSTPD}?
| +---w input
|   +---w vrf-name  string
+---x elk-filebeat-service-enable {feature-list:HAVE_HOSTPD}?
| +---w input
|   +---w vrf-name  string
+---x elk-metricbeat-service-disable {feature-list:HAVE_HOSTPD}?
| +---w input
|   +---w vrf-name  string
+---x elk-filebeat-service-disable {feature-list:HAVE_HOSTPD}?
  +---w input
    +---w vrf-name  string
```

---

## module: ipi-enhanced-pbr

```
+--rw enhanced-pbr
  +--ro class-maps-default
    | +--ro class-map-default* [name]
    |   +--ro name    -> ../state/name
    |   +--ro state
    |     +--ro name?      string
    |     +--ro type?      ipi-enhanced-pbr-types:epbr_class_map_t
    |     +--ro match-criteria? ipi-enhanced-pbr-types:epbr_match_criteria_t
  +--rw class-maps
```

```
| +--rw class-map* [name class-type]
|   +--rw name      -> ../config/name
|   +--rw class-type -> ../config/class-type
|   +--rw config
|     | +--rw name?      string
|     | +--rw class-type? ipi-enhanced-pbr-types:epbr_class_map_t
|     | +--rw match-criteria ipi-enhanced-pbr-types:epbr_match_criteria_t
|     | +--rw reference-description? cml-data-types:cml_line_t
|     +--ro state
|       | +--ro name?      string
|       | +--ro class-type? ipi-enhanced-pbr-types:epbr_class_map_t
|       | +--ro match-criteria ipi-enhanced-pbr-types:epbr_match_criteria_t
|       | +--ro reference-description? cml-data-types:cml_line_t
|     +--rw match-filters
|       +--rw config
|         | +--rw protocol?    cml-data-types:cml_range_t
|         | +--rw port?       cml-data-types:cml_range_t
|         | +--rw destination-port? cml-data-types:cml_range_t
|         | +--rw source-port?  cml-data-types:cml_range_t
|         | +--rw packet-length? cml-data-types:cml_range_t
|         | +--rw fragment-type? ipi-enhanced-pbr-types:epbr_fragment_type_t
|         +--ro state
|           | +--ro protocol?    cml-data-types:cml_range_t
|           | +--ro port?       cml-data-types:cml_range_t
|           | +--ro destination-port? cml-data-types:cml_range_t
|           | +--ro source-port?  cml-data-types:cml_range_t
|           | +--ro packet-length? cml-data-types:cml_range_t
|           | +--ro fragment-type? ipi-enhanced-pbr-types:epbr_fragment_type_t
|         +--rw ipv4
|           | +--rw config
|             | +--rw destination-prefix? cml-data-types:cml_ipv4_addr_prefix_t
|             | +--rw source-prefix?    cml-data-types:cml_ipv4_addr_prefix_t
|             +--ro state
|               | +--ro destination-prefix? cml-data-types:cml_ipv4_addr_prefix_t
|               | +--ro source-prefix?    cml-data-types:cml_ipv4_addr_prefix_t
|             +--rw icmp
```

```

|   |   +--rw config
|   |   |   +--rw icmp-type?  cml-data-types:cml_range_t
|   |   |   +--rw icmp-code?  cml-data-types:cml_range_t
|   |   +--ro state
|   |       +--ro icmp-type?  cml-data-types:cml_range_t
|   |       +--ro icmp-code?  cml-data-types:cml_range_t
|   +--rw tcp-flag
|   |   +--rw config
|   |   |   +--rw value?      string
|   |   |   +--rw bit-mask?  string
|   |   +--ro state
|   |       +--ro value?      string
|   |       +--ro bit-mask?  string
|   +--rw dscp
|       +--rw config
|           +--rw match-dscp-value?  cml-data-types:cml_range_t
|           +--ro state
|               +--ro match-dscp-value?  cml-data-types:cml_range_t
+--rw policy-maps
+--rw policy-map* [policy-map-name type]
+--rw policy-map-name  -> ../config/policy-map-name
+--rw type              -> ../config/type
+--rw config
| +--rw policy-map-name?      string
| +--rw type?                ipi-enhanced-pbr-types:epbr_policy_map_t
| +--rw reference-description? cml-data-types:cml_line_t
+--ro state
| +--ro policy-map-name?      string
| +--ro type?                ipi-enhanced-pbr-types:epbr_policy_map_t
| +--ro reference-description? cml-data-types:cml_line_t
+--rw classes
+--rw class* [class-map-name class-type]
+--rw class-map-name  -> ../config/class-map-name
+--rw class-type      -> ../config/class-type
+--rw config
| +--rw class-map-name?  string

```

```

| +--rw class-type?   ipi-enhanced-pbr-types:epbr_class_map_t
+--ro state
| +--ro class-map-name? string
| +--ro class-type?   ipi-enhanced-pbr-types:epbr_class_map_t
+--rw policy-actions
  +--rw config
  | +--rw drop-traffic? empty
  | +--rw dscp-set-value? ipi-enhanced-pbr-types:epbr_hex_dscp_t
  +--ro state
  | +--ro drop-traffic? empty
  | +--ro dscp-set-value? ipi-enhanced-pbr-types:epbr_hex_dscp_t
  +--rw police
  | +--rw config
  | | +--rw rate?      uint64
  | | +--rw rate-unit? ipi-enhanced-pbr-types:epbr_rate_unit_t
  | +--ro state
  |   +--ro rate?      uint64
  |   +--ro rate-unit? ipi-enhanced-pbr-types:epbr_rate_unit_t
  +--rw redirect
    +--rw ipv4
      +--rw extcommunity
        +--rw config
        | +--rw route-target? ipi-enhanced-pbr-types:epbr_vrf_rt_t
        +--ro state
          +--ro route-target? ipi-enhanced-pbr-types:epbr_vrf_rt_t

```

---

## module: ipi-erpsv2

```

+--rw erpsv2 {feature-list:HAVE_G8032V2}?
  +--rw rings
  | +--rw ring* [ring-name]
  |   +--rw ring-name -> ../config/ring-name
  |   +--rw config
  |     | +--rw ring-name?   string
  |     | +--rw east-interface? -> /ipi-interface:interfaces/interface/name

```

---

```
| | +--rw west-interface? -> /ipi-interface:interfaces/interface/name
| | +--rw description?   cml-data-types:cml_line_t
| +--ro state
|   +--ro ring-name?     string
|   +--ro east-interface? -> /ipi-interface:interfaces/interface/name
|   +--ro west-interface? -> /ipi-interface:interfaces/interface/name
|   +--ro description?   cml-data-types:cml_line_t
+--rw profiles
| +--rw profile* [profile-name]
|   +--rw profile-name -> ../config/profile-name
|   +--rw config
|     | +--rw profile-name?      string
|     | +--rw wait-to-restore-timer? uint8
|     | +--rw hold-off-timer?    uint16
|     | +--rw guard-time?       uint16
|     | +--rw protection-mode?   ipi-erpsv2-types:erpsv2_protection_mode_t
|     +--ro state
|       +--ro profile-name?      string
|       +--ro wait-to-restore-timer? uint8
|       +--ro hold-off-timer?    uint16
|       +--ro guard-time?       uint16
|       +--ro protection-mode?   ipi-erpsv2-types:erpsv2_protection_mode_t
|       +--ro wait-to-block-time? uint32
+--rw erp-instances
| +--rw erp-instance* [name]
|   +--rw name          -> ../config/name
|   +--rw config
|     | +--rw name?              string
|     | +--rw ring-name?        -> /erpsv2/rings/ring/ring-name
|     | +--rw mapped-profile-name? -> /erpsv2/profiles/profile/profile-name
|     | +--rw ring-type?        ipi-erpsv2-types:erpsv2_ring_type_t
|     | +--rw enable-tcn-propagation? empty
|     | +--rw tcn-to-instances*  string
|     | +--rw non-virtual-channel? empty
|     | +--rw ring-id?          uint8
|     | +--rw description?      cml-data-types:cml_line_t
```

---

---

```
|  +--ro state
|  |  +--ro name?          string
|  |  +--ro ring-name?     -> /erpsv2/rings/ring/ring-name
|  |  +--ro mapped-profile-name?  -> /erpsv2/profiles/profile/profile-name
|  |  +--ro ring-type?     ipi-erpsv2-types:erpsv2_ring_type_t
|  |  +--ro enable-tcn-propagation? empty
|  |  +--ro tcn-to-instances*  string
|  |  +--ro non-virtual-channel? empty
|  |  +--ro ring-id?        uint8
|  |  +--ro description?    cml-data-types:cml_line_t
|  |  +--ro current-state?  ipi-erpsv2-types:erpsv2_ring_state_t
|  |  +--ro previous-state? ipi-erpsv2-types:erpsv2_ring_state_t
|  +--rw associate-rings
|  |  +--rw associate-ring* [associate-ring-name]
|  |  |  +--rw associate-ring-name -> ../config/associate-ring-name
|  |  |  +--rw config
|  |  |  |  +--rw associate-ring-name? string
|  |  |  |  +--ro state
|  |  |  |  |  +--ro associate-ring-name? string
|  |  +--rw instance-role
|  |  |  +--rw config
|  |  |  |  +--rw (role-option)?
|  |  |  |  |  +--:(owner)
|  |  |  |  |  |  +--rw owner-port-id?    ipi-erpsv2-types:erpsv2_port_id_t
|  |  |  |  |  |  +--:(neighbor)
|  |  |  |  |  |  |  +--rw neighbor-port-id? ipi-erpsv2-types:erpsv2_port_id_t
|  |  |  |  |  |  |  +--:(next-neighbor)
|  |  |  |  |  |  |  |  +--rw next-neighbor-port-id? ipi-erpsv2-types:erpsv2_port_id_t
|  |  |  |  |  |  |  |  +--:(non-owner)
|  |  |  |  |  |  |  |  |  +--rw non-owner?    empty
|  |  |  +--ro state
|  |  |  |  +--ro (role-option)?
|  |  |  |  |  +--:(owner)
|  |  |  |  |  |  +--ro owner-port-id?    ipi-erpsv2-types:erpsv2_port_id_t
|  |  |  |  |  |  +--:(neighbor)
|  |  |  |  |  |  |  +--ro neighbor-port-id? ipi-erpsv2-types:erpsv2_port_id_t
```

```
| |   +--:(next-neighbor)
| |   | +--ro next-neighbor-port-id? ipi-erpsv2-types:erpsv2_port_id_t
| |   +--:(non-owner)
| |     +--ro non-owner?          empty
| +--rw aps-channel
| | +--rw config
| | | +--rw level?  uint8
| | +--ro state
| |   +--ro level?  uint8
| +--rw aps-channel-vlans
| | +--rw aps-channel-vlan* [vlan-id]
| |   +--rw vlan-id  -> ../config/vlan-id
| |   +--rw config
| | | +--rw vlan-id?   uint16
| | | +--rw inner-vlan-id? uint16
| | +--ro state
| |   +--ro vlan-id?   uint16
| |   +--ro inner-vlan-id? uint16
| +--rw data
| | +--rw config
| | | +--rw data-vlan? cml-data-types:cml_range_t
| | +--ro state
| |   +--ro data-vlan? cml-data-types:cml_range_t
| +--rw virtual-channel
| | +--rw config!
| | | +--rw channel-id      uint16
| | | +--rw attached-instance -> /erpsv2/erp-instances/erp-instance/name
| | +--ro state
| |   +--ro channel-id      uint16
| |   +--ro attached-instance -> /erpsv2/erp-instances/erp-instance/name
| +--rw east-link
| | +--ro state
| |   +--ro link-name?      string
| |   +--ro link-state?     ipi-erpsv2-types:erpsv2_link_state_t
| |   +--ro remote-node-id? cml-data-types:cml_mac_addr_t
| |   +--ro remote-blocked-port-reference? uint8
```

```

|  +--rw west-link
|  |  +--ro state
|  |  +--ro link-name?          string
|  |  +--ro link-state?        ipi-erpsv2-types:erpsv2_link_state_t
|  |  +--ro remote-node-id?    cml-data-types:cml_mac_addr_t
|  |  +--ro remote-blocked-port-reference? uint8
|  +--rw aps-statistics
|  |  +--ro state
|  |  +--ro tx-ring-aps-messages? yang:counter32
|  |  +--ro rx-ring-aps-messages? yang:counter32
+--rw debug
|  +--rw config
|  |  +--rw options? ipi-erpsv2-types:erpsv2_debug_t
|  |  +--ro state
|  |  +--ro options?          ipi-erpsv2-types:erpsv2_debug_t
|  |  +--ro terminal-debug-status? ipi-erpsv2-types:erpsv2_debug_t
+--rw subinterfaces

```

rpcs:

```

+---x erpsv2-switch-erp-instance {feature-list:HAVE_G8032V2,feature-list:HAVE_ONMD}?
|  +---w input
|  |  +---w instance-name  string
|  |  +---w operation      ipi-erpsv2-types:erpsv2_switch_operation_t
|  |  +---w port-id        ipi-erpsv2-types:erpsv2_port_id_t
+---x erpsv2-clear-ring-erp-instance {feature-list:HAVE_G8032V2,feature-list:HAVE_ONMD}?
|  +---w input
|  |  +---w instance-name  string
+---x erpsv2-clear-aps-statistics {feature-list:HAVE_G8032V2,feature-list:HAVE_ONMD}?
|  +---w input
|  |  +---w instance-name  string
+---x erpsv2-terminal-debug-on {feature-list:HAVE_G8032V2}?
|  +---w input
|  |  +---w terminal-debug-options ipi-erpsv2-types:erpsv2_debug_t
+---x erpsv2-terminal-debug-off {feature-list:HAVE_G8032V2}?
|  +---w input
|  |  +---w terminal-debug-options ipi-erpsv2-types:erpsv2_debug_t

```

notifications:

```

+---n erpsv2-instance-state-change-notification {feature-list:HAVE_G8032V2}?
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro name?         string
| +--ro current-state? ipi-erpsv2-types:erpsv2_ring_state_t
| +--ro previous-state? ipi-erpsv2-types:erpsv2_ring_state_t
+---n erpsv2-east-interface-state-change-notification {feature-list:HAVE_G8032V2}?
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?        string
| +--ro link-name?   string
| +--ro link-state?  ipi-erpsv2-types:erpsv2_link_state_t
+---n erpsv2-west-interface-state-change-notification {feature-list:HAVE_G8032V2}?
  +--ro severity?     cml-data-types:cml_notif_severity_t
  +--ro eventClass?  cml-data-types:cml_notif_class_t
  +--ro name?        string
  +--ro link-name?   string
  +--ro link-state?  ipi-erpsv2-types:erpsv2_link_state_t

```

---

## module: ipi-ethernet-vpn

```

+--rw evpn
  +--rw multi-homing
  | +--rw config
  | | +--rw esi-hold-time? uint32 {feature-list:HAVE_BGP_EVPN}?
  | +--ro state
  | +--ro esi-hold-time? uint32 {feature-list:HAVE_BGP_EVPN}?
+--rw global
  | +--rw config
  | | +--rw enable-vxlan-multihoming? empty {feature-list:HAVE_TUNNEL,feature-list:HAVE_NVO}?
  | | +--rw enable-irb?              empty {feature-list:HAVE_TUNNEL,feature-list:HAVE_NVO}?
  | | +--rw enable-evpn-etree?      empty {feature-list:HAVE_BGP_EVPN,feature-list:HAVE_NVO}?
  | +--ro state

```

---

```

|  +--ro enable-vxlan-multihoming?  empty {feature-list:HAVE_TUNNEL,feature-list:HAVE_NVO}?
|  +--ro enable-irb?                empty {feature-list:HAVE_TUNNEL,feature-list:HAVE_NVO}?
|  +--ro enable-evpn-etree?        empty {feature-list:HAVE_BGP_EVPN,feature-list:HAVE_NVO}?
+--rw irb-forwarding
|  +--rw config
|  |  +--rw mac-address?  cml-data-types:cml_mac_addr_t {feature-list:HAVE_TUNNEL,feature-
list:HAVE_NVO,feature-list:HAVE_BGP_EVPN}?
|  |  +--ro state
|  |  |  +--ro mac-address?  cml-data-types:cml_mac_addr_t {feature-list:HAVE_TUNNEL,feature-
list:HAVE_NVO,feature-list:HAVE_BGP_EVPN}?
|  |  +--rw irb-interfaces
|  |  |  +--rw irb-interface* [name]
|  |  |  |  +--rw name      -> ../config/name
|  |  |  |  +--rw config
|  |  |  |  |  +--rw name?      -> /ipi-interface:interfaces/interface/name {feature-list:HAVE_TUNNEL,feature-
list:HAVE_NVO,feature-list:HAVE_BGP_EVPN}?
|  |  |  |  |  +--rw gateway-mac?  empty {feature-list:HAVE_TUNNEL,feature-list:HAVE_NVO,feature-
list:HAVE_VXLAN,feature-list:HAVE_BGP_EVPN}?
|  |  |  |  |  +--ro state
|  |  |  |  |  |  +--ro name?      -> /ipi-interface:interfaces/interface/name {feature-list:HAVE_TUNNEL,feature-
list:HAVE_NVO,feature-list:HAVE_BGP_EVPN}?
|  |  |  |  |  |  +--ro gateway-mac?  empty {feature-list:HAVE_TUNNEL,feature-list:HAVE_NVO,feature-
list:HAVE_VXLAN,feature-list:HAVE_BGP_EVPN}?
+--rw interfaces
|  +--rw interface* [name]
|  |  +--rw name          -> ../config/name
|  |  +--rw config
|  |  |  +--rw name?      -> /ipi-interface:interfaces/interface/name
|  |  |  +--rw evpn-segment-id?  string
|  |  |  +--rw system-mac?    cml-data-types:cml_mac_addr_t
|  |  +--ro state
|  |  |  +--ro name?      -> /ipi-interface:interfaces/interface/name
|  |  |  +--ro evpn-segment-id?  string
|  |  |  +--ro system-mac?    cml-data-types:cml_mac_addr_t
|  +--rw access-interfaces
+--rw vrfs
  +--rw vrf* [vrf-name]
    +--rw vrf-name  -> ../config/vrf-name

```

---

```

+--rw config
| +-rw vrf-name?   -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
| +-rw service-type? cml-data-types:cml_evpn_service_type_t
+--ro state
  +-ro vrf-name?   -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
  +-ro service-type? cml-data-types:cml_evpn_service_type_t

```

---

## module: ipi-event-manager

```

+--rw event-manager
  +-rw config
  | +-rw feature? cml-data-types:cml_enable_disable_t
  +--ro state
  | +-ro feature? cml-data-types:cml_enable_disable_t
  +--rw event-entries
  | +-rw event-entry* [event-name]
  |   +-rw event-name -> ../config/event-name
  |   +-rw config
  |   | +-rw event-name? string
  |   | +-rw event-type ipi-event-manager-types:event_manager_event_type_t
  |   | +-rw event-id string
  |   | +-rw event-pattern? cml-data-types:cml_line_t
  |   | +-rw severity? ipi-event-manager-types:event_manager_severity_level_t
  |   +-ro state
  |     +-ro event-name? string
  |     +-ro event-type ipi-event-manager-types:event_manager_event_type_t
  |     +-ro event-id string
  |     +-ro event-pattern? cml-data-types:cml_line_t
  |     +-ro severity? ipi-event-manager-types:event_manager_severity_level_t
  |     +-ro trigger-count? yang:counter64
  |     +-ro policy-count? yang:counter64
  |     +-ro status? ipi-event-manager-types:event_manager_status_t
  |     +-ro policy-map? -> /event-manager/policies/policy/config/policy-name
  +--rw action-entries
  | +-rw action-entry* [action-name]

```

---

```

| +--rw action-name  -> ../config/action-name
| +--rw config
| | +--rw action-name?  string
| | +--rw action-type   ipi-event-manager-types:event_manager_action_type_t
| | +--rw action-script string
| +--ro state
|   +--ro action-name?  string
|   +--ro action-type   ipi-event-manager-types:event_manager_action_type_t
|   +--ro action-script string
|   +--ro trigger-count? yang:counter64
|   +--ro policy-count? yang:counter64
|   +--ro status?       ipi-event-manager-types:event_manager_status_t
|   +--ro policy-map*   -> /event-manager/policies/policy/config/policy-name
+--rw policies
  +--rw policy* [policy-name]
    +--rw policy-name  -> ../config/policy-name
    +--rw config
    | +--rw policy-name? string
    | +--rw event-name   -> /event-manager/event-entries/event-entry/event-name
    | +--rw action-name  -> /event-manager/action-entries/action-entry/action-name
    +--ro state
      +--ro policy-name?      string
      +--ro event-name        -> /event-manager/event-entries/event-entry/event-name
      +--ro action-name       -> /event-manager/action-entries/action-entry/action-name
      +--ro trigger-count?    yang:counter64
      +--ro status?           ipi-event-manager-types:event_manager_status_t
      +--ro last-execution-status? ipi-event-manager-types:event_manager_execution_status_t
      +--ro last-execution-time? string

```

rpcs:

```

+---x event-manager-clear-statistics-all {feature-list:HAVE_VLOGD,feature-list:HAVE_EVENT_MANAGER}?
+---x event-manager-clear-statistics-on-policy {feature-list:HAVE_VLOGD,feature-list:HAVE_EVENT_MANAGER}?
  +---w input
    +---w policy-name  string

```

---

## module: ipi-evpn-mpls

```

+--rw evpn-mpls
  +--rw global
    | +--rw config!
    | | +--rw enable-evpn-mpls  empty {feature-list:NOT_HAVE_MARVELL}?
    | | +--rw vtep-ipv4?       inet:ipv4-address
    | | +--rw mac-ageing-timer? uint32
    | +--ro state
    | | +--ro enable-evpn-mpls  empty {feature-list:NOT_HAVE_MARVELL}?
    | | +--ro vtep-ipv4?       inet:ipv4-address
    | | +--ro mac-ageing-timer? uint32
    | +--ro route-count
    | +--ro state
    |   +--ro max_route?  uint32
    |   +--ro active_route? uint32
+--rw arp-nd-global
  +--rw config
  | +--rw arp-nd-refresh-time? uint32
  +--ro state
  | +--ro arp-nd-refresh-time? uint32
+--rw mpls-tenants
  +--rw mpls-tenant* [tenant-identifier]
  | +--rw tenant-identifier  -> ../config/tenant-identifier
  | +--rw config
  | | +--rw vrf-name?       -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
  | | +--rw mac-holdtime?   int32
  | | +--rw tenant-description? string
  | | +--rw tunnel-policy-name? string {feature-list:HAVE_SERVICE_MAPPING}?
  | | +--rw irb-name?       -> /ipi-interface:interfaces/interface/name
  | | +--rw tenant-identifier? uint32
  | | +--rw vpws-identifier? uint32 {feature-list:HAVE_EVPN_VPWS}?
  | | +--rw control-word?   empty
  | | +--rw etree-leaf?    empty
  | +--ro state
  | | +--ro vrf-name?       -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name

```

---

```

| | +--ro mac-holdtime?    int32
| | +--ro tenant-description? string
| | +--ro tunnel-policy-name? string {feature-list:HAVE_SERVICE_MAPPING}?
| | +--ro irb-name?       -> /ipi-interface:interfaces/interface/name
| | +--ro tenant-identifier? uint32
| | +--ro vpws-identifier?  uint32 {feature-list:HAVE_EVPN_VPWS}?
| | +--ro control-word?    empty
| | +--ro etree-leaf?     empty
| +--ro route-count-info
| | +--ro state
| |   +--ro total?    uint32
| |   +--ro mac-only? uint32
| |   +--ro mac-ipv4? uint32
| |   +--ro mac-ipv6? uint32 {feature-list:HAVE_IPV6}?
| +--ro xconnect-mapping-info {feature-list:HAVE_EVPN_VPWS}?
| | +--ro state
| |   +--ro source-tenant-description? string
| |   +--ro destination-vpws-identifier? uint32
| |   +--ro source-interface?          string
| |   +--ro destination-interface?    string
| |   +--ro vtep-ip-address?          inet:ipv4-address
| |   +--ro connection-type?          ipi-evpn-mpls-types:evpn_mpls_xconnect_connection_type_t
| |   +--ro connection-status?       ipi-evpn-mpls-types:evpn_mpls_xconnect_connection_status_t
| +--rw irb
| | +--rw config
| | | +--rw irb-advertise-host-route? empty
| | +--ro state
| |   +--ro irb-advertise-host-route? empty
| +--ro arp-cache-info* [host-ip]
| | +--ro host-ip -> ../state/host-ip
| | +--ro state
| |   +--ro host-ip?  inet:ipv4-address
| |   +--ro host-mac? cml-data-types:cml_mac_addr_t
| |   +--ro host-type? ipi-evpn-mpls-types:evpn_mpls_host_t
| +--ro nd-cache-info* [host-ip]
| | +--ro host-ip -> ../state/host-ip

```

---

```

| | +--ro state
| |   +--ro host-ip?   inet:ipv6-address
| |   +--ro host-mac?  cml-data-types:cml_mac_addr_t
| |   +--ro host-type? ipi-evpn-mpls-types:evpn_mpls_host_t
| +--ro mac-table-info* [mac-address]
| | +--ro mac-address  -> ../state/mac-address
| | +--ro state
| |   +--ro mac-address?      cml-data-types:cml_mac_addr_t
| |   +--ro interface-name?   -> /ipi-interface:interfaces/interface/name
| |   +--ro vtep-ip-esi?      string
| |   +--ro host-type?        ipi-evpn-mpls-types:evpn_mpls_host_t
| |   +--ro host-status?      ipi-evpn-mpls-types:evpn_mpls_host_status_t
| |   +--ro access-port-description? string
| +--ro access-interface-info* [access-interface-name]
|   +--ro access-interface-name  -> ../state/access-interface-name
|   +--ro state
|     +--ro access-interface-name? string
|     +--ro tenant-description?   string
|     +--ro ethernet-segment-id?  string
|     +--ro port-status?          string
+--ro tunnel* [destination-vtep-ip destination-evpn-identifier]
  +--ro destination-vtep-ip      -> ../state/destination-vtep-ip
  +--ro destination-evpn-identifier -> ../state/destination-evpn-identifier
  +--ro state
    +--ro destination-vtep-ip?    inet:ipv4-address
    +--ro destination-evpn-identifier? uint32
    +--ro source-vtep-ip?         inet:ipv4-address
    +--ro up-down-time?           yang:timeticks
    +--ro tunnel-status?          ipi-evpn-mpls-types:evpn_mpls_tunnel_status_t
    +--ro source-vpws-identifier?  uint32
    +--ro destination-vpws-identifier? uint32
    +--ro local-multicast-label?   uint32
    +--ro local-unicast-label?     uint32
    +--ro remote-multicast-label?  uint32
    +--ro remote-unicast-label?    uint32
    +--ro is_xconnect?            boolean

```

```

+--ro mpls-multipath-grp-name?   string
+--ro mpls-multipath-nhlfe-ix?   uint32
+--ro tunnel-label?             uint32
+--ro network-interface?        -> /ipi-interface:interfaces/interface/name
+--ro counters
  +--ro out-bum-packets?         yang:counter64
  +--ro out-unicast-packets?     yang:counter64
  +--ro in-bum-packets?         yang:counter64
  +--ro in-unicast-packets?     yang:counter64

```

rpcs:

```

+---x clear-nvo-mpls-dynamic-mac-address-table {feature-list:HAVE_MPLS,feature-list:HAVE_SUBINTERFACE}?
+---x clear-nvo-mpls-dynamic-mac-address-table-evid {feature-list:HAVE_MPLS,feature-
list:HAVE_SUBINTERFACE}?
| +---w input
|   +---w tenant-identifier   uint32
|   +---w mac-address?       cml-data-types:cml_mac_addr_t
+---x clear-evpn-mpls-egress-counters {feature-list:HAVE_MPLS,feature-list:HAVE_SUBINTERFACE}?
| +---w input
|   +---w tenant-identifier?  uint32
|   +---w egress-direction   ipi-evpn-mpls-types:evpn_mpls_egress_dir_t
|   +---w destination-ip?    inet:ipv4-address
+---x clear-evpn-mpls-ingress-counters {feature-list:HAVE_MPLS,feature-list:HAVE_SUBINTERFACE}?
+---w input
  +---w tenant-identifier?    uint32
  +---w ingress-direction    ipi-evpn-mpls-types:evpn_mpls_ingress_dir_t

```

---

## module: ipi-evpn-srv6

```

+--rw evpn-srv6
  +--rw global
  | +--rw config!
  | | +--rw enabled          empty
  | | +--rw vtep-ipv6-address? inet:ipv6-address
  | | +--rw mac-ageing-timer? uint32
  | +--ro state

```

---

```

| +--ro enabled          empty
| +--ro vtep-ipv6-address? inet:ipv6-address
| +--ro mac-ageing-timer? uint32
+--rw arp-nd-global
| +--rw config
| | +--rw arp-nd-refresh-time? uint32
| +--ro state
| +--ro arp-nd-refresh-time? uint32
+--rw tenants
  +--rw tenant* [tenant-identifier]
    +--rw tenant-identifier -> ../config/tenant-identifier
    +--rw config
      | +--rw vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
      | +--rw mac-holdtime?  int32
      | +--rw tenant-description? string
      | +--rw tunnel-policy-name? string {feature-list:HAVE_SERVICE_MAPPING_OR_HAVE_SRV6}?
      | +--rw srv6-locator-name? string
      | +--rw tenant-identifier? uint32
      | +--rw vpws-identifier?  uint32 {feature-list:HAVE_EVPN_VPWS}?
      +--ro state
        +--ro vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
        +--ro mac-holdtime?  int32
        +--ro tenant-description? string
        +--ro tunnel-policy-name? string {feature-list:HAVE_SERVICE_MAPPING_OR_HAVE_SRV6}?
        +--ro srv6-locator-name? string
        +--ro tenant-identifier? uint32
        +--ro vpws-identifier?  uint32 {feature-list:HAVE_EVPN_VPWS}?

rpcs:
  +---x clear-nvo-srv6-dynamic-mac-address-table {feature-list:HAVE_SRV6,feature-list:HAVE_SUBINTERFACE}?
  +---x clear-nvo-srv6-dynamic-mac-address-table-evid {feature-list:HAVE_SRV6,feature-list:HAVE_SUBINTERFACE}?
  | +---w input
  | +---w tenant-identifier  uint32
  | +---w mac-address?      cml-data-types:cml_mac_addr_t
  +---x clear-evpn-srv6-egress-counters {feature-list:HAVE_SRV6,feature-list:HAVE_SUBINTERFACE}?
  | +---w input

```

---

```

| +---w tenant-identifier? uint32
| +---w egress-direction  cml-data-types:evpn_egress_dir_t
| +---w destination-ip?   inet:ipv6-address
+---x clear-evpn-srv6-ingress-counters {feature-list:HAVE_SRV6,feature-list:HAVE_SUBINTERFACE}?
  +---w input
    +---w tenant-identifier? uint32
    +---w ingress-direction  cml-data-types:evpn_ingress_dir_t

```

---

## module: ipi-g8031

```

+--rw g8031
  +--rw instances
    | +--rw instance* [eps-id] {feature-list:HAVE_G8031}?
    |   +--rw eps-id  -> ../config/eps-id
    |   +--rw config
    |     | +--rw eps-id?      uint8
    |     | +--rw bridge-id   -> /ipi-network-instance:network-instances/network-instance/instance-name
    |     | +--rw working-port? -> /ipi-interface:interfaces/interface/name
    |     | +--rw protection-port? -> /ipi-interface:interfaces/interface/name
    |     | +--rw elps-instance-id? uint8
    |     | +--rw data-vlans?   cml-data-types:cml_range_t
    |     | +--rw primary-vlan? -> /ipi-network-instance:network-instances/network-instance/ipi-bridge:bridge/ipi-
vlan:vlans/vlan/vlan-id
    |     | +--ro state
    |     |   +--ro eps-id?      uint8
    |     |   +--ro bridge-id   -> /ipi-network-instance:network-instances/network-instance/instance-name
    |     |   +--ro working-port? -> /ipi-interface:interfaces/interface/name
    |     |   +--ro protection-port? -> /ipi-interface:interfaces/interface/name
    |     |   +--ro elps-instance-id? uint8
    |     |   +--ro data-vlans?   cml-data-types:cml_range_t
    |     |   +--ro primary-vlan? -> /ipi-network-instance:network-instances/network-instance/ipi-bridge:bridge/ipi-
vlan:vlans/vlan/vlan-id
    |     +--rw elps
    |       +--rw config

```

---

```
| | +--rw protection-type?      ipi-g8031-elps-types:g8031_elps_protection_type_t
| | +--rw enable-revertive-mode? empty
| | +--rw level-identifier?     uint8
| +--ro state
| | +--ro protection-type?      ipi-g8031-elps-types:g8031_elps_protection_type_t
| | +--ro enable-revertive-mode? empty
| | +--ro level-identifier?     uint8
| | +--ro direction?           ipi-g8031-elps-types:g8031_direction_type_t
| | +--ro active-path?         ipi-g8031-elps-types:g8031_active_path_type_t
| | +--ro request-signal?      ipi-g8031-elps-types:g8031_request_signal_type_t
| | +--ro current-state?       ipi-g8031-elps-types:g8031_current_state_type_t
| | +--ro failure-of-protocol-state? ipi-g8031-elps-types:g8031_failure_of_protocol_state_type_t
| | +--ro rx-lps-frame-count?   yang:counter32
| | +--ro tx-lps-frame-count?   yang:counter32
| +--rw timers
| | +--rw config
| | | +--rw wait-to-restore?    uint16
| | | +--rw hold-off?          uint8
| | | +--ro state
| | |   +--ro wait-to-restore?  uint16
| | |   +--ro hold-off?         uint8
| +--rw traffic-switch
|   +--rw config
|   | +--rw local-freeze?      empty
|   | +--ro state
|   |   +--ro local-freeze?    empty
+--rw g8031-elps
| +--rw profiles
| | +--rw profile* [name] {feature-list:HAVE_G8031}?
| |   +--rw name      -> ../config/name
| |   +--rw config
| |   | +--rw name?      string
| |   | +--rw mode?      ipi-g8031-elps-types:g8031_mode_type_t
| |   | +--rw switching-mode? ipi-g8031-elps-types:g8031_switching_mode_type_t
| |   | +--rw timer-hold-off?  uint8
| |   | +--rw timer-wait-to-restore? uint32
```

```

| | +--ro state
| |   +--ro name?          string
| |   +--ro mode?          ipi-g8031-elps-types:g8031_mode_type_t
| |   +--ro switching-mode? ipi-g8031-elps-types:g8031_switching_mode_type_t
| |   +--ro timer-hold-off? uint8
| |   +--ro timer-wait-to-restore? uint32
| +--rw protections
| | +--rw protection* [group-name] {feature-list:HAVE_G8031}?
| |   +--rw group-name  -> ../config/group-name
| |   +--rw config
| |     | +--rw group-name?  string
| |     | +--rw working-port? -> /ipi-interface:interfaces/interface/name
| |     | +--rw protection-port? -> /ipi-interface:interfaces/interface/name
| |     +--ro state
| |       +--ro group-name?  string
| |       +--ro working-port? -> /ipi-interface:interfaces/interface/name
| |       +--ro protection-port? -> /ipi-interface:interfaces/interface/name
| +--rw eps-instances
| | +--rw eps-instance* [name]
| |   +--rw name          -> ../config/name
| |   +--rw config
| |     | +--rw name?          string
| |     | +--rw eps-protection-group? -> /g8031/g8031-elps/protections/protection/group-name
| |     | +--rw g8031-profile-name? -> /g8031/g8031-elps/profiles/profile/name
| |     +--ro state
| |       | +--ro name?          string
| |       | +--ro eps-protection-group? -> /g8031/g8031-elps/protections/protection/group-name
| |       | +--ro g8031-profile-name? -> /g8031/g8031-elps/profiles/profile/name
| |     +--rw aps-channel
| |       | +--rw config
| |       | | +--rw level?  uint8
| |       | +--ro state
| |       | | +--ro level?  uint8
| |     +--rw control-vlans
| |       | +--rw control-vlan* [vlan-id]
| |       | | +--rw vlan-id  -> ../config/vlan-id

```

```

|   |   +--rw config
|   |   |   +--rw vlan-id?      uint16
|   |   |   +--rw inner-vlan-id? uint16
|   |   +--ro state
|   |       +--ro vlan-id?      uint16
|   |       +--ro inner-vlan-id? uint16
|   +--rw data
|       +--rw config
|           | +--rw data-vlan?  cml-data-types:cml_range_t
|           +--ro state
|               +--ro data-vlan? cml-data-types:cml_range_t
+--rw debug
    +--rw config
    |   +--rw options? ipi-g8031-elps-types:g8031_debug_t
    +--ro state
        +--ro options?          ipi-g8031-elps-types:g8031_debug_t
        +--ro terminal-debug-status? ipi-g8031-elps-types:g8031_debug_t

```

rpcs:

```

+---x g8031-lockout {feature-list:HAVE_G8031,feature-list:HAVE_ONMD}?
| +---w input
|   +---w instance-name  string
+---x g8031-exercise {feature-list:HAVE_G8031,feature-list:HAVE_ONMD}?
| +---w input
|   +---w instance-name  string
+---x g8031-clear {feature-list:HAVE_G8031,feature-list:HAVE_ONMD}?
| +---w input
|   +---w instance-name  string
+---x g8031-terminal-debug-on {feature-list:HAVE_G8031,feature-list:HAVE_ONMD}?
| +---w input
|   +---w terminal-debug-options ipi-g8031-elps-types:g8031_debug_t
+---x g8031-terminal-debug-off {feature-list:HAVE_G8031,feature-list:HAVE_ONMD}?
| +---w input
|   +---w terminal-debug-options ipi-g8031-elps-types:g8031_debug_t
+---x elps-switch-elp-instance {feature-list:HAVE_G8031,feature-list:HAVE_ONMD}?
| +---w input

```

---

```
| +---w instance-name  string
| +---w operation      ipi-g8031-elps-types:g8031_eps_instance_switch
+---x eps-clear-ring-instance {feature-list:HAVE_G8031,feature-list:HAVE_ONMD}?
  +---w input
    +---w instance-name  string
    +---w eps-type       ipi-g8031-elps-types:g8031_eps_instance_type
```

---

## module: ipi-global-te

```
+--rw admin-groups
| +--rw admin-group* [name id]
|   +--rw name    -> ../config/name
|   +--rw id      -> ../config/id
|   +--rw config
|     | +--rw name?  string
|     | +--rw id?   uint8
|     +--ro state
|       +--ro name?  string
|       +--ro id?   uint8
+--rw extended-admin-groups
| +--rw extended-admin-group* [name id]
|   +--rw name    -> ../config/name
|   +--rw id      -> ../config/id
|   +--rw config
|     | +--rw name?  string
|     | +--rw id?   uint32
|     +--ro state
|       +--ro name?  string
|       +--ro id?   uint32
+--rw extended-admin-group-ranges
  +--rw extended-admin-group-range* [minimum-id maximum-id]
    +--rw minimum-id  -> ../config/minimum-id
    +--rw maximum-id  -> ../config/maximum-id
    +--rw config
      | +--rw minimum-id?  uint32
      | +--rw maximum-id?  uint32
```

```
+--ro state
  +--ro minimum-id?  uint32
  +--ro maximum-id?  uint32
```

---

## module: ipi-host

```
+--rw system-host {feature-list:HAVE_IMI}?
  +--rw config
    | +--rw banner-motd?          cml-data-types:cml_banner_t
    | +--rw banner-motd-file?    cml-data-types:cml_file_t
    | +--rw service-passwd-encryption?  boolean
    | +--rw service-term-length?  uint16
    | +--rw system-enable-passwd?  cml-data-types:cml_line_t
    | +--rw passwd-encrypted?     empty
    | +--rw disable-default-autoenable?  empty
    | +--rw disable-service-advanced-vty?  empty
  +--ro state
    +--ro banner-motd?          cml-data-types:cml_banner_t
    +--ro banner-motd-file?    cml-data-types:cml_file_t
    +--ro service-passwd-encryption?  boolean
    +--ro service-term-length?  uint16
    +--ro system-enable-passwd?  cml-data-types:cml_line_t
    +--ro passwd-encrypted?     empty
    +--ro disable-default-autoenable?  empty
    +--ro disable-service-advanced-vty?  empty
```

---

## module: ipi-hwtable

```
notifications:
  +---n hwtable-monitor-full-notification
    | +--ro severity?  cml-data-types:cml_notif_severity_t
    | +--ro eventClass?  cml-data-types:cml_notif_class_t
    | +--ro message?    string
  +---n hwtable-monitor-full-clear-notification
```

```

+--ro severity?  cml-data-types:cml_notif_severity_t
+--ro eventClass? cml-data-types:cml_notif_class_t
+--ro message?   string

```

---

## module: ipi-if-aggregate

augment /ipi-interface:interfaces/ipi-interface:interface:

```

+--rw member-aggregation
  +--rw config!
    | +--rw agg-type    ipi-lag-types:lag_link_agg_type_t
    | +--rw aggregate-id uint16
    | +--rw lacp-mode   ipi-lag-types:lacp_mode_t
  +--ro state
    +--ro agg-type    ipi-lag-types:lag_link_agg_type_t
    +--ro aggregate-id uint16
    +--ro lacp-mode   ipi-lag-types:lacp_mode_t

```

augment /ipi-interface:interfaces/ipi-interface:interface:

```

+--rw aggregator
  +--rw config
    | +--rw min-links?   uint8 {feature-list:HAVE_LACP}?
    | +--rw min-bandwidth? string {feature-list:HAVE_LACP}?
  +--ro state
    | +--ro min-links?   uint8 {feature-list:HAVE_LACP}?
    | +--ro min-bandwidth? string {feature-list:HAVE_LACP}?
    | +--ro agg-min-links-state? ipi-lag-types:lag_agg_min_links_status
  +--ro members
    +--ro member* [link-name]
      +--ro link-name  -> ../state/link-name
      +--ro state
        +--ro link-name? string
        +--ro link-state? ipi-lag-types:lag_member_link_status_t

```

notifications:

```

+---n agg-min-links-state-update
  +--ro severity?      cml-data-types:cml_notif_severity_t

```

```

+--ro eventClass?      cml-data-types:cml_notif_class_t
+--ro name?           string
+--ro agg-min-links-state? ipi-lag-types:lag_agg_min_links_status

```

---

## module: ipi-if-ethernet

augment /ipi-interface:interfaces/ipi-interface:interface:

```

+--rw ethernet
  +--rw config
    | +--rw duplex-mode?      ipi-if-types:if_duplex_t
    | +--rw mac-address?      cml-data-types:cml_mac_addr_t {feature-list:NOT_HAVE_DUNE}?
    | +--rw secondary-mac-address? empty {feature-list:HAVE_MLAG}?
    | +--rw port-speed?      ipi-if-types:if_interface_speed_t {feature-list:NOT_HAVE_TIBIT}?
  +--ro state
    | +--ro duplex-mode?      ipi-if-types:if_duplex_t
    | +--ro mac-address?      cml-data-types:cml_mac_addr_t {feature-list:NOT_HAVE_DUNE}?
    | +--ro secondary-mac-address? empty {feature-list:HAVE_MLAG}?
    | +--ro port-speed?      ipi-if-types:if_interface_speed_t {feature-list:NOT_HAVE_TIBIT}?
    | +--ro hw-mac-address?    cml-data-types:cml_mac_addr_t
    | +--ro negotiated-duplex-mode? ipi-if-types:if_duplex_t
    | +--ro negotiated-port-speed? ipi-if-types:if_interface_speed_t
    | +--ro counters
      | +--ro in-mac-control-frames? yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
      | +--ro in-mac-pause-frames?  yang:counter64
      | +--ro in-undersize-frames?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-list:HAVE_HAL,feature-
list:NOT_HAVE_SWFWDR}?
      | +--ro in-oversize-frames?   yang:counter64 {feature-list:HAVE_BROADCOM,feature-list:HAVE_HAL,feature-
list:NOT_HAVE_SWFWDR}?
      | +--ro in-fragment-frames?   yang:counter64 {feature-list:HAVE_BROADCOM,feature-list:HAVE_HAL,feature-
list:NOT_HAVE_SWFWDR}?
      | +--ro in-jabber-frames?     yang:counter64 {feature-list:HAVE_BROADCOM,feature-list:HAVE_HAL,feature-
list:NOT_HAVE_SWFWDR}?
      | +--ro in-crc-errors?        yang:counter64 {feature-list:HAVE_BROADCOM,feature-list:HAVE_HAL,feature-
list:NOT_HAVE_SWFWDR}?
      | +--ro out-mac-control-frames? yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?

```

---

```
|  +--ro out-mac-pause-frames?  yang:counter64
|  +--ro in-distribution
|  |  +--ro in-frames-64-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro in-frames-65-127-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro in-frames-128-255-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro in-frames-256-511-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro in-frames-512-1023-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro in-frames-1024-1518-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro in-frames-1519-2047-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro in-frames-2048-4095-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro in-frames-4096-9216-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro in-frames-9217-16383-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  +--ro out-distribution
|  |  +--ro out-frames-64-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro out-frames-65-127-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro out-frames-128-255-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro out-frames-256-511-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro out-frames-512-1023-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro out-frames-1024-1518-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro out-frames-1519-2047-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro out-frames-2048-4095-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro out-frames-4096-9216-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
|  |  +--ro out-frames-9217-16383-octets?  yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR}?
```

---

```

+--rw flow-control {feature-list:HAVE_L2}?
  +--rw config
  | +--rw enable-rcv? ipi-if-types:if_flowctrl_t {feature-list:HAVE_L2}?
  | +--rw enable-snd? ipi-if-types:if_flowctrl_t {feature-list:HAVE_L2}?
  +--ro state
    +--ro enable-rcv? ipi-if-types:if_flowctrl_t {feature-list:HAVE_L2}?
    +--ro enable-snd? ipi-if-types:if_flowctrl_t {feature-list:HAVE_L2}?
    +--ro rcv-oper-status? ipi-if-types:if_flowctrl_t
    +--ro snd-oper-status? ipi-if-types:if_flowctrl_t

```

---

## module: ipi-if-extended

```

+--rw mac-ageing
  +--rw config
  | +--rw hit-based-ageing? ipi-if-types:cml_mac_ageing_t {feature-list:NOT_HAVE_DUNE}?
  +--ro state
    +--ro hit-based-ageing? ipi-if-types:cml_mac_ageing_t {feature-list:NOT_HAVE_DUNE}?

```

augment /ipi-interface:interfaces/ipi-interface:interface:

```

+--rw extended
  +--rw l2-control-protocol* [l2cp-type] {feature-list:HAVE_L2}?
  | +--rw l2cp-type -> ../config/l2cp-type
  | +--rw config
  | | +--rw l2cp-type? ipi-if-types:if_l2cp_t
  | | +--rw protocol-process ipi-if-types:if_l2cp_process_t
  | +--ro state
  | +--ro l2cp-type? ipi-if-types:if_l2cp_t
  | +--ro protocol-process ipi-if-types:if_l2cp_process_t
  +--rw config
  | +--rw link-flap-error-disable? empty {feature-list:HAVE_L2}?
  | +--rw storm-control-error-disable? empty {feature-list:HAVE_RATE_LIMIT}?
  | +--rw mac-move-limit-error-disable? empty {feature-list:HAVE_L2}?
  | +--rw mac-move-priority? uint32 {feature-list:HAVE_L2}?
  | +--rw disable-snmp-trap-link-status? empty
  | +--rw mau-default-type? ipi-if-types:if_mautype_t {feature-list:HAVE_L2}?
  | +--rw debounce-time? uint16

```

---

```

| +-rw protected-port?          ipi-if-types:if_protected_port_type_t
| +-rw ucmp-port?              ipi-if-types:if_ucmp_state
+--ro state
| +-ro link-flap-error-disable?  empty {feature-list:HAVE_L2}?
| +-ro storm-control-error-disable?  empty {feature-list:HAVE_RATE_LIMIT}?
| +-ro mac-move-limit-error-disable?  empty {feature-list:HAVE_L2}?
| +-ro mac-move-priority?        uint32 {feature-list:HAVE_L2}?
| +-ro disable-snmp-trap-link-status?  empty
| +-ro mau-default-type?         ipi-if-types:if_mautype_t {feature-list:HAVE_L2}?
| +-ro debounce-time?           uint16
| +-ro protected-port?          ipi-if-types:if_protected_port_type_t
| +-ro ucmp-port?              ipi-if-types:if_ucmp_state
| +-ro properties?             ipi-if-types:if_iface_prop_t
| +-ro mapped-name?            string
| +-ro if-counter-discontinuity-time?  yang:timestamp
| +-ro slot-id?                uint32
| +-ro hardware-type?          ipi-if-types:if_hw_type_t
| +-ro storm-total-discards?     yang:counter64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_RATE_LIMIT,feature-list:NOT_HAVE_DUNE}?
| +-ro metric?                 int32
| +-ro if-type?                ipi-if-types:if_interface_type_t
| +-ro trust-state?            ipi-if-types:if_trust_state_t {feature-list:HAVE_QOS}?
| +-ro monitor-port-grp?        boolean {feature-list:HAVE_TFO}?
| +-ro failover-link-type?      ipi-if-types:if_tfo_link_type_t {feature-list:HAVE_TFO}?
| +-ro udld-flush-transmitted?   uint16 {feature-list:HAVE_UDLD}?
| +-ro debounce-flap-count?     uint16
| +-ro debounce-last-flap-time?  yang:date-and-time
| +-ro debounce-remain-time?    yang:counter32
| +-ro debounce-running-status?  ipi-if-types:if_debounce_running_state
| +-ro debounce-config-status?  ipi-if-types:if_debounce_running_state
| +-ro last-flapped?           ipi-if-types:if_last_clear_time_t
| +-ro auto-ipv6-link-local-address?  cml-data-types:cml_ipv6_prefix_t {feature-list:HAVE_IPV6}?
+--rw bandwidth-management
| +-rw config
|   +-rw enable-re-routing?  empty
+--rw port-monitor
| +-rw config

```

---

---

```
| | +--rw enable-speed?      empty
| | +--rw enable-queue-drops? empty
| +--ro state
| | +--ro enable-speed?      empty
| | +--ro enable-queue-drops? empty
| +--rw port-monitor-threshold
|   +--rw config!
|   | +--rw warning-threshold  uint8
|   | +--rw recovery-threshold uint8
|   +--ro state
|     +--ro warning-threshold  uint8
|     +--ro recovery-threshold uint8
+--ro capabilities {feature-list:HAVE_HAL}?
| +--ro state
|   +--ro speed-half-duplex?  string
|   +--ro speed-full-duplex?  string
|   +--ro pause?              ipi-if-types:if_raw_string_t
|   +--ro interface-type?     ipi-if-types:if_raw_string_t
|   +--ro medium?             ipi-if-types:if_raw_string_t
|   +--ro loopback?           ipi-if-types:if_raw_string_t
|   +--ro flags?              string
|   +--ro eee?                ipi-if-types:if_raw_string_t
|   +--ro fcmmap?             string
|   +--ro encapsulation?      ipi-if-types:if_raw_string_t
|   +--ro fec?                ipi-if-types:if_raw_string_t
+--rw aclif
| +--rw config
| | +--rw aclif-type? ipi-if-types:if_aclif_type_t
| +--ro state
|   +--ro aclif-type? ipi-if-types:if_aclif_type_t
+--rw link-debounce-time
  +--rw config!
  | +--rw linkup-debounce-time  uint16
  | +--rw linkdown-debounce-time uint16
  +--ro state
    +--ro linkup-debounce-time  uint16
```

```

    +--ro linkdown-debounce-time  uint16
augment /ipi-interface:interfaces/ipi-interface:interface/ipi-if-ethernet:ethernet:
+--rw extended-ethernet
  +--rw config
    | +--rw forward-err-correction?  ipi-if-types:if_intf_fec_t
    | +--rw load-interval?          uint16 {feature-list:HAVE_BROADCOM_OR_HAVE_MARVELL}?
  +--ro state
    | +--ro forward-err-correction?  ipi-if-types:if_intf_fec_t
    | +--ro load-interval?          uint16 {feature-list:HAVE_BROADCOM_OR_HAVE_MARVELL}?
    | +--ro default-duplex-mode?    uint8
    | +--ro default-speed?         string
  +--rw switchport-allowed-ether-types {feature-list:HAVE_ALLOWED_ETHERTYPE}?
    +--rw config
      | +--rw arp?                  boolean
      | +--rw ipv4?                 boolean
      | +--rw ipv6?                 boolean
      | +--rw mpls?                 boolean
      | +--rw ether-type-value*    string
      | +--rw log?                  boolean
    +--ro state {feature-list:HAVE_ALLOWED_ETHERTYPE}?
      +--ro statistics* [ether-type]
        | +--ro ether-type  ipi-if-types:if_switchport_ether_type_t
        | +--ro packets?    yang:counter64
        | +--ro bytes?     yang:counter64
      +--ro arp?            boolean
      +--ro ipv4?           boolean
      +--ro ipv6?           boolean
      +--ro mpls?           boolean
      +--ro ether-type-value* string
      +--ro log?            boolean
augment /ipi-interface:interfaces/ipi-interface:interface/ipi-if-ethernet:ethernet:
+--rw storm-control {feature-list:HAVE_RATE_LIMIT}?
  +--rw broadcast {feature-list:HAVE_RATE_LIMIT}?
    | +--rw config! {feature-list:HAVE_RATE_LIMIT}?
      | | +--rw bcast-value          ipi-if-types:if_rate_limit_t
      | | +--rw bcast-rate-limit-format  ipi-if-types:if_rate_limit_type

```

```

| | +--rw bcast-burst-value      uint32
| +--ro state {feature-list:HAVE_RATE_LIMIT}?
|   +--ro bcast-value           ipi-if-types:if_rate_limit_t
|   +--ro bcast-rate-limit-format ipi-if-types:if_rate_limit_type
|   +--ro bcast-burst-value      uint32
|   +--ro hardware-applied-bcast-value? decimal64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_RATE_LIMIT}?
+--rw multicast {feature-list:HAVE_RATE_LIMIT}?
| +--rw config! {feature-list:HAVE_RATE_LIMIT}?
| | +--rw mcast-value           ipi-if-types:if_rate_limit_t
| | +--rw mcast-rate-limit-format ipi-if-types:if_rate_limit_type
| | +--rw mcast-burst-value      uint32
| +--ro state {feature-list:HAVE_RATE_LIMIT}?
|   +--ro mcast-value           ipi-if-types:if_rate_limit_t
|   +--ro mcast-rate-limit-format ipi-if-types:if_rate_limit_type
|   +--ro mcast-burst-value      uint32
|   +--ro hardware-applied-mcast-value? decimal64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_RATE_LIMIT}?
+--rw dlf-broadcast {feature-list:HAVE_RATE_LIMIT}?
  +--rw config! {feature-list:HAVE_RATE_LIMIT}?
  | +--rw dlf-bcast-value       ipi-if-types:if_rate_limit_t
  | +--rw dlf-bcast-rate-limit-format ipi-if-types:if_rate_limit_type
  | +--rw dlf-bcast-burst-value  uint32
  +--ro state {feature-list:HAVE_RATE_LIMIT}?
    +--ro dlf-bcast-value       ipi-if-types:if_rate_limit_t
    +--ro dlf-bcast-rate-limit-format ipi-if-types:if_rate_limit_type
    +--ro dlf-bcast-burst-value  uint32
    +--ro hardware-applied-dlf-bcast-value? decimal64 {feature-list:HAVE_BROADCOM,feature-
list:HAVE_RATE_LIMIT}?
augment /ipi-interface/interfaces/ipi-interface:interface/ipi-interface:state:
+--ro custom-state
  +--ro current-bandwidth? uint64
augment /ipi-interface/interfaces/ipi-interface:interface/ipi-interface:state/ipi-interface:counters:
+--ro extended-counters
  +--ro in-compressed?      yang:counter64
  +--ro out-compressed?     yang:counter64
  +--ro collisions?        yang:counter64

```

---

```

+--ro unicast-rpf-discard? yang:counter64
+--ro in-length-errors? yang:counter64
+--ro in-oversize-errors? yang:counter64
+--ro in-crc-errors? yang:counter64
+--ro in-frame-errors? yang:counter64
+--ro in-fifo-errors? yang:counter64
+--ro in-missed-errors? yang:counter64
+--ro out-aborted-errors? yang:counter64
+--ro out-carrier-errors? yang:counter64
+--ro out-fifo-errors? yang:counter64
+--ro out-heartbeat-errors? yang:counter64
+--ro out-window-errors? yang:counter64
+--ro l2-protocol-pkt-stat* [l2cp-counter-type] {feature-list:HAVE_HAL,feature-list:HAVE_BROADCOM}?
| +--ro lacp-counters? yang:counter64
| +--ro stp-counters? yang:counter64
| +--ro lldp-counters? yang:counter64
| +--ro efmCounters? yang:counter64
| +--ro elmi-counters? yang:counter64
| +--ro dot1x-counters? yang:counter64
| +--ro synce-counters? yang:counter64
| +--ro l2cp-counter-type ipi-if-types:if_l2cp_stats_process_t
+--ro error-disable-reason? ipi-if-types:if_errdisable_state_t

augment /ipi-interface:interfaces/ipi-interface:interface/ipi-if-ethernet:ethernet/ipi-if-ethernet:state/ipi-if-ethernet:counters:
+--ro extended-ethernet-counters {feature-list:HAVE_BROADCOM,feature-list:HAVE_HAL,feature-list:NOT_HAVE_SWFWDR,feature-list:NOT_HAVE_POND}?
+--ro protocol-pkt-stats {feature-list:HAVE_HAL,feature-list:HAVE_BROADCOM}?
| +--ro in-bgp-pkts? yang:counter32
| +--ro in-ospf-pkts? yang:counter32
| +--ro in-isis-pkts? yang:counter32
| +--ro in-ldp-rsvp-pkts? yang:counter32
| +--ro in-arp-pkts? yang:counter32
| +--ro in-evpn-pkts? yang:counter32
| +--ro in-igmp-pkts? yang:counter32
| +--ro in-pim-pkts? yang:counter32
| +--ro in-total-pkts? yang:counter32
+--ro in-good-octets? yang:counter64

```

---

```

+--ro in-bad-octets?      yang:counter64
+--ro mac-transmit-error? yang:counter64
+--ro in-good-pkts?      yang:counter64
+--ro in-bad-pkts?       yang:counter64
+--ro out-good-octets?   yang:counter64
+--ro out-good-pkts?    yang:counter64
+--ro excessive-collisions? yang:counter64
+--ro in-unrecognized-mac-control? yang:counter64
+--ro drop-events?      yang:counter64
+--ro in-mac-errors?     yang:counter64
+--ro in-dribble-errors? yang:counter64
+--ro collisions-state?  yang:counter64
+--ro late-collisions?   yang:counter64
+--ro deferred-tx?       yang:counter64
+--ro mtu-exceed-discards? yang:counter64
+--ro in-jumbo-frames?   yang:counter64
+--ro out-jumbo-frames?  yang:counter64
+--ro receive-pkt-rate?  yang:counter64
+--ro receive-bit-rate?  yang:counter64
+--ro send-pkt-rate?     yang:counter64
+--ro send-bit-rate?     yang:counter64

```

```
augment /ipi-interface:interfaces:
```

```

+--rw global
+--rw error-disable
  +--rw config
    | +--rw reason?          ipi-if-types:if_err_reason_t
    | +--rw error-disable-stp-bpdu-guard? boolean
    | +--rw timeout-interval? uint32 {feature-list:HAVE_L2}?
    | +--rw link-flap-max-count? uint32 {feature-list:HAVE_L2}?
    | +--rw link-flap-timer-interval? uint32 {feature-list:HAVE_L2}?
    | +--rw mac-move-limit? uint32 {feature-list:HAVE_L2}?
    | +--rw storm-control-max-count? uint32 {feature-list:HAVE_RATE_LIMIT}?
    | +--rw storm-control-timer-interval? uint32 {feature-list:HAVE_RATE_LIMIT}?
  +--ro state
    +--ro reason?          ipi-if-types:if_err_reason_t
    +--ro error-disable-stp-bpdu-guard? boolean

```

```

+--ro timeout-interval?      uint32 {feature-list:HAVE_L2}?
+--ro link-flap-max-count?   uint32 {feature-list:HAVE_L2}?
+--ro link-flap-timer-interval? uint32 {feature-list:HAVE_L2}?
+--ro mac-move-limit?       uint32 {feature-list:HAVE_L2}?
+--ro storm-control-max-count? uint32 {feature-list:HAVE_RATE_LIMIT}?
+--ro storm-control-timer-interval? uint32 {feature-list:HAVE_RATE_LIMIT}?

```

augment /ipi-interface:interfaces/ipi-interface:interface:

```

+--rw tunnel {feature-list:HAVE_TUNNEL}?
  +--rw config
    | +--rw mode?          ipi-if-types:if_tunnel_mode_t
    | +--rw src?          inet:ipv4-address
    | +--rw multicast-interface? string {feature-list:HAVE_VXLAN}?
    | +--rw dst?          inet:ipv4-address
    | +--rw checksum-enable? empty
    | +--rw tos-byte?     uint16
    | +--rw ttl?          uint16
    | +--rw path-mtu-enable? empty
    | +--rw dst-mac-address? string {feature-list:HAVE_USER_HSL}?
    | +--rw gre-key?      ipi-if-types:if_tunnel_key_t {feature-list:HAVE_GRE_KEY}?
  +--ro state
    +--ro mode?          ipi-if-types:if_tunnel_mode_t
    +--ro src?          inet:ipv4-address
    +--ro multicast-interface? string {feature-list:HAVE_VXLAN}?
    +--ro dst?          inet:ipv4-address
    +--ro checksum-enable? empty
    +--ro tos-byte?     uint16
    +--ro ttl?          uint16
    +--ro path-mtu-enable? empty
    +--ro dst-mac-address? string {feature-list:HAVE_USER_HSL}?
    +--ro gre-key?      ipi-if-types:if_tunnel_key_t {feature-list:HAVE_GRE_KEY}?

```

rpcs:

```

+---x clear-interface-forward-error-correction-counters
| +---w input
|   +---w if-name string
+---x clear-interface-error-disable

```

---

```
+---w input
  +---w if-name  string
```

notifications:

```
+---n interface-error-disable-notification
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro name?         string
| +--ro error-disable-reason? ipi-if-types:if_errdisable_state_t
+---n interface-bandwidth-start
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro name?         string
| +--ro current-bandwidth? uint64
+---n interface-bandwidth-upgrade
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro name?         string
| +--ro current-bandwidth? uint64
+---n interface-bandwidth-downgrade
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro name?         string
| +--ro current-bandwidth? uint64
+---n interface-bandwidth-close
  +--ro severity?      cml-data-types:cml_notif_severity_t
  +--ro eventClass?   cml-data-types:cml_notif_class_t
  +--ro name?         string
  +--ro current-bandwidth? uint64
```

---

## module: ipi-if-flowspec

augment /ipi-interface:interfaces/ipi-interface:interface:

```
+--rw interface-flowspec
  +--rw ipv4
```

```

+--rw config
| +--rw flowspec-disable? empty
+--ro state
  +--ro flowspec-disable? empty

```

---

## module: ipi-if-ip

```

+--rw ip-global
  +--rw vrf* [vrf-name] {feature-list:HAVE_VRF}?
  | +--rw vrf-name -> ../config/vrf-name
  | +--rw config
  | | +--rw vrf-name? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
  | | +--rw disable-ip-vrf-forwarding? empty
  | | +--rw disable-ipv6-vrf-forwarding? empty {feature-list:HAVE_IPV6}?
  | | +--rw enable-icmp-broadcast? empty
  | +--ro state
  | +--ro vrf-name? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
  | +--ro disable-ip-vrf-forwarding? empty
  | +--ro disable-ipv6-vrf-forwarding? empty {feature-list:HAVE_IPV6}?
  | +--ro enable-icmp-broadcast? empty
  +--rw config
  | +--rw router-id? string
  | +--rw enable-auto-router-id-selection? empty
  | +--rw disable-ip-forwarding? empty
  | +--rw disable-ipv6-forwarding? empty {feature-list:HAVE_IPV6}?
  | +--rw default-vrf-enable-icmp-broadcast? empty
  +--ro state
  +--ro router-id? string
  +--ro enable-auto-router-id-selection? empty
  +--ro disable-ip-forwarding? empty
  +--ro disable-ipv6-forwarding? empty {feature-list:HAVE_IPV6}?
  +--ro default-vrf-enable-icmp-broadcast? empty

```

augment /ipi-interface:interfaces/ipi-interface:interface:

```

+--rw ipv4
  +--rw secondary-addresses* [ip-address]
  | +--rw ip-address -> ../config/ip-address
  | +--rw config
  | | +--rw ip-address?      cml-data-types:cml_ipv4_prefix_t
  | | +--rw ip-label?       cml-data-types:cml_line_t
  | | +--rw secondary-anycast? empty
  | +--ro state
  |   +--ro ip-address?      cml-data-types:cml_ipv4_prefix_t
  |   +--ro ip-label?       cml-data-types:cml_line_t
  |   +--ro secondary-anycast? empty
+--rw config
  | +--rw primary-ip-addr?    cml-data-types:cml_ipv4_prefix_t
  | +--rw enable-dhcp-ip-address? empty {feature-list:HAVE_DHCP_CLIENT}?
  | +--rw prefix-length?     uint8
  | +--rw ip-addr-label?     cml-data-types:cml_line_t
  | +--rw ipv4-unnumbered-if-name? string {feature-list:HAVE_NSM_IF_UNNUMBERED}?
  | +--rw remote-address?    string {feature-list:HAVE_NSM_IF_UNNUMBERED}?
  | +--rw primary-anycast?   empty
+--ro state
  +--ro primary-ip-addr?    cml-data-types:cml_ipv4_prefix_t
  +--ro enable-dhcp-ip-address? empty {feature-list:HAVE_DHCP_CLIENT}?
  +--ro prefix-length?     uint8
  +--ro ip-addr-label?     cml-data-types:cml_line_t
  +--ro ipv4-unnumbered-if-name? string {feature-list:HAVE_NSM_IF_UNNUMBERED}?
  +--ro remote-address?    string {feature-list:HAVE_NSM_IF_UNNUMBERED}?
  +--ro primary-anycast?   empty
  +--ro dhcp-ip-address?    cml-data-types:cml_ipv4_prefix_t {feature-list:HAVE_DHCP_CLIENT}?
  +--ro ipv4-enabled-status? boolean
augment /ipi-interface:interfaces/ipi-interface:interface:
+--rw ipv6 {feature-list:HAVE_IPV6}?
  +--rw addresses* [ipv6-address] {feature-list:HAVE_IPV6}?
  | +--rw ipv6-address -> ../config/ipv6-address
  | +--rw config
  | | +--rw ipv6-address? cml-data-types:cml_ipv6_prefix_t
  | | +--rw anycast?     empty

```

---

```
| +--ro state
|   +--ro ipv6-address?  cml-data-types:cml_ipv6_prefix_t
|   +--ro anycast?      empty
+--rw config
| +--rw ipv6-unnumbered-if-name?      string {feature-list:HAVE_NSM_IF_UNNUMBERED,feature-
list:HAVE_IPV6}?
| +--rw enable-dhcp-ipv6-address?      empty {feature-list:HAVE_DHCP_CLIENT}?
| +--rw enable-dhcp-temporary-ipv6-address?  empty {feature-list:HAVE_DHCP_CLIENT}?
| +--rw dhcp-address-prefix-length?      uint8 {feature-list:HAVE_DHCP_CLIENT}?
| +--rw enable-auto-config?             boolean {feature-list:HAVE_IPV6}?
| +--rw max-autoconfig-address?         uint8
+--ro state
| +--ro ipv6-unnumbered-if-name?        string {feature-list:HAVE_NSM_IF_UNNUMBERED,feature-
list:HAVE_IPV6}?
| +--ro enable-dhcp-ipv6-address?        empty {feature-list:HAVE_DHCP_CLIENT}?
| +--ro enable-dhcp-temporary-ipv6-address?  empty {feature-list:HAVE_DHCP_CLIENT}?
| +--ro dhcp-address-prefix-length?      uint8 {feature-list:HAVE_DHCP_CLIENT}?
| +--ro enable-auto-config?             boolean {feature-list:HAVE_IPV6}?
| +--ro max-autoconfig-address?         uint8
| +--ro dhcp-ipv6-address?              cml-data-types:cml_ipv6_prefix_t {feature-list:HAVE_DHCP_CLIENT}?
| +--ro forwarding-status?              boolean {feature-list:HAVE_IPV6}?
+--ro auto-addresses {feature-list:HAVE_IPV6}?
  +--ro auto-address* [ipv6-address]
    +--ro ipv6-address  -> ../state/ipv6-address
  +--ro state
    +--ro ipv6-address?  cml-data-types:cml_ipv6_prefix_t
    +--ro anycast?      empty
    +--ro virtual?      empty
    +--ro vrrp?         empty {feature-list:HAVE_VRRP_V3}?
```

---

## module: ipi-igmp-snooping

```

+--rw igmp-snooping
  +--rw global
    | +--rw config
    | | +--rw disable-igmp-snooping?    empty
    | | +--rw disable-report-suppression? empty
    | | +--rw unknown-multicast-action? ipi-igmp-snooping-types:igmp_snoop_unknown_mcast_action_t
    | +--ro state
    | +--ro disable-igmp-snooping?    empty
    | +--ro disable-report-suppression? empty
    | +--ro unknown-multicast-action? ipi-igmp-snooping-types:igmp_snoop_unknown_mcast_action_t
  +--rw debug
    | +--rw config
    | | +--rw options? ipi-igmp-snooping-types:igmp_snoop_debug_options_t
    | +--ro state
    | +--ro options?          ipi-igmp-snooping-types:igmp_snoop_debug_options_t
    | +--ro terminal-debug-status? ipi-igmp-snooping-types:igmp_snoop_debug_options_t
  +--rw interfaces
    +--rw interface* [name]
      +--rw name          -> ../config/name
      +--rw config
        | +--rw name?          -> /ipi-interface:interfaces/interface/name
        | +--rw igmp-snooping?    cml-data-types:cml_enable_disable_t
        | +--rw enable-fast-leave? empty
        | +--rw report-suppression? cml-data-types:cml_enable_disable_t
        | +--rw mrouter-interface-name* -> /ipi-interface:interfaces/interface/name
        | +--rw enable-querier?    empty
      +--ro state
        | +--ro name?          -> /ipi-interface:interfaces/interface/name
        | +--ro igmp-snooping?    cml-data-types:cml_enable_disable_t
        | +--ro enable-fast-leave? empty
        | +--ro report-suppression? cml-data-types:cml_enable_disable_t
        | +--ro mrouter-interface-name* -> /ipi-interface:interfaces/interface/name
        | +--ro enable-querier?    empty
      +--rw static-groups

```

```

+--rw ssm-groups
| +--rw ssm-group* [group-address source-address interface-name]
|   +--rw group-address   -> ../config/group-address
|   +--rw source-address  -> ../config/source-address
|   +--rw interface-name  -> ../config/interface-name
|   +--rw config
|     | +--rw group-address?  inet:ipv4-address
|     | +--rw interface-name? string
|     | +--rw source-address? inet:ipv4-address
|     +--ro state
|       +--ro group-address?  inet:ipv4-address
|       +--ro interface-name? string
|       +--ro source-address? inet:ipv4-address
+--rw asm-groups
+--rw asm-group* [group-address interface-name]
  +--rw group-address   -> ../config/group-address
  +--rw interface-name  -> ../config/interface-name
  +--rw config
  | +--rw group-address?  inet:ipv4-address
  | +--rw interface-name? string
  +--ro state
    +--ro group-address?  inet:ipv4-address
    +--ro interface-name? string

```

rpcs:

```

+---x igmp-snooping-clear-group-interface {feature-list:HAVE_L2MRIBD}?
| +---w input
|   +---w group-address  inet:ipv4-address
|   +---w interface-name string
+---x igmp-snooping-clear-interface {feature-list:HAVE_L2MRIBD}?
| +---w input
|   +---w interface-name string
+---x igmp-snooping-clear-all {feature-list:HAVE_L2MRIBD}?
+---x igmp-snooping-clear-group {feature-list:HAVE_L2MRIBD}?
| +---w input
|   +---w group-address  inet:ipv4-address

```

```

+---x igmp-snooping-terminal-debug-on {feature-list:HAVE_L2MRIBD}?
| +---w input
|   +---w terminal-debug-options   ipi-igmp-snooping-types:igmp_snoop_debug_options_t
+---x igmp-snooping-terminal-debug-off {feature-list:HAVE_L2MRIBD}?
  +---w input
    +---w terminal-debug-options   ipi-igmp-snooping-types:igmp_snoop_debug_options_t

```

---

## module: ipi-igmp

```

+--rw igmp
  +--rw vrfs
    | +--rw vrf* [vrf-name]
    |   +--rw vrf-name          -> ../config/vrf-name
    |   +--rw config
    |     | +--rw vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
    |     | +--rw disable-ssm-map?  empty
    |     | +--rw disable-tos-check? empty
    |     +--ro state
    |       | +--ro vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
    |       | +--ro disable-ssm-map?  empty
    |       | +--ro disable-tos-check? empty
    |       +--rw group-membership-control
    |         | +--rw config
    |         | | +--rw member-limit?    uint32
    |         | | +--rw limit-exception-acl? string
    |         | | +--ro state
    |         | |   +--ro member-limit?    uint32
    |         | |   +--ro limit-exception-acl? string
    |         | |   +--ro current-states-count? uint32
    |         +--rw ssm
    |           | +--rw static-mappings
    |           | | +--rw static-mapping* [group-ranges-acl source]
    |           | |   +--rw group-ranges-acl -> ../config/group-ranges-acl
    |           | |   +--rw source          -> ../config/source
    |           | |   +--rw config

```

---

```
| | | +--rw group-ranges-acl? string
| | | +--rw source?          inet:ipv4-address
| |   +--ro state
| |     +--ro group-ranges-acl? string
| |     +--ro source?          inet:ipv4-address
| +--rw debug
|   +--rw config
|     +--rw options? ipi-igmp-types:igmp_debug_options_t
|     +--ro state
|       +--ro options?          ipi-igmp-types:igmp_debug_options_t
|       +--ro terminal-debug-status? ipi-igmp-types:igmp_debug_options_t
+--rw interfaces
| +--rw interface* [name]
|   +--rw name          -> ../config/name
|   +--rw config
|     +--rw name?          -> /ipi-interface:interfaces/interface/name
|     +--rw enabled?      empty
|     +--rw last-member-query-count? uint8
|     +--rw last-member-query-interval? uint16
|     +--rw querier-timeout? uint16
|     +--rw query-interval? uint16
|     +--rw query-max-response-time? uint8
|     +--rw startup-query-interval? uint16
|     +--rw startup-query-count? uint8
|     +--rw robustness-variable? uint8
|     +--rw version?      uint8
|     +--rw require-router-alert-option? empty
|     +--rw allow-offlink-host? empty
|     +--ro state
|     +--ro counters
|       +--ro v1-reports-received? yang:counter32
|       +--ro v2-reports-received? yang:counter32
|       +--ro v2-leaves-received? yang:counter32
|       +--ro v3-reports-received? yang:counter32
|       +--ro current-group-records? yang:counter32
|     +--ro internet-address? inet:ipv4-address
```

---

```

| | +--ro oper-status?          ipi-igmp-types:igmp_if_oper_status_t
| | +--ro host-version?         uint8
| | +--ro is-querier?          boolean
| | +--ro querying-router?     inet:ipv4-address
| | +--ro group-membership-interval?  uint32
| | +--ro name?                -> /ipi-interface:interfaces/interface/name
| | +--ro enabled?             empty
| | +--ro last-member-query-count?  uint8
| | +--ro last-member-query-interval? uint16
| | +--ro querier-timeout?       uint16
| | +--ro query-interval?       uint16
| | +--ro query-max-response-time?  uint8
| | +--ro startup-query-interval?  uint16
| | +--ro startup-query-count?     uint8
| | +--ro robustness-variable?    uint8
| | +--ro version?              uint8
| | +--ro require-router-alert-option? empty
| | +--ro allow-offlink-host?     empty
| +--rw proxy
| | +--rw config
| | | +--rw enable-proxy-service?  empty
| | | +--rw mroute-proxy-interface? string
| | | +--rw unsolicited-report-interval? uint16
| | +--ro state
| |   +--ro enable-proxy-service?  empty
| |   +--ro mroute-proxy-interface? string
| |   +--ro unsolicited-report-interval? uint16
| |   +--ro oper-status?          ipi-igmp-types:igmp_proxy_if_oper_status_t
| +--rw group-membership-control
| | +--rw config
| | | +--rw access-group-name?     string
| | | +--rw immediate-leave-groups-list? string
| | | +--rw member-limit?         uint32
| | | +--rw limit-exception-acl?   string
| | +--ro state
| |   +--ro access-group-name?     string

```

---

---

```
| | +--ro immediate-leave-groups-list? string
| | +--ro member-limit?          uint32
| | +--ro limit-exception-acl?   string
| +--rw asm-static-groups
| | +--rw asm-static-group* [group-address]
| |   +--rw group-address  -> ../config/group-address
| |   +--rw config
| |     | +--rw group-address? inet:ipv4-address
| |     +--ro state
| |       +--ro group-address? inet:ipv4-address
| +--rw ssm-static-groups
| | +--rw ssm-static-group* [group-address source]
| |   +--rw group-address  -> ../config/group-address
| |   +--rw source         -> ../config/source
| |   +--rw config
| |     | +--rw group-address? inet:ipv4-address
| |     | +--rw source?       ipi-igmp-types:igmp_static_ssm_source_t
| |     +--ro state
| |       +--ro group-address? inet:ipv4-address
| |       +--ro source?       ipi-igmp-types:igmp_static_ssm_source_t
| +--rw asm-join-groups
| | +--rw asm-join-group* [group-address]
| |   +--rw group-address  -> ../config/group-address
| |   +--rw config
| |     | +--rw group-address? inet:ipv4-address
| |     +--ro state
| |       +--ro group-address? inet:ipv4-address
| +--rw ssm-join-groups
| | +--rw ssm-join-group* [group-address source]
| |   +--rw group-address  -> ../config/group-address
| |   +--rw source         -> ../config/source
| |   +--rw config
| |     | +--rw group-address? inet:ipv4-address
| |     | +--rw source?       inet:ipv4-address
| |     +--ro state
| |       +--ro group-address? inet:ipv4-address
```

---

```
|      +--ro source?      inet:ipv4-address
+--ro group-membership-tree
  +--ro igmp-instances
    +--ro igmp-instance* [vrf-name]
      +--ro vrf-name      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
      +--ro interfaces
        +--ro interface* [if-name]
          +--ro if-name    -> /ipi-interface:interfaces/interface/name
          +--ro member-groups
            | +--ro member-group* [group-address]
            | +--ro group-address  -> ../state/group-address
            | +--ro state
            | | +--ro group-address?  inet:ipv4-address
            | | +--ro dynamic-remote? empty
            | | +--ro static-group?   empty
            | | +--ro local?          empty
            | | +--ro ssm-mapped?     empty
            | | +--ro static-source?   empty
            | | +--ro up-time?        string
            | | +--ro group-mode?     ipi-igmp-types:igmp_ssm_group_mode_t
            | | +--ro expiry?        string
            | | +--ro last-reporter?  inet:ipv4-address
            | +--ro include-sources
            | | +--ro include-source* [source-address]
            | | +--ro source-address  -> ../state/source-address
            | | +--ro state
            | | +--ro source-address? inet:ipv4-address
            | | +--ro dynamic-remote? empty
            | | +--ro static-source?   empty
            | | +--ro local?          empty
            | | +--ro ssm-mapped?     empty
            | | +--ro up-time?        string
            | | +--ro expiry?        string
            | | +--ro is-forwarded?   ipi-igmp-types:igmp_yes_no_t
            | +--ro exclude-sources
            | +--ro exclude-source* [source-address]
```

---

```

|     +--ro source-address  -> ../state/source-address
|     +--ro state
|         +--ro source-address?  inet:ipv4-address
|         +--ro dynamic-remote?  empty
|         +--ro static-source?   empty
|         +--ro local?           empty
|         +--ro ssm-mapped?      empty
|         +--ro up-time?         string
|         +--ro expiry?          string
|         +--ro is-forwarded?    ipi-igmp-types:igmp_yes_no_t
+--ro proxy-groups
    +--ro proxy-group* [group-address]
        +--ro group-address  -> ../state/group-address
        +--ro state
            +--ro group-address?  inet:ipv4-address
            +--ro proxy-interface? string
            +--ro group-mode?     ipi-igmp-types:igmp_ssm_group_mode_t
            +--ro state?         ipi-igmp-types:igmp_if_state_t
            +--ro membership-state? ipi-igmp-types:igmp_proxy_grp_membership_state_t
            +--ro multicast-sources* inet:ipv4-address

```

rpcs:

```

+---x igmp-terminal-debug-on {feature-list:HAVE_MRIBD}?
| +---w input
|   +---w vrf-name?          string
|   +---w terminal-debug-options ipi-igmp-types:igmp_debug_options_t
+---x igmp-terminal-debug-off {feature-list:HAVE_MRIBD}?
| +---w input
|   +---w vrf-name?          string
|   +---w terminal-debug-options ipi-igmp-types:igmp_debug_options_t
+---x igmp-clear-all-groups {feature-list:HAVE_MRIBD}?
| +---w input
|   +---w vrf-name?  string
|   +---w clear-all  empty
+---x igmp-clear-group-on-interface {feature-list:HAVE_MRIBD}?
| +---w input

```

```

| +---w vrf-name?    string
| +---w group-address inet:ipv4-address
| +---w if-name      string
+---x igmp-clear-all-groups-on-interface {feature-list:HAVE_MRIBD}?
| +---w input
|   +---w vrf-name? string
|   +---w if-name   string
+---x igmp-clear-group {feature-list:HAVE_MRIBD}?
  +---w input
    +---w vrf-name?  string
    +---w group-address inet:ipv4-address

```

---

## module: ipi-igp-te

```

+--rw igp-te
  +--rw interfaces
    +--rw interface* [name]
      +--rw name      -> ../config/name
      +--rw config
        | +--rw name? -> /ipi-interface:interfaces/interface/name
        +--ro state
        | +--ro name? -> /ipi-interface:interfaces/interface/name
      +--rw uni-link
        +--rw config
          | +--rw delay?          uint32
          | +--rw delay-variation? uint32
          | +--rw loss-percentage? decimal64
        +--ro state
          | +--ro delay?          uint32
          | +--ro delay-variation? uint32
          | +--ro loss-percentage? decimal64
        +--rw twamp-loss-parameter {feature-list:HAVE_TWAMP}?
          | +--rw config
          | | +--rw loss-dynamic? empty
          | +--ro state
          | | +--ro loss-dynamic? empty

```

```

+--rw irb-twamp-loss-parameter {feature-list:HAVE_TWAMP}?
| +--rw config
| | +--rw loss-dynamic? empty
| | +--ro state
| |   +--ro loss-dynamic? empty
+--rw twamp-session-parameters {feature-list:HAVE_TWAMP}?
| +--rw twamp-session-parameter* [delay-dynamic-twamp reflector-ip]
| | +--rw delay-dynamic-twamp -> ../config/delay-dynamic-twamp
| | +--rw reflector-ip -> ../config/reflector-ip
| | +--rw config
| | | +--rw delay-dynamic-twamp? empty
| | | +--rw reflector-ip? cml-data-types:cml_hostname_t
| | | +--rw reflector-port? uint16
| | | +--rw sender-ip? cml-data-types:cml_hostname_t
| | | +--rw sender-port? uint16
| | | +--rw dscp? string
| | +--ro state
| | | +--ro delay-dynamic-twamp? empty
| | | +--ro reflector-ip? cml-data-types:cml_hostname_t
| | | +--ro reflector-port? uint16
| | | +--ro sender-ip? cml-data-types:cml_hostname_t
| | | +--ro sender-port? uint16
| | | +--ro dscp? string
| | +--ro statistics
| |   +--ro state
| |     +--ro last-advertised-calculation-time? yang:date-and-time
| |     +--ro last-advertised-minimum-delay? uint64
| |     +--ro last-advertised-maximum-delay? uint64
| |     +--ro last-advertised-average-delay? uint64
| |     +--ro last-advertised-minimum-delay-variation? uint64
| |     +--ro last-advertised-maximum-delay-variation? uint64
| |     +--ro last-advertised-average-delay-variation? uint64
| |     +--ro last-advertised-packets-sent? yang:counter64
| |     +--ro last-advertised-packets-received? yang:counter64
| |     +--ro last-advertised-packets-timeout? yang:counter64
| |     +--ro last-advertised-packet-loss? decimal64

```

---

```
| |   +--ro last-calculated-calculation-time?   yang:date-and-time
| |   +--ro last-calculated-minimum-delay?     uint64
| |   +--ro last-calculated-maximum-delay?    uint64
| |   +--ro last-calculated-average-delay?    uint64
| |   +--ro last-calculated-minimum-delay-variation? uint64
| |   +--ro last-calculated-maximum-delay-variation? uint64
| |   +--ro last-calculated-average-delay-variation? uint64
| |   +--ro last-calculated-packets-sent?     yang:counter64
| |   +--ro last-calculated-packets-received? yang:counter64
| |   +--ro last-calculated-packets-timeout?  yang:counter64
| |   +--ro last-calculated-packet-loss?     decimal64
| +--rw irb-twamp-session-parameter* [delay-dynamic-twamp reflector-ip]
|   +--rw delay-dynamic-twamp  -> ../config/delay-dynamic-twamp
|   +--rw reflector-ip        -> ../config/reflector-ip
|   +--rw config
|     | +--rw delay-dynamic-twamp? empty
|     | | +--rw reflector-ip?      cml-data-types:cml_hostpname_t
|     | | +--rw reflector-port?   uint16
|     | | +--rw sender-ip?       cml-data-types:cml_hostpname_t
|     | | +--rw sender-port?     uint16
|     | | +--rw dscp?            string
|     +--ro state
|     | +--ro delay-dynamic-twamp? empty
|     | | +--ro reflector-ip?     cml-data-types:cml_hostpname_t
|     | | +--ro reflector-port?   uint16
|     | | +--ro sender-ip?       cml-data-types:cml_hostpname_t
|     | | +--ro sender-port?     uint16
|     | | +--ro dscp?            string
|     +--ro statistics
|       +--ro state
|         +--ro last-advertised-calculation-time?   yang:date-and-time
|         +--ro last-advertised-minimum-delay?     uint64
|         +--ro last-advertised-maximum-delay?    uint64
|         +--ro last-advertised-average-delay?    uint64
|         +--ro last-advertised-minimum-delay-variation? uint64
|         +--ro last-advertised-maximum-delay-variation? uint64
```

---

```
|   +--ro last-advertised-average-delay-variation? uint64
|   +--ro last-advertised-packets-sent?          yang:counter64
|   +--ro last-advertised-packets-received?     yang:counter64
|   +--ro last-advertised-packets-timeout?      yang:counter64
|   +--ro last-advertised-packet-loss?          decimal64
|   +--ro last-calculated-calculation-time?     yang:date-and-time
|   +--ro last-calculated-minimum-delay?        uint64
|   +--ro last-calculated-maximum-delay?        uint64
|   +--ro last-calculated-average-delay?        uint64
|   +--ro last-calculated-minimum-delay-variation? uint64
|   +--ro last-calculated-maximum-delay-variation? uint64
|   +--ro last-calculated-average-delay-variation? uint64
|   +--ro last-calculated-packets-sent?          yang:counter64
|   +--ro last-calculated-packets-received?     yang:counter64
|   +--ro last-calculated-packets-timeout?      yang:counter64
|   +--ro last-calculated-packet-loss?          decimal64
+--rw delay-threshold
| +--rw a-bit* [a-bit-min a-bit-max]
|   +--rw a-bit-min  -> ../config/a-bit-min
|   +--rw a-bit-max  -> ../config/a-bit-max
|   +--rw config
|     | +--rw a-bit-min? uint32
|     | +--rw a-bit-max? uint32
|     +--ro state
|       +--ro a-bit-min? uint32
|       +--ro a-bit-max? uint32
+--rw min-max-delay
| +--rw delay* [min-value max-value]
|   +--rw min-value  -> ../config/min-value
|   +--rw max-value  -> ../config/max-value
|   +--rw config
|     | +--rw min-value? uint32
|     | +--rw max-value? uint32
|     +--ro state
|       +--ro min-value? uint32
|       +--ro max-value? uint32
```

```

+--rw loss
| +--rw threshold* [loss-a-bit-min loss-a-bit-max]
|   +--rw loss-a-bit-min  -> ../config/loss-a-bit-min
|   +--rw loss-a-bit-max  -> ../config/loss-a-bit-max
|   +--rw config
|     | +--rw loss-a-bit-min?  decimal64
|     | +--rw loss-a-bit-max?  decimal64
|     +--ro state
|       +--ro loss-a-bit-min?  decimal64
|       +--ro loss-a-bit-max?  decimal64
+--rw min-max-delay-threshold
+--rw a-bit* [a-bit-min-range-minimum a-bit-min-range-maximum a-bit-max-range-minimum a-bit-max-range-
maximum]
+--rw a-bit-min-range-minimum  -> ../config/a-bit-min-range-minimum
+--rw a-bit-min-range-maximum  -> ../config/a-bit-min-range-maximum
+--rw a-bit-max-range-minimum  -> ../config/a-bit-max-range-minimum
+--rw a-bit-max-range-maximum  -> ../config/a-bit-max-range-maximum
+--rw config
| +--rw a-bit-min-range-minimum?  uint32
| +--rw a-bit-min-range-maximum?  uint32
| +--rw a-bit-max-range-minimum?  uint32
| +--rw a-bit-max-range-maximum?  uint32
+--ro state
+--ro a-bit-min-range-minimum?  uint32
+--ro a-bit-min-range-maximum?  uint32
+--ro a-bit-max-range-minimum?  uint32
+--ro a-bit-max-range-maximum?  uint32

```

rpcs:

```

+---x twamp-clear-measurement-intf {feature-list:HAVE_TWAMP}?
| +---w input
|   +---w interface-name  string
+---x twamp-clear-measurement-all {feature-list:HAVE_TWAMP}?

```

notifications:

```

+---n delay-measurement-status {feature-list:HAVE_TWAMP}?
+--ro severity?  cml-data-types:cml_notif_severity_t

```

```

+--ro eventClass?  cml-data-types:cml_notif_class_t
+--ro message?    string

```

---

## module: ipi-interface

```

+--rw interfaces
  +--rw interface* [name]
    +--rw name          -> ../config/name
    +--rw config
      | +--rw name?      string
      | +--rw enable-switchport? empty
      | +--rw vrf-name?  -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
      {feature-list:HAVE_VRF}?
      | +--rw vr-name?   string {feature-list:HAVE_VR}?
      | +--rw type?     ipi-if-types:if_iana_if_type_t
      | +--rw mtu?      uint32
      | +--rw allow-first-frame? empty {feature-list:NOT_HAVE_DUNE}?
      | +--rw dot1ad-ether-type? string {feature-list:HAVE_VLAN_STACK,feature-list:NOT_HAVE_SWFWDR}?
      | +--rw description? cml-data-types:cml_line_t
      | +--rw shutdown?   empty
    +--ro state
      | +--ro name?      string
      | +--ro enable-switchport? empty
      | +--ro vrf-name?  -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
      {feature-list:HAVE_VRF}?
      | +--ro vr-name?   string {feature-list:HAVE_VR}?
      | +--ro type?     ipi-if-types:if_iana_if_type_t
      | +--ro mtu?      uint32
      | +--ro allow-first-frame? empty {feature-list:NOT_HAVE_DUNE}?
      | +--ro dot1ad-ether-type? string {feature-list:HAVE_VLAN_STACK,feature-list:NOT_HAVE_SWFWDR}?
      | +--ro description? cml-data-types:cml_line_t
      | +--ro shutdown?   empty
      | +--ro ifindex?   uint32
      | +--ro admin-status? ipi-if-types:if_interface_admin_status_t
      | +--ro oper-status? ipi-if-types:if_interface_oper_status_t
      | +--ro last-change? yang:timeticks

```

---

```

| +--ro logical?      boolean
| +--ro counters
|   +--ro in-octets?  yang:counter64
|   +--ro in-pkts?    yang:counter64
|   +--ro in-unicast-pkts? yang:counter64 {feature-list:HAVE_BROADCOM,feature-list:HAVE_HAL,feature-
list:NOT_HAVE_SWFWDR}?
|   +--ro in-broadcast-pkts? yang:counter64 {feature-list:HAVE_BROADCOM,feature-list:HAVE_HAL,feature-
list:NOT_HAVE_SWFWDR}?
|   +--ro in-multicast-pkts? yang:counter64
|   +--ro in-discards?  yang:counter64
|   +--ro in-errors?    yang:counter64
|   +--ro in-fcs-errors? yang:counter64 {feature-list:HAVE_BROADCOM,feature-list:HAVE_HAL,feature-
list:NOT_HAVE_SWFWDR}?
|   +--ro out-octets?   yang:counter64
|   +--ro out-pkts?     yang:counter64
|   +--ro out-unicast-pkts? yang:counter64 {feature-list:HAVE_BROADCOM,feature-list:HAVE_HAL,feature-
list:NOT_HAVE_SWFWDR}?
|   +--ro out-broadcast-pkts? yang:counter64 {feature-list:HAVE_BROADCOM,feature-list:HAVE_HAL,feature-
list:NOT_HAVE_SWFWDR}?
|   +--ro out-multicast-pkts? yang:counter64 {feature-list:HAVE_BROADCOM,feature-list:HAVE_HAL,feature-
list:NOT_HAVE_SWFWDR}?
|   +--ro out-discards? yang:counter64
|   +--ro out-errors?   yang:counter64
|   +--ro last-clear?   ipi-if-types:if_last_clear_time_t
+--rw interface-loopback
+--rw config!
| +--rw if-loopback      ipi-if-types:if_loopback_dir_type_t
| +--rw if-loopback-level ipi-if-types:if_loopback_type_t
+--ro state
+--ro if-loopback      ipi-if-types:if_loopback_dir_type_t
+--ro if-loopback-level ipi-if-types:if_loopback_type_t

```

rpcs:

```

+---x clear-interface-counters
+---w input
+---w name  string

```

notifications:

```

+---n interface-link-state-change-notification
  +--ro severity?   cml-data-types:cml_notif_severity_t
  +--ro eventClass? cml-data-types:cml_notif_class_t
  +--ro name?       string
  +--ro oper-status? ipi-if-types:if_interface_oper_status_t

```

---

## module: ipi-ip-sla

```

+--rw ip-sla
  +--rw processes
    | +--rw process* [identifier]
    |   +--rw identifier      -> ../config/identifier
    |   +--rw config
    |     | +--rw identifier?  uint16
    |     | +--ro state
    |     | | +--ro identifier? uint16
    |     | +--ro ip-sla-statistics
    |     | | +--ro state
    |     | |   +--ro start-time?      yang:date-and-time
    |     | |   +--ro elapsed-time?    uint64
    |     | |   +--ro packets-sent?    uint32
    |     | |   +--ro packets-received? uint32
    |     | |   +--ro packets-lost?    decimal64
    |     | |   +--ro invalid-tests?   uint32
    |     | |   +--ro minimum-round-trip-delay? uint64
    |     | |   +--ro maximum-round-trip-delay? uint64
    |     | |   +--ro average-round-trip-delay? uint64
    |     +--rw icmp-echo-processes
    |       +--rw icmp-echo-process* [host]
    |         +--rw host      -> ../config/host
    |         +--rw config
    |           | +--rw host?        ip_sla_hostname_t
    |           | +--rw source-interface? string
    |           | +--rw frequency?   uint8
    |           | +--rw timeout?     uint16
    |           | +--rw threshold?   uint16

```

---

```
|     +--ro state
|     +--ro host?      ip_sla_hostname_t
|     +--ro source-interface? string
|     +--ro frequency?  uint8
|     +--ro timeout?   uint16
|     +--ro threshold?  uint16
+--rw scheduled-processes
  +--rw scheduled-process* [scheduled-pid time-range-name]
    +--rw scheduled-pid   -> ../config/scheduled-pid
    +--rw time-range-name -> ../config/time-range-name
    +--rw config
      | +--rw scheduled-pid?  uint16
      | +--rw time-range-name? string
      | +--rw vrf-name?      string
      +--ro state
        +--ro scheduled-pid?  uint16
        +--ro time-range-name? string
        +--ro vrf-name?      string

rpcs:
+---x ip-sla-clear-statistics {feature-list:HAVE_IPSLA,feature-list:HAVE_BFD}?
  +---w input
    +---w identifier  uint16

notifications:
+---n icmp-echo-threshold {feature-list:HAVE_IPSLA}?
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro host?      ip_sla_hostname_t
| +--ro identifier? uint16
| +--ro threshold? uint16
+---n icmp-echo-timeout {feature-list:HAVE_IPSLA}?
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro host?      ip_sla_hostname_t
| +--ro identifier? uint16
```

```

| +--ro timeout?   uint16
+---n icmp-echo-disconnect {feature-list:HAVE_IPSLA}?
  +--ro severity?  cml-data-types:cml_notif_severity_t
  +--ro eventClass? cml-data-types:cml_notif_class_t
  +--ro identifier? uint16

```

---

## module: ipi-ipsec

```

+--rw ipsec {feature-list:HAVE_IPSEC}?
  +--rw transform-sets
    | +--rw transform-set* [transform-set-name]
    |   +--rw transform-set-name  -> ../config/transform-set-name
    |   +--rw config
    |     | +--rw transform-set-name?  string
    |     | +--rw transform-set-mode?  ipi-ipsec-types:ipsec_ts_mode_t
    |     +--ro state
    |       | +--ro transform-set-name?  string
    |       | +--ro transform-set-mode?  ipi-ipsec-types:ipsec_ts_mode_t
    |       | +--ro transform-set-protocol? ipi-ipsec-types:ipsec_ts_protocol_t
    |       +--rw ah-auth
    |         | +--rw config
    |         | | +--rw ah-authentication? ipi-ipsec-types:ipsec_ah_authentication_t
    |         | | +--ro state
    |         | | +--ro ah-authentication? ipi-ipsec-types:ipsec_ah_authentication_t
    |         +--rw esp-auth
    |           +--rw config!
    |             | +--rw esp-authentication ipi-ipsec-types:ipsec_esp_authentication_t
    |             | +--rw esp-encryption   ipi-ipsec-types:ipsec_esp_encryption_t
    |             +--ro state
    |               +--ro esp-authentication ipi-ipsec-types:ipsec_esp_authentication_t
    |               +--ro esp-encryption   ipi-ipsec-types:ipsec_esp_encryption_t
  +--rw crypto-maps
    +--rw crypto-map* [name]
      +--rw name      -> ../config/name

```

```
+--rw config
| +--rw name?   string
| +--rw sa-type ipi-ipsec-types:ipsec_sa_type_t
+--ro state
| +--ro name?   string
| +--ro sa-type ipi-ipsec-types:ipsec_sa_type_t
+--rw sessions
  +--rw session* [sequence-id]
    +--rw sequence-id  -> ../config/sequence-id
    +--rw config
      | +--rw sequence-id? uint16
      +--ro state
        | +--ro sequence-id? uint16
      +--rw transform-sets
        | +--rw transform-set* [transform-set-name]
        |   +--rw transform-set-name  -> ../config/transform-set-name
        |   +--rw config
        |     | +--rw transform-set-name? -> /ipsec/transform-sets/transform-set/transform-set-name
        |     | +--ro state
        |     |   +--ro transform-set-name? -> /ipsec/transform-sets/transform-set/transform-set-name
        +--rw peer-addresses
          | +--rw peer-address* [peer]
          |   +--rw peer  -> ../config/peer
          |   +--rw config
          |     | +--rw peer?  inet:ip-address
          |     | +--rw spi    ipi-ipsec-types:ipsec_peer_spi_t
          |     | +--ro state
          |     |   +--ro peer?  inet:ip-address
          |     |   +--ro spi    ipi-ipsec-types:ipsec_peer_spi_t
          +--rw session-keys
            +--rw session-key* [direction protocol security-parameter-index]
              +--rw direction          -> ../config/direction
              +--rw protocol            -> ../config/protocol
              +--rw security-parameter-index  -> ../config/security-parameter-index
              +--rw config
                | +--rw direction?          ipi-ipsec-types:ipsec_session_key_direction_t
```

```

| +--rw protocol?          ipi-ipsec-types:ipsec_session_key_protocol_t
| +--rw security-parameter-index? uint16
| +--rw cipher             string
| +--rw authentication-key  string
+--ro state
  +--ro direction?        ipi-ipsec-types:ipsec_session_key_direction_t
  +--ro protocol?         ipi-ipsec-types:ipsec_session_key_protocol_t
  +--ro security-parameter-index? uint16
  +--ro cipher            string
  +--ro authentication-key  string

```

---

## module: ipi-ipv6-router-adv

```

+--rw router-advertisement {feature-list:HAVE_RTADV}?
  +--rw interfaces
    +--rw interface* [name]
      +--rw name          -> ../config/name
      +--rw config
        | +--rw name?      -> /ipi-interface:interfaces/interface/name
        | +--rw suppress-ra?  empty
        | +--rw suppress-ra-mtu?  empty
        | +--rw managed-flag?  empty
        | +--rw other-config-flag? empty
        | +--rw current-hop-limit? uint8
        | +--rw link-mtu?     uint32
        | +--rw dad-attempts?  uint16
        +--ro state
          | +--ro name?      -> /ipi-interface:interfaces/interface/name
          | +--ro suppress-ra?  empty
          | +--ro suppress-ra-mtu?  empty
          | +--ro managed-flag?  empty
          | +--ro other-config-flag? empty
          | +--ro current-hop-limit? uint8
          | +--ro link-mtu?     uint32
          | +--ro dad-attempts?  uint16
          +--rw ipv6-prefixes

```

---

```
| +--rw config
| | +--rw off-link?          empty
| | +--rw no-auto-configuration?  empty
| | +--rw valid-lifetime?      uint32
| | +--rw preferred-lifetime?   uint32
| +--ro state
| | +--ro off-link?          empty
| | +--ro no-auto-configuration?  empty
| | +--ro valid-lifetime?      uint32
| | +--ro preferred-lifetime?   uint32
| +--rw ipv6-prefix* [ipv6-address]
|   +--rw ipv6-address  -> ../config/ipv6-address
|   +--rw config
|     | +--rw ipv6-address?      cml-data-types:cml_ipv6_prefix_t
|     | +--rw valid-lifetime?   uint32
|     | +--rw preferred-lifetime? uint32
|     | +--rw off-link?        empty
|     | +--rw no-auto-configuration?  empty
|     +--ro state
|       +--ro ipv6-address?      cml-data-types:cml_ipv6_prefix_t
|       +--ro valid-lifetime?   uint32
|       +--ro preferred-lifetime? uint32
|       +--ro off-link?        empty
|       +--ro no-auto-configuration?  empty
+--rw timers
  +--rw config
  | +--rw reachable-time?      uint32
  | +--rw retransmission-time? uint32
  | +--rw router-lifetime?    uint16
  +--ro state
  | +--ro reachable-time?      uint32
  | +--ro retransmission-time? uint32
  | +--ro router-lifetime?    uint16
  | +--ro random-interval?    uint32
  | +--ro time-remaining?     uint32
  +--rw ra-interval
```

```
+--rw config!  
| +--rw max-ra-interval uint32  
| +--rw min-ra-interval uint32  
+--ro state  
  +--ro max-ra-interval uint32  
  +--ro min-ra-interval uint32
```

---

## module: ipi-isis

```
+--rw isis  
  +--rw isis-instances  
  | +--rw isis-instance* [instance]  
  |   +--rw instance          -> ../config/instance  
  |   +--ro ipv4-route* [destination-prefix]  
  |   | +--ro destination-prefix -> ../state/destination-prefix  
  |   | +--ro nexthop* [nexthop-ip]  
  |   | | +--ro nexthop-ip -> ../state/nexthop-ip  
  |   | | +--ro state  
  |   | |   +--ro nexthop-ip?      inet:ipv4-address  
  |   | |   +--ro outgoing-interface? string  
  |   | |   +--ro redistribute-map-tag? uint32  
  |   | |   +--ro source-identifier? string  
  |   | +--ro state  
  |   |   +--ro destination-prefix?      cml-data-types:cml_ipv4_addr_prefix_t  
  |   |   +--ro destination-path-metric? uint32  
  |   |   +--ro destination-path-type?   string
```

```

| | +--ro is-destination-path-type-external? boolean
| +--ro ipv6-route* [destination-prefix]
| | +--ro destination-prefix -> ../state/destination-prefix
| | +--ro nexthop* [nexthop-ip]
| | | +--ro nexthop-ip -> ../state/nexthop-ip
| | | +--ro state
| | | | +--ro nexthop-ip?          inet:ipv6-address
| | | | +--ro outgoing-interface? string
| | | | +--ro redistribute-map-tag? uint32
| | +--ro state
| | +--ro destination-prefix?      cml-data-types:cml_ipv6_prefix_t
| | +--ro destination-path-metric? uint32
| | +--ro destination-path-type?   string
| | +--ro is-destination-path-type-external? boolean
| +--rw config
| | +--rw instance?                string
| | +--rw distance?                uint8
| | +--rw vrf-name                 -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
| | +--rw dynamic-host-name?      ipi-isis-types:isis_dynamic_hostanme_t
| | +--rw disable-adjacency-check? empty
| | +--rw ignore-lsp-errors?       empty
| | +--rw lfa-hold-timer?          int32 {feature-list:HAVE_ISIS_LFA}?
| | +--rw protocol-topology?       empty {feature-list:HAVE_PROTOCOL_TOPOLOGY}?
| | +--rw level-capability?        ipi-isis-types:isis_is_type_t
| | +--rw authentication-send-only? ipi-isis-types:isis_auth_level_type_t
| | +--rw incremental-spf-levels?  ipi-isis-types:isis_is_type_t
| | +--rw priority-tag?            uint32 {feature-list:HAVE_WIDE_METRIC}?
| | +--rw disable-gr-capability?    empty {feature-list:HAVE_RESTART}?
| | +--rw enable-bfd-all-interfaces? empty {feature-list:HAVE_BFD}?
| | +--rw maximum-area-addresses?  uint8
| | +--rw context-name?            string {feature-list:HAVE_SNMP}?
| | +--rw disable-asla-usage-flex-algo? empty
| | +--rw disable-asla-strict-flex-algo? empty
| | +--rw disable-flex-algo-usage?  empty
| +--ro state
| | +--ro counters

```

```

| | | +--ro system-level-1-adjacency-count? uint32
| | | +--ro system-level-2-adjacency-count? uint32
| | | +--ro system-total-adjacency-count? uint32
| | +--ro next-global-update-level-1? uint32
| | +--ro next-global-update-level-2? uint32
| | +--ro overload? ipi-isis-types:isis_overload_state_t
| | +--ro instance? string
| | +--ro distance? uint8
| | +--ro vrf-name -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
| | +--ro dynamic-host-name? ipi-isis-types:isis_dynamic_hostname_t
| | +--ro disable-adjacency-check? empty
| | +--ro ignore-lsp-errors? empty
| | +--ro lfa-hold-timer? int32 {feature-list:HAVE_ISIS_LFA}?
| | +--ro protocol-topology? empty {feature-list:HAVE_PROTOCOL_TOPOLOGY}?
| | +--ro level-capability? ipi-isis-types:isis_is_type_t
| | +--ro authentication-send-only? ipi-isis-types:isis_auth_level_type_t
| | +--ro incremental-spf-levels? ipi-isis-types:isis_is_type_t
| | +--ro priority-tag? uint32 {feature-list:HAVE_WIDE_METRIC}?
| | +--ro disable-gr-capability? empty {feature-list:HAVE_RESTART}?
| | +--ro enable-bfd-all-interfaces? empty {feature-list:HAVE_BFD}?
| | +--ro maximum-area-addresses? uint8
| | +--ro context-name? string {feature-list:HAVE_SNMP}?
| | +--ro disable-asla-usage-flex-algo? empty
| | +--ro disable-asla-strict-flex-algo? empty
| | +--ro disable-flex-algo-usage? empty
| +--ro vrf
| | +--ro igp-shortcut-lsp* [index]
| |   +--ro index -> ../state/index
| |   +--ro state
| |     +--ro index? uint32
| |     +--ro metric? uint16
| |     +--ro tunnel-id? uint32
| |     +--ro tunnel-endpoint? string
| |     +--ro lock? uint16
| |     +--ro status? ipi-isis-types:isis_igp_shortcut_lsp_status_t
| +--rw partial-route-computations

```

---

```
| | +--rw partial-route-computation* [minimum-delay maximum-delay]
| |   +--rw minimum-delay  -> ../config/minimum-delay
| |   +--rw maximum-delay  -> ../config/maximum-delay
| |   +--rw config
| |     | +--rw minimum-delay?  uint32
| |     | +--rw maximum-delay?  uint32
| |     +--ro state
| |       +--ro minimum-delay?  uint32
| |       +--ro maximum-delay?  uint32
| +--rw area-authentication
| | +--rw config!
| | | +--rw area-password      string
| | | +--rw sequence-number-packet?  ipi-isis-types:isis_snp_t
| | +--ro state
| |   +--ro area-password      string
| |   +--ro sequence-number-packet?  ipi-isis-types:isis_snp_t
| +--rw network-entity-title
| | +--rw config
| | | +--rw net*  string
| | +--ro state
| |   +--ro net*  string
| +--rw domain-authentication
| | +--rw config!
| | | +--rw domain-password  string
| | | +--rw domain-snp?     ipi-isis-types:isis_snp_t
| | +--ro state
| |   +--ro domain-password  string
| |   +--ro domain-snp?     ipi-isis-types:isis_snp_t
| +--rw metric {feature-list:HAVE_WIDE_METRIC}?
| | +--rw config
| | | +--rw style?          ipi-isis-types:isis_metric_style_t {feature-list:HAVE_WIDE_METRIC}?
| | | +--rw level-number?  ipi-isis-types:isis_level3_t {feature-list:HAVE_WIDE_METRIC}?
| | +--ro state
| |   +--ro style?          ipi-isis-types:isis_metric_style_t {feature-list:HAVE_WIDE_METRIC}?
| |   +--ro level-number?  ipi-isis-types:isis_level3_t {feature-list:HAVE_WIDE_METRIC}?
| +--rw manual-area-addresses
```

---

```
| | +--ro state
| |   +--ro address* string
| +--rw receive-area-addresses
| | +--ro state
| |   +--ro address* string
| +--rw timers
| | +--rw config
| | | +--rw lsp-refresh-interval? uint16
| | | +--rw lsp-lifetime-interval? uint16
| | +--ro state
| |   +--ro lsp-refresh-interval? uint16
| |   +--ro lsp-lifetime-interval? uint16
| +--rw traffic-engineering
| | +--rw config
| | +--ro state
| +--rw address-family-ipv6
| | +--rw level-1-into-2-redistributes
| | | +--rw redistribute-level-1-into-2* [enable]
| | |   +--rw enable -> ../config/enable
| | |   +--rw config
| | |     | +--rw enable? empty
| | |     | +--rw level-1-acl? string
| | |     +--ro state
| | |       +--ro enable? empty
| | |       +--ro level-1-acl? string
| | +--rw level-2-into-1-redistributes
| | | +--rw redistribute-level-2-into-1* [enable]
| | |   +--rw enable -> ../config/enable
| | |   +--rw config
| | |     | +--rw enable? empty
| | |     | +--rw level-2-acl? string
| | |     +--ro state
| | |       +--ro enable? empty
| | |       +--ro level-2-acl? string
| | +--rw default-route-informations
| | | +--rw default-route-information* [originate]
```

---

```
| | | +--rw originate -> ../config/originate
| | | +--rw config
| | | | +--rw originate? ipi-isis-types:isis_origin_type_t
| | | | +--rw route-map-name? string
| | | +--ro state
| | |   +--ro originate? ipi-isis-types:isis_origin_type_t
| | |   +--ro route-map-name? string
| | +--rw config!
| | | +--rw afi-name ipi-isis-types:isis_address_ipv6_t
| | | +--rw administrative-distance? uint32
| | | +--rw disable-adjacency-check? empty
| | +--ro state
| | | +--ro afi-name ipi-isis-types:isis_address_ipv6_t
| | | +--ro administrative-distance? uint32
| | | +--ro disable-adjacency-check? empty
| | +--rw redistributions
| | | +--rw redistribute* [ipv6-protocol-type]
| | |   +--rw ipv6-protocol-type -> ../config/ipv6-protocol-type
| | |   +--rw config
| | | | +--rw ipv6-protocol-type? ipi-isis-types:isis_redistribute_t
| | | | +--rw ipv6-level? ipi-isis-types:isis_is_type3_t
| | | | +--rw ipv6-metric-value? uint32
| | | | +--rw ipv6-metric-type? ipi-isis-types:isis_metric_t
| | | | +--rw ipv6-route-map? string
| | | +--ro state
| | |   +--ro ipv6-protocol-type? ipi-isis-types:isis_redistribute_t
| | |   +--ro ipv6-level? ipi-isis-types:isis_is_type3_t
| | |   +--ro ipv6-metric-value? uint32
| | |   +--ro ipv6-metric-type? ipi-isis-types:isis_metric_t
| | |   +--ro ipv6-route-map? string
| | +--rw summary-prefixes
| | | +--rw summary-prefix* [prefix]
| | |   +--rw prefix -> ../config/prefix
| | |   +--rw config
| | | | +--rw prefix? cml-data-types:cml_ipv6_prefix_t
| | | | +--rw level ipi-isis-types:isis_summary_level_t
```

---

```

| | | | +--rw metric? uint8
| | | +--ro state
| | |   +--ro prefix? cml-data-types:cml_ipv6_prefix_t
| | |   +--ro level   ipi-isis-types:isis_summary_level_t
| | |   +--ro metric? uint8
| | +--rw multi-topologies
| |   +--rw multi-topology* [level] {feature-list:HAVE_MULTI_TOPOLOGY}?
| |     +--rw level   -> ../config/level
| |     +--rw config
| |       | +--rw level? ipi-isis-types:isis_multi_topology_level_type_t
| |       +--ro state
| |         +--ro level? ipi-isis-types:isis_multi_topology_level_type_t
| +--rw distances
| | +--rw distance* [system-id]
| |   +--rw system-id -> ../config/system-id
| |   +--rw config
| |     | +--rw system-id?   string
| |     | +--rw value       uint8
| |     | +--rw access-list-name? string
| |     +--ro state
| |       +--ro system-id?   string
| |       +--ro value       uint8
| |       +--ro access-list-name? string
| +--rw lsp-over-load
| | +--rw config!
| | | +--rw enabled      empty
| | | +--rw suppress-type? ipi-isis-types:isis_suppress_t
| | | +--rw set-bit-on-boot? ipi-isis-types:isis_onstartup_t
| | +--ro state
| |   +--ro enabled      empty
| |   +--ro suppress-type? ipi-isis-types:isis_suppress_t
| |   +--ro set-bit-on-boot? ipi-isis-types:isis_onstartup_t
| +--rw address-family-ipv4
| | +--ro state
| | | +--ro existence-state?   uint8
| | | +--ro redistribute-update? int32

```

---

---

```
| | | +--ro redistribute-timer-value? string
| | +--rw level-1-into-2-redistributes
| | | +--rw redistribute-level-1-into-2* [enable]
| | |   +--rw enable -> ../config/enable
| | |   +--rw config
| | |     | +--rw enable? empty
| | |     | +--rw level-1-acl? string
| | |     +--ro state
| | |       +--ro enable? empty
| | |       +--ro level-1-acl? string
| | +--rw level-2-into-1-redistributes
| | | +--rw redistribute-level-2-into-1* [enable]
| | |   +--rw enable -> ../config/enable
| | |   +--rw config
| | |     | +--rw enable? empty
| | |     | +--rw level-2-acl? string
| | |     +--ro state
| | |       +--ro enable? empty
| | |       +--ro level-2-acl? string
| | +--rw default-route-informations
| | | +--rw default-route-information* [originate]
| | |   +--rw originate -> ../config/originate
| | |   +--rw config
| | |     | +--rw originate? ipi-isis-types:isis_origin_type_t
| | |     | +--rw route-map-name? string
| | |     +--ro state
| | |       +--ro originate? ipi-isis-types:isis_origin_type_t
| | |       +--ro route-map-name? string
| | +--rw redistributions
| | | +--rw redistribute* [protocol-type]
| | |   +--rw protocol-type -> ../config/protocol-type
| | |   +--rw config
| | |     | +--rw protocol-type? ipi-isis-types:isis_redistribute_t
| | |     | +--rw level? ipi-isis-types:isis_is_type3_t
| | |     | +--rw metric-value? uint32
| | |     | +--rw metric-type? ipi-isis-types:isis_metric_t
```

---

```
| | | | +--rw route-map?    string
| | | +--ro state
| | |   +--ro protocol-type? ipi-isis-types:isis_redistribute_t
| | |   +--ro level?        ipi-isis-types:isis_is_type3_t
| | |   +--ro metric-value? uint32
| | |   +--ro metric-type?  ipi-isis-types:isis_metric_t
| | |   +--ro route-map?    string
| | +--rw summary-addresses
| | | +--rw summary-address* [prefix]
| | |   +--rw prefix  -> ../config/prefix
| | |   +--rw config
| | | | +--rw prefix?  cml-data-types:cml_ipv4_prefix_t
| | | | +--rw level   ipi-isis-types:isis_summary_level_t
| | | | +--rw metric? uint8
| | | +--ro state
| | |   +--ro prefix?  cml-data-types:cml_ipv4_prefix_t
| | |   +--ro level   ipi-isis-types:isis_summary_level_t
| | |   +--ro metric? uint8
| | +--rw redistribute-isis-instances
| | | +--rw redistribute-isis-instance* [id]
| | |   +--rw id      -> ../config/id
| | |   +--rw config
| | | | +--rw id?      string
| | | | +--rw level?   ipi-isis-types:isis_is_type3_t
| | | | +--rw metric-value? uint32
| | | | +--rw metric-type? ipi-isis-types:isis_metric_t
| | | | +--rw route-map? string
| | | +--ro state
| | |   +--ro id?      string
| | |   +--ro level?   ipi-isis-types:isis_is_type3_t
| | |   +--ro metric-value? uint32
| | |   +--ro metric-type? ipi-isis-types:isis_metric_t
| | |   +--ro route-map? string
| +--rw passive-interfaces
| | +--rw config
| | | +--rw passive-interface-all? empty
```

```
| | +--ro state
| | | +--ro passive-interface-all? empty
| | +--rw passive-interface* [name]
| | | +--rw name -> ../config/name
| | | +--rw config
| | | | +--rw name? -> /ipi-interface:interfaces/interface/name
| | | +--ro state
| | | | +--ro name? -> /ipi-interface:interfaces/interface/name
| | +--rw disable-passive-interfaces
| | | +--rw disable-passive-interface* [name]
| | | | +--rw name -> ../config/name
| | | | +--rw config
| | | | | +--rw name? -> /ipi-interface:interfaces/interface/name
| | | | +--ro state
| | | | | +--ro name? -> /ipi-interface:interfaces/interface/name
| +--rw microloop-avoidances {feature-list:HAVE_ISIS_LFA_OR_HAVE_ISIS_TI_LFA}?
| | +--rw microloop-avoidance* [level-type]
| | | +--rw level-type -> ../config/level-type
| | | +--rw config
| | | | +--rw hold-timer? uint8
| | | | +--rw max-fib? uint8
| | | | +--rw level-type? ipi-isis-types:isis_level2_t
| | | | +--rw enable? empty
| | | +--ro state
| | | | +--ro hold-timer? uint8
| | | | +--ro max-fib? uint8
| | | | +--ro level-type? ipi-isis-types:isis_level2_t
| | | | +--ro enable? empty
| +--rw mpls-traffic-engg
| | +--rw config
| | +--ro state
| +--ro extended-admin-groups
| | +--ro extended-admin-group* [name id]
| | | +--ro name -> ../state/name
| | | +--ro id -> ../state/id
| | | +--ro state
```

---

```
| |   +--ro name?  string
| |   +--ro id?   uint16
| +--rw flexalgos
| | +--rw flexalgo* [algo-number]
| |   +--rw algo-number          -> ../config/algo-number
| |   +--rw config!
| | | +--rw algo-number?         uint8
| | | +--rw metric-type?         ipi-isis-types:isis_fad_metric_type_t
| | | +--rw calculation-type?    ipi-isis-types:isis_fad_calculation_type_t
| | | +--rw priority?           uint8
| | | +--rw exclude-minimum-bandwidth?  string
| | | +--rw exclude-maximum-delay?     uint32
| | | +--rw enable-intf-group-mode-bw-calc?  empty
| | | +--rw reference-bandwidth?         string
| | | +--rw granularity-bandwidth?      string
| | | +--rw enable-advertise-definition?  empty
| | | +--rw enable-participate?         empty
| | | +--rw enable-fast-reroute?       empty
| | | +--rw enable-remote-lfa?        empty
| | | +--rw enable-ti-lfa?            empty
| | | +--rw enable-prefix-metric-flag?  empty
| | | +--rw fapm-metric?              uint8
| | | +--rw affinity-eag-exclude-any*   string
| | | +--rw affinity-eag-include-any*   string
| | | +--rw affinity-eag-include-all*   string
| | | +--rw affinity-eag-reverse-exclude-any*  string
| | | +--rw affinity-eag-reverse-include-any*  string
| | | +--rw affinity-eag-reverse-include-all*  string
| | | +--rw affinity-ag-exclude-any*     string
| | | +--rw affinity-ag-include-any*     string
| | | +--rw affinity-ag-include-all*    string
| | | +--rw affinity-ag-reverse-exclude-any*  string
| | | +--rw affinity-ag-reverse-include-any*  string
| | | +--rw affinity-ag-reverse-include-all*  string
| | +--ro state
| | | +--ro algo-number?              uint8
```

---

---

```

| | | +--ro metric-type?          ipi-isis-types:isis_fad_metric_type_t
| | | +--ro calculation-type?     ipi-isis-types:isis_fad_calculation_type_t
| | | +--ro priority?            uint8
| | | +--ro exclude-minimum-bandwidth?  string
| | | +--ro exclude-maximum-delay?     uint32
| | | +--ro enable-intf-group-mode-bw-calc?  empty
| | | +--ro reference-bandwidth?        string
| | | +--ro granularity-bandwidth?     string
| | | +--ro enable-advertise-definition?  empty
| | | +--ro enable-participate?        empty
| | | +--ro enable-fast-reroute?       empty
| | | +--ro enable-remote-lfa?        empty
| | | +--ro enable-ti-lfa?            empty
| | | +--ro enable-prefix-metric-flag?  empty
| | | +--ro fapm-metric?              uint8
| | | +--ro affinity-eag-exclude-any*   string
| | | +--ro affinity-eag-include-any*   string
| | | +--ro affinity-eag-include-all*   string
| | | +--ro affinity-eag-reverse-exclude-any* string
| | | +--ro affinity-eag-reverse-include-any* string
| | | +--ro affinity-eag-reverse-include-all* string
| | | +--ro affinity-ag-exclude-any*    string
| | | +--ro affinity-ag-include-any*    string
| | | +--ro affinity-ag-include-all*    string
| | | +--ro affinity-ag-reverse-exclude-any* string
| | | +--ro affinity-ag-reverse-include-any* string
| | | +--ro affinity-ag-reverse-include-all* string
| | +--rw flexalgo-bandwidth-thresholds
| | | +--rw flexalgo-bandwidth-threshold* [bandwidth-threshold]
| | |   +--rw bandwidth-threshold  -> ../config/bandwidth-threshold
| | |   +--rw config
| | |     | +--rw bandwidth-threshold? string
| | |     | +--rw threshold-metric?  uint32
| | |     +--ro state
| | |       +--ro bandwidth-threshold? string
| | |       +--ro threshold-metric?  uint32

```

---

```

| | +--rw flexalgo-microloop-avoidances {feature-list:HAVE_ISIS_LFA_OR_HAVE_ISIS_TI_LFA}?
| |   +--rw flexalgo-microloop-avoidance* [level-type]
| |     +--rw level-type -> ../config/level-type
| |     +--rw config
| |       | +--rw level-type? ipi-isis-types:isis_level2_t
| |       | +--rw enable? empty
| |       +--ro state
| |         +--ro level-type? ipi-isis-types:isis_level2_t
| |         +--ro enable? empty
| +--ro level-runtime* [type]
| | +--ro type -> ../state/type
| | +--ro lspdb* [lsp-identifier]
| | | +--ro lsp-identifier -> ../state/lsp-identifier
| | | +--ro tlvs* [index]
| | | | +--ro index -> ../state/index
| | | | +--ro is-neighbors* [system-id]
| | | | | +--ro system-id -> ../state/system-id
| | | | | +--ro state
| | | | | +--ro system-id? string
| | | | | +--ro metric? uint32
| | | | +--ro es-neighbors* [system-id]
| | | | | +--ro system-id -> ../state/system-id
| | | | | +--ro state
| | | | | +--ro system-id? string
| | | | | +--ro metric? uint32
| | | +--ro ip-internal-reachability-information* [prefix]
| | | | +--ro prefix -> ../state/prefix
| | | | +--ro state
| | | | | +--ro prefix? cml-data-types:cml_line_t
| | | | | +--ro metric? string
| | | +--ro ip-external-reachability-information* [prefix]
| | | | +--ro prefix -> ../state/prefix
| | | | +--ro state
| | | | | +--ro prefix? cml-data-types:cml_line_t
| | | | | +--ro metric? string
| | | +--ro extended-is-reachability* [extended-is-index] {feature-list:HAVE_WIDE_METRIC}?

```

```

| | | | +--ro extended-is-index  -> ../state/extended-is-index
| | | | +--ro subtlv* [subtlv-index]
| | | | | +--ro subtlv-index      -> ../state/subtlv-index
| | | | | +--ro state
| | | | | | +--ro subtlv-index?  uint16
| | | | | +--ro protocols-supported {feature-list:HAVE_PROTOCOL_TOPOLOGY}?
| | | | | | +--ro state
| | | | | | | +--ro nlp-id* ipi-isis-types:isis_level_proto_t
| | | | | | +--ro state
| | | | | | +--ro extended-is-index? uint32
| | | | | | +--ro system-id?      string
| | | | | | +--ro metric?        uint32
| | | | +--ro extended-ipv4-reachability* [ipv4-reach-index] {feature-list:HAVE_WIDE_METRIC}?
| | | | +--ro ipv4-reach-index  -> ../state/ipv4-reach-index
| | | | +--ro subtlv* [stlv-reach-index]
| | | | | +--ro stlv-reach-index  -> ../state/stlv-reach-index
| | | | | +--ro state
| | | | | | +--ro stlv-reach-index? uint16
| | | | | | +--ro admin-tag-info
| | | | | | | +--ro state
| | | | | | | +--ro admin-tag?    uint32
| | | | | | | +--ro mismatch-length? uint16
| | | | | | +--ro state
| | | | | | +--ro ipv4-reach-index? uint32
| | | | | | +--ro prefix?        cml-data-types:cml_ipv4_addr_prefix_t
| | | | | | +--ro metric?        uint32
| | | | +--ro ipv6-reachability* [ipv6-reach-index] {feature-list:HAVE_IPV6}?
| | | | +--ro ipv6-reach-index  -> ../state/ipv6-reach-index
| | | | +--ro subtlv* [stlv-reach-index]
| | | | | +--ro stlv-reach-index  -> ../state/stlv-reach-index
| | | | | +--ro state
| | | | | | +--ro stlv-reach-index? uint16
| | | | | | +--ro admin-tag-info
| | | | | | | +--ro state
| | | | | | | +--ro admin-tag?    uint32
| | | | | | | +--ro mismatch-length? uint16

```

```

| | | | +--ro state
| | | | +--ro ipv6-reach-index? uint32
| | | | +--ro prefix?          cml-data-types:cml_ipv6_prefix_t
| | | | +--ro metric?         cml-data-types:cml_line_t
| | | | +--ro up-down?        boolean
| | | +--ro multi-topology* [id] {feature-list:HAVE_MULTI_TOPOLOGY}?
| | | | +--ro id      -> ../state/id
| | | | +--ro state
| | | | +--ro id?   string
| | | +--ro multi-topology-is-reachability* [multi-is-index] {feature-list:HAVE_MULTI_TOPOLOGY}?
| | | | +--ro multi-is-index  -> ../state/multi-is-index
| | | | +--ro subtlv* [subtlv-index]
| | | | | +--ro subtlv-index    -> ../state/subtlv-index
| | | | | +--ro state
| | | | | | +--ro subtlv-index? uint16
| | | | | +--ro protocols-supported {feature-list:HAVE_PROTOCOL_TOPOLOGY}?
| | | | | | +--ro state
| | | | | | | +--ro nlp-id* ipi-isis-types:isis_level_proto_t
| | | | | | +--ro state
| | | | | | +--ro multi-is-index? uint32
| | | | | | +--ro system-id?   string
| | | | | | +--ro metric?     uint32
| | | | +--ro multi-topology-ipv6-reachability* [multi-ipv6-reach-index] {feature-
list:HAVE_MULTI_TOPOLOGY,feature-list:HAVE_IPV6}?
| | | | | +--ro multi-ipv6-reach-index  -> ../state/multi-ipv6-reach-index
| | | | | +--ro subtlv* [stlv-reach-index]
| | | | | | +--ro stlv-reach-index  -> ../state/stlv-reach-index
| | | | | | +--ro state
| | | | | | | +--ro stlv-reach-index? uint16
| | | | | | +--ro admin-tag-info
| | | | | | | +--ro state
| | | | | | | | +--ro admin-tag?   uint32
| | | | | | | | +--ro mismatch-length? uint16
| | | | | | +--ro state
| | | | | | +--ro prefix?         string
| | | | | | +--ro metric?        string
| | | | | | +--ro up-down?       boolean

```

---

```
| | | | +--ro multi-ipv6-reach-index? uint16
| | | | +--ro id? uint16
| | | +--ro multi-topology-ipv4-reachability* [id] {feature-list:HAVE_MULTI_TOPOLOGY}?
| | | | +--ro id -> ../state/id
| | | | +--ro stlv* [stlv-reach-index]
| | | | | +--ro stlv-reach-index -> ../state/stlv-reach-index
| | | | | +--ro state
| | | | | | +--ro stlv-reach-index? uint16
| | | | | | +--ro admin-tag-info
| | | | | | +--ro state
| | | | | | +--ro admin-tag? uint32
| | | | | | +--ro mismatch-length? uint16
| | | | | | +--ro state
| | | | | +--ro prefix? inet:ipv4-address
| | | | | +--ro metric? uint32
| | | | | +--ro id? uint16
| | | | +--ro state
| | | | +--ro index? uint32
| | | +--ro area-addresses
| | | | +--ro state
| | | | +--ro address* string
| | | +--ro supported-protocol
| | | | +--ro state
| | | | +--ro nlp-id* ipi-isis-types:isis_level_proto_t
| | | +--ro host-name
| | | | +--ro state
| | | | +--ro host-name? string
| | | +--ro ipv4-interface-addresses
| | | | +--ro state
| | | | +--ro address? inet:ipv4-address
| | | +--ro ipv6-interface-address {feature-list:HAVE_IPV6}?
| | | | +--ro state
| | | | +--ro address? inet:ipv6-address
| | | +--ro state
| | +--ro lsp-identifier? string
| | +--ro is-self-lsp? string
```

---

```
| | | +--ro checksum?      string
| | | +--ro remaining-lifetime? uint16
| | | +--ro flags?         uint8
| | | +--ro partition-repair? boolean
| | | +--ro over-loaded?   boolean
| | | +--ro sequence-number? string
| | | +--ro pdu-length?    uint32
| | +--ro protocol-data* [index]
| | | +--ro index      uint8
| | | +--ro vertex* [destination-system-id]
| | |   +--ro destination-system-id -> ../state/destination-system-id
| | |   +--ro vertex-nexthop* [nexthop-interface nexthop-system-id]
| | |     | +--ro nexthop-interface -> ../state/nexthop-interface
| | |     | +--ro nexthop-system-id -> ../state/nexthop-system-id
| | |     | +--ro state
| | |     |   +--ro nexthop-interface? string
| | |     |   +--ro nexthop-system-id? string
| | |     |   +--ro snpa-mac-address? cml-data-types:cml_mac_addr_t
| | |     +--ro state
| | |       +--ro distance?          uint32
| | |       +--ro destination-system-id? string
| | +--ro state
| | +--ro counters
| | | +--ro authentication-type-fails?      uint32
| | | +--ro authentication-fails?         uint32
| | | +--ro corrupted-lsps?                uint32
| | | +--ro database-overloads?            uint32
| | | +--ro manual-address-drop-from-areas? uint32
| | | +--ro attempt-to-exceed-maximum-sequence-numbers? uint32
| | | +--ro sequence-number-skips?         uint32
| | | +--ro own-lsp-purges?                uint32
| | | +--ro lsp-sourced?                   uint32
| | | +--ro maximum-area-address-mismatches? uint32
| | | +--ro id-length-mismatch?            uint32
| | | +--ro partition-changes?             uint32
| | | +--ro spf-runs?                      uint32
```

---

```
| | | +--ro partial-route-calculation-count?      uint32
| | | +--ro lan-designated-is-changes?          uint32
| | +--ro type?      ipi-isis-types:isis_level2_t
| | +--ro topology-type?  uint8
| +--rw spf-levels
| | +--rw spf-level* [level]
| |   +--rw level      -> ../config/level
| |   +--rw spf-delays
| |     +--rw spf-delay* [spf-min-delay spf-max-delay]
| |       +--rw spf-min-delay  -> ../config/spf-min-delay
| |       +--rw spf-max-delay  -> ../config/spf-max-delay
| |       +--rw config
| |         +--rw spf-min-delay?  uint32
| |         +--rw spf-max-delay?  uint32
| |         +--ro state
| |           +--ro spf-min-delay?  uint32
| |           +--ro spf-max-delay?  uint32
| |         +--rw config
| |           +--rw level?  ipi-isis-types:isis_level3_t
| |           +--ro state
| |             +--ro level?  ipi-isis-types:isis_level3_t
| +--rw levels
| | +--rw level* [type]
| |   +--rw type      -> ../config/type
| |   +--rw config
| |     +--rw type?          ipi-isis-types:isis_level3_t
| |     +--rw wait-timer?    uint16
| |     +--rw restart-timer?  uint16
| |     +--rw lsp-max-wait-interval?  uint32
| |     +--rw lsp-mtu-size?    uint16
| |     +--ro state
| |       +--ro type?          ipi-isis-types:isis_level3_t
| |       +--ro wait-timer?    uint16
| |       +--ro restart-timer?  uint16
| |       +--ro lsp-max-wait-interval?  uint32
| |       +--ro lsp-mtu-size?    uint16
```

```

| | +--rw authentication
| |   +--rw config!
| |     | +--rw key-chain? string
| |     | +--rw mode      ipi-isis-types:isis_auth_mode_t
| |     +--ro state
| |       +--ro key-chain? string
| |       +--ro mode      ipi-isis-types:isis_auth_mode_t
| +--ro ipv4-lfa-route* [destination-prefix]
| | +--ro destination-prefix -> ../state/destination-prefix
| | +--ro route-nexthop* [primary-nexthop nexthop-type]
| | | +--ro primary-nexthop -> ../state/primary-nexthop
| | | +--ro nexthop-type    -> ../state/nexthop-type
| | | +--ro state
| | |   +--ro primary-nexthop?      inet:ipv4-address
| | |   +--ro nexthop-type?        ipi-isis-types:isis_lfa_nexthop_type_t
| | |   +--ro primary-nexthop-interface-name? string
| | |   +--ro remote-router-id?    inet:ipv4-address
| | |   +--ro lfa-nexthop?         inet:ipv4-address
| | |   +--ro lfa-nexthop-interface-name? string
| | |   +--ro lfa-path-metric?     uint32
| | |   +--ro protection-provided? cml-data-types:cml_line_t
| | +--ro state
| |   +--ro destination-prefix?    cml-data-types:cml_ipv4_addr_prefix_t
| |   +--ro destination-path-type? string
| +--ro ipv6-lfa-route* [destination-prefix]
| | +--ro destination-prefix -> ../state/destination-prefix
| | +--ro route-nexthop* [primary-nexthop]
| | | +--ro primary-nexthop -> ../state/primary-nexthop
| | | +--ro state
| | |   +--ro primary-nexthop?      inet:ipv6-address
| | |   +--ro primary-nexthop-interface-name? string
| | |   +--ro lfa-nexthop?         inet:ipv6-address
| | |   +--ro lfa-nexthop-interface-name? string
| | |   +--ro lfa-path-metric?     uint32
| | |   +--ro protection-provided? string
| | +--ro state

```

---

```

| | +--ro destination-prefix?  cml-data-types:cml_ipv6_prefix_t
| | +--ro destination-path-type? string
| +--rw fast-reroute-levels
|   +--rw fast-reroute* [level-type]
|     +--rw level-type  -> ../config/level-type
|     +--rw config
|       | +--rw level-type?  ipi-isis-types:isis_level2_t
|       +--ro state
|         | +--ro level-type?  ipi-isis-types:isis_level2_t
|         +--rw route-maps
|           | +--rw route-map* [protocol] {feature-list:HAVE_ISIS_LFA}?
|           |   +--rw protocol  -> ../config/protocol
|           |   +--rw config
|           |     | +--rw protocol?      ipi-isis-types:isis_lfa_level_proto_t
|           |     | +--rw name?          string
|           |     | +--rw enable-all-prefixes?  ipi-isis-types:isis_frr_enum_t
|           |     +--ro state
|           |       +--ro protocol?      ipi-isis-types:isis_lfa_level_proto_t
|           |       +--ro name?          string
|           |       +--ro enable-all-prefixes?  ipi-isis-types:isis_frr_enum_t
|           +--rw ti-lfas
|           +--rw protocols
|             +--rw protocol* [lfa-protocol preference-value] {feature-list:HAVE_ISIS_LFA}?
|               +--rw lfa-protocol  -> ../config/lfa-protocol
|               +--rw preference-value  -> ../config/preference-value
|               +--rw config
|                 | +--rw lfa-protocol?  ipi-isis-types:isis_lfa_level_proto_t
|                 | +--rw preference-value?  ipi-isis-types:isis_frr_tie_break_val_t
|                 | +--rw preference-index  uint32
|                 +--ro state
|                   +--ro lfa-protocol?  ipi-isis-types:isis_lfa_level_proto_t
|                   +--ro preference-value?  ipi-isis-types:isis_frr_tie_break_val_t
|                   +--ro preference-index  uint32
+--rw debug
| +--rw config
| | +--rw options?      ipi-isis-types:isis_debug_t

```

---

---

```
| | +--rw enable-hello?    empty
| | +--rw interface-hello* string
| | +--rw system-id-hello* string
| +--ro state
|   +--ro options?        ipi-isis-types:isis_debug_t
|   +--ro enable-hello?   empty
|   +--ro interface-hello* string
|   +--ro system-id-hello* string
|   +--ro terminal-debug
|     +--ro terminal-debug-status?          ipi-isis-types:isis_debug_t
|     +--ro terminal-debug-status-hello?    cml-data-types:cml_on_off_t
|     +--ro terminal-debug-status-interface-hello* string
|     +--ro terminal-debug-status-system-id-hello* string
+--ro state
| +--ro host-name*        string
| +--ro lsp-identifier?   -> /isis/isis-instances/isis-instance/level-runtime/lspdb/state/lsp-identifier
| +--ro overload?        -> /isis/isis-instances/isis-instance/state/overload
| +--ro pdu-length?      -> /isis/isis-instances/isis-instance/level-runtime/lspdb/state/pdu-length
| +--ro raw-pdu?         string
| +--ro pdu-field-len?   uint8
| +--ro max-area-addresses? uint8
| +--ro protocol-version? uint8
| +--ro reason?          string
| +--ro protocols?       uint8
| +--ro error-offset?    uint32
| +--ro tlv-type?        uint8
+--rw graceful-restart
| +--rw config
| | +--rw grace-period?    uint16
| | +--rw enable-helper-only? empty
| | +--rw suppress-adjacency? empty
| +--ro state
|   +--ro grace-period?    uint16
|   +--ro enable-helper-only? empty
|   +--ro suppress-adjacency? empty
+--rw interfaces
```

---

```
+--rw interface* [name]
  +--rw name          -> ../config/name
  +--ro bandwidth-priority* [priority]
  | +--ro priority    -> ../state/priority
  | +--ro state
  |   +--ro priority?      uint8
  |   +--ro available-bandwidth? string
  +--ro neighbor-lan* [system-id]
  | +--ro system-id      -> ../state/system-id
  | +--ro adjacency* [level]
  | | +--ro level        -> ../state/level
  | | +--ro state
  | |   +--ro level?          ipi-isis-types:isis_level_t
  | |   +--ro adjacency-state? ipi-isis-types:isis_state_t
  | |   +--ro adjacency-id?   uint32
  | |   +--ro remaining-hold-time? string
  | |   +--ro priority?      uint8
  | +--ro state
  | | +--ro system-id?       string
  | | +--ro adjacency-type?   ipi-isis-types:isis_level_t
  | | +--ro adjacency-advertisement? ipi-isis-types:isis_nbr_adj_t
  | | +--ro neighbor-snpa?    string
  | | +--ro level-1-nlp-id*    ipi-isis-types:isis_level_proto_t
  | | +--ro level-2-nlp-id*    ipi-isis-types:isis_level_proto_t
  | | +--ro multi-topology-type? ipi-isis-types:isis_multi_topology_types_t
  | | +--ro up-time?          string
  | | +--ro neighbor-protocol? ipi-isis-types:isis_neighbour_protocol_t
  | | +--ro area-address*     string
  +--ro ipv4-addresses
  | +--ro state
  | | +--ro address* inet:ipv4-address
  +--ro ipv6-addresses
  | +--ro state
  | | +--ro address* inet:ipv6-address
  +--ro level* [level-number]
  | +--ro level-number      -> ../state/level-number
```

---

```
| +--ro state
| | +--ro level-number?          ipi-isis-types:isis_iflevel_t
| | +--ro next-hello-interval?   cml-data-types:cml_line_t
| | +--ro mtu?                   uint32
| | +--ro circuit-id?           string
| | +--ro active-adjacency-count? int32
| | +--ro csnp-interval?        cml-data-types:cml_line_t
| | +--ro adjacency-changes?    uint32
| | +--ro adjacency-number?     uint32
| | +--ro init-fails?           uint32
| | +--ro rejected-adjacency?   uint32
| | +--ro id-field-length-mismatches? uint32
| | +--ro max-area-address-mismatches? uint32
| | +--ro authentication-type-fails? uint32
| | +--ro authentication-fails?  uint32
| | +--ro lan-dis-changes?      uint32
| +--ro isis-hellos
| | +--ro state
| | | +--ro received? uint32
| | | +--ro sent?    uint32
| | +--ro link-state-pdu
| | | +--ro state
| | | | +--ro received? uint32
| | | | +--ro sent?    uint32
| | +--ro complete-sequence-number-pdu
| | | +--ro state
| | | | +--ro received? uint32
| | | | +--ro sent?    uint32
| | +--ro partial-sequence-number-pdu
| | | +--ro state
| | | | +--ro received? uint32
| | | | +--ro sent?    uint32
| +--ro unknown
| | +--ro state
| | | +--ro received? uint32
| | | +--ro sent?    uint32
```

---

```
+--rw config
| +--rw name?          -> /ipi-interface:interfaces/interface/name
| +--rw minimal?      ipi-isis-types:isis_auth_level_type_t
| +--rw send-only?    ipi-isis-types:isis_auth_level_type_t
| +--rw maximum-bandwidth-flex-algo? string
| +--rw disable-asla-usage-flex-algo? empty
+--ro state
| +--ro name?          -> /ipi-interface:interfaces/interface/name
| +--ro minimal?      ipi-isis-types:isis_auth_level_type_t
| +--ro send-only?    ipi-isis-types:isis_auth_level_type_t
| +--ro maximum-bandwidth-flex-algo? string
| +--ro disable-asla-usage-flex-algo? empty
| +--ro isis-tag?      string
| +--ro network-type? string
| +--ro circuit-type? ipi-isis-types:isis_circuit_type_t
| +--ro local-circuit-id? string
| +--ro extended-circuit-id? string
| +--ro local-snpa?    cml-data-types:cml_mac_addr_t
+--ro bandwidth
| +--ro state
+--ro p2p-circuit-counters
| +--ro state
| +--ro adjacency-changes? uint32
| +--ro adjacency-number?  uint32
| +--ro init-fails?        uint32
| +--ro rejected-adjacency? uint32
| +--ro id-field-length-mismatches? uint32
| +--ro max-area-address-mismatches? uint32
| +--ro authentication-type-fails?  uint32
| +--ro authentication-fails?      uint32
| +--ro lan-dis-changes?           uint32
+--rw connected-ipv4
| +--ro state
| +--ro address* cml-data-types:cml_ipv4_addr_prefix_t
+--rw connected-ipv6
| +--ro state
```

---

```
|  +--ro address*  cml-data-types:cml_ipv6_prefix_t
+--ro neighbor-P2P
|  +--ro ipv4-addresses* [address]
| |  +--ro address  -> ../state/address
| |  +--ro state
| |  +--ro address*  inet:ipv4-address
|  +--ro ipv6-addresses* [address]
| |  +--ro address  -> ../state/address
| |  +--ro state
| |  +--ro address*  inet:ipv6-address
|  +--ro state
|  +--ro system-id?      string
|  +--ro circuit-id?     string
|  +--ro adjacency-state? ipi-isis-types:isis_state_t
|  +--ro remaining-hold-time? string
|  +--ro adjacency-type?  string
|  +--ro adjacency-advertisement? ipi-isis-types:isis_nbr_adj_t
|  +--ro neighbor-snpa?   string
|  +--ro level-1-nlp-id*  ipi-isis-types:isis_level_proto_t
|  +--ro level-2-nlp-id*  ipi-isis-types:isis_level_proto_t
|  +--ro multi-topology-type? ipi-isis-types:isis_multi_topology_types_t
|  +--ro up-time?        string
|  +--ro neighbor-protocol? ipi-isis-types:isis_neighbour_protocol_t
|  +--ro area-address*   string
+--rw interface-parameters
  +--rw config
  |  +--rw network-type?   ipi-isis-types:isis_network_t
  |  +--rw circuit-type?   ipi-isis-types:isis_circuit_type_t
  |  +--rw ipv4-instance-tag? string
  |  +--rw ipv6-instance-tag? string {feature-list:HAVE_IPV6}?
  |  +--rw lsp-interval?   uint32
  |  +--rw retransmit-interval? uint16
  |  +--rw disable-padding? empty
  |  +--rw mesh-group-id?  ipi-isis-types:isis_mesh_type_t
  +--ro state
  |  +--ro network-type?   ipi-isis-types:isis_network_t
```

---

---

```

| +--ro circuit-type?      ipi-isis-types:isis_circuit_type_t
| +--ro ipv4-instance-tag? string
| +--ro ipv6-instance-tag? string {feature-list:HAVE_IPV6}?
| +--ro lsp-interval?     uint32
| +--ro retransmit-interval? uint16
| +--ro disable-padding?  empty
| +--ro mesh-group-id?    ipi-isis-types:isis_mesh_type_t
+--rw bfd {feature-list:HAVE_BFD}?
| +--rw config
| | +--rw enable?  empty
| | +--rw disable? empty
| +--ro state
|   +--ro enable?  empty
|   +--ro disable? empty
+--rw fast-re-route
| +--rw config
| | +--rw disable-level-1? empty {feature-list:HAVE_ISIS_LFA}?
| | +--rw disable-level-2? empty {feature-list:HAVE_ISIS_LFA}?
| +--ro state
|   +--ro disable-level-1? empty {feature-list:HAVE_ISIS_LFA}?
|   +--ro disable-level-2? empty {feature-list:HAVE_ISIS_LFA}?
+--rw level-infos
  +--rw level-info* [level]
    +--rw level      -> ../config/level
    +--rw config
      | +--rw te-minimum-delay?      uint32
      | +--rw te-maximum-delay?     uint32
      | +--rw te-minimum-delay-flex-algo? uint32
      | +--rw te-maximum-delay-flex-algo? uint32
      | +--rw level?                ipi-isis-types:isis_level_t
      | +--rw hello-interval?       uint16
      | +--rw hello-multiplier?     uint8
      | +--rw csnp-interval?        uint16
      | +--rw priority?             uint8
      | +--rw metric?              uint8
      | +--rw password?            string

```

---

```

| +--rw tag?                uint32
| +--rw wide-metric?        uint32
| +--rw restart-hello-interval?  uint16
+--ro state
| +--ro te-minimum-delay?    uint32
| +--ro te-maximum-delay?    uint32
| +--ro te-minimum-delay-flex-algo?  uint32
| +--ro te-maximum-delay-flex-algo?  uint32
| +--ro level?              ipi-isis-types:isis_level_t
| +--ro hello-interval?     uint16
| +--ro hello-multiplier?   uint8
| +--ro csnp-interval?      uint16
| +--ro priority?           uint8
| +--ro metric?             uint8
| +--ro password?           string
| +--ro tag?                uint32
| +--ro wide-metric?        uint32
| +--ro restart-hello-interval?  uint16
+--rw authentication
  +--rw config!
    | +--rw mode      ipi-isis-types:isis_auth_mode_t
    | +--rw key-chain? string
  +--ro state
    +--ro mode      ipi-isis-types:isis_auth_mode_t
    +--ro key-chain? string

```

rpcs:

```

+---x isis-restart-graceful {feature-list:HAVE_RESTART}?
| +---w input
|   +---w grace-period?  uint16
+---x isis-clear-interface-counters {feature-list:HAVE_ISISD}?
| +---w input
|   +---w name?  string
+---x isis-clear-is-neighbors {feature-list:HAVE_ISISD}?
| +---w input
|   +---w system-id  string

```

---

```
+---x isis-clear-clns-neighbors {feature-list:HAVE_ISISD}?
+---x isis-clear-ip-route {feature-list:HAVE_ISISD}?
| +---w input
|   +---w instance?  string
|   +---w ipv4-route  ipi-isis-types:isis_route_t
+---x isis-clear-ipv6-route {feature-list:HAVE_ISISD}?
| +---w input
|   +---w instance?  string
|   +---w ipv6-route  ipi-isis-types:isis_route_t
+---x isis-process-clear {feature-list:HAVE_ISISD}?
| +---w input
|   +---w instance  string
+---x isis-clear-counters {feature-list:HAVE_ISISD}?
+---x isis-clear-adjacency-all {feature-list:HAVE_ISISD}?
| +---w input
|   +---w adjacency-vrf-name?  string
+---x isis-process-clear-adjacency-all {feature-list:HAVE_ISISD}?
| +---w input
|   +---w tag-name            string
|   +---w adjacency-vrf-name?  string
+---x isis-process-clear-adjacency-interface {feature-list:HAVE_ISISD}?
| +---w input
|   +---w tag-name            string
|   +---w tag-if-name?       string
|   +---w adjacency-vrf-name?  string
+---x isis-clear-adjacency-interface {feature-list:HAVE_ISISD}?
| +---w input
|   +---w adjacency-if-name?  string
|   +---w adjacency-vrf-name?  string
+---x isis-process-clear-adjacency-system-id {feature-list:HAVE_ISISD}?
| +---w input
|   +---w tag-name            string
|   +---w tag-system-id       ipi-isis-types:isis_systemid_t
|   +---w tag-vrf-name?       string
+---x isis-clear-adjacency-system-id {feature-list:HAVE_ISISD}?
| +---w input
```

---

```
| +---w adjacency-system-id  ipi-isis-types:isis_systemid_t
| +---w adjacency-vrf-name?  string
+---x isis-restart-snmp {feature-list:HAVE_SNMP}?
+---x isis-terminal-debug-all-on {feature-list:HAVE_ISISD}?
+---x isis-terminal-debug-all-off {feature-list:HAVE_ISISD}?
+---x isis-terminal-debug-on {feature-list:HAVE_ISISD}?
| +---w input
| +---w terminal-debug-options  ipi-isis-types:isis_debug_t
+---x isis-debug-off {feature-list:HAVE_ISISD}?
| +---w input
| +---w terminal-debug-options  ipi-isis-types:isis_debug_t
+---x isis-debug-hello-on {feature-list:HAVE_ISISD}?
+---x isis-debug-hello-off {feature-list:HAVE_ISISD}?
+---x isis-debug-interface-hello-on {feature-list:HAVE_ISISD}?
| +---w input
| +---w interface  string
+---x isis-debug-interface-hello-off {feature-list:HAVE_ISISD}?
| +---w input
| +---w interface  string
+---x isis-debug-system-id-hello-on {feature-list:HAVE_ISISD}?
| +---w input
| +---w system-id  string
+---x isis-debug-system-id-hello-off {feature-list:HAVE_ISISD}?
| +---w input
| +---w system-id  string
+---x isis-all-debug-off {feature-list:HAVE_ISISD}?
```

## notifications:

```
+---n isis-database-overload
| +-ro severity?  cml-data-types:cml_notif_severity_t
| +-ro eventClass?  cml-data-types:cml_notif_class_t
| +-ro overload?  ipi-isis-types:isis_overload_state_t
+---n isis-lsp-too-large
| +-ro severity?  cml-data-types:cml_notif_severity_t
| +-ro eventClass?  cml-data-types:cml_notif_class_t
| +-ro lsp-identifier?  string
```

---

```
| +--ro pdu-length?    uint32
+---n isis-corrupted-lsp-detected
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro lsp-identifier? string
+---n isis-attempt-to-exceed-max-sequence
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro lsp-identifier? string
+---n isis-id-len-mismatch
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro pdu-field-len? uint8
| +--ro raw-pdu?      string
+---n isis-max-area-addresses-mismatch
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro max-area-addresses? uint8
| +--ro raw-pdu?      string
+---n isis-own-lsp-purge
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro lsp-identifier? string
+---n isis-sequence-number-skipped
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro lsp-identifier? string
+---n isis-authentication-type-failure
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro raw-pdu?      string
+---n isis-authentication-failure
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro raw-pdu?      string
+---n isis-version-skew
```

---

```

| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro protocol-version? uint8
| +--ro raw-pdu?      string
+---n isis-area-mismatch
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro raw-pdu?      string
+---n isis-rejected-adjacency
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro raw-pdu?      string
| +--ro reason?       string
+---n isis-protocols-supported-mismatch
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro raw-pdu?      string
| +--ro protocols?    uint8
+---n isis-lsp-error-detected
  +--ro severity?      cml-data-types:cml_notif_severity_t
  +--ro eventClass?    cml-data-types:cml_notif_class_t
  +--ro lsp-identifier? string
  +--ro raw-pdu?       string
  +--ro error-offset?  uint32
  +--ro tlv-type?      uint8

```

---

## module: ipi-keychain

```

+--rw key-chains
  +--rw key-chain* [name]
    +--rw name    -> ../config/name
    +--rw config
      | +--rw name? string
      +--ro state
      | +--ro name? string
      +--rw keys

```

```
+--rw key-list* [key-id]
  +--rw key-id      -> ../config/key-id
  +--rw config
  | +--rw key-id?      uint32
  | +--rw (key-style)?
  |   +--:(key-string)
  |   | +--rw key-string? string
  |   +--:(hexadecimal)
  |     +--rw encrypted?  keychain_hex_string_t
  +--ro state
  | +--ro key-id?      uint32
  | +--ro (key-style)?
  |   +--:(key-string)
  |   | +--ro key-string? string
  |   +--:(hexadecimal)
  |     +--ro encrypted?  keychain_hex_string_t
  +--rw accept-lifetime
  | +--rw config
  | | +--rw start-date-time-for-accept?  keychain_date_time_t
  | | +--rw (end-time)?
  | |   +--:(end-time)
  | |   | +--rw end-date-time-for-accept?  keychain_date_time_t
  | |   +--:(infinite)
  | |   | +--rw infinite-for-accept?      empty
  | |   +--:(duration)
  | |     +--rw duration-for-accept?      uint32
  | +--ro state
  | +--ro start-date-time-for-accept?  keychain_date_time_t
  | +--ro (end-time)?
  |   +--:(end-time)
  |   | +--ro end-date-time-for-accept?  keychain_date_time_t
  |   +--:(infinite)
  |   | +--ro infinite-for-accept?      empty
  |   +--:(duration)
  |     +--ro duration-for-accept?      uint32
  +--rw send-lifetime
```

```

+--rw config
| +--rw start-date-time-for-send?    keychain_date_time_t
| +--rw (end-time)?
|   +--:(end-time)
|     | +--rw end-date-time-for-send? keychain_date_time_t
|     | +--:(infinite)
|     | +--rw infinite-for-send?     empty
|     | +--:(duration)
|     | +--rw duration-for-send?     uint32
+--ro state
  +--ro start-date-time-for-send?    keychain_date_time_t
  +--ro (end-time)?
  | +--:(end-time)
  |   | +--ro end-date-time-for-send? keychain_date_time_t
  |   | +--:(infinite)
  |   | +--ro infinite-for-send?     empty
  |   | +--:(duration)
  |   | +--ro duration-for-send?     uint32

```

---

## module: ipi-l2vpn-vpls

```

+--rw vpls
  +--rw attachment-circuit
  | +--rw service-template-mappings
  |   +--rw service-template-mapping* [interface-name vpls-name service-template-name]
  |     +--rw interface-name          -> ../config/interface-name
  |     +--rw vpls-name               -> ../config/vpls-name
  |     +--rw service-template-name   -> ../config/service-template-name
  |     +--rw config
  |       | +--rw interface-name?      -> /ipi-interface:interfaces/interface/name
  |       | +--rw service-template-name? -> /ipi-mpls:mpls/l2vpn/customer-service-templates/customer-service-
template/config/name
  |       | +--rw vpls-name?           string
  |       | +--rw admin-status?        ipi-vpls-types:vpls_ac_admin_status_t
  |       | +--rw attachment-circuit-description? cml-data-types:cml_line_t
  |       | +--rw mac-learning?        ipi-vpls-types:vpls_mac_learning_t

```

```

| | +--rw split-horizon?          ipi-if-types:if_split_horizon_t {feature-list:HAVE_CUSTOM2_MPLS}?
| | +--rw static-mac-address*     cml-data-types:cml_mac_addr_t
|   +--ro state
| | +--ro interface-name?        -> /ipi-interface:interfaces/interface/name
| | +--ro service-template-name?  -> /ipi-mpls:mpls/l2vpn/customer-service-templates/customer-service-
template/config/name
| | +--ro vpls-name?             string
| | +--ro admin-status?          ipi-vpls-types:vpls_ac_admin_status_t
| | +--ro attachment-circuit-description? cml-data-types:cml_line_t
| | +--ro mac-learning?          ipi-vpls-types:vpls_mac_learning_t
| | +--ro split-horizon?         ipi-if-types:if_split_horizon_t {feature-list:HAVE_CUSTOM2_MPLS}?
| | +--ro static-mac-address*     cml-data-types:cml_mac_addr_t
|   +--rw quality-of-service-profiles
|     +--rw quality-of-service-profile* [profile-type profile-name] {feature-list:HAVE_QOS}?
|       +--rw profile-type  -> ../config/profile-type
|       +--rw profile-name  -> ../config/profile-name
|       +--rw config
|         | +--rw profile-type? ipi-vpls-types:vpls_qos_map_profile_type_t
|         | +--rw profile-name? string
|         +--ro state
|           +--ro profile-type? ipi-vpls-types:vpls_qos_map_profile_type_t
|           +--ro profile-name? string
+--rw static-forwarding
| +--rw vpls-entries
| | +--rw vpls-entry* [vpls-identifier peer-address]
| |   +--rw vpls-identifier  -> ../config/vpls-identifier
| |   +--rw peer-address     -> ../config/peer-address
| |   +--rw config
| |     | +--rw in-label      uint32
| |     | +--rw out-label     uint32
| |     | +--rw out-interface-name string
| |     | +--rw vpls-identifier? -> /ipi-network-instance:network-instances/network-instance/vpls-instance/config/
vpls-identifier
| |     | +--rw peer-address?  -> /ipi-network-instance:network-instances/network-instance/vpls-instance/vpls-
peers/vpls-peer/config/peer-address
| |     +--ro state
| |     +--ro in-label        uint32

```

---

```
| |   +--ro out-label      uint32
| |   +--ro out-interface-name  string
| |   +--ro vpls-identifier?  -> /ipi-network-instance:network-instances/network-instance/vpls-instance/config/
vpls-identifier
| |   +--ro peer-address?    -> /ipi-network-instance:network-instances/network-instance/vpls-instance/vpls-
peers/vpls-peer/config/peer-address
| +--rw hierarchical-vpls-entries
| +--rw hierarchical-vpls-entry* [vpls-identifier spoke-pseudowire-name]
|   +--rw vpls-identifier    -> ../config/vpls-identifier
|   +--rw spoke-pseudowire-name -> ../config/spoke-pseudowire-name
|   +--rw config
|     | +--rw in-label      uint32
|     | +--rw out-label    uint32
|     | +--rw out-interface-name  string
|     | +--rw vpls-identifier?  -> /ipi-network-instance:network-instances/network-instance/vpls-instance/config/
vpls-identifier
|     | +--rw spoke-pseudowire-name? -> /ipi-network-instance:network-instances/network-instance/vpls-instance/
spoke-pseudowires/spoke-pseudowire/config/pseudowire-name
|     +--ro state
|       +--ro in-label      uint32
|       +--ro out-label    uint32
|       +--ro out-interface-name  string
|       +--ro vpls-identifier?  -> /ipi-network-instance:network-instances/network-instance/vpls-instance/config/
vpls-identifier
|       +--ro spoke-pseudowire-name? -> /ipi-network-instance:network-instances/network-instance/vpls-instance/
spoke-pseudowires/spoke-pseudowire/config/pseudowire-name
+--rw interfaces
| +--rw interface* [name]
|   +--rw name      -> ../config/name
|   +--rw config
|     | +--rw name?  -> /ipi-interface:interfaces/interface/name
|     +--ro state
|     | +--ro name?  -> /ipi-interface:interfaces/interface/name
|     +--rw vpls-access {feature-list:HAVE_SUBINTERFACE}?
|       +--rw config!
|         | +--rw enable      empty
|         | +--rw vpls-name?  string
|         | +--rw disable-mac-learning? empty
```

---

```

|   | +--rw static-mac-address*  cml-data-types:cml_mac_addr_t
|   +--ro state
|     +--ro enable                empty
|     +--ro vpls-name?            string
|     +--ro disable-mac-learning? empty
|     +--ro static-mac-address*  cml-data-types:cml_mac_addr_t
+--rw global
  +--ro state
    +--ro counters
      +--ro total-instances?      yang:counter32
      +--ro total-peers?          yang:counter32
      +--ro active-peer-instances? yang:counter32
      +--ro inactive-peer-instances? yang:counter32

```

augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance:

```

+--rw vpls-instance
  +--rw config!
    | +--rw vpls-identifier          uint32
    | +--rw service-transport-identifier? ipi-vpls-types:vpls_svc_tpid_t
    | +--rw maximum-transmission-unit?  uint16
    | +--rw vpls-description?         cml-data-types:cml_line_t
    | +--rw control-word?             empty
    | +--rw mac-learning-disable?     empty
    | +--rw mac-learning-limit?       uint32 {feature-list:NOT_HAVE_TRIDENT2,feature-
list:NOT_HAVE_TRIDENT2PLUS}?
    | +--rw attachment-circuit-group-name? -> /ipi-mpls:mpls/l2vpn/access-circuit-groups/access-circuit-group/config/
group-name
    +--ro state
      | +--ro vpls-identifier          uint32
      | +--ro service-transport-identifier? ipi-vpls-types:vpls_svc_tpid_t
      | +--ro maximum-transmission-unit?  uint16
      | +--ro vpls-description?         cml-data-types:cml_line_t
      | +--ro control-word?             empty
      | +--ro mac-learning-disable?     empty
      | +--ro mac-learning-limit?       uint32 {feature-list:NOT_HAVE_TRIDENT2,feature-
list:NOT_HAVE_TRIDENT2PLUS}?
      | +--ro attachment-circuit-group-name? -> /ipi-mpls:mpls/l2vpn/access-circuit-groups/access-circuit-group/config/
group-name

```

---

```

| +--ro signaling-protocol?      ipi-vpls-types:vpls_signaling_type_t
| +--ro route-distinguisher?    string
| +--ro route-target?          string
| +--ro vpls-edge-id?          uint32
| +--ro attachment-circuit-status? ipi-vpls-types:vpls_ac_status_t
| +--ro vpls-type?             ipi-vpls-types:vpls_vc_type_t
| +--ro service-vlan-id?       uint16
| +--ro group-identifier?      uint32
| +--ro total-mac-addresses-learnt? uint32
+--rw spoke-pseudowires
| +--rw spoke-pseudowire* [pseudowire-name]
|   +--rw pseudowire-name  -> ../config/pseudowire-name
|   +--rw config
|     | +--rw pseudowire-name?      string
|     | +--rw secondary-pseudowire-name? string
|     | +--rw split-horizon?       ipi-if-types:if_split_horizon_t {feature-list:HAVE_CUSTOM2_MPLS}?
|     +--ro state
|       +--ro pseudowire-name?      string
|       +--ro secondary-pseudowire-name? string
|       +--ro split-horizon?       ipi-if-types:if_split_horizon_t {feature-list:HAVE_CUSTOM2_MPLS}?
+--rw fat-label
| +--rw config!
| | +--rw enable-flow-label        empty
| | +--rw flow-label-direction?    ipi-vpls-types:vpls_mpls_flow_label_direction_t
| | +--rw enable-static-flow-label? empty
| | +--rw enable-interface-parameter-tlv? empty
| +--ro state
|   +--ro enable-flow-label        empty
|   +--ro flow-label-direction?    ipi-vpls-types:vpls_mpls_flow_label_direction_t
|   +--ro enable-static-flow-label? empty
|   +--ro enable-interface-parameter-tlv? empty
+--rw vpls-peers
| +--rw vpls-peer* [peer-address]
| | +--rw peer-address  -> ../config/peer-address
| | +--rw config
| | | +--rw peer-address?  inet:ipv4-address

```

---

---

```

| | | +--rw tunnel-name?      string
| | | +--rw tunnel-policy?    string {feature-list:HAVE_SERVICE_MAPPING}?
| | | +--rw tunnel-identifier? uint32
| | | +--rw peer-type?        ipi-vpls-types:vpls_peer_type_t
| | | +--rw vpls-type?        ipi-vpls-types:vpls_vc_type_t
| | +--ro state
| | | +--ro peer-address?     inet:ipv4-address
| | | +--ro tunnel-name?     string
| | | +--ro tunnel-policy?    string {feature-list:HAVE_SERVICE_MAPPING}?
| | | +--ro tunnel-identifier? uint32
| | | +--ro peer-type?        ipi-vpls-types:vpls_peer_type_t
| | | +--ro vpls-type?        ipi-vpls-types:vpls_vc_type_t
| | +--rw fec129s
| |   +--rw fec129* [attachment-group-identifier source-attachment-individual-identifier target-attachment-
individual-identifier]
| |     +--rw attachment-group-identifier      -> ../config/attachment-group-identifier
| |     +--rw source-attachment-individual-identifier  -> ../config/source-attachment-individual-identifier
| |     +--rw target-attachment-individual-identifier -> ../config/target-attachment-individual-identifier
| |     +--rw config
| |       | +--rw attachment-group-identifier?      string
| |       | +--rw source-attachment-individual-identifier? string
| |       | +--rw target-attachment-individual-identifier? string
| |       | +--rw tunnel-name?                      string
| |       | +--rw tunnel-policy?                    string {feature-list:HAVE_SERVICE_MAPPING}?
| |       | +--rw tunnel-identifier?                string
| |       +--ro state
| |         +--ro attachment-group-identifier?      string
| |         +--ro source-attachment-individual-identifier? string
| |         +--ro target-attachment-individual-identifier? string
| |         +--ro tunnel-name?                      string
| |         +--ro tunnel-policy?                    string {feature-list:HAVE_SERVICE_MAPPING}?
| |         +--ro tunnel-identifier?                string
| |     +--rw config!
| |     +--rw signaling-protocol-ldp      empty
| |     +--rw disable-mac-withdrawal?    empty
| |     +--rw vpls-ac-treatment-type?    ipi-vpls-types:cml_nsm_vpls_ac_treat_type_t
| |     +--rw vpls-encapsulation-type?    ipi-vpls-types:vpls_vc_type_t

```

---

---

```
| +--ro state
|   +--ro signaling-protocol-ldp  empty
|   +--ro disable-mac-withdrawal?  empty
|   +--ro vpls-ac-treatment-type?  ipi-vpls-types:cml_nsm_vpls_ac_treat_type_t
|   +--ro vpls-encapsulation-type?  ipi-vpls-types:vpls_vc_type_t
+--rw bgp-signaling {feature-list:HAVE_BGP_VPLS}?
| +--rw config!
| | +--rw signaling-protocol-bgp  empty
| | +--rw vpls-edge-identifier?  uint16
| | +--rw tunnel-policy?         string {feature-list:HAVE_SERVICE_MAPPING}?
| +--ro state
|   +--ro signaling-protocol-bgp  empty
|   +--ro vpls-edge-identifier?  uint16
|   +--ro tunnel-policy?         string {feature-list:HAVE_SERVICE_MAPPING}?
+--rw quality-of-service-profiles
| +--rw quality-of-service-profile* [profile-type profile-name] {feature-list:HAVE_QOS}?
|   +--rw profile-type  -> ../config/profile-type
|   +--rw profile-name  -> ../config/profile-name
|   +--rw config
|   | +--rw profile-type?  ipi-vpls-types:vpls_qos_map_profile_type_t
|   | +--rw profile-name?  string
|   +--ro state
|     +--ro profile-type?  ipi-vpls-types:vpls_qos_map_profile_type_t
|     +--ro profile-name?  string
+--ro mac-learning-table* [mac-address]
| +--ro mac-address  -> ../state/mac-address
| +--ro state
|   +--ro mac-address?          cml-data-types:cml_mac_addr_t
|   +--ro vpls-identifier?      uint32
|   +--ro learning-source-interface?  string
|   +--ro matched-vlan?         uint16
|   +--ro peer-address?         inet:ipv4-address
|   +--ro ageing-timeout?       uint32
+--ro peer-list* [peer-address]
| +--ro peer-address  -> ../state/peer-address
| +--ro state
```

```

|  +--ro peer-address?      inet:ipv4-address
|  +--ro vpls-identifier?   uint32
|  +--ro tunnel-label?     uint32
|  +--ro pseudowire-in-label? uint32
|  +--ro pseudowire-out-label? uint32
|  +--ro peer-state?       ipi-vpls-types:vpls_peer_state_t
|  +--ro pseudowire-status? ipi-vpls-types:vpls_pseudowire_status_t
|  +--ro peer-vpls-type?   ipi-vpls-types:vpls_vc_type_t
|  +--ro network-interface? string
|  +--ro signaling-protocol? ipi-vpls-types:vpls_signaling_type_t
+--ro access-interface-counters* [interface-name] {feature-list:HAVE_MPLS_STATS}?
|  +--ro interface-name  -> ../state/interface-name
|  +--ro state
|  +--ro interface-name?  -> /ipi-interface:interfaces/interface/name
|  +--ro vpls-identifier? uint32
|  +--ro service-template-name? string
|  +--ro in-packets?      uint64
|  +--ro in-bytes?       uint64
|  +--ro out-packets?    uint64
|  +--ro out-bytes?      uint64
+--ro network-interface-counters* [peer-address] {feature-list:HAVE_MPLS_STATS}?
  +--ro peer-address  -> ../state/peer-address
  +--ro state
    +--ro peer-address?  inet:ipv4-address
    +--ro vpls-identifier? uint32
    +--ro peer-state?    ipi-vpls-types:vpls_peer_state_t
    +--ro interface-name? -> /ipi-interface:interfaces/interface/name
    +--ro in-packets?    uint64
    +--ro in-bytes?     uint64
    +--ro out-packets?  uint64
    +--ro out-bytes?    uint64

```

rpcs:

```

+---x clear-mpls-vpls-name-statistics-port-type {feature-list:HAVE_MPLS_STATS,feature-list:HAVE_VPLS}?
|  +---w input
|  +---w port-type      ipi-vpls-types:vpls_port_type_t

```

---

```

| +---w port-circuit-name  string
+---x clear-mpls-vpls-name-statistics-network-port-peer {feature-list:HAVE_MPLS_STATS,feature-
list:HAVE_VPLS}?
| +---w input
|   +---w port-circuit-name  string
|   +---w vc-circuit-type    ipi-vpls-types:vpls_peer_address_type_t
+---x clear-mpls-vpls-name-statistics-network-port-spoke {feature-list:HAVE_MPLS_STATS,feature-
list:HAVE_VPLS}?
| +---w input
|   +---w port-circuit-name  string
|   +---w vc-circuit-type    ipi-vpls-types:vpls_spoke_vc_type_t
+---x clear-mpls-vpls-name-statistics-access-port {feature-list:HAVE_MPLS_STATS,feature-list:HAVE_VPLS}?
| +---w input
|   +---w port-circuit-name  string
|   +---w vc-interface-name  string
|   +---w vc-access-type     ipi-vpls-types:vpls_mpls_access_type_t
+---x clear-mpls-vpls-name-statistics {feature-list:HAVE_VPLS,feature-list:HAVE_MPLS_STATS}?
| +---w input
|   +---w vpls-circuit-name  string
+---x clear-mpls-vpls-mac-addresses-for-instance {feature-list:HAVE_VPLS}?
| +---w input
|   +---w name  string
+---x clear-mpls-vpls-mac-addresses-all {feature-list:HAVE_VPLS}?

```

---

## module: ipi-l2vpn-vpws

```

+--rw vpws
  +--rw interfaces
    | +--rw interface* [name]
    |   +--rw name          -> ../config/name
    |   +--rw config
    |     | +--rw name? -> /ipi-interface:interfaces/interface/name
    |     +--ro state
    |     | +--ro name? -> /ipi-interface:interfaces/interface/name
    |     +--rw pseudowire-modes
    |       | +--rw pseudowire-mode* [service-template]

```

```

| | +--rw service-template -> ../config/service-template
| | +--rw config
| | | +--rw service-template? string
| | | +--rw mode ipi-vpws-types:vpws_mpls_vcmode_t
| | +--ro state
| | +--ro service-template? string
| | +--ro mode ipi-vpws-types:vpws_mpls_vcmode_t
| +--rw vpws-access {feature-list:HAVE_SUBINTERFACE}?
| | +--rw config!
| | | +--rw enable empty
| | | +--rw enable-revertive-mode? empty
| | +--ro state
| | | +--ro enable empty
| | | +--ro enable-revertive-mode? empty
| | +--rw bindings
| | +--rw binding* [vpws-name]
| | +--rw vpws-name -> ../config/vpws-name
| | +--rw config
| | | +--rw vpws-name? string
| | | +--rw pseudowire-link-mode ipi-vpws-types:vpws_mpls_vclinkmode_t
| | +--ro state
| | +--ro vpws-name? string
| | +--ro pseudowire-link-mode ipi-vpws-types:vpws_mpls_vclinkmode_t
| +--rw service-template-mappings
| +--rw service-template-mapping* [pseudowire-name]
| +--rw pseudowire-name -> ../config/pseudowire-name
| +--rw config
| | +--rw pseudowire-name? string
| | +--rw service-template-name -> /ipi-mpls:mpls/l2vpn/customer-service-templates/customer-service-
template/name
| | +--rw pseudowire-link-mode ipi-vpws-types:vpws_mpls_vclinkmode_t
| | +--rw cos-to-queue-profile-name? string {feature-list:HAVE_QOS_MAPPING_PROFILE}?
| | +--rw queue-to-cos-profile-name? string {feature-list:HAVE_QOS_MAPPING_PROFILE,feature-
list:NOT_HAVE_CUSTOM1_MPLS}?
| +--ro state
| +--ro pseudowire-name? string

```

```

|      +--ro service-template-name    -> /ipi-mpls:mpls/l2vpn/customer-service-templates/customer-service-
template/name
|      +--ro pseudowire-link-mode     ipi-vpws-types:vpws_mpls_vclinkmode_t
|      +--ro cos-to-queue-profile-name? string {feature-list:HAVE_QOS_MAPPING_PROFILE}?
|      +--ro queue-to-cos-profile-name? string {feature-list:HAVE_QOS_MAPPING_PROFILE,feature-
list:NOT_HAVE_CUSTOM1_MPLS}?
+--rw static-forwarding
| +--rw forwarding-information-bases
|   +--rw forwarding-information-base* [pseudowire-identifier]
|     +--rw pseudowire-identifier    -> ../config/pseudowire-identifier
|     +--rw config
|       | +--rw pseudowire-identifier? -> /ipi-network-instance:network-instances/network-instance/vpws-instance/
pseudowires/pseudowire/config/pseudowire-identifier
|       | +--rw incoming-label       uint32
|       | +--rw outgoing-label       uint32
|       | +--rw nexthop-address      inet:ip-address
|       | +--rw provider-interface-name -> /ipi-interface:interfaces/interface/name
|       | +--rw access-interface-name -> /vpws/interfaces/interface/name
|       +--ro state
|         +--ro pseudowire-identifier? -> /ipi-network-instance:network-instances/network-instance/vpws-instance/
pseudowires/pseudowire/config/pseudowire-identifier
|         +--ro incoming-label       uint32
|         +--ro outgoing-label       uint32
|         +--ro nexthop-address      inet:ip-address
|         +--ro provider-interface-name -> /ipi-interface:interfaces/interface/name
|         +--ro access-interface-name -> /vpws/interfaces/interface/name
+--ro global
+--ro state
+--ro counters
+--ro total-pseudowires?  uint32
+--ro active-pseudowires? uint32
+--ro inactive-pseudowires? uint32
+--ro oam-pseudowires?   uint32

augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance:
+--rw vpws-instance
+--rw pseudowires
| +--rw pseudowire* [pseudowire-identifier peer-address]

```

---

```

|  +--rw pseudowire-identifier  -> ../config/pseudowire-identifier
|  +--rw peer-address           -> ../config/peer-address
|  +--rw config
|  |  +--rw pseudowire-identifier?  uint32
|  |  +--rw peer-address?           ipi-vpws-types:vpws_ip_addr_t
|  +--ro state
|  |  +--ro pseudowire-identifier?   uint32
|  |  +--ro peer-address?           ipi-vpws-types:vpws_ip_addr_t
|  |  +--ro vc-admin-status?        ipi-vpws-types:vpws_mpls_vc_admin_status_t {feature-
list:HAVE_UNI_CLI}?
|  |  +--ro up-time?                yang:date-and-time
|  |  +--ro last-change-time?       yang:date-and-time
|  |  +--ro create-time?            yang:date-and-time
|  |  +--ro owner?                  ipi-vpws-types:vpws_mpls_vc_owner_t
|  |  +--ro non-te-mapping-direction? ipi-vpws-types:vpws_mpls_mapping_dir_t
|  |  +--ro remote-pseudowire-status? ipi-vpws-types:vpws_mpls_pw_status_t
|  |  +--ro pseudowire-state?       ipi-vpws-types:vpws_mpls_pw_state_t
|  |  +--ro pseudowire-index?       uint32
|  |  +--ro pseudowire-type?        ipi-vpws-types:vpws_mpls_pw_type_t
|  |  +--ro pseudowire-mode?        ipi-vpws-types:vpws_mpls_pw_mode_t
|  |  +--ro pseudowire-label?       uint32
|  |  +--ro tunnel-label?           uint32
|  |  +--ro network-interface-name?  string
|  |  +--ro customer-service-template-name? string
|  |  +--ro ldp-ecmp-svc?           string {feature-list:HAVE_MPLS_ECMP}?
|  |  +--ro rsvp-multipath-svc?     string {feature-list:HAVE_RSVP_MULTIPATH}?
|  |  +--ro down-reason?            cml-data-types:cml_line_t
|  +--rw default-tagged
|  |  +--rw config!
|  |  |  +--rw group-name?          string
|  |  |  +--rw group-identifier?    uint32
|  |  |  +--rw enable-control-word? empty
|  |  |  +--rw tunnel-name?         string
|  |  |  +--rw tunnel-policy?       string {feature-list:HAVE_SERVICE_MAPPING}?
|  |  |  +--rw tunnel-identifier?   uint32
|  |  |  +--rw enable-default-tagged-mode  empty
|  |  |  +--rw enable-flow-label?     empty

```

---

---

```

| | | +--rw flow-label-direction?      ipi-vpws-types:vpws_mpls_flow_label_direction_t
| | | +--rw enable-static-flow-label?   empty
| | | +--rw enable-interface-parameter-tlv? empty
| | | +--rw service-tpid?              ipi-vpws-types:vpws_svc_tpid_t
| | | +--rw enable-manual-pseudowire?   empty
| | | +--rw control-channel-type?       ipi-vpws-types:vpws_mpls_vccv_cc_type_t {feature-
list:HAVE_VCCV,feature-list:HAVE_CUSTOM1_MPLS_BFD}?
| | | +--rw control-verification-type?  ipi-vpws-types:vpws_mpls_vccv_cv_type_t {feature-
list:HAVE_VCCV,feature-list:HAVE_CUSTOM1_MPLS_BFD}?
| | +--ro state
| |   +--ro group-name?                string
| |   +--ro group-identifier?          uint32
| |   +--ro enable-control-word?       empty
| |   +--ro tunnel-name?              string
| |   +--ro tunnel-policy?            string {feature-list:HAVE_SERVICE_MAPPING}?
| |   +--ro tunnel-identifier?         uint32
| |   +--ro enable-default-tagged-mode  empty
| |   +--ro enable-flow-label?         empty
| |   +--ro flow-label-direction?      ipi-vpws-types:vpws_mpls_flow_label_direction_t
| |   +--ro enable-static-flow-label?   empty
| |   +--ro enable-interface-parameter-tlv? empty
| |   +--ro service-tpid?             ipi-vpws-types:vpws_svc_tpid_t
| |   +--ro enable-manual-pseudowire?   empty
| |   +--ro control-channel-type?       ipi-vpws-types:vpws_mpls_vccv_cc_type_t {feature-
list:HAVE_VCCV,feature-list:HAVE_CUSTOM1_MPLS_BFD}?
| |   +--ro control-verification-type?  ipi-vpws-types:vpws_mpls_vccv_cv_type_t {feature-
list:HAVE_VCCV,feature-list:HAVE_CUSTOM1_MPLS_BFD}?
|   +--rw tagged
|   +--rw config!
|   | +--rw group-name?                string
|   | +--rw group-identifier?          uint32
|   | +--rw enable-control-word?       empty
|   | +--rw tunnel-name?              string
|   | +--rw tunnel-policy?            string {feature-list:HAVE_SERVICE_MAPPING}?
|   | +--rw tunnel-identifier?         uint32
|   | +--rw enable-flow-label?         empty
|   | +--rw flow-label-direction?      ipi-vpws-types:vpws_mpls_flow_label_direction_t
|   | +--rw enable-static-flow-label?   empty

```

---

---

```

| | | +--rw enable-interface-parameter-tlv? empty
| | | +--rw enable-manual-pseudowire? empty
| | | +--rw enable-tagged-mode empty
| | | +--rw control-channel-type? ipi-vpws-types:vpws_mpls_vccv_cc_type_t {feature-
list:HAVE_VCCV,feature-list:HAVE_CUSTOM1_MPLS_BFD}?
| | | +--rw control-verification-type? ipi-vpws-types:vpws_mpls_vccv_cv_type_t {feature-
list:HAVE_VCCV,feature-list:HAVE_CUSTOM1_MPLS_BFD}?
| | +--ro state
| |   +--ro group-name? string
| |   +--ro group-identifier? uint32
| |   +--ro enable-control-word? empty
| |   +--ro tunnel-name? string
| |   +--ro tunnel-policy? string {feature-list:HAVE_SERVICE_MAPPING}?
| |   +--ro tunnel-identifier? uint32
| |   +--ro enable-flow-label? empty
| |   +--ro flow-label-direction? ipi-vpws-types:vpws_mpls_flow_label_direction_t
| |   +--ro enable-static-flow-label? empty
| |   +--ro enable-interface-parameter-tlv? empty
| |   +--ro enable-manual-pseudowire? empty
| |   +--ro enable-tagged-mode empty
| |   +--ro control-channel-type? ipi-vpws-types:vpws_mpls_vccv_cc_type_t {feature-
list:HAVE_VCCV,feature-list:HAVE_CUSTOM1_MPLS_BFD}?
| |   +--ro control-verification-type? ipi-vpws-types:vpws_mpls_vccv_cv_type_t {feature-
list:HAVE_VCCV,feature-list:HAVE_CUSTOM1_MPLS_BFD}?
| +--rw raw
|   +--rw config!
|     | +--rw group-name? string
|     | +--rw group-identifier? uint32
|     | +--rw enable-control-word? empty
|     | +--rw tunnel-name? string
|     | +--rw tunnel-policy? string {feature-list:HAVE_SERVICE_MAPPING}?
|     | +--rw tunnel-identifier? uint32
|     | +--rw enable-flow-label? empty
|     | +--rw flow-label-direction? ipi-vpws-types:vpws_mpls_flow_label_direction_t
|     | +--rw enable-static-flow-label? empty
|     | +--rw enable-interface-parameter-tlv? empty
|     | +--rw enable-raw-mode empty
|     | +--rw enable-manual-pseudowire? empty

```

---

```

|   | +--rw control-channel-type?      ipi-vpws-types:vpws_mpls_vccv_cc_type_t {feature-
list:HAVE_VCCV,feature-list:HAVE_CUSTOM1_MPLS_BFD}?
|   | +--rw control-verification-type? ipi-vpws-types:vpws_mpls_vccv_cv_type_t {feature-
list:HAVE_VCCV,feature-list:HAVE_CUSTOM1_MPLS_BFD}?
|   +--ro state
|     +--ro group-name?                string
|     +--ro group-identifier?          uint32
|     +--ro enable-control-word?       empty
|     +--ro tunnel-name?               string
|     +--ro tunnel-policy?              string {feature-list:HAVE_SERVICE_MAPPING}?
|     +--ro tunnel-identifier?         uint32
|     +--ro enable-flow-label?         empty
|     +--ro flow-label-direction?      ipi-vpws-types:vpws_mpls_flow_label_direction_t
|     +--ro enable-static-flow-label?  empty
|     +--ro enable-interface-parameter-tlv? empty
|     +--ro enable-raw-mode             empty
|     +--ro enable-manual-pseudowire?  empty
|     +--ro control-channel-type?      ipi-vpws-types:vpws_mpls_vccv_cc_type_t {feature-
list:HAVE_VCCV,feature-list:HAVE_CUSTOM1_MPLS_BFD}?
|     +--ro control-verification-type? ipi-vpws-types:vpws_mpls_vccv_cv_type_t {feature-
list:HAVE_VCCV,feature-list:HAVE_CUSTOM1_MPLS_BFD}?
+--ro access-interface-counters* [interface-name] {feature-list:HAVE_MPLS_STATS}?
| +--ro interface-name  -> ../state/interface-name
| +--ro state
|   +--ro interface-name?  -> /ipi-interface:interfaces/interface/name
|   +--ro pseudowire-identifier? uint32
|   +--ro service-template-name? string
|   +--ro in-packets?       uint64
|   +--ro in-bytes?         uint64
|   +--ro out-packets?     uint64
|   +--ro out-bytes?       uint64
+--ro network-interface-counters* [peer-address] {feature-list:HAVE_MPLS_STATS}?
  +--ro peer-address  -> ../state/peer-address
  +--ro state
    +--ro peer-address?    inet:ipv4-address
    +--ro pseudowire-identifier? uint32
    +--ro interface-name?  -> /ipi-interface:interfaces/interface/name
    +--ro in-packets?      uint64

```

---

```

+--ro in-bytes?          uint64
+--ro out-packets?      uint64
+--ro out-bytes?        uint64

```

## rpcs:

```

+---x pseudowire-trap-configuration {feature-list:HAVE_SNMP}?
| +---w input
|   +---w status-notification    boolean
|   +---w delete-notification    boolean
|   +---w configure-notification  cml-data-types:cml_enable_disable_t
+---x clear-mpls-l2-circuit-statistics {feature-list:HAVE_MPLS_STATS,feature-list:HAVE_MPLS_VC}?
| +---w input
|   +---w pseudowire-name    string
+---x clear-mpls-l2-circuit-port-statistics {feature-list:HAVE_MPLS_STATS,feature-list:HAVE_MPLS_VC}?
| +---w input
|   +---w port-type          ipi-vpws-types:vpws_mpls_port_type_t
|   +---w port-pseudowire-name  string
+---x pseudowire-manual-switchover {feature-list:HAVE_MPLS_VC}?
  +---w input
    +---w primary-pseudowire    string
    +---w secondary-pseudowire  string

```

## notifications:

```

+---n mpls-pseudowire-up
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro pseudowire-identifier?  uint32
| +--ro peer-address?     ipi-vpws-types:vpws_ip_addr_t
| +--ro instance-type?    ipi-network-instance-types:net_inst_type_t
| +--ro instance-name?    string
| +--ro pseudowire-state?  ipi-vpws-types:vpws_mpls_pw_state_t
+---n mpls-pseudowire-down
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro pseudowire-identifier?  uint32
| +--ro peer-address?     ipi-vpws-types:vpws_ip_addr_t

```

---

```

| +--ro instance-type?      ipi-network-instance-types:net_inst_type_t
| +--ro instance-name?     string
| +--ro pseudowire-state?  ipi-vpws-types:vpws_mpls_pw_state_t
+---n mpls-pseudowire-deleted
  +--ro severity?          cml-data-types:cml_notif_severity_t
  +--ro eventClass?        cml-data-types:cml_notif_class_t
  +--ro pseudowire-identifier? uint32
  +--ro peer-address?      ipi-vpws-types:vpws_ip_addr_t
  +--ro instance-type?     ipi-network-instance-types:net_inst_type_t
  +--ro instance-name?     string
  +--ro pseudowire-state?  ipi-vpws-types:vpws_mpls_pw_state_t

```

---

## module: ipi-lacp

```

+--rw lacp
  +--rw global
    | +--rw config
    | | +--rw system-priority? uint32
    | +--ro state
    | +--ro system-priority? uint32
    | +--ro system-id?      cml-data-types:cml_mac_addr_t
  +--rw debug
    | +--rw config
    | | +--rw options? ipi-lacp-types:lacp_debug_t
    | +--ro state
    | +--ro options?      ipi-lacp-types:lacp_debug_t
    | +--ro terminal-debug-status? ipi-lacp-types:lacp_debug_t
  +--ro aggregators
    | +--ro aggregator* [agg-name]
    | +--ro agg-name  -> ../state/agg-name
    | +--ro state
    | | +--ro agg-name?      string
    | | +--ro interface-index? uint32
    | | +--ro type?          ipi-lag-types:lag_aggregator_type_t
    | | +--ro mac-address?   cml-data-types:cml_mac_addr_t

```

---

```
| | +--ro rx-link-count?      yang:counter32
| | +--ro tx-link-count?      yang:counter32
| | +--ro individual-aggregator? ipi-lacp-types:lacp_individual_aggregator_t
| | +--ro aggregator-ready?    empty
| +--ro actor
| | +--ro state
| |   +--ro admin-key?        uint16
| |   +--ro oper-key?         uint16
| |   +--ro system-priority?   uint16
| |   +--ro system-id?        cml-data-types:cml_mac_addr_t
| +--ro partner
| | +--ro state
| |   +--ro oper-key?         uint16
| |   +--ro system-priority?   uint16
| |   +--ro system-id?        cml-data-types:cml_mac_addr_t
| +--ro members
|   +--ro member* [link-name]
|     +--ro link-name  -> ../state/link-name
|     +--ro state
|       | +--ro link-name?      string
|       | +--ro sync-state?     ipi-lacp-types:lacp_synchronization_type_t
|       | +--ro receive-state?  ipi-lacp-types:lacp_rcv_state_t
|       | +--ro periodic-transmission-state? ipi-lacp-types:lacp_periodic_tx_state_t
|       | +--ro mux-machine-state? ipi-lacp-types:lacp_mux_state_t
|       | +--ro admin-key?      uint16
|       | +--ro counters
|       |   +--ro lacp-out-pkts? yang:counter32
|       |   +--ro lacp-in-pkts?  yang:counter32
|       |   +--ro lacp-in-marker-pdu? yang:counter32
|       |   +--ro lacp-out-marker-pdu? yang:counter32
|       |   +--ro lacp-tx-errors? yang:counter32
|       |   +--ro lacp-rx-errors? yang:counter32
|       |   +--ro lacp-in-marker-pdu-response? yang:counter32
|       |   +--ro lacp-out-marker-pdu-response? yang:counter32
|       +--ro actor
|       | +--ro state
```

---

---

```
|      |  +--ro operational
|      |  |  +--ro activity?      ipi-lacp-types:lacp_activity_type_t
|      |  |  +--ro timeout?      ipi-lacp-types:lacp_timeout_type_t
|      |  |  +--ro aggregatable?  boolean
|      |  |  +--ro synchronization? ipi-lacp-types:lacp_synchronization_type_t
|      |  |  +--ro collecting?    boolean
|      |  |  +--ro distributing?  boolean
|      |  |  +--ro defaulted?    boolean
|      |  |  +--ro expired?      boolean
|      |  |  +--ro port-key?     uint16
|      |  +--ro admin
|      |  |  +--ro activity?      ipi-lacp-types:lacp_activity_type_t
|      |  |  +--ro timeout?      ipi-lacp-types:lacp_timeout_type_t
|      |  |  +--ro aggregatable?  boolean
|      |  |  +--ro synchronization? ipi-lacp-types:lacp_synchronization_type_t
|      |  |  +--ro collecting?    boolean
|      |  |  +--ro distributing?  boolean
|      |  |  +--ro defaulted?    boolean
|      |  |  +--ro expired?      boolean
|      |  |  +--ro port-key?     uint16
|      |  +--ro system-id?      cml-data-types:cml_mac_addr_t
|      |  +--ro system-priority? uint16
|      |  +--ro port-number?    uint16
|      |  +--ro port-priority?  uint16
|      +--ro partner
|          +--ro state
|              +--ro operational
|                  |  +--ro activity?      ipi-lacp-types:lacp_activity_type_t
|                  |  +--ro timeout?      ipi-lacp-types:lacp_timeout_type_t
|                  |  +--ro aggregatable?  boolean
|                  |  +--ro synchronization? ipi-lacp-types:lacp_synchronization_type_t
|                  |  +--ro collecting?    boolean
|                  |  +--ro distributing?  boolean
|                  |  +--ro defaulted?    boolean
|                  |  +--ro expired?      boolean
|                  |  +--ro system-id?     cml-data-types:cml_mac_addr_t
```

---

```

|         | +--ro system-priority?  uint16
|         | +--ro port-number?      uint16
|         | +--ro port-priority?    uint16
|         | +--ro port-key?         uint16
|         +--ro admin
|             +--ro activity?       ipi-lacp-types:lacp_activity_type_t
|             +--ro timeout?        ipi-lacp-types:lacp_timeout_type_t
|             +--ro aggregatable?   boolean
|             +--ro synchronization? ipi-lacp-types:lacp_synchronization_type_t
|             +--ro collecting?      boolean
|             +--ro distributing?   boolean
|             +--ro defaulted?      boolean
|             +--ro expired?        boolean
|             +--ro system-id?      cml-data-types:cml_mac_addr_t
|             +--ro system-priority? uint16
|             +--ro port-number?    uint16
|             +--ro port-priority?  uint16

```

+--rw interfaces

```

+--rw interface* [name]
  +--rw name          -> ../config/name
  +--rw config
  | +--rw name?      -> /ipi-interface:interfaces/interface/name
  +--ro state
  | +--ro name?     -> /ipi-interface:interfaces/interface/name
  +--rw member-aggregation
  | +--rw config
  | | +--rw port-priority?  uint32
  | | +--rw timeout?       ipi-lacp-types:lacp_timeout_type_t
  | | +--rw bridge-type?   ipi-lacp-types:lacp_bridgetype_t
  | | +--rw force-up?      empty
  | | +--rw agg-force-up?  empty
  | +--ro state
  |   +--ro port-priority?  uint32
  |   +--ro timeout?       ipi-lacp-types:lacp_timeout_type_t
  |   +--ro bridge-type?   ipi-lacp-types:lacp_bridgetype_t
  |   +--ro force-up?      empty

```

```

| +--ro agg-force-up?  empty
+--rw aggregator
  +--rw config
  +--ro state

```

rpcs:

```

+---x lacp-snmp-restart {feature-list:HAVE_SNMP}?
+---x clear-lacp-counters {feature-list:HAVE_LAGD}?
| +---w input
|   +---w aggregate-id  uint16
+---x lacp-terminal-debug-on {feature-list:HAVE_LAGD}?
| +---w input
|   +---w terminal-debug-options  ipi-lacp-types:lacp_debug_t
+---x lacp-terminal-debug-off {feature-list:HAVE_LAGD}?
  +---w input
    +---w terminal-debug-options  ipi-lacp-types:lacp_debug_t

```

---

## module: ipi-ldp

```

+--rw ldp
  +--rw global
  | +--rw config!
  | | +--rw ldp-instance          ipi-ldp-types:ldp_instance_t
  | | +--rw router-identifier?    inet:ipv4-address
  | | +--rw pseudowire-status-tlv?  boolean {feature-list:HAVE_MPLS_VC}?
  | | +--rw rlfa-ilm-optimization?  boolean
  | | +--rw entropy-label-capability-enable?  boolean {feature-list:NOT_HAVE_CUSTOM1_MPLS}?
  | | +--rw multicast-hello-disable?  empty
  | | +--rw advertise-label-for-default-route?  empty
  | | +--rw import-bgp-routes?      boolean

```

---

```

| | +--rw ldp-optimization?          boolean
| | +--rw explicit-null?            boolean
| | +--rw global-merge?            ipi-ldp-types:ldp_merge_capable_t
| | +--rw propagate-release?       boolean
| | +--rw fast-reroute?            empty {feature-list:HAVE_LDP_LFA}?
| | +--rw auto-targeted-session?    empty {feature-list:HAVE_LDP_LFA}?
| | +--rw prefer-tunnel-in-tunnel?  empty {feature-list:HAVE_LDP_TUNNELING}?
| +--ro state
| | +--ro ldp-instance              ipi-ldp-types:ldp_instance_t
| | +--ro router-identifier?        inet:ipv4-address
| | +--ro pseudowire-status-tlv?    boolean {feature-list:HAVE_MPLS_VC}?
| | +--ro rfa-ilm-optimization?     boolean
| | +--ro entropy-label-capability-enable?  boolean {feature-list:NOT_HAVE_CUSTOM1_MPLS}?
| | +--ro multicast-hello-disable?  empty
| | +--ro advertise-label-for-default-route? empty
| | +--ro import-bgp-routes?       boolean
| | +--ro ldp-optimization?        boolean
| | +--ro explicit-null?           boolean
| | +--ro global-merge?            ipi-ldp-types:ldp_merge_capable_t
| | +--ro propagate-release?       boolean
| | +--ro fast-reroute?            empty {feature-list:HAVE_LDP_LFA}?
| | +--ro auto-targeted-session?    empty {feature-list:HAVE_LDP_LFA}?
| | +--ro prefer-tunnel-in-tunnel?  empty {feature-list:HAVE_LDP_TUNNELING}?
| +--rw label-management
| | +--rw config
| | | +--rw control-mode?          ipi-ldp-types:ldp_controlmode_t
| | | +--rw retention-mode?        ipi-ldp-types:ldp_retention_mode_t
| | | +--rw advertisement-mode?    ipi-ldp-types:ldp_advertise_mode_t
| | +--ro state
| |   +--ro control-mode?          ipi-ldp-types:ldp_controlmode_t
| |   +--ro retention-mode?        ipi-ldp-types:ldp_retention_mode_t
| |   +--ro advertisement-mode?    ipi-ldp-types:ldp_advertise_mode_t
| +--rw timers
| | +--rw config
| | | +--rw hello-interval?        uint16
| | | +--rw hello-holdtime?        uint16

```

---

---

```
| | | +--rw keepalive-timeout?  uint16
| | | +--rw keepalive-interval?  uint16
| | +--ro state
| |   +--ro hello-interval?    uint16
| |   +--ro hello-holdtime?    uint16
| |   +--ro keepalive-timeout?  uint16
| |   +--ro keepalive-interval? uint16
| +--rw label-request-policy
| | +--rw config
| | | +--rw request-retry-timeout?  uint16
| | | +--rw request-retry?          boolean
| | | +--rw label-request-policy-ipv4? string
| | +--ro state
| |   +--ro request-retry-timeout?  uint16
| |   +--ro request-retry?          boolean
| |   +--ro label-request-policy-ipv4? string
| +--rw loop-detection-policy
| | +--rw config!
| | | +--rw loop-detection-enable  empty
| | | +--rw path-vector-limit?    uint32
| | | +--rw hop-count-limit?      uint32
| | +--ro state
| |   +--ro loop-detection-enable  empty
| |   +--ro path-vector-limit?    uint32
| |   +--ro hop-count-limit?      uint32
| +--rw session-protection {feature-list:HAVE_LDP_SESS_PROT}?
| | +--rw config!
| | | +--rw session-protection-enable  empty
| | | +--rw duration?                  ipi-ldp-types:ldp_sess_prot_duration_t
| | | +--rw session-protection-prefix-list-name? ipi-ldp-types:ldp_sess_prot_pfx_lst_t
| | +--ro state
| |   +--ro session-protection-enable  empty
| |   +--ro duration?                  ipi-ldp-types:ldp_sess_prot_duration_t
| |   +--ro session-protection-prefix-list-name? ipi-ldp-types:ldp_sess_prot_pfx_lst_t
+--rw debug
| +--rw config
```

```
| | +--rw ldp? ipi-ldp-types:ldp_debug_t
| +--ro state
|   +--ro ldp? ipi-ldp-types:ldp_debug_t
|   +--ro terminal-debug-options? ipi-ldp-types:ldp_debug_t
+--rw graceful-restart {feature-list:HAVE_RESTART}?
| +--rw config!
| | +--rw enable ipi-ldp-types:ldp_gr_mode_t
| | +--rw neighbor-liveness-time? uint16
| | +--rw max-recovery-time? uint16
| +--ro state
|   +--ro enable ipi-ldp-types:ldp_gr_mode_t
|   +--ro neighbor-liveness-time? uint16
|   +--ro max-recovery-time? uint16
|   +--ro restart-count? uint32
+--ro ldp-tunnels {feature-list:HAVE_LDP_TUNNELING}?
| +--ro ldp-tunnel* [tunnel-endpoint]
|   +--ro tunnel-endpoint -> ../state/tunnel-endpoint
|   +--ro state
|     | +--ro tunnel-endpoint? cml-data-types:cml_ipv4_addr_prefix_t
|     +--ro tunnel-lists
|       +--ro tunnel-list* [tunnel-name]
|         +--ro tunnel-name -> ../state/tunnel-name
|         +--ro state
|           | +--ro tunnel-name? string
|           | +--ro cost? uint32
|           | +--ro owner? string
|           | +--ro status? string
|           | +--ro fec-count? uint8
|           +--ro fec-lists
|             +--ro fec-list* [fec-prefix]
|               +--ro fec-prefix -> ../state/fec-prefix
|               +--ro state
|                 +--ro fec-prefix? cml-data-types:cml_ipv4_addr_prefix_t
|                 +--ro upstream-peer? inet:ipv4-address
|                 +--ro in-label? string
|                 +--ro out-label? string
```

```

+--rw lfa {feature-list:HAVE_LDP_LFA}?
| +--ro fecs
|   +--ro fec* [prefix-address]
|     +--ro prefix-address  -> ../state/prefix-address
|     +--ro state
|       | +--ro prefix-address?  inet:ip-address
|       +--ro primary-paths
|         +--ro primary-path* [nexthop-address nexthop-interface-name]
|           +--ro nexthop-address      -> ../state/nexthop-address
|           +--ro nexthop-interface-name -> ../state/nexthop-interface-name
|           +--ro state
|             | +--ro nexthop-address?      inet:ip-address
|             | +--ro nexthop-interface-name? string
|             +--ro backup-path
|               +--ro state
|                 +--ro backup-address?      inet:ip-address
|                 +--ro backup-interface-name? string
+--rw transport-addresses
| +--rw transport-address* [label-space-identifier]
|   +--rw label-space-identifier  -> ../config/label-space-identifier
|   +--rw config
|     | +--rw label-space-identifier? ipi-ldp-types:ldp_label_space_identifier_t
|     | +--rw transport-address-ipv4?  inet:ipv4-address
|     +--ro state
|       +--ro label-space-identifier? ipi-ldp-types:ldp_label_space_identifier_t
|       +--ro transport-address-ipv4?  inet:ipv4-address
+--rw peer-authentication
| +--rw peer-authentication-lists
| | +--rw peer-authentication-list* [peer-address] {feature-list:HAVE_TCP_MD5SIG}?
| |   +--rw peer-address  -> ../config/peer-address
| |   +--rw config
| |     | +--rw peer-address?  ipi-ldp-types:ldp_auth_neighbor_type_t
| |     | +--rw password-type ipi-ldp-types:ldp_md5_encrypt_password_t
| |     | +--rw password      ipi-ldp-types:ldp_md5_password_t
| |     +--ro state
| |     +--ro peer-address?  ipi-ldp-types:ldp_auth_neighbor_type_t

```

```

| |   +--ro password-type   ipi-ldp-types:ldp_md5_encrypt_password_t
| |   +--ro password       ipi-ldp-types:ldp_md5_password_t
| +--rw authentication-exclusions
| | +--rw config
| | | +--rw peer-address*  inet:ipv4-address
| | +--ro state
| |   +--ro peer-address*  inet:ipv4-address
| +--rw authentication-groups
|   +--rw authentication-group* [group-name]
|     +--rw group-name    -> ../config/group-name
|     +--rw config
|     | +--rw group-name?   string
|     | +--rw prefix-list?  string
|     | +--rw authentication-group-passwords
|     |   +--rw authentication-group-password* [auth]
|     |     +--rw auth      -> ../config/auth
|     |     +--rw config
|     |       | +--rw auth?    ipi-ldp-types:ldp_auth_group_type_t
|     |       | +--rw password-type ipi-ldp-types:ldp_md5_encrypt_password_t
|     |       | +--rw password   ipi-ldp-types:ldp_md5_password_t
|     |       | +--ro state
|     |       |   +--ro auth?    ipi-ldp-types:ldp_auth_group_type_t
|     |       |   +--ro password-type ipi-ldp-types:ldp_md5_encrypt_password_t
|     |       |   +--ro password   ipi-ldp-types:ldp_md5_password_t
|     |       +--ro state
|     |       +--ro group-name?  string
|     |       +--ro prefix-list? string
| +--rw label-mapping-access-lists
|   +--rw label-mapping-access-list* [peer-access-control-list-name prefix-access-control-list-name]
|     +--rw peer-access-control-list-name  -> ../config/peer-access-control-list-name
|     +--rw prefix-access-control-list-name -> ../config/prefix-access-control-list-name
|     +--rw config
|     | +--rw prefix-access-control-list-name? string
|     | +--rw peer-access-control-list-name?  string
|     +--ro state
|     | +--ro prefix-access-control-list-name? string

```

---

```
| | +--ro peer-access-control-list-name?  string
| | +--ro advertisement-type?            ipi-ldp-types:ldp_advertisement_type_t
| +--ro statistics
|   +--ro state
|     +--ro label-deny-mapping?  uint32
|     +--ro label-deny-request?  uint32
+--rw tcp-mss-lists
| +--rw tcp-mss-list* [peer-address]
|   +--rw peer-address  -> ../config/peer-address
|   +--rw config
|     | +--rw peer-address?  ipi-ldp-types:ldp_neighbor_type_t
|     | +--rw tcp-mss-range?  uint32
|     +--ro state
|       +--ro peer-address?  ipi-ldp-types:ldp_neighbor_type_t
|       +--ro tcp-mss-range?  uint32
+--rw interfaces
| +--rw interface* [name]
|   +--rw name          -> ../config/name
|   +--rw config
|     | +--rw name?          -> /ipi-interface:interfaces/interface/name
|     | +--rw enable-ldp-ipv4?      empty
|     | +--rw multicast-hello-disable?  empty
|     | +--rw maximum-pdu-length?    uint32
|     | +--rw ldp-igp-sync-delay-interval?  uint32
|     +--ro state
|       | +--ro name?          -> /ipi-interface:interfaces/interface/name
|       | +--ro enable-ldp-ipv4?      empty
|       | +--ro multicast-hello-disable?  empty
|       | +--ro maximum-pdu-length?    uint32
|       | +--ro ldp-igp-sync-delay-interval?  uint32
|       | +--ro primary-address-ipv4?  string
|       | +--ro primary-address-ipv6?  string
|       +--ro counters
|         +--ro packets
|           | +--ro received
|           | | +--ro notification?  yang:counter32
```

---

---

```
| | | | +--ro hello?          yang:counter32
| | | | +--ro initialization? yang:counter32
| | | | +--ro keepalive?     yang:counter32
| | | | +--ro address-message? yang:counter32
| | | | +--ro address-withdraw? yang:counter32
| | | | +--ro label-mapping?  yang:counter32
| | | | +--ro label-request?  yang:counter32
| | | | +--ro label-withdraw? yang:counter32
| | | | +--ro label-release?  yang:counter32
| | | | +--ro request-abort?  yang:counter32
| | | +--ro sent
| | |   +--ro notification?   yang:counter32
| | |   +--ro hello?         yang:counter32
| | |   +--ro initialization? yang:counter32
| | |   +--ro keepalive?     yang:counter32
| | |   +--ro address-message? yang:counter32
| | |   +--ro address-withdraw? yang:counter32
| | |   +--ro label-mapping?  yang:counter32
| | |   +--ro label-request?  yang:counter32
| | |   +--ro label-withdraw? yang:counter32
| | |   +--ro label-release?  yang:counter32
| | |   +--ro request-abort?  yang:counter32
| | +--ro events
| |   +--ro ldp-shutdown-notification-received? yang:counter32
| |   +--ro ldp-shutdown-notification-sent?    yang:counter32
| |   +--ro ldp-sessions-attempted?           yang:counter32
| |   +--ro ldp-session-rejected-no-hello-errors? yang:counter32
| |   +--ro ldp-session-rejected-advertisement-errors? yang:counter32
| |   +--ro ldp-session-rejected-maximum-pdu-errors? yang:counter32
| |   +--ro ldp-session-rejected-label-range-errors? yang:counter32
| |   +--ro ldp-bad-ldp-identifier-errors?      yang:counter32
| |   +--ro ldp-bad-pdu-length-errors?         yang:counter32
| |   +--ro ldp-bad-message-length-errors?     yang:counter32
| |   +--ro ldp-bad-tlv-length-errors?        yang:counter32
| |   +--ro ldp-malformed-tlv-value-errors?   yang:counter32
| |   +--ro ldp-keepalive-timer-expired-errors? yang:counter32
```

```

|  +--rw hello-timers
|  |  +--rw config
|  |  |  +--rw hello-interval?  uint16
|  |  |  +--rw hello-holdtime?  uint16
|  |  +--ro state
|  |  |  +--ro hello-interval?  uint16
|  |  |  +--ro hello-holdtime?  uint16
|  +--rw session-timers
|  |  +--rw config
|  |  |  +--rw keepalive-timeout?  uint16
|  |  |  +--rw keepalive-interval?  uint16
|  |  +--ro state
|  |  |  +--ro keepalive-timeout?  uint16
|  |  |  +--ro keepalive-interval?  uint16
|  +--rw label-management
|  |  +--rw config
|  |  |  +--rw interface-advertisement-mode?  ipi-ldp-types:ldp_advertise_mode_t
|  |  |  +--rw interface-retention-mode?     ipi-ldp-types:ldp_retention_mode_t
|  |  +--ro state
|  |  |  +--ro interface-advertisement-mode?  ipi-ldp-types:ldp_advertise_mode_t
|  |  |  +--ro interface-retention-mode?     ipi-ldp-types:ldp_retention_mode_t
|  |  |  +--ro label-merge-capability?      ipi-ldp-types:ldp_label_merge_capability_t
|  |  |  +--ro ldp-identifier?              string
+--ro l2vpn
|  +--ro vpls-list* [vpls-identifier] {feature-list:HAVE_VPLS}?
|  |  +--ro vpls-identifier    -> ../state/vpls-identifier
|  |  +--ro state
|  |  |  +--ro vpls-identifier?  uint32
|  |  |  +--ro mesh-vc-count?   uint32
|  |  +--ro virtual-circuit-list* [neighbor-address]
|  |  |  +--ro neighbor-address  -> ../state/neighbor-address
|  |  |  +--ro state
|  |  |  |  +--ro virtual-circuit-identifier?  uint32
|  |  |  |  +--ro neighbor-address?          inet:ipv4-address
|  |  |  |  +--ro virtual-circuit-state?     ipi-ldp-types:ldp_vc_state_t
|  |  |  |  +--ro local-pw-status-capability?  uint32

```

---

```
| |   +--ro remote-pw-status-capability?   uint32
| |   +--ro current-pw-status-tlv?       uint32
| |   +--ro local-pseudowire-status?     string
| |   +--ro remote-pseudowire-status?    string
| |   +--ro virtual-circuit-label-sent?   uint32
| |   +--ro virtual-circuit-label-received? uint32
| +--ro state
| | +--ro counters {feature-list:HAVE_VPLS}?
| |   +--ro total-vpls-instances?        yang:counter32
| |   +--ro total-virtual-circuit-instances? yang:counter32
| |   +--ro active-virtual-circuit-instances? yang:counter32
| |   +--ro inactive-virtual-circuit-instances? yang:counter32
| +--ro virtual-circuit-list* [virtual-circuit-identifier] {feature-list:HAVE_MPLS_VC}?
|   +--ro virtual-circuit-identifier -> ../state/virtual-circuit-identifier
|   +--ro state
|     +--ro virtual-circuit-identifier?   uint32
|     +--ro neighbor-address?            inet:ipv4-address
|     +--ro virtual-circuit-state?       ipi-ldp-types:ldp_vc_state_t
|     +--ro local-pw-status-capability?   uint32
|     +--ro remote-pw-status-capability?  uint32
|     +--ro current-pw-status-tlv?       uint32
|     +--ro local-pseudowire-status?     string
|     +--ro remote-pseudowire-status?    string
|     +--ro virtual-circuit-label-sent?   uint32
|     +--ro virtual-circuit-label-received? uint32
+--rw targeted-peers
| +--rw global-timers
| | +--rw config
| | | +--rw targeted-global-hello-interval? uint16
| | | +--rw targeted-global-hello-holdtime? uint16
| | +--ro state
| |   +--ro targeted-global-hello-interval? uint16
| |   +--ro targeted-global-hello-holdtime? uint16
| +--rw targeted-peer* [target-address]
|   +--rw target-address -> ../config/target-address
|   +--rw config
```

---

---

```
| | +--rw target-address? ipi-ldp-types:ldp_ip_addr_t
| | +--rw hello-interval? uint16
| | +--rw hello-holdtime? uint16
| +--ro state
|   +--ro target-address? ipi-ldp-types:ldp_ip_addr_t
|   +--ro hello-interval? uint16
|   +--ro hello-holdtime? uint16
|   +--ro counters
|     +--ro packets
|       +--ro received
|         +--ro notification? yang:counter32
|         +--ro hello? yang:counter32
|         +--ro initialization? yang:counter32
|         +--ro keepalive? yang:counter32
|         +--ro address-message? yang:counter32
|         +--ro address-withdraw? yang:counter32
|         +--ro label-mapping? yang:counter32
|         +--ro label-request? yang:counter32
|         +--ro label-withdraw? yang:counter32
|         +--ro label-release? yang:counter32
|         +--ro request-abort? yang:counter32
|       +--ro sent
|         +--ro notification? yang:counter32
|         +--ro hello? yang:counter32
|         +--ro initialization? yang:counter32
|         +--ro keepalive? yang:counter32
|         +--ro address-message? yang:counter32
|         +--ro address-withdraw? yang:counter32
|         +--ro label-mapping? yang:counter32
|         +--ro label-request? yang:counter32
|         +--ro label-withdraw? yang:counter32
|         +--ro label-release? yang:counter32
|         +--ro request-abort? yang:counter32
|     +--ro events
|       +--ro ldp-shutdown-notification-received? yang:counter32
|       +--ro ldp-shutdown-notification-sent? yang:counter32
```

---

```

|   +--ro ldp-sessions-attempted?          yang:counter32
|   +--ro ldp-session-rejected-no-hello-errors? yang:counter32
|   +--ro ldp-session-rejected-advertisement-errors? yang:counter32
|   +--ro ldp-session-rejected-maximum-pdu-errors? yang:counter32
|   +--ro ldp-session-rejected-label-range-errors? yang:counter32
|   +--ro ldp-bad-ldp-identifier-errors?      yang:counter32
|   +--ro ldp-bad-pdu-length-errors?         yang:counter32
|   +--ro ldp-bad-message-length-errors?    yang:counter32
|   +--ro ldp-bad-tlv-length-errors?        yang:counter32
|   +--ro ldp-malformed-tlv-value-errors?    yang:counter32
|   +--ro ldp-keepalive-timer-expired-errors? yang:counter32

```

```
+--ro peers
```

```

+--ro peer* [peer-address]
  +--ro peer-address      -> ../state/peer-address
  +--ro adjacency-list* [adjacency-prefix]
  | +--ro adjacency-prefix -> ../state/adjacency-prefix
  | +--ro state
  |   +--ro adjacency-prefix? inet:ipv4-address
  |   +--ro is-targeted-peer? boolean
  |   +--ro name?             -> /ipi-interface:interfaces/interface/name
  |   +--ro local-address?   inet:ipv4-address
  +--ro received-label-list* [fec-prefix]
  | +--ro fec-prefix -> ../state/fec-prefix
  | +--ro state
  |   +--ro fec-prefix? cml-data-types:cml_ipv4_addr_prefix_t
  |   +--ro label?     string
  +--ro sent-label-list* [fec-prefix]
  | +--ro fec-prefix -> ../state/fec-prefix
  | +--ro state
  |   +--ro fec-prefix? cml-data-types:cml_ipv4_addr_prefix_t
  |   +--ro label?     string
  +--ro state
    +--ro peer-address?          inet:ipv4-address
    +--ro ldp-identifier?        string
    +--ro label-space?          uint16
    +--ro keepalive-timeout?     uint32

```

---

```

+--ro session-up-time?          string
+--ro session-state?           ipi-ldp-types:ldp_session_state_t
+--ro session-role?            ipi-ldp-types:ldp_session_role_t
+--ro advertisement-mode?      ipi-ldp-types:ldp_advertise_mode_t
+--ro retention-mode?          ipi-ldp-types:ldp_retention_mode_t
+--ro tcp-established?          ipi-ldp-types:ldp_tcp_status_t
+--ro ldp-interface-name?      string
+--ro discontinuity-time?      uint32
+--ro unknown-message-type-errors?  uint32
+--ro unknown-tlv-type-errors?  uint32
+--ro initialization-session-threshold-limit?  uint32
+--ro entity-path-vector-limit?  uint32
+--ro peer-path-vector-limit?  uint32
+--ro session-protection-status? ipi-ldp-types:ldp_sess_prot_status_t {feature-
list:HAVE_LDP_SESS_PROT}?

```

rpcs:

```

+---x clear-ldp-statistics {feature-list:HAVE_LDPD}?
+---x clear-ldp-statistics-advertise-labels {feature-list:HAVE_LDPD}?
+---x clear-ldp-statistics-advertise-labels-prefix {feature-list:HAVE_LDPD}?
| +---w input
|   +---w prefix  string
+---x clear-ldp-statistics-advertise-labels-prefix-peer {feature-list:HAVE_LDPD}?
| +---w input
|   +---w prefix  string
|   +---w peer    string
+---x clear-ldp-session-all {feature-list:HAVE_LDPD}?
+---x clear-ldp-session-ipv4 {feature-list:HAVE_LDPD}?
| +---w input
|   +---w addr   inet:ipv4-address
+---x clear-ldp-adjacency-all {feature-list:HAVE_LDPD}?
+---x clear-ldp-adjacency-ipv4 {feature-list:HAVE_LDPD}?
| +---w input
|   +---w addr   inet:ipv4-address
+---x snmp-restart-ldp {feature-list:HAVE_SNMP}?
+---x ldp-terminal-debug-on {feature-list:HAVE_LDPD}?
| +---w input

```

---

```

| +---w terminal-debug-options ipi-ldp-types:ldp_debug_t
+---x ldp-terminal-debug-off {feature-list:HAVE_LDPPD}?
| +---w input
| +---w terminal-debug-options ipi-ldp-types:ldp_debug_t
+---x restart-ldp-graceful {feature-list:HAVE_RESTART}?

```

notifications:

```

+---n mpls-ldp-session-up
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro peer-address?     inet:ipv4-address
| +--ro session-state?    ipi-ldp-types:ldp_session_state_t
| +--ro discontinuity-time? uint32
| +--ro unknown-message-type-errors? uint32
| +--ro unknown-tlv-type-errors?  uint32
+---n mpls-ldp-session-down
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro peer-address?     inet:ipv4-address
| +--ro session-state?    ipi-ldp-types:ldp_session_state_t
| +--ro discontinuity-time? uint32
| +--ro unknown-message-type-errors? uint32
| +--ro unknown-tlv-type-errors?  uint32
+---n mpls-ldp-init-session-threshold-exceeded
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro peer-address?     inet:ipv4-address
| +--ro initialization-session-threshold-limit? uint32
+---n mpls-ldp-path-vector-limit-mismatch
  +--ro severity?          cml-data-types:cml_notif_severity_t
  +--ro eventClass?       cml-data-types:cml_notif_class_t
  +--ro peer-address?     inet:ipv4-address
  +--ro entity-path-vector-limit? uint32
  +--ro peer-path-vector-limit?  uint32

```

---

## module: ipi-lldpv2

```
+--rw lldp
  +--rw global
    | +--rw config
    | | +--rw enable?          empty
    | | +--rw notification-interval? uint16 {feature-list:HAVE_SNMP}?
    | | +--ro state
    | | | +--ro enable?          empty
    | | | +--ro notification-interval? uint16 {feature-list:HAVE_SNMP}?
    | | | +--ro system-capabilities-enabled? cml-data-types:cml_line_t
    | | | +--ro host-name-information? string
    | | | +--ro counters
    | | |   +--ro remote-inserts? yang:counter32
    | | |   +--ro remote-deletes? yang:counter32
    | | |   +--ro remote-drops? yang:counter32
    | | |   +--ro remote-ageouts? yang:counter32
    | | +--rw global-tlv-control
    | | | +--rw global-basic-management
    | | | | +--rw config
    | | | | | +--rw port-description? empty
    | | | | | +--rw system-description? empty
    | | | | | +--rw system-name? empty
    | | | | | +--rw system-capabilities? empty
    | | | | | +--rw management-address? empty
    | | | | +--ro state
    | | | | | +--ro port-description? empty
    | | | | | +--ro system-description? empty
    | | | | | +--ro system-name? empty
    | | | | | +--ro system-capabilities? empty
    | | | | | +--ro management-address? empty
    | | +--rw global-ieee-8021-org-specific
    | | | +--rw config
    | | | | +--rw port-vlan-id? empty
    | | | | +--rw port-protocol-vlan-id? empty
```

```

| | | +--rw vlan-name?      empty
| | | +--rw protocol-identifier?  empty
| | | +--rw vid-digest?      empty
| | | +--rw management-vlan-id?  empty
| | | +--rw link-aggregation?  empty
| | | +--rw dcb-exchange?      empty {feature-list:HAVE_DCB}?
| | +--ro state
| |   +--ro port-vlan-id?      empty
| |   +--ro port-protocol-vlan-id?  empty
| |   +--ro vlan-name?        empty
| |   +--ro protocol-identifier?  empty
| |   +--ro vid-digest?        empty
| |   +--ro management-vlan-id?  empty
| |   +--ro link-aggregation?  empty
| |   +--ro dcb-exchange?      empty {feature-list:HAVE_DCB}?
| +--rw global-ieee-8023-org-specific
| | +--rw config
| | | +--rw mac-phy?      empty
| | | +--rw max-mtu-size?  empty
| | +--ro state
| |   +--ro mac-phy?      empty
| |   +--ro max-mtu-size?  empty
| +--rw management-if
| | +--rw config
| | | +--rw locally-assigned-chassis-id?  string
| | +--ro state
| |   +--ro locally-assigned-chassis-id?  string
+--rw debug
| +--rw config
| | +--rw options?  ipi-ldp-types:lldp_debug_t
| +--ro state
| | +--ro options?      ipi-ldp-types:lldp_debug_t
| | +--ro terminal-debug-status?  ipi-ldp-types:lldp_debug_t
+--rw interfaces
  +--rw interface* [name]
    +--rw name      -> ../config/name

```

---

```
+--rw config
| +--rw name?          -> /ipi-interface:interfaces/interface/name
| +--rw disable-ldp-agent? empty
| +--rw agent-circuit-id? string
| +--rw med-device-type? ipi-ldp-types:lldp_meddev_t
| +--rw local-name?    string
+--ro state
| +--ro name?          -> /ipi-interface:interfaces/interface/name
| +--ro disable-ldp-agent? empty
| +--ro agent-circuit-id? string
| +--ro med-device-type? ipi-ldp-types:lldp_meddev_t
| +--ro local-name?    string
+--ro neighbors
| +--ro agent* [agent-type]
|   +--ro agent-type ipi-ldp-types:lldp_agent_t
|   +--ro neighbor* [mac-address]
|     +--ro mac-address -> ../state/mac-address
|     +--ro state
|       +--ro mac-address?          cml-data-types:cml_mac_addr_t
|       +--ro system-name?          string
|       +--ro chassis-component?    string
|       +--ro chassis-id-type?      uint8
|       +--ro port-component?       string
|       +--ro port-id?              string
|       +--ro port-description?     string
|       +--ro port-sub-type?        uint16
|       +--ro interface-alias?      string
|       +--ro interface-agent-circuit-id? string
|       +--ro ttl?                  uint16
|       +--ro interface-number?     uint32
|       +--ro interface-number-sub-type? string
|       +--ro port-vlan-id?         uint16
|       +--ro pp-vlanid?            uint16
|       +--ro protocol?             ipi-ldp-types:lldp_protoid_t
|       +--ro vid-usage-digest?     uint32
|       +--ro management-vlan?      uint16
```

---

```
|   +--ro auto-negotiation-support?   uint8
|   +--ro auto-negotiation-capability? uint16
|   +--ro operational-mau-type?       uint16
|   +--ro link-aggregate-capability?  cml-data-types:cml_line_t
|   +--ro link-aggregate-id?          uint32
|   +--ro max-frame-size?             uint16
|   +--ro system-description?         string
|   +--ro system-capabilities?        cml-data-types:cml_line_t
|   +--ro system-capabilities-enabled? cml-data-types:cml_line_t
|   +--ro vlan-list* [vlan-id]
|     | +--ro vlan-id   uint16
|     | +--ro vlan-name? string
|   +--ro management-list* [address]
|     +--ro address      string
|     +--ro address-sub-type? cml-data-types:cml_line_t
|     +--ro interface-number-sub-type? string
|     +--ro interface-number?   uint32
|     +--ro oid?                string
```

```
+--rw agents
```

```
  +--rw agent* [agent-type]
```

```
    +--rw agent-type  -> ../config/agent-type
```

```
    +--rw config
```

```
      | +--rw agent-type?  ipi-ldp-types:lldp_agent_t
```

```
      | +--rw enable-tx-rx? ipi-ldp-types:lldp_enable_t
```

```
      | +--rw dcbx-enable? empty {feature-list:HAVE_DCB}?
```

```
    +--ro state
```

```
      | +--ro agent-type?  ipi-ldp-types:lldp_agent_t
```

```
      | +--ro enable-tx-rx? ipi-ldp-types:lldp_enable_t
```

```
      | +--ro dcbx-enable? empty {feature-list:HAVE_DCB}?
```

```
    +--rw transmit
```

```
      | +--rw config
```

```
        | | +--rw reinit-delay?          uint32
```

```
        | | +--rw message-tx-interval?   uint32
```

```
        | | +--rw message-tx-hold-multiplier? uint32
```

```
        | | +--rw message-fast-tx?       uint32
```

```
        | | +--rw tx-credit-max?         uint32
```

---

```
| | +--rw tx-fast-init?          uint32
| +--ro state
|   +--ro reinit-delay?         uint32
|   +--ro message-tx-interval?  uint32
|   +--ro message-tx-hold-multiplier? uint32
|   +--ro message-fast-tx?      uint32
|   +--ro tx-credit-max?        uint32
|   +--ro tx-fast-init?         uint32
|   +--ro tx-ttl?               uint16
|   +--ro counters
|     +--ro frames-out?         yang:counter32
+--rw receive
| +--rw config
| | +--rw neighbor-limit?      uint32
| | +--rw neighbor-timer?     uint32
| | +--rw port-mac?            cml-data-types:cml_mac_addr_t
| | +--rw port-timer?          uint32
| +--ro state
|   +--ro neighbor-limit?      uint32
|   +--ro neighbor-timer?     uint32
|   +--ro port-mac?            cml-data-types:cml_mac_addr_t
|   +--ro port-timer?          uint32
|   +--ro frames-aged-out?     yang:counter32
|   +--ro frames-discarded?    yang:counter32
|   +--ro frames-invalid?      yang:counter32
|   +--ro frames-valid?        yang:counter32
|   +--ro tlvs-discarded?      yang:counter32
|   +--ro tlvs-unrecognized?   yang:counter32
+--rw agent-tlv
| +--rw config
| | +--rw port-address?        ipi-lldp-types:lldp_mgmt_addr_t
| | +--rw chassis-id?          ipi-lldp-types:lldp_chassis_t
| | +--rw port-id?             ipi-lldp-types:lldp_port_t
| +--ro state
|   +--ro port-address?        ipi-lldp-types:lldp_mgmt_addr_t
|   +--ro chassis-id?          ipi-lldp-types:lldp_chassis_t
```

---

```
|  +--ro port-id?      ipi-ldp-types:lldp_port_t
+--rw tlv-control
  +--rw basic-management
    | +--rw config
    | | +--rw port-description?  ipi-ldp-types:lldp_tlv_select_type
    | | +--rw system-description? ipi-ldp-types:lldp_tlv_select_type
    | | +--rw system-name?      ipi-ldp-types:lldp_tlv_select_type
    | | +--rw system-capabilities? ipi-ldp-types:lldp_tlv_select_type
    | | +--rw management-address? ipi-ldp-types:lldp_tlv_select_type
    | +--ro state
    | +--ro port-description?  ipi-ldp-types:lldp_tlv_select_type
    | +--ro system-description? ipi-ldp-types:lldp_tlv_select_type
    | +--ro system-name?      ipi-ldp-types:lldp_tlv_select_type
    | +--ro system-capabilities? ipi-ldp-types:lldp_tlv_select_type
    | +--ro management-address? ipi-ldp-types:lldp_tlv_select_type
  +--rw ieee-8021-org-specific
    | +--rw config
    | | +--rw port-vlan-id?      ipi-ldp-types:lldp_tlv_select_type
    | | +--rw port-protocol-vlan-id? ipi-ldp-types:lldp_tlv_select_type
    | | +--rw vlan-name?        ipi-ldp-types:lldp_tlv_select_type
    | | +--rw protocol-identifier? ipi-ldp-types:lldp_tlv_select_type
    | | +--rw vid-digest?        ipi-ldp-types:lldp_tlv_select_type
    | | +--rw management-vlan-id? ipi-ldp-types:lldp_tlv_select_type
    | | +--rw link-aggregation?  ipi-ldp-types:lldp_tlv_select_type
    | | +--rw dcb-exchange?      ipi-ldp-types:lldp_tlv_select_type {feature-list:HAVE_DCB}?
    | +--ro state
    | +--ro port-vlan-id?      ipi-ldp-types:lldp_tlv_select_type
    | +--ro port-protocol-vlan-id? ipi-ldp-types:lldp_tlv_select_type
    | +--ro vlan-name?        ipi-ldp-types:lldp_tlv_select_type
    | +--ro protocol-identifier? ipi-ldp-types:lldp_tlv_select_type
    | +--ro vid-digest?        ipi-ldp-types:lldp_tlv_select_type
    | +--ro management-vlan-id? ipi-ldp-types:lldp_tlv_select_type
    | +--ro link-aggregation?  ipi-ldp-types:lldp_tlv_select_type
    | +--ro dcb-exchange?      ipi-ldp-types:lldp_tlv_select_type {feature-list:HAVE_DCB}?
  +--rw ieee-8023-org-specific
    | +--rw config
```

---

```

| | +--rw mac-phy?      ipi-lldp-types:lldp_tlv_select_type
| | +--rw max-mtu-size? ipi-lldp-types:lldp_tlv_select_type
| | +--ro state
| |   +--ro mac-phy?      ipi-lldp-types:lldp_tlv_select_type
| |   +--ro max-mtu-size? ipi-lldp-types:lldp_tlv_select_type
+--rw tlv-media-capabilities
  +--rw config
    | +--rw network-policy? ipi-lldp-types:lldp_tlv_select_type
    | +--rw location?       ipi-lldp-types:lldp_tlv_select_type
    | +--rw inventory?      ipi-lldp-types:lldp_tlv_select_type
    | +--rw media-capabilities? ipi-lldp-types:lldp_tlv_select_type
  +--ro state
    +--ro network-policy? ipi-lldp-types:lldp_tlv_select_type
    +--ro location?       ipi-lldp-types:lldp_tlv_select_type
    +--ro inventory?      ipi-lldp-types:lldp_tlv_select_type
    +--ro media-capabilities? ipi-lldp-types:lldp_tlv_select_type

```

## rpcs:

```

+---x lldp-terminal-debug-on {feature-list:HAVE_ONMD,feature-list:HAVE_LLDPV2}?
| +---w input
|   +---w terminal-debug-options ipi-lldp-types:lldp_debug_t
+---x lldp-terminal-debug-off {feature-list:HAVE_ONMD,feature-list:HAVE_LLDPV2}?
| +---w input
|   +---w terminal-debug-options ipi-lldp-types:lldp_debug_t
+---x clear-lldp-counter {feature-list:HAVE_ONMD,feature-list:HAVE_LLDPV2}?
| +---w input
|   +---w interface-name? string
+---x lldp-snmp-restart {feature-list:HAVE_SNMP}?

```

## notifications:

```

+---n lldp-remote-inserts-notification
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro remote-inserts? yang:counter32
+---n lldp-remote-deletes-notification
  +--ro severity?      cml-data-types:cml_notif_severity_t

```

---

```
+-ro eventClass?    cml-data-types:cml_notif_class_t
+-ro remote-deletes? yang:counter32
```

---

## module: ipi-logging

```
+-rw logging
+-rw logging-modules
| +-rw module-logging* [module-name]
|   +-rw module-name  -> ../config/module-name
|   +-rw config
|     +-rw module-name?  ipi-logging-types:module_names_t
|     +-rw severity-level ipi-logging-types:log_severity_t
|     +-ro state
|       +-ro module-name?  ipi-logging-types:module_names_t
|       +-ro severity-level ipi-logging-types:log_severity_t
+-rw monitor-logging
| +-rw config!
| | +-rw enable-logging  cml-data-types:cml_enable_disable_t
| | +-rw severity-level? ipi-logging-types:log_severity_t
| +-ro state
|   +-ro enable-logging  cml-data-types:cml_enable_disable_t
|   +-ro severity-level? ipi-logging-types:log_severity_t
+-rw console-logging
| +-rw config!
| | +-rw enable-logging  cml-data-types:cml_enable_disable_t
| | +-rw severity-level? ipi-logging-types:log_severity_t
| +-ro state
|   +-ro enable-logging  cml-data-types:cml_enable_disable_t
|   +-ro severity-level? ipi-logging-types:log_severity_t
+-rw logfile
| +-rw config!
| | +-rw file-name      string
```

```

| | +--rw severity-level ipi-logging-types:log_severity_t
| | +--rw max-file-size? uint32
| +--ro state
|   +--ro file-name string
|   +--ro severity-level ipi-logging-types:log_severity_t
|   +--ro max-file-size? uint32
+--rw debug-logfile
| +--rw config!
| | +--rw file-name string
| | +--rw max-file-size uint32
| +--ro state
|   +--ro file-name string
|   +--ro max-file-size uint32
+--rw syslog {feature-list:HAVE_SYSLOG}?
| +--rw config
| | +--rw enable-syslog? empty
| | +--rw timestamp-granularity? ipi-logging-types:timestamp_units_t
| | +--rw cli-timestamp? empty
| +--ro state
|   +--ro enable-syslog? empty
|   +--ro timestamp-granularity? ipi-logging-types:timestamp_units_t
|   +--ro cli-timestamp? empty
+--rw remote-logging
| +--rw config
| | +--rw enable-rsyslog? empty
| +--ro state
| | +--ro enable-rsyslog? empty
| +--rw remote-servers {feature-list:HAVE_VRF}?
| | +--rw remote-server* [vrf]
| |   +--rw vrf -> ../config/vrf
| |   +--rw config
| | | +--rw vrf? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name {feature-
list:HAVE_VRF}?
| | | +--ro state
| | | +--ro vrf? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name {feature-
list:HAVE_VRF}?
| | +--rw servers

```

---

```
| |   +--rw server* [address]
| |     +--rw address  -> ../config/address
| |     +--rw config
| |       | +--rw address?  cml-data-types:cml_hostname_t
| |       | +--rw severity  ipi-logging-types:log_severity_t
| |       | +--rw port?     uint16
| |     +--ro state
| |       +--ro address?  cml-data-types:cml_hostname_t
| |       +--ro severity  ipi-logging-types:log_severity_t
| |       +--ro port?     uint16
| +--rw default-instance
|   +--rw config
|     | +--rw disable-default-instance?  empty
|     +--ro state
|       +--ro disable-default-instance?  empty
+--rw global
| +--rw config
| | +--rw remote-server-facility?  ipi-logging-types:log_facility_t
| | +--rw remote-authpriv-facility?  empty
| +--ro state
|   +--ro remote-server-facility?  ipi-logging-types:log_facility_t
|   +--ro remote-authpriv-facility?  empty
+--rw cli-logging
| +--rw config
| | +--rw enable-logging?  empty
| +--ro state
| | +--ro enable-logging?  empty
| +--rw max-session-limit
|   +--rw config
|     | +--rw max-session-limit?  uint8
|     +--ro state
|       +--ro max-session-limit?  uint8
+--rw fault-management
  +--rw config
  | +--rw enable-fault-management?  empty
  +--ro state
```

---

---

```
+--ro enable-fault-management? empty
```

```
rpcs:
```

```
+---x logging-fms-flush-db {feature-list:HAVE_FMS}?
+---x logging-fms-shelve {feature-list:HAVE_FMS}?
| +---w input
|   +---w alarm-type string
+---x logging-fms-close {feature-list:HAVE_FMS}?
| +---w input
|   +---w active-alarm-id string
+---x terminal-debug-all-off
+---x logging-clear-debug-logfile
+---x logging-clear-logging-logfile
+---x remove-file
+---w input
+---w file_type ipi-logging-types:remove_files_t
+---w filename ipi-logging-types:file_type_t
```

---

## module: ipi-management-server

```
+--rw netconf-server {feature-list:HAVE_NETCONF}?
| +--rw callhome {feature-list:HAVE_NETCONF}?
| | +--rw config!
| | | +--rw feature-enabled empty
| | | +--rw management-port? -> /ipi-interface:interfaces/interface/name
| | +--ro state
| | | +--ro feature-enabled empty
| | | +--ro management-port? -> /ipi-interface:interfaces/interface/name
| | +--rw netconf-clients
| | | +--rw netconf-client* [name]
| | |   +--rw name -> ../config/name
| | |   +--rw config
| | | | +--rw name? string
```

---

```

| | | | +--rw address string
| | | | +--rw port? inet:port-number
| | | +--ro state
| | | +--ro name? string
| | | +--ro address string
| | | +--ro port? inet:port-number
| | +--rw reconnect
| | +--rw config!
| | | +--rw enable empty
| | | +--rw retry-max-attempts? uint8
| | | +--rw retry-interval? uint32
| | +--ro state
| | +--ro enable empty
| | +--ro retry-max-attempts? uint8
| | +--ro retry-interval? uint32
| +--rw netconf-translation {feature-list:HAVE_NETCONF_OC_TRANSLATION}?
| | +--rw config
| | | +--rw translation-mode? ipi-management-server-types:management_server_translation_type_t
| | | +--ro state
| | | +--ro translation-mode? ipi-management-server-types:management_server_translation_type_t
| +--rw debug
| | +--rw config
| | | +--rw enable? empty
| | | +--ro state
| | | +--ro enable? empty
| +--rw vrfs {feature-list:HAVE_VRF}?
| | +--rw vrf* [vrf-name]
| | | +--rw vrf-name -> ../config/vrf-name
| | | +--rw config
| | | | +--rw vrf-name? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
{feature-list:HAVE_VRF}?
| | | +--ro state
| | | | +--ro vrf-name? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
{feature-list:HAVE_VRF}?
| | | +--rw netconf-ssh-config
| | | | +--rw config!
| | | | +--rw feature-netconf-ssh boolean {feature-list:HAVE_NETCONF}?

```

---

---

```

| | | | +--rw ssh-port?          uint32 {feature-list:HAVE_NETCONF}?
| | | +--ro state
| | |   +--ro feature-netconf-ssh  boolean {feature-list:HAVE_NETCONF}?
| | |   +--ro ssh-port?           uint32 {feature-list:HAVE_NETCONF}?
| | +--rw netconf-tls-config
| |   +--rw config!
| |     +--rw feature-netconf-tls  boolean {feature-list:HAVE_NETCONF}?
| |     +--rw tls-port?           uint32 {feature-list:HAVE_NETCONF}?
| |     +--ro state
| |       +--ro feature-netconf-tls  boolean {feature-list:HAVE_NETCONF}?
| |       +--ro tls-port?           uint32 {feature-list:HAVE_NETCONF}?
| +--rw notification-cache {feature-list:HAVE_NETCONF}?
|   +--rw config!
|     +--rw feature-enabled        empty
|     +--rw max-cache-notifications? uint16
|     +--rw cache-period?         uint32
|     +--ro state
|       +--ro feature-enabled        empty
|       +--ro max-cache-notifications? uint16
|       +--ro cache-period?         uint32
+--rw management-server
  +--rw module-notifications
    +--rw module-notification* [module-name]
      +--rw module-name  -> ../config/module-name
      +--rw config
        | +--rw module-name?  ipi-management-server-notification-types:notif_module_names_t
        | +--rw enable        cml-data-types:cml_enable_disable_t
        | +--rw severity?    cml-data-types:cml_notif_severity_t
        +--ro state
          +--ro module-name?  ipi-management-server-notification-types:notif_module_names_t
          +--ro enable        cml-data-types:cml_enable_disable_t
          +--ro severity?    cml-data-types:cml_notif_severity_t

notifications:
+---n suppress-bulk-notification
  +--ro severity?  cml-data-types:cml_notif_severity_t

```

---

---

```
+--ro eventClass? cml-data-types:cml_notif_class_t
+--ro message?   string
```

---

## module: ipi-mcec

```
+--rw mcec
  +--rw debug
    | +--rw config
    | | +--rw options? ipi-mcec-types:mcec_debug_t
    | +--ro state
    | +--ro options?      ipi-mcec-types:mcec_debug_t
    | +--ro terminal-debug-status? ipi-mcec-types:mcec_debug_t
  +--rw domain
    | +--rw config
    | | +--rw system-number? uint8
    | | +--rw address?      ipi-mcec-types:mcec_domain_addr_t
    | | +--rw priority?    uint16
    | | +--rw hello-timeout? ipi-mcec-types:mcec_hello_t
    | +--ro state
    | +--ro system-number?  uint8
    | +--ro address?       ipi-mcec-types:mcec_domain_addr_t
    | +--ro priority?      uint16
    | +--ro hello-timeout? ipi-mcec-types:mcec_hello_t
    | +--ro domain-sync?   ipi-mcec-types:mcec_domain_sync_status_t
    | +--ro domain-adjacency? ipi-mcec-types:mcec_domain_adjacency_state_t
    | +--ro mcec-invalid-pdu-rx? uint32
  +--ro mcec-instance* [mlag-id]
    | +--ro mlag-id  -> ../state/mlag-id
    | +--ro state
    | | +--ro mlag-id?          uint16
    | | +--ro interface?       string
    | | +--ro administrative-aggregation-key? uint16
    | | +--ro operational-aggregation-key?   uint16
    | | +--ro physical-properties-digest?   string
    | | +--ro operational-partner-aggregation-key? uint16
```

---

```

| | +--ro partner-system?          string
| | +--ro partner-system-priority? uint16
| | +--ro member-interface-bandwidth? string
| | +--ro member-interface-state?   ipi-mcec-types:mcec_if_state_t
| | +--ro mlag-sync?                ipi-mcec-types:mcec_sync_state_t
| | +--ro flood-enabled?            ipi-mcec-types:mcec_flood_state_t
| | +--ro mlag-port-state?          ipi-mcec-types:mcec_if_state_t
| | +--ro mlag-interface-state?     ipi-mcec-types:mcec_if_state_t
| | +--ro aggregation-mapped?       boolean
| | +--ro mlag-bandwidth?           string
| | +--ro info-receive-state?       ipi-mcec-types:mcec_info_receive_state_t
| | +--ro info-periodic-tx-state?   ipi-mcec-types:mcec_info_periodic_tx_state_t
| | +--ro valid-info-pdu-rx?        uint32
| | +--ro valid-info-pdu-tx?        uint32
| +--ro neighbor
|   +--ro state
|     +--ro administrative-aggregation-key? uint16
|     +--ro physical-properties-digest?    string
|     +--ro operational-partner-aggregation-key? uint16
|     +--ro partner-system?                string
|     +--ro partner-system-priority?        uint16
|     +--ro member-interface-bandwidth?     string
|     +--ro member-interface-state?         ipi-mcec-types:mcec_if_state_t
|     +--ro mlag-sync?                     ipi-mcec-types:mcec_sync_state_t
+--rw intra-domain
| +--rw peer-link
| | +--rw config
| | | +--rw interface? -> /ipi-interface:interfaces/interface/name
| | | +--rw higid?     empty {feature-list:NOT_HAVE_DUNE}?
| | +--ro state
| |   +--ro interface? -> /ipi-interface:interfaces/interface/name
| |   +--ro higid?     empty {feature-list:NOT_HAVE_DUNE}?
| +--rw peer-address
| | +--rw config!
| | | +--rw peer-address  inet:ipv4-address
| | | +--rw local-address inet:ipv4-address

```

---

```

| | | +--rw vrf          -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
{feature-list:HAVE_VRF}?
| | +--ro state
| |   +--ro peer-address  inet:ipv4-address
| |   +--ro local-address inet:ipv4-address
| |   +--ro vrf           -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
{feature-list:HAVE_VRF}?
| +--ro neighbor-info
| | +--ro state
| |   +--ro domain-address?   ipi-mcec-types:mcec_domain_addr_t
| |   +--ro domain-priority?  uint32
| |   +--ro domain-system-number? uint16
| |   +--ro domain-sync?      ipi-mcec-types:mcec_domain_sync_status_t
| |   +--ro hello-timeout?    uint16
| +--ro intra-domain-peer-info
|   +--ro state
|     +--ro mcec-hello-periodic-tx-state? ipi-mcec-types:mcec_hello_periodic_tx_state_t
|     +--ro mcec-valid-hello-pdu-rx?     uint32
|     +--ro mcec-valid-hello-pdu-tx?     uint32
|     +--ro mcec-valid-info-pdu-rx?      uint32
|     +--ro mcec-valid-info-pdu-tx?      uint32
|     +--ro mcec-valid-mac-sync-pdu-rx?  uint32
|     +--ro mcec-valid-mac-sync-pdu-tx?  uint32
+--ro mac-sync
| +--ro local-mac-table* [mac-address vlan-id]
| | +--ro mac-address  -> ../state/mac-address
| | +--ro vlan-id     -> ../state/vlan-id
| | +--ro state
| |   +--ro mac-address?  string
| |   +--ro vlan-id?     uint16
| |   +--ro output-interface? string
| +--ro remote-mac-table* [mac-address vlan-id]
|   +--ro mac-address  -> ../state/mac-address
|   +--ro vlan-id     -> ../state/vlan-id
|   +--ro state
|     +--ro mac-address?  string
|     +--ro vlan-id?     uint16

```

---

```

|   +--ro output-interface?  string
+--ro stp-sync
| +--ro state
| | +--ro bridge-priority?    uint16
| | +--ro path-cost-method?   uint8
| | +--ro domain-digest?     string
| | +--ro neighbor-domain-digest? string
| +--ro mlag-interface-sync-entry* [mlag-id]
|   +--ro mlag-id  -> ../state/mlag-id
|   +--ro state
|     +--ro mlag-id?          uint16
|     +--ro port-priority?    uint16
|     +--ro path-cost?       uint32
|     +--ro interface-digest? string
|     +--ro neighbor-interface-digest? string
+--rw mlag-interfaces
  +--rw mlag-interface* [name]
    +--rw name          -> ../config/name
    +--rw config
      | +--rw name?      -> /ipi-interface:interfaces/interface/name
      | +--rw interface-mode? ipi-mcec-types:mcec_mode_type_t
      +--ro state
        | +--ro name?      -> /ipi-interface:interfaces/interface/name
        | +--ro interface-mode? ipi-mcec-types:mcec_mode_type_t
      +--rw switchover-type
        +--rw config
          | +--rw revertive-timer?    uint8
          | +--rw enable-non-revertive? empty
          +--ro state
            +--ro revertive-timer?    uint8
            +--ro enable-non-revertive? empty

rpcs:
+---x mcec-terminal-debug-on {feature-list:HAVE_LAGD,feature-list:HAVE_MCEC}?
| +---w input
|   +---w terminal-debug-options  ipi-mcec-types:mcec_debug_t

```

```

+---x mcec-terminal-debug-off {feature-list:HAVE_LAGD,feature-list:HAVE_MCEC}?
| +---w input
|   +---w terminal-debug-options   ipi-mcec-types:mcec_debug_t
+---x clear-mcec-statistics {feature-list:HAVE_LAGD,feature-list:HAVE_MCEC}?

```

---

## module: ipi-mlag

```

+--ro mlag
  +--ro mlag-interface* [mlag-id]
    | +--ro mlag-id   -> ../state/mlag-id
    | +--ro state
    |   +--ro mlag-id?      uint16
    |   +--ro interface-flags? ipi-mlag-types:mlag_interface_flags_t
    |   +--ro bandwidth?   string
  +--ro intra-domain-port
    | +--ro state
    |   +--ro interface-name? string
    |   +--ro interface-index? uint32
    |   +--ro interface-type? ipi-mlag-types:mlag_idp_interface_type_t
    |   +--ro bridge-name?   string
  +--ro mstp-sync-info
    +--ro state
      | +--ro bridge-priority?  uint16
      | +--ro path-cost-method?  uint8
      | +--ro num-of-interfaces? uint16
      | +--ro domain-digest*    string
    +--ro interface-sync-info* [interface-mlag-id]
      +--ro interface-mlag-id   -> ../state/interface-mlag-id
      +--ro state
        +--ro interface-mlag-id?  uint16
        +--ro interface-priority? uint16
        +--ro path-cost?          uint32
        +--ro interface-digest*   string

```

```
augment /ipi-interface:interfaces/ipi-interface:interface:
```

```
+--rw mlag-aggregation!  
  +--rw config!  
    | +--rw mlag-id  uint16  
  +--ro state  
    +--ro mlag-id  uint16
```

---

## module: ipi-mld-snooping

```
+--rw mld-snooping  
  +--rw global  
    | +--rw config  
    | | +--rw disable-mld-snooping?    empty  
    | | +--rw disable-report-suppression? empty  
    | +--ro state  
    | +--ro disable-mld-snooping?    empty  
    | +--ro disable-report-suppression? empty  
  +--rw debug  
    | +--rw config  
    | | +--rw options? ipi-mld-snooping-types:mld_snoop_debug_options_t  
    | +--ro state  
    | +--ro options?          ipi-mld-snooping-types:mld_snoop_debug_options_t  
    | +--ro terminal-debug-status? ipi-mld-snooping-types:mld_snoop_debug_options_t  
  +--rw interfaces  
    +--rw interface* [name]  
      +--rw name    -> ../config/name  
      +--rw config  
        | +--rw name?          -> /ipi-interface:interfaces/interface/name  
        | +--rw mld-snooping?    cml-data-types:cml_enable_disable_t  
        | +--rw enable-fast-leave?  empty  
        | +--rw report-suppression?  cml-data-types:cml_enable_disable_t  
        | +--rw mrouter-interface-name* -> /ipi-interface:interfaces/interface/name  
        | +--rw enable-querier?    empty  
      +--ro state
```

```

+--ro name?          -> /ipi-interface:interfaces/interface/name
+--ro mld-snooping?  cml-data-types:cml_enable_disable_t
+--ro enable-fast-leave?  empty
+--ro report-suppression? cml-data-types:cml_enable_disable_t
+--ro mrouter-interface-name* -> /ipi-interface:interfaces/interface/name
+--ro enable-querier?  empty

```

rpcs:

```

+---x mld-snooping-terminal-debug-on {feature-list:HAVE_MLD_SNOOP}?
| +---w input
|   +---w terminal-debug-options  ipi-mld-snooping-types:mld_snoop_debug_options_t
+---x mld-snooping-terminal-debug-off {feature-list:HAVE_MLD_SNOOP}?
| +---w input
|   +---w terminal-debug-options  ipi-mld-snooping-types:mld_snoop_debug_options_t
+---x mld-snooping-clear-group-on-interface {feature-list:HAVE_MLD_SNOOP}?
| +---w input
|   +---w group-address  string
|   +---w interface-name string
+---x mld-snooping-clear-all-groups-on-interface {feature-list:HAVE_MLD_SNOOP}?
| +---w input
|   +---w interface-name string
+---x mld-snooping-clear-group {feature-list:HAVE_MLD_SNOOP}?
| +---w input
|   +---w group-address  string
+---x mld-snooping-clear-all-groups {feature-list:HAVE_MLD_SNOOP}?

```

---

## module: ipi-mld

```

+--rw mld
+--rw vrfs
| +--rw vrf* [vrf-name]
|   +--rw vrf-name          -> ../config/vrf-name
|   +--rw config
|     | +--rw vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
|     | +--rw disable-ssm-map? empty

```

---

```

|  +--ro state
|  |  +--ro vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
|  |  +--ro disable-ssm-map?  empty
|  +--rw group-membership-control
|  |  +--rw config
|  |  |  +--rw member-limit?      uint32
|  |  |  +--rw limit-exception-acl?  string
|  |  +--ro state
|  |  |  +--ro member-limit?      uint32
|  |  |  +--ro limit-exception-acl?  string
|  |  |  +--ro current-states-count?  yang:counter32
|  +--rw ssm
|  |  +--rw static-mappings
|  |  |  +--rw static-mapping* [group-ranges-acl source]
|  |  |  |  +--rw group-ranges-acl  -> ../config/group-ranges-acl
|  |  |  |  +--rw source           -> ../config/source
|  |  |  |  +--rw config
|  |  |  |  |  +--rw group-ranges-acl?  string
|  |  |  |  |  +--rw source?          inet:ipv6-address
|  |  |  |  +--ro state
|  |  |  |  |  +--ro group-ranges-acl?  string
|  |  |  |  |  +--ro source?          inet:ipv6-address
|  +--rw debug
|  |  +--rw config
|  |  |  +--rw debug-options?  ipi-mld-types:mld_debug_options_t
|  +--ro state
|  |  +--ro debug-options?      ipi-mld-types:mld_debug_options_t
|  |  +--ro terminal-debug-status-on?  ipi-mld-types:mld_debug_options_t
+--rw interfaces
|  +--rw interface* [name]
|  |  +--rw name                -> ../config/name
|  |  +--rw config
|  |  |  +--rw name?            -> /ipi-interface:interfaces/interface/name
|  |  |  +--rw enabled?        empty
|  |  |  +--rw last-member-query-count?  uint8
|  |  |  +--rw last-member-query-interval?  uint16

```

---

```
| | +--rw querier-timeout?      uint16
| | +--rw query-interval?      uint16
| | +--rw query-max-response-time?  uint8
| | +--rw startup-query-interval?  uint16
| | +--rw startup-query-count?    uint8
| | +--rw robustness-variable?    uint8
| | +--rw version?              uint8
| +--ro state
| | +--ro counters
| | | +--ro v1-reports-received?  yang:counter32
| | | +--ro v2-reports-received?  yang:counter32
| | | +--ro v1-leaves-received?   yang:counter32
| | | +--ro current-group-records? yang:counter32
| | +--ro internet-address?      inet:ipv6-address
| | +--ro oper-status?           ipi-mld-types:mld_if_oper_status_t
| | +--ro host-version?         uint8
| | +--ro is-querier?           boolean
| | +--ro querying-router?      inet:ipv6-address
| | +--ro group-membership-interval?  uint32
| | +--ro name?                 -> /ipi-interface:interfaces/interface/name
| | +--ro enabled?              empty
| | +--ro last-member-query-count?  uint8
| | +--ro last-member-query-interval?  uint16
| | +--ro querier-timeout?        uint16
| | +--ro query-interval?        uint16
| | +--ro query-max-response-time?  uint8
| | +--ro startup-query-interval?  uint16
| | +--ro startup-query-count?    uint8
| | +--ro robustness-variable?    uint8
| | +--ro version?              uint8
| +--rw proxy
| | +--rw config
| | | +--rw enable-proxy-service?  empty
| | | +--rw mroute-proxy-interface?  string
| | | +--rw unsolicited-report-interval?  uint16
| | +--ro state
```

---

```

| | +--ro enable-proxy-service?    empty
| | +--ro mroute-proxy-interface?  string
| | +--ro unsolicited-report-interval? uint16
| | +--ro oper-status?             ipi-mld-types:mld_proxy_if_oper_status_t
| | +--ro upstream-interface?      string
| | +--ro mcast-groups-count?      yang:counter32
| +--rw group-membership-control
| | +--rw config
| | | +--rw access-group-name?     string
| | | +--rw immediate-leave-groups-list? string
| | | +--rw member-limit?         uint32
| | | +--rw limit-exception-acl?   string
| | +--ro state
| |   +--ro access-group-name?     string
| |   +--ro immediate-leave-groups-list? string
| |   +--ro member-limit?         uint32
| |   +--ro limit-exception-acl?   string
| +--rw asm-static-groups
| | +--rw asm-static-group* [group-address]
| |   +--rw group-address -> ../config/group-address
| |   +--rw config
| |     +--rw group-address? inet:ipv6-address
| |     +--ro state
| |       +--ro group-address? inet:ipv6-address
| +--rw ssm-static-groups
| | +--rw ssm-static-group* [group-address source]
| |   +--rw group-address -> ../config/group-address
| |   +--rw source -> ../config/source
| |   +--rw config
| |     +--rw group-address? inet:ipv6-address
| |     +--rw source? ipi-mld-types:mld_static_ssm_source_t
| |     +--ro state
| |       +--ro group-address? inet:ipv6-address
| |       +--ro source? ipi-mld-types:mld_static_ssm_source_t
+--ro group-membership-tree
  +--ro mld-instances

```

---

```
+--ro mld-instance* [vrf-name]
  +--ro vrf-name    -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
  +--ro interfaces
    +--ro interface* [if-name]
      +--ro if-name    -> /ipi-interface:interfaces/interface/name
      +--ro member-groups
        | +--ro member-group* [group-address]
        |   +--ro group-address    -> ../state/group-address
        |   +--ro state
        |     | +--ro group-address?  inet:ipv6-address
        |     | +--ro dynamic-remote? empty
        |     | +--ro static-group?   empty
        |     | +--ro ssm-mapped?    empty
        |     | +--ro static-source?  empty
        |     | +--ro up-time?        string
        |     | +--ro group-mode?     ipi-mld-types:mld_ssm_group_mode_t
        |     | +--ro expiry?         string
        |     | +--ro last-reporter?  inet:ipv6-address
        |     +--ro include-sources
        |       | +--ro include-source* [source-address]
        |       |   +--ro source-address    -> ../state/source-address
        |       |   +--ro state
        |       |     +--ro source-address? inet:ipv6-address
        |       |     +--ro dynamic-remote? empty
        |       |     +--ro static-source?  empty
        |       |     +--ro ssm-mapped?    empty
        |       |     +--ro up-time?        string
        |       |     +--ro expiry?         string
        |       |     +--ro is-forwarded?  ipi-mld-types:mld_yes_no_t
        |       +--ro exclude-sources
        |         +--ro exclude-source* [source-address]
        |         +--ro source-address    -> ../state/source-address
        |         +--ro state
        |           +--ro source-address? inet:ipv6-address
        |           +--ro dynamic-remote? empty
        |           +--ro static-source?  empty
```

```

|      +--ro ssm-mapped?    empty
|      +--ro up-time?      string
|      +--ro expiry?       string
|      +--ro is-forwarded?  ipi-mld-types:mld_yes_no_t
+--ro proxy-groups
  +--ro proxy-group* [group-address]
    +--ro group-address  -> ../state/group-address
    +--ro state
      +--ro group-address?  inet:ipv6-address
      +--ro proxy-interface? string
      +--ro group-mode?     ipi-mld-types:mld_ssm_group_mode_t
      +--ro oper-state?     ipi-mld-types:mld_if_state_t
      +--ro membership-state? ipi-mld-types:mld_proxy_grp_membership_state_t
      +--ro multicast-sources* inet:ipv6-address

```

rpcs:

```

+---x mld-terminal-debug-on {feature-list:HAVE_MCAST_IPV6,feature-list:NOT_HAVE_DUNE_OR_HAVE_DNX}?
| +---w input
|   +---w vrf-name?      string
|   +---w term-debug-options  ipi-mld-types:mld_debug_options_t
+---x mld-terminal-debug-off {feature-list:HAVE_MCAST_IPV6,feature-list:NOT_HAVE_DUNE_OR_HAVE_DNX}?
| +---w input
|   +---w vrf-name?      string
|   +---w term-debug-options  ipi-mld-types:mld_debug_options_t
+---x mld-clear-all-groups {feature-list:HAVE_MCAST_IPV6,feature-list:NOT_HAVE_DUNE_OR_HAVE_DNX}?
| +---w input
|   +---w vrf-name?  string
|   +---w clear-all  empty
+---x mld-clear-group-on-interface {feature-list:HAVE_MCAST_IPV6,feature-
list:NOT_HAVE_DUNE_OR_HAVE_DNX}?
| +---w input
|   +---w vrf-name?  string
|   +---w if-name    string
|   +---w group-address  inet:ipv6-address
+---x mld-clear-all-groups-on-interface {feature-list:HAVE_MCAST_IPV6,feature-
list:NOT_HAVE_DUNE_OR_HAVE_DNX}?
| +---w input

```

```

| +---w vrf-name? string
| +---w if-name string
+---x mld-clear-group {feature-list:HAVE_MCAST_IPV6,feature-list:NOT_HAVE_DUNE_OR_HAVE_DNX}?
  +---w input
    +---w vrf-name? string
    +---w group-address inet:ipv6-address

```

---

## module: ipi-mpls-bfd

augment /ipi-bfd:bfd:

```

+--rw mpls-lsp
  +--rw session-groups
    +--rw session-group* [lsp-type fec-address]
      +--rw lsp-type -> ../config/lsp-type
      +--rw fec-address -> ../config/fec-address
      +--rw config
        | +--rw lsp-type? ipi-bfd-types:mpls_bfd_lsp_type_t
        | +--rw fec-address? cml-data-types:cml_ipv4_addr_prefix_t
        +--ro state
          | +--ro lsp-type? ipi-bfd-types:mpls_bfd_lsp_type_t
          | +--ro fec-address? cml-data-types:cml_ipv4_addr_prefix_t
        +--rw session-attributes
          +--rw config
            | +--rw lsp-ping-interval? uint16
            | +--rw admin-down? empty
          +--ro state
            | +--ro lsp-ping-interval? uint16
            | +--ro admin-down? empty
          +--rw intervals
            +--rw interval* [minimum-tx minimum-rx detection-multiplier]
              +--rw minimum-tx -> ../config/minimum-tx
              +--rw minimum-rx -> ../config/minimum-rx
              +--rw detection-multiplier -> ../config/detection-multiplier
            +--rw config

```

```

| +--rw minimum-tx?      uint32
| +--rw minimum-rx?      uint32
| +--rw detection-multiplier? uint8
+--ro state
  +--ro minimum-tx?      uint32
  +--ro minimum-rx?      uint32
  +--ro detection-multiplier? uint8

```

augment /ipi-bfd:bfd:

```

+--rw mpls-all-lsps
  +--rw mpls-all-lsp* [lsp-type]
    +--rw lsp-type      -> ../config/lsp-type
    +--rw config
      | +--rw lsp-type? ipi-bfd-types:mpls_bfd_all_lsp_type_t
    +--ro state
      | +--ro lsp-type? ipi-bfd-types:mpls_bfd_all_lsp_type_t
    +--rw session-attributes
      +--rw config
        | +--rw lsp-ping-interval? uint16
        | +--rw admin-down?      empty
      +--ro state
        | +--ro lsp-ping-interval? uint16
        | +--ro admin-down?      empty
      +--rw intervals
        +--rw interval* [minimum-tx minimum-rx detection-multiplier]
          +--rw minimum-tx      -> ../config/minimum-tx
          +--rw minimum-rx      -> ../config/minimum-rx
          +--rw detection-multiplier -> ../config/detection-multiplier
        +--rw config
          | +--rw minimum-tx?      uint32
          | +--rw minimum-rx?      uint32
          | +--rw detection-multiplier? uint8
        +--ro state
          +--ro minimum-tx?      uint32
          +--ro minimum-rx?      uint32
          +--ro detection-multiplier? uint8

```

augment /ipi-bfd:bfd:

```
+--rw mpls-tunnels
  +--rw mpls-tunnel* [lsp-type tunnel-name]
    +--rw lsp-type      -> ../config/lsp-type
    +--rw tunnel-name   -> ../config/tunnel-name
    +--rw config
      | +--rw lsp-type?   ipi-bfd-types:mpls_bfd_te_type_t
      | +--rw tunnel-name? string
    +--ro state
      | +--ro lsp-type?   ipi-bfd-types:mpls_bfd_te_type_t
      | +--ro tunnel-name? string
    +--rw session-attributes
      +--rw config
        | +--rw lsp-ping-interval? uint16
        | +--rw admin-down?        empty
      +--ro state
        | +--ro lsp-ping-interval? uint16
        | +--ro admin-down?        empty
      +--rw intervals
        +--rw interval* [minimum-tx minimum-rx detection-multiplier]
          +--rw minimum-tx      -> ../config/minimum-tx
          +--rw minimum-rx      -> ../config/minimum-rx
          +--rw detection-multiplier -> ../config/detection-multiplier
          +--rw config
            | +--rw minimum-tx?      uint32
            | +--rw minimum-rx?      uint32
            | +--rw detection-multiplier? uint8
          +--ro state
            +--ro minimum-tx?      uint32
            +--ro minimum-rx?      uint32
            +--ro detection-multiplier? uint8
```

---

## module: ipi-mpls-rib

augment /ipi-mpls:mpls:

```
+--rw rib
```

```

+--ro global-fts-table
| +--ro ipv4-fts-entry* [fec-prefix owner lsp-type tunnel-id] {feature-list:HAVE_VRF}?
| | +--ro fec-prefix    -> ../state/fec-prefix
| | +--ro owner        -> ../state/owner
| | +--ro lsp-type     -> ../state/lsp-type
| | +--ro tunnel-id    -> ../state/tunnel-id
| | +--ro nhlfes-entry* [out-interface out-label administrative-status xc-index]
| | | +--ro out-interface    -> ../state/out-interface
| | | +--ro out-label        -> ../state/out-label
| | | +--ro administrative-status -> ../state/administrative-status
| | | +--ro xc-index         -> ../state/xc-index
| | | +--ro state
| | |   +--ro out-interface?   -> /ipi-interface:interfaces/interface/name
| | |   +--ro out-label?       uint32
| | |   +--ro nexthop-address?  inet:ipv4-address
| | |   +--ro nhlfes-type?     ipi-mpls-types:mpls_rib_nhlfes_type_t
| | |   +--ro xc-index?        uint32
| | |   +--ro administrative-status? ipi-mpls-types:mpls_rib_entry_admin_status_t
| | |   +--ro oper-status?     ipi-mpls-types:mpls_rib_entry_oper_status_t
| | |   +--ro nhlfes-owner?    ipi-mpls-types:mpls_rib_entry_owner_t
| | |   +--ro nhlfes-index?    uint32
| | |   +--ro is-stale?        boolean
| | |   +--ro label-op-code?   ipi-mpls-types:mpls_rib_label_op_code_t
| | |   +--ro in-interface?    string
| | |   +--ro in-label?        uint32
| | +--ro state
| | | +--ro fec-prefix?       cml-data-types:cml_ipv4_addr_prefix_t
| | | +--ro owner?           ipi-mpls-types:mpls_rib_entry_owner_t
| | | +--ro lsp-type?        ipi-mpls-types:mpls_rib_lsp_type_t
| | | +--ro unique-nhlfes-ix?  uint32
| | | +--ro fts-index?        uint32
| | | +--ro is-primary?       boolean
| | | +--ro route-distance?   uint8
| | | +--ro redirect-action-type? ipi-mpls-types:mpls_rib_action_type_t
| | | +--ro qos-exp-bits?     uint8
| | | +--ro is-entropy-label?  boolean

```

---

```

| | +--ro in-dscp-class-name?  string
| | +--ro tunnel-id?          uint32
| | +--ro protected-lsp-id?   uint32
| | +--ro qos-resource-id?    uint32
| | +--ro color?              uint32 {feature-list:HAVE_SERVICE_MAPPING}?
| | +--ro tunnel-policy-name? string {feature-list:HAVE_SERVICE_MAPPING}?
| | +--ro rsvp-multipath-name? string {feature-list:HAVE_RSVP_MULTIPATH}?
| | +--ro row-status?         string
| | +--ro state?              string
| | +--ro create-time?        cml-data-types:cml_line_t
| | +--ro up-time?            cml-data-types:cml_line_t
| | +--ro last-update?        cml-data-types:cml_line_t
| | +--ro description?        string
| +--ro ipv6-ften-entry* [fec-prefix6 owner lsp-type tunnel-id] {feature-list:HAVE_IPV6}?
|   +--ro fec-prefix6  -> ../state/fec-prefix6
|   +--ro owner        -> ../state/owner
|   +--ro lsp-type     -> ../state/lsp-type
|   +--ro tunnel-id    -> ../state/tunnel-id
|   +--ro nhlfe-entry* [out-interface out-label administrative-status]
|     +--ro out-interface  -> ../state/out-interface
|     +--ro out-label      -> ../state/out-label
|     +--ro administrative-status -> ../state/administrative-status
|     +--ro state
|       +--ro out-interface? -> /ipi-interface:interfaces/interface/name
|       +--ro out-label?     uint32
|       +--ro nexthop-address?  inet:ip-address
|       +--ro nhlfe-type?       ipi-mpls-types:mpls_rib_nhlfe_type_t
|       +--ro administrative-status? ipi-mpls-types:mpls_rib_entry_admin_status_t
|       +--ro oper-status?      ipi-mpls-types:mpls_rib_entry_oper_status_t
|       +--ro nhlfe-owner?      ipi-mpls-types:mpls_rib_entry_owner_t
|       +--ro nhlfe-index?      uint32
|       +--ro is-stale?         boolean
|       +--ro label-op-code?    ipi-mpls-types:mpls_rib_label_op_code_t
|       +--ro in-interface?     string
|       +--ro in-label?         uint32
|   +--ro state

```

---

---

```

|   +--ro fec-prefix6?      cml-data-types:cml_ipv6_prefix_t
|   +--ro owner?           ipi-mpls-types:mpls_rib_entry_owner_t
|   +--ro lsp-type?        ipi-mpls-types:mpls_rib_lsp_type_t
|   +--ro unique-nhlfe-ix?  uint32
|   +--ro ftn-index?       uint32
|   +--ro is-primary?      boolean
|   +--ro route-distance?  uint8
|   +--ro redirect-action-type? ipi-mpls-types:mpls_rib_action_type_t
|   +--ro qos-exp-bits?    uint8
|   +--ro is-entropy-label? boolean
|   +--ro in-dscp-class-name? string
|   +--ro tunnel-id?       uint32
|   +--ro protected-lsp-id? uint32
|   +--ro qos-resource-id?  uint32
|   +--ro color?           uint32 {feature-list:HAVE_SERVICE_MAPPING}?
|   +--ro tunnel-policy-name? string {feature-list:HAVE_SERVICE_MAPPING}?
|   +--ro rsvp-multipath-name? string {feature-list:HAVE_RSVP_MULTIPATH}?
|   +--ro row-status?      string
|   +--ro state?           string
|   +--ro create-time?     cml-data-types:cml_line_t
|   +--ro up-time?         cml-data-types:cml_line_t
|   +--ro last-update?     cml-data-types:cml_line_t
|   +--ro description?     string
+--ro ilm-table
| +--ro ip-ilm-entry* [in-interface in-label] {feature-list:HAVE_VRF}?
|   +--ro in-interface  -> ../state/in-interface
|   +--ro in-label      -> ../state/in-label
|   +--ro nhlfe-entry* [out-interface out-label xc-type]
|     | +--ro out-interface -> ../state/out-interface
|     | +--ro out-label    -> ../state/out-label
|     | +--ro xc-type      -> ../state/xc-type
|     | +--ro state
|     |   +--ro out-interface? -> /ipi-interface:interfaces/interface/name
|     |   +--ro out-label?    uint32
|     |   +--ro xc-type?      ipi-mpls-types:mpls_rib_xc_type_t
|     |   +--ro nexthop-address? inet:ip-address

```

---

```

| | +--ro nhlfe-owner?   ipi-mpls-types:mpls_rib_entry_owner_t
| | +--ro nhlfe-index?   uint32
| | +--ro label-op-code? ipi-mpls-types:mpls_rib_label_op_code_t
| +--ro state
|   +--ro in-interface?  -> /ipi-interface:interfaces/interface/name
|   +--ro in-label?      uint32
|   +--ro vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
{feature-list:HAVE_VRF}?
|   +--ro owner?         ipi-mpls-types:mpls_rib_entry_owner_t
|   +--ro ilm-index?     uint32
|   +--ro is-stitched-to-ften?  boolean
|   +--ro is-installed-in-fib?  boolean
|   +--ro is-selected?     boolean
|   +--ro is-stale?       boolean
|   +--ro fec-prefix?     cml-data-types:cml_ip_prefix_t
|   +--ro label-op-code?   ipi-mpls-types:mpls_rib_label_op_code_t
|   +--ro pseudowire-id?   uint32
|   +--ro evpn-id?       uint32 {feature-list:HAVE_BGP_EVPN,feature-list:HAVE_NVO}?
+--ro rsvp-multipath-table {feature-list:HAVE_RSVP_MULTIPATH}?
| +--ro rsvp-multipath-entry* [multipath-identifier]
|   +--ro multipath-identifier -> ../state/multipath-identifier
|   +--ro state
|     +--ro multipath-identifier?  uint16
|     +--ro multipath-name?        string
|     +--ro multipath-nhlfe-index?  uint32
|     +--ro fec-prefix?            cml-data-types:cml_ipv4_addr_prefix_t
|     +--ro active-member-count?   uint16
+--rw map-route
| +--rw static-ipv4-map-routes
|   +--rw static-ipv4-map-route* [route-prefix]
|     +--rw route-prefix -> ../config/route-prefix
|     +--rw config
|       | +--rw route-prefix?  cml-data-types:cml_ipv4_prefix_t
|       | +--rw mapped-fec     cml-data-types:cml_ipv4_prefix_t
|       +--ro state
|         +--ro route-prefix?  cml-data-types:cml_ipv4_prefix_t
|         +--ro mapped-fec     cml-data-types:cml_ipv4_prefix_t

```

```

+--rw static-lsps
  +--rw ipv4-static-ftn-entries
    | +--rw ipv4-static-ftn-entry* [fec-prefix pushed-label nexthop-ip-address out-interface-name]
    |   +--rw fec-prefix      -> ../config/fec-prefix
    |   +--rw pushed-label    -> ../config/pushed-label
    |   +--rw nexthop-ip-address -> ../config/nexthop-ip-address
    |   +--rw out-interface-name -> ../config/out-interface-name
    |   +--rw config
    |     | +--rw fec-prefix?      cml-data-types:cml_ipv4_prefix_t
    |     | +--rw pushed-label?    uint32
    |     | +--rw nexthop-ip-address? inet:ipv4-address
    |     | +--rw out-interface-name? -> /ipi-interface:interfaces/interface/name
    |     +--ro state
    |       +--ro fec-prefix?      cml-data-types:cml_ipv4_prefix_t
    |       +--ro pushed-label?    uint32
    |       +--ro nexthop-ip-address? inet:ipv4-address
    |       +--ro out-interface-name? -> /ipi-interface:interfaces/interface/name
  +--rw static-ftn-tunnels
    | +--rw static-ftn-tunnel* [tunnel-id fec-prefix pushed-label nexthop-ip-address out-interface-name is-primary]
  {feature-list:NOT_HAVE_MPLS_TUNNEL}?
    | +--rw tunnel-id      -> ../config/tunnel-id
    | +--rw fec-prefix     -> ../config/fec-prefix
    | +--rw pushed-label   -> ../config/pushed-label
    | +--rw nexthop-ip-address -> ../config/nexthop-ip-address
    | +--rw out-interface-name -> ../config/out-interface-name
    | +--rw is-primary     -> ../config/is-primary
    | +--rw config
    |   | +--rw tunnel-id?      uint32
    |   | +--rw fec-prefix?    cml-data-types:cml_ip_prefix_t
    |   | +--rw pushed-label?  uint32
    |   | +--rw nexthop-ip-address? inet:ip-address
    |   | +--rw out-interface-name? -> /ipi-interface:interfaces/interface/name
    |   | +--rw is-primary?    ipi-mpls-types:mpls_vpls_ftn_entry_lsp_type_t
    |   +--ro state
    |     +--ro tunnel-id?      uint32
    |     +--ro fec-prefix?    cml-data-types:cml_ip_prefix_t
    |     +--ro pushed-label?  uint32

```

---

```

|   +--ro nexthop-ip-address?  inet:ip-address
|   +--ro out-interface-name?  -> /ipi-interface:interfaces/interface/name
|   +--ro is-primary?          ipi-mpls-types:mpls_vpls_ftn_entry_lsp_type_t
+--rw static-ilm-entries
  +--rw static-ilm-entry* [incoming-label]
    +--rw incoming-label  -> ../config/incoming-label
    +--rw config
      | +--rw incoming-label?  uint32
    +--ro state
      | +--ro incoming-label?  uint32
    +--rw pop
      | +--rw config!
      | | +--rw enable-pop-label  empty
      | +--ro state
      | +--ro enable-pop-label  empty
    +--rw swaps
      +--rw swap* [in-interface-name swapped-label out-interface-name nexthop-ip-address fec-prefix]
        +--rw in-interface-name  -> ../config/in-interface-name
        +--rw swapped-label      -> ../config/swapped-label
        +--rw out-interface-name  -> ../config/out-interface-name
        +--rw nexthop-ip-address  -> ../config/nexthop-ip-address
        +--rw fec-prefix          -> ../config/fec-prefix
        +--rw config
          | +--rw in-interface-name?  string
          | +--rw swapped-label?      uint32
          | +--rw out-interface-name?  -> /ipi-interface:interfaces/interface/name
          | +--rw nexthop-ip-address?  inet:ip-address
          | +--rw fec-prefix?          cml-data-types:cml_ip_prefix_t
        +--ro state
          +--ro in-interface-name?  string
          +--ro swapped-label?      uint32
          +--ro out-interface-name?  -> /ipi-interface:interfaces/interface/name
          +--ro nexthop-ip-address?  inet:ip-address
          +--ro fec-prefix?          cml-data-types:cml_ip_prefix_t

```

```
augment /ipi-mpls:mpls:
```

```
+--ro vrf* [vrf-name] {feature-list:HAVE_VRF}?
```

```

+--ro vrf-name  -> ../rib/vrf-name
+--ro rib
  +--ro ftn-table
    | +--ro ipv4-ften-entry* [fec-prefix owner lsp-type tunnel-id]
    | | +--ro fec-prefix  -> ../state/fec-prefix
    | | +--ro owner      -> ../state/owner
    | | +--ro lsp-type   -> ../state/lsp-type
    | | +--ro tunnel-id  -> ../state/tunnel-id
    | | +--ro nhlfe-entry* [out-interface out-label]
    | | | +--ro out-interface  -> ../state/out-interface
    | | | +--ro out-label     -> ../state/out-label
    | | | +--ro state
    | | |   +--ro out-interface?  -> /ipi-interface:interfaces/interface/name
    | | |   +--ro out-label?      uint32
    | | |   +--ro nexthop-address?  inet:ipv4-address
    | | |   +--ro nhlfe-type?      ipi-mpls-types:mpls_rib_nhlfe_type_t
    | | |   +--ro xc-index?       uint32
    | | |   +--ro administrative-status? ipi-mpls-types:mpls_rib_entry_admin_status_t
    | | |   +--ro oper-status?     ipi-mpls-types:mpls_rib_entry_oper_status_t
    | | |   +--ro nhlfe-owner?     ipi-mpls-types:mpls_rib_entry_owner_t
    | | |   +--ro nhlfe-index?    uint32
    | | |   +--ro is-stale?       boolean
    | | |   +--ro label-op-code?   ipi-mpls-types:mpls_rib_label_op_code_t
    | | |   +--ro in-interface?   string
    | | |   +--ro in-label?      uint32
    | | +--ro state
    | |   +--ro fec-prefix?       cml-data-types:cml_ipv4_addr_prefix_t
    | |   +--ro owner?           ipi-mpls-types:mpls_rib_entry_owner_t
    | |   +--ro lsp-type?        ipi-mpls-types:mpls_rib_lsp_type_t
    | |   +--ro unique-nhlfe-ix?  uint32
    | |   +--ro ftn-index?       uint32
    | |   +--ro is-primary?      boolean
    | |   +--ro route-distance?   uint8
    | |   +--ro redirect-action-type? ipi-mpls-types:mpls_rib_action_type_t
    | |   +--ro qos-exp-bits?     uint8
    | |   +--ro is-entropy-label?  boolean

```

---

```

| | +--ro in-dscp-class-name?  string
| | +--ro tunnel-id?          uint32
| | +--ro protected-lsp-id?   uint32
| | +--ro qos-resource-id?    uint32
| | +--ro color?              uint32 {feature-list:HAVE_SERVICE_MAPPING}?
| | +--ro tunnel-policy-name? string {feature-list:HAVE_SERVICE_MAPPING}?
| | +--ro rsvp-multipath-name? string {feature-list:HAVE_RSVP_MULTIPATH}?
| | +--ro row-status?         string
| | +--ro state?              string
| | +--ro create-time?        cml-data-types:cml_line_t
| | +--ro up-time?            cml-data-types:cml_line_t
| | +--ro last-update?        cml-data-types:cml_line_t
| | +--ro description?        string
| +--ro ipv6-ften-entry* [fec-prefix6 owner lsp-type tunnel-id] {feature-list:HAVE_IPV6}?
|   +--ro fec-prefix6  -> ../state/fec-prefix6
|   +--ro owner        -> ../state/owner
|   +--ro lsp-type     -> ../state/lsp-type
|   +--ro tunnel-id   -> ../state/tunnel-id
|   +--ro nhlfe-entry* [out-interface out-label]
|     | +--ro out-interface  -> ../state/out-interface
|     | +--ro out-label     -> ../state/out-label
|     | +--ro state
|     |   +--ro out-interface?  -> /ipi-interface:interfaces/interface/name
|     |   +--ro out-label?      uint32
|     |   +--ro nexthop-address?  inet:ip-address
|     |   +--ro nhlfe-type?       ipi-mpls-types:mpls_rib_nhlfe_type_t
|     |   +--ro administrative-status? ipi-mpls-types:mpls_rib_entry_admin_status_t
|     |   +--ro oper-status?      ipi-mpls-types:mpls_rib_entry_oper_status_t
|     |   +--ro nhlfe-owner?      ipi-mpls-types:mpls_rib_entry_owner_t
|     |   +--ro nhlfe-index?      uint32
|     |   +--ro is-stale?         boolean
|     |   +--ro label-op-code?    ipi-mpls-types:mpls_rib_label_op_code_t
|     |   +--ro in-interface?     string
|     |   +--ro in-label?         uint32
|     +--ro state
|       +--ro fec-prefix6?        cml-data-types:cml_ipv6_prefix_t

```

---

---

```

|   +--ro owner?          ipi-mpls-types:mpls_rib_entry_owner_t
|   +--ro lsp-type?       ipi-mpls-types:mpls_rib_lsp_type_t
|   +--ro unique-nhlfe-ix? uint32
|   +--ro ftn-index?      uint32
|   +--ro is-primary?     boolean
|   +--ro route-distance? uint8
|   +--ro redirect-action-type? ipi-mpls-types:mpls_rib_action_type_t
|   +--ro qos-exp-bits?   uint8
|   +--ro is-entropy-label? boolean
|   +--ro in-dscp-class-name? string
|   +--ro tunnel-id?      uint32
|   +--ro protected-lsp-id? uint32
|   +--ro qos-resource-id? uint32
|   +--ro color?          uint32 {feature-list:HAVE_SERVICE_MAPPING}?
|   +--ro tunnel-policy-name? string {feature-list:HAVE_SERVICE_MAPPING}?
|   +--ro rsvp-multipath-name? string {feature-list:HAVE_RSVP_MULTIPATH}?
|   +--ro row-status?     string
|   +--ro state?          string
|   +--ro create-time?    cml-data-types:cml_line_t
|   +--ro up-time?        cml-data-types:cml_line_t
|   +--ro last-update?    cml-data-types:cml_line_t
|   +--ro description?    string
+--ro vrf-name? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name {feature-list:HAVE_VRF}?

```

---

## module: ipi-mpls

```

+--rw mpls
  +--rw l2vpn
    | +--rw customer-service-templates
    | | +--rw customer-service-template* [name] {feature-list:HAVE_VPLS_OR_HAVE_MPLS_VC}?
    | |   +--rw name          -> ../config/name
    | |   +--rw config
    | | | +--rw name?          string
    | | | +--rw match-all?    empty

```

```

| | | +--rw match-single-tag-outer-vlan-range* string
| | | +--rw match-untagged?          empty
| | +--ro state
| | | +--ro name?                    string
| | | +--ro match-all?              empty
| | | +--ro match-single-tag-outer-vlan-range* string
| | | +--ro match-untagged?          empty
| | +--rw double-tags
| | | +--rw double-tag* [match-outer-vlan-id]
| | |   +--rw match-outer-vlan-id  -> ../config/match-outer-vlan-id
| | |   +--rw config
| | |     | +--rw match-outer-vlan-id? uint16
| | |     | +--rw match-inner-vlan-id* string
| | |     +--ro state
| | |       +--ro match-outer-vlan-id? uint16
| | |       +--ro match-inner-vlan-id* string
| | +--rw action-types
| | | +--rw action-type* [vlan-action-type]
| | |   +--rw vlan-action-type  -> ../config/vlan-action-type
| | |   +--rw config
| | |     | +--rw vlan-action-type?    ipi-mpls-types:mpls_l2vpn_vlan_action_type_t
| | |     | +--rw outer-vlan-identifier? uint16
| | |     | +--rw tag-protocol-identifier? ipi-mpls-types:mpls_svc_tpid_t
| | |     +--ro state
| | |       +--ro vlan-action-type?    ipi-mpls-types:mpls_l2vpn_vlan_action_type_t
| | |       +--ro outer-vlan-identifier? uint16
| | |       +--ro tag-protocol-identifier? ipi-mpls-types:mpls_svc_tpid_t
| | +--ro map-list* [vpls-name] {feature-list:HAVE_VPLS}?
| |   +--ro vpls-name  -> ../state/vpls-name
| |   +--ro state
| |     +--ro vpls-name?      string
| |     +--ro error-status?   ipi-mpls-types:mpls_l2vpn_serv_temp_error_status_t
| |     +--ro binding-interface-name? string
| +--rw access-circuit-groups
|   +--rw access-circuit-group* [group-name] {feature-list:HAVE_MPLS_VC}?
|     +--rw group-name  -> ../config/group-name

```

```

|   +--rw config
|   |   +--rw group-name?    string
|   |   +--rw group-identifier uint32
|   +--ro state
|       +--ro group-name?    string
|       +--ro group-identifier uint32
+--rw global
| +--rw config
| | +--rw local-packet-handling? empty
| | +--rw lsp-stitching?        empty
| | +--rw propagate-ttl?        empty
| | +--rw ingress-ttl-value?    uint8
| | +--rw lsp-model-uniform?    empty
| | +--rw lsp-encap-dscp-preserve? empty {feature-list:HAVE_DUNE}?
| | +--rw six-pe-dscp-preserve? ipi-mpls-types:mpls_dscp_preserve_state_t {feature-list:HAVE_6PE,feature-
list:HAVE_DUNE}?
| +--ro state
| | +--ro local-packet-handling? empty
| | +--ro lsp-stitching?        empty
| | +--ro propagate-ttl?        empty
| | +--ro ingress-ttl-value?    uint8
| | +--ro lsp-model-uniform?    empty
| | +--ro lsp-encap-dscp-preserve? empty {feature-list:HAVE_DUNE}?
| | +--ro six-pe-dscp-preserve? ipi-mpls-types:mpls_dscp_preserve_state_t {feature-list:HAVE_6PE,feature-
list:HAVE_DUNE}?
| +--ro graceful-restart {feature-list:HAVE_RESTART}?
| +--ro rsvp
| | +--ro state
| | | +--ro graceful-restart-state? ipi-mpls-types:mpls_graceful_restart_status_t
| | | +--ro remaining-restart-time? uint32
| | | +--ro disconnected-time?      yang:date-and-time
| +--ro ldp
|   +--ro state
|       +--ro graceful-restart-state? ipi-mpls-types:mpls_graceful_restart_status_t
|       +--ro remaining-restart-time? uint32
|       +--ro disconnected-time?      yang:date-and-time
+--rw interfaces

```

```

| +--rw interface* [name]
|   +--rw name          -> ../config/name
|   +--rw config
|     | +--rw name?    -> /ipi-interface:interfaces/interface/name
|     +--ro state
|       | +--ro name?  -> /ipi-interface:interfaces/interface/name
|       +--rw label-switching
|         | +--rw config!
|         | | +--rw enable      empty
|         | | +--rw label-space? uint16
|         | | +--ro state
|         | |   +--ro enable      empty
|         | |   +--ro label-space? uint16
|         +--rw mpls-interface-bandwidth
|           +--rw config
|             | +--rw admin-group-name*      -> /ipi-global-te:admin-groups/admin-group/name {feature-list:HAVE_TE}?
|             | +--rw extended-admin-group-name* -> /ipi-global-te:extended-admin-groups/extended-admin-group/name
|             {feature-list:HAVE_TE}?
|               | +--rw bandwidth?          string {feature-list:HAVE_TE,feature-list:NOT_IF_BANDWIDTH_INFO}?
|               | +--rw reservable-bandwidth?  string {feature-list:HAVE_TE}?
|               | +--rw shared-risk-link-group* uint32 {feature-list:HAVE_SRLG}?
|               | +--rw uni-available-bandwidth? string {feature-list:HAVE_TE,feature-list:NOT_IF_BANDWIDTH_INFO}?
|               | +--rw uni-residual-bandwidth? string {feature-list:HAVE_TE,feature-list:NOT_IF_BANDWIDTH_INFO}?
|               | +--rw uni-utilized-bandwidth? string {feature-list:HAVE_TE,feature-list:NOT_IF_BANDWIDTH_INFO}?
|               +--ro state
|                 +--ro admin-group-name*      -> /ipi-global-te:admin-groups/admin-group/name {feature-list:HAVE_TE}?
|                 +--ro extended-admin-group-name* -> /ipi-global-te:extended-admin-groups/extended-admin-group/name
|                 {feature-list:HAVE_TE}?
|                   +--ro bandwidth?          string {feature-list:HAVE_TE,feature-list:NOT_IF_BANDWIDTH_INFO}?
|                   +--ro reservable-bandwidth?  string {feature-list:HAVE_TE}?
|                   +--ro shared-risk-link-group* uint32 {feature-list:HAVE_SRLG}?
|                   +--ro uni-available-bandwidth? string {feature-list:HAVE_TE,feature-list:NOT_IF_BANDWIDTH_INFO}?
|                   +--ro uni-residual-bandwidth? string {feature-list:HAVE_TE,feature-list:NOT_IF_BANDWIDTH_INFO}?
|                   +--ro uni-utilized-bandwidth? string {feature-list:HAVE_TE,feature-list:NOT_IF_BANDWIDTH_INFO}?
+--rw label-spaces
| +--rw label-space* [label-space-name]
|   +--rw label-space-name  -> ../config/label-space-name

```

---

```

| +--rw config
| | +--rw label-space-name? uint16
| +--ro state
| | +--ro label-space-name? uint16
| +--rw global-label-range
| | +--rw config!
| | | +--rw min-label uint32
| | | +--rw max-label uint32
| | +--ro state
| | +--ro min-label uint32
| | +--ro max-label uint32
| +--rw module-label-ranges
|   +--rw module-label-range* [module-name]
|     +--rw module-name -> ../config/module-name
|     +--rw config
|       | +--rw module-name? ipi-mpls-types:mpls_module_t
|       | +--rw min-label uint32
|       | +--rw max-label uint32
|       +--ro state
|         +--ro module-name? ipi-mpls-types:mpls_module_t
|         +--ro min-label uint32
|         +--ro max-label uint32
+--rw ecmp
| +--rw config
| | +--rw ftn-ecmp-protocol? ipi-mpls-types:mpls_ecmp_protocol_t {feature-list:HAVE_MPLS_ECMP}?
| | +--rw ilm-ecmp-protocol? ipi-mpls-types:mpls_ecmp_protocol_t {feature-list:HAVE_MPLS_ECMP}?
| +--ro state
| +--ro ftn-ecmp-protocol? ipi-mpls-types:mpls_ecmp_protocol_t {feature-list:HAVE_MPLS_ECMP}?
| +--ro ilm-ecmp-protocol? ipi-mpls-types:mpls_ecmp_protocol_t {feature-list:HAVE_MPLS_ECMP}?
+--rw six-pe-tunnel-policies {feature-list:HAVE_SERVICE_MAPPING,feature-list:HAVE_6PE}?
| +--rw six-pe-tunnel-policy* [name]
|   +--rw name -> ../config/name
|   +--rw config
|     | +--rw name? string
|     +--ro state
|       +--ro name? string

```

---

```

+--rw bandwidth-classes
  +--rw bandwidth-class* [name] {feature-list:HAVE_TE}?
    +--rw name      -> ../config/name
    +--rw config
      | +--rw name?  string
    +--ro state
      | +--ro name?  string
    +--rw properties
      +--rw config!
        | +--rw max-bandwidth  string
        | +--rw setup-priority  uint8
        | +--rw hold-priority   uint8
      +--ro state
        +--ro max-bandwidth  string
        +--ro setup-priority  uint8
        +--ro hold-priority   uint8

```

---

## module: ipi-mrib

```

+--rw mrib
  +--rw ipv4
    | +--rw vrfs
    | | +--rw vrf* [vrf-name]
    | |   +--rw vrf-name      -> ../config/vrf-name
    | |   +--rw config
    | | | +--rw vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
    | | | +--rw multicast-routing-enable?  empty
    | |   +--ro state
    | | | +--ro counters
    | | | | +--ro total-multicast-routes?  yang:counter32
    | | | | +--ro dense-mode-multicast-routes?  yang:counter32

```

---

```

| | | +--ro sparse-mode-multicast-routes? yang:counter32
| | | +--ro no-cache-received?          yang:counter32
| | | +--ro no-cache-sent?              yang:counter32
| | | +--ro wrong-VIF-received?         yang:counter32
| | | +--ro wrong-VIF-sent?            yang:counter32
| | | +--ro whole-packet-received?     yang:counter32
| | | +--ro whole-packet-sent?         yang:counter32
| | | +--ro immediate-stat-updates-sent? yang:counter32
| | | +--ro timed-stat-updates-sent?   yang:counter32
| | | +--ro register-packets-sent?     yang:counter32
| | | +--ro register-acks-received?    yang:counter32
| | | +--ro register-nacks-received?   yang:counter32
| | | +--ro no-cache-receive-rate?     decimal64
| | | +--ro register-packet-sent-rate?  decimal64
| | | +--ro vrf-name?                  -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
| | | +--ro multicast-routing-enable?  empty
| | | +--ro stats-poll-expiry-time?    string
| | +--rw route-limit
| | | +--rw config
| | | | +--rw maximum-routes?         uint32
| | | | +--rw warning-threshold?     uint32
| | | +--ro state
| | | | +--ro maximum-routes?         uint32
| | | | +--ro warning-threshold?     uint32
| | +--rw debug
| | | +--rw config
| | | | +--rw options?               ipi-mrib-types:mrib_debug_t
| | | | +--ro state
| | | | +--ro options?               ipi-mrib-types:mrib_debug_t
| | | | +--ro terminal-debug-status?  ipi-mrib-types:mrib_debug_t
| | +--ro multicast-routes
| | | +--ro multicast-route* [source group]
| | | | +--ro source                  -> ../state/source
| | | | +--ro group                   -> ../state/group
| | | | +--ro state
| | | | | +--ro counters

```

---

```

| | | | +--ro packets-forwarded? yang:counter32
| | | | +--ro bytes-forwarded? yang:counter32
| | | | +--ro wrong-VIF-sent? yang:counter32
| | | | +--ro wrong-VIF-received? yang:counter32
| | | | +--ro source? inet:ip-address
| | | | +--ro group? inet:ip-address
| | | | +--ro incoming-interface? string
| | | | +--ro rpf-address? inet:ip-address
| | | | +--ro route-type? ipi-mrib-types:mrib_route_type_t
| | | | +--ro uptime? string
| | | | +--ro stats-poll-expiry-time? string
| | | | +--ro immediate-stats? empty
| | | | +--ro timed-stats? empty
| | | | +--ro forwarder-installed? empty
| | +--ro outgoing-interfaces
| |   +--ro outgoing-interface* [name]
| |     +--ro name -> ../state/name
| |     +--ro state
| |       +--ro name? -> /ipi-interface:interfaces/interface/name
| |       +--ro time-to-live? uint8
| +--rw interfaces
|   +--rw interface* [name]
|     +--rw name -> ../config/name
|     +--rw config
|       | +--rw name? -> /ipi-interface:interfaces/interface/name
|       | +--rw ttl-threshold? uint8
|       +--ro state
|         +--ro name? -> /ipi-interface:interfaces/interface/name
|         +--ro ttl-threshold? uint8
|         +--ro local-address? inet:ip-address {feature-list:HAVE_MRIB_IPV4}?
|         +--ro remote-address? inet:ip-address {feature-list:HAVE_MRIB_IPV4}?
|         +--ro uptime? string
|         +--ro module-name? string
|         +--ro vif-index? uint32
+--rw ipv6
  +--rw vrfs

```

```

| +--rw vrf* [vrf-name]
|   +--rw vrf-name      -> ../config/vrf-name
|   +--rw config
|     | +--rw vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
|     | +--rw multicast-routing-enable? empty
|     | +--ro state
|     |   +--ro counters
|     |     | +--ro total-multicast-routes?    yang:counter32
|     |     | +--ro dense-mode-multicast-routes? yang:counter32
|     |     | +--ro sparse-mode-multicast-routes? yang:counter32
|     |     | +--ro no-cache-received?        yang:counter32
|     |     | +--ro no-cache-sent?            yang:counter32
|     |     | +--ro wrong-VIF-received?       yang:counter32
|     |     | +--ro wrong-VIF-sent?          yang:counter32
|     |     | +--ro whole-packet-received?    yang:counter32
|     |     | +--ro whole-packet-sent?        yang:counter32
|     |     | +--ro immediate-stat-updates-sent? yang:counter32
|     |     | +--ro timed-stat-updates-sent?  yang:counter32
|     |     | +--ro register-packets-sent?    yang:counter32
|     |     | +--ro register-acks-received?   yang:counter32
|     |     | +--ro register-nacks-received?  yang:counter32
|     |     | +--ro no-cache-receive-rate?    decimal64
|     |     | +--ro register-packet-sent-rate? decimal64
|     |     | +--ro vrf-name?                -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
|     |     | +--ro multicast-routing-enable? empty
|     |     | +--ro stats-poll-expiry-time?   string
|     |     | +--rw route-limit
|     |     |   +--rw config
|     |     |     | +--rw maximum-routes?    uint32
|     |     |     | +--rw warning-threshold? uint32
|     |     |     | +--ro state
|     |     |     |   +--ro maximum-routes?  uint32
|     |     |     |   +--ro warning-threshold? uint32
|     |     |     | +--rw debug
|     |     |     |   +--rw config

```

```

| | | +--rw options? ipi-mrib-types:mrib_debug_t
| | +--ro state
| | +--ro options? ipi-mrib-types:mrib_debug_t
| | +--ro terminal-debug-status? ipi-mrib-types:mrib_debug_t
| +--ro multicast-routes
|   +--ro multicast-route* [source group]
|     +--ro source -> ../state/source
|     +--ro group -> ../state/group
|     +--ro state
|       | +--ro counters
|       | | +--ro packets-forwarded? yang:counter32
|       | | +--ro bytes-forwarded? yang:counter32
|       | | +--ro wrong-VIF-sent? yang:counter32
|       | | +--ro wrong-VIF-received? yang:counter32
|       | | +--ro source? inet:ip-address
|       | | +--ro group? inet:ip-address
|       | | +--ro incoming-interface? string
|       | | +--ro rpf-address? inet:ip-address
|       | | +--ro route-type? ipi-mrib-types:mrib_route_type_t
|       | | +--ro uptime? string
|       | | +--ro stats-poll-expiry-time? string
|       | | +--ro immediate-stats? empty
|       | | +--ro timed-stats? empty
|       | | +--ro forwarder-installed? empty
|       +--ro outgoing-interfaces
|         +--ro outgoing-interface* [name]
|           +--ro name -> ../state/name
|           +--ro state
|             +--ro name? -> /ipi-interface:interfaces/interface/name
|             +--ro time-to-live? uint8
+--rw interfaces
+--rw interface* [name]
+--rw name -> ../config/name
+--rw config
| +--rw name? -> /ipi-interface:interfaces/interface/name
| +--rw ttl-threshold? uint8

```

```
+--ro state
  +--ro name?      -> /ipi-interface:interfaces/interface/name
  +--ro ttl-threshold?  uint8
  +--ro local-address?  inet:ip-address {feature-list:HAVE_MRIB_IPV4}?
  +--ro remote-address? inet:ip-address {feature-list:HAVE_MRIB_IPV4}?
  +--ro uptime?      string
  +--ro module-name?  string
  +--ro vif-index?    uint32
```

rpcs:

```
+---x mrib-ipv4-terminal-debug-on {feature-list:HAVE_MRIBD}?
| +---w input
|   +---w vrf-name?      string
|   +---w terminal-debug-options  ipi-mrib-types:mrib_debug_t
+---x mrib-ipv4-terminal-debug-off {feature-list:HAVE_MRIBD}?
| +---w input
|   +---w vrf-name?      string
|   +---w terminal-debug-options  ipi-mrib-types:mrib_debug_t
+---x mrib-ipv4-clear-mroute-all {feature-list:HAVE_MRIBD}?
| +---w input
|   +---w vrf-name?  string
|   +---w all-routes  empty
+---x mrib-ipv4-clear-mroute-group {feature-list:HAVE_MRIBD}?
| +---w input
|   +---w vrf-name?  string
|   +---w group-address  inet:ipv4-address
+---x mrib-ipv4-clear-mroute-source-group {feature-list:HAVE_MRIBD}?
| +---w input
|   +---w vrf-name?  string
|   +---w source-address  inet:ipv4-address
|   +---w group-address  inet:ipv4-address
+---x mrib-ipv4-clear-mroute-statistics-all {feature-list:HAVE_MRIBD}?
| +---w input
|   +---w vrf-name?  string
|   +---w all-routes  empty
+---x mrib-ipv4-clear-mroute-statistics-group {feature-list:HAVE_MRIBD}?
```

---

```
| +---w input
|   +---w vrf-name?    string
|   +---w group-address  inet:ipv4-address
+---x mrib-ipv4-clear-mroute-statistics-source-group {feature-list:HAVE_MRIBD}?
| +---w input
|   +---w vrf-name?    string
|   +---w source-address  inet:ipv4-address
|   +---w group-address  inet:ipv4-address
+---x mrib-ipv4-snmpr-restart {feature-list:HAVE_SNMP}?
+---x mrib-ipv6-terminal-debug-on {feature-list:HAVE_MRIBD,feature-list:HAVE_MCAST_IPV6}?
| +---w input
|   +---w vrf-name?    string
|   +---w terminal-debug-options  ipi-mrib-types:mrib_debug_t
+---x mrib-ipv6-terminal-debug-off {feature-list:HAVE_MRIBD,feature-list:HAVE_MCAST_IPV6}?
| +---w input
|   +---w vrf-name?    string
|   +---w terminal-debug-options  ipi-mrib-types:mrib_debug_t
+---x mrib-ipv6-clear-mroute-all {feature-list:HAVE_MRIBD,feature-list:HAVE_MCAST_IPV6}?
| +---w input
|   +---w vrf-name    string
|   +---w all-routes  empty
+---x mrib-ipv6-clear-mroute-group {feature-list:HAVE_MRIBD,feature-list:HAVE_MCAST_IPV6}?
| +---w input
|   +---w vrf-name    string
|   +---w group-address  inet:ipv6-address
+---x mrib-ipv6-clear-mroute-source-group {feature-list:HAVE_MRIBD,feature-list:HAVE_MCAST_IPV6}?
| +---w input
|   +---w vrf-name    string
|   +---w source-address  inet:ipv6-address
|   +---w group-address  inet:ipv6-address
+---x mrib-ipv6-clear-mroute-statistics-all {feature-list:HAVE_MRIBD,feature-list:HAVE_MCAST_IPV6}?
| +---w input
|   +---w vrf-name    string
|   +---w all-routes  empty
+---x mrib-ipv6-clear-mroute-statistics-group {feature-list:HAVE_MRIBD,feature-list:HAVE_MCAST_IPV6}?
| +---w input
```

---

```

| +---w vrf-name      string
| +---w group-address inet:ipv6-address
+---x mrib-ipv6-clear-mroute-statistics-source-group {feature-list:HAVE_MRIBD,feature-list:HAVE_MCAST_IPV6}?
  +---w input
    +---w vrf-name      string
    +---w source-address inet:ipv6-address
    +---w group-address inet:ipv6-address

```

---

## module: ipi-neighbor-discovery

```

+--rw neighbor-discovery
  +--rw entries
    | +--rw entry* [ipv6-address interface-name]
    |   +--rw ipv6-address  -> ../config/ipv6-address
    |   +--rw interface-name -> ../config/interface-name
    |   +--rw config
    |     | +--rw ipv6-address?  inet:ipv6-address
    |     | +--rw interface-name? -> /ipi-interface:interfaces/interface/name
    |     | +--rw mac-address    cml-data-types:cml_mac_addr_t
    |     +--ro state
    |       +--ro ipv6-address?  inet:ipv6-address
    |       +--ro interface-name? -> /ipi-interface:interfaces/interface/name
    |       +--ro mac-address    cml-data-types:cml_mac_addr_t
    |       +--ro neighbor-age?   string
    |       +--ro neighbor-source? ipi-nd-types:ndd_nd_src_type_t
    |       +--ro neighbor-state? ipi-nd-types:ndd_nd_state_t
    |       +--ro neighbor-if-state? ipi-nd-types:ndd_nd_if_type_t
  +--rw debug
    | +--rw config
    |   | +--rw enable?  empty
    |   +--ro state
    |     +--ro enable?          empty
    |     +--ro terminal-debug-status? cml-data-types:cml_on_off_t
  +--rw interfaces
    | +--rw interface* [name]

```

```

| +--rw name    -> ../config/name
| +--rw config
| | +--rw name?          -> /ipi-interface:interfaces/interface/name
| | +--rw nd-ageing-timeout?  uint16
| | +--rw nd-reachable-time?  uint32
| | +--rw no-ip-unreachable?  empty
| | +--rw no-ipv6-unreachable? empty
| +--ro state
|   +--ro name?          -> /ipi-interface:interfaces/interface/name
|   +--ro nd-ageing-timeout?  uint16
|   +--ro nd-reachable-time?  uint32
|   +--ro no-ip-unreachable?  empty
|   +--ro no-ipv6-unreachable? empty
+--ro dynamic-neighbor-discovery* [vrf-name]
  +--ro vrf-name      string
  +--ro entry* [ipv6-address]
    | +--ro ipv6-address    inet:ipv6-address
    | +--ro mac-address?    cml-data-types:cml_mac_addr_t
    | +--ro interface-name? string
    | +--ro neighbor-age?   string
    | +--ro neighbor-source? ipi-nd-types:ndd_nd_src_type_t
    | +--ro neighbor-state? ipi-nd-types:ndd_nd_state_t
    | +--ro neighbor-if-state? ipi-nd-types:ndd_nd_if_type_t
  +--ro adjacency-summary
    +--ro resolved-arp?    uint32
    +--ro incomplete-arp?  uint32
    +--ro unknown-arp?    uint32
    +--ro total-arp?      uint32

```

rpcs:

```

+---x nd-terminal-debug-on {feature-list:HAVE_L3,feature-list:HAVE_IPV6,feature-list:HAVE_NDD}?
+---x nd-terminal-debug-off {feature-list:HAVE_L3,feature-list:HAVE_IPV6,feature-list:HAVE_NDD}?
+---x clear-ipv6-nd-entry {feature-list:HAVE_L3,feature-list:HAVE_IPV6,feature-list:HAVE_NDD}?
| +---w input
|   +---w ipv6-address?  cml-data-types:cml_ipv6_prefix_t
|   +---w vrf-name?     string

```

---

```
+---x clear-ipv6-nd-entry-per-interface {feature-list:HAVE_L3,feature-list:HAVE_IPV6,feature-list:HAVE_NDD}?
+---w input
+---w if-name    string
+---w vrf-name?  string
```

---

## module: ipi-network-instance

```
+--rw network-instances
+--rw network-instance* [instance-name instance-type]
+--rw instance-name    -> ../config/instance-name
+--rw instance-type    -> ../config/instance-type
+--rw config
| +--rw instance-name?  string
| +--rw instance-type? ipi-network-instance-types:net_inst_type_t
+--ro state
+--ro instance-name?   string
+--ro instance-type?  ipi-network-instance-types:net_inst_type_t
```

---

## module: ipi-network-services-manager

```
+--rw network-services-manager
+--rw debug
+--rw nsm
| +--rw config
| | +--rw options? ipi-network-services-manager-types:nsm_debug_t
| +--ro state
|   +--ro options? ipi-network-services-manager-types:nsm_debug_t
+--rw pkt-mgr
| +--rw config
| | +--rw options? ipi-network-services-manager-types:nsm_pkt_mgr_debug_t {feature-list:HAVE_L2}?
| +--ro state
|   +--ro options? ipi-network-services-manager-types:nsm_pkt_mgr_debug_t {feature-list:HAVE_L2}?
+--rw hsl {feature-list:HAVE_USER_HSL}?
```

---

```

| +--rw hsl-module* [module-name]
|   +--rw module-name  -> ../config/module-name
|   +--rw config
|     | +--rw module-name?  ipi-network-services-manager-types:hsl_debug_module_t
|     | +--rw level        ipi-network-services-manager-types:hsl_debug_level_t
|     +--ro state
|       +--ro module-name?  ipi-network-services-manager-types:hsl_debug_module_t
|       +--ro level        ipi-network-services-manager-types:hsl_debug_level_t
+--ro terminal
  +--ro nsm
  | +--ro state
  | +--ro terminal-debug-status?  ipi-network-services-manager-types:nsm_debug_t
  +--ro pkt-mgr
  +--ro state
    +--ro terminal-debug-status?  ipi-network-services-manager-types:nsm_pkt_mgr_debug_t {feature-
list:HAVE_L2}?

```

rpcs:

```

+---x nsm-terminal-debug-on
| +---w input
|   +---w terminal-debug-options  ipi-network-services-manager-types:nsm_exec_debug_t
+---x nsm-terminal-debug-off
| +---w input
|   +---w terminal-debug-options  ipi-network-services-manager-types:nsm_exec_debug_t
+---x hsl-terminal-debug-on {feature-list:NOT_HAVE_SWFWDR,feature-list:HAVE_HAL}?
| +---w input
|   +---w module-name  ipi-network-services-manager-types:hsl_debug_module_t
|   +---w level        ipi-network-services-manager-types:hsl_debug_level_t
+---x hsl-terminal-debug-off {feature-list:NOT_HAVE_SWFWDR,feature-list:HAVE_HAL}?
| +---w input
|   +---w module-name  ipi-network-services-manager-types:hsl_debug_module_t
|   +---w level        ipi-network-services-manager-types:hsl_debug_level_t
+---x pktmgr-terminal-debug-on {feature-list:HAVE_L2}?
| +---w input
|   +---w terminal-debug-options  ipi-network-services-manager-types:nsm_pkt_mgr_debug_t
+---x pktmgr-terminal-debug-off {feature-list:HAVE_L2}?
+---x pktmgr-debug-statistics-enable

```

```

+---x pktmgr-debug-statistics-disable
+---x pktmgr-debug-statistics-get
+---x pktmgr-debug-error-statistics-get
| +---w input
|   +---w debug-error-statistics   ipi-network-services-manager-types:nsm_pktmgr_statistics_type_t
+---x clear-nsm-ipc-statistics {feature-list:HAVE_ASYNC}?
+---x clear-nsm-server-ipc-statistics
+---x nsm-snmp-restart {feature-list:HAVE_SNMP}?

```

---

## module: ipi-ntp

```

+--rw ntp
  +--rw vrfs
    | +--rw vrf* [vrf-name]
    |   +--rw vrf-name          -> ../config/vrf-name
    |   +--rw config
    |     | +--rw vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
    |     | +--rw feature-enable?  boolean
    |     | +--rw enable-ntp?     boolean
    |     | +--rw enable-logging?  empty
    |     +--ro state
    |       | +--ro vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
    |       | +--ro feature-enable?  boolean
    |       | +--ro enable-ntp?     boolean
    |       | +--ro enable-logging?  empty
    |       +--rw ref-clock-master
    |         | +--rw config!
    |         | | +--rw enable-local-master  empty
    |         | | +--rw local-stratum?     uint8
    |         | +--ro state
    |         |   +--ro enable-local-master  empty
    |         |   +--ro local-stratum?     uint8
    |         +--rw authentication
    |           | +--rw config
    |           | | +--rw enable-ntp-auth?  empty

```

---

```
| | | +--rw ntp-trusted-keys* uint32
| | | +--rw ntp-request-key? uint32
| | +--ro state
| | | +--ro enable-ntp-auth? empty
| | | +--ro ntp-trusted-keys* uint32
| | | +--ro ntp-request-key? uint32
| | +--rw ntp-keys
| |   +--rw ntp-key* [key-id]
| |     +--rw key-id -> ../config/key-id
| |     +--rw config
| |       | +--rw key-id? uint32
| |       | +--rw key-value string
| |       | +--rw key-type ipi-ntp-types:ntp_hostp_key_type_t
| |       +--ro state
| |         +--ro key-id? uint32
| |         +--ro key-value string
| |         +--ro key-type ipi-ntp-types:ntp_hostp_key_type_t
| +--rw servers
| | +--rw server* [server-address]
| |   +--rw server-address -> ../config/server-address
| |   +--rw config
| |     | +--rw server-address? string
| |     | +--rw prefer? empty
| |     | +--rw auth-key? uint32
| |     | +--rw minpoll? uint16
| |     | +--rw maxpoll? uint16
| |     +--ro state
| |       +--ro server-address? string
| |       +--ro prefer? empty
| |       +--ro auth-key? uint32
| |       +--ro minpoll? uint16
| |       +--ro maxpoll? uint16
| +--rw peers
| | +--rw peer* [peer-address]
| |   +--rw peer-address -> ../config/peer-address
| |   +--rw config
```

---

```
| | | +--rw peer-address? string
| | | +--rw prefer?      empty
| | | +--rw auth-key?    uint32
| | | +--rw minpoll?     uint16
| | | +--rw maxpoll?     uint16
| | +--ro state
| |   +--ro peer-address? string
| |   +--ro prefer?      empty
| |   +--ro auth-key?    uint32
| |   +--ro minpoll?     uint16
| |   +--ro maxpoll?     uint16
| +--rw rate-limiting
| | +--rw config
| | | +--rw minimum-pkt-spacing? uint16
| | | +--ro state
| | |   +--ro minimum-pkt-spacing? uint16
| +--rw access-control-entries
|   +--rw access-control-entry* [client-ip-address]
|     +--rw client-ip-address  -> ../config/client-ip-address
|     +--rw config
|       | +--rw client-ip-address? inet:ip-address
|       | +--rw netmask?          ipi-ntp-types:ntp_client_ip_net_mask_t
|       | +--rw access-options?   ipi-ntp-types:ntp_acl_options_t
|       +--ro state
|         +--ro client-ip-address? inet:ip-address
|         +--ro netmask?          ipi-ntp-types:ntp_client_ip_net_mask_t
|         +--ro access-options?   ipi-ntp-types:ntp_acl_options_t
+--rw debug
| +--rw config
| | +--rw enable?  empty
| | +--ro state
| |   +--ro enable?          empty
| |   +--ro terminal-debug-status? cml-data-types:cml_on_off_t
+--ro peer-info
  +--ro peers
    +--ro peer* [peer-address]
```

---

```

+--ro peer-address -> ../state/peer-address
+--ro state
  +--ro peer-address?  cml-data-types:cml_hostname_t
  +--ro stratum?      uint8
  +--ro poll-interval? uint32
  +--ro reach-value?  uint16
  +--ro root-delay?   decimal64
  +--ro offset?       decimal64

```

rpcs:

```

+---x ntp-clear-statistics {feature-list:HAVE_HOSTPD,feature-list:HAVE_HOSTP_NTP}?
| +---w input
|   +---w statistics-type  ipi-ntp-types:ntp_statistics_type_t
+---x ntp-retry-server-synchronization {feature-list:HAVE_HOSTPD,feature-list:HAVE_HOSTP_NTP}?
| +---w input
|   +---w vrf-name  string
+---x ntp-terminal-debug-on {feature-list:HAVE_HOSTPD,feature-list:HAVE_HOSTP_NTP}?
+---x ntp-terminal-debug-off {feature-list:HAVE_HOSTPD,feature-list:HAVE_HOSTP_NTP}?

```

---

## module: ipi-object-tracking

```

+--rw object-tracking
  +--rw trackers
  | +--rw tracker* [tracker-id]
  |   +--rw tracker-id -> ../config/tracker-id
  |   +--rw config
  |     | +--rw tracker-id?  uint16
  |     | +--rw ip-sla-id   uint16
  |     | +--rw delay-up?   uint16
  |     | +--rw delay-down? uint16
  |     +--ro state
  |       +--ro tracker-id?   uint16
  |       +--ro ip-sla-id     uint16
  |       +--ro delay-up?     uint16
  |       +--ro delay-down?   uint16

```

```

|   +--ro reachability-status? ipi-object-tracking-types:object_tracking_reachability_status_t {feature-
list:HAVE_OBJ_TRACKING}?
+--rw interfaces
+--rw interface* [name]
+--rw name          -> ../config/name
+--rw config
| +--rw name?       -> /ipi-interface:interfaces/interface/name
| +--rw select-option? ipi-object-tracking-types:object_tracking_select_option_t
+--ro state
| +--ro name?       -> /ipi-interface:interfaces/interface/name
| +--ro select-option? ipi-object-tracking-types:object_tracking_select_option_t
+--rw track-interfaces
+--rw track-interface* [track-id]
+--rw track-id     -> ../config/track-id
+--rw config
| +--rw track-id?  uint32
+--ro state
+--ro track-id?   uint32

```

---

## module: ipi-ospf-interface-tracking

```

+--rw ospf-interfaces-events-tracking
+--rw ospf-interface-events-tracking* [event-name]
+--rw event-name  -> ../config/event-name
+--rw config
| +--rw event-name?      string
| +--rw event-match-criteria ipi-ospf-interface-tracking-types:intf_track_match_type_t
| +--rw event-neighbor-ip-address* inet:ipv4-address
+--ro state

```

---

```

| +--ro event-name?          string
| +--ro event-match-criteria ipi-ospf-interface-tracking-types:intf_track_match_type_t
| +--ro event-neighbor-ip-address* inet:ipv4-address
+--rw actions
  +--rw interfaces
    +--rw interface* [name]
      +--rw name    -> ../config/name
      +--rw config
        | +--rw name? -> /ipi-interface:interfaces/interface/name
        | +--rw cost  uint32
      +--ro state
        +--ro name? -> /ipi-interface:interfaces/interface/name
        +--ro cost  uint32

```

---

## module: ipi-ospf

```

+--rw ospfv2
  +--rw global
    | +--rw config
    | | +--rw area-interface-config-mode?    empty
    | | +--rw enable-multi-instance-capability? empty {feature-list:HAVE_OSPF_MULTI_INST}?
    | +--ro state
    | | +--ro area-interface-config-mode?    empty
    | | +--ro enable-multi-instance-capability? empty {feature-list:HAVE_OSPF_MULTI_INST}?
    | +--rw graceful-restart {feature-list:HAVE_RESTART}?
    |   +--rw config
    |   | +--rw grace-period?  uint16
    |   +--ro state
    |   | +--ro grace-period?  uint16

```

```

| +--rw helper
|   +--rw config
|     | +--rw max-grace-period?   uint16
|     | +--rw disable-all-neighbors? empty
|     | +--rw disable-neighbor*   inet:ipv4-address
|     +--ro state
|       +--ro max-grace-period?   uint16
|       +--ro disable-all-neighbors? empty
|       +--ro disable-neighbor*   inet:ipv4-address
+--rw processes
| +--rw process* [ospf-id]
|   +--rw ospf-id          -> ../config/ospf-id
|   +--rw config
|     | +--rw ospf-id?          uint16
|     | +--rw vrf-name          -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name {feature-list:HAVE_VRF}?
|     | +--rw router-id?       inet:ipv4-address
|     | +--rw flood-reduction?  empty
|     | +--rw rfc1583-compatibility? empty
|     | +--rw database-summary?  empty
|     | +--rw bfd-enable-all-interfaces? empty {feature-list:HAVE_BFD}?
|     | +--rw log-adjacency-changes? ipi-ospf-types:ospf_log_adj_opt_t
|     | +--rw shutdown?        empty
|     | +--rw area-border-type?  ipi-ospf-types:ospf_abr_type_t
|     | +--rw reference-bandwidth? uint32
|     | +--rw max-database-descriptors? uint16
|     | +--rw p2p-rfc-incompatible? empty
|     | +--rw context-name?     string
|     +--ro state
|       | +--ro statistics
|       | | +--ro router
|       | | | +--ro area-counter? yang:counter64
|       | | | +--ro database-description-exchanges
|       | | | +--ro in? yang:counter64
|       | | | +--ro out? yang:counter64
|       | | +--ro link-state-advertisement
|       | | | +--ro originate? yang:counter64

```

---

```
| | | +--ro received?      yang:counter64
| | | +--ro external?     yang:counter64
| | | +--ro opaque?      yang:counter64
| | | +--ro non-default-external? yang:counter64
| | +--ro router-event
| | | +--ro packet
| | | | +--ro packets-send-buffer? yang:counter64
| | | | +--ro unused-packets?     yang:counter64
| | | | +--ro max-unused-packets? yang:counter64
| | | +--ro lsa
| | | | +--ro older-lsa-received? yang:counter64
| | | | +--ro lsa-buffer?         uint32
| | | +--ro spf
| | | | +--ro full?      yang:counter64
| | | | +--ro summary?  yang:counter64
| | | | +--ro external? yang:counter64
| | | +--ro neighbor
| | | | +--ro state-change?      yang:counter64
| | | | +--ro dead-interval-expiration? yang:counter64
| | | | +--ro bad-link-state-request? yang:counter64
| | | | +--ro sequence-number-mismatch? yang:counter64
| | | +--ro router-id-changes?   yang:counter64
| | | +--ro designated-router-election? yang:counter64
| | +--ro error
| | | +--ro discarded-in?      yang:counter64
| | | +--ro discarded-out?    yang:counter64
| | | +--ro hello-in?        yang:counter64
| | | +--ro database-descriptor-in? yang:counter64
| | | +--ro ls-request-in?    yang:counter64
| | | +--ro ls-update-in?    yang:counter64
| | | +--ro ls-acknowledge-in? yang:counter64
| | | +--ro unknown-in?      yang:counter64
| | | +--ro unknown-out?     yang:counter64
| | | +--ro bad-version?     yang:counter64
| | | +--ro bad-crc?         yang:counter64
| | | +--ro invalid-source?   yang:counter64
```

---

```

| | | +--ro invalid-destination? yang:counter64
| | | +--ro no-neighbor?        yang:counter64
| | | +--ro passive?           yang:counter64
| | | +--ro wrong-area?        yang:counter64
| | | +--ro packets-length?     yang:counter64
| | | +--ro bad-authentication? yang:counter64
| | +--ro traffic
| | | +--ro total-packets-in?    yang:counter64
| | | +--ro total-packets-out?  yang:counter64
| | | +--ro hello-packets-in?   yang:counter64
| | | +--ro hello-packets-out?  yang:counter64
| | | +--ro database-descriptor-packets-in? yang:counter64
| | | +--ro database-descriptor-packets-out? yang:counter64
| | | +--ro ls-request-packets-in? yang:counter64
| | | +--ro ls-request-packets-out? yang:counter64
| | | +--ro ls-update-packets-in? yang:counter64
| | | +--ro ls-update-packets-out? yang:counter64
| | | +--ro ls-acknowledge-packets-in? yang:counter64
| | | +--ro ls-acknowledge-packets-out? yang:counter64
| | +--ro up-time?              string
| | +--ro ospf-id?              uint16
| | +--ro vrf-name              -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name {feature-list:HAVE_VRF}?
| | +--ro router-id?            inet:ipv4-address
| | +--ro flood-reduction?      empty
| | +--ro rfc1583-compatibility? empty
| | +--ro database-summary?     empty
| | +--ro bfd-enable-all-interfaces? empty {feature-list:HAVE_BFD}?
| | +--ro log-adjacency-changes? ipi-ospf-types:ospf_log_adj_opt_t
| | +--ro shutdown?            empty
| | +--ro area-border-type?     ipi-ospf-types:ospf_abr_type_t
| | +--ro reference-bandwidth?  uint32
| | +--ro max-database-descriptors? uint16
| | +--ro p2p-rfc-incompatible? empty
| | +--ro context-name?        string
| | +--ro dste-status?         ipi-ospf-types:ospf_dste_status
| +--ro link-state-database

```

---

```
| | +--ro state
| |   +--ro external-checksum? yang:phys-address
| |   +--ro opaque-checksum?  yang:phys-address
| +--rw passive-interfaces
| | +--rw config
| | | +--rw passive-interface-all? empty
| | | +--ro state
| | | | +--ro passive-interface-all? empty
| | | +--rw passive-interface* [name]
| | |   +--rw name          -> ../config/name
| | |   +--rw config
| | | | +--rw name?        -> /ipi-interface:interfaces/interface/name
| | | | +--rw passive-mode? ipi-ospf-types:ospf_passive_mode_t
| | |   +--ro state
| | | | +--ro name?        -> /ipi-interface:interfaces/interface/name
| | | | +--ro passive-mode? ipi-ospf-types:ospf_passive_mode_t
| | |   +--rw passive-addresses
| | |     +--rw passive-address* [address]
| | |       +--rw address  -> ../config/address
| | |       +--rw config
| | | | +--rw address?     inet:ipv4-address
| | | | +--rw passive-mode ipi-ospf-types:ospf_passive_addr_mode_t
| | |   +--ro state
| | |     +--ro address?   inet:ipv4-address
| | |     +--ro passive-mode ipi-ospf-types:ospf_passive_addr_mode_t
| +--rw default-information
| | +--rw config
| | | +--rw originate?          empty
| | | +--rw always-advertise-default-route? empty
| | | +--rw metric?            uint32
| | | +--rw metric-type?       ipi-ospf-types:ospf_metric_type_t
| | | +--rw route-map?         string
| | | +--ro state
| | |   +--ro originate?          empty
| | |   +--ro always-advertise-default-route? empty
| | |   +--ro metric?            uint32
```

---

```

| | +--ro metric-type?          ipi-ospf-types:ospf_metric_type_t
| | +--ro route-map?           string
| +--rw capability
| | +--rw config
| | | +--rw enable-vrf-lite?    empty {feature-list:HAVE_VRF_OSPF}?
| | | +--rw disable-opaque-lsa? empty {feature-list:HAVE_OPAQUE_LSA}?
| | | +--rw disable-graceful-restart? empty {feature-list:HAVE_RESTART}?
| | | +--rw link-local-signaling? empty {feature-list:HAVE_RESTART}?
| | +--ro state
| | | +--ro enable-vrf-lite?    empty {feature-list:HAVE_VRF_OSPF}?
| | | +--ro disable-opaque-lsa? empty {feature-list:HAVE_OPAQUE_LSA}?
| | | +--ro disable-graceful-restart? empty {feature-list:HAVE_RESTART}?
| | | +--ro link-local-signaling? empty {feature-list:HAVE_RESTART}?
| +--rw areas
| | +--rw area* [area-id]
| | | +--rw area-id      -> ../config/area-id
| | | +--rw config
| | | | +--rw area-id?      ipi-ospf-types:ospf_area_t
| | | | +--rw authentication-type? ipi-ospf-types:ospf_area_authentication_type_t
| | | | +--rw default-cost?   uint32
| | | | +--rw shortcut?      ipi-ospf-types:ospf_area_shortcut_type_t
| | | +--ro state
| | | | +--ro area-id?      ipi-ospf-types:ospf_area_t
| | | | +--ro authentication-type? ipi-ospf-types:ospf_area_authentication_type_t
| | | | +--ro default-cost?   uint32
| | | | +--ro shortcut?      ipi-ospf-types:ospf_area_shortcut_type_t
| | | | +--ro interface-count? yang:counter64
| | | | +--ro neighbor-count? yang:counter64
| | | | +--ro spf-last-execution-time? string
| | | | +--ro spf-execution-count? yang:counter64
| | | | +--ro lsa-count?      yang:counter64
| | | | +--ro lsa-checksum?    yang:phys-address
| | | +--rw interfaces
| | | | +--rw interface* [name]
| | | | | +--rw name      -> ../config/name
| | | | | +--rw config

```

---

---

```

| | | | | +--rw name?          string
| | | | | +--rw cost?          uint16
| | | | | +--rw network-type?   ipi-ospf-types:ospf_network_t
| | | | | +--rw passive?        empty
| | | | | +--rw priority?       uint8
| | | | | +--rw authentication-type? ipi-ospf-types:ospf_if_authentication_type_t
| | | | | +--rw key?            ipi-ospf-types:ospf_md5_password_t
| | | | | +--ro state
| | | | | +--ro name?          string
| | | | | +--ro cost?          uint16
| | | | | +--ro network-type?   ipi-ospf-types:ospf_network_t
| | | | | +--ro passive?        empty
| | | | | +--ro priority?       uint8
| | | | | +--ro authentication-type? ipi-ospf-types:ospf_if_authentication_type_t
| | | | | +--ro key?            ipi-ospf-types:ospf_md5_password_t
| | | | | +--rw enable-bfd {feature-list:HAVE_BFD}?
| | | | | +--rw config
| | | | | | +--rw enabled? ipi-ospf-types:ospf_bfd_state
| | | | | | +--ro state
| | | | | | +--ro enabled? ipi-ospf-types:ospf_bfd_state
| | | | | +--rw lsa-filter
| | | | | +--rw config
| | | | | | +--rw filter-out? empty
| | | | | | +--ro state
| | | | | | +--ro filter-out? empty
| | | | | +--rw mpls
| | | | | +--rw config
| | | | | +--ro state
| | | | | +--rw igp-ldp-sync
| | | | | +--rw config
| | | | | +--ro state
| | | | | +--rw timers
| | | | | +--rw config
| | | | | | +--rw dead-interval? uint16
| | | | | | +--rw hello-interval? uint16
| | | | | | +--rw retransmission-interval? uint16

```

---

```

| | | | +--ro state
| | | |   +--ro dead-interval?      uint16
| | | |   +--ro hello-interval?     uint16
| | | |   +--ro retransmission-interval? uint16
| | | +--rw stub
| | | | +--rw config
| | | | | +--rw is-stub?      empty
| | | | | +--rw no-summary?  empty
| | | | +--ro state
| | | |   +--ro is-stub?      empty
| | | |   +--ro no-summary?  empty
| | | +--rw nssas {feature-list:HAVE_NSSA}?
| | | | +--rw nssa* [nssa-enable]
| | | |   +--rw nssa-enable  -> ../config/nssa-enable
| | | |   +--rw config
| | | | | +--rw nssa-enable?      ipi-ospf-types:ospf_nssa_t
| | | | | +--rw no-summary?      empty
| | | | | +--rw stability-interval? uint32
| | | | | +--rw translator-role?  ipi-ospf-types:ospf_translator_role_t
| | | | | +--rw no-redistribution? empty
| | | | | +--rw default-information-originate? empty
| | | | | +--rw metric?          uint32
| | | | | +--rw metric-type?     ipi-ospf-types:ospf_metric_type_t
| | | | | +--rw route-map?       string
| | | | +--ro state
| | | |   +--ro nssa-enable?      ipi-ospf-types:ospf_nssa_t
| | | |   +--ro no-summary?      empty
| | | |   +--ro stability-interval? uint32
| | | |   +--ro translator-role?  ipi-ospf-types:ospf_translator_role_t
| | | |   +--ro no-redistribution? empty
| | | |   +--ro default-information-originate? empty
| | | |   +--ro metric?          uint32
| | | |   +--ro metric-type?     ipi-ospf-types:ospf_metric_type_t
| | | |   +--ro route-map?       string
| | | |   +--ro translator-count? yang:counter64
| | | |   +--ro translator-state? ipi-ospf-types:ospf_nssa_translator_state_t

```

---

```
| | | +--rw filter-list {feature-list:HAVE_ACL}?
| | | | +--rw prefix-list {feature-list:HAVE_ACL}?
| | | | | +--rw filter-in
| | | | | | +--rw config
| | | | | | | +--rw name? string
| | | | | | | +--ro state
| | | | | | | | +--ro name? string
| | | | | | | | +--rw filter-out
| | | | | | | | | +--rw config
| | | | | | | | | | +--rw name? string
| | | | | | | | | | +--ro state
| | | | | | | | | | | +--ro name? string
| | | | +--rw access-control-list {feature-list:HAVE_ACL}?
| | | | | +--rw filter-in
| | | | | | +--rw config
| | | | | | | +--rw name? string
| | | | | | | +--ro state
| | | | | | | | +--ro name? string
| | | | | | | | +--rw filter-out
| | | | | | | | | +--rw config
| | | | | | | | | | +--rw name? string
| | | | | | | | | | +--ro state
| | | | | | | | | | | +--ro name? string
| | | +--rw hosts
| | | | +--rw host* [ip-address]
| | | | | +--rw ip-address -> ../config/ip-address
| | | | | +--rw config
| | | | | | +--rw ip-address? inet:ipv4-address
| | | | | | +--rw cost? uint16
| | | | | | +--ro state
| | | | | | | +--ro ip-address? inet:ipv4-address
| | | | | | | +--ro cost? uint16
| | | +--rw networks
| | | | +--rw network* [prefix]
| | | | | +--rw prefix -> ../config/prefix
| | | | | +--rw config
```

```

| | | | +-rw prefix?      cml-data-types:cml_ipv4_prefix_t
| | | | +-rw instance-id  uint8 {feature-list:HAVE_OSPF_MULTI_INST}?
| | | | +-ro state
| | | | +-ro prefix?      cml-data-types:cml_ipv4_prefix_t
| | | | +-ro instance-id  uint8 {feature-list:HAVE_OSPF_MULTI_INST}?
| | | +-rw area-ranges
| | | | +-rw area-range* [address]
| | | | +-rw address     -> ../config/address
| | | | +-rw config
| | | | | +-rw address?    cml-data-types:cml_ipv4_prefix_t
| | | | | +-rw disable-advertise? empty
| | | | +-ro state
| | | | | +-ro address?    cml-data-types:cml_ipv4_prefix_t
| | | | | +-ro disable-advertise? empty
| | | +-rw virtual-links
| | | | +-rw virtual-link* [remote-router-id]
| | | | +-rw remote-router-id          -> ../config/remote-router-id
| | | | +-rw config
| | | | | +-rw remote-router-id? inet:ipv4-address
| | | | +-ro state
| | | | | +-ro remote-router-id?      inet:ipv4-address
| | | | | +-ro name?                  string
| | | | | +-ro interface?             string
| | | | | +-ro virtual-link-interface-state? ipi-ospf-types:ospf_vlink_interface_state_t
| | | | | +-ro link-state?             ipi-ospf-types:ospf_vlink_status_t
| | | | | +-ro adjacency-state?        ipi-ospf-types:ospf_vlink_adj_state_t
| | | | | +-ro hello-packet-due-in?    string
| | | | | +-ro local-address?          cml-data-types:cml_ipv4_prefix_t
| | | | | +-ro remote-address?         cml-data-types:cml_ipv4_prefix_t
| | | | +-rw bfd
| | | | | +-rw config
| | | | | | +-rw fall-over? empty {feature-list:HAVE_BFD}?
| | | | | | +-ro state
| | | | | | +-ro fall-over? empty {feature-list:HAVE_BFD}?
| | | | +-rw authentication
| | | | | +-rw config

```

```

| | | | | +--rw authentication-type? ipi-ospf-types:ospf_if_authentication_type_t
| | | | | +--rw key? ipi-ospf-types:ospf_md5_password_t
| | | | | +--ro state
| | | | | +--ro authentication-type? ipi-ospf-types:ospf_if_authentication_type_t
| | | | | +--ro key? ipi-ospf-types:ospf_md5_password_t
| | | | | +--rw message-digests
| | | | | +--rw message-digest* [message-digest-id]
| | | | | +--rw message-digest-id -> ../config/message-digest-id
| | | | | +--rw config
| | | | | | +--rw message-digest-id? uint8
| | | | | | +--rw message-digest-encryption-type ipi-ospf-types:ospf_cipher_type_t
| | | | | | +--rw message-digest-key ipi-ospf-types:ospf_md5_password_t
| | | | | +--ro state
| | | | | +--ro message-digest-id? uint8
| | | | | +--ro message-digest-encryption-type ipi-ospf-types:ospf_cipher_type_t
| | | | | +--ro message-digest-key ipi-ospf-types:ospf_md5_password_t
| | | +--rw timers
| | | | +--rw config
| | | | | +--rw dead-interval? uint16
| | | | | +--rw hello-interval? uint16
| | | | | +--rw transmit-delay? uint16
| | | | | +--rw retransmission-interval? uint16
| | | | | +--ro state
| | | | | +--ro dead-interval? uint16
| | | | | +--ro hello-interval? uint16
| | | | | +--ro transmit-delay? uint16
| | | | | +--ro retransmission-interval? uint16
| | | +--ro virtual-link-interface-state-change
| | | | +--ro router-id? inet:ipv4-address
| | | | +--ro interface-state? ipi-ospf-types:ospf_interface_state_t
| | | +--ro virtual-neighbor-state-change
| | | | +--ro router-id? inet:ipv4-address
| | | | +--ro neighbor-state? ipi-ospf-types:ospf_neighbor_state_change_t
| | | +--ro virtual-link-interface-rx-bad-packet
| | | | +--ro router-id? inet:ipv4-address
| | | | +--ro packet-type? ipi-ospf-types:ospf_packet_type_t

```

```
| | | +--ro virtual-link-interface-tx-retransmit
| | | | +--ro router-id?   inet:ipv4-address
| | | | +--ro packet-type? ipi-ospf-types:ospf_packet_type_t
| | | | +--ro lsdb-type?   ipi-ospf-types:ospf_lsdb_type_t
| | | | +--ro lsdb-lsid?   inet:ipv4-address
| | | | +--ro lsdb-router-id? inet:ipv4-address
| | | +--ro virtual-link-interface-config-error
| | |   +--ro router-id?   inet:ipv4-address
| | |   +--ro error-type?  ipi-ospf-types:ospf_config_error_type_t
| | |   +--ro packet-type? ipi-ospf-types:ospf_packet_type_t
| | +--rw config
| | | +--rw maximum-areas-number? uint32
| | | +--ro state
| | |   +--ro maximum-areas-number? uint32
| | +--rw lsdb
| | | +--rw overflow
| | |   +--rw normal-lsa
| | | | +--rw config!
| | | | | +--rw max-limit   uint32
| | | | | +--rw limit-type ipi-ospf-types:ospf_db_limit_type_t
| | | | | +--ro state
| | | | |   +--ro max-limit   uint32
| | | | |   +--ro limit-type ipi-ospf-types:ospf_db_limit_type_t
| | | +--rw external-lsa {feature-list:HAVE_OSPF_DB_OVERFLOW}?
| | | | +--rw config!
| | | | | +--rw max-limit   uint32
| | | | | +--rw exit-interval uint16
| | | | | +--ro state
| | | | |   +--ro max-limit   uint32
| | | | |   +--ro exit-interval uint16
| | | +--ro lsdb-overflow-external-lsa
| | |   +--ro router-id? -> /ospfv2/processes/process/state/router-id
| | |   +--ro max-limit?  uint32
| +--rw lfa {feature-list:HAVE_OSPF_LFA}?
| | +--rw fast-reroute
| |   +--rw config
```

---

```
| | | +--rw keep-all-paths? empty
| | | +--rw route-map? string
| | +--ro state
| | | +--ro keep-all-paths? empty
| | | +--ro route-map? string
| | +--rw tie-breaks
| | | +--rw tie-break* [type]
| | |   +--rw type -> ../config/type
| | |   +--rw config
| | |     | +--rw type? ipi-ospf-types:ospf_frr_tie_break_t
| | |     | +--rw idx uint8
| | |     +--ro state
| | |       +--ro type? ipi-ospf-types:ospf_frr_tie_break_t
| | |       +--ro idx uint8
| | +--rw topologies-independent-lfa
| +--rw administrative-distance
| | +--rw config
| | | +--rw default-distance? uint8
| | +--ro state
| | | +--ro default-distance? uint8
| | +--rw ospf
| | | +--rw config
| | | | +--rw intra-area-distance? uint8
| | | | +--rw inter-area-distance? uint8
| | | | +--rw external-routes-distance? uint8
| | | +--ro state
| | | | +--ro intra-area-distance? uint8
| | | | +--ro inter-area-distance? uint8
| | | | +--ro external-routes-distance? uint8
| | +--rw networks
| | | +--rw network* [prefix]
| | |   +--rw prefix -> ../config/prefix
| | |   +--rw config
| | |     | +--rw prefix? cml-data-types:cml_ipv4_addr_prefix_t
| | |     | +--rw distance? uint8
| | |     | +--rw access-control-list? string
```

```

| |   +--ro state
| |   +--ro prefix?          cml-data-types:cml_ipv4_addr_prefix_t
| |   +--ro distance?       uint8
| |   +--ro access-control-list? string
| +--rw summary-addresses
| | +--rw summary-address* [address]
| |   +--rw address -> ../config/address
| |   +--rw config
| | | +--rw address?        cml-data-types:cml_ipv4_prefix_t
| | | +--rw not-advertise?  empty
| | | +--rw tag?           uint32
| |   +--ro state
| |   +--ro address?        cml-data-types:cml_ipv4_prefix_t
| |   +--ro not-advertise?  empty
| |   +--ro tag?           uint32
| +--rw distribute-list {feature-list:HAVE_ACL}?
| | +--rw filter-in
| | | +--rw config
| | | | +--rw access-control-list? string
| | | | +--ro state
| | | | +--ro access-control-list? string
| | +--rw filter-out
| |   +--rw config
| | | +--rw access-control-list-isis?  string
| | | +--rw access-control-list-bgp?   string
| | | +--rw access-control-list-rip?   string
| | | +--rw access-control-list-static? string
| | | +--rw access-control-list-connected? string
| | | +--rw access-control-list-kernel? string
| |   +--ro state
| | | +--ro access-control-list-isis?  string
| | | +--ro access-control-list-bgp?   string
| | | +--ro access-control-list-rip?   string
| | | +--ro access-control-list-static? string
| | | +--ro access-control-list-connected? string
| | | +--ro access-control-list-kernel? string

```

```

| | +--rw ospfv2-processes
| |   +--rw ospfv2-process* [ospf-process-id]
| |     +--rw ospf-process-id  -> ../config/ospf-process-id
| |     +--rw config
| |       | +--rw ospf-process-id?          uint16
| |       | +--rw access-control-list-out-ospf? string
| |       +--ro state
| |         +--ro ospf-process-id?          uint16
| |         +--ro access-control-list-out-ospf? string
| +--rw domain-id
| | +--rw primary-domain {feature-list:HAVE_VRF_OSPF}?
| | | +--rw config
| | | | +--rw primary-domain-id-address? inet:ipv4-address
| | | | +--ro state
| | | | +--ro primary-domain-id-address? inet:ipv4-address
| | | | +--rw hexes
| | | |   +--rw hex* [primary-hex-type primary-domain-id-hex] {feature-list:HAVE_VRF_OSPF}?
| | | |     +--rw primary-hex-type      -> ../config/primary-hex-type
| | | |     +--rw primary-domain-id-hex -> ../config/primary-domain-id-hex
| | | |     +--rw config
| | | |       | +--rw primary-hex-type?    ipi-ospf-types:ospf_domain_type_t
| | | |       | +--rw primary-domain-id-hex? ipi-ospf-types:ospf_domain_id_hex_string_t
| | | |       +--ro state
| | | |         +--ro primary-hex-type?    ipi-ospf-types:ospf_domain_type_t
| | | |         +--ro primary-domain-id-hex? ipi-ospf-types:ospf_domain_id_hex_string_t
| | +--rw secondary-domain
| | | +--rw addresses
| | | | +--rw address* [secondary-domain-id-address] {feature-list:HAVE_VRF_OSPF}?
| | | |   +--rw secondary-domain-id-address -> ../config/secondary-domain-id-address
| | | |   +--rw config
| | | |     | +--rw secondary-domain-id-address? inet:ipv4-address
| | | |     +--ro state
| | | |       +--ro secondary-domain-id-address? inet:ipv4-address
| | +--rw hexes
| |   +--rw hex* [secondary-hex-type secondary-domain-id-hex] {feature-list:HAVE_VRF_OSPF}?
| |   +--rw secondary-hex-type      -> ../config/secondary-hex-type

```

```

| |     +--rw secondary-domain-id-hex  -> ../config/secondary-domain-id-hex
| |     +--rw config
| |       | +--rw secondary-hex-type?   ipi-ospf-types:ospf_domain_type_t
| |       | +--rw secondary-domain-id-hex? ipi-ospf-types:ospf_domain_id_hex_string_t
| |       +--ro state
| |         +--ro secondary-hex-type?   ipi-ospf-types:ospf_domain_type_t
| |         +--ro secondary-domain-id-hex? ipi-ospf-types:ospf_domain_id_hex_string_t
| +--rw neighbors
| | +--rw neighbor* [address]
| |   +--rw address          -> ../config/address
| |   +--rw config
| |     | +--rw address?      inet:ipv4-address
| |     | +--rw cost?        uint16
| |     | +--rw priority?    uint8
| |     | +--rw poll-interval? uint32
| |     +--ro state
| |       | +--ro address?    inet:ipv4-address
| |       | +--ro cost?      uint16
| |       | +--ro priority?  uint8
| |       | +--ro poll-interval? uint32
| |       +--ro neighbor-state-change
| |         | +--ro router-id?      inet:ipv4-address
| |         | +--ro address?        inet:ipv4-address
| |         | +--ro neighbor-address-less-index? uint32
| |         | +--ro neighbor-router-id?      inet:ipv4-address
| |         | +--ro neighbor-state?        ipi-ospf-types:ospf_neighbor_state_change_t
| |         +--ro tx-retransmit
| |           +--ro router-id?      inet:ipv4-address
| |           +--ro address?        inet:ipv4-address
| |           +--ro neighbor-address-less-index? uint32
| |           +--ro neighbor-router-id?      inet:ipv4-address
| |           +--ro packet-type?        ipi-ospf-types:ospf_packet_type_t
| |           +--ro lsdb-type?          ipi-ospf-types:ospf_lsdb_type_t
| |           +--ro lsdb-lsid?          inet:ipv4-address
| |           +--ro lsdb-router-id?     inet:ipv4-address
| +--rw timers

```

---

```
| | +--rw config
| | +--ro state
| | +--rw lfa
| | | +--rw config
| | | | +--rw termination-hold-interval? uint32 {feature-list:HAVE_OSPF_LFA}?
| | | | +--ro state
| | | | +--ro termination-hold-interval? uint32 {feature-list:HAVE_OSPF_LFA}?
| | | +--rw lsa
| | | | +--rw config
| | | | | +--rw min-arrival-interval? uint32
| | | | | +--ro state
| | | | | +--ro min-arrival-interval? uint32
| | | | +--rw delays
| | | | | +--rw delay* [start-delay min-delay max-delay]
| | | | | | +--rw start-delay -> ../config/start-delay
| | | | | | +--rw min-delay -> ../config/min-delay
| | | | | | +--rw max-delay -> ../config/max-delay
| | | | | +--rw config
| | | | | | +--rw start-delay? uint32
| | | | | | +--rw min-delay? uint32
| | | | | | +--rw max-delay? uint32
| | | | | +--ro state
| | | | | | +--ro start-delay? uint32
| | | | | | +--ro min-delay? uint32
| | | | | | +--ro max-delay? uint32
| | | +--rw spf
| | | | +--rw delay
| | | | | +--rw config!
| | | | | | +--rw min-delay uint32
| | | | | | +--rw max-delay uint32
| | | | | +--ro state
| | | | | | +--ro min-delay uint32
| | | | | | +--ro max-delay uint32
| | +--rw redistribute
| | | +--rw config
| | | | +--rw default-metric? uint32
```

```
| | +--ro state
| | | +--ro default-metric? uint32
| | +--rw routing-protocols
| | | +--rw routing-protocol* [protocol]
| | | | +--rw protocol -> ../config/protocol
| | | | +--rw config
| | | | | +--rw metric? uint32
| | | | | +--rw metric-type? ipi-ospf-types:ospf_metric_type_t
| | | | | +--rw route-map? string
| | | | | +--rw tag? uint32
| | | | | +--rw protocol? ipi-ospf-types:ospf_route_source_type_t
| | | +--ro state
| | | | +--ro metric? uint32
| | | | +--ro metric-type? ipi-ospf-types:ospf_metric_type_t
| | | | +--ro route-map? string
| | | | +--ro tag? uint32
| | | | +--ro protocol? ipi-ospf-types:ospf_route_source_type_t
| | +--rw ospf-processes
| | | +--rw ospf-process* [ospf-process-id]
| | | | +--rw ospf-process-id -> ../config/ospf-process-id
| | | | +--rw config
| | | | | +--rw metric? uint32
| | | | | +--rw metric-type? ipi-ospf-types:ospf_metric_type_t
| | | | | +--rw route-map? string
| | | | | +--rw tag? uint32
| | | | | +--rw ospf-process-id? uint16
| | | +--ro state
| | | | +--ro metric? uint32
| | | | +--ro metric-type? ipi-ospf-types:ospf_metric_type_t
| | | | +--ro route-map? string
| | | | +--ro tag? uint32
| | | | +--ro ospf-process-id? uint16
| | +--rw isis-processes
| | | +--rw isis-process* [isis-process-id]
| | | | +--rw isis-process-id -> ../config/isis-process-id
| | | | +--rw config
```

---

```
| | | +--rw metric?      uint32
| | | +--rw metric-type? ipi-ospf-types:ospf_metric_type_t
| | | +--rw route-map?   string
| | | +--rw tag?         uint32
| | | +--rw isis-process-id? string
| | +--ro state
| |   +--ro metric?      uint32
| |   +--ro metric-type? ipi-ospf-types:ospf_metric_type_t
| |   +--ro route-map?   string
| |   +--ro tag?         uint32
| |   +--ro isis-process-id? string
| +--ro originate-lsa
| | +--ro router-id?    -> /ospfv2/processes/process/state/router-id
| | +--ro lsdB-area-id? inet:ipv4-address
| | +--ro lsdB-type?    ipi-ospf-types:ospf_lsdB_type_t
| | +--ro lsdB-id?      inet:ipv4-address
| | +--ro lsdB-router-id? inet:ipv4-address
| +--rw max-metric {feature-list:HAVE_OSPF_STUB_ROUTER}?
| | +--rw config!
| | | +--rw enable-max-router-lsa  empty
| | | +--rw max-external-lsa?      uint32
| | | +--rw max-summary-lsa?      uint32
| | | +--rw include-stub?         empty
| | +--ro state
| |   +--ro enable-max-router-lsa  empty
| |   +--ro max-external-lsa?      uint32
| |   +--ro max-summary-lsa?      uint32
| |   +--ro include-stub?         empty
| +--rw max-metric-on-startup {feature-list:HAVE_OSPF_STUB_ROUTER}?
|   +--rw config!
| | +--rw max-on-startup          uint32
| | +--rw max-on-startup-external-lsa? uint32
| | +--rw max-on-startup-summary-lsa? uint32
| | +--rw on-startup-include-stub?  empty
| +--ro state
|   +--ro max-on-startup          uint32
```

---

```
|     +--ro max-on-startup-external-lsa?  uint32
|     +--ro max-on-startup-summary-lsa?  uint32
|     +--ro on-startup-include-stub?     empty
+--rw multi-area-interfaces {feature-list:HAVE_OSPF_MULTI_AREA}?
| +--rw multi-area-interface* [name]
|   +--rw name          -> ../config/name
|   +--rw config
|   | +--rw name?     -> /ipi-interface:interfaces/interface/name
|   +--ro state
|   | +--ro name?    -> /ipi-interface:interfaces/interface/name
|   +--rw ospfv2-processes
|     +--rw ospfv2-process* [ospf-process-id]
|       +--rw ospf-process-id    -> ../config/ospf-process-id
|       +--rw config
|       | +--rw ospf-process-id?  uint16
|       +--ro state
|       | +--ro ospf-process-id?  uint16
|       +--rw multi-areas
|       | +--rw multi-area* [area-id]
|       |   +--rw area-id  -> ../config/area-id
|       |   +--rw config
|       |   | +--rw area-id?  ipi-ospf-types:ospf_area_t
|       |   | +--ro state
|       |   |   +--ro area-id?  ipi-ospf-types:ospf_area_t
|       +--rw multi-areas-neighbors
|         +--rw multi-area-neighbor* [area-id]
|           +--rw area-id  -> ../config/area-id
|           +--rw config
|           | +--rw area-id?  ipi-ospf-types:ospf_area_t
|           | +--rw neighbor  inet:ipv4-address
|           +--ro state
|           | +--ro area-id?  ipi-ospf-types:ospf_area_t
|           | +--ro neighbor  inet:ipv4-address
+--rw debug
| +--rw config
| | +--rw bfd?          empty {feature-list:HAVE_BFD}?
```

---

---

```
| | +--rw rate-limit?      empty
| | +--rw route?          ipi-ospf-types:ospf_debug_route_t
| | +--rw rib?            ipi-ospf-types:ospf_debug_rib_t {feature-list:HAVE_RIBD}?
| | +--rw nsm?           ipi-ospf-types:ospf_debug_nsm_t
| | +--rw nfm?           ipi-ospf-types:ospf_debug_nfm_t
| | +--rw lsa?           ipi-ospf-types:ospf_debug_lsa_t
| | +--rw ifsm?          ipi-ospf-types:ospf_debug_ifsm_t
| | +--rw events?        ipi-ospf-types:ospf_debug_event_t
| | +--rw retransmission? empty
| | +--rw lfa?           empty {feature-list:HAVE OSPF_LFA}?
| | +--rw policy?        empty
| | +--rw redistribute?   ipi-ospf-types:ospf_debug_redist_t
| | +--rw graceful-restart? ipi-ospf-types:ospf_debug_graceful_t
| | +--rw packet-hello?   ipi-ospf-types:ospf_debug_packet_options_t
| | +--rw packet-dd?     ipi-ospf-types:ospf_debug_packet_options_t
| | +--rw packet-ls-request? ipi-ospf-types:ospf_debug_packet_options_t
| | +--rw packet-ls-update? ipi-ospf-types:ospf_debug_packet_options_t
| | +--rw packet-ls-ack?  ipi-ospf-types:ospf_debug_packet_options_t
| +--ro state
|   +--ro bfd?           empty {feature-list:HAVE_BFD}?
|   +--ro rate-limit?    empty
|   +--ro route?         ipi-ospf-types:ospf_debug_route_t
|   +--ro rib?           ipi-ospf-types:ospf_debug_rib_t {feature-list:HAVE_RIBD}?
|   +--ro nsm?           ipi-ospf-types:ospf_debug_nsm_t
|   +--ro nfm?           ipi-ospf-types:ospf_debug_nfm_t
|   +--ro lsa?           ipi-ospf-types:ospf_debug_lsa_t
|   +--ro ifsm?          ipi-ospf-types:ospf_debug_ifsm_t
|   +--ro events?        ipi-ospf-types:ospf_debug_event_t
|   +--ro retransmission? empty
|   +--ro lfa?           empty {feature-list:HAVE OSPF_LFA}?
|   +--ro policy?        empty
|   +--ro redistribute?   ipi-ospf-types:ospf_debug_redist_t
|   +--ro graceful-restart? ipi-ospf-types:ospf_debug_graceful_t
|   +--ro packet-hello?   ipi-ospf-types:ospf_debug_packet_options_t
|   +--ro packet-dd?     ipi-ospf-types:ospf_debug_packet_options_t
|   +--ro packet-ls-request? ipi-ospf-types:ospf_debug_packet_options_t
```

---

```

| +--ro packet-ls-update?      ipi-ospf-types:ospf_debug_packet_options_t
| +--ro packet-ls-ack?        ipi-ospf-types:ospf_debug_packet_options_t
| +--ro terminal-debug-status
|   +--ro bfd?                cml-data-types:cml_on_off_t {feature-list:HAVE_BFD}?
|   +--ro rate-limit?         cml-data-types:cml_on_off_t
|   +--ro route?              ipi-ospf-types:ospf_debug_route_t
|   +--ro rib?                ipi-ospf-types:ospf_debug_rib_t {feature-list:HAVE_RIBD}?
|   +--ro nsm?                ipi-ospf-types:ospf_debug_nsm_t
|   +--ro nfsm?               ipi-ospf-types:ospf_debug_nfsm_t
|   +--ro lsa?                ipi-ospf-types:ospf_debug_lsa_t
|   +--ro ifsm?               ipi-ospf-types:ospf_debug_ifsm_t
|   +--ro events?             ipi-ospf-types:ospf_debug_event_t
|   +--ro retransmission?     cml-data-types:cml_on_off_t
|   +--ro lfa?                cml-data-types:cml_on_off_t {feature-list:HAVE OSPF_LFA}?
|   +--ro policy?             cml-data-types:cml_on_off_t
|   +--ro redistribute?       ipi-ospf-types:ospf_debug_redist_t
|   +--ro graceful-restart?   ipi-ospf-types:ospf_debug_graceful_t
|   +--ro packet-hello?       ipi-ospf-types:ospf_debug_packet_options_t
|   +--ro packet-dd?          ipi-ospf-types:ospf_debug_packet_options_t
|   +--ro packet-ls-request?   ipi-ospf-types:ospf_debug_packet_options_t
|   +--ro packet-ls-update?   ipi-ospf-types:ospf_debug_packet_options_t
|   +--ro packet-ls-ack?      ipi-ospf-types:ospf_debug_packet_options_t
+--rw interfaces
  +--rw interface* [name]
    +--rw name                -> ../config/name
    +--rw config
      | +--rw cost?            uint16
      | +--rw priority?       uint8
      | +--rw mtu-ignore?     empty
      | +--rw name?           -> /ipi-interface:interfaces/interface/name
      | +--rw network-type?   ipi-ospf-types:ospf_network_t
      | +--rw disable-all-ospf? empty
      | +--rw mtu?            uint16
      | +--rw enable-flood-reduction? empty
      | +--rw enable-demand-circuit? empty {feature-list:HAVE OSPF_OD,feature-list:HAVE OSPF_MULTI_INST}?
      | +--rw enable-bfd?     ipi-ospf-types:ospf_bfd_state {feature-list:HAVE_BFD}?

```

---

---

```
| +--rw disable-fast-reroute?  empty {feature-list:HAVE_OSPF_LFA}?
+--ro state
| +--ro cost?                  uint16
| +--ro priority?             uint8
| +--ro mtu-ignore?           empty
| +--ro name?                 -> /ipi-interface:interfaces/interface/name
| +--ro network-type?         ipi-ospf-types:ospf_network_t
| +--ro disable-all-ospf?     empty
| +--ro mtu?                  uint16
| +--ro enable-flood-reduction? empty
| +--ro enable-demand-circuit? empty {feature-list:HAVE_OSPF_OD,feature-list:HAVE_OSPF_MULTI_INST}?
| +--ro enable-bfd?           ipi-ospf-types:ospf_bfd_state {feature-list:HAVE_BFD}?
| +--ro disable-fast-reroute?  empty {feature-list:HAVE_OSPF_LFA}?
| +--ro link-state-change
| | +--ro router-id?          inet:ipv4-address
| | +--ro name?              string
| | +--ro interface-address?  inet:ipv4-address
| | +--ro address-less-interface? uint32
| | +--ro interface-state?    ipi-ospf-types:ospf_interface_state_t
| +--ro rx-bad-packet
| | +--ro router-id?          inet:ipv4-address
| | +--ro name?              string
| | +--ro interface-address?  inet:ipv4-address
| | +--ro address-less-interface? uint32
| | +--ro packet-src?         inet:ipv4-address
| | +--ro packet-type?        ipi-ospf-types:ospf_packet_type_t
| +--ro interface-config-error
|   +--ro router-id?          inet:ipv4-address
|   +--ro name?              string
|   +--ro interface-address?  inet:ipv4-address
|   +--ro address-less-interface? uint32
|   +--ro error-type?         ipi-ospf-types:ospf_config_error_type_t
|   +--ro packet-type?        ipi-ospf-types:ospf_packet_type_t
+--ro interface-states
| +--ro state
| | +--ro interface-state?    int32
```

---

```
| | +--ro lsa-count?          int32
| | +--ro lsa-checksum?      int32
| | +--ro interface-events?  int32
| | +--ro addressless-interface? int32
| +--ro statistics
| | +--ro errors
| | | +--ro discarded-in?      yang:counter64
| | | +--ro discarded-out?    yang:counter64
| | | +--ro hello-in?        yang:counter64
| | | +--ro database-descriptor-in? yang:counter64
| | | +--ro ls-request-in?    yang:counter64
| | | +--ro ls-update-in?    yang:counter64
| | | +--ro ls-acknowledge-in? yang:counter64
| | | +--ro unknown-in?      yang:counter64
| | | +--ro unknown-out?     yang:counter64
| | | +--ro bad-version?     yang:counter64
| | | +--ro bad-crc?         yang:counter64
| | | +--ro invalid-source?   yang:counter64
| | | +--ro invalid-destination? yang:counter64
| | | +--ro no-neighbor?     yang:counter64
| | | +--ro passive?         yang:counter64
| | | +--ro wrong-area?      yang:counter64
| | | +--ro packet-length?    yang:counter64
| | | +--ro authentication?   yang:counter64
| | +--ro traffic
| | | +--ro total-packets-in?   yang:counter64
| | | +--ro total-packets-out?  yang:counter64
| | | +--ro hello-packets-in?  yang:counter64
| | | +--ro hello-packets-out? yang:counter64
| | | +--ro database-descriptor-packets-in? yang:counter64
| | | +--ro database-descriptor-packets-out? yang:counter64
| | | +--ro ls-request-packets-in? yang:counter64
| | | +--ro ls-request-packets-out? yang:counter64
| | | +--ro ls-update-packets-in? yang:counter64
| | | +--ro ls-update-packets-out? yang:counter64
| | | +--ro ls-acknowledge-packets-in? yang:counter64
```

```
| | +--ro ls-acknowledge-packets-out?   yang:counter64
| +--ro designated-router
| | +--ro state
| | +--ro router-id?   inet:ipv4-address
| | +--ro address?   inet:ipv4-address
| +--ro backup-designated-router
| | +--ro state
| | +--ro router-id?   inet:ipv4-address
| | +--ro address?   inet:ipv4-address
| +--ro timers
|   +--ro state
|     +--ro runtime-dead-interval?   uint32
+--rw authentication
| +--rw config
| | +--rw authentication-type?   ipi-ospf-types:ospf_if_authentication_type_t
| | +--rw key?                   ipi-ospf-types:ospf_md5_password_t
| +--ro state
| | +--ro authentication-type?   ipi-ospf-types:ospf_if_authentication_type_t
| | +--ro key?                   ipi-ospf-types:ospf_md5_password_t
| +--rw message-digests
|   +--rw message-digest* [message-digest-id]
|     +--rw message-digest-id   -> ../config/message-digest-id
|     +--rw config
|       | +--rw message-digest-id?       uint8
|       | +--rw message-digest-encryption-type   ipi-ospf-types:ospf_cipher_type_t
|       | +--rw message-digest-key         ipi-ospf-types:ospf_md5_password_t
|       +--ro state
|         +--ro message-digest-id?       uint8
|         +--ro message-digest-encryption-type   ipi-ospf-types:ospf_cipher_type_t
|         +--ro message-digest-key         ipi-ospf-types:ospf_md5_password_t
+--rw database-filter
| +--rw lsa
|   +--rw config
|     | +--rw filter-out?   empty
|     +--ro state
|       +--ro filter-out?   empty
```

---

```
+--rw timers
| +--rw config
| | +--rw dead-interval?      uint16
| | +--rw hello-interval?    uint16
| | +--rw retransmission-interval?  uint16
| | +--rw transmit-delay?    uint16
| | +--rw resync-timeout?    uint16
| +--ro state
|   +--ro dead-interval?      uint16
|   +--ro hello-interval?    uint16
|   +--ro retransmission-interval?  uint16
|   +--ro transmit-delay?    uint16
|   +--ro resync-timeout?    uint16
+--rw addresses
  +--rw address* [interface-address]
    +--rw interface-address  -> ../config/interface-address
    +--rw config
    | +--rw interface-address?  inet:ipv4-address
    | +--rw cost?              uint16
    | +--rw priority?          uint8
    | +--rw mtu-ignore?        empty
    +--ro state
    | +--ro interface-address?  inet:ipv4-address
    | +--ro cost?              uint16
    | +--ro priority?          uint8
    | +--ro mtu-ignore?        empty
    | +--ro designated-router
    | | +--ro state
    | |   +--ro router-id?     inet:ipv4-address
    | |   +--ro address?      inet:ipv4-address
    | +--ro backup-designated-router
    | | +--ro state
    | |   +--ro router-id?     inet:ipv4-address
    | |   +--ro address?      inet:ipv4-address
    | +--ro timers
    |   +--ro state
```

---

```
|   +--ro runtime-dead-interval?  uint32
+--rw authentication
| +--rw config
| | +--rw authentication-type?  ipi-ospf-types:ospf_if_authentication_type_t
| | +--rw key?                  ipi-ospf-types:ospf_md5_password_t
| +--ro state
| | +--ro authentication-type?  ipi-ospf-types:ospf_if_authentication_type_t
| | +--ro key?                  ipi-ospf-types:ospf_md5_password_t
| +--rw message-digests
|   +--rw message-digest* [message-digest-id]
|     +--rw message-digest-id  -> ../config/message-digest-id
|     +--rw config
|       | +--rw message-digest-id?      uint8
|       | +--rw message-digest-encryption-type  ipi-ospf-types:ospf_cipher_type_t
|       | +--rw message-digest-key        ipi-ospf-types:ospf_md5_password_t
|       +--ro state
|         +--ro message-digest-id?      uint8
|         +--ro message-digest-encryption-type  ipi-ospf-types:ospf_cipher_type_t
|         +--ro message-digest-key        ipi-ospf-types:ospf_md5_password_t
+--rw timers
| +--rw config
| | +--rw dead-interval?      uint16
| | +--rw hello-interval?    uint16
| | +--rw retransmission-interval?  uint16
| | +--rw transmit-delay?     uint16
| | +--rw resync-timeout?     uint16
| +--ro state
|   +--ro dead-interval?      uint16
|   +--ro hello-interval?    uint16
|   +--ro retransmission-interval?  uint16
|   +--ro transmit-delay?     uint16
|   +--ro resync-timeout?     uint16
+--rw database-filter
  +--rw lsa
    +--rw config
      | +--rw filter-out?  empty
```

```

+--ro state
  +--ro filter-out?  empty

```

rpcs:

```

+---x ospfv2-terminal-debug-ospf-all-on {feature-list:HAVE_OSPFD}?
+---x ospfv2-terminal-debug-ospf-all-off {feature-list:HAVE_OSPFD}?
+---x ospfv2-terminal-debug-bfd-on {feature-list:HAVE_BFD}?
+---x ospfv2-terminal-debug-bfd-off {feature-list:HAVE_BFD}?
+---x ospfv2-terminal-debug-rate-limit-on {feature-list:HAVE_OSPFD}?
+---x ospfv2-terminal-debug-rate-limit-off {feature-list:HAVE_OSPFD}?
+---x ospfv2-terminal-debug-route-on {feature-list:HAVE_OSPFD}?
| +---w input
|   +---w route  ipi-ospf-types:ospf_debug_route_t
+---x ospfv2-terminal-debug-route-off {feature-list:HAVE_OSPFD}?
| +---w input
|   +---w route  ipi-ospf-types:ospf_debug_route_t
+---x ospfv2-terminal-debug-rib-on {feature-list:HAVE_RIBD}?
| +---w input
|   +---w rib    ipi-ospf-types:ospf_debug_rib_t
+---x ospfv2-terminal-debug-rib-off {feature-list:HAVE_RIBD}?
| +---w input
|   +---w rib    ipi-ospf-types:ospf_debug_rib_t
+---x ospfv2-terminal-debug-packet-all-on {feature-list:HAVE_OSPFD}?
| +---w input
|   +---w all    ipi-ospf-types:ospf_debug_packet_options_t
+---x ospfv2-terminal-debug-packet-all-off {feature-list:HAVE_OSPFD}?
| +---w input
|   +---w all    ipi-ospf-types:ospf_debug_packet_options_t
+---x ospfv2-terminal-debug-packet-hello-on {feature-list:HAVE_OSPFD}?
| +---w input
|   +---w hello  ipi-ospf-types:ospf_debug_packet_options_t
+---x ospfv2-terminal-debug-packet-hello-off {feature-list:HAVE_OSPFD}?
| +---w input
|   +---w hello  ipi-ospf-types:ospf_debug_packet_options_t
+---x ospfv2-terminal-debug-packet-dd-on {feature-list:HAVE_OSPFD}?
| +---w input

```

---

```
| +---w dd ipi-ospf-types:ospf_debug_packet_options_t
+---x ospfv2-terminal-debug-packet-dd-off {feature-list:HAVE OSPFD}?
| +---w input
| +---w dd ipi-ospf-types:ospf_debug_packet_options_t
+---x ospfv2-terminal-debug-packet-ls-request-on {feature-list:HAVE OSPFD}?
| +---w input
| +---w ls-request ipi-ospf-types:ospf_debug_packet_options_t
+---x ospfv2-terminal-debug-packet-ls-request-off {feature-list:HAVE OSPFD}?
| +---w input
| +---w ls-request ipi-ospf-types:ospf_debug_packet_options_t
+---x ospfv2-terminal-debug-packet-ls-update-on {feature-list:HAVE OSPFD}?
| +---w input
| +---w ls-update ipi-ospf-types:ospf_debug_packet_options_t
+---x ospfv2-terminal-debug-packet-ls-update-off {feature-list:HAVE OSPFD}?
| +---w input
| +---w ls-update ipi-ospf-types:ospf_debug_packet_options_t
+---x ospfv2-terminal-debug-packet-ls-ack-on {feature-list:HAVE OSPFD}?
| +---w input
| +---w ls-ack ipi-ospf-types:ospf_debug_packet_options_t
+---x ospfv2-terminal-debug-packet-ls-ack-off {feature-list:HAVE OSPFD}?
| +---w input
| +---w ls-ack ipi-ospf-types:ospf_debug_packet_options_t
+---x ospfv2-terminal-debug-nsm-on {feature-list:HAVE OSPFD}?
| +---w input
| +---w nsm ipi-ospf-types:ospf_debug_nsm_t
+---x ospfv2-terminal-debug-nsm-off {feature-list:HAVE OSPFD}?
| +---w input
| +---w nsm ipi-ospf-types:ospf_debug_nsm_t
+---x ospfv2-terminal-debug-nfsm-on {feature-list:HAVE OSPFD}?
| +---w input
| +---w nfsm ipi-ospf-types:ospf_debug_nfsm_t
+---x ospfv2-terminal-debug-nfsm-off {feature-list:HAVE OSPFD}?
| +---w input
| +---w nfsm ipi-ospf-types:ospf_debug_nfsm_t
+---x ospfv2-terminal-debug-lsa-on {feature-list:HAVE OSPFD}?
| +---w input
```

---

---

```
| +---w lsa ipi-ospf-types:ospf_debug_lsa_t
+---x ospfv2-terminal-debug-lsa-off {feature-list:HAVE_OSPFD}?
| +---w input
| +---w lsa ipi-ospf-types:ospf_debug_lsa_t
+---x ospfv2-terminal-debug-ifsm-on {feature-list:HAVE_OSPFD}?
| +---w input
| +---w ifsm ipi-ospf-types:ospf_debug_ifsm_t
+---x ospfv2-terminal-debug-ifsm-off {feature-list:HAVE_OSPFD}?
| +---w input
| +---w ifsm ipi-ospf-types:ospf_debug_ifsm_t
+---x ospfv2-terminal-debug-events-on {feature-list:HAVE_OSPFD}?
| +---w input
| +---w events ipi-ospf-types:ospf_debug_event_t
+---x ospfv2-terminal-debug-events-off {feature-list:HAVE_OSPFD}?
| +---w input
| +---w events ipi-ospf-types:ospf_debug_event_t
+---x ospfv2-terminal-debug-all-on {feature-list:HAVE_OSPFD}?
+---x ospfv2-terminal-debug-all-off {feature-list:HAVE_OSPFD}?
+---x ospfv2-terminal-debug-retransmission-on {feature-list:HAVE_OSPFD}?
+---x ospfv2-terminal-debug-retransmission-off {feature-list:HAVE_OSPFD}?
+---x ospfv2-terminal-debug-lfa-on {feature-list:HAVE_OSPF_LFA}?
+---x ospfv2-terminal-debug-lfa-off {feature-list:HAVE_OSPF_LFA}?
+---x ospfv2-terminal-debug-policy-on {feature-list:HAVE_OSPFD}?
+---x ospfv2-terminal-debug-policy-off {feature-list:HAVE_OSPFD}?
+---x ospfv2-terminal-debug-redistribute-on {feature-list:HAVE_OSPFD}?
| +---w input
| +---w redistribute ipi-ospf-types:ospf_debug_redist_t
+---x ospfv2-terminal-debug-redistribute-off {feature-list:HAVE_OSPFD}?
| +---w input
| +---w redistribute ipi-ospf-types:ospf_debug_redist_t
+---x ospfv2-terminal-debug-graceful-restart-on {feature-list:HAVE_OSPFD}?
| +---w input
| +---w graceful-restart ipi-ospf-types:ospf_debug_graceful_t
+---x ospfv2-terminal-debug-graceful-restart-off {feature-list:HAVE_OSPFD}?
| +---w input
| +---w graceful-restart ipi-ospf-types:ospf_debug_graceful_t
```

```

+---x ospfv2-clear-process {feature-list:HAVE_OSPFD}?
| +---w input
|   +---w process-id  uint16
+---x ospfv2-clear-process-all {feature-list:HAVE_OSPFD}?
+---x ospfv2-restart-graceful {feature-list:HAVE_RESTART}?
| +---w input
|   +---w grace-period  uint16
+---x ospfv2-snmp-restart {feature-list:HAVE_SNMP}?

```

notifications:

```

+---n ospfv2-neighbor-state-change
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro address?          inet:ipv4-address
| +--ro ospf-id?          uint16
| +--ro router-id?        inet:ipv4-address
| +--ro neighbor-address-less-index?  uint32
| +--ro neighbor-router-id?  inet:ipv4-address
| +--ro neighbor-state?    ipi-ospf-types:ospf_neighbor_state_change_t
+---n ospfv2-tx-retransmit
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro address?          inet:ipv4-address
| +--ro ospf-id?          uint16
| +--ro router-id?        inet:ipv4-address
| +--ro neighbor-address-less-index?  uint32
| +--ro neighbor-router-id?  inet:ipv4-address
| +--ro packet-type?       ipi-ospf-types:ospf_packet_type_t
| +--ro lsdb-type?         ipi-ospf-types:ospf_lsdb_type_t
| +--ro lsdb-lsid?         inet:ipv4-address
| +--ro lsdb-router-id?    inet:ipv4-address
+---n ospfv2-originate-lsa
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro ospf-id?          uint16
| +--ro router-id?        inet:ipv4-address

```

---

```
| +--ro lsdB-area-id?   inet:ipv4-address
| +--ro lsdB-type?     ipi-ospf-types:ospf_lsdB_type_t
| +--ro lsdB-id?       inet:ipv4-address
| +--ro lsdB-router-id? inet:ipv4-address
+---n ospfv2-lsdB-overflow-external-lsa
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro ospf-id?      uint16
| +--ro router-id?    inet:ipv4-address
| +--ro max-limit?    uint32
+---n ospfv2-virtual-link-interface-config-error
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro remote-router-id? inet:ipv4-address
| +--ro area-id?      ipi-ospf-types:ospf_area_t
| +--ro ospf-id?      uint16
| +--ro router-id?    inet:ipv4-address
| +--ro error-type?   ipi-ospf-types:ospf_config_error_type_t
| +--ro packet-type?  ipi-ospf-types:ospf_packet_type_t
+---n ospfv2-virtual-link-interface-state-change
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro remote-router-id? inet:ipv4-address
| +--ro area-id?      ipi-ospf-types:ospf_area_t
| +--ro ospf-id?      uint16
| +--ro router-id?    inet:ipv4-address
| +--ro interface-state? ipi-ospf-types:ospf_interface_state_t
+---n ospfv2-virtual-neighbor-state-change
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro remote-router-id? inet:ipv4-address
| +--ro area-id?      ipi-ospf-types:ospf_area_t
| +--ro ospf-id?      uint16
| +--ro router-id?    inet:ipv4-address
| +--ro neighbor-state? ipi-ospf-types:ospf_neighbor_state_change_t
+---n ospfv2-virtual-link-interface-rx-bad-packet
```

---

```
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro remote-router-id?  inet:ipv4-address
| +--ro area-id?      ipi-ospf-types:ospf_area_t
| +--ro ospf-id?      uint16
| +--ro router-id?    inet:ipv4-address
| +--ro packet-type?   ipi-ospf-types:ospf_packet_type_t
+---n ospfv2-virtual-link-interface-tx-retransmit
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro remote-router-id?  inet:ipv4-address
| +--ro area-id?      ipi-ospf-types:ospf_area_t
| +--ro ospf-id?      uint16
| +--ro router-id?    inet:ipv4-address
| +--ro packet-type?   ipi-ospf-types:ospf_packet_type_t
| +--ro lsdb-type?     ipi-ospf-types:ospf_lsdb_type_t
| +--ro lsdb-ls-id?    inet:ipv4-address
| +--ro lsdb-router-id?  inet:ipv4-address
+---n ospfv2-interface-link-state-change
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro name?         string
| +--ro router-id?    inet:ipv4-address
| +--ro interface-address?  inet:ipv4-address
| +--ro address-less-interface? uint32
| +--ro interface-state?  ipi-ospf-types:ospf_interface_state_t
+---n ospfv2-interface-rx-bad-packet
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro name?         string
| +--ro router-id?    inet:ipv4-address
| +--ro interface-address?  inet:ipv4-address
| +--ro address-less-interface? uint32
| +--ro packet-src?    inet:ipv4-address
| +--ro packet-type?   ipi-ospf-types:ospf_packet_type_t
+---n ospfv2-interface-config-error
```

---

+--ro severity?	cml-data-types:cml_notif_severity_t
+--ro eventClass?	cml-data-types:cml_notif_class_t
+--ro name?	string
+--ro router-id?	inet:ipv4-address
+--ro interface-address?	inet:ipv4-address
+--ro address-less-interface?	uint32
+--ro error-type?	ipi-ospf-types:ospf_config_error_type_t
+--ro packet-type?	ipi-ospf-types:ospf_packet_type_t

---

## module: ipi-ospfv3

```
+--rw ospfv3
  +--rw global
    | +--rw config
    | | +--rw display-route-on-single-line? empty
    | +--ro state
    | | +--ro display-route-on-single-line? empty
    | +--rw graceful-restart {feature-list:HAVE_RESTART}?
    |   +--rw config
    |   | +--rw grace-period?          uint16
    |   | +--rw controlled-restarts-only? empty
    |   +--ro state
    |   | +--ro grace-period?          uint16
    |   | +--ro controlled-restarts-only? empty
    |   +--rw helper
```

```

|   +--rw config
|   |   +--rw max-grace-period?   uint16
|   |   +--rw disable-all-neighbors?  empty
|   |   +--rw disable-neighbor*    inet:ipv4-address
|   +--ro state
|   |   +--ro max-grace-period?   uint16
|   |   +--ro disable-all-neighbors?  empty
|   |   +--ro disable-neighbor*    inet:ipv4-address
+--rw processes
| +--rw process* [ospfv3-id]
| | +--rw ospfv3-id          -> ../config/ospfv3-id
| | +--rw config
| | | +--rw ospfv3-id?      ipi-ospfv3-types:ospfv3_string_t
| | | +--rw vrf-name       -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
| | | +--rw router-id?     inet:ipv4-address
| | | +--rw bfd-enable-all-interfaces?  empty {feature-list:HAVE_BFD}?
| | | +--rw database-summary?      empty
| | | +--rw area-border-type?      ipi-ospfv3-types:ospfv3_abr_type_t
| | | +--rw default-metric?       uint32
| | | +--rw shutdown?            empty
| | | +--rw log-adjacency-changes? ipi-ospfv3-types:ospfv3_log_adj_opt_t
| | | +--rw reference-bandwidth?   uint32
| | | +--rw max-database-descriptors? uint16
| | +--ro state
| | | +--ro statistics
| | | | +--ro up-time?          string
| | | | +--ro database-description-in?  yang:counter64
| | | | +--ro database-description-out? yang:counter64
| | | | +--ro external-lsa-count?     yang:counter64
| | | | +--ro external-lsa-checksum?  string
| | | | +--ro unknown-lsa-count?     yang:counter64
| | | | +--ro lsa-out?              yang:counter64
| | | | +--ro lsa-in?              yang:counter64
| | | | +--ro area-count?          yang:counter64
| | +--ro ospfv3-id?            ipi-ospfv3-types:ospfv3_string_t

```

---

```

| | +--ro vrf-name          -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
| | +--ro router-id?       inet:ipv4-address
| | +--ro bfd-enable-all-interfaces?  empty {feature-list:HAVE_BFD}?
| | +--ro database-summary?    empty
| | +--ro area-border-type?    ipi-ospfv3-types:ospfv3_abr_type_t
| | +--ro default-metric?     uint32
| | +--ro shutdown?          empty
| | +--ro log-adjacency-changes?  ipi-ospfv3-types:ospfv3_log_adj_opt_t
| | +--ro reference-bandwidth?  uint32
| | +--ro max-database-descriptors? uint16
| +--ro link-state-database
| | +--ro link* [link-index]
| | | +--ro link-index  -> ../state/link-index
| | | +--ro lsa-prefix* [prefix]
| | | | +--ro prefix  -> ../state/prefix
| | | | +--ro state
| | | | +--ro prefix?    cml-data-types:cml_ipv6_prefix_t
| | | | +--ro no-unicast-bit?  empty
| | | | +--ro prefix-options? ipi-ospfv3-types:ospfv3_prefix_options_t
| | | +--ro state
| | | +--ro link-index?    uint32
| | | +--ro link-local-address?  inet:ipv6-address
| | | +--ro priority?      uint8
| | | +--ro interface-name?  string
| | | +--ro prefix-count?   uint32
| | | +--ro advertising-router? inet:ipv4-address
| | | +--ro ls-age?        uint16
| | | +--ro ls-type?       ipi-ospfv3-types:ospfv3_ls_type_t
| | | +--ro ls-id?        string
| | | +--ro ls-sequence-number? string
| | | +--ro ls-checksum?   string
| | | +--ro ls-length?    uint16
| | | +--ro ls-options?    ipi-ospfv3-types:ospfv3_ls_options_t
| | +--ro router* [router-index]
| | | +--ro router-index  -> ../state/router-index
| | | +--ro link* [link-index]

```

---

```
| | | +--ro link-index -> ../state/link-index
| | | +--ro state
| | |   +--ro link-index?      uint32
| | |   +--ro neighbor-router-id?  inet:ipv4-address
| | |   +--ro neighbor-interface-id? uint32
| | |   +--ro interface-id?      uint32
| | |   +--ro metric?           uint16
| | |   +--ro metric-type?      ipi-ospfv3-types:ospfv3_link_metric_type_t
| | | +--ro state
| | |   +--ro router-index?      uint32
| | |   +--ro area-id?          inet:ipv4-address
| | |   +--ro ls-router-properties? ipi-ospfv3-types:ospfv3_router_properties_t
| | |   +--ro advertising-router?  inet:ipv4-address
| | |   +--ro ls-age?           uint16
| | |   +--ro ls-type?         ipi-ospfv3-types:ospfv3_ls_type_t
| | |   +--ro ls-id?           string
| | |   +--ro ls-sequence-number? string
| | |   +--ro ls-checksum?      string
| | |   +--ro ls-length?       uint16
| | |   +--ro ls-options?      ipi-ospfv3-types:ospfv3_ls_options_t
| | +--ro network* [advertising-router]
| | | +--ro advertising-router -> ../state/advertising-router
| | | +--ro state
| | |   +--ro advertising-router?  inet:ipv4-address
| | |   +--ro ls-age?             uint16
| | |   +--ro ls-type?           ipi-ospfv3-types:ospfv3_ls_type_t
| | |   +--ro ls-id?            string
| | |   +--ro ls-sequence-number? string
| | |   +--ro ls-checksum?       string
| | |   +--ro ls-length?        uint16
| | |   +--ro ls-options?       ipi-ospfv3-types:ospfv3_ls_options_t
| | |   +--ro attached-router*    inet:ipv4-address
| | +--ro intra-prefix* [intra-prefix-index]
| | | +--ro intra-prefix-index -> ../state/intra-prefix-index
| | | +--ro lsa-prefix* [prefix]
| | | +--ro prefix -> ../state/prefix
```

```
| | | +--ro state
| | |   +--ro prefix?      cml-data-types:cml_ipv6_prefix_t
| | |   +--ro no-unicast-bit? empty
| | |   +--ro prefix-options? ipi-ospfv3-types:ospfv3_prefix_options_t
| | |   +--ro metric?      uint16
| | +--ro state
| | |   +--ro intra-prefix-index?      uint32
| | |   +--ro area-id?                  inet:ipv4-address
| | |   +--ro referenced-ls-advertising-router? inet:ipv4-address
| | |   +--ro referenced-ls-id?         string
| | |   +--ro referenced-ls-type?       string
| | |   +--ro prefix-count?            uint32
| | |   +--ro advertising-router?      inet:ipv4-address
| | |   +--ro ls-age?                   uint16
| | |   +--ro ls-type?                   ipi-ospfv3-types:ospfv3_ls_type_t
| | |   +--ro ls-id?                     string
| | |   +--ro ls-sequence-number?       string
| | |   +--ro ls-checksum?              string
| | |   +--ro ls-length?                uint16
| | +--ro inter-prefix* [inter-prefix-index]
| | | +--ro inter-prefix-index -> ../state/inter-prefix-index
| | | +--ro lsa-prefix* [prefix]
| | | | +--ro prefix -> ../state/prefix
| | | | +--ro state
| | | | | +--ro prefix?      cml-data-types:cml_ipv6_prefix_t
| | | | | +--ro no-unicast-bit? empty
| | | | | +--ro prefix-options? ipi-ospfv3-types:ospfv3_prefix_options_t
| | | | | +--ro metric?      uint16
| | | | +--ro state
| | | | | +--ro inter-prefix-index? uint32
| | | | | +--ro area-id?            inet:ipv4-address
| | | | | +--ro advertising-router? inet:ipv4-address
| | | | | +--ro ls-age?             uint16
| | | | | +--ro ls-type?           ipi-ospfv3-types:ospfv3_ls_type_t
| | | | | +--ro ls-id?             string
| | | | | +--ro ls-sequence-number? string
```

---

```
| | | +--ro ls-checksum?      string
| | | +--ro ls-length?       uint16
| | +--ro inter-router* [inter-router-index]
| | | +--ro inter-router-index -> ../state/inter-router-index
| | | +--ro state
| | |   +--ro inter-router-index? uint32
| | |   +--ro area-id?          inet:ipv4-address
| | |   +--ro router-id?       inet:ipv4-address
| | |   +--ro advertising-router? inet:ipv4-address
| | |   +--ro ls-age?          uint16
| | |   +--ro ls-type?         ipi-ospfv3-types:ospfv3_ls_type_t
| | |   +--ro ls-id?          string
| | |   +--ro ls-sequence-number? string
| | |   +--ro ls-checksum?     string
| | |   +--ro ls-length?      uint16
| | |   +--ro metric?         uint16
| | |   +--ro ls-options?     ipi-ospfv3-types:ospfv3_ls_options_t
| | +--ro external* [external-index]
| | | +--ro external-index -> ../state/external-index
| | | +--ro lsa-prefix* [prefix]
| | | | +--ro prefix -> ../state/prefix
| | | | +--ro state
| | | |   +--ro prefix?        cml-data-types:cml_ipv6_prefix_t
| | | |   +--ro no-unicast-bit? empty
| | | |   +--ro prefix-options? ipi-ospfv3-types:ospfv3_prefix_options_t
| | | +--ro state
| | |   +--ro external-index?  uint32
| | |   +--ro referenced-ls-id? string
| | |   +--ro referenced-ls-type? uint32
| | |   +--ro route-tag?      uint32
| | |   +--ro forwarding-address? inet:ip-address
| | |   +--ro metric?         uint16
| | |   +--ro metric-type?    ipi-ospfv3-types:ospfv3_ls_metric_type_t
| | |   +--ro advertising-router? inet:ipv4-address
| | |   +--ro ls-age?         uint16
| | |   +--ro ls-type?        ipi-ospfv3-types:ospfv3_ls_type_t
```

---

```
| | | +--ro ls-id?          string
| | | +--ro ls-sequence-number? string
| | | +--ro ls-checksum?    string
| | | +--ro ls-length?      uint16
| | +--ro not-so-stubby-area* [nssa-index]
| |   +--ro nssa-index -> ../state/nssa-index
| |   +--ro lsa-prefix* [prefix]
| |     | +--ro prefix -> ../state/prefix
| |     | +--ro state
| |     |   +--ro prefix?      cml-data-types:cml_ipv6_prefix_t
| |     |   +--ro no-unicast-bit? empty
| |     |   +--ro prefix-options? ipi-ospfv3-types:ospfv3_prefix_options_t
| |     +--ro state
| |       +--ro nssa-index?      uint32
| |       +--ro referenced-ls-id? string
| |       +--ro referenced-ls-type? uint32
| |       +--ro route-tag?      uint32
| |       +--ro forwarding-address? inet:ip-address
| |       +--ro metric?         uint16
| |       +--ro metric-type?     ipi-ospfv3-types:ospfv3_ls_metric_type_t
| |       +--ro advertising-router? inet:ipv4-address
| |       +--ro ls-age?         uint16
| |       +--ro ls-type?        ipi-ospfv3-types:ospfv3_ls_type_t
| |       +--ro ls-id?         string
| |       +--ro ls-sequence-number? string
| |       +--ro ls-checksum?    string
| |       +--ro ls-length?      uint16
| +--ro route* [prefix]
| | +--ro prefix -> ../state/prefix
| | +--ro next-hop* [address]
| | | +--ro address -> ../state/address
| | | +--ro state
| | | | +--ro address?      inet:ip-address
| | | | +--ro interface-name? string
| | | | +--ro transit-area? empty
| | | | +--ro area-id?     inet:ipv4-address
```

---

```
| | | +--ro connected?    empty
| | | +--ro invalid?     empty
| | | +--ro code?        string
| | +--ro state
| | | +--ro prefix?     cml-data-types:cml_ip_prefix_t
| | | +--ro distance?  uint8
| | +--ro route-path
| |   +--ro state
| |     +--ro type?      ipi-ospfv3-types:ospfv3_path_type_t
| |     +--ro code?      string
| |     +--ro discard-connection? empty
| |     +--ro cost?      uint32
| |     +--ro type-2-cost?  uint32
| |     +--ro path-flags?  ipi-ospfv3-types:ospfv3_path_flags_t
| +--rw administrative-distance
| | +--rw config
| | | +--rw default-distance?  uint8
| | | +--ro state
| | | +--ro default-distance?  uint8
| | +--rw ospf
| | | +--rw config
| | | | +--rw intra-area-distance?  uint8
| | | | +--rw inter-area-distance?  uint8
| | | | +--rw external-routes-distance?  uint8
| | | +--ro state
| | |   +--ro intra-area-distance?  uint8
| | |   +--ro inter-area-distance?  uint8
| | |   +--ro external-routes-distance?  uint8
| +--rw capability
| | +--rw config
| | | +--rw disable-graceful-restart?  empty {feature-list:HAVE_RESTART}?
| | | +--ro state
| | |   +--ro disable-graceful-restart?  empty {feature-list:HAVE_RESTART}?
| +--rw timers
| | +--rw spf
| | | +--rw config!
```

---

```
| | | +--rw exponential-min-delay uint32
| | | +--rw exponential-max-delay uint32
| | +--ro state
| |   +--ro exponential-min-delay uint32
| |   +--ro exponential-max-delay uint32
| +--rw passive-interfaces
| | +--rw config
| | | +--rw all-interfaces? empty
| | +--ro state
| | | +--ro all-interfaces? empty
| | +--rw passive-interface* [name]
| |   +--rw name -> ../config/name
| |   +--rw config
| | | +--rw name? string
| | | +--rw passive-mode ipi-ospfv3-types:ospfv3_passive_mode_t
| | +--ro state
| |   +--ro name? string
| |   +--ro passive-mode ipi-ospfv3-types:ospfv3_passive_mode_t
| +--rw summary-addresses
| | +--rw summary-address* [address]
| |   +--rw address -> ../config/address
| |   +--rw config
| | | +--rw address? cml-data-types:cml_ipv6_prefix_t
| | | +--rw not-advertise? empty
| | | +--rw translate-tag? uint32
| | | +--rw all-tag? uint32
| | +--ro state
| |   +--ro address? cml-data-types:cml_ipv6_prefix_t
| |   +--ro not-advertise? empty
| |   +--ro translate-tag? uint32
| |   +--ro all-tag? uint32
| +--rw default-information
| | +--rw config
| | | +--rw originate? empty
| | | +--rw always-advertise-default-route? empty
| | | +--rw metric? uint32
```

```

| | | +--rw metric-type?          ipi-ospfv3-types:ospfv3_metric_type_t
| | | +--rw route-map?           string
| | +--ro state
| |   +--ro originate?          empty
| |   +--ro always-advertise-default-route? empty
| |   +--ro metric?             uint32
| |   +--ro metric-type?       ipi-ospfv3-types:ospfv3_metric_type_t
| |   +--ro route-map?         string
| +--rw distribute-list {feature-list:HAVE_ACL}?
| | +--rw filter-in
| | | +--rw config
| | | | +--rw access-control-list? string
| | | | +--ro state
| | | |   +--ro access-control-list? string
| | | +--rw filter-out
| | |   +--rw routing-protocols
| | | | +--rw routing-protocol* [protocol]
| | | |   +--rw protocol -> ../config/protocol
| | | |   +--rw config
| | | | | +--rw protocol?        ipi-ospfv3-types:ospfv3_route_source_type_t
| | | | | +--rw access-control-list string
| | | | | +--ro state
| | | | |   +--ro protocol?      ipi-ospfv3-types:ospfv3_route_source_type_t
| | | | |   +--ro access-control-list string
| | | +--rw ospf-processes
| | |   +--rw ospf-process* [ospf-process-id]
| | |   +--rw ospf-process-id -> ../config/ospf-process-id
| | |   +--rw config
| | | | +--rw ospf-process-id?   ipi-ospfv3-types:ospfv3_string_t
| | | | +--rw access-control-list string
| | | | +--ro state
| | | |   +--ro ospf-process-id? ipi-ospfv3-types:ospfv3_string_t
| | | |   +--ro access-control-list string
| +--rw redistribute
| | +--rw routing-protocols
| | | +--rw routing-protocol* [protocol]

```

```
| | | +--rw protocol -> ../config/protocol
| | | +--rw config
| | | | +--rw metric? uint32
| | | | +--rw metric-type? ipi-ospfv3-types:ospfv3_metric_type_t
| | | | +--rw route-map? string
| | | | +--rw route-tag? uint32
| | | | +--rw protocol? ipi-ospfv3-types:ospfv3_route_source_type_t
| | | +--ro state
| | |   +--ro metric? uint32
| | |   +--ro metric-type? ipi-ospfv3-types:ospfv3_metric_type_t
| | |   +--ro route-map? string
| | |   +--ro route-tag? uint32
| | |   +--ro protocol? ipi-ospfv3-types:ospfv3_route_source_type_t
| | +--rw ospf-processes
| |   +--rw ospf-process* [ospf-process-id]
| |     +--rw ospf-process-id -> ../config/ospf-process-id
| |     +--rw config
| |       | +--rw metric? uint32
| |       | +--rw metric-type? ipi-ospfv3-types:ospfv3_metric_type_t
| |       | +--rw route-map? string
| |       | +--rw route-tag? uint32
| |       | +--rw ospf-process-id? ipi-ospfv3-types:ospfv3_string_t
| |       +--ro state
| |         +--ro metric? uint32
| |         +--ro metric-type? ipi-ospfv3-types:ospfv3_metric_type_t
| |         +--ro route-map? string
| |         +--ro route-tag? uint32
| |         +--ro ospf-process-id? ipi-ospfv3-types:ospfv3_string_t
| +--rw areas
| | +--rw area* [area-id]
| |   +--rw area-id -> ../config/area-id
| |   +--rw config
| |     | +--rw area-id? ipi-ospfv3-types:ospfv3_area_t
| |     | +--rw default-cost? uint32
| |     +--ro state
| |     | +--ro area-id? ipi-ospfv3-types:ospfv3_area_t
```

```

| | | +--ro default-cost? uint32
| | +--rw stub
| | | +--rw config!
| | | | +--rw enable      empty
| | | | +--rw no-summary? empty
| | | +--ro state
| | |   +--ro enable      empty
| | |   +--ro no-summary? empty
| | +--rw nssa {feature-list:HAVE_NSSA}?
| | | +--rw config!
| | | | +--rw enable          empty
| | | | +--rw no-summary?    empty
| | | | +--rw stability-interval? uint32
| | | | +--rw translator-role? ipi-ospfv3-types:ospfv3_translator_role_t
| | | | +--rw no-redistribution? empty
| | | | +--rw default-information-originate? empty
| | | | +--rw metric?        uint32
| | | | +--rw metric-type?   ipi-ospfv3-types:ospfv3_metric_type_t
| | | | +--rw route-map?    string
| | | +--ro state
| | |   +--ro enable          empty
| | |   +--ro no-summary?    empty
| | |   +--ro stability-interval? uint32
| | |   +--ro translator-role? ipi-ospfv3-types:ospfv3_translator_role_t
| | |   +--ro no-redistribution? empty
| | |   +--ro default-information-originate? empty
| | |   +--ro metric?        uint32
| | |   +--ro metric-type?   ipi-ospfv3-types:ospfv3_metric_type_t
| | |   +--ro route-map?    string
| | +--rw virtual-links
| | | +--rw virtual-link* [remote-router-id]
| | |   +--rw remote-router-id -> ../config/remote-router-id
| | |   +--rw config
| | |     | +--rw remote-router-id?    inet:ipv4-address
| | |     | +--rw bfd-fall-over?      empty {feature-list:HAVE_BFD}?
| | |     | +--rw instance-id?       uint8

```

```

| | | | +-rw authentication-cryptomap? -> /ipi-ipsec:ipsec/crypto-maps/crypto-map/config/name {feature-
list:HAVE_IPSEC,feature-list:HAVE_TUNNEL}?
| | | | +-ro state
| | | | +-ro remote-router-id?          inet:ipv4-address
| | | | +-ro bfd-fall-over?             empty {feature-list:HAVE_BFD}?
| | | | +-ro instance-id?              uint8
| | | | +-ro authentication-cryptomap? -> /ipi-ipsec:ipsec/crypto-maps/crypto-map/config/name
{feature-list:HAVE_IPSEC,feature-list:HAVE_TUNNEL}?
| | | | +-ro name?                     string
| | | | +-ro status?                   ipi-ospfv3-types:ospfv3_link_status_t
| | | | +-ro interface-name?           string
| | | | +-ro virtual-link-interface-state? string
| | | | +-ro local-address?            inet:ipv4-address
| | | | +-ro remote-address?           inet:ipv4-address
| | | | +-ro virtual-link-instance-id? uint32
| | | | +-ro hello-suppression-enable? empty
| | | | +-ro do-not-age-lsa-enable?     empty
| | | | +-ro hello-due-in?             yang:date-and-time
| | | | +-ro adjacency-state?          string
| | | | +-ro virtual-link-config-error
| | | | | +-ro router-id?              inet:ipv4-address
| | | | | +-ro instance-id?           uint8
| | | | | +-ro error-type?            ipi-ospfv3-types:ospfv3_config_error_type_t
| | | | | +-ro packet-type?          ipi-ospfv3-types:ospfv3_packet_type_t
| | | | | +-ro virtual-link-state-change
| | | | | +-ro router-id?             inet:ipv4-address
| | | | | +-ro instance-id?          uint8
| | | | | +-ro virtual-link-state?    ipi-ospfv3-types:ospfv3_interface_state_t
| | | | | +-ro virtual-link-neighbor-state-change
| | | | | +-ro router-id?            inet:ipv4-address
| | | | | +-ro instance-id?          uint8
| | | | | +-ro neighbor-state?       ipi-ospfv3-types:ospfv3_interface_state_t
| | | | | +-ro virtual-link-tx-retransmit
| | | | | +-ro router-id?            inet:ipv4-address
| | | | | +-ro instance-id?          uint8
| | | | | +-ro packet-type?          ipi-ospfv3-types:ospfv3_packet_type_t
| | | | | +-ro lsdb-type?            uint32

```

---

```
| | | | +--ro lsdB-lsid?      uint32
| | | | +--ro lsdB-router-id? inet:ipv4-address
| | | | +--ro virtual-link-rx-bad-packet
| | | | +--ro router-id?     inet:ipv4-address
| | | | +--ro instance-id?   uint8
| | | | +--ro packet-type?   ipi-ospfv3-types:ospfv3_packet_type_t
| | | +--rw timers
| | |   +--rw config
| | |     | +--rw dead-interval?      uint16
| | |     | +--rw hello-interval?    uint16
| | |     | +--rw transmission-delay? uint16
| | |     | +--rw retransmission-interval? uint16
| | |     +--ro state
| | |       +--ro dead-interval?      uint16
| | |       +--ro hello-interval?    uint16
| | |       +--ro transmission-delay? uint16
| | |       +--ro retransmission-interval? uint16
| | +--rw address-ranges
| |   +--rw address-range* [address]
| |     +--rw address  -> ../config/address
| |     +--rw config
| |       | +--rw address?      cml-data-types:cml_ipv6_prefix_t
| |       | +--rw not-advertise? empty
| |       +--ro state
| |         +--ro address?      cml-data-types:cml_ipv6_prefix_t
| |         +--ro not-advertise? empty
| +--ro area-info* [area-id]
| | +--ro area-id  -> ../state/area-id
| | +--ro state
| | | +--ro statistics
| | | | +--ro active-interface-count? yang:counter64
| | | | +--ro interface-count?       yang:counter64
| | | | +--ro spf-algorithm-executed-count? yang:counter64
| | | | +--ro lsa-count?              yang:counter64
| | | | +--ro lsa-checksum?           string
| | | | +--ro unknown-lsa-count?     yang:counter64
```

---

```
| | | +--ro area-id?      inet:ipv4-address
| | | +--ro interface-name* string
| | | +--ro backbone?    empty
| | | +--ro active?      empty
| | | +--ro asbr?        empty
| | +--ro vertex* [router-id]
| |   +--ro router-id  -> ../state/router-id
| |   +--ro next-hop* [address]
| |     +--ro address  -> ../state/address
| |     +--ro state
| |       +--ro address?    inet:ip-address
| |       +--ro interface-name? string
| |       +--ro transit-area? empty
| |       +--ro area-id?    inet:ipv4-address
| |       +--ro connected?  empty
| |       +--ro invalid?    empty
| |       +--ro code?       string
| |     +--ro state
| |       +--ro router-id?  inet:ipv4-address
| |       +--ro distance?  uint8
| +--rw address-family
| | +--rw ipv4
| |   +--rw config
| |     +--rw enable-af?  empty
| |     +--ro state
| |       +--ro enable-af? empty
| |     +--rw areas
| |       +--rw area* [area-id]
| |         +--rw area-id  -> ../config/area-id
| |         +--rw config
| |           | +--rw area-id? ipi-ospfv3-types:ospfv3_area_t
| |           | +--ro state
| |           | +--ro area-id? ipi-ospfv3-types:ospfv3_area_t
| |           +--rw address-ranges
| |             +--rw address-range* [address]
| |             +--rw address  -> ../config/address
```

```

| | |   +--rw config
| | |   | +--rw address?    cml-data-types:cml_ipv4_addr_prefix_t
| | |   | +--rw not-advertise? empty
| | |   +--ro state
| | |     +--ro address?    cml-data-types:cml_ipv4_addr_prefix_t
| | |     +--ro not-advertise? empty
| | +--rw summary-addresses
| | | +--rw summary-address* [address]
| | |   +--rw address  -> ../config/address
| | |   +--rw config
| | |     | +--rw address?    cml-data-types:cml_ipv4_prefix_t
| | |     | +--rw not-advertise? empty
| | |     | +--rw tag?       uint32
| | |     +--ro state
| | |       +--ro address?    cml-data-types:cml_ipv4_prefix_t
| | |       +--ro not-advertise? empty
| | |       +--ro tag?       uint32
| | +--rw default-information
| | | +--rw config
| | | | +--rw originate?      empty
| | | | +--rw always-advertise-default-route? empty
| | | | +--rw metric?        uint32
| | | | +--rw metric-type?   ipi-ospfv3-types:ospfv3_metric_type_t
| | | | +--rw route-map?    string
| | | +--ro state
| | |   +--ro originate?      empty
| | |   +--ro always-advertise-default-route? empty
| | |   +--ro metric?        uint32
| | |   +--ro metric-type?   ipi-ospfv3-types:ospfv3_metric_type_t
| | |   +--ro route-map?    string
| | +--rw redistribute
| |   +--rw routing-protocols
| |     | +--rw routing-protocol* [protocol-af]
| |     |   +--rw protocol-af  -> ../config/protocol-af
| |     |   +--rw config
| |     | | +--rw protocol-af? ipi-ospfv3-types:ospfv3_af_route_source_type_t

```

```

| | | | +--rw metric?      uint32
| | | | +--rw metric-type? ipi-ospfv3-types:ospfv3_metric_type_t
| | | | +--rw route-map?   string
| | | | +--rw route-tag?   uint32
| | | | +--ro state
| | | |   +--ro protocol-af? ipi-ospfv3-types:ospfv3_af_route_source_type_t
| | | |   +--ro metric?     uint32
| | | |   +--ro metric-type? ipi-ospfv3-types:ospfv3_metric_type_t
| | | |   +--ro route-map?  string
| | | |   +--ro route-tag?  uint32
| | +--rw ospf-processes
| |   +--rw ospf-process* [ospfv2-process-id]
| |     +--rw ospfv2-process-id -> ../config/ospfv2-process-id
| |     +--rw config
| |       | +--rw ospfv2-process-id? uint16
| |       | +--rw metric?           uint32
| |       | +--rw metric-type?     ipi-ospfv3-types:ospfv3_metric_type_t
| |       | +--rw route-map?       string
| |       | +--rw route-tag?       uint32
| |       +--ro state
| |         +--ro ospfv2-process-id? uint16
| |         +--ro metric?           uint32
| |         +--ro metric-type?     ipi-ospfv3-types:ospfv3_metric_type_t
| |         +--ro route-map?       string
| |         +--ro route-tag?       uint32
| +--ro originate-lsa
| | +--ro router-id?    -> /ospfv3/processes/process/state/router-id
| | +--ro lsdB-area-id? inet:ipv4-address
| | +--ro lsdB-type?    uint32
| | +--ro lsdB-id?     uint32
| | +--ro lsdB-router-id? inet:ipv4-address
| +--ro tx-retransmit
| | +--ro router-id?    inet:ipv4-address
| | +--ro if-index?     int32
| | +--ro instance-id? uint8
| | +--ro neighbor-router-id? inet:ipv4-address

```

---

```
| | +--ro packet-type?      ipi-ospfv3-types:ospfv3_packet_type_t
| | +--ro lsdb-type?       uint32
| | +--ro lsdb-lsid?       uint32
| | +--ro lsdb-router-id?  inet:ipv4-address
| +--ro neighbor-state-change
|   +--ro router-id?       inet:ipv4-address
|   +--ro if-index?        int32
|   +--ro instance-id?     uint8
|   +--ro neighbor-router-id? inet:ipv4-address
|   +--ro neighbor-state?  ipi-ospfv3-types:ospfv3_neighbor_state_change_t
+--rw debug
| +--rw config
| | +--rw bfd?              empty {feature-list:HAVE_BFD}?
| | +--rw retransmission?  empty
| | +--rw events?          ipi-ospfv3-types:ospfv3_debug_event_t
| | +--rw ifsm?            ipi-ospfv3-types:ospfv3_debug_ifsm_t
| | +--rw lsa?             ipi-ospfv3-types:ospfv3_debug_lsa_t
| | +--rw n fsm?           ipi-ospfv3-types:ospfv3_debug_n fsm_t
| | +--rw nsm?             ipi-ospfv3-types:ospfv3_debug_nsm_t
| | +--rw rib?             ipi-ospfv3-types:ospfv3_debug_rib_t {feature-list:HAVE_RIBD}?
| | +--rw route?          ipi-ospfv3-types:ospfv3_debug_route_t
| | +--rw packet-hello?    ipi-ospfv3-types:ospfv3_debug_packet_options_t
| | +--rw packet-dd?       ipi-ospfv3-types:ospfv3_debug_packet_options_t
| | +--rw packet-ls-request? ipi-ospfv3-types:ospfv3_debug_packet_options_t
| | +--rw packet-ls-update? ipi-ospfv3-types:ospfv3_debug_packet_options_t
| | +--rw packet-ls-ack?    ipi-ospfv3-types:ospfv3_debug_packet_options_t
| +--ro state
|   +--ro bfd?              empty {feature-list:HAVE_BFD}?
|   +--ro retransmission?  empty
|   +--ro events?          ipi-ospfv3-types:ospfv3_debug_event_t
|   +--ro ifsm?            ipi-ospfv3-types:ospfv3_debug_ifsm_t
|   +--ro lsa?             ipi-ospfv3-types:ospfv3_debug_lsa_t
|   +--ro n fsm?           ipi-ospfv3-types:ospfv3_debug_n fsm_t
|   +--ro nsm?             ipi-ospfv3-types:ospfv3_debug_nsm_t
|   +--ro rib?             ipi-ospfv3-types:ospfv3_debug_rib_t {feature-list:HAVE_RIBD}?
|   +--ro route?          ipi-ospfv3-types:ospfv3_debug_route_t
```

---

---

```

| +--ro packet-hello?      ipi-ospfv3-types:ospfv3_debug_packet_options_t
| +--ro packet-dd?        ipi-ospfv3-types:ospfv3_debug_packet_options_t
| +--ro packet-ls-request? ipi-ospfv3-types:ospfv3_debug_packet_options_t
| +--ro packet-ls-update? ipi-ospfv3-types:ospfv3_debug_packet_options_t
| +--ro packet-ls-ack?    ipi-ospfv3-types:ospfv3_debug_packet_options_t
| +--ro terminal-debug-status
|   +--ro bfd?            cml-data-types:cml_on_off_t {feature-list:HAVE_BFD}?
|   +--ro retransmission? cml-data-types:cml_on_off_t
|   +--ro events?        ipi-ospfv3-types:ospfv3_debug_event_t
|   +--ro ifsm?          ipi-ospfv3-types:ospfv3_debug_ifsm_t
|   +--ro lsa?           ipi-ospfv3-types:ospfv3_debug_lsa_t
|   +--ro nfsm?          ipi-ospfv3-types:ospfv3_debug_nfsm_t
|   +--ro nsm?           ipi-ospfv3-types:ospfv3_debug_nsm_t
|   +--ro rib?           ipi-ospfv3-types:ospfv3_debug_rib_t {feature-list:HAVE_RIBD}?
|   +--ro route?         ipi-ospfv3-types:ospfv3_debug_route_t
|   +--ro packet-hello?  ipi-ospfv3-types:ospfv3_debug_packet_options_t
|   +--ro packet-dd?     ipi-ospfv3-types:ospfv3_debug_packet_options_t
|   +--ro packet-ls-request? ipi-ospfv3-types:ospfv3_debug_packet_options_t
|   +--ro packet-ls-update? ipi-ospfv3-types:ospfv3_debug_packet_options_t
|   +--ro packet-ls-ack?  ipi-ospfv3-types:ospfv3_debug_packet_options_t
+--rw interfaces
  +--rw interface* [interface-name]
    +--rw interface-name -> ../config/interface-name
    +--rw config
      | +--rw interface-name? -> /ipi-interface:interfaces/interface/name
      | +--rw shutdown?      empty
      +--ro state
        | +--ro interface-name? -> /ipi-interface:interfaces/interface/name
        | +--ro shutdown?      empty
        | +--ro interface-config-error
        | | +--ro router-id?      inet:ipv4-address
        | | +--ro interface-index? uint32
        | | +--ro interface-instance-id? uint8
        | | +--ro error-type?     ipi-ospfv3-types:ospfv3_config_error_type_t
        | | +--ro packet-type?    ipi-ospfv3-types:ospfv3_packet_type_t
        | +--ro interface-state-change

```

---

```

| | +--ro router-id?          inet:ipv4-address
| | +--ro interface-index?    uint32
| | +--ro interface-instance-id? uint8
| | +--ro interface-state?    ipi-ospfv3-types:ospfv3_interface_state_t
| +--ro interface-rx-bad-packet
|   +--ro router-id?          inet:ipv4-address
|   +--ro interface-index?    uint32
|   +--ro interface-instance-id? uint8
|   +--ro packet-src?         inet:ipv6-address
|   +--ro packet-type?       ipi-ospfv3-types:ospfv3_packet_type_t
+--rw instances
  +--rw instance* [instance-id]
    +--rw instance-id          -> ../config/instance-id
    +--rw config
      +--rw instance-id?      uint8
      +--rw network-type?    ipi-ospfv3-types:ospfv3_network_type_t
      +--rw cost?            uint16
      +--rw priority?        uint8
      +--rw mtu?             uint16
      +--rw mtu-ignore?      empty
      +--rw enable-link-lsa-suppression? empty
      +--rw enable-bfd?      boolean {feature-list:HAVE_BFD}?
      +--rw authentication-cryptomap? -> /ipi-ipsec:ipsec/crypto-maps/crypto-map/config/name {feature-
list:HAVE_IPSEC,feature-list:HAVE_TUNNEL}?
    +--ro state
      +--ro statistics
        +--ro neighbor-count?    uint32
        +--ro adjacent-neighbor-count? uint32
        +--ro hello-due-in?      string
        +--ro hello-in?          yang:counter64
        +--ro hello-out?         yang:counter64
        +--ro database-description-in? yang:counter64
        +--ro database-description-out? yang:counter64
        +--ro ls-request-in?      yang:counter64
        +--ro ls-request-out?     yang:counter64
        +--ro ls-update-in?      yang:counter64
        +--ro ls-update-out?     yang:counter64

```

---

```

| | +--ro ls-ack-in?          yang:counter64
| | +--ro ls-ack-out?        yang:counter64
| | +--ro ls-ack-discarded?  yang:counter64
| +--ro instance-id?         uint8
| +--ro network-type?        ipi-ospfv3-types:ospfv3_network_type_t
| +--ro cost?                 uint16
| +--ro priority?            uint8
| +--ro mtu?                  uint16
| +--ro mtu-ignore?          empty
| +--ro enable-link-lsa-suppression? empty
| +--ro enable-bfd?          boolean {feature-list:HAVE_BFD}?
| +--ro authentication-cryptomap? -> /ipi-ipsec:ipsec/crypto-maps/crypto-map/config/name {feature-
list:HAVE_IPSEC,feature-list:HAVE_TUNNEL}?
| +--ro administrative-state? ipi-ospfv3-types:ospfv3_interface_admin_state_t
| +--ro interface-index?     uint32
| +--ro interface-state?     ipi-ospfv3-types:ospfv3_interface_state_t
| +--ro address?              inet:ipv6-address
| +--ro link-local-address?   inet:ipv6-address
| +--ro router-id?           inet:ipv4-address
+--rw routers
| +--rw router* [ospfv3-id area-id]
|   +--rw ospfv3-id -> ../config/ospfv3-id
|   +--rw area-id   -> ../config/area-id
|   +--rw config
|     | +--rw ospfv3-id? ipi-ospfv3-types:ospfv3_string_t
|     | +--rw area-id?  ipi-ospfv3-types:ospfv3_area_t
|     +--ro state
|       +--ro ospfv3-id? ipi-ospfv3-types:ospfv3_string_t
|       +--ro area-id?  ipi-ospfv3-types:ospfv3_area_t
+--rw timers
| +--rw config
| | +--rw dead-interval?    uint16
| | +--rw hello-interval?  uint16
| | +--rw transmission-delay? uint16
| | +--rw retransmission-interval? uint16
| +--ro state
|   +--ro dead-interval?    uint16

```

---

---

```
| +--ro hello-interval?      uint16
| +--ro transmission-delay?  uint16
| +--ro retransmission-interval? uint16
+--rw neighbors-static
| +--rw neighbor-static* [address]
|   +--rw address  -> ../config/address
|   +--rw config
|     | +--rw address?      inet:ipv6-address
|     | +--rw cost?        uint16
|     | +--rw priority?    uint8
|     | +--rw poll-interval? uint32
|     +--ro state
|       +--ro address?      inet:ipv6-address
|       +--ro cost?        uint16
|       +--ro priority?    uint8
|       +--ro poll-interval? uint32
|       +--ro interface-state? string
+--ro designated-router
| +--ro state
|   +--ro router-id?  inet:ipv4-address
|   +--ro address?    inet:ipv6-address
+--ro backup-designated-router
| +--ro state
|   +--ro router-id?  inet:ipv4-address
|   +--ro address?    inet:ipv6-address
+--ro neighbor* [router-id]
  +--ro router-id  -> ../state/router-id
  +--ro state
  | +--ro statistics
  | | +--ro dead-timer-due-in?  string
  | | +--ro timer-dump?        string
  | | +--ro state-changes?     yang:counter64
  | | +--ro database-summary-count? yang:counter64
  | | +--ro ls-request-count?   yang:counter64
  | | +--ro ls-retransmission-count? yang:counter64
  | +--ro router-id?          inet:ipv4-address
```

---

```

| +--ro address?          inet:ipv6-address
| +--ro area-id?         inet:ipv4-address
| +--ro state?           string
| +--ro state-message?   string
| +--ro bfd-enable?      empty {feature-list:HAVE_BFD}?
| +--ro priority?        uint8
| +--ro neighbor-options? ipi-ospfv3-types:ospfv3_ls_options_t
| +--ro designated-router-router-id? inet:ipv4-address
| +--ro backup-designated-router-router-id? inet:ipv4-address
+--ro route* [prefix]
  +--ro prefix    -> ../state/prefix
  +--ro next-hop* [address]
    | +--ro address  -> ../state/address
    | +--ro state
    |   +--ro address?    inet:ip-address
    |   +--ro interface-name? string
    |   +--ro transit-area? empty
    |   +--ro area-id?    inet:ipv4-address
    |   +--ro connected?  empty
    |   +--ro invalid?    empty
    |   +--ro code?       string
    +--ro state
      | +--ro prefix?    cml-data-types:cml_ip_prefix_t
      | +--ro distance?  uint8
      +--ro route-path
        +--ro state
          +--ro type?          ipi-ospfv3-types:ospfv3_path_type_t
          +--ro code?          string
          +--ro discard-connection? empty
          +--ro cost?          uint32
          +--ro type-2-cost?    uint32
          +--ro path-flags?    ipi-ospfv3-types:ospfv3_path_flags_t

```

rpcs:

```

+---x ospfv3-terminal-debug-ospf-all-on {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
+---x ospfv3-terminal-debug-ospf-all-off {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?

```

---

```
+---x ospfv3-terminal-debug-bfd-on {feature-list:HAVE_BFD}?
+---x ospfv3-terminal-debug-bfd-off {feature-list:HAVE_BFD}?
+---x ospfv3-terminal-debug-retransmission-on {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
+---x ospfv3-terminal-debug-retransmission-off {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
+---x ospfv3-terminal-debug-events-on {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
|   +---w events   ipi-ospfv3-types:ospfv3_debug_event_t
+---x ospfv3-terminal-debug-events-off {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
|   +---w events   ipi-ospfv3-types:ospfv3_debug_event_t
+---x ospfv3-terminal-debug-ifsm-on {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
|   +---w ifsm     ipi-ospfv3-types:ospfv3_debug_ifsm_t
+---x ospfv3-terminal-debug-ifsm-off {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
|   +---w ifsm     ipi-ospfv3-types:ospfv3_debug_ifsm_t
+---x ospfv3-terminal-debug-lsa-on {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
|   +---w lsa      ipi-ospfv3-types:ospfv3_debug_lsa_t
+---x ospfv3-terminal-debug-lsa-off {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
|   +---w lsa      ipi-ospfv3-types:ospfv3_debug_lsa_t
+---x ospfv3-terminal-debug-nfsm-on {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
|   +---w nfsm     ipi-ospfv3-types:ospfv3_debug_nfsm_t
+---x ospfv3-terminal-debug-nfsm-off {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
|   +---w nfsm     ipi-ospfv3-types:ospfv3_debug_nfsm_t
+---x ospfv3-terminal-debug-nsm-on {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
|   +---w nsm      ipi-ospfv3-types:ospfv3_debug_nsm_t
+---x ospfv3-terminal-debug-nsm-off {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
|   +---w nsm      ipi-ospfv3-types:ospfv3_debug_nsm_t
+---x ospfv3-terminal-debug-packet-all-on {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
```

---

```
| +---w all ipi-ospfv3-types:ospfv3_debug_packet_options_t
+---x ospfv3-terminal-debug-packet-all-off {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w all ipi-ospfv3-types:ospfv3_debug_packet_options_t
+---x ospfv3-terminal-debug-packet-hello-on {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w hello ipi-ospfv3-types:ospfv3_debug_packet_options_t
+---x ospfv3-terminal-debug-packet-hello-off {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w hello ipi-ospfv3-types:ospfv3_debug_packet_options_t
+---x ospfv3-terminal-debug-packet-dd-on {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w dd ipi-ospfv3-types:ospfv3_debug_packet_options_t
+---x ospfv3-terminal-debug-packet-dd-off {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w dd ipi-ospfv3-types:ospfv3_debug_packet_options_t
+---x ospfv3-terminal-debug-packet-ls-request-on {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w ls-request ipi-ospfv3-types:ospfv3_debug_packet_options_t
+---x ospfv3-terminal-debug-packet-ls-request-off {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w ls-request ipi-ospfv3-types:ospfv3_debug_packet_options_t
+---x ospfv3-terminal-debug-packet-ls-update-on {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w ls-update ipi-ospfv3-types:ospfv3_debug_packet_options_t
+---x ospfv3-terminal-debug-packet-ls-update-off {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w ls-update ipi-ospfv3-types:ospfv3_debug_packet_options_t
+---x ospfv3-terminal-debug-packet-ls-ack-on {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w ls-ack ipi-ospfv3-types:ospfv3_debug_packet_options_t
+---x ospfv3-terminal-debug-packet-ls-ack-off {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w ls-ack ipi-ospfv3-types:ospfv3_debug_packet_options_t
+---x ospfv3-terminal-debug-rib-on {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
```

```

| +---w rib ipi-ospfv3-types:ospfv3_debug_rib_t
+---x ospfv3-terminal-debug-rib-off {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w rib ipi-ospfv3-types:ospfv3_debug_rib_t
+---x ospfv3-terminal-debug-route-on {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w route ipi-ospfv3-types:ospfv3_debug_route_t
+---x ospfv3-terminal-debug-route-off {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w route ipi-ospfv3-types:ospfv3_debug_route_t
+---x ospfv3-clear-process {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w process-id string
+---x ospfv3-clear-process-all {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
+---x ospfv3-graceful-restart {feature-list:HAVE_OSPF6D,feature-list:HAVE_IPV6}?
| +---w input
| +---w grace-period uint16
+---x ospfv3-snmp-restart {feature-list:HAVE_SNMP}?

```

notifications:

```

+---n ospfv3-originate-lsa
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro ospfv3-id? ipi-ospfv3-types:ospfv3_string_t
| +--ro router-id? inet:ipv4-address
| +--ro lsdB-area-id? inet:ipv4-address
| +--ro lsdB-type? uint32
| +--ro lsdB-id? uint32
| +--ro lsdB-router-id? inet:ipv4-address
+---n ospfv3-tx-retransmit
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro ospfv3-id? ipi-ospfv3-types:ospfv3_string_t
| +--ro router-id? inet:ipv4-address
| +--ro if-index? int32
| +--ro instance-id? uint8

```

---

```
| +--ro neighbor-router-id?  inet:ipv4-address
| +--ro packet-type?        ipi-ospfv3-types:ospfv3_packet_type_t
| +--ro lsdb-type?          uint32
| +--ro lsdb-lsid?          uint32
| +--ro lsdb-router-id?     inet:ipv4-address
+---n ospfv3-neighbor-state-change
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?        cml-data-types:cml_notif_class_t
| +--ro ospfv3-id?         ipi-ospfv3-types:ospfv3_string_t
| +--ro router-id?         inet:ipv4-address
| +--ro if-index?          int32
| +--ro instance-id?       uint8
| +--ro neighbor-router-id? inet:ipv4-address
| +--ro neighbor-state?    ipi-ospfv3-types:ospfv3_neighbor_state_change_t
+---n ospfv3-virtual-link-config-error
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?        cml-data-types:cml_notif_class_t
| +--ro remote-router-id?  inet:ipv4-address
| +--ro area-id?           ipi-ospfv3-types:ospfv3_area_t
| +--ro ospfv3-id?         ipi-ospfv3-types:ospfv3_string_t
| +--ro router-id?         inet:ipv4-address
| +--ro instance-id?       uint8
| +--ro error-type?        ipi-ospfv3-types:ospfv3_config_error_type_t
| +--ro packet-type?       ipi-ospfv3-types:ospfv3_packet_type_t
+---n ospfv3-virtual-link-state-change
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?        cml-data-types:cml_notif_class_t
| +--ro remote-router-id?  inet:ipv4-address
| +--ro area-id?           ipi-ospfv3-types:ospfv3_area_t
| +--ro ospfv3-id?         ipi-ospfv3-types:ospfv3_string_t
| +--ro router-id?         inet:ipv4-address
| +--ro instance-id?       uint8
| +--ro virtual-link-state? ipi-ospfv3-types:ospfv3_interface_state_t
+---n ospfv3-virtual-link-neighbor-state-change
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?        cml-data-types:cml_notif_class_t
```

---

---

```
| +--ro remote-router-id? inet:ipv4-address
| +--ro area-id?         ipi-ospfv3-types:ospfv3_area_t
| +--ro ospfv3-id?      ipi-ospfv3-types:ospfv3_string_t
| +--ro router-id?     inet:ipv4-address
| +--ro instance-id?   uint8
| +--ro neighbor-state? ipi-ospfv3-types:ospfv3_interface_state_t
+---n ospfv3-virtual-link-rx-bad-packet
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro remote-router-id? inet:ipv4-address
| +--ro area-id?      ipi-ospfv3-types:ospfv3_area_t
| +--ro ospfv3-id?    ipi-ospfv3-types:ospfv3_string_t
| +--ro router-id?    inet:ipv4-address
| +--ro instance-id?  uint8
| +--ro packet-type?  ipi-ospfv3-types:ospfv3_packet_type_t
+---n ospfv3-virtual-link-tx-retransmit
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro remote-router-id? inet:ipv4-address
| +--ro area-id?      ipi-ospfv3-types:ospfv3_area_t
| +--ro ospfv3-id?    ipi-ospfv3-types:ospfv3_string_t
| +--ro router-id?    inet:ipv4-address
| +--ro instance-id?  uint8
| +--ro packet-type?  ipi-ospfv3-types:ospfv3_packet_type_t
| +--ro lsdB-type?     uint32
| +--ro lsdB-lsid?     uint32
| +--ro lsdB-router-id? inet:ipv4-address
+---n ospfv3-interface-config-error
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro interface-name? string
| +--ro router-id?     inet:ipv4-address
| +--ro interface-index? uint32
| +--ro interface-instance-id? uint8
| +--ro error-type?    ipi-ospfv3-types:ospfv3_config_error_type_t
| +--ro packet-type?  ipi-ospfv3-types:ospfv3_packet_type_t
```

```

+---n ospfv3-interface-state-change
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro interface-name?  string
| +--ro router-id?     inet:ipv4-address
| +--ro interface-index?  uint32
| +--ro interface-instance-id?  uint8
| +--ro interface-state?  ipi-ospfv3-types:ospfv3_interface_state_t
+---n ospfv3-interface-rx-bad-packet
  +--ro severity?      cml-data-types:cml_notif_severity_t
  +--ro eventClass?   cml-data-types:cml_notif_class_t
  +--ro interface-name?  string
  +--ro router-id?     inet:ipv4-address
  +--ro interface-index?  uint32
  +--ro interface-instance-id?  uint8
  +--ro packet-src?     inet:ipv6-address
  +--ro packet-type?    ipi-ospfv3-types:ospfv3_packet_type_t

```

---

## module: ipi-pbr

```

+--rw pbr
  +--rw config
  | +--rw enabled?  empty
  +--ro state
  | +--ro enabled?  empty
  +--rw interfaces
    +--rw interface* [name]
      +--rw name    -> ../config/name
      +--rw config
      | +--rw name?      -> /ipi-interface:interfaces/interface/name
      | +--rw route-map-name?  string
      | +--rw route-map-v6-name?  string {feature-list:HAVE_IPV6}?
      +--ro state
        +--ro name?      -> /ipi-interface:interfaces/interface/name
        +--ro route-map-name?  string
        +--ro route-map-v6-name?  string {feature-list:HAVE_IPV6}?

```

rpcs:

```
+---x clear-route-map-pbr-statistics {feature-list:HAVE_PBR}?
  +---w input
    +---w route-map-name  string
```

---

## module: ipi-pcep

```
+--rw pcep
  +--rw entities
    | +--rw entity* [entity-id]
    |   +--rw entity-id    -> ../config/entity-id
    |   +--rw config
    |     | +--rw entity-id?      uint32
    |     | +--rw keep-alive-interval?  uint8
    |     | +--rw dead-interval?    uint8
    |     | +--rw request-timeout?   uint16
    |     | +--rw tolerance-keepalive? uint32
    |     | +--rw tolerance-dead-interval? uint32
    |     | +--rw cool-off-timeout?   int32
    |     | +--rw source-address?    inet:ip-address
    |     | +--rw recovery-policy?   ipi-pcep-types:pcep_dlg_recovery_type_t
    |     +--ro state
    |       | +--ro entity-id?      uint32
    |       | +--ro keep-alive-interval?  uint8
    |       | +--ro dead-interval?    uint8
    |       | +--ro request-timeout?   uint16
    |       | +--ro tolerance-keepalive?  uint32
    |       | +--ro tolerance-dead-interval? uint32
    |       | +--ro cool-off-timeout?   int32
    |       | +--ro source-address?    inet:ip-address
    |       | +--ro recovery-policy?   ipi-pcep-types:pcep_dlg_recovery_type_t
```

---

```
| | +--ro role?          ipi-pcep-types:pcep_role_t
| | +--ro connect-timer?  uint32
| | +--ro connect-max-retry?  uint32
| | +--ro init-backoff-timer?  uint32
| | +--ro max-backoff-timer?  uint32
| | +--ro open-wait-timer?    uint32
| | +--ro keep-wait-timer?    uint32
| +--rw capability
| | +--rw config
| | | +--rw pce-instantiate?  empty
| | | +--rw segment-routing?  empty {feature-list:HAVE_PCEP_SR}?
| | | +--rw segment-routing-v6?  empty {feature-list:HAVE_PCEP_SRV6}?
| | +--ro state
| |   +--ro pce-instantiate?  empty
| |   +--ro segment-routing?  empty {feature-list:HAVE_PCEP_SR}?
| |   +--ro segment-routing-v6?  empty {feature-list:HAVE_PCEP_SRV6}?
| +--rw stateful
| | +--rw config
| | | +--rw redelegation-timeout?  uint32
| | | +--rw lsp-state-timeout?    ipi-pcep-types:pcep_lsp_state_timeout_t
| | +--ro state
| |   +--ro redelegation-timeout?  uint32
| |   +--ro lsp-state-timeout?    ipi-pcep-types:pcep_lsp_state_timeout_t
| +--rw flap-limit
| | +--rw config!
| | | +--rw flap-count    int32
| | | +--rw flap-interval  int32
| | +--ro state
| |   +--ro flap-count    int32
| |   +--ro flap-interval  int32
| +--rw update-limit
| | +--rw config!
| | | +--rw count    int32
| | | +--rw interval  int32
| | +--ro state
| |   +--ro count    int32
```

```

| | +--ro interval int32
| +--rw lsp-database
| | +--ro ingress-tunnel* [plsp-id]
| | +--ro plsp-id -> ../state/plsp-id
| | +--ro lsp* [lsp-id]
| | | +--ro lsp-id -> ../state/lsp-id
| | | +--ro state
| | | | +--ro lsp-id? uint32
| | | | +--ro operational-state? ipi-pcep-types:pcep_lsp_oper_status_t
| | | | +--ro last-lsp-error? ipi-pcep-types:pcep_lsp_error_t
| | | +--ro binding-label-status
| | | +--ro state
| | | +--ro label-value? uint32
| | | +--ro allocation-mode? ipi-pcep-types:pcep_binding_alloc_mode_t
| | +--ro state
| | | +--ro plsp-id? uint32
| | | +--ro tunnel-id? uint32
| | | +--ro candidate-path-id? uint32 {feature-list:HAVE_PCEP_SR}?
| | | +--ro source? inet:ipv4-address
| | | +--ro destination? inet:ipv4-address
| | | +--ro extended-tunnel-id? inet:ipv4-address
| | | +--ro admin-state? boolean
| | | +--ro symbolic-name? string
| | | +--ro tunnel-name? string
| | | +--ro setup-type? ipi-pcep-types:pcep_lsp_setup_type_t
| | | +--ro local-policy-active? empty
| | | +--ro request-id? uint32
| | | +--ro request-state? ipi-pcep-types:pcep_tunnel_request_state_t
| | | +--ro request-flags? ipi-pcep-types:pcep_tunnel_request_flags_t
| | | +--ro error-flags? ipi-pcep-types:pcep_tunnel_err_flags_t
| | | +--ro recent-lsp-id? uint32 {feature-list:HAVE_PCEP_RSVP}?
| | | +--ro pending-updates? empty
| | | +--ro last-event? ipi-pcep-types:pcep_tunnel_recent_event_t
| | +--ro pce-delegation
| | | +--ro state
| | | +--ro enabled? empty

```

---

```
| | | +--ro address?          inet:ipv4-address
| | | +--ro stateful-request-parameter-id? uint32
| | +--ro initiation
| |   +--ro state
| |     +--ro enabled? empty
| |     +--ro address? inet:ipv4-address
| +--rw peers
|   +--rw peer* [address]
|     +--rw address -> ../config/address
|     +--rw config
|       | +--rw address?          ipi-pcep-types:pcep_ip_addr_t
|       | +--rw delegation-preference? uint32
|       | +--rw authentication-key? string {feature-list:HAVE_TCP_MD5SIG}?
|       +--ro state
|         | +--ro address?          ipi-pcep-types:pcep_ip_addr_t
|         | +--ro delegation-preference? uint32
|         | +--ro authentication-key? string {feature-list:HAVE_TCP_MD5SIG}?
|         | +--ro role?            ipi-pcep-types:pcep_role_t
|         | +--ro session-exists?  empty
|         | +--ro session-up-time?  yang:timestamp
|         | +--ro session-fail-time? yang:timestamp
|         +--ro counters
|           | +--ro stateful
|           | | +--ro tx-path-reports? yang:counter32
|           | | +--ro tx-reports?     yang:counter32
|           | | +--ro rx-path-updates? yang:counter32
|           | | +--ro rx-updates?     yang:counter32
|           | | +--ro rx-pc-initiate? yang:counter32
|           | | +--ro rx-lsp-initiate? yang:counter32
|           | +--ro session-setup-fail? yang:counter32
|           | +--ro tx-open-message?   yang:counter32
|           | +--ro tx-keep-alive?     yang:counter32
|           | +--ro tx-pc-notifications? yang:counter32
|           | +--ro tx-path-request-errors? yang:counter32
|           | +--ro tx-path-request?   yang:counter32
|           | +--ro tx-request?       yang:counter32
```

---

```

|   |   +--ro tx-request-for-pending-reply?  yang:counter32
|   |   +--ro tx-request-for-error-received? yang:counter32
|   |   +--ro tx-request-for-nopath-receive? yang:counter32
|   |   +--ro tx-request-for-cancel-receive? yang:counter32
|   |   +--ro tx-request-for-ero-received?   yang:counter32
|   |   +--ro tx-request-timed-out?         yang:counter32
|   |   +--ro tx-request-sent-cancel-sent?   yang:counter32
|   |   +--ro tx-request-sent-closed?       yang:counter32
|   |   +--ro rx-open-message?              yang:counter32
|   |   +--ro rx-keep-alive?                yang:counter32
|   |   +--ro rx-pc-notifications?          yang:counter32
|   |   +--ro rx-path-request-errors?       yang:counter32
|   |   +--ro rx-path-reply?                yang:counter32
|   |   +--ro rx-unknown?                   yang:counter32
|   |   +--ro rx-corrupt?                   yang:counter32
|   +--ro capability
|   |   +--ro state
|   |   |   +--ro pce-instantiate?  empty
|   |   |   +--ro segment-routing?  empty {feature-list:HAVE_PCEP_SR}?
|   |   |   +--ro lsp-update?       empty
|   +--ro session
|   |   +--ro state
|   |   |   +--ro initiator?          ipi-pcep-types:pcep_initiator_t
|   |   |   +--ro state?              ipi-pcep-types:pcep_session_state_t
|   |   |   +--ro state-changes?      uint32
|   |   |   +--ro state-last-change?   yang:timestamp
|   |   |   +--ro creation-time?       yang:timestamp
|   |   |   +--ro connect-retry?       yang:counter32
|   |   |   +--ro open-retry?          uint8
|   |   |   +--ro local-id?            uint8
|   |   |   +--ro remote-id?           uint8
|   |   |   +--ro peer-overloaded?     boolean
|   |   |   +--ro peer-overload-time?  uint32
|   |   |   +--ro keepalive-timer?     uint8
|   |   |   +--ro peer-keepalive-timer? uint8
|   |   |   +--ro dead-timer?          uint8

```

---

```

|         +--ro peer-dead-timer?          uint8
|         +--ro keepalive-hold-timer-remain? uint8
|         +--ro max-unknown-message?      uint32
+--rw init-lsp-limit
| +--rw config!
| | +--rw lsp-limit  uint32
| +--ro state
|   +--ro lsp-limit  uint32
+--rw debug
| +--rw config
| | +--rw options?  ipi-pcep-types:pcep_debug_t
| +--ro state
|   +--ro options?          ipi-pcep-types:pcep_debug_t
|   +--ro terminal-debug-status? ipi-pcep-types:pcep_debug_t
+--rw srv6-spirent-comp
  +--rw config
  | +--rw srv6-spirent-comp?  empty
  +--ro state
    +--ro srv6-spirent-comp?  empty

```

rpcs:

```

+---x clear-pcep-peer-all {feature-list:HAVE_PCEP}?
+---x clear-pcep-peer {feature-list:HAVE_PCEP}?
| +---w input
|   +---w address  inet:ip-address
+---x clear-pcep-statistics {feature-list:HAVE_PCEP}?
+---x debug-pcep-all {feature-list:HAVE_PCEP}?
+---x pcep-terminal-debug-on {feature-list:HAVE_PCEP}?
| +---w input
|   +---w terminal-debug-options  ipi-pcep-types:pcep_debug_t
+---x pcep-terminal-debug-off {feature-list:HAVE_PCEP}?
| +---w input
|   +---w terminal-debug-options  ipi-pcep-types:pcep_debug_t
+---x clear-pcep-requests {feature-list:HAVE_PCEP}?
  +---w input
    +---w tunnel-id  string

```

---

notifications:

+---n pcep-session-up

| +--ro severity? cml-data-types:cml\_notif\_severity\_t  
| +--ro eventClass? cml-data-types:cml\_notif\_class\_t  
| +--ro address? ipi-pcep-types:pcep\_ip\_addr\_t  
| +--ro entity-id? uint32  
| +--ro initiator? ipi-pcep-types:pcep\_initiator\_t  
| +--ro state-last-change? yang:timestamp  
| +--ro state? ipi-pcep-types:pcep\_session\_state\_t

+---n pcep-session-down

| +--ro severity? cml-data-types:cml\_notif\_severity\_t  
| +--ro eventClass? cml-data-types:cml\_notif\_class\_t  
| +--ro address? ipi-pcep-types:pcep\_ip\_addr\_t  
| +--ro entity-id? uint32  
| +--ro initiator? ipi-pcep-types:pcep\_initiator\_t  
| +--ro state-last-change? yang:timestamp  
| +--ro state? ipi-pcep-types:pcep\_session\_state\_t

+---n pcep-session-peer-overload

| +--ro severity? cml-data-types:cml\_notif\_severity\_t  
| +--ro eventClass? cml-data-types:cml\_notif\_class\_t  
| +--ro address? ipi-pcep-types:pcep\_ip\_addr\_t  
| +--ro entity-id? uint32  
| +--ro initiator? ipi-pcep-types:pcep\_initiator\_t  
| +--ro peer-overloaded? boolean  
| +--ro peer-overload-time? uint32

+---n pcep-session-peer-overload-clear

+--ro severity? cml-data-types:cml\_notif\_severity\_t  
+--ro eventClass? cml-data-types:cml\_notif\_class\_t  
+--ro address? ipi-pcep-types:pcep\_ip\_addr\_t  
+--ro entity-id? uint32  
+--ro initiator? ipi-pcep-types:pcep\_initiator\_t  
+--ro peer-overloaded? boolean

---

## module: ipi-pim

```

+--rw pim
  +--rw debug {feature-list:HAVE_BFD}?
    | +--rw config
    | | +--rw bfd? empty
    | +--ro state
    | +--ro bfd? empty
    | +--ro terminal-debug-status? cml-data-types:cml_on_off_t
  +--rw ipv4
    | +--rw instances
    | | +--rw instance* [vrf-name]
    | | +--rw vrf-name -> ../config/vrf-name
    | | +--rw config
    | | | +--rw vrf-name? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
    | | | +--rw router-id? inet:ipv4-address {feature-list:HAVE_PIM_SM}?
    | | | +--rw join-prune-interval? uint16 {feature-list:HAVE_PIM_SM}?
    | | | +--rw ecmp-bundle* string {feature-list:HAVE_PIM_ECMP_REDIRECT}?
    | | | +--rw enable-bfd-all-interfaces? empty {feature-list:HAVE_BFD}?
    | | +--ro state
    | | | +--ro vrf-name? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
    | | | +--ro router-id? inet:ipv4-address {feature-list:HAVE_PIM_SM}?
    | | | +--ro join-prune-interval? uint16 {feature-list:HAVE_PIM_SM}?

```

```
| | | +--ro ecmp-bundle*          string {feature-list:HAVE_PIM_ECMP_REDIRECT}?
| | | +--ro enable-bfd-all-interfaces? empty {feature-list:HAVE_BFD}?
| | | +--ro counters
| | | | +--ro joins-sent?      yang:counter64
| | | | +--ro joins-received? yang:counter64
| | | +--ro rp-sets
| | |   +--ro rp-set* [group-address]
| | |     +--ro group-address -> ../state/group-address
| | |     +--ro state
| | |       | +--ro group-address?  cml-data-types:cml_ipv4_addr_prefix_t
| | |       | +--ro fragment-tag?   uint16
| | |       | +--ro number-of-rp?   uint32
| | |       | +--ro expiration-time? string
| | |       +--ro rps
| | |         +--ro rp* [rp-address]
| | |           +--ro rp-address -> ../state/rp-address
| | |           +--ro state
| | |             +--ro rp-address?  inet:ipv4-address
| | |             +--ro from?        inet:ipv4-address
| | |             +--ro mode?        ipi-pim-ipv4-types:pim_ipv4_rp_mode_t
| | |             +--ro type?        ipi-pim-ipv4-types:pim_ipv4_rp_type_t
| | |             +--ro priority?    uint8
| | |             +--ro hold-time?   uint16
| | |             +--ro up-time?     string
| | |             +--ro expiration-time? string
| | +--ro next-hop-destinations
| | | +--ro next-hop-destination* [destination-address]
| | |   +--ro destination-address -> ../state/destination-address
| | |   +--ro state
| | |     | +--ro destination-address?  inet:ipv4-address
| | |     | +--ro destination-type?    ipi-pim-ipv4-types:pim_ipv4_next_hop_flags_t
| | |     | +--ro next-hop-count?      uint32
| | |     | +--ro preference?          uint16
| | |     | +--ro metric?              uint32
| | |     | +--ro reference-count?     uint32
| | |     | +--ro route-type?          ipi-pim-ipv4-types:pim_ipv4_route_type_t
```

```

| | | | +--ro route-sub-type?          ipi-pim-ipv4-types:pim_ipv4_route_sub_type_t
| | | | +--ro subaddress-family-identifier? uint32
| | | | +--ro interface-index?         uint16
| | | +--ro next-hops
| | |   +--ro next-hop* [ipv4-address]
| | |     +--ro ipv4-address  -> ../state/ipv4-address
| | |     +--ro state
| | |       +--ro ipv4-address?      inet:ipv4-address
| | |       +--ro type?              ipi-pim-ipv4-types:pim_ipv4_next_hop_type_t
| | |       +--ro recursive-active-next-hop? uint8
| | |       +--ro recursive-type?     ipi-pim-ipv4-types:pim_ipv4_next_hop_type_t
| | |       +--ro recursive-interface-id? uint8
| | |       +--ro interface-index?    uint16
| | |       +--ro bfd-interface-index? uint16
| | |       +--ro interface-name?     string
| | +--rw register-packet {feature-list:HAVE_PIM_SM}?
| | | +--rw config
| | | | +--rw register-reachability-check? cml-data-types:cml_enable_disable_t
| | | | +--rw rate-limit?                 uint16
| | | | +--rw suppress-interval?         uint16
| | | | +--rw keep-alive-interval?      uint16
| | | | +--rw source-address?           ipi-pim-ipv4-types:pim_ipv4_reg_source_t
| | | | +--rw accept-register?          string
| | | +--ro state
| | |   +--ro register-reachability-check? cml-data-types:cml_enable_disable_t
| | |   +--ro rate-limit?                 uint16
| | |   +--ro suppress-interval?         uint16
| | |   +--ro keep-alive-interval?      uint16
| | |   +--ro source-address?           ipi-pim-ipv4-types:pim_ipv4_reg_source_t
| | |   +--ro accept-register?          string
| | |   +--ro counters
| | |     +--ro register-packet-received? yang:counter64
| | |     +--ro register-null-received?  yang:counter64
| | |     +--ro register-stop-sent?     yang:counter64
| | |     +--ro register-stop-received?  yang:counter64
| | +--rw interop

```

```

| | | +--rw config
| | | | +--rw ignore-rp-set-priority?  empty {feature-list:HAVE_PIM_SM}?
| | | | +--rw cisco-bsr-interop-enable?  empty {feature-list:HAVE_PIM_SM}?
| | | +--ro state
| | | | +--ro ignore-rp-set-priority?  empty {feature-list:HAVE_PIM_SM}?
| | | | +--ro cisco-bsr-interop-enable?  empty {feature-list:HAVE_PIM_SM}?
| | | +--rw register-packet
| | |   +--rw config!
| | |     | +--rw cisco-register-checksum-enable  empty {feature-list:HAVE_PIM_SM}?
| | |     | +--rw access-control-list?          string {feature-list:HAVE_PIM_SM}?
| | |     +--ro state
| | |       +--ro cisco-register-checksum-enable  empty {feature-list:HAVE_PIM_SM}?
| | |       +--ro access-control-list?          string {feature-list:HAVE_PIM_SM}?
| | +--rw spt-switch
| | | +--rw config!
| | | | +--rw enable          empty {feature-list:HAVE_PIM_SM}?
| | | | +--rw access-control-list?  string {feature-list:HAVE_PIM_SM}?
| | | +--ro state
| | |   +--ro enable          empty {feature-list:HAVE_PIM_SM}?
| | |   +--ro access-control-list?  string {feature-list:HAVE_PIM_SM}?
| | +--rw ssm {feature-list:HAVE_PIM_SSM}?
| | | +--rw config
| | | | +--rw range-policy?  ipi-pim-ipv4-types:pim_ipv4_ssm_range_policy_type_t
| | | +--ro state
| | |   +--ro range-policy?  ipi-pim-ipv4-types:pim_ipv4_ssm_range_policy_type_t
| | +--rw anycast-rps {feature-list:HAVE_PIM_SM}?
| | | +--rw anycast-rp* [anycast-rp-address member-rp-address]
| | |   +--rw anycast-rp-address  -> ../config/anycast-rp-address
| | |   +--rw member-rp-address  -> ../config/member-rp-address
| | |   +--rw config
| | |     | +--rw anycast-rp-address?  inet:ipv4-address
| | |     | +--rw member-rp-address?  inet:ipv4-address
| | |     +--ro state
| | |       +--ro anycast-rp-address?  inet:ipv4-address
| | |       +--ro member-rp-address?  inet:ipv4-address
| | +--rw rendezvous-point

```

```
| | | +--rw static-rps
| | | | +--rw static-rps-default
| | | | | +--rw static-rp-default* [rp-address]
| | | | | +--rw rp-address -> ../config/rp-address
| | | | | +--rw config
| | | | | | +--rw rp-address?          inet:ipv4-address
| | | | | | +--rw access-control-list?      string
| | | | | | +--rw override-dynamically-learned-rp?  empty
| | | | | +--ro state
| | | | | | +--ro rp-address?          inet:ipv4-address
| | | | | | +--ro access-control-list?      string
| | | | | | +--ro override-dynamically-learned-rp?  empty
| | | +--rw bootstrap-router
| | | | +--rw bsr-candidate
| | | | | +--rw config
| | | | | | +--rw interface-name? -> /ipi-interface:interfaces/interface/name
| | | | | | +--rw hash-mask-length? uint8
| | | | | | +--rw priority?      uint8
| | | | | +--ro state
| | | | | | +--ro interface-name? -> /ipi-interface:interfaces/interface/name
| | | | | | +--ro hash-mask-length? uint8
| | | | | | +--ro priority?      uint8
| | | +--rw rp-candidates
| | | | +--rw rp-candidate* [interface-name]
| | | | | +--rw interface-name -> ../config/interface-name
| | | | | +--rw config
| | | | | | +--rw interface-name? -> /ipi-interface:interfaces/interface/name
| | | | | | +--rw access-control-list?      string
| | | | | | +--rw advertisement-interval? uint16
| | | | | | +--rw priority?          uint8
| | | | | +--ro state
| | | | | | +--ro interface-name? -> /ipi-interface:interfaces/interface/name
| | | | | | +--ro access-control-list?      string
| | | | | | +--ro advertisement-interval? uint16
| | | | | | +--ro priority?          uint8
| | | +--rw msdp {feature-list:HAVE_PIM_MSDP}?
```

```
| | | +--rw config
| | | | +--rw originator-id? string
| | | | +--ro state
| | | | | +--ro originator-id? string
| | | | | +--ro source-active-entries-entries-count? uint32
| | | | +--rw source-active-entries
| | | | | +--rw source-active-entry* [source-address group-address]
| | | | | | +--rw source-address -> ../config/source-address
| | | | | | +--rw group-address -> ../config/group-address
| | | | | +--rw config
| | | | | | +--rw source-address? inet:ipv4-address
| | | | | | +--rw group-address? inet:ipv4-address
| | | | | | +--rw rp-address inet:ipv4-address
| | | | | +--ro state
| | | | | | +--ro source-address? inet:ipv4-address
| | | | | | +--ro group-address? inet:ipv4-address
| | | | | | +--ro rp-address inet:ipv4-address
| | | | | | +--ro static-configured? empty
| | | | | | +--ro uptime? string
| | | | | | +--ro expire-time? uint32
| | | | | | +--ro stopped? empty
| | | | | | +--ro sa-rp-forward-count? yang:counter64
| | | | | | +--ro reverse-path-forwarding-peer? inet:ipv4-address
| | | +--rw peers
| | | | +--rw peer* [address]
| | | | | +--rw address -> ../config/address
| | | | | +--rw config
| | | | | | +--rw address? inet:ipv4-address
| | | | | | +--rw source-address? ipi-pim-ipv4-types:pim_ipv4_reg_source_t
| | | | | | +--rw mesh-group? string
| | | | | | +--rw default-peer? empty
| | | | | | +--rw prefix-list? ipi-pim-ipv4-types:pim_ipv4_msdp_peer_acl_t
| | | | | +--ro state
| | | | | | +--ro counters
| | | | | | | +--ro keepalives-sent? yang:counter64
| | | | | | | +--ro keepalives-received? yang:counter64
```

```

| | | | | +--ro connection-retries? yang:counter64
| | | | | +--ro address?          inet:ipv4-address
| | | | | +--ro source-address?   ipi-pim-ipv4-types:pim_ipv4_reg_source_t
| | | | | +--ro mesh-group?      string
| | | | | +--ro default-peer?    empty
| | | | | +--ro prefix-list?     ipi-pim-ipv4-types:pim_ipv4_msdp_peer_acl_t
| | | | | +--ro peer-state?      ipi-pim-ipv4-types:pim_ipv4_msdp_peer_state_t
| | | | | +--ro peer-role?      ipi-pim-ipv4-types:pim_ipv4_msdp_peer_role_t
| | | | +--rw authentication
| | | |   +--rw config
| | | |     | +--rw password? string {feature-list:HAVE_TCP_MD5SIG}?
| | | |     +--ro state
| | | |       +--ro password? string {feature-list:HAVE_TCP_MD5SIG}?
| | +--rw debug
| | | +--rw config
| | | | +--rw options? ipi-pim-ipv4-types:pim_ipv4_debug_t
| | | | +--ro state
| | | |   +--ro options?          ipi-pim-ipv4-types:pim_ipv4_debug_t
| | | |   +--ro terminal-debug-status? ipi-pim-ipv4-types:pim_ipv4_debug_t
| | +--ro multicast-route-table
| | | +--ro state
| | | | +--ro counters
| | | |   +--ro xxrp-entries? yang:counter32
| | | |   +--ro g-prefix-entries? yang:counter32
| | | |   +--ro xg-entries? yang:counter32
| | | |   +--ro sg-entries? yang:counter32
| | | |   +--ro sg-rpt-entries? yang:counter32
| | | |   +--ro fcr-entries? yang:counter32
| | | +--ro multicast-routes
| | | | +--ro multicast-route* [source-address group-address type]
| | | |   +--ro source-address      -> ../state/source-address
| | | |   +--ro group-address       -> ../state/group-address
| | | |   +--ro type                -> ../state/type
| | | |   +--ro state
| | | |     | +--ro source-address?   inet:ipv4-address
| | | |     | +--ro group-address?   inet:ipv4-address

```

```

| | | +-ro mode?          ipi-pim-ipv4-types:pim_ipv4_multicast_route_mode_t
| | | +-ro type?         ipi-pim-ipv4-types:pim_ipv4_multicast_route_type_t
| | | +-ro uptime?      string
| | | +-ro next-hop-address?  inet:ipv4-address
| | | +-ro next-hop-interface-name? string
| | | +-ro last-rendezvous-point?  inet:ipv4-address
| | | +-ro spt-switch?    empty
| | | +-ro local-olist*   string
| | | +-ro joined-olist*  string
| | | +-ro inherited-olist* string
| | | +-ro pruned-olist*  string
| | +-ro upstream-xxrp
| | | +-ro state
| | | | +-ro route-state?      ipi-pim-ipv4-types:pim_ipv4_multicast_route_upstream_state_t
| | | | +-ro join-prune-timer?  uint32
| | | | +-ro last-rpf-neighbor-address?  inet:ipv4-address
| | | | +-ro last-rpf-next-hop-address?  inet:ipv4-address
| | | | +-ro macro-state?      ipi-pim-ipv4-types:pim_ipv4_multicast_route_upstream_macro_state_t
{feature-list:HAVE_PIM_SM}?
| | +-ro upstream-xg
| | | +-ro state
| | | | +-ro route-state?      ipi-pim-ipv4-types:pim_ipv4_multicast_route_upstream_state_t
| | | | +-ro join-prune-timer?  uint32
| | | | +-ro last-rpf-neighbor-address?  inet:ipv4-address
| | | | +-ro macro-state?      ipi-pim-ipv4-types:pim_ipv4_multicast_route_upstream_macro_state_t
{feature-list:HAVE_PIM_SM}?
| | +-ro upstream-sg
| | | +-ro state
| | | | +-ro route-state?      ipi-pim-ipv4-types:pim_ipv4_multicast_route_upstream_state_t
| | | | +-ro join-prune-timer?  uint32
| | | | +-ro last-rpf-neighbor-address?  inet:ipv4-address
| | | | +-ro keep-alive-timer?  uint32
| | | | +-ro spt-switch?        empty
| | | | +-ro macro-state?      ipi-pim-ipv4-types:pim_ipv4_multicast_route_upstream_macro_state_t
{feature-list:HAVE_PIM_SM}?
| | +-ro upstream-sg-rpt
| | | +-ro state

```

```

| | | +--ro route-state?   ipi-pim-ipv4-types:pim_ipv4_multicast_route_upstream_sg_rpt_mode_t
| | | +--ro override-timer? uint32
| | | +--ro forwarding-cache-registers
| | | | +--ro forwarding-cache-register* [address]
| | | | +--ro address   -> ../state/address
| | | | +--ro state
| | | | | +--ro address?      inet:ipv4-address
| | | | | +--ro keep-alive-timer? uint32
| | | | | +--ro inherited-olist* string
| | | +--ro downstream-interfaces
| | | | +--ro downstream-interface* [interface-name]
| | | | | +--ro interface-name   -> ../state/interface-name
| | | | | +--ro state
| | | | | | +--ro interface-name? string
| | | | | +--ro downstream-xg-sg
| | | | | | +--ro state
| | | | | | | +--ro route-state?      ipi-pim-ipv4-types:pim_ipv4_multicast_route_downstream_state_t
| | | | | | | +--ro expiry-timer?      uint32
| | | | | | | +--ro prune-pending-timer? uint32
| | | | | | | +--ro assert-state?      ipi-pim-ipv4-types:pim_ipv4_multicast_route_downstream_assert_state_t
| | | | | | | +--ro assert-timer?      uint32
| | | | | | | +--ro winner-address?    inet:ipv4-address
| | | | | | | +--ro metric?            uint32
| | | | | | | +--ro preference?       uint32
| | | | | | | +--ro rpt-bit?          empty
| | | | | | | +--ro macro-state?      ipi-pim-ipv4-types:pim_ipv4_multicast_route_downstream_macro_state_t
| | | | +--ro downstream-xxrp-sg-rpt
| | | | | +--ro state
| | | | | | +--ro route-state?      ipi-pim-ipv4-types:pim_ipv4_multicast_route_downstream_state_t
| | | | | | +--ro rpt-state?        ipi-pim-ipv4-types:pim_ipv4_multicast_route_downstream_rpt_state_t
| | | | | | +--ro expiry-timer?      uint32
| | | | | | +--ro prune-pending-timer? uint32
| | +--rw interfaces
| | | +--rw interface* [name]
| | | | +--rw name   -> ../config/name
| | | | +--rw config

```

```

| | +--rw name?                -> /ipi-interface:interfaces/interface/name
| | +--rw pim-mode?           ipi-pim-ipv4-types:pim_ipv4_mode_t
| | +--rw bsr-border?        empty {feature-list:HAVE_PIM_SM}?
| | +--rw dr-priority?       uint32
| | +--rw hello-interval?    uint16
| | +--rw hello-holdtime?    uint16
| | +--rw passive-enable?    empty
| | +--rw exclude-generated-id? empty {feature-list:HAVE_PIM_SM}?
| | +--rw unicast-bootstrap-router? empty {feature-list:HAVE_PIM_SM}?
| | +--rw neighbor-access-control-list-filter? string
| | +--rw state-refresh-origination-interval? uint16 {feature-list:HAVE_PIM_DM}?
| | +--rw ecmp-bundle?       string {feature-list:HAVE_PIM_ECMP_REDIRECT}?
| | +--rw propagation-delay? uint16
| | +--rw enable-bfd?        cml-data-types:cml_enable_disable_t {feature-list:HAVE_BFD}?
| +--ro state
| | +--ro name?              -> /ipi-interface:interfaces/interface/name
| | +--ro pim-mode?          ipi-pim-ipv4-types:pim_ipv4_mode_t
| | +--ro bsr-border?        empty {feature-list:HAVE_PIM_SM}?
| | +--ro dr-priority?       uint32
| | +--ro hello-interval?    uint16
| | +--ro hello-holdtime?    uint16
| | +--ro passive-enable?    empty
| | +--ro exclude-generated-id? empty {feature-list:HAVE_PIM_SM}?
| | +--ro unicast-bootstrap-router? empty {feature-list:HAVE_PIM_SM}?
| | +--ro neighbor-access-control-list-filter? string
| | +--ro state-refresh-origination-interval? uint16 {feature-list:HAVE_PIM_DM}?
| | +--ro ecmp-bundle?       string {feature-list:HAVE_PIM_ECMP_REDIRECT}?
| | +--ro propagation-delay? uint16
| | +--ro enable-bfd?        cml-data-types:cml_enable_disable_t {feature-list:HAVE_BFD}?
| | +--ro next-hello?        string
| | +--ro router-id?         inet:ipv4-address
| | +--ro local-id?          uint32
| | +--ro dr-address?        inet:ipv4-address
| +--ro neighbors
| | +--ro neighbor* [address]
| |   +--ro address -> ../state/address

```

```

| | +--ro state
| |   +--ro address?          inet:ipv4-address
| |   +--ro designated-router? empty
| |   +--ro neighbor-established? string
| |   +--ro neighbor-expires?  string
| |   +--ro secondary-address*  inet:ipv4-address
| |   +--ro hello-holdtime?     uint16
| |   +--ro lan-delay?          uint16
| |   +--ro override-interval?  uint32
| |   +--ro dr-priority?        uint32 {feature-list:HAVE_PIM_SM}?
| |   +--ro generated-id?       uint32
| |   +--ro router-id?          inet:ipv4-address
| |   +--ro local-id?           uint32
| |   +--ro tracking-support?   empty
| |   +--ro ecmp-redirect-enabled? empty {feature-list:HAVE_PIM_ECMP_REDIRECT}?
| +--rw pim-redundancy
|   +--rw vrrp {feature-list:HAVE_PIM_SM_VRRP_AWARE}?
|     +--rw config!
|       | +--rw virtual-router-id  uint8
|       | +--rw dr-priority        uint32
|       +--ro state
|         +--ro virtual-router-id  uint8
|         +--ro dr-priority        uint32
|         +--ro selected-dr-priority? uint32
|         +--ro vrrp-master?       boolean
+--rw ipv6
  +--rw instances
  | +--rw instance* [vrf-name]
  |   +--rw vrf-name          -> ../config/vrf-name
  |   +--rw config
  | | +--rw vrf-name?          -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
  | | +--rw router-id?         inet:ipv4-address {feature-list:HAVE_PIM_SM}?
  | | +--rw join-prune-interval? uint16 {feature-list:HAVE_PIM_SM}?
  | | +--rw ecmp-bundle*       string {feature-list:HAVE_PIM_ECMP_REDIRECT}?
  | | +--rw enable-bfd-all-interfaces? empty {feature-list:HAVE_BFD}?
  | +--ro state

```

---

```

| | +--ro vrf-name?          -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
| | +--ro router-id?        inet:ipv4-address {feature-list:HAVE_PIM_SM}?
| | +--ro join-prune-interval? uint16 {feature-list:HAVE_PIM_SM}?
| | +--ro ecmp-bundle*      string {feature-list:HAVE_PIM_ECMP_REDIRECT}?
| | +--ro enable-bfd-all-interfaces? empty {feature-list:HAVE_BFD}?
| | +--ro counters
| | | +--ro joins-sent?      yang:counter64
| | | +--ro joins-received? yang:counter64
| | +--ro rp-sets
| |   +--ro rp-set* [group-address]
| |     +--ro group-address -> ../state/group-address
| |     +--ro state
| |       | +--ro group-address? cml-data-types:cml_ipv6_prefix_t
| |       | +--ro fragment-tag?  uint16
| |       | +--ro number-of-rp?  uint32
| |       | +--ro expiration-time? string
| |       +--ro rps
| |         +--ro rp* [rp-address]
| |           +--ro rp-address -> ../state/rp-address
| |           +--ro state
| |             +--ro rp-address?  inet:ipv6-address
| |             +--ro from?        inet:ipv6-address
| |             +--ro mode?        ipi-pim-ipv6-types:pim_ipv6_rp_mode_t
| |             +--ro type?        ipi-pim-ipv6-types:pim_ipv6_rp_type_t
| |             +--ro priority?    uint8
| |             +--ro hold-time?   uint16
| |             +--ro up-time?     string
| |             +--ro expiration-time? string
| | +--ro next-hop-destinations
| |   +--ro next-hop-destination* [destination-address]
| |     +--ro destination-address -> ../state/destination-address
| |     +--ro state
| |       | +--ro destination-address?  inet:ipv6-address
| |       | +--ro destination-type?    ipi-pim-ipv6-types:pim_ipv6_next_hop_flags_t
| |       | +--ro next-hop-count?      uint32
| |       | +--ro preference?          uint16

```

---

---

```
| | | +--ro metric?          uint32
| | | +--ro reference-count?      uint32
| | | +--ro route-type?          ipi-pim-ipv6-types:pim_ipv6_route_type_t
| | | +--ro route-sub-type?      ipi-pim-ipv6-types:pim_ipv6_route_sub_type_t
| | | +--ro subaddress-family-identifier?  uint32
| | | +--ro interface-index?     uint16
| | +--ro next-hops
| |   +--ro next-hop* [ipv6-address]
| |     +--ro ipv6-address  -> ../state/ipv6-address
| |     +--ro state
| |       +--ro ipv6-address?    inet:ipv6-address
| |       +--ro type?           ipi-pim-ipv6-types:pim_ipv6_next_hop_type_t
| |       +--ro recursive-active-next-hop?  uint8
| |       +--ro recursive-type?    ipi-pim-ipv6-types:pim_ipv6_next_hop_type_t
| |       +--ro recursive-interface-id?  uint8
| |       +--ro interface-index?    uint16
| |       +--ro bfd-interface-index?  uint16
| |       +--ro interface-name?     string
| +--rw register-packet {feature-list:HAVE_PIM_SM}?
| | +--rw config
| | | +--rw register-reachability-check?  cml-data-types:cml_enable_disable_t
| | | +--rw rate-limit?                  uint16
| | | +--rw suppress-interval?          uint16
| | | +--rw keep-alive-interval?        uint16
| | | +--rw source-address?             ipi-pim-ipv6-types:pim_ipv6_reg_source_t
| | | +--rw accept-register?           string
| | +--ro state
| |   +--ro register-reachability-check?  cml-data-types:cml_enable_disable_t
| |   +--ro rate-limit?                  uint16
| |   +--ro suppress-interval?          uint16
| |   +--ro keep-alive-interval?        uint16
| |   +--ro source-address?             ipi-pim-ipv6-types:pim_ipv6_reg_source_t
| |   +--ro accept-register?           string
| |   +--ro counters
| |     +--ro register-packet-received?  yang:counter64
| |     +--ro register-null-received?   yang:counter64
```

---

```

| |   +--ro register-stop-sent?      yang:counter64
| |   +--ro register-stop-received?  yang:counter64
| +--rw interop
| |   +--rw config
| | |   +--rw ignore-rp-set-priority?  empty {feature-list:HAVE_PIM_SM}?
| | |   +--rw cisco-bsr-interop-enable? empty {feature-list:HAVE_PIM_SM}?
| | |   +--ro state
| | |   +--ro ignore-rp-set-priority?  empty {feature-list:HAVE_PIM_SM}?
| | |   +--ro cisco-bsr-interop-enable? empty {feature-list:HAVE_PIM_SM}?
| | +--rw register-packet
| | |   +--rw config!
| | | |   +--rw cisco-register-checksum-enable  empty {feature-list:HAVE_PIM_SM}?
| | | |   +--rw access-control-list?          string {feature-list:HAVE_PIM_SM}?
| | | +--ro state
| | |   +--ro cisco-register-checksum-enable  empty {feature-list:HAVE_PIM_SM}?
| | |   +--ro access-control-list?          string {feature-list:HAVE_PIM_SM}?
| +--rw spt-switch
| |   +--rw config!
| | |   +--rw enable                    empty {feature-list:HAVE_PIM_SM}?
| | |   +--rw access-control-list?     string {feature-list:HAVE_PIM_SM}?
| | | +--ro state
| | |   +--ro enable                    empty {feature-list:HAVE_PIM_SM}?
| | |   +--ro access-control-list?     string {feature-list:HAVE_PIM_SM}?
| +--rw ssm {feature-list:HAVE_PIM_SSM}?
| |   +--rw config
| | |   +--rw range-policy? ipi-pim-ipv6-types:pim_ipv6_ssm_range_policy_type_t
| | | +--ro state
| | |   +--ro range-policy? ipi-pim-ipv6-types:pim_ipv6_ssm_range_policy_type_t
| +--rw anycast-rps {feature-list:HAVE_PIM_SM}?
| |   +--rw anycast-rp* [anycast-rp-address member-rp-address]
| | |   +--rw anycast-rp-address  -> ../config/anycast-rp-address
| | |   +--rw member-rp-address   -> ../config/member-rp-address
| | | +--rw config
| | | |   +--rw anycast-rp-address?  inet:ipv6-address
| | | |   +--rw member-rp-address?  inet:ipv6-address
| | | +--ro state

```

---

---

```

| |   +--ro anycast-rp-address?  inet:ipv6-address
| |   +--ro member-rp-address?  inet:ipv6-address
| +--rw rendezvous-point
| | +--rw config
| | | +--rw embed-rp?  cml-data-types:cml_enable_disable_t
| | | +--ro state
| | | +--ro embed-rp?  cml-data-types:cml_enable_disable_t
| | | +--rw static-rps
| | | | +--rw static-rps-default
| | | | | +--rw static-rp-default* [rp-address]
| | | | | +--rw rp-address  -> ../config/rp-address
| | | | | +--rw config
| | | | | | +--rw rp-address?          inet:ipv6-address
| | | | | | +--rw access-control-list?      string
| | | | | | +--rw override-dynamically-learned-rp?  empty
| | | | | +--ro state
| | | | | +--ro rp-address?          inet:ipv6-address
| | | | | +--ro access-control-list?      string
| | | | | +--ro override-dynamically-learned-rp?  empty
| | | +--rw bootstrap-router
| | | | +--rw bsr-candidate
| | | | | +--rw config
| | | | | | +--rw interface-name?  -> /ipi-interface:interfaces/interface/name
| | | | | | +--rw hash-mask-length?  uint8
| | | | | | +--rw priority?          uint8
| | | | | +--ro state
| | | | | +--ro interface-name?  -> /ipi-interface:interfaces/interface/name
| | | | | +--ro hash-mask-length?  uint8
| | | | | +--ro priority?          uint8
| | | +--rw rp-candidates
| | | | +--rw rp-candidate* [interface-name]
| | | | | +--rw interface-name  -> ../config/interface-name
| | | | | +--rw config
| | | | | | +--rw interface-name?  -> /ipi-interface:interfaces/interface/name
| | | | | | +--rw access-control-list?  string
| | | | | | +--rw advertisement-interval?  uint16

```

```
| | | +--rw priority?          uint8
| |   +--ro state
| |     +--ro interface-name?   -> /ipi-interface:interfaces/interface/name
| |     +--ro access-control-list?  string
| |     +--ro advertisement-interval? uint16
| |     +--ro priority?          uint8
| +--rw debug
| | +--rw config
| | | +--rw options? ipi-pim-ipv6-types:pim_ipv6_debug_t
| | | +--ro state
| | |   +--ro options?          ipi-pim-ipv6-types:pim_ipv6_debug_t
| | |   +--ro terminal-debug-status? ipi-pim-ipv6-types:pim_ipv6_debug_t
| +--ro multicast-route-table
|   +--ro state
|     | +--ro counters
|     |   +--ro xxrp-entries?  yang:counter32
|     |   +--ro g-prefix-entries? yang:counter32
|     |   +--ro xg-entries?    yang:counter32
|     |   +--ro sg-entries?    yang:counter32
|     |   +--ro sg-rpt-entries? yang:counter32
|     |   +--ro fcr-entries?   yang:counter32
|     +--ro multicast-routes
|       +--ro multicast-route* [source-address group-address type]
|         +--ro source-address   -> ../state/source-address
|         +--ro group-address    -> ../state/group-address
|         +--ro type             -> ../state/type
|         +--ro state
|           | +--ro source-address?  inet:ipv6-address
|           | +--ro group-address?   inet:ipv6-address
|           | +--ro mode?            ipi-pim-ipv6-types:pim_ipv6_multicast_route_mode_t
|           | +--ro type?           ipi-pim-ipv6-types:pim_ipv6_multicast_route_type_t
|           | +--ro uptime?         string
|           | +--ro next-hop-address?  inet:ipv6-address
|           | +--ro next-hop-interface-name? string
|           | +--ro last-rendezvous-point? inet:ipv6-address
|           | +--ro spt-switch?      empty
```

```

|     | +--ro local-olist*      string
|     | +--ro joined-olist*    string
|     | +--ro inherited-olist* string
|     | +--ro pruned-olist*    string
|     +--ro upstream-xxrp
|     | +--ro state
|     |   +--ro route-state?    ipi-pim-ipv6-types:pim_ipv6_multicast_route_upstream_state_t
|     |   +--ro join-prune-timer? uint32
|     |   +--ro last-rpf-neighbor-address? inet:ipv6-address
|     |   +--ro last-rpf-next-hop-address? inet:ipv6-address
|     |   +--ro macro-state?    ipi-pim-ipv6-types:pim_ipv6_multicast_route_upstream_macro_state_t
{feature-list:HAVE_PIM_SM}?
|     +--ro upstream-xg
|     | +--ro state
|     |   +--ro route-state?    ipi-pim-ipv6-types:pim_ipv6_multicast_route_upstream_state_t
|     |   +--ro join-prune-timer? uint32
|     |   +--ro last-rpf-neighbor-address? inet:ipv6-address
|     |   +--ro macro-state?    ipi-pim-ipv6-types:pim_ipv6_multicast_route_upstream_macro_state_t
{feature-list:HAVE_PIM_SM}?
|     +--ro upstream-sg
|     | +--ro state
|     |   +--ro route-state?    ipi-pim-ipv6-types:pim_ipv6_multicast_route_upstream_state_t
|     |   +--ro join-prune-timer? uint32
|     |   +--ro last-rpf-neighbor-address? inet:ipv6-address
|     |   +--ro keep-alive-timer? uint32
|     |   +--ro spt-switch?      empty
|     |   +--ro macro-state?    ipi-pim-ipv6-types:pim_ipv6_multicast_route_upstream_macro_state_t
{feature-list:HAVE_PIM_SM}?
|     +--ro upstream-sg-rpt
|     | +--ro state
|     |   +--ro route-state?    ipi-pim-ipv6-types:pim_ipv6_multicast_route_upstream_sgrpt_mode_t
|     |   +--ro override-timer? uint32
|     +--ro forwarding-cache-registers
|     | +--ro forwarding-cache-register* [address]
|     |   +--ro address -> ../state/address
|     |   +--ro state
|     |   +--ro address?        inet:ipv6-address

```

```

|     |   +--ro keep-alive-timer?  uint32
|     |   +--ro inherited-olist*   string
|     +--ro downstream-interfaces
|         +--ro downstream-interface* [interface-name]
|             +--ro interface-name      -> ../state/interface-name
|             +--ro state
|                 | +--ro interface-name?  string
|                 +--ro downstream-xg-sg
|                     | +--ro state
|                         | +--ro route-state?      ipi-pim-ipv6-types:pim_ipv6_multicast_route_downstream_state_t
|                         | +--ro expiry-timer?     uint32
|                         | +--ro prune-pending-timer?  uint32
|                         | +--ro assert-state?      ipi-pim-ipv6-types:pim_ipv6_multicast_route_downstream_assert_state_t
|                         | +--ro assert-timer?     uint32
|                         | +--ro winner-address?    inet:ipv6-address
|                         | +--ro metric?           uint32
|                         | +--ro preference?       uint32
|                         | +--ro rpt-bit?         empty
|                         | +--ro macro-state?      ipi-pim-ipv6-types:pim_ipv6_multicast_route_downstream_macro_state_t
|                 +--ro downstream-xxrp-sg-rpt
|                     +--ro state
|                         +--ro route-state?      ipi-pim-ipv6-types:pim_ipv6_multicast_route_downstream_state_t
|                         +--ro rpt-state?       ipi-pim-ipv6-types:pim_ipv6_multicast_route_downstream_rpt_state_t
|                         +--ro expiry-timer?    uint32
|                         +--ro prune-pending-timer?  uint32

```

+--rw interfaces

```

+--rw interface* [name]
    +--rw name      -> ../config/name
    +--rw config
        | +--rw name?          -> /ipi-interface:interfaces/interface/name
        | +--rw pim-mode?     ipi-pim-ipv6-types:pim_ipv6_mode_t
        | +--rw bsr-border?   empty {feature-list:HAVE_PIM_SM}?
        | +--rw dr-priority?  uint32
        | +--rw hello-interval?  uint16
        | +--rw hello-holdtime?  uint16
        | +--rw passive-enable?  empty

```

---

```

| +--rw exclude-generated-id?          empty {feature-list:HAVE_PIM_SM}?
| +--rw unicast-bootstrap-router?      empty {feature-list:HAVE_PIM_SM}?
| +--rw neighbor-access-control-list-filter? string
| +--rw state-refresh-origination-interval? uint16 {feature-list:HAVE_PIM_DM}?
| +--rw ecmp-bundle?                   string {feature-list:HAVE_PIM_ECMP_REDIRECT}?
| +--rw propagation-delay?             uint16
| +--rw enable-bfd?                    cml-data-types:cml_enable_disable_t {feature-list:HAVE_BFD}?
+--ro state
| +--ro name?                          -> /ipi-interface:interfaces/interface/name
| +--ro pim-mode?                       ipi-pim-ipv6-types:pim_ipv6_mode_t
| +--ro bsr-border?                     empty {feature-list:HAVE_PIM_SM}?
| +--ro dr-priority?                    uint32
| +--ro hello-interval?                 uint16
| +--ro hello-holdtime?                 uint16
| +--ro passive-enable?                 empty
| +--ro exclude-generated-id?          empty {feature-list:HAVE_PIM_SM}?
| +--ro unicast-bootstrap-router?      empty {feature-list:HAVE_PIM_SM}?
| +--ro neighbor-access-control-list-filter? string
| +--ro state-refresh-origination-interval? uint16 {feature-list:HAVE_PIM_DM}?
| +--ro ecmp-bundle?                   string {feature-list:HAVE_PIM_ECMP_REDIRECT}?
| +--ro propagation-delay?             uint16
| +--ro enable-bfd?                    cml-data-types:cml_enable_disable_t {feature-list:HAVE_BFD}?
| +--ro next-hello?                    string
| +--ro router-id?                     inet:ipv4-address
| +--ro local-id?                       uint32
| +--ro dr-address?                     inet:ipv6-address
+--ro neighbors
  +--ro neighbor* [address]
    +--ro address -> ../state/address
    +--ro state
      +--ro address?                     inet:ipv6-address
      +--ro designated-router?          empty
      +--ro neighbor-established?       string
      +--ro neighbor-expires?          string
      +--ro secondary-address*          inet:ipv6-address
      +--ro hello-holdtime?             uint16

```

---

```

+--ro lan-delay?          uint16
+--ro override-interval? uint32
+--ro dr-priority?       uint32 {feature-list:HAVE_PIM_SM}?
+--ro generated-id?     uint32
+--ro router-id?        inet:ipv4-address
+--ro local-id?         uint32
+--ro tracking-support?  empty
+--ro ecmp-redirect-enabled? empty {feature-list:HAVE_PIM_ECMP_REDIRECT}?

```

rpcs:

```

+---x pim-snmpp-restart {feature-list:HAVE_SNMP}?
+---x pim-ipv4-clear-bsr-rendezvous-point {feature-list:HAVE_PIM_IPV4,feature-list:HAVE_PIM_SM}?
| +---w input
|   +---w vrf-name?  string
|   +---w pim-mode   ipi-pim-ipv4-types:pim_ipv4_mode_clear_bsr_rp_t
+---x pim-ipv4-clear-multicast-route {feature-list:HAVE_PIM_IPV4}?
| +---w input
|   +---w vrf-name?  string
|   +---w pim-mode   ipi-pim-ipv4-types:pim_ipv4_mode_t
+---x pim-ipv4-clear-multicast-route-source-group {feature-list:HAVE_PIM_IPV4}?
| +---w input
|   +---w vrf-name?  string
|   +---w group-address  inet:ipv4-address
+---x pim-ipv4-clear-multicast-route-source-group-mode {feature-list:HAVE_PIM_IPV4}?
| +---w input
|   +---w vrf-name?    string
|   +---w group-address  inet:ipv4-address
|   +---w source-address inet:ipv4-address
|   +---w pim-mode      ipi-pim-ipv4-types:pim_ipv4_mode_t
+---x pim-ipv4-clear-msdp-peer {feature-list:HAVE_PIM_IPV4,feature-list:HAVE_PIM_MSDP_API}?
| +---w input
|   +---w vrf-name?  string
|   +---w address    inet:ipv4-address
+---x pim-ipv4-clear-msdp-sa-cache {feature-list:HAVE_PIM_IPV4,feature-list:HAVE_PIM_MSDP_API}?
| +---w input
|   +---w vrf-name?  string

```

---

```
| +---w group-address  inet:ipv4-address
+---x pim-ipv4-terminal-debug-on {feature-list:HAVE_PIM_IPV4}?
| +---w input
|   +---w vrf-name?      string
|   +---w terminal-debug-options  ipi-pim-ipv4-types:pim_ipv4_debug_t
+---x pim-ipv4-terminal-debug-off {feature-list:HAVE_PIM_IPV4}?
| +---w input
|   +---w vrf-name?      string
|   +---w terminal-debug-options  ipi-pim-ipv4-types:pim_ipv4_debug_t
+---x pim-ipv4-terminal-debug-all-on {feature-list:HAVE_PIM_IPV4}?
| +---w input
|   +---w vrf-name?  string
+---x pim-ipv4-terminal-debug-all-off {feature-list:HAVE_PIM_IPV4}?
| +---w input
|   +---w vrf-name?  string
+---x pim-ipv6-clear-bsr-rendezvous-point {feature-list:HAVE_PIM_IPV6,feature-list:HAVE_PIM_SM}?
| +---w input
|   +---w vrf-name?  string
|   +---w pim-mode  ipi-pim-ipv6-types:pim_ipv6_mode_clear_bsr_rp_t
+---x pim-ipv6-clear-multicast-route {feature-list:HAVE_PIM_IPV6}?
| +---w input
|   +---w vrf-name?  string
|   +---w pim-mode  ipi-pim-ipv6-types:pim_ipv6_mode_t
+---x pim-ipv6-clear-multicast-route-source-group {feature-list:HAVE_PIM_IPV6}?
| +---w input
|   +---w vrf-name?  string
|   +---w group-address  inet:ipv6-address
+---x pim-ipv6-clear-multicast-route-source-group-mode {feature-list:HAVE_PIM_IPV6}?
| +---w input
|   +---w vrf-name?      string
|   +---w group-address  inet:ipv6-address
|   +---w source-address  inet:ipv6-address
|   +---w pim-mode      ipi-pim-ipv6-types:pim_ipv6_mode_t
+---x pim-terminal-debug-bfd-on {feature-list:HAVE_PIMD,feature-list:HAVE_PIM_IPV4,feature-
list:HAVE_PIM_IPV4_OR_HAVE_PIM_IPV6}?
+---x pim-terminal-debug-bfd-off {feature-list:HAVE_PIMD,feature-list:HAVE_PIM_IPV4,feature-
list:HAVE_PIM_IPV4_OR_HAVE_PIM_IPV6}?
```

---

```

+---x pim-ipv6-terminal-debug-on {feature-list:HAVE_PIM_IPV6}?
| +---w input
|   +---w vrf-name?          string
|   +---w terminal-debug-options  ipi-pim-ipv6-types:pim_ipv6_debug_t
+---x pim-ipv6-terminal-debug-off {feature-list:HAVE_PIM_IPV6}?
| +---w input
|   +---w vrf-name?          string
|   +---w terminal-debug-options  ipi-pim-ipv6-types:pim_ipv6_debug_t
+---x pim-ipv6-terminal-debug-all-on {feature-list:HAVE_PIM_IPV6}?
| +---w input
|   +---w vrf-name?  string
+---x pim-ipv6-terminal-debug-all-off {feature-list:HAVE_PIM_IPV6}?
  +---w input
    +---w vrf-name?  string

```

---

## module: ipi-ping

```

+--rw ping
  +--ro test-result* [test-name]
    +--ro test-name      -> ../state/test-name
    +--ro replies* [sequence-number]
      | +--ro sequence-number  -> ../state/sequence-number
      | +--ro state
      |   +--ro sequence-number?  uint32
      |   +--ro ttl-or-hop-limit?  uint8
      |   +--ro round-trip-time?  decimal64
      |   +--ro result?           ipi-ping-types:ping_packet_result_t
    +--ro state
      | +--ro test-name?  string
      | +--ro test-status? ipi-ping-types:ping_test_status_t
      | +--ro start-time?  yang:date-and-time
      | +--ro end-time?   yang:date-and-time
    +--ro test-parameters
      | +--ro state
      |   +--ro destination?  string

```

---

```
|  +--ro protocol?    ipi-ping-types:ping_ip_protocol_t
|  +--ro vrf-name?    string
|  +--ro repeat-count? uint32
|  +--ro interval?    uint16
|  +--ro time-to-live? uint8
|  +--ro datagram-size? uint32
|  +--ro timeout?     uint32
|  +--ro deadline?    uint32
+--ro summary-info
  +--ro state
    +--ro packets-transmitted? uint32
    +--ro packets-received?    uint32
    +--ro success-rate?        uint8
    +--ro loss-rate?           uint8
    +--ro min-rtt?             decimal64
    +--ro rtt-avg?             decimal64
    +--ro max-rtt?             decimal64
```

rpcs:

```
+---x ping-start-test {feature-list:HAVE_HOSTPD}?
| +---w input
|   +---w test-name    string
|   +---w destination  string
|   +---w protocol     ipi-ping-types:ping_ip_protocol_t
|   +---w vrf-name?    string
|   +---w repeat-count? uint32
|   +---w interval?    uint16
|   +---w time-to-live? uint8
|   +---w datagram-size? uint32
|   +---w timeout?     uint32
|   +---w deadline?    uint32
+---x ping-stop {feature-list:HAVE_HOSTPD}?
  +---w input
    +---w test-name    string
```

notifications:

---

```
+---n ping-test-completed
  +--ro severity?   cml-data-types:cml_notif_severity_t
  +--ro eventClass? cml-data-types:cml_notif_class_t
  +--ro test-name?  string
  +--ro test-status? ipi-ping-types:ping_test_status_t
  +--ro destination? string
```

---

## module: ipi-platform-port

```
augment /ipi-platform:components/ipi-platform:component:
  +--ro port
```

---

## module: ipi-platform-transceiver-smart-sfp

```
+--rw smart-sfp
  +--rw interfaces
    | +--rw interface* [interface-name]
    |   +--rw interface-name  -> ../config/interface-name
    |   +--rw config
    |     | +--rw interface-name?    -> /ipi-interface:interfaces/interface/name
    |     | +--rw xcvr-loopback-remote?  cmm_xcvr_direction_t
    |     +--ro state
    |       +--ro interface-name?    -> /ipi-interface:interfaces/interface/name
    |       +--ro xcvr-loopback-remote?  cmm_xcvr_direction_t
  +--rw components
    +--ro component* [name]
      +--ro name  -> ../state/name
      +--ro state
        +--ro name?  string
```

rpcs:

```
+---x smart-sfp-xcvr-txdisable-duration {feature-list:HAVE_CMMD}?
  | +---w input
  |   +---w if-name          string
  |   +---w xcvr-tx-disable-duration  uint16
+---x smart-sfp-xcvr-reset-remote {feature-list:HAVE_CMMD}?
  +---w input
    +---w if-name  string
```

---

## module: ipi-platform

```

+--rw components
| +--ro component* [name]
| | +--ro name          -> ../state/name
| | +--ro state
| | | +--ro name?      string
| | | +--ro type?     ipi-platform-types:cmm_component_type_t {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro location?  string {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro mfg-name?  string {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro mfg-date?  yang:date-and-time {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro description? string {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro hardware-version? string {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro firmware-version? string {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro software-version? string {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro serial-no? string {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro part-no?   string {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro removable? boolean {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro oper-status? ipi-platform-types:cmm_component_oper_status_t {feature-
list:NOT_HAVE_TIBIT}?
| | | +--ro product-name? string {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro asset-tag?    string {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro component-additional-details* string {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro parent?      -> /components/component/state/name {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro empty?       boolean {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro memory {feature-list:NOT_HAVE_TIBIT}?
| | | | +--ro available? uint64
| | | | +--ro utilized?  uint64
| | | +--ro board-fru {feature-list:NOT_HAVE_TIBIT}?
| | | | +--ro board-name? string
| | | | +--ro board-serial-no? string
| | | | +--ro board-mfg-name? string
| | | | +--ro board-mfg-date? yang:date-and-time
| | | +--ro temperature
| | |   +--ro instant?    decimal64
| | |   +--ro min?       decimal64

```

---

```
| | | +--ro max?                decimal64
| | | +--ro avg?                decimal64
| | | +--ro interval?          uint32
| | | +--ro sensor-name?       string
| | | +--ro sensor-index?      uint8
| | | +--ro alarm-status?      boolean
| | | +--ro alarm-threshold?   decimal64
| | | +--ro alarm-severity?    cml_alarm_severity_t
| | | +--ro minimum-emergency-temperature? decimal64
| | | +--ro maximum-emergency-temperature? decimal64
| | | +--ro minimum-alert-temperature? decimal64
| | | +--ro maximum-alert-temperature? decimal64
| | | +--ro minimum-critical-temperature? decimal64
| | | +--ro maximum-critical-temperature? decimal64
| | +--ro bmc-sensor-data-record {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro state
| | | +--ro sensor-name?       string
| | | +--ro value?             ipi-platform-types:cmm_bmc_value_t
| | | +--ro units?             string
| | | +--ro lower-non-recoverable? decimal64
| | | +--ro lower-non-critical? decimal64
| | | +--ro lower-critical?    decimal64
| | | +--ro upper-non-critical? decimal64
| | | +--ro upper-critical?    decimal64
| | | +--ro upper-non-recoverable? decimal64
| | | +--ro operational-status? string
| | | +--ro threshold?        decimal64
| | | +--ro event-type?       ipi-platform-types:cmm_bmc_event_type_t
| | +--ro subcomponents
| | | +--ro subcomponent* [subcomponent-name]
| | | +--ro subcomponent-name  -> ../state/subcomponent-name
| | | +--ro state
| | | +--ro subcomponent-name? -> /components/component/state/name
| | +--ro cpu
| | | +--ro state
| | | +--ro processor-count?   uint32
```

---

---

```
| | | +--ro cpu-1min-load-percentage?  decimal64
| | | +--ro cpu-5min-load-percentage?  decimal64
| | | +--ro cpu-15min-load-percentage?  decimal64
| | | +--ro cpu-1min-alert-threshold?   uint8
| | | +--ro cpu-1min-critical-threshold? uint8
| | | +--ro cpu-5min-alert-threshold?   uint8
| | | +--ro cpu-15min-alert-threshold?  uint8
| | | +--ro cpu-utilization?            decimal64
| | | +--ro cpu-utilization-alert?      uint8
| | | +--ro cpu-utilization-critical?   uint8
| | +--ro storage
| | | +--ro state
| | | | +--ro serial-number?            string
| | | | +--ro model-number?            string
| | | | +--ro firmware-revision?       string
| | | | +--ro cylinder-count?          uint16
| | | | +--ro head-count?              uint16
| | | | +--ro sector-count?            uint32
| | | | +--ro unformatted-bytes-or-track?  uint16
| | | | +--ro unformatted-bytes-or-sector?  uint16
| | | | +--ro revision-number?         string
| | | | +--ro total-memory?            uint64
| | | | +--ro used-memory?             uint64
| | | | +--ro free-memory?             uint64
| | | | +--ro usage-critical-threshold?  int32
| | | | +--ro usage-alert-threshold?    int32
| | | | +--ro remaining-life?          int32
| | | | +--ro remain-life-critical-threshold? int32
| | | | +--ro remain-life-alert-threshold? int32
| | | | +--ro available-reserved-space?  int32
| | | | +--ro available-reserved-space-critical-threshold? int32
| | | | +--ro available-reserved-space-alert-threshold? int32
| | | | +--ro reallocated-sector-count?  int32
| | | | +--ro uncorrectable-sector-count? int32
| | | | +--ro manufacturer-id?         string
| | | | +--ro manufacture-date?       string
```

---

---

```
| | | +--ro device-type?          string
| | | +--ro cache-size?          uint64
| | | +--ro storage-status?      ipi-platform-types:cml_cmm_storage_status_t
| | +--ro hddisk-monitoring
| | | +--ro state
| | |   +--ro interval?          int32
| | |   +--ro read-average?      int32
| | |   +--ro write-average?     int32
| | |   +--ro read-current?      int32
| | |   +--ro write-current?     int32
| | |   +--ro read-threshold?    int32
| | |   +--ro write-threshold?   int32
| | +--ro mounted-fileSystems
| |   +--ro mounted-filesystem* [mount-point]
| |   +--ro mount-point -> ../state/mount-point
| |   +--ro state
| |     +--ro mount-point?      string
| |     +--ro total?            uint64
| |     +--ro used?              uint64
| |     +--ro free?              uint64
| |     +--ro usage?             uint8
| | +--ro ram
| | | +--ro state
| | |   +--ro total-memory?      uint64
| | |   +--ro used-memory?       uint64
| | |   +--ro available-memory?  uint64
| | |   +--ro shared-memory?     uint64
| | |   +--ro buffers?           uint64
| | |   +--ro total-swap?        uint64
| | |   +--ro free-swap?         uint64
| | |   +--ro current-process-count? uint16
| | |   +--ro total-high-memory? uint64
| | |   +--ro available-high-memory? uint64
| | |   +--ro unit-size?         uint32
| | |   +--ro usage-critical-threshold? uint32
| | |   +--ro usage-alert-threshold? uint32
```

---

---

```

| | +--ro transceiver {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro state
| | | | +--ro port-no?                uint8
| | | | +--ro presence?              ipi-platform-transceiver-types:ddm_cmm_trans_presence_t
| | | | +--ro type?                  ipi-platform-transceiver-types:ddm_cmm_trans_type_t
| | | | +--ro channel-count?         int32
| | | | +--ro transceiver-identifier? ipi-platform-transceiver-types:ddm_cmm_trans_identifier_t
| | | | +--ro connector-type?        ipi-platform-transceiver-types:ddm_cmm_trans_connector_type_t
| | | | +--ro ethernet-compliance-code? ipi-platform-transceiver-types:ddm_cmm_trans_eth_compliance_t
| | | | +--ro extended-ethernet-compliance-code? ipi-platform-transceiver-
types:ddm_cmm_trans_ext_eth_compliance_t
| | | | +--ro sonet-compliance-code?  ipi-platform-transceiver-types:ddm_cmm_trans_sonet_compliance_t
| | | | +--ro fiber-channel-link-length? ipi-platform-transceiver-
types:ddm_cmm_trans_fiber_channel_linklen_t
| | | | +--ro fiber-channel-transmission-technology? ipi-platform-transceiver-
types:ddm_cmm_trans_fiber_channel_transmittech_t
| | | | +--ro fiber-channel-transmission-media?      ipi-platform-transceiver-
types:ddm_cmm_trans_fiber_channel_transmitmedia_t
| | | | +--ro serial-encoding-algorithm?            ipi-platform-transceiver-types:ddm_cmm_trans_encoding_t
| | | | +--ro link-length-kilometer?                int32
| | | | +--ro link-length-meter?                   int32
| | | | +--ro om1-link-length?                      int32
| | | | +--ro om2-link-length?                      int32
| | | | +--ro om3-link-length?                      int32
| | | | +--ro om4-link-length?                      int32
| | | | +--ro vendor-name?                          string
| | | | +--ro vendor-ieee-id?                       string
| | | | +--ro vendor-part-number?                   string
| | | | +--ro vendor-revision-number?               string
| | | | +--ro check-code?                           string
| | | | +--ro extended-check-code?                  string
| | | | +--ro nominal-signalling-rate?              int32
| | | | +--ro maximum-signalling-rate?              int32
| | | | +--ro minimum-signalling-rate?              int32
| | | | +--ro vendor-serial-number?                 string
| | | | +--ro vendor-manufacturing-date?            string
| | | | +--ro ddm-type?                             ipi-platform-transceiver-types:ddm_cmm_trans_ddm_support_t
| | | | +--ro maximum-case-temperature?             decimal64

```

---

---

```

| | | +--ro grid-spacing?                decimal64
| | | +--ro first-frequency?            decimal64
| | | +--ro last-frequency?            decimal64
| | | +--ro frequency-error?           decimal64
| | | +--ro frequency-error-critical-min-threshold? decimal64
| | | +--ro frequency-error-critical-max-threshold? decimal64
| | | +--ro frequency-error-alert-min-threshold? decimal64
| | | +--ro frequency-error-alert-max-threshold? decimal64
| | | +--ro wavelength-error?          decimal64
| | | +--ro wavelength-error-critical-min-threshold? decimal64
| | | +--ro wavelength-error-critical-max-threshold? decimal64
| | | +--ro wavelength-error-alert-min-threshold? decimal64
| | | +--ro wavelength-error-alert-max-threshold? decimal64
| | | +--ro tx-tune-ready?              boolean
| | | +--ro thermoelectric-cooler-fault? boolean
| | | +--ro wavelength-locked?          boolean
| | | +--ro transceiver-temperature?    decimal64
| | | +--ro temperature-alert-max-threshold? decimal64
| | | +--ro temperature-critical-max-threshold? decimal64
| | | +--ro temperature-critical-min-threshold? decimal64
| | | +--ro temperature-alert-min-threshold? decimal64
| | | +--ro transceiver-voltage?        decimal64
| | | +--ro voltage-alert-max-threshold? decimal64
| | | +--ro voltage-critical-max-threshold? decimal64
| | | +--ro voltage-critical-min-threshold? decimal64
| | | +--ro voltage-alert-min-threshold? decimal64
| | | +--ro module-functional-type?     ipi-platform-transceiver-types:cmm_transceiver_functional_type_t
| | +--ro sfp
| | | +--ro state
| | | | +--ro transmit-status?          ipi-platform-transceiver-types:ddm_tx_rx_state_t
| | | | +--ro receive-loss-status?      ipi-platform-transceiver-types:ddm_tx_rx_state_t
| | | | +--ro sfp-identifier?           ipi-platform-transceiver-types:ddm_cmm_trans_sfp_extended_identifier_t
| | | | +--ro sfp-options-implemented? ipi-platform-transceiver-
types:ddm_cmm_trans_sfp_options_implemented_t
| | | | +--ro fiber-channel-sfp-speed?  ipi-platform-transceiver-types:ddm_cmm_trans_fiber_channel_speed_t
| | | | +--ro sfp-infiniband-compliance-code? ipi-platform-transceiver-
types:ddm_cmm_trans_sfp_infiniband_compliance_t

```

---

---

```

| | | | +--ro sfp-escon-compliance-code?      ipi-platform-transceiver-
types:ddm_cmm_trans_sfp_escon_compliance_t
| | | | +--ro sfp-plus-cable-technology?      ipi-platform-transceiver-types:ddm_cmm_trans_sfp_plus_cable_tech_t
| | | +--ro xfp
| | | | +--ro state
| | | | +--ro transmit-status?                  ipi-platform-transceiver-types:ddm_tx_rx_state_t
| | | | +--ro recieve-loss-status?              ipi-platform-transceiver-types:ddm_tx_rx_state_t
| | | | +--ro xsfp-identifier?                  ipi-platform-transceiver-
types:ddm_cmm_trans_xfp_extended_identifier_t
| | | | +--ro xfp-10g-ethernet-compliance-code? ipi-platform-transceiver-
types:ddm_cmm_trans_xfp_10g_eth_compliance_t
| | | | +--ro xfp-10g-fiber-channel-compliance-code? ipi-platform-transceiver-
types:ddm_cmm_trans_xfp_10g_fiber_chn_compliance_t
| | | | +--ro xfp-10g-copper-link-compliance-code? ipi-platform-transceiver-
types:ddm_cmm_trans_xfp_10g_copper_links_rsvd_t
| | | | +--ro xfp-lower-speed-link-compliance-code? ipi-platform-transceiver-
types:ddm_cmm_trans_xfp_lower_speed_links_t
| | | | +--ro xfp-sonet-interconnect-compliance-code? ipi-platform-transceiver-
types:ddm_cmm_trans_xfp_sonet_interconnect_t
| | | | +--ro xfp-sonet-short-haul-compliance-code? ipi-platform-transceiver-
types:ddm_cmm_trans_xfp_sonet_short_haul_t
| | | | +--ro xfp-sonet-long-haul-compliance-code? ipi-platform-transceiver-
types:ddm_cmm_trans_xfp_sonet_long_haul_t
| | | | +--ro xfp-sonet-very-long-haul-compliance-code? ipi-platform-transceiver-
types:ddm_cmm_trans_xfp_sonet_very_long_haul_t
| | | | +--ro xfp-serial-encoding-algorithm?      ipi-platform-transceiver-types:ddm_cmm_trans_xfp_encoding_t
| | | | +--ro xsfp-options-implemented?          ipi-platform-transceiver-
types:ddm_cmm_trans_xfp_options_implemented_t
| | | | +--ro xfp-auxillary-voltage?              ipi-platform-transceiver-
types:ddm_cmm_trans_xfp_voltage_aux_monitor_t
| | | +--ro qsfp
| | | | +--ro state
| | | | +--ro reset-status?                      ipi-platform-transceiver-types:ddm_cmm_trans_reset_t
| | | | +--ro power?                            ipi-platform-transceiver-types:ddm_cmm_trans_power_t
| | | | +--ro lane1-transmission?                ipi-platform-transceiver-types:ddm_tx_rx_state_t
| | | | +--ro lane1-transmission-loss?          ipi-platform-transceiver-types:ddm_tx_rx_state_t
| | | | +--ro lane1-recieve-loss?                ipi-platform-transceiver-types:ddm_tx_rx_state_t
| | | | +--ro lane2-transmission?                ipi-platform-transceiver-types:ddm_tx_rx_state_t
| | | | +--ro lane2-transmission-loss?          ipi-platform-transceiver-types:ddm_tx_rx_state_t
| | | | +--ro lane2-recieve-loss?                ipi-platform-transceiver-types:ddm_tx_rx_state_t

```

---

```

| | | +--ro lane3-transmission?      ipi-platform-transceiver-types:ddm_tx_rx_state_t
| | | +--ro lane3-transmission-loss? ipi-platform-transceiver-types:ddm_tx_rx_state_t
| | | +--ro lane3-recieve-loss?      ipi-platform-transceiver-types:ddm_tx_rx_state_t
| | | +--ro lane4-transmission?      ipi-platform-transceiver-types:ddm_tx_rx_state_t
| | | +--ro lane4-transmission-loss? ipi-platform-transceiver-types:ddm_tx_rx_state_t
| | | +--ro lane4-recieve-loss?      ipi-platform-transceiver-types:ddm_tx_rx_state_t
| | | +--ro qsfp-identifier?         ipi-platform-transceiver-types:ddm_cmm_qsfp_extended_identifier_t
| | | +--ro fiber-channel-qsfp-speed? ipi-platform-transceiver-types:ddm_cmm_trans_fiber_channel_speed_t
| | | +--ro qsfp-options-implemented? ipi-platform-transceiver-
types:ddm_cmm_trans_qsfp_options_implemented_t
| | +--ro channels
| | | +--ro channel* [index]
| | | +--ro index  -> ../state/index
| | | +--ro state
| | |   +--ro index?                  uint8
| | |   +--ro input-power?            decimal64
| | |   +--ro input-power-alert-max-threshold?    decimal64
| | |   +--ro input-power-critical-max-threshold? decimal64
| | |   +--ro input-power-critical-min-threshold? decimal64
| | |   +--ro input-power-alert-min-threshold?    decimal64
| | |   +--ro output-power?           decimal64
| | |   +--ro output-power-alert-max-threshold?   decimal64
| | |   +--ro output-power-critical-max-threshold? decimal64
| | |   +--ro output-power-critical-min-threshold? decimal64
| | |   +--ro output-power-alert-min-threshold?   decimal64
| | |   +--ro laser-bias-current?      decimal64
| | |   +--ro laser-bias-current-alert-max-threshold? decimal64
| | |   +--ro laser-bias-current-critical-max-threshold? decimal64
| | |   +--ro laser-bias-current-critical-min-threshold? decimal64
| | |   +--ro laser-bias-current-alert-min-threshold? decimal64
| | +--ro cmis-module
| | | +--ro eeprom
| | | | +--ro state
| | | | | +--ro identifier?           ipi-platform-sff8024-types:cmm_sff8024_identifier_t
| | | | | +--ro vendor-name?         string
| | | | | +--ro vendor-oui?         string
| | | | | +--ro part-number?        string

```

---

```

| | | | +--ro revision-level?      string
| | | | +--ro serial-number?       string
| | | | +--ro manufacturing-date?   string
| | | | +--ro clei-code?           string
| | | | +--ro module-power-class?   ipi-platform-cmis-types:cmm_cmis_module_power_class_t
| | | | +--ro module-max-power?     decimal64
| | | | +--ro cooling-implemented?   ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | +--ro temperature-max?     int16
| | | | +--ro temperature-min?     int16
| | | | +--ro operatin-voltage-min? decimal64
| | | | +--ro optical-detector?     ipi-platform-cmis-types:cmm_cmis_optical_detector_t
| | | | +--ro rx-power-measurement?  ipi-platform-cmis-types:cmm_cmis_rx_power_measur_t
| | | | +--ro tx-disable-module-wide? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | +--ro cable-assembly-link-length? int16
| | | | +--ro connector-type?       ipi-platform-sff8024-types:cmm_sff8024_connector_type_t
| | | | +--ro cca-5ghz?            uint8
| | | | +--ro cca-7ghz?            uint8
| | | | +--ro cca-12p9ghz?         uint8
| | | | +--ro cca-25p8ghz?         uint8
| | | | +--ro media-interface-technology? ipi-platform-cmis-types:cmm_cmis_media_intf_tech_t
| | | | +--ro cmis-revision?        string
| | | | +--ro memory-model?         ipi-platform-cmis-types:cmm_cmis_memory_model_t
| | | | +--ro mci-max-speed?        ipi-platform-cmis-types:cmm_cmis_mci_max_speed_t
| | | | +--ro active-firmware-revision? string
| | | | +--ro inactive-firmware-revision? string
| | | | +--ro hardware-revision?    string
| | | | +--ro media-type?           ipi-platform-cmis-types:cmm_cmis_media_type_t
| | | | +--ro max-smf-link-length?   decimal64
| | | | +--ro max-mmf-om2-link-length? uint8
| | | | +--ro max-mmf-om3-link-length? uint16
| | | | +--ro max-mmf-om4-link-length? uint16
| | | | +--ro max-mmf-om5-link-length? uint16
| | | | +--ro wavelength-nominal?   decimal64
| | | | +--ro wavelength-tolerance? decimal64
| | | | +--ro advertisement
| | | | +--ro applications

```

---

```

| | | | | +--ro application* [id]
| | | | |   +--ro id    -> ../state/id
| | | | |   +--ro state
| | | | | | +--ro id?  uint8
| | | | |   +--ro host
| | | | | | +--ro state
| | | | | |   +--ro interface-type?    ipi-platform-cmis-types:cmm_cmis_interface_type_t
| | | | | |   +--ro application-bitrate? ipi-platform-cmis-types:cmm_cmis_bit_rate_t
| | | | | |   +--ro lane-count?        uint8
| | | | | |   +--ro signal-bitrate?    ipi-platform-cmis-types:cmm_cmis_bit_rate_t
| | | | | |   +--ro modulation-format? ipi-platform-cmis-types:cmm_cmis_modulation_format_t
| | | | | |   +--ro bits-per-unit-interval? decimal64
| | | | | |   +--ro lane-assignment?    ipi-platform-cmis-types:cmm_cmis_lane_assignment_t
| | | | | |   +--ro host-config?        string
| | | | |   +--ro media
| | | | |     +--ro state
| | | | |     +--ro interface-type?    ipi-platform-cmis-types:cmm_cmis_interface_type_t
| | | | |     +--ro application-bitrate? ipi-platform-cmis-types:cmm_cmis_bit_rate_t
| | | | |     +--ro lane-count?        uint8
| | | | |     +--ro signal-bitrate?    ipi-platform-cmis-types:cmm_cmis_bit_rate_t
| | | | |     +--ro modulation-format? ipi-platform-cmis-types:cmm_cmis_modulation_format_t
| | | | |     +--ro bits-per-unit-interval? decimal64
| | | | |     +--ro lane-assignment?    ipi-platform-cmis-types:cmm_cmis_lane_assignment_t
| | | | | +--ro custom-application
| | | | |   +--ro state
| | | | | | +--ro application-selector?  uint8
| | | | | | +--ro host-ids
| | | | | | +--ro host-id* [id]
| | | | | |   +--ro id    -> ../state/id
| | | | | |   +--ro state
| | | | | |     +--ro id?        uint8
| | | | | |     +--ro interface-type?    ipi-platform-cmis-types:cmm_cmis_interface_type_t
| | | | | |     +--ro application-bitrate? ipi-platform-cmis-types:cmm_cmis_bit_rate_t
| | | | | |     +--ro lane-count?        uint8
| | | | | |     +--ro signal-bitrate?    ipi-platform-cmis-types:cmm_cmis_bit_rate_t
| | | | | |     +--ro modulation-format? ipi-platform-cmis-types:cmm_cmis_modulation_format_t

```

---

```

| | | | | | +--ro bits-per-unit-interval? decimal64
| | | | | | +--ro lane-assignment?      ipi-platform-cmis-types:cmm_cmis_lane_assignment_t
| | | | | | +--ro host-config?          string
| | | | | | +--ro media-ids
| | | | | | +--ro media-id* [id]
| | | | | | +--ro id      -> ../state/id
| | | | | | +--ro state
| | | | | | +--ro id?          uint8
| | | | | | +--ro interface-type?      ipi-platform-cmis-types:cmm_cmis_interface_type_t
| | | | | | +--ro application-bitrate?  ipi-platform-cmis-types:cmm_cmis_bit_rate_t
| | | | | | +--ro lane-count?          uint8
| | | | | | +--ro signal-bitrate?      ipi-platform-cmis-types:cmm_cmis_bit_rate_t
| | | | | | +--ro modulation-format?   ipi-platform-cmis-types:cmm_cmis_modulation_format_t
| | | | | | +--ro bits-per-unit-interval? decimal64
| | | | | | +--ro lane-assignment?      ipi-platform-cmis-types:cmm_cmis_lane_assignment_t
| | | | | +--ro controls
| | | | | | +--ro state
| | | | | | +--ro wavelength-control?    ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +--ro tunable-transmitter?    ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +--ro tx-output-squelching-method? ipi-platform-cmis-types:cmm_cmis_tx_squelch_method_t
| | | | | | +--ro forced-tx-output-squelching? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +--ro tx-output-squelching-disable? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +--ro tx-output-disable?      ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +--ro input-polarity-flip-tx? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +--ro rx-output-squelching-disable? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +--ro rx-output-disable?      ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +--ro output-polarity-flip-rx? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | +--ro diagnostics
| | | | | | +--ro module
| | | | | | | +--ro state
| | | | | | | +--ro simultaneous-host-and-media-loopback? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | | +--ro report-bit-error-ratio?          ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | | +--ro count-bits-and-errors?          ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +--ro host
| | | | | | | +--ro state
| | | | | | | +--ro output-loopback?          ipi-platform-cmis-types:cmm_cmis_yes_no_t

```

---

---

```

| | | | | | +-ro input-loopack?      ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +-ro per-lane-loopack?    ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +-ro report-input-snr?   ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +-ro report-fec?        ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +-ro prbs-checker-post-fec? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +-ro prbs-checker-pre-fec? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +-ro prbs-checker-types?  ipi-platform-cmis-types:cmm_cmis_prbs_support_type_t
| | | | | | +-ro prbs-generator-post-fec? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +-ro prbs-generator-pre-fec? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +-ro prbs-generator-types? ipi-platform-cmis-types:cmm_cmis_prbs_support_type_t
| | | | | +-ro media
| | | | | +-ro state
| | | | | +-ro output-loopack?      ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | +-ro input-loopack?      ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | +-ro per-lane-loopack?    ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | +-ro report-input-snr?   ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | +-ro report-fec?        ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | +-ro prbs-checker-post-fec? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | +-ro prbs-checker-pre-fec? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | +-ro prbs-checker-types?  ipi-platform-cmis-types:cmm_cmis_prbs_support_type_t
| | | | | +-ro prbs-generator-post-fec? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | +-ro prbs-generator-pre-fec? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | +-ro prbs-generator-types? ipi-platform-cmis-types:cmm_cmis_prbs_support_type_t
| | | | +-ro durations
| | | | | +-ro state
| | | | | +-ro modsel-wait-time?     uint32
| | | | | +-ro dpinit-maximun-duration? ipi-platform-cmis-types:cmm_cmis_durations_t
| | | | | +-ro dpdeinit-maximun-duration? ipi-platform-cmis-types:cmm_cmis_durations_t
| | | | | +-ro dptxturnon-maximum-duration? ipi-platform-cmis-types:cmm_cmis_durations_t
| | | | | +-ro dptxturnoff-maximum-duration? ipi-platform-cmis-types:cmm_cmis_durations_t
| | | | | +-ro modulepwrup-maximum-duration? ipi-platform-cmis-types:cmm_cmis_durations_t
| | | | | +-ro modulepwrdown-maximum-duration? ipi-platform-cmis-types:cmm_cmis_durations_t
| | | | | +-ro npinit-maximum-duration? ipi-platform-cmis-types:cmm_cmis_durations_t
| | | | | +-ro npdeinit-maximum-duration? ipi-platform-cmis-types:cmm_cmis_durations_t
| | | | | +-ro nptxturnon-maximum-duration? ipi-platform-cmis-types:cmm_cmis_durations_t
| | | | | +-ro nptxturnoff-maximum-duration? ipi-platform-cmis-types:cmm_cmis_durations_t

```

---

```

| | | | | +--ro laser
| | | | | +--ro state
| | | | | | +--ro supported-grids?          ipi-platform-cmis-types:cmm_cmis_laser_grid_support_t
| | | | | | +--ro fine-tune-supported?      ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +--ro fine-tune-resolution?    decimal64
| | | | | | +--ro fine-tune-low-offset?    decimal64
| | | | | | +--ro fine-tune-high-offset?   decimal64
| | | | | | +--ro per-lane-programmable-output-power? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +--ro minimum-programmable-output-power? decimal64
| | | | | | +--ro maximum-programmable-output-power? decimal64
| | | | | | +--ro grids
| | | | | |   +--ro grid* [id]
| | | | | |   +--ro id    -> ../state/id
| | | | | |   +--ro state
| | | | | |   +--ro id?      ipi-platform-cmis-types:cmm_cmis_laser_grid_spacing_t
| | | | | |   +--ro lowest-channel-frequency? decimal64
| | | | | |   +--ro highest-channel-frequency? decimal64
| | | | | |   +--ro channel-count?          uint16
| | | | | +--ro monitoring
| | | | | +--ro module
| | | | | | +--ro monitors
| | | | | |   +--ro monitor* [id]
| | | | | |   +--ro id    -> ../state/id
| | | | | |   +--ro state
| | | | | |   +--ro id?      ipi-platform-cmis-types:cmm_cmis_module_monitor_id_t
| | | | | |   +--ro supported? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | +--ro host
| | | | | | +--ro monitors
| | | | | | | +--ro monitor* [id]
| | | | | | | +--ro id    -> ../state/id
| | | | | | | +--ro state
| | | | | | |   +--ro id?      ipi-platform-cmis-types:cmm_cmis_host_monitor_id_t
| | | | | | |   +--ro supported? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | |   +--ro lanes-assigned? ipi-platform-cmis-types:cmm_cmis_lane_assignment_t
| | | | | | +--ro flags
| | | | | |   +--ro flag* [id]

```

```

| | | | | +--ro id -> ../state/id
| | | | | +--ro state
| | | | | +--ro id? ipi-platform-cmis-types:cmm_cmis_host_flag_id_t
| | | | | +--ro supported? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | +--ro lanes-assigned? ipi-platform-cmis-types:cmm_cmis_lane_assignment_t
| | | | | +--ro media
| | | | | +--ro monitors
| | | | | | +--ro monitor* [id]
| | | | | | +--ro id -> ../state/id
| | | | | | +--ro state
| | | | | | +--ro id? ipi-platform-cmis-types:cmm_cmis_media_monitor_id_t
| | | | | | +--ro supported? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | | +--ro lanes-assigned? ipi-platform-cmis-types:cmm_cmis_lane_assignment_t
| | | | | +--ro flags
| | | | | +--ro flag* [id]
| | | | | +--ro id -> ../state/id
| | | | | +--ro state
| | | | | +--ro id? ipi-platform-cmis-types:cmm_cmis_media_flag_id_t
| | | | | +--ro supported? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | | +--ro lanes-assigned? ipi-platform-cmis-types:cmm_cmis_lane_assignment_t
| | | | +--ro pages
| | | | +--ro state
| | | | +--ro network-path-pages-supported? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | +--ro vdm-pages-supported? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | +--ro vdm-groups? ipi-platform-cmis-types:cmm_cmis_vdm_pages_support_t
| | | | +--ro diagnostics-pages-supported? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | +--ro user-page-supported? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | +--ro banks-per-page? ipi-platform-cmis-types:cmm_cmis_bank_per_page_support_t
| | | | +--ro signal-integrity
| | | | +--ro state
| | | | +--ro tx-input-manual-eq? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | +--ro tx-input-eq-max? uint8
| | | | +--ro rx-output-eq-pre-cursor? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | +--ro rx-output-eq-pre-cursor-max? uint8
| | | | +--ro rx-output-eq-post-cursor? ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | +--ro rx-output-eq-post-cursor-max? uint8

```

---

```

| | | | +--ro rx-output-amp?          ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | +--ro rx-output-amp-codes?    ipi-platform-cmis-types:cmm_cmis_si_amp_codes_t
| | | | +--ro tx-cdr?                  ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | +--ro tx-cdr-bypass?          ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | +--ro rx-cdr?                  ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | | +--ro rx-cdr-bypass?          ipi-platform-cmis-types:cmm_cmis_yes_no_t
| | | +--ro module-state
| | | | +--ro state
| | | | | +--ro fault-state?          ipi-platform-cmis-types:cmm_cmis_module_fault_state_t
| | | | | +--ro current-state?       ipi-platform-cmis-types:cmm_cmis_module_state_t
| | | | +--ro datapaths
| | | | | +--ro datapath* [lane]
| | | | | +--ro lane    -> ../state/lane
| | | | | +--ro state
| | | | | +--ro lane?          uint8
| | | | | +--ro current-state?  ipi-platform-cmis-types:cmm_cmis_datapath_states_t
| | | | | +--ro host-rate?      decimal64
| | | | | +--ro media-rate?     decimal64
| | | | | +--ro interface-name?  string
| | | +--ro module-monitors
| | | | +--ro monitors
| | | | | +--ro monitor* [id]
| | | | | | +--ro id    -> ../state/id
| | | | | | +--ro state
| | | | | | | +--ro id?          ipi-platform-cmis-types:cmm_cmis_module_monitor_id_t
| | | | | | | +--ro description?  string
| | | | | | | +--ro value?       decimal64
| | | | | | | +--ro high-alarm?   decimal64
| | | | | | | +--ro high-warning? decimal64
| | | | | | | +--ro low-warning?  decimal64
| | | | | | | +--ro low-alarm?   decimal64
| | | | | +--ro monitor-alarm
| | | | | +--ro state
| | | | | | +--ro alarm-id?        ipi-platform-cmis-types:cmm_cmis_module_monitor_id_t
| | | | | | +--ro alarm-type?      ipi-platform-cmis-types:cmm_cmis_threshold_alarm_t
| | | | | | +--ro current-value?   decimal64

```

---

```

| | | | +--ro threshold-minimum? decimal64
| | | | +--ro threshold-maximum? decimal64
| | | | +--ro host-monitors
| | | | +--ro lanes
| | | | +--ro lane* [number]
| | | | +--ro number -> ../state/number
| | | | +--ro state
| | | | | +--ro number? uint8
| | | | | +--ro dp-assigned? boolean
| | | | +--ro monitors
| | | | | +--ro monitor* [id]
| | | | | +--ro id -> ../state/id
| | | | | +--ro state
| | | | | +--ro id? ipi-platform-cmis-types:cmm_cmis_host_monitor_id_t
| | | | | +--ro description? string
| | | | | +--ro value? decimal64
| | | | | +--ro high-alarm? decimal64
| | | | | +--ro high-warning? decimal64
| | | | | +--ro low-warning? decimal64
| | | | | +--ro low-alarm? decimal64
| | | | +--ro flags
| | | | | +--ro flag* [id]
| | | | | +--ro id -> ../state/id
| | | | | +--ro state
| | | | | +--ro id? ipi-platform-cmis-types:cmm_cmis_host_flag_id_t
| | | | | +--ro description? string
| | | | | +--ro value? boolean
| | | | +--ro monitor-alarm
| | | | | +--ro state
| | | | | +--ro alarm-id? ipi-platform-cmis-types:cmm_cmis_host_monitor_id_t
| | | | | +--ro alarm-type? ipi-platform-cmis-types:cmm_cmis_threshold_alarm_t
| | | | | +--ro current-value? decimal64
| | | | | +--ro threshold-minimum? decimal64
| | | | | +--ro threshold-maximum? decimal64
| | | | +--ro flag-alarm
| | | | +--ro state

```

```
| | | |      +--ro alarm-id? ipi-platform-cmis-types:cmm_cmis_host_flag_id_t
| | | | +--ro media-monitors
| | | | | +--ro lanes
| | | | | +--ro lane* [number]
| | | | |   +--ro number      -> ../state/number
| | | | |   +--ro state
| | | | |   | +--ro number?  uint8
| | | | |   +--ro monitors
| | | | |   | +--ro monitor* [id]
| | | | |   |   +--ro id      -> ../state/id
| | | | |   |   +--ro state
| | | | |   |     +--ro id?      ipi-platform-cmis-types:cmm_cmis_media_monitor_id_t
| | | | |   |     +--ro description?  string
| | | | |   |     +--ro value?      decimal64
| | | | |   |     +--ro high-alarm?  decimal64
| | | | |   |     +--ro high-warning? decimal64
| | | | |   |     +--ro low-warning? decimal64
| | | | |   |     +--ro low-alarm?  decimal64
| | | | |   +--ro flags
| | | | |   | +--ro flag* [id]
| | | | |   |   +--ro id      -> ../state/id
| | | | |   |   +--ro state
| | | | |   |     +--ro id?      ipi-platform-cmis-types:cmm_cmis_media_flag_id_t
| | | | |   |     +--ro description? string
| | | | |   |     +--ro value?    boolean
| | | | |   +--ro monitor-alarm
| | | | |   | +--ro state
| | | | |   |   +--ro alarm-id?      ipi-platform-cmis-types:cmm_cmis_media_monitor_id_t
| | | | |   |   +--ro alarm-type?    ipi-platform-cmis-types:cmm_cmis_threshold_alarm_t
| | | | |   |   +--ro current-value? decimal64
| | | | |   |   +--ro threshold-minimum? decimal64
| | | | |   |   +--ro threshold-maximum? decimal64
| | | | |   +--ro flag-alarm
| | | | |   +--ro state
| | | | |     +--ro alarm-id? ipi-platform-cmis-types:cmm_cmis_media_flag_id_t
| | | | +--ro user-thresholds
```

---

```
| | | | +--ro host
| | | | | +--ro lanes
| | | | | | +--ro lane* [number]
| | | | | | | +--ro number    -> ../state/number
| | | | | | | +--ro state
| | | | | | | | +--ro number?  uint8
| | | | | | | | +--ro thresholds
| | | | | | | | | +--ro threshold* [id]
| | | | | | | | | +--ro id    -> ../state/id
| | | | | | | | | +--ro state
| | | | | | | | | | +--ro id?    ipi-platform-cmis-types:cmm_ccmis_thres_state_host_id_t
| | | | | | | | | | +--ro value?  decimal64
| | | | | | | | | | +--ro minimum? decimal64
| | | | | | | | | | +--ro maximum? decimal64
| | | | | | | | | | +--ro active?  boolean
| | | | | +--ro media
| | | | | | +--ro lanes
| | | | | | | +--ro lane* [number]
| | | | | | | | +--ro number    -> ../state/number
| | | | | | | | +--ro state
| | | | | | | | | +--ro number?  uint8
| | | | | | | | | +--ro thresholds
| | | | | | | | | | +--ro threshold* [id]
| | | | | | | | | | +--ro id    -> ../state/id
| | | | | | | | | | +--ro state
| | | | | | | | | | | +--ro id?    ipi-platform-cmis-types:cmm_ccmis_thres_state_media_id_t
| | | | | | | | | | | +--ro value?  decimal64
| | | | | | | | | | | +--ro minimum? decimal64
| | | | | | | | | | | +--ro maximum? decimal64
| | | | | | | | | | | +--ro active?  boolean
| | | | +--ro signal-integrity
| | | | | +--ro host
| | | | | | +--ro lanes
| | | | | | | +--ro lane* [number]
| | | | | | | | +--ro number    -> ../state/number
| | | | | | | | +--ro state
```

---

---

```

| | | | +--ro number?                uint8
| | | | +--ro tx-input-equalizer-target?  uint8
| | | | +--ro rx-output-equalizer-pre-cursor-target?  uint8
| | | | +--ro rx-output-equalizer-post-cursor-target?  uint8
| | | | +--ro rx-output-amplitude-target?    uint8
| | | | +--ro tx-cdr-bypass?                boolean
| | | | +--ro rx-cdr-bypass?                boolean
| | | +--ro laser-status
| | |   +--ro media
| | |     +--ro lanes
| | |       +--ro lane* [number]
| | |         +--ro number  -> ../state/number
| | |           +--ro state
| | |             +--ro number?    uint8
| | |             +--ro laser-frequency?  decimal64
| | |             +--ro wavelength?  decimal64
| | +--ro tibat-olt-micropug
| |   +--ro state
| |     +--ro interface-name?        -> /ipi-interface:interfaces/interface/name
| |     +--ro warranty-seal?         ipi-platform-transceiver-tibat-types:trans_tibat_cmm_warranty_seal_t
| |     +--ro operational-management? ipi-platform-transceiver-tibat-types:trans_tibat_cmm_oper_mode_t
| |     +--ro pon-mode?              ipi-platform-transceiver-tibat-types:trans_tibat_cmm_pon_mode_t
| |     +--ro active-firmware-bank-id?  uint8
| |     +--ro next-active-firmware-bank-id?  uint8
| |     +--ro management-vlan-tpid?    string
| |     +--ro management-vlan-id?     uint16
| |     +--ro pon-mac-address?        string
| |     +--ro ethernet-mac-address?   string
| |     +--ro pon-port-administrative-state? ipi-platform-transceiver-tibat-types:trans_tibat_cmm_pon_status_t
| |     +--ro pon-port-operational-status? ipi-platform-transceiver-tibat-types:trans_tibat_cmm_pon_status_t
| |     +--ro pon-link-count?         uint16
| |   +--ro firmware-banks
| |     +--ro bank* [bank-id]
| |       +--ro bank-id  -> ../state/bank-id
| |       +--ro state
| |         +--ro bank-id?    uint8

```

---

---

```
| | |   +--ro release-type?      string
| | |   +--ro major-version?   uint8
| | |   +--ro minor-version?   uint8
| | |   +--ro maintenance-version? uint8
| | |   +--ro suffix-build-tag?  ipi-platform-transceiver-tibit-types:trans_tibit_cmm_string_t
| | |   +--ro suffix-build-number? uint16
| | |   +--ro build-sha?        ipi-platform-transceiver-tibit-types:trans_tibit_cmm_string_t
| | |   +--ro application-type?  ipi-platform-transceiver-tibit-types:trans_tibit_cmm_application_type_t
| | |   +--ro created-timestamp? yang:date-and-time
| | |   +--ro updated-timestamp? yang:date-and-time
| | +--ro power-supply
| | | +--ro state
| | |   +--ro operational-status?    cml_cmm_power_supply_operstatus_t
| | |   +--ro hot-swap-state?        ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro capacity?              decimal64
| | |   +--ro power-consumption?     decimal64
| | |   +--ro input-power?           decimal64
| | |   +--ro input-voltage?         decimal64
| | |   +--ro output-voltage?        decimal64
| | |   +--ro input-current?         decimal64
| | |   +--ro output-current?        decimal64
| | |   +--ro temperature-sensor1?   decimal64
| | |   +--ro temperature-sensor2?   decimal64
| | |   +--ro temperature-sensor3?   decimal64
| | |   +--ro fan1-rpm?              uint32
| | |   +--ro fan2-rpm?              uint32
| | |   +--ro fan3-rpm?              uint32
| | |   +--ro fan4-rpm?              uint32
| | |   +--ro input-power-status?    ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro output-power-status?   ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro supported-parameters?  cml_cmm_psu_pmbus_param_support_t
| | |   +--ro vin-alert-threshold-min? decimal64
| | |   +--ro vin-alert-threshold-max? decimal64
| | |   +--ro vin-critical-threshold-min? decimal64
| | |   +--ro vin-critical-threshold-max? decimal64
| | |   +--ro vout-alert-threshold-min? decimal64
```

---

---

	+-ro vout-alert-threshold-max?	decimal64
	+-ro vout-critical-threshold-min?	decimal64
	+-ro vout-critical-threshold-max?	decimal64
	+-ro pout-alert-threshold-min?	decimal64
	+-ro pout-alert-threshold-max?	decimal64
	+-ro pout-critical-threshold-min?	decimal64
	+-ro pout-critical-threshold-max?	decimal64
	+-ro pin-alert-threshold-min?	decimal64
	+-ro pin-alert-threshold-max?	decimal64
	+-ro pin-critical-threshold-min?	decimal64
	+-ro pin-critical-threshold-max?	decimal64
	+-ro iin-alert-threshold-min?	decimal64
	+-ro iin-alert-threshold-max?	decimal64
	+-ro iin-critical-threshold-min?	decimal64
	+-ro iin-critical-threshold-max?	decimal64
	+-ro iout-alert-threshold-min?	decimal64
	+-ro iout-alert-threshold-max?	decimal64
	+-ro iout-critical-threshold-min?	decimal64
	+-ro iout-critical-threshold-max?	decimal64
	+-ro temp1-alert-threshold-min?	decimal64
	+-ro temp1-alert-threshold-max?	decimal64
	+-ro temp1-critical-threshold-min?	decimal64
	+-ro temp1-critical-threshold-max?	decimal64
	+-ro temp2-alert-threshold-min?	decimal64
	+-ro temp2-alert-threshold-max?	decimal64
	+-ro temp2-critical-threshold-min?	decimal64
	+-ro temp2-critical-threshold-max?	decimal64
	+-ro vin-hw-shut-max-threshold?	decimal64
	+-ro vin-hw-shut-min-threshold?	decimal64
	+-ro vin-hw-resume_max_threshold?	decimal64
	+-ro vin-hw-resume_min_threshold?	decimal64
	+-ro vout-hw-shut-max-threshold?	decimal64
	+-ro vout-hw-shut-min-threshold?	decimal64
	+-ro vout-hw-resume_max_threshold?	decimal64
	+-ro vout-hw-resume_min_threshold?	decimal64
	+-ro pin-hw-shut-max-threshold?	decimal64

---

```
| | | +--ro pin-hw-shut-min-threshold?   decimal64
| | | +--ro pin-hw-resume_max_threshold?  decimal64
| | | +--ro pin-hw-resume_min_threshold?  decimal64
| | | +--ro pout-hw-shut-max-threshold?   decimal64
| | | +--ro pout-hw-shut-min-threshold?   decimal64
| | | +--ro pout-hw-resume_max_threshold?  decimal64
| | | +--ro pout-hw-resume_min_threshold?  decimal64
| | | +--ro iin-hw-shut-max-threshold?    decimal64
| | | +--ro iin-hw-shut-min-threshold?    decimal64
| | | +--ro iin-hw-resume_max_threshold?   decimal64
| | | +--ro iin-hw-resume_min_threshold?   decimal64
| | | +--ro iout-hw-shut-max-threshold?   decimal64
| | | +--ro iout-hw-shut-min-threshold?   decimal64
| | | +--ro iout-hw-resume_max_threshold?  decimal64
| | | +--ro iout-hw-resume_min_threshold?  decimal64
| | | +--ro temp1-hw-shut-max-threshold?  decimal64
| | | +--ro temp1-hw-shut-min-threshold?  decimal64
| | | +--ro temp1-hw-resume_max_threshold? decimal64
| | | +--ro temp1-hw-resume_min_threshold? decimal64
| | | +--ro temp2-hw-shut-max-threshold?  decimal64
| | | +--ro temp2-hw-shut-min-threshold?  decimal64
| | | +--ro temp2-hw-resume_max_threshold? decimal64
| | | +--ro temp2-hw-resume_min_threshold? decimal64
| | | +--ro temp3-alert-threshold-min?    decimal64
| | | +--ro temp3-alert-threshold-max?    decimal64
| | | +--ro temp3-critical-threshold-min?  decimal64
| | | +--ro temp3-critical-threshold-max?  decimal64
| | | +--ro temp3-hw-shut-max-threshold?   decimal64
| | | +--ro temp3-hw-shut-min-threshold?   decimal64
| | | +--ro temp3-hw-resume_max_threshold? decimal64
| | | +--ro temp3-hw-resume_min_threshold? decimal64
| | +--ro fan
| | | +--ro state
| | | +--ro fan-index?   uint8
| | | +--ro rpm?        uint32
| | | +--ro minimum-rpm? uint32
```

---

```
| | | +--ro maximum-rpm?  uint32
| | | +--ro fan-status?  cml_cmm_fan_status_t
| | | +--ro fan-location? cml_cmm_fan_location_t
| | +--ro fan-tray
| | | +--ro state
| | | +--ro tray-number? uint8
| | | +--ro status?      cml_cmm_fan_tray_status_t
| | | +--ro led-color?   cml_cmm_led_color_code_t
| | | +--ro fan-count?   uint32
| | +--ro chassis
| | | +--ro state
| | | +--ro up-time?      yang:timeticks
| | | +--ro mac-address?  yang:mac-address
| | | +--ro label-revision? string
| | | +--ro country-code? string
| | | +--ro fan-tray-count? uint32
| | | +--ro power-supplies-count? uint32
| | | +--ro chassis-fast-ethernet-count? uint32
| | | +--ro chassis-1g-ethernet-count?  uint32
| | | +--ro chassis-10g-ethernet-count? uint32
| | | +--ro chassis-25g-ethernet-count? uint32
| | | +--ro chassis-40g-ethernet-count? uint32
| | | +--ro chassis-50g-ethernet-count? uint32
| | | +--ro chassis-100g-ethernet-count? uint32
| | | +--ro chassis-400g-ethernet-count? uint32
| | | +--ro service-tag?   string
| | | +--ro platform-name? string
| | | +--ro onie-version?  string
| | | +--ro vendor-name?   string
| | | +--ro diagnostic-version? string
| | | +--ro cyclic-redundancy-32bit-value? string
| | | +--ro switch-chip-revision? string
| | | +--ro fan-board-id?  string
| | | +--ro supported-label-revision? string
| | | +--ro supported-switch-chip-revision? string
| | | +--ro system_status? ipi-platform-types:platform_system_status_type_t
```

---

---

```
| | | +--ro cpu_status?          ipi-platform-types:platform_system_status_type_t
| | | +--ro ram_status?         ipi-platform-types:platform_system_status_type_t
| | | +--ro storage_status?     ipi-platform-types:platform_system_status_type_t
| | | +--ro temperature_status? ipi-platform-types:platform_system_status_type_t
| | | +--ro fan_status?         ipi-platform-types:platform_system_status_type_t
| | | +--ro psu_status?         ipi-platform-types:platform_system_status_type_t
| | | +--ro software_status?    ipi-platform-types:platform_system_status_type_t
| | +--ro linecard
| | | +--ro state
| | |   +--ro slot-id? string
| | +--ro power-rail
| | | +--ro state
| | |   +--ro power-vddr-status? ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro power-core-status? ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro v1p1-power-rail?   ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro main-board-power-rail? ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro vcc-5v-power-status? ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro vcc-3v-power-status? ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro vcc-1v-mac-power-status? ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro vcc-1v-mac-avs-power-status? ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro vccv1p05-power-status? ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro vccv1p5-power-status? ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro vccv1p8-power-status? ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro v1p05-power-rail?   ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro vcc-power-rail?     ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro sbv1p5-power-rail?  ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro v1p0-power-rail?    ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro v1p5-power-rail?    ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro v3p3-power-rail?    ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro v1p8-power-rail?    ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro v1p9-power-rail?    ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro v1p35-power-rail?   ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro vcc-avs-1v-power-status? ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro ddrvt-power-status? ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro vcc-mac-v1p25-power-status? ipi-platform-types:cml_cmm_power_rail_t
| | |   +--ro mac-v1p8-power-status? ipi-platform-types:cml_cmm_power_rail_t
```

---

---

```

| | | +--ro power-supply-1-power-status?      ipi-platform-types:cml_cmm_power_rail_t
| | | +--ro power-supply-2-power-status?      ipi-platform-types:cml_cmm_power_rail_t
| | | +--ro power-supply-1-power-rail?        ipi-platform-types:cml_cmm_power_rail_t
| | | +--ro power-supply-2-power-rail?        ipi-platform-types:cml_cmm_power_rail_t
| | | +--ro power-supply-1-v12-power-rail?    ipi-platform-types:cml_cmm_power_rail_t
| | | +--ro power-supply-2-v12-power-rail?    ipi-platform-types:cml_cmm_power_rail_t
| | | +--ro power-supply-1-ac-alert-power-rail? ipi-platform-types:cml_cmm_power_rail_t
| | | +--ro power-supply-2-ac-alert-power-rail? ipi-platform-types:cml_cmm_power_rail_t
| | | +--ro power-vccp-status?                ipi-platform-types:cml_cmm_power_rail_t
| | | +--ro v5a-power-rail?                   ipi-platform-types:cml_cmm_power_rail_t
| | | +--ro v3p3a-power-rail?                 ipi-platform-types:cml_cmm_power_rail_t
| | | +--ro hot-swap-1-power-rail?            ipi-platform-types:cml_cmm_power_rail_t
| | | +--ro hot-swap-2-power-rail?            ipi-platform-types:cml_cmm_power_rail_t
| | | +--ro xp0r-v75-power-rail?              ipi-platform-types:cml_cmm_power_rail_t
| | | +--ro xp1r-v07-cp-power-rail?          ipi-platform-types:cml_cmm_power_rail_t
| | +--ro edfas
| | | +--ro edfa* [port]
| | |   +--ro port      -> ../state/port
| | |   +--ro state
| | |     | +--ro port?  uint8
| | |     +--ro monitors
| | |       | +--ro monitor* [id]
| | |       |   +--ro id    -> ../state/id
| | |       |   +--ro state
| | |       |     +--ro id?      ipi-platform-transceiver-types:cmm_edfa_ddm_monitor_id_t
| | |       |     +--ro description?  string
| | |       |     +--ro value?    decimal64
| | |       |     +--ro high-alarm?  decimal64
| | |       |     +--ro high-warning? decimal64
| | |       |     +--ro low-warning? decimal64
| | |       |     +--ro low-alarm?  decimal64
| | |     +--ro monitor-alarm
| | |       +--ro state
| | |         +--ro alarm-id?      ipi-platform-transceiver-types:cmm_edfa_ddm_monitor_id_t
| | |         +--ro alarm-type?    ipi-platform-transceiver-types:cmm_ddm_threshold_alarm_t
| | |         +--ro current-value? decimal64

```

---

---

```

| | |      +--ro threshold-minimum?  decimal64
| | |      +--ro threshold-maximum?  decimal64
| | +--ro remote-sfps
| |   +--ro remote-sfp* [port]
| |     +--ro port      -> ../state/port
| |     +--ro state
| |       | +--ro port?  uint8
| |       +--ro eeprom
| |         | +--ro state
| |         |   +--ro identifier?          ipi-platform-transceiver-types:ddm_cmm_trans_identifier_t
| |         |   +--ro sfp-extended-identifier?          ipi-platform-transceiver-
types:ddm_cmm_trans_sfp_extended_identifier_t
| |         |   +--ro connector-type?          ipi-platform-transceiver-types:ddm_cmm_trans_connector_type_t
| |         |   +--ro ethernet-compliance-code?          ipi-platform-transceiver-
types:ddm_cmm_trans_eth_compliance_t
| |         |   +--ro extended-ethernet-compliance-code?  ipi-platform-transceiver-
types:ddm_cmm_trans_ext_eth_compliance_t
| |         |   +--ro sonet-compliance-code?          ipi-platform-transceiver-
types:ddm_cmm_trans_sonet_compliance_t
| |         |   +--ro fiber-channel-link-length?          ipi-platform-transceiver-
types:ddm_cmm_trans_fiber_channel_linklen_t
| |         |   +--ro fiber-channel-transmission-technology?  ipi-platform-transceiver-
types:ddm_cmm_trans_fiber_channel_transmittech_t
| |         |   +--ro fiber-channel-transmission-media?  ipi-platform-transceiver-
types:ddm_cmm_trans_fiber_channel_transmitmedia_t
| |         |   +--ro fiber-channel-sfp-speed?          ipi-platform-transceiver-
types:ddm_cmm_trans_fiber_channel_speed_t
| |         |   +--ro sfp-infiniband-compliance-code?  ipi-platform-transceiver-
types:ddm_cmm_trans_sfp_infiniband_compliance_t
| |         |   +--ro sfp-escon-compliance-code?          ipi-platform-transceiver-
types:ddm_cmm_trans_sfp_escon_compliance_t
| |         |   +--ro sfp-plus-cable-technology?          ipi-platform-transceiver-
types:ddm_cmm_trans_sfp_plus_cable_tech_t
| |         |   +--ro serial-encoding-algorithm?          ipi-platform-transceiver-types:ddm_cmm_trans_encoding_t
| |         |   +--ro link-length-kilometer?          int32
| |         |   +--ro link-length-meter?          int32
| |         |   +--ro om1-link-length?          int32
| |         |   +--ro om2-link-length?          int32
| |         |   +--ro om3-link-length?          int32
| |         |   +--ro om4-link-length?          int32

```

---

---

```

| | | +--ro vendor-name?          string
| | | +--ro vendor-ieee-id?       string
| | | +--ro vendor-part-number?   string
| | | +--ro vendor-revision-number? string
| | | +--ro check-code?           string
| | | +--ro extended-check-code?  string
| | | +--ro nominal-signalling-rate? int32
| | | +--ro maximum-signalling-rate? int32
| | | +--ro minimum-signalling-rate? int32
| | | +--ro vendor-serial-number?  string
| | | +--ro vendor-manufacturing-date? string
| | | +--ro ddm-type?              ipi-platform-transceiver-types:ddm_cmm_trans_ddm_support_t
| | | +--ro maximum-case-temperature? decimal64
| | | +--ro sfp-options-implemented? ipi-platform-transceiver-
types:ddm_cmm_trans_sfp_options_implemented_t
| | +--ro monitors
| | | +--ro monitor* [id]
| | | | +--ro id    -> ../state/id
| | | | +--ro state
| | | | | +--ro id?      ipi-platform-transceiver-types:cmm_smart_sfp_ddm_monitor_id_t
| | | | | +--ro description? string
| | | | | +--ro value?    decimal64
| | | | | +--ro high-alarm? decimal64
| | | | | +--ro high-warning? decimal64
| | | | | +--ro low-warning? decimal64
| | | | | +--ro low-alarm? decimal64
| | | +--ro monitor-alarm
| | | | +--ro state
| | | | | +--ro alarm-id?      ipi-platform-transceiver-types:cmm_smart_sfp_ddm_monitor_id_t
| | | | | +--ro alarm-type?    ipi-platform-transceiver-types:cmm_ddm_threshold_alarm_t
| | | | | +--ro current-value? decimal64
| | | | | +--ro threshold-minimum? decimal64
| | | | | +--ro threshold-maximum? decimal64
| | +--ro protocol
| | | +--ro state
| | | | +--ro protocol-running-state? ipi-platform-transceiver-types:cmm_smart_sfp_protocol_running_state_t
| | | | +--ro protocol-local-status? ipi-platform-transceiver-types:cmm_smart_sfp_protocol_status_t

```

---

```

| | | +--ro protocol-remote-status? ipi-platform-transceiver-types:cmm_smart_sfp_protocol_status_t
| | | +--ro packets-rx? int32
| | | +--ro packets-tx? int32
| | | +--ro packets-error? int32
| | +--ro alarm
| | +--ro state
| | | +--ro alarm-id? ipi-platform-transceiver-types:cmm_smart_sfp_protocol_alarm_id_t
| | | +--ro current-status? ipi-platform-transceiver-types:cmm_smart_sfp_protocol_status_t
| +--rw debug
| | +--rw config
| | | +--rw enable-cmm? empty
| | | +--rw enable-ddm? empty {feature-list:NOT_HAVE_TIBIT}?
| | +--ro state
| | | +--ro enable-cmm? empty
| | | +--ro enable-ddm? empty {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro terminal-debug-status-cmm? cml-data-types:cml_on_off_t
| | | +--ro terminal-debug-status-ddm? cml-data-types:cml_on_off_t {feature-list:NOT_HAVE_TIBIT}?
| +--rw global
| | +--rw config
| | | +--rw warning-repeat? empty
| | | +--rw locator-led-enable? empty {feature-list:NOT_HAVE_TIBIT}?
| | | +--rw ddm-monitor-time-interval? uint16 {feature-list:NOT_HAVE_TIBIT}?
| | | +--rw service-unsupported-transceiver? empty {feature-list:NOT_HAVE_TIBIT}?
| | | +--rw enable-ddm-monitor? empty {feature-list:NOT_HAVE_TIBIT}?
| | +--ro state
| | | +--ro warning-repeat? empty
| | | +--ro locator-led-enable? empty {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro ddm-monitor-time-interval? uint16 {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro service-unsupported-transceiver? empty {feature-list:NOT_HAVE_TIBIT}?
| | | +--ro enable-ddm-monitor? empty {feature-list:NOT_HAVE_TIBIT}?
| | +--rw system-load-average-thresholds
| | | +--rw system-load-average-threshold* [system-1min-load-avg-warning-threshold system-1min-load-avg-alarm
system-5min-load-avg-alarm system-15min-load-avg-alarm]
| | | | +--rw system-1min-load-avg-warning-threshold -> ../config/system-1min-load-avg-warning-threshold
| | | | +--rw system-1min-load-avg-alarm -> ../config/system-1min-load-avg-alarm
| | | | +--rw system-5min-load-avg-alarm -> ../config/system-5min-load-avg-alarm
| | | | +--rw system-15min-load-avg-alarm -> ../config/system-15min-load-avg-alarm

```

```

| | | +--rw config
| | | | +--rw system-1min-load-avg-warning-threshold? uint8
| | | | +--rw system-1min-load-avg-alarm?          uint8
| | | | +--rw system-5min-load-avg-alarm?          uint8
| | | | +--rw system-15min-load-avg-alarm?         uint8
| | | +--ro state
| | |   +--ro system-1min-load-avg-warning-threshold? uint8
| | |   +--ro system-1min-load-avg-alarm?            uint8
| | |   +--ro system-5min-load-avg-alarm?            uint8
| | |   +--ro system-15min-load-avg-alarm?           uint8
| | +--rw cpu-core-usage-thresholds
| |   +--rw cpu-core-usage-threshold* [warning-threshold alarm-threshold]
| |     +--rw warning-threshold  -> ../config/warning-threshold
| |     +--rw alarm-threshold    -> ../config/alarm-threshold
| |   +--rw config
| |     | +--rw warning-threshold? uint8
| |     | +--rw alarm-threshold?  uint8
| |     +--ro state
| |       +--ro warning-threshold? uint8
| |       +--ro alarm-threshold?   uint8
| +--rw interfaces {feature-list:NOT_HAVE_TIBIT}?
| | +--rw interface* [interface-name]
| |   +--rw interface-name  -> ../config/interface-name
| |   +--rw config
| |     | +--rw interface-name?      -> /ipi-interface:interfaces/interface/name
| |     | +--rw monitor-port?        ipi-platform-types:cmm_monitor_state
| |     | +--rw poe-enable?           empty
| |     | +--rw transceiver-code?     ipi-platform-transceiver-types:ddm_transceiver_t
| |     | +--rw wavelength?          ipi-platform-types:cml_wavelength_t
| |     | +--rw tx-disable?           empty
| |     | +--rw edfa-operating-mode?  ipi-platform-types:edfa_operating_mode_t
| |     | +--rw edfa-target-output-power? decimal64
| |     | +--rw edfa-target-gain?     decimal64
| |     | +--rw tx-cdr-bypass?        empty
| |     | +--rw rx-cdr-bypass?        empty
| |     +--ro state

```

---

```
| | +--ro interface-name?      -> /ipi-interface:interfaces/interface/name
| | +--ro monitor-port?       ipi-platform-types:cmm_monitor_state
| | +--ro poe-enable?        empty
| | +--ro transceiver-code?   ipi-platform-transceiver-types:ddm_transceiver_t
| | +--ro wavelength?        ipi-platform-types:cml_wavelength_t
| | +--ro tx-disable?        empty
| | +--ro edfa-operating-mode? ipi-platform-types:edfa_operating_mode_t
| | +--ro edfa-target-output-power? decimal64
| | +--ro edfa-target-gain?   decimal64
| | +--ro tx-cdr-bypass?     empty
| | +--ro rx-cdr-bypass?     empty
| +--rw disk-activity-monitoring
| | +--rw config
| | | +--rw interval?        uint16
| | | +--rw read-threshold?  uint32
| | | +--rw write-threshold? uint32
| | +--ro state
| | | +--ro interval?        uint16
| | | +--ro read-threshold?  uint32
| | | +--ro write-threshold? uint32
| +--rw temperature
| | +--rw config
| | | +--rw temperature-policy? ipi-platform-types:cml_temp_policy_t
| | +--ro state
| | | +--ro temperature-policy? ipi-platform-types:cml_temp_policy_t
| +--rw thresholds
| | +--rw threshold* [sensor-id]
| | | +--rw sensor-id  -> ../config/sensor-id
| | | +--rw config
| | | | +--rw sensor-id? uint8
| | | +--ro state
| | | | +--ro sensor-id? uint8
| | +--rw severities
| | | +--rw severity* [severity]
| | | | +--rw severity  -> ../config/severity
| | | +--rw config
```

---

---

```

|         | +--rw severity?  ipi-platform-types:cml_temp_threshold_t
|         | +--rw value?    int16
|         +--ro state
|         +--ro severity?  ipi-platform-types:cml_temp_threshold_t
|         +--ro value?    int16
+--rw forwarding-profile-route-modes {feature-list:HAVE_BROADCOM}?
| +--rw config {feature-list:HAVE_BCM_UFT,feature-list:NOT_HAVE_DUNE}?
| | +--rw route-mode?  ipi-platform-profile-types:platform_forwarding_profile_route_mode_t {feature-
list:HAVE_BCM_UFT,feature-list:NOT_HAVE_DUNE}?
| | +--ro state {feature-list:HAVE_BCM_UFT,feature-list:NOT_HAVE_DUNE}?
| | +--ro route-mode?  ipi-platform-profile-types:platform_forwarding_profile_route_mode_t {feature-
list:HAVE_BCM_UFT,feature-list:NOT_HAVE_DUNE}?
+--rw profiles {feature-list:HAVE_BROADCOM}?
| +--rw hardware-profile
| | +--rw config
| | +--ro state
| | +--rw filters
| | | +--rw config
| | | | +--rw egress-ipv6?      cml-data-types:cml_enable_disable_t {feature-list:HAVE_ACL,feature-
list:NOT_HAVE_DUNE}?
| | | | +--rw ingress-ipv6-acl?  cml-data-types:cml_enable_disable_t {feature-list:HAVE_ACL,feature-
list:NOT_HAVE_DUNE}?
| | | | +--rw ingress-ipv4-custom0?  cml-data-types:cml_enable_disable_t {feature-list:HAVE_ACL,feature-
list:NOT_HAVE_DUNE}?
| | | | +--rw ingress-arp?      empty {feature-list:HAVE_ACL}?
| | | | +--rw ingress-mirror?    empty {feature-list:HAVE_ADVANCE_MIRROR,feature-
list:HAVE_BROADCOM,feature-list:NOT_HAVE_DUNE}?
| | | | +--rw ingress-bfd?      cml-data-types:cml_enable_disable_t {feature-
list:HAVE_BFD_HW_OFFLOAD,feature-list:NOT_HAVE_CUSTOM1_HW_BFD}?
| | | | +--rw ipsg-ipv6?        empty {feature-list:HAVE_DHCP_SNOOP,feature-list:HAVE_BROADCOM}?
| | | | +--rw isolation?        cml-data-types:cml_enable_disable_t {feature-list:NOT_HAVE_DUNE}?
| | | +--ro state
| | | | +--ro egress-ipv6?      cml-data-types:cml_enable_disable_t {feature-list:HAVE_ACL,feature-
list:NOT_HAVE_DUNE}?
| | | | +--ro ingress-ipv6-acl?  cml-data-types:cml_enable_disable_t {feature-list:HAVE_ACL,feature-
list:NOT_HAVE_DUNE}?
| | | | +--ro ingress-ipv4-custom0?  cml-data-types:cml_enable_disable_t {feature-list:HAVE_ACL,feature-
list:NOT_HAVE_DUNE}?
| | | | +--ro ingress-arp?      empty {feature-list:HAVE_ACL}?

```

---

---

```
| | | +-ro ingress-mirror?    empty {feature-list:HAVE_ADVANCE_MIRROR,feature-
list:HAVE_BROADCOM,feature-list:NOT_HAVE_DUNE}?
| | | +-ro ingress-bfd?      cml-data-types:cml_enable_disable_t {feature-
list:HAVE_BFD_HW_OFFLOAD,feature-list:NOT_HAVE_CUSTOM1_HW_BFD}?
| | | +-ro ipsg-ipv6?        empty {feature-list:HAVE_DHCP_SNOOP,feature-list:HAVE_BROADCOM}?
| | | +-ro isolation?       cml-data-types:cml_enable_disable_t {feature-list:NOT_HAVE_DUNE}?
| | +-ro tcam-utilization {feature-list:HAVE_ACL}?
| |   +-ro state
| |     +-ro warning-threshold-level?    int32
| |     +-ro critical-alert-threshold-level? int32
| |     +-ro filter-groups
| |       +-ro filter-group* [group-id]
| |         +-ro group-id  -> ../state/group-id
| |         +-ro state
| |           +-ro group-id?    uint32
| |           +-ro group-name?  cml-data-types:cml_line_t
| |           +-ro free-entries? int32
| |           +-ro used-entries? int32
| |           +-ro used-percentage? int32
| |           +-ro total-entries? int32
| |           +-ro dedicated-entries? int32
| |           +-ro shared-entries? int32
| +-rw filter-evpn-mpls-mh
| | +-rw config
| | +-ro state
| | +-ro tcam-utilization {feature-list:HAVE_ACL}?
| |   +-ro state
| |     +-ro warning-threshold-level?    int32
| |     +-ro critical-alert-threshold-level? int32
| |     +-ro filter-groups
| |       +-ro filter-group* [group-id]
| |         +-ro group-id  -> ../state/group-id
| |         +-ro state
| |           +-ro group-id?    uint32
| |           +-ro group-name?  cml-data-types:cml_line_t
| |           +-ro free-entries? int32
| |           +-ro used-entries? int32
```

---

---

```

| | |      +--ro used-percentage?  int32
| | |      +--ro total-entries?    int32
| | |      +--ro dedicated-entries? int32
| | |      +--ro shared-entries?   int32
| | +--rw statistics
| |   +--rw config
| |   +--ro state
| +--rw forwarding-profiles
|   +--rw config {feature-list:HAVE_BCM_UFT,feature-list:NOT_HAVE_DUNE}?
|   | +--rw profile? ipi-platform-profile-types:platform_forwarding_profile_t {feature-list:HAVE_BCM_UFT,feature-
list:NOT_HAVE_DUNE}?
|   |   +--ro state {feature-list:HAVE_BCM_UFT,feature-list:NOT_HAVE_DUNE}?
|   |   +--ro profile? ipi-platform-profile-types:platform_forwarding_profile_t {feature-list:HAVE_BCM_UFT,feature-
list:NOT_HAVE_DUNE}?
|   |   +--ro table-limit {feature-list:HAVE_BCM_UFT}?
|   |   | +--ro state {feature-list:HAVE_BCM_UFT}?
|   |   | | +--ro forwarding-profile? ipi-platform-profile-types:platform_forwarding_profile_t {feature-
list:NOT_HAVE_DUNE}?
|   |   | | +--ro table-sizes {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_MARVELL,feature-
list:NOT_HAVE_MARVELL}?
|   |   | |   +--ro table-size* [profile]
|   |   | |   +--ro profile  -> ../state/profile
|   |   | |   +--ro state
|   |   | |   +--ro profile?          ipi-platform-profile-types:platform_forwarding_profile_t
|   |   | |   +--ro mac-address-entries?  uint32
|   |   | |   +--ro host-ipv4-entries?    uint32
|   |   | |   +--ro host-ipv6-entries?    uint32
|   |   | |   +--ro prefix-ipv4-entries?  uint32
|   |   | |   +--ro prefix-ipv6-entries?  uint32
|   |   | |   +--ro prefix-ipv6-128-entries? uint32 {feature-list:NOT_HAVE_HELIX4}?
|   |   +--rw custom-profile {feature-list:HAVE_BCM_UFT,feature-list:NOT_HAVE_DUNE,feature-
list:NOT_HAVE_MARVELL,feature-list:NOT_HAVE_MARVELL}?
|   |     +--rw config
|   |     | +--rw l2-banks?          uint8
|   |     | +--rw l3-banks?          uint8
|   |     | +--rw lpm-banks?        ipi-platform-profile-types:platform_lpm_custom_profile_t
|   |     | +--rw vlan-xlate-banks?  uint8
|   |     | +--rw ep-vlan-xlate-banks? uint8

```

---

```

|   +--ro state
|   +--ro l2-banks?      uint8
|   +--ro l3-banks?      uint8
|   +--ro lpm-banks?     ipi-platform-profile-types:platform_lpm_custom_profile_t
|   +--ro vlan-xlate-banks?  uint8
|   +--ro ep-vlan-xlate-banks? uint8
+--rw hardware {feature-list:HAVE_BROADCOM}?
| +--rw hw-soc-property
| | +--rw config
| | +--ro state
| +--rw load-balance {feature-list:HAVE_BROADCOM}?
| | +--rw config!
| | | +--rw mpls-ip-payload?  empty {feature-list:NOT_HAVE_DUNE}?
| | | +--rw hash?            ipi-platform-profile-types:platform_load_hash_t {feature-list:NOT_HAVE_DUNE}?
| | | +--rw macro-flow-based? empty {feature-list:NOT_HAVE_DUNE}?
| | | +--rw enable           empty
| | | +--rw mpls-label-based? empty
| | +--ro state
| | | +--ro mpls-ip-payload?  empty {feature-list:NOT_HAVE_DUNE}?
| | | +--ro hash?            ipi-platform-profile-types:platform_load_hash_t {feature-list:NOT_HAVE_DUNE}?
| | | +--ro macro-flow-based? empty {feature-list:NOT_HAVE_DUNE}?
| | | +--ro enable           empty
| | | +--ro mpls-label-based? empty
| | +--rw l2 {feature-list:HAVE_L2}?
| | | +--rw config
| | | | +--rw dest-mac-based?  empty {feature-list:NOT_HAVE_DNX}?
| | | | +--rw src-mac-based?   empty {feature-list:NOT_HAVE_DNX}?
| | | | +--rw ether-type-based? empty
| | | | +--rw vlan-based?      empty
| | | +--ro state
| | | | +--ro dest-mac-based?  empty {feature-list:NOT_HAVE_DNX}?
| | | | +--ro src-mac-based?   empty {feature-list:NOT_HAVE_DNX}?
| | | | +--ro ether-type-based? empty
| | | | +--ro vlan-based?      empty
| | +--rw ipv4 {feature-list:HAVE_L3}?
| | | +--rw config

```

---

```
| | | +--rw symmetric?          empty {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_DNX}?
| | | +--rw src-ipv4-address-based?  empty {feature-list:NOT_HAVE_DNX}?
| | | +--rw dest-ipv4-address-based?  empty {feature-list:NOT_HAVE_DNX}?
| | | +--rw src-l4-port-based?       empty {feature-list:NOT_HAVE_DNX}?
| | | +--rw dest-l4-port-based?      empty {feature-list:NOT_HAVE_DNX}?
| | | +--rw protocol-id-based?       empty
| | +--ro state
| |   +--ro symmetric?             empty {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_DNX}?
| |   +--ro src-ipv4-address-based?  empty {feature-list:NOT_HAVE_DNX}?
| |   +--ro dest-ipv4-address-based?  empty {feature-list:NOT_HAVE_DNX}?
| |   +--ro src-l4-port-based?       empty {feature-list:NOT_HAVE_DNX}?
| |   +--ro dest-l4-port-based?      empty {feature-list:NOT_HAVE_DNX}?
| |   +--ro protocol-id-based?       empty
| +--rw ipv6 {feature-list:HAVE_L3}?
| | +--rw config
| | | +--rw symmetric?            empty {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_DNX}?
| | | +--rw src-ipv6-address-based?  empty {feature-list:NOT_HAVE_DNX}?
| | | +--rw dest-ipv6-address-based?  empty {feature-list:NOT_HAVE_DNX}?
| | | +--rw src-l4-port-based?       empty {feature-list:NOT_HAVE_DNX}?
| | | +--rw dest-l4-port-based?      empty {feature-list:NOT_HAVE_DNX}?
| | | +--rw next-header-based?       empty
| | +--ro state
| |   +--ro symmetric?            empty {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_DNX}?
| |   +--ro src-ipv6-address-based?  empty {feature-list:NOT_HAVE_DNX}?
| |   +--ro dest-ipv6-address-based?  empty {feature-list:NOT_HAVE_DNX}?
| |   +--ro src-l4-port-based?       empty {feature-list:NOT_HAVE_DNX}?
| |   +--ro dest-l4-port-based?      empty {feature-list:NOT_HAVE_DNX}?
| |   +--ro next-header-based?       empty
| +--rw tunnel {feature-list:HAVE_L3,feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_MARVELL,feature-
list:NOT_HAVE_MARVELL}?
| | +--rw config
| | | +--rw outer-l3-header?  empty
| | +--ro state
| |   +--ro outer-l3-header?  empty
| +--rw vxlan {feature-list:HAVE_VXLAN,feature-list:NOT_HAVE_DUNE,feature-
list:NOT_HAVE_MARVELL,feature-list:NOT_HAVE_MARVELL}?
| | +--rw inner-l2
```

---

---

```
| | | +--rw config
| | | | +--rw dest-mac-based? empty
| | | | +--rw src-mac-based? empty
| | | +--ro state
| | |   +--ro dest-mac-based? empty
| | |   +--ro src-mac-based? empty
| | +--rw inner-l3
| |   +--rw config
| |     +--rw src-ip-based? empty
| |     +--rw dest-ip-based? empty
| |     +--rw src-l4-port-based? empty
| |     +--rw dest-l4-port-based? empty
| |     +--rw protocol-id-based? empty
| |   +--ro state
| |     +--ro src-ip-based? empty
| |     +--ro dest-ip-based? empty
| |     +--ro src-l4-port-based? empty
| |     +--ro dest-l4-port-based? empty
| |     +--ro protocol-id-based? empty
| | +--rw mpls-ler {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_MARVELL,feature-
list:NOT_HAVE_MARVELL}?
| |   +--rw inner-l2
| |     +--rw config
| |       +--rw dest-mac-based? empty
| |       +--rw src-mac-based? empty
| |       +--rw ether-type-based? empty
| |       +--rw vlan-based? empty
| |     +--ro state
| |       +--ro dest-mac-based? empty
| |       +--ro src-mac-based? empty
| |       +--ro ether-type-based? empty
| |       +--ro vlan-based? empty
| |   +--rw inner-l3
| |     +--rw config
| |       +--rw src-ip-address-based? empty
| |       +--rw dest-ip-address-based? empty
| |       +--rw src-l4-port-based? empty
```

---

```

| | | | +--rw dest-l4-port-based?    empty
| | | | +--rw protocol-id-based?    empty
| | | | +--ro state
| | | |   +--ro src-ip-address-based? empty
| | | |   +--ro dest-ip-address-based? empty
| | | |   +--ro src-l4-port-based?    empty
| | | |   +--ro dest-l4-port-based?    empty
| | | |   +--ro protocol-id-based?    empty
| | +--rw port-channel {feature-list:NOT_HAVE_MARVELL,feature-list:NOT_HAVE_MARVELL}?
| |   +--rw interfaces {feature-list:HAVE_LACP,feature-list:NOT_HAVE_DUNE}?
| |     +--rw interface* [name]
| |       +--rw name    -> ../config/name
| |       +--rw config
| |         | +--rw name?  -> /ipi-interface:interfaces/interface/name
| |         | +--rw type?  ipi-platform-profile-types:platform_lacp_psc_t
| |         +--ro state
| |           +--ro name?  -> /ipi-interface:interfaces/interface/name
| |           +--ro type?  ipi-platform-profile-types:platform_lacp_psc_t
| | +--ro dram-tune {feature-list:HAVE_BROADCOM}?
| |   +--ro state
| |     +--ro dram-tune-status? int32 {feature-list:HAVE_BROADCOM}?
| +--rw cpu-queue {feature-list:HAVE_BROADCOM_OR_HAVE_MARVELL}?
| | +--rw rate-limits
| |   +--rw rate-limit* [queue-name]
| |     +--rw queue-name  -> ../config/queue-name
| |     +--rw config
| |       | +--rw lossy?    ipi-platform-profile-types:platform_cpu_queue_lossy_t {feature-list:NOT_HAVE_DUNE}?
| |       | +--rw monitor?  ipi-platform-profile-types:platform_cpu_queue_monitor_t {feature-list:NOT_HAVE_DUNE}?
| |       | +--rw queue-name? ipi-platform-profile-types:platform_cpu_queue_name_t
| |       | +--rw rate?     int32
| |       +--ro state
| |         +--ro lossy?    ipi-platform-profile-types:platform_cpu_queue_lossy_t {feature-list:NOT_HAVE_DUNE}?
| |         +--ro monitor?  ipi-platform-profile-types:platform_cpu_queue_monitor_t {feature-list:NOT_HAVE_DUNE}?
| |         +--ro queue-name? ipi-platform-profile-types:platform_cpu_queue_name_t
| |         +--ro rate?     int32
| +--rw mac-ageing {feature-list:NOT_HAVE_MARVELL,feature-list:NOT_HAVE_MARVELL}?

```

```

| | +--rw config
| | | +--rw enable-mac-ageing-timer? empty {feature-list:HAVE_L2_AGE_SHOW}?
| | +--ro state
| |   +--ro enable-mac-ageing-timer? empty {feature-list:HAVE_L2_AGE_SHOW}?
| +--rw platform {feature-list:NOT_HAVE_MARVELL,feature-list:NOT_HAVE_MARVELL}?
| | +--rw config
| |   +--rw soc? ipi-platform-profile-types:platform_soc_type_t
| +--rw cpu-control {feature-list:HAVE_VXLAN,feature-list:NOT_HAVE_DUNE,feature-
list:NOT_HAVE_MARVELL,feature-list:NOT_HAVE_MARVELL}?
|   +--rw packets
|     +--rw config
|       | +--rw disable-vxlan? empty
|       +--ro state
|         +--ro disable-vxlan? empty
+--rw qsfp-dds
  +--rw qsfp-dd* [fp-port]
    +--rw fp-port      -> ../config/fp-port
    +--rw config
      | +--rw fp-port?      uint8
      | +--rw application?  uint8
      | +--rw service-disable? empty
      | +--rw custom-app-host-id? uint8
      | +--rw custom-app-media-id? uint8
    +--ro state
      | +--ro fp-port?      uint8
      | +--ro application?  uint8
      | +--ro service-disable? empty
      | +--ro custom-app-host-id? uint8
      | +--ro custom-app-media-id? uint8
    +--rw host
      | +--rw prbs
      | | +--rw generator
      | | | +--rw config
      | | | | +--rw type?    ipi-platform-cmis-types:cmm_cmis_prbs_type_t
      | | | | +--rw location? ipi-platform-cmis-types:cmm_cmis_prbs_location_t
      | | | +--ro state
      | | | +--ro type?    ipi-platform-cmis-types:cmm_cmis_prbs_type_t

```

```
| | | +--ro location? ipi-platform-cmis-types:cmm_cmis_prbs_location_t
| | +--rw checker
| | +--rw config
| | | +--rw type? ipi-platform-cmis-types:cmm_cmis_prbs_type_t
| | | +--rw location? ipi-platform-cmis-types:cmm_cmis_prbs_location_t
| | +--ro state
| | +--ro type? ipi-platform-cmis-types:cmm_cmis_prbs_type_t
| | +--ro location? ipi-platform-cmis-types:cmm_cmis_prbs_location_t
| +--rw loopback
| | +--rw config
| | | +--rw type? ipi-platform-cmis-types:cmm_cmis_loopback_type_t
| | +--ro state
| | +--ro type? ipi-platform-cmis-types:cmm_cmis_loopback_type_t
| +--rw lanes
| +--rw lane* [lane-number]
| +--rw lane-number -> ../config/lane-number
| +--rw config
| | +--rw lane-number? uint8
| +--ro state
| | +--ro lane-number? uint8
| +--rw thresholds
| | +--rw threshold* [id]
| | +--rw id -> ../config/id
| | +--rw config
| | | +--rw id? ipi-platform-cmis-types:cmm_ccmis_host_lane_thres_id_t
| | | +--rw high-alarm? decimal64
| | | +--rw low-alarm? decimal64
| | | +--rw high-warning? decimal64
| | | +--rw low-warning? decimal64
| | +--ro state
| | +--ro id? ipi-platform-cmis-types:cmm_ccmis_host_lane_thres_id_t
| | +--ro high-alarm? decimal64
| | +--ro low-alarm? decimal64
| | +--ro high-warning? decimal64
| | +--ro low-warning? decimal64
| +--rw signal-integrity
```

---

```
|   +--rw config
|   |   +--rw tx-input-equalizer-target?      uint8
|   |   +--rw rx-output-equalizer-pre-cursor-target?  uint8
|   |   +--rw rx-output-equalizer-post-cursor-target? uint8
|   |   +--rw rx-output-amplitude-target?      uint8
|   |   +--rw tx-cdr-bypass?                  empty
|   |   +--rw rx-cdr-bypass?                  empty
|   +--ro state
|   |   +--ro tx-input-equalizer-target?      uint8
|   |   +--ro rx-output-equalizer-pre-cursor-target?  uint8
|   |   +--ro rx-output-equalizer-post-cursor-target? uint8
|   |   +--ro rx-output-amplitude-target?      uint8
|   |   +--ro tx-cdr-bypass?                  empty
|   |   +--ro rx-cdr-bypass?                  empty
+--rw media
| +--rw prbs
| | +--rw generator
| | | +--rw config
| | | | +--rw type?    ipi-platform-cmis-types:cmm_cmis_prbs_type_t
| | | | +--rw location? ipi-platform-cmis-types:cmm_cmis_prbs_location_t
| | | +--ro state
| | | | +--ro type?    ipi-platform-cmis-types:cmm_cmis_prbs_type_t
| | | | +--ro location? ipi-platform-cmis-types:cmm_cmis_prbs_location_t
| | +--rw checker
| | | +--rw config
| | | | +--rw type?    ipi-platform-cmis-types:cmm_cmis_prbs_type_t
| | | | +--rw location? ipi-platform-cmis-types:cmm_cmis_prbs_location_t
| | | +--ro state
| | | | +--ro type?    ipi-platform-cmis-types:cmm_cmis_prbs_type_t
| | | | +--ro location? ipi-platform-cmis-types:cmm_cmis_prbs_location_t
| +--rw loopback
| | +--rw config
| | | +--rw type? ipi-platform-cmis-types:cmm_cmis_loopback_type_t
| | +--ro state
| | | +--ro type? ipi-platform-cmis-types:cmm_cmis_loopback_type_t
| +--rw lanes
```

---

```

|  +--rw lane* [lane-number]
|  +--rw lane-number  -> ../config/lane-number
|  +--rw config
|  |  +--rw lane-number?  uint8
|  +--ro state
|  |  +--ro lane-number?  uint8
|  +--rw laser
|  |  +--rw config
|  |  |  +--rw channel?      int16
|  |  |  +--rw grid?        ipi-platform-cmis-types:cmm_cmis_laser_grid_spacing_t
|  |  |  +--rw fine-tune-freq?  decimal64
|  |  |  +--rw output-power?  decimal64
|  |  +--ro state
|  |  |  +--ro channel?      int16
|  |  |  +--ro grid?        ipi-platform-cmis-types:cmm_cmis_laser_grid_spacing_t
|  |  |  +--ro fine-tune-freq?  decimal64
|  |  |  +--ro output-power?  decimal64
|  +--rw thresholds
|  |  +--rw threshold* [id]
|  |  |  +--rw id      -> ../config/id
|  |  |  +--rw config
|  |  |  |  +--rw id?        ipi-platform-cmis-types:cmm_ccmis_media_lane_thres_id_t
|  |  |  |  +--rw high-alarm?  decimal64
|  |  |  |  +--rw low-alarm?   decimal64
|  |  |  |  +--rw high-warning? decimal64
|  |  |  |  +--rw low-warning? decimal64
|  |  |  +--ro state
|  |  |  |  +--ro id?        ipi-platform-cmis-types:cmm_ccmis_media_lane_thres_id_t
|  |  |  |  +--ro high-alarm?  decimal64
|  |  |  |  +--ro low-alarm?   decimal64
|  |  |  |  +--ro high-warning? decimal64
|  |  |  |  +--ro low-warning? decimal64
+--rw laser
|  +--rw config
|  |  +--rw channel?      int16
|  |  +--rw grid?        ipi-platform-cmis-types:cmm_cmis_laser_grid_spacing_t

```

---

---

```

| | +--rw fine-tune-freq?  decimal64
| | +--rw output-power?   decimal64
| +--ro state
|   +--ro channel?       int16
|   +--ro grid?          ipi-platform-cmis-types:cmm_cmis_laser_grid_spacing_t
|   +--ro fine-tune-freq? decimal64
|   +--ro output-power?  decimal64
+--rw thresholds
| +--rw threshold* [id]
|   +--rw id      -> ../config/id
|   +--rw config
|     | +--rw id?          ipi-platform-cmis-types:cmm_ccmis_thres_id_t
|     | +--rw high-alarm?  decimal64
|     | +--rw low-alarm?   decimal64
|     | +--rw high-warning? decimal64
|     | +--rw low-warning? decimal64
|     +--ro state
|       +--ro id?          ipi-platform-cmis-types:cmm_ccmis_thres_id_t
|       +--ro high-alarm?  decimal64
|       +--ro low-alarm?   decimal64
|       +--ro high-warning? decimal64
|       +--ro low-warning? decimal64
+--rw signal-integrity
  +--rw config
    | +--rw tx-input-equalizer-target?      uint8
    | +--rw rx-output-equalizer-pre-cursor-target?  uint8
    | +--rw rx-output-equalizer-post-cursor-target? uint8
    | +--rw rx-output-amplitude-target?        uint8
    | +--rw tx-cdr-bypass?                    empty
    | +--rw rx-cdr-bypass?                    empty
  +--ro state
    +--ro tx-input-equalizer-target?      uint8
    +--ro rx-output-equalizer-pre-cursor-target?  uint8
    +--ro rx-output-equalizer-post-cursor-target? uint8
    +--ro rx-output-amplitude-target?        uint8
    +--ro tx-cdr-bypass?                    empty

```

---

```
+--ro rx-cdr-bypass?          empty
```

```
rpcs:
```

```
+---x tibit-olt-microplug-set-management-vlan-tpid {feature-list:NOT_HAVE_TIBIT}?
| +---w input
|   +---w interface-name  string
|   +---w vlan-tpid      ipi-platform-transceiver-tibit-types:trans_tibit_cmm_tpid_t
+---x tibit-olt-microplug-set-management-vlan-id {feature-list:NOT_HAVE_TIBIT}?
| +---w input
|   +---w interface-name  string
|   +---w vlan-id        uint16
+---x tibit-olt-microplug-set-ethernet-mac-address {feature-list:NOT_HAVE_TIBIT}?
| +---w input
|   +---w interface-name  string
|   +---w mac-address     yang:mac-address
+---x tibit-olt-microplug-set-next-active-firmware-bank {feature-list:NOT_HAVE_TIBIT}?
| +---w input
|   +---w interface-name  string
|   +---w bank-id        uint8
+---x tibit-olt-microplug-reboot {feature-list:NOT_HAVE_TIBIT}?
| +---w input
|   +---w interface-name  string
+---x ddm-clear-transceiver-alarm-all {feature-list:NOT_HAVE_TIBIT}?
+---x ddm-clear-transceiver-alarm {feature-list:NOT_HAVE_TIBIT}?
| +---w input
|   +---w name           string
+---x cmm-terminal-debug-ddm-on {feature-list:NOT_HAVE_TIBIT}?
+---x cmm-terminal-debug-ddm-off {feature-list:NOT_HAVE_TIBIT}?
+---x cmm-terminal-debug-cmm-on {feature-list:HAVE_CMMD}?
+---x cmm-terminal-debug-cmm-off {feature-list:HAVE_CMMD}?
```

```
notifications:
```

```
+---n bmc-lower-non-critical-low-threshold-notification {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro name?         string
```

---

```
| +--ro lower-non-critical?  decimal64
| +--ro threshold?          decimal64
| +--ro units?              string
| +--ro event-type?         ipi-platform-types:cmm_bmc_event_type_t
+---n bmc-lower-non-critical-high-threshold-notification {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?        cml-data-types:cml_notif_class_t
| +--ro name?              string
| +--ro lower-non-critical? decimal64
| +--ro threshold?        decimal64
| +--ro units?            string
| +--ro event-type?       ipi-platform-types:cmm_bmc_event_type_t
+---n bmc-lower-critical-low-threshold-notification {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?        cml-data-types:cml_notif_class_t
| +--ro name?              string
| +--ro lower-critical?    decimal64
| +--ro threshold?        decimal64
| +--ro units?            string
| +--ro event-type?       ipi-platform-types:cmm_bmc_event_type_t
+---n bmc-lower-critical-high-threshold-notification {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?        cml-data-types:cml_notif_class_t
| +--ro name?              string
| +--ro lower-critical?    decimal64
| +--ro threshold?        decimal64
| +--ro units?            string
| +--ro event-type?       ipi-platform-types:cmm_bmc_event_type_t
+---n bmc-lower-non-recoverable-low-threshold-notification {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?        cml-data-types:cml_notif_class_t
| +--ro name?              string
| +--ro lower-non-recoverable? decimal64
| +--ro threshold?        decimal64
| +--ro units?            string
| +--ro event-type?       ipi-platform-types:cmm_bmc_event_type_t
```

---

---

```
+---n bmc-lower-non-recoverable-high-threshold-notification {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro lower-non-recoverable? decimal64
| +--ro threshold?        decimal64
| +--ro units?            string
| +--ro event-type?       ipi-platform-types:cmm_bmc_event_type_t
+---n bmc-upper-non-critical-low-threshold-notification {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro upper-non-critical? decimal64
| +--ro threshold?        decimal64
| +--ro units?            string
| +--ro event-type?       ipi-platform-types:cmm_bmc_event_type_t
+---n bmc-upper-non-critical-high-threshold-notification {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro upper-non-critical? decimal64
| +--ro threshold?        decimal64
| +--ro units?            string
| +--ro event-type?       ipi-platform-types:cmm_bmc_event_type_t
+---n bmc-upper-critical-low-threshold-notification {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro upper-critical?    decimal64
| +--ro threshold?        decimal64
| +--ro units?            string
| +--ro event-type?       ipi-platform-types:cmm_bmc_event_type_t
+---n bmc-upper-critical-high-threshold-notification {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
```

---

---

```
| +--ro upper-critical? decimal64
| +--ro threshold? decimal64
| +--ro units? string
| +--ro event-type? ipi-platform-types:cmm_bmc_event_type_t
+---n bmc-upper-non-recoverable-low-threshold-notification {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name? string
| +--ro upper-non-recoverable? decimal64
| +--ro threshold? decimal64
| +--ro units? string
| +--ro event-type? ipi-platform-types:cmm_bmc_event_type_t
+---n bmc-upper-non-recoverable-high-threshold-notification {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name? string
| +--ro upper-non-recoverable? decimal64
| +--ro threshold? decimal64
| +--ro units? string
| +--ro event-type? ipi-platform-types:cmm_bmc_event_type_t
+---n bmc-device-state-notification {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name? string
| +--ro operational-status? string
+---n cpu-load-15min-alert
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name? string
| +--ro cpu-15min-load-percentage? decimal64
| +--ro cpu-15min-alert-threshold? uint8
+---n cpu-load-15min-alert-recovery
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name? string
| +--ro cpu-15min-load-percentage? decimal64
```

---

```
| +--ro cpu-15min-alert-threshold? uint8
+---n cpu-load-5min-alert
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro cpu-5min-load-percentage? decimal64
| +--ro cpu-5min-alert-threshold? uint8
+---n cpu-load-5min-alert-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro cpu-5min-load-percentage? decimal64
| +--ro cpu-5min-alert-threshold? uint8
+---n cpu-load-1min-critical
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro cpu-1min-load-percentage? decimal64
| +--ro cpu-1min-critical-threshold? uint8
+---n cpu-load-1min-critical-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro cpu-1min-load-percentage? decimal64
| +--ro cpu-1min-critical-threshold? uint8
+---n cpu-load-1min-alert
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro cpu-1min-load-percentage? decimal64
| +--ro cpu-1min-alert-threshold? uint8
+---n cpu-load-1min-alert-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro cpu-1min-load-percentage? decimal64
```

---

```
| +--ro cpu-1min-alert-threshold? uint8
+---n storage-usage-rising-alert
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro used-memory?      uint64
| +--ro usage-alert-threshold? int32
| +--ro mount-point?     string
+---n storage-usage-critical-alert
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro used-memory?      uint64
| +--ro usage-critical-threshold? int32
| +--ro mount-point?     string
+---n storage-usage-recovery-from-alert-level
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro used-memory?      uint64
| +--ro usage-alert-threshold? int32
| +--ro mount-point?     string
+---n storage-usage-recovery-from-critical-level
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro used-memory?      uint64
| +--ro usage-critical-threshold? int32
| +--ro mount-point?     string
+---n storage-remaining-life-rising-alert
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro remaining-life?    int32
| +--ro remain-life-alert-threshold? int32
+---n storage-remaining-life-rising-critical
```

---

```
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro remaining-life?   int32
| +--ro remain-life-critical-threshold? int32
+---n storage-available-reserved-space-rising-alert
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro available-reserved-space? int32
| +--ro available-reserved-space-alert-threshold? int32
+---n storage-available-reserved-space-rising-critical
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro available-reserved-space? int32
| +--ro available-reserved-space-critical-threshold? int32
+---n storage-reallocated-sector-count-rising-alert
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro reallocated-sector-count? int32
+---n storage-uncorrectable-sector-count-rising-critical
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro uncorrectable-sector-count? int32
+---n storage-harddisk-monitoring-read-alert
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro read-average?     int32
| +--ro read-threshold?  int32
+---n storage-harddisk-recovery-from-read-alert-level
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
```

---

```
| +--ro name?      string
| +--ro read-average?  int32
| +--ro read-threshold? int32
+---n storage-harddisk-monitoring-write-alert
| +--ro severity?    cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?      string
| +--ro write-average?  int32
| +--ro write-threshold? int32
+---n storage-harddisk-recovery-from-write-alert-level
| +--ro severity?    cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?      string
| +--ro write-average?  int32
| +--ro write-threshold? int32
+---n storage-storage-status-alert
| +--ro severity?    cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?      string
| +--ro storage-status? ipi-platform-types:cml_cmm_storage_status_t
+---n storage-storage-status-critical
| +--ro severity?    cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?      string
| +--ro storage-status? ipi-platform-types:cml_cmm_storage_status_t
+---n ram-usage-rising-critical
| +--ro severity?    cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?      string
| +--ro used-memory?    uint64
| +--ro usage-critical-threshold? uint32
+---n ram-usage-rising-alert
| +--ro severity?    cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?      string
| +--ro used-memory?    uint64
```

---

```
| +--ro usage-alert-threshold? uint32
+---n ram-usage-recovery-from-critical-level
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro used-memory?      uint64
| +--ro usage-critical-threshold? uint32
+---n ram-usage-recovery-from-alert-level
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro used-memory?      uint64
| +--ro usage-alert-threshold? uint32
+---n transceiver-inserted {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro port-no?          uint8
| +--ro type?             ipi-platform-transceiver-types:ddm_cmm_trans_type_t
| +--ro vendor-name?      string
| +--ro vendor-serial-number? string
| +--ro connector-type?   ipi-platform-transceiver-types:ddm_cmm_trans_connector_type_t
+---n transceiver-removed {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro port-no?          uint8
| +--ro type?             ipi-platform-transceiver-types:ddm_cmm_trans_type_t
| +--ro vendor-name?      string
| +--ro vendor-serial-number? string
| +--ro connector-type?   ipi-platform-transceiver-types:ddm_cmm_trans_connector_type_t
+---n faulty-transceiver-inserted {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro port-no?          uint8
```

---

```
| +--ro type?      ipi-platform-transceiver-types:ddm_cmm_trans_type_t
+---n incompatible-transceiver-inserted {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name?      string
| +--ro port-no?   uint8
+---n incompatible-transceiver-removed {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name?      string
| +--ro port-no?   uint8
+---n frequency-error-high-critical {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro frequency-error?   decimal64
| +--ro frequency-error-critical-min-threshold? decimal64
| +--ro frequency-error-critical-max-threshold? decimal64
+---n frequency-error-low-critical {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro frequency-error?   decimal64
| +--ro frequency-error-critical-min-threshold? decimal64
| +--ro frequency-error-critical-max-threshold? decimal64
+---n frequency-error-high-alert {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro frequency-error?   decimal64
| +--ro frequency-error-alert-min-threshold? decimal64
| +--ro frequency-error-alert-max-threshold? decimal64
+---n frequency-error-low-alert {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
```

---

```
| +--ro frequency-error?          decimal64
| +--ro frequency-error-alert-min-threshold? decimal64
| +--ro frequency-error-alert-max-threshold? decimal64
+---n frequency-error-recovery {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro frequency-error?  decimal64
+---n wavelength-error-high-critical {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro wavelength-error? decimal64
| +--ro wavelength-error-critical-min-threshold? decimal64
| +--ro wavelength-error-critical-max-threshold? decimal64
+---n wavelength-error-low-critical {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro wavelength-error? decimal64
| +--ro wavelength-error-critical-min-threshold? decimal64
| +--ro wavelength-error-critical-max-threshold? decimal64
+---n wavelength-error-high-alert {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro wavelength-error? decimal64
| +--ro wavelength-error-alert-min-threshold? decimal64
| +--ro wavelength-error-alert-max-threshold? decimal64
+---n wavelength-error-low-alert {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro wavelength-error? decimal64
| +--ro wavelength-error-alert-min-threshold? decimal64
| +--ro wavelength-error-alert-max-threshold? decimal64
```

---

```
+---n wavelength-error-recovery {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro name?         string
| +--ro wavelength-error? decimal64
+---n thermoelectric-cooler-fault-alert {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro name?         string
| +--ro thermoelectric-cooler-fault? boolean
+---n thermoelectric-cooler-fault-recovery {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro name?         string
| +--ro thermoelectric-cooler-fault? boolean
+---n rx-loss-of-signal {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro index?       uint8
| +--ro name?        string
+---n rx-loss-of-signal-recovery {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro index?       uint8
| +--ro name?        string
+---n input-power-error-high-critical {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro index?        uint8
| +--ro name?         string
| +--ro input-power?   decimal64
| +--ro input-power-critical-min-threshold? decimal64
| +--ro input-power-critical-max-threshold? decimal64
+---n input-power-error-low-critical {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
```

---

```
| +--ro index?                uint8
| +--ro name?                 string
| +--ro input-power?         decimal64
| +--ro input-power-critical-min-threshold? decimal64
| +--ro input-power-critical-max-threshold? decimal64
+---n input-power-error-high-alert {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?            cml-data-types:cml_notif_severity_t
| +--ro eventClass?         cml-data-types:cml_notif_class_t
| +--ro index?              uint8
| +--ro name?               string
| +--ro input-power?        decimal64
| +--ro input-power-alert-min-threshold? decimal64
| +--ro input-power-alert-max-threshold? decimal64
+---n input-power-error-low-alert {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?            cml-data-types:cml_notif_severity_t
| +--ro eventClass?         cml-data-types:cml_notif_class_t
| +--ro index?              uint8
| +--ro name?               string
| +--ro input-power?        decimal64
| +--ro input-power-alert-min-threshold? decimal64
| +--ro input-power-alert-max-threshold? decimal64
+---n input-power-error-recovery {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?            cml-data-types:cml_notif_severity_t
| +--ro eventClass?         cml-data-types:cml_notif_class_t
| +--ro index?              uint8
| +--ro name?               string
| +--ro input-power?        decimal64
+---n output-power-error-high-critical {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?            cml-data-types:cml_notif_severity_t
| +--ro eventClass?         cml-data-types:cml_notif_class_t
| +--ro index?              uint8
| +--ro name?               string
| +--ro output-power?        decimal64
| +--ro output-power-critical-min-threshold? decimal64
| +--ro output-power-critical-max-threshold? decimal64
+---n output-power-error-low-critical {feature-list:NOT_HAVE_TIBIT}?
```

---

```
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro index?            uint8
| +--ro name?             string
| +--ro output-power?     decimal64
| +--ro output-power-critical-min-threshold? decimal64
| +--ro output-power-critical-max-threshold? decimal64
+---n output-power-error-high-alert {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro index?            uint8
| +--ro name?             string
| +--ro output-power?     decimal64
| +--ro output-power-alert-min-threshold? decimal64
| +--ro output-power-alert-max-threshold? decimal64
+---n output-power-error-low-alert {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro index?            uint8
| +--ro name?             string
| +--ro output-power?     decimal64
| +--ro output-power-alert-min-threshold? decimal64
| +--ro output-power-alert-max-threshold? decimal64
+---n output-power-error-recovery {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro index?            uint8
| +--ro name?             string
| +--ro output-power?     decimal64
+---n laser-bias-current-error-high-critical {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro index?            uint8
| +--ro name?             string
| +--ro laser-bias-current? decimal64
| +--ro laser-bias-current-critical-min-threshold? decimal64
```

---

```
| +--ro laser-bias-current-critical-max-threshold? decimal64
+---n laser-bias-current-error-low-critical {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro index? uint8
| +--ro name? string
| +--ro laser-bias-current? decimal64
| +--ro laser-bias-current-critical-min-threshold? decimal64
| +--ro laser-bias-current-critical-max-threshold? decimal64
+---n laser-bias-current-error-high-alert {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro index? uint8
| +--ro name? string
| +--ro laser-bias-current? decimal64
| +--ro laser-bias-current-alert-min-threshold? decimal64
| +--ro laser-bias-current-alert-max-threshold? decimal64
+---n laser-bias-current-error-low-alert {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro index? uint8
| +--ro name? string
| +--ro laser-bias-current? decimal64
| +--ro laser-bias-current-alert-min-threshold? decimal64
| +--ro laser-bias-current-alert-max-threshold? decimal64
+---n laser-bias-current-error-recovery {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro index? uint8
| +--ro name? string
| +--ro laser-bias-current? decimal64
+---n transceiver-temperature-error-high-critical {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name? string
| +--ro transceiver-temperature? decimal64
```

---

---

```
| +--ro temperature-critical-min-threshold? decimal64
| +--ro temperature-critical-max-threshold? decimal64
+---n transceiver-temperature-error-low-critical {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name? string
| +--ro transceiver-temperature? decimal64
| +--ro temperature-critical-min-threshold? decimal64
| +--ro temperature-critical-max-threshold? decimal64
+---n transceiver-temperature-error-high-alert {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name? string
| +--ro transceiver-temperature? decimal64
| +--ro temperature-alert-min-threshold? decimal64
| +--ro temperature-alert-max-threshold? decimal64
+---n transceiver-temperature-error-low-alert {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name? string
| +--ro transceiver-temperature? decimal64
| +--ro temperature-alert-min-threshold? decimal64
| +--ro temperature-alert-max-threshold? decimal64
+---n transceiver-temperature-error-recovery {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name? string
| +--ro transceiver-temperature? decimal64
+---n transceiver-voltage-error-high-critical {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity? cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name? string
| +--ro transceiver-voltage? decimal64
| +--ro voltage-critical-min-threshold? decimal64
| +--ro voltage-critical-max-threshold? decimal64
+---n transceiver-voltage-error-low-critical {feature-list:NOT_HAVE_TIBIT}?
```

---

```
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro transceiver-voltage?  decimal64
| +--ro voltage-critical-min-threshold? decimal64
| +--ro voltage-critical-max-threshold? decimal64
+---n transceiver-voltage-error-high-alert {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro transceiver-voltage?  decimal64
| +--ro voltage-alert-min-threshold? decimal64
| +--ro voltage-alert-max-threshold? decimal64
+---n transceiver-voltage-error-low-alert {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro transceiver-voltage?  decimal64
| +--ro voltage-alert-min-threshold? decimal64
| +--ro voltage-alert-max-threshold? decimal64
+---n transceiver-voltage-error-recovery {feature-list:NOT_HAVE_TIBIT}?
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro transceiver-voltage?  decimal64
+---n temperature-high
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro alarm-status?     boolean
| +--ro alarm-threshold?  decimal64
| +--ro instant?          decimal64
+---n temperature-low
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
```

---

```
| +--ro alarm-status?   boolean
| +--ro alarm-threshold? decimal64
| +--ro instant?       decimal64
+---n power-supply-inserted
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?        string
+---n power-supply-removed
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?        string
+---n power-supply-ac-failed
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?        string
+---n power-supply-ac-recovery
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?        string
+---n power-supply-12v-failed
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?        string
+---n power-supply-12v-recovery
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?        string
+---n psu-vin-low-alert
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?        string
| +--ro input-voltage?   decimal64
| +--ro vin-alert-threshold-min? decimal64
| +--ro vin-alert-threshold-max? decimal64
+---n psu-vin-high-alert
| +--ro severity?     cml-data-types:cml_notif_severity_t
```

---

```
| +--ro eventClass?          cml-data-types:cml_notif_class_t
| +--ro name?                string
| +--ro input-voltage?       decimal64
| +--ro vin-alert-threshold-min? decimal64
| +--ro vin-alert-threshold-max? decimal64
+---n psu-vin-low-critical
| +--ro severity?           cml-data-types:cml_notif_severity_t
| +--ro eventClass?        cml-data-types:cml_notif_class_t
| +--ro name?              string
| +--ro input-voltage?     decimal64
| +--ro vin-critical-threshold-min? decimal64
| +--ro vin-critical-threshold-max? decimal64
+---n psu-vin-high-critical
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?        cml-data-types:cml_notif_class_t
| +--ro name?              string
| +--ro input-voltage?     decimal64
| +--ro vin-critical-threshold-min? decimal64
| +--ro vin-critical-threshold-max? decimal64
+---n psu-vin-low-alert-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?        cml-data-types:cml_notif_class_t
| +--ro name?              string
| +--ro input-voltage?     decimal64
| +--ro vin-alert-threshold-min? decimal64
| +--ro vin-alert-threshold-max? decimal64
+---n psu-vin-high-alert-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?        cml-data-types:cml_notif_class_t
| +--ro name?              string
| +--ro input-voltage?     decimal64
| +--ro vin-alert-threshold-min? decimal64
| +--ro vin-alert-threshold-max? decimal64
+---n psu-vin-low-critical-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?        cml-data-types:cml_notif_class_t
```

---

```
| +--ro name?          string
| +--ro input-voltage?  decimal64
| +--ro vin-critical-threshold-min?  decimal64
| +--ro vin-critical-threshold-max?  decimal64
+---n psu-vin-high-critical-recovery
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?    cml-data-types:cml_notif_class_t
| +--ro name?          string
| +--ro input-voltage?  decimal64
| +--ro vin-critical-threshold-min?  decimal64
| +--ro vin-critical-threshold-max?  decimal64
+---n psu-vout-low-alert
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?    cml-data-types:cml_notif_class_t
| +--ro name?          string
| +--ro output-voltage?  decimal64
| +--ro vout-alert-threshold-min?  decimal64
| +--ro vout-alert-threshold-max?  decimal64
+---n psu-vout-high-alert
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?    cml-data-types:cml_notif_class_t
| +--ro name?          string
| +--ro output-voltage?  decimal64
| +--ro vout-alert-threshold-min?  decimal64
| +--ro vout-alert-threshold-max?  decimal64
+---n psu-vout-low-critical
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?    cml-data-types:cml_notif_class_t
| +--ro name?          string
| +--ro output-voltage?  decimal64
| +--ro vout-critical-threshold-min?  decimal64
| +--ro vout-critical-threshold-max?  decimal64
+---n psu-vout-high-critical
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?    cml-data-types:cml_notif_class_t
| +--ro name?          string
```

---

```
| +--ro output-voltage?          decimal64
| +--ro vout-critical-threshold-min? decimal64
| +--ro vout-critical-threshold-max? decimal64
+---n psu-vout-low-alert-recovery
| +--ro severity?               cml-data-types:cml_notif_severity_t
| +--ro eventClass?            cml-data-types:cml_notif_class_t
| +--ro name?                  string
| +--ro output-voltage?        decimal64
| +--ro vout-alert-threshold-min? decimal64
| +--ro vout-alert-threshold-max? decimal64
+---n psu-vout-high-alert-recovery
| +--ro severity?              cml-data-types:cml_notif_severity_t
| +--ro eventClass?            cml-data-types:cml_notif_class_t
| +--ro name?                  string
| +--ro output-voltage?        decimal64
| +--ro vout-alert-threshold-min? decimal64
| +--ro vout-alert-threshold-max? decimal64
+---n psu-vout-low-critical-recovery
| +--ro severity?              cml-data-types:cml_notif_severity_t
| +--ro eventClass?            cml-data-types:cml_notif_class_t
| +--ro name?                  string
| +--ro output-voltage?        decimal64
| +--ro vout-critical-threshold-min? decimal64
| +--ro vout-critical-threshold-max? decimal64
+---n psu-vout-high-critical-recovery
| +--ro severity?              cml-data-types:cml_notif_severity_t
| +--ro eventClass?            cml-data-types:cml_notif_class_t
| +--ro name?                  string
| +--ro output-voltage?        decimal64
| +--ro vout-critical-threshold-min? decimal64
| +--ro vout-critical-threshold-max? decimal64
+---n psu-pin-low-alert
| +--ro severity?              cml-data-types:cml_notif_severity_t
| +--ro eventClass?            cml-data-types:cml_notif_class_t
| +--ro name?                  string
| +--ro input-power?           decimal64
```

---

```
| +--ro pin-alert-threshold-min?  decimal64
| +--ro pin-alert-threshold-max?  decimal64
+---n psu-pin-high-alert
| +--ro severity?                 cml-data-types:cml_notif_severity_t
| +--ro eventClass?              cml-data-types:cml_notif_class_t
| +--ro name?                    string
| +--ro input-power?             decimal64
| +--ro pin-alert-threshold-min?  decimal64
| +--ro pin-alert-threshold-max?  decimal64
+---n psu-pin-low-critical
| +--ro severity?                 cml-data-types:cml_notif_severity_t
| +--ro eventClass?              cml-data-types:cml_notif_class_t
| +--ro name?                    string
| +--ro input-power?             decimal64
| +--ro pin-critical-threshold-min? decimal64
| +--ro pin-critical-threshold-max? decimal64
+---n psu-pin-high-critical
| +--ro severity?                 cml-data-types:cml_notif_severity_t
| +--ro eventClass?              cml-data-types:cml_notif_class_t
| +--ro name?                    string
| +--ro input-power?             decimal64
| +--ro pin-critical-threshold-min? decimal64
| +--ro pin-critical-threshold-max? decimal64
+---n psu-pin-low-alert-recovery
| +--ro severity?                 cml-data-types:cml_notif_severity_t
| +--ro eventClass?              cml-data-types:cml_notif_class_t
| +--ro name?                    string
| +--ro input-power?             decimal64
| +--ro pin-alert-threshold-min?  decimal64
| +--ro pin-alert-threshold-max?  decimal64
+---n psu-pin-high-alert-recovery
| +--ro severity?                 cml-data-types:cml_notif_severity_t
| +--ro eventClass?              cml-data-types:cml_notif_class_t
| +--ro name?                    string
| +--ro input-power?             decimal64
| +--ro pin-alert-threshold-min?  decimal64
```

---

```
| +--ro pin-alert-threshold-max? decimal64
+---n psu-pin-low-critical-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro input-power?      decimal64
| +--ro pin-critical-threshold-min? decimal64
| +--ro pin-critical-threshold-max? decimal64
+---n psu-pin-high-critical-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro input-power?      decimal64
| +--ro pin-critical-threshold-min? decimal64
| +--ro pin-critical-threshold-max? decimal64
+---n psu-pout-low-alert
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro power-consumption? decimal64
| +--ro pout-alert-threshold-min? decimal64
| +--ro pout-alert-threshold-max? decimal64
+---n psu-pout-high-alert
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro power-consumption? decimal64
| +--ro pout-alert-threshold-min? decimal64
| +--ro pout-alert-threshold-max? decimal64
+---n psu-pout-low-critical
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro power-consumption? decimal64
| +--ro pout-critical-threshold-min? decimal64
| +--ro pout-critical-threshold-max? decimal64
```

---

```
+---n psu-pout-high-critical
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro power-consumption? decimal64
| +--ro pout-critical-threshold-min? decimal64
| +--ro pout-critical-threshold-max? decimal64
+---n psu-pout-low-alert-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro power-consumption? decimal64
| +--ro pout-alert-threshold-min? decimal64
| +--ro pout-alert-threshold-max? decimal64
+---n psu-pout-high-alert-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro power-consumption? decimal64
| +--ro pout-alert-threshold-min? decimal64
| +--ro pout-alert-threshold-max? decimal64
+---n psu-pout-low-critical-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro power-consumption? decimal64
| +--ro pout-critical-threshold-min? decimal64
| +--ro pout-critical-threshold-max? decimal64
+---n psu-pout-high-critical-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro power-consumption? decimal64
| +--ro pout-critical-threshold-min? decimal64
| +--ro pout-critical-threshold-max? decimal64
+---n psu-iout-low-alert
```

---

```
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro output-current?   decimal64
| +--ro iout-alert-threshold-min? decimal64
| +--ro iout-alert-threshold-max? decimal64
+---n psu-iout-high-alert
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro output-current?   decimal64
| +--ro iout-alert-threshold-min? decimal64
| +--ro iout-alert-threshold-max? decimal64
+---n psu-iout-low-critical
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro output-current?   decimal64
| +--ro iout-critical-threshold-min? decimal64
| +--ro iout-critical-threshold-max? decimal64
+---n psu-iout-high-critical
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro output-current?   decimal64
| +--ro iout-critical-threshold-min? decimal64
| +--ro iout-critical-threshold-max? decimal64
+---n psu-iout-low-alert-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro output-current?   decimal64
| +--ro iout-alert-threshold-min? decimal64
| +--ro iout-alert-threshold-max? decimal64
+---n psu-iout-high-alert-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
```

---

```
| +--ro eventClass?          cml-data-types:cml_notif_class_t
| +--ro name?               string
| +--ro output-current?     decimal64
| +--ro iout-alert-threshold-min? decimal64
| +--ro iout-alert-threshold-max? decimal64
+---n psu-iout-low-critical-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro output-current?   decimal64
| +--ro iout-critical-threshold-min? decimal64
| +--ro iout-critical-threshold-max? decimal64
+---n psu-iout-high-critical-recovery
| +--ro severity?         cml-data-types:cml_notif_severity_t
| +--ro eventClass?      cml-data-types:cml_notif_class_t
| +--ro name?            string
| +--ro output-current?  decimal64
| +--ro iout-critical-threshold-min? decimal64
| +--ro iout-critical-threshold-max? decimal64
+---n psu-iin-low-alert
| +--ro severity?        cml-data-types:cml_notif_severity_t
| +--ro eventClass?     cml-data-types:cml_notif_class_t
| +--ro name?           string
| +--ro input-current?  decimal64
| +--ro iin-alert-threshold-min? decimal64
| +--ro iin-alert-threshold-max? decimal64
+---n psu-iin-high-alert
| +--ro severity?       cml-data-types:cml_notif_severity_t
| +--ro eventClass?    cml-data-types:cml_notif_class_t
| +--ro name?          string
| +--ro input-current? decimal64
| +--ro iin-alert-threshold-min? decimal64
| +--ro iin-alert-threshold-max? decimal64
+---n psu-iin-low-critical
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
```

---

```
| +--ro name?          string
| +--ro input-current?  decimal64
| +--ro iin-critical-threshold-min?  decimal64
| +--ro iin-critical-threshold-max?  decimal64
+---n psu-iin-high-critical
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?    cml-data-types:cml_notif_class_t
| +--ro name?          string
| +--ro input-current?  decimal64
| +--ro iin-critical-threshold-min?  decimal64
| +--ro iin-critical-threshold-max?  decimal64
+---n psu-iin-low-alert-recovery
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?    cml-data-types:cml_notif_class_t
| +--ro name?          string
| +--ro input-current?  decimal64
| +--ro iin-alert-threshold-min?  decimal64
| +--ro iin-alert-threshold-max?  decimal64
+---n psu-iin-high-alert-recovery
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?    cml-data-types:cml_notif_class_t
| +--ro name?          string
| +--ro input-current?  decimal64
| +--ro iin-alert-threshold-min?  decimal64
| +--ro iin-alert-threshold-max?  decimal64
+---n psu-iin-low-critical-recovery
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?    cml-data-types:cml_notif_class_t
| +--ro name?          string
| +--ro input-current?  decimal64
| +--ro iin-critical-threshold-min?  decimal64
| +--ro iin-critical-threshold-max?  decimal64
+---n psu-iin-high-critical-recovery
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?    cml-data-types:cml_notif_class_t
| +--ro name?          string
```

---

```
| +--ro input-current?          decimal64
| +--ro iin-critical-threshold-min? decimal64
| +--ro iin-critical-threshold-max? decimal64
+---n psu-temp1-low-alert
| +--ro severity?              cml-data-types:cml_notif_severity_t
| +--ro eventClass?           cml-data-types:cml_notif_class_t
| +--ro name?                  string
| +--ro temperature-sensor1?   decimal64
| +--ro temp1-alert-threshold-min? decimal64
| +--ro temp1-alert-threshold-max? decimal64
+---n psu-temp1-high-alert
| +--ro severity?              cml-data-types:cml_notif_severity_t
| +--ro eventClass?           cml-data-types:cml_notif_class_t
| +--ro name?                  string
| +--ro temperature-sensor1?   decimal64
| +--ro temp1-alert-threshold-min? decimal64
| +--ro temp1-alert-threshold-max? decimal64
+---n psu-temp1-low-critical
| +--ro severity?              cml-data-types:cml_notif_severity_t
| +--ro eventClass?           cml-data-types:cml_notif_class_t
| +--ro name?                  string
| +--ro temperature-sensor1?   decimal64
| +--ro temp1-critical-threshold-min? decimal64
| +--ro temp1-critical-threshold-max? decimal64
+---n psu-temp1-high-critical
| +--ro severity?              cml-data-types:cml_notif_severity_t
| +--ro eventClass?           cml-data-types:cml_notif_class_t
| +--ro name?                  string
| +--ro temperature-sensor1?   decimal64
| +--ro temp1-critical-threshold-min? decimal64
| +--ro temp1-critical-threshold-max? decimal64
+---n psu-temp1-low-alert-recovery
| +--ro severity?              cml-data-types:cml_notif_severity_t
| +--ro eventClass?           cml-data-types:cml_notif_class_t
| +--ro name?                  string
| +--ro temperature-sensor1?   decimal64
```

---

```
| +--ro temp1-alert-threshold-min? decimal64
| +--ro temp1-alert-threshold-max? decimal64
+---n psu-temp1-high-alert-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor1? decimal64
| +--ro temp1-alert-threshold-min? decimal64
| +--ro temp1-alert-threshold-max? decimal64
+---n psu-temp1-low-critical-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor1? decimal64
| +--ro temp1-critical-threshold-min? decimal64
| +--ro temp1-critical-threshold-max? decimal64
+---n psu-temp1-high-critical-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor1? decimal64
| +--ro temp1-critical-threshold-min? decimal64
| +--ro temp1-critical-threshold-max? decimal64
+---n psu-temp2-low-alert
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor2? decimal64
| +--ro temp2-alert-threshold-min? decimal64
| +--ro temp2-alert-threshold-max? decimal64
+---n psu-temp2-high-alert
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor2? decimal64
| +--ro temp2-alert-threshold-min? decimal64
```

---

```
| +--ro temp2-alert-threshold-max? decimal64
+---n psu-temp2-low-critical
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor2? decimal64
| +--ro temp2-critical-threshold-min? decimal64
| +--ro temp2-critical-threshold-max? decimal64
+---n psu-temp2-high-critical
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor2? decimal64
| +--ro temp2-critical-threshold-min? decimal64
| +--ro temp2-critical-threshold-max? decimal64
+---n psu-temp2-low-alert-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor2? decimal64
| +--ro temp2-alert-threshold-min? decimal64
| +--ro temp2-alert-threshold-max? decimal64
+---n psu-temp2-high-alert-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor2? decimal64
| +--ro temp2-alert-threshold-min? decimal64
| +--ro temp2-alert-threshold-max? decimal64
+---n psu-temp2-low-critical-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor2? decimal64
| +--ro temp2-critical-threshold-min? decimal64
| +--ro temp2-critical-threshold-max? decimal64
```

---

```
+---n psu-temp2-high-critical-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor2? decimal64
| +--ro temp2-critical-threshold-min? decimal64
| +--ro temp2-critical-threshold-max? decimal64
+---n psu-temp3-low-alert
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor3? decimal64
| +--ro temp3-alert-threshold-min? decimal64
| +--ro temp3-alert-threshold-max? decimal64
+---n psu-temp3-high-alert
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor3? decimal64
| +--ro temp3-alert-threshold-min? decimal64
| +--ro temp3-alert-threshold-max? decimal64
+---n psu-temp3-low-critical
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor3? decimal64
| +--ro temp3-critical-threshold-min? decimal64
| +--ro temp3-critical-threshold-max? decimal64
+---n psu-temp3-high-critical
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor3? decimal64
| +--ro temp3-critical-threshold-min? decimal64
| +--ro temp3-critical-threshold-max? decimal64
+---n psu-temp3-low-alert-recovery
```

---

```
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor3?  decimal64
| +--ro temp3-alert-threshold-min? decimal64
| +--ro temp3-alert-threshold-max? decimal64
+---n psu-temp3-high-alert-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor3?  decimal64
| +--ro temp3-alert-threshold-min? decimal64
| +--ro temp3-alert-threshold-max? decimal64
+---n psu-temp3-low-critical-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor3?  decimal64
| +--ro temp3-critical-threshold-min? decimal64
| +--ro temp3-critical-threshold-max? decimal64
+---n psu-temp3-high-critical-recovery
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro name?             string
| +--ro temperature-sensor3?  decimal64
| +--ro temp3-critical-threshold-min? decimal64
| +--ro temp3-critical-threshold-max? decimal64
+---n fan-status-alarm
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name?     string
| +--ro fan-index? uint8
| +--ro fan-status? cml_cmm_fan_status_t
+---n fan-status-alarm-recovery
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
```

---

```
| +--ro name?      string
| +--ro fan-index? uint8
| +--ro fan-status? cml_cmm_fan_status_t
+---n fan-rpm-max-alert
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name?      string
| +--ro maximum-rpm? uint32
+---n fan-rpm-decreased-notify
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name?      string
| +--ro rpm?       uint32
+---n fan-rpm-increased-notify
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name?      string
| +--ro rpm?       uint32
+---n fan-tray-inserted
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name?      string
+---n fan-tray-removed
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name?      string
+---n hardware-tcam-util-warning-notification {feature-list:HAVE_BROADCOM}?
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro group-id?  uint32
| +--ro group-name? cml-data-types:cml_line_t
| +--ro used-percentage? int32
| +--ro free-entries? int32
+---n hardware-tcam-util-recovery-warning-notification {feature-list:HAVE_BROADCOM}?
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
```

---

---

```
| +--ro group-id?      uint32
| +--ro group-name?   cml-data-types:cml_line_t
| +--ro used-percentage? int32
| +--ro free-entries?  int32
+---n hardware-tcam-util-critical-notification {feature-list:HAVE_BROADCOM}?
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro group-id?     uint32
| +--ro group-name?   cml-data-types:cml_line_t
| +--ro used-percentage? int32
| +--ro free-entries?  int32
+---n hardware-tcam-util-recovery-critical-notification {feature-list:HAVE_BROADCOM}?
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro group-id?     uint32
| +--ro group-name?   cml-data-types:cml_line_t
| +--ro used-percentage? int32
| +--ro free-entries?  int32
+---n platform-interface-load-balance-update {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_MARVELL}?
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro name?         string
| +--ro type?         ipi-platform-profile-types:platform_lacp_psc_t
+---n cmis-module-monitor-alarm-notification
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro name?         string
| +--ro alarm-id?     ipi-platform-cmis-types:cmm_cmis_module_monitor_id_t
| +--ro alarm-type?   ipi-platform-cmis-types:cmm_cmis_threshold_alarm_t
| +--ro current-value? decimal64
| +--ro threshold-minimum? decimal64
| +--ro threshold-maximum? decimal64
+---n cmis-module-monitor-recovery-notification
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro name?         string
```

---

---

```
| +--ro alarm-id?      ipi-platform-cmis-types:cmm_cmis_module_monitor_id_t
| +--ro alarm-type?   ipi-platform-cmis-types:cmm_cmis_threshold_alarm_t
| +--ro current-value? decimal64
| +--ro threshold-minimum? decimal64
| +--ro threshold-maximum? decimal64
+---n cmis-module-host-monitor-alarm-notification
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro number?       uint8
| +--ro name?         string
| +--ro alarm-id?     ipi-platform-cmis-types:cmm_cmis_host_monitor_id_t
| +--ro alarm-type?   ipi-platform-cmis-types:cmm_cmis_threshold_alarm_t
| +--ro current-value? decimal64
| +--ro threshold-minimum? decimal64
| +--ro threshold-maximum? decimal64
+---n cmis-module-host-monitor-recovery-notification
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro number?       uint8
| +--ro name?         string
| +--ro alarm-id?     ipi-platform-cmis-types:cmm_cmis_host_monitor_id_t
| +--ro alarm-type?   ipi-platform-cmis-types:cmm_cmis_threshold_alarm_t
| +--ro current-value? decimal64
| +--ro threshold-minimum? decimal64
| +--ro threshold-maximum? decimal64
+---n cmis-module-host-flag-alarm-notification
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro number?       uint8
| +--ro name?         string
| +--ro alarm-id?     ipi-platform-cmis-types:cmm_cmis_host_flag_id_t
+---n cmis-module-host-flag-recovery-notification
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro number?       uint8
| +--ro name?         string
```

---

---

```
| +--ro alarm-id?   ipi-platform-cmis-types:cmm_cmis_host_flag_id_t
+---n cmis-module-media-monitor-alarm-notification
| +--ro severity?   cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro number?     uint8
| +--ro name?       string
| +--ro alarm-id?   ipi-platform-cmis-types:cmm_cmis_media_monitor_id_t
| +--ro alarm-type? ipi-platform-cmis-types:cmm_cmis_threshold_alarm_t
| +--ro current-value? decimal64
| +--ro threshold-minimum? decimal64
| +--ro threshold-maximum? decimal64
+---n cmis-module-media-monitor-recovery-notification
| +--ro severity?   cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro number?     uint8
| +--ro name?       string
| +--ro alarm-id?   ipi-platform-cmis-types:cmm_cmis_media_monitor_id_t
| +--ro alarm-type? ipi-platform-cmis-types:cmm_cmis_threshold_alarm_t
| +--ro current-value? decimal64
| +--ro threshold-minimum? decimal64
| +--ro threshold-maximum? decimal64
+---n cmis-module-media-flag-alarm-notification
| +--ro severity?   cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro number?     uint8
| +--ro name?       string
| +--ro alarm-id?   ipi-platform-cmis-types:cmm_cmis_media_flag_id_t
+---n cmis-module-media-flag-recovery-notification
| +--ro severity?   cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro number?     uint8
| +--ro name?       string
| +--ro alarm-id?   ipi-platform-cmis-types:cmm_cmis_media_flag_id_t
+---n edfa-alarm-notification
| +--ro severity?   cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
```

---

```
| +--ro port?          uint8
| +--ro name?         string
| +--ro alarm-id?     ipi-platform-transceiver-types:cmm_edfa_ddm_monitor_id_t
| +--ro alarm-type?   ipi-platform-transceiver-types:cmm_ddm_threshold_alarm_t
| +--ro current-value? decimal64
| +--ro threshold-minimum? decimal64
| +--ro threshold-maximum? decimal64
+---n edfa-alarm-recovery-notification
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro port?        uint8
| +--ro name?        string
| +--ro alarm-id?    ipi-platform-transceiver-types:cmm_edfa_ddm_monitor_id_t
| +--ro current-value? decimal64
| +--ro threshold-minimum? decimal64
| +--ro threshold-maximum? decimal64
+---n smart-sfp-ddm-alarm-notification
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro port?        uint8
| +--ro name?        string
| +--ro alarm-id?    ipi-platform-transceiver-types:cmm_smart_sfp_ddm_monitor_id_t
| +--ro alarm-type?   ipi-platform-transceiver-types:cmm_ddm_threshold_alarm_t
| +--ro current-value? decimal64
| +--ro threshold-minimum? decimal64
| +--ro threshold-maximum? decimal64
+---n smart-sfp-ddm-alarm-recovery-notification
| +--ro severity?     cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro port?        uint8
| +--ro name?        string
| +--ro alarm-id?    ipi-platform-transceiver-types:cmm_smart_sfp_ddm_monitor_id_t
| +--ro current-value? decimal64
| +--ro threshold-minimum? decimal64
| +--ro threshold-maximum? decimal64
+---n smart-sfp-descrete-alarm-notification
```

---

---

```

| +--ro severity?    cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro port?        uint8
| +--ro name?         string
| +--ro alarm-id?    ipi-platform-transceiver-types:cmm_smart_sfp_protocol_alarm_id_t
| +--ro current-status? ipi-platform-transceiver-types:cmm_smart_sfp_protocol_status_t
+---n smart-sfp-descrete-alarm-recovery-notification
  +--ro severity?    cml-data-types:cml_notif_severity_t
  +--ro eventClass?  cml-data-types:cml_notif_class_t
  +--ro port?        uint8
  +--ro name?         string
  +--ro alarm-id?    ipi-platform-transceiver-types:cmm_smart_sfp_protocol_alarm_id_t
  +--ro current-status? ipi-platform-transceiver-types:cmm_smart_sfp_protocol_status_t

```

---

## module: ipi-port-breakout

```

+--rw port-breakout
  +--rw breakouts
    | +--rw breakout* [interface]
    |   +--rw interface  -> ../config/interface
    |   +--rw config
    |     | +--rw interface? string
    |     | +--rw mode      ipi-port-breakout-types:port_breakout_mode_t
    |     | +--rw serdes?   ipi-port-breakout-types:port_breakout_serdes_type_t
    |     +--ro state
    |       +--ro interface? string
    |       +--ro mode      ipi-port-breakout-types:port_breakout_mode_t
    |       +--ro serdes?   ipi-port-breakout-types:port_breakout_serdes_type_t
    |       +--ro block?    uint8
  +--rw groups-speed
    | +--rw group-speed* [port-group] {feature-list:NOT_HAVE_DUNE}?
    |   +--rw port-group  -> ../config/port-group
    |   +--rw config
    |     | +--rw port-group? uint8

```

```

| | +--rw speed      ipi-port-breakout-types:port_breakout_group_speed_t
| +--ro state
|   +--ro port-group? uint8
|   +--ro speed      ipi-port-breakout-types:port_breakout_group_speed_t
|   +--ro ports*    uint8
+--rw interfaces
  +--rw interface* [name]
    +--rw name      -> ../config/name
    +--rw config
      | +--rw name?  -> /ipi-interface:interfaces/interface/name
      | +--rw mode? ipi-port-breakout-types:port_breakout_if_mode_t
      +--ro state
        +--ro name? -> /ipi-interface:interfaces/interface/name
        +--ro mode? ipi-port-breakout-types:port_breakout_if_mode_t

```

---

## module: ipi-port-mirror

```

+--rw port-mirror
  +--rw sessions
    | +--rw session* [id] {feature-list:HAVE_ADVANCE_MIRROR}?
    |   +--rw id      -> ../config/id
    |   +--rw config
    |     | +--rw id?    uint32
    |     | +--rw type   ipi-port-mirror-types:pmirror_sess_type_t
    |     | +--rw enabled? empty
    |     | +--rw description? cml-data-types:cml_line_t
    |     | +--rw source-vlan? cml-data-types:cml_range_t
    |     +--ro state
    |       | +--ro counters
    |       | | +--ro filter-count? yang:counter32
    |       | | +--ro tx-source-count? yang:counter32
    |       | +--ro id?    uint32
    |       | +--ro type   ipi-port-mirror-types:pmirror_sess_type_t
    |       | +--ro enabled? empty
    |       | +--ro description? cml-data-types:cml_line_t

```

```
| | +--ro source-vlan?  cml-data-types:cml_range_t
| +--rw destination
| | +--rw local
| | | +--rw config
| | | | +--rw interface-name?  -> /ipi-interface:interfaces/interface/name
| | | +--ro state
| | | | +--ro interface-name?  -> /ipi-interface:interfaces/interface/name
| | +--rw remote
| | | +--rw config!
| | | | +--rw vlan-id          uint16
| | | | +--rw reflector-interface-name  -> /ipi-interface:interfaces/interface/name
| | | +--ro state
| | | | +--ro vlan-id          uint16
| | | | +--ro reflector-interface-name  -> /ipi-interface:interfaces/interface/name
| +--rw source-interfaces
| | +--rw source-interface* [name]
| | | +--rw name  -> ../config/name
| | | +--rw config!
| | | | +--rw name?    -> /ipi-interface:interfaces/interface/name
| | | | +--rw direction  ipi-port-mirror-types:pmirror_dir_t
| | | +--ro state
| | | | +--ro name?    -> /ipi-interface:interfaces/interface/name
| | | | +--ro direction  ipi-port-mirror-types:pmirror_dir_t
| +--rw session-filters
| | +--rw session-filter* [seq-id]
| | | +--rw seq-id  -> ../config/seq-id
| | | +--rw config
| | | | +--rw seq-id?  uint32
| | | +--ro state
| | | | +--ro seq-id?  uint32
| | +--rw filters
| | | +--rw config
| | | | +--rw (destination-mac-options)?
| | | | | +--:(host-mac)
| | | | | | +--rw destination-mac-address-host?  ipi-port-mirror-types:pmirror_mac_addr_t
| | | | | +--:(mac-with-mask)
```

```

|   | | +--rw destination-mac-address?    ipi-port-mirror-types:pmirror_mac_addr_t
|   | | +--rw destination-mac-mask?      ipi-port-mirror-types:pmirror_mac_addr_t
|   | +--rw frame-type?                  ipi-port-mirror-types:pmirror_ethertype_t
|   | +--rw arp-type?                    ipi-port-mirror-types:pmirror_arp_type_t
|   | +--rw sender-ip-address?           inet:ipv4-address
|   | +--rw target-ip-address?           inet:ipv4-address
|   | +--rw cos?                         uint8
|   | +--rw vlan?                        cml-data-types:cml_range_t
|   | +--rw inner-vlan?                  cml-data-types:cml_range_t {feature-list:NOT_HAVE_DUNE}?
|   | +--rw source-ipv4-address?         cml-data-types:cml_ipv4_addr_or_prefix_t
|   | +--rw destination-ipv4-address?    cml-data-types:cml_ipv4_addr_or_prefix_t
|   | +--rw source-ipv6-address?         cml-data-types:cml_ipv6_prefix_t
|   | +--rw destination-ipv6-address?    cml-data-types:cml_ipv6_prefix_t
|   | +--rw (source-mac-options)?
|   | | +--:(host-mac)
|   | | | +--rw source-mac-address-host?  ipi-port-mirror-types:pmirror_mac_addr_t
|   | | | +--:(mac-with-mask)
|   | | | +--rw source-mac-address?       ipi-port-mirror-types:pmirror_mac_addr_t
|   | | | +--rw source-mac-mask?         ipi-port-mirror-types:pmirror_mac_addr_t
|   +--ro state
|   | +--ro (destination-mac-options)?
|   | | +--:(host-mac)
|   | | | +--ro destination-mac-address-host? ipi-port-mirror-types:pmirror_mac_addr_t
|   | | | +--:(mac-with-mask)
|   | | | +--ro destination-mac-address?    ipi-port-mirror-types:pmirror_mac_addr_t
|   | | | +--ro destination-mac-mask?      ipi-port-mirror-types:pmirror_mac_addr_t
|   | +--ro frame-type?                    ipi-port-mirror-types:pmirror_ethertype_t
|   | +--ro arp-type?                      ipi-port-mirror-types:pmirror_arp_type_t
|   | +--ro sender-ip-address?             inet:ipv4-address
|   | +--ro target-ip-address?             inet:ipv4-address
|   | +--ro cos?                           uint8
|   | +--ro vlan?                          cml-data-types:cml_range_t
|   | +--ro inner-vlan?                    cml-data-types:cml_range_t {feature-list:NOT_HAVE_DUNE}?
|   | +--ro source-ipv4-address?           cml-data-types:cml_ipv4_addr_or_prefix_t
|   | +--ro destination-ipv4-address?     cml-data-types:cml_ipv4_addr_or_prefix_t
|   | +--ro source-ipv6-address?           cml-data-types:cml_ipv6_prefix_t

```

```

|      +--ro destination-ipv6-address?      cml-data-types:cml_ipv6_prefix_t
|      +--ro (source-mac-options)?
|      +--:(host-mac)
|      | +--ro source-mac-address-host?    ipi-port-mirror-types:pmirror_mac_addr_t
|      +--:(mac-with-mask)
|      +--ro source-mac-address?          ipi-port-mirror-types:pmirror_mac_addr_t
|      +--ro source-mac-mask?            ipi-port-mirror-types:pmirror_mac_addr_t
+--rw interfaces

```

---

## module: ipi-port-vlan

augment /ipi-interface:interfaces/ipi-interface:interface:

```

+--rw port-vlan
  +--rw global
    | +--rw config
    | | +--rw isolated-vlan-id?          cml-data-types:cml_range_t {feature-list:NOT_HAVE_SWFWDR}?
    | | +--rw cvlan-registration-table? -> /ipi-network-instance:network-instances/network-instance/ipi-bridge:bridge/
ipi-vlan:cvlan-registration-tables/cvlan-registration-table/config/table-name {feature-list:HAVE_PROVIDER_BRIDGE}?
    | +--ro state
    | +--ro isolated-vlan-id?          cml-data-types:cml_range_t {feature-list:NOT_HAVE_SWFWDR}?
    | +--ro cvlan-registration-table? -> /ipi-network-instance:network-instances/network-instance/ipi-bridge:bridge/
ipi-vlan:cvlan-registration-tables/cvlan-registration-table/config/table-name {feature-list:HAVE_PROVIDER_BRIDGE}?
    +--rw ennis
  +--rw switched-vlans
    | +--rw switched-vlan* [interface-mode]
    | +--rw interface-mode             -> ../config/interface-mode
    | +--rw config
    | | +--rw interface-mode?          ipi-port-vlan-types:port_vlan_switch_port_mode_t
    | | +--rw ingress-filter?          cml-data-types:cml_enable_disable_t {feature-list:NOT_HAVE_DUNE}?
    | | +--rw acceptable-frame-type?  ipi-port-vlan-types:port_vlan_frame_type_t
    | | +--rw disable-native-vlan?    empty
    | | +--rw remove-default-vlan?    empty
    | +--ro state
    | | +--ro interface-mode?          ipi-port-vlan-types:port_vlan_switch_port_mode_t

```

---

```

| | +--ro ingress-filter?      cml-data-types:cml_enable_disable_t {feature-list:NOT_HAVE_DUNE}?
| | +--ro acceptable-frame-type? ipi-port-vlan-types:port_vlan_frame_type_t
| | +--ro disable-native-vlan?  empty
| | +--ro remove-default-vlan?  empty
| +--rw vlans
| | +--rw config
| | | +--rw vlan-id?          uint16
| | | +--rw native-vlan-id?  uint16
| | +--ro state
| |   +--ro vlan-id?          uint16
| |   +--ro native-vlan-id?  uint16
| +--rw allowed-vlan
| | +--rw config
| | | +--rw allowed-vlan-id?      cml-data-types:cml_range_t
| | | +--rw egress-tagging-disabled-vlans? cml-data-types:cml_range_t
| | +--ro state
| |   +--ro allowed-vlan-id?      cml-data-types:cml_range_t
| |   +--ro egress-tagging-disabled-vlans? cml-data-types:cml_range_t
| +--rw ce-vlan-translations
| +--rw svlan-translations
| | +--rw svlan-translation* [original-svlan-id] {feature-list:HAVE_PROVIDER_BRIDGE}?
| |   +--rw original-svlan-id  -> ../config/original-svlan-id
| |   +--rw config
| | | +--rw translated-svlan-id?  uint16
| | | +--rw original-svlan-id?   uint16
| | | +--rw translated-cvlan-id?  uint16
| | | +--rw svlan-cos?           uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?
| | | +--rw svlan-cfi?          uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?
| | | +--rw cvlan-cos?          uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?
| | | +--rw cvlan-cfi?          uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?
| | +--ro state
| |   +--ro translated-svlan-id?  uint16
| |   +--ro original-svlan-id?   uint16
| |   +--ro translated-cvlan-id?  uint16
| |   +--ro svlan-cos?           uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?
| |   +--ro svlan-cfi?          uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?

```

---

```

| |   +--ro cvlan-cos?          uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?
| |   +--ro cvlan-cfi?         uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?
|   +--rw cvlan-svlan-translations
|     +--rw cvlan-svlan-translation* [cvlan-id svlan-id] {feature-list:HAVE_PROVIDER_BRIDGE}?
|       +--rw cvlan-id   -> ../config/cvlan-id
|       +--rw svlan-id   -> ../config/svlan-id
|       +--rw config
|         | +--rw cvlan-id?      uint16
|         | +--rw svlan-id?     uint16
|         | +--rw translated-cvlan-id? uint16
|         | +--rw translated-svlan-id  uint16
|         | +--rw svlan-cos?      uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?
|         | +--rw svlan-cfi?     uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?
|         | +--rw cvlan-cos?     uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?
|         | +--rw cvlan-cfi?     uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?
|         +--ro state
|           +--ro cvlan-id?      uint16
|           +--ro svlan-id?     uint16
|           +--ro translated-cvlan-id? uint16
|           +--ro translated-svlan-id  uint16
|           +--ro svlan-cos?     uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?
|           +--ro svlan-cfi?     uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?
|           +--ro cvlan-cos?     uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?
|           +--ro cvlan-cfi?     uint8 {feature-list:NOT_HAVE_DUNE,feature-list:NOT_HAVE_POND}?
+--rw port-security
| +--rw config!
| | +--rw mode          ipi-port-vlan-types:port_vlan_port_sec_mode_t
| | +--rw maximum-limit? uint16
| | +--rw logging?     empty
| +--ro state
| | +--ro mode          ipi-port-vlan-types:port_vlan_port_sec_mode_t
| | +--ro maximum-limit? uint16
| | +--ro logging?     empty
+--rw secure-mac {feature-list:HAVE_PROVIDER_BRIDGE}?
| +--rw default-vlan-mappings
| | +--rw default-vlan-mapping* [mac-address]

```

---

```
| | +--rw mac-address -> ../config/mac-address
| | +--rw config
| | | +--rw mac-address? cml-data-types:cml_mac_addr_t
| | | +--ro state
| | |   +--ro mac-address? cml-data-types:cml_mac_addr_t
| +--rw vlan-mappings
| | +--rw vlan-mapping* [mac-address]
| | | +--rw mac-address -> ../config/mac-address
| | | +--rw config
| | | | +--rw mac-address? cml-data-types:cml_mac_addr_t
| | | | +--rw cvlan-id* uint16
| | | | +--rw svlan-id* uint16
| | | | +--ro state
| | | |   +--ro mac-address? cml-data-types:cml_mac_addr_t
| | | |   +--ro cvlan-id* uint16
| | | |   +--ro svlan-id* uint16
| +--rw cvlan-svlan-mappings
| | +--rw cvlan-svlan-mapping* [mac-address cvlan-id svlan-id]
| | | +--rw mac-address -> ../config/mac-address
| | | +--rw cvlan-id -> ../config/cvlan-id
| | | +--rw svlan-id -> ../config/svlan-id
| | | +--rw config
| | | | +--rw mac-address? cml-data-types:cml_mac_addr_t
| | | | +--rw cvlan-id? uint16
| | | | +--rw svlan-id? uint16
| | | | +--ro state
| | | |   +--ro mac-address? cml-data-types:cml_mac_addr_t
| | | |   +--ro cvlan-id? uint16
| | | |   +--ro svlan-id? uint16
+--rw private-vlan {feature-list:HAVE_PVLAN}?
| +--rw config!
| | +--rw mode ipi-port-vlan-types:port_vlan_pvlan_mode_t
| | +--ro state
| | | +--ro mode ipi-port-vlan-types:port_vlan_pvlan_mode_t
| +--rw associations
| | +--rw association* [vlan-id]
```

```

|   +--rw vlan-id   -> ../config/vlan-id
|   +--rw config
|   |   +--rw vlan-id?           uint16
|   |   +--rw associate-vlan-id?  uint16
|   |   +--rw mapping-vlan-id?    cml-data-types:cml_range_t
|   |   +--rw association-trunk-vlan-id?  uint16
|   +--ro state
|   |   +--ro vlan-id?           uint16
|   |   +--ro associate-vlan-id?  uint16
|   |   +--ro mapping-vlan-id?    cml-data-types:cml_range_t
|   |   +--ro association-trunk-vlan-id?  uint16
+--rw oep-mappings
augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance/ipi-bridge:bridge:
+--rw vlan-static-fdb
+--rw entries
+--rw entry* [mac-address vlan-id]
+--rw mac-address   -> ../config/mac-address
+--rw vlan-id       -> ../config/vlan-id
+--rw config
| +--rw interface-name -> /ipi-interface:interfaces/interface/name
| +--rw mac-address?   cml-data-types:cml_mac_addr_t
| +--rw action         ipi-port-vlan-types:port_vlan_l2_fdb_action_t
| +--rw vlan-id?      uint16
+--ro state
+--ro interface-name -> /ipi-interface:interfaces/interface/name
+--ro mac-address?   cml-data-types:cml_mac_addr_t
+--ro action         ipi-port-vlan-types:port_vlan_l2_fdb_action_t
+--ro vlan-id?      uint16

```

---

## module: ipi-prefix-list

```

+--rw prefixes
+--rw prefix* [prefix-list-name prefix-list-type]
+--rw prefix-list-name -> ../config/prefix-list-name
+--rw prefix-list-type  -> ../config/prefix-list-type

```

```

+--rw config
| +--rw prefix-list-name? string
| +--rw prefix-list-type? ipi-prefix-list-types:prefix_list_type_t
| +--rw description? cml-data-types:cml_line_t
+--ro state
| +--ro prefix-list-name? string
| +--ro prefix-list-type? ipi-prefix-list-types:prefix_list_type_t
| +--ro description? cml-data-types:cml_line_t
+--rw prefix-entries
  +--rw prefix-entry* [sequence-id]
    +--rw sequence-id -> ../config/sequence-id
    +--rw config
      | +--rw sequence-id? uint32
    +--ro state
      | +--ro sequence-id? uint32
    +--rw ipv4
      | +--rw entry* [action prefix-addr]
      | +--rw action -> ../config/action
      | +--rw prefix-addr -> ../config/prefix-addr
      | +--rw config
      | | +--rw action? ipi-prefix-list-types:prefix_list_action_t
      | | +--rw minimum-prefix-length-match? uint8
      | | +--rw maximum-prefix-length-match? uint8
      | | +--rw prefix-addr? ipi-prefix-list-types:prefix_list_ipv4_network_t
      | | +--rw exact-prefix-length-match? uint8
      | +--ro state
      | +--ro action? ipi-prefix-list-types:prefix_list_action_t
      | +--ro minimum-prefix-length-match? uint8
      | +--ro maximum-prefix-length-match? uint8
      | +--ro prefix-addr? ipi-prefix-list-types:prefix_list_ipv4_network_t
      | +--ro exact-prefix-length-match? uint8
    +--rw ipv6 {feature-list:HAVE_IPV6}?
      +--rw entry* [action ipv6-prefix-addr] {feature-list:HAVE_IPV6}?
        +--rw action -> ../config/action
        +--rw ipv6-prefix-addr -> ../config/ipv6-prefix-addr
        +--rw config {feature-list:HAVE_IPV6}?

```

```

| +--rw ipv6-prefix-addr?          ipi-prefix-list-types:prefix_list_ipv6_network_t
| +--rw action?                   ipi-prefix-list-types:prefix_list_action_t
| +--rw minimum-prefix-length-match? uint8
| +--rw maximum-prefix-length-match? uint8
+--ro state {feature-list:HAVE_IPV6}?
  +--ro ipv6-prefix-addr?          ipi-prefix-list-types:prefix_list_ipv6_network_t
  +--ro action?                   ipi-prefix-list-types:prefix_list_action_t
  +--ro minimum-prefix-length-match? uint8
  +--ro maximum-prefix-length-match? uint8

```

rpcs:

```

+---x clear-prefix-list-all
+---x clear-prefix-list-ipv6-all
+---x clear-ipv4-prefix-list
| +---w input
|   +---w prefix-list-name  string
|   +---w prefix?          cml-data-types:cml_ipv4_addr_prefix_t
+---x clear-ipv6-prefix-list {feature-list:HAVE_IPV6}?
  +---w input
  +---w prefix-list-name  string
  +---w prefix?          cml-data-types:cml_ipv6_prefix_t

```

---

## module: ipi-ptp

```

+--rw ptp {feature-list:HAVE_PTP_HW_OFFLOAD}?
  +--rw ptp-instances
  | +--rw ptp-instance* [instance-type]
  |   +--rw instance-type    -> ../config/instance-type
  |   +--rw config
  |     | +--rw instance-type? uint8
  |     | +--rw profile      ipi-ptp-types:ptp_profile_t
  |     +--rw tlvs {feature-list:HAVE_PTP_HW_OFFLOAD_CUSTOM1}?
  |       | +--rw config
  |       | | +--rw color-frame? empty

```

---

```

| | | +--rw drop-frame?  empty
| | | +--rw numerator?   uint32
| | | +--rw denominator? uint32
| | +--ro state
| |   +--ro color-frame?  empty
| |   +--ro drop-frame?  empty
| |   +--ro numerator?   uint32
| |   +--ro denominator? uint32
| +--rw default-data-set {feature-list:HAVE_DUNE_OR_HAVE_MARVELL}?
| | +--rw config
| | | +--rw l2-pkt-forward?      empty
| | | +--rw domain?             uint8
| | | +--rw servo-config?       ipi-ptp-types:ptp_servo_config_type_t
| | | +--rw external-clock-holdover-duration? uint16
| | | +--rw system-clock-sync?  uint16
| | | +--rw ptp-clock-sync?     empty
| | | +--rw ptsf-wtr-duration?  uint16
| | | +--rw g8265p1-wtr-duration? uint64
| | | +--rw g8265p1-option?     ipi-ptp-types:ptp_g8265p1_option_type_t
| | | +--rw reserved-vlan-base? uint16
| | | +--rw two-step?           empty {feature-
list:HAVE_PTP_HW_OFFLOAD_CUSTOM1_OR_HAVE_PTP_HW_OFFLOAD_CUSTOM2}?
| | | +--rw clock-type-tgm?     ipi-ptp-types:ptp_clock_type_tgm_t
| | | +--rw one-way?            empty
| | | +--rw number-ports?       uint8
| | | +--rw pps-pulse-offset?   int16
| | | +--rw pps-in-smx-tod-type? ipi-ptp-types:ptp_1pss_in_smx_tod_type_t
| | | +--rw priority-1?         uint8
| | | +--rw priority-2?         uint8
| | | +--rw slave-only?         empty
| | | +--rw local-priority?     uint8
| | | +--rw max-steps-removed?  uint8
| | | +--rw start-boundary-hops? uint8
| | +--ro state
| | | +--ro l2-pkt-forward?     empty
| | | +--ro domain?            uint8
| | | +--ro servo-config?      ipi-ptp-types:ptp_servo_config_type_t

```

---

---

```

| | | +--ro external-clock-holdover-duration? uint16
| | | +--ro system-clock-sync?          uint16
| | | +--ro ptp-clock-sync?             empty
| | | +--ro ptsf-wtr-duration?          uint16
| | | +--ro g8265p1-wtr-duration?       uint64
| | | +--ro g8265p1-option?             ipi-ptp-types:ptp_g8265p1_option_type_t
| | | +--ro reserved-vlan-base?         uint16
| | | +--ro two-step?                   empty {feature-
list:HAVE_PTP_HW_OFFLOAD_CUSTOM1_OR_HAVE_PTP_HW_OFFLOAD_CUSTOM2}?
| | | +--ro clock-type-tgm?             ipi-ptp-types:ptp_clock_type_tgm_t
| | | +--ro one-way?                   empty
| | | +--ro number-ports?               uint8
| | | +--ro pps-pulse-offset?           int16
| | | +--ro pps-in-smx-tod-type?        ipi-ptp-types:ptp_1pss_in_smx_tod_type_t
| | | +--ro priority-1?                 uint8
| | | +--ro priority-2?                 uint8
| | | +--ro slave-only?                 empty
| | | +--ro local-priority?             uint8
| | | +--ro max-steps-removed?          uint8
| | | +--ro start-boundary-hops?        uint8
| | | +--ro clock-identity?             string
| | +--rw servo-history
| | | +--rw config!
| | | | +--rw servo-history-enabled     empty
| | | | +--rw servo-history-interval   uint8
| | | +--ro state
| | | | +--ro servo-history-enabled     empty
| | | | +--ro servo-history-interval   uint8
| | +--rw clock-quality
| | | +--rw config
| | | | +--rw clock-class?              uint8
| | | | +--rw clock-accuracy?           uint8
| | | | +--rw offset-scaled-log-variance? uint16
| | | +--ro state
| | | | +--ro clock-class?              uint8
| | | | +--ro clock-accuracy?           uint8
| | | | +--ro offset-scaled-log-variance? uint16

```

---

```

| | +--rw gps-offset
| |   +--rw config!
| |     +--rw offset-seconds      int8
| |     +--rw offset-nano-seconds int16
| |   +--ro state
| |     +--ro offset-seconds      int8
| |     +--ro offset-nano-seconds int16
| +--rw ports {feature-list:HAVE_DUNE_OR_HAVE_MARVELL}?
| | +--rw port* [port-number]
| |   +--rw port-number          -> ../config/port-number
| |   +--rw config
| |     +--rw port-number?       uint16
| |     +--rw local-priority?    uint8
| |     +--rw description?       cml-data-types:cml_line_t
| |     +--rw transport-type?    ipi-ntp-types:ntp_encap_type_t
| |     +--rw transport-v6-multicast-type? ipi-ntp-types:ntp_v6_multicast_type_t
| |     +--rw non-forwardable-mac-addr? empty
| |     +--rw log-min-delay-req-interval? int8
| |     +--rw log-announce-interval? int8
| |     +--rw announce-receipt-timeout? uint8
| |     +--rw log-sync-interval? int8
| |     +--rw time-to-live?      uint8
| |     +--rw ip-dscp?           uint8
| |     +--rw unicast-grant-duration? uint16
| |     +--rw delay-mechanism?   ipi-ntp-types:ntp_delay_mechanism_t
| |     +--rw version-number?    int8
| |     +--rw master-only?       empty
| |     +--rw grandmaster-priority-2? uint8
| |     +--rw append?            empty {feature-list:HAVE_PTP_HW_OFFLOAD_CUSTOM1}?
| |     +--rw process?           empty {feature-list:HAVE_PTP_HW_OFFLOAD_CUSTOM1}?
| |     +--rw source-ipv6-link-local-address? empty {feature-list:HAVE_IPV6}?
| |     +--rw source-ipv6-interface-address? string {feature-list:HAVE_IPV6}?
| |     +--rw source-ipv4-interface-address? string
| |     +--rw source-ipv6-address? inet:ipv6-address {feature-list:HAVE_IPV6}?
| |     +--rw source-ipv4-address? inet:ipv4-address
| |   +--ro state

```

---

```
| | | +--ro port-number?          uint16
| | | +--ro local-priority?       uint8
| | | +--ro description?         cml-data-types:cml_line_t
| | | +--ro transport-type?      ipi-ptp-types:ptp_encap_type_t
| | | +--ro transport-v6-multicast-type? ipi-ptp-types:ptp_v6_multicast_type_t
| | | +--ro non-forwardable-mac-addr? empty
| | | +--ro log-min-delay-req-interval? int8
| | | +--ro log-announce-interval? int8
| | | +--ro announce-receipt-timeout? uint8
| | | +--ro log-sync-interval?    int8
| | | +--ro time-to-live?        uint8
| | | +--ro ip-dscp?             uint8
| | | +--ro unicast-grant-duration? uint16
| | | +--ro delay-mechanism?     ipi-ptp-types:ptp_delay_mechanism_t
| | | +--ro version-number?      int8
| | | +--ro master-only?        empty
| | | +--ro grandmaster-priority-2? uint8
| | | +--ro append?             empty {feature-list:HAVE_PTP_HW_OFFLOAD_CUSTOM1}?
| | | +--ro process?            empty {feature-list:HAVE_PTP_HW_OFFLOAD_CUSTOM1}?
| | | +--ro port-state?         ipi-ptp-types:ptp_port_state_t
| | | +--ro peer-mean-path-delay? ipi-ptp-types:ptp_time_interval_t
| | | +--ro signal-fail?        boolean
| | | +--ro port-identity?       string
| | +--rw clock-quality
| | | +--rw config
| | | | +--rw clock-class?       uint8
| | | | +--rw clock-accuracy?    uint8
| | | | +--rw offset-scaled-log-variance? uint16
| | | +--ro state
| | |   +--ro clock-class?       uint8
| | |   +--ro clock-accuracy?    uint8
| | |   +--ro offset-scaled-log-variance? uint16
| | +--rw asymmetry-delay
| | | +--rw config!
| | | | +--rw delay-asymmetry-msec int8
| | | | +--rw delay-asymmetry-nsec int32
```

---

```
| | | +--ro state
| | |   +--ro delay-asymmetry-msec  int8
| | |   +--ro delay-asymmetry-nsec  int32
| | +--rw network-interfaces
| | | +--rw network-interface* [network-interface]
| | |   +--rw network-interface  -> ../config/network-interface
| | |   +--rw config
| | |     | +--rw network-interface?      ipi-ptp-types:ptp_network_interface_t
| | |     | +--rw vlan-physical-interface-name?  cml-data-types:cml_ifname_t
| | |     | +--rw vlan-physical-dot1q-vlan-id?  uint16
| | |     | +--rw dot1q-vlan-id?              uint16
| | |     | +--rw dot1ad-vlan-id?             uint16
| | |     | +--rw inner-dot1q-vlan-id?        uint16
| | |     +--ro state
| | |       +--ro network-interface?      ipi-ptp-types:ptp_network_interface_t
| | |       +--ro vlan-physical-interface-name?  cml-data-types:cml_ifname_t
| | |       +--ro vlan-physical-dot1q-vlan-id?  uint16
| | |       +--ro dot1q-vlan-id?            uint16
| | |       +--ro dot1ad-vlan-id?           uint16
| | |       +--ro inner-dot1q-vlan-id?       uint16
| | +--rw master-ipv4-addresses
| | | +--rw master-ipv4-address* [master-clock-source-ipv4-address]
| | |   +--rw master-clock-source-ipv4-address  -> ../config/master-clock-source-ipv4-address
| | |   +--rw config
| | |     | +--rw master-clock-source-ipv4-address?  inet:ipv4-address
| | |     | +--rw master-ipv4-address-priority?    uint8
| | |     +--ro state
| | |       +--ro master-clock-source-ipv4-address?  inet:ipv4-address
| | |       +--ro master-ipv4-address-priority?    uint8
| | +--rw master-ipv6-addresses
| | | +--rw master-ipv6-address* [master-clock-source-ipv6-address]
| | |   +--rw master-clock-source-ipv6-address  -> ../config/master-clock-source-ipv6-address
| | |   +--rw config
| | |     | +--rw master-clock-source-ipv6-address?  inet:ipv6-address
| | |     | +--rw master-ipv6-address-priority?    uint8
| | |     +--ro state
```

---

```
| | |   +--ro master-clock-source-ipv6-address?  inet:ipv6-address
| | |   +--ro master-ipv6-address-priority?     uint8
| |   +--rw statistics
| | |   +--ro state
| | |     +--ro packets-transmitted?  yang:counter32
| | |     +--ro packets-received?    yang:counter32
| | |     +--ro packets-discarded?   yang:counter32
| |   +--ro foreign-data-sets
| | |   +--ro foreign-data-set* [foreign-master-id]
| | |     +--ro foreign-master-id  -> ../state/foreign-master-id
| | |     +--ro state
| | |       +--ro foreign-master-id?    uint8
| | |       +--ro current?              boolean
| | |       +--ro ipv4-address?         inet:ipv4-address
| | |       +--ro ipv6-address?        inet:ipv6-address {feature-list:HAVE_IPV6}?
| | |       +--ro l2-address?          yang:mac-address
| | |       +--ro clock-identity?      string
| | |       +--ro port-id?             string
| | |       +--ro clock-class?         uint8
| | |       +--ro clock-accuracy?      uint8
| | |       +--ro offset-scaled-log-variance?  uint16
| | |       +--ro priority-1?         uint8
| | |       +--ro priority-2?         uint8
| | |       +--ro steps-removed?      uint16
| | |       +--ro pdv-scaled-allan-variance?  uint64
| |   +--ro peer-data-sets
| | |   +--ro peer-data-set* [peer-id]
| | |     +--ro peer-id  -> ../state/peer-id
| | |     +--ro state
| | |       +--ro peer-id?            uint8
| | |       +--ro ipv4-address?      inet:ipv4-address
| | |       +--ro ipv6-address?      inet:ipv6-address {feature-list:HAVE_IPV6}?
| | |       +--ro l2-address?        yang:mac-address
| | |       +--ro clock-identity?    string
| | |       +--ro received-announce? yang:counter64
| | |       +--ro received-sync?     yang:counter64
```

---

```
| | | +--ro received-followup? yang:counter64
| | | +--ro received-reject? yang:counter64
| | | +--ro received-delay-request? yang:counter64
| | | +--ro received-delay-response? yang:counter64
| | | +--ro received-management? yang:counter64
| | | +--ro received-signaling? yang:counter64
| | | +--ro transmitted-announce? yang:counter64
| | | +--ro transmitted-sync? yang:counter64
| | | +--ro transmitted-followup? yang:counter64
| | | +--ro transmitted-delay-request? yang:counter64
| | | +--ro transmitted-delay-response? yang:counter64
| | | +--ro transmitted-management? yang:counter64
| | | +--ro transmitted-signaling? yang:counter64
| | +--ro master-data-sets
| | | +--ro master-data-set* [master-id]
| | | +--ro master-id -> ../state/master-id
| | | +--ro state
| | | +--ro master-id? uint8
| | | +--ro ipv4-address? inet:ipv4-address
| | | +--ro ipv6-address? inet:ipv6-address {feature-list:HAVE_IPV6}?
| | +--ro slave-data-sets
| | | +--ro slave-data-set* [slave-id]
| | | +--ro slave-id -> ../state/slave-id
| | | +--ro state
| | | +--ro slave-id? uint8
| | | +--ro ipv4-address? inet:ipv4-address
| | | +--ro ipv6-address? inet:ipv6-address {feature-list:HAVE_IPV6}?
| | | +--ro clock-identity? string
| | | +--ro delay-mechanism? ipi-ptp-types:ptp_delay_mechanism_t
| | | +--ro log-announce-interval? int8
| | | +--ro log-sync-interval? int8
| | | +--ro log-delay-request-interval? int8
| | +--rw drop-counters
| | +--ro state
| | +--ro domain-mismatch? yang:counter32
| | +--ro memory-alloc-failure? yang:counter32
```

---

```

| |   +--ro pkt-len-too-short?          yang:counter32
| |   +--ro pkt-rcvd-on-bad-port-state? yang:counter32
| |   +--ro pkt-profile-mismatch?      yang:counter32
| |   +--ro clock-port-mismatch?      yang:counter32
| |   +--ro ptp-packet-parsing-failure? yang:counter32
| |   +--ro delreq-from-unknown-slave? yang:counter32
| |   +--ro announce-on-master-only-port? yang:counter32
| |   +--ro invalid-steps-removed-field? yang:counter32
| |   +--ro unknown-unicast-master?    yang:counter32
| |   +--ro announce-on-gps-ntp-port?  yang:counter32
| |   +--ro sync-rcvd-invalid?        yang:counter32
| |   +--ro sync-rcvd-without-master?  yang:counter32
| +--rw time-of-day {feature-list:HAVE_DUNE_OR_HAVE_MARVELL}?
| | +--rw config
| | | +--rw io-type? ipi-ptp-types:ptp_clock_io_type_t
| | | +--ro state
| | |   +--ro io-type? ipi-ptp-types:ptp_clock_io_type_t
| +--rw ptp-servo {feature-list:HAVE_DUNE_OR_HAVE_MARVELL}?
| | +--ro state
| | | +--ro config-state? ipi-ptp-types:ptp_config_state_t
| | | +--ro servo-config? string {feature-list:HAVE_PTP_HW_OFFLOAD_CUSTOM1}?
| | | +--ro previous-state? ipi-ptp-types:ptp_servo_state_t
| | | +--ro current-state? ipi-ptp-types:ptp_servo_state_t
| | |   +--ro previous-servo-state? ipi-ptp-types:ptp_servo_state_custom_t {feature-
list:HAVE_PTP_HW_OFFLOAD_CUSTOM1_OR_HAVE_PTP_HW_OFFLOAD_CUSTOM2}?
| | |   +--ro current-servo-state? ipi-ptp-types:ptp_servo_state_custom_t {feature-
list:HAVE_PTP_HW_OFFLOAD_CUSTOM1_OR_HAVE_PTP_HW_OFFLOAD_CUSTOM2}?
| | | +--ro duration?      string
| | | +--ro apts-mode?      ipi-ptp-types:ptp_servo_apts_mode_t
| | | +--ro freq-correction? decimal64
| | | +--ro phase-correction? decimal64
| | | +--ro mean-path-delay? ipi-ptp-types:ptp_time_interval_t
| | | +--ro apts-gps-to-ntp-offset? ipi-ptp-types:ptp_time_interval_t
| | | +--ro offset-from-master? decimal64
| | | +--ro sync-packet-rate? uint32
| | | +--ro delay-packet-rate? uint32
| +--rw current-data-set {feature-list:HAVE_DUNE_OR_HAVE_MARVELL}?

```

---

---

```
| | +--ro state
| |   +--ro steps-removed?          uint8
| |   +--ro offset-from-master?     ipi-ptp-types:ptp_time_interval_t
| |   +--ro offset-from-master-in-nsec? decimal64
| |   +--ro mean-path-delay?        ipi-ptp-types:ptp_time_interval_t
| +--rw parent-data-set {feature-list:HAVE_DUNE_OR_HAVE_MARVELL}?
| | +--ro state
| | | +--ro parent-stats-enabled?    boolean
| | | +--ro parent-offset-scaled-log-variance? uint16
| | | +--ro parent-phase-change-rate?  uint32
| | | +--ro grandmaster-identity?     ipi-ptp-types:ptp_clock_identity_t
| | | +--ro grandmaster-priority-1?   uint8
| | | +--ro grandmaster-priority-2?   uint8
| | | +--ro port-identity
| | | | +--ro clock-identity? string
| | | | +--ro port-number?   uint16
| | | +--ro grandmaster-clock-quality
| | | | +--ro clock-class?      uint8
| | | | +--ro clock-accuracy?   uint8
| | | | +--ro offset-scaled-log-variance? uint16
| | +--rw port-identity
| | | +--ro state
| | | | +--ro clock-identity? string
| | | | +--ro port-number?   uint16
| | +--rw grandmaster-clock-quality
| | | +--ro state
| | | | +--ro clock-class?      uint8
| | | | +--ro clock-accuracy?   uint8
| | | | +--ro offset-scaled-log-variance? uint16
| +--rw time-properties {feature-list:HAVE_DUNE_OR_HAVE_MARVELL}?
| | +--ro state
| | | +--ro current-utc-offset-valid? boolean
| | | +--ro current-utc-offset?     int16
| | | +--ro leap59?                  empty
| | | +--ro leap61?                  empty
| | | +--ro time-traceable?          empty
```

---

```
| | +--ro frequency-traceable?    empty
| | +--ro ptp-timescale?         empty
| | +--ro time-source?          ipi-ntp-types:ntp_time_source_t
| | +--ro ptp-time-of-day?      string
| +--rw statistics {feature-list:HAVE_DUNE_OR_HAVE_MARVELL}?
| | +--ro state
| | +--ro packets-transmitted?  yang:counter32
| | +--ro packets-received?    yang:counter32
| | +--ro packets-discarded?   yang:counter32
| | +--ro ipv4-packets-received? yang:counter32
| | +--ro ipv6-packets-received? yang:counter32 {feature-list:HAVE_IPV6}?
| | +--ro l2-packets-received?  yang:counter32
| | +--ro rx-queue-overflows?   yang:counter32
| +--ro servo-history-data {feature-list:HAVE_DUNE_OR_HAVE_MARVELL}?
| | +--ro servo-history-data-entry* [entry-id]
| | +--ro entry-id  -> ../state/entry-id
| | +--ro state
| |   +--ro entry-id?      uint8
| |   +--ro timestamp?    string
| |   +--ro phase-correction?  decimal64
| |   +--ro frequency-correction? decimal64
| +--rw utc-offset-dates
|   +--rw utc-offset-date* [utc-date]
|   | +--rw utc-date  -> ../config/utc-date
|   | +--rw config
|   | | +--rw utc-date?    string
|   | | +--rw offset-seconds  uint8
|   | | +--ro state
|   | | +--ro utc-date?    string
|   | | +--ro offset-seconds  uint8
|   +--rw baseline
|   +--rw config
|   | +--rw baseline-seconds?  uint8
|   +--ro state
|     +--ro baseline-seconds?  uint8
+--rw debug
```

---

---

```

| +--rw config
| | +--rw enable?  empty
| +--ro state
|   +--ro enable?      empty
|   +--ro terminal-debug-status?  cml-data-types:cml_on_off_t
+--rw interfaces
  +--rw interface* [interface-name]
    +--rw interface-name  -> ../config/interface-name
    +--rw config
    | +--rw interface-name?  -> /ipi-interface:interfaces/interface/name
    | +--rw hw-timestamp?    empty {feature-list:HAVE_DUNE}?
    +--ro state
      +--ro interface-name?  -> /ipi-interface:interfaces/interface/name
      +--ro hw-timestamp?    empty {feature-list:HAVE_DUNE}?

rpcs:
+---x ptp-clear-statistics {feature-list:HAVE_PTP_HW_OFFLOAD,feature-list:HAVE_PTPD,feature-
list:HAVE_DUNE_OR_HAVE_MARVELL}?
| +---w input
|   +---w clear-clock  uint8
+---x ptp-terminal-debug-on {feature-list:HAVE_PTP_HW_OFFLOAD,feature-list:HAVE_DUNE}?
+---x ptp-terminal-debug-off {feature-list:HAVE_PTP_HW_OFFLOAD,feature-list:HAVE_DUNE}?

notifications:
+---n ptp-servo-state-change-notify {feature-list:HAVE_PTP_HW_OFFLOAD,feature-list:HAVE_DUNE}?
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?    cml-data-types:cml_notif_class_t
| +--ro instance-type?  uint8
| +--ro previous-state? ipi-ptp-types:ptp_servo_state_t
| +--ro current-state?  ipi-ptp-types:ptp_servo_state_t
+---n ptp-servo-state-change-custom1-notify {feature-list:HAVE_DUNE,feature-
list:HAVE_PTP_HW_OFFLOAD_CUSTOM1_OR_HAVE_PTP_HW_OFFLOAD_CUSTOM2}?
  +--ro severity?      cml-data-types:cml_notif_severity_t
  +--ro eventClass?    cml-data-types:cml_notif_class_t
  +--ro instance-type?  uint8
  +--ro previous-servo-state?  ipi-ptp-types:ptp_servo_state_custom_t
  +--ro current-servo-state?  ipi-ptp-types:ptp_servo_state_custom_t

```

---

---

## module: ipi-qos-if

augment /ipi-qos:qos:

```
+--rw interfaces
  +--rw interface* [name]
    +--rw name          -> ../config/name
    +--rw config
      | +--rw name?      -> /ipi-interface:interfaces/interface/name
      | +--rw untagged-priority? uint8
      | +--rw trust-dscp?   empty
    +--ro state
      | +--ro name?      -> /ipi-interface:interfaces/interface/name
      | +--ro untagged-priority? uint8
      | +--ro trust-dscp?   empty
    +--rw remark
      | +--rw config
      | | +--rw cos?   ipi-qos-types:cml_remark_state_t
      | | +--rw dei?   ipi-qos-types:cml_remark_state_t {feature-list:NOT_HAVE_CUSTOM2_QOS}?
      | | +--rw dscp?   ipi-qos-types:cml_remark_state_t
      | +--ro state
      |   +--ro cos?   ipi-qos-types:cml_remark_state_t
      |   +--ro dei?   ipi-qos-types:cml_remark_state_t {feature-list:NOT_HAVE_CUSTOM2_QOS}?
      |   +--ro dscp?   ipi-qos-types:cml_remark_state_t
    +--rw traffic-shape
      | +--rw config!
      | | +--rw rate      uint64
      | | +--rw rate-unit ipi-qos-types:qos_shape_rate_unit_t
      | | +--rw burst-rate uint64 {feature-list:NOT_HAVE_CUSTOM2_QOS}?
      | +--ro state
      |   +--ro rate      uint64
      |   +--ro rate-unit ipi-qos-types:qos_shape_rate_unit_t
      |   +--ro burst-rate uint64 {feature-list:NOT_HAVE_CUSTOM2_QOS}?
    +--rw map-profile {feature-list:HAVE_QOS_MAPPING_PROFILE}?
      | +--rw config
```

---

```
| | +--rw cos-to-queue?      string
| | +--rw dscp-to-queue?    string
| | +--rw precedence-to-queue? string
| | +--rw queue-color-to-cos? string
| | +--rw queue-color-to-dscp? string {feature-list:HAVE_CUSTOM1_QOS_OR_HAVE_CUSTOM4_QOS}?
| | +--rw queue-to-precedence? string {feature-list:HAVE_CUSTOM1_QOS_OR_HAVE_CUSTOM4_QOS}?
| +--ro state
|   +--ro cos-to-queue?      string
|   +--ro dscp-to-queue?    string
|   +--ro precedence-to-queue? string
|   +--ro queue-color-to-cos? string
|   +--ro queue-color-to-dscp? string {feature-list:HAVE_CUSTOM1_QOS_OR_HAVE_CUSTOM4_QOS}?
|   +--ro queue-to-precedence? string {feature-list:HAVE_CUSTOM1_QOS_OR_HAVE_CUSTOM4_QOS}?
+--rw service-policy
  +--rw ingress
  | +--rw config
  | | +--rw type-qos-policy-map-name? string
  | +--ro state
  | | +--ro type-qos-policy-map-name? string
  | +--ro class-maps-level-1
  |   +--ro class-map-level-1* [class-map-name-level-1]
  |     +--ro class-map-name-level-1 -> ../state/class-map-name-level-1
  |     +--ro state
  |       | +--ro class-map-name-level-1? string
  |       | +--ro counters
  |         | +--ro matched-packets? yang:counter64
  |         | +--ro matched-octets? yang:counter64
  |         | +--ro transmitted-packets? yang:counter64
  |         | +--ro transmitted-octets? yang:counter64
  |         | +--ro dropped-packets? yang:counter64
  |         | +--ro dropped-octets? yang:counter64
  |     +--ro class-maps-level-2
  |       +--ro class-map-level-2* [class-map-name-level-2]
  |         +--ro class-map-name-level-2 -> ../state/class-map-name-level-2
  |         +--ro state
  |           | +--ro class-map-name-level-2? string
```

```

|         | +--ro counters
|         |   +--ro matched-packets?   yang:counter64
|         |   +--ro matched-octets?    yang:counter64
|         |   +--ro transmitted-packets? yang:counter64
|         |   +--ro transmitted-octets? yang:counter64
|         |   +--ro dropped-packets?   yang:counter64
|         |   +--ro dropped-octets?    yang:counter64
|         +--ro class-maps-level-3
|           +--ro class-map-level-3* [class-map-name-level-3]
|             +--ro class-map-name-level-3  -> ../state/class-map-name-level-3
|             +--ro state
|               +--ro class-map-name-level-3? string
|               +--ro counters
|                 +--ro matched-packets?   yang:counter64
|                 +--ro matched-octets?    yang:counter64
|                 +--ro transmitted-packets? yang:counter64
|                 +--ro transmitted-octets? yang:counter64
|                 +--ro dropped-packets?   yang:counter64
|                 +--ro dropped-octets?    yang:counter64
+--rw egress
  +--rw config
    | +--rw type-qos-policy-map-name?   string {feature-
list:HAVE_CUSTOM1_QOS_OR_HAVE_CUSTOM3_QOS_OR_HAVE_CUSTOM4_QOS}?
    | +--rw type-queuing-policy-map-name? string
    +--ro state
      | +--ro type-qos-policy-map-name?   string {feature-
list:HAVE_CUSTOM1_QOS_OR_HAVE_CUSTOM3_QOS_OR_HAVE_CUSTOM4_QOS}?
      | +--ro type-queuing-policy-map-name? string
      +--ro class-maps-level-1
        +--ro class-map-level-1* [class-map-name-level-1]
          +--ro class-map-name-level-1  -> ../state/class-map-name-level-1
          +--ro state
            | +--ro class-map-name-level-1? string
            | +--ro queues
            |   +--ro queue* [id]
            |     +--ro id      uint8
            |     +--ro counters

```

---

```
|   +--ro total-transmitted-packets?   yang:counter64
|   +--ro total-transmitted-octets?   yang:counter64
|   +--ro total-dropped-packets?     yang:counter64
|   +--ro total-dropped-octets?      yang:counter64
|   +--ro green-transmitted-packets?  yang:counter64
|   +--ro non-green-transmitted-packets? yang:counter64
|   +--ro green-dropped-packets?     yang:counter64
|   +--ro yellow-dropped-packets?    yang:counter64
|   +--ro red-dropped-packets?       yang:counter64
|   +--ro rate-kbps?                  decimal64
|   +--ro rate-mbps?                  decimal64
|   +--ro rate-gbps?                  decimal64
+--ro class-maps-level-2
  +--ro class-map-level-2* [class-map-name-level-2]
    +--ro class-map-name-level-2 -> ../state/class-map-name-level-2
    +--ro state
      | +--ro class-map-name-level-2? string
      | +--ro queues
      |   +--ro queue* [id]
      |     +--ro id      uint8
      |     +--ro counters
      |       +--ro total-transmitted-packets? yang:counter64
      |       +--ro total-transmitted-octets? yang:counter64
      |       +--ro total-dropped-packets?   yang:counter64
      |       +--ro total-dropped-octets?    yang:counter64
      |       +--ro green-transmitted-packets? yang:counter64
      |       +--ro non-green-transmitted-packets? yang:counter64
      |       +--ro green-dropped-packets?   yang:counter64
      |       +--ro yellow-dropped-packets?  yang:counter64
      |       +--ro red-dropped-packets?     yang:counter64
      |       +--ro rate-kbps?                decimal64
      |       +--ro rate-mbps?                decimal64
      |       +--ro rate-gbps?                decimal64
    +--ro class-maps-level-3
      +--ro class-map-level-3* [class-map-name-level-3]
        +--ro class-map-name-level-3 -> ../state/class-map-name-level-3
```

---

```

+--ro state
  +--ro class-map-name-level-3? string
  +--ro queues
    +--ro queue* [id]
      +--ro id      uint8
      +--ro counters
        +--ro total-transmitted-packets? yang:counter64
        +--ro total-transmitted-octets?  yang:counter64
        +--ro total-dropped-packets?    yang:counter64
        +--ro total-dropped-octets?     yang:counter64
        +--ro green-transmitted-packets? yang:counter64
        +--ro non-green-transmitted-packets? yang:counter64
        +--ro green-dropped-packets?    yang:counter64
        +--ro yellow-dropped-packets?   yang:counter64
        +--ro red-dropped-packets?      yang:counter64
        +--ro rate-kbps?                 decimal64
        +--ro rate-mbps?                 decimal64
        +--ro rate-gbps?                 decimal64

```

notifications:

```

+---n qos-subinterface-default-policy-add-notification
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro message?   string
+---n qos-subinterface-default-policy-delete-notification
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro message?   string
+---n qos-subinterface-traffic-shape-add-notification
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro message?   string
+---n qos-subinterface-traffic-shape-delete-notification
  +--ro severity?  cml-data-types:cml_notif_severity_t
  +--ro eventClass? cml-data-types:cml_notif_class_t
  +--ro message?   string

```

---

## module: ipi-qos

```

+--rw qos
  +--rw global
    +--rw config
      | +--rw enable-qos?  cml-data-types:cml_enable_disable_t
    +--ro state
      | +--ro enable-qos?  cml-data-types:cml_enable_disable_t
    +--rw map-profile {feature-list:HAVE_QOS_MAPPING_PROFILE}?
      | +--rw cos-to-queue-profiles
      | | +--rw cos-to-queue-profile* [name]
      | |   +--rw name          -> ../config/name
      | |   +--rw config
      | |     | +--rw name?  string
      | |     +--ro state
      | |     | +--ro name?  string
      | |     +--rw cos-dei-to-queues {feature-list:NOT_HAVE_CUSTOM2_QOS}?
      | |       +--rw cos-dei-to-queue* [cos-value dei-value]
      | |         +--rw cos-value  -> ../config/cos-value
      | |         +--rw dei-value  -> ../config/dei-value
      | |         +--rw config
      | |           | +--rw cos-value?  uint8
      | |           | +--rw dei-value?  ipi-qos-types:qos_dei_t
      | |           | +--rw queue-id   uint8
      | |           | +--rw color?    ipi-qos-types:qos_color_t
      | |           +--ro state
      | |             +--ro cos-value?  uint8
      | |             +--ro dei-value?  ipi-qos-types:qos_dei_t
      | |             +--ro queue-id   uint8
      | |             +--ro color?    ipi-qos-types:qos_color_t
      | +--rw dscp-to-queue-profiles
      | | +--rw dscp-to-queue-profile* [name]
      | |   +--rw name          -> ../config/name
      | |   +--rw config

```

```

| | | +--rw name? string
| | +--ro state
| | | +--ro name? string
| | +--rw dscp-to-queues
| |   +--rw dscp-to-queue* [dscp-value]
| |     +--rw dscp-value -> ../config/dscp-value
| |     +--rw config
| |       | +--rw dscp-value? uint8
| |       | +--rw queue-id uint8
| |       | +--rw color? ipi-qos-types:qos_color_t
| |     +--ro state
| |       +--ro dscp-value? uint8
| |       +--ro queue-id uint8
| |       +--ro color? ipi-qos-types:qos_color_t
| +--rw queue-color-to-cos-profiles
| | +--rw queue-color-to-cos-profile* [name]
| |   +--rw name -> ../config/name
| |   +--rw config
| |     | +--rw name? string
| |     +--ro state
| |     | +--ro name? string
| |   +--rw queue-color-to-coses
| |     +--rw queue-color-to-cos* [queue-id color]
| |       +--rw queue-id -> ../config/queue-id
| |       +--rw color -> ../config/color
| |       +--rw config
| |         | +--rw queue-id? uint8
| |         | +--rw color? ipi-qos-types:qos_color_key_t
| |         | +--rw cos-value uint8
| |       +--ro state
| |         +--ro queue-id? uint8
| |         +--ro color? ipi-qos-types:qos_color_key_t
| |         +--ro cos-value uint8
| +--rw queue-to-precedence-profiles {feature-list:HAVE_CUSTOM1_QOS_OR_HAVE_CUSTOM4_QOS}?
| | +--rw queue-to-precedence-profile* [name]
| |   +--rw name -> ../config/name

```

---

```
| | +--rw config
| | | +--rw name? string
| | +--ro state
| | | +--ro name? string
| | +--rw queue-to-precedences
| |   +--rw queue-to-precedence* [queue-id]
| |     +--rw queue-id -> ../config/queue-id
| |     +--rw config
| |       | +--rw queue-id? uint8
| |       | +--rw precedence-value uint8
| |       +--ro state
| |         +--ro queue-id? uint8
| |         +--ro precedence-value uint8
| +--rw precedence-to-queue-profiles
| | +--rw precedence-to-queue-profile* [name]
| |   +--rw name -> ../config/name
| |   +--rw config
| |     | +--rw name? string
| |     +--ro state
| |     | +--ro name? string
| |     +--rw precedence-to-queues
| |       +--rw precedence-to-queue* [precedence-value]
| |       +--rw precedence-value -> ../config/precedence-value
| |       +--rw config
| |         | +--rw precedence-value? uint8
| |         | +--rw queue-id uint8
| |         +--ro state
| |         +--ro precedence-value? uint8
| |         +--ro queue-id uint8
| +--rw queue-color-to-dscp-profiles
|   +--rw queue-color-to-dscp-profile* [name]
|     +--rw name -> ../config/name
|     +--rw config
|       | +--rw name? string
|       +--ro state
|       | +--ro name? string
```

---

```
|   +--rw queue-color-to-dscps
|   +--rw queue-color-to-dscp* [queue-id color]
|     +--rw queue-id   -> ../config/queue-id
|     +--rw color      -> ../config/color
|     +--rw config
|       | +--rw queue-id?   uint8
|       | +--rw color?     ipi-qos-types:qos_color_key_t
|       | +--rw dscp-value  uint8
|     +--ro state
|       +--ro queue-id?   uint8
|       +--ro color?     ipi-qos-types:qos_color_key_t
|       +--ro dscp-value  uint8
+--rw remark
| +--rw config
| | +--rw cos?   empty
| | +--rw dei?  empty {feature-list:HAVE_CUSTOM1_QOS_OR_HAVE_CUSTOM3_QOS}?
| | +--rw dscp? empty
| +--ro state
|   +--ro cos?   empty
|   +--ro dei?  empty {feature-list:HAVE_CUSTOM1_QOS_OR_HAVE_CUSTOM3_QOS}?
|   +--ro dscp? empty
+--ro class-maps-default
| +--ro class-map-default* [name]
|   +--ro name   -> ../state/name
|   +--ro state
|     +--ro name?      string
|     +--ro type?     ipi-qos-types:qos_class_map_default_t
|     +--ro match-criteria? ipi-qos-types:qos_match_criteria_t
+--rw class-maps
| +--rw class-map* [name]
|   +--rw name      -> ../config/name
|   +--rw config
|     | +--rw name?      string
|     | +--rw type      ipi-qos-types:qos_class_map_t
|     | +--rw match-criteria ipi-qos-types:qos_match_criteria_t
|     | +--rw reference-description? cml-data-types:cml_line_t
```

---

```

|  +--ro state
|  |  +--ro name?          string
|  |  +--ro type           ipi-qos-types:qos_class_map_t
|  |  +--ro match-criteria ipi-qos-types:qos_match_criteria_t
|  |  +--ro reference-description? cml-data-types:cml_line_t
|  +--rw match-any-conditions
|  |  +--rw config
|  |  |  +--rw access-control-list-name? string
|  |  |  +--rw ethertype*           string
|  |  |  +--rw traffic-type*       ipi-qos-types:qos_traffic_type_t
|  |  |  +--rw cos?               cml-data-types:cml_range_t
|  |  |  +--rw inner-cos?         cml-data-types:cml_range_t
|  |  |  +--rw vlan?             cml-data-types:cml_range_t
|  |  |  +--rw vlan-id?          uint16 {feature-list:HAVE_BROADCOM}?
|  |  |  +--rw inner-vlan?       cml-data-types:cml_range_t
|  |  |  +--rw inner-vlan-id?    uint16 {feature-list:HAVE_BROADCOM}?
|  |  |  +--rw rtp?             cml-data-types:cml_range_t
|  |  |  +--rw dscp?            cml-data-types:cml_range_t
|  |  |  +--rw precedence?       cml-data-types:cml_range_t
|  |  |  +--rw packet-protocol*   ipi-qos-types:qos_proto_type_t {feature-list:HAVE_CUSTOM1_QOS}?
|  |  |  +--rw source-mac*       ipi-qos-types:qos_mac_address_t {feature-list:HAVE_CUSTOM1_QOS}?
|  |  |  +--rw destination-mac*  ipi-qos-types:qos_mac_address_t {feature-list:HAVE_CUSTOM1_QOS}?
|  |  +--ro state
|  |  |  +--ro access-control-list-name? string
|  |  |  +--ro ethertype*       string
|  |  |  +--ro traffic-type*    ipi-qos-types:qos_traffic_type_t
|  |  |  +--ro cos?            cml-data-types:cml_range_t
|  |  |  +--ro inner-cos?      cml-data-types:cml_range_t
|  |  |  +--ro vlan?          cml-data-types:cml_range_t
|  |  |  +--ro vlan-id?       uint16 {feature-list:HAVE_BROADCOM}?
|  |  |  +--ro inner-vlan?    cml-data-types:cml_range_t
|  |  |  +--ro inner-vlan-id? uint16 {feature-list:HAVE_BROADCOM}?
|  |  |  +--ro rtp?          cml-data-types:cml_range_t
|  |  |  +--ro dscp?         cml-data-types:cml_range_t
|  |  |  +--ro precedence?    cml-data-types:cml_range_t
|  |  |  +--ro packet-protocol* ipi-qos-types:qos_proto_type_t {feature-list:HAVE_CUSTOM1_QOS}?

```

---

---

```

| | | +--ro source-mac*          ipi-qos-types:qos_mac_address_t {feature-list:HAVE_CUSTOM1_QOS}?
| | | +--ro destination-mac*     ipi-qos-types:qos_mac_address_t {feature-list:HAVE_CUSTOM1_QOS}?
| | +--rw ipv4
| | | +--rw layer4-match* [protocol port-type]
| | |   +--rw protocol   -> ../config/protocol
| | |   +--rw port-type  -> ../config/port-type
| | |   +--rw config
| | |     | +--rw protocol?  ipi-qos-types:qos_layer4_protocol_t
| | |     | +--rw port-type? ipi-qos-types:qos_layer4_port_t
| | |     | +--rw port      cml-data-types:cml_range_t
| | |     +--ro state
| | |       +--ro protocol?  ipi-qos-types:qos_layer4_protocol_t
| | |       +--ro port-type? ipi-qos-types:qos_layer4_port_t
| | |       +--ro port      cml-data-types:cml_range_t
| | +--rw ipv6
| +--rw match-all-conditions
|   +--rw config
|     | +--rw ethertype-all?  string
|     | +--rw traffic-type-all? ipi-qos-types:qos_traffic_type_t
|     | +--rw cos-all?        uint8
|     | +--rw inner-cos-all?  uint8
|     | +--rw vlan-all?       uint16
|     | +--rw inner-vlan-all? uint16
|     | +--rw rtp-all?        uint32
|     | +--rw dscp-all?       string
|     | +--rw precedence-all? string
|     | +--rw packet-protocol-all? ipi-qos-types:qos_proto_type_t {feature-list:HAVE_CUSTOM1_QOS}?
|     | +--rw source-mac-all?  ipi-qos-types:qos_mac_address_t {feature-list:HAVE_CUSTOM1_QOS}?
|     | +--rw destination-mac-all? ipi-qos-types:qos_mac_address_t {feature-list:HAVE_CUSTOM1_QOS}?
|     +--ro state
|       | +--ro ethertype-all?  string
|       | +--ro traffic-type-all? ipi-qos-types:qos_traffic_type_t
|       | +--ro cos-all?        uint8
|       | +--ro inner-cos-all?  uint8
|       | +--ro vlan-all?       uint16
|       | +--ro inner-vlan-all? uint16

```

---

---

```

| | +--ro rtp-all?          uint32
| | +--ro dscp-all?        string
| | +--ro precedence-all?  string
| | +--ro packet-protocol-all? ipi-qos-types:qos_proto_type_t {feature-list:HAVE_CUSTOM1_QOS}?
| | +--ro source-mac-all?   ipi-qos-types:qos_mac_address_t {feature-list:HAVE_CUSTOM1_QOS}?
| | +--ro destination-mac-all? ipi-qos-types:qos_mac_address_t {feature-list:HAVE_CUSTOM1_QOS}?
| +--rw layer4-matches-ipv4
|   +--rw layer4-match-ipv4* [protocol-all port-type-all port-all]
|     +--rw protocol-all  -> ../config/protocol-all
|     +--rw port-type-all  -> ../config/port-type-all
|     +--rw port-all      -> ../config/port-all
|     +--rw config
|       | +--rw protocol-all? ipi-qos-types:qos_layer4_protocol_t
|       | +--rw port-type-all? ipi-qos-types:qos_layer4_port_t
|       | +--rw port-all?     uint16
|       +--ro state
|         +--ro protocol-all? ipi-qos-types:qos_layer4_protocol_t
|         +--ro port-type-all? ipi-qos-types:qos_layer4_port_t
|         +--ro port-all?     uint16
+--rw class-maps-queuing
| +--rw class-map-queuing* [name]
|   +--rw name          -> ../config/name
|   +--rw config
|     | +--rw name?      string
|     | +--rw type       ipi-qos-types:qos_class_map_t
|     | +--rw reference-description? cml-data-types:cml_line_t
|     +--ro state
|       | +--ro name?    string
|       | +--ro type     ipi-qos-types:qos_class_map_t
|       | +--ro reference-description? cml-data-types:cml_line_t
|     +--rw match-conditions
|       +--rw config
|         | +--rw vlan-queue? uint16 {feature-list:NOT_HAVE_MARVELL}?
|         | +--rw cos?       cml-data-types:cml_range_t {feature-list:HAVE_CUSTOM1_QOS}?
|         | +--rw qos-group? uint32 {feature-list:HAVE_CUSTOM1_QOS}?
|         +--ro state

```

---

---

```

|     +--ro vlan-queue?  uint16 {feature-list:NOT_HAVE_MARVELL}?
|     +--ro cos?        cml-data-types:cml_range_t {feature-list:HAVE_CUSTOM1_QOS}?
|     +--ro qos-group?  uint32 {feature-list:HAVE_CUSTOM1_QOS}?
+--rw policy-maps
| +--rw policy-map* [policy-map-name]
|   +--rw policy-map-name  -> ../config/policy-map-name
|   +--rw config
|     | +--rw policy-map-name?    string
|     | +--rw type                ipi-qos-types:qos_policy_map_t
|     | +--rw reference-description? cml-data-types:cml_line_t
|     +--ro state
|       | +--ro policy-map-name?    string
|       | +--ro type                ipi-qos-types:qos_policy_map_t
|       | +--ro reference-description? cml-data-types:cml_line_t
|     +--rw classes
|       +--rw class* [class-map-name]
|         +--rw class-map-name  -> ../config/class-map-name
|         +--rw config
|           | +--rw class-map-name?    ipi-qos-types:qos_policy_map_class_t
|           | +--rw type                ipi-qos-types:qos_policy_map_t
|           | +--rw child-service-policy-name? -> /qos/global/policy-maps/policy-map/policy-map-name
|           | +--rw reference-description?    cml-data-types:cml_line_t
|           +--ro state
|             | +--ro class-map-name?    ipi-qos-types:qos_policy_map_class_t
|             | +--ro type                ipi-qos-types:qos_policy_map_t
|             | +--ro child-service-policy-name? -> /qos/global/policy-maps/policy-map/policy-map-name
|             | +--ro reference-description?    cml-data-types:cml_line_t
|           +--rw queue-mode
|             | +--rw config
|               | | +--rw lossless?          empty {feature-list:HAVE_CUSTOM1_QOS}?
|               | | +--rw weighted-round-robin-queue-weight?  uint8 {feature-list:NOT_HAVE_CUSTOM2_QOS}?
|               | | +--rw strict-priority-enabled?            empty {feature-list:NOT_HAVE_CUSTOM2_QOS}?
|               | +--ro state
|               | | +--ro lossless?          empty {feature-list:HAVE_CUSTOM1_QOS}?
|               | | +--ro weighted-round-robin-queue-weight?  uint8 {feature-list:NOT_HAVE_CUSTOM2_QOS}?
|               | | +--ro strict-priority-enabled?            empty {feature-list:NOT_HAVE_CUSTOM2_QOS}?

```

---

```

|   | +--rw red
|   | | +--rw config
|   | | | +--rw weight?  uint8
|   | | +--ro state
|   | | | +--ro weight?  uint8
|   | | +--rw wred {feature-list:HAVE_CUSTOM1_QOS_OR_HAVE_CUSTOM4_QOS}?
|   | | | +--rw config
|   | | | | +--rw min-threshold?          uint32
|   | | | | +--rw threshold-unit?        ipi-qos-types:qos_threshold_t
|   | | | | +--rw max-threshold?          uint32
|   | | | | +--rw drop-probability?       uint8
|   | | | | +--rw min-threshold-yellow?   uint32
|   | | | | +--rw max-threshold-yellow?   uint32
|   | | | | +--rw drop-probability-yellow? uint8
|   | | | | +--rw min-threshold-red?      uint32
|   | | | | +--rw max-threshold-red?      uint32
|   | | | | +--rw drop-probability-red?   uint8
|   | | | | +--rw explicit-congestion-notification? empty
|   | | | +--ro state
|   | | | | +--ro min-threshold?          uint32
|   | | | | +--ro threshold-unit?        ipi-qos-types:qos_threshold_t
|   | | | | +--ro max-threshold?          uint32
|   | | | | +--ro drop-probability?       uint8
|   | | | | +--ro min-threshold-yellow?   uint32
|   | | | | +--ro max-threshold-yellow?   uint32
|   | | | | +--ro drop-probability-yellow? uint8
|   | | | | +--ro min-threshold-red?      uint32
|   | | | | +--ro max-threshold-red?      uint32
|   | | | | +--ro drop-probability-red?   uint8
|   | | | +--ro explicit-congestion-notification? empty
|   | | +--rw tail-drops
|   | | | +--rw tail-drop* [max-threshold max-threshold-type]
|   | | | | +--rw max-threshold    -> ../config/max-threshold
|   | | | | +--rw max-threshold-type -> ../config/max-threshold-type
|   | | | | +--rw config
|   | | | | | +--rw max-threshold?  uint32

```

```

|   | | | +--rw max-threshold-type? ipi-qos-types:qos_threshold_t
|   | | +--ro state
|   | |   +--ro max-threshold? uint32
|   | |   +--ro max-threshold-type? ipi-qos-types:qos_threshold_t
|   | +--rw bandwidths {feature-list:NOT_HAVE_CUSTOM2_QOS}?
|   | | +--rw bandwidth* [rate-value rate-type]
|   | |   +--rw rate-value -> ../config/rate-value
|   | |   +--rw rate-type -> ../config/rate-type
|   | |   +--rw config
|   | | | +--rw rate-value? uint32
|   | | | +--rw rate-type? ipi-qos-types:qos_shape_rate_unit_extended_t
|   | | +--ro state
|   | |   +--ro rate-value? uint32
|   | |   +--ro rate-type? ipi-qos-types:qos_shape_rate_unit_extended_t
|   | +--rw shapes
|   | | +--rw shape* [rate-value rate-unit]
|   | |   +--rw rate-value -> ../config/rate-value
|   | |   +--rw rate-unit -> ../config/rate-unit
|   | |   +--rw config
|   | | | +--rw rate-value? uint32
|   | | | +--rw rate-unit? ipi-qos-types:qos_shape_rate_unit_extended_t
|   | | +--ro state
|   | |   +--ro rate-value? uint32
|   | |   +--ro rate-unit? ipi-qos-types:qos_shape_rate_unit_extended_t
|   +--rw qos-mode
|   | +--rw config
|   | | +--rw priority? uint16
|   | | +--rw (set-option)?
|   | | | +--:(port-action)
|   | | | +--:(precedence)
|   | | | | +--rw precedence-remark? string
|   | | | +--:(bridge-precedence)
|   | | | +--:(cos)
|   | | | | +--rw cos-value? uint8
|   | | | +--:(bridge-cos)
|   | | | | +--rw cos-remark-only-bridged? uint8 {feature-list:HAVE_CUSTOM1_QOS}?

```

```

|   |   +--:(dscp)
|   |   |   +--rw dscp-value-remark?      string
|   |   +--:(bridge-dscp)
|   |   |   +--rw dscp-remark-only-bridged? string {feature-list:HAVE_CUSTOM1_QOS}?
|   |   +--:(queue)
|   |   |   +--rw queue-id?                uint8
|   |   +--:(bridge-queue)
|   |   |   +--rw queue-remark-only-bridged? uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|   |   +--:(qos-group)
|   |   |   +--rw qos-group?                uint16 {feature-list:HAVE_CUSTOM1_QOS}?
|   +--ro state
|   |   +--ro priority?                    uint16
|   |   +--ro (set-option)?
|   |   |   +--:(port-action)
|   |   |   +--:(precedence)
|   |   |   |   +--ro precedence-remark?    string
|   |   |   +--:(bridge-precedence)
|   |   |   +--:(cos)
|   |   |   |   +--ro cos-value?            uint8
|   |   |   +--:(bridge-cos)
|   |   |   |   +--ro cos-remark-only-bridged? uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|   |   |   +--:(dscp)
|   |   |   |   +--ro dscp-value-remark?    string
|   |   |   +--:(bridge-dscp)
|   |   |   |   +--ro dscp-remark-only-bridged? string {feature-list:HAVE_CUSTOM1_QOS}?
|   |   |   +--:(queue)
|   |   |   |   +--ro queue-id?            uint8
|   |   |   +--:(bridge-queue)
|   |   |   |   +--ro queue-remark-only-bridged? uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|   |   |   +--:(qos-group)
|   |   |   |   +--ro qos-group?            uint16 {feature-list:HAVE_CUSTOM1_QOS}?
|   +--rw police
|   |   +--rw config
|   |   |   +--rw type?                    ipi-qos-types:qos_police_t
|   |   |   +--rw cir?                    uint64
|   |   |   +--rw cir-unit?               ipi-qos-types:qos_rate_unit_t

```

---

```

|         | +--rw bc?           uint64
|         | +--rw bc-unit?      ipi-qos-types:qos_burst_rate_unit_t
|         | +--rw pir?         uint64 {feature-list:HAVE_CUSTOM1_QOS_OR_HAVE_CUSTOM4_QOS}?
|         | +--rw pir-unit?    ipi-qos-types:qos_rate_unit_t {feature-
list:HAVE_CUSTOM1_QOS_OR_HAVE_CUSTOM4_QOS}?
|         | +--rw be?         uint32
|         | +--rw be-unit?     ipi-qos-types:qos_burst_rate_unit_t
|         | +--rw set-conform-action? ipi-qos-types:qos_conform_action_t {feature-
list:HAVE_CUSTOM1_QOS}?
|         | +--rw conform-cos?  uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|         | +--rw conform-dscp?  uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|         | +--rw conform-precedence? uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|         | +--rw set-exceed-action? ipi-qos-types:qos_exceed_action_t {feature-list:HAVE_CUSTOM1_QOS}?
|         | +--rw exceed-cos?    uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|         | +--rw exceed-dscp?   uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|         | +--rw set-violate-action? ipi-qos-types:qos_violate_action_t {feature-list:HAVE_CUSTOM1_QOS}?
|         | +--rw violate-cos?   uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|         | +--rw violate-dscp?  uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|         +--ro state
|           +--ro type?         ipi-qos-types:qos_police_t
|           +--ro cir?         uint64
|           +--ro cir-unit?    ipi-qos-types:qos_rate_unit_t
|           +--ro bc?         uint64
|           +--ro bc-unit?     ipi-qos-types:qos_burst_rate_unit_t
|           +--ro pir?         uint64 {feature-list:HAVE_CUSTOM1_QOS_OR_HAVE_CUSTOM4_QOS}?
|           +--ro pir-unit?    ipi-qos-types:qos_rate_unit_t {feature-
list:HAVE_CUSTOM1_QOS_OR_HAVE_CUSTOM4_QOS}?
|           +--ro be?         uint32
|           +--ro be-unit?     ipi-qos-types:qos_burst_rate_unit_t
|           +--ro set-conform-action? ipi-qos-types:qos_conform_action_t {feature-
list:HAVE_CUSTOM1_QOS}?
|           +--ro conform-cos?  uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|           +--ro conform-dscp?  uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|           +--ro conform-precedence? uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|           +--ro set-exceed-action? ipi-qos-types:qos_exceed_action_t {feature-list:HAVE_CUSTOM1_QOS}?
|           +--ro exceed-cos?    uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|           +--ro exceed-dscp?   uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|           +--ro set-violate-action? ipi-qos-types:qos_violate_action_t {feature-list:HAVE_CUSTOM1_QOS}?

```

---

```

|         +--ro violate-cos?      uint8 {feature-list:HAVE_CUSTOM1_QOS}?
|         +--ro violate-dscp?    uint8 {feature-list:HAVE_CUSTOM1_QOS}?
+--rw scheduler-mode {feature-list:HAVE_CUSTOM1_QOS_OR_HAVE_CUSTOM4_QOS}?
| +--rw weighted-round-robins
| | +--rw weighted-round-robin* [unicast-queue-weight non-unicast-queue-weight]
| |   +--rw unicast-queue-weight  -> ../config/unicast-queue-weight
| |   +--rw non-unicast-queue-weight -> ../config/non-unicast-queue-weight
| |   +--rw config
| |     | +--rw unicast-queue-weight?  uint8
| |     | +--rw non-unicast-queue-weight? uint8
| |     +--ro state
| |       +--ro unicast-queue-weight?  uint8
| |       +--ro non-unicast-queue-weight? uint8
| +--rw strict-priority
|   +--rw config
|   | +--rw enabled?  empty
|   +--ro state
|     +--ro enabled?  empty
+--rw statistics
| +--rw config
| | +--rw enabled?  empty
| +--ro state
|   +--ro enabled?  empty
+--rw red-drop
| +--rw config
| +--ro state
+--rw vlan-queuing
  +--rw config
  | +--rw block-size?  uint8 {feature-list:HAVE_FLEXPOR,feature-list:HAVE_CUSTOM1_QOS}?
  +--ro state
    +--ro block-size?  uint8 {feature-list:HAVE_FLEXPOR,feature-list:HAVE_CUSTOM1_QOS}?

```

rpcs:

```

+---x qos-clear-statistics {feature-list:HAVE_QOS}?
  +---w input
    +---w interface-name?  string

```

---

```
+---w type?          ipi-qos-types:qos_clear_stats_t
```

---

## module: ipi-radius

```
+--rw radius
  +--rw vrfs
    | +--rw vrf* [vrf-name] {feature-list:HAVE_AAA}?
    |   +--rw vrf-name      -> ../config/vrf-name
    |   +--rw config
    |     | +--rw vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
    |     | +--rw key-type?      ipi-radius-types:radius_hostp_key_type_t
    |     | +--rw secret-key-string? string
    |     | +--rw timeout?      uint8
    |     +--ro state
    |       | +--ro vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
    |       | +--ro key-type?      ipi-radius-types:radius_hostp_key_type_t
    |       | +--ro secret-key-string? string
    |       | +--ro timeout?      uint8
    |     +--rw remote-servers
    |       +--rw server* [host-address] {feature-list:HAVE_AAA}?
    |         +--rw host-address  -> ../config/host-address
    |         +--rw config
    |           | +--rw host-address?    cml-data-types:cml_hostname_t
    |           | +--rw sequence-number  uint8
    |           | +--rw key-type?        ipi-radius-types:radius_hostp_key_type_t
    |           | +--rw secret-key-string? string
    |           | +--rw accounting-port? uint16
    |           | +--rw authentication-port? uint16
    |           | +--rw timeout?        uint8
    |           +--ro state
    |             +--ro host-address?    cml-data-types:cml_hostname_t
    |             +--ro sequence-number  uint8
    |             +--ro key-type?        ipi-radius-types:radius_hostp_key_type_t
    |             +--ro secret-key-string? string
    |             +--ro accounting-port? uint16
```

```

|      +--ro authentication-port?          uint16
|      +--ro timeout?                     uint8
|      +--ro last-successful-authentication-time? yang:date-and-time
|      +--ro counters
|          +--ro successful-authentications? yang:counter64
|          +--ro authentication-failures?   yang:counter64
|          +--ro connection-failures?      yang:counter64
+--rw debug
  +--rw config
    | +--rw enable?  empty
    +--ro state
      +--ro enable?          empty
      +--ro terminal-debug-status? cml-data-types:cml_on_off_t

```

rpcs:

```

+---x radius-clear-all-server-counters {feature-list:HAVE_HOSTPD,feature-list:HAVE_RADIUS_CLIENT}?
| +---w input
|   +---w vrf-name  string
+---x radius-clear-server-counters {feature-list:HAVE_HOSTPD,feature-list:HAVE_RADIUS_CLIENT}?
| +---w input
|   +---w hostname  cml-data-types:cml_hostname_t
|   +---w vrf-name  string
+---x radius-terminal-debug-on {feature-list:HAVE_HOSTPD,feature-list:HAVE_RADIUS_CLIENT}?
+---x radius-terminal-debug-off {feature-list:HAVE_HOSTPD,feature-list:HAVE_RADIUS_CLIENT}?

```

---

## module: ipi-ras

rpcs:

```

+---x platform-clear-hsl-ipc-stat-values {feature-list:HAVE_HAL,feature-list:HAVE_PLATFORM_RAS}?
| +---w input
|   +---w start-value  uint16
|   +---w end-value    uint16
+---x platform-clear-hsl-ipc-stat {feature-list:HAVE_HAL,feature-list:HAVE_PLATFORM_RAS}?
+---x platform-clear-hsl-mlag-mac-sync {feature-list:HAVE_MLAG}?
+---x platform-clear-hardware-discard-counters {feature-list:HAVE_HAL,feature-list:HAVE_PLATFORM_RAS}?

```

+---x platform-clear-hsl-fdb-debug-counters {feature-list:HAVE\_HAL,feature-list:HAVE\_PLATFORM\_RAS}?

+---x platform-clear-hsl-system-cpu-stats {feature-list:HAVE\_HAL,feature-list:HAVE\_PLATFORM\_RAS}?

---

## module: ipi-rib-vrf

augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance/ipi-vrf:vrf:

+--rw global

+--rw config

| +--rw ipv4-enable-bfd-all-interfaces? empty {feature-list:HAVE\_BFD}?

| +--rw ipv6-enable-bfd-all-interfaces? empty {feature-list:HAVE\_BFD,feature-list:HAVE\_IPV6}?

+--ro state

+--ro ipv4-enable-bfd-all-interfaces? empty {feature-list:HAVE\_BFD}?

+--ro ipv6-enable-bfd-all-interfaces? empty {feature-list:HAVE\_BFD,feature-list:HAVE\_IPV6}?

augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance/ipi-vrf:vrf:

+--rw static-routes

+--rw ipv4

| +--rw gateway-interface-routes-global

| | +--rw gateway-interface-route-global\* [destination-prefix interface-name enable-global-table-lookup]

| | | +--rw destination-prefix -> ../config/destination-prefix

| | | +--rw interface-name -> ../config/interface-name

| | | +--rw enable-global-table-lookup -> ../config/enable-global-table-lookup

| | | +--rw config

| | | | +--rw destination-prefix? cml-data-types:cml\_ipv4\_prefix\_t

| | | | +--rw interface-name? string

| | | | +--rw enable-global-table-lookup? empty

| | | | +--rw track-id? uint16 {feature-list:HAVE\_OBJ\_TRACKING}?

| | | +--ro state

| | | | +--ro destination-prefix? cml-data-types:cml\_ipv4\_prefix\_t

| | | | +--ro interface-name? string

| | | | +--ro enable-global-table-lookup? empty

| | | | +--ro track-id? uint16 {feature-list:HAVE\_OBJ\_TRACKING}?

| +--rw routes

| | +--rw route\* [destination-prefix gateway-address]

---

```
| | +--rw destination-prefix    -> ../config/destination-prefix
| | +--rw gateway-address      -> ../config/gateway-address
| | +--rw config
| | | +--rw bfd-state?         ipi-rib-types:rib_static_bfd_enable_disable_t {feature-list:HAVE_BFD}?
| | | +--rw destination-prefix? cml-data-types:cml_ipv4_prefix_t
| | | +--rw gateway-address?   inet:ipv4-address
| | +--ro state
| | | +--ro bfd-state?         ipi-rib-types:rib_static_bfd_enable_disable_t {feature-list:HAVE_BFD}?
| | | +--ro destination-prefix? cml-data-types:cml_ipv4_prefix_t
| | | +--ro gateway-address?   inet:ipv4-address
| | +--rw gateway-interface-routes
| | | +--rw gateway-interface-route* [interface-name]
| | |   +--rw interface-name    -> ../config/interface-name
| | |   +--rw config
| | |   | +--rw distance?       uint32
| | |   | +--rw tag?           uint32
| | |   | +--rw track-id?      uint16 {feature-list:HAVE_OBJ_TRACKING}?
| | |   | +--rw description?   cml-data-types:cml_line_t
| | |   | +--rw interface-name? string
| | |   +--ro state
| | |   | +--ro distance?      uint32
| | |   | +--ro tag?          uint32
| | |   | +--ro track-id?     uint16 {feature-list:HAVE_OBJ_TRACKING}?
| | |   | +--ro description?   cml-data-types:cml_line_t
| | |   | +--ro interface-name? string
| | +--rw interface-routes-global
| |   +--rw interface-route-global* [interface-name enable-global-table-lookup]
| |     +--rw interface-name    -> ../config/interface-name
| |     +--rw enable-global-table-lookup -> ../config/enable-global-table-lookup
| |     +--rw config
| |     | +--rw interface-name?   string
| |     | +--rw enable-global-table-lookup? empty
| |     | +--rw track-id?        uint16 {feature-list:HAVE_OBJ_TRACKING}?
| |     +--ro state
| |     | +--ro interface-name?   string
| |     | +--ro enable-global-table-lookup? empty
```

---

```

| |      +--ro track-id?          uint16 {feature-list:HAVE_OBJ_TRACKING}?
| +--rw interface-routes
| | +--rw interface-route* [destination-prefix interface-name]
| |   +--rw destination-prefix  -> ../config/destination-prefix
| |   +--rw interface-name     -> ../config/interface-name
| |   +--rw config
| |     | +--rw destination-prefix?  cml-data-types:cml_ipv4_prefix_t
| |     | +--rw interface-name?     string
| |     | +--rw distance?           uint32
| |     | +--rw tag?                uint32
| |     | +--rw track-id?           uint16 {feature-list:HAVE_OBJ_TRACKING}?
| |     | +--rw description?        cml-data-types:cml_line_t
| |     +--ro state
| |       +--ro destination-prefix?  cml-data-types:cml_ipv4_prefix_t
| |       +--ro interface-name?     string
| |       +--ro distance?           uint32
| |       +--ro tag?                uint32
| |       +--ro track-id?           uint16 {feature-list:HAVE_OBJ_TRACKING}?
| |       +--ro description?        cml-data-types:cml_line_t
| +--rw multicast-routes
| | +--rw multicast-route* [source-prefix protocol-type]
| |   +--rw source-prefix  -> ../config/source-prefix
| |   +--rw protocol-type  -> ../config/protocol-type
| |   +--rw config
| |     | +--rw source-prefix?  cml-data-types:cml_ipv4_prefix_t
| |     | +--rw protocol-type?  ipi-rib-types:rib_mroute_route_type_t
| |     | +--rw gateway-address  inet:ipv4-address
| |     | +--rw distance?       uint32
| |     +--ro state
| |       +--ro source-prefix?  cml-data-types:cml_ipv4_prefix_t
| |       +--ro protocol-type?  ipi-rib-types:rib_mroute_route_type_t
| |       +--ro gateway-address  inet:ipv4-address
| |       +--ro distance?       uint32
+--rw ipv6 {feature-list:HAVE_IPV6}?
  +--rw interface-routes-global
  | +--rw interface-route-global* [destination-prefix interface-name enable-ipv6-global-table-lookup]

```

```

| +--rw destination-prefix      -> ../config/destination-prefix
| +--rw interface-name         -> ../config/interface-name
| +--rw enable-ipv6-global-table-lookup -> ../config/enable-ipv6-global-table-lookup
| +--rw config
| | +--rw destination-prefix?   cml-data-types:cml_ipv6_prefix_t
| | +--rw interface-name?      string
| | +--rw enable-ipv6-global-table-lookup? empty
| | +--rw track-id?            uint16 {feature-list:HAVE_OBJ_TRACKING}?
| +--ro state
|   +--ro destination-prefix?   cml-data-types:cml_ipv6_prefix_t
|   +--ro interface-name?       string
|   +--ro enable-ipv6-global-table-lookup? empty
|   +--ro track-id?             uint16 {feature-list:HAVE_OBJ_TRACKING}?
+--rw gateway-interface-routes-global
| +--rw gateway-interface-route-global* [destination-prefix gateway-address interface-name enable-ipv6-global-
table-lookup]
| | +--rw destination-prefix    -> ../config/destination-prefix
| | +--rw gateway-address       -> ../config/gateway-address
| | +--rw interface-name        -> ../config/interface-name
| | +--rw enable-ipv6-global-table-lookup -> ../config/enable-ipv6-global-table-lookup
| | +--rw config
| | | +--rw destination-prefix? cml-data-types:cml_ipv6_prefix_t
| | | +--rw gateway-address?    inet:ipv6-address
| | | +--rw interface-name?     string
| | | +--rw enable-ipv6-global-table-lookup? empty
| | | +--rw track-id?          uint16 {feature-list:HAVE_OBJ_TRACKING}?
| | +--ro state
| |   +--ro destination-prefix? cml-data-types:cml_ipv6_prefix_t
| |   +--ro gateway-address?    inet:ipv6-address
| |   +--ro interface-name?     string
| |   +--ro enable-ipv6-global-table-lookup? empty
| |   +--ro track-id?          uint16 {feature-list:HAVE_OBJ_TRACKING}?
+--rw routes
| +--rw route* [destination-prefix gateway-address]
| | +--rw destination-prefix -> ../config/destination-prefix
| | +--rw gateway-address   -> ../config/gateway-address
| | +--rw config

```

---

```

| | +--rw bfd-state?          ipi-rib-types:rib_static_bfd_enable_disable_t {feature-list:HAVE_BFD}?
| | +--rw destination-prefix? cml-data-types:cml_ipv6_prefix_t
| | +--rw gateway-address?    inet:ipv6-address
| | +--rw enable-ipv6-global-table-lookup? empty
| +--ro state
| | +--ro bfd-state?          ipi-rib-types:rib_static_bfd_enable_disable_t {feature-list:HAVE_BFD}?
| | +--ro destination-prefix? cml-data-types:cml_ipv6_prefix_t
| | +--ro gateway-address?    inet:ipv6-address
| | +--ro enable-ipv6-global-table-lookup? empty
| +--rw out-interfaces
|   +--rw out-interface* [interface-name]
|     +--rw interface-name -> ../config/interface-name
|     +--rw config
|       | +--rw interface-name? string
|       | +--rw track-id?      uint16 {feature-list:HAVE_OBJ_TRACKING}?
|       | +--rw description?   cml-data-types:cml_line_t
|       +--ro state
|         +--ro interface-name? string
|         +--ro track-id?      uint16 {feature-list:HAVE_OBJ_TRACKING}?
|         +--ro description?   cml-data-types:cml_line_t
+--rw interface-routes
| +--rw interface-route* [destination-prefix interface-name]
|   +--rw destination-prefix -> ../config/destination-prefix
|   +--rw interface-name     -> ../config/interface-name
|   +--rw config
|     | +--rw destination-prefix? cml-data-types:cml_ipv6_prefix_t
|     | +--rw interface-name?    string
|     | +--rw track-id?          uint16 {feature-list:HAVE_OBJ_TRACKING}?
|     | +--rw description?       cml-data-types:cml_line_t
|     +--ro state
|       +--ro destination-prefix? cml-data-types:cml_ipv6_prefix_t
|       +--ro interface-name?    string
|       +--ro track-id?          uint16 {feature-list:HAVE_OBJ_TRACKING}?
|       +--ro description?       cml-data-types:cml_line_t
+--rw multicast-routes
  +--rw multicast-route* [source-prefix protocol-type]

```

---

```

+--rw source-prefix  -> ../config/source-prefix
+--rw protocol-type  -> ../config/protocol-type
+--rw config
| +--rw source-prefix?  cml-data-types:cml_ipv6_prefix_t
| +--rw protocol-type?  ipi-rib-types:rib_mroute_ipv6_route_type_t
+--ro state
| +--ro source-prefix?  cml-data-types:cml_ipv6_prefix_t
| +--ro protocol-type?  ipi-rib-types:rib_mroute_ipv6_route_type_t
+--rw nexthop
  +--rw config!
  | +--rw gateway-mroute  inet:ipv6-address
  | +--rw distance?      uint32
  +--ro state
    +--ro gateway-mroute  inet:ipv6-address
    +--ro distance?      uint32

```

augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance/ipi-vrf:vrf:

```

+--ro ribs
  +--ro ipv4
  | +--ro ecmp-path-summary* [path-count]
  | | +--ro path-count  -> ../state/path-count
  | | +--ro state
  | |   +--ro counters
  | |   | +--ro number-of-routes?  yang:counter32
  | |   +--ro path-count?  uint32
  | +--ro protocol-rib-summary* [protocol-type]
  | | +--ro protocol-type  -> ../state/protocol-type
  | | +--ro state
  | |   +--ro counters
  | |   | +--ro number-of-routes?  yang:counter32
  | |   +--ro protocol-type?  ipi-rib-types:rib_route_type_t
  | +--ro routes
  | | +--ro route* [destination-prefix protocol-type]
  | | | +--ro destination-prefix  -> ../state/destination-prefix
  | | | +--ro protocol-type      -> ../state/protocol-type
  | | | +--ro next-hop* [gateway-address]
  | | | | +--ro gateway-address  -> ../state/gateway-address

```

```

| | | +--ro state
| | |   +--ro gateway-address?      string
| | |   +--ro recursive-hop*        string
| | |   +--ro interface-name?       string
| | |   +--ro active?                empty
| | |   +--ro fib-installed?         empty
| | |   +--ro object-tracking-reachability? ipi-rib-types:rib_object_tracking_reachability_status_t {feature-
list:HAVE_OBJ_TRACKING}?
| | | +--ro state
| | |   +--ro destination-prefix?  cml-data-types:cml_ipv4_prefix_t
| | |   +--ro protocol-type?       ipi-rib-types:rib_route_type_t
| | |   +--ro sub-type?            ipi-rib-types:rib_route_sub_type_t
| | |   +--ro distance?            uint8
| | |   +--ro metric?              uint32
| | |   +--ro black-hole?          empty
| | |   +--ro up-time?             string
| | |   +--ro selected?            empty
| | |   +--ro stale?              empty
| | +--ro state
| |   +--ro gateway-last-resort?  string
| +--ro state
|   +--ro counters
|     +--ro total-routes?          yang:counter32
|     +--ro total-paths?          yang:counter32
|     +--ro total-routes-in-fib?  yang:counter32
|     +--ro ecmp-routes?          yang:counter32
|     +--ro ecmp-paths?          yang:counter32
+--ro ipv6 {feature-list:HAVE_IPV6}?
  +--ro ecmp-path-summary* [path-count]
  | +--ro path-count  -> ../state/path-count
  | +--ro state
  |   +--ro counters
  |     | +--ro number-of-routes?  yang:counter32
  |     +--ro path-count?  uint32
  +--ro protocol-rib-summary* [protocol-type]
  | +--ro protocol-type  -> ../state/protocol-type
  | +--ro state

```

---

```

|   +--ro counters
|   |   +--ro number-of-routes? yang:counter32
|   +--ro protocol-type? ipi-rib-types:rib_route_type_t
+--ro routes
| +--ro route* [destination-prefix protocol-type]
|   +--ro destination-prefix  -> ../state/destination-prefix
|   +--ro protocol-type       -> ../state/protocol-type
|   +--ro next-hop* [gateway-address]
|   |   +--ro gateway-address  -> ../state/gateway-address
|   |   +--ro state
|   |   |   +--ro gateway-address?      string
|   |   |   +--ro recursive-hop*       string
|   |   |   +--ro interface-name?     string
|   |   |   +--ro active?              empty
|   |   |   +--ro fib-installed?      empty
|   |   |   +--ro object-tracking-reachability? ipi-rib-types:rib_object_tracking_reachability_status_t {feature-
list:HAVE_OBJ_TRACKING}?
|   |   +--ro state
|   |   |   +--ro destination-prefix? cml-data-types:cml_ipv6_prefix_t
|   |   |   +--ro protocol-type?     ipi-rib-types:rib_route_type_t
|   |   |   +--ro sub-type?          ipi-rib-types:rib_route_sub_type_t
|   |   |   +--ro distance?         uint8
|   |   |   +--ro metric?           uint32
|   |   |   +--ro black-hole?       empty
|   |   |   +--ro up-time?          string
|   |   |   +--ro selected?         empty
|   |   |   +--ro stale?            empty
+--ro state
  +--ro counters
    +--ro total-routes?      yang:counter32
    +--ro total-paths?      yang:counter32
    +--ro total-routes-in-fib? yang:counter32
    +--ro ecmp-routes?      yang:counter32
    +--ro ecmp-paths?       yang:counter32

rpcs:
+---x clear-ip-vrf-route-all {feature-list:HAVE_VRF}?

```

---

```

| +---w input
|   +---w vrf-name  string
+---x clear-ip-vrf-route {feature-list:HAVE_VRF}?
| +---w input
|   +---w vrf-name    string
|   +---w prefix-address  cml-data-types:cml_ipv4_prefix_t
+---x clear-ipv6-vrf-route-all {feature-list:HAVE_VRF,feature-list:HAVE_IPV6}?
| +---w input
|   +---w vrf-name  string
+---x clear-ipv6-vrf-route {feature-list:HAVE_VRF,feature-list:HAVE_IPV6}?
  +---w input
    +---w vrf-name      string
    +---w prefix-ipv6-address  cml-data-types:cml_ipv6_prefix_t

```

---

## module: ipi-rib

```

+--rw routing
  +--rw global
    | +--rw config
    | | +--rw ipv4-enable-bfd-all-interfaces?  empty {feature-list:HAVE_BFD}?
    | | +--rw ipv6-enable-bfd-all-interfaces?  empty {feature-list:HAVE_BFD,feature-list:HAVE_IPV6}?
    | | +--rw fib-retain?                      ipi-rib-types:rib_fib_retain_t {feature-list:HAVE_L3}?
    | | +--rw max-ecmp-paths?                  uint8 {feature-list:HAVE_MULTIPATH}?
    | | +--rw max-static-routes?              uint32
    | | +--rw max-fib-routes?                 uint32
    | +--ro state
    | +--ro ipv4-enable-bfd-all-interfaces?  empty {feature-list:HAVE_BFD}?
    | +--ro ipv6-enable-bfd-all-interfaces?  empty {feature-list:HAVE_BFD,feature-list:HAVE_IPV6}?
    | +--ro fib-retain?                      ipi-rib-types:rib_fib_retain_t {feature-list:HAVE_L3}?
    | +--ro max-ecmp-paths?                  uint8 {feature-list:HAVE_MULTIPATH}?
    | +--ro max-static-routes?              uint32
    | +--ro max-fib-routes?                 uint32
  +--rw debug
    | +--rw config
    | | +--rw rib-options?                    ipi-rib-types:rib_conf_debug_t
    | | +--rw ipv4-routing-options?          ipi-rib-types:rib_debug_routing_t

```

```

| | +--rw ipv6-routing-options? ipi-rib-types:rib_debug_routing_t
| +--ro state
|   +--ro terminal-debug-status
|     +--ro rib-options?      ipi-rib-types:rib_debug_t
|     +--ro ip-routing-options? ipi-rib-types:rib_debug_routing_t
|     +--ro ipv6-routing-options? ipi-rib-types:rib_debug_routing_t
|     +--ro rib-options?      ipi-rib-types:rib_conf_debug_t
|     +--ro ipv4-routing-options? ipi-rib-types:rib_debug_routing_t
|     +--ro ipv6-routing-options? ipi-rib-types:rib_debug_routing_t
+--rw static-routes
| +--rw ipv4
| | +--rw route-vrfs
| | | +--rw route-vrf* [destination-prefix gateway-address interface-name]
| | |   +--rw destination-prefix -> ../config/destination-prefix
| | |   +--rw gateway-address    -> ../config/gateway-address
| | |   +--rw interface-name     -> ../config/interface-name
| | |   +--rw config
| | |     +--rw destination-prefix? cml-data-types:cml_ipv4_prefix_t
| | |     +--rw gateway-address?   inet:ipv4-address
| | |     +--rw interface-name?    string
| | |     +--ro state
| | |       +--ro destination-prefix? cml-data-types:cml_ipv4_prefix_t
| | |       +--ro gateway-address?   inet:ipv4-address
| | |       +--ro interface-name?    string
| | +--rw routes
| | | +--rw route* [destination-prefix gateway-address]
| | |   +--rw destination-prefix -> ../config/destination-prefix
| | |   +--rw gateway-address    -> ../config/gateway-address
| | |   +--rw config
| | |     +--rw bfd-state?        ipi-rib-types:rib_static_bfd_enable_disable_t {feature-list:HAVE_BFD}?
| | |     +--rw destination-prefix? cml-data-types:cml_ipv4_prefix_t
| | |     +--rw gateway-address?   inet:ipv4-address
| | |     +--rw distance?         uint32
| | |     +--rw tag?              uint32
| | |     +--rw track-id?         uint16 {feature-list:HAVE_OBJ_TRACKING}?
| | |     +--rw description?      cml-data-types:cml_line_t

```

---

```
| | | +--ro state
| | |   +--ro bfd-state?      ipi-rib-types:rib_static_bfd_enable_disable_t {feature-list:HAVE_BFD}?
| | |   +--ro destination-prefix?  cml-data-types:cml_ipv4_prefix_t
| | |   +--ro gateway-address?    inet:ipv4-address
| | |   +--ro distance?         uint32
| | |   +--ro tag?             uint32
| | |   +--ro track-id?        uint16 {feature-list:HAVE_OBJ_TRACKING}?
| | |   +--ro description?     cml-data-types:cml_line_t
| | +--rw interface-routes
| | | +--rw interface-route* [destination-prefix interface-name]
| | |   +--rw destination-prefix -> ../config/destination-prefix
| | |   +--rw interface-name     -> ../config/interface-name
| | |   +--rw config
| | |     | +--rw destination-prefix?  cml-data-types:cml_ipv4_prefix_t
| | |     | +--rw interface-name?    string
| | |     | +--rw distance?         uint32
| | |     | +--rw tag?             uint32
| | |     | +--rw track-id?        uint16 {feature-list:HAVE_OBJ_TRACKING}?
| | |     | +--rw description?     cml-data-types:cml_line_t
| | |   +--ro state
| | |     +--ro destination-prefix?  cml-data-types:cml_ipv4_prefix_t
| | |     +--ro interface-name?    string
| | |     +--ro distance?         uint32
| | |     +--ro tag?             uint32
| | |     +--ro track-id?        uint16 {feature-list:HAVE_OBJ_TRACKING}?
| | |     +--ro description?     cml-data-types:cml_line_t
| | +--rw multicast-routes
| | | +--rw multicast-route* [source-prefix protocol-type]
| | |   +--rw source-prefix -> ../config/source-prefix
| | |   +--rw protocol-type -> ../config/protocol-type
| | |   +--rw config
| | |     | +--rw source-prefix?  cml-data-types:cml_ipv4_prefix_t
| | |     | +--rw protocol-type?  ipi-rib-types:rib_mroute_route_type_t
| | |     | +--rw gateway-address  inet:ipv4-address
| | |     | +--rw distance?      uint32
| | |   +--ro state
```

---

---

```
| |      +--ro source-prefix?  cml-data-types:cml_ipv4_prefix_t
| |      +--ro protocol-type?  ipi-rib-types:rib_mroute_route_type_t
| |      +--ro gateway-address  inet:ipv4-address
| |      +--ro distance?       uint32
| +--rw ipv6 {feature-list:HAVE_IPV6}?
|   +--rw routes
|     +--rw route* [destination-prefix gateway-address]
|       +--rw destination-prefix  -> ../config/destination-prefix
|       +--rw gateway-address     -> ../config/gateway-address
|       +--rw config
|         +--rw bfd-state?        ipi-rib-types:rib_static_bfd_enable_disable_t {feature-list:HAVE_BFD}?
|         +--rw destination-prefix?  cml-data-types:cml_ipv6_prefix_t
|         +--rw gateway-address?    inet:ipv6-address
|         +--rw distance?          uint32
|         +--rw track-id?          uint16 {feature-list:HAVE_OBJ_TRACKING}?
|         +--rw description?       cml-data-types:cml_line_t
|         +--ro state
|           +--ro bfd-state?        ipi-rib-types:rib_static_bfd_enable_disable_t {feature-list:HAVE_BFD}?
|           +--ro destination-prefix?  cml-data-types:cml_ipv6_prefix_t
|           +--ro gateway-address?    inet:ipv6-address
|           +--ro distance?          uint32
|           +--ro track-id?          uint16 {feature-list:HAVE_OBJ_TRACKING}?
|           +--ro description?       cml-data-types:cml_line_t
|     +--rw interface-routes
|       +--rw interface-route* [destination-prefix interface-name]
|         +--rw destination-prefix  -> ../config/destination-prefix
|         +--rw interface-name     -> ../config/interface-name
|         +--rw config
|           +--rw destination-prefix?  cml-data-types:cml_ipv6_prefix_t
|           +--rw interface-name?     string
|           +--rw distance?          uint32
|           +--rw track-id?          uint16 {feature-list:HAVE_OBJ_TRACKING}?
|           +--rw description?       cml-data-types:cml_line_t
|           +--ro state
|             +--ro destination-prefix?  cml-data-types:cml_ipv6_prefix_t
|             +--ro interface-name?     string
```

```

| |   +--ro distance?      uint32
| |   +--ro track-id?     uint16 {feature-list:HAVE_OBJ_TRACKING}?
| |   +--ro description?   cml-data-types:cml_line_t
| +--rw gateway-interface-routes
| | +--rw gateway-interface-route* [destination-prefix gateway-address interface-name]
| |   +--rw destination-prefix -> ../config/destination-prefix
| |   +--rw gateway-address   -> ../config/gateway-address
| |   +--rw interface-name    -> ../config/interface-name
| |   +--rw config
| | | +--rw destination-prefix? cml-data-types:cml_ipv6_prefix_t
| | | +--rw gateway-address?   inet:ipv6-address
| | | +--rw interface-name?    string
| | | +--rw distance?         uint32
| | | +--rw track-id?         uint16 {feature-list:HAVE_OBJ_TRACKING}?
| | | +--rw description?      cml-data-types:cml_line_t
| | +--ro state
| |   +--ro destination-prefix? cml-data-types:cml_ipv6_prefix_t
| |   +--ro gateway-address?   inet:ipv6-address
| |   +--ro interface-name?    string
| |   +--ro distance?         uint32
| |   +--ro track-id?         uint16 {feature-list:HAVE_OBJ_TRACKING}?
| |   +--ro description?      cml-data-types:cml_line_t
| +--rw multicast-routes
| | +--rw multicast-route* [source-prefix protocol-type]
| |   +--rw source-prefix -> ../config/source-prefix
| |   +--rw protocol-type -> ../config/protocol-type
| |   +--rw config
| | | +--rw source-prefix? cml-data-types:cml_ipv6_prefix_t
| | | +--rw protocol-type? ipi-rib-types:rib_mroute_ipv6_route_type_t
| | +--ro state
| | | +--ro source-prefix? cml-data-types:cml_ipv6_prefix_t
| | | +--ro protocol-type? ipi-rib-types:rib_mroute_ipv6_route_type_t
| +--rw nexthop
| | +--rw config!
| | | +--rw gateway-mroute  inet:ipv6-address
| | | +--rw distance?      uint32

```

```

|      +--ro state
|      +--ro gateway-mroute  inet:ipv6-address
|      +--ro distance?      uint32
+--rw interfaces
  +--rw interface* [name] {feature-list:HAVE_BFD}?
    +--rw name    -> ../config/name
    +--rw config
      | +--rw name? -> /ipi-interface:interfaces/interface/name
      +--rw state
      | +--rw name? -> /ipi-interface:interfaces/interface/name
      +--rw bfd {feature-list:HAVE_BFD}?
        +--rw config
          | +--rw ipv4-enable-bfd?  ipi-rib-types:rib_bfd_state {feature-list:HAVE_BFD}?
          | +--rw ipv6-enable-bfd?  ipi-rib-types:rib_bfd_state {feature-list:HAVE_BFD,feature-list:HAVE_IPV6}?
          +--ro state
            +--ro ipv4-enable-bfd?  ipi-rib-types:rib_bfd_state {feature-list:HAVE_BFD}?
            +--ro ipv6-enable-bfd?  ipi-rib-types:rib_bfd_state {feature-list:HAVE_BFD,feature-list:HAVE_IPV6}?

```

rpcs:

```

+---x rib-snmpp-restart {feature-list:HAVE_SNMP}?
+---x clear-ip-stale-kernel-routes {feature-list:HAVE_RIBD}?
+---x clear-ipv6-stale-kernel-routes {feature-list:HAVE_IPV6}?
+---x clear-ip-route-all {feature-list:HAVE_RIBD}?
+---x clear-ip-route {feature-list:HAVE_RIBD}?
| +---w input
|   +---w prefix-address  cml-data-types:cml_ipv4_prefix_t
+---x clear-ipv6-route-all {feature-list:HAVE_IPV6}?
+---x clear-ipv6-route {feature-list:HAVE_IPV6}?
| +---w input
|   +---w prefix-ipv6-address  cml-data-types:cml_ipv6_prefix_t
+---x rib-terminal-debug-on {feature-list:HAVE_RIBD}?
| +---w input
|   +---w terminal-debug-options  ipi-rib-types:rib_debug_t
+---x rib-terminal-debug-off {feature-list:HAVE_RIBD}?
| +---w input
|   +---w terminal-debug-options  ipi-rib-types:rib_debug_t

```

```

+---x rib-terminal-debug-ipv4-routing-on {feature-list:HAVE_RIBD}?
| +---w input
|   +---w terminal-debug-options  ipi-rib-types:rib_debug_routing_t
+---x rib-terminal-debug-ipv4-routing-off {feature-list:HAVE_RIBD}?
| +---w input
|   +---w terminal-debug-options  ipi-rib-types:rib_debug_routing_t
+---x rib-terminal-debug-ipv6-routing-on {feature-list:HAVE_IPV6}?
| +---w input
|   +---w terminal-debug-options  ipi-rib-types:rib_debug_routing_t
+---x rib-terminal-debug-ipv6-routing-off {feature-list:HAVE_IPV6}?
  +---w input
    +---w terminal-debug-options  ipi-rib-types:rib_debug_routing_t

```

---

## module: ipi-rip

```

+--rw rip
  +--rw global
  | +--rw config
  | +--ro state
  +--rw debug
  | +--rw config
  | | +--rw options?  ipi-rip-types:rip_debug_t
  | +--ro state
  | +--ro options?      ipi-rip-types:rip_debug_t
  | +--ro terminal-debug-status?  ipi-rip-types:rip_debug_t
  +--rw interfaces
  | +--rw interface* [name]
  |   +--rw name    -> ../config/name
  |   +--rw config
  |   | +--rw name?      -> /ipi-interface:interfaces/interface/name
  |   | +--rw disable-receive-packet?  empty
  |   | +--rw disable-send-packet?     empty
  |   | +--rw receive-version?        ipi-rip-types:rip_version_t

```

---

```

| | +--rw send-version?      ipi-rip-types:rip_version_t
| | +--rw auth-mode?        ipi-rip-types:rip_auth_mode_t
| | +--rw auth-string?     cml-data-types:cml_line_t
| | +--rw auth-keychain?   string
| | +--rw split-horizon?   boolean
| +--ro state
|   +--ro name?            -> /ipi-interface:interfaces/interface/name
|   +--ro disable-receive-packet? empty
|   +--ro disable-send-packet? empty
|   +--ro receive-version? ipi-rip-types:rip_version_t
|   +--ro send-version?    ipi-rip-types:rip_version_t
|   +--ro auth-mode?      ipi-rip-types:rip_auth_mode_t
|   +--ro auth-string?    cml-data-types:cml_line_t
|   +--ro auth-keychain?  string
|   +--ro split-horizon?  boolean
|   +--ro statistics
|     +--ro sent-mcast-updates? yang:counter32
|     +--ro sent-mcast-requests? yang:counter32
|     +--ro sent-unicast-updates? yang:counter32
|     +--ro sent-unicast-requests? yang:counter32
|     +--ro received-mcast-updates? yang:counter32
|     +--ro received-mcast-requests? yang:counter32
|     +--ro received-unicast-updates? yang:counter32
|     +--ro received-unicast-requests? yang:counter32
|     +--ro received-bad-packets? yang:counter32
|     +--ro received-bad-routes? yang:counter32
+--rw instance
  +--rw config!
    | +--rw enable-cisco-metric-behavior? cml-data-types:cml_enable_disable_t
    | +--rw default-metric?             uint8
    | +--rw version?                   uint8
    | +--rw distance?                  uint8
    | +--rw network-interfaces*        -> /ipi-interface:interfaces/interface/name
    | +--rw network-routes*           cml-data-types:cml_ipv4_prefix_t
    | +--rw rip-enabled                empty
    | +--rw bfd-enable?                empty {feature-list:HAVE_BFD}?

```

---

---

```

| +--rw receive-buffer-size?      uint32
| +--rw passive-interfaces*       -> /ipi-interface:interfaces/interface/name
| +--rw static-routes*           cml-data-types:cml_ipv4_prefix_t
| +--rw neighbors*               inet:ipv4-address
| +--rw neighbor-fall-over-bfd*   inet:ipv4-address {feature-list:HAVE_BFD}?
+--ro state
| +--ro enable-cisco-metric-behavior? cml-data-types:cml_enable_disable_t
| +--ro default-metric?          uint8
| +--ro version?                 uint8
| +--ro distance?                uint8
| +--ro network-interfaces*       -> /ipi-interface:interfaces/interface/name
| +--ro network-routes*          cml-data-types:cml_ipv4_prefix_t
| +--ro rip-enabled               empty
| +--ro bfd-enable?              empty {feature-list:HAVE_BFD}?
| +--ro receive-buffer-size?     uint32
| +--ro passive-interfaces*       -> /ipi-interface:interfaces/interface/name
| +--ro static-routes*           cml-data-types:cml_ipv4_prefix_t
| +--ro neighbors*               inet:ipv4-address
| +--ro neighbor-fall-over-bfd*   inet:ipv4-address {feature-list:HAVE_BFD}?
+--rw distances
| +--rw distance* [source-prefix]
|   +--rw source-prefix -> ../config/source-prefix
|   +--rw config
|     | +--rw source-prefix?   cml-data-types:cml_ipv4_prefix_t
|     | +--rw distance        uint8
|     | +--rw access-list-name? string
|     +--ro state
|       +--ro source-prefix?   cml-data-types:cml_ipv4_prefix_t
|       +--ro distance         uint8
|       +--ro access-list-name? string
+--rw timers
| +--rw config!
| | +--rw route-table-update-interval  uint32
| | +--rw route-info-timeout-interval  uint32
| | +--rw garbage-collection-interval  uint32
| +--ro state

```

---

---

```
|  +--ro route-table-update-interval  uint32
|  +--ro route-info-timeout-interval  uint32
|  +--ro garbage-collection-interval  uint32
+--rw maximum-prefix
|  +--rw config!
|  |  +--rw max-routes                uint32
|  |  +--rw warning-threshold-percentage?  uint32
|  +--ro state
|  +--ro max-routes                uint32
|  +--ro warning-threshold-percentage?  uint32
+--rw redistribute-policies
|  +--rw redistribute-policy* [route-type]
|  +--rw route-type  -> ../config/route-type
|  +--rw config
|  |  +--rw route-type?  ipi-rip-types:rip_redistribute_proto_t
|  |  +--rw metric?     uint8
|  |  +--rw route-map?  string
|  +--ro state
|  +--ro route-type?  ipi-rip-types:rip_redistribute_proto_t
|  +--ro metric?     uint8
|  +--ro route-map?  string
+--rw default-information
|  +--rw config!
|  |  +--rw originate      empty
|  |  +--rw always-advertise?  empty
|  |  +--rw route-map?     string
|  +--ro state
|  +--ro originate      empty
|  +--ro always-advertise?  empty
|  +--ro route-map?     string
+--rw offset-lists
|  +--rw offset-list* [direction]
|  +--rw direction  -> ../config/direction
|  +--rw config
|  |  +--rw direction?      ipi-rip-types:rip_direction_t
|  |  +--rw access-list-name  string
```

---

```
| | +--rw metric          uint8
| +--ro state
|   +--ro direction?     ipi-rip-types:rip_direction_t
|   +--ro access-list-name string
|   +--ro metric          uint8
+--rw distribute-filter-lists
| +--rw distribute-filter-list* [direction]
|   +--rw direction -> ../config/direction
|   +--rw config
|     | +--rw direction?     ipi-rip-types:rip_direction_t
|     | +--rw access-list-name string
|     +--ro state
|       +--ro direction?     ipi-rip-types:rip_direction_t
|       +--ro access-list-name string
+--rw distribute-prefix-lists
| +--rw distribute-prefix-list* [direction]
|   +--rw direction -> ../config/direction
|   +--rw config
|     | +--rw direction?     ipi-rip-types:rip_direction_t
|     | +--rw access-list-name string
|     +--ro state
|       +--ro direction?     ipi-rip-types:rip_direction_t
|       +--ro access-list-name string
+--rw interfaces
| +--rw interface* [name]
|   +--rw name            -> ../config/name
|   +--rw config
|     | +--rw name? -> /ipi-interface:interfaces/interface/name
|     +--ro state
|       | +--ro name? -> /ipi-interface:interfaces/interface/name
|       +--rw offset-lists
|         | +--rw offset-list* [direction]
|         |   +--rw direction -> ../config/direction
|         |   +--rw config
|         |     | +--rw direction?     ipi-rip-types:rip_direction_t
|         |     | +--rw access-list-name string
```

```

| | | +--rw metric      uint8
| | +--ro state
| |   +--ro direction?  ipi-rip-types:rip_direction_t
| |   +--ro access-list-name  string
| |   +--ro metric      uint8
| +--rw distribute-filter-lists
| | +--rw distribute-filter-list* [direction]
| |   +--rw direction  -> ../config/direction
| |   +--rw config
| | | +--rw direction?  ipi-rip-types:rip_direction_t
| | | +--rw access-list-name  string
| | +--ro state
| |   +--ro direction?  ipi-rip-types:rip_direction_t
| |   +--ro access-list-name  string
| +--rw distribute-prefix-lists
| | +--rw distribute-prefix-list* [direction]
| |   +--rw direction  -> ../config/direction
| |   +--rw config
| | | +--rw direction?  ipi-rip-types:rip_direction_t
| | | +--rw access-list-name  string
| | +--ro state
| |   +--ro direction?  ipi-rip-types:rip_direction_t
| |   +--ro access-list-name  string
+--ro routes
| +--ro route* [prefix]
| | +--ro prefix  -> ../state/prefix
| | +--ro state
| | | +--ro prefix?    cml-data-types:cml_ipv4_prefix_t
| | | +--ro type?     ipi-rip-types:rip_route_type_t
| | | +--ro rip-sub-type?  ipi-rip-types:rip_route_subtype_t
| | | +--ro tag?      uint16
| | +--ro nexthops
| | | +--ro nexthop* [address]
| | |   +--ro address  -> ../state/address
| | |   +--ro state
| | |     +--ro address?  inet:ipv4-address

```

---

```

|     +--ro if-name?  string
|     +--ro metric?  uint8
|     +--ro up-time?  string
+--rw vrfs
  +--rw vrf* [vrf-name]
    +--rw vrf-name      -> ../config/vrf-name
    +--rw config
      | +--rw enable-cisco-metric-behavior?  cml-data-types:cml_enable_disable_t
      | +--rw default-metric?                uint8
      | +--rw version?                       uint8
      | +--rw distance?                      uint8
      | +--rw network-interfaces*            -> /ipi-interface:interfaces/interface/name
      | +--rw network-routes*                cml-data-types:cml_ipv4_prefix_t
      | +--rw vrf-name?                      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/
vrf-name
      +--ro state
        | +--ro enable-cisco-metric-behavior?  cml-data-types:cml_enable_disable_t
        | +--ro default-metric?                uint8
        | +--ro version?                       uint8
        | +--ro distance?                      uint8
        | +--ro network-interfaces*            -> /ipi-interface:interfaces/interface/name
        | +--ro network-routes*                cml-data-types:cml_ipv4_prefix_t
        | +--ro vrf-name?                      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/
vrf-name
      +--rw distances
        | +--rw distance* [source-prefix]
        |   +--rw source-prefix  -> ../config/source-prefix
        |   +--rw config
        |     | +--rw source-prefix?  cml-data-types:cml_ipv4_prefix_t
        |     | +--rw distance       uint8
        |     | +--rw access-list-name?  string
        |     +--ro state
        |       +--ro source-prefix?  cml-data-types:cml_ipv4_prefix_t
        |       +--ro distance        uint8
        |       +--ro access-list-name?  string
        +--rw redistribute-policies
          | +--rw redistribute-policy* [route-type]

```

---

---

```
| +--rw route-type -> ../config/route-type
| +--rw config
| | +--rw route-type? ipi-rip-types:rip_vrf_redistribute_proto_t
| | +--rw metric? uint8
| | +--rw route-map? string
| +--ro state
|   +--ro route-type? ipi-rip-types:rip_vrf_redistribute_proto_t
|   +--ro metric? uint8
|   +--ro route-map? string
+--rw default-information
| +--rw config!
| | +--rw originate empty
| | +--rw always-advertise? empty
| | +--rw route-map? string
| +--ro state
|   +--ro originate empty
|   +--ro always-advertise? empty
|   +--ro route-map? string
+--rw offset-lists
| +--rw offset-list* [direction]
|   +--rw direction -> ../config/direction
|   +--rw config
|   | +--rw direction? ipi-rip-types:rip_direction_t
|   | +--rw access-list-name string
|   | +--rw metric uint8
|   +--ro state
|     +--ro direction? ipi-rip-types:rip_direction_t
|     +--ro access-list-name string
|     +--ro metric uint8
+--rw distribute-filter-lists
| +--rw distribute-filter-list* [direction]
|   +--rw direction -> ../config/direction
|   +--rw config
|   | +--rw direction? ipi-rip-types:rip_direction_t
|   | +--rw access-list-name string
|   +--ro state
```

---

```
|   +--ro direction?      ipi-rip-types:rip_direction_t
|   +--ro access-list-name  string
+--rw distribute-prefix-lists
| +--rw distribute-prefix-list* [direction]
|   +--rw direction  -> ../config/direction
|   +--rw config
|   | +--rw direction?      ipi-rip-types:rip_direction_t
|   | +--rw access-list-name  string
|   +--ro state
|     +--ro direction?      ipi-rip-types:rip_direction_t
|     +--ro access-list-name  string
+--rw interfaces
| +--rw interface* [name]
|   +--rw name              -> ../config/name
|   +--rw config
|   | +--rw name?  -> /ipi-interface:interfaces/interface/name
|   +--ro state
|   | +--ro name?  -> /ipi-interface:interfaces/interface/name
|   +--rw offset-lists
|   | +--rw offset-list* [direction]
|   |   +--rw direction  -> ../config/direction
|   |   +--rw config
|   |   | +--rw direction?      ipi-rip-types:rip_direction_t
|   |   | +--rw access-list-name  string
|   |   | +--rw metric          uint8
|   |   +--ro state
|   |     +--ro direction?      ipi-rip-types:rip_direction_t
|   |     +--ro access-list-name  string
|   |     +--ro metric          uint8
|   +--rw distribute-filter-lists
|   | +--rw distribute-filter-list* [direction]
|   |   +--rw direction  -> ../config/direction
|   |   +--rw config
|   |   | +--rw direction?      ipi-rip-types:rip_direction_t
|   |   | +--rw access-list-name  string
|   |   +--ro state
```

```

| |   +--ro direction?      ipi-rip-types:rip_direction_t
| |   +--ro access-list-name  string
|   +--rw distribute-prefix-lists
|     +--rw distribute-prefix-list* [direction]
|       +--rw direction   -> ../config/direction
|       +--rw config
|         | +--rw direction?      ipi-rip-types:rip_direction_t
|         | +--rw access-list-name  string
|         +--ro state
|           +--ro direction?      ipi-rip-types:rip_direction_t
|           +--ro access-list-name  string
+--ro routes
  +--ro route* [prefix]
    +--ro prefix   -> ../state/prefix
    +--ro state
      | +--ro prefix?      cml-data-types:cml_ipv4_prefix_t
      | +--ro type?       ipi-rip-types:rip_route_type_t
      | +--ro rip-sub-type? ipi-rip-types:rip_route_subtype_t
      | +--ro tag?       uint16
    +--ro nexthops
      +--ro nexthop* [address]
        +--ro address   -> ../state/address
        +--ro state
          +--ro address?  inet:ipv4-address
          +--ro if-name?  string
          +--ro metric?   uint8
          +--ro up-time?  string

```

rpcs:

```

+---x rip-vrf-clear-route {feature-list:HAVE_VRF_RIP,feature-list:HAVE_RIPD}?
| +---w input
|   +---w vrf-name  string
|   +---w prefix    cml-data-types:cml_ipv4_prefix_t
+---x rip-vrf-clear-route-all {feature-list:HAVE_VRF_RIP,feature-list:HAVE_RIPD}?
| +---w input
|   +---w vrf-name  string

```

```

+---x rip-clear-route {feature-list:HAVE_RIPD}?
| +---w input
|   +---w route-type   ipi-rip-types:rip_redistribute_proto_clear_t
+---x rip-clear-route-prefix {feature-list:HAVE_RIPD}?
| +---w input
|   +---w prefix-address  cml-data-types:cml_ipv4_prefix_t
+---x rip-clear-statistics {feature-list:HAVE_RIPD}?
| +---w input
|   +---w name    string
+---x rip-snmp-restart {feature-list:HAVE_SNMP}?
+---x rip-terminal-debugging-on {feature-list:HAVE_RIPD}?
| +---w input
|   +---w terminal-debug-options  ipi-rip-types:rip_debug_t
+---x rip-terminal-debugging-off {feature-list:HAVE_RIPD}?
  +---w input
    +---w terminal-debug-options  ipi-rip-types:rip_debug_t

```

---

## module: ipi-ripng

```

+--rw ripng
  +--rw debug
  | +--rw config
  | | +--rw options?  ipi-ripng-types:ripng_debug_t
  | +--ro state
  |   +--ro options?      ipi-ripng-types:ripng_debug_t
  |   +--ro terminal-debug-status?  ipi-ripng-types:ripng_debug_t
+--rw interfaces
  | +--rw interface* [name]
  |   +--rw name    -> ../config/name
  |   +--rw config
  |     | +--rw name?      -> /ipi-interface:interfaces/interface/name
  |     | +--rw enabled?   empty
  |     | +--rw split-horizon?  boolean

```

---

```
| | +--rw metric-offset? uint8
| +--ro state
|   +--ro name?      -> /ipi-interface:interfaces/interface/name
|   +--ro enabled?   empty
|   +--ro split-horizon? boolean
|   +--ro metric-offset? uint8
+--rw instance
  +--rw config!
    +--rw passive-interfaces*      -> /ipi-interface:interfaces/interface/name
    +--rw distance?                uint8
    +--rw static-routes*           cml-data-types:cml_ipv6_prefix_t
    +--rw aggregate-prefixes*      cml-data-types:cml_ipv6_prefix_t
    +--rw default-metric?          uint8
    +--rw originate-default-route? empty
    +--rw enable-cisco-metric-behavior? boolean
    +--rw receive-buffer-size?     uint32
    +--rw ripng-enabled            empty
  +--ro state
    +--ro passive-interfaces*      -> /ipi-interface:interfaces/interface/name
    +--ro distance?                uint8
    +--ro static-routes*           cml-data-types:cml_ipv6_prefix_t
    +--ro aggregate-prefixes*      cml-data-types:cml_ipv6_prefix_t
    +--ro default-metric?          uint8
    +--ro originate-default-route? empty
    +--ro enable-cisco-metric-behavior? boolean
    +--ro receive-buffer-size?     uint32
    +--ro ripng-enabled            empty
  +--rw redistribute-policies
    +--rw redistribute-policy* [route-type]
      +--rw route-type  -> ../config/route-type
      +--rw config
        +--rw metric?    uint8
        +--rw route-map? string
        +--rw route-type? ipi-ripng-types:ripng_redistribute_proto_t
      +--ro state
        +--ro metric?    uint8
```

---

```
|   +--ro route-map?  string
|   +--ro route-type? ipi-ripng-types:ripng_redistribute_proto_t
+--rw timers
| +--rw config!
| | +--rw route-table-update-interval  uint32
| | +--rw route-info-timeout-interval  uint32
| | +--rw garbage-collection-interval  uint32
| +--ro state
|   +--ro route-table-update-interval  uint32
|   +--ro route-info-timeout-interval  uint32
|   +--ro garbage-collection-interval  uint32
+--rw neighbors
| +--rw neighbor* [address]
|   +--rw address  -> ../config/address
|   +--rw config
|   | +--rw address?  inet:ipv6-address
|   | +--rw if-name  -> /ipi-interface:interfaces/interface/name
|   +--ro state
|     +--ro address?  inet:ipv6-address
|     +--ro if-name  -> /ipi-interface:interfaces/interface/name
+--rw interfaces
| +--rw interface* [name]
|   +--rw name          -> ../config/name
|   +--rw config
|   | +--rw name?  -> /ipi-interface:interfaces/interface/name
|   +--ro state
|     +--ro name?  -> /ipi-interface:interfaces/interface/name
|   +--rw filtering-route-maps
|   | +--rw filtering-route-map* [type]
|   |   +--rw type  -> ../config/type
|   |   +--rw config
|   |   | +--rw type?          ipi-ripng-types:ripng_direction_t
|   |   | +--rw route-map-name  string
|   |   +--ro state
|   |     +--ro type?          ipi-ripng-types:ripng_direction_t
|   |     +--ro route-map-name  string
```

---

```
|  +--rw offset-lists
|  |  +--rw offset-list* [direction]
|  |  |  +--rw direction  -> ../config/direction
|  |  |  +--rw config
|  |  |  |  +--rw direction?      ipi-ripng-types:ripng_direction_t
|  |  |  |  +--rw access-list-name  string
|  |  |  |  +--rw metric          uint8
|  |  |  +--ro state
|  |  |  |  +--ro direction?      ipi-ripng-types:ripng_direction_t
|  |  |  |  +--ro access-list-name  string
|  |  |  |  +--ro metric          uint8
|  +--rw distribute-lists
|  |  +--rw distribute-list* [direction]
|  |  |  +--rw direction  -> ../config/direction
|  |  |  +--rw config
|  |  |  |  +--rw direction?      ipi-ripng-types:ripng_direction_t
|  |  |  |  +--rw access-list-name  string
|  |  |  +--ro state
|  |  |  |  +--ro direction?      ipi-ripng-types:ripng_direction_t
|  |  |  |  +--ro access-list-name  string
|  +--rw distribute-prefix-lists
|  |  +--rw distribute-prefix-list* [direction]
|  |  |  +--rw direction  -> ../config/direction
|  |  |  +--rw config
|  |  |  |  +--rw direction? ipi-ripng-types:ripng_direction_t
|  |  |  |  +--rw list-name  string
|  |  |  +--ro state
|  |  |  |  +--ro direction? ipi-ripng-types:ripng_direction_t
|  |  |  |  +--ro list-name  string
+--rw offset-lists
|  +--rw offset-list* [direction]
|  |  +--rw direction  -> ../config/direction
|  |  +--rw config
|  |  |  +--rw direction?      ipi-ripng-types:ripng_direction_t
|  |  |  +--rw access-list-name  string
|  |  |  +--rw metric          uint8
```

---

```
|  +--ro state
|  +--ro direction?      ipi-ripng-types:ripng_direction_t
|  +--ro access-list-name  string
|  +--ro metric          uint8
+--rw distribute-lists
| +--rw distribute-list* [direction]
|   +--rw direction  -> ../config/direction
|   +--rw config
|   | +--rw direction?      ipi-ripng-types:ripng_direction_t
|   | +--rw access-list-name  string
|   +--ro state
|   +--ro direction?      ipi-ripng-types:ripng_direction_t
|   +--ro access-list-name  string
+--rw distribute-prefix-lists
| +--rw distribute-prefix-list* [direction]
|   +--rw direction  -> ../config/direction
|   +--rw config
|   | +--rw direction? ipi-ripng-types:ripng_direction_t
|   | +--rw list-name  string
|   +--ro state
|   +--ro direction? ipi-ripng-types:ripng_direction_t
|   +--ro list-name  string
+--ro routes
| +--ro route* [prefix]
|   +--ro prefix      -> ../state/prefix
|   +--ro state
|   | +--ro prefix?  cml-data-types:cml_ipv6_prefix_t
|   | +--ro type?   ipi-ripng-types:ripng_route_type_t
|   | +--ro sub-type? ipi-ripng-types:ripng_route_sub_type_t
|   | +--ro tag?    uint16
|   +--ro next-hops
|   | +--ro next-hop* [address]
|   |   +--ro address  -> ../state/address
|   |   +--ro state
|   |   +--ro address? inet:ipv6-address
|   |   +--ro if-name? string
```

```

| |   +--ro metric?  uint8
| |   +--ro up-time? string
|   +--ro aggregate-route
|     +--ro state
|       +--ro count?  uint32
|       +--ro metric?  uint8
|       +--ro tag?    uint16
+--rw vrfs
  +--rw vrf* [vrf-name]
    +--rw vrf-name          -> ../config/vrf-name
    +--rw config
      +--rw passive-interfaces* -> /ipi-interface:interfaces/interface/name
      +--rw distance?          uint8
      +--rw static-routes*     cml-data-types:cml_ipv6_prefix_t
      +--rw aggregate-prefixes* cml-data-types:cml_ipv6_prefix_t
      +--rw default-metric?    uint8
      +--rw originate-default-route? empty
      +--rw enable-cisco-metric-behavior? boolean
      +--rw receive-buffer-size? uint32
      +--rw vrf-name?          -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/
vrf-name
    +--ro state
      +--ro passive-interfaces* -> /ipi-interface:interfaces/interface/name
      +--ro distance?          uint8
      +--ro static-routes*     cml-data-types:cml_ipv6_prefix_t
      +--ro aggregate-prefixes* cml-data-types:cml_ipv6_prefix_t
      +--ro default-metric?    uint8
      +--ro originate-default-route? empty
      +--ro enable-cisco-metric-behavior? boolean
      +--ro receive-buffer-size? uint32
      +--ro vrf-name?          -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/
vrf-name
    +--rw redistribute-policies
      +--rw redistribute-policy* [route-type]
      +--rw route-type -> ../config/route-type
      +--rw config
        +--rw metric?  uint8

```

---

```

| | +--rw route-map?  string
| | +--rw route-type? ipi-ripng-types:ripng_vrf_redistribute_proto_t
|   +--ro state
|     +--ro metric?   uint8
|     +--ro route-map? string
|     +--ro route-type? ipi-ripng-types:ripng_vrf_redistribute_proto_t
+--rw timers
| +--rw config!
| | +--rw route-table-update-interval  uint32
| | +--rw route-info-timeout-interval  uint32
| | +--rw garbage-collection-interval  uint32
|   +--ro state
|     +--ro route-table-update-interval  uint32
|     +--ro route-info-timeout-interval  uint32
|     +--ro garbage-collection-interval  uint32
+--rw neighbors
| +--rw neighbor* [address]
|   +--rw address  -> ../config/address
|   +--rw config
|     | +--rw address?  inet:ipv6-address
|     | +--rw if-name  -> /ipi-interface:interfaces/interface/name
|     +--ro state
|       +--ro address?  inet:ipv6-address
|       +--ro if-name  -> /ipi-interface:interfaces/interface/name
+--rw interfaces
| +--rw interface* [name]
|   +--rw name          -> ../config/name
|   +--rw config
|     | +--rw name?  -> /ipi-interface:interfaces/interface/name
|     +--ro state
|       | +--ro name?  -> /ipi-interface:interfaces/interface/name
|     +--rw filtering-route-maps
|       | +--rw filtering-route-map* [type]
|       |   +--rw type  -> ../config/type
|       |   +--rw config
|       |     | +--rw type?          ipi-ripng-types:ripng_direction_t

```

---

---

```
| | | +--rw route-map-name  string
| |   +--ro state
| |     +--ro type?          ipi-ripng-types:ripng_direction_t
| |     +--ro route-map-name  string
| +--rw offset-lists
| | +--rw offset-list* [direction]
| |   +--rw direction  -> ../config/direction
| |   +--rw config
| |     | +--rw direction?      ipi-ripng-types:ripng_direction_t
| |     | +--rw access-list-name  string
| |     | +--rw metric           uint8
| |     +--ro state
| |       +--ro direction?      ipi-ripng-types:ripng_direction_t
| |       +--ro access-list-name  string
| |       +--ro metric           uint8
| +--rw distribute-lists
| | +--rw distribute-list* [direction]
| |   +--rw direction  -> ../config/direction
| |   +--rw config
| |     | +--rw direction?      ipi-ripng-types:ripng_direction_t
| |     | +--rw access-list-name  string
| |     +--ro state
| |       +--ro direction?      ipi-ripng-types:ripng_direction_t
| |       +--ro access-list-name  string
| +--rw distribute-prefix-lists
|   +--rw distribute-prefix-list* [direction]
|     +--rw direction  -> ../config/direction
|     +--rw config
|       | +--rw direction? ipi-ripng-types:ripng_direction_t
|       | +--rw list-name  string
|       +--ro state
|         +--ro direction? ipi-ripng-types:ripng_direction_t
|         +--ro list-name  string
+--rw offset-lists
| +--rw offset-list* [direction]
| +--rw direction  -> ../config/direction
```

---

```
| +--rw config
| | +--rw direction?      ipi-ripng-types:ripng_direction_t
| | +--rw access-list-name  string
| | +--rw metric          uint8
| +--ro state
|   +--ro direction?      ipi-ripng-types:ripng_direction_t
|   +--ro access-list-name  string
|   +--ro metric          uint8
+--rw distribute-lists
| +--rw distribute-list* [direction]
|   +--rw direction  -> ../config/direction
|   +--rw config
|   | +--rw direction?      ipi-ripng-types:ripng_direction_t
|   | +--rw access-list-name  string
|   +--ro state
|     +--ro direction?      ipi-ripng-types:ripng_direction_t
|     +--ro access-list-name  string
+--rw distribute-prefix-lists
| +--rw distribute-prefix-list* [direction]
|   +--rw direction  -> ../config/direction
|   +--rw config
|   | +--rw direction? ipi-ripng-types:ripng_direction_t
|   | +--rw list-name  string
|   +--ro state
|     +--ro direction? ipi-ripng-types:ripng_direction_t
|     +--ro list-name  string
+--ro routes
  +--ro route* [prefix]
    +--ro prefix      -> ../state/prefix
    +--ro state
    | +--ro prefix?  cml-data-types:cml_ipv6_prefix_t
    | +--ro type?   ipi-ripng-types:ripng_route_type_t
    | +--ro sub-type? ipi-ripng-types:ripng_route_sub_type_t
    | +--ro tag?    uint16
    +--ro next-hops
    | +--ro next-hop* [address]
```

```

|   +--ro address  -> ../state/address
|   +--ro state
|     +--ro address?  inet:ipv6-address
|     +--ro if-name?  string
|     +--ro metric?   uint8
|     +--ro up-time?  string
+--ro aggregate-route
  +--ro state
    +--ro count?   uint32
    +--ro metric?  uint8
    +--ro tag?     uint16

```

rpcs:

```

+---x ripng-terminal-debug-on {feature-list:HAVE_RIPNGD}?
| +---w input
|   +---w terminal-debug-options  ipi-ripng-types:ripng_debug_t
+---x ripng-terminal-debug-off {feature-list:HAVE_RIPNGD}?
| +---w input
|   +---w terminal-debug-options  ipi-ripng-types:ripng_debug_t
+---x ripng-clear-route {feature-list:HAVE_RIPNGD}?
| +---w input
|   +---w type  ipi-ripng-types:ripng_clear_route_type_t
+---x ripng-clear-route-prefix {feature-list:HAVE_RIPNGD}?
  +---w input
    +---w prefix  cml-data-types:cml_ipv6_prefix_t

```

---

## module: ipi-role-based-access-control

```

+--rw role-based-access-control
  +--rw config
  | +--rw enable?  empty
  +--ro state
  | +--ro enable?  empty
  +--rw policies
  | +--rw policy* [policy-name]

```

---

```
| +--rw policy-name -> ../config/policy-name
| +--rw config
| | +--rw policy-name? string
| +--ro state
| | +--ro policy-name? string
| +--rw rules
|   +--rw rule* [rule-name]
|     +--rw rule-name -> ../config/rule-name
|     +--rw config
|     | +--rw rule-name? cml-data-types:cml_line_t
|     | +--rw rule-type ipi-role-based-access-control-types:rbac_rule_type_t
|     | +--rw command-mode* string
|     +--ro state
|     +--ro rule-name? cml-data-types:cml_line_t
|     +--ro rule-type ipi-role-based-access-control-types:rbac_rule_type_t
|     +--ro command-mode* string
+--rw roles
  +--rw role* [role-name]
    +--rw role-name -> ../config/role-name
    +--rw config
    | +--rw role-name? string
    | +--rw default-policy? ipi-role-based-access-control-types:rbac_default_rule_type_t
    +--ro state
    | +--ro role-name? string
    | +--ro default-policy? ipi-role-based-access-control-types:rbac_default_rule_type_t
  +--rw policies
    +--rw policy* [policy-name]
      +--rw policy-name -> ../config/policy-name
      +--rw config
      | +--rw policy-name? -> /role-based-access-control/policies/policy/policy-name
      +--ro state
      +--ro policy-name? -> /role-based-access-control/policies/policy/policy-name
```

---

## module: ipi-routemap

```

+--rw routemaps
+--rw routemap* [routemap-name sequence-id]
  +--rw routemap-name    -> ../config/routemap-name
  +--rw sequence-id      -> ../config/sequence-id
  +--rw config
    | +--rw routemap-name?  string
    | +--rw action          ipi-routemap-types:rmap_action_type_t
    | +--rw sequence-id?   uint32
  +--ro state
    | +--ro routemap-name?  string
    | +--ro action          ipi-routemap-types:rmap_action_type_t
    | +--ro sequence-id?   uint32
  +--rw continue-on-match
    | +--rw config
    | | +--rw continue-to-next-sequence?  empty
    | | +--rw next-sequence-number?      uint32
    | +--ro state
    |   +--ro continue-to-next-sequence?  empty
    |   +--ro next-sequence-number?      uint32
  +--rw match-condition
    | +--rw config
    | | +--rw interface-name? -> /ipi-interface:interfaces/interface/name
    | | +--rw metric?         uint32
    | | +--rw tag?            uint32
    | | +--rw route-type?    ipi-routemap-types:rmap_route_type_t
    | | +--rw as-path-name?  string
    | | +--rw route-origin?  ipi-routemap-types:rmap_origin_type_t
    | +--ro state
    | | +--ro interface-name? -> /ipi-interface:interfaces/interface/name
    | | +--ro metric?         uint32
    | | +--ro tag?            uint32
    | | +--ro route-type?    ipi-routemap-types:rmap_route_type_t
    | | +--ro as-path-name?  string
    | | +--ro route-origin?  ipi-routemap-types:rmap_origin_type_t

```

---

```
| +--rw communities
| | +--rw community* [community-identifier]
| |   +--rw community-identifier -> ../config/community-identifier
| |   +--rw config
| |     | +--rw community-identifier? ipi-routemap-types:rmap_community_string_t
| |     | +--rw match-type          ipi-routemap-types:rmap_community_type_t
| |     +--ro state
| |       +--ro community-identifier? ipi-routemap-types:rmap_community_string_t
| |       +--ro match-type          ipi-routemap-types:rmap_community_type_t
| +--rw extended-communities
| | +--rw extended-community* [extended-community-identifier]
| |   +--rw extended-community-identifier -> ../config/extended-community-identifier
| |   +--rw config
| |     | +--rw extended-community-identifier? ipi-routemap-types:rmap_extcommunity_string_t
| |     | +--rw match-type          ipi-routemap-types:rmap_community_type_t
| |     +--ro state
| |       +--ro extended-community-identifier? ipi-routemap-types:rmap_extcommunity_string_t
| |       +--ro match-type          ipi-routemap-types:rmap_community_type_t
| +--rw ipv4
| | +--rw config
| | | +--rw ip-access-list-name?    string
| | | +--rw ip-prefix-list-name?   string
| | | +--rw peer-access-list-name? string
| | | +--rw next-hop-prefix-list-name? string
| | | +--rw next-hop-access-list-name? string
| | +--ro state
| |   +--ro ip-access-list-name?    string
| |   +--ro ip-prefix-list-name?   string
| |   +--ro peer-access-list-name? string
| |   +--ro next-hop-prefix-list-name? string
| |   +--ro next-hop-access-list-name? string
| +--rw ipv6 {feature-list:HAVE_IPV6}?
| | +--rw config {feature-list:HAVE_IPV6}?
| | | +--rw ipv6-address-access-list-name? string
| | | +--rw ipv6-prefix-list-name?      string
| | | +--rw peer-access-list-name?      string
```

---

```
| | | +--rw next-hop-prefix-list-name?    string
| | | +--rw next-hop-match-string?      ipi-routemap-types:rmap_ipv6_nexthop_t
| | +--ro state
| |   +--ro ipv6-address-access-list-name? string
| |   +--ro ipv6-prefix-list-name?      string
| |   +--ro peer-access-list-name?      string
| |   +--ro next-hop-prefix-list-name?   string
| |   +--ro next-hop-match-string?      ipi-routemap-types:rmap_ipv6_nexthop_t
| +--rw large-match-community
|   +--rw config!
|     +--rw large-community-number-match? cml-data-types:cml_line_t
|     +--ro state
|     +--ro large-community-number-match? cml-data-types:cml_line_t
+--rw set-action
  +--rw config
    +--rw forward-interface-type?      ipi-routemap-types:rmap_forward_interface_type_t
    +--rw metric-value?                string
    +--rw route-tag?                   uint32
    +--rw weight?                      uint32
    +--rw local-preference?            uint32
    +--rw route-origin-type?           ipi-routemap-types:rmap_origin_type_t
    +--rw metric-type?                 ipi-routemap-types:rmap_metric_type_t
    +--rw aigp-metric?                 ipi-routemap-types:aigp_metric_type_t {feature-list:HAVE_BGP_AIGP}?
    +--rw level-type?                 ipi-routemap-types:rmap_level_type_t
    +--rw enable-as-path-tag?          empty
    +--rw atomic-aggregate?            empty
    +--rw delete-community-value?      ipi-routemap-types:rmap_community_string_t
    +--rw bgp-originator-id?          inet:ipv4-address
    +--rw as-path-prepend?             cml-data-types:cml_line_t
    +--rw ext-community-site-of-origin? cml-data-types:cml_line_t
    +--rw ext-community-color?         uint32
  +--ro state
    +--ro forward-interface-type?      ipi-routemap-types:rmap_forward_interface_type_t
    +--ro metric-value?                string
    +--ro route-tag?                   uint32
    +--ro weight?                      uint32
```

---

```

| +--ro local-preference?          uint32
| +--ro route-origin-type?        ipi-routemap-types:rmap_origin_type_t
| +--ro metric-type?              ipi-routemap-types:rmap_metric_type_t
| +--ro aigp-metric?              ipi-routemap-types:aigp_metric_type_t {feature-list:HAVE_BGP_AIGP}?
| +--ro level-type?               ipi-routemap-types:rmap_level_type_t
| +--ro enable-as-path-tag?       empty
| +--ro atomic-aggregate?         empty
| +--ro delete-community-value?   ipi-routemap-types:rmap_community_string_t
| +--ro bgp-originator-id?       inet:ipv4-address
| +--ro as-path-prepend?          cml-data-types:cml_line_t
| +--ro ext-community-site-of-origin? cml-data-types:cml_line_t
| +--ro ext-community-color?      uint32
+--rw ipv4
| +--rw config
| | +--rw ip-nexthop-address?     inet:ipv4-address
| | +--rw use-peer-address?      empty
| | +--rw vpv4-nexthop-address?  inet:ipv4-address {feature-list:HAVE_VRF}?
| +--ro state
|   +--ro ip-nexthop-address?     inet:ipv4-address
|   +--ro use-peer-address?      empty
|   +--ro vpv4-nexthop-address?  inet:ipv4-address {feature-list:HAVE_VRF}?
+--rw ipv6
| +--rw config
| | +--rw ipv6-nexthop-address?   inet:ipv6-address {feature-list:HAVE_IPV6}?
| | +--rw local-ipv6-nexthop-address? inet:ipv6-address {feature-list:HAVE_IPV6}?
| +--ro state
|   +--ro ipv6-nexthop-address?   inet:ipv6-address {feature-list:HAVE_IPV6}?
|   +--ro local-ipv6-nexthop-address? inet:ipv6-address {feature-list:HAVE_IPV6}?
+--rw bgp-aggregator-attributes
| +--rw bgp-aggregator-attribute* [as-number aggregator-ip-address]
|   +--rw as-number              -> ../config/as-number
|   +--rw aggregator-ip-address  -> ../config/aggregator-ip-address
|   +--rw config
|     +--rw as-number?           uint32
|     +--rw aggregator-ip-address? inet:ipv4-address
|   +--ro state

```

---

```

|   +--ro as-number?          uint32
|   +--ro aggregator-ip-address?  inet:ipv4-address
+--rw extended-community
| +--rw route-targets
| | +--rw route-target* [ext-community-rt]
| | | +--rw ext-community-rt  -> ../config/ext-community-rt
| | | +--rw config
| | | | +--rw ext-community-rt?  cml-data-types:cml_line_t
| | | | +--rw additive-type      ipi-routemap-types:rmap_additive_type_t
| | | +--ro state
| | |   +--ro ext-community-rt?  cml-data-types:cml_line_t
| | |   +--ro additive-type      ipi-routemap-types:rmap_additive_type_t
| | +--rw costs
| |   +--rw cost* [comparison-type community-id cost-value]
| |   +--rw comparison-type  -> ../config/comparison-type
| |   +--rw community-id     -> ../config/community-id
| |   +--rw cost-value       -> ../config/cost-value
| |   +--rw config
| |   | +--rw comparison-type?  ipi-routemap-types:rmap_ext_cost_type_t
| |   | +--rw community-id?     uint8
| |   | +--rw cost-value?       uint32
| |   +--ro state
| |     +--ro comparison-type?  ipi-routemap-types:rmap_ext_cost_type_t
| |     +--ro community-id?     uint8
| |     +--ro cost-value?       uint32
+--rw dampening
| +--rw config!
| | +--rw enable-dampening      empty
| | +--rw reachability-half-life-time?  uint8
| | +--rw reuse-time-limit?      uint16
| | +--rw suppress-time-limit?     uint16
| | +--rw max-suppress-time-limit?   uint8
| | +--rw unreachable-half-life-time? uint8
| +--ro state
|   +--ro enable-dampening      empty
|   +--ro reachability-half-life-time?  uint8

```

---

```
|  +--ro reuse-time-limit?      uint16
|  +--ro suppress-time-limit?   uint16
|  +--ro max-suppress-time-limit?  uint8
|  +--ro unreachable-half-life-time? uint8
+--rw communities
|  +--rw config
|  |  +--rw enable-internet?      empty
|  |  +--rw enable-local-as?     empty
|  |  +--rw enable-no-advertise?  empty
|  |  +--rw enable-no-export?     empty
|  |  +--rw no-community-attribute? empty
|  |  +--rw additive-set?        empty
|  |  +--rw community-number?     cml-data-types:cml_line_t
|  |  +--rw community-with-as-number? cml-data-types:cml_line_t
|  +--ro state
|  +--ro enable-internet?      empty
|  +--ro enable-local-as?     empty
|  +--ro enable-no-advertise?  empty
|  +--ro enable-no-export?     empty
|  +--ro no-community-attribute? empty
|  +--ro additive-set?        empty
|  +--ro community-number?     cml-data-types:cml_line_t
|  +--ro community-with-as-number? cml-data-types:cml_line_t
+--rw large-community
  +--rw config!
  |  +--rw large-community-number-set? cml-data-types:cml_line_t
  +--ro state
  +--ro large-community-number-set? cml-data-types:cml_line_t
```

---

## module: ipi-rsvp

```
+--rw rsvp-te
```

---

```
+--ro admin-group* [name]
| +--ro name   -> ../state/name
| +--ro state
|   +--ro name?  string
|   +--ro value? uint32
+--rw debug
| +--rw config
| | +--rw options? ipi-rsvp-types:rsvp_debug_t
| +--ro state
|   +--ro options?          ipi-rsvp-types:rsvp_debug_t
|   +--ro terminal-debug-status? ipi-rsvp-types:rsvp_debug_t
+--rw snmp-configuration
| +--rw config
| | +--rw enable-rsvp-trap? empty {feature-list:HAVE_SNMP}?
| +--ro state
|   +--ro enable-rsvp-trap? empty {feature-list:HAVE_SNMP}?
+--ro dscp
| +--ro state
|   +--ro class-exp-mapping*   uint32 {feature-list:NOT_HAVE_SWFWDR}?
|   +--ro class-exp-mapping-value* uint8 {feature-list:NOT_HAVE_SWFWDR}?
+--rw rsvp-instance
| +--ro summary-refresh* [address]
| | +--ro address  -> ../state/address
| | +--ro state
| | | +--ro address?          inet:ip-address
| | | +--ro trunk-id?         uint32
| | | +--ro lsp-id?           uint16
| | | +--ro session-frr-type? ipi-rsvp-types:rsvp_session_frr_type_t
| | | +--ro ingress?          inet:ip-address
| | | +--ro egress?           inet:ip-address
| | | +--ro trunk-session-type? ipi-rsvp-types:rsvp_sess_type_t
| +--ro local-address-ipv4* [addr]
| | +--ro addr   -> ../state/addr
| | +--ro state
| | | +--ro if-name? -> /ipi-interface:interfaces/interface/name
| | | +--ro family? ipi-rsvp-types:rsvp_addr_family_t
```

```
| | +--ro addr?   inet:ip-address
| +--ro local-address-ipv6* [addr]
| | +--ro addr   -> ../state/addr
| | +--ro state
| | +--ro if-name? -> /ipi-interface:interfaces/interface/name
| | +--ro family?  ipi-rsvp-types:rsvp_addr_family_t
| | +--ro addr?   inet:ip-address
| +--ro rsvp-nexthop* [prefix]
| | +--ro prefix   -> ../state/prefix
| | +--ro state
| | +--ro prefix?   cml-data-types:cml_ip_prefix_addr_t
| | +--ro number-of-sessions? uint32
| | +--ro ip-addr?   inet:ip-address
| | +--ro if-name?   -> /ipi-interface:interfaces/interface/name
| +--rw config!
| | +--rw rsvp           ipi-rsvp-types:rsvp_instance_t
| | +--rw enable-explicit-null?   empty
| | +--rw enable-local-protection? empty
| | +--rw enable-php?           empty
| | +--rw enable-entropy-label-capability? empty {feature-list:NOT_HAVE_CUSTOM1_MPLS}?
| | +--rw disable-refresh-resv-parsing? empty
| | +--rw disable-refresh-path-parsing? empty
| | +--rw disable-loop-detection? empty
| | +--rw revert-timer?          uint32
| | +--rw enable-bundle-send?    empty
| | +--rw ingress?              inet:ipv4-address
| | +--rw on-boot-sample-interval? uint16 {feature-list:HAVE_AUTO_BANDWIDTH}?
| | +--rw on-boot-adjust-interval? uint16 {feature-list:HAVE_AUTO_BANDWIDTH}?
| | +--rw on-boot-adjust-multiplier? uint8 {feature-list:HAVE_AUTO_BANDWIDTH}?
| +--ro state
| | +--ro counters
| | | +--ro in-path-messages?          uint32
| | | +--ro in-path-error-messages?    uint32
| | | +--ro in-path-tear-messages?     uint32
| | | +--ro in-reservation-fixed-filter-messages? uint32
| | | +--ro in-reservation-wildcard-filter-messages? uint32
```

---

```
| | | +--ro in-reservation-shared-explicit-messages? uint32
| | | +--ro in-reservation-error-messages?          uint32
| | | +--ro in-reservation-tear-messages?          uint32
| | | +--ro in-reservation-conform-messages?       uint32
| | | +--ro in-hello-messages?                    uint32
| | | +--ro in-bundle-messages?                   uint32
| | | +--ro in-acknowledge-messages?              uint32
| | | +--ro in-srefresh-messages?                uint32
| | | +--ro in-notify-messages?                  uint32
| | | +--ro out-path-messages?                   uint32
| | | +--ro out-path-error-messages?              uint32
| | | +--ro out-path-tear-messages?              uint32
| | | +--ro out-reservation-fixed-filter-messages? uint32
| | | +--ro out-reservation-wildcard-filter-messages? uint32
| | | +--ro out-reservatoion-shared-explicit-messages? uint32
| | | +--ro out-reservation-error-messages?       uint32
| | | +--ro out-reservation-tear-messages?       uint32
| | | +--ro out-reservation-conform-messages?     uint32
| | | +--ro out-hello-messages?                  uint32
| | | +--ro out-bundle-messages?                 uint32
| | | +--ro out-acknowledge-messages?            uint32
| | | +--ro out-srefresh-messages?              uint32
| | | +--ro out-notify-messages?                uint32
| | | +--ro total-number-of-sessions?            int32
| | | +--ro active-sessions?                     int32
| | | +--ro total-ingress-sessions?              int32
| | | +--ro active-ingress-sessions?            int32
| | | +--ro total-transit-sessions?              int32
| | | +--ro active-transit-sessions?            int32
| | | +--ro total-egress-sessions?              int32
| | | +--ro active-egress-sessions?             int32
| | +--ro rsvp                                  ipi-rsvp-types:rsvp_instance_t
| | +--ro enable-explicit-null?                 empty
| | +--ro enable-local-protection?             empty
| | +--ro enable-php?                          empty
| | +--ro enable-entropy-label-capability?     empty {feature-list:NOT_HAVE_CUSTOM1_MPLS}?
```

---

---

```
| | +--ro disable-refresh-resv-parsing?    empty
| | +--ro disable-refresh-path-parsing?    empty
| | +--ro disable-loop-detection?          empty
| | +--ro revert-timer?                    uint32
| | +--ro enable-bundle-send?              empty
| | +--ro ingress?                         inet:ipv4-address
| | +--ro on-boot-sample-interval?         uint16 {feature-list:HAVE_AUTO_BANDWIDTH}?
| | +--ro on-boot-adjust-interval?         uint16 {feature-list:HAVE_AUTO_BANDWIDTH}?
| | +--ro on-boot-adjust-multiplier?       uint8 {feature-list:HAVE_AUTO_BANDWIDTH}?
| | +--ro rsvp-version?                    uint16
| | +--ro rsvp-state?                      ipi-rsvp-types:rsvp_status_t
| | +--ro refresh-timer?                   uint32
| | +--ro keep-multiplier?                 uint32
| | +--ro preemption-type?                 ipi-rsvp-types:rsvp_preemption_type_t
| | +--ro selected-ingress-ipv4?           inet:ipv4-address
| | +--ro selected-ingress-ipv6?           inet:ipv6-address {feature-list:HAVE_IPV6}?
| +--rw route-refresh
| | +--rw config
| | | +--rw enable-message-ack?            empty
| | | +--rw disable-refresh-reduction?     empty
| | | +--rw ack-wait-timeout?              uint32
| | | +--rw refresh-time?                  uint16
| | | +--rw keep-multiplier?               int32
| | | +--rw ack-send-timer?                uint16
| | +--ro state
| |   +--ro enable-message-ack?            empty
| |   +--ro disable-refresh-reduction?     empty
| |   +--ro ack-wait-timeout?              uint32
| |   +--ro refresh-time?                  uint16
| |   +--ro keep-multiplier?               int32
| |   +--ro ack-send-timer?                uint16
| +--rw fast-reroute {feature-list:HAVE_MPLS_FRR}?
| | +--rw config
| | | +--rw default-frr-protection?         ipi-rsvp-types:rsvp_frr_protection_t {feature-list:HAVE_MPLS_FRR}?
| | | +--rw preemption-type?                ipi-rsvp-types:rsvp_preemp_t {feature-list:HAVE_MPLS_FRR}?
| | | +--rw bypass-lsp-addr-query-interval? uint8 {feature-list:HAVE_MPLS_FRR}?
```

---

```

| | | +--rw detour-id?                ipi-rsvp-types:rsvp_detour_iden_t {feature-list:HAVE_MPLS_FRR}?
| | | +--rw detour-allow-primary-upstream-path? empty {feature-list:HAVE_MPLS_FRR}?
| | +--ro state
| | | +--ro default-frr-protection?    ipi-rsvp-types:rsvp_frr_protection_t {feature-list:HAVE_MPLS_FRR}?
| | | +--ro preemption-type?           ipi-rsvp-types:rsvp_preemp_t {feature-list:HAVE_MPLS_FRR}?
| | | +--ro bypass-lsp-addr-query-interval? uint8 {feature-list:HAVE_MPLS_FRR}?
| | | +--ro detour-id?                ipi-rsvp-types:rsvp_detour_iden_t {feature-list:HAVE_MPLS_FRR}?
| | | +--ro detour-allow-primary-upstream-path? empty {feature-list:HAVE_MPLS_FRR}?
| | +--rw auto-bypass
| |   +--rw config!
| |     | +--rw auto-bypass      empty
| |     | +--rw enable?         empty
| |     | +--rw inactivity-timer? uint32
| |     +--ro state
| |       | +--ro auto-bypass    empty
| |       | +--ro enable?       empty
| |       | +--ro inactivity-timer? uint32
| |     +--rw attributes
| |       +--rw attribute* [type]
| |         +--rw type          -> ../config/type
| |         +--rw config
| |           | +--rw type?      ipi-rsvp-types:rsvp_bypass_attr_type_t
| |           | +--rw protection-capability? ipi-rsvp-types:rsvp_exclude_path_type_t
| |           | +--rw bandwidth?   string
| |           | +--rw setup-priority? uint8
| |           | +--rw hold-priority? uint8
| |           | +--rw hop-limit?   uint16
| |           | +--rw reoptimize?  empty
| |         +--ro state
| |           | +--ro type?      ipi-rsvp-types:rsvp_bypass_attr_type_t
| |           | +--ro protection-capability? ipi-rsvp-types:rsvp_exclude_path_type_t
| |           | +--ro bandwidth?   string
| |           | +--ro setup-priority? uint8
| |           | +--ro hold-priority? uint8
| |           | +--ro hop-limit?   uint16
| |           | +--ro reoptimize?  empty

```

```

| |      +--rw exclude-addresses
| |      +--rw exclude-address* [address]
| |      +--rw address  -> ../config/address
| |      +--rw config
| |      | +--rw exclude-type  ipi-rsvp-types:rsvp_exclude_path_type_t
| |      | +--rw address?     inet:ipv4-address
| |      +--ro state
| |      +--ro exclude-type  ipi-rsvp-types:rsvp_exclude_path_type_t
| |      +--ro address?     inet:ipv4-address
| +--rw cspf {feature-list:HAVE_CSPF}?
| | +--rw config
| | | +--rw disable-cspf?          empty
| | | +--rw cspf-lsp-reoptimization-time? uint32
| | +--ro state
| | +--ro disable-cspf?          empty
| | +--ro cspf-lsp-reoptimization-time? uint32
| +--rw global
| | +--rw hellos
| | | +--rw config
| | | | +--rw enable-hello-receipt? empty
| | | | +--rw hello-interval?      int32
| | | | +--rw hello-timeout?      int32
| | | +--ro state
| | | +--ro enable-hello-receipt? empty
| | | +--ro hello-interval?      int32
| | | +--ro hello-timeout?      int32
| | +--rw graceful-restart {feature-list:HAVE_RSVP_GRST}?
| | +--rw config!
| | | +--rw enable-graceful-restart empty
| | | +--rw restart-time?          uint32
| | | +--rw recovery-time?        uint32
| | +--ro state
| | +--ro enable-graceful-restart empty
| | +--ro restart-time?          uint32
| | +--ro recovery-time?        uint32
| +--rw gmpls {feature-list:HAVE_GMPLS}?

```

```

| | +--rw config
| | | +--rw enable-gmpls-notification?      empty
| | | +--rw enable-pre-program-suggested-label?  empty
| | +--ro state
| |   +--ro enable-gmpls-notification?      empty
| |   +--ro enable-pre-program-suggested-label?  empty
| +--rw srlg {feature-list:HAVE_SRLG}?
| | +--rw config
| | | +--rw srlg-disjoint? ipi-rsvp-types:rsvp_te_srlg_disjoint_type_t {feature-list:HAVE_SRLG}?
| | +--ro state
| |   +--ro srlg-disjoint? ipi-rsvp-types:rsvp_te_srlg_disjoint_type_t {feature-list:HAVE_SRLG}?
| +--rw diff-serv {feature-list:HAVE_DIFFSERV}?
| | +--rw config
| | | +--rw enable-override-diff-serv?  empty {feature-list:HAVE_DIFFSERV}?
| | +--ro state
| |   +--ro enable-override-diff-serv?  empty {feature-list:HAVE_DIFFSERV}?
| +--rw neighbors
|   +--rw neighbor* [address]
|   | +--rw address  -> ../config/address
|   | +--rw config
|   | | +--rw address?  inet:ip-address
|   | +--ro state
|   |   +--ro address?  inet:ip-address
|   +--ro protocol-neighbor* [neighbor-ip-address]
|     +--ro neighbor-ip-address  -> ../state/neighbor-ip-address
|     +--ro state
|       +--ro neighbor-ip-address?      inet:ip-address
|       +--ro session-count?            uint32
|       +--ro refresh-reduction?        ipi-rsvp-types:rsvp_neighbor_refresh_reduction_status_t
|       +--ro upstream-lsp-count?       uint32
|       +--ro downstream-lsp-count?     uint32
|       +--ro neighbor-state?           ipi-rsvp-types:rsvp_neighbor_hello_state_t
|       +--ro srefresh-remaining-time?   uint32
|       +--ro neighbor-type?            ipi-rsvp-types:rsvp_neighbor_type_t
|       +--ro max-acknowledge-packet?    uint16
|       +--ro used-acknowledge-packet?   uint16

```

---

```

|   +-ro max-bundle-packet?      uint16
|   +-ro used-bundle-packet?     uint16
|   +-ro lsp-id?                 uint16
|   +-ro session-frr-type?       ipi-rsvp-types:rsvp_session_frr_type_t
|   +-ro ingress?                inet:ip-address
|   +-ro egress?                 inet:ip-address
|   +-ro trunk-session-type?     ipi-rsvp-types:rsvp_sess_type_t
|   +-ro trunk-id?               uint32
|   +-ro graceful-restart-state? ipi-rsvp-types:rsvp_graceful_restart_status_t {feature-
list:HAVE_RSVP_GRST}?
|   +-ro graceful-restart-set-recovery? ipi-rsvp-types:rsvp_graceful_restart_recovery_status_t {feature-
list:HAVE_RSVP_GRST}?
|   +-ro restart-time?           uint32 {feature-list:HAVE_RSVP_GRST}?
|   +-ro recovery-time?          uint32 {feature-list:HAVE_RSVP_GRST}?
|   +-ro remaining-restart-time? uint32 {feature-list:HAVE_RSVP_GRST}?
|   +-ro remaining-recovery-time? uint32 {feature-list:HAVE_RSVP_GRST}?
+--rw rsvp-paths {feature-list:NOT_HAVE_MPLS_TUNNEL}?
| +-rw rsvp-path* [path-name]
|   +-rw path-name      -> ../config/path-name
|   +-rw config
|   | +-rw path-name?   string
|   | +-rw path-type   ipi-rsvp-types:rsvp_path_type_t
|   | +-rw description? cml-data-types:cml_line_t
|   +-ro state
|   | +-ro path-name?   string
|   | +-ro path-type   ipi-rsvp-types:rsvp_path_type_t
|   | +-ro description? cml-data-types:cml_line_t
|   | +-ro path-identifier? uint16
|   | +-ro hop-count?   uint16
|   +-rw explicit-route-object
|     +-rw mpls-hops
|       +-rw mpls-hop* [hop-address hop-type]
|         +-rw hop-address -> ../config/hop-address
|         +-rw hop-type   -> ../config/hop-type
|         +-rw config
|         | +-rw hop-address? inet:ipv4-address
|         | +-rw hop-type?   ipi-rsvp-types:rsvp_path_status_t

```

---

```

|   |   +--ro state
|   |   +--ro hop-address?  inet:ipv4-address
|   |   +--ro hop-type?    ipi-rsvp-types:rsvp_path_status_t
|   +--rw gmpls-strict-hops
+--rw multipaths {feature-list:HAVE_RSVP_MULTIPATH}?
| +--rw multipath* [multipath-name]
|   +--rw multipath-name  -> ../config/multipath-name
|   +--rw config
|   | +--rw description?   cml-data-types:cml_line_t
|   | +--rw destination?  inet:ipv4-address
|   | +--rw multipath-name? string
|   +--ro state
|   | +--ro description?   cml-data-types:cml_line_t
|   | +--ro destination?  inet:ipv4-address
|   | +--ro multipath-name? string
|   | +--ro multipath-identifier? uint16
|   | +--ro member-trunk-count? uint16
|   +--ro member-trunks
|     +--ro member-trunk* [trunk-name]
|       +--ro trunk-name  -> ../state/trunk-name
|       +--ro state
|         +--ro trunk-name?   string
|         +--ro trunk-identifier? uint32
|         +--ro trunk-status? ipi-rsvp-types:rsvp_trunk_status_t
+--rw trunks
| +--rw bypass-trunks
| | +--rw bypass-trunk* [bypass-name] {feature-list:HAVE_MPLS_FRR}?
| |   +--rw bypass-name  -> ../config/bypass-name
| |   +--rw config
| |   | +--rw bypass-name?   string
| |   | +--rw backup-bandwidth-type? ipi-rsvp-types:rsvp_backup_bandwidth_type
| |   | +--rw ingress?      inet:ipv4-address
| |   | +--rw egress?      inet:ipv4-address
| |   | +--rw ext-tunnel-id? inet:ipv4-address
| |   | +--rw update-type?   ipi-rsvp-types:rsvp_update_type_t
| |   | +--rw description?   cml-data-types:cml_line_t

```

---

```

| | | +--rw enable-reoptimize?    empty
| | | +--rw shutdown?            empty
| | +--ro state
| | | +--ro bypass-name?         string
| | | +--ro backup-bandwidth-type? ipi-rsvp-types:rsvp_backup_bandwidth_type
| | | +--ro ingress?            inet:ipv4-address
| | | +--ro egress?             inet:ipv4-address
| | | +--ro ext-tunnel-id?       inet:ipv4-address
| | | +--ro update-type?         ipi-rsvp-types:rsvp_update_type_t
| | | +--ro description?        cml-data-types:cml_line_t
| | | +--ro enable-reoptimize?   empty
| | | +--ro shutdown?           empty
| | +--rw session
| |   +--rw config
| |     | +--rw traffic-type?     ipi-rsvp-types:rsvp_traffic_type_t
| |     | +--rw retry-count?      uint16
| |     | +--rw retry-interval?   uint16
| |     | +--rw disable-route-record? empty
| |     | +--rw enable-reuse-route-record? empty
| |     | +--rw cspf-retry-count?  uint16 {feature-list:HAVE_CSPF}?
| |     | +--rw cspf-retry-interval? uint16 {feature-list:HAVE_CSPF}?
| |     +--ro state
| |       | +--ro traffic-type?     ipi-rsvp-types:rsvp_traffic_type_t
| |       | +--ro retry-count?      uint16
| |       | +--ro retry-interval?   uint16
| |       | +--ro disable-route-record? empty
| |       | +--ro enable-reuse-route-record? empty
| |       | +--ro cspf-retry-count?  uint16 {feature-list:HAVE_CSPF}?
| |       | +--ro cspf-retry-interval? uint16 {feature-list:HAVE_CSPF}?
| |     +--rw exclude-path {feature-list:HAVE_MPLS_FRR}?
| |       | +--rw config!
| |       | | +--rw exclude-type ipi-rsvp-types:rsvp_exclude_path_type_t
| |       | | +--rw exclude-addr inet:ipv4-address
| |       | +--ro state
| |       |   +--ro exclude-type ipi-rsvp-types:rsvp_exclude_path_type_t
| |       |   +--ro exclude-addr inet:ipv4-address

```

```

| |   +--rw path-state-block
| |   | +--rw config
| |   | | +--rw path-name? string
| |   | +--ro state
| |   | | +--ro path-name? string
| |   | +--rw session-attributes
| |   |   +--rw config
| |   |   | +--rw bandwidth? string
| |   |   | +--rw hold-priority? uint8
| |   |   | +--rw setup-priority? uint8
| |   |   | +--rw enable-label-record? empty
| |   |   | +--rw hop-limit? uint16
| |   |   | +--rw filter-type? ipi-rsvp-types:rsvp_filter_type_t
| |   |   +--ro state
| |   |   +--ro bandwidth? string
| |   |   +--ro hold-priority? uint8
| |   |   +--ro setup-priority? uint8
| |   |   +--ro enable-label-record? empty
| |   |   +--ro hop-limit? uint16
| |   |   +--ro filter-type? ipi-rsvp-types:rsvp_filter_type_t
| |   +--rw diff-serv-info {feature-list:HAVE_MPLS_FRR,feature-list:HAVE_DIFFSERV}?
| |   +--rw config
| |   +--ro state
| |   +--rw dscp-exp-maps
| |   +--rw dscp-exp-map* [dscp-exp-map-exp-val]
| |   +--rw dscp-exp-map-exp-val -> ../config/dscp-exp-map-exp-val
| |   +--rw config
| |   | +--rw dscp-exp-map-exp-val? int32
| |   | +--rw dscp-exp-map-class-name string
| |   +--ro state
| |   +--ro dscp-exp-map-exp-val? int32
| |   +--ro dscp-exp-map-class-name string
| +--rw ingress-trunks
| | +--rw ingress-trunk* [trunk-name]
| | +--rw trunk-name -> ../config/trunk-name
| | +--rw config

```

---

```
| | | +--rw bsid-value?          uint32
| | | +--rw trunk-color?        uint32 {feature-list:HAVE_SERVICE_MAPPING}?
| | | +--rw ingress?           inet:ipv4-address
| | | +--rw egress?            inet:ipv4-address
| | | +--rw ext-tunnel-id?      inet:ipv4-address
| | | +--rw update-type?        ipi-rsvp-types:rsvp_update_type_t
| | | +--rw description?        cml-data-types:cml_line_t
| | | +--rw enable-reoptimize?  empty
| | | +--rw shutdown?          empty
| | | +--rw trunk-name?        string
| | | +--rw trunk-family        ipi-rsvp-types:rsvp_trunk_family_t
| | | +--rw enable-igp-shortcut? empty
| | | +--rw absolute-metric?    uint32
| | | +--rw relative-metric?    int32
| | | +--rw revert-timer?       uint32
| | | +--rw auto-bandwidth?     -> /rsvp-te/rsvp-auto-bandwidths/rsvp-auto-bandwidth/config/profile-name
{feature-list:HAVE_AUTO_BANDWIDTH}?
| | | +--rw ldp-tunneling?      empty {feature-list:HAVE_LDP_TUNNELING}?
| | | +--rw multipath-group?    -> /rsvp-te/multipaths/multipath/config/multipath-name {feature-
list:HAVE_RSVP_MULTIPATH}?
| | +--ro state
| | | +--ro bsid-value?          uint32
| | | +--ro trunk-color?        uint32 {feature-list:HAVE_SERVICE_MAPPING}?
| | | +--ro ingress?           inet:ipv4-address
| | | +--ro egress?            inet:ipv4-address
| | | +--ro ext-tunnel-id?      inet:ipv4-address
| | | +--ro update-type?        ipi-rsvp-types:rsvp_update_type_t
| | | +--ro description?        cml-data-types:cml_line_t
| | | +--ro enable-reoptimize?  empty
| | | +--ro shutdown?          empty
| | | +--ro trunk-name?        string
| | | +--ro trunk-family        ipi-rsvp-types:rsvp_trunk_family_t
| | | +--ro enable-igp-shortcut? empty
| | | +--ro absolute-metric?    uint32
| | | +--ro relative-metric?    int32
| | | +--ro revert-timer?       uint32
```

---

```

| | | +--ro auto-bandwidth?    -> /rsvp-te/rsvp-auto-bandwidths/rsvp-auto-bandwidth/config/profile-name
{feature-list:HAVE_AUTO_BANDWIDTH}?
| | | +--ro ldp-tunneling?     empty {feature-list:HAVE_LDP_TUNNELING}?
| | | +--ro multipath-group?   -> /rsvp-te/multipaths/multipath/config/multipath-name {feature-
list:HAVE_RSVP_MULTIPATH}?
| | +--rw path-computation-element {feature-list:HAVE_PCEP_RSVP}?
| | | +--rw config
| | | | +--rw path-option-dynamic?  cml-data-types:cml_pcep_path_dyn_t {feature-list:HAVE_PCEP_RSVP}?
| | | | +--rw pce-entity-identifier? uint8 {feature-list:HAVE_PCEP_RSVP}?
| | | | +--rw pce-state-report?     empty {feature-list:HAVE_PCEP_RSVP}?
| | | | +--rw pce-lsp-delegate?     empty {feature-list:HAVE_PCEP_RSVP}?
| | | +--ro state
| | | | +--ro path-option-dynamic?  cml-data-types:cml_pcep_path_dyn_t {feature-list:HAVE_PCEP_RSVP}?
| | | | +--ro pce-entity-identifier? uint8 {feature-list:HAVE_PCEP_RSVP}?
| | | | +--ro pce-state-report?     empty {feature-list:HAVE_PCEP_RSVP}?
| | | | +--ro pce-lsp-delegate?     empty {feature-list:HAVE_PCEP_RSVP}?
| | +--rw mapped-ip-routes
| | | +--rw mapped-ip-route* [address]
| | | | +--rw address  -> ../config/address
| | | | +--rw config
| | | | | +--rw address?  cml-data-types:cml_ipv4_prefix_t
| | | | +--ro state
| | | | | +--ro address?  cml-data-types:cml_ipv4_prefix_t
| | +--rw mapped-prefix-class-routes
| | | +--rw mapped-prefix-class-route* [dst-addr]
| | | | +--rw dst-addr  -> ../config/dst-addr
| | | | +--rw config
| | | | | +--rw dst-addr  cml-data-types:cml_ipv4_prefix_t
| | | | | +--rw name      string {feature-list:HAVE_DIFFSERV}?
| | | | +--ro state
| | | | | +--ro dst-addr  cml-data-types:cml_ipv4_prefix_t
| | | | | +--ro name      string {feature-list:HAVE_DIFFSERV}?
| | +--rw secondary-priorities
| | | +--rw secondary-priority* [priority-value]
| | | | +--rw priority-value  -> ../config/priority-value
| | | | +--rw config
| | | | | +--rw bandwidth?      string

```

---

```

| | | | +--rw priority-value?          int32
| | | | +--rw priority-path?          string
| | | | +--rw secondary-priority-srlg-disjoint? ipi-rsvp-types:rsvp_te_srlg_disjoint_type_t {feature-
list:HAVE_SRLG}?
| | | | +--rw hold-priority?          uint8
| | | | +--rw setup-priority?        uint8
| | | | +--rw enable-label-record?    empty
| | | | +--rw hop-limit?             uint16
| | | +--ro state
| | |   +--ro bandwidth?             string
| | |   +--ro priority-value?        int32
| | |   +--ro priority-path?        string
| | |   +--ro secondary-priority-srlg-disjoint? ipi-rsvp-types:rsvp_te_srlg_disjoint_type_t {feature-
list:HAVE_SRLG}?
| | |   +--ro hold-priority?        uint8
| | |   +--ro setup-priority?      uint8
| | |   +--ro enable-label-record?  empty
| | |   +--ro hop-limit?           uint16
| | +--rw sessions
| |   +--rw session* [trunk-session-type]
| |     +--rw trunk-session-type -> ../config/trunk-session-type
| |     +--rw config
| |       +--rw traffic-type?       ipi-rsvp-types:rsvp_traffic_type_t
| |       +--rw retry-count?       uint16
| |       +--rw retry-interval?    uint16
| |       +--rw disable-route-record? empty
| |       +--rw enable-reuse-route-record? empty
| |       +--rw cspf-retry-count?   uint16 {feature-list:HAVE_CSPF}?
| |       +--rw cspf-retry-interval? uint16 {feature-list:HAVE_CSPF}?
| |       +--rw trunk-session-type? ipi-rsvp-types:rsvp_sess_type_t
| |       +--rw disable-cspf?      empty {feature-list:HAVE_CSPF}?
| |       +--rw disable-affinity?   empty {feature-list:HAVE_TE}?
| |       +--rw enable-local-protection? empty
| |     +--ro state
| |       +--ro traffic-type?       ipi-rsvp-types:rsvp_traffic_type_t
| |       +--ro retry-count?       uint16
| |       +--ro retry-interval?    uint16

```

---

```
| | | | +--ro disable-route-record?    empty
| | | | +--ro enable-reuse-route-record? empty
| | | | +--ro cspf-retry-count?        uint16 {feature-list:HAVE_CSPF}?
| | | | +--ro cspf-retry-interval?     uint16 {feature-list:HAVE_CSPF}?
| | | | +--ro trunk-session-type?      ipi-rsvp-types:rsvp_sess_type_t
| | | | +--ro disable-cspf?            empty {feature-list:HAVE_CSPF}?
| | | | +--ro disable-affinity?        empty {feature-list:HAVE_TE}?
| | | | +--ro enable-local-protection?  empty
| | | +--rw admin-groups
| | | | +--rw admin-group* [name] {feature-list:HAVE_TE}?
| | | | | +--rw name    -> ../config/name
| | | | | +--rw config
| | | | | | +--rw name?  string
| | | | | | +--rw type?  ipi-rsvp-types:rsvp_admin_type_t
| | | | | +--ro state
| | | | | | +--ro name?  string
| | | | | | +--ro type?  ipi-rsvp-types:rsvp_admin_type_t
| | | | +--rw path-state-block
| | | | | +--rw config
| | | | | | +--rw path-name? -> /rsvp-te/rsvp-paths/rsvp-path/config/path-name
| | | | | +--ro state
| | | | | | +--ro path-name? -> /rsvp-te/rsvp-paths/rsvp-path/config/path-name
| | | | +--rw session-attributes
| | | | | +--rw config
| | | | | | +--rw bandwidth?    string
| | | | | | +--rw hold-priority?  uint8
| | | | | | +--rw setup-priority? uint8
| | | | | | +--rw enable-label-record? empty
| | | | | | +--rw hop-limit?     uint16
| | | | | | +--rw filter-type?    ipi-rsvp-types:rsvp_filter_type_t
| | | | | +--ro state
| | | | | | +--ro bandwidth?    string
| | | | | | +--ro hold-priority?  uint8
| | | | | | +--ro setup-priority? uint8
| | | | | | +--ro enable-label-record? empty
| | | | | | +--ro hop-limit?     uint16
```

```

| | | | +--ro filter-type?      ipi-rsvp-types:rsvp_filter_type_t
| | | | +--rw diff-serv-info {feature-list:HAVE_DIFFSERV}?
| | | |   +--rw config
| | | |   +--ro state
| | | |   +--rw dscp-exp-maps
| | | |     | +--rw dscp-exp-map* [dscp-exp-map-exp-val]
| | | |     |   +--rw dscp-exp-map-exp-val  -> ../config/dscp-exp-map-exp-val
| | | |     |   +--rw config
| | | |     |     | +--rw dscp-exp-map-exp-val?  int32
| | | |     |     | +--rw dscp-exp-map-class-name  string
| | | |     |     | +--ro state
| | | |     |     |   +--ro dscp-exp-map-exp-val?  int32
| | | |     |     |   +--ro dscp-exp-map-class-name  string
| | | |     | +--rw elsp-class
| | | |     |   +--rw config
| | | |     |     | +--rw elsp-signal?      empty
| | | |     |     | +--rw elsp-signal-class1?  string
| | | |     |     | +--rw elsp-signal-class2?  string
| | | |     |     | +--rw elsp-signal-class3?  string
| | | |     |     | +--rw elsp-signal-class4?  string
| | | |     |     | +--rw elsp-signal-class5?  string
| | | |     |     | +--rw elsp-signal-class6?  string
| | | |     |     | +--rw elsp-signal-class7?  string
| | | |     | +--ro state
| | | |     |   +--ro elsp-signal?      empty
| | | |     |   +--ro elsp-signal-class1?  string
| | | |     |   +--ro elsp-signal-class2?  string
| | | |     |   +--ro elsp-signal-class3?  string
| | | |     |   +--ro elsp-signal-class4?  string
| | | |     |   +--ro elsp-signal-class5?  string
| | | |     |   +--ro elsp-signal-class6?  string
| | | |     |   +--ro elsp-signal-class7?  string
| | | +--rw fast-reroute {feature-list:HAVE_MPLS_FRR}?
| | |   +--rw config
| | |     | +--rw fast-reroute-bandwidth?  string
| | |     | +--rw protection?              ipi-rsvp-types:rsvp_frr_protection_t {feature-list:HAVE_MPLS_FRR}?

```

```

| | | | +--rw enable-node-protection? empty {feature-list:HAVE_MPLS_FRR}?
| | | | +--rw frr-hold-priority? uint32
| | | | +--rw frr-setup-priority? uint32
| | | | +--rw frr-hop-limit? uint32
| | | +--ro state
| | | | +--ro fast-reroute-bandwidth? string
| | | | +--ro protection? ipi-rsvp-types:rsvp_frr_protection_t {feature-list:HAVE_MPLS_FRR}?
| | | | +--ro enable-node-protection? empty {feature-list:HAVE_MPLS_FRR}?
| | | | +--ro frr-hold-priority? uint32
| | | | +--ro frr-setup-priority? uint32
| | | | +--ro frr-hop-limit? uint32
| | | +--rw frr-admin-groups
| | | | +--rw frr-admin-group* [admin-group-name] {feature-list:HAVE_MPLS_FRR}?
| | | | | +--rw admin-group-name -> ../config/admin-group-name
| | | | | +--rw config
| | | | | | +--rw admin-group-name? string
| | | | | | +--rw admin-group-type? ipi-rsvp-types:rsvp_frr_admin_type_t
| | | | | +--ro state
| | | | | | +--ro admin-group-name? string
| | | | | | +--ro admin-group-type? ipi-rsvp-types:rsvp_frr_admin_type_t
| | | +--rw srlg {feature-list:HAVE_SRLG}?
| | | | +--rw config
| | | | | +--rw srlg-disjoint-secondary? ipi-rsvp-types:rsvp_te_srlg_disjoint_type_t {feature-list:HAVE_SRLG}?
| | | | +--ro state
| | | | | +--ro srlg-disjoint-secondary? ipi-rsvp-types:rsvp_te_srlg_disjoint_type_t {feature-list:HAVE_SRLG}?
| +--ro trunk* [trunk-id extended-tunnel-id egress]
| | +--ro trunk-id -> ../state/trunk-id
| | +--ro extended-tunnel-id -> ../state/extended-tunnel-id
| | +--ro egress -> ../state/egress
| +--ro sessions
| | +--ro session* [session-name]
| | | +--ro session-name -> ../state/session-name
| | | +--ro state
| | | | +--ro received-explicit-route-object* [link-address]
| | | | | +--ro link-address -> ../state/link-address
| | | | | +--ro state

```

---

```
| | | +--ro link-address? inet:ip-address
| | | +--ro link-type? ipi-rsvp-types:rsvp_path_status_t
| | +--ro explicit-route-object* [link-address]
| | | +--ro link-address -> ../state/link-address
| | | +--ro state
| | | +--ro link-address? inet:ip-address
| | | +--ro link-type? ipi-rsvp-types:rsvp_path_status_t
| | +--ro constrained-shortest-path
| | | +--ro state
| | | +--ro cspf-state? ipi-rsvp-types:rsvp_status_t
| | | +--ro lsp-reoptimization-state? ipi-rsvp-types:rsvp_status_t
| | | +--ro lsp-reoptimization-timer? uint32
| | | +--ro cspf-client? ipi-rsvp-types:rsvp_cspf_client_t
| | +--ro fast-reroute {feature-list:HAVE_MPLS_FRR}?
| | | +--ro state
| | | +--ro lsp-protection? ipi-rsvp-types:rsvp_frr_protection_t {feature-list:HAVE_MPLS_FRR}?
| | | +--ro bypass-trunk-name? string {feature-list:HAVE_MPLS_FRR}?
| | | +--ro merge-point-address? inet:ipv4-address {feature-list:HAVE_MPLS_FRR}?
| | | +--ro merge-point-label? uint32 {feature-list:HAVE_MPLS_FRR}?
| | +--ro upstream-downstream-state
| | | +--ro state
| | | +--ro upstream-ip-address? inet:ip-address
| | | +--ro upstream-interface-name? string
| | | +--ro downstream-ip-address? inet:ip-address
| | | +--ro downstream-interface-name? string
| | +--ro traffic-flow-specification
| | | +--ro state
| | | +--ro traffic-specification-rate? uint32
| | | +--ro filter-specification-rate? uint32
| | +--ro session-priority
| | | +--ro state
| | | +--ro setup-priority? uint8
| | | +--ro hold-priority? uint8
| | | +--ro hop-limit? uint8
| | | +--ro bandwidth? string
| | +--ro path-refresh-timers
```

---

```

| | | +--ro state
| | |   +--ro path-refresh-time?      uint32
| | |   +--ro remaining-path-refresh-time?  uint32
| | |   +--ro path-lifetime?          uint32
| | |   +--ro remaining-path-lifetime?  uint32
| | +--ro reserve-refresh-timers
| | | +--ro state
| | |   +--ro reserve-refresh-time?      uint32
| | |   +--ro remaining-reserve-refresh-time?  uint32
| | |   +--ro reserve-lifetime?          uint32
| | |   +--ro remaining-reserve-lifetime?  uint32
| | +--ro retry-timers
| | | +--ro state
| | |   +--ro remaining-retry-time?  uint32
| | |   +--ro next-retry-time?      uint32
| | +--ro upstream-route-record-object
| | | +--ro state
| | |   +--ro address*  inet:ip-address
| | +--ro downstream-route-record-object
| | | +--ro state
| | |   +--ro address*  inet:ip-address
| | +--ro session-name?      string
| | +--ro lsp-id?            uint16
| | +--ro session-frr-type?  ipi-rsvp-types:rsvp_session_frr_type_t
| | +--ro ingress?          inet:ip-address
| | +--ro trunk-session-type?  ipi-rsvp-types:rsvp_sess_type_t
| | +--ro session-role?     ipi-rsvp-types:rsvp_session_role_t
| | +--ro is-pseudo-primary? ipi-rsvp-types:rsvp_yes_no_t
| | +--ro lsp-state?        string
| | +--ro fsm-state?        string
| | +--ro transit-downstream-fsm-state?  string
| | +--ro establishment-time?  cml-data-types:cml_line_t
| | +--ro revert-hold-timer?    ipi-rsvp-types:rsvp_yes_no_t
| | +--ro remaining-revert-time?  uint32
| | +--ro session-filter-style?  ipi-rsvp-types:rsvp_filter_state_type_t
| | +--ro in-label?           uint32

```

---

```
| |   +--ro out-label?           uint32
| |   +--ro bypass-out-label?   uint32
| |   +--ro bypass-out-interface? string
| |   +--ro gmpls-label-type?   ipi-rsvp-types:rsvp_gmpls_label_type_t
| |   +--ro qos-traffic-type?   ipi-rsvp-types:rsvp_traffic_type_state_t
| |   +--ro minimum-path-mtu?   uint32
| +--ro state
| | +--ro trunk-id?             uint32
| | +--ro extended-tunnel-id?   inet:ip-address
| | +--ro egress?               inet:ip-address
| | +--ro trunk-name?          string
| | +--ro multipath-group-name? string {feature-list:HAVE_RSVP_MULTIPATH}?
| | +--ro multipath-group-identifier? uint16 {feature-list:HAVE_RSVP_MULTIPATH}?
+--ro auto-bandwidth {feature-list:HAVE_AUTO_BANDWIDTH}?
|   +--ro state
|     +--ro last-bandwidth?      string
|     +--ro requested-bandwidth? string
|     +--ro signaled-bandwidth?  string
|     +--ro current-bandwidth?   string
|     +--ro highest-watermark-bandwidth? string
|     +--ro last-adjusted-bandwidth? string
|     +--ro total-bandwidth-adjustments? uint32
|     +--ro successful-adjustments? uint32
|     +--ro failed-adjustments?   uint32
|     +--ro minimum-average-bandwidth? string
|     +--ro maximum-average-bandwidth? string
|     +--ro overflow-sample-count? uint16
|     +--ro underflow-sample-count? uint16
|     +--ro maxbw-exceed-sample-count? uint16
|     +--ro teardown-count?      uint32
|     +--ro sample-request-due-time? uint32
|     +--ro next-adjustment-due-time? uint32
|     +--ro last-bandwidth-request-time? cml-data-types:cml_line_t
|     +--ro last-bandwidth-signal-time? cml-data-types:cml_line_t
|     +--ro last-adjustment-time?      cml-data-types:cml_line_t
|     +--ro highest-watermark-time?    cml-data-types:cml_line_t
```

---

```
|   +-ro total-force-adjustments?   uint32
|   +-ro successful-force-adjustments? uint32
|   +-ro failed-force-adjustments?   uint32
+--rw rsvp-auto-bandwidths {feature-list:HAVE_AUTO_BANDWIDTH}?
| +-rw rsvp-auto-bandwidth* [profile-name]
|   +-rw profile-name  -> ../config/profile-name
|   +-rw config
|   | +-rw profile-name?           string
|   | +-rw sample-interval?        uint16
|   | +-rw adjust-interval?        uint16
|   | +-rw minimum-bandwidth?      string
|   | +-rw maximum-bandwidth?      string
|   | +-rw overflow-threshold-percent? uint8
|   | +-rw underflow-threshold-percent? uint8
|   | +-rw overflow-threshold-bandwidth? string
|   | +-rw underflow-threshold-bandwidth? string
|   | +-rw underflow-threshold-activate-bandwidth? string
|   | +-rw overflow-threshold-activate-bandwidth? string
|   | +-rw overflow-limit?         uint16
|   | +-rw underflow-limit?        uint16
|   | +-rw initial-bandwidth?      string
|   | +-rw maximum-bandwidth-exceed-limit? uint16
|   | +-rw maximum-bandwidth-exceed-action? ipi-rsvp-types:rsvp_auto_bandwidth_action_type_t
|   | +-rw resignal-failure-action? ipi-rsvp-types:rsvp_auto_bandwidth_action_type_t
|   | +-rw sync-bandwidth?         empty
|   | +-rw monitor-bandwidth?      empty
|   | +-rw minimum-samples-percent? uint8
|   | +-rw minimum-samples-absolute? uint16
|   +-ro state
|     +-ro profile-name?           string
|     +-ro sample-interval?        uint16
|     +-ro adjust-interval?        uint16
|     +-ro minimum-bandwidth?      string
|     +-ro maximum-bandwidth?      string
|     +-ro overflow-threshold-percent? uint8
|     +-ro underflow-threshold-percent? uint8
```

---

---

```

|   +--ro overflow-threshold-bandwidth?      string
|   +--ro underflow-threshold-bandwidth?    string
|   +--ro underflow-threshold-activate-bandwidth? string
|   +--ro overflow-threshold-activate-bandwidth? string
|   +--ro overflow-limit?                    uint16
|   +--ro underflow-limit?                   uint16
|   +--ro initial-bandwidth?                 string
|   +--ro maximum-bandwidth-exceed-limit?   uint16
|   +--ro maximum-bandwidth-exceed-action?   ipi-rsvp-types:rsvp_auto_bandwidth_action_type_t
|   +--ro resignal-failure-action?          ipi-rsvp-types:rsvp_auto_bandwidth_action_type_t
|   +--ro sync-bandwidth?                    empty
|   +--ro monitor-bandwidth?                empty
|   +--ro minimum-samples-percent?          uint8
|   +--ro minimum-samples-absolute?         uint16
+--rw interfaces
  +--rw interface* [name]
    +--rw name          -> ../config/name
    +--rw config
      | +--rw name?      -> /ipi-interface:interfaces/interface/name
      | +--rw enable-rsvp?      empty
      | +--rw enable-iana-hello-config? empty
      +--ro state
        | +--ro name?      -> /ipi-interface:interfaces/interface/name
        | +--ro enable-rsvp?      empty
        | +--ro enable-iana-hello-config? empty
        | +--ro selected-ipv4-address?  inet:ipv4-address
        | +--ro selected-ipv6-address?  inet:ipv6-address
        | +--ro interface-type?        ipi-rsvp-types:rsvp_interface_type_t
        | +--ro interface-index?       uint32
        | +--ro rsvp-status?           ipi-rsvp-types:rsvp_status_t
        | +--ro administrative-group-name* string
        | +--ro bundle-buffer-size?    uint16
        | +--ro epoch?                 uint32
    +--rw refresh-reduction
      | +--rw config
      | | +--rw enable-message-ack?    empty

```

---

---

```
| | +--rw disable-refresh-reduction? empty
| | +--rw ack-wait-timeout?      uint32
| | +--rw refresh-time?         uint16
| | +--rw keep-multiplier?      int32
| +--ro state
|   +--ro enable-message-ack?    empty
|   +--ro disable-refresh-reduction? empty
|   +--ro ack-wait-timeout?      uint32
|   +--ro refresh-time?         uint16
|   +--ro keep-multiplier?      int32
+--rw hellos
  +--rw config
    | +--rw enable-hello-receipt? empty
    | +--rw hello-interval?      int32
    | +--rw hello-timeout?      int32
  +--ro state
    +--ro enable-hello-receipt? empty
    +--ro hello-interval?      int32
    +--ro hello-timeout?      int32
```

## rpcs:

```
+---x clear-rsvp-session {feature-list:HAVE_RSVPD}?
+---x clear-rsvp-trunk {feature-list:HAVE_RSVPD}?
| +---w input
|   +---w trunk-name  string
+---x clear-rsvp-primary-trunk {feature-list:HAVE_RSVPD}?
| +---w input
|   +---w trunk-name  string
+---x clear-rsvp-secondary-trunk {feature-list:HAVE_RSVPD}?
| +---w input
|   +---w trunk-name  string
+---x clear-rsvp-ingress-trunk {feature-list:HAVE_RSVPD}?
| +---w input
|   +---w trunk-name  string
+---x clear-rsvp-non-ingress-trunk {feature-list:HAVE_RSVPD}?
| +---w input
```

---

```
| +---w trunk-name  string
+---x rsvp-trunk-force-reoptimize-on {feature-list:HAVE_RSVPD}?
| +---w input
|   +---w trunk-name  string
+---x rsvp-trunk-force-switchover-secondary {feature-list:HAVE_RSVPD}?
| +---w input
|   +---w trunk-name  string
|   +---w action      ipi-rsvp-types:rsvp_force_secondary_t
+---x rsvp-trunk-restart {feature-list:HAVE_RSVPD}?
| +---w input
|   +---w trunk-name  string
+---x rsvp-session-reset {feature-list:HAVE_RSVPD}?
| +---w input
|   +---w tunnel-id   uint32
|   +---w lsp-id      uint32
|   +---w ingress     inet:ipv4-address
|   +---w egress      inet:ipv4-address
+---x rsvp-trunk-force-auto-bandwidth-adjustment {feature-list:HAVE_AUTO_BANDWIDTH}?
| +---w input
|   +---w trunk-name      string
|   +---w force-auto-bandwidth-adjustment  boolean
|   +---w bandwidth      string
+---x rsvp-clear-auto-bandwidth {feature-list:HAVE_AUTO_BANDWIDTH}?
| +---w input
|   +---w autobw-profile  string
+---x clear-rsvp-trunk-auto-bandwidth-statistics {feature-list:HAVE_AUTO_BANDWIDTH}?
| +---w input
|   +---w trunk-name  string
+---x clear-rsvp-statistics {feature-list:HAVE_RSVPD}?
+---x rsvp-snmp-restart {feature-list:HAVE_SNMP}?
+---x rsvp-terminal-debug-on {feature-list:HAVE_RSVPD}?
| +---w input
|   +---w terminal-debug-options  ipi-rsvp-types:rsvp_debug_t
+---x rsvp-terminal-debug-off {feature-list:HAVE_RSVPD}?
| +---w input
|   +---w terminal-debug-options  ipi-rsvp-types:rsvp_debug_t
```

---

---

+---x restart-rsvp-graceful {feature-list:HAVE\_RSVP\_GRST}?

notifications:

+---n rsvp-session-up

| +--ro severity? cml-data-types:cml\_notif\_severity\_t  
| +--ro eventClass? cml-data-types:cml\_notif\_class\_t  
| +--ro session-name? string  
| +--ro trunk-id? uint32  
| +--ro extended-tunnel-id? inet:ip-address  
| +--ro egress? inet:ip-address  
| +--ro lsp-id? uint16  
| +--ro ingress? inet:ip-address  
| +--ro trunk-session-type? ipi-rsvp-types:rsvp\_sess\_type\_t

+---n rsvp-session-down

| +--ro severity? cml-data-types:cml\_notif\_severity\_t  
| +--ro eventClass? cml-data-types:cml\_notif\_class\_t  
| +--ro session-name? string  
| +--ro trunk-id? uint32  
| +--ro extended-tunnel-id? inet:ip-address  
| +--ro egress? inet:ip-address  
| +--ro lsp-id? uint16  
| +--ro ingress? inet:ip-address  
| +--ro trunk-session-type? ipi-rsvp-types:rsvp\_sess\_type\_t

+---n rsvp-session-force-switchover

| +--ro severity? cml-data-types:cml\_notif\_severity\_t  
| +--ro eventClass? cml-data-types:cml\_notif\_class\_t  
| +--ro session-name? string  
| +--ro trunk-id? uint32  
| +--ro extended-tunnel-id? inet:ip-address  
| +--ro egress? inet:ip-address  
| +--ro lsp-id? uint16  
| +--ro ingress? inet:ip-address  
| +--ro trunk-session-type? ipi-rsvp-types:rsvp\_sess\_type\_t

+---n rsvp-tunnel-reoptimized

| +--ro severity? cml-data-types:cml\_notif\_severity\_t  
| +--ro eventClass? cml-data-types:cml\_notif\_class\_t

---

```
| +--ro session-name?    string
| +--ro trunk-id?       uint32
| +--ro extended-tunnel-id?  inet:ip-address
| +--ro egress?         inet:ip-address
| +--ro lsp-id?         uint16
| +--ro ingress?        inet:ip-address
| +--ro trunk-session-type? ipi-rsvp-types:rsvp_sess_type_t
+---n rsvp-auto-bw-subceed-minimum-bandwidth {feature-list:HAVE_AUTO_BANDWIDTH}?
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro message?      string
+---n rsvp-auto-bw-exceed-maximum-bandwidth {feature-list:HAVE_AUTO_BANDWIDTH}?
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro message?      string
+---n rsvp-auto-bw-adjust-time-expiry {feature-list:HAVE_AUTO_BANDWIDTH}?
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro message?      string
+---n rsvp-auto-bw-overflow {feature-list:HAVE_AUTO_BANDWIDTH}?
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro message?      string
+---n rsvp-auto-bw-underflow {feature-list:HAVE_AUTO_BANDWIDTH}?
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro message?      string
+---n rsvp-auto-bw-exceed-limit {feature-list:HAVE_AUTO_BANDWIDTH}?
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?   cml-data-types:cml_notif_class_t
| +--ro message?      string
+---n rsvp-auto-bw-teardown {feature-list:HAVE_AUTO_BANDWIDTH}?
  +--ro severity?      cml-data-types:cml_notif_severity_t
  +--ro eventClass?   cml-data-types:cml_notif_class_t
  +--ro message?      string
```

---

## module: ipi-seamless-bfd

```
+--rw seamless-bfd
  +--ro state
  | +--ro remote-discriminator* string
  +--rw sr-policies
  | +--rw sr-policy* [lsp-type sr-policy-name]
  |   +--rw lsp-type      -> ../config/lsp-type
  |   +--rw sr-policy-name -> ../config/sr-policy-name
  |   +--rw config
  |     | +--rw lsp-type?    ipi-sbfd-types:sbfd_sr_type_t
  |     | +--rw sr-policy-name? string
  |     +--ro state
  |     | +--ro lsp-type?    ipi-sbfd-types:sbfd_sr_type_t
  |     | +--ro sr-policy-name? string
  |     +--rw session-attributes
  |       +--rw config
  |         | +--rw admin-down? empty
  |         +--ro state
  |         | +--ro admin-down? empty
  |         +--rw intervals
  |           +--rw interval* [minimum-tx detection-multiplier]
  |             +--rw minimum-tx      -> ../config/minimum-tx
  |             +--rw detection-multiplier -> ../config/detection-multiplier
  |             +--rw config
  |               | +--rw minimum-tx?      uint32
  |               | +--rw detection-multiplier? uint8
  |               +--ro state
  |                 +--ro minimum-tx?      uint32
  |                 +--ro detection-multiplier? uint8
  +--rw local-discriminators
  +--rw local-discriminator* [discriminator]
  +--rw discriminator -> ../config/discriminator
  +--rw config
  | +--rw discriminator?      string
```

```

| +--rw required-min-rx-interval? uint32
+--ro state
  +--ro discriminator? string
  +--ro required-min-rx-interval? uint32

```

---

## module: ipi-segment-routing

```

+--rw segment-routing {feature-list:HAVE_SRV6_OR_HAVE_SR_MPLS}?
  +--rw config!
    | +--rw enable empty
    | +--rw flex-algo-enable? empty
    +--ro state
      | +--ro enable empty
      | +--ro flex-algo-enable? empty
    +--rw interfaces {feature-list:HAVE_SR_MPLS}?
      | +--rw interface* [name]
      |   +--rw name -> ../config/name
      |   +--rw config
      |     | +--rw name? -> /ipi-interface:interfaces/interface/name
      |     +--rw adjacency-segment {feature-list:HAVE_SR_MPLS}?
      |       | +--rw config
      |       | | +--rw adj-sid-absolute? uint32
      |       | | +--rw adj-sid-index? uint32
      |       | | +--ro state
      |       | |   +--ro adj-sid-absolute? uint32
      |       | |   +--ro adj-sid-index? uint32
      |     +--rw prefix-segment-algorithms {feature-list:HAVE_SR_MPLS}?
      |       +--rw prefix-segment-algorithm* [algorithm-num]
      |         +--rw algorithm-num -> ../config/algorithm-num
      |         +--rw config
      |           | +--rw algorithm-num? ipi-sr-types:sr_algo_choice_t
      |           | +--rw sid-absolute? uint32

```

```

|   | +--rw sid-index?    uint32
|   | +--rw exp-null?    ipi-sr-types:if_sr_prefix_flag_t
|   | +--rw n-flag-clear? ipi-sr-types:if_sr_n_flag_clear_t
|   +--ro state
|     +--ro algorithm-num? ipi-sr-types:sr_algo_choice_t
|     +--ro sid-absolute?  uint32
|     +--ro sid-index?    uint32
|     +--ro exp-null?    ipi-sr-types:if_sr_prefix_flag_t
|     +--ro n-flag-clear? ipi-sr-types:if_sr_n_flag_clear_t
+--rw sr-mpls {feature-list:HAVE_SR_MPLS}?
| +--rw sr-prefer-over-ldp
| | +--rw config
| | | +--rw enable-preference? empty
| | +--ro state
| | +--ro enable-preference? empty
| +--rw bindings
| | +--rw mapping-server
| | +--rw config!
| | | +--rw enable empty
| | +--ro state
| | | +--ro enable empty
| | +--rw srms-preferenece
| | | +--rw config
| | | | +--rw preference? uint8
| | | +--ro state
| | | +--ro preference? uint8
| | +--rw prefix-sid-map-ipv4
| | +--rw config!
| | | +--rw enable empty
| | +--ro state
| | | +--ro enable empty
| | +--rw mapping-entries
| | +--rw mapping-entry* [start-address start-sid]
| | +--rw start-address -> ../config/start-address
| | +--rw start-sid -> ../config/start-sid
| | +--rw config

```

---

```
| | | +-rw start-address? cml-data-types:cml_ipv4_prefix_t
| | | +-rw start-sid? uint32
| | | +-rw range? uint32
| | | +-rw attached? boolean
| | | +-rw algorithm-num? uint32
| | +-ro state
| | | +-ro start-address? cml-data-types:cml_ipv4_prefix_t
| | | +-ro start-sid? uint32
| | | +-ro range? uint32
| | | +-ro attached? boolean
| | | +-ro algorithm-num? uint32
| | +-ro ipv4-table
| | +-ro state
| | | +-ro start-prefix? cml-data-types:cml_ip_prefix_addr_t
| | | +-ro algorithm-num? uint8
| | | +-ro start-sid-index? uint16
| | | +-ro range? uint16
| | | +-ro end-prefix? cml-data-types:cml_ip_prefix_addr_t
| | | +-ro end-sid-index? uint16
| | | +-ro attached? empty
| | | +-ro preference? uint8
| +-rw global-block {feature-list:HAVE_SR_MPLS}?
| | +-rw config!
| | | +-rw start uint32
| | | +-rw end uint32
| | +-ro state
| | | +-ro start uint32
| | | +-ro end uint32
| +-rw local-block {feature-list:HAVE_SR_MPLS}?
| | +-rw config!
| | | +-rw start uint32
| | | +-rw end uint32
| | +-ro state
| | | +-ro start uint32
| | | +-ro end uint32
+-rw traffic-engineering {feature-list:HAVE_SR_POLICY_OR_HAVE_SRV6}?
```

```

| +--rw config!
| | +--rw fast-reroute-enable? empty {feature-list:HAVE_SR_POLICY}?
| | +--rw enable          empty
| +--ro state
| | +--ro fast-reroute-enable? empty {feature-list:HAVE_SR_POLICY}?
| | +--ro enable          empty
| +--rw attributes
| | +--rw segment-lists {feature-list:HAVE_SR_POLICY_OR_HAVE_SRV6}?
| |   +--rw segment-list* [list-name]
| |     +--rw list-name  -> ../config/list-name
| |     +--rw config
| |       | +--rw list-name? string
| |       +--ro state
| |         | +--ro list-name? string
| |         +--rw segments
| |           +--rw segment* [segment-index type]
| |             | +--rw segment-index  -> ../config/segment-index
| |             | +--rw type          -> ../config/type
| |             | +--rw config
| |             | | +--rw segment-index? uint32
| |             | | +--rw type?        ipi-sr-types:srte_segment_type_mpls_t
| |             | +--ro state
| |             | | +--ro segment-index? uint32
| |             | | +--ro type?        ipi-sr-types:srte_segment_type_mpls_t
| |             | +--rw segment-type-1 {feature-list:HAVE_SR_MPLS}?
| |             |   +--rw config
| |             |   | +--rw sid-value? uint32
| |             |   +--ro state
| |             |   +--ro sid-value? uint32
| |             +--rw segment-v6* [segment-index type]
| |               +--rw segment-index  -> ../config/segment-index
| |               +--rw type          -> ../config/type
| |               +--rw config
| |                 | +--rw segment-index? uint32
| |                 | +--rw type?        ipi-sr-types:srte_segment_type_2_t
| |                 +--ro state

```

```

| | | | +--ro segment-index? uint32
| | | | +--ro type? ipi-sr-types:srte_segment_type_2_t
| | | | +--rw segment-type-2 {feature-list:HAVE_SRV6}?
| | | |   +--rw config
| | | | | +--rw prefix? inet:ipv6-address
| | | | | +--ro state
| | | | |   +--ro prefix? inet:ipv6-address
| | +--rw policies {feature-list:HAVE_SR_POLICY_OR_HAVE_SRV6}?
| | +--rw policy* [name]
| | | +--rw name -> ../config/name
| | | +--rw policy-keys
| | | | +--rw policy-key* [color end-point]
| | | | | +--rw color -> ../config/color
| | | | | +--rw end-point -> ../config/end-point
| | | | | +--rw config
| | | | | | +--rw color? uint32
| | | | | | +--rw end-point? inet:ip-address
| | | | | | +--ro state
| | | | | |   +--ro color? uint32
| | | | | |   +--ro end-point? inet:ip-address
| | | +--rw config
| | | | +--rw name? string
| | | | +--rw admin-state? empty
| | | | +--rw explicit-null? ipi-sr-types:srte_explicite_null_type_t {feature-list:HAVE_SR_POLICY}?
| | | | +--rw cspf-retry-limit? uint32 {feature-list:HAVE_SR_POLICY}?
| | | | +--rw cspf-retry-interval? uint32 {feature-list:HAVE_SR_POLICY}?
| | | | +--rw entropy-erld? uint8 {feature-list:HAVE_SR_POLICY}?
| | | | +--rw pce-lsp-delegate? empty {feature-list:HAVE_PCEP_SR_OR_HAVE_PCEP_SRV6}?
| | | | +--rw pce-state-report? empty {feature-list:HAVE_PCEP_SR_OR_HAVE_PCEP_SRV6}?
| | | | +--rw pce-entity-id? uint32 {feature-list:HAVE_PCEP_SR_OR_HAVE_PCEP_SRV6}?
| | | | +--rw bsid-value? uint32 {feature-list:HAVE_SR_POLICY}?
| | +--rw candidate-paths
| | | +--rw candidate-path* [discriminator protocol-origin originator]
| | | | +--rw discriminator -> ../config/discriminator
| | | | +--rw protocol-origin -> ../config/protocol-origin
| | | | +--rw originator -> ../config/originator

```

```

| | | +--rw config
| | | | +--rw discriminator? uint32
| | | | +--rw protocol-origin? ipi-sr-types:srte_protocol_origin_type_type_t
| | | | +--rw originator? string
| | | | +--rw preference? uint32
| | | +--ro state
| | | | +--ro discriminator? uint32
| | | | +--ro protocol-origin? ipi-sr-types:srte_protocol_origin_type_type_t
| | | | +--ro originator? string
| | | | +--ro preference? uint32
| | | | +--ro is-valid? boolean
| | | | +--ro non-selection-reason? cml-data-types:cml_line_t
| | | | +--ro is-best-candidate-path? boolean
| | | +--ro forwarding-paths
| | | | +--ro forwarding-path
| | | | | +--ro state
| | | | | | +--ro path-id? uint8
| | | | | | +--ro next-hop-address? inet:ip-address
| | | | | | +--ro outgoing-interface? string
| | | | | | +--ro path-type? string
| | | | | +--ro label-stack
| | | | | | +--ro labels
| | | | | | +--ro state
| | | | | | +--ro label? string
| | | +--rw dynamic {feature-list:HAVE_SR_POLICY_OR_HAVE_PCEP_SRV6}?
| | | | +--rw config
| | | | | +--rw pcep? empty {feature-list:HAVE_PCEP_SR_OR_HAVE_PCEP_SRV6}?
| | | | | +--rw isis? string
| | | | | +--rw ospf? int32
| | | | | +--rw ospf-empty? empty
| | | | +--ro state
| | | | | +--ro pcep? empty {feature-list:HAVE_PCEP_SR_OR_HAVE_PCEP_SRV6}?
| | | | | +--ro isis? string
| | | | | +--ro ospf? int32
| | | | | +--ro ospf-empty? empty
| | | | +--rw constraints

```

```

| | | | +--rw config!
| | | | | +--rw enable empty
| | | | +--ro state
| | | | | +--ro enable empty
| | | | +--rw admin-groups {feature-list:HAVE_SR_POLICY_OR_HAVE_PCEP_SRV6}?
| | | | | +--rw admin-group* [admin-group-name] {feature-list:HAVE_SR_POLICY_OR_HAVE_PCEP_SRV6}?
| | | | | | +--rw admin-group-name -> ../config/admin-group-name
| | | | | +--rw config
| | | | | | +--rw affinity-type? ipi-sr-types:sr_te_admin_group_type_t
| | | | | | +--rw admin-group-name? string
| | | | | +--ro state
| | | | | | +--ro affinity-type? ipi-sr-types:sr_te_admin_group_type_t
| | | | | | +--ro admin-group-name? string
| | | | +--rw bounds
| | | | | +--rw bound* [metric-type]
| | | | | | +--rw metric-type -> ../config/metric-type
| | | | | +--rw config
| | | | | | +--rw metric-type? ipi-sr-types:srte_cp_metric_type_t
| | | | | | +--rw bound? uint32
| | | | | | +--rw segment-bound? uint32
| | | | | +--ro state
| | | | | | +--ro metric-type? ipi-sr-types:srte_cp_metric_type_t
| | | | | | +--ro bound? uint32
| | | | | | +--ro segment-bound? uint32
| | | | +--rw ip
| | | | | +--rw include-hop* [address]
| | | | | | +--rw address -> ../config/address
| | | | | +--rw config
| | | | | | +--rw address? inet:ip-address
| | | | | | +--rw type? ipi-sr-types:srte_ip_constraint_hop_type_t
| | | | | +--ro state
| | | | | | +--ro address? inet:ip-address
| | | | | | +--ro type? ipi-sr-types:srte_ip_constraint_hop_type_t
| | | | +--rw segment-rule
| | | | | +--rw config!
| | | | | | +--rw enable empty

```

```

| | | | | +--ro state
| | | | | | +--ro enable   empty
| | | | | | +--rw property
| | | | | |   +--rw config!
| | | | | | | +--rw dataplane-type? ipi-sr-types:sr_dyn_cp_dataplane_type_t
| | | | | | | +--rw sid-algorithm?   uint32
| | | | | | | +--rw protection-type? ipi-sr-types:sr_dyn_cp_protection_type_t
| | | | | |   +--ro state
| | | | | |   +--ro dataplane-type? ipi-sr-types:sr_dyn_cp_dataplane_type_t
| | | | | |   +--ro sid-algorithm?   uint32
| | | | | |   +--ro protection-type? ipi-sr-types:sr_dyn_cp_protection_type_t
| | | | | +--rw disjoint-paths
| | | | |   +--rw disjoint-path* [group-id disjoint-type]
| | | | |     +--rw group-id      -> ../config/group-id
| | | | |     +--rw disjoint-type -> ../config/disjoint-type
| | | | |     +--rw config!
| | | | |       +--rw group-id?    uint32
| | | | |       +--rw disjoint-type? ipi-sr-types:sr_dyn_cp_disjoint_path_type_t
| | | | |       +--rw sub-id?     uint32
| | | | |     +--ro state
| | | | |       +--ro group-id?    uint32
| | | | |       +--ro disjoint-type? ipi-sr-types:sr_dyn_cp_disjoint_path_type_t
| | | | |       +--ro sub-id?     uint32
| | | | +--rw explicit
| | | |   +--rw segment-lists {feature-list:HAVE_SR_POLICY_OR_HAVE_SRV6}?
| | | |     +--rw segment-list* [list-name]
| | | |       +--rw list-name  -> ../config/list-name
| | | |       +--rw config
| | | |       +--rw list-name?  string
| | +--ro state
| |   +--ro statistics {feature-list:HAVE_SR_POLICY}?
| |     +--ro tx-bytes?   uint64
| |     +--ro rx-bytes?   uint64
| |     +--ro tx-packets? uint64
| |     +--ro rx-packets? uint64
| |   +--ro name?        string

```

---

```

| | +--ro admin-state?      empty
| | +--ro explicit-null?   ipi-sr-types:srte_explicite_null_type_t {feature-list:HAVE_SR_POLICY}?
| | +--ro cspf-retry-limit? uint32 {feature-list:HAVE_SR_POLICY}?
| | +--ro cspf-retry-interval? uint32 {feature-list:HAVE_SR_POLICY}?
| | +--ro entropy-erld?    uint8 {feature-list:HAVE_SR_POLICY}?
| | +--ro pce-lsp-delegate? empty {feature-list:HAVE_PCEP_SR_OR_HAVE_PCEP_SRV6}?
| | +--ro pce-state-report? empty {feature-list:HAVE_PCEP_SR_OR_HAVE_PCEP_SRV6}?
| | +--ro pce-entity-id?   uint32 {feature-list:HAVE_PCEP_SR_OR_HAVE_PCEP_SRV6}?
| | +--ro bsid-value?      uint32 {feature-list:HAVE_SR_POLICY}?
| | +--ro oper-state?      ipi-sr-types:srte_policy_oper_state_t
| | +--ro transition-count? uint32
| | +--ro up-time?         string
| | +--ro down-time?       string
| | +--ro bsid-alloc-mode? string
| | +--ro bsid-oper-state? ipi-sr-types:sr_policy_bsid_oper_state
| +--rw on-demand-nexthops {feature-list:HAVE_SR_POLICY}?
|   +--rw on-demand-nexthop* [color]
|     +--rw color          -> ../config/color
|     +--rw config
|       | +--rw color?      uint32
|       | +--rw cspf-retry-limit? uint16
|       | +--rw cspf-retry-interval? uint16
|       | +--rw pce-lsp-delegate? empty {feature-list:HAVE_PCEP_SR}?
|       | +--rw pce-state-report? empty {feature-list:HAVE_PCEP_SR}?
|       | +--rw pce-entity-id?   uint8 {feature-list:HAVE_PCEP_SR}?
|       | +--rw binding-sid-label? uint16
|       +--ro state
|         | +--ro color?      uint32
|         | +--ro cspf-retry-limit? uint16
|         | +--ro cspf-retry-interval? uint16
|         | +--ro pce-lsp-delegate? empty {feature-list:HAVE_PCEP_SR}?
|         | +--ro pce-state-report? empty {feature-list:HAVE_PCEP_SR}?
|         | +--ro pce-entity-id?   uint8 {feature-list:HAVE_PCEP_SR}?
|         | +--ro binding-sid-label? uint16
|         +--rw candidate-paths
|           +--rw candidate-path* [discriminator protocol-origin originator]

```

---

```

|   +--rw discriminator   -> ../config/discriminator
|   +--rw protocol-origin -> ../config/protocol-origin
|   +--rw originator      -> ../config/originator
|   +--rw config
|   |   +--rw discriminator?   uint32
|   |   +--rw protocol-origin? ipi-sr-types:srte_protocol_origin_type_type_t
|   |   +--rw originator?      string
|   |   +--rw preference?      uint16
|   +--ro state
|   |   +--ro discriminator?   uint32
|   |   +--ro protocol-origin? ipi-sr-types:srte_protocol_origin_type_type_t
|   |   +--ro originator?      string
|   |   +--ro preference?      uint16
|   +--rw dynamic {feature-list:HAVE_SR_POLICY}?
|   |   +--rw config
|   |   |   +--rw pcep?          empty {feature-list:HAVE_PCEP_SR}?
|   |   |   +--rw isis-instance-id? string
|   |   |   +--rw ospf-process-id? int32
|   |   |   +--rw ospf-empty?    empty
|   |   +--ro state
|   |   |   +--ro pcep?          empty {feature-list:HAVE_PCEP_SR}?
|   |   |   +--ro isis-instance-id? string
|   |   |   +--ro ospf-process-id? int32
|   |   |   +--ro ospf-empty?    empty
|   |   +--rw constraints
|   |   |   +--rw config!
|   |   |   |   +--rw enable    empty
|   |   +--ro state
|   |   |   +--ro enable    empty
|   |   +--rw affinity-admin-groups
|   |   |   +--rw affinity-admin-group* [admin-group-name] {feature-list:HAVE_SR_POLICY}?
|   |   |   |   +--rw admin-group-name -> ../config/admin-group-name
|   |   |   |   +--rw config
|   |   |   |   |   +--rw affinity-type?    ipi-sr-types:sr_te_admin_group_type_t
|   |   |   |   |   +--rw admin-group-name? string
|   |   |   +--ro state

```

```

|         |   +--ro affinity-type?   ipi-sr-types:sr_te_admin_group_type_t
|         |   +--ro admin-group-name? string
|         +--rw bounds
|         |   +--rw bound* [metric-type]
|         |   +--rw metric-type   -> ../config/metric-type
|         |   +--rw config
|         |   |   +--rw metric-type? ipi-sr-types:srte_cp_metric_type_t
|         |   |   +--rw bound?      uint32
|         |   +--ro state
|         |   +--ro metric-type? ipi-sr-types:srte_cp_metric_type_t
|         |   +--ro bound?      uint32
|         +--rw ip
|         |   +--rw include-hops
|         |   |   +--rw include-hop* [address]
|         |   |   +--rw address   -> ../config/address
|         |   |   +--rw config
|         |   |   |   +--rw address? inet:ip-address
|         |   |   |   +--rw type?   ipi-sr-types:srte_ip_constraint_hop_type_t
|         |   |   +--ro state
|         |   |   +--ro address?  inet:ip-address
|         |   |   +--ro type?    ipi-sr-types:srte_ip_constraint_hop_type_t
+--rw srv6 {feature-list:HAVE_SRV6}?
| +--rw config!
| | +--rw enable  empty
| | +--ro state
| | +--ro enable  empty
| +--rw locators {feature-list:HAVE_SRV6}?
| | +--rw config!
| | | +--rw enable  empty
| | | +--ro state
| | | +--ro enable  empty
| | +--rw locator* [locator-name]
| | | +--rw locator-name  -> ../config/locator-name
| | | +--rw config
| | | | +--rw locator-name? string
| | | | +--rw prefix?      cml-data-types:cml_ipv6_prefix_t

```

```
| | +--ro state
| |   +--ro locator-name?  string
| |   +--ro prefix?       cml-data-types:cml_ipv6_prefix_t
| |   +--ro uptime?       string
| +--ro services-entries
| | +--ro services-entry* [fec-ipv4-prefix service-vrf-id]
| |   +--ro fec-ipv4-prefix -> ../state/fec-ipv4-prefix
| |   +--ro service-vrf-id  -> ../state/service-vrf-id
| |   +--ro state
| |     +--ro fec-ipv4-prefix?  cml-data-types:cml_ipv4_prefix_t
| |     +--ro service-vrf-id?   uint32
| |     +--ro service-vrf-name? string
| |     +--ro service-type?     string
| |     +--ro flags?            string
| |     +--ro address-family?   uint32
| |     +--ro sid?              inet:ipv6-address
| |     +--ro nexthop-ipv6-prefix? inet:ipv6-address
| |     +--ro service-policy-name? string
| +--ro transport-entries
| | +--ro transport-entry* [fec]
| |   +--ro fec      -> ../state/fec
| |   +--ro state
| |     | +--ro fec?          inet:ipv6-address
| |     | +--ro policy-name?  string
| |     | +--ro policy-id?    uint32
| |     | +--ro transport-color? uint32
| |     | +--ro code?         string
| |     | +--ro is-primary?   boolean
| |     | +--ro out-sid?      inet:ipv6-address
| |     | +--ro out-interface? string
| |     | +--ro nexthop?      inet:ipv6-address
| |   +--ro ftn-entries
| |     +--ro ftn-entry* [vrf-id fec-prefix]
| |       +--ro vrf-id      -> ../state/vrf-id
| |       +--ro fec-prefix  -> ../state/fec-prefix
| |       +--ro state
```

```

| |      +--ro vrf-id?      uint32
| |      +--ro fec-prefix?  cml-data-types:cml_ipv4_addr_prefix_t
| |      +--ro vrf-name?    string
| |      +--ro ftn-nexthop? inet:ipv6-address
| |      +--ro tunnel-policy? string
| |      +--ro ftn-color?   uint32
| +--ro manager-entries {feature-list:HAVE_SRV6}?
|   +--ro state
|     +--ro protocol-state?          ipi-sr-types:srv6_protocol_state_t
|     +--ro srv6-locator-name?       string
|     +--ro platform-capabilities-end-function*  string
|     +--ro platform-capabilities-ingress-function*  string
|     +--ro platform-capabilities-ingress-sr-policy*  string
+--rw debug {feature-list:HAVE_SR_POLICY_OR_HAVE_SRV6}?
  +--rw config
  | +--rw options? ipi-sr-types:sr_te_debug_t
  +--ro state
    +--ro options?          ipi-sr-types:sr_te_debug_t
    +--ro terminal-debug-status? ipi-sr-types:sr_te_debug_t

```

## rpcs:

```

+---x sr-policy-terminal-debug-all-on {feature-list:HAVE_SR_POLICY_OR_HAVE_SRV6_OR_HAVE_SR_MPLS}?
+---x sr-policy-terminal-debug-on {feature-list:HAVE_SR_POLICY_OR_HAVE_SRV6_OR_HAVE_SR_MPLS}?
| +---w input
|   +---w terminal-debug-options ipi-sr-types:sr_te_debug_t
+---x sr-policy-terminal-debug-off {feature-list:HAVE_SR_POLICY_OR_HAVE_SRV6_OR_HAVE_SR_MPLS}?
  +---w input
    +---w terminal-debug-options ipi-sr-types:sr_te_debug_t

```

## notifications:

```

+---n sr-policy-oper-state-down
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name?      string
| +--ro oper-state? ipi-sr-types:srte_policy_oper_state_t
+---n sr-policy-oper-state-up

```

---

```

| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro name?      string
| +--ro oper-state? ipi-sr-types:srte_policy_oper_state_t
+---n sr-policy-cp-active
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro discriminator? uint32
| +--ro protocol-origin? ipi-sr-types:srte_protocol_origin_type_type_t
| +--ro originator?  string
| +--ro name?        string
| +--ro is-valid?    boolean
+---n sr-policy-cp-inactive
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass? cml-data-types:cml_notif_class_t
| +--ro discriminator? uint32
| +--ro protocol-origin? ipi-sr-types:srte_protocol_origin_type_type_t
| +--ro originator?  string
| +--ro name?        string
| +--ro is-valid?    boolean
+---n sr-policy-binding-sid-unavailable-event {feature-list:HAVE_SR_POLICY}?
  +--ro severity?  cml-data-types:cml_notif_severity_t
  +--ro eventClass? cml-data-types:cml_notif_class_t
  +--ro name?      string
  +--ro bsid-value? uint32

```

---

## module: ipi-service-map

```

+--rw service-map {feature-list:HAVE_SERVICE_MAPPING}?
  +--rw tunnel-policies
    +--rw tunnel-policy* [name]
      +--rw name  -> ../config/name
      +--rw config
        | +--rw name?      string
        | +--rw color-code* uint32

```

```

| +--rw selection-mode? ipi-service-map-types:tunnel_selection_mode_t
| +--rw tunnel-type? ipi-service-map-types:tunnel_selection_type_t {feature-
list:HAVE_SRV6_OR_HAVE_SR_MPLS_OR_HAVE_MPLS}?
+--ro state
+--ro name? string
+--ro color-code* uint32
+--ro selection-mode? ipi-service-map-types:tunnel_selection_mode_t
+--ro tunnel-type? ipi-service-map-types:tunnel_selection_type_t {feature-
list:HAVE_SRV6_OR_HAVE_SR_MPLS_OR_HAVE_MPLS}?

```

---

## module: ipi-sflow-interface

augment /ipi-sflow:sampling/ipi-sflow:sflow:

```

+--rw interfaces
+--rw interface* [name]
+--rw name -> ../config/name
+--rw config
| +--rw name? -> /ipi-interface:interfaces/interface/name
| +--rw enabled? empty
| +--rw polling-interval? uint8
| +--rw collector-id? uint8
+--ro state
| +--ro name? -> /ipi-interface:interfaces/interface/name
| +--ro enabled? empty
| +--ro polling-interval? uint8
| +--ro collector-id? uint8
| +--ro polling-count? yang:counter32
+--rw ingress
| +--rw config!
| | +--rw sampling-rate uint32
| | +--rw sample-size uint16
| +--ro state
| +--ro sampling-rate uint32
| +--ro sample-size uint16
| +--ro sampling-status? ipi-sflow-types:sflow_egress_ingress_t

```

```

|   +--ro sampled-packet-count? yang:counter32
+--rw egress
  +--rw config!
    |   +--rw sampling-rate  uint32
    |   +--rw sample-size   uint16
    +--ro state
      +--ro sampling-rate      uint32
      +--ro sample-size       uint16
      +--ro sampling-status?   ipi-sflow-types:sflow_egress_ingress_t
      +--ro sampled-packet-count? yang:counter32

```

rpcs:

```

+---x sflow-clear-statistics {feature-list:HAVE_SFLOW}?
  +---w input
    +---w interface  string

```

---

## module: ipi-sflow-ipfix

```

+--rw ipfix
  +--rw ip-flow-exporters
    |   +--rw ip-flow-exporter* [exporter-name]
    |   +--rw exporter-name  -> ../config/exporter-name
    |   +--rw config
    |     |   +--rw exporter-name?      string
    |     |   +--rw source-if?          -> /ipi-interface:interfaces/interface/name
    |     |   +--rw collector-ip?       inet:ipv4-address
    |     |   +--rw collector-port?     inet:port-number
    |     |   +--rw collector-vrf?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name {feature-list:HAVE_VRF}?
    |     |   +--rw template-id?        uint32
    |     |   +--rw template-refresh-interval? uint32
    |     |   +--rw samples-per-message?  uint32
    |     +--ro state
    |       +--ro exporter-name?        string
    |       +--ro source-if?            -> /ipi-interface:interfaces/interface/name
    |       +--ro collector-ip?         inet:ipv4-address

```

---

```

|   +--ro collector-port?      inet:port-number
|   +--ro collector-vrf?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name {feature-list:HAVE_VRF}?
|   +--ro template-id?        uint32
|   +--ro template-refresh-interval? uint32
|   +--ro samples-per-message?  uint32
+--rw ip-flow-monitors
| +--rw ip-flow-monitor* [monitor-name]
|   +--rw monitor-name  -> ../config/monitor-name
|   +--rw config
|     | +--rw monitor-name?      string
|     | +--rw flow-exporter?     -> /ipfix/ip-flow-exporters/ip-flow-exporter/exporter-name
|     | +--rw sampling-rate?     uint32
|     | +--rw observation-domain-id? uint32
|     +--ro state
|       +--ro monitor-name?      string
|       +--ro flow-exporter?     -> /ipfix/ip-flow-exporters/ip-flow-exporter/exporter-name
|       +--ro sampling-rate?     uint32
|       +--ro observation-domain-id? uint32
+--rw interfaces
  +--rw interface* [interface-name]
    +--rw interface-name  -> ../config/interface-name
    +--rw config
      | +--rw interface-name? -> /ipi-interface:interfaces/interface/name
      | +--rw flow-monitor?   -> /ipfix/ip-flow-monitors/ip-flow-monitor/config/monitor-name
    +--ro state
      +--ro interface-name? -> /ipi-interface:interfaces/interface/name
      +--ro flow-monitor?   -> /ipfix/ip-flow-monitors/ip-flow-monitor/config/monitor-name

```

---

## module: ipi-sflow

```

+--rw sampling
  +--rw sflow
    +--rw config!
      | +--rw enabled      empty

```

---

```

| +--rw source-address?  inet:ipv4-address
| +--rw cpu-rate-limit?  uint32 {feature-list:HAVE_BROADCOM,feature-list:NOT_HAVE_DUNE}?
+--ro state
| +--ro enabled          empty
| +--ro source-address?  inet:ipv4-address
| +--ro cpu-rate-limit?  uint32 {feature-list:HAVE_BROADCOM,feature-list:NOT_HAVE_DUNE}?
| +--ro sflow-version?   string
| +--ro datagram-version? uint8
+--rw collectors
| +--rw collector* [address port collector-id]
|   +--rw address      -> ../config/address
|   +--rw port         -> ../config/port
|   +--rw collector-id -> ../config/collector-id
|   +--rw config
|     | +--rw address?      inet:ipv4-address
|     | +--rw port?        inet:port-number
|     | +--rw receiver-timeout  uint32
|     | +--rw max-datagram-size  uint16
|     | +--rw collector-id?     uint8
|     | +--rw vrf-name        -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
|     {feature-list:HAVE_VRF}?
|     | +--ro state
|     |   +--ro address?      inet:ipv4-address
|     |   +--ro port?        inet:port-number
|     |   +--ro receiver-timeout  uint32
|     |   +--ro max-datagram-size  uint16
|     |   +--ro collector-id?     uint8
|     |   +--ro vrf-name        -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
|     {feature-list:HAVE_VRF}?
|     +--rw logging {feature-list:HAVE_CUSTOM1_ACL}?
|     | +--rw config
|     | | +--rw max-entries?  uint16
|     | | +--rw rate-limit?   uint16 {feature-list:HAVE_BROADCOM}?
|     | +--ro state
|     |   +--ro max-entries?  uint16
|     |   +--ro rate-limit?   uint16 {feature-list:HAVE_BROADCOM}?
+--rw debug

```

---

```

+--rw config
| +--rw options? ipi-sflow-types:sflow_debug_t
+--ro state
  +--ro options? ipi-sflow-types:sflow_debug_t
  +--ro terminal-debug-status? ipi-sflow-types:sflow_debug_t

```

rpcs:

```

+---x sflow-clear-access-list-log-cache {feature-list:HAVE_CUSTOM1_ACL}?
+---x sflow-terminal-debug-on {feature-list:HAVE_SFLOW}?
| +---w input
|   +---w terminal-debug-options ipi-sflow-types:sflow_debug_t
+---x sflow-terminal-debug-off {feature-list:HAVE_SFLOW}?
  +---w input
    +---w terminal-debug-options ipi-sflow-types:sflow_debug_t

```

notifications:

```

+---n sflow-receiver-timeout-alarm-message
  +--ro severity? cml-data-types:cml_notif_severity_t
  +--ro eventClass? cml-data-types:cml_notif_class_t
  +--ro message? string

```

---

## module: ipi-snmp-server-extended

```

+--rw snmp-dir
  +--rw config
  | +--rw include-directive? empty
  +--ro state
    +--ro include-directive? empty

```

augment /ipi-snmp:snmp/ipi-snmp-server:servers:

```

+--rw debug {feature-list:HAVE_SNMP_AGENT}?
  +--rw config
  | +--rw enable? empty
  +--ro state
    +--ro enable? empty

```

```

    +--ro terminal-debug-status?  cml-data-types:cml_on_off_t
augment /ipi-snmp:snmp/ipi-snmp-server:servers/ipi-snmp-server:server:
+--rw snmp-views {feature-list:HAVE_SNMP_AGENT}?
  +--rw snmp-view* [view-name] {feature-list:HAVE_SNMP_AGENT}?
    +--rw view-name  -> ../config/view-name
    +--rw config
      | +--rw view-name?  string
    +--ro state
      | +--ro view-name?  string
    +--rw oid-trees
      +--rw oid-tree* [oid] {feature-list:HAVE_SNMP_AGENT}?
        +--rw oid      -> ../config/oid
        +--rw config!
          | +--rw oid?      string
          | +--rw filter-type  ipi-snmp-server-extended-types:snmp_server_oid_tree_t
        +--ro state
          +--ro oid?      string
          +--ro filter-type  ipi-snmp-server-extended-types:snmp_server_oid_tree_t
augment /ipi-snmp:snmp:
+--rw engine-id {feature-list:HAVE_SNMP_V3,feature-list:HAVE_SNMP_AGENT}?
  +--rw config
    | +--rw engine-id?  string
  +--ro state
    +--ro engine-id?  string
augment /ipi-snmp:snmp/ipi-snmp-server:servers/ipi-snmp-server:server:
+--rw smux-port {feature-list:HAVE_SNMP_AGENT}?
  +--rw config
    | +--rw smux-port-enable?  empty
  +--ro state
    +--ro smux-port-enable?  empty
augment /ipi-snmp:snmp/ipi-snmp-server:servers/ipi-snmp-server:server:
+--rw hosts {feature-list:HAVE_SNMP_AGENT}?
  +--rw host* [host-name] {feature-list:HAVE_SNMP_AGENT}?
    +--rw host-name  -> ../config/host-name
    +--rw config
      | +--rw host-name?      string

```

```

| +--rw snmp-version?      ipi-snmp-server-extended-types:snmp_server_version_t
| +--rw notification-type? ipi-snmp-server-extended-types:snmp_server_notification_t
| +--rw udp-port?          uint32
| +--rw (host-option)?
|   +---:(use-community)
|     | +--rw community?   -> /ipi-snmp:snmp/ipi-snmp-server:servers/server/communities/community/
community-name
|     +---:(use-snmpv3-user)
|       | +--rw snmpv3-auth-type? ipi-snmp-server-extended-types:snmp_server_version3_auth_type_t
|       | +--rw snmpv3-user?     -> /ipi-snmp:snmp/ipi-snmp-server:servers/server/users/user/config/user-name
|       +---:(use-host-user)
|         +--rw host-user?      string
+--ro state
  +--ro host-name?             string
  +--ro snmp-version?          ipi-snmp-server-extended-types:snmp_server_version_t
  +--ro notification-type?     ipi-snmp-server-extended-types:snmp_server_notification_t
  +--ro udp-port?              uint32
  +--ro (host-option)?
    +---:(use-community)
      | +--ro community?      -> /ipi-snmp:snmp/ipi-snmp-server:servers/server/communities/community/
community-name
      +---:(use-snmpv3-user)
        | +--ro snmpv3-auth-type? ipi-snmp-server-extended-types:snmp_server_version3_auth_type_t
        | +--ro snmpv3-user?     -> /ipi-snmp:snmp/ipi-snmp-server:servers/server/users/user/config/user-name
        +---:(use-host-user)
          +--ro host-user?      string
augment /ipi-snmp:snmp/ipi-snmp-server:servers/ipi-snmp-server:server:
+--rw users {feature-list:HAVE_SNMP_AGENT}?
+--rw user* [user-name] {feature-list:HAVE_SNMP_AGENT,feature-list:HAVE_SNMP_V3}?
  +--rw user-name  -> ../config/user-name
  +--rw config
  | +--rw user-name?      string
  | +--rw user-type?      ipi-snmp-server-extended-types:snmp_server_group_name_t
  | +--rw user-group?     string
  | +--rw encryption-type? ipi-snmp-server-extended-types:snmp_server_key_type_t
  | +--rw authentication-type? ipi-snmp-server-extended-types:snmp_server_auth_t
  | +--rw authentication-password? string

```

---

```

| +--rw privilege-type?      ipi-snmp-server-extended-types:snmp_server_priv_t
| +--rw privilege-password?  string
+--ro state
  +--ro user-name?          string
  +--ro user-type?          ipi-snmp-server-extended-types:snmp_server_group_name_t
  +--ro user-group?         string
  +--ro encryption-type?    ipi-snmp-server-extended-types:snmp_server_key_type_t
  +--ro authentication-type? ipi-snmp-server-extended-types:snmp_server_auth_t
  +--ro authentication-password? string
  +--ro privilege-type?     ipi-snmp-server-extended-types:snmp_server_priv_t
  +--ro privilege-password? string
augment /ipi-snmp:snmp/ipi-snmp-server:servers/ipi-snmp-server:server:
+--rw contexts {feature-list:HAVE_SNMP_AGENT}?
  +--rw context* [context-name]
    +--rw context-name -> ../config/context-name
    +--rw config
    | +--rw context-name? string
    +--ro state
      +--ro context-name? string
augment /ipi-snmp:snmp/ipi-snmp-server:servers/ipi-snmp-server:server:
+--rw communities {feature-list:HAVE_SNMP_AGENT}?
  +--rw community* [community-name] {feature-list:HAVE_SNMP_AGENT}?
    +--rw community-name -> ../config/community-name
    +--rw config
    | +--rw community-name? string
    | +--rw acl-name? -> /ipi-acl:acl/standard-acl-sets/standard-acl-set/name
    | +--rw community-view-name? -> /ipi-snmp:snmp/ipi-snmp-server:servers/server/snmp-views/snmp-view/
view-name
    | +--rw version? ipi-snmp-server-extended-types:snmp_server_view_version_t
    | +--rw access? ipi-snmp-server-extended-types:snmp_server_access_t
    | +--rw (community-option)?
    | | +--:(use-group)
    | | | +--rw snmp-group? ipi-snmp-server-extended-types:snmp_server_group_t
    | | +--:(use-access)
    | | +--rw access-privileges? ipi-snmp-server-extended-types:snmp_server_access_t
    +--ro state
    | +--ro community-name? string

```

---

---

```

    | +--ro acl-name?          -> /ipi-acl:acl/standard-acl-sets/standard-acl-set/name
    | +--ro community-view-name?  -> /ipi-snmp:snmp/ipi-snmp-server:servers/server/snmp-views/snmp-view/
view-name
    | +--ro version?          ipi-snmp-server-extended-types:snmp_server_view_version_t
    | +--ro access?          ipi-snmp-server-extended-types:snmp_server_access_t
    | +--ro (community-option)?
    |   +--:(use-group)
    |     | +--ro snmp-group?    ipi-snmp-server-extended-types:snmp_server_group_t
    |     | +--:(use-access)
    |     |   +--ro access-privileges? ipi-snmp-server-extended-types:snmp_server_access_t
+--rw community-context-mapping
+--rw config
  | +--rw community-context?  string
  | +--rw community-user?    string
+--ro state
  +--ro community-context?  string
  +--ro community-user?    string
augment /ipi-snmp:snmp/ipi-snmp-server:servers/ipi-snmp-server:server:
+--rw server-groups {feature-list:HAVE_SNMP_AGENT}?
+--rw server-group* [group-name] {feature-list:HAVE_SNMP_AGENT}?
  +--rw group-name  -> ../config/group-name
  +--rw config
  | +--rw group-name?      string
  | +--rw group-version?  ipi-snmp-server-extended-types:snmp_server_version_t
  | +--rw snmpv3-group-auth-type? ipi-snmp-server-extended-types:snmp_v3_server_group_auth_type_t
  | +--rw context*        ipi-snmp-server-extended-types:snmp_server_context_name_t
+--ro state
  +--ro group-name?      string
  +--ro group-version?  ipi-snmp-server-extended-types:snmp_server_version_t
  +--ro snmpv3-group-auth-type? ipi-snmp-server-extended-types:snmp_v3_server_group_auth_type_t
  +--ro context*        ipi-snmp-server-extended-types:snmp_server_context_name_t
augment /ipi-snmp:snmp:
+--ro statistics {feature-list:HAVE_SNMP_AGENT}?
+--ro state
  +--ro engine-id?  cml-data-types:cml_line_t
augment /ipi-snmp:snmp:
+--ro default-global-values {feature-list:HAVE_SNMP_AGENT}?

```

---

```

+--ro state
  +--ro system-default-contact? ipi-snmp-server-extended-types:cml_line_without_pattern_t {feature-
list:HAVE_SNMP_AGENT}?
  +--ro system-default-location? ipi-snmp-server-extended-types:cml_line_without_pattern_t {feature-
list:HAVE_SNMP_AGENT}?

rpcs:
+---x snmp-server-terminal-debug-on {feature-list:HAVE_HOSTPD}?
+---x snmp-server-terminal-debug-off {feature-list:HAVE_HOSTPD}?

```

---

## module: ipi-snmp-server

```

+--rw custom
  +--rw config
  | +--rw ent-ipi-iftable? empty {feature-list:HAVE_SNMP_AGENT}?
  +--ro state
  | +--ro ent-ipi-iftable? empty {feature-list:HAVE_SNMP_AGENT}?

augment /ipi-snmp:snmp:
  +--rw servers {feature-list:HAVE_SNMP_AGENT}?
  | +--rw server* [vrf-name]
  | | +--rw vrf-name -> ../config/vrf-name
  | | +--rw config!
  | | | +--rw vrf-name? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
  | | | {feature-list:HAVE_VRF}?
  | | | +--rw enabled empty
  | | | +--ro state
  | | | +--ro vrf-name? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
  | | | {feature-list:HAVE_VRF}?
  | | | +--ro enabled empty
  | | +--rw global
  | | +--rw config
  | | | +--rw system-contact? cml-data-types:cml_line_t {feature-list:HAVE_SNMP_AGENT}?
  | | | +--rw system-location? cml-data-types:cml_line_t {feature-list:HAVE_SNMP_AGENT}?
  | | | +--rw tcp-session-enabled? empty {feature-list:HAVE_SNMP_AGENT}?
  | | +--ro state
  | | +--ro system-contact? cml-data-types:cml_line_t {feature-list:HAVE_SNMP_AGENT}?

```

```

|   +--ro system-location?    cml-data-types:cml_line_t {feature-list:HAVE_SNMP_AGENT}?
|   +--ro tcp-session-enabled? empty {feature-list:HAVE_SNMP_AGENT}?
+--rw default-instance
  +--rw config
    | +--rw disable-default-instance? empty
  +--ro state
    +--ro disable-default-instance? empty

```

---

## module: ipi-snmp

```

+--rw snmp {feature-list:HAVE_SNMP_AGENT}?
  +--rw server-traps
    +--rw config
      | +--rw enable-traps?      ipi-snmp-types:snmp_trap_protocols
      | +--rw enable-link-down-trap? boolean
      | +--rw enable-link-up-trap? boolean
      | +--rw include-interface-name? empty
    +--ro state
      | +--ro enable-traps?      ipi-snmp-types:snmp_trap_protocols
      | +--ro enable-link-down-trap? boolean
      | +--ro enable-link-up-trap? boolean
      | +--ro include-interface-name? empty
    +--rw trap-cache
      +--rw config!
        | +--rw enable-trap-cache empty {feature-list:HAVE_SNMP_AGENT}?
        | +--rw timeout?         int8
        | +--rw disable-ping?    empty
        | +--rw max-count?       int16
      +--ro state
        +--ro enable-trap-cache empty {feature-list:HAVE_SNMP_AGENT}?
        +--ro timeout?          int8
        +--ro disable-ping?     empty
        +--ro max-count?        int16

```

rpcs:

```

+---x snmp-agentx-enable-terminal-debugging {feature-list:HAVE_AGENTX}?
| +---w input
|   +---w debug   ipi-snmp-types:snmp_agentx_debug_type_t
+---x snmp-agentx-disable-terminal-debugging {feature-list:HAVE_AGENTX}?
  +---w input
    +---w debug   ipi-snmp-types:snmp_agentx_debug_type_t

```

---

## module: ipi-source-interface

```

+--rw source-interface {feature-list:HAVE_HOSTPD}?
  +--rw address-family-ipv4
  | +--rw source-nat-mappings
  |   +--rw source-nat-mapping* [interface-name protocol-type vrf-name]
  |     +--rw interface-name  -> ../config/interface-name
  |     +--rw protocol-type   -> ../config/protocol-type
  |     +--rw vrf-name        -> ../config/vrf-name
  |     +--rw config
  |       | +--rw interface-name? -> /ipi-interface:interfaces/interface/name
  |       | +--rw protocol-type?  ipi-source-interface-types:src_intf_proto_types_t
  |       | +--rw port-number     ipi-source-interface-types:src_intf_port_number_t
  |       | +--rw vrf-name?       -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
  |       {feature-list:HAVE_VRF}?
  |         +--ro state
  |         +--ro interface-name? -> /ipi-interface:interfaces/interface/name
  |         +--ro protocol-type?  ipi-source-interface-types:src_intf_proto_types_t
  |         +--ro port-number     ipi-source-interface-types:src_intf_port_number_t
  |         +--ro vrf-name?       -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
  |         {feature-list:HAVE_VRF}?
  |           +--ro address?      inet:ip-address
  |           +--ro status?      ipi-source-interface-types:src_intf_status_t
  +--rw address-family-ipv6 {feature-list:HAVE_IPV6}?
    +--rw source-nat-mappings
      +--rw source-nat-mapping* [interface-name protocol-type vrf-name]
        +--rw interface-name  -> ../config/interface-name
        +--rw protocol-type   -> ../config/protocol-type

```

```

+--rw vrf-name      -> ../config/vrf-name
+--rw config
| +--rw interface-name? -> /ipi-interface:interfaces/interface/name
| +--rw protocol-type?  ipi-source-interface-types:src_intf_proto_types_t
| +--rw port-number     ipi-source-interface-types:src_intf_port_number_t
| +--rw vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
{feature-list:HAVE_VRF}?
+--ro state
+--ro interface-name? -> /ipi-interface:interfaces/interface/name
+--ro protocol-type?  ipi-source-interface-types:src_intf_proto_types_t
+--ro port-number     ipi-source-interface-types:src_intf_port_number_t
+--ro vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
{feature-list:HAVE_VRF}?
+--ro address?       inet:ip-address
+--ro status?        ipi-source-interface-types:src_intf_status_t

```

---

## module: ipi-ssh

```

+--rw ssh-server
+--rw debug
| +--rw config
| | +--rw enable?  empty
| +--ro state
| +--ro enable?    empty
| +--ro terminal-debug-status? cml-data-types:cml_on_off_t
+--rw vrfs
+--rw vrf* [vrf-name]
+--rw vrf-name      -> ../config/vrf-name
+--rw config
| +--rw vrf-name?   -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
| +--rw enable      boolean {feature-list:HAVE_SSH_SERVER}?
| +--rw port?       uint32 {feature-list:HAVE_SSH_SERVER}?
| +--rw session-limit?  uint8 {feature-list:HAVE_SSH_SERVER}?

```

---

```
| +--rw max-login-attempts? uint8 {feature-list:HAVE_SSH_SERVER}?
| +--rw default-algorithm? empty
+--ro state
| +--ro vrf-name?          -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
| +--ro enable             boolean {feature-list:HAVE_SSH_SERVER}?
| +--ro port?             uint32 {feature-list:HAVE_SSH_SERVER}?
| +--ro session-limit?    uint8 {feature-list:HAVE_SSH_SERVER}?
| +--ro max-login-attempts? uint8 {feature-list:HAVE_SSH_SERVER}?
| +--ro default-algorithm? empty
+--rw encryption-algorithms {feature-list:HAVE_SSH_SERVER}?
| +--rw config
| | +--rw aes128-ctr?      empty
| | +--rw aes192-ctr?     empty
| | +--rw aes256-ctr?     empty
| | +--rw aes128-cbc?     empty
| | +--rw aes192-cbc?     empty
| | +--rw aes256-cbc?     empty
| | +--rw triple-des-cbc? empty
| | +--rw rijndael-cbc?   empty
| | +--rw aes128-gcm?     empty
| | +--rw aes256-gcm?     empty
| | +--rw chacha20-poly1305? empty
| +--ro state
|   +--ro aes128-ctr?      empty
|   +--ro aes192-ctr?     empty
|   +--ro aes256-ctr?     empty
|   +--ro aes128-cbc?     empty
|   +--ro aes192-cbc?     empty
|   +--ro aes256-cbc?     empty
|   +--ro triple-des-cbc? empty
|   +--ro rijndael-cbc?   empty
|   +--ro aes128-gcm?     empty
|   +--ro aes256-gcm?     empty
|   +--ro chacha20-poly1305? empty
+--rw kex-algorithms {feature-list:HAVE_SSH_SERVER}?
| +--rw config
```

---

---

```
| | +--rw diffie-hellman-group1-sha1?      empty
| | +--rw diffie-hellman-group14-sha1?     empty
| | +--rw diffie-hellman-group14-sha256?   empty
| | +--rw diffie-hellman-group16-sha512?   empty
| | +--rw diffie-hellman-group18-sha512?   empty
| | +--rw diffie-hellman-group-exchange-sha1?  empty
| | +--rw diffie-hellman-group-exchange-sha256? empty
| | +--rw ecdh-sha2-nistp256?             empty
| | +--rw ecdh-sha2-nistp384?            empty
| | +--rw ecdh-sha2-nistp521?            empty
| | +--rw curve25519-sha256?             empty
| | +--rw curve25519-sha256-libssh-org?    empty
| +--ro state
|   +--ro diffie-hellman-group1-sha1?      empty
|   +--ro diffie-hellman-group14-sha1?     empty
|   +--ro diffie-hellman-group14-sha256?   empty
|   +--ro diffie-hellman-group16-sha512?   empty
|   +--ro diffie-hellman-group18-sha512?   empty
|   +--ro diffie-hellman-group-exchange-sha1?  empty
|   +--ro diffie-hellman-group-exchange-sha256? empty
|   +--ro ecdh-sha2-nistp256?             empty
|   +--ro ecdh-sha2-nistp384?            empty
|   +--ro ecdh-sha2-nistp521?            empty
|   +--ro curve25519-sha256?             empty
|   +--ro curve25519-sha256-libssh-org?    empty
+--rw mac-algorithms {feature-list:HAVE_SSH_SERVER}?
  +--rw config
    | +--rw hmac-sha1?      empty
    | +--rw hmac-sha1-96?  empty
    | +--rw hmac-sha2-256?  empty
    | +--rw hmac-sha2-512?  empty
    | +--rw hmac-md5?      empty
    | +--rw hmac-md5-96?   empty
    | +--rw umac-64?       empty
    | +--rw umac-128?      empty
    | +--rw hmac-sha1-etm?  empty
```

---

```
| +--rw hmac-sha1-96-etm?  empty
| +--rw hmac-sha2-256-etm? empty
| +--rw hmac-sha2-512-etm? empty
| +--rw hmac-md5-etm?     empty
| +--rw hmac-md5-96-etm?  empty
| +--rw umac-64-etm?      empty
| +--rw umac-128-etm?     empty
+--ro state
  +--ro hmac-sha1?        empty
  +--ro hmac-sha1-96?    empty
  +--ro hmac-sha2-256?   empty
  +--ro hmac-sha2-512?   empty
  +--ro hmac-md5?        empty
  +--ro hmac-md5-96?     empty
  +--ro umac-64?         empty
  +--ro umac-128?       empty
  +--ro hmac-sha1-etm?   empty
  +--ro hmac-sha1-96-etm? empty
  +--ro hmac-sha2-256-etm? empty
  +--ro hmac-sha2-512-etm? empty
  +--ro hmac-md5-etm?   empty
  +--ro hmac-md5-96-etm? empty
  +--ro umac-64-etm?    empty
  +--ro umac-128-etm?   empty
```

augment /ipi-user-management:user-management/ipi-user-management:users/ipi-user-management:user:

```
+--rw ssh-keys
  +--rw config
    | +--rw public-key* ipi-ssh-types:ssh_public_key_t
  +--ro state
    +--ro public-key*   ipi-ssh-types:ssh_public_key_t
    +--ro rsa-key?     ipi-ssh-types:ssh_public_key_t
    +--ro dsa-key?     ipi-ssh-types:ssh_public_key_t
    +--ro fingerprint-rsa? ipi-ssh-types:ssh_public_key_t
    +--ro fingerprint-dsa? ipi-ssh-types:ssh_public_key_t
```

---

rpcs:

```
+---x ssh-terminal-debug-on {feature-list:HAVE_HOSTPD}?
+---x ssh-terminal-debug-off {feature-list:HAVE_HOSTPD}?
+---x ssh-clear-hosts {feature-list:HAVE_HOSTPD}?
+---x ssh-generate-server-dsa-key {feature-list:HAVE_SSH_SERVER}?
| +---w input
|   +---w vrf-name?  string
|   +---w force?    boolean
+---x ssh-generate-server-rsa-key {feature-list:HAVE_SSH_SERVER}?
| +---w input
|   +---w length?   uint32
|   +---w vrf-name? string
|   +---w force?    boolean
+---x ssh-generate-server-ecdsa-key {feature-list:HAVE_SSH_SERVER}?
| +---w input
|   +---w length?   ipi-ssh-types:ssh_ecdsa_key_len_t
|   +---w vrf-name? string
|   +---w force?    boolean
+---x ssh-generate-server-ed25519-key {feature-list:HAVE_SSH_SERVER}?
| +---w input
|   +---w vrf-name? string
|   +---w force?    boolean
+---x ssh-clear-server-keys {feature-list:HAVE_SSH_SERVER}?
| +---w input
|   +---w type?     ipi-ssh-types:ssh_host_key_type_t
|   +---w vrf-name? string
+---x ssh-generate-user-rsa-key {feature-list:HAVE_SSH_SERVER}?
| +---w input
|   +---w user-name  string
|   +---w length?   uint32
|   +---w force?    boolean
+---x ssh-generate-user-dsa-key {feature-list:HAVE_SSH_SERVER}?
| +---w input
|   +---w user-name  string
|   +---w force?    boolean
+---x ssh-clear-user-keys {feature-list:HAVE_SSH_SERVER}?
```

```
+---w input
  +---w user-name  string
```

---

## module: ipi-streaming-telemetry

```
+--rw telemetry-system
  +--rw vrfs {feature-list:HAVE_VRF}?
    +--rw vrf* [vrf-name]
      +--rw vrf-name      -> ../config/vrf-name
      +--rw config
        | +--rw vrf-name?  -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
        {feature-list:HAVE_VRF}?
          +--ro state
            | +--ro vrf-name? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
            {feature-list:HAVE_VRF}?
              +--rw streaming-telemetry
                | +--rw config
                | | +--rw feature-enabled?  empty
                | | +--rw retry-interval?  uint32
                | | +--ro state
                | | | +--ro feature-enabled?      empty
                | | | +--ro retry-interval?      uint32
                | | | +--ro maximum-sensor-paths?  uint8
                | | | +--ro minimum-sample-interval?  uint8
                | | | +--ro platform-type?          ipi-streaming-telemetry-types:cml_telemetry_platform_type_t
                | | | +--ro default-retry-interval?  uint8
                | | | +--ro active-sensor-paths?    uint8
                | | | +--ro active-dial-in-sensor-paths?  uint8
                | | | +--ro active-dial-out-sensor-paths?  uint8
                | +--rw debug
                |   +--rw config
                |   | +--rw gnmi-debug?  empty
                |   | +--rw gnmi-severity? ipi-streaming-telemetry-types:cml_gnmi_debug_severity_t
                |   +--ro state
                |     +--ro gnmi-debug?  empty
```

---

```

|   +--ro gnmi-severity? ipi-streaming-telemetry-types:cml_gnmi_debug_severity_t
+--rw subscriptions
| +--ro dynamic-subscriptions
| | +--ro dynamic-subscription* [id]
| |   +--ro id          -> ../state/id
| |   +--ro state
| |     | +--ro id?      uint64
| |     | +--ro client-address? string
| |     | +--ro sample-interval? uint64
| |     | +--ro stream-mode?   ipi-streaming-telemetry-types:cml_streaming_mode_types_t
| |     | +--ro encoding?     ipi-streaming-telemetry-types:cml_data_encode_t
| |     +--ro sensor-paths
| |       +--ro sensor-path* [path]
| |         +--ro path   -> ../state/path
| |         +--ro state
| |           +--ro path? string
| +--rw persistent-subscriptions
|   +--rw persistent-subscription* [name]
|     +--rw name          -> ../config/name
|     +--rw config
|       | +--rw name?     string
|       | +--rw encoding? ipi-streaming-telemetry-types:cml_data_encode_t
|       +--ro state
|         | +--ro name?      string
|         | +--ro encoding?  ipi-streaming-telemetry-types:cml_data_encode_t
|         | +--ro id?       uint64
|         | +--ro subscription-status? ipi-streaming-telemetry-types:cml_telemetry_status_t
|         | +--ro inactive-cause?  string
|         | +--ro protocol?       ipi-streaming-telemetry-types:cml_telemetry_protocol_t
|       +--rw sensor-profiles
|         | +--rw sensor-profile* [sensor-group]
|         |   +--rw sensor-group -> ../config/sensor-group
|         |   +--rw config
|         |     | +--rw sensor-group? -> /telemetry-system/vrfs/vrf/sensor-groups/sensor-group/sensor-group-id
|         |     | +--rw sample-interval uint64
|         |     +--ro state

```

---

---

```

|   |   +--ro sensor-group?   -> /telemetry-system/vrfs/vrf/sensor-groups/sensor-group/sensor-group-id
|   |   +--ro sample-interval uint64
|   +--rw destination-groups
|       +--rw destination-group* [group-id]
|           +--rw group-id   -> ../config/group-id
|           +--rw config
|               | +--rw group-id? -> /telemetry-system/vrfs/vrf/destination-groups/destination-group/group-id
|               +--ro state
|                   +--ro group-id? -> /telemetry-system/vrfs/vrf/destination-groups/destination-group/group-id
+--rw sensor-groups
| +--rw sensor-group* [sensor-group-id]
|   +--rw sensor-group-id -> ../config/sensor-group-id
|   +--rw config
|       | +--rw sensor-group-id? string
|       +--ro state
|       | +--ro sensor-group-id? string
|       +--rw sensor-paths
|           +--rw sensor-path* [path]
|               +--rw path   -> ../config/path
|               +--rw config
|                   | +--rw path? string
|                   +--ro state
|                   +--ro path? string
+--rw destination-groups
  +--rw destination-group* [group-id]
    +--rw group-id   -> ../config/group-id
    +--rw config
    | +--rw group-id? string
    +--ro state
    | +--ro group-id? string
  +--rw destinations
    +--rw destination* [destination-address destination-port]
      +--rw destination-address -> ../config/destination-address
      +--rw destination-port   -> ../config/destination-port
      +--rw config
      | +--rw destination-address? inet:ipv4-address

```

---

```

| +--rw destination-port?   uint16
+--ro state
  +--ro destination-address? inet:ipv4-address
  +--ro destination-port?   uint16

```

---

## module: ipi-synce

```

+--rw synce {feature-list:HAVE_SYNCED}?
  +--rw globals
    | +--rw config!
    | | +--rw enable          empty
    | | +--rw network-option? ipi-synce-types:synce_sync_option_t
    | | +--rw clock-selection-mode? ipi-synce-types:synce_clk_selection_mode_t
    | | +--rw dpll3-select-10mhz-in? empty
    | | +--rw holdover-timer?   uint16
    | +--ro state
    | +--ro enable          empty
    | +--ro network-option? ipi-synce-types:synce_sync_option_t
    | +--ro clock-selection-mode? ipi-synce-types:synce_clk_selection_mode_t
    | +--ro dpll3-select-10mhz-in? empty
    | +--ro holdover-timer?   uint16
    | +--ro equipment-clock?  string
    | +--ro locked-interface? string
    | +--ro esmc-state?       ipi-synce-types:synce_esmc_state_t
    | +--ro is-source-selected? ipi-synce-types:synce_is_src_selected_t
    | +--ro quality-level?    string
    | +--ro current-clock-state? ipi-synce-types:synce_clock_state_t
    | +--ro dpll-clock-state?  ipi-synce-types:synce_clock_state_t
    | +--ro state-duration?   ipi-synce-types:synce_uptime_t
    | +--ro selected-clock-src-id? uint32
  +--rw interfaces
    | +--rw interface* [name]
    | +--rw name    -> ../config/name
    | +--rw config!
    | | +--rw name?          -> /ipi-interface:interfaces/interface/name

```

---

```

| | +--rw enable          empty
| | +--rw synchronous-mode?  ipi-synce-types:synce_mode_option_t
| | +--rw input-source-priority? uint8
| | +--rw is-output-source?   boolean
| | +--rw wait-to-restore-timer? uint8
| | +--rw vlan-id?          uint16
| | +--rw hold-off-timer?    uint16
| | +--rw quality-level?     string
| | +--rw clock-source-id?   uint8
| | +--rw auto-neg-mode?     ipi-synce-types:synce_autoneg_mode_t
| +--ro state
|   +--ro name?             -> /ipi-interface:interfaces/interface/name
|   +--ro enable           empty
|   +--ro synchronous-mode? ipi-synce-types:synce_mode_option_t
|   +--ro input-source-priority? uint8
|   +--ro is-output-source?   boolean
|   +--ro wait-to-restore-timer? uint8
|   +--ro vlan-id?         uint16
|   +--ro hold-off-timer?   uint16
|   +--ro quality-level?    string
|   +--ro clock-source-id?  uint8
|   +--ro auto-neg-mode?    ipi-synce-types:synce_autoneg_mode_t
|   +--ro esmc-state?       ipi-synce-types:synce_esmc_state_t
|   +--ro is-source-selected? ipi-synce-types:synce_is_src_selected_t
|   +--ro esmc-received?    uint64
|   +--ro esmc-sent?        uint64
|   +--ro quality-level-received-esmc? string
|   +--ro operational-quality-level? string
|   +--ro configured-quality-level? string
|   +--ro interface-config-priority? uint8
|   +--ro signal-fail?      ipi-synce-types:synce_is_sf_t
|   +--ro external-command? ipi-synce-types:synce_external_cmds_t
|   +--ro wtr-timer-status? ipi-synce-types:synce_is_timer_running_t
|   +--ro hold-off-timer-status? ipi-synce-types:synce_is_timer_running_t
|   +--ro link-state?       ipi-synce-types:synce_link_state_t
+--rw external-interfaces

```

---

---

```

| +--rw external-interface* [external-synce-interface]
|   +--rw external-synce-interface -> ../config/external-synce-interface
|   +--rw config
|     | +--rw external-synce-interface? ipi-synce-types:synce_external_interface_t
|     | +--rw synchronous-mode?       ipi-synce-types:synce_mode_option_t
|     | +--rw input-source-priority?   uint8
|     | +--rw wait-to-restore-timer?   uint8
|     | +--rw hold-off-timer?         uint16
|     | +--rw quality-level?          string
|     +--ro state
|       +--ro external-synce-interface? ipi-synce-types:synce_external_interface_t
|       +--ro synchronous-mode?        ipi-synce-types:synce_mode_option_t
|       +--ro input-source-priority?   uint8
|       +--ro wait-to-restore-timer?   uint8
|       +--ro hold-off-timer?         uint16
|       +--ro quality-level?          string
|       +--ro esmc-state?              ipi-synce-types:synce_esmc_state_t
|       +--ro is-source-selected?      ipi-synce-types:synce_is_src_selected_t
|       +--ro esmc-received?          uint64
|       +--ro esmc-sent?              uint64
|       +--ro quality-level-received-esmc? string
|       +--ro operational-quality-level? string
|       +--ro configured-quality-level? string
|       +--ro interface-config-priority? uint8
|       +--ro signal-fail?            ipi-synce-types:synce_is_sf_t
|       +--ro external-command?       ipi-synce-types:synce_external_cmds_t
|       +--ro wtr-timer-status?       ipi-synce-types:synce_is_timer_running_t
|       +--ro hold-off-timer-status?   ipi-synce-types:synce_is_timer_running_t
|       +--ro link-state?             ipi-synce-types:synce_link_state_t
+--rw debug
  +--rw config
  | +--rw options? ipi-synce-types:synce_debug_t
  +--ro state
    +--ro options? ipi-synce-types:synce_debug_t
    +--ro terminal-debug-status? ipi-synce-types:synce_debug_t

```

---

rpcs:

```
+---x clear-synce-stats {feature-list:HAVE_SYNCED}?
| +---w input
|   +---w interface-name  string
+---x synce-terminal-debug-on {feature-list:HAVE_SYNCED}?
| +---w input
|   +---w debug-options  ipi-synce-types:synce_debug_t
+---x synce-terminal-debug-off {feature-list:HAVE_SYNCED}?
  +---w input
    +---w debug-options  ipi-synce-types:synce_debug_t
```

notifications:

```
+---n synce-clock-status {feature-list:HAVE_SYNCED}?
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro message?   string
+---n synce-clock-state-change-notify {feature-list:HAVE_SYNCED}?
| +--ro severity?      cml-data-types:cml_notif_severity_t
| +--ro eventClass?    cml-data-types:cml_notif_class_t
| +--ro previous-clock-state?  ipi-synce-types:synce_clock_state_t
| +--ro current-clock-state?  ipi-synce-types:synce_clock_state_t
+---n synce-clock-state-transition-locked-interface {feature-list:HAVE_SYNCED}?
  +--ro severity?      cml-data-types:cml_notif_severity_t
  +--ro eventClass?    cml-data-types:cml_notif_class_t
  +--ro previous-clock-state?  ipi-synce-types:synce_clock_state_t
  +--ro current-clock-state?  ipi-synce-types:synce_clock_state_t
  +--ro locked-interface?  string
```

---

## module: ipi-sys-mgmt

rpcs:

```
+---x sys-shutdown {feature-list:HAVE_PSERVD}?
  +---w input
    +---w save-config  boolean
```

---

## module: ipi-sys-notifications

notifications:

```
+---n lock-forcibly-released
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro message?   string
+---n config-sync-completion-status
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro message?   string
+---n config-change
| +--ro message?  string
+---n system-shutdown-or-reload
  +--ro severity?  cml-data-types:cml_notif_severity_t
  +--ro eventClass?  cml-data-types:cml_notif_class_t
  +--ro message?   string
```

---

## module: ipi-sys-update

```
+--rw system-update
  +--rw docker
    | +--ro images
    | | +--ro image* [name]
    | |   +--ro name  -> ../state/name
    | |   +--ro state
    | |     +--ro name?  string
    | +--ro info
    | | +--ro state
    | |   +--ro version?  string
    | |   +--ro status?  string
    | +--ro download-status
    |   +--ro state
```

---

```

|   +--ro inprogress?  boolean
+--ro installers
| +--ro installer* [name]
|   +--ro name    -> ../state/name
|   +--ro state
|   +--ro name?   string
+--ro system-update-details
  +--ro state
    +--ro previous-version?  cml-data-types:cml_line_t
    +--ro current-version?   cml-data-types:cml_line_t
    +--ro last-upgraded-time? cml-data-types:cml_line_t
    +--ro auto-rollback-end-time? cml-data-types:cml_line_t

```

rpcs:

```

+---x sys-update-install {feature-list:HAVE_PSERVD,feature-list:NOT_HAVE_TIBIT}?
| +---w input
|   +---w installer-name    string
|   +---w ignore-feature-check  boolean
+---x sys-update-uninstall {feature-list:HAVE_PSERVD,feature-list:NOT_HAVE_TIBIT}?
+---x sys-update-get {feature-list:HAVE_PSERVD,feature-list:NOT_HAVE_TIBIT}?
| +---w input
|   +---w source-interface  string
|   +---w source-ip?       inet:ip-address
|   +---w url               string
|   +---w known-hosts-add?  boolean
+---x sys-update-delete {feature-list:HAVE_PSERVD,feature-list:NOT_HAVE_TIBIT}?
| +---w input
|   +---w image-name  string
+---x sys-update-cancel-download {feature-list:HAVE_PSERVD,feature-list:NOT_HAVE_TIBIT}?
+---x sys-container-install {feature-list:HAVE_PSERVD,feature-list:NOT_HAVE_TIBIT}?
| +---w input
|   +---w type          ipi-sys-update-types:system_container_type_t
|   +---w upgrade-type  ipi-sys-update-types:system_container_upgrade_t
|   +---w file          string
+---x sys-container-uninstall {feature-list:HAVE_PSERVD,feature-list:NOT_HAVE_TIBIT}?
| +---w input

```

---

```
| +---w type      ipi-sys-update-types:system_container_type_t
| +---w un-install  boolean
+---x sys-container-boot {feature-list:HAVE_PSERVD,feature-list:NOT_HAVE_TIBIT}?
| +---w input
| +---w type      ipi-sys-update-types:system_container_type_t
| +---w boot-type  ipi-sys-update-types:system_container_boot_t
+---x sys-container-get {feature-list:HAVE_PSERVD,feature-list:NOT_HAVE_TIBIT}?
| +---w input
| +---w type      ipi-sys-update-types:system_container_type_t
| +---w url        string
| +---w source-interface  string
+---x sys-container-remove {feature-list:HAVE_PSERVD,feature-list:NOT_HAVE_TIBIT}?
| +---w input
| +---w type      ipi-sys-update-types:system_container_type_t
| +---w file      string
+---x sys-container-verify {feature-list:HAVE_PSERVD,feature-list:NOT_HAVE_TIBIT}?
| +---w input
| +---w type      ipi-sys-update-types:system_container_type_t
| +---w image     string
| +---w signature  string
+---x sys-container-cancel-download {feature-list:HAVE_PSERVD,feature-list:NOT_HAVE_TIBIT}?
```

## notifications:

```
+---n sys-update-installation-status
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro message?    string
+---n sys-update-download-status
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro message?    string
+---n sys-container-download-status
  +--ro severity?  cml-data-types:cml_notif_severity_t
  +--ro eventClass?  cml-data-types:cml_notif_class_t
  +--ro message?    string
```

---

## module: ipi-system

```

+--rw system-info
  +--rw config
    | +--rw hostname? string
  +--ro state
    | +--ro hostname? string
    | +--ro software-version? string
    | +--ro system-uptime? system_time_duration
    | +--ro boot-time? uint64
    | +--ro current-datetime? yang:date-and-time
  +--rw clock
    +--rw config
      | +--rw timezone-name? system_timezone_name_t
    +--ro state
      +--ro timezone-name? system_timezone_name_t

```

---

## module: ipi-tacacs

```

+--rw tacacs
  +--rw vrfs
    | +--rw vrf* [vrf-name] {feature-list:HAVE_HOSTPD,feature-list:HAVE_AAA,feature-list:HAVE_TACACS_CLIENT}?
    |   +--rw vrf-name -> ../config/vrf-name
    |   +--rw config
    |     | +--rw vrf-name? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
    |     | +--rw feature-enable empty
    |     | +--rw timeout? uint8
    |     | +--rw key-type? ipi-tacacs-types:tacacs_hostp_key_type_t
    |     | +--rw secret-key-string? string
    |     +--ro state
    |       | +--ro vrf-name? -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
    |       | +--ro feature-enable empty
    |       | +--ro timeout? uint8
    |       | +--ro key-type? ipi-tacacs-types:tacacs_hostp_key_type_t

```

```

| | +--ro secret-key-string? string
| +--rw remote-servers
|   +--rw server* [host-address] {feature-list:HAVE_HOSTPD,feature-list:HAVE_AAA,feature-
list:HAVE_TACACS_CLIENT}?
|     +--rw host-address -> ../config/host-address
|     +--rw config
|       | +--rw host-address?    cml-data-types:cml_hostname_t
|       | +--rw sequence-number  uint8
|       | +--rw port?            uint32
|       | +--rw timeout?         uint32
|       | +--rw key-type?        ipi-tacacs-types:tacacs_hostp_key_type_t
|       | +--rw secret-key-string? string
|       +--ro state
|         +--ro host-address?      cml-data-types:cml_hostname_t
|         +--ro sequence-number    uint8
|         +--ro port?              uint32
|         +--ro timeout?           uint32
|         +--ro key-type?          ipi-tacacs-types:tacacs_hostp_key_type_t
|         +--ro secret-key-string? string
|         +--ro last-successful-authentication-time? yang:date-and-time
|         +--ro counters
|           +--ro successful-authentications? yang:counter64
|           +--ro authentication-failures?   yang:counter64
|           +--ro connection-failures?      yang:counter64
+--rw debug
  +--rw config
  | +--rw enable? empty
  +--ro state
    +--ro enable?      empty
    +--ro terminal-debug-status? cml-data-types:cml_on_off_t

```

rpcs:

```

+---x clear-all-tacacs-server-counters {feature-list:HAVE_HOSTPD}?
| +---w input
|   +---w vrf-name string
+---x clear-tacacs-server-host-counters {feature-list:HAVE_HOSTPD}?
| +---w input

```

```

| +---w hostname  cml-data-types:cml_hostname_t
| +---w vrf-name  string
+---x tacacs-terminal-debug-on {feature-list:HAVE_HOSTPD}?
+---x tacacs-terminal-debug-off {feature-list:HAVE_HOSTPD}?

```

---

## module: ipi-telnet

```

+--rw telnet-server
  +--rw debug
    | +--rw config
    | | +--rw enable?  empty
    | +--ro state
    | +--ro enable?    empty
    | +--ro terminal-debug-status?  cml-data-types:cml_on_off_t
  +--rw vrfs
    +--rw vrf* [vrf-name]
      +--rw vrf-name  -> ../config/vrf-name
      +--rw config
        | +--rw vrf-name?  -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
        | +--rw enable     boolean
        | +--rw port?      uint32 {feature-list:HAVE_TELNET_SERVER}?
        | +--rw session-limit?  uint8 {feature-list:HAVE_TELNET_SERVER}?
        +--ro state
          +--ro vrf-name?  -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
          +--ro enable     boolean
          +--ro port?      uint32 {feature-list:HAVE_TELNET_SERVER}?
          +--ro session-limit?  uint8 {feature-list:HAVE_TELNET_SERVER}?

```

rpcs:

```

+---x telnet-terminal-debug-on {feature-list:HAVE_HOSTPD}?
+---x telnet-terminal-debug-off {feature-list:HAVE_HOSTPD}?

```

---

## module: ipi-tfo

```
+--rw trigger-failover
  +--rw config
    | +--rw admin-status?  cml-data-types:cml_enable_disable_t
  +--ro state
    | +--ro admin-status?  cml-data-types:cml_enable_disable_t
  +--rw interfaces
    | +--rw interface* [name]
    |   +--rw name      -> ../config/name
    |   +--rw config
    |     | +--rw name?    -> /ipi-interface:interfaces/interface/name
    |     | +--rw link-type? ipi-tfo-types:tfo_fog_link_type_t
    |     +--ro state
    |       | +--ro name?    -> /ipi-interface:interfaces/interface/name
    |       | +--ro link-type? ipi-tfo-types:tfo_fog_link_type_t
    |     +--rw tfo-groups
    |       +--rw tfo-group* [fog-id]
    |         +--rw fog-id  -> ../config/fog-id
    |         +--rw config
    |           | +--rw fog-id?    uint32
    |           | +--rw group-type  ipi-tfo-types:tfo_fog_group_type_t
    |           +--ro state
    |             +--ro fog-id?    uint32
    |             +--ro group-type  ipi-tfo-types:tfo_fog_group_type_t
  +--rw failover-groups
    +--rw failover-group* [group-id]
      +--rw group-id  -> ../config/group-id
      +--rw config
        | +--rw group-id?          uint32
        | +--rw admin-status        cml-data-types:cml_enable_disable_t
        | +--rw failover-trigger-count?  uint32
      +--ro state
        | +--ro group-id?          uint32
        | +--ro admin-status        cml-data-types:cml_enable_disable_t
        | +--ro failover-trigger-count?  uint32
```

```

| +--ro cpg-disable-status?    boolean
| +--ro mpg-disable-status?    boolean
+--ro counters
  +--ro mpg-link-failure-count? uint64
  +--ro mpg-link-recover-count? uint64
  +--ro cpg-auto-disable-count? uint64
  +--ro cpg-auto-enable-count? uint64

```

rpcs:

```

+---x tfo-clear-counters-all {feature-list:HAVE_TFO}?
+---x tfo-clear-fog-counters {feature-list:HAVE_TFO}?
+---w input
  +---w group-id  uint32

```

---

## module: ipi-time-range

```

+--rw time-ranges
  +--rw time-range* [name]
    +--rw name          -> ../config/name
    +--rw config
      | +--rw name?    string
      +--ro state
      | +--ro name?    string
      +--rw start-time-options
      | +--rw config
      | | +--rw (start-time)?
      | |   +--:(absolute-start-time)
      | |   | +--rw absolute-start-time?  time_range_date_time_t
      | |   +--:(relative-start-time)
      | |     +--rw relative-start-time?  time_range_relative_time_t
      | +--ro state
      |   +--ro (start-time)?
      |   +--:(absolute-start-time)
      |   | +--ro absolute-start-time?  time_range_date_time_t
      |   +--:(relative-start-time)
      |     +--ro relative-start-time?  time_range_relative_time_t

```

```

+--rw end-time-options
| +--rw config
| | +--rw (end-time)?
| |   +--:(absolute-end-time)
| |     | +--rw absolute-end-time?  time_range_date_time_t
| |     +--:(relative-end-time)
| |       +--rw relative-end-time?  string
| +--ro state
|   +--ro (end-time)?
|     +--:(absolute-end-time)
|       | +--ro absolute-end-time?  time_range_date_time_t
|       +--:(relative-end-time)
|         +--ro relative-end-time?  string
+--rw frequency-options
  +--rw config
  | +--rw frequency?  time_range_frequency_t
  +--ro state
    +--ro frequency?  time_range_frequency_t

```

---

## module: ipi-twamp

```

+--rw twamp
  +--rw light
  | +--rw control
  | | +--rw config!
  | | | +--rw enable          empty
  | | | +--rw administrative-state?  cml-data-types:cml_enable_disable_t
  | | +--ro state
  | | | +--ro enable          empty
  | | | +--ro administrative-state?  cml-data-types:cml_enable_disable_t
  | | +--rw test-sessions
  | |   +--rw test-session* [session-name vrf-name]
  | |     +--rw session-name  -> ../config/session-name
  | |     +--rw vrf-name      -> ../config/vrf-name

```

---

```
| | +--rw config
| | | +--rw session-name?      string
| | | +--rw sender-ip-address  ipi-twamp-types:twamp_hostname_t
| | | +--rw sender-udp-port    ipi-twamp-types:twamp_udp_port_t
| | | +--rw reflector-ip-address ipi-twamp-types:twamp_hostname_t
| | | +--rw reflector-udp-port  ipi-twamp-types:twamp_udp_port_t
| | | +--rw dscp-value?        ipi-twamp-types:twamp_dscp_t
| | | +--rw vrf-name?          string
| | +--ro state
| |   +--ro session-name?      string
| |   +--ro sender-ip-address  ipi-twamp-types:twamp_hostname_t
| |   +--ro sender-udp-port    ipi-twamp-types:twamp_udp_port_t
| |   +--ro reflector-ip-address ipi-twamp-types:twamp_hostname_t
| |   +--ro reflector-udp-port  ipi-twamp-types:twamp_udp_port_t
| |   +--ro dscp-value?        ipi-twamp-types:twamp_dscp_t
| |   +--ro vrf-name?          string
| |   +--ro start-time?        yang:date-and-time
| |   +--ro elapsed-time?      uint32
| |   +--ro statistics
| |     +--ro packets-sent?     yang:counter64
| |     +--ro packets-received? yang:counter64
| |     +--ro packet-loss?     decimal64
| |     +--ro round-trip-delay
| |       | +--ro minimum?  uint64
| |       | +--ro maximum?  uint64
| |       | +--ro average?  uint64
| |     +--ro forward-delay
| |       | +--ro minimum?  uint64
| |       | +--ro maximum?  uint64
| |       | +--ro average?  uint64
| |     +--ro reverse-delay
| |       | +--ro minimum?  uint64
| |       | +--ro maximum?  uint64
| |       | +--ro average?  uint64
| |     +--ro round-trip-delay-variation
| |       | +--ro minimum?  uint64
```

```

| |      | +--ro maximum?  uint64
| |      | +--ro average?  uint64
| |      +--ro forward-delay-variation
| |      | +--ro minimum?  uint64
| |      | +--ro maximum?  uint64
| |      | +--ro average?  uint64
| |      +--ro reverse-delay-variation
| |      +--ro minimum?  uint64
| |      +--ro maximum?  uint64
| |      +--ro average?  uint64
| +--rw session-reflector
|   +--rw config!
|     | +--rw enable          empty
|     | +--rw administrative-state?  cml-data-types:cml_enable_disable_t
|     +--ro state
|       | +--ro enable          empty
|       | +--ro administrative-state?  cml-data-types:cml_enable_disable_t
|     +--rw sessions
|       +--rw session* [name vrf-name]
|         +--rw name      -> ../config/name
|         +--rw vrf-name  -> ../config/vrf-name
|         +--rw config
|           | +--rw name?          string
|           | +--rw reflector-ip-address  ipi-twamp-types:twamp_hostname_t
|           | +--rw reflector-udp-port    ipi-twamp-types:twamp_udp_port_t
|           | +--rw sender-ip-address    ipi-twamp-types:twamp_hostname_t
|           | +--rw sender-udp-port      ipi-twamp-types:twamp_ref_src_udp_port_t
|           | +--rw vrf-name?          string
|         +--ro state
|           +--ro name?          string
|           +--ro reflector-ip-address  ipi-twamp-types:twamp_hostname_t
|           +--ro reflector-udp-port    ipi-twamp-types:twamp_udp_port_t
|           +--ro sender-ip-address    ipi-twamp-types:twamp_hostname_t
|           +--ro sender-udp-port      ipi-twamp-types:twamp_ref_src_udp_port_t
|           +--ro vrf-name?          string
+--rw debug

```

```

| +--rw config
| | +--rw options? ipi-twamp-types:twamp_debug_t
| | +--ro state
| |   +--ro options?          ipi-twamp-types:twamp_debug_t
| |   +--ro terminal-debug-status? ipi-twamp-types:twamp_debug_t
+--rw server
| +--rw config
| | +--rw port?          ipi-twamp-types:twamp_udp_port_t
| | +--rw max-connection-duration? uint8
| | +--rw max-connections?          uint8
| | +--rw max-connections-per-client? uint8
| | +--rw maximum-sessions?          uint8
| | +--rw maximum-sessions-per-connection? uint8
| | +--rw inactivity-timeout?          uint8
| | +--rw vrf-name*          -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
| |   +--ro state
| | | +--ro port?          ipi-twamp-types:twamp_udp_port_t
| | | +--ro max-connection-duration? uint8
| | | +--ro max-connections?          uint8
| | | +--ro max-connections-per-client? uint8
| | | +--ro maximum-sessions?          uint8
| | | +--ro maximum-sessions-per-connection? uint8
| | | +--ro inactivity-timeout?          uint8
| | | +--ro vrf-name*          -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-
name
| | |   +--ro nb-connections?          yang:counter32
| | |   +--ro nb-sessions?          yang:counter32
| | |   +--ro nb-running-sessions?          yang:counter32
| | |   +--ro connections
| | | | +--ro connection* [connection-id]
| | | | | +--ro connection-id -> ../state/connection-id
| | | | | +--ro state
| | | | | | +--ro connection-id?          uint32
| | | | | | +--ro client-address?          inet:ip-address
| | | | | | +--ro client-port?          uint16
| | | | | | +--ro client-vrf?          string

```

---

```
| |   +--ro connection-state?   string
| |   +--ro connection-time?   yang:date-and-time
| |   +--ro last-activity-time? yang:date-and-time
| |   +--ro nb-session-requests? yang:counter32
| |   +--ro nb-accepted-sessions? yang:counter32
| +--ro sessions
| | +--ro session* [session-id]
| |   +--ro session-id  -> ../state/session-id
| |   +--ro state
| |     +--ro session-id?   string
| |     +--ro connection-id? uint32
| |     +--ro session-state? string
| |     +--ro sender-address? inet:ip-address
| |     +--ro sender-port?   uint16
| |     +--ro receiver-address? inet:ip-address
| |     +--ro receiver-port?  uint16
| |     +--ro receiver-vrf?   string
| |     +--ro start-time?    yang:date-and-time
| |     +--ro timeout?       uint32
| +--rw admin
|   +--rw config!
|     | +--rw enable          empty
|     | +--rw administrative-state? cml-data-types:cml_enable_disable_t
|     +--ro state
|       +--ro enable          empty
|       +--ro administrative-state? cml-data-types:cml_enable_disable_t
+--rw client
  +--rw config!
    | +--rw enable          empty
    | +--rw maximum-sessions?      uint8
    | +--rw maximum-connections?   uint8
    | +--rw maximum-sessions-per-connection? uint8
    +--ro state
      | +--ro enable          empty
      | +--ro maximum-sessions?      uint8
      | +--ro maximum-connections?   uint8
```

---

```
| +--ro maximum-sessions-per-connection? uint8
+--rw connections
  +--rw connection* [connection-name vrf-name]
    +--rw connection-name -> ../config/connection-name
    +--rw vrf-name        -> ../config/vrf-name
    +--rw config
      | +--rw connection-name? string
      | +--rw server-address?  ipi-twamp-types:twamp_hostname_t
      | +--rw server-port?    ipi-twamp-types:twamp_udp_port_t
      | +--rw vrf-name?      string
    +--ro state
      | +--ro connection-name? string
      | +--ro server-address?  ipi-twamp-types:twamp_hostname_t
      | +--ro server-port?    ipi-twamp-types:twamp_udp_port_t
      | +--ro vrf-name?      string
      | +--ro client-port?    uint32
      | +--ro client-address?  inet:ip-address
      | +--ro connection-time? yang:date-and-time
      | +--ro last-activity-time? yang:date-and-time
      | +--ro connection-state? string
      | +--ro nb-session-requested? yang:counter32
      | +--ro nb-sessions-accepted? yang:counter32
    +--rw sessions
      +--rw session* [session-name]
        +--rw session-name -> ../config/session-name
        +--rw config
          | +--rw session-name? string
          | +--rw sender-port?  uint32
          | +--rw receiver-port? uint32
          | +--rw sender-address? ipi-twamp-types:twamp_hostname_t
          | +--rw receiver-address? ipi-twamp-types:twamp_hostname_t
          | +--rw start-time?    ipi-twamp-types:twamp_date_time_t
          | +--rw interface-name? string
        +--ro state
          +--ro session-name?    string
          +--ro sender-port?    uint32
```

---

```

+--ro receiver-port?      uint32
+--ro sender-address?    ipi-twamp-types:twamp_hostname_t
+--ro receiver-address?  ipi-twamp-types:twamp_hostname_t
+--ro start-time?        ipi-twamp-types:twamp_date_time_t
+--ro interface-name?    string
+--ro requested-receiver-port? uint32
+--ro session-id?        string

```

rpcs:

```

+---x twamp-client-start-connection {feature-list:HAVE_TWAMP}?
| +---w input
|   +---w connection-name  string
|   +---w vrf-name?        string
|   +---w packet-count     uint32
+---x twamp-client-stop-connection {feature-list:HAVE_TWAMP}?
| +---w input
|   +---w connection-name  string
|   +---w vrf-name?        string
+---x twamp-client-reset-session {feature-list:HAVE_TWAMP}?
| +---w input
|   +---w connection-name  string
|   +---w session-name     string
|   +---w vrf-name?        string
+---x twamp-test-session-start {feature-list:HAVE_TWAMP}?
| +---w input
|   +---w session-name     string
|   +---w packet-count     uint16
|   +---w packet-interval? uint16
|   +---w delay-threshold? uint32
+---x twamp-test-session-stop {feature-list:HAVE_TWAMP}?
| +---w input
|   +---w session-name     string
+---x twamp-terminal-debug-on {feature-list:HAVE_TWAMP}?
| +---w input
|   +---w terminal-debug-options ipi-twamp-types:twamp_debug_t
+---x twamp-terminal-debug-off {feature-list:HAVE_TWAMP}?

```

```
+---w input
  +---w terminal-debug-options  ipi-twamp-types:twamp_debug_t
```

notifications:

```
+---n twamp-delay-threshold-breached {feature-list:HAVE_TWAMP}?
  +--ro severity?    cml-data-types:cml_notif_severity_t
  +--ro eventClass?  cml-data-types:cml_notif_class_t
  +--ro session-name? string
  +--ro vrf-name?    string
  +--ro average?     uint64
```

---

## module: ipi-udld

```
+--rw udld
  +--rw global
  | +--rw config
  | | +--rw enable?    empty
  | | +--rw message-time? uint8
  | +--ro state
  | +--ro enable?     empty
  | +--ro message-time? uint8
  +--rw debug
  | +--rw config
  | | +--rw options?  ipi-udld-types:udld_debug_t
  | +--ro state
  | +--ro options?    ipi-udld-types:udld_debug_t
  | +--ro terminal-debug-status? ipi-udld-types:udld_debug_t
  +--rw interfaces
  +--rw interface* [name]
  +--rw name    -> ../config/name
  +--rw config
  | +--rw name?          -> /ipi-interface:interfaces/interface/name
  | +--rw mode?          ipi-udld-types:udld_mode_type_t
  | +--rw administrative-state? cml-data-types:cml_enable_disable_t
```

```

+--ro state
  +--ro name?          -> /ipi-interface:interfaces/interface/name
  +--ro mode?          ipi-udld-types:udld_mode_type_t
  +--ro administrative-state?  cml-data-types:cml_enable_disable_t
  +--ro link-state?    ipi-udld-types:udld_link_state_type_t

```

rpcs:

```

+---x udld-terminal-debug-on {feature-list:HAVE_UDLD}?
| +---w input
|   +---w terminal-debug-options  ipi-udld-types:udld_debug_t
+---x udld-terminal-debug-off {feature-list:HAVE_UDLD}?
  +---w input
    +---w terminal-debug-options  ipi-udld-types:udld_debug_t

```

---

## module: ipi-unicast-rpf

```

+--rw unicast-rpf {feature-list:HAVE_RPF}?
  +--rw global
  | +--rw config
  | | +--rw enable-route-lookup?  empty
  | +--ro state
  |   +--ro enable-route-lookup?  empty
  +--rw interfaces
    +--rw interface* [name]
      +--rw name    -> ../config/name
      +--rw config
      | +--rw name?          -> /ipi-interface:interfaces/interface/name
      | +--rw source-reachability-mode  ipi-unicast-rpf-types:urpf_src_reachability_mode_t
      +--ro state
        +--ro name?          -> /ipi-interface:interfaces/interface/name
        +--ro source-reachability-mode  ipi-unicast-rpf-types:urpf_src_reachability_mode_t

```

---

## module: ipi-user-management

```

+--rw user-management
  +--rw debug
    | +--rw config
    | | +--rw enable?  empty
    | +--ro state
    | +--ro enable?      empty
    | +--ro terminal-debug-status?  cml-data-types:cml_on_off_t
  +--rw global
    | +--rw config
    | | +--rw disable-default-user?  empty
    | +--ro state
    | +--ro disable-default-user?  empty
  +--rw users
    +--rw user* [username]
      +--rw username  -> ../config/username
      +--rw config
        | +--rw username?      string
        | +--rw role?          ipi-user-management-types:user_mgmt_role_types_t
        | +--rw rbac-role?     ipi-user-management-types:user_mgmt_rbac_role_t {feature-list:HAVE_RBAC}?
        | +--rw (password-type)?
        | +--:(plain-text)
        | | +--rw password?    string
        | +--:(hashed)
        | +--rw password-hashed?  string
      +--ro state
        +--ro username?      string
        +--ro role?          ipi-user-management-types:user_mgmt_role_types_t
        +--ro rbac-role?     ipi-user-management-types:user_mgmt_rbac_role_t {feature-list:HAVE_RBAC}?
        +--ro (password-type)?
        +--:(plain-text)
        | +--ro password?    string
        +--:(hashed)
        +--ro password-hashed?  string

```

rpcs:

+---x user-management-terminal-debug-on {feature-list:HAVE\_HOSTPD,feature-list:HAVE\_USER\_MGMT}?

+---x user-management-terminal-debug-off {feature-list:HAVE\_HOSTPD,feature-list:HAVE\_USER\_MGMT}?

---

## module: ipi-user-session-management

```
+--rw user-session
  +--rw line-console
    | +--rw console* [console-id]
    |   +--rw console-id -> ../config/console-id
    |   +--rw config
    |     | +--rw privilege-level?      uint8
    |     | +--rw command-history-max-limit? uint32
    |     | +--rw console-id?          ipi-user-session-management-types:line_console_id_t
    |     +--ro state
    |       | +--ro privilege-level?      uint8
    |       | +--ro command-history-max-limit? uint32
    |       | +--ro console-id?          ipi-user-session-management-types:line_console_id_t
    |       +--rw timeout
    |         +--rw config!
    |           | +--rw minutes  uint32
    |           | +--rw seconds? uint32
    |           +--ro state
    |             +--ro minutes  uint32
    |             +--ro seconds? uint32
    +--rw line-vty
      | +--rw vty* [vty-id]
      |   +--rw vty-id -> ../config/vty-id
      |   +--rw config
      |     | +--rw privilege-level?      uint8
      |     | +--rw command-history-max-limit? uint32
      |     | +--rw vty-id?              cml-data-types:cml_range_t
      |     +--ro state
      |       | +--ro privilege-level?      uint8
      |       | +--ro command-history-max-limit? uint32
```

```

| | +--ro vty-id?          cml-data-types:cml_range_t
| +--rw timeout
|   +--rw config!
|     | +--rw minutes  uint32
|     | +--rw seconds? uint32
|     +--ro state
|       +--ro minutes  uint32
|       +--ro seconds? uint32
+--ro sessions
  +--ro session* [id]
    +--ro id    -> ../state/id
    +--ro state
      +--ro id?      string
      +--ro line?    string
      +--ro user-name?  string
      +--ro client-type?  ipi-user-session-types:user_session_user_type_t
      +--ro idle-time?   string
      +--ro process-identifier? uint32
      +--ro type?       ipi-user-session-types:user_session_type_t
      +--ro user-role?   ipi-user-session-types:user_session_user_role_type_t
      +--ro remote-ip?   string

```

rpcs:

```

+---x clear-line {feature-list:HAVE_IMI}?
  +---w input
    +---w line-name  string

```

---

## module: ipi-vlan-xc

```

+--rw cross-connects
  +--rw cross-connect* [xconnect-name] {feature-list:HAVE_VLAN_XC}?
    +--rw xconnect-name          -> ../config/xconnect-name

```

---

```
+--rw config
| +--rw xconnect-name? string
| +--rw disable?      empty
+--ro state
| +--ro xconnect-name? string
| +--ro disable?      empty
| +--ro admin-status? ipi-vlan-xc-types:vlan_xc_admin_status_t
| +--ro oper-status?  ipi-vlan-xc-types:vlan_xc_oper_status_t
| +--ro ep1-rx-pkts?  yang:counter64
| +--ro ep1-rx-bytes? yang:counter64
| +--ro ep1-tx-pkts?  yang:counter64
| +--ro ep1-tx-bytes? yang:counter64
| +--ro ep2-rx-pkts?  yang:counter64
| +--ro ep2-rx-bytes? yang:counter64
| +--ro ep2-tx-pkts?  yang:counter64
| +--ro ep2-tx-bytes? yang:counter64
| +--ro bkp-ep1-rx-pkts? yang:counter64
| +--ro bkp-ep1-rx-bytes? yang:counter64
| +--ro bkp-ep1-tx-pkts? yang:counter64
| +--ro bkp-ep1-tx-bytes? yang:counter64
| +--ro bkp-ep2-rx-pkts? yang:counter64
| +--ro bkp-ep2-rx-bytes? yang:counter64
| +--ro bkp-ep2-tx-pkts? yang:counter64
| +--ro bkp-ep2-tx-bytes? yang:counter64
+--rw cross-connect-port
| +--rw config!
| | +--rw port-endpoint-1 -> /ipi-interface:interfaces/interface/name
| | +--rw port-endpoint-2 -> /ipi-interface:interfaces/interface/name
| +--ro state
|   +--ro port-endpoint-1 -> /ipi-interface:interfaces/interface/name
|   +--ro port-endpoint-2 -> /ipi-interface:interfaces/interface/name
|   +--ro ep1-rx-pkts?    yang:counter64
|   +--ro ep1-rx-bytes?   yang:counter64
|   +--ro ep1-tx-pkts?    yang:counter64
|   +--ro ep1-tx-bytes?   yang:counter64
|   +--ro ep2-rx-pkts?    yang:counter64
```

---

```
|  +--ro ep2-rx-bytes?   yang:counter64
|  +--ro ep2-tx-pkts?   yang:counter64
|  +--ro ep2-tx-bytes?  yang:counter64
|  +--ro bkp-ep1-rx-pkts? yang:counter64
|  +--ro bkp-ep1-rx-bytes? yang:counter64
|  +--ro bkp-ep1-tx-pkts? yang:counter64
|  +--ro bkp-ep1-tx-bytes? yang:counter64
|  +--ro bkp-ep2-rx-pkts? yang:counter64
|  +--ro bkp-ep2-rx-bytes? yang:counter64
|  +--ro bkp-ep2-tx-pkts? yang:counter64
|  +--ro bkp-ep2-tx-bytes? yang:counter64
+--rw cross-connect-port-specific
|  +--rw config!
|  |  +--rw backup-endpoint-1?      string
|  |  +--rw backup-endpoint-2?      string
|  |  +--rw revertive?              empty
|  |  +--rw link-fault-pass-through-enable? empty
|  +--ro state
|  |  +--ro backup-endpoint-1?      string
|  |  +--ro backup-endpoint-2?      string
|  |  +--ro revertive?              empty
|  |  +--ro link-fault-pass-through-enable? empty
+--rw cross-connect-vlan
  +--rw config!
  |  +--rw vlan-endpoint-1  -> /ipi-interface:interfaces/interface/name
  |  +--rw vlan-endpoint-2  -> /ipi-interface:interfaces/interface/name
  +--ro state
  |  +--ro vlan-endpoint-1  -> /ipi-interface:interfaces/interface/name
  |  +--ro vlan-endpoint-2  -> /ipi-interface:interfaces/interface/name
+--rw vlan-xc-entries
  +--rw vlan-xc-entry* [outer-vlan-range inner-vlan-range]
  |  +--rw outer-vlan-range  -> ../config/outer-vlan-range
  |  +--rw inner-vlan-range  -> ../config/inner-vlan-range
  |  +--rw config
  |  |  +--rw outer-vlan-range? string
  |  |  +--rw inner-vlan-range? string
```

```

+--ro state
  +--ro outer-vlan-range? string
  +--ro inner-vlan-range? string
  +--ro ep1-rx-pkts? yang:counter64
  +--ro ep1-rx-bytes? yang:counter64
  +--ro ep1-tx-pkts? yang:counter64
  +--ro ep1-tx-bytes? yang:counter64
  +--ro ep2-rx-pkts? yang:counter64
  +--ro ep2-rx-bytes? yang:counter64
  +--ro ep2-tx-pkts? yang:counter64
  +--ro ep2-tx-bytes? yang:counter64
  +--ro bkp-ep1-rx-pkts? yang:counter64
  +--ro bkp-ep1-rx-bytes? yang:counter64
  +--ro bkp-ep1-tx-pkts? yang:counter64
  +--ro bkp-ep1-tx-bytes? yang:counter64
  +--ro bkp-ep2-rx-pkts? yang:counter64
  +--ro bkp-ep2-rx-bytes? yang:counter64
  +--ro bkp-ep2-tx-pkts? yang:counter64
  +--ro bkp-ep2-tx-bytes? yang:counter64

```

rpcs:

```

+---x clear-cross-connect-counters {feature-list:HAVE_VLAN_XC}?
  +---w input
    +---w xc-name string

```

---

## module: ipi-vlan

```

+--rw vlan-classifier {feature-list:HAVE_VLAN_CLASS}?
| +--rw classifier-rules
| | +--rw classifier-rule* [rule-id]
| |   +--rw rule-id -> ../config/rule-id
| |   +--rw config
| |     | +--rw rule-id? uint16
| |     +--ro state
| |     | +--ro rule-id? uint16
| |     +--rw rule-criteria

```

```

| |   +--rw config
| |   | +--rw mac-address?  cml-data-types:cml_mac_addr_t
| |   | +--rw ipv4-address? cml-data-types:cml_ipv4_prefix_t
| |   | +--rw ether-type?   ipi-vlan-types:vlan_classifier_ethertype_t
| |   +--ro state
| |     +--ro mac-address?  cml-data-types:cml_mac_addr_t
| |     +--ro ipv4-address? cml-data-types:cml_ipv4_prefix_t
| |     +--ro ether-type?   ipi-vlan-types:vlan_classifier_ethertype_t
| +--rw classifier-groups
| | +--rw classifier-group* [group-id rule-id]
| |   +--rw group-id   -> ../config/group-id
| |   +--rw rule-id    -> ../config/rule-id
| |   +--rw config
| |     | +--rw group-id?  uint8
| |     | +--rw rule-id?   -> /vlan-classifier/classifier-rules/classifier-rule/rule-id
| |     +--ro state
| |       +--ro group-id?  uint8
| |       +--ro rule-id?   -> /vlan-classifier/classifier-rules/classifier-rule/rule-id
| +--rw ports
| | +--rw port* [port-name group-id]
| |   +--rw port-name   -> ../config/port-name
| |   +--rw group-id    -> ../config/group-id
| |   +--rw config
| |     | +--rw port-name? -> /ipi-interface:interfaces/interface/name
| |     | +--rw group-id?  -> /vlan-classifier/classifier-groups/classifier-group/group-id
| |     | +--rw vlan-id    -> /ipi-network-instance:network-instances/network-instance/ipi-bridge:bridge/vlans/vlan/vlan-
id
| |     +--ro state
| |       +--ro port-name? -> /ipi-interface:interfaces/interface/name
| |       +--ro group-id?  -> /vlan-classifier/classifier-groups/classifier-group/group-id
| |       +--ro vlan-id    -> /ipi-network-instance:network-instances/network-instance/ipi-bridge:bridge/vlans/vlan/vlan-id
+--rw vlan-reservation {feature-list:HAVE_FLEXPORT,feature-list:NOT_HAVE_DUNE}?
| +--rw config
| | +--rw vlan-id?  cml-data-types:cml_range_t {feature-list:NOT_HAVE_DUNE}?
| +--ro state
| | +--ro vlan-id?  cml-data-types:cml_range_t {feature-list:NOT_HAVE_DUNE}?
+--rw layer2-global

```

```

+--rw config
| +--rw disable-vlan-classifier-feature? empty {feature-list:HAVE_VLAN_CLASS}?
| +--rw disable-port-security?         empty
| +--rw vlan-xlate-1?                  empty
+--ro state
  +--ro disable-vlan-classifier-feature? empty {feature-list:HAVE_VLAN_CLASS}?
  +--ro disable-port-security?         empty
  +--ro vlan-xlate-1?                  empty

```

augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance/ipi-bridge:bridge:

```

+--rw vlans
  +--rw vlan* [vlan-id]
    +--rw vlan-id    -> ../config/vlan-id
    +--rw config
      | +--rw vlan-id?      cml-data-types:cml_range_t
      | +--rw disable-mac-learning? empty
      +--ro state
        | +--ro vlan-id?      cml-data-types:cml_range_t
        | +--ro disable-mac-learning? empty
    +--rw customer-vlan
      | +--rw config
      | | +--rw type? ipi-vlan-types:cvlan_type_t
      | | +--rw name? string
      | | +--rw state? ipi-vlan-types:vlan_state_t
      | +--ro state
      | | +--ro type? ipi-vlan-types:cvlan_type_t
      | | +--ro name? string
      | | +--ro state? ipi-vlan-types:vlan_state_t
      | | +--ro operational-status? ipi-vlan-types:vlan_oper_status_t
      | | +--ro tagged-interface* string
    +--rw service-vlan {feature-list:HAVE_PROVIDER_BRIDGE}?
      | +--rw config
      | | +--rw type? ipi-vlan-types:svlan_type_t
      | | +--rw name? string
      | | +--rw state? ipi-vlan-types:vlan_state_t
      | +--ro state

```

```

| +--ro type?          ipi-vlan-types:svlan_type_t
| +--ro name?         string
| +--ro state?        ipi-vlan-types:vlan_state_t
| +--ro operational-status? ipi-vlan-types:vlan_oper_status_t
| +--ro tagged-interface* string
+--rw private-vlan {feature-list:HAVE_PVLAN}?
  +--rw config!
  | +--rw type ipi-vlan-types:vlan_pvlan_type_t
  +--ro state
  | +--ro type ipi-vlan-types:vlan_pvlan_type_t
  +--rw association
    +--rw config
    | +--rw secondary-vlan? cml-data-types:cml_range_t
    +--ro state
      +--ro secondary-vlan? cml-data-types:cml_range_t
augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance/ipi-bridge:bridge:
+--rw cvlan-registration-tables {feature-list:HAVE_VLAN,feature-list:HAVE_PROVIDER_BRIDGE}?
+--rw cvlan-registration-table* [table-name]
  +--rw table-name -> ../config/table-name
  +--rw config
  | +--rw table-name? string
  +--ro state
  | +--ro table-name? string
+--rw cvlan-mappings
  +--rw cvlan-mapping* [svlan-id cvlan-id]
    +--rw svlan-id -> ../config/svlan-id
    +--rw cvlan-id -> ../config/cvlan-id
    +--rw config
    | +--rw svlan-id? uint16
    | +--rw cvlan-id? cml-data-types:cml_range_t
    | +--rw untagged-ep? ipi-vlan-types:cvlan_config_t
    | +--rw translated-cvlan-id? uint16
    | +--rw svlan-cos? uint8 {feature-list:NOT_HAVE_CUSTOM2_QOS,feature-
list:NOT_HAVE_CUSTOM4_QOS}?
    | +--rw svlan-cfi? uint8 {feature-list:NOT_HAVE_CUSTOM2_QOS,feature-
list:NOT_HAVE_CUSTOM4_QOS}?

```

```

    | +--rw cvlan-cos?          uint8 {feature-list:NOT_HAVE_CUSTOM2_QOS,feature-
list:NOT_HAVE_CUSTOM4_QOS}?
    | +--rw cvlan-cfi?         uint8 {feature-list:NOT_HAVE_CUSTOM2_QOS,feature-
list:NOT_HAVE_CUSTOM4_QOS}?
    +--ro state
      +--ro svlan-id?          uint16
      +--ro cvlan-id?          cml-data-types:cml_range_t
      +--ro untagged-ep?       ipi-vlan-types:cvlan_config_t
      +--ro translated-cvlan-id? uint16
      +--ro svlan-cos?         uint8 {feature-list:NOT_HAVE_CUSTOM2_QOS,feature-
list:NOT_HAVE_CUSTOM4_QOS}?
      +--ro svlan-cfi?         uint8 {feature-list:NOT_HAVE_CUSTOM2_QOS,feature-
list:NOT_HAVE_CUSTOM4_QOS}?
      +--ro cvlan-cos?         uint8 {feature-list:NOT_HAVE_CUSTOM2_QOS,feature-
list:NOT_HAVE_CUSTOM4_QOS}?
      +--ro cvlan-cfi?         uint8 {feature-list:NOT_HAVE_CUSTOM2_QOS,feature-
list:NOT_HAVE_CUSTOM4_QOS}?

```

---

## module: ipi-vrf

augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance:

```

+--rw vrf
  +--rw config
    | +--rw vrf-name?          -> /ipi-network-instance:network-instances/network-instance/instance-name
    | +--rw description?       cml-data-types:cml_line_t
    | +--rw router-id?         inet:ipv4-address
    | +--rw evpn-layer3-network-id? uint32 {feature-list:HAVE_BGP_EVPN,feature-list:HAVE_NVO}?
  +--ro state
    | +--ro vrf-name?          -> /ipi-network-instance:network-instances/network-instance/instance-name
    | +--ro description?       cml-data-types:cml_line_t
    | +--ro router-id?         inet:ipv4-address
    | +--ro evpn-layer3-network-id? uint32 {feature-list:HAVE_BGP_EVPN,feature-list:HAVE_NVO}?
    | +--ro vrf-id?           uint32
    | +--ro fib-id?           uint32

```

---

```
+--rw snmp {feature-list:HAVE_SNMP}?
  +--rw config
    | +--rw snmp-context-name? string
  +--ro state
    +--ro snmp-context-name? string
```

rpcs:

```
+---x clear-default-router-id {feature-list:HAVE_L3}?
+---x clear-vrf-router-id {feature-list:HAVE_VRF}?
  +---w input
    +---w vrfName string
```

---

## module: ipi-vrrp

```
+--rw vrrp
  +--rw global
    | +--rw config
    | | +--rw disable-virtual-router-mac-address? empty
    | | +--rw vrrp-v2-compatible? empty
    | | +--rw ipv4-exclude-pseudo-header? empty
    | +--ro state
    | | +--ro disable-virtual-router-mac-address? empty
    | | +--ro vrrp-v2-compatible? empty
    | | +--ro ipv4-exclude-pseudo-header? empty
    | | +--ro notification-control? empty
    | +--ro session
    | | +--ro state
    | | | +--ro session-table-maximum? uint32
    | | | +--ro session-table-size? uint32
    | | | +--ro ipv4-session-count? uint32
```

```
| | +--ro ipv6-session-count?   uint32
| +--ro new-master
| | +--ro operational-master-address?  inet:ip-address
| | +--ro virtual-router-id?         uint8
| | +--ro new-master-reason?         ipi-vrrp-types:vrrp_new_master_reason_t
| | +--ro uptime?                   string
| +--ro protocol-error
| | +--ro operational-master-address?  inet:ip-address
| | +--ro virtual-router-id?         uint8
| | +--ro error-reason?              ipi-vrrp-types:vrrp_error_reason_t
| | +--ro uptime?                   string
| +--ro packet-error
| | +--ro error-reason?              ipi-vrrp-types:vrrp_error_reason_t
| +--ro errors
| +--ro state
|   +--ro checksum-error?           yang:counter64
|   +--ro version-error?           yang:counter64
|   +--ro invalid-virtual-router-id? yang:counter64
+--rw debug
| +--rw config
| | +--rw options? ipi-vrrp-types:vrrp_debug_t
| +--ro state
|   +--ro options? ipi-vrrp-types:vrrp_debug_t
|   +--ro terminal-debug-status? ipi-vrrp-types:vrrp_debug_t
+--rw ipv4-instances
| +--rw ipv4-instance* [virtual-router-id]
|   +--rw virtual-router-id  -> ../config/virtual-router-id
|   +--rw config
|     | +--rw virtual-router-id? uint8
|     +--ro state
|     | +--ro virtual-router-id? uint8
|     +--rw interfaces
|       +--rw interface* [interface-name]
|         +--rw interface-name  -> ../config/interface-name
|         +--rw config
|           | +--rw interface-name?  -> /ipi-interface:interfaces/interface/name
```

---

```

|   | +--rw disable-preempt-mode?    empty
|   | +--rw priority?                uint8
|   | +--rw preempt-delay?          uint32
|   | +--rw advertisement-interval?  uint16
|   | +--rw disable-accept-mode?    empty
|   | +--rw vrrp-v2-compatible?     empty
|   | +--rw ipv4-exclude-pseudo-header? empty
|   | +--rw authentication-data?    string
|   | +--rw primary-ip-address?     inet:ipv4-address
|   | +--rw mlag-active-standby?    empty {feature-list:HAVE_MLAG}?
|   +--ro state
|   | +--ro interface-name?         -> /ipi-interface:interfaces/interface/name
|   | +--ro disable-preempt-mode?   empty
|   | +--ro priority?               uint8
|   | +--ro preempt-delay?          uint32
|   | +--ro advertisement-interval?  uint16
|   | +--ro disable-accept-mode?    empty
|   | +--ro vrrp-v2-compatible?     empty
|   | +--ro ipv4-exclude-pseudo-header? empty
|   | +--ro authentication-data?    string
|   | +--ro primary-ip-address?     inet:ipv4-address
|   | +--ro mlag-active-standby?    empty {feature-list:HAVE_MLAG}?
|   +--rw protocol-enable
|   | +--rw config
|   | | +--rw enable? empty
|   | +--ro state
|   | | +--ro enable? empty
|   +--rw virtual-ip
|   | +--rw config!
|   | | +--rw virtual-ip-address  inet:ipv4-address
|   | | +--rw ip-address-owner    boolean
|   | +--ro state
|   | | +--ro virtual-ip-address  inet:ipv4-address
|   | | +--ro ip-address-owner    boolean
|   +--rw interfaces-tracking
|   | +--rw interface-tracking* [interface-tracking-name]

```

---

---

```
| | +--rw interface-tracking-name -> ../config/interface-tracking-name
| | +--rw config
| | | +--rw interface-tracking-name? -> /ipi-interface:interfaces/interface/name
| | | +--rw priority-decrement uint8
| | +--ro state
| | +--ro interface-tracking-name? -> /ipi-interface:interfaces/interface/name
| | +--ro priority-decrement uint8
| | +--ro interface-status? ipi-vrrp-types:vrrp_iface_status_t
| | +--ro interface-down-events? uint32
+--ro addresses
| +--ro state
| +--ro operational-primary-address? inet:ipv4-address
| +--ro operational-master-address? inet:ipv4-address
+--ro session-info
| +--ro state
| +--ro multicast-membership? ipi-vrrp-types:vrrp_member_state_t
| +--ro address-family? ipi-vrrp-types:vrrp_addr_family_t
| +--ro running-priority? uint8
| +--ro virtual-mac-mbyte-word? cml-data-types:cml_mac_addr_t
| +--ro administrative-state? ipi-vrrp-types:vrrp_admin_state_t
| +--ro init-message-code? ipi-vrrp-types:vrrp_init_message_code_t
+--ro reasons
| +--ro state
| +--ro new-master-reason? ipi-vrrp-types:vrrp_new_master_reason_t
+--ro session-status
| +--ro state
| +--ro vrrp-state? ipi-vrrp-types:vrrp_session_state_t
| +--ro virtual-address-status? ipi-vrrp-types:vrrp_ip_status_t
+--ro timers
| +--ro state
| +--ro switchback-delay-timer? uint32
| +--ro countdown-timer? uint32
| +--ro skew-time? uint32
| +--ro garp-packet-delay? uint32
| +--ro master-advertise-interval? uint32
| +--ro refresh-rate-interval? uint32
```

```
|   +--ro statistics
|   |   +--ro state
|   |   |   +--ro transitions-to-master?      yang:counter64
|   |   |   +--ro advertise-received?        yang:counter64
|   |   |   +--ro priority-zero-received-packets? yang:counter64
|   |   |   +--ro priority-zero-sent-packets? yang:counter64
|   |   |   +--ro disconnection-time?        string
|   |   |   +--ro monitored-circuit-up-events? yang:counter64
|   |   |   +--ro monitored-circuit-down-events? yang:counter64
|   +--ro errors
|   |   +--ro state
|   |   |   +--ro ttl-error-packets?          yang:counter64
|   |   |   +--ro invalid-type-packets?      yang:counter64
|   |   |   +--ro address-list-errors?       yang:counter64
|   |   |   +--ro invalid-authentication-type? yang:counter64
|   |   |   +--ro authentication-type-mismatch? yang:counter64
|   |   |   +--ro wrong-authentication-password? yang:counter64
|   |   |   +--ro address-mismatch-packets?  yang:counter64
|   |   |   +--ro packet-length-errors?      yang:counter64
|   +--rw objects-tracking {feature-list:HAVE_OBJ_TRACKING}?
|   |   +--rw object-tracking* [tracking-id]
|   |   |   +--rw tracking-id  -> ../config/tracking-id
|   |   |   +--rw config
|   |   |   |   +--rw tracking-id?  uint16
|   |   |   |   +--rw decrement    uint8
|   |   |   +--ro state
|   |   |   |   +--ro tracking-id?    uint16
|   |   |   |   +--ro decrement      uint8
|   |   |   |   +--ro object-status?  ipi-vrrp-types:vrrp_iface_status_t
|   |   |   |   +--ro object-down-events? uint32
+--rw ipv6-instances
+--rw ipv6-instance* [virtual-router-id]
+--rw virtual-router-id  -> ../config/virtual-router-id
+--rw config
| +--rw virtual-router-id?  uint8
+--ro state
```

---

```
| +--ro virtual-router-id? uint8
+--rw interfaces
  +--rw interface* [interface-name]
    +--rw interface-name      -> ../config/interface-name
    +--rw config
      | +--rw interface-name?   -> /ipi-interface:interfaces/interface/name
      | +--rw disable-preempt-mode? empty
      | +--rw priority?         uint8
      | +--rw preempt-delay?    uint32
      | +--rw advertisement-interval? uint16
      | +--rw disable-accept-mode? empty
      | +--rw primary-ip-address? inet:ipv6-address
    +--ro state
      | +--ro interface-name?   -> /ipi-interface:interfaces/interface/name
      | +--ro disable-preempt-mode? empty
      | +--ro priority?         uint8
      | +--ro preempt-delay?    uint32
      | +--ro advertisement-interval? uint16
      | +--ro disable-accept-mode? empty
      | +--ro primary-ip-address? inet:ipv6-address
    +--rw protocol-enable
      | +--rw config
      | | +--rw enable? empty
      | +--ro state
      | +--ro enable? empty
    +--rw virtual-ip-addresses {feature-list:HAVE_IPV6}?
      | +--rw virtual-ip-address* [virtual-ip-address]
      | +--rw virtual-ip-address -> ../config/virtual-ip-address
      | +--rw config
      | | +--rw virtual-ip-address? inet:ipv6-address
      | | +--rw ip-address-owner? boolean
      | +--ro state
      | +--ro virtual-ip-address? inet:ipv6-address
      | +--ro ip-address-owner? boolean
    +--rw interfaces-tracking
      | +--rw interface-tracking* [interface-tracking-name]
```

---

```
| +--rw interface-tracking-name -> ../config/interface-tracking-name
| +--rw config
| | +--rw interface-tracking-name? -> /ipi-interface:interfaces/interface/name
| | +--rw priority-decrement      uint8
| +--ro state
|   +--ro interface-tracking-name? -> /ipi-interface:interfaces/interface/name
|   +--ro priority-decrement      uint8
|   +--ro interface-status?       ipi-vrrp-types:vrrp_iface_status_t
|   +--ro interface-down-events?  uint32
+--ro addresses
| +--ro state
|   +--ro operational-primary-ipv6? inet:ipv6-address
|   +--ro operational-master-ipv6?  inet:ipv6-address
+--ro session-info
| +--ro state
|   +--ro multicast-membership?     ipi-vrrp-types:vrrp_member_state_t
|   +--ro address-family?          ipi-vrrp-types:vrrp_addr_family_t
|   +--ro running-priority?        uint8
|   +--ro virtual-mac-mbyte-word?  cml-data-types:cml_mac_addr_t
|   +--ro administrative-state?    ipi-vrrp-types:vrrp_admin_state_t
|   +--ro init-message-code?       ipi-vrrp-types:vrrp_init_message_code_t
+--ro reasons
| +--ro state
|   +--ro new-master-reason?       ipi-vrrp-types:vrrp_new_master_reason_t
+--ro session-status
| +--ro state
|   +--ro vrrp-state?              ipi-vrrp-types:vrrp_session_state_t
|   +--ro virtual-address-status?  ipi-vrrp-types:vrrp_ip_status_t
+--ro timers
| +--ro state
|   +--ro switchback-delay-timer?  uint32
|   +--ro countdown-timer?        uint32
|   +--ro skew-time?              uint32
|   +--ro garp-packet-delay?       uint32
|   +--ro master-advertise-interval? uint32
|   +--ro refresh-rate-interval?   uint32
```

```

+--ro statistics
| +--ro state
|   +--ro transitions-to-master?      yang:counter64
|   +--ro advertise-received?        yang:counter64
|   +--ro priority-zero-received-packets? yang:counter64
|   +--ro priority-zero-sent-packets? yang:counter64
|   +--ro disconnection-time?        string
|   +--ro monitored-circuit-up-events? yang:counter64
|   +--ro monitored-circuit-down-events? yang:counter64
+--ro errors
| +--ro state
|   +--ro ttl-error-packets?          yang:counter64
|   +--ro invalid-type-packets?      yang:counter64
|   +--ro address-list-errors?       yang:counter64
|   +--ro invalid-authentication-type? yang:counter64
|   +--ro authentication-type-mismatch? yang:counter64
|   +--ro wrong-authentication-password? yang:counter64
|   +--ro address-mismatch-packets?   yang:counter64
|   +--ro packet-length-errors?      yang:counter64
+--rw objects-tracking {feature-list:HAVE_OBJ_TRACKING}?
  +--rw object-tracking* [tracking-id]
    +--rw tracking-id  -> ../config/tracking-id
    +--rw config
      | +--rw tracking-id?  uint16
      | +--rw decrement   uint8
      +--ro state
        +--ro tracking-id?    uint16
        +--ro decrement      uint8
        +--ro object-status?  ipi-vrrp-types:vrrp_iface_status_t
        +--ro object-down-events? uint32

```

rpcs:

```

+---x vrrp-snmp-restart {feature-list:HAVE_SNMP}?
+---x vrrp-clear-statistics {feature-list:HAVE_VRRPD}?
+---x vrrp-clear-ipv4-statistics {feature-list:HAVE_VRRPD}?
+---x vrrp-clear-ipv6-statistics {feature-list:HAVE_VRRPD}?

```

```

+---x vrrp-clear-session-ipv4-statistics {feature-list:HAVE_VRRPD}?
| +---w input
|   +---w vrrp-id      uint8
|   +---w interface-name  string
+---x vrrp-clear-session-ipv6-statistics {feature-list:HAVE_VRRPD}?
| +---w input
|   +---w vrrp-id      uint8
|   +---w interface-name  string
+---x vrrp-terminal-debug-all-on {feature-list:HAVE_VRRPD}?
+---x vrrp-terminal-debug-all-off {feature-list:HAVE_VRRPD}?
+---x vrrp-terminal-debug-on {feature-list:HAVE_VRRPD}?
| +---w input
|   +---w terminal-debug-options  ipi-vrrp-types:vrrp_debug_t
+---x vrrp-terminal-debug-off {feature-list:HAVE_VRRPD}?
  +---w input
    +---w terminal-debug-options  ipi-vrrp-types:vrrp_debug_t

```

notifications:

```

+---n vrrp-new-master
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro operational-master-address?  inet:ip-address
| +--ro virtual-router-id?   uint8
| +--ro new-master-reason?   ipi-vrrp-types:vrrp_new_master_reason_t
| +--ro uptime?           string
+---n vrrp-protocol-error
| +--ro severity?          cml-data-types:cml_notif_severity_t
| +--ro eventClass?       cml-data-types:cml_notif_class_t
| +--ro operational-master-address?  inet:ip-address
| +--ro virtual-router-id?   uint8
| +--ro error-reason?       ipi-vrrp-types:vrrp_error_reason_t
| +--ro uptime?           string
+---n vrrp-packet-error
  +--ro severity?          cml-data-types:cml_notif_severity_t
  +--ro eventClass?       cml-data-types:cml_notif_class_t
  +--ro error-reason?     ipi-vrrp-types:vrrp_error_reason_t

```

---

## module: ipi-vxlan

```

+--rw vxlan
  +--rw global
    | +--rw config!
    | | +--rw enable-vxlan          empty
    | | +--rw vtep-ipv4?           inet:ipv4-address
    | | +--rw mac-ageing-timer?    uint32
    | | +--rw arp-nd-refresh-timer? uint32 {feature-list:HAVE_BGP_EVPN}?
    | | +--rw mac-address?         cml-data-types:cml_mac_addr_t {feature-list:HAVE_BGP_EVPN}?
    | | +--rw maximum-cache-disable-count? uint16 {feature-list:HAVE_BGP_EVPN,feature-
list:NOT_HAVE_DUNE}?
    | | +--rw disable-arp-storm-control-for-cpu? empty {feature-list:NOT_HAVE_DUNE}?
    | +--ro state
    | +--ro enable-vxlan          empty
    | +--ro vtep-ipv4?           inet:ipv4-address
    | +--ro mac-ageing-timer?    uint32
    | +--ro arp-nd-refresh-timer? uint32 {feature-list:HAVE_BGP_EVPN}?
    | +--ro mac-address?         cml-data-types:cml_mac_addr_t {feature-list:HAVE_BGP_EVPN}?
    | +--ro maximum-cache-disable-count? uint16 {feature-list:HAVE_BGP_EVPN,feature-
list:NOT_HAVE_DUNE}?
    | +--ro disable-arp-storm-control-for-cpu? empty {feature-list:NOT_HAVE_DUNE}?
  +--rw qos-tunnel-mappings
    | +--rw qos-tunnel-mapping* [qos-map-mode traffic-direction] {feature-list:HAVE_QOS}?
    | +--rw qos-map-mode      -> ../config/qos-map-mode
    | +--rw traffic-direction -> ../config/traffic-direction
    | +--rw config
    | | +--rw traffic-direction? ipi-vxlan-types:vxlan_qos_dir_t
    | | +--rw qos-map-mode?     ipi-vxlan-types:vxlan_qos_global_mode_t
    | | +--rw profile-name      string
    | +--ro state
    | +--ro traffic-direction? ipi-vxlan-types:vxlan_qos_dir_t
    | +--ro qos-map-mode?     ipi-vxlan-types:vxlan_qos_global_mode_t
    | +--ro profile-name      string

```

```

+--rw vxlan-tenants
| +--rw vxlan-tenant* [vxlan-identifier]
|   +--rw vxlan-identifier   -> ../config/vxlan-identifier
|   +--rw config
|     | +--rw vrf-name?      -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
{feature-list:HAVE_BGP_EVPN}?
|     | +--rw map-network*   string
|     | +--rw mac-hold-timer? int32 {feature-list:HAVE_BGP_EVPN}?
|     | +--rw tenant-description? string
|     | +--rw irb-name?     -> /ipi-interface:interfaces/interface/name {feature-list:HAVE_BGP_EVPN}?
|     | +--rw vxlan-identifier? uint32
|     | +--rw tenant-type?   ipi-vxlan-types:vxlan_tenant_type_t
|     | +--rw tenant-type-bridge? ipi-vxlan-types:vxlan_tenant_type_bridge_t
|     | +--rw bridge-vlan-id? -> /ipi-network-instance:network-instances/network-instance/ipi-bridge:bridge/ipi-
vlan:vlan/vlan/vlan-id {feature-list:NOT_HAVE_DUNE}?
|     | +--rw etree-leaf?   empty
|     | +--rw tenant-xconnect-type? ipi-vxlan-types:vxlan_tenant_xconnect_type_t
|     +--ro state
|     | +--ro vrf-name?     -> /ipi-network-instance:network-instances/network-instance/ipi-vrf:vrf/config/vrf-name
{feature-list:HAVE_BGP_EVPN}?
|     | +--ro map-network*   string
|     | +--ro mac-hold-timer? int32 {feature-list:HAVE_BGP_EVPN}?
|     | +--ro tenant-description? string
|     | +--ro irb-name?     -> /ipi-interface:interfaces/interface/name {feature-list:HAVE_BGP_EVPN}?
|     | +--ro vxlan-identifier? uint32
|     | +--ro tenant-type?   ipi-vxlan-types:vxlan_tenant_type_t
|     | +--ro tenant-type-bridge? ipi-vxlan-types:vxlan_tenant_type_bridge_t
|     | +--ro bridge-vlan-id? -> /ipi-network-instance:network-instances/network-instance/ipi-bridge:bridge/ipi-
vlan:vlan/vlan/vlan-id {feature-list:NOT_HAVE_DUNE}?
|     | +--ro etree-leaf?   empty
|     | +--ro tenant-xconnect-type? ipi-vxlan-types:vxlan_tenant_xconnect_type_t
|     +--ro route-count-info
|     | +--ro state
|     |   +--ro total?   uint32
|     |   +--ro mac-only? uint32
|     |   +--ro mac-ipv4? uint32
|     |   +--ro mac-ipv6? uint32 {feature-list:HAVE_IPV6}?
|     +--rw irb

```

```

| | +--rw config
| | | +--rw irb-advertise-host-route? empty {feature-list:HAVE_BGP_EVPN}?
| | | +--ro state
| | |   +--ro irb-advertise-host-route? empty {feature-list:HAVE_BGP_EVPN}?
| | +--rw static-tenants
| | | +--rw static-tenant* [mac-address]
| | |   +--rw mac-address -> ../config/mac-address
| | |   +--rw config
| | | | +--rw mac-address? cml-data-types:cml_mac_addr_t
| | | | +--rw remote-vtep-ipv4 inet:ipv4-address
| | |   +--ro state
| | |     +--ro mac-address? cml-data-types:cml_mac_addr_t
| | |     +--ro remote-vtep-ipv4 inet:ipv4-address
| +--ro arp-cache-info* [host-ip]
| | +--ro host-ip -> ../state/host-ip
| | +--ro state
| | | +--ro host-ip? inet:ipv4-address
| | | +--ro host-mac? cml-data-types:cml_mac_addr_t
| | | +--ro host-type? ipi-vxlan-types:vxlan_host_t
| | | +--ro interface-index? uint32
| +--ro nd-cache-info* [host-ip]
| | +--ro host-ip -> ../state/host-ip
| | +--ro state
| | | +--ro host-ip? inet:ipv6-address
| | | +--ro host-mac? cml-data-types:cml_mac_addr_t
| | | +--ro host-type? ipi-vxlan-types:vxlan_host_t
| | | +--ro interface-index? uint32
| +--ro mac-table-info* [mac-address]
| | +--ro mac-address -> ../state/mac-address
| | +--ro state
| | | +--ro mac-address? cml-data-types:cml_mac_addr_t
| | | +--ro interface-name? -> /ipi-interface:interfaces/interface/name
| | | +--ro vlan-id? string
| | | +--ro inner-vlan-id? uint32
| | | +--ro vtep-ip-esi? string
| | | +--ro host-type? ipi-vxlan-types:vxlan_host_t

```

```

| | +--ro host-status?          ipi-vxlan-types:vxlan_host_status_t
| | +--ro access-port-description? string
| +--ro static-host-info* [mac-address host-ipv4]
| | +--ro mac-address -> ../state/mac-address
| | +--ro host-ipv4 -> ../state/host-ipv4
| | +--ro state
| | +--ro mac-address?        cml-data-types:cml_mac_addr_t
| | +--ro static-host-state?  ipi-vxlan-types:vxlan_static_host_state_t
| | +--ro host-ipv4?         inet:ipv4-address
| +--ro static-host-ipv6-info* [mac-address host-ipv6]
|   +--ro mac-address -> ../state/mac-address
|   +--ro host-ipv6 -> ../state/host-ipv6
|   +--ro state
|     +--ro mac-address?      cml-data-types:cml_mac_addr_t
|     +--ro static-host-state? ipi-vxlan-types:vxlan_static_host_state_t
|     +--ro host-ipv6?       inet:ipv6-address {feature-list:HAVE_IPV6}?
+--ro tunnel* [destination-vtep-ip]
| +--ro destination-vtep-ip -> ../state/destination-vtep-ip
| +--ro state
|   +--ro destination-vtep-ip? inet:ipv4-address
|   +--ro source-vtep-ip?     inet:ipv4-address
|   +--ro up-down-time?      yang:timeticks
|   +--ro tunnel-status?     ipi-vxlan-types:vxlan_tunnel_status_t
|   +--ro counters
|     +--ro out-bytes?        yang:counter64
|     +--ro out-packets?     yang:counter64
|     +--ro in-bytes?        yang:counter64
|     +--ro in-packets?      yang:counter64
|     +--ro tx-arp-discard-packets? yang:counter64
|     +--ro tx-nd-discard-packets? yang:counter64
|     +--ro tx-arp-request-packets? yang:counter64
|     +--ro tx-arp-reply-packets?  yang:counter64
|     +--ro tx-neighbor-solicitation-packets? yang:counter64
|     +--ro tx-neighbor-advertisement-packets? yang:counter64
|     +--ro tx-garp-packets?     yang:counter64
|     +--ro tx-gna-packets?     yang:counter64

```

```

+--rw untagged-access-interfaces
| +--rw untagged-access-interface* [untagged-interface-name] {feature-list:NOT_HAVE_DNX}?
|   +--rw untagged-interface-name          -> ../config/untagged-interface-name
|   +--rw config
|     | +--rw interface-name?              -> /ipi-interface:interfaces/interface/name
|     | +--rw admin-shutdown?             empty
|     | +--rw description?                cml-data-types:cml_line_t
|     | +--rw dynamic-learning-disable?   empty
|     | +--rw access-mac-hold-time?       int32
|     | +--rw arp-nd-flood-suppress?      empty {feature-list:HAVE_BGP_EVPN}?
|     | +--rw garp-gna-enable?            empty {feature-list:HAVE_BGP_EVPN}?
|     | +--rw mac-address*                 cml-data-types:cml_mac_addr_t
|     | +--rw default-access-interface?   empty
|     | +--rw untagged-interface-name?    -> /ipi-interface:interfaces/interface/name
|     +--ro state
|       | +--ro interface-name?           -> /ipi-interface:interfaces/interface/name
|       | +--ro admin-shutdown?           empty
|       | +--ro description?              cml-data-types:cml_line_t
|       | +--ro dynamic-learning-disable? empty
|       | +--ro access-mac-hold-time?     int32
|       | +--ro arp-nd-flood-suppress?    empty {feature-list:HAVE_BGP_EVPN}?
|       | +--ro garp-gna-enable?          empty {feature-list:HAVE_BGP_EVPN}?
|       | +--ro mac-address*              cml-data-types:cml_mac_addr_t
|       | +--ro default-access-interface? empty
|       | +--ro untagged-interface-name?  -> /ipi-interface:interfaces/interface/name
|     +--rw cache
|       | +--rw config
|       | | +--rw arp-cache-disable?      empty {feature-list:HAVE_BGP_EVPN}?
|       | | +--rw nd-cache-disable?      empty {feature-list:HAVE_BGP_EVPN}?
|       | +--ro state
|       | | +--ro arp-cache-disable?      empty {feature-list:HAVE_BGP_EVPN}?
|       | | +--ro nd-cache-disable?      empty {feature-list:HAVE_BGP_EVPN}?
|     +--rw map
|       | +--rw config
|       | | +--rw vxlan-identifier?      -> /vxlan/vxlan-tenants/vxlan-tenant/config/vxlan-identifier
|       | | +--rw tenant-description?    -> /vxlan/vxlan-tenants/vxlan-tenant/config/tenant-description

```

```
| | +--ro state
| |   +--ro vxlan-identifier?  -> /vxlan/vxlan-tenants/vxlan-tenant/config/vxlan-identifier
| |   +--ro tenant-description? -> /vxlan/vxlan-tenants/vxlan-tenant/config/tenant-description
| +--rw host-macs-ipv4
| | +--rw host-mac-ipv4* [mac-address ipv4-address] {feature-list:NOT_HAVE_DNX}?
| |   +--rw mac-address  -> ../config/mac-address
| |   +--rw ipv4-address  -> ../config/ipv4-address
| |   +--rw config
| |     | +--rw mac-address?  cml-data-types:cml_mac_addr_t
| |     | +--rw ipv4-address? inet:ipv4-address
| |     +--ro state
| |       +--ro mac-address?  cml-data-types:cml_mac_addr_t
| |       +--ro ipv4-address?  inet:ipv4-address
| +--rw host-macs-ipv6
| | +--rw host-mac-ipv6* [mac-address ipv6-address] {feature-list:HAVE_IPV6,feature-list:NOT_HAVE_DNX}?
| |   +--rw mac-address  -> ../config/mac-address
| |   +--rw ipv6-address  -> ../config/ipv6-address
| |   +--rw config
| |     | +--rw mac-address?  cml-data-types:cml_mac_addr_t
| |     | +--rw ipv6-address? inet:ipv6-address
| |     +--ro state
| |       +--ro mac-address?  cml-data-types:cml_mac_addr_t
| |       +--ro ipv6-address?  inet:ipv6-address
| +--rw access-interface-qos-type-mappings
|   +--rw access-interface-qos-type-mapping* [profile-map-type] {feature-list:HAVE_QOS}?
|     +--rw profile-map-type  -> ../config/profile-map-type
|     +--rw config
|       | +--rw profile-map-type? ipi-vxlan-types:vxlan_qos_map_profile_type_t
|       | +--rw profile-name      string
|       +--ro state
|         +--ro profile-map-type? ipi-vxlan-types:vxlan_qos_map_profile_type_t
|         +--ro profile-name      string
+--rw tagged-access-interfaces
| +--rw tagged-access-interface* [interface-name vlan-identifier] {feature-list:NOT_HAVE_DNX}?
|   +--rw interface-name      -> ../config/interface-name
|   +--rw vlan-identifier      -> ../config/vlan-identifier
```

```
| +--rw config
| | +--rw tag-protocol-identifier? string
| | +--rw interface-name? -> /ipi-interface:interfaces/interface/name
| | +--rw admin-shutdown? empty
| | +--rw description? cml-data-types:cml_line_t
| | +--rw dynamic-learning-disable? empty
| | +--rw access-mac-hold-time? int32
| | +--rw arp-nd-flood-suppress? empty {feature-list:HAVE_BGP_EVPN}?
| | +--rw garp-gna-enable? empty {feature-list:HAVE_BGP_EVPN}?
| | +--rw mac-address* cml-data-types:cml_mac_addr_t
| | +--rw vlan-identifier? string
| +--ro state
| | +--ro tag-protocol-identifier? string
| | +--ro interface-name? -> /ipi-interface:interfaces/interface/name
| | +--ro admin-shutdown? empty
| | +--ro description? cml-data-types:cml_line_t
| | +--ro dynamic-learning-disable? empty
| | +--ro access-mac-hold-time? int32
| | +--ro arp-nd-flood-suppress? empty {feature-list:HAVE_BGP_EVPN}?
| | +--ro garp-gna-enable? empty {feature-list:HAVE_BGP_EVPN}?
| | +--ro mac-address* cml-data-types:cml_mac_addr_t
| | +--ro vlan-identifier? string
| +--rw cache
| | +--rw config
| | | +--rw arp-cache-disable? empty {feature-list:HAVE_BGP_EVPN}?
| | | +--rw nd-cache-disable? empty {feature-list:HAVE_BGP_EVPN}?
| | +--ro state
| | +--ro arp-cache-disable? empty {feature-list:HAVE_BGP_EVPN}?
| | +--ro nd-cache-disable? empty {feature-list:HAVE_BGP_EVPN}?
| +--rw map
| | +--rw config
| | | +--rw vxlan-identifier? -> /vxlan/vxlan-tenants/vxlan-tenant/config/vxlan-identifier
| | | +--rw tenant-description? -> /vxlan/vxlan-tenants/vxlan-tenant/config/tenant-description
| | +--ro state
| | +--ro vxlan-identifier? -> /vxlan/vxlan-tenants/vxlan-tenant/config/vxlan-identifier
| | +--ro tenant-description? -> /vxlan/vxlan-tenants/vxlan-tenant/config/tenant-description
```

```

|  +--rw host-macs-ipv4
|  |  +--rw host-mac-ipv4* [mac-address ipv4-address]
|  |    +--rw mac-address  -> ../config/mac-address
|  |    +--rw ipv4-address  -> ../config/ipv4-address
|  |    +--rw config
|  |      |  +--rw mac-address?  cml-data-types:cml_mac_addr_t
|  |      |  +--rw ipv4-address?  inet:ipv4-address
|  |      +--ro state
|  |        +--ro mac-address?  cml-data-types:cml_mac_addr_t
|  |        +--ro ipv4-address?  inet:ipv4-address
|  +--rw host-macs-ipv6
|  |  +--rw host-mac-ipv6* [mac-address ipv6-address] {feature-list:HAVE_IPV6}?
|  |    +--rw mac-address  -> ../config/mac-address
|  |    +--rw ipv6-address  -> ../config/ipv6-address
|  |    +--rw config
|  |      |  +--rw mac-address?  cml-data-types:cml_mac_addr_t
|  |      |  +--rw ipv6-address?  inet:ipv6-address
|  |      +--ro state
|  |        +--ro mac-address?  cml-data-types:cml_mac_addr_t
|  |        +--ro ipv6-address?  inet:ipv6-address
|  +--rw access-interface-qos-type-mappings
|    +--rw access-interface-qos-type-mapping* [profile-map-type] {feature-list:HAVE_QOS}?
|    +--rw profile-map-type  -> ../config/profile-map-type
|    +--rw config
|      |  +--rw profile-map-type?  ipi-vxlan-types:vxlan_qos_map_profile_type_t
|      |  +--rw profile-name      string
|      +--ro state
|        +--ro profile-map-type?  ipi-vxlan-types:vxlan_qos_map_profile_type_t
|        +--ro profile-name      string
+--rw double-tagged-access-interfaces
|  +--rw double-tagged-access-interface* [interface-name vlan-identifier inner-vlan-identifier] {feature-
list:NOT_HAVE_DNX}?
|  +--rw interface-name      -> ../config/interface-name
|  +--rw vlan-identifier      -> ../config/vlan-identifier
|  +--rw inner-vlan-identifier  -> ../config/inner-vlan-identifier
|  +--rw config
|    |  +--rw tag-protocol-identifier?  string

```

---

```

| | +--rw interface-name?      -> /ipi-interface:interfaces/interface/name
| | +--rw admin-shutdown?      empty
| | +--rw description?         cml-data-types:cml_line_t
| | +--rw dynamic-learning-disable? empty
| | +--rw access-mac-hold-time? int32
| | +--rw arp-nd-flood-suppress? empty {feature-list:HAVE_BGP_EVPN}?
| | +--rw garp-gna-enable?     empty {feature-list:HAVE_BGP_EVPN}?
| | +--rw mac-address*         cml-data-types:cml_mac_addr_t
| | +--rw vlan-identifier?     string
| | +--rw inner-vlan-identifier? uint32
| +--ro state
| | +--ro tag-protocol-identifier? string
| | +--ro interface-name?      -> /ipi-interface:interfaces/interface/name
| | +--ro admin-shutdown?      empty
| | +--ro description?         cml-data-types:cml_line_t
| | +--ro dynamic-learning-disable? empty
| | +--ro access-mac-hold-time? int32
| | +--ro arp-nd-flood-suppress? empty {feature-list:HAVE_BGP_EVPN}?
| | +--ro garp-gna-enable?     empty {feature-list:HAVE_BGP_EVPN}?
| | +--ro mac-address*         cml-data-types:cml_mac_addr_t
| | +--ro vlan-identifier?     string
| | +--ro inner-vlan-identifier? uint32
| +--rw map
| | +--rw config
| | | +--rw vxlan-identifier?   -> /vxlan/vxlan-tenants/vxlan-tenant/config/vxlan-identifier
| | | +--rw tenant-description? -> /vxlan/vxlan-tenants/vxlan-tenant/config/tenant-description
| | +--ro state
| |   +--ro vxlan-identifier?   -> /vxlan/vxlan-tenants/vxlan-tenant/config/vxlan-identifier
| |   +--ro tenant-description? -> /vxlan/vxlan-tenants/vxlan-tenant/config/tenant-description
| +--rw cache
| | +--rw config
| | | +--rw arp-cache-disable?  empty {feature-list:HAVE_BGP_EVPN}?
| | | +--rw nd-cache-disable?   empty {feature-list:HAVE_BGP_EVPN}?
| | +--ro state
| |   +--ro arp-cache-disable?  empty {feature-list:HAVE_BGP_EVPN}?
| |   +--ro nd-cache-disable?   empty {feature-list:HAVE_BGP_EVPN}?

```

---

```
| +--rw host-macs-ipv4
| | +--rw host-mac-ipv4* [mac-address ipv4-address] {feature-list:NOT_HAVE_DNX}?
| |   +--rw mac-address   -> ../config/mac-address
| |   +--rw ipv4-address  -> ../config/ipv4-address
| |   +--rw config
| |     | +--rw mac-address?  cml-data-types:cml_mac_addr_t
| |     | +--rw ipv4-address? inet:ipv4-address
| |     +--ro state
| |       +--ro mac-address?  cml-data-types:cml_mac_addr_t
| |       +--ro ipv4-address?  inet:ipv4-address
| +--rw host-macs-ipv6
| | +--rw host-mac-ipv6* [mac-address ipv6-address] {feature-list:HAVE_IPV6}?
| |   +--rw mac-address   -> ../config/mac-address
| |   +--rw ipv6-address  -> ../config/ipv6-address
| |   +--rw config
| |     | +--rw mac-address?  cml-data-types:cml_mac_addr_t
| |     | +--rw ipv6-address? inet:ipv6-address
| |     +--ro state
| |       +--ro mac-address?  cml-data-types:cml_mac_addr_t
| |       +--ro ipv6-address?  inet:ipv6-address
| +--rw access-interface-qos-type-mappings
|   +--rw access-interface-qos-type-mapping* [profile-map-type] {feature-list:HAVE_QOS}?
|   +--rw profile-map-type -> ../config/profile-map-type
|   +--rw config
|     | +--rw profile-map-type? ipi-vxlan-types:vxlan_qos_map_profile_type_t
|     | +--rw profile-name     string
|     +--ro state
|       +--ro profile-map-type? ipi-vxlan-types:vxlan_qos_map_profile_type_t
|       +--ro profile-name     string
+--ro access-interfaces
| +--ro access-interface* [interface-index]
| +--ro interface-index -> ../state/interface-index
| +--ro state
|   +--ro interface-index? uint32
|   +--ro if-name?        cml-data-types:cml_line_t
|   +--ro access-counters
```

---

```

|   +--ro rx-arp-discard-packets?      yang:counter64
|   +--ro tx-arp-discard-packet?      yang:counter64
|   +--ro rx-arp-request-packets?    yang:counter64
|   +--ro rx-arp-reply-packets?      yang:counter64
|   +--ro tx-arp-request-packet?     yang:counter64
|   +--ro tx-arp-reply-packet?       yang:counter64
|   +--ro rx-nd-discard-packets?     yang:counter64
|   +--ro tx-nd-discard-packet?     yang:counter64
|   +--ro rx-neighbor-solicitation-packets? yang:counter64
|   +--ro rx-neighbor-advertisement-packets? yang:counter64
|   +--ro tx-neighbor-solicitation-packet? yang:counter64
|   +--ro tx-neighbor-advertisement-packet? yang:counter64
|   +--ro rx-gratuitous-arp-packets?  yang:counter64
|   +--ro tx-gratuitous-arp-packets?  yang:counter64
|   +--ro rx-gratuitous-na-packets?   yang:counter64
|   +--ro tx-gratuitous-na-packets?   yang:counter64
|   +--ro rx-data-packets?           yang:counter64
|   +--ro rx-data-bytes?             yang:counter64
|   +--ro tx-data-packets?           yang:counter64
|   +--ro tx-data-bytes?             yang:counter64
+--rw interfaces
  +--rw interface* [name] {feature-list:HAVE_XGS5,feature-list:NOT_HAVE_DUNE}?
    +--rw name    -> ../config/name
    +--rw config
      | +--rw name?    -> /ipi-interface:interfaces/interface/name
      | +--rw access-if? empty
      +--ro state
        +--ro name?    -> /ipi-interface:interfaces/interface/name
        +--ro access-if? empty

```

rpcs:

```

+---x clear-nvo-vxlan-dynamic-mac-address-table {feature-list:HAVE_VXLAN}?
+---x clear-nvo-vxlan-dynamic-mac-address-table-vnid {feature-list:HAVE_VXLAN}?
| +---w input
|   +---w vxlan-identifier  uint32
|   +---w mac-address?     cml-data-types:cml_mac_addr_t

```

```

+---x clear-nvo-vxlan-tunnels {feature-list:HAVE_VXLAN}?
+---x clear-nvo-id-vxlan-tunnels-destip {feature-list:HAVE_VXLAN}?
| +---w input
|   +---w destination-vtep-ip  inet:ipv4-address
+---x clear-nvo-vxlan-mac-stale-entries {feature-list:HAVE_VXLAN}?
| +---w input
|   +---w vxlan-identifier?  uint32
+---x clear-vxlan-untagged-access-port-counters {feature-list:HAVE_VXLAN}?
| +---w input
|   +---w interface-name  string
+---x clear-vxlan-single-tagged-access-port-counters {feature-list:NOT_HAVE_DNX}?
| +---w input
|   +---w interface-name  string
|   +---w vlan-identifier  string
+---x clear-vxlan-double-tagged-access-port-counters {feature-list:NOT_HAVE_DNX}?
| +---w input
|   +---w interface-name      string
|   +---w outer-vlan-identifier  uint32
|   +---w inner-vlan-identifier  uint32
+---x clear-vxlan-access-port-counters-all {feature-list:HAVE_VXLAN}?
+---x clear-vxlan-network-port-counters {feature-list:HAVE_VXLAN}?
| +---w input
|   +---w destination-vtep-ip  inet:ipv4-address
+---x clear-vxlan-network-port-counters-all {feature-list:HAVE_VXLAN}?

```

notifications:

```

+---n vxlan-tunnel-status-change-notification
  +--ro severity?          cml-data-types:cml_notif_severity_t
  +--ro eventClass?       cml-data-types:cml_notif_class_t
  +--ro destination-vtep-ip?  inet:ipv4-address
  +--ro tunnel-status?     ipi-vxlan-types:vxlan_tunnel_status_t

```

---

## module: ipi-watchdog

```

+--rw watchdog {feature-list:HAVE_PSERVD}?

```

```

+--rw config
| +--rw watchdog-disabled?  empty
| +--rw keepalive-interval? uint16
+--ro state
| +--ro watchdog-disabled?  empty
| +--ro keepalive-interval? uint16
| +--ro watchdog-status?    ipi-watchdog-types:watchdog_status_t
| +--ro all-processes-status? ipi-watchdog-types:watchdog_global_processes_status_t
+--rw software-modules
  +--rw software-module* [name]
    +--rw name    -> ../config/name
    +--rw config
      | +--rw name?                ipi-watchdog-types:watchdog_module_name_t
      | +--rw module-watchdog-status-disabled  empty
    +--ro state
      | +--ro name?                ipi-watchdog-types:watchdog_module_name_t
      | +--ro module-watchdog-status-disabled  empty
    +--rw process
      +--ro state
        +--ro process-name?  ipi-watchdog-types:watchdog_module_name_t
        +--ro process-status? ipi-watchdog-types:watchdog_process_status_t
        +--ro start-time?    yang:date-and-time
        +--ro down-reason?   cml-data-types:cml_line_t

```

rpcs:

```

+---x clear-core-dump {feature-list:HAVE_PSERVD,feature-list:HAVE_ZEBOS_CORE_ANALYSER}?
  +---w input
    +---w core-dump  string

```

notifications:

```

+---n protocol-module-down {feature-list:HAVE_PSERVD}?
| +--ro severity?  cml-data-types:cml_notif_severity_t
| +--ro eventClass?  cml-data-types:cml_notif_class_t
| +--ro name?       ipi-watchdog-types:watchdog_module_name_t
| +--ro process-name? ipi-watchdog-types:watchdog_module_name_t
| +--ro down-reason?  cml-data-types:cml_line_t

```

```

+---n protocol-module-restarted {feature-list:HAVE_PSERVD}?
  +--ro severity?    cml-data-types:cml_notif_severity_t
  +--ro eventClass?  cml-data-types:cml_notif_class_t
  +--ro name?        ipi-watchdog-types:watchdog_module_name_t
  +--ro process-name? ipi-watchdog-types:watchdog_module_name_t
  +--ro start-time?  yang:date-and-time

```

---

## module: ipi-xstp

```

+--rw xstp
  +--rw interfaces
    | +--rw interface* [name]
    |   +--rw name          -> ../config/name
    |   +--rw config
    |     | +--rw name?          -> /ipi-interface:interfaces/interface/name
    |     | +--rw hello-time?     uint8
    |     | +--rw port-configuration?  ipi-xstp-types:xstp_port_edge_t
    |     | +--rw enable-automatic-edge-detection?  empty
    |     | +--rw bpdu-guard?        ipi-xstp-types:xstp_bpdu_t
    |     | +--rw bpdu-filter?       ipi-xstp-types:xstp_bpdu_t
    |     | +--rw enable-root-guard?  empty
    |     | +--rw link-type?         ipi-xstp-types:xstp_link_type_t
    |     | +--rw enable-restricted-domain-role?  empty
    |     | +--rw enable-restricted-role?    empty
    |     | +--rw enable-restricted-tcn?    empty
    |     +--ro state
    |       | +--ro name?          -> /ipi-interface:interfaces/interface/name
    |       | +--ro hello-time?     uint8
    |       | +--ro port-configuration?  ipi-xstp-types:xstp_port_edge_t
    |       | +--ro enable-automatic-edge-detection?  empty
    |       | +--ro bpdu-guard?        ipi-xstp-types:xstp_bpdu_t
    |       | +--ro bpdu-filter?       ipi-xstp-types:xstp_bpdu_t
    |       | +--ro enable-root-guard?  empty
    |       | +--ro link-type?         ipi-xstp-types:xstp_link_type_t
    |       | +--ro enable-restricted-domain-role?  empty

```

```

| | +--ro enable-restricted-role?      empty
| | +--ro enable-restricted-tcn?      empty
| +--rw mstp
| | +--rw mst-instances
| |   +--rw mst-instance* [instance-id]
| |     +--rw instance-id  -> ../config/instance-id
| |     +--rw config
| |       | +--rw instance-id?          -> /ipi-network-instance:network-instances/network-instance/ipi-
bridge:bridge/stp/mstp/mst-instances/mst-instance/instance-id
| |       | +--rw enable-instance-restricted-role?  empty
| |       | +--rw enable-instance-restricted-tcn?  empty
| |       +--ro state
| |         +--ro instance-id?          -> /ipi-network-instance:network-instances/network-instance/ipi-
bridge:bridge/stp/mstp/mst-instances/mst-instance/instance-id
| |         +--ro enable-instance-restricted-role?  empty
| |         +--ro enable-instance-restricted-tcn?  empty
| +--rw rapid-pvst {feature-list:HAVE_RPVST_PLUS}?
| | +--rw vlans
| |   +--rw vlan* [vlan-id]
| |     +--rw vlan-id  -> ../config/vlan-id
| |     +--rw config
| |       | +--rw enable-restricted-role?  empty
| |       | +--rw enable-restricted-tcn?  empty
| |       | +--rw vlan-id?                uint16
| |       +--ro state
| |         +--ro enable-restricted-role?  empty
| |         +--ro enable-restricted-tcn?  empty
| |         +--ro vlan-id?                uint16
| +--rw customer-spanning-tree {feature-list:HAVE_PROVIDER_BRIDGE}?
|   +--rw config
| | +--rw bridge-priority?  uint16
| | +--rw max-age?         uint8
| | +--rw hello-time?     uint8
| | +--rw forward-delay?  uint8
| | +--rw transmit-hold-count? uint8
| +--ro state
| | +--ro bridge-priority?  uint16

```

```

| | +--ro max-age?      uint8
| | +--ro hello-time?   uint8
| | +--ro forward-delay? uint8
| | +--ro transmit-hold-count? uint8
| +--rw customer-edge
| | +--rw config
| | | +--rw port-priority? uint8
| | | +--rw path-cost?    uint32
| | +--ro state
| | | +--ro port-priority? uint8
| | | +--ro path-cost?    uint32
| +--rw provider-edge
|   +--rw vlans
|     +--rw vlan* [svlan-id]
|       +--rw svlan-id  -> ../config/svlan-id
|       +--rw config
|         | +--rw svlan-id?    uint16
|         | +--rw port-priority? uint8
|         | +--rw path-cost?   uint32
|         +--ro state
|           +--ro svlan-id?    uint16
|           +--ro port-priority? uint8
|           +--ro path-cost?   uint32

```

```
+--rw mstp
```

```

+--rw debug
  +--rw config
    | +--rw options? ipi-xstp-types:mstp_debug_t
  +--ro state
    +--ro options?          ipi-xstp-types:mstp_debug_t
    +--ro terminal-debug-status? ipi-xstp-types:mstp_debug_t

```

```
augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance/ipi-bridge:bridge:
```

```

+--rw stp
  +--rw config
    | +--rw ageing-time?          ipi-xstp-types:xstp_ageing_time_t
    | +--rw enable-cisco-interoperability? empty

```

---

```
| +--rw forwarding-delay?          uint8
| +--rw hello-time?               uint8
| +--rw max-age?                  uint8
| +--rw max-hops?                 uint8
| +--rw bridge-priority?          uint32
| +--rw transmit-hold-count?      uint8
+--ro state
| +--ro ageing-time?              ipi-xstp-types:xstp_ageing_time_t
| +--ro enable-cisco-interoperability? empty
| +--ro forwarding-delay?         uint8
| +--ro hello-time?              uint8
| +--ro max-age?                  uint8
| +--ro max-hops?                 uint8
| +--ro bridge-priority?          uint32
| +--ro transmit-hold-count?      uint8
+--rw global
| +--rw config
| | +--rw enable-bpdu-filter?     empty
| | +--rw enable-bpdu-guard?     empty
| | +--rw enable-error-disable-timeout? empty
| | +--rw force-version?         uint8
| | +--rw path-cost-method?      ipi-xstp-types:xstp_path_cost_method_t
| +--ro state
| | +--ro enable-bpdu-filter?     empty
| | +--ro enable-bpdu-guard?     empty
| | +--ro enable-error-disable-timeout? empty
| | +--ro force-version?         uint8
| | +--ro path-cost-method?      ipi-xstp-types:xstp_path_cost_method_t
+--rw bridge-admins
| | +--rw bridge-admin* [bridge-type disable-spanning-tree]
| |   +--rw bridge-type          -> ../config/bridge-type
| |   +--rw disable-spanning-tree -> ../config/disable-spanning-tree
| |   +--rw config
| |     | +--rw bridge-forwarding? ipi-xstp-types:xstp_bridge_forward_t
| |     | +--rw bridge-type?      ipi-xstp-types:xstp_bridge_type_t
| |     | +--rw disable-spanning-tree? empty
```

---

```
| | +--ro state
| |   +--ro bridge-forwarding?   ipi-xstp-types:xstp_bridge_forward_t
| |   +--ro bridge-type?         ipi-xstp-types:xstp_bridge_type_t
| |   +--ro disable-spanning-tree? empty
| +--rw bridge-shutdowns
|   +--rw bridge-shutdown* [enable-shutdown]
|     +--rw enable-shutdown  -> ../config/enable-shutdown
|     +--rw config
|       | +--rw bridge-forwarding? ipi-xstp-types:xstp_bridge_forward_t
|       | +--rw enable-shutdown?   empty
|       +--ro state
|         +--ro bridge-forwarding? ipi-xstp-types:xstp_bridge_forward_t
|         +--ro enable-shutdown?   empty
+--rw mstp
| +--rw config
| | +--rw region-name?   string
| | +--rw revision-number? uint16
| +--ro state
| | +--ro counters
| | | +--ro topology-changes-count?   uint32
| | | +--ro total-topology-changes-count? uint32
| | | +--ro max-age-count?            uint32
| | | +--ro region-name?              string
| | | +--ro revision-number?          uint16
| | | +--ro topology-change-detected?  boolean
| | | +--ro last-topology-change?      yang:date-and-time
| | | +--ro topology-change-initiator? uint16
| | | +--ro topology-change-last-received-from? string
| | | +--ro cist-bridge-id?           string
| | | +--ro cist-designated-root?     string
| | | +--ro cist-regional-root?       string
| | | +--ro cist-designated-bridge?   string
| | | +--ro cist-port-root-id?        uint16
| | | +--ro external-root-path-cost?  uint32
| | | +--ro internal-root-path-cost?  uint32
| +--rw mst-instances
```

```

|  +--rw mst-instance* [instance-id]
|  |  +--rw instance-id  -> ../config/instance-id
|  |  +--rw config
|  |  |  +--rw instance-id?   ipi-xstp-types:mstp_instance_t
|  |  |  +--rw bridge-priority? uint32
|  |  |  +--rw vlan-id?      cml-data-types:cml_range_t
|  |  +--ro state
|  |  |  +--ro instance-id?      ipi-xstp-types:mstp_instance_t
|  |  |  +--ro bridge-priority?  uint32
|  |  |  +--ro vlan-id?         cml-data-types:cml_range_t
|  |  |  +--ro bridge-id?      string
|  |  |  +--ro designated-root-priority? uint16
|  |  |  +--ro designated-root-address? yang:mac-address
|  |  |  +--ro internal-root-path-cost? uint32
|  |  |  +--ro root-port-ifindex?  uint32
|  |  |  +--ro topology-change-detected? boolean
|  |  |  +--ro topology-change-initiator? uint16
|  |  |  +--ro topology-change-last-received-from? string
|  |  |  +--ro last-topology-change? yang:date-and-time
|  |  |  +--ro topology-changes?  uint32
|  |  +--rw interfaces
|  |  |  +--rw interface* [name]
|  |  |  |  +--rw name  -> ../config/name
|  |  |  |  +--rw config
|  |  |  |  |  +--rw name?   -> /ipi-interface:interfaces/interface/name
|  |  |  |  |  +--rw path-cost?  uint32
|  |  |  |  |  +--rw port-priority? int16
|  |  |  |  +--ro state
|  |  |  |  |  +--ro counters
|  |  |  |  |  |  +--ro config-bpdu-sent?  uint32
|  |  |  |  |  |  +--ro config-bpdu-received? uint32
|  |  |  |  |  |  +--ro tcn-bpdu-sent?    uint32
|  |  |  |  |  |  +--ro tcn-bpdu-received? uint32
|  |  |  |  |  |  +--ro similar-bpdu-count? uint32
|  |  |  |  +--ro name?      -> /ipi-interface:interfaces/interface/name
|  |  |  |  +--ro path-cost?  uint32

```

---

```

| |   +--ro port-priority?      int16
| |   +--ro port-id?           uint16
| |   +--ro internal-root-path-cost?  uint32
| |   +--ro designated-root-priority?  uint16
| |   +--ro designated-root-address?  yang:mac-address
| |   +--ro designated-bridge-priority?  uint16
| |   +--ro designated-bridge-address?  yang:mac-address
| |   +--ro designated-port-priority?  uint16
| |   +--ro designated-port-num?      uint16
| |   +--ro designated-cost?         uint16
| |   +--ro hello-time-remaining?    uint32
| |   +--ro forward-time-remaining?  uint32
| |   +--ro message-age-time-remaining?  uint32
| |   +--ro port-state?              ipi-xstp-types:mstp_port_state_t
| |   +--ro port-role?              ipi-xstp-types:mstp_port_role_t
|   +--rw te-mst-instance
|     +--rw config
|       | +--rw vlan-id*         uint16
|       | +--rw disable-spanning-tree?  empty
|       +--ro state
|         | +--ro vlan-id*         uint16
|         | +--ro disable-spanning-tree?  empty
|         | +--ro bridge-id?       string
|         | +--ro designated-root-priority?  uint16
|         | +--ro designated-root-address?  yang:mac-address
|         | +--ro internal-root-path-cost?  uint32
|         | +--ro root-port-ifindex?    uint32
|         | +--ro topology-change-detected?  boolean
|         | +--ro topology-change-initiator?  uint16
|         | +--ro topology-change-last-received-from?  string
|         | +--ro last-topology-change?     yang:date-and-time
|         | +--ro topology-changes?       uint32
|     +--rw interfaces
|       +--rw interface* [name]
|         +--rw name   -> ../config/name
|         +--rw config

```

```

|     | +--rw name? -> /ipi-interface:interfaces/interface/name
|     +--ro state
|     +--ro counters
|     | +--ro config-bpdu-sent?   uint32
|     | +--ro config-bpdu-received? uint32
|     | +--ro tcn-bpdu-sent?     uint32
|     | +--ro tcn-bpdu-received? uint32
|     | +--ro similar-bpdu-count? uint32
|     +--ro name?                -> /ipi-interface:interfaces/interface/name
|     +--ro port-id?             uint16
|     +--ro internal-root-path-cost? uint32
|     +--ro designated-root-priority? uint16
|     +--ro designated-root-address? yang:mac-address
|     +--ro designated-bridge-priority? uint16
|     +--ro designated-bridge-address? yang:mac-address
|     +--ro designated-port-priority? uint16
|     +--ro designated-port-num?     uint16
|     +--ro designated-cost?        uint16
|     +--ro hello-time-remaining?   uint32
|     +--ro forward-time-remaining?  uint32
|     +--ro message-age-time-remaining? uint32
|     +--ro port-state?             ipi-xstp-types:mstp_port_state_t
|     +--ro port-role?             ipi-xstp-types:mstp_port_role_t
+--rw rapid-pvst {feature-list:HAVE_RPVST_PLUS}?
  +--rw vlans
    +--rw vlan* [vlan-id]
      +--rw vlan-id -> ../config/vlan-id
      +--rw config
        | +--rw bridge-priority? uint32
        | +--rw vlan-id?       uint16
      +--ro state
        +--ro bridge-priority? uint32
        +--ro vlan-id?        uint16

augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance/ipi-bridge:bridge/ipi-bridge:bridge-ports/ipi-bridge:interface:
  +--rw mstp-port
    +--rw port-bridge

```

---

```
+--rw config
| +--rw path-cost?   uint32
| +--rw port-priority? int16
+--ro state
  +--ro counters
  | +--ro config-bpdu-sent?   uint32
  | +--ro config-bpdu-received? uint32
  | +--ro tcn-bpdu-sent?     uint32
  | +--ro tcn-bpdu-received? uint32
  | +--ro source-mac-count?   uint32
  | +--ro similar-bpdu-count? uint32
  | +--ro total-src-mac-count? uint32
  +--ro path-cost?           uint32
  +--ro port-priority?       int16
  +--ro link-type?           ipi-xstp-types:xstp_link_type_t
  +--ro bpdu-filter?         ipi-xstp-types:xstp_bpdu_t
  +--ro bpdu-guard?         ipi-xstp-types:xstp_bpdu_t
  +--ro root-guard?         empty
  +--ro cist-path-cost?     uint32
  +--ro cist-priority?      uint32
  +--ro cist-port-id?       uint16
  +--ro cist-port-number?   uint16
  +--ro cist-root?          string
  +--ro cist-regional-root? string
  +--ro cist-designated-bridge? string
  +--ro cist-designated-root-path-cost? uint32
  +--ro cist-designated-external-root-path-cost? uint32
  +--ro cist-designated-internal-root-path-cost? uint32
  +--ro cist-designated-port-id? uint32
  +--ro cist-hello-time-remaining? uint32
  +--ro cist-forward-time-remaining? uint32
  +--ro cist-message-age-time-remaining? uint32
  +--ro cist-topology-change-time-remaining? uint32
  +--ro cist-port-state?    string
  +--ro cist-port-role?     ipi-xstp-types:mstp_port_role_t
  +--ro cist-forward-transitions? uint32
```

```

    +--ro service-vlan-id?                uint16 {feature-list:HAVE_PROVIDER_BRIDGE}?
augment /ipi-network-instance:network-instances/ipi-network-instance:network-instance/ipi-bridge:bridge/ipi-bridge:bridge-ports/ipi-bridge:interface:
+--rw vlan-port {feature-list:HAVE_RPVST_PLUS}?
  +--rw vlans
    +--rw vlan* [vlan-id]
      +--rw vlan-id  -> ../config/vlan-id
      +--rw config
        | +--rw vlan-id?    uint16
        | +--rw port-priority? uint8
        | +--rw path-cost?   uint32
      +--ro state
        +--ro vlan-id?    uint16
        +--ro port-priority? uint8
        +--ro path-cost?   uint32

```

rpcs:

```

+---x mstp-terminal-debug-on {feature-list:HAVE_MSTPD}?
| +---w input
|   +---w terminal-debug-options  ipi-xstp-types:mstp_debug_t
+---x mstp-terminal-debug-off {feature-list:HAVE_MSTPD}?
| +---w input
|   +---w terminal-debug-options  ipi-xstp-types:mstp_debug_t
+---x clear-spanning-tree-detected-protocols-per-bridge {feature-list:HAVE_MSTPD}?
| +---w input
|   +---w bridge-id  string
+---x clear-spanning-tree-detected-protocols-per-interface {feature-list:HAVE_MSTPD}?
| +---w input
|   +---w interface-name  string
+---x clear-spanning-tree-statistics-per-instance-and-bridge {feature-list:HAVE_MSTPD,feature-list:HAVE_PROVIDER_BRIDGE_OR_HAVE_B_BEB}?
| +---w input
|   +---w bridge-id      string
|   +---w mst-instance-id  ipi-xstp-types:mstp_instance_spbm_type_t
+---x clear-spanning-tree-statistics-per-interface-vlan-and-bridge {feature-list:HAVE_MSTPD,feature-list:HAVE_PROVIDER_BRIDGE_OR_HAVE_B_BEB}?
| +---w input

```

---

```
| +---w bridge-id    string
| +---w interface-name string
| +---w vlan-id      uint16
+---x clear-spanning-tree-statistics-per-interface-and-bridge {feature-list:HAVE_MSTPD}?
| +---w input
|   +---w bridge-id    string
|   +---w interface-name string
+---x clear-spanning-tree-statistics-per-bridge {feature-list:HAVE_MSTPD}?
| +---w input
|   +---w bridge-id    string
+---x clear-spanning-tree-statistics-per-vlan-and-bridge {feature-list:HAVE_MSTPD}?
| +---w input
|   +---w bridge-id    string
|   +---w vlan-id      uint16
+---x clear-spanning-tree-statistics-per-interface-instance-and-bridge {feature-list:HAVE_MSTPD}?
| +---w input
|   +---w bridge-id    string
|   +---w interface-name string
|   +---w mst-instance-id ipi-xstp-types:mstp_instance_spbm_type_t
+---x mstp-snmp-restart {feature-list:HAVE_SNMP}?
```

## notifications:

```
+---n bridge-new-root-notification
  +--ro severity?  cml-data-types:cml_notif_severity_t
  +--ro eventClass? cml-data-types:cml_notif_class_t
  +--ro message?   string
```

